# EMC TEST REPORT

| | | | |
|---|---|---|---|
| **Project No.** | LBE20143198 | **Issue No.** | 0 |
| **Applicant** | **Name of organization** | Samsung Electronics Co., Ltd. | |
| | **Address** | (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-742, Republic of Korea | |
| | **Date of application** | May 27, 2014 | |
| **EUT** | **Type of device** | ☒ Class B personal computers and peripherals<br>☐ All other devices | |
| | **Equipment authorization** | ☐ Declaration of Conformity ☒ Certification ☐ Verification | |
| | **FCC ID** | A3LSMG800H | |
| | **Kind of product** | Mobile Phone | |
| | **Model No.** | SM-G800H/DS, SM-G800H | |
| | **Variant Model No.** | Refer to clause 4.6 | |
| | **Manufacturer** | SAMSUNG ELECTRONICS CO., LTD.<br>94-1, Imsu-dong, Gumi-si, Gyengsangbuk-do, 730-722, Republic of Korea<br>SAMSUNG ELECTRONICS HUIZHOU CO.,LTD.<br>516229, Chenjiang Town, HuiZhou City, Guangdong Province, China | |
| **Applied Standards** | | FCC Part 15, Subpart B, Class B / ANSI C63.4-2009 | |
| **Test Period** | | May 28, 2014 ~ May 30, 2014 | |
| **Issue date** | | June 5, 2014 | |

**Test result : Complied**

The equipment under test has found to be compliant with the applied standards.
(Refer to the attached test result for more detail.)

**Tested by** : Young-Hun Kim

Y. H. Kim

**Reviewed by** : Jong-Sup Jeong

The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from CS & Environment center.

SAMSUNG

(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-742, Republic of Korea
Tel: 82 31 279 1750, Fax: 82 31 279 1745

# Table of contents

**1. Report Information**

1.1 Revision history ..... 3

**2. Summary of test results**

2.1 Emission ..... 3

**3. General Information**

3.1 Test facility ..... 3

**4. Test Configuration**

4.1 Test Peripherals ..... 4

4.2 EUT operating mode ..... 4

4.3 Details of Sampling ..... 5

4.4 Used cable description ..... 5

4.5 Test arrangement ..... 5

4.6 EUT Description ..... 6

4.7 Clock Frequencies ..... 6

4.8 Test configuration and condition ..... 7

4.9 Measurement uncertainty ..... 7

**5. Result of individual tests**

5.1 Conducted disturbance ..... 8

5.2 Radiated disturbance ..... 10



This report must not be reproduced, except in full, without written permission from CS & Environment center.

# 1. Report Information

## 1.1 Revision history

| No. | Revised detailed information |
|---|---|
| Issue 0 | There are no revisions and this version is basic test report. |

# 2. Summary of test results

## 1.1 Emission

The EUT has been tested according to the following specifications:

| Applied | Test type | Applied standard | Result |
|---|---|---|---|
| ☒ | Conducted Disturbance (Mains port) | FCC Part 15 Subpart B / ANSI C63.4-2009 (Class B) | Complied |
| ☒ | Radiated Disturbance | | Complied |

# 3. General Information

## 3.1 Test facility

The CS & Environment center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Republic of Korea.
All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 22, 16-1 and 16-2. and Shielded rooms.

The CS & Environment center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.



This report must not be reproduced, except in full, without written permission from CS & Environment center.

# 4. Test Setup configuration

## 4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.
The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

| Mark | Description | Model No. | Serial No. | Manufacturer / Trademark | FCC ID / DoC |
|---|---|---|---|---|---|
| A | Mobile Phone | SM-G800H/DS | R31F500SDXK | SAMSUNG | A3LSMG800H |
| B | Battery | EB-BG800CBE | AAaF515KS/2-B | SAMSUNG | - |
| C | Headset | EHS64AVFWE | - | SAMSUNG | - |
| D | Data Cable | ECB-DU4AWE | SW1F310ASE | SAMSUNG | - |
| E | microSD Card | 32GB | - | SANDISK | - |
| F | Travel Adapter | ETA0U83EWE | DW1F401DS/A-E | SAMSUNG | - |
| G | Desk-Top Computer | DM300S3A | - | SAMSUNG | DoC |
| | | | EBDEDC6FFD | SAMSUNG | DoC |
| H | LCD TV Monitor | CF19MS | CF19H1LS700048Y | SAMSUNG | DoC |
| | | EF23TS | EM23H1LS300070L | SAMSUNG | DoC |
| I | Mouse | SML-210PB | TAKD125024 V | SAMSUNG | DoC |
| | | | TAKD124911 M | SAMSUNG | DoC |
| J | Keyboard | SDM8500P | 8M001183 | SAMSUNG | DoC |
| | | | 8M001033 | SAMSUNG | DoC |
| K | Gigabit Switch 8 | J9794A | CN33FQ703Q | HP | DoC |
| | | | CN33FQ71XK | HP | DoC |
| L | Power Supply | EADP-15DC A | DIKD1245096741 | Delta | DoC |
| | | | DIKD1245096576 | Delta | DoC |

## 4.2 EUT operating mode

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

| | |
|---|---|
| **Operating Mode 1** | USB Mode (Data Communication) |



This report must not be reproduced, except in full, without written permission from CS & Environment center.

## 4.3 Details of Sampling

Customer selected, single unit.

## 4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:

| No. | Connected cable | Length [m] | Shielded [Y/N] | Note |
|---|---|---|---|---|
| 1 | Data Cable / Travel Adapter | 1.0 | Yes | From EUT to Desk-Top Computer |
| 2 | Headset | 1.2 | No | For EUT |
| 3 | Power | 1.8 | No | For Desk-Top Computer |
| 4 | Power | 1.8 | No | For LCD TV Monitor |
| 5 | Power | 1.8 | No | For Power Supply |
| 6 | Power | 1.8 | No | From Router to Power Supply |
| 7 | LAN | 1.5 | No | From Desk-Top Computer to Router |
| 8 | LAN | 1.5 | No | From Router to Local Area Network |
| 9 | RGB | 1.8 | Yes | From Desk-Top Computer to LCD TV Monitor |
| 10 | PS/2 | 1.8 | Yes | From Desk-Top Computer to Mouse |
| 11 | PS/2 | 1.8 | Yes | From Desk-Top Computer to Keyboard |

## 4.5 Test arrangement






This report must not be reproduced, except in full, without written permission from CS & Environment center.

## 4.6 EUT Description

4.6.1 The following features describe EUT represented by this report:

| Item | Specification | |
|---|---|---|
| Frequency Range | GSM 850 | TX : 824.2 ~ 848.8 MHz<br>RX : 869.2 ~ 893.8 MHz |
| | GSM 1900 | TX : 1 850.2 ~ 1 909.8 MHz<br>RX : 1 930.2 ~ 1 989.8 MHz |
| | WCDMA850 | TX : 824 ~ 849 MHz<br>RX : 869 ~ 894 MHz |
| | WCDMA1900 | TX : 1 850 ~ 1 910 MHz<br>RX : 1 930 ~ 1 990 MHz |
| Operating Temperature (℃) | -20 ~ +60 | |
| Operating Humidity (%) | 0 ~ 95 | |

4.6.2 The variant models
- None

## 4.7 Clock Frequencies

| Kind of Clocks | Frequency [ MHz ] | Kind of Clocks | Frequency [ MHz ] |
|---|---|---|---|
| CPU | 1 400 | USB 2.0 | 24 |



This report must not be reproduced, except in full, without written permission from CS & Environment center.

## 4.8 Test configuration and condition

☐ The EUT exercise program which is the samsung standardized emission test program for windows was used during all EMC measurements were tested. This program was contained on the PC hard disk drive. Once loaded, the program sequentially exercises each system component in turn.

☒ The EUT was exercised during the testing by data read and write cycles repeated with internal storage devices. At the end of the test, the copied back data was compared with original.

☐ The EUT was connected to the PC by using USB data cable to charge.

☐ The system was configured for testing in a typical fashion that a customer would normally use, and was tested while in an automated non-attendant mode.

Power source for the EUT operating was supplied by CVCF made by the Pacific Power Source Corp.

**- Test Voltage : AC 120 V, 60 Hz**

## 4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4 and UKAS Lab 34.)

4.9.1 Emission

| Test type | | Measurement uncertainty (C.L. 95 %, k = 2) |
|---|---|---|
| Conducted disturbance | AC Mains | 3.12 dB |
| Radiated Disturbance (30 MHz ~ 1 GHz) | Horizontal | 4.03 dB |
| | Vertical | 4.13 dB |
| Radiated Disturbance (1 GHz ~ 6 GHz) | Horizontal | 4.53 dB |
| | Vertical | 4.51 dB |



This report must not be reproduced, except in full, without written permission from CS & Environment center.

Form No.: SRA-TRF-46/1

# 5. Results of individual test

## 5.1 Conducted disturbance

The EUT was connected to the Desk-Top Computer which was powered from one LISN for the measurements. The support equipment power cables were connected to a second LISN.

Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

**Limits for conducted disturbance at the mains ports of Class B ITE**

| Frequency range Limits [ MHz ] | Resolution Bandwidth [ kHz ] | Limits [ dB(μV) ] | |
|---|---|---|---|
| | | Quasi-peak | Average |
| 0,15 to 0,50 | 9 | 66 to 56 | 56 to 46 |
| 0,50 to 5 | 9 | 56 | 46 |
| 5 to 30 | 9 | 60 | 50 |
| NOTE 1 The lower limit shall apply at the transition frequency.<br>NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. | | | |

### 5.1.1 Test instrumentation

| EMC No. | Test Instrument | Model name | Manufacturer | Serial No. | Calibration | |
|---|---|---|---|---|---|---|
| | | | | | Date | Interval (Month) |
| E5I-010 | LISN | ESH3-Z5 | R&S | 100263 | 2013-10-17 | 12 |
| E5I-016 | EMI Test Receiver | ESU8 | R&S | 100482 | 2013-06-11 | 12 |
| E5I-043 | LISN | ENV216 | R&S | 101630 | 2013-06-07 | 12 |

### 5.1.2 Temperature and humidity condition

| | | | |
|---|---|---|---|
| **Test date** | 2014-05-28 | **Test engineer** | Young-Hun Kim |
| **Climate condition** | Ambient temperature | 23.3 ℃ | Limit (15.0 to 35.0) ℃ |
| | Relative humidity | 42.0 % R.H. | Limit (25.0 to 75.0) % R.H. |
| | Atmospheric pressure | 100.7 kPa | Limit (86.0 to 106.0) kPa |
| **Test place** | Shield Room (SR14) | | |



This report must not be reproduced, except in full, without written permission from CS & Environment center.

Form No.: SRA-TRF-46/1

## 5.1.3 Test results

### ☐ Operating Mode 1: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP/CAV final measurement results table:

| Frequency (MHz) | QuasiPeak (dBµV) | CAV (dBµV) | Limit (dBµV) | Margin (dB) | Line | Corr. (dB) |
|---|---|---|---|---|---|---|
| 0.292 | --- | 32.68 | 50.50 | 17.82 | L1 | 9.9 |
| 0.292 | 34.92 | --- | 60.50 | 25.58 | L1 | 9.9 |
| 0.881 | --- | 27.57 | 46.00 | 18.43 | L1 | 9.8 |
| 0.881 | 28.54 | --- | 56.00 | 27.46 | L1 | 9.8 |
| 1.115 | --- | 26.81 | 46.00 | 19.19 | L1 | 9.8 |
| 1.115 | 29.71 | --- | 56.00 | 26.29 | L1 | 9.8 |
| 1.291 | 31.33 | --- | 56.00 | 24.67 | L1 | 9.8 |
| 1.291 | --- | 26.73 | 46.00 | 19.27 | L1 | 9.8 |
| 2.172 | 31.74 | --- | 56.00 | 24.26 | L1 | 9.7 |
| 4.228 | --- | 29.75 | 46.00 | 16.25 | L1 | 9.7 |
| 4.275 | 36.21 | --- | 56.00 | 19.79 | L1 | 9.7 |
| 23.085 | --- | 35.86 | 50.00 | 14.14 | N | 9.9 |

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor



This report must not be reproduced, except in full, without written permission from CS & Environment center.

Form No.: SRA-TRF-46/1

## 5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

| Antenna Height [ cm ] | Antenna Polarisation | Resolution Bandwidth [ kHz ] | Video Bandwidth [ kHz ] | Turntable position [ degrees ] |
|---|---|---|---|---|
| 100 ~ 400 | Horizontal, Vertical | 120 | 300 | Continuous |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position.
Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency in accordance with internal maximum operating frequency at a measurement distance of 3 m for the following antenna and turntable arrangements:

| Antenna Height [ cm ] | Antenna Polarisation | Resolution Bandwidth [ MHz ] | Video Bandwidth [ MHz ] | Turntable position [ degrees ] |
|---|---|---|---|---|
| 100 ~ 400 | Horizontal, Vertical | 1 | 3 | 0 ~ 345 (Step size: 15 degrees) |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position.
Final measurements were made using peak and CISPR-average detectors.

**Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m**

| Frequency range Limits [ MHz ] | Field Strength | | |
|---|---|---|---|
| | 3 m [ μV/m ] | 3 m [ dB(μV/m) ] | 10 m [ dB(μV/m) ] |
| 30 to 88 | 100 | 40.0 | 29.5 |
| 88 to 216 | 150 | 43.5 | 33.0 |
| 216 to 960 | 200 | 46.0 | 35.5 |
| Above 960 | 500 | 54.0 | 43.5 |

Results checked manually; and points close to the limit line were re-measured.



This report must not be reproduced, except in full, without written permission from CS & Environment center.

## 5.2.1 Test instrumentation

| EMC No. | Test Instrument | Model name | Manufacturer | Serial No. | Calibration | |
|---|---|---|---|---|---|---|
| | | | | | Date | Interval (Month) |
| E5I-017 | EMI Test Receiver | R&S | ESU8 | 100483 | 2013-06-11 | 12 |
| E5I-021 | EMI Test Receiver | R&S | ESU40 | 100376 | 2013-06-11 | 12 |
| E5I-036 | Horn Antenna | R&S | HF907 | 100507 | 2013-04-02 | 24 |
| E5I-071 | BiLog Antenna | Teseq | CBL6112D | 35384 | 2013-05-23 | 24 |
| E5I-072 | BiLog Antenna | Teseq | CBL6112D | 36009 | 2013-06-03 | 24 |
| E5I-073 | Preamplifier | Sonoma | 310N | 332016 | 2013-06-10 | 12 |
| E5I-074 | Preamplifier | Sonoma | 310N | 332017 | 2013-06-10 | 12 |

## 5.2.2 Temperature and humidity condition

| | | | |
|---|---|---|---|
| **Test date** | 2014-05-30 | **Test engineer** | Young-Hun Kim |
| **Climate condition** | Ambient temperature | 23.1 ℃ | Limit (15.0 to 35.0) ℃ |
| | Relative humidity | 39.0 % R.H. | Limit (25.0 to 75.0) % R.H. |
| | Atmospheric pressure | 100.9 kPa | Limit (86.0 to 106.0) kPa |
| **Test place** | Semi-Anechoic Chamber (SAC8) | | |



This report must not be reproduced, except in full, without written permission from CS & Environment center.

Form No.: SRA-TRF-46/1

## 5.2.3 Test results

### ☐ Operating Mode 1

### - Frequencies below 1 GHz




Final Result

| No. | Frequency [MHz] | (P) | Reading QP [dB(uV)] | c.f [dB(1/m)] | Result QP [dB(uV/m)] | Limit QP [dB(uV/m)] | Margin QP [dB] | Height [cm] | Angle [deg] | System |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 40.549 | V | 33.1 | -18.7 | 14.4 | 29.5 | 15.1 | 116 | 293 | 2 |
| 2 | 107.679 | V | 38.5 | -18.9 | 19.6 | 33.0 | 13.4 | 108 | 181 | 2 |
| 3 | 150.644 | V | 34.2 | -19.6 | 14.6 | 33.0 | 18.4 | 100 | 80 | 2 |
| 4 | 300.145 | V | 32.5 | -15.6 | 16.9 | 35.5 | 18.6 | 196 | 2 | 2 |
| 5 | 403.571 | H | 36.8 | -13.5 | 23.3 | 35.5 | 12.2 | 300 | 225 | 1 |
| 6 | 500.086 | H | 34.2 | -11.5 | 22.7 | 35.5 | 12.8 | 204 | 250 | 1 |
| 7 | 739.676 | H | 29.8 | -8.6 | 21.2 | 35.5 | 14.3 | 300 | 295 | 1 |

Note) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 10 m, Antenna Height : 1 to 4 meters
Level (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
Margin (QP) = Limit – Level (QP)
QP = Quasi-Peak, c.f = Correction Factor



This report must not be reproduced, except in full, without written permission from CS & Environment center.

## 5.2.3 Test results

### ☐ Operating Mode 1

### - Frequencies above 1 GHz






This report must not be reproduced, except in full, without written permission from CS & Environment center.

Form No.: SRA-TRF-46/1

QP/CAV Final measurement results table:

| Frequency (MHz) | MaxPeak (dB μ V/m) | CAV (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|---|---|---|---|---|---|---|---|---|
| 1 084.000 | 44.31 | --- | 74.00 | 29.69 | 100.0 | H | 180.0 | -8.6 |
| 1 386.500 | --- | 27.44 | 54.00 | 26.56 | 100.0 | V | 180.0 | -7.5 |
| 1 392.500 | 51.32 | --- | 74.00 | 22.68 | 100.0 | V | 180.0 | -7.5 |
| 1 496.000 | 49.97 | --- | 74.00 | 24.03 | 100.0 | V | 180.0 | -6.7 |
| 1 560.000 | 51.22 | --- | 74.00 | 22.78 | 100.0 | V | 180.0 | -6.2 |
| 1 560.000 | --- | 28.74 | 54.00 | 25.26 | 100.0 | V | 180.0 | -6.2 |
| 1 998.000 | 41.57 | --- | 74.00 | 32.43 | 100.0 | H | 180.0 | -2.6 |
| 1 998.000 | --- | 27.07 | 54.00 | 26.93 | 100.0 | H | 180.0 | -2.6 |
| 2 238.000 | 45.87 | --- | 74.00 | 28.13 | 100.0 | V | 0.0 | -2.5 |
| 2 241.000 | --- | 25.85 | 54.00 | 28.15 | 100.0 | V | 0.0 | -2.5 |
| 2 413.500 | 45.81 | --- | 74.00 | 28.19 | 100.0 | H | 180.0 | -1.5 |
| 2 625.500 | --- | 27.37 | 54.00 | 26.63 | 100.0 | H | 0.0 | -0.1 |
| 2 631.500 | 45.34 | --- | 74.00 | 28.66 | 100.0 | H | 0.0 | -0.1 |
| 3 132.000 | 47.21 | --- | 74.00 | 26.79 | 100.0 | V | 180.0 | 3.1 |
| 3 431.500 | 44.92 | --- | 74.00 | 29.08 | 100.0 | H | 180.0 | 4.1 |
| 4 924.000 | 47.81 | --- | 74.00 | 26.19 | 100.0 | H | 180.0 | 10.0 |
| 6 000.000 | --- | 36.10 | 54.00 | 17.90 | 100.0 | H | 0.0 | 13.0 |

Note) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 3 m, Antenna Height : 1 to 4 meters
Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)
Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)
PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor



This report must not be reproduced, except in full, without written permission from CS & Environment center.