PCTEST ENGINEERING LABORATORY, INC.
7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. +1.410.290.6652 / Fax +1.410.290.6654
http://www.pctestlab.com

SAR EVALUATION REPORT

Applicant Name:
Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:
05/14/14 - 06/11/14
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Document Serial No.:
0Y1405301099-R1.A3L

FCC ID: **A3LSMG800M**

APPLICANT: **SAMSUNG ELECTRONICS, CO. LTD.**

DUT Type: Portable Handset
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model(s): SM-G800M

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.52	0.53	1.01
PCE	UMTS 850	826.40 - 846.60 MHz	< 0.1	0.49	0.49
PCE	UMTS 1750	1712.4 - 1752.5 MHz	0.72	0.96	1.00
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.36	0.48	0.76
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.69	0.74	0.74
PCE	LTE Band 17	706.5 - 713.5 MHz	0.31	0.33	0.33
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.47	0.58	0.58
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.69	0.79	0.79
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.72	0.71	0.73
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.52	0.12	0.12
DTS	5.8 GHz WLAN	5745 - 5825 MHz	< 0.1	0.26	
NII	5.2 GHz WLAN	5180 - 5240 MHz	< 0.1	0.11	
NII	5.3 GHz WLAN	5260 - 5320 MHz	< 0.1	0.11	
NII	5.5 GHz WLAN	5500 - 5700 MHz	< 0.1	0.13	
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A		
Simultaneous SAR per KDB 690783 D01v01r02:			0.95	1.26	1.10

This revised Test Report (S/N: 0Y1405301099-R1.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez
President

ACCREDITED
TESTING CERT#2041.01

© 2014 PCTEST Engineering Laboratory, Inc.

TABLE OF CONTENTS

1 DEVICE UNDER TEST 3

2 LTE INFORMATION 10

3 INTRODUCTION 11

4 DOSIMETRIC ASSESSMENT 12

5 DEFINITION OF REFERENCE POINTS 13

6 TEST CONFIGURATION POSITIONS FOR HANDSETS 14

7 RF EXPOSURE LIMITS 18

8 FCC MEASUREMENT PROCEDURES 19

9 RF CONDUCTED POWERS 24

10 SYSTEM VERIFICATION 45

11 SAR DATA SUMMARY 47

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS 56

13 SAR MEASUREMENT VARIABILITY 60

14 EQUIPMENT LIST 61

15 MEASUREMENT UNCERTAINTIES 62

16 CONCLUSION 64

17 REFERENCES 65

APPENDIX A: SAR TEST PLOTS

APPENDIX B: SAR DIPOLE VERIFICATION PLOTS

APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES

APPENDIX D: SAR TISSUE SPECIFICATIONS

APPENDIX E: SAR SYSTEM VALIDATION

APPENDIX F: SAR TEST SETUP PHOTOGRAPHS

© 2014 PCTEST Engineering Laboratory, Inc.

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.5 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 17	Data	706.5 - 713.5 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
5.8 GHz WLAN	Data	5745 - 5825 MHz
5.2 GHz WLAN	Data	5180 - 5240 MHz
5.3 GHz WLAN	Data	5260 - 5320 MHz
5.5 GHz WLAN	Data	5500 - 5700 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz

© 2014 PCTEST Engineering Laboratory, Inc.

1.2 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	*1 TX Slots*	*2 TX Slots*	*3 TX Slots*	*4 TX Slots*	*1 TX Slots*	*2 TX Slots*	*3 TX Slots*	*4 TX Slots*
GSM/GPRS/EDGE 850	Maximum	**33.0**	**33.0**	**32.0**	**30.0**	**28.5**	**27.5**	**26.5**	**24.0**	**22.5**
	Nominal	**32.5**	**32.5**	**31.5**	**29.5**	**28.0**	**27.0**	**26.0**	**23.5**	**22.0**
GSM/GPRS/EDGE 1900	Maximum	**30.0**	**30.0**	**29.0**	**26.5**	**25.0**	**27.0**	**25.5**	**23.0**	**21.5**
	Nominal	**29.5**	**29.5**	**28.5**	**26.0**	**24.5**	**26.5**	**25.0**	**22.5**	**21.0**

Mode / Band		Modulated Average (dBm)			
		3GPP RMC Rel 99	*3GPP HSDPA Rel 5*	*3GPP HSUPA Rel 6*	*3GPP DC-HSDPA Rel 8*
UMTS Band 5 (850 MHz)	Maximum	**23.0**	**22.4**	**22.0**	**23.0**
	Nominal	**22.5**	**21.9**	**21.5**	**22.5**
UMTS Band 4 (1750 MHz)	Maximum	**23.3**	**22.4**	**22.0**	**23.3**
	Nominal	**22.8**	**21.9**	**21.5**	**22.8**
UMTS Band 2 (1900 MHz)	Maximum	**23.0**	**22.4**	**21.0**	**23.0**
	Nominal	**22.5**	**21.9**	**20.5**	**22.5**

Mode / Band		Modulated Average (dBm)
LTE Band 17	Maximum	**23.0**
	Nominal	**22.5**
LTE Band 5 (Cell)	Maximum	**23.3**
	Nominal	**22.8**
LTE Band 4 (AWS)	Maximum	**23.8**
	Nominal	**23.3**
LTE Band 2 (PCS)	Maximum	**23.4**
	Nominal	**22.9**

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	**16.5**
	Nominal	**16.0**
IEEE 802.11g (2.4 GHz)	Maximum	**13.5**
	Nominal	**13.0**
IEEE 802.11n (2.4 GHz)	Maximum	**9.5**
	Nominal	**9.0**
IEEE 802.11a (5 GHz - 20 MHz)	Maximum	**10.5**
	Nominal	**10.0**
IEEE 802.11n (5 GHz - 40 MHz)	Maximum	**10.5**
	Nominal	**10.0**
Bluetooth	Maximum	**11.5**
	Nominal	**11.0**
Bluetooth LE	Maximum	**8.5**
	Nominal	**8.0**

© 2014 PCTEST Engineering Laboratory, Inc.

1.3 DUT Antenna Locations



1. Main Antenna Tx/Rx
   - GSM/GPRS/EDGE 850/1900 MHz
   - UMTS 850/1700/1900 MHz
   - LTE 700/850/1700/1900 MHz
2. Diversity Antenna Rx
   - GSM/GPRS/EDGE 850/1900 MHz
   - UMTS 850/1700/1900 MHz
   - LTE 700/850/1700/1900 MHz
3. BT/WIFI Antenna Tx/Rx
   - 2.4 GHz WIFI/BT
   - 5 GHz WIFI
4. GPS Rx

Note: Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC Filing.

Figure 1-1
DUT Antenna Locations

© 2014 PCTEST Engineering Laboratory, Inc.

Table 1-1
Mobile Hotspot Sides for SAR Testing

Mobile Hotspot Sides for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
LTE Band 17	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for Wireless Router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v01 guidance, page 2. When the wireless router mode is enabled, all 5 GHz bands are disabled. Therefore 5 GHz WIFI is not considered in this section.

1.4 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the specialized battery. The SAR tests were performed with the specialized battery (model: EB-BG800BBE).

Figure 1-2
NFC Antenna Locations



© 2014 PCTEST Engineering Laboratory, Inc.

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-3 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.

Figure 1-3
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router
1	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A
2	GSM voice + 5 GHz WI-FI	Yes	Yes	N/A
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A
4	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes
5	UMTS + 5 GHz WI-FI	Yes	Yes	N/A
6	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A
7	LTE + 2.4 GHz WI-FI	Yes*	Yes*	Yes
8	LTE + 2.4 GHz Bluetooth	N/A	Yes*	N/A
9	GPRS/EDGE + 2.4 GHz WI-FI	N/A	N/A	Yes
10	LTE + 5 GHz WI-FI	N/A	N/A	N/A
11	GPRS/EDGE + 5 GHz WI-FI	N/A	N/A	N/A

Notes:

1. (*) – Pre-installed VOIP applications are considered.
2. 2.4 GHz WLAN, 2.4 GHz Bluetooth, and 5 GHz WLAN share the same antenna path and cannot transmit simultaneously.
3. GSM/GPRS/EDGE, LTE and UMTS share the same antenna path and cannot transmit simultaneously.
4. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
5. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
6. When the wireless router mode is enabled, all 5 GHz bands are disabled.

© 2014 PCTEST Engineering Laboratory, Inc.

1.6 SAR Test Exclusions Applied

(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using 5 GHz WIFI, only 2.4 GHz WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v01.

Per FCC KDB 447498 D01v05, the SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{Max\ Power\ of\ Channel\ (mW)}{Test\ Separation\ Dist\ (mm)} * \sqrt{Frequency(GHz)} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, Bluetooth SAR was not required; [(14/10)* √2.441] = 2.2< 3.0. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports 20 MHz and 40 MHz Bandwidths for IEEE 802.11n for 5 GHz WIFI only. IEEE 802.11n was not evaluated for SAR since the average output power of 20 MHz and 40 MHz bandwidths was not more than 0.25 dB higher than the average output power of IEEE 802.11a.

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v02.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02.

1.7 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

1.8 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01-D06 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v01r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05 (General SAR Guidance)
- FCC KDB Publication 865664 D01-D02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

© 2014 PCTEST Engineering Laboratory, Inc.

1.9 Device Serial Numbers

Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
GSM/GPRS/EDGE 850	FL-208-A	FL-208-A	FL-208-A
UMTS 850	FL-208-A	FL-208-A	FL-208-A
UMTS 1750	FL-208-A	FL-208-B	FL-208-B
GSM/GPRS/EDGE 1900	FL-208-A	FL-208-A	FL-208-A
UMTS 1900	FL-208-A	FL-208-A	FL-208-A
LTE Band 17	FL-208-A	FL-208-C	FL-208-C
LTE Band 5 (Cell)	FL-208-B	FL-208-B	FL-208-B
LTE Band 4 (AWS)	FL-208-B	FL-208-B	FL-208-B
LTE Band 2 (PCS)	FL-208-A	FL-208-A	FL-208-A
2.4 GHz WLAN	FL-208-B	FL-208-A	FL-208-A
5 GHz WLAN	FCC2	FCC2	-

© 2014 PCTEST Engineering Laboratory, Inc.

2 LTE INFORMATION

LTE Information			
FCC ID	**A3LSMG800M**		
Form Factor	Portable Handset		
Frequency Range of each LTE transmission band	LTE Band 17 (706.5 - 713.5 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
Channel Bandwidths	LTE Band 17: 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
UE Category	4		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		

© 2014 PCTEST Engineering Laboratory, Inc.

3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt}\left(\frac{dU}{dm}\right) = \frac{d}{dt}\left(\frac{dU}{\rho dv}\right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

σ = conductivity of the tissue-simulating material (S/m)
ρ = mass density of the tissue-simulating material (kg/m^3)
E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

© 2014 PCTEST Engineering Laboratory, Inc.

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:



Figure 4-1
Sample SAR Area Scan

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
   a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
   b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
   c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01*

Frequency	Maximum Area Scan Resolution (mm) (Δx_{area}, Δy_{area})	Maximum Zoom Scan Resolution (mm) (Δx_{zoom}, Δy_{zoom})	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)$*	$\Delta z_{zoom}(n>1)$*	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5*$\Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5*$\Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5*$\Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5*$\Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5*$\Delta z_{zoom}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

© 2014 PCTEST Engineering Laboratory, Inc.

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point "M" is the reference point for the center of the mouth, "LE" is the left ear reference point (ERP), and "RE" is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].



Figure 5-1
Close-Up Side view of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Figure 5-3). The acoustic output was than located at the same level as the center of the ear reference point. The test device was positioned so that the "vertical centerline" was bisecting the front surface of the handset at its top and bottom edges, positioning the "ear reference point" on the outer surface of the both the left and right head phantoms on the ear reference point.

Figure 5-2
Front, back and side view of SAM Twin Phantom



Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

© 2014 PCTEST Engineering Laboratory, Inc.

6 TEST CONFIGURATION POSITIONS FOR HANDSETS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity ε = 3 and loss tangent δ = 0.02.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.

Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical was respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15º Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

© 2014 PCTEST Engineering Laboratory, Inc.



Figure 6-2 Front, Side and Top View of Ear/15º Tilt Position



Figure 6-3
Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04_v01. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

Figure 6-4 Twin SAM Chin20

© 2014 PCTEST Engineering Laboratory, Inc.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-5). Per FCC KDB Publication 648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v05 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.



Figure 6-5
Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 44798 D01v05 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v05, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

© 2014 PCTEST Engineering Laboratory, Inc.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

© 2014 PCTEST Engineering Laboratory, Inc.

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT *General Population* (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT *Occupational* (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

© 2014 PCTEST Engineering Laboratory, Inc.

8 FCC MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 “SAR Measurement Procedures for 3G Devices” v02, October 2007.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

8.3 SAR Measurement Conditions for UMTS

8.3.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1s”.

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

© 2014 PCTEST Engineering Laboratory, Inc.

8.3.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all “1s”. SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

8.3.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”.

8.3.4 SAR Measurements for Handsets with Rel 5 HSDPA

Body SAR for HSDPA is not required for handsets with HSDPA capabilities when the maximum average output power of each RF channel with HSDPA active is less than 0.25 dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is ≤ 75% of the SAR limit. Otherwise, SAR is measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration measured in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that resulted in the highest SAR in 12.2 kbps RMC mode for that RF channel.

The H-set used in FRC for HSDPA should be configured according to the UE category of a test device. The number of HS-DSCH/HSPDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the applicable H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the FRC for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 2 ms to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors of βc=9 and βd=15, and power offset parameters of ΔACK= ΔNACK =5 and ΔCQI=2 is used. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the FRC.

Sub-Test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 8 ⇔ $A_{hs} = \beta_{hs}/\beta_c$ = 30/15 ⇔ β_{hs}= 30/15 *β_c.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and Δ_{NACK} = 8 (A_{hs} = 30/15) with β_{hs} = 30/15 * β_c, and Δ_{CQI} = 7 (A_{hs} = 24/15) with β_{hs} = 24/15 * β_c.

Note 3: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c=24/15. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Figure 8-1
Table C.10.1.4 of TS 234.121-1

© 2014 PCTEST Engineering Laboratory, Inc.

8.3.5 SAR Measurements for Handsets with Rel 6 HSUPA

Body SAR for HSUPA is not required when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25 dB higher than as measured without HSUPA/HSDPA using 12.2 kbps RMC and maximum SAR for 12.2 kbps RMC is ≤ 75 % of the SAR limit. Otherwise SAR is measured on the maximum output channel for the body exposure configuration produced highest SAR in 12.2 kbps RMC for that RF channel, using the additional procedures under "Release 6 HSPA data devices"

Head SAR for VOIP operations under HSPA is not required when maximum average output of each RF channel with HSPA is less than 0.25 dB higher than as measured using 12.2 kbps RMC. Otherwise SAR is measured using same HSPA configuration as used for body SAR.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (1)	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (2) (dB)	MPR (dB)	AG (4) Index	E-TFCI
1	11/15 (3)	15/15 (3)	64	11/15 (2)	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1}: 47/15 β_{ed2}: 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (4)	15/15 (4)	64	15/15 (4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.
Note 2: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c=24/15. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.
Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to β_c = 10/15 and β_d = 15/15.
Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to β_c = 14/15 and β_d = 15/15.
Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.
Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

8.3.6 SAR Measurement Conditions for DC-HSDPA

SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion. DC-HSDPA uplink maximum output power measurements using the four Rel. 5 HSDPA subtests in Table C.10.1.4 of TS 234.121-1 is required.

When the maximum average output power of each RF channel with DC-HSDPA active is ≤ ¼ dB higher than that measured using 12.2 kbps RMC, or the maximum reported SAR for 12.2 kbps RMC is ≤ 75% of the SAR limit, SAR evaluation for DC-HSDPA is not required.

8.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

© 2014 PCTEST Engineering Laboratory, Inc.

8.4.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.4.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.4.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r01:

a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
    i. The required channel and offset combination with the highest maximum output power is required for SAR.
    ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
    iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to ½ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is <1.45 W/kg.

8.5 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g/n transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v01r02 for more details.

© 2014 PCTEST Engineering Laboratory, Inc.

8.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

8.5.2 Frequency Channel Configurations [24]

For 2.4 GHz, the highest average RF output power channel between the low, mid and high channel at the lowest data rate was selected for SAR evaluation in 802.11b mode. 802.11g/n modes and higher data rates for 802.11b were additionally evaluated for SAR if the output power of the respective mode was 0.25 dB or higher than the powers of the SAR configurations tested in the 802.11b mode.

For 5 GHz, the highest average RF output power channel across the default test channels at the lowest data rate was selected for SAR evaluation in 802.11a. When the adjacent channels are higher in power then the default channels, these “required channels” were considered instead of the default channels for SAR testing. 802.11n modes and higher data rates for 802.11a/n were evaluated only if the respective mode was higher than 0.25 dB or more than the 802.11a mode.

If the maximum extrapolated peak SAR of the zoom scan for the highest output channel was less than 1.6 W/kg and if the 1g averaged SAR was less than 0.8 W/kg, SAR testing was not required for the other test channels in the band.

© 2014 PCTEST Engineering Laboratory, Inc.

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

		Maximum Burst-Averaged Output Power								
		Voice	*GPRS/EDGE Data (GMSK)*				*EDGE Data (8-PSK)*			
Band	**Channel**	**GSM [dBm] CS (1 Slot)**	**GPRS [dBm] 1 Tx Slot**	**GPRS [dBm] 2 Tx Slot**	**GPRS [dBm] 3 Tx Slot**	**GPRS [dBm] 4 Tx Slot**	**EDGE [dBm] 1 Tx Slot**	**EDGE [dBm] 2 Tx Slot**	**EDGE [dBm] 3 Tx Slot**	**EDGE [dBm] 4 Tx Slot**
GSM 850	128	32.68	32.73	31.83	**29.68**	28.13	27.26	26.32	23.69	21.83
	190	32.60	32.66	31.75	**29.69**	28.07	27.31	26.10	23.59	21.77
	251	32.64	32.69	31.80	**29.76**	28.17	27.50	26.38	23.77	22.05
GSM 1900	512	29.87	29.90	**28.70**	26.22	24.76	26.36	25.06	22.74	21.13
	661	29.84	29.86	**28.61**	26.10	24.62	26.45	24.93	22.67	21.05
	810	29.86	29.89	**28.79**	26.31	24.95	26.74	25.26	22.64	20.88
GSM 850	**Targets:**	32.5	32.5	31.5	**29.5**	28.0	27.0	26.0	23.5	22.0
GSM 1900		29.5	29.5	**28.5**	26.0	24.5	26.5	25.0	22.5	21.0
		Calculated Maximum Frame-Averaged Output Power								
		Voice	*GPRS/EDGE Data (GMSK)*				*EDGE Data (8-PSK)*			
Band	**Channel**	**GSM [dBm] CS (1 Slot)**	**GPRS [dBm] 1 Tx Slot**	**GPRS [dBm] 2 Tx Slot**	**GPRS [dBm] 3 Tx Slot**	**GPRS [dBm] 4 Tx Slot**	**EDGE [dBm] 1 Tx Slot**	**EDGE [dBm] 2 Tx Slot**	**EDGE [dBm] 3 Tx Slot**	**EDGE [dBm] 4 Tx Slot**
GSM 850	128	23.65	23.70	25.81	**25.42**	25.12	18.23	20.30	19.43	18.82
	190	23.57	23.63	25.73	**25.43**	25.06	18.28	20.08	19.33	18.76
	251	23.61	23.66	25.78	**25.50**	25.16	18.47	20.36	19.51	19.04
GSM 1900	512	20.84	20.87	**22.68**	21.96	21.75	17.33	19.04	18.48	18.12
	661	20.81	20.83	**22.59**	21.84	21.61	17.42	18.91	18.41	18.04
	810	20.83	20.86	**22.77**	22.05	21.94	17.71	19.24	18.38	17.87
GSM 850	**Frame Avg.Targets:**	23.47	23.47	25.48	**25.24**	24.99	17.97	19.98	19.24	18.99
GSM 1900		20.47	20.47	**22.48**	21.74	21.49	17.47	18.98	18.24	17.99

Notes:
1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
4. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33 (Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A

Figure 9-1
Power Measurement Setup

© 2014 PCTEST Engineering Laboratory, Inc.

9.2 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1862	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.88	22.87	22.85	23.00	23.29	22.87	22.99	22.80	22.85	-
99		12.2 kbps AMR	22.87	22.99	22.88	23.02	23.28	22.85	23.00	22.84	22.83	-
6	HSDPA	Subtest 1	20.62	20.41	20.40	20.43	20.44	20.44	20.40	20.42	20.43	0
6		Subtest 2	21.91	21.84	21.90	22.37	22.33	22.33	22.05	22.11	22.11	0
6		Subtest 3	21.96	21.87	21.91	22.38	22.33	22.30	22.06	22.08	22.16	0.5
6		Subtest 4	21.94	22.03	21.90	22.36	22.39	22.29	22.09	22.04	22.10	0.5
6	HSUPA	Subtest 1	22.00	21.98	22.00	21.40	21.15	22.00	20.98	20.97	20.95	0
6		Subtest 2	19.23	19.14	19.21	19.34	19.47	19.27	19.20	19.22	19.25	2
6		Subtest 3	20.19	20.11	20.14	20.36	20.42	20.26	20.17	20.19	20.16	1
6		Subtest 4	20.92	20.83	19.03	19.29	19.43	19.21	19.14	19.12	19.13	2
6		Subtest 5	20.11	20.10	20.13	20.28	20.42	20.17	19.05	19.16	19.14	0
8	DC-HSDPA	Subtest 1	22.99	22.95	22.74	22.82	23.30	23.21	22.88	23.00	22.59	0
8		Subtest 2	22.53	22.59	22.68	22.91	23.03	22.81	21.59	21.69	21.67	0
8		Subtest 3	22.52	21.64	21.74	21.93	21.02	21.78	21.57	21.64	21.62	0.5
8		Subtest 4	22.56	20.60	20.74	20.94	21.02	20.93	22.33	20.66	22.34	0.5

UMTS SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- Measured maximum output powers for DC-HSDPA were not greater than 1/4 dB higher than the WCDMA 12.2 kbps RMC maximum output, as a result, SAR is not required for DC-HSDPA
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.

Figure 9-2
Power Measurement Setup

© 2014 PCTEST Engineering Laboratory, Inc.

9.3 LTE Conducted Powers

9.3.1 LTE Band 17

Table 9-1
LTE Band 17 Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	710.0	23790	10	QPSK	1	0	**22.98**	0	0
	710.0	23790	10	QPSK	1	25	22.91	0	0
	710.0	23790	10	QPSK	1	49	22.90	0	0
	710.0	23790	10	QPSK	25	0	**21.94**	0-1	1
	710.0	23790	10	QPSK	25	12	21.93	0-1	1
	710.0	23790	10	QPSK	25	25	21.91	0-1	1
	710.0	23790	10	QPSK	50	0	21.93	0-1	1
	710.0	23790	10	16QAM	1	0	21.99	0-1	1
	710.0	23790	10	16QAM	1	25	21.94	0-1	1
	710.0	23790	10	16QAM	1	49	21.98	0-1	1
	710.0	23790	10	16QAM	25	0	20.96	0-2	2
	710.0	23790	10	16QAM	25	12	20.93	0-2	2
	710.0	23790	10	16QAM	25	25	20.98	0-2	2
	710.0	23790	10	16QAM	50	0	20.96	0-2	2

Note: LTE Band 17 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-2
LTE Band 17 Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	710.0	23790	5	QPSK	1	0	22.94	0	0
	710.0	23790	5	QPSK	1	12	22.89	0	0
	710.0	23790	5	QPSK	1	24	22.84	0	0
	710.0	23790	5	QPSK	12	0	21.35	0-1	1
	710.0	23790	5	QPSK	12	6	21.43	0-1	1
	710.0	23790	5	QPSK	12	13	21.37	0-1	1
	710.0	23790	5	QPSK	25	0	21.47	0-1	1
	710.0	23790	5	16-QAM	1	0	21.77	0-1	1
	710.0	23790	5	16-QAM	1	12	21.54	0-1	1
	710.0	23790	5	16-QAM	1	24	21.82	0-1	1
	710.0	23790	5	16-QAM	12	0	20.39	0-2	2
	710.0	23790	5	16-QAM	12	6	20.42	0-2	2
	710.0	23790	5	16-QAM	12	13	20.34	0-2	2
	710.0	23790	5	16-QAM	25	0	20.17	0-2	2

Note: LTE Band 17 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

© 2014 PCTEST Engineering Laboratory, Inc.

9.3.2 LTE Band 5 (Cell)

Table 9-3
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	836.5	20525	10	QPSK	1	0	**23.23**	0	0
	836.5	20525	10	QPSK	1	25	23.21	0	0
	836.5	20525	10	QPSK	1	49	23.17	0	0
	836.5	20525	10	QPSK	25	0	**22.01**	0-1	1
	836.5	20525	10	QPSK	25	12	21.99	0-1	1
	836.5	20525	10	QPSK	25	25	21.98	0-1	1
	836.5	20525	10	QPSK	50	0	21.98	0-1	1
	836.5	20525	10	16QAM	1	0	22.30	0-1	1
	836.5	20525	10	16QAM	1	25	22.29	0-1	1
	836.5	20525	10	16QAM	1	49	22.26	0-1	1
	836.5	20525	10	16QAM	25	0	20.88	0-2	2
	836.5	20525	10	16QAM	25	12	20.90	0-2	2
	836.5	20525	10	16QAM	25	25	21.02	0-2	2
	836.5	20525	10	16QAM	50	0	20.89	0-2	2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-4
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	826.5	20425	5	QPSK	1	0	23.22	0	0
	826.5	20425	5	QPSK	1	12	23.16	0	0
	826.5	20425	5	QPSK	1	24	23.18	0	0
	826.5	20425	5	QPSK	12	0	21.77	0-1	1
	826.5	20425	5	QPSK	12	6	21.72	0-1	1
	826.5	20425	5	QPSK	12	13	21.70	0-1	1
	826.5	20425	5	QPSK	25	0	21.71	0-1	1
	826.5	20425	5	16-QAM	1	0	21.98	0-1	1
	826.5	20425	5	16-QAM	1	12	21.92	0-1	1
	826.5	20425	5	16-QAM	1	24	21.99	0-1	1
	826.5	20425	5	16-QAM	12	0	20.72	0-2	2
	826.5	20425	5	16-QAM	12	6	20.68	0-2	2
	826.5	20425	5	16-QAM	12	13	20.62	0-2	2
	826.5	20425	5	16-QAM	25	0	20.65	0-2	2
Mid	836.5	20525	5	QPSK	1	0	23.25	0	0
	836.5	20525	5	QPSK	1	12	23.23	0	0
	836.5	20525	5	QPSK	1	24	23.22	0	0
	836.5	20525	5	QPSK	12	0	21.71	0-1	1
	836.5	20525	5	QPSK	12	6	21.69	0-1	1
	836.5	20525	5	QPSK	12	13	21.68	0-1	1
	836.5	20525	5	QPSK	25	0	21.69	0-1	1
	836.5	20525	5	16-QAM	1	0	22.29	0-1	1
	836.5	20525	5	16-QAM	1	12	22.21	0-1	1
	836.5	20525	5	16-QAM	1	24	22.25	0-1	1
	836.5	20525	5	16-QAM	12	0	20.51	0-2	2
	836.5	20525	5	16-QAM	12	6	20.53	0-2	2
	836.5	20525	5	16-QAM	12	13	20.51	0-2	2
	836.5	20525	5	16-QAM	25	0	20.67	0-2	2
High	846.5	20625	5	QPSK	1	0	22.72	0	0
	846.5	20625	5	QPSK	1	12	22.70	0	0
	846.5	20625	5	QPSK	1	24	22.69	0	0
	846.5	20625	5	QPSK	12	0	21.75	0-1	1
	846.5	20625	5	QPSK	12	6	21.75	0-1	1
	846.5	20625	5	QPSK	12	13	21.75	0-1	1
	846.5	20625	5	QPSK	25	0	21.77	0-1	1
	846.5	20625	5	16-QAM	1	0	22.29	0-1	1
	846.5	20625	5	16-QAM	1	12	22.29	0-1	1
	846.5	20625	5	16-QAM	1	24	22.23	0-1	1
	846.5	20625	5	16-QAM	12	0	20.76	0-2	2
	846.5	20625	5	16-QAM	12	6	20.76	0-2	2
	846.5	20625	5	16-QAM	12	13	20.74	0-2	2
	846.5	20625	5	16-QAM	25	0	20.62	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-5
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	Deviation [dB]
Low	825.5	20415	3	QPSK	1	0	23.23	0	0	0.43
	825.5	20415	3	QPSK	1	7	23.22	0	0	0.42
	825.5	20415	3	QPSK	1	14	23.26	0	0	0.46
	825.5	20415	3	QPSK	8	0	21.72	0-1	1	-0.08
	825.5	20415	3	QPSK	8	4	21.70	0-1	1	-0.10
	825.5	20415	3	QPSK	8	7	21.69	0-1	1	-0.11
	825.5	20415	3	QPSK	15	0	21.73	0-1	1	-0.07
	825.5	20415	3	16-QAM	1	0	22.30	0-1	1	0.50
	825.5	20415	3	16-QAM	1	7	22.28	0-1	1	0.48
	825.5	20415	3	16-QAM	1	14	22.27	0-1	1	0.47
	825.5	20415	3	16-QAM	8	0	20.82	0-2	2	0.02
	825.5	20415	3	16-QAM	8	4	20.83	0-2	2	0.03
	825.5	20415	3	16-QAM	8	7	20.80	0-2	2	0.00
	825.5	20415	3	16-QAM	15	0	20.65	0-2	2	-0.15
Mid	836.5	20525	3	QPSK	1	0	22.99	0	0	0.19
	836.5	20525	3	QPSK	1	7	22.91	0	0	0.11
	836.5	20525	3	QPSK	1	14	22.95	0	0	0.15
	836.5	20525	3	QPSK	8	0	21.69	0-1	1	-0.11
	836.5	20525	3	QPSK	8	4	21.69	0-1	1	-0.11
	836.5	20525	3	QPSK	8	7	21.71	0-1	1	-0.09
	836.5	20525	3	QPSK	15	0	21.72	0-1	1	-0.08
	836.5	20525	3	16-QAM	1	0	22.30	0-1	1	0.50
	836.5	20525	3	16-QAM	1	7	22.28	0-1	1	0.48
	836.5	20525	3	16-QAM	1	14	22.23	0-1	1	0.43
	836.5	20525	3	16-QAM	8	0	20.63	0-2	2	-0.17
	836.5	20525	3	16-QAM	8	4	20.64	0-2	2	-0.16
	836.5	20525	3	16-QAM	8	7	20.63	0-2	2	-0.17
	836.5	20525	3	16-QAM	15	0	20.61	0-2	2	-0.19
High	847.5	20635	3	QPSK	1	0	23.20	0	0	0.40
	847.5	20635	3	QPSK	1	7	23.22	0	0	0.42
	847.5	20635	3	QPSK	1	14	23.27	0	0	0.47
	847.5	20635	3	QPSK	8	0	21.77	0-1	1	-0.03
	847.5	20635	3	QPSK	8	4	21.75	0-1	1	-0.05
	847.5	20635	3	QPSK	8	7	21.76	0-1	1	-0.04
	847.5	20635	3	QPSK	15	0	21.78	0-1	1	-0.02
	847.5	20635	3	16-QAM	1	0	21.87	0-1	1	0.07
	847.5	20635	3	16-QAM	1	7	21.75	0-1	1	-0.05
	847.5	20635	3	16-QAM	1	14	21.77	0-1	1	-0.03
	847.5	20635	3	16-QAM	8	0	20.59	0-2	2	-0.21
	847.5	20635	3	16-QAM	8	4	20.60	0-2	2	-0.20
	847.5	20635	3	16-QAM	8	7	20.61	0-2	2	-0.19
	847.5	20635	3	16-QAM	15	0	20.67	0-2	2	-0.13

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-6
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	824.7	20407	1.4	QPSK	1	0	23.20	0	0
	824.7	20407	1.4	QPSK	1	2	23.28	0	0
	824.7	20407	1.4	QPSK	1	5	23.29	0	0
	824.7	20407	1.4	QPSK	3	0	22.81	0	0
	824.7	20407	1.4	QPSK	3	2	22.83	0	0
	824.7	20407	1.4	QPSK	3	3	22.87	0	0
	824.7	20407	1.4	QPSK	6	0	21.65	0-1	1
	824.7	20407	1.4	16-QAM	1	0	22.25	0-1	1
	824.7	20407	1.4	16-QAM	1	2	22.27	0-1	1
	824.7	20407	1.4	16-QAM	1	5	22.29	0-1	1
	824.7	20407	1.4	16-QAM	3	0	21.63	0-1	1
	824.7	20407	1.4	16-QAM	3	2	21.63	0-1	1
	824.7	20407	1.4	16-QAM	3	3	21.61	0-1	1
	824.7	20407	1.4	16-QAM	6	0	20.61	0-2	2
Mid	836.5	20525	1.4	QPSK	1	0	23.29	0	0
	836.5	20525	1.4	QPSK	1	2	23.21	0	0
	836.5	20525	1.4	QPSK	1	5	23.30	0	0
	836.5	20525	1.4	QPSK	3	0	22.79	0	0
	836.5	20525	1.4	QPSK	3	2	22.79	0	0
	836.5	20525	1.4	QPSK	3	3	22.80	0	0
	836.5	20525	1.4	QPSK	6	0	21.62	0-1	1
	836.5	20525	1.4	16-QAM	1	0	22.12	0-1	1
	836.5	20525	1.4	16-QAM	1	2	22.11	0-1	1
	836.5	20525	1.4	16-QAM	1	5	22.16	0-1	1
	836.5	20525	1.4	16-QAM	3	0	21.56	0-1	1
	836.5	20525	1.4	16-QAM	3	2	21.53	0-1	1
	836.5	20525	1.4	16-QAM	3	3	21.55	0-1	1
	836.5	20525	1.4	16-QAM	6	0	20.48	0-2	2
High	848.3	20643	1.4	QPSK	1	0	23.22	0	0
	848.3	20643	1.4	QPSK	1	2	23.21	0	0
	848.3	20643	1.4	QPSK	1	5	23.25	0	0
	848.3	20643	1.4	QPSK	3	0	22.84	0	0
	848.3	20643	1.4	QPSK	3	2	22.83	0	0
	848.3	20643	1.4	QPSK	3	3	22.80	0	0
	848.3	20643	1.4	QPSK	6	0	21.62	0-1	1
	848.3	20643	1.4	16-QAM	1	0	22.26	0-1	1
	848.3	20643	1.4	16-QAM	1	2	22.22	0-1	1
	848.3	20643	1.4	16-QAM	1	5	22.29	0-1	1
	848.3	20643	1.4	16-QAM	3	0	21.79	0-1	1
	848.3	20643	1.4	16-QAM	3	2	21.85	0-1	1
	848.3	20643	1.4	16-QAM	3	3	21.83	0-1	1
	848.3	20643	1.4	16-QAM	6	0	20.87	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

9.3.3 LTE Band 4 (AWS)

Table 9-7
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	1732.5	20175	20	QPSK	1	0	23.71	0	0
	1732.5	20175	20	QPSK	1	50	23.69	0	0
	1732.5	20175	20	QPSK	1	99	**23.76**	0	0
	1732.5	20175	20	QPSK	50	0	22.60	0-1	1
	1732.5	20175	20	QPSK	50	25	22.62	0-1	1
	1732.5	20175	20	QPSK	50	50	**22.75**	0-1	1
	1732.5	20175	20	QPSK	100	0	22.61	0-1	1
	1732.5	20175	20	16QAM	1	0	22.46	0-1	1
	1732.5	20175	20	16QAM	1	50	22.57	0-1	1
	1732.5	20175	20	16QAM	1	99	22.56	0-1	1
	1732.5	20175	20	16QAM	50	0	21.55	0-2	2
	1732.5	20175	20	16QAM	50	25	21.57	0-2	2
	1732.5	20175	20	16QAM	50	50	21.64	0-2	2
	1732.5	20175	20	16QAM	100	0	21.54	0-2	2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-8
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1717.5	20025	15	QPSK	1	0	23.56	0	0
	1717.5	20025	15	QPSK	1	36	23.66	0	0
	1717.5	20025	15	QPSK	1	74	23.71	0	0
	1717.5	20025	15	QPSK	36	0	22.18	0-1	1
	1717.5	20025	15	QPSK	36	18	22.16	0-1	1
	1717.5	20025	15	QPSK	36	37	22.00	0-1	1
	1717.5	20025	15	QPSK	75	0	22.17	0-1	1
	1717.5	20025	15	16QAM	1	0	22.30	0-1	1
	1717.5	20025	15	16QAM	1	36	22.36	0-1	1
	1717.5	20025	15	16QAM	1	74	22.39	0-1	1
	1717.5	20025	15	16QAM	36	0	21.06	0-2	2
	1717.5	20025	15	16QAM	36	18	21.05	0-2	2
	1717.5	20025	15	16QAM	36	37	21.04	0-2	2
	1717.5	20025	15	16QAM	75	0	21.08	0-2	2
Mid	1732.5	20175	15	QPSK	1	0	23.54	0	0
	1732.5	20175	15	QPSK	1	36	23.58	0	0
	1732.5	20175	15	QPSK	1	74	23.61	0	0
	1732.5	20175	15	QPSK	36	0	22.33	0-1	1
	1732.5	20175	15	QPSK	36	18	22.39	0-1	1
	1732.5	20175	15	QPSK	36	37	22.40	0-1	1
	1732.5	20175	15	QPSK	75	0	22.35	0-1	1
	1732.5	20175	15	16QAM	1	0	22.76	0-1	1
	1732.5	20175	15	16QAM	1	36	22.80	0-1	1
	1732.5	20175	15	16QAM	1	74	22.80	0-1	1
	1732.5	20175	15	16QAM	36	0	21.27	0-2	2
	1732.5	20175	15	16QAM	36	18	21.28	0-2	2
	1732.5	20175	15	16QAM	36	37	21.31	0-2	2
	1732.5	20175	15	16QAM	75	0	21.33	0-2	2
High	1747.5	20325	15	QPSK	1	0	23.19	0	0
	1747.5	20325	15	QPSK	1	36	23.17	0	0
	1747.5	20325	15	QPSK	1	74	23.18	0	0
	1747.5	20325	15	QPSK	36	0	22.05	0-1	1
	1747.5	20325	15	QPSK	36	18	22.07	0-1	1
	1747.5	20325	15	QPSK	36	37	22.08	0-1	1
	1747.5	20325	15	QPSK	75	0	22.07	0-1	1
	1747.5	20325	15	16QAM	1	0	22.34	0-1	1
	1747.5	20325	15	16QAM	1	36	22.38	0-1	1
	1747.5	20325	15	16QAM	1	74	22.43	0-1	1
	1747.5	20325	15	16QAM	36	0	21.00	0-2	2
	1747.5	20325	15	16QAM	36	18	21.02	0-2	2
	1747.5	20325	15	16QAM	36	37	21.05	0-2	2
	1747.5	20325	15	16QAM	75	0	21.00	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-9
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1715	20000	10	QPSK	1	0	23.62	0	0
	1715	20000	10	QPSK	1	25	23.63	0	0
	1715	20000	10	QPSK	1	49	23.69	0	0
	1715	20000	10	QPSK	25	0	22.19	0-1	1
	1715	20000	10	QPSK	25	12	22.19	0-1	1
	1715	20000	10	QPSK	25	25	22.21	0-1	1
	1715	20000	10	QPSK	50	0	22.19	0-1	1
	1715	20000	10	16QAM	1	0	22.76	0-1	1
	1715	20000	10	16QAM	1	25	22.78	0-1	1
	1715	20000	10	16QAM	1	49	22.80	0-1	1
	1715	20000	10	16QAM	25	0	21.15	0-2	2
	1715	20000	10	16QAM	25	12	21.13	0-2	2
	1715	20000	10	16QAM	25	25	21.14	0-2	2
	1715	20000	10	16QAM	50	0	21.15	0-2	2
Mid	1732.5	20175	10	QPSK	1	0	23.58	0	0
	1732.5	20175	10	QPSK	1	25	23.57	0	0
	1732.5	20175	10	QPSK	1	49	23.60	0	0
	1732.5	20175	10	QPSK	25	0	22.36	0-1	1
	1732.5	20175	10	QPSK	25	12	22.34	0-1	1
	1732.5	20175	10	QPSK	25	25	22.38	0-1	1
	1732.5	20175	10	QPSK	50	0	22.36	0-1	1
	1732.5	20175	10	16QAM	1	0	22.80	0-1	1
	1732.5	20175	10	16QAM	1	25	22.78	0-1	1
	1732.5	20175	10	16QAM	1	49	22.79	0-1	1
	1732.5	20175	10	16QAM	25	0	21.22	0-2	2
	1732.5	20175	10	16QAM	25	12	21.24	0-2	2
	1732.5	20175	10	16QAM	25	25	21.25	0-2	2
	1732.5	20175	10	16QAM	50	0	21.24	0-2	2
High	1750	20350	10	QPSK	1	0	23.44	0	0
	1750	20350	10	QPSK	1	25	23.47	0	0
	1750	20350	10	QPSK	1	49	23.57	0	0
	1750	20350	10	QPSK	25	0	22.06	0-1	1
	1750	20350	10	QPSK	25	12	22.03	0-1	1
	1750	20350	10	QPSK	25	25	22.06	0-1	1
	1750	20350	10	QPSK	50	0	22.03	0-1	1
	1750	20350	10	16QAM	1	0	22.63	0-1	1
	1750	20350	10	16QAM	1	25	22.61	0-1	1
	1750	20350	10	16QAM	1	49	22.68	0-1	1
	1750	20350	10	16QAM	25	0	20.93	0-2	2
	1750	20350	10	16QAM	25	12	20.94	0-2	2
	1750	20350	10	16QAM	25	25	20.94	0-2	2
	1750	20350	10	16QAM	50	0	20.95	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-10
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1712.5	19975	5	QPSK	1	0	23.44	0	0
	1712.5	19975	5	QPSK	1	12	23.42	0	0
	1712.5	19975	5	QPSK	1	24	23.49	0	0
	1712.5	19975	5	QPSK	12	0	22.17	0-1	1
	1712.5	19975	5	QPSK	12	6	22.18	0-1	1
	1712.5	19975	5	QPSK	12	13	22.19	0-1	1
	1712.5	19975	5	QPSK	25	0	22.17	0-1	1
	1712.5	19975	5	16-QAM	1	0	22.65	0-1	1
	1712.5	19975	5	16-QAM	1	12	22.55	0-1	1
	1712.5	19975	5	16-QAM	1	24	22.66	0-1	1
	1712.5	19975	5	16-QAM	12	0	21.18	0-2	2
	1712.5	19975	5	16-QAM	12	6	21.16	0-2	2
	1712.5	19975	5	16-QAM	12	13	21.17	0-2	2
	1712.5	19975	5	16-QAM	25	0	21.01	0-2	2
Mid	1732.5	20175	5	QPSK	1	0	23.80	0	0
	1732.5	20175	5	QPSK	1	12	23.73	0	0
	1732.5	20175	5	QPSK	1	24	23.75	0	0
	1732.5	20175	5	QPSK	12	0	22.33	0-1	1
	1732.5	20175	5	QPSK	12	6	22.34	0-1	1
	1732.5	20175	5	QPSK	12	13	22.32	0-1	1
	1732.5	20175	5	QPSK	25	0	22.34	0-1	1
	1732.5	20175	5	16-QAM	1	0	22.40	0-1	1
	1732.5	20175	5	16-QAM	1	12	22.38	0-1	1
	1732.5	20175	5	16-QAM	1	24	22.42	0-1	1
	1732.5	20175	5	16-QAM	12	0	21.27	0-2	2
	1732.5	20175	5	16-QAM	12	6	21.30	0-2	2
	1732.5	20175	5	16-QAM	12	13	21.33	0-2	2
	1732.5	20175	5	16-QAM	25	0	21.34	0-2	2
High	1752.5	20375	5	QPSK	1	0	22.87	0	0
	1752.5	20375	5	QPSK	1	12	22.82	0	0
	1752.5	20375	5	QPSK	1	24	22.85	0	0
	1752.5	20375	5	QPSK	12	0	21.94	0-1	1
	1752.5	20375	5	QPSK	12	6	21.93	0-1	1
	1752.5	20375	5	QPSK	12	13	21.96	0-1	1
	1752.5	20375	5	QPSK	25	0	21.96	0-1	1
	1752.5	20375	5	16-QAM	1	0	22.54	0-1	1
	1752.5	20375	5	16-QAM	1	12	22.59	0-1	1
	1752.5	20375	5	16-QAM	1	24	22.63	0-1	1
	1752.5	20375	5	16-QAM	12	0	20.92	0-2	2
	1752.5	20375	5	16-QAM	12	6	20.93	0-2	2
	1752.5	20375	5	16-QAM	12	13	20.93	0-2	2
	1752.5	20375	5	16-QAM	25	0	20.86	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-11
LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1711.5	19965	3	QPSK	1	0	23.80	0	0
	1711.5	19965	3	QPSK	1	7	23.77	0	0
	1711.5	19965	3	QPSK	1	14	23.71	0	0
	1711.5	19965	3	QPSK	8	0	22.17	0-1	1
	1711.5	19965	3	QPSK	8	4	22.15	0-1	1
	1711.5	19965	3	QPSK	8	7	22.16	0-1	1
	1711.5	19965	3	QPSK	15	0	22.20	0-1	1
	1711.5	19965	3	16-QAM	1	0	22.55	0-1	1
	1711.5	19965	3	16-QAM	1	7	22.56	0-1	1
	1711.5	19965	3	16-QAM	1	14	22.63	0-1	1
	1711.5	19965	3	16-QAM	8	0	21.07	0-2	2
	1711.5	19965	3	16-QAM	8	4	21.07	0-2	2
	1711.5	19965	3	16-QAM	8	7	21.11	0-2	2
	1711.5	19965	3	16-QAM	15	0	21.13	0-2	2
Mid	1732.5	20175	3	QPSK	1	0	23.62	0	0
	1732.5	20175	3	QPSK	1	7	23.62	0	0
	1732.5	20175	3	QPSK	1	14	23.64	0	0
	1732.5	20175	3	QPSK	8	0	22.31	0-1	1
	1732.5	20175	3	QPSK	8	4	22.29	0-1	1
	1732.5	20175	3	QPSK	8	7	22.30	0-1	1
	1732.5	20175	3	QPSK	15	0	22.34	0-1	1
	1732.5	20175	3	16-QAM	1	0	22.72	0-1	1
	1732.5	20175	3	16-QAM	1	7	22.74	0-1	1
	1732.5	20175	3	16-QAM	1	14	22.74	0-1	1
	1732.5	20175	3	16-QAM	8	0	21.38	0-2	2
	1732.5	20175	3	16-QAM	8	4	21.44	0-2	2
	1732.5	20175	3	16-QAM	8	7	21.40	0-2	2
	1732.5	20175	3	16-QAM	15	0	21.17	0-2	2
High	1753.5	20385	3	QPSK	1	0	23.37	0	0
	1753.5	20385	3	QPSK	1	7	23.38	0	0
	1753.5	20385	3	QPSK	1	14	23.44	0	0
	1753.5	20385	3	QPSK	8	0	21.87	0-1	1
	1753.5	20385	3	QPSK	8	4	21.86	0-1	1
	1753.5	20385	3	QPSK	8	7	21.89	0-1	1
	1753.5	20385	3	QPSK	15	0	21.88	0-1	1
	1753.5	20385	3	16-QAM	1	0	21.80	0-1	1
	1753.5	20385	3	16-QAM	1	7	21.82	0-1	1
	1753.5	20385	3	16-QAM	1	14	21.83	0-1	1
	1753.5	20385	3	16-QAM	8	0	20.87	0-2	2
	1753.5	20385	3	16-QAM	8	4	20.85	0-2	2
	1753.5	20385	3	16-QAM	8	7	20.87	0-2	2
	1753.5	20385	3	16-QAM	15	0	20.80	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-12
LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1710.7	19957	1.4	QPSK	1	0	23.74	0	0
	1710.7	19957	1.4	QPSK	1	2	23.69	0	0
	1710.7	19957	1.4	QPSK	1	5	23.74	0	0
	1710.7	19957	1.4	QPSK	3	0	23.35	0	0
	1710.7	19957	1.4	QPSK	3	2	23.36	0	0
	1710.7	19957	1.4	QPSK	3	3	23.35	0	0
	1710.7	19957	1.4	QPSK	6	0	22.21	0-1	1
	1710.7	19957	1.4	16-QAM	1	0	22.73	0-1	1
	1710.7	19957	1.4	16-QAM	1	2	22.71	0-1	1
	1710.7	19957	1.4	16-QAM	1	5	22.74	0-1	1
	1710.7	19957	1.4	16-QAM	3	0	22.32	0-1	1
	1710.7	19957	1.4	16-QAM	3	2	22.37	0-1	1
	1710.7	19957	1.4	16-QAM	3	3	22.34	0-1	1
	1710.7	19957	1.4	16-QAM	6	0	21.15	0-2	2
Mid	1732.5	20175	1.4	QPSK	1	0	23.78	0	0
	1732.5	20175	1.4	QPSK	1	2	23.76	0	0
	1732.5	20175	1.4	QPSK	1	5	23.71	0	0
	1732.5	20175	1.4	QPSK	3	0	23.52	0	0
	1732.5	20175	1.4	QPSK	3	2	23.52	0	0
	1732.5	20175	1.4	QPSK	3	3	23.55	0	0
	1732.5	20175	1.4	QPSK	6	0	22.34	0-1	1
	1732.5	20175	1.4	16-QAM	1	0	22.74	0-1	1
	1732.5	20175	1.4	16-QAM	1	2	22.78	0-1	1
	1732.5	20175	1.4	16-QAM	1	5	22.72	0-1	1
	1732.5	20175	1.4	16-QAM	3	0	22.46	0-1	1
	1732.5	20175	1.4	16-QAM	3	2	22.45	0-1	1
	1732.5	20175	1.4	16-QAM	3	3	22.42	0-1	1
	1732.5	20175	1.4	16-QAM	6	0	21.12	0-2	2
High	1754.3	20393	1.4	QPSK	1	0	23.49	0	0
	1754.3	20393	1.4	QPSK	1	2	23.50	0	0
	1754.3	20393	1.4	QPSK	1	5	23.59	0	0
	1754.3	20393	1.4	QPSK	3	0	23.03	0	0
	1754.3	20393	1.4	QPSK	3	2	23.05	0	0
	1754.3	20393	1.4	QPSK	3	3	23.05	0	0
	1754.3	20393	1.4	QPSK	6	0	21.89	0-1	1
	1754.3	20393	1.4	16-QAM	1	0	21.92	0-1	1
	1754.3	20393	1.4	16-QAM	1	2	21.89	0-1	1
	1754.3	20393	1.4	16-QAM	1	5	21.90	0-1	1
	1754.3	20393	1.4	16-QAM	3	0	21.87	0-1	1
	1754.3	20393	1.4	16-QAM	3	2	21.89	0-1	1
	1754.3	20393	1.4	16-QAM	3	3	21.88	0-1	1
	1754.3	20393	1.4	16-QAM	6	0	20.88	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

9.3.4 LTE Band 2 (PCS)

Table 9-13
LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1860	18700	20	QPSK	1	0	23.05	0	0
	1860	18700	20	QPSK	1	50	23.15	0	0
	1860	18700	20	QPSK	1	99	23.17	0	0
	1860	18700	20	QPSK	50	0	22.18	0-1	1
	1860	18700	20	QPSK	50	25	**22.23**	0-1	1
	1860	18700	20	QPSK	50	50	22.22	0-1	1
	1860	18700	20	QPSK	100	0	22.21	0-1	1
	1860	18700	20	16QAM	1	0	22.30	0-1	1
	1860	18700	20	16QAM	1	50	22.35	0-1	1
	1860	18700	20	16QAM	1	99	22.27	0-1	1
	1860	18700	20	16QAM	50	0	21.20	0-2	2
	1860	18700	20	16QAM	50	25	21.21	0-2	2
	1860	18700	20	16QAM	50	50	21.26	0-2	2
	1860	18700	20	16QAM	100	0	21.24	0-2	2
Mid	1880.0	18900	20	QPSK	1	0	23.20	0	0
	1880.0	18900	20	QPSK	1	50	23.21	0	0
	1880.0	18900	20	QPSK	1	99	**23.39**	0	0
	1880.0	18900	20	QPSK	50	0	22.11	0-1	1
	1880.0	18900	20	QPSK	50	25	22.14	0-1	1
	1880.0	18900	20	QPSK	50	50	22.16	0-1	1
	1880.0	18900	20	QPSK	100	0	22.14	0-1	1
	1880.0	18900	20	16QAM	1	0	22.40	0-1	1
	1880.0	18900	20	16QAM	1	50	22.40	0-1	1
	1880.0	18900	20	16QAM	1	99	22.38	0-1	1
	1880.0	18900	20	16QAM	50	0	21.05	0-2	2
	1880.0	18900	20	16QAM	50	25	21.07	0-2	2
	1880.0	18900	20	16QAM	50	50	21.13	0-2	2
	1880.0	18900	20	16QAM	100	0	21.05	0-2	2
High	1900	19100	20	QPSK	1	0	23.02	0	0
	1900	19100	20	QPSK	1	50	23.08	0	0
	1900	19100	20	QPSK	1	99	23.17	0	0
	1900	19100	20	QPSK	50	0	22.08	0-1	1
	1900	19100	20	QPSK	50	25	22.11	0-1	1
	1900	19100	20	QPSK	50	50	22.10	0-1	1
	1900	19100	20	QPSK	100	0	22.11	0-1	1
	1900	19100	20	16QAM	1	0	22.10	0-1	1
	1900	19100	20	16QAM	1	50	22.15	0-1	1
	1900	19100	20	16QAM	1	99	22.22	0-1	1
	1900	19100	20	16QAM	50	0	21.01	0-2	2
	1900	19100	20	16QAM	50	25	21.06	0-2	2
	1900	19100	20	16QAM	50	50	21.05	0-2	2
	1900	19100	20	16QAM	100	0	21.03	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-14
LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1857.5	18675	15	QPSK	1	0	22.85	0	0
	1857.5	18675	15	QPSK	1	36	22.80	0	0
	1857.5	18675	15	QPSK	1	74	23.02	0	0
	1857.5	18675	15	QPSK	36	0	21.54	0-1	1
	1857.5	18675	15	QPSK	36	18	21.43	0-1	1
	1857.5	18675	15	QPSK	36	37	21.48	0-1	1
	1857.5	18675	15	QPSK	75	0	21.41	0-1	1
	1857.5	18675	15	16QAM	1	0	21.92	0-1	1
	1857.5	18675	15	16QAM	1	36	21.89	0-1	1
	1857.5	18675	15	16QAM	1	74	21.86	0-1	1
	1857.5	18675	15	16QAM	36	0	20.72	0-2	2
	1857.5	18675	15	16QAM	36	18	20.47	0-2	2
	1857.5	18675	15	16QAM	36	37	20.53	0-2	2
	1857.5	18675	15	16QAM	75	0	20.49	0-2	2
Mid	1880.0	18900	15	QPSK	1	0	22.91	0	0
	1880.0	18900	15	QPSK	1	36	22.86	0	0
	1880.0	18900	15	QPSK	1	74	22.94	0	0
	1880.0	18900	15	QPSK	36	0	21.47	0-1	1
	1880.0	18900	15	QPSK	36	18	21.41	0-1	1
	1880.0	18900	15	QPSK	36	37	21.45	0-1	1
	1880.0	18900	15	QPSK	75	0	21.46	0-1	1
	1880.0	18900	15	16QAM	1	0	21.91	0-1	1
	1880.0	18900	15	16QAM	1	36	21.97	0-1	1
	1880.0	18900	15	16QAM	1	74	21.86	0-1	1
	1880.0	18900	15	16QAM	36	0	20.78	0-2	2
	1880.0	18900	15	16QAM	36	18	20.44	0-2	2
	1880.0	18900	15	16QAM	36	37	20.45	0-2	2
	1880.0	18900	15	16QAM	75	0	20.42	0-2	2
High	1902.5	19125	15	QPSK	1	0	22.95	0	0
	1902.5	19125	15	QPSK	1	36	22.91	0	0
	1902.5	19125	15	QPSK	1	74	22.85	0	0
	1902.5	19125	15	QPSK	36	0	21.44	0-1	1
	1902.5	19125	15	QPSK	36	18	21.47	0-1	1
	1902.5	19125	15	QPSK	36	37	21.50	0-1	1
	1902.5	19125	15	QPSK	75	0	21.41	0-1	1
	1902.5	19125	15	16QAM	1	0	21.93	0-1	1
	1902.5	19125	15	16QAM	1	36	22.00	0-1	1
	1902.5	19125	15	16QAM	1	74	21.82	0-1	1
	1902.5	19125	15	16QAM	36	0	20.80	0-2	2
	1902.5	19125	15	16QAM	36	18	20.43	0-2	2
	1902.5	19125	15	16QAM	36	37	20.55	0-2	2
	1902.5	19125	15	16QAM	75	0	20.43	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-15
LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1855	18650	10	QPSK	1	0	23.14	0	0
	1855	18650	10	QPSK	1	25	22.96	0	0
	1855	18650	10	QPSK	1	49	23.14	0	0
	1855	18650	10	QPSK	25	0	21.42	0-1	1
	1855	18650	10	QPSK	25	12	21.62	0-1	1
	1855	18650	10	QPSK	25	25	21.44	0-1	1
	1855	18650	10	QPSK	50	0	21.54	0-1	1
	1855	18650	10	16QAM	1	0	21.43	0-1	1
	1855	18650	10	16QAM	1	25	21.59	0-1	1
	1855	18650	10	16QAM	1	49	21.48	0-1	1
	1855	18650	10	16QAM	25	0	20.45	0-2	2
	1855	18650	10	16QAM	25	12	20.44	0-2	2
	1855	18650	10	16QAM	25	25	20.55	0-2	2
	1855	18650	10	16QAM	50	0	20.48	0-2	2
Mid	1880.0	18900	10	QPSK	1	0	23.10	0	0
	1880.0	18900	10	QPSK	1	25	22.96	0	0
	1880.0	18900	10	QPSK	1	49	23.05	0	0
	1880.0	18900	10	QPSK	25	0	21.47	0-1	1
	1880.0	18900	10	QPSK	25	12	21.58	0-1	1
	1880.0	18900	10	QPSK	25	25	21.46	0-1	1
	1880.0	18900	10	QPSK	50	0	21.53	0-1	1
	1880.0	18900	10	16QAM	1	0	21.50	0-1	1
	1880.0	18900	10	16QAM	1	25	21.67	0-1	1
	1880.0	18900	10	16QAM	1	49	21.40	0-1	1
	1880.0	18900	10	16QAM	25	0	20.55	0-2	2
	1880.0	18900	10	16QAM	25	12	20.48	0-2	2
	1880.0	18900	10	16QAM	25	25	20.59	0-2	2
	1880.0	18900	10	16QAM	50	0	20.45	0-2	2
High	1905	19150	10	QPSK	1	0	23.14	0	0
	1905	19150	10	QPSK	1	25	22.98	0	0
	1905	19150	10	QPSK	1	49	22.99	0	0
	1905	19150	10	QPSK	25	0	21.42	0-1	1
	1905	19150	10	QPSK	25	12	21.57	0-1	1
	1905	19150	10	QPSK	25	25	21.40	0-1	1
	1905	19150	10	QPSK	50	0	21.43	0-1	1
	1905	19150	10	16QAM	1	0	21.45	0-1	1
	1905	19150	10	16QAM	1	25	21.77	0-1	1
	1905	19150	10	16QAM	1	49	21.42	0-1	1
	1905	19150	10	16QAM	25	0	20.53	0-2	2
	1905	19150	10	16QAM	25	12	20.54	0-2	2
	1905	19150	10	16QAM	25	25	20.64	0-2	2
	1905	19150	10	16QAM	50	0	20.49	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-16
LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1852.5	18625	5	QPSK	1	0	23.06	0	0
	1852.5	18625	5	QPSK	1	12	22.97	0	0
	1852.5	18625	5	QPSK	1	24	22.98	0	0
	1852.5	18625	5	QPSK	12	0	21.41	0-1	1
	1852.5	18625	5	QPSK	12	6	21.43	0-1	1
	1852.5	18625	5	QPSK	12	13	21.43	0-1	1
	1852.5	18625	5	QPSK	25	0	21.58	0-1	1
	1852.5	18625	5	16-QAM	1	0	21.91	0-1	1
	1852.5	18625	5	16-QAM	1	12	21.64	0-1	1
	1852.5	18625	5	16-QAM	1	24	21.62	0-1	1
	1852.5	18625	5	16-QAM	12	0	20.89	0-2	2
	1852.5	18625	5	16-QAM	12	6	20.53	0-2	2
	1852.5	18625	5	16-QAM	12	13	20.48	0-2	2
	1852.5	18625	5	16-QAM	25	0	20.42	0-2	2
Mid	1880.0	18900	5	QPSK	1	0	23.03	0	0
	1880.0	18900	5	QPSK	1	12	23.04	0	0
	1880.0	18900	5	QPSK	1	24	23.00	0	0
	1880.0	18900	5	QPSK	12	0	21.51	0-1	1
	1880.0	18900	5	QPSK	12	6	21.42	0-1	1
	1880.0	18900	5	QPSK	12	13	21.48	0-1	1
	1880.0	18900	5	QPSK	25	0	21.48	0-1	1
	1880.0	18900	5	16-QAM	1	0	21.87	0-1	1
	1880.0	18900	5	16-QAM	1	12	21.62	0-1	1
	1880.0	18900	5	16-QAM	1	24	21.64	0-1	1
	1880.0	18900	5	16-QAM	12	0	20.91	0-2	2
	1880.0	18900	5	16-QAM	12	6	20.52	0-2	2
	1880.0	18900	5	16-QAM	12	13	20.51	0-2	2
	1880.0	18900	5	16-QAM	25	0	20.43	0-2	2
High	1907.5	19175	5	QPSK	1	0	23.02	0	0
	1907.5	19175	5	QPSK	1	12	23.01	0	0
	1907.5	19175	5	QPSK	1	24	22.91	0	0
	1907.5	19175	5	QPSK	12	0	21.60	0-1	1
	1907.5	19175	5	QPSK	12	6	21.45	0-1	1
	1907.5	19175	5	QPSK	12	13	21.40	0-1	1
	1907.5	19175	5	QPSK	25	0	21.55	0-1	1
	1907.5	19175	5	16-QAM	1	0	21.92	0-1	1
	1907.5	19175	5	16-QAM	1	12	21.62	0-1	1
	1907.5	19175	5	16-QAM	1	24	21.71	0-1	1
	1907.5	19175	5	16-QAM	12	0	20.94	0-2	2
	1907.5	19175	5	16-QAM	12	6	20.46	0-2	2
	1907.5	19175	5	16-QAM	12	13	20.44	0-2	2
	1907.5	19175	5	16-QAM	25	0	20.47	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-17
LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1851.5	18615	3	QPSK	1	0	23.02	0	0
	1851.5	18615	3	QPSK	1	7	22.99	0	0
	1851.5	18615	3	QPSK	1	14	23.16	0	0
	1851.5	18615	3	QPSK	8	0	21.55	0-1	1
	1851.5	18615	3	QPSK	8	4	21.51	0-1	1
	1851.5	18615	3	QPSK	8	7	21.41	0-1	1
	1851.5	18615	3	QPSK	15	0	21.51	0-1	1
	1851.5	18615	3	16-QAM	1	0	21.51	0-1	1
	1851.5	18615	3	16-QAM	1	7	21.44	0-1	1
	1851.5	18615	3	16-QAM	1	14	21.77	0-1	1
	1851.5	18615	3	16-QAM	8	0	20.50	0-2	2
	1851.5	18615	3	16-QAM	8	4	20.76	0-2	2
	1851.5	18615	3	16-QAM	8	7	20.47	0-2	2
	1851.5	18615	3	16-QAM	15	0	20.61	0-2	2
Mid	1880.0	18900	3	QPSK	1	0	23.04	0	0
	1880.0	18900	3	QPSK	1	7	23.00	0	0
	1880.0	18900	3	QPSK	1	14	23.13	0	0
	1880.0	18900	3	QPSK	8	0	21.56	0-1	1
	1880.0	18900	3	QPSK	8	4	21.45	0-1	1
	1880.0	18900	3	QPSK	8	7	21.48	0-1	1
	1880.0	18900	3	QPSK	15	0	21.46	0-1	1
	1880.0	18900	3	16-QAM	1	0	21.45	0-1	1
	1880.0	18900	3	16-QAM	1	7	21.41	0-1	1
	1880.0	18900	3	16-QAM	1	14	21.75	0-1	1
	1880.0	18900	3	16-QAM	8	0	20.55	0-2	2
	1880.0	18900	3	16-QAM	8	4	20.68	0-2	2
	1880.0	18900	3	16-QAM	8	7	20.48	0-2	2
	1880.0	18900	3	16-QAM	15	0	20.62	0-2	2
High	1908.5	19185	3	QPSK	1	0	23.01	0	0
	1908.5	19185	3	QPSK	1	7	23.03	0	0
	1908.5	19185	3	QPSK	1	14	23.14	0	0
	1908.5	19185	3	QPSK	8	0	21.63	0-1	1
	1908.5	19185	3	QPSK	8	4	21.40	0-1	1
	1908.5	19185	3	QPSK	8	7	21.55	0-1	1
	1908.5	19185	3	QPSK	15	0	21.48	0-1	1
	1908.5	19185	3	16-QAM	1	0	21.53	0-1	1
	1908.5	19185	3	16-QAM	1	7	21.48	0-1	1
	1908.5	19185	3	16-QAM	1	14	21.80	0-1	1
	1908.5	19185	3	16-QAM	8	0	20.65	0-2	2
	1908.5	19185	3	16-QAM	8	4	20.68	0-2	2
	1908.5	19185	3	16-QAM	8	7	20.42	0-2	2
	1908.5	19185	3	16-QAM	15	0	20.54	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-18
LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1850.7	18607	1.4	QPSK	1	0	23.05	0	0
	1850.7	18607	1.4	QPSK	1	2	23.13	0	0
	1850.7	18607	1.4	QPSK	1	5	23.02	0	0
	1850.7	18607	1.4	QPSK	3	0	22.71	0	0
	1850.7	18607	1.4	QPSK	3	2	22.65	0	0
	1850.7	18607	1.4	QPSK	3	3	22.51	0	0
	1850.7	18607	1.4	QPSK	6	0	21.60	0-1	1
	1850.7	18607	1.4	16-QAM	1	0	21.76	0-1	1
	1850.7	18607	1.4	16-QAM	1	2	21.79	0-1	1
	1850.7	18607	1.4	16-QAM	1	5	21.91	0-1	1
	1850.7	18607	1.4	16-QAM	3	0	21.95	0-1	1
	1850.7	18607	1.4	16-QAM	3	2	21.70	0-1	1
	1850.7	18607	1.4	16-QAM	3	3	21.81	0-1	1
	1850.7	18607	1.4	16-QAM	6	0	20.54	0-2	2
Mid	1880.0	18900	1.4	QPSK	1	0	23.03	0	0
	1880.0	18900	1.4	QPSK	1	2	23.06	0	0
	1880.0	18900	1.4	QPSK	1	5	23.10	0	0
	1880.0	18900	1.4	QPSK	3	0	22.69	0	0
	1880.0	18900	1.4	QPSK	3	2	22.70	0	0
	1880.0	18900	1.4	QPSK	3	3	22.60	0	0
	1880.0	18900	1.4	QPSK	6	0	21.50	0-1	1
	1880.0	18900	1.4	16-QAM	1	0	21.84	0-1	1
	1880.0	18900	1.4	16-QAM	1	2	21.69	0-1	1
	1880.0	18900	1.4	16-QAM	1	5	21.90	0-1	1
	1880.0	18900	1.4	16-QAM	3	0	21.95	0-1	1
	1880.0	18900	1.4	16-QAM	3	2	21.60	0-1	1
	1880.0	18900	1.4	16-QAM	3	3	21.74	0-1	1
	1880.0	18900	1.4	16-QAM	6	0	20.64	0-2	2
High	1909.3	19193	1.4	QPSK	1	0	23.08	0	0
	1909.3	19193	1.4	QPSK	1	2	23.12	0	0
	1909.3	19193	1.4	QPSK	1	5	23.06	0	0
	1909.3	19193	1.4	QPSK	3	0	22.59	0	0
	1909.3	19193	1.4	QPSK	3	2	22.65	0	0
	1909.3	19193	1.4	QPSK	3	3	22.55	0	0
	1909.3	19193	1.4	QPSK	6	0	21.54	0-1	1
	1909.3	19193	1.4	16-QAM	1	0	21.81	0-1	1
	1909.3	19193	1.4	16-QAM	1	2	21.70	0-1	1
	1909.3	19193	1.4	16-QAM	1	5	21.91	0-1	1
	1909.3	19193	1.4	16-QAM	3	0	21.87	0-1	1
	1909.3	19193	1.4	16-QAM	3	2	21.52	0-1	1
	1909.3	19193	1.4	16-QAM	3	3	21.74	0-1	1
	1909.3	19193	1.4	16-QAM	6	0	20.58	0-2	2

© 2014 PCTEST Engineering Laboratory, Inc.

9.4 WLAN Conducted Powers

Table 9-19
IEEE 802.11b Average RF Power

Mode	Freq [MHz]	Channel	802.11b Conducted Power [dBm]			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1*	16.04	16.22	16.27	16.23
802.11b	2437	6*	**16.28**	16.36	16.39	16.40
802.11b	2462	11*	16.18	16.36	16.41	16.37

Table 9-20
IEEE 802.11g Average RF Power

Mode	Freq [MHz]	Channel	802.11g Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	13.21	13.20	13.27	13.24	13.22	13.21	13.29	13.26
802.11g	2437	6	13.39	13.36	13.48	13.48	13.41	13.43	13.47	13.47
802.11g	2462	11	13.43	13.42	13.49	13.46	13.39	13.40	13.41	13.39

Table 9-21
IEEE 802.11n Average RF Power

Mode	Freq [MHz]	Channel	802.11n (2.4GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	2412	1	8.50	8.51	8.36	8.49	8.42	8.35	8.41	8.44
802.11n	2437	6	8.55	8.56	8.40	8.51	8.47	8.40	8.42	8.43
802.11n	2462	11	9.04	9.09	8.88	9.09	8.98	8.89	8.96	8.94

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-22
IEEE 802.11a Average RF Power

Mode	Freq [MHz]	Channel	802.11a Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11a	5180	36*	10.10	10.18	10.11	10.11	10.08	10.06	10.06	10.12
802.11a	5200	40	10.24	10.24	10.23	10.20	10.26	10.30	10.13	10.28
802.11a	5220	44	**10.30**	10.29	10.22	10.24	10.32	10.10	10.34	10.19
802.11a	5240	48*	10.26	10.37	10.36	10.38	10.31	10.42	10.37	10.39
802.11a	5260	52*	**10.39**	10.32	10.31	10.33	10.31	10.33	10.25	10.29
802.11a	5280	56	10.20	10.20	10.12	10.29	10.16	10.19	10.26	10.18
802.11a	5300	60	10.32	10.40	10.46	10.27	10.31	10.29	10.44	10.31
802.11a	5320	64*	10.31	10.34	10.25	10.29	10.29	10.22	10.37	10.29
802.11a	5500	100	9.96	9.90	9.97	9.98	9.89	9.91	9.96	10.06
802.11a	5520	104*	9.94	9.87	9.91	9.90	9.87	9.98	9.86	9.94
802.11a	5540	108	**9.96**	9.97	9.94	9.93	10.00	9.96	9.92	9.99
802.11a	5560	112	9.77	9.75	9.77	9.77	9.69	9.88	9.72	9.79
802.11a	5580	116*	9.72	9.77	9.67	9.58	9.73	9.73	9.74	9.63
802.11a	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5660	132	9.77	9.82	9.85	9.67	9.75	9.84	9.78	9.83
802.11a	5680	136*	9.65	9.62	9.69	9.62	9.64	9.67	9.66	9.72
802.11a	5700	140	9.45	9.38	9.44	9.43	9.32	9.48	9.40	9.47
802.11a	5745	149*	9.80	9.70	9.72	9.74	9.78	9.81	9.73	9.72
802.11a	5765	153	**9.90**	9.84	9.88	9.91	9.91	9.90	9.93	9.95
802.11a	5785	157*	9.75	9.79	9.74	9.68	9.74	9.66	9.77	9.76
802.11a	5805	161	9.74	9.73	9.77	9.79	9.74	9.81	9.77	9.76
802.11a	5825	165*	9.74	9.90	9.87	9.89	9.83	9.86	9.83	9.90

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power then the default channels, these “required channels” are considered for SAR testing instead of the default channels.

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-23
IEEE 802.11n Average RF Power – 20 MHz Bandwidth

Mode	Freq [MHz]	Channel	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	5180	36	9.37	9.40	9.44	9.47	9.48	9.50	9.59	9.55
802.11n	5200	40	9.39	9.37	9.40	9.41	9.47	9.44	9.54	9.53
802.11n	5220	44	9.38	9.40	9.34	9.37	9.35	9.46	9.49	9.53
802.11n	5240	48	9.38	9.45	9.33	9.40	9.41	9.38	9.44	9.39
802.11n	5260	52	9.28	9.39	9.39	9.39	9.51	9.48	9.40	9.41
802.11n	5280	56	9.28	9.32	9.30	9.28	9.44	9.41	9.38	9.46
802.11n	5300	60	9.30	9.32	9.37	9.41	9.37	9.45	9.43	9.42
802.11n	5320	64	9.25	9.29	9.28	9.34	9.40	9.44	9.37	9.38
802.11n	5500	100	10.05	10.11	10.10	10.00	10.17	10.17	10.14	10.16
802.11n	5520	104	10.06	10.07	10.05	10.07	10.09	10.12	10.08	10.20
802.11n	5540	108	10.06	10.06	10.09	10.10	9.93	10.12	10.06	10.12
802.11n	5560	112	9.90	10.02	9.98	10.02	10.05	10.02	10.06	10.00
802.11n	5580	116	9.92	9.92	9.91	9.94	10.01	9.99	9.89	10.03
802.11n	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5660	132	9.87	9.85	9.78	9.76	9.87	9.92	9.84	9.83
802.11n	5680	136	9.76	9.74	9.71	9.82	9.79	9.86	9.87	9.78
802.11n	5700	140	9.72	9.76	9.74	9.87	9.73	9.80	9.79	9.78
802.11n	5745	149	9.99	10.03	10.03	10.04	10.07	10.08	10.05	10.08
802.11n	5765	153	10.04	10.01	10.08	10.06	10.11	10.06	10.03	10.05
802.11n	5785	157	9.89	10.00	10.03	10.00	9.99	10.03	9.97	10.09
802.11n	5805	161	10.00	9.96	9.96	9.95	10.00	10.06	10.02	9.99
802.11n	5825	165	9.94	9.98	10.03	10.02	9.96	9.99	10.10	9.95

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

© 2014 PCTEST Engineering Laboratory, Inc.

Table 9-24
IEEE 802.11n Average RF Power – 40 MHz Bandwidth

Mode	Freq [MHz]	Channel	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			13.5	27	40.5	54	81	108	121.5	135
802.11n	5190	38	9.50	9.49	9.43	9.42	9.48	9.49	9.52	9.50
802.11n	5230	46	9.46	9.35	9.39	9.47	9.40	9.43	9.42	9.44
802.11n	5270	54	9.42	9.42	9.41	9.46	9.34	9.28	9.39	9.34
802.11n	5310	62	9.35	9.34	9.39	9.34	9.34	9.36	9.33	9.33
802.11n	5510	102	9.00	9.00	8.92	9.07	9.01	9.03	9.09	8.99
802.11n	5550	110	10.15	10.15	10.12	10.14	10.11	10.12	10.14	10.16
802.11n	5590	118	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5630	126	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5670	134	9.85	9.85	9.85	9.86	9.93	9.94	9.92	9.91
802.11n	5755	151	9.93	9.86	9.95	9.90	9.90	9.93	9.87	9.92
802.11n	5795	159	9.89	9.83	9.85	9.88	9.80	9.76	9.77	9.81

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- For 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- For 5 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11a were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.



Figure 9-3
Power Measurement Setup

© 2014 PCTEST Engineering Laboratory, Inc.

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C˚)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ε	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ε	% dev σ	% dev ε
6/3/2014	740H	22.4	710	0.893	43.880	0.890	42.149	0.34%	4.11%
			725	0.907	43.688	0.891	42.071	1.80%	3.84%
			740	0.920	43.431	0.893	41.994	3.02%	3.42%
			755	0.934	43.233	0.894	41.916	4.47%	3.14%
6/4/2014	835H	23.2	820	0.905	41.569	0.899	41.578	0.67%	-0.02%
			835	0.919	41.372	0.900	41.500	2.11%	-0.31%
			850	0.933	41.174	0.916	41.500	1.86%	-0.79%
6/4/2014	1750H	22.6	1710	1.311	39.740	1.348	40.142	-2.74%	-1.00%
			1750	1.348	39.518	1.371	40.079	-1.68%	-1.40%
			1790	1.389	39.352	1.394	40.016	-0.36%	-1.66%
6/5/2014	1900H	22.9	1850	1.353	38.521	1.400	40.000	-3.36%	-3.70%
			1880	1.384	38.397	1.400	40.000	-1.14%	-4.01%
			1910	1.414	38.269	1.400	40.000	1.00%	-4.33%
6/5/2014	2450H	23.1	2401	1.727	39.920	1.756	39.287	-1.65%	1.61%
			2450	1.783	39.777	1.800	39.200	-0.94%	1.47%
			2499	1.834	39.576	1.853	39.138	-1.03%	1.12%
05/14/2014	5200H-5800H	23.9	5200	4.563	36.659	4.655	35.986	-1.98%	1.87%
			5220	4.596	36.629	4.676	35.963	-1.71%	1.85%
			5260	4.638	36.641	4.717	35.917	-1.67%	2.02%
			5300	4.649	36.515	4.758	35.871	-2.29%	1.80%
			5500	4.861	36.288	4.963	35.643	-2.06%	1.81%
			5540	4.888	36.251	5.004	35.597	-2.32%	1.84%
			5765	5.113	35.944	5.234	35.340	-2.31%	1.71%
			5800	5.130	35.894	5.270	35.300	-2.66%	1.68%
6/2/2014	740B	23.0	710	0.940	55.938	0.960	55.687	-2.08%	0.45%
			725	0.954	55.800	0.961	55.629	-0.73%	0.31%
			740	0.968	55.615	0.963	55.570	0.52%	0.08%
			755	0.981	55.465	0.964	55.512	1.76%	-0.08%
6/2/2014	835B	21.9	820	0.992	54.172	0.969	55.258	2.37%	-1.97%
			835	1.006	54.021	0.970	55.200	3.71%	-2.14%
			850	1.020	53.858	0.988	55.154	3.24%	-2.35%
6/11/2014	835B	22.8	820	0.987	54.270	0.969	55.258	1.86%	-1.79%
			835	1.002	54.094	0.970	55.200	3.30%	-2.00%
			850	1.016	53.948	0.988	55.154	2.83%	-2.19%
6/4/2014	1750B	22.8	1710	1.414	53.024	1.463	53.537	-3.35%	-0.96%
			1750	1.457	52.864	1.488	53.432	-2.08%	-1.06%
			1790	1.497	52.719	1.514	53.326	-1.12%	-1.14%
6/4/2014	1900B	23.2	1850	1.457	52.549	1.520	53.300	-4.14%	-1.41%
			1880	1.490	52.454	1.520	53.300	-1.97%	-1.59%
			1910	1.527	52.358	1.520	53.300	0.46%	-1.77%
6/5/2014	2450B	23.8	2401	1.888	51.886	1.903	52.765	-0.79%	-1.67%
			2450	1.960	51.741	1.950	52.700	0.51%	-1.82%
			2499	2.022	51.525	2.019	52.638	0.15%	-2.11%
05/19/2014	5200B-5800B	22.8	5200	5.458	47.166	5.299	49.014	3.00%	-3.77%
			5220	5.501	47.116	5.323	48.987	3.34%	-3.82%
			5260	5.560	47.092	5.369	48.933	3.56%	-3.76%
			5300	5.598	47.018	5.416	48.879	3.36%	-3.81%
			5500	5.877	46.628	5.650	48.607	4.02%	-4.07%
			5540	5.919	46.619	5.696	48.553	3.92%	-3.98%
			5765	6.241	46.229	5.959	48.248	4.73%	-4.18%
			5800	6.275	46.131	6.000	48.200	4.58%	-4.29%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

© 2014 PCTEST Engineering Laboratory, Inc.

10.2 Test System Verification

Prior to SAR assessment, the system is verified to ±10% of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-2
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR_{1g} (W/kg)	1 W Target SAR_{1g} (W/kg)	1 W Normalized SAR_{1g} (W/kg)	$Deviation_{1g}$ (%)
G	750	HEAD	06/03/2014	23.9	22.4	0.100	1003	3258	0.802	8.370	8.020	-4.18%
D	835	HEAD	06/04/2014	24.0	23.4	0.100	4d119	3022	0.964	9.220	9.640	4.56%
G	1750	HEAD	06/04/2014	24.4	22.6	0.100	1051	3258	3.410	36.200	34.100	-5.80%
E	1900	HEAD	06/05/2014	24.3	22.9	0.100	5d149	3914	4.010	40.400	40.100	-0.74%
K	2450	HEAD	06/05/2014	23.9	23.1	0.100	719	3333	5.680	53.200	56.800	6.77%
E	5200	HEAD	05/14/2014	24.5	24.2	0.100	1057	3914	7.270	78.000	72.700	-6.79%
E	5300	HEAD	05/14/2014	24.5	24.3	0.100	1057	3914	7.680	83.000	76.800	-7.47%
E	5500	HEAD	05/14/2014	24.4	24.0	0.100	1057	3914	7.670	84.300	76.700	-9.02%
E	5800	HEAD	05/14/2014	24.5	24.1	0.100	1057	3914	7.640	79.300	76.400	-3.66%
J	750	BODY	06/02/2014	23.3	23.0	0.100	1003	3332	0.903	8.770	9.030	2.96%
D	835	BODY	06/02/2014	23.3	21.9	0.100	4d119	3022	0.965	9.340	9.650	3.32%
K	835	BODY	06/11/2014	24.4	23.0	0.100	4d119	3287	0.993	9.340	9.930	6.32%
K	1750	BODY	06/04/2014	24.0	22.8	0.100	1051	3333	3.840	37.400	38.400	2.67%
G	1900	BODY	06/04/2014	22.7	23.6	0.100	5d149	3258	4.050	40.500	40.500	0.00%
G	2450	BODY	06/05/2014	23.8	23.0	0.100	797	3258	4.990	49.400	49.900	1.01%
A	5200	BODY	05/19/2014	23.2	22.8	0.100	1007	3920	7.180	72.600	71.800	-1.10%
A	5300	BODY	05/19/2014	23.1	22.8	0.100	1007	3920	7.140	74.700	71.400	-4.42%
A	5500	BODY	05/19/2014	23.1	22.8	0.100	1007	3920	7.200	75.900	72.000	-5.14%
A	5800	BODY	05/19/2014	23.1	22.8	0.100	1007	3920	6.700	72.900	67.000	-8.09%



Figure 10-1
System Verification Setup Diagram

Figure 10-2
System Verification Setup Photo

© 2014 PCTEST Engineering Laboratory, Inc.

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM850	GSM	33.0	32.60	0.07	Right	Cheek	FL-208-A	1:8.3	0.375	1.096	0.411	
836.60	190	GSM850	GSM	33.0	32.60	0.04	Right	Tilt	FL-208-A	1:8.3	0.244	1.096	0.267	
836.60	190	GSM850	GSM	33.0	32.60	0.03	Left	Cheek	FL-208-A	1:8.3	0.478	1.096	0.524	A1
836.60	190	GSM850	GSM	33.0	32.60	0.04	Left	Tilt	FL-208-A	1:8.3	0.259	1.096	0.284	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-2
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.0	22.87	0.17	Right	Cheek	FL-208-A	1:1	0.062	1.030	0.064	
836.60	4183	UMTS 850	RMC	23.0	22.87	0.09	Right	Tilt	FL-208-A	1:1	0.045	1.030	0.046	
836.60	4183	UMTS 850	RMC	23.0	22.87	0.08	Left	Cheek	FL-208-A	1:1	0.080	1.030	0.082	A2
836.60	4183	UMTS 850	RMC	23.0	22.87	0.03	Left	Tilt	FL-208-A	1:1	0.053	1.030	0.055	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-3
UMTS 1750 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	23.3	23.29	-0.07	Right	Cheek	FL-208-A	1:1	0.415	1.002	0.416	
1732.40	1412	UMTS 1750	RMC	23.3	23.29	0.02	Right	Tilt	FL-208-A	1:1	0.277	1.002	0.278	
1732.40	1412	UMTS 1750	RMC	23.3	23.29	0.02	Left	Cheek	FL-208-A	1:1	0.716	1.002	0.717	A3
1732.40	1412	UMTS 1750	RMC	23.3	23.29	0.12	Left	Tilt	FL-208-A	1:1	0.191	1.002	0.191	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

© 2014 PCTEST Engineering Laboratory, Inc.

Table 11-4
GSM 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.0	29.84	-0.04	Right	Cheek	FL-208-A	1:8.3	0.184	1.038	0.191	
1880.00	661	GSM 1900	GSM	30.0	29.84	0.01	Right	Tilt	FL-208-A	1:8.3	0.122	1.038	0.127	
1880.00	661	GSM 1900	GSM	30.0	29.84	0.05	Left	Cheek	FL-208-A	1:8.3	0.349	1.038	0.362	A4
1880.00	661	GSM 1900	GSM	30.0	29.84	0.06	Left	Tilt	FL-208-A	1:8.3	0.108	1.038	0.112	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-5
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.00	Right	Cheek	FL-208-A	1:1	0.357	1.047	0.374	
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.06	Right	Tilt	FL-208-A	1:1	0.229	1.047	0.240	
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.13	Left	Cheek	FL-208-A	1:1	0.661	1.047	0.692	A5
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.01	Left	Tilt	FL-208-A	1:1	0.209	1.047	0.219	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-6
LTE Band 17 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	0.03	0	Right	Cheek	QPSK	1	0	FL-208-A	1:1	0.218	1.005	0.219	
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.05	1	Right	Cheek	QPSK	25	0	FL-208-A	1:1	0.167	1.014	0.169	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	-0.09	0	Right	Tilt	QPSK	1	0	FL-208-A	1:1	0.139	1.005	0.140	
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.13	1	Right	Tilt	QPSK	25	0	FL-208-A	1:1	0.104	1.014	0.105	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	0.02	0	Left	Cheek	QPSK	1	0	FL-208-A	1:1	0.303	1.005	0.305	A6
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.01	1	Left	Cheek	QPSK	25	0	FL-208-A	1:1	0.228	1.014	0.231	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	0.01	0	Left	Tilt	QPSK	1	0	FL-208-A	1:1	0.155	1.005	0.156	
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.07	1	Left	Tilt	QPSK	25	0	FL-208-A	1:1	0.116	1.014	0.118	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram												

© 2014 PCTEST Engineering Laboratory, Inc.

Table 11-7
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																				
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.02	0	Right	Cheek	QPSK	1	0	FL-208-B	1:1	0.378	1.016	0.384	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.04	1	Right	Cheek	QPSK	25	0	FL-208-B	1:1	0.270	1.069	0.289	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.03	0	Right	Tilt	QPSK	1	0	FL-208-B	1:1	0.261	1.016	0.265	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	-0.02	1	Right	Tilt	QPSK	25	0	FL-208-B	1:1	0.188	1.069	0.201	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.06	0	Left	Cheek	QPSK	1	0	FL-208-B	1:1	0.463	1.016	0.470	A7
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.05	1	Left	Cheek	QPSK	25	0	FL-208-B	1:1	0.333	1.069	0.356	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.01	0	Left	Tilt	QPSK	1	0	FL-208-B	1:1	0.274	1.016	0.278	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.08	1	Left	Tilt	QPSK	25	0	FL-208-B	1:1	0.195	1.069	0.208	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-8
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																				
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	-0.05	0	Right	Cheek	QPSK	1	99	FL-208-B	1:1	0.423	1.009	0.427	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.12	1	Right	Cheek	QPSK	50	50	FL-208-B	1:1	0.337	1.012	0.341	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	0.04	0	Right	Tilt	QPSK	1	99	FL-208-B	1:1	0.248	1.009	0.250	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.16	1	Right	Tilt	QPSK	50	50	FL-208-B	1:1	0.177	1.012	0.179	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	0.02	0	Left	Cheek	QPSK	1	99	FL-208-B	1:1	0.679	1.009	0.685	A8
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.00	1	Left	Cheek	QPSK	50	50	FL-208-B	1:1	0.544	1.012	0.551	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	0.02	0	Left	Tilt	QPSK	1	99	FL-208-B	1:1	0.191	1.009	0.193	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.03	1	Left	Tilt	QPSK	50	50	FL-208-B	1:1	0.143	1.012	0.145	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-9
LTE Band 2 (PCS) Head SAR

MEASUREMENT RESULTS																				
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	0.00	0	Right	Cheek	QPSK	1	99	FL-208-A	1:1	0.354	1.002	0.355	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	0.07	1	Right	Cheek	QPSK	50	25	FL-208-A	1:1	0.267	1.040	0.278	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	-0.03	0	Right	Tilt	QPSK	1	99	FL-208-A	1:1	0.216	1.002	0.216	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	-0.02	1	Right	Tilt	QPSK	50	25	FL-208-A	1:1	0.163	1.040	0.170	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	0.10	0	Left	Cheek	QPSK	1	99	FL-208-A	1:1	0.721	1.002	0.722	A9
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	-0.12	1	Left	Cheek	QPSK	50	25	FL-208-A	1:1	0.532	1.040	0.553	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	-0.06	0	Left	Tilt	QPSK	1	99	FL-208-A	1:1	0.219	1.002	0.219	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	0.05	1	Left	Tilt	QPSK	50	25	FL-208-A	1:1	0.159	1.040	0.165	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

© 2014 PCTEST Engineering Laboratory, Inc.

Table 11-10
DTS Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2437	6	IEEE 802.11b	DSSS	16.5	16.28	-0.16	Right	Cheek	FL-208-B	1	1:1	0.498	1.052	**0.524**	A10
2437	6	IEEE 802.11b	DSSS	16.5	16.28	0.02	Right	Tilt	FL-208-B	1	1:1	0.112	1.052	0.118	
2437	6	IEEE 802.11b	DSSS	16.5	16.28	0.02	Left	Cheek	FL-208-B	1	1:1	0.171	1.052	0.180	
2437	6	IEEE 802.11b	DSSS	16.5	16.28	-0.15	Left	Tilt	FL-208-B	1	1:1	0.119	1.052	0.125	
5765	153	IEEE 802.11a	OFDM	10.5	9.90	0.18	Right	Cheek	FCC2	6	1:1	0.076	1.148	0.087	A11
5765	153	IEEE 802.11a	OFDM	10.5	9.90	0.13	Right	Tilt	FCC2	6	1:1	0.022	1.148	0.025	
5765	153	IEEE 802.11a	OFDM	10.5	9.90	-0.09	Left	Cheek	FCC2	6	1:1	0.037	1.148	0.042	
5765	153	IEEE 802.11a	OFDM	10.5	9.90	0.11	Left	Tilt	FCC2	6	1:1	0.030	1.148	0.034	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							**Head 1.6 W/kg (mW/g) averaged over 1 gram**								

Table 11-11
NII Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
5220	44	IEEE 802.11a	OFDM	10.5	10.30	0.09	Right	Cheek	FCC2	6	1:1	0.054	1.047	0.057	
5220	44	IEEE 802.11a	OFDM	10.5	10.30	0.10	Right	Tilt	FCC2	6	1:1	0.022	1.047	0.023	
5220	44	IEEE 802.11a	OFDM	10.5	10.30	-0.05	Left	Cheek	FCC2	6	1:1	0.013	1.047	0.014	
5220	44	IEEE 802.11a	OFDM	10.5	10.30	0.13	Left	Tilt	FCC2	6	1:1	0.011	1.047	0.012	
5260	52	IEEE 802.11a	OFDM	10.5	10.39	0.21	Right	Cheek	FCC2	6	1:1	0.052	1.026	0.053	
5260	52	IEEE 802.11a	OFDM	10.5	10.39	-0.18	Right	Tilt	FCC2	6	1:1	0.020	1.026	0.021	
5260	52	IEEE 802.11a	OFDM	10.5	10.39	-0.10	Left	Cheek	FCC2	6	1:1	0.017	1.026	0.017	
5260	52	IEEE 802.11a	OFDM	10.5	10.39	-0.01	Left	Tilt	FCC2	6	1:1	0.013	1.026	0.013	
5540	108	IEEE 802.11a	OFDM	10.5	9.96	0.04	Right	Cheek	FCC2	6	1:1	0.062	1.132	**0.070**	A12
5540	108	IEEE 802.11a	OFDM	10.5	9.96	0.17	Right	Tilt	FCC2	6	1:1	0.020	1.132	0.023	
5540	108	IEEE 802.11a	OFDM	10.5	9.96	-0.14	Left	Cheek	FCC2	6	1:1	0.022	1.132	0.025	
5540	108	IEEE 802.11a	OFDM	10.5	9.96	-0.17	Left	Tilt	FCC2	6	1:1	0.019	1.132	0.022	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							**Head 1.6 W/kg (mW/g) averaged over 1 gram**								

© 2014 PCTEST Engineering Laboratory, Inc.

11.2 Standalone Body-Worn SAR Data

Table 11-12
GSM/UMTS Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.0	32.60	-0.01	10 mm	FL-208-A	1	1:8.3	back	0.479	1.096	0.525	A13
836.60	4183	UMTS 850	RMC	23.0	22.87	0.12	10 mm	FL-208-A	N/A	1:1	back	0.473	1.030	0.487	A15
1712.40	1312	UMTS 1750	RMC	23.3	23.00	0.10	10 mm	FL-208-B	N/A	1:1	back	0.899	1.072	0.964	A16
1732.40	1412	UMTS 1750	RMC	23.3	23.29	0.05	10 mm	FL-208-B	N/A	1:1	back	0.893	1.002	0.895	
1752.50	1862	UMTS 1750	RMC	23.3	22.87	0.09	10 mm	FL-208-B	N/A	1:1	back	0.802	1.104	0.885	
1880.00	661	GSM 1900	GSM	30.0	29.84	0.15	10 mm	FL-208-A	1	1:8.3	back	0.460	1.038	0.477	A18
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.12	10 mm	FL-208-A	N/A	1:1	back	0.709	1.047	0.742	A20
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-13
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	0.03	0	FL-208-C	QPSK	1	0	10 mm	back	1:1	0.332	1.005	0.334	A21
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.02	1	FL-208-C	QPSK	25	0	10 mm	back	1:1	0.233	1.014	0.236	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.07	0	FL-208-B	QPSK	1	0	10 mm	back	1:1	0.569	1.016	0.578	A22
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.02	1	FL-208-B	QPSK	25	0	10 mm	back	1:1	0.419	1.069	0.448	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	0.03	0	FL-208-B	QPSK	1	99	10 mm	back	1:1	0.781	1.009	0.788	A23
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.04	1	FL-208-B	QPSK	50	50	10 mm	back	1:1	0.617	1.012	0.624	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	-0.02	0	FL-208-A	QPSK	1	99	10 mm	back	1:1	0.713	1.002	0.714	A24
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	0.04	1	FL-208-A	QPSK	50	25	10 mm	back	1:1	0.572	1.040	0.595	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-14
DTS Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2437	6	IEEE 802.11b	DSSS	16.5	16.28	0.07	10 mm	FL-208-A	1	back	1:1	0.111	1.052	0.117	A26
5765	153	IEEE 802.11a	OFDM	10.5	9.90	0.03	10 mm	FCC2	6	back	1:1	0.224	1.148	0.257	A27
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-15
NII Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
5220	44	IEEE 802.11a	OFDM	10.5	10.30	0.10	10 mm	FCC2	6	back	1:1	0.102	1.047	0.107	
5260	52	IEEE 802.11a	OFDM	10.5	10.39	0.04	10 mm	FCC2	6	back	1:1	0.107	1.026	0.110	
5540	108	IEEE 802.11a	OFDM	10.5	9.96	0.03	10 mm	FCC2	6	back	1:1	0.117	1.132	0.132	A28
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

© 2014 PCTEST Engineering Laboratory, Inc.

11.3 Standalone Wireless Router SAR Data

Table 11-16
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	30.0	29.69	0.08	10 mm	FL-208-A	3	1:2.76	back	0.738	1.074	0.793	
836.60	190	GSM 850	GPRS	30.0	29.69	0.03	10 mm	FL-208-A	3	1:2.76	front	0.708	1.074	0.760	
836.60	190	GSM 850	GPRS	30.0	29.69	0.01	10 mm	FL-208-A	3	1:2.76	bottom	0.221	1.074	0.237	
836.60	190	GSM 850	GPRS	30.0	29.69	0.07	10 mm	FL-208-A	3	1:2.76	right	0.457	1.074	0.491	
824.20	128	GSM 850	GPRS	30.0	29.68	0.00	10 mm	FL-208-A	3	1:2.76	left	0.846	1.076	0.910	
836.60	190	GSM 850	GPRS	30.0	29.69	0.08	10 mm	FL-208-A	3	1:2.76	left	0.794	1.074	0.853	
848.80	251	GSM 850	GPRS	30.0	29.76	0.10	10 mm	FL-208-A	3	1:2.76	left	0.671	1.057	0.709	
824.20	128	GSM 850	GPRS	30.0	29.68	0.00	10 mm	FL-208-A	3	1:2.76	left	0.935	1.076	1.006	A14
836.60	4183	UMTS 850	RMC	23.0	22.87	0.12	10 mm	FL-208-A	N/A	1:1	back	0.473	1.030	0.487	A15
836.60	4183	UMTS 850	RMC	23.0	22.87	-0.04	10 mm	FL-208-A	N/A	1:1	front	0.436	1.030	0.449	
836.60	4183	UMTS 850	RMC	23.0	22.87	0.01	10 mm	FL-208-A	N/A	1:1	bottom	0.134	1.030	0.138	
836.60	4183	UMTS 850	RMC	23.0	22.87	0.07	10 mm	FL-208-A	N/A	1:1	right	0.227	1.030	0.234	
836.60	4183	UMTS 850	RMC	23.0	22.87	0.03	10 mm	FL-208-A	N/A	1:1	left	0.392	1.030	0.404	
1712.40	1312	UMTS 1750	RMC	23.3	23.00	0.10	10 mm	FL-208-B	N/A	1:1	back	0.899	1.072	0.964	
1732.40	1412	UMTS 1750	RMC	23.3	23.29	0.05	10 mm	FL-208-B	N/A	1:1	back	0.893	1.002	0.895	
1752.50	1862	UMTS 1750	RMC	23.3	22.87	0.09	10 mm	FL-208-B	N/A	1:1	back	0.802	1.104	0.885	
1712.40	1312	UMTS 1750	RMC	23.3	23.00	-0.03	10 mm	FL-208-B	N/A	1:1	front	0.908	1.072	0.973	
1732.40	1412	UMTS 1750	RMC	23.3	23.29	-0.07	10 mm	FL-208-B	N/A	1:1	front	0.884	1.002	0.886	
1752.50	1862	UMTS 1750	RMC	23.3	22.87	-0.04	10 mm	FL-208-B	N/A	1:1	front	0.792	1.104	0.874	
1732.40	1412	UMTS 1750	RMC	23.3	23.29	0.13	10 mm	FL-208-B	N/A	1:1	bottom	0.548	1.002	0.549	
1732.40	1412	UMTS 1750	RMC	23.3	23.29	0.02	10 mm	FL-208-B	N/A	1:1	right	0.082	1.002	0.082	
1732.40	1412	UMTS 1750	RMC	23.3	23.29	0.05	10 mm	FL-208-B	N/A	1:1	left	0.329	1.002	0.330	
1712.40	1312	UMTS 1750	RMC	23.3	23.00	-0.08	10 mm	FL-208-B	N/A	1:1	front	0.932	1.072	0.999	A17
1880.00	661	GSM 1900	GPRS	29.0	28.61	0.01	10 mm	FL-208-A	2	1:4.15	back	0.697	1.094	0.763	A19
1880.00	661	GSM 1900	GPRS	29.0	28.61	0.08	10 mm	FL-208-A	2	1:4.15	front	0.652	1.094	0.713	
1880.00	661	GSM 1900	GPRS	29.0	28.61	-0.09	10 mm	FL-208-A	2	1:4.15	bottom	0.439	1.094	0.480	
1880.00	661	GSM 1900	GPRS	29.0	28.61	-0.03	10 mm	FL-208-A	2	1:4.15	right	0.063	1.094	0.069	
1880.00	661	GSM 1900	GPRS	29.0	28.61	0.08	10 mm	FL-208-A	2	1:4.15	left	0.193	1.094	0.211	
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.12	10 mm	FL-208-A	N/A	1:1	back	0.709	1.047	0.742	A20
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.02	10 mm	FL-208-A	N/A	1:1	front	0.676	1.047	0.708	
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.08	10 mm	FL-208-A	N/A	1:1	bottom	0.575	1.047	0.602	
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.08	10 mm	FL-208-A	N/A	1:1	right	0.101	1.047	0.106	
1880.00	9400	UMTS 1900	RMC	23.0	22.80	0.01	10 mm	FL-208-A	N/A	1:1	left	0.288	1.047	0.302	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Blue entries represent variability data.

© 2014 PCTEST Engineering Laboratory, Inc.

Table 11-17
LTE Band 17 Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	0.03	0	FL-208-C	QPSK	1	0	10 mm	back	1:1	0.332	1.005	0.334	A21
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.02	1	FL-208-C	QPSK	25	0	10 mm	back	1:1	0.233	1.014	0.236	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	0.05	0	FL-208-C	QPSK	1	0	10 mm	front	1:1	0.278	1.005	0.279	
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.03	1	FL-208-C	QPSK	25	0	10 mm	front	1:1	0.195	1.014	0.198	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	-0.02	0	FL-208-C	QPSK	1	0	10 mm	bottom	1:1	0.043	1.005	0.043	
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.00	1	FL-208-C	QPSK	25	0	10 mm	bottom	1:1	0.033	1.014	0.033	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	0.02	0	FL-208-C	QPSK	1	0	10 mm	right	1:1	0.105	1.005	0.106	
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.04	1	FL-208-C	QPSK	25	0	10 mm	right	1:1	0.072	1.014	0.073	
710.00	23790	Mid	LTE Band 17	10	23.0	22.98	-0.04	0	FL-208-C	QPSK	1	0	10 mm	left	1:1	0.237	1.005	0.238	
710.00	23790	Mid	LTE Band 17	10	22.0	21.94	0.05	1	FL-208-C	QPSK	25	0	10 mm	left	1:1	0.167	1.014	0.169	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-18
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.07	0	FL-208-B	QPSK	1	0	10 mm	back	1:1	0.569	1.016	0.578	A22
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.02	1	FL-208-B	QPSK	25	0	10 mm	back	1:1	0.419	1.069	0.448	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.03	0	FL-208-B	QPSK	1	0	10 mm	front	1:1	0.500	1.016	0.508	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.02	1	FL-208-B	QPSK	25	0	10 mm	front	1:1	0.366	1.069	0.391	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.09	0	FL-208-B	QPSK	1	0	10 mm	bottom	1:1	0.113	1.016	0.115	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.01	1	FL-208-B	QPSK	25	0	10 mm	bottom	1:1	0.076	1.069	0.081	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	-0.07	0	FL-208-B	QPSK	1	0	10 mm	right	1:1	0.304	1.016	0.309	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.02	1	FL-208-B	QPSK	25	0	10 mm	right	1:1	0.223	1.069	0.238	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.3	23.23	0.04	0	FL-208-B	QPSK	1	0	10 mm	left	1:1	0.432	1.016	0.439	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.3	22.01	0.04	1	FL-208-B	QPSK	25	0	10 mm	left	1:1	0.324	1.069	0.346	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-19
LTE Band 4 (AWS) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	0.03	0	FL-208-B	QPSK	1	99	10 mm	back	1:1	0.781	1.009	0.788	A23
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.04	1	FL-208-B	QPSK	50	50	10 mm	back	1:1	0.617	1.012	0.624	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	0.05	0	FL-208-B	QPSK	1	99	10 mm	front	1:1	0.668	1.009	0.674	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.03	1	FL-208-B	QPSK	50	50	10 mm	front	1:1	0.536	1.012	0.542	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	0.05	0	FL-208-B	QPSK	1	99	10 mm	bottom	1:1	0.663	1.009	0.669	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.05	1	FL-208-B	QPSK	50	50	10 mm	bottom	1:1	0.517	1.012	0.523	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	-0.02	0	FL-208-B	QPSK	1	99	10 mm	right	1:1	0.080	1.009	0.081	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.02	1	FL-208-B	QPSK	50	50	10 mm	right	1:1	0.059	1.012	0.060	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.8	23.76	0.08	0	FL-208-B	QPSK	1	99	10 mm	left	1:1	0.280	1.009	0.283	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.8	22.75	0.08	1	FL-208-B	QPSK	50	50	10 mm	left	1:1	0.222	1.012	0.225	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

© 2014 PCTEST Engineering Laboratory, Inc.

Table 11-20
LTE Band 2 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	-0.02	0	FL-208-A	QPSK	1	99	10 mm	back	1:1	0.713	1.002	0.714	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	0.04	1	FL-208-A	QPSK	50	25	10 mm	back	1:1	0.572	1.040	0.595	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	-0.01	0	FL-208-A	QPSK	1	99	10 mm	front	1:1	0.733	1.002	0.734	A25
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	0.01	1	FL-208-A	QPSK	50	25	10 mm	front	1:1	0.541	1.040	0.563	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	0.05	0	FL-208-A	QPSK	1	99	10 mm	bottom	1:1	0.545	1.002	0.546	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	-0.02	1	FL-208-A	QPSK	50	25	10 mm	bottom	1:1	0.448	1.040	0.466	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	-0.10	0	FL-208-A	QPSK	1	99	10 mm	right	1:1	0.065	1.002	0.065	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	0.14	1	FL-208-A	QPSK	50	25	10 mm	right	1:1	0.058	1.040	0.060	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.4	23.39	-0.02	0	FL-208-A	QPSK	1	99	10 mm	left	1:1	0.236	1.002	0.236	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.4	22.23	0.02	1	FL-208-A	QPSK	50	25	10 mm	left	1:1	0.191	1.040	0.199	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram													

Table 11-21
WLAN Hotspot SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2437	6	IEEE 802.11b	DSSS	16.5	16.28	0.07	10 mm	FL-208-A	1	back	1:1	0.111	1.052	**0.117**	A26
2437	6	IEEE 802.11b	DSSS	16.5	16.28	0.07	10 mm	FL-208-A	1	front	1:1	0.070	1.052	0.074	
2437	6	IEEE 802.11b	DSSS	16.5	16.28	0.14	10 mm	FL-208-A	1	top	1:1	0.028	1.052	0.029	
2437	6	IEEE 802.11b	DSSS	16.5	16.28	0.15	10 mm	FL-208-A	1	left	1:1	0.092	1.052	0.097	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram									

11.4 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements. A specialized battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

© 2014 PCTEST Engineering Laboratory, Inc.

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D03v01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r01. The general test procedures used for testing can be found in Section 8.4.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

WLAN Notes:

1. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
2. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 5 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11a. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz bandwidths) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
3. When Hotspot is enabled, all 5 GHz bands are disabled. Therefore no 5 GHz WIFI Wireless Router SAR Data was required.
4. WIFI transmission was verified using an uncalibrated spectrum analyzer.
5. Since the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other default channels was not required.

© 2014 PCTEST Engineering Laboratory, Inc.

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g/n and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤1.6 W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(GHz)}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2441	11.50	10	**0.292**

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

© 2014 PCTEST Engineering Laboratory, Inc.

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.411	0.524	**0.935**	Head SAR	Right Cheek	0.064	0.524	**0.588**
	Right Tilt	0.267	0.118	0.385		Right Tilt	0.046	0.118	0.164
	Left Cheek	0.524	0.180	0.704		Left Cheek	0.082	0.180	0.262
	Left Tilt	0.284	0.125	0.409		Left Tilt	0.055	0.125	0.180
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.416	0.524	**0.940**	Head SAR	Right Cheek	0.191	0.524	**0.715**
	Right Tilt	0.278	0.118	0.396		Right Tilt	0.127	0.118	0.245
	Left Cheek	0.717	0.180	0.897		Left Cheek	0.362	0.180	0.542
	Left Tilt	0.191	0.125	0.316		Left Tilt	0.112	0.125	0.237
Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.374	0.524	**0.898**	Head SAR	Right Cheek	0.219	0.524	**0.743**
	Right Tilt	0.240	0.118	0.358		Right Tilt	0.140	0.118	0.258
	Left Cheek	0.692	0.180	0.872		Left Cheek	0.305	0.180	0.485
	Left Tilt	0.219	0.125	0.344		Left Tilt	0.156	0.125	0.281
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.384	0.524	**0.908**	Head SAR	Right Cheek	0.427	0.524	**0.951**
	Right Tilt	0.265	0.118	0.383		Right Tilt	0.250	0.118	0.368
	Left Cheek	0.470	0.180	0.650		Left Cheek	0.685	0.180	0.865
	Left Tilt	0.278	0.125	0.403		Left Tilt	0.193	0.125	0.318

Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.355	0.524	0.879
	Right Tilt	0.216	0.118	0.334
	Left Cheek	0.722	0.180	**0.902**
	Left Tilt	0.219	0.125	0.344

Table 12-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.411	0.087	0.498	Head SAR	Right Cheek	0.064	0.087	**0.151**
	Right Tilt	0.267	0.025	0.292		Right Tilt	0.046	0.025	0.071
	Left Cheek	0.524	0.042	**0.566**		Left Cheek	0.082	0.042	0.124
	Left Tilt	0.284	0.034	0.318		Left Tilt	0.055	0.034	0.089
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.416	0.087	0.503	Head SAR	Right Cheek	0.191	0.087	0.278
	Right Tilt	0.278	0.025	0.303		Right Tilt	0.127	0.025	0.152
	Left Cheek	0.717	0.042	**0.759**		Left Cheek	0.362	0.042	**0.404**
	Left Tilt	0.191	0.034	0.225		Left Tilt	0.112	0.034	0.146

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.374	0.087	0.461
	Right Tilt	0.240	0.025	0.265
	Left Cheek	0.692	0.042	**0.734**
	Left Tilt	0.219	0.034	0.253

© 2014 PCTEST Engineering Laboratory, Inc.

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.525	0.117	0.642
Back Side	UMTS 850	0.487	0.117	0.604
Back Side	UMTS 1750	0.964	0.117	**1.081**
Back Side	GSM 1900	0.477	0.117	0.594
Back Side	UMTS 1900	0.742	0.117	0.859
Back Side	LTE Band 17	0.334	0.117	0.451
Back Side	LTE Band 5 (Cell)	0.578	0.117	0.695
Back Side	LTE Band 4 (AWS)	0.788	0.117	0.905
Back Side	LTE Band 2 (PCS)	0.714	0.117	0.831

Table 12-5
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.525	0.257	0.782
Back Side	UMTS 850	0.487	0.257	0.744
Back Side	UMTS 1750	0.964	0.257	**1.221**
Back Side	GSM 1900	0.477	0.257	0.734
Back Side	UMTS 1900	0.742	0.257	0.999

Table 12-6
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.525	0.292	0.817
Back Side	UMTS 850	0.487	0.292	0.779
Back Side	UMTS 1750	0.964	0.292	**1.256**
Back Side	GSM 1900	0.477	0.292	0.769
Back Side	UMTS 1900	0.742	0.292	1.034
Back Side	LTE Band 17	0.334	0.292	0.626
Back Side	LTE Band 5 (Cell)	0.578	0.292	0.870
Back Side	LTE Band 4 (AWS)	0.788	0.292	1.080
Back Side	LTE Band 2 (PCS)	0.714	0.292	1.006

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

© 2014 PCTEST Engineering Laboratory, Inc.

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR ("-").

Table 12-7
Simultaneous Transmission Scenario (2.4 GHz Hotspot at 1.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.793	0.117	0.910
	Front	0.760	0.074	0.834
	Top	-	0.029	0.029
	Bottom	0.237	-	0.237
	Right	0.491	-	0.491
	Left	1.006	0.097	**1.103**

Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.487	0.117	**0.604**
	Front	0.449	0.074	0.523
	Top	-	0.029	0.029
	Bottom	0.138	-	0.138
	Right	0.234	-	0.234
	Left	0.404	0.097	0.501

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.964	0.117	**1.081**
	Front	0.999	0.074	1.073
	Top	-	0.029	0.029
	Bottom	0.549	-	0.549
	Right	0.082	-	0.082
	Left	0.330	0.097	0.427

Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.763	0.117	**0.880**
	Front	0.713	0.074	0.787
	Top	-	0.029	0.029
	Bottom	0.480	-	0.480
	Right	0.069	-	0.069
	Left	0.211	0.097	0.308

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.742	0.117	**0.859**
	Front	0.708	0.074	0.782
	Top	-	0.029	0.029
	Bottom	0.602	-	0.602
	Right	0.106	-	0.106
	Left	0.302	0.097	0.399

Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.334	0.117	**0.451**
	Front	0.279	0.074	0.353
	Top	-	0.029	0.029
	Bottom	0.043	-	0.043
	Right	0.106	-	0.106
	Left	0.238	0.097	0.335

Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.578	0.117	**0.695**
	Front	0.508	0.074	0.582
	Top	-	0.029	0.029
	Bottom	0.115	-	0.115
	Right	0.309	-	0.309
	Left	0.439	0.097	0.536

Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.788	0.117	**0.905**
	Front	0.674	0.074	0.748
	Top	-	0.029	0.029
	Bottom	0.669	-	0.669
	Right	0.081	-	0.081
	Left	0.283	0.097	0.380

Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.714	0.117	**0.831**
	Front	0.734	0.074	0.808
	Top	-	0.029	0.029
	Bottom	0.546	-	0.546
	Right	0.065	-	0.065
	Left	0.236	0.097	0.333

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

© 2014 PCTEST Engineering Laboratory, Inc.

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
2) A second repeated measurement was preformed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.
4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS														
Band	FREQUENCY		Mode	Service	# of Time Slots	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)		(W/kg)	
835	824.20	128	GSM 850	GPRS	3	left	10 mm	0.846	0.851	1.01	N/A	N/A	N/A	N/A
1750	1712.40	1312	UMTS 1750	RMC	N/A	front	10 mm	0.908	0.932	1.03	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was <1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

© 2014 PCTEST Engineering Laboratory, Inc.

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/15/2014	Annual	4/15/2015	MY45470194
Agilent	8753E	(30kHz-6GHz) Network Analyzer	7/23/2013	Annual	7/23/2014	US37390350
Agilent	8648D	(9kHz-4GHz) Signal Generator	4/15/2014	Annual	4/15/2015	3629U00687
Agilent	E4438C	ESG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY45091346
Agilent	E4438C	ESG Vector Signal Generator	4/25/2014	Annual	4/25/2015	MY42082385
Agilent	N5182A	MXG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY47420800
Agilent	N5182A	MXG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY47420651
Agilent	E5515C	Wireless Communications Test Set	5/9/2013	Biennial	5/9/2015	GB43304447
Agilent	E5515C	Wireless Communications Test Set	3/28/2014	Annual	3/28/2015	GB44400860
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433976
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433977
Anritsu	ML2495A	Power Meter	10/31/2013	Annual	10/31/2014	1039008
Anritsu	ML2469A	Power Meter	3/14/2014	Annual	3/14/2015	1306009
Anritsu	MA2481A	Power Sensor	10/30/2013	Annual	10/30/2014	5605
Anritsu	MA2411B	Pulse Power Sensor	2/3/2014	Annual	2/3/2015	1339018
Anritsu	MA2411B	Pulse Power Sensor	3/25/2014	Annual	3/25/2015	1207470
Anritsu	MT8820C	Radio Communication Analyzer	5/6/2014	Annual	5/6/2015	6201144419
Anritsu	MA24106A	USB Power Sensor	1/3/2014	Annual	1/3/2015	1349509
Anritsu	MA24106A	USB Power Sensor	1/3/2014	Annual	1/3/2015	1349514
Anritsu	MA24106A	USB Power Sensor	1/3/2014	Annual	1/3/2015	1344554
Anritsu	MA24106A	USB Power Sensor	1/3/2014	Annual	1/3/2015	1344557
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M1S5A00-009
Fisher Scientific	S407993	Long Stem Thermometer	11/4/2013	Biennial	11/4/2015	130671801
Fisher Scientific	S407993	Long Stem Thermometer	11/4/2013	Biennial	11/4/2015	130671821
Fisher Scientific	S97611	Thermometer	4/12/2013	Biennial	4/12/2015	130219303
Fisher Scientific	S97611	Thermometer	4/12/2013	Biennial	4/12/2015	130219304
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/30/2013	Annual	10/30/2014	1833460
Gigatronics	8651A	Universal Power Meter	10/30/2013	Annual	10/30/2014	8650319
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264162
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264165
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	NRVD	Dual Channel Power Meter	10/12/2012	Biennial	10/12/2014	101695
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	10/4/2013	Biennial	10/4/2015	103962
Rohde & Schwarz	NRV-Z32	Peak Power Sensor	10/12/2012	Biennial	10/12/2014	836019/013
Rohde & Schwarz	SME06	Signal Generator	10/30/2013	Annual	10/30/2014	832026
Rohde & Schwarz	NRVS	Single Channel Power Meter	10/31/2013	Annual	10/31/2014	835360/0079
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	N/A
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	N/A
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	22313
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
SPEAG	D1750V2	1750 MHz SAR Dipole	4/10/2014	Annual	4/10/2015	1051
SPEAG	D1900V2	1900 MHz SAR Dipole	7/22/2013	Annual	7/22/2014	5d149
SPEAG	D2450V2	2450 MHz SAR Dipole	1/21/2014	Annual	1/21/2015	797
SPEAG	D2450V2	2450 MHz SAR Dipole	8/23/2013	Annual	8/23/2014	719
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/23/2013	Annual	9/23/2014	1007
SPEAG	D5GHzV2	5 GHz SAR Dipole	1/27/2014	Annual	1/27/2015	1057
SPEAG	D750V3	750 MHz Dipole	1/20/2014	Annual	1/20/2015	1003
SPEAG	D835V2	835 MHz SAR Dipole	4/7/2014	Annual	4/7/2015	4d119
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/21/2013	Annual	8/21/2014	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/18/2013	Annual	11/18/2014	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/19/2013	Annual	11/19/2014	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/19/2013	Annual	11/19/2014	1408
SPEAG	DAE4	Dasy Data Acquisition Electronics	12/12/2013	Annual	12/12/2014	649
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/26/2014	Annual	2/26/2015	665
SPEAG	ES3DV2	SAR Probe	8/22/2013	Annual	8/22/2014	3022
SPEAG	EX3DV4	SAR Probe	10/23/2013	Annual	10/23/2014	3914
SPEAG	ES3DV3	SAR Probe	11/22/2013	Annual	11/22/2014	3333
SPEAG	ES3DV3	SAR Probe	11/25/2013	Annual	11/25/2014	3332
SPEAG	EX3DV4	SAR Probe	12/18/2013	Annual	12/18/2014	3920
SPEAG	ES3DV3	SAR Probe	2/25/2014	Annual	2/25/2015	3258
SPEAG	ES3DV3	SAR Probe	11/20/2013	Annual	11/20/2014	3287
Tektronix	RSA6114A	Real Time Spectrum Analyzer	4/16/2014	Annual	4/16/2015	B010177
VWR	23226-658	Long Stem Thermometer	7/11/2012	Biennial	7/11/2014	122389334
VWR	23226-658	Long Stem Thermometer	7/11/2012	Biennial	7/11/2014	122389330
VWR	36934-158	Wall-Mounted Thermometer	8/8/2013	Biennial	8/8/2015	130477877
VWR	36934-158	Wall-Mounted Thermometer	8/8/2013	Biennial	8/8/2015	130477866

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements. All calibrated equipment was used within their calibration period.

© 2014 PCTEST Engineering Laboratory, Inc.

15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	**IEEE 1528 Sec.**	**Tol. (± %)**	**Prob. Dist.**	**Div.**	**c_i 1gm**	**c_i 10 gms**	**1gm u_i (± %)**	**10gms u_i (± %)**	**v_i**
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)			RSS				12.1	11.7	299
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k=2				24.2	23.5	

The above measurement uncertainties are according to IEEE Std. 1528-2003

© 2014 PCTEST Engineering Laboratory, Inc.

Applicable for frequencies up to 6 GHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	**IEEE 1528 Sec.**	**Tol. (± %)**	**Prob. Dist.**	**Div.**	**c_i 1gm**	**c_i 10 gms**	**1gm u_i (± %)**	**10gms u_i (± %)**	**v_i**
Measurement System									
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)			RSS				12.4	12.0	299
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k=2				24.7	24.0	

The above measurement uncertainties are according to IEEE Std. 1528-2003

© 2014 PCTEST Engineering Laboratory, Inc.

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

© 2014 PCTEST Engineering Laboratory, Inc.

17 REFERENCES

[1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.

[2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.

[3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.

[4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.

[5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.

[6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.

[7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.

[8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.

[9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.

[10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.

[11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.

[12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.

[13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.

[14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.

[15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.

[16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

[17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

© 2014 PCTEST Engineering Laboratory, Inc.

[18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

[19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hoschschule Zürich, Dosimetric Evaluation of the Cellular Phone.

[20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.

[21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.

[22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009

[23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07

[24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v01r02

[25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D02-D04

[26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04

[27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02

[28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02

[29] Anexo à Resolução No. 533, de 10 de Septembro de 2009.

[30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

© 2014 PCTEST Engineering Laboratory, Inc.

APPENDIX A: SAR TEST DATA

© 2014 PCTEST Engineering Laboratory, Inc.

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8.3
Medium: 835 Head Medium parameters used (interpolated):
f = 836.6 MHz; σ = 0.92 S/m; ε_r = 41.351; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-04-2014; Ambient Temp: 24.0°C; Tissue Temp: 23.4°C

Probe: ES3DV2 - SN3022; ConvF(6.09, 6.09, 6.09); Calibrated: 8/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/21/2013
Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: GSM 850, Left Head, Cheek, Mid.ch

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.781 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.626 W/kg
SAR(1 g) = 0.478 W/kg



0 dB = 0.498 W/kg = -3.03 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, UMTS; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium: 835 Head Medium parameters used (interpolated):
f = 836.6 MHz; σ = 0.92 S/m; ε_r = 41.351; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-04-2014; Ambient Temp: 24.0°C; Tissue Temp: 23.4°C

Probe: ES3DV2 - SN3022; ConvF(6.09, 6.09, 6.09); Calibrated: 8/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/21/2013
Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 850, Left Head, Cheek, Mid.ch

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.579 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 0.102 W/kg
SAR(1 g) = 0.080 W/kg



0 dB = 0.0839 W/kg = -10.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz;Duty Cycle: 1:1
Medium: 1750 Head Medium parameters used (interpolated):
f = 1732.4 MHz; σ = 1.332 S/m; ε_r = 39.616; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-04-2014; Ambient Temp: 24.4°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5.19, 5.19, 5.19); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: AWS UMTS, Left Head, Cheek, Mid.ch

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.013 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 1.09 W/kg
SAR(1 g) = 0.716 W/kg



0 dB = 0.776 W/kg = -1.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, GSM; Frequency: 1880 MHz;Duty Cycle: 1:8.3
Medium: 1900 Head Medium parameters used:
f = 1880 MHz; σ = 1.384 S/m; ε_r = 38.397; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-05-2014; Ambient Temp: 24.3°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3914; ConvF(7.69, 7.69, 7.69); Calibrated: 10/23/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: GSM 1900, Left Head, Cheek, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 16.651 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.539 W/kg
SAR(1 g) = 0.349 W/kg



0 dB = 0.384 W/kg = -4.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, UMTS; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used:
f = 1880 MHz; σ = 1.384 S/m; ε_r = 38.397; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-05-2014; Ambient Temp: 24.3°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3914; ConvF(7.69, 7.69, 7.69); Calibrated: 10/23/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.657 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 1.03 W/kg
SAR(1 g) = 0.661 W/kg



0 dB = 0.728 W/kg = -1.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, LTE Band 17; Frequency: 710 MHz;Duty Cycle: 1:1
Medium: 740 Head Medium parameters used:
f = 710 MHz; σ = 0.893 S/m; ε_r = 43.88; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-03-2014; Ambient Temp: 23.9°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3258; ConvF(6.53, 6.53, 6.53); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 17, Left Head, Cheek, Mid.ch, QPSK,
10 MHz Bandwidth, 1 RB, 0 RB Offset

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.176 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.379 W/kg
SAR(1 g) = 0.303 W/kg



0 dB = 0.319 W/kg = -4.96 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-B

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: 835 Head Medium parameters used (interpolated):
f = 836.5 MHz; σ = 0.92 S/m; ε_r = 41.352; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-04-2014; Ambient Temp: 24.0°C; Tissue Temp: 23.4°C

Probe: ES3DV2 - SN3022; ConvF(6.09, 6.09, 6.09); Calibrated: 8/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/21/2013
Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 5 (Cell), Left Head, Cheek, Mid.ch, QPSK, 10 MHz Bandwidth, 1 RB, 0 RB Offset

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.897 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 0.590 W/kg
SAR(1 g) = 0.463 W/kg



0 dB = 0.481 W/kg = -3.18 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-B

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: 1750 Head Medium parameters used (interpolated):
f = 1732.5 MHz; σ = 1.332 S/m; ε_r = 39.615; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-04-2014; Ambient Temp: 24.4°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5.19, 5.19, 5.19); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch, QPSK, 20 MHz Bandwidth, 1 RB, 99 RB Offset

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.381 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 1.05 W/kg
SAR(1 g) = 0.679 W/kg



0 dB = 0.741 W/kg = -1.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used:
f = 1880 MHz; σ = 1.384 S/m; ε_r = 38.397; ρ = 1000 kg/m^3
Phantom section: Left Section

Test Date: 06-05-2014; Ambient Temp: 24.3°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3914; ConvF(7.69, 7.69, 7.69); Calibrated: 10/23/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 2 (PCS), Left Head, Cheek, Mid.ch, QPSK, 20 MHz Bandwidth, 1 RB, 99 RB Offset

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.806 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 1.12 W/kg
SAR(1 g) = 0.721 W/kg



0 dB = 0.790 W/kg = -1.02 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-B

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: 2450 Head Medium parameters used (interpolated):
f = 2437 MHz; σ = 1.768 S/m; ε_r = 39.815; ρ = 1000 kg/m^3
Phantom section: Right Section

Test Date: 06-05-2014; Ambient Temp: 23.9°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3333; ConvF(4.42, 4.42, 4.42); Calibrated: 11/22/2013;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 11/19/2013
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11b, Right Head, Cheek, Ch 06, 1 Mbps

Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 18.074 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 1.15 W/kg
SAR(1 g) = 0.498 W/kg



0 dB = 0.644 W/kg = -1.91 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FCC2

Communication System: UID 0, IEEE 802.11a; Frequency: 5765 MHz;Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used:
f = 5765 MHz; σ = 5.113 S/m; ε_r = 35.944; ρ = 1000 kg/m^3
Phantom section: Right Section

Test Date: 05-14-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.1°C

Probe: EX3DV4 - SN3914; ConvF(4.52, 4.52, 4.52); Calibrated: 10/23/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11a, 5.8 GHz, Right Head, Cheek, Ch 153, 6 Mbps

Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Reference Value = 3.514 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 0.416 W/kg
SAR(1 g) = 0.076 W/kg



0 dB = 0.242 W/kg = -6.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FCC2

Communication System: UID 0, IEEE 802.11a; Frequency: 5540 MHz;Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used:
f = 5540 MHz; σ = 4.888 S/m; ε_r = 36.251; ρ = 1000 kg/m^3
Phantom section: Right Section

Test Date: 05-14-2014; Ambient Temp: 24.4°C; Tissue Temp: 24.0°C

Probe: EX3DV4 - SN3914; ConvF(4.55, 4.55, 4.55); Calibrated: 10/23/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11a, 5.5 - 5.7 GHz, Right Head, Cheek, Ch 108, 6 Mbps

Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Reference Value = 3.435 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.346 W/kg
SAR(1 g) = 0.062 W/kg



0 dB = 0.212 W/kg = -6.74 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8.3
Medium: 835 Body Medium parameters used (interpolated):
f = 836.6 MHz; σ = 1.007 S/m; ε_r = 54.004; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-02-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(5.91, 5.91, 5.91); Calibrated: 8/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/21/2013
Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: GSM 850, Body SAR, Back side, Mid.ch

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.595 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.617 W/kg
SAR(1 g) = 0.479 W/kg



0 dB = 0.499 W/kg = -3.02 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 824.2 MHz;Duty Cycle: 1:2.76
Medium: 835 Body Medium parameters used (interpolated):
f = 824.2 MHz; σ = 0.991 S/m; ε_r = 54.221; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-11-2014; Ambient Temp: 24.4°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3287; ConvF(6.04, 6.04, 6.04); Calibrated: 11/20/2013;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 11/19/2013
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7164)

Mode: GPRS 850, Body SAR, Left Edge, Low.ch, 3 Tx Slots

Area Scan (11x12x1): Measurement grid: dx=5mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 31.985 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 1.27 W/kg
SAR(1 g) = 0.935 W/kg



0 dB = 1.00 W/kg = 0.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, UMTS; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium: 835 Body Medium parameters used (interpolated):
f = 836.6 MHz; σ = 1.007 S/m; ε_r = 54.004; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-02-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(5.91, 5.91, 5.91); Calibrated: 8/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/21/2013
Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 850, Body SAR, Back side, Mid.ch

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.051 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.603 W/kg
SAR(1 g) = 0.473 W/kg



0 dB = 0.499 W/kg = -3.02 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-B

Communication System: UID 0, UMTS; Frequency: 1712.4 MHz;Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
f = 1712.4 MHz; σ = 1.417 S/m; ε_r = 53.014; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3333; ConvF(4.95, 4.95, 4.95); Calibrated: 11/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 11/19/2013
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: AWS UMTS, Body SAR, Back Side, Low.ch

Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.964 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 1.48 W/kg
SAR(1 g) = 0.899 W/kg



0 dB = 1.01 W/kg = 0.04 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-B

Communication System: UID 0, UMTS (0); Frequency: 1712.4 MHz;Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
f = 1712.4 MHz; σ = 1.417 S/m; ε_r = 53.014; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3333; ConvF(4.95, 4.95, 4.95); Calibrated: 11/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 11/19/2013
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: AWS UMTS, Body SAR, Front Side, Low.ch

Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 26.189 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.52 W/kg
SAR(1 g) = 0.932 W/kg



0 dB = 1.05 W/kg = 0.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, GSM; Frequency: 1880 MHz;Duty Cycle: 1:8.3
Medium: 1900 Body Medium parameters used:
f = 1880 MHz; σ = 1.49 S/m; ε_r = 52.454; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: GSM 1900, Body SAR, Back side, Mid.ch

Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 17.601 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.782 W/kg
SAR(1 g) = 0.460 W/kg



0 dB = 0.520 W/kg = -2.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz;Duty Cycle: 1:4.15
Medium: 1900 Body Medium parameters used:
f = 1880 MHz; σ = 1.49 S/m; ε_r = 52.454; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 2 Tx Slots

Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.274 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 1.18 W/kg
SAR(1 g) = 0.697 W/kg



0 dB = 0.806 W/kg = -0.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, UMTS; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used:
f = 1880 MHz; σ = 1.49 S/m; ε_r = 52.454; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.680 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 1.17 W/kg
SAR(1 g) = 0.709 W/kg



0 dB = 0.794 W/kg = -1.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-C

Communication System: UID 0, LTE Band 17; Frequency: 710 MHz;Duty Cycle: 1:1
Medium: 695 Body Medium parameters used:
f = 710 MHz; σ = 0.94 S/m; ε_r = 55.938; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-02-2014; Ambient Temp: 23.3°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3332; ConvF(6.21, 6.21, 6.21); Calibrated: 11/25/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 11/18/2013
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 17, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.553 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.419 W/kg
SAR(1 g) = 0.332 W/kg



0 dB = 0.350 W/kg = -4.56 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-B

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: 835 Body Medium parameters used (interpolated):
f = 836.5 MHz; σ = 1.007 S/m; ε_r = 54.005; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-02-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(5.91, 5.91, 5.91); Calibrated: 8/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/21/2013
Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset

Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.510 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.723 W/kg
SAR(1 g) = 0.569 W/kg



0 dB = 0.602 W/kg = -2.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-B

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
f = 1732.5 MHz; σ = 1.438 S/m; ε_r = 52.934; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3333; ConvF(4.95, 4.95, 4.95); Calibrated: 11/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 11/19/2013
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 4 (AWS), Body SAR, Back Side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset

Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.806 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 1.29 W/kg
SAR(1 g) = 0.781 W/kg



0 dB = 0.858 W/kg = -0.67 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used:
f = 1880 MHz; σ = 1.49 S/m; ε_r = 52.454; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 2 (PCS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset

Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.362 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 1.21 W/kg
SAR(1 g) = 0.713 W/kg



0 dB = 0.789 W/kg = -1.03 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used:
f = 1880 MHz; σ = 1.49 S/m; ε_r = 52.454; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: LTE Band 2 (PCS), Body SAR, Front side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset

Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.714 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 1.24 W/kg
SAR(1 g) = 0.733 W/kg



0 dB = 0.798 W/kg = -0.98 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FL-208-A

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used (interpolated):
f = 2437 MHz; σ = 1.941 S/m; ε_r = 51.779; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-05-2014; Ambient Temp: 23.8°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(4.14, 4.14, 4.14); Calibrated: 2/25/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11b, Body SAR, Ch 06, 1 Mbps, Back Side

Area Scan (9x14x1): Measurement grid: dx=12mm, dy=12mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.824 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.237 W/kg
SAR(1 g) = 0.111 W/kg



0 dB = 0.145 W/kg = -8.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FCC2

Communication System: UID 0, IEEE 802.11a; Frequency: 5765 MHz;Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used:
f = 5765 MHz; σ = 6.241 S/m; ε_r = 46.229; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-19-2014; Ambient Temp: 23.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3920; ConvF(4, 4, 4); Calibrated: 12/18/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 12/12/2013
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357
Measurement SW: DASY4, Version 4.7 (80);SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11a, 5.8 GHz, Body SAR, Ch 153, 6 Mbps, Back Side

Area Scan (11x17x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Reference Value = 6.041 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.943 W/kg
SAR(1 g) = 0.224 W/kg



0 dB = 0.547 W/kg = -2.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG800M; Type: Portable Handset; Serial: FCC2

Communication System: UID 0, IEEE 802.11a, Frequency: 5540 MHz;Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used:
f = 5540 MHz; σ = 5.919 S/m; ε_r = 46.619; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-19-2014; Ambient Temp: 23.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3920; ConvF(3.8, 3.8, 3.8); Calibrated: 12/18/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 12/12/2013
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357
Measurement SW: DASY4, Version 4.7 (80);SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11a, 5.5 - 5.7 GHz, Body SAR, Ch 108, 6 Mbps, Back Side

Area Scan (11x17x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Reference Value = 4.512 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.455 W/kg
SAR(1 g) = 0.117 W/kg



APPENDIX B: SYSTEM VERIFICATION

© 2014 PCTEST Engineering Laboratory, Inc.

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz;Duty Cycle: 1:1
Medium: 740 Head Medium parameters used (interpolated):
f = 750 MHz; σ = 0.929 S/m; ε_r = 43.299; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 06-03-2014; Ambient Temp: 23.9°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3258; ConvF(6.53, 6.53, 6.53); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.18 W/kg
SAR(1 g) = 0.802 W/kg
Deviation = -4.18%



0 dB = 0.868 W/kg = -0.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz;Duty Cycle: 1:1
Medium: 835 Head Medium parameters used:
f = 835 MHz; σ = 0.919 S/m; ε_r = 41.372; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 06-04-2014; Ambient Temp: 24.0°C; Tissue Temp: 23.4°C

Probe: ES3DV2 - SN3022; ConvF(6.09, 6.09, 6.09); Calibrated: 8/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/21/2013
Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.41 W/kg
SAR(1 g) = 0.964 W/kg
Deviation = 4.56%



0 dB = 1.04 W/kg = 0.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz;Duty Cycle: 1:1
Medium: 1750 Head Medium parameters used:
f = 1750 MHz; σ = 1.348 S/m; ε_r = 39.518; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 24.4°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5.19, 5.19, 5.19); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 6.28 W/kg
SAR(1 g) = 3.41 W/kg
Deviation = -5.80%



0 dB = 3.77 W/kg = 5.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz;Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used (interpolated):
f = 1900 MHz; σ = 1.404 S/m; ε_r = 38.312; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-05-2014; Ambient Temp: 24.3°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3914; ConvF(7.69, 7.69, 7.69); Calibrated: 10/23/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 7.43 W/kg
SAR(1 g) = 4.01 W/kg
Deviation = -0.74%



0 dB = 4.42 W/kg = 6.45 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz;Duty Cycle: 1:1
Medium: 2450 Head Medium parameters used:
f = 2450 MHz; σ = 1.783 S/m; ε_r = 39.777; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-05-2014; Ambient Temp: 23.9°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3333; ConvF(4.42, 4.42, 4.42); Calibrated: 11/22/2013;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 11/19/2013
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 11.5 W/kg
SAR(1 g) = 5.68 W/kg
Deviation = 6.77%



0 dB = 7.40 W/kg = 8.69 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5200 MHz;Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used:
f = 5200 MHz; σ = 4.563 S/m; ε_r = 36.659; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-14-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.2°C

Probe: EX3DV4 - SN3914; ConvF(4.99, 4.99, 4.99); Calibrated: 10/23/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

5200 MHz System Verification

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 30.0 W/kg
SAR(1 g) = 7.27 W/kg
Deviation: -6.79%



0 dB = 16.8 W/kg = 12.25 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5300 MHz;Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used:
f = 5300 MHz; σ = 4.649 S/m; ε_r = 36.515; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-14-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.3°C

Probe: EX3DV4 - SN3914; ConvF(4.82, 4.82, 4.82); Calibrated: 10/23/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 32.5 W/kg
SAR(1 g) = 7.68 W/kg
Deviation: -7.47%



0 dB = 15.9 W/kg = 12.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5500 MHz;Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used:
f = 5500 MHz; σ = 4.861 S/m; ε_r = 36.288; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-14-2014; Ambient Temp: 24.4°C; Tissue Temp: 24.0°C

Probe: EX3DV4 - SN3914; ConvF(4.55, 4.55, 4.55); Calibrated: 10/23/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

5500 MHz System Verification

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 33.6 W/kg
SAR(1 g) = 7.67 W/kg
Deviation: -9.02%



0 dB = 18.4 W/kg = 12.65 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5800 MHz;Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used:
f = 5800 MHz; σ = 5.13 S/m; ε_r = 35.894; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-14-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.1°C

Probe: EX3DV4 - SN3914; ConvF(4.52, 4.52, 4.52); Calibrated: 10/23/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 11/19/2013
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

5800 MHz System Verification

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 35.3 W/kg
SAR(1 g) = 7.64 W/kg
Deviation: -3.66%



0 dB = 19.0 W/kg = 12.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz;Duty Cycle: 1:1
Medium: 740 Body Medium parameters used (interpolated):
f = 750 MHz; σ = 0.977 S/m; ε_r = 55.515; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 06-02-2014; Ambient Temp: 23.3°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3332; ConvF(6.21, 6.21, 6.21); Calibrated: 11/25/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 11/18/2013
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.32 W/kg
SAR(1 g) = 0.903 W/kg
Deviation = 2.96%



0 dB = 0.973 W/kg = -0.12 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz;Duty Cycle: 1:1
Medium: 835 Body Medium parameters used:
f = 835 MHz; σ = 1.006 S/m; ε_r = 54.021; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 06-02-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(5.91, 5.91, 5.91); Calibrated: 8/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/21/2013
Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.39 W/kg
SAR(1 g) = 0.965 W/kg
Deviation = 3.32%



0 dB = 1.04 W/kg = 0.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz;Duty Cycle: 1:1
Medium: 835 Head Medium parameters used:
f = 835 MHz; σ = 1.002 S/m; ε_r = 54.094; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 06-11-2014; Ambient Temp: 24.4°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3287; ConvF(6.04, 6.04, 6.04); Calibrated: 11/20/2013;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 11/19/2013
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7164)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.45 W/kg
SAR(1 g) = 0.993 W/kg
Deviation = 6.32%



0 dB = 1.16 W/kg = 0.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz;Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used:
f = 1750 MHz; σ = 1.457 S/m; ε_r = 52.864; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3333; ConvF(4.95, 4.95, 4.95); Calibrated: 11/22/2013;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 11/19/2013
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 6.80 W/kg
SAR(1 g) = 3.84 W/kg
Deviation = 2.67%



0 dB = 4.22 W/kg = 6.25 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz;Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used (interpolated):
f = 1900 MHz; σ = 1.515 S/m; ε_r = 52.39; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-04-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 7.18 W/kg
SAR(1 g) = 4.05 W/kg
Deviation = 0.00%



0 dB = 4.58 W/kg = 6.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz;Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used:
f = 2450 MHz; σ = 1.96 S/m; ε_r = 51.741; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-05-2014; Ambient Temp: 23.8°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(4.14, 4.14, 4.14); Calibrated: 2/25/2014;
Sensor-Surface: 4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158
Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Input Power = 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 10.3 W/kg
SAR(1 g) = 4.99 W/kg
Deviation = 1.01%



0 dB = 6.54 W/kg = 8.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1007

Communication System: UID 0, CW; Frequency: 5200 MHz;Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used:
f = 5200 MHz; σ = 5.458 S/m; ε_r = 47.166; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-19-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3920; ConvF(4.23, 4.23, 4.23); Calibrated: 12/18/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 12/12/2013
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357
Measurement SW: DASY4, Version 4.7 (80);SEMCAD X Version 14.6.10 (7164)

5200 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 32.5 W/kg
SAR(1 g) = 7.18 W/kg
Deviation: -1.10%



0 dB = 17.9 W/kg = 12.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1007

Communication System: UID 0, CW; Frequency: 5300 MHz;Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used:
f = 5300 MHz; σ = 5.598 S/m; ε_r = 47.018; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-19-2014; Ambient Temp: 23.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3920; ConvF(4.11, 4.11, 4.11); Calibrated: 12/18/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 12/12/2013
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357
Measurement SW: DASY4, Version 4.7 (80);SEMCAD X Version 14.6.10 (7164)

5300 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 33.0 W/kg
SAR(1 g) = 7.14 W/kg
Deviation: -4.42%



0 dB = 18.6 W/kg = 12.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1007

Communication System: UID 0, CW; Frequency: 5500 MHz;Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used:
f = 5500 MHz; σ = 5.877 S/m; ε_r = 46.628; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-19-2014; Ambient Temp: 23.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3920; ConvF(3.8, 3.8, 3.8); Calibrated: 12/18/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 12/12/2013
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357
Measurement SW: DASY4, Version 4.7 (80);SEMCAD X Version 14.6.10 (7164)

5500 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 35.4 W/kg
SAR(1 g) = 7.20 W/kg
Deviation: -5.14%



0 dB = 18.9 W/kg = 12.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1007

Communication System: UID 0, CW; Frequency: 5800 MHz;Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used:
f = 5800 MHz; σ = 6.275 S/m; ε_r = 46.131; ρ = 1000 kg/m^3
Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 05-19-2014; Ambient Temp: 23.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3920; ConvF(4, 4, 4); Calibrated: 12/18/2013;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 12/12/2013
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357
Measurement SW: DASY4, Version 4.7 (80);SEMCAD X Version 14.6.10 (7164)

5800 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm
Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 34.4 W/kg
SAR(1 g) = 6.70 W/kg
Deviation: -8.09%