HCT CO.,LTD.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
TEL: +82-31-645-6300 FAX: +82-31-645-6401

FCC LTE REPORT

Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Address:
129, Samsung-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Date of Issue:
May 24, 2018

Location:
HCT CO., LTD.,
74, Seoicheon-ro 578beon-gil, Majang-myeon,
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-RF-1805-FC044

FCC ID:	**A3LSMG885S**
APPLICANT:	**SAMSUNG Electronics Co., Ltd.**

Model(s): SM-G885S
EUT Type: Mobile Phone
FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)
FCC Rule Part(s): §90, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band26 (1.4)	814.7 – 823.3	1M10G7D	QPSK	0.020	13.08
		1M09W7D	16QAM	0.017	12.43
		1M09W7D	64QAM	0.014	11.43
LTE – Band26 (3)	815.5 – 822.5	2M72G7D	QPSK	0.021	13.26
		2M70W7D	16QAM	0.018	12.62
		2M71W7D	64QAM	0.014	11.57
LTE – Band26 (5)	816.5 – 821.5	4M52G7D	QPSK	0.021	13.21
		4M50W7D	16QAM	0.018	12.56
		4M54W7D	64QAM	0.014	11.55
LTE – Band26 (10)	819.0	8M97G7D	QPSK	0.021	13.24
		8M98W7D	16QAM	0.018	12.58
		9M00W7D	64QAM	0.014	11.54

The measurements shown in this report were made in accordance` with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report prepared by : Jae Ryang Do
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1805-FC044	May 24, 2018	- First Approval Report

Table of Contents

1. GENERAL INFORMATION 4
2. INTRODUCTION 5
2.1. DESCRIPTION OF EUT 5
2.2. MEASURING INSTRUMENT CALIBRATION 5
2.3. TEST FACILITY 5
3. DESCRIPTION OF TESTS 6
3.1 TEST PROCEDURE 6
3.2 RADIATED POWER 7
3.3 RADIATED SPURIOUS EMISSIONS 8
3.4 OCCUPIED BANDWIDTH. 9
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL 10
3.6 BAND EDGE 11
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE 12
3.8 WORST CASE(RADIATED TEST) 13
3.9 WORST CASE(CONDUCTED TEST) 14
4. LIST OF TEST EQUIPMENT 15
5. MEASUREMENT UNCERTAINTY 16
6. SUMMARY OF TEST RESULTS 17
7. SAMPLE CALCULATION 18
8. TEST DATA 20
8.1 EFFECTIVE RADIATED POWER 20
8.2 RADIATED SPURIOUS EMISSIONS 22
8.3 OCCUPIED BANDWIDTH 26
8.4 CONDUCTED SPURIOUS EMISSIONS 27
8.5 BAND EDGE 27
8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE 28
9. TEST PLOTS 32

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMG885S
Application Type:	Certification
FCC Classification:	Licensed Portable Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§90, §2
EUT Type:	Mobile Phone
Model(s):	SM-G885S
Tx Frequency:	814.7 MHz – 823.3 MHz (LTE – Band 26 (1.4 MHz)) 815.5 MHz – 822.5 MHz (LTE – Band 26 (3 MHz)) 816.5 MHz – 821.5 MHz (LTE – Band 26 (5 MHz)) 819.0 MHz (LTE – Band 26 (10 MHz))
Date(s) of Tests:	May 07, 2018 ~ May 18, 2018

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE.

It also supports IEEE 802.11a/b/g/n/ac (HT20/40/80), Bluetooth, NFC and ANT+.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 - ANSI C63.26-2015 – Section 5.2.6(only GSM)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI C63.26-2015 – Section 5.2 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW ≥ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

   The power is calculated by the following formula;

   $$P_{d(dBm)} = Pg_{(dBm)} - \text{cable loss}_{(dB)} + \text{antenna gain}_{(dB)}$$

   Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.
3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

   These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW ≥ 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points > 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
   The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data

3.4 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW ≥ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW ≥ 3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep ≥ 2 * Span / RBW

3.6 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW :
   .- EA licensee's frequency block by up to and including 37.5 kHz : 300Hz
   .- EA licensee's frequency block greater than 37.5 kHz : 100kHz
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points ≥ 2 x Span/RBW
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

For 90.691(a), RBW=300 Hz for offset less than 37.5 kHz from channel edge and RBW=100 kHz for offsets greater than 37.5 kHz is allowed.

3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:
   The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
2. Primary Supply Voltage:
   .- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
   .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.8 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	QPSK, 16QAM, 64QAM	1	0	X
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Z

3.9 WORST CASE(CONDUCTED TEST)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM	1.4, 3, 5, 10, 15, 20	Low, Mid, High	Full RB	0
Band Edge	* QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		1.4, 3, 5, 10, 15, 20	Low, High	Full RB	0
Channel Edge	* QPSK	1.4, 3, 5, 10, 15, 20	Low, Mid, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	* QPSK	1	Low, Mid, High	1	0

* Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.
Conducted Output Power value can be confirmed on the SAR report.

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/17/2018	Annual	04/17/2019
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/04/2018	Annual	04/04/2019
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/04/2018	Annual	04/04/2019
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	5001	06/12/2017	Annual	06/12/2018
Agilent	E3632A/DC Power Supply	KR75303243	07/18/2017	Annual	07/18/2018
Schwarzbeck	UHAP/ Dipole Antenna	557	03/31/2017	Biennial	03/31/2019
Schwarzbeck	UHAP/ Dipole Antenna	558	03/31/2017	Biennial	03/31/2019
ESPEC	SU-642 / Chamber	93000718	07/21/2017	Annual	07/21/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	09/09/2016	Biennial	09/09/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	10/14/2016	Biennial	10/14/2018
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/25/2017	Biennial	04/25/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	04/25/2017	Biennial	04/25/2019
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY52090906	06/01/2017	Annual	06/01/2018
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/22/2017	Annual	06/22/2018
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/30/2017	Annual	10/30/2018
Agilent	8960 (E5515C)/ Base Station	MY48360800	09/26/2017	Annual	09/26/2018
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	04/19/2017	Biennial	04/19/2019
Schwarzbeck	VULB9160/ Bilog Antenna	3150	09/30/2016	Biennial	09/30/2018
Schwarzbeck	VULB9160/ Bilog Antenna	9360-3368	10/14/2016	Biennial	10/14/2018
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6200863156	02/13/2018	Annual	02/13/2019
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	02/08/2018	Annual	02/08/2019
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/18/2017	Annual	07/18/2018
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer	100931	10/30/2017	Annual	10/30/2018
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	08/16/2017	Annual	08/16/2018
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of k = 2 to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (±dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §90.691	< 50 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5 kHz of Block Edge	PASS
Conducted Output Power	§2.1046	N/A	**See Note1**
Frequency stability / variation of ambient temperature	§2.1055, §90.213	< 2.5 ppm	PASS

Note:

1. See SAR Report

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§90.635	< 100 Watts	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §90.691	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
26697	814.7	-30.11	32.45	-10.54	1.32	V	0.115	20.59

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
2) During the test , the turn table is rotated until the maximum signal is found.
3) Record the field strength meter's level.
4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
2) During the test , the turn table is rotated until the maximum signal is found.
3) Record the field strength meter's level.
4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

64QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
814.7	LTE B26/ 1.4 MHz	QPSK	-36.77	25.01	-10.63	1.30	H	< 7.00	0.020	13.08
		16-QAM	-37.42	24.36	-10.63	1.30	H		0.017	12.43
		64-QAM	-38.42	23.36	-10.63	1.30	H		0.014	11.43
823.3		QPSK	-37.50	24.59	-10.59	1.31	H		0.019	12.69
		16-QAM	-38.05	24.04	-10.59	1.31	H		0.016	12.14
		64-QAM	-39.11	22.98	-10.59	1.31	H		0.013	11.08

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
815.5	LTE B26/ 3 MHz	QPSK	-36.71	25.19	-10.63	1.30	H	< 7.00	0.021	13.26
		16-QAM	-37.35	24.55	-10.63	1.30	H		0.018	12.62
		64-QAM	-38.40	23.50	-10.63	1.30	H		0.014	11.57
822.5		QPSK	-37.36	24.72	-10.60	1.31	H		0.019	12.81
		16-QAM	-37.91	24.17	-10.60	1.31	H		0.017	12.26
		64-QAM	-38.98	23.10	-10.60	1.31	H		0.013	11.19

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
816.5	LTE B26/ 5 MHz	QPSK	-36.74	25.13	-10.62	1.30	H	< 7.00	0.021	13.21
		16-QAM	-37.39	24.48	-10.62	1.30	H		0.018	12.56
		64-QAM	-38.40	23.47	-10.62	1.30	H		0.014	11.55
821.5		QPSK	-37.18	24.88	-10.60	1.31	H		0.020	12.97
		16-QAM	-37.77	24.29	-10.60	1.31	H		0.017	12.38
		64-QAM	-38.81	23.25	-10.60	1.31	H		0.014	11.34

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
819.0	LTE B26/ 10 MHz	QPSK	-36.80	25.15	-10.61	1.30	H	< 7.00	0.021	13.24
		16-QAM	-37.46	24.49	-10.61	1.30	H		0.018	12.58
		64-QAM	-38.50	23.45	-10.61	1.30	H		0.014	11.54

8.2 RADIATED SPURIOUS EMISSIONS

▣ OPERATING FREQUENTY: 814.70 MHz

▣ MEASURED OUTPUT POWER: 13.08 dBm = 0.020 W

▣ MODE: LTE B26

▣ MODULATION SIGNAL: 1.4 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 $\log_{10}$ (W) = 26.08 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	ERP (dBm)	dBc
26697 (814.7)	1,629.40	-53.70	9.07	-66.10	1.87	V	-58.90	71.98
	2,444.10	-56.92	10.89	-65.80	2.31	H	-57.22	70.30
	3,258.80	-57.38	11.84	-65.86	2.71	H	-56.73	69.81
26783 (823.3)	1,646.60	-53.99	9.12	-66.39	1.88	V	-59.15	72.23
	2,469.90	-57.85	10.91	-66.62	2.32	V	-58.03	71.11
	3,293.20	-58.22	11.92	-67.41	2.72	H	-58.21	71.29

▣ OPERATING FREQUENTY: 815.50 MHz

▣ MEASURED OUTPUT POWER: 13.26 dBm = 0.021 W

▣ MODE: LTE B26

▣ MODULATION SIGNAL: 3 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log_{10} (W) = 26.26 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	ERP (dBm)	dBc
26705 (815.5)	1,631.00	-54.00	9.09	-66.43	1.87	H	-59.21	72.47
	2,446.50	-58.47	10.89	-67.28	2.31	H	-58.70	71.96
	3,262.00	-57.42	11.86	-65.96	2.71	V	-56.81	70.07
26775 (822.5)	1,645.00	-54.67	9.14	-67.11	1.88	V	-59.85	73.11
	2,467.50	-56.79	10.91	-65.64	2.32	H	-57.05	70.31
	3,290.00	-57.63	11.92	-66.79	2.72	V	-57.59	70.85

▣ OPERATING FREQUENTY: 816.50 MHz

▣ MEASURED OUTPUT POWER: 13.21 dBm = 0.021 W

▣ MODE: LTE B26

▣ MODULATION SIGNAL: 5 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 $\log_{10}$ (W) = 26.21 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	ERP (dBm)	dBc
26715 (816.5)	1,633.00	-53.61	9.27	-66.17	1.88	H	-58.78	71.99
	2,449.50	-57.39	10.92	-66.65	2.33	H	-58.06	71.27
	3,266.00	-58.15	11.95	-67.38	2.72	H	-58.15	71.36
26765 (821.5)	1,643.00	-54.53	9.31	-67.01	1.91	V	-59.61	72.82
	2,464.50	-58.59	10.98	-67.37	2.38	V	-58.77	71.98
	3,286.00	-57.72	12.11	-67.26	2.77	V	-57.92	71.13

▣ OPERATING FREQUENTY: 819.00 MHz

▣ MEASURED OUTPUT POWER: 13.24 dBm = 0.021 W

▣ MODE: LTE B26

▣ MODULATION SIGNAL: 10 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log_{10} (W) = 26.24 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	ERP (dBm)	dBc
26740 (819.0)	1638.00	-54.00	9.09	-66.43	1.87	V	-59.21	72.45
	2457.00	-58.21	10.90	-67.20	2.31	H	-58.61	71.85
	3276.00	-57.76	11.88	-66.63	2.71	H	-57.46	70.70

8.3 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
Band 26	1.4 MHz	823.3	QPSK	6	0	1.0951
			16-QAM			1.0931
			64-QAM			1.0945
	3 MHz	822.5	QPSK	15		2.7178
			16-QAM			2.7032
			64-QAM			2.7051
	5 MHz	821.5	QPSK	25		4.5238
			16-QAM			4.5001
			64-QAM			4.5357
	10 MHz	819.0	QPSK	50		8.9687
			16-QAM			8.9819
			64-QAM			8.9978

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 33 ~ 44.

8.4 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
26	1.4	814.7	3.6845	27.976	-67.288	-39.312	-13.00
		823.3	3.7164	27.976	-66.889	-38.913	
	3	815.5	3.7189	27.976	-67.312	-39.336	
		822.5	3.7104	27.976	-67.371	-39.395	
	5	816.5	3.6775	27.976	-67.378	-39.402	
		821.5	3.6700	27.976	-67.415	-39.439	
	10	819.0	3.7049	27.976	-67.129	-39.153	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 53 ~ 59.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131

8.5 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 45 ~ 52.

8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

▣ MODE: LTE 26

▣ OPERATING FREQUENCY: 814,700,000 Hz

▣ CHANNEL: 26697(1.4 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	823 299 991	0.0	0.000 000	0.000
100%		-30	823 299 985	-6.1	-0.000 001	-0.007
100%		-20	823 299 984	-6.6	-0.000 001	-0.008
100%		-10	823 299 986	-5.0	-0.000 001	-0.006
100%		0	823 299 985	-6.0	-0.000 001	-0.007
100%		+10	823 299 983	-8.1	-0.000 001	-0.010
100%		+30	823 299 972	-19.3	-0.000 002	-0.023
100%		+40	823 299 986	-4.7	-0.000 001	-0.006
100%		+50	823 299 986	-4.8	-0.000 001	-0.006
Batt. Endpoint	3.55	+20	823 299 985	-6.0	-0.000 001	-0.007



▣ MODE: LTE 26

▣ OPERATING FREQUENCY: 815,500,000 Hz

▣ CHANNEL: 26705(3 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	822 500 011	0.0	0.000 000	0.000
100%		-30	822 500 023	11.6	0.000 001	0.014
100%		-20	822 500 024	12.8	0.000 002	0.016
100%		-10	822 500 025	13.7	0.000 002	0.017
100%		0	822 500 033	21.8	0.000 003	0.027
100%		+10	822 500 025	14.4	0.000 002	0.018
100%		+30	822 500 027	16.1	0.000 002	0.020
100%		+40	822 500 004	-7.2	-0.000 001	-0.009
100%		+50	822 500 021	9.6	0.000 001	0.012
Batt. Endpoint	3.55	+20	822 500 025	14.5	0.000 002	0.018



▣ MODE: LTE 26

▣ OPERATING FREQUENCY: 816.500,000 Hz

▣ CHANNEL: 26715(5MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	821 499 994	0.0	0.000 000	0.000
100%		-30	821 499 988	-6.0	-0.000 001	-0.007
100%		-20	821 499 989	-5.6	-0.000 001	-0.007
100%		-10	821 499 989	-5.3	-0.000 001	-0.006
100%		0	821 499 987	-7.5	-0.000 001	-0.009
100%		+10	821 499 988	-6.5	-0.000 001	-0.008
100%		+30	821 499 989	-5.8	-0.000 001	-0.007
100%		+40	821 499 990	-4.0	0.000 000	-0.005
100%		+50	821 499 989	-5.2	-0.000 001	-0.006
Batt. Endpoint	3.55	+20	821 499 990	-4.4	-0.000 001	-0.005



▣ MODE: LTE 26

▣ OPERATING FREQUENCY: 819,000,000 Hz

▣ CHANNEL: 26740(10 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	818 999 996	0.0	0.000 000	0.000
100%		-30	818 999 990	-6.1	-0.000 001	-0.007
100%		-20	818 999 993	-3.3	0.000 000	-0.004
100%		-10	818 999 994	-2.5	0.000 000	-0.003
100%		0	818 999 993	-3.1	0.000 000	-0.004
100%		+10	818 999 992	-3.7	0.000 000	-0.005
100%		+30	818 999 992	-3.7	0.000 000	-0.005
100%		+40	818 999 993	-2.6	0.000 000	-0.003
100%		+50	818 999 991	-4.8	-0.000 001	-0.006
Batt. Endpoint	3.55	+20	818 999 982	-13.8	-0.000 002	-0.017



9. TEST PLOTS

BAND 26. Occupied Bandwidth Plot (1.4M BW Ch.26783 QPSK RB 6_0)



BAND 26. Occupied Bandwidth Plot (1.4M BW Ch.26783 16QAM RB 6_0)



BAND 26. Occupied Bandwidth Plot (1.4M BW Ch.26783 64QAM RB 6_0)



BAND 26. Occupied Bandwidth Plot (3M BW Ch.26775 QPSK RB 15_0)



BAND 26. Occupied Bandwidth Plot (3M BW Ch.26775 16QAM RB 15_0)



BAND 26. Occupied Bandwidth Plot (3M BW Ch.26775 64QAM RB 15_0)



BAND 26. Occupied Bandwidth Plot (5M BW Ch.26765 QPSK RB 25_0)



BAND 26. Occupied Bandwidth Plot (5M BW Ch.26765 16QAM RB 25_0)



BAND 26. Occupied Bandwidth Plot (5M BW Ch.26765 64QAM RB 25_0)



BAND 26. Occupied Bandwidth Plot (10M BW Ch.26740 QPSK RB 50_0)



BAND 26. Occupied Bandwidth Plot (10M BW Ch.26740 16QAM RB 50_0)



BAND 26. Occupied Bandwidth Plot (10M BW Ch.26740 64QAM RB 50_0)



BAND 26. Lower Channel Edge Plot (1.4M BW Ch.26697 QPSK_RB6_Offset 0)

Start Freq	Stop Freq	Integ BW	dBm	Lower ΔLim(dB)	Freq (Hz)	<- Peak -> dBm	Upper ΔLim(dB)	Freq (Hz)
700.0 kHz	737.6 kHz	300.0 Hz	-42.72	(-22.72)	-712.0 k	-41.25	(-21.25)	704.2 k
737.5 kHz	1.400 MHz	100.0 kHz	-21.72	(-8.72)	-737.5 k	-21.27	(-8.27)	744.1 k
3.515 MHz	4.000 MHz	30.00 kHz	---	(---)	---	---	(---)	---
4.000 MHz	8.000 MHz	1.000 MHz	---	(---)	---	---	(---)	---
8.000 MHz	12.50 MHz	1.000 MHz	---	(---)	---	---	(---)	---

BAND 26. Lower Channel Edge Plot (3M BW Ch. 26705 QPSK_RB15_Offset 0)



BAND 26. Lower Channel Edge Plot (5M BW Ch. 26715 QPSK_RB25_Offset 0)

BAND 26. Mid Channel Edge Plot (10M BW Ch. 26740 QPSK_RB50_Offset 0)



Start Freq	Stop Freq	Integ BW	dBm	Lower ΔLim(dB)	Freq (Hz)	<- Peak -> dBm	Upper ΔLim(dB)	Freq (Hz)
5.000 MHz	5.038 MHz	300.0 Hz	-49.60	(-29.60)	-5.001 M	-50.91	(-30.91)	5.016 M
5.038 MHz	10.00 MHz	100.0 kHz	-29.31	(-16.31)	-5.559 M	-29.73	(-16.73)	5.633 M
3.515 MHz	4.000 MHz	30.00 kHz	---	(---)	---	---	(---)	---
4.000 MHz	8.000 MHz	1.000 MHz	---	(---)	---	---	(---)	---
8.000 MHz	12.50 MHz	1.000 MHz	---	(---)	---	---	(---)	---

BAND 26. Upper Channel Edge Plot (1.4M BW Ch.26783 QPSK_RB6_Offset 0)

Start Freq	Stop Freq	Integ BW	dBm	Lower ΔLim(dB)	Freq (Hz)	<- Peak -> dBm	Upper ΔLim(dB)	Freq (Hz)
700.0 kHz	737.6 kHz	300.0 Hz	-42.59	(-22.59)	-736.3 k	-41.81	(-21.81)	716.9 k
737.5 kHz	1.400 MHz	100.0 kHz	-22.19	(-9.19)	-740.8 k	-21.37	(-8.37)	737.5 k
3.515 MHz	4.000 MHz	30.00 kHz	---	(---)	---	---	(---)	---
4.000 MHz	8.000 MHz	1.000 MHz	---	(---)	---	---	(---)	---
8.000 MHz	12.50 MHz	1.000 MHz	---	(---)	---	---	(---)	---

BAND 26. Upper Channel Edge Plot (3M BW Ch. 26775 QPSK_RB15_Offset 0)



BAND 26. Upper Channel Edge Plot (5M BW Ch. 26765 QPSK_RB25_Offset 0)



BAND 26. Upper Channel Edge Plot (10M BW Ch. 26740 QPSK_RB50_Offset 0)



BAND 26. Conducted Spurious (26697 ch_1.4MHz_QPSK_RB 1_0)



BAND 26. Conducted Spurious (26783 ch_1.4MHz_QPSK_RB 1_0)



BAND 26. Conducted Spurious (26705 ch_3MHz_QPSK_RB 1_0)



BAND 26. Conducted Spurious (26775 ch_3MHz_QPSK_RB 1_0)



BAND 26. Conducted Spurious (26715 ch_5MHz_QPSK_RB 1_0)



BAND 26. Conducted Spurious (26765 ch_5MHz_QPSK_RB 1_0)



BAND 26. Conducted Spurious (26740 ch_10MHz_QPSK_RB 1_0)