7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h) §27.53(m) §27.53(a.4)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level for Band 30 is > 43 + 10log10 (P[Watts] at 2300-2305MHz & 2345-2360MHz, > 55 + 10log10 (P[Watts]) at 2320-2324MHz & 2341-2345MHz, > 61 + 10log10 (P[Watts]) at 2324-2328MHz & 2337-2341MHz, > 67 + 10log10 (P[Watts]) at 2288-2292MHz & 2328-2337MHz, and > 70 + 10log10 (P[Watts]) at frequencies < 2288MHz & >2365MHz.

The minimum permissible attenuation level for Band 41 is as noted in the Test Notes on the following page.

The minimum permissible attenuation level of any spurious emission is 43 + $\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW ≥ 1% of the emission bandwidth
4. VBW ≥ 3 x RBW
5. Detector = RMS
6. Number of sweep points ≥ 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

© 2016 PCTEST Engineering Laboratory, Inc.

Test Notes

Per 22.917(b), 24.238(a) and 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

Per 27.53(a)(5) in the 1 MHz bands immediately outside and adjacent to the channel blocks at 2305, 2310, 2315, 2320, 2345, 2350, 2355, and 2360 MHz, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e., 1 MHz). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Per 27.53(m) for operations in the BRS/EBS bands, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz.

Plot 7-107. Lower Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-108. Lower Extended Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)

Plot 7-109. Upper Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-110. Upper Extended Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)



Plot 7-111. Lower Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-112. Lower Extended Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)



Plot 7-113. Upper Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-114. Upper Extended Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)



Plot 7-115. Lower Band Edge Plot (Band 12 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-116. Lower Extended Band Edge Plot (Band 12 – 5.0MHz QPSK – RB Size 25)

Plot 7-117. Upper Band Edge Plot (Band 12 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-118. Upper Extended Band Edge Plot (Band 12 – 5.0MHz QPSK – RB Size 25)



Plot 7-119. Lower Band Edge Plot (Band 12 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-120. Upper Band Edge Plot (Band 12 – 10.0MHz QPSK – RB Size 50)



Plot 7-121. Lower Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-122. Lower Extended Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)



Plot 7-123. Upper Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-124. Upper Extended Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)



Plot 7-125. Lower Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-126. Lower Extended Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)



Plot 7-127. Upper Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-128. Upper Extended Band Edge Plot (Band 5 – Band 5 – 3.0MHz QPSK – RB Size 15)



Plot 7-129. Lower Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-130. Lower Extended Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)



Plot 7-131. Upper Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-132. Upper Extended Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)



Plot 7-133. Lower Band Edge Plot (Band 5 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-134. Upper Band Edge Plot (Band 5 – 10.0MHz QPSK – RB Size 50)

Plot 7-135. Lower Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-136. Lower Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)



Plot 7-137. Upper Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-138. Upper Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)



Plot 7-139. Lower Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-140. Lower Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)



Plot 7-141. Upper Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-142. Upper Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)



Plot 7-143. Lower Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-144. Lower Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

Plot 7-145. Upper Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-146. Upper Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)



Plot 7-147. Lower Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-148. Lower Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

Plot 7-149. Upper Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-150. Upper Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)



Plot 7-151. Lower Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-152. Lower Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)



Plot 7-153. Upper Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-154. Upper Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)



Plot 7-155. Lower Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-156. Lower Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)



Plot 7-157. Upper Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-158. Upper Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

Plot 7-159. Lower Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-160. Lower Extended Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)

Plot 7-161. Upper Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-162. Upper Extended Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)



Plot 7-163. Lower Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-164. Lower Extended Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)

Plot 7-165. Upper Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-166. Upper Extended Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)



Plot 7-167. Lower Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-168. Lower Extended Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)



Plot 7-169. Upper Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-170. Upper Extended Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)

Plot 7-171. Lower Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-172. Lower Extended Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)

Plot 7-173. Upper Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-174. Upper Extended Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)



Plot 7-175. Lower Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-176. Lower Extended Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)



Plot 7-177. Upper Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-178. Upper Extended Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)



Plot 7-179. Lower Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-180. Lower Extended Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)

Plot 7-181. Upper Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-182. Upper Extended Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)



Plot 7-183. Lower Band Edge Plot (Band 30 – 5.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-184. Lower Extended Band Edge Plot (Band 30 – 5.0MHz QPSK – RB Size 50)



Plot 7-185. Upper Band Edge Plot (Band 30 – 5.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-186. Upper Extended Band Edge Plot (Band 30 – 5.0MHz QPSK – RB Size 50)



Plot 7-187. Lower Band Edge Plot (Band 30 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.

Plot 7-188. Lower Extended Band Edge Plot (Band 30 – 10.0MHz QPSK – RB Size 50)



Plot 7-189. Upper Band Edge Plot (Band 30 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-190. Upper Extended Band Edge Plot (Band 30 – 10.0MHz QPSK – RB Size 50)



Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude		Δ Limit
1	1	2.4750 GHz	2.4905 GHz	1.000 MHz	2.490241667 GHz	-38.51 dBm		-13.51 dB
2	2	2.4905 GHz	2.4950 GHz	1.000 MHz	2.494670000 GHz	-32.29 dBm		-19.29 dB
3	3	2.4950 GHz	2.4960 GHz	51.00 kHz	2.495980000 GHz	-27.75 dBm		-14.75 dB
4	4	2.4960 GHz	2.5170 GHz	200.0 kHz	2.497715000 GHz	12.17 dBm		-12.83 dB

Plot 7-191. Lower ACP Plot (Band 41 – 5.0MHz QPSK – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.



Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude		Δ Limit
1	1	2.6650 GHz	2.6900 GHz	1.000 MHz	2.689125000 GHz	15.20 dBm		-9.797 dB
2	2	2.6900 GHz	2.6910 GHz	100.0 kHz	2.690030000 GHz	-22.43 dBm		-12.43 dB
3	3	2.6910 GHz	2.6950 GHz	1.000 MHz	2.691233333 GHz	-24.26 dBm		-14.26 dB
4	4	2.6950 GHz	2.6960 GHz	1.000 MHz	2.695505000 GHz	-37.21 dBm		-24.21 dB
5	5	2.6960 GHz	2.7150 GHz	1.000 MHz	2.696063333 GHz	-38.97 dBm		-13.97 dB

Plot 7-192. Upper ACP Plot (Band 41 – 5.0MHz QPSK – RB Size 25)



Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude		Δ Limit
1	1	2.4750 GHz	2.4905 GHz	1.000 MHz	2.490086667 GHz	-34.14 dBm		-9.135 dB
2	2	2.4905 GHz	2.4950 GHz	1.000 MHz	2.494647500 GHz	-31.28 dBm		-18.28 dB
3	3	2.4950 GHz	2.4960 GHz	100.0 kHz	2.495981667 GHz	-32.55 dBm		-19.55 dB
4	4	2.4960 GHz	2.5170 GHz	200.0 kHz	2.502510000 GHz	8.140 dBm		-16.86 dB

Plot 7-193. Lower ACP Plot (Band 41 – 10.0MHz QPSK – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.



Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude		Δ Limit
1	1	2.6650 GHz	2.6900 GHz	1.000 MHz	2.682958333 GHz	12.51 dBm		-12.49 dB
2	2	2.6900 GHz	2.6910 GHz	200.0 kHz	2.690093333 GHz	-27.02 dBm		-17.02 dB
3	3	2.6910 GHz	2.6950 GHz	1.000 MHz	2.691106667 GHz	-24.59 dBm		-14.59 dB
4	4	2.6950 GHz	2.6997 GHz	1.000 MHz	2.695078483 GHz	-29.34 dBm		-16.34 dB
5	5	2.6997 GHz	2.7150 GHz	1.000 MHz	2.700346125 GHz	-42.16 dBm		-17.16 dB

Plot 7-194. Upper ACP Plot (Band 41 – 10.0MHz QPSK – RB Size 50)



Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude		Δ Limit
1	1	2.4750 GHz	2.4905 GHz	1.000 MHz	2.490396667 GHz	-35.57 dBm		-10.57 dB
2	2	2.4905 GHz	2.4950 GHz	1.000 MHz	2.494790000 GHz	-29.08 dBm		-16.08 dB
3	3	2.4950 GHz	2.4960 GHz	150.0 kHz	2.495903333 GHz	-32.36 dBm		-19.36 dB
4	4	2.4960 GHz	2.5170 GHz	200.0 kHz	2.507060000 GHz	6.105 dBm		-18.90 dB

Plot 7-195. Lower ACP Plot (Band 41 – 15.0MHz QPSK – RB Size 75)

© 2016 PCTEST Engineering Laboratory, Inc.



Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude		Δ Limit
1	1	2.6650 GHz	2.6900 GHz	1.000 MHz	2.683041667 GHz	10.52 dBm		-14.48 dB
2	2	2.6900 GHz	2.6910 GHz	300.0 kHz	2.690006667 GHz	-25.72 dBm		-15.72 dB
3	3	2.6910 GHz	2.6950 GHz	1.000 MHz	2.691553333 GHz	-23.92 dBm		-13.92 dB
4	4	2.6950 GHz	2.7049 GHz	1.000 MHz	2.695164500 GHz	-26.87 dBm		-13.87 dB
5	5	2.7049 GHz	2.7150 GHz	1.000 MHz	2.706085600 GHz	-41.95 dBm		-16.95 dB

Plot 7-196. Upper ACP Plot (Band 41 – 15.0MHz QPSK – RB Size 75)



Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude		Δ Limit
1	1	2.4750 GHz	2.4905 GHz	1.000 MHz	2.488846667 GHz	-32.70 dBm		-7.704 dB
2	2	2.4905 GHz	2.4950 GHz	1.000 MHz	2.494422500 GHz	-27.87 dBm		-14.87 dB
3	3	2.4950 GHz	2.4960 GHz	200.0 kHz	2.495911667 GHz	-30.47 dBm		-17.47 dB
4	4	2.4960 GHz	2.5170 GHz	200.0 kHz	2.507690000 GHz	5.260 dBm		-19.74 dB

Plot 7-197. Lower ACP Plot (Band 41 – 20.0MHz QPSK – RB Size 100)

© 2016 PCTEST Engineering Laboratory, Inc.



Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude		Δ Limit
1	1	2.6650 GHz	2.6900 GHz	1.000 MHz	2.675875000 GHz	10.06 dBm		-14.94 dB
2	2	2.6900 GHz	2.6910 GHz	390.0 kHz	2.690456667 GHz	-28.61 dBm		-18.61 dB
3	3	2.6910 GHz	2.6950 GHz	1.000 MHz	2.691106667 GHz	-25.76 dBm		-15.76 dB
4	4	2.6950 GHz	2.7097 GHz	1.000 MHz	2.696469900 GHz	-29.65 dBm		-16.65 dB
5	5	2.7097 GHz	2.7150 GHz	1.000 MHz	2.709849195 GHz	-46.83 dBm		-21.83 dB

Plot 7-198. Upper ACP Plot (Band 41 – 20.0MHz QPSK – RB Size 100)

© 2016 PCTEST Engineering Laboratory, Inc.

7.5 Peak-Average Ratio

§24.232(d)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes

None.

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-199. PAR Plot (Band 2 – 1.4MHz QPSK – RB Size 6)



Plot 7-200. PAR Plot (Band 2 – 1.4MHz 16-QAM – RB Size 6)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-201. PAR Plot (Band 2 – 3.0MHz QPSK – RB Size 15)



Plot 7-202. PAR Plot (Band 2 – 3.0MHz 16-QAM – RB Size 15)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-203. PAR Plot (Band 2 – 5.0MHz QPSK – RB Size 25)



Plot 7-204. PAR Plot (Band 2 – 5.0MHz 16-QAM – RB Size 25)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-205. PAR Plot (Band 2 – 10.0MHz QPSK – RB Size 50)



Plot 7-206. PAR Plot (Band 2 – 10.0MHz 16-QAM – RB Size 50)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-207. PAR Plot (Band 2 – 15.0MHz QPSK – RB Size 75)



Plot 7-208. PAR Plot (Band 2 – 15.0MHz 16-QAM – RB Size 75)

© 2016 PCTEST Engineering Laboratory, Inc.



Plot 7-209. PAR Plot (Band 2 – 20.0MHz QPSK – RB Size 100)



Plot 7-210. PAR Plot (Band 2 – 20.0MHz 16-QAM – RB Size 100)

© 2016 PCTEST Engineering Laboratory, Inc.

7.6 Radiated Power (ERP/EIRP)

§22.913(a.2) §24.232(c.2) §27.50(h.2) §27.50(c.10) §27.50(d.4) §27.50(a.3)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using horizontally and vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW ≥ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points ≥ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto". Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

© 2016 PCTEST Engineering Laboratory, Inc.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. Radiated Test Setup <1GHz



Figure 7-6. Radiated Test Setup >1GHz

Test Notes

1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.

2) This unit was tested with its standard battery.

© 2016 PCTEST Engineering Laboratory, Inc.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
699.70	1.4	QPSK	H	2.58	340	3 / 2	18.23	2.11	20.34	34.77	-14.43
707.50	1.4	QPSK	H	2.60	0	3 / 2	19.47	2.31	21.78	34.77	-12.99
707.50	1.4	QPSK	V	1.12	11	3 / 2	16.05	2.88	18.93	34.77	-15.84
715.30	1.4	QPSK	H	2.66	337	3 / 2	18.34	2.52	20.86	34.77	-13.91
699.70	1.4	16-QAM	H	2.58	340	1 / 0	17.11	2.11	19.22	34.77	-15.55
707.50	1.4	16-QAM	H	2.60	0	3 / 2	18.57	2.31	20.88	34.77	-13.89
715.30	1.4	16-QAM	H	2.66	337	3 / 2	17.44	2.52	19.96	34.77	-14.81
700.50	3	QPSK	H	2.87	337	1 / 0	17.82	2.12	19.94	34.77	-14.83
707.50	3	QPSK	H	2.67	333	1 / 14	19.27	2.31	21.58	34.77	-13.19
714.50	3	QPSK	H	2.70	338	1 / 0	18.34	2.50	20.84	34.77	-13.93
700.50	3	16-QAM	H	2.87	337	1 / 0	17.07	2.12	19.19	34.77	-15.58
707.50	3	16-QAM	H	2.67	333	1 / 0	18.07	2.31	20.38	34.77	-14.39
714.50	3	16-QAM	H	2.70	338	1 / 0	17.50	2.50	20.00	34.77	-14.77
701.50	5	QPSK	H	2.56	349	1 / 0	18.16	2.15	20.31	34.77	-14.46
707.50	5	QPSK	H	2.67	326	1 / 24	19.18	2.31	21.49	34.77	-13.28
713.50	5	QPSK	H	2.68	337	1 / 0	18.81	2.48	21.29	34.77	-13.49
701.50	5	16-QAM	H	2.56	349	1 / 0	17.43	2.15	19.58	34.77	-15.19
707.50	5	16-QAM	H	2.67	326	1 / 0	18.28	2.31	20.59	34.77	-14.18
713.50	5	16-QAM	H	2.68	337	1 / 0	18.42	2.48	20.90	34.77	-13.88
704.00	10	QPSK	H	2.61	329	1 / 49	19.35	2.22	21.57	34.77	-13.21
707.50	10	QPSK	H	2.67	327	1 / 49	18.30	2.31	20.61	34.77	-14.16
711.00	10	QPSK	H	2.62	329	1 / 49	19.32	2.41	21.73	34.77	-13.04
704.00	10	16-QAM	H	2.61	329	1 / 49	18.51	2.22	20.73	34.77	-14.05
707.50	10	16-QAM	H	2.67	327	1 / 49	17.55	2.31	19.86	34.77	-14.91
711.00	10	16-QAM	H	2.62	329	1 / 49	18.60	2.41	21.01	34.77	-13.76

Table 7-2. ERP Data (Band 12)

© 2016 PCTEST Engineering Laboratory, Inc.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
824.70	1.4	QPSK	H	2.27	329	3 / 2	20.81	5.01	25.82	38.45	-12.63
836.50	1.4	QPSK	H	2.08	317	1 / 0	19.94	5.16	25.10	38.45	-13.35
848.30	1.4	QPSK	H	2.27	304	1 / 0	19.39	5.30	24.69	38.45	-13.76
824.70	1.4	16-QAM	H	2.27	329	3 / 2	19.99	5.01	25.00	38.45	-13.45
836.50	1.4	16-QAM	H	2.08	317	1 / 0	19.03	5.16	24.19	38.45	-14.26
848.30	1.4	16-QAM	H	2.27	304	1 / 0	18.61	5.30	23.91	38.45	-14.54
825.50	3	QPSK	H	2.09	330	1 / 0	21.41	5.02	26.43	38.45	-12.02
836.50	3	QPSK	H	2.10	321	1 / 0	20.55	5.16	25.71	38.45	-12.74
847.50	3	QPSK	H	2.06	314	1 / 0	19.79	5.29	25.08	38.45	-13.37
825.50	3	16-QAM	H	2.09	330	1 / 0	20.64	5.02	25.66	38.45	-12.79
836.50	3	16-QAM	H	2.10	321	1 / 0	19.81	5.16	24.97	38.45	-13.48
847.50	3	16-QAM	H	2.06	314	1 / 0	18.99	5.29	24.28	38.45	-14.17
826.50	5	QPSK	H	2.25	327	1 / 0	21.73	5.03	26.76	38.45	-11.69
826.50	5	QPSK	V	1.25	310	1 / 0	14.21	4.95	19.16	38.45	-19.29
836.50	5	QPSK	H	2.30	180	1 / 0	19.43	5.16	24.59	38.45	-13.86
846.50	5	QPSK	H	2.08	313	1 / 0	19.14	5.28	24.42	38.45	-14.03
826.50	5	16-QAM	H	2.25	327	1 / 0	21.02	5.03	26.05	38.45	-12.40
836.50	5	16-QAM	H	2.30	180	1 / 0	18.64	5.16	23.80	38.45	-14.65
846.50	5	16-QAM	H	2.08	313	1 / 0	18.41	5.28	23.69	38.45	-14.76
829.00	10	QPSK	H	2.03	324	1 / 0	20.64	5.06	25.70	38.45	-12.75
836.50	10	QPSK	H	2.08	319	1 / 0	20.24	5.16	25.40	38.45	-13.05
844.00	10	QPSK	H	2.03	315	1 / 49	19.21	5.25	24.46	38.45	-13.99
829.00	10	16-QAM	H	2.03	324	1 / 0	19.91	5.06	24.97	38.45	-13.48
836.50	10	16-QAM	H	2.08	319	1 / 0	19.69	5.16	24.85	38.45	-13.60
844.00	10	16-QAM	H	2.03	315	1 / 49	18.35	5.25	23.60	38.45	-14.85

Table 7-3. ERP Data (Band 5)

© 2016 PCTEST Engineering Laboratory, Inc.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1710.70	1.4	QPSK	H	1.19	132	3 / 2	14.19	9.66	23.85	30.00	-6.15
1732.50	1.4	QPSK	H	1.15	45	1 / 0	15.21	9.61	24.82	30.00	-5.18
1754.30	1.4	QPSK	H	1.15	138	3 / 2	14.78	9.57	24.35	30.00	-5.65
1710.70	1.4	16-QAM	H	1.19	132	3 / 2	13.20	9.66	22.86	30.00	-7.14
1732.50	1.4	16-QAM	H	1.08	129	3 / 2	14.39	9.61	24.00	30.00	-6.00
1754.30	1.4	16-QAM	H	1.15	138	1 / 0	13.87	9.57	23.44	30.00	-6.56
1711.50	3	QPSK	H	1.19	132	1 / 0	13.82	9.65	23.47	30.00	-6.53
1732.50	3	QPSK	H	1.08	129	1 / 0	14.89	9.61	24.50	30.00	-5.50
1753.50	3	QPSK	H	1.15	138	1 / 0	14.93	9.57	24.50	30.00	-5.50
1711.50	3	16-QAM	H	1.19	132	1 / 0	13.05	9.65	22.70	30.00	-7.30
1732.50	3	16-QAM	H	1.08	129	1 / 0	14.12	9.61	23.73	30.00	-6.27
1753.50	3	16-QAM	H	1.15	138	1 / 14	14.09	9.57	23.66	30.00	-6.34
1712.50	5	QPSK	H	1.19	132	1 / 0	14.78	9.65	24.43	30.00	-5.57
1732.50	5	QPSK	H	1.08	129	1 / 0	15.34	9.61	24.95	30.00	-5.05
1752.50	5	QPSK	H	1.15	138	1 / 0	15.71	9.57	25.28	30.00	-4.72
1752.50	5	QPSK	V	1.48	27	1 / 0	11.35	9.40	20.75	30.00	-9.25
1712.50	5	16-QAM	H	1.19	132	1 / 0	13.71	9.65	23.36	30.00	-6.64
1732.50	5	16-QAM	H	1.08	129	1 / 0	14.38	9.61	23.99	30.00	-6.01
1752.50	5	16-QAM	H	1.15	138	1 / 0	14.68	9.57	24.25	30.00	-5.75
1715.00	10	QPSK	H	1.19	132	1 / 49	14.44	9.65	24.09	30.00	-5.91
1732.50	10	QPSK	H	1.08	129	1 / 49	14.94	9.61	24.55	30.00	-5.45
1750.00	10	QPSK	H	1.15	138	1 / 0	14.92	9.58	24.50	30.00	-5.50
1715.00	10	16-QAM	H	1.19	132	1 / 49	13.52	9.65	23.17	30.00	-6.83
1732.50	10	16-QAM	H	1.08	129	1 / 0	14.29	9.61	23.90	30.00	-6.10
1750.00	10	16-QAM	H	1.15	138	1 / 0	13.98	9.58	23.56	30.00	-6.44
1717.50	15	QPSK	H	1.19	132	1 / 0	13.80	9.64	23.44	30.00	-6.56
1732.50	15	QPSK	H	1.08	129	1 / 0	13.97	9.61	23.58	30.00	-6.42
1747.50	15	QPSK	H	1.15	138	1 / 0	14.42	9.58	24.00	30.00	-6.00
1717.50	15	16-QAM	H	1.19	132	1 / 0	13.00	9.64	22.64	30.00	-7.36
1732.50	15	16-QAM	H	1.08	129	1 / 0	13.29	9.61	22.90	30.00	-7.10
1747.50	15	16-QAM	H	1.15	138	1 / 0	13.82	9.58	23.40	30.00	-6.60
1720.00	20	QPSK	H	1.19	132	1 / 99	14.57	9.64	24.21	30.00	-5.79
1732.50	20	QPSK	H	1.08	129	1 / 99	15.29	9.61	24.90	30.00	-5.10
1745.00	20	QPSK	H	1.15	138	1 / 0	15.18	9.59	24.77	30.00	-5.23
1720.00	20	16-QAM	H	1.19	132	1 / 99	14.16	9.64	23.80	30.00	-6.20
1732.50	20	16-QAM	H	1.08	129	1 / 99	14.74	9.61	24.35	30.00	-5.65
1745.00	20	16-QAM	H	1.15	138	1 / 0	14.52	9.59	24.11	30.00	-5.89

Table 7-4. EIRP Data (Band 4)

© 2016 PCTEST Engineering Laboratory, Inc.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1850.70	1.4	QPSK	H	1.11	126	1 / 0	16.24	9.35	25.59	33.01	-7.42
1880.00	1.4	QPSK	H	1.11	126	1 / 0	15.35	9.27	24.62	33.01	-8.39
1909.30	1.4	QPSK	H	1.11	122	1 / 0	14.85	9.25	24.10	33.01	-8.91
1850.70	1.4	16-QAM	H	1.11	126	1 / 0	15.55	9.35	24.90	33.01	-8.11
1880.00	1.4	16-QAM	H	1.11	126	1 / 0	14.59	9.27	23.86	33.01	-9.15
1909.30	1.4	16-QAM	H	1.11	122	1 / 0	14.08	9.25	23.33	33.01	-9.68
1851.50	3	QPSK	H	1.11	130	1 / 0	16.24	9.35	25.59	33.01	-7.42
1880.00	3	QPSK	H	1.11	129	1 / 0	15.73	9.27	25.00	33.01	-8.01
1908.50	3	QPSK	H	1.11	124	1 / 14	15.93	9.25	25.18	33.01	-7.83
1851.50	3	16-QAM	H	1.11	130	1 / 0	15.50	9.35	24.85	33.01	-8.16
1880.00	3	16-QAM	H	1.11	129	1 / 0	14.98	9.27	24.25	33.01	-8.76
1908.50	3	16-QAM	H	1.11	124	1 / 14	15.10	9.25	24.35	33.01	-8.66
1852.50	5	QPSK	H	1.11	127	1 / 0	16.59	9.34	25.93	33.01	-7.08
1852.50	5	QPSK	V	1.92	15	1 / 0	9.85	9.22	19.07	33.01	-13.94
1880.00	5	QPSK	H	1.11	127	1 / 0	15.93	9.27	25.20	33.01	-7.81
1907.50	5	QPSK	H	1.11	127	1 / 24	14.96	9.24	24.20	33.01	-8.81
1852.50	5	16-QAM	H	1.11	127	1 / 0	15.79	9.34	25.13	33.01	-7.88
1880.00	5	16-QAM	H	1.11	127	1 / 0	15.17	9.27	24.44	33.01	-8.57
1907.50	5	16-QAM	H	1.11	127	1 / 24	14.14	9.24	23.38	33.01	-9.63
1855.00	10	QPSK	H	1.11	123	1 / 0	16.33	9.34	25.67	33.01	-7.34
1880.00	10	QPSK	H	1.11	130	1 / 0	15.74	9.27	25.01	33.01	-8.00
1905.00	10	QPSK	H	1.11	121	1 / 0	15.65	9.24	24.89	33.01	-8.12
1855.00	10	16-QAM	H	1.11	123	1 / 0	15.52	9.34	24.86	33.01	-8.15
1880.00	10	16-QAM	H	1.11	130	1 / 0	15.32	9.27	24.59	33.01	-8.42
1905.00	10	16-QAM	H	1.11	121	1 / 0	15.15	9.24	24.39	33.01	-8.62
1857.50	15	QPSK	H	1.11	123	1 / 0	16.08	9.33	25.41	33.01	-7.60
1880.00	15	QPSK	H	1.11	126	1 / 0	15.96	9.27	25.23	33.01	-7.78
1902.50	15	QPSK	H	1.11	121	1 / 0	16.23	9.23	25.46	33.01	-7.55
1857.50	15	16-QAM	H	1.11	123	1 / 0	15.03	9.33	24.36	33.01	-8.65
1880.00	15	16-QAM	H	1.11	126	1 / 0	15.46	9.27	24.73	33.01	-8.28
1902.50	15	16-QAM	H	1.11	121	1 / 0	15.19	9.23	24.42	33.01	-8.59
1860.00	20	QPSK	H	1.11	119	1 / 99	15.72	9.32	25.04	33.01	-7.97
1880.00	20	QPSK	H	1.11	124	1 / 0	16.02	9.27	25.29	33.01	-7.72
1900.00	20	QPSK	H	1.11	129	1 / 0	16.18	9.22	25.40	33.01	-7.61
1860.00	20	16-QAM	H	1.11	119	1 / 99	14.80	9.32	24.12	33.01	-8.89
1880.00	20	16-QAM	H	1.11	124	1 / 0	15.06	9.27	24.33	33.01	-8.68
1900.00	20	16-QAM	H	1.11	129	1 / 0	15.31	9.22	24.53	33.01	-8.48

Table 7-5. EIRP Data (Band 2)

© 2016 PCTEST Engineering Laboratory, Inc.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
2307.50	5	QPSK	H	2.65	109	1 / 0	13.79	9.09	22.88	23.98	-1.10
2310.00	5	QPSK	H	2.65	113	1 / 0	11.67	9.09	20.76	23.98	-3.22
2312.50	5	QPSK	H	2.67	113	1 / 24	11.30	9.08	20.38	23.98	-3.60
2307.50	5	16-QAM	H	2.65	109	1 / 0	13.16	9.09	22.25	23.98	-1.73
2310.00	5	16-QAM	H	2.65	113	1 / 0	10.02	9.09	19.11	23.98	-4.87
2312.50	5	16-QAM	H	2.67	113	1 / 24	10.60	9.08	19.68	23.98	-4.30
2310.00	10	QPSK	H	2.65	111	1 / 0	13.10	9.09	22.19	23.98	-1.79
2310.00	10	16-QAM	H	2.65	111	1 / 0	12.39	9.09	21.48	23.98	-2.50
2307.50	5	QPSK	V	1.89	185	1 / 0	9.81	9.03	18.84	23.98	-5.14

Table 7-6. EIRP Data (Band 30)

© 2016 PCTEST Engineering Laboratory, Inc.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
2498.50	5	QPSK	H	2.02	260	1 / 0	16.68	8.60	25.28	33.01	-7.73
2498.50	5	QPSK	V	1.15	25	1 / 0	12.46	8.58	21.04	33.01	-11.97
2593.00	5	QPSK	H	1.96	245	1 / 0	15.06	8.53	23.59	33.01	-9.42
2687.50	5	QPSK	H	1.00	209	1 / 0	10.27	8.79	19.06	33.01	-13.95
2498.50	5	16-QAM	H	2.02	260	1 / 0	16.45	8.60	25.05	33.01	-7.96
2593.00	5	16-QAM	H	1.96	245	1 / 0	14.91	8.53	23.44	33.01	-9.57
2687.50	5	16-QAM	H	1.00	209	1 / 0	9.51	8.79	18.30	33.01	-14.71
2501.00	10	QPSK	H	1.00	216	1 / 0	15.17	8.60	23.77	33.01	-9.24
2593.00	10	QPSK	H	1.00	225	1 / 0	13.26	8.53	21.79	33.01	-11.22
2685.00	10	QPSK	H	1.00	219	1 / 0	10.15	8.78	18.93	33.01	-14.08
2501.00	10	16-QAM	H	1.00	216	1 / 0	13.76	8.60	22.36	33.01	-10.65
2593.00	10	16-QAM	H	1.00	225	1 / 0	11.97	8.53	20.50	33.01	-12.51
2685.00	10	16-QAM	H	1.00	219	1 / 0	9.43	8.78	18.21	33.01	-14.80
2503.50	15	QPSK	H	1.00	213	1 / 0	15.51	8.59	24.10	33.01	-8.91
2593.00	15	QPSK	H	1.00	216	1 / 0	12.97	8.53	21.50	33.01	-11.51
2682.50	15	QPSK	H	1.00	218	1 / 0	10.13	8.77	18.90	33.01	-14.11
2503.50	15	16-QAM	H	1.00	213	1 / 0	14.77	8.59	23.36	33.01	-9.65
2593.00	15	16-QAM	H	1.00	216	1 / 0	11.86	8.53	20.39	33.01	-12.62
2682.50	15	16-QAM	H	1.00	218	1 / 0	9.07	8.77	17.84	33.01	-15.17
2506.00	20	QPSK	H	1.00	221	1 / 99	13.43	8.59	22.02	33.01	-10.99
2593.00	20	QPSK	H	1.00	223	1 / 0	13.34	8.53	21.87	33.01	-11.14
2680.00	20	QPSK	H	1.00	217	1 / 0	9.95	8.77	18.72	33.01	-14.29
2506.00	20	16-QAM	H	1.00	221	1 / 99	12.84	8.59	21.43	33.01	-11.58
2593.00	20	16-QAM	H	1.00	23	1 / 0	12.88	8.53	21.41	33.01	-11.60
2680.00	20	16-QAM	H	1.00	217	1 / 0	9.31	8.77	18.08	33.01	-14.93

Table 7-7. EIRP Data (Band 41)

© 2016 PCTEST Engineering Laboratory, Inc.

7.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h) §27.53(m) §27.53(a.4)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW ≥ 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points ≥ 2 x span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

© 2016 PCTEST Engineering Laboratory, Inc.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-7. Test Instrument & Measurement Setup

Test Notes

1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.

2) This unit was tested with its standard battery.

3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.

4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

5) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	699.70	MHz		
CHANNEL:	23017			
MEASURED OUTPUT POWER:	20.34	dBm	=	0.108 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	1.4	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	33.34	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1399.40	H	1.94	116	-70.32	6.17	-64.15	84.5
2099.10	H	-	-	-67.95	6.07	-61.88	82.2

Table 7-8. Radiated Spurious Data (Band 12 – Low Channel)

OPERATING FREQUENCY:	707.50	MHz		
CHANNEL:	23095			
MEASURED OUTPUT POWER:	21.78	dBm	=	0.151 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	1.4	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	34.78	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1415.00	H	-	-	-71.68	6.14	-65.54	87.3
2122.50	H	1.75	313	-61.76	6.20	-55.56	77.3
2830.00	H	-	-	-67.23	7.50	-59.73	81.5

Table 7-9. Radiated Spurious Data (Band 12 – Mid Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	715.31	MHz			
CHANNEL:	23173				
MEASURED OUTPUT POWER:	20.86	dBm	=	0.122	W
MODULATION SIGNAL:	QPSK				
BANDWIDTH:	1.4	MHz			
DISTANCE:	3	meters			
LIMIT:	43 + 10 log10 (W)	33.86	dBc		

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1430.62	H	-	-	-70.54	6.11	-64.43	85.3
2145.93	H	1.76	306	-64.75	6.34	-58.41	79.3
2861.24	H	-	-	-67.42	7.56	-59.86	80.7

Table 7-10. Radiated Spurious Data (Band 12 – High Channel)

OPERATING FREQUENCY:	707.50	MHz			
CHANNEL:	23095				
MEASURED OUTPUT POWER:	21.78	dBm	=	0.151	W
MODULATION SIGNAL:	QPSK				
BANDWIDTH:	1.4	MHz			
DISTANCE:	3	meters			
LIMIT:	43 + 10 log10 (W)	34.78	dBc		

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1415.00	H	2.05	0	-69.92	6.14	-63.78	85.6
2122.50	H	-	-	-66.31	6.20	-60.11	81.9

Table 7-11. Radiated Spurious Data with WCP (Band 12 – Mid Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	826.50	MHz		
CHANNEL:	20425			
MEASURED OUTPUT POWER:	26.76	dBm	=	0.475 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	39.76	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1653.00	H	-	-	-61.35	3.60	-57.75	84.5

Table 7-12. Radiated Spurious Data (Band 5 – Low Channel)

OPERATING FREQUENCY:	836.50	MHz		
CHANNEL:	20525			
MEASURED OUTPUT POWER:	24.59	dBm	=	0.288 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	37.59	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.00	H	1.11	173	-58.28	3.53	-54.75	79.3
2509.50	H	-	-	-59.76	3.57	-56.19	80.8

Table 7-13. Radiated Spurious Data (Band 5 – Mid Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	846.50	MHz		
CHANNEL:	20625			
MEASURED OUTPUT POWER:	24.42	dBm	=	0.277 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	37.42	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1693.00	H	-	-	-63.85	3.46	-60.39	84.8

Table 7-14. Radiated Spurious Data (Band 5 – High Channel)

OPERATING FREQUENCY:	836.50	MHz		
CHANNEL:	20525			
MEASURED OUTPUT POWER:	24.59	dBm	=	0.288 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	37.59	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.00	H	1.00	234	-58.67	3.53	-55.14	79.7
2509.50	H	-	-	-58.83	3.57	-55.26	79.9

Table 7-15. Radiated Spurious Data with WCP (Band 5 – Mid Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	1712.50	MHz		
CHANNEL:	19975			
MEASURED OUTPUT POWER:	24.43	dBm	=	0.277 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	37.43	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3425.00	H	-	-	-61.69	8.15	-53.54	78.0

Table 7-16. Radiated Spurious Data (Band 4 – Low Channel)

OPERATING FREQUENCY:	1732.50	MHz		
CHANNEL:	20175			
MEASURED OUTPUT POWER:	24.95	dBm	=	0.313 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	37.95	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3465.00	H	-	-	-61.61	8.29	-53.32	78.3

Table 7-17. Radiated Spurious Data (Band 4 – Mid Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	1752.50	MHz		
CHANNEL:	20375			
MEASURED OUTPUT POWER:	25.28	dBm	=	0.338 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	38.28	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3505.00	H	-	-	-61.95	8.40	-53.55	78.8

Table 7-18. Radiated Spurious Data (Band 4 – High Channel)

OPERATING FREQUENCY:	1712.50	MHz		
CHANNEL:	19975			
MEASURED OUTPUT POWER:	24.43	dBm	=	0.277 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	37.43	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3425.00	H	-	-	-61.52	8.15	-53.37	77.8

Table 7-19. Radiated Spurious Data with WCP (Band 4 – Low Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	1852.50	MHz		
CHANNEL:	18625			
MEASURED OUTPUT POWER:	25.93	dBm	=	0.392 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	38.93	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3705.00	H	1.11	38	-50.72	9.43	-41.29	67.2
5557.50	H	1.11	289	-58.64	10.80	-47.84	73.8
7410.00	H	1.11	109	-53.32	10.71	-42.61	68.5
9262.50	H	-	-	-54.06	11.58	-42.48	68.4

Table 7-20. Radiated Spurious Data (Band 2 – Low Channel)

OPERATING FREQUENCY:	1880.00	MHz		
CHANNEL:	18900			
MEASURED OUTPUT POWER:	25.20	dBm	=	0.331 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	38.20	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	1.11	137	-51.31	9.28	-42.03	67.2
5640.00	H	1.11	283	-56.67	11.03	-45.64	70.8
7520.00	H	1.11	281	-53.35	10.97	-42.38	67.6
9400.00	H	-	-	-54.60	11.53	-43.07	68.3

Table 7-21. Radiated Spurious Data (Band 2 – Mid Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	1907.50	MHz		
CHANNEL:	19175			
MEASURED OUTPUT POWER:	24.20	dBm	=	0.263 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	37.20	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3815.00	H	1.10	259	-54.83	9.19	-45.64	69.8
5722.50	H	1.10	280	-55.71	11.27	-44.44	68.6
7630.00	H	1.10	302	-52.73	11.17	-41.56	65.8
9537.50	H	1.10	261	-53.89	11.80	-42.09	66.3
11445.00	H	-	-	-51.31	12.72	-38.59	62.8

Table 7-22. Radiated Spurious Data (Band 2 – High Channel)

OPERATING FREQUENCY:	1907.50	MHz		
CHANNEL:	18625			
MEASURED OUTPUT POWER:	24.20	dBm	=	0.263 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	43 + 10 $\log_{10}$ (W) =	37.20	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3815.00	H	1.10	86	-54.87	9.19	-45.68	69.9
5722.50	H	1.10	81	-56.18	11.27	-44.91	69.1
7630.00	H	1.10	77	-52.97	11.17	-41.80	66.0
9537.50	H	1.10	103	-55.00	11.80	-43.20	67.4
11445.00	H	-	-	-50.41	12.72	-37.69	61.9

Table 7-23. Radiated Spurious Data with WCP (Band 2 – High Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	2307.50	MHz		
CHANNEL:	27685			
MEASURED OUTPUT POWER:	22.88	dBm	=	0.194 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	70 + 10 $\log_{10}$ (W) =	62.88	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
4615.00	H	1.10	64	-53.00	9.51	-43.49	66.4
6922.50	H	1.66	123	-64.00	11.48	-52.52	75.4
9230.00	H	1.93	170	-65.34	13.22	-52.12	75.0
11537.50	H	1.44	260	-57.05	13.34	-43.71	66.6
13845.00	H	1.44	239	-59.11	14.55	-44.56	67.4
16152.50	H	-	-	-57.79	13.58	-44.21	67.1

Table 7-24. Radiated Spurious Data (Band 30 – Low Channel)

OPERATING FREQUENCY:	2310.00	MHz		
CHANNEL:	27710			
MEASURED OUTPUT POWER:	20.76	dBm	=	0.119 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	70 + 10 $\log_{10}$ (W) =	60.76	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
4620.00	H	1.00	75	-58.82	9.52	-49.30	70.1
6930.00	H	1.07	241	-65.56	11.49	-54.07	74.8
9240.00	H	1.00	162	-66.31	13.22	-53.09	73.8
11550.00	H	1.94	260	-61.96	13.33	-48.63	69.4
13860.00	H	-	-	-63.30	14.56	-48.74	69.5

Table 7-25. Radiated Spurious Data (Band 30 – Mid Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	2312.50	MHz			
CHANNEL:	27735				
MEASURED OUTPUT POWER:	20.38	dBm	=	0.109	W
MODULATION SIGNAL:	QPSK				
BANDWIDTH:	5.0	MHz			
DISTANCE:	3	meters			
LIMIT:	70 + 10 $\log_{10}$ (W) =	60.38	dBc		

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
4625.00	H	1.91	206	-66.45	9.53	-56.92	77.3
6937.50	H	1.27	119	-66.52	11.49	-55.03	75.4
9250.00	H	1.41	142	-65.43	13.22	-52.21	72.6
11562.50	H	-	-	-60.89	13.33	-47.56	67.9

Table 7-26. Radiated Spurious Data (Band 30 – High Channel)

OPERATING FREQUENCY:	2307.50	MHz			
CHANNEL:	27685				
MEASURED OUTPUT POWER:	22.88	dBm	=	0.194	W
MODULATION SIGNAL:	QPSK				
BANDWIDTH:	5.0	MHz			
DISTANCE:	3	meters			
LIMIT:	70 + 10 log10 (W)	62.88	dBc		

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
4615.00	H	1.10	0	-64.86	9.53	-55.33	78.2
6922.50	H	-	-	-65.05	11.49	-53.55	76.4

Table 7-27. Radiated Spurious Data with WCP (Band 30 – Low Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	2498.50	MHz		
CHANNEL:	39675			
MEASURED OUTPUT POWER:	25.28	dBm	=	0.337 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	55 + 10 log10 (W)	50.28	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
4997.00	H	1.15	349	-53.84	10.14	-43.70	71.4
7495.50	H	1.16	81	-44.88	12.08	-32.79	60.5
9994.00	H	1.28	254	-49.82	13.25	-36.57	64.3
12492.50	H	-	-	-51.56	13.19	-38.36	66.1

Table 7-28. Radiated Spurious Data (Band 41 – Low Channel)

OPERATING FREQUENCY:	2593.00	MHz		
CHANNEL:	40620			
MEASURED OUTPUT POWER:	23.59	dBm	=	0.229 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	55 + 10 log10 (W)	48.59	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
5186.00	H	1.08	356	-56.52	10.33	-46.19	69.8
7779.00	H	1.00	38	-51.97	12.32	-39.64	63.2
10372.00	H	1.00	80	-49.26	13.18	-36.08	59.7
12965.00	H	-	-	-51.25	13.43	-37.82	61.4

Table 7-29. Radiated Spurious Data (Band 41 – Mid Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

OPERATING FREQUENCY:	2687.50	MHz		
CHANNEL:	41565			
MEASURED OUTPUT POWER:	19.06	dBm	=	0.080 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	55 + 10 log10 (W)	44.06	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
5375.00	H	-	-	-56.10	10.37	-45.73	64.8

Table 7-30. Radiated Spurious Data (Band 41 – High Channel)

OPERATING FREQUENCY:	2498.50	MHz		
CHANNEL:	39675			
MEASURED OUTPUT POWER:	25.28	dBm	=	0.337 W
MODULATION SIGNAL:	QPSK			
BANDWIDTH:	5.0	MHz		
DISTANCE:	3	meters		
LIMIT:	55 + 10 log10 (W)	50.28	dBc	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
4997.00	H	1.32	156	-60.18	10.33	-49.85	75.1
7495.50	H	-	-	-59.28	12.32	-46.95	72.2

Table 7-31. Radiated Spurious Data with WCP (Band 41 – Low Channel)

© 2016 PCTEST Engineering Laboratory, Inc.

7.8 Frequency Stability / Temperature Variation

§2.1055 §22.355 §24.235 §27.54

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-C-2004

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

© 2016 PCTEST Engineering Laboratory, Inc.

Band 12 Frequency Stability Measurements

§2.1055 §27.54

OPERATING FREQUENCY:	707,500,000	Hz
CHANNEL:	23790	
REFERENCE VOLTAGE:	3.80	VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	707,499,768	-232	-0.0000328
100 %		- 30	707,500,004	4	0.0000006
100 %		- 20	707,499,912	-88	-0.0000124
100 %		- 10	707,500,194	194	0.0000274
100 %		0	707,499,806	-194	-0.0000274
100 %		+ 10	707,499,984	-16	-0.0000023
100 %		+ 20	707,500,140	140	0.0000198
100 %		+ 30	707,500,197	197	0.0000278
100 %		+ 40	707,500,029	29	0.0000041
100 %		+ 50	707,499,793	-207	-0.0000293
BATT. ENDPOINT	3.40	+ 20	707,500,286	286	0.0000404

Table 7-32. Frequency Stability Data (Band 12)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

© 2016 PCTEST Engineering Laboratory, Inc.

Band 12 Frequency Stability Measurements

§2.1055 §27.54



Figure 7-8. Frequency Stability Graph (Band 12)

© 2016 PCTEST Engineering Laboratory, Inc.

Band 5 Frequency Stability Measurements

§2.1055 §22.355

OPERATING FREQUENCY:	836,500,000	Hz
CHANNEL:	20525	
REFERENCE VOLTAGE:	3.80	VDC
DEVIATION LIMIT:	± 0.00025 % or 2.5 ppm	

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,499,715	-285	-0.0000341
100 %		- 30	836,499,978	-22	-0.0000026
100 %		- 20	836,499,703	-297	-0.0000355
100 %		- 10	836,500,052	52	0.0000062
100 %		0	836,499,904	-96	-0.0000115
100 %		+ 10	836,499,900	-100	-0.0000120
100 %		+ 20	836,499,796	-204	-0.0000244
100 %		+ 30	836,500,062	62	0.0000074
100 %		+ 40	836,500,003	3	0.0000004
100 %		+ 50	836,500,410	410	0.0000490
BATT. ENDPOINT	3.40	+ 20	836,500,297	297	0.0000355

Table 7-33. Frequency Stability Data (Band 5)

© 2016 PCTEST Engineering Laboratory, Inc.

Band 5 Frequency Stability Measurements

§2.1055 §22.355



Figure 7-9. Frequency Stability Graph (Band 5)

© 2016 PCTEST Engineering Laboratory, Inc.

Band 4 Frequency Stability Measurements

§2.1055 §§27.54

OPERATING FREQUENCY:	1,732,500,000	Hz
CHANNEL:	20175	
REFERENCE VOLTAGE:	3.80	VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,732,499,963	-37	-0.0000021
100 %		- 30	1,732,499,807	-193	-0.0000111
100 %		- 20	1,732,499,854	-146	-0.0000084
100 %		- 10	1,732,499,868	-132	-0.0000076
100 %		0	1,732,500,310	310	0.0000179
100 %		+ 10	1,732,499,813	-187	-0.0000108
100 %		+ 20	1,732,499,798	-202	-0.0000117
100 %		+ 30	1,732,499,950	-50	-0.0000029
100 %		+ 40	1,732,500,044	44	0.0000025
100 %		+ 50	1,732,499,612	-388	-0.0000224
BATT. ENDPOINT	3.40	+ 20	1,732,499,877	-123	-0.0000071

Table 7-34. Frequency Stability Data (Band 4)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

© 2016 PCTEST Engineering Laboratory, Inc.

Band 4 Frequency Stability Measurements

§2.1055 §§27.54



Figure 7-10. Frequency Stability Graph (Band 4)

© 2016 PCTEST Engineering Laboratory, Inc.

Band 2 Frequency Stability Measurements
§2.1055 §24.235

OPERATING FREQUENCY:	1,880,000,000	Hz
CHANNEL:	18900	
REFERENCE VOLTAGE:	3.80	VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,879,999,804	-196	-0.0000104
100 %		- 30	1,879,999,962	-38	-0.0000020
100 %		- 20	1,879,999,743	-257	-0.0000137
100 %		- 10	1,879,999,709	-291	-0.0000155
100 %		0	1,879,999,952	-48	-0.0000026
100 %		+ 10	1,880,000,311	311	0.0000165
100 %		+ 20	1,879,999,992	-8	-0.0000004
100 %		+ 30	1,879,999,804	-196	-0.0000104
100 %		+ 40	1,879,999,985	-15	-0.0000008
100 %		+ 50	1,880,000,279	279	0.0000148
BATT. ENDPOINT	3.40	+ 20	1,879,999,820	-180	-0.0000096

Table 7-35. Frequency Stability Data (Band 2)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

© 2016 PCTEST Engineering Laboratory, Inc.

Band 2 Frequency Stability Measurements

§2.1055 §24.235



Figure 7-11. Frequency Stability Graph (Band 2)

© 2016 PCTEST Engineering Laboratory, Inc.

Band 30 Frequency Stability Measurements

§2.1055 §24.235

OPERATING FREQUENCY:	2,310,000,000	Hz
CHANNEL:	27710	
REFERENCE VOLTAGE:	3.80	VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	2,309,999,851	-149	-0.0000065
100 %		- 30	2,310,000,301	301	0.0000130
100 %		- 20	2,310,000,157	157	0.0000068
100 %		- 10	2,309,999,830	-170	-0.0000074
100 %		0	2,310,000,083	83	0.0000036
100 %		+ 10	2,310,000,405	405	0.0000175
100 %		+ 20	2,310,000,157	157	0.0000068
100 %		+ 30	2,310,000,387	387	0.0000168
100 %		+ 40	2,310,000,193	193	0.0000084
100 %		+ 50	2,309,999,894	-106	-0.0000046
BATT. ENDPOINT	3.40	+ 20	2,310,000,483	483	0.0000209

Table 7-36. Frequency Stability Data (Band 30)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

© 2016 PCTEST Engineering Laboratory, Inc.

Band 30 Frequency Stability Measurements

§2.1055 §24.235



Figure 7-12. Frequency Stability Graph (Band 30)

© 2016 PCTEST Engineering Laboratory, Inc.

Band 41 Frequency Stability Measurements

§2.1055 §27.54

OPERATING FREQUENCY:	2,593,000,000	Hz
CHANNEL:	40620	
REFERENCE VOLTAGE:	3.80	VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	2,592,999,827	-173	-0.0000067
100 %		- 30	2,593,000,176	176	0.0000068
100 %		- 20	2,593,000,054	54	0.0000021
100 %		- 10	2,592,999,842	-158	-0.0000061
100 %		0	2,592,999,668	-332	-0.0000128
100 %		+ 10	2,593,000,011	11	0.0000004
100 %		+ 20	2,592,999,707	-293	-0.0000113
100 %		+ 30	2,592,999,904	-96	-0.0000037
100 %		+ 40	2,593,000,219	219	0.0000084
100 %		+ 50	2,593,000,107	107	0.0000041
BATT. ENDPOINT	3.40	+ 20	2,593,000,155	155	0.0000060

Table 7-37. Frequency Stability Data (Band 41)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

© 2016 PCTEST Engineering Laboratory, Inc.

Band 41 Frequency Stability Measurements

§2.1055 §27.54



Figure 7-13. Frequency Stability Graph (Band 41)

© 2016 PCTEST Engineering Laboratory, Inc.

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG891A** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules for LTE operation only.

© 2016 PCTEST Engineering Laboratory, Inc.