



## SAR EVALUATION REPORT

**Applicant Name:**

Samsung Electronics, Co. Ltd.  
129, Samsung-ro, Maetan dong,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do 443-742, Korea

**Date of Testing:**

02/03/14 - 03/31/14

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Document Serial No.:**

0Y1403190578.A3L

**FCC ID:**

**A3LSMG900R7**

**APPLICANT:**

**SAMSUNG ELECTRONICS, CO. LTD.**

**DUT Type:**

Portable Handset

**Application Type:**

Certification

**FCC Rule Part(s):**

CFR §2.1093

**Model(s):**

SM-G900R7

| Equipment Class                                   | Band & Mode       | Tx Frequency          | SAR              |                       |                     |
|---------------------------------------------------|-------------------|-----------------------|------------------|-----------------------|---------------------|
|                                                   |                   |                       | 1 gm Head (W/kg) | 1 gm Body-Worn (W/kg) | 1 gm Hotspot (W/kg) |
| PCE                                               | Cell. CDMA/EVDO   | 824.70 - 848.31 MHz   | 0.61             | 0.78                  | 0.78                |
| PCE                                               | PCS CDMA/EVDO     | 1851.25 - 1908.75 MHz | 0.62             | 0.53                  | 0.57                |
| PCE                                               | LTE Band 12       | 701.5 - 713.5 MHz     | 0.34             | 0.41                  | 0.52                |
| PCE                                               | LTE Band 4 (AWS)  | 1712.5 - 1752.5 MHz   | 0.38             | 0.51                  | 0.59                |
| PCE                                               | LTE Band 25 (PCS) | 1852.5 - 1912.5 MHz   | 0.63             | 0.22                  | 0.57                |
| DTS                                               | 2.4 GHz WLAN      | 2412 - 2462 MHz       | 0.19             | 0.26                  | 0.26                |
| DTS                                               | 5.8 GHz WLAN      | 5745 - 5825 MHz       | 0.17             | 0.33                  | 0.33                |
| NII                                               | 5.2 GHz WLAN      | 5180 - 5240 MHz       | < 0.1            | 0.24                  |                     |
| NII                                               | 5.3 GHz WLAN      | 5260 - 5320 MHz       | < 0.1            | 0.23                  |                     |
| NII                                               | 5.5 GHz WLAN      | 5500 - 5700 MHz       | 0.22             | 0.35                  |                     |
| DSS/DTS                                           | Bluetooth         | 2402 - 2480 MHz       | N/A              |                       |                     |
| <b>Simultaneous SAR per KDB 690783 D01v01r02:</b> |                   |                       | 1.55             |                       |                     |

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.9 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

  
Randy Ortanez  
President



|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 1 of 79                                                                          |                                 |

# T A B L E O F C O N T E N T S

|    |                                                  |    |
|----|--------------------------------------------------|----|
| 1  | DEVICE UNDER TEST .....                          | 3  |
| 2  | LTE INFORMATION .....                            | 10 |
| 3  | INTRODUCTION .....                               | 11 |
| 4  | DOSIMETRIC ASSESSMENT .....                      | 12 |
| 5  | DEFINITION OF REFERENCE POINTS .....             | 13 |
| 6  | TEST CONFIGURATION POSITIONS FOR HANDSETS .....  | 14 |
| 7  | RF EXPOSURE LIMITS .....                         | 18 |
| 8  | FCC MEASUREMENT PROCEDURES.....                  | 19 |
| 9  | RF CONDUCTED POWERS.....                         | 24 |
| 10 | SYSTEM VERIFICATION.....                         | 40 |
| 11 | SAR DATA SUMMARY .....                           | 42 |
| 12 | FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS..... | 52 |
| 13 | SAR MEASUREMENT VARIABILITY .....                | 73 |
| 14 | EQUIPMENT LIST .....                             | 74 |
| 15 | MEASUREMENT UNCERTAINTIES .....                  | 75 |
| 16 | CONCLUSION.....                                  | 77 |
| 17 | REFERENCES .....                                 | 78 |

APPENDIX A: SAR TEST PLOTS

APPENDIX B: SAR DIPOLE VERIFICATION PLOTS

APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES

APPENDIX D: SAR TISSUE SPECIFICATIONS

APPENDIX E: SAR SYSTEM VALIDATION

APPENDIX F: SAR TEST SETUP PHOTOGRAPHS

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 2 of 79                           |

# 1 DEVICE UNDER TEST

## 1.1 Device Overview

| Band & Mode       | Operating Modes | Tx Frequency          |
|-------------------|-----------------|-----------------------|
| Cell. CDMA/EVDO   | Voice/Data      | 824.70 - 848.31 MHz   |
| PCS CDMA/EVDO     | Voice/Data      | 1851.25 - 1908.75 MHz |
| LTE Band 12       | Data            | 701.5 - 713.5 MHz     |
| LTE Band 4 (AWS)  | Data            | 1712.5 - 1752.5 MHz   |
| LTE Band 2 (PCS)  | Data            | 1852.5 - 1907.5 MHz   |
| LTE Band 25 (PCS) | Data            | 1852.5 - 1912.5 MHz   |
| 2.4 GHz WLAN      | Data            | 2412 - 2462 MHz       |
| 5.8 GHz WLAN      | Data            | 5745 - 5825 MHz       |
| 5.2 GHz WLAN      | Data            | 5180 - 5240 MHz       |
| 5.3 GHz WLAN      | Data            | 5260 - 5320 MHz       |
| 5.5 GHz WLAN      | Data            | 5500 - 5700 MHz       |
| Bluetooth         | Data            | 2402 - 2480 MHz       |
| NFC               | Data            | 13.56 MHz             |
| ANT+              | Data            | 2402 - 2480 MHz       |

## 1.2 Power Reduction for SAR

This device utilizes power reduction using an independent single fixed level of reduction through a static table look-up, triggered by a single event/operation for the following modes:

### 1.2.1 CDMA2000

- PCS CDMA/EVDO power is reduced when Hotspot is active.

### 1.2.2 WI-FI

- Power is reduced for all held-to-ear exposure conditions.

## 1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

### 1.3.1 Maximum Power

| Mode / Band     |         | Modulated Average (dBm) |
|-----------------|---------|-------------------------|
| Cell. CDMA/EVDO | Maximum | 25.0                    |
|                 | Nominal | 24.5                    |
| PCS CDMA/EVDO   | Maximum | 25.0                    |
|                 | Nominal | 24.5                    |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 3 of 79                                                                          |                                        |

| Mode / Band       |         | Modulated Average (dBm) |
|-------------------|---------|-------------------------|
| LTE Band 12       | Maximum | 23.5                    |
|                   | Nominal | 23.0                    |
| LTE Band 4 (AWS)  | Maximum | 23.5                    |
|                   | Nominal | 23.0                    |
| LTE Band 2 (PCS)  | Maximum | 23.5                    |
|                   | Nominal | 23.0                    |
| LTE Band 25 (PCS) | Maximum | 23.5                    |
|                   | Nominal | 23.0                    |

| Mode / Band                             |         | Modulated Average (dBm) |
|-----------------------------------------|---------|-------------------------|
| IEEE 802.11b (2.4 GHz)                  | Maximum | 17.5                    |
|                                         | Nominal | 17.0                    |
| IEEE 802.11g (2.4 GHz)                  | Maximum | 14.5                    |
|                                         | Nominal | 14.0                    |
| IEEE 802.11n (2.4 GHz)                  | Maximum | 14.0                    |
|                                         | Nominal | 13.5                    |
| IEEE 802.11a (5 GHz)                    | Maximum | 14.0                    |
|                                         | Nominal | 13.5                    |
| IEEE 802.11n (5 GHz, 20 MHz Bandwidth)  | Maximum | 13.5                    |
|                                         | Nominal | 13.0                    |
| IEEE 802.11n (5 GHz, 40 MHz Bandwidth)  | Maximum | 12.5                    |
|                                         | Nominal | 12.0                    |
| IEEE 802.11ac (5 GHz, 80 MHz Bandwidth) | Maximum | 11.5                    |
|                                         | Nominal | 11.0                    |
| Bluetooth                               | Maximum | 10.0                    |
|                                         | Nominal | 9.5                     |
| Bluetooth LE                            | Maximum | 8.5                     |
|                                         | Nominal | 8.0                     |

### 1.3.2 Reduced Power with Hotspot Mode Activated


| Mode / Band   |         | Modulated Average (dBm) |
|---------------|---------|-------------------------|
| PCS CDMA/EVDO | Maximum | 23.0                    |
|               | Nominal | 22.5                    |

### 1.3.3 Reduced Power – Held-to-Ear

| Mode / Band                             |         | Modulated Average (dBm) |
|-----------------------------------------|---------|-------------------------|
| IEEE 802.11b (2.4 GHz)                  | Maximum | 12.5                    |
|                                         | Nominal | 12.0                    |
| IEEE 802.11g (2.4 GHz)                  | Maximum | 12.5                    |
|                                         | Nominal | 12.0                    |
| IEEE 802.11n (2.4 GHz)                  | Maximum | 12.5                    |
|                                         | Nominal | 12.0                    |
| IEEE 802.11a (5 GHz)                    | Maximum | 7.5                     |
|                                         | Nominal | 7.0                     |
| IEEE 802.11n (5 GHz, 20 MHz Bandwidth)  | Maximum | 7.5                     |
|                                         | Nominal | 7.0                     |
| IEEE 802.11n (5 GHz, 40 MHz Bandwidth)  | Maximum | 7.5                     |
|                                         | Nominal | 7.0                     |
| IEEE 802.11ac (5 GHz, 80 MHz Bandwidth) | Maximum | 7.5                     |
|                                         | Nominal | 7.0                     |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 4 of 79                                                                          |                                        |

## 1.4 DUT Antenna Locations



Note: Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC Filing.

**Figure 1-1**  
**DUT Antenna Locations**

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 5 of 79                    |

**Table 1-1**  
**Mobile Hotspot Sides for SAR Testing**

| Mode              | Back | Front | Top | Bottom | Right | Left |
|-------------------|------|-------|-----|--------|-------|------|
| Cell. EVDO        | Yes  | Yes   | No  | Yes    | Yes   | No   |
| PCS EVDO          | Yes  | Yes   | No  | Yes    | Yes   | No   |
| LTE Band 12       | Yes  | Yes   | No  | Yes    | No    | Yes  |
| LTE Band 4 (AWS)  | Yes  | Yes   | No  | Yes    | No    | Yes  |
| LTE Band 25 (PCS) | Yes  | Yes   | No  | Yes    | No    | Yes  |
| 2.4 GHz WLAN      | Yes  | Yes   | Yes | No     | No    | Yes  |
| 5.8 GHz WLAN      | Yes  | Yes   | Yes | No     | No    | Yes  |

Note: Particular DUT edges were not required to be evaluated for Wireless Router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v01 guidance, page 2.

### 1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the specialized battery. The SAR tests were performed with the specialized battery (model: EB-BG900BBU).




**Figure 1-2**  
**NFC Antenna Locations**

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 6 of 79                                                                          |                                 |

## 1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-3 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another. This device supports MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.



Figure 1-3  
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

Table 1-2  
Simultaneous Transmission Scenarios

| No. | Capable Transmit Configuration          | Head | Body-Worn Accessory | Wireless Router | Notes                                             |
|-----|-----------------------------------------|------|---------------------|-----------------|---------------------------------------------------|
| 1   | 1x CDMA voice + 2.4 GHz WI-FI           | Yes  | Yes                 | N/A             |                                                   |
| 2   | 1x CDMA voice + 5 GHz WI-FI             | Yes  | Yes                 | N/A             |                                                   |
| 3   | 1x CDMA voice + 2.4 GHz Bluetooth       | N/A  | Yes                 | N/A             |                                                   |
| 4   | LTE + 2.4 GHz WI-FI                     | Yes* | Yes*                | Yes             | *-Pre-installed VOIP applications are considered. |
| 5   | LTE + 5 GHz WI-FI                       | Yes* | Yes*                | Yes             | *-Pre-installed VOIP applications are considered. |
| 6   | LTE + 2.4 GHz Bluetooth                 | N/A  | Yes*                | N/A             | *-Pre-installed VOIP applications are considered. |
| 7   | CDMA/EVDO data + 2.4 GHz WI-FI          | Yes* | Yes*                | Yes             | *-Pre-installed VOIP applications are considered. |
| 8   | CDMA/EVDO data + 5 GHz WI-FI            | Yes* | Yes*                | Yes             | *-Pre-installed VOIP applications are considered. |
| 9   | CDMA/EVDO data + 2.4 GHz Bluetooth      | N/A  | Yes*                | N/A             | *-Pre-installed VOIP applications are considered. |
| 10  | 1x CDMA voice + LTE                     | Yes  | Yes                 | N/A             |                                                   |
| 11  | 1x CDMA voice + LTE + 2.4 GHz WI-FI     | Yes  | Yes                 | Yes             |                                                   |
| 12  | 1x CDMA voice + LTE + 5 GHz WI-FI       | Yes  | Yes                 | Yes             |                                                   |
| 13  | 1x CDMA voice + LTE + 2.4 GHz Bluetooth | N/A  | Yes                 | N/A             |                                                   |
| 14  | 1x CDMA voice + CDMA/EVDO data          | N/A  | N/A                 | N/A             | Not supported by HW                               |
| 15  | CDMA/EVDO data + LTE                    | N/A  | N/A                 | N/A             | Not supported by SW                               |

Note:

1. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
2. This device supports 2x2 MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.

## 1.7 Wireless Charging Cover

This DUT may be used with a standard battery cover or with an optional wireless charging battery cover. Per FCC KDB Publication 648474 D04, SAR was measured using the standard battery cover and then repeated with the wireless charging battery cover for the highest reported SAR for each wireless technology, frequency band, operating mode, and exposure condition. No other additional test with wireless charging cover was required since all reported SAR were less than 1.2 W/kg.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 7 of 79                    |

## 1.8 SAR Test Exclusions Applied

### (A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using 5 GHz NII WIFI, only 2.4 GHz and 5.8 GHz WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v01.

Per FCC KDB 447498 D01v05, the SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, Bluetooth SAR was not required;  $[(10/15) * \sqrt{2.441}] = 1.0 < 3.0$ . Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports 20 MHz and 40 MHz Bandwidths for IEEE 802.11n for 5 GHz WIFI only. SISO IEEE 802.11n was not evaluated for SAR since the average output power of 20 MHz and 40 MHz bandwidths was not more than 0.25 dB higher than the average output power of IEEE 802.11a.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) No new 5 GHz channels

### (B) Licensed Transmitter(s)

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02.

CDMA 1X Advanced technology was not required for SAR since the maximum output powers for 1x Advanced was not more than 0.25 dB higher than the maximum measured powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg.

This Device additionally supports LTE Band 2. All LTE bands share the same transmission path. LTE Band 2 was not evaluated for SAR since the supported frequency range falls within the LTE Band 25 supported frequency range.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 8 of 79                                                                          |                                        |



## 1.9 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01-D06 (1x Advanced, 2G/3G/4G, and Hotspot)
- FCC KDB Publication 248227 D01v01r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05 (General SAR Guidance)
- FCC KDB Publication 865664 D01-D02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D03-D04 (Wireless Charging Cover)
- April 2013 TCB Workshop Notes (IEEE 802.11ac)

## 1.10 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

|                   | Head Serial Number | Head Serial Number (reduced power) | Body-Worn Serial Number | Hotspot Serial Number |
|-------------------|--------------------|------------------------------------|-------------------------|-----------------------|
| Cell. CDMA/EVDO   | 32EF0              | -                                  | 32EF0                   | 32EF0                 |
| PCS CDMA/EVDO     | 32EC6              | 3R725                              | 32EF0                   | 3R725                 |
| LTE Band 12       | 32EC6              | -                                  | 32EF0                   | 32EF0                 |
| LTE Band 4 (AWS)  | 32EC6              | -                                  | 32EC6                   | 32EC6                 |
| LTE Band 25 (PCS) | 32EC6              | -                                  | 32E32                   | 32E32                 |
| 2.4 GHz WLAN      | -                  | 328C6                              | 00F05                   | 00F05                 |
| 5 GHz WLAN        | -                  | 31F35                              | 32712, 15ECE            | 32712, 15ECE          |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 9 of 79                                                                          |                                        |

## 2

## LTE INFORMATION

| LTE Information                                                                                                   |                                         |                |                |
|-------------------------------------------------------------------------------------------------------------------|-----------------------------------------|----------------|----------------|
| FCC ID                                                                                                            | A3LSMG900R7                             |                |                |
| Form Factor                                                                                                       | Portable Handset                        |                |                |
| Frequency Range of each LTE transmission band                                                                     | LTE Band 12 (701.5 - 713.5 MHz)         |                |                |
|                                                                                                                   | LTE Band 4 (AWS) (1712.5 - 1752.5 MHz)  |                |                |
|                                                                                                                   | LTE Band 2 (PCS) (1852.5 - 1907.5 MHz)  |                |                |
|                                                                                                                   | LTE Band 25 (PCS) (1852.5 - 1912.5 MHz) |                |                |
| Channel Bandwidths                                                                                                | LTE Band 12: 5 MHz, 10 MHz              |                |                |
|                                                                                                                   | LTE Band 4 (AWS): 5 MHz, 10 MHz         |                |                |
|                                                                                                                   | LTE Band 2 (PCS): 5 MHz, 10 MHz         |                |                |
|                                                                                                                   | LTE Band 25 (PCS): 5 MHz, 10 MHz        |                |                |
| Channel Numbers and Frequencies (MHz)                                                                             | Low                                     | Mid            | High           |
| LTE Band 12: 5 MHz                                                                                                | 701.5 (23035)                           | 707.5 (23095)  | 713.5 (23155)  |
| LTE Band 12: 10 MHz                                                                                               | 704 (23060)                             | 707.5 (23095)  | 711 (23130)    |
| LTE Band 4 (AWS): 5 MHz                                                                                           | 1712.5 (19975)                          | 1732.5 (20175) | 1752.5 (20375) |
| LTE Band 4 (AWS): 10 MHz                                                                                          | 1715 (20000)                            | 1732.5 (20175) | 1750 (20350)   |
| LTE Band 2 (PCS): 5 MHz                                                                                           | 1852.5 (18625)                          | 1880 (18900)   | 1907.5 (19175) |
| LTE Band 2 (PCS): 10 MHz                                                                                          | 1855 (18650)                            | 1880 (18900)   | 1905 (19150)   |
| LTE Band 25 (PCS): 5 MHz                                                                                          | 1852.5 (26065)                          | 1882.5 (26365) | 1912.5 (26665) |
| LTE Band 25 (PCS): 10 MHz                                                                                         | 1855 (26090)                            | 1882.5 (26365) | 1910 (26640)   |
| UE Category                                                                                                       | 3                                       |                |                |
| Modulations Supported in UL                                                                                       | QPSK, 16QAM                             |                |                |
| LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided) | YES                                     |                |                |
| A-MPR (Additional MPR) disabled for SAR Testing?                                                                  | YES                                     |                |                |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 10 of 79                                                                         |                                        |

### 3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

#### 3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1**  
**SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dv} \right)$$

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- $\sigma$  = conductivity of the tissue-simulating material (S/m)
- $\rho$  = mass density of the tissue-simulating material ( $\text{kg/m}^3$ )
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 11 of 79                                                                         |                                        |

## 4 DOSIMETRIC ASSESSMENT

### 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




**Figure 4-1**  
**Sample SAR Area**  
**Scan**

**Table 4-1**  
**Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01\***

| Frequency | Maximum Area Scan Resolution (mm)<br>( $\Delta x_{\text{area}}, \Delta y_{\text{area}}$ ) | Maximum Zoom Scan Resolution (mm)<br>( $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$ ) | Maximum Zoom Scan Spatial Resolution (mm) |                             |                                      | Minimum Zoom Scan Volume (mm)<br>(x,y,z) |
|-----------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------|-----------------------------|--------------------------------------|------------------------------------------|
|           |                                                                                           |                                                                                           | Uniform Grid                              | Graded Grid                 |                                      |                                          |
|           |                                                                                           |                                                                                           |                                           | $\Delta z_{\text{zoom}}(n)$ | $\Delta z_{\text{zoom}}(1)^*$        |                                          |
| ≤ 2 GHz   | ≤ 15                                                                                      | ≤ 8                                                                                       | ≤ 5                                       | ≤ 4                         | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 30                                     |
| 2-3 GHz   | ≤ 12                                                                                      | ≤ 5                                                                                       | ≤ 5                                       | ≤ 4                         | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 30                                     |
| 3-4 GHz   | ≤ 12                                                                                      | ≤ 5                                                                                       | ≤ 4                                       | ≤ 3                         | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 28                                     |
| 4-5 GHz   | ≤ 10                                                                                      | ≤ 4                                                                                       | ≤ 3                                       | ≤ 2.5                       | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 25                                     |
| 5-6 GHz   | ≤ 10                                                                                      | ≤ 4                                                                                       | ≤ 2                                       | ≤ 2                         | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 22                                     |

\*Also compliant to IEEE 1528-2013 Table 6

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 12 of 79                                                                         |                                        |

## 5

## DEFINITION OF REFERENCE POINTS

### 5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




**Figure 5-1**  
Close-Up Side view  
of ERP

### 5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



**Figure 5-2**  
Front, back and side view of SAM Twin Phantom




**Figure 5-3**  
Handset Vertical Center & Horizontal Line Reference Points

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 13 of 79                          |

## 6 TEST CONFIGURATION POSITIONS FOR HANDSETS

### 6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ .

### 6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

### 6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 14 of 79                                                                         |                                        |





## 6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-5). Per FCC KDB Publication 648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v05 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2 \text{ W/kg}$ , the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




**Figure 6-5**  
**Sample Body-Worn Diagram**

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

## 6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 44798 D01v05 should be applied to determine SAR test requirements.

Per KDB Publication 44798 D01v05, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 16 of 79                                                                         |                                        |



## 6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v01 where SAR test considerations for handsets ( $L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$ ) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 17 of 79                                                                         |                                        |

## 7 RF EXPOSURE LIMITS

### 7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1**  
**SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

| HUMAN EXPOSURE LIMITS                                               |                                                                           |                                                                   |
|---------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------|
|                                                                     | UNCONTROLLED ENVIRONMENT<br><i>General Population</i><br>(W/kg) or (mW/g) | CONTROLLED ENVIRONMENT<br><i>Occupational</i><br>(W/kg) or (mW/g) |
| <b>Peak Spatial Average SAR</b><br>Head                             | 1.6                                                                       | 8.0                                                               |
| <b>Whole Body SAR</b>                                               | 0.08                                                                      | 0.4                                                               |
| <b>Peak Spatial Average SAR</b><br>Hands, Feet, Ankle, Wrists, etc. | 4.0                                                                       | 20                                                                |

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 18 of 79                                                                         |                                        |

## 8 FCC MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

### 8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

### 8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

### 8.3 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

#### 8.3.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by "SAR Measurement Procedures for 3G Devices" v02, October 2007. Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the "All Up" condition.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH<sub>0</sub> and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH<sub>0</sub> data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 19 of 79                                                                         |                                        |

**Table 8-1**  
**Parameters for Max. Power for RC1**

| Parameter                    | Units        | Value |
|------------------------------|--------------|-------|
| $I_{or}$                     | dBm/1.23 MHz | -104  |
| $\frac{Pilot E_c}{I_{or}}$   | dB           | -7    |
| $\frac{Traffic E_c}{I_{or}}$ | dB           | -7.4  |

**Table 8-2**  
**Parameters for Max. Power for RC3**

| Parameter                    | Units        | Value |
|------------------------------|--------------|-------|
| $I_{or}$                     | dBm/1.23 MHz | -86   |
| $\frac{Pilot E_c}{I_{or}}$   | dB           | -7    |
| $\frac{Traffic E_c}{I_{or}}$ | dB           | -7.4  |

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

### 8.3.2 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers were measured using SO75 with RC8 on the uplink and RC11 on the downlink per KDB Publication 941225 D02v02. Smart blanking was disabled for all measurements. The EUT was configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers were measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

Based on the maximum output power measured for 1x Advanced, SAR is required for 1x advanced when if the maximum output for 1x Advanced is more than 0.25 dB higher than the maximum measured for 1x. Also, if the measured SAR in any 1x mode exposure conditions (head, body etc.) is larger than 1.2 W/kg, the highest of those configurations above 1.2 W/kg for each exposure condition in 1x Advanced has to be repeated. All measured SAR in 1x mode higher than 1.5 W/kg must be repeated for 1x Advanced.

### 8.3.3 Head SAR Measurements

SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

Head SAR was additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.3.5 for EVDO Rev. A configuration parameters.

### 8.3.4 Body SAR Measurements

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCH<sub>n</sub>) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + SCH<sub>n</sub>) with FCH at full rate and SCH<sub>0</sub> enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts. Body SAR was measured using TDSO / SO32 with power control bits in the “All Up”

Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 20 of 79                                                                         |                                        |

### 8.3.5 Handsets with EVDO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev. 0 is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR for EV-DO is not required. Otherwise, SAR for Rev. 0 is measured on the maximum output channel at 153.6 kbps using the body exposure configuration that results in the highest SAR for that channel in RC3. SAR for Rev. A is not required when the maximum average output of each channel is less than that measured in Rev. 0 or less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots would be configured in the downlink for both Rev. 0 and Rev. A.

### 8.3.6 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 per KDB Publication 941225 D01 procedures for “1x Ev-Do data Devices”. SAR for Subtype 2 Physical layer configurations is not required for Rev. A when the maximum average output of each RF channels is less than that measured in Subtype 0/1 Physical layer configurations. Otherwise, SAR is measured on the maximum output channel for Rev. A using the exposure configuration that results in the highest SAR for the RF channels in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

SAR is not required for 1x RTT for Ev-Do devices that also support 1x RTT voice and/or data operations, when the maximum average output of each channel is less than 1/4 dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0. Otherwise, CDMA “Body-SAR Measurement” procedures for “CDMA 2000 1x Handsets” were applied.

## 8.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### 8.4.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 8.4.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 21 of 79                                                                         |                                        |

### 8.4.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

### 8.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r01:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $< 0.8$  W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to  $\frac{1}{2}$  dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.

## 8.5 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g/n /ac transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v01r02 for more details.

### 8.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

### 8.5.2 Frequency Channel Configurations [24]

For 2.4 GHz, the highest average RF output power channel between the low, mid and high channel at the lowest data rate was selected for SAR evaluation in 802.11b mode. 802.11g/n modes and higher data rates for 802.11b were additionally evaluated for SAR if the output power of the respective mode was 0.25 dB or higher than the powers of the SAR configurations tested in the 802.11b mode.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 22 of 79                                                                         |                                        |



For 5 GHz, the highest average RF output power channel across the default test channels at the lowest data rate was selected for SAR evaluation in 802.11a. When the adjacent channels are higher in power than the default channels, these “required channels” were considered instead of the default channels for SAR testing. 802.11n modes and higher data rates for 802.11a/n were evaluated only if the respective mode was higher than 0.25 dB or more than the 802.11a mode. 802.11ac SAR was evaluated for highest 802.11a configuration in each 5 GHz band and each exposure condition. 802.11ac modes were additionally evaluated for SAR if the output power for the respective mode was more than 0.25 dB higher than powers of 802.11a modes.

If the maximum extrapolated peak SAR of the zoom scan for the highest output channel was less than 1.6 W/kg and if the 1g averaged SAR was less than 0.8 W/kg, SAR testing was not required for the other test channels in the band.

### 8.5.3 MIMO SAR Considerations

Per KDB 248227, SAR for MIMO was measured with both antennas transmitting simultaneously and was evaluated independently of SISO operation. For 2.4 GHz MIMO, 802.11n was evaluated. For 5 GHz MIMO, 20 MHz Bandwidth 802.11n was evaluated. Additional evaluations for 40 MHz bandwidth 802.11n and 802.11ac were not required since the maximum allowed output power was not higher than 802.11n 20 MHz bandwidth.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 23 of 79                                                                         |                                        |



## 9 RF CONDUCTED POWERS

### 9.1 CDMA Conducted Powers

**Table 9-1**  
**Maximum CDMA Conducted Powers with Hotspot Inactive**

| Band     | Channel | Frequency | SO55 [dBm] | SO55 [dBm] | SO75 [dBm] | TDSO SO32 [dBm] | TDSO SO32 [dBm] | 1x EvDO Rev. 0 [dBm] | 1x EvDO Rev. A [dBm] |
|----------|---------|-----------|------------|------------|------------|-----------------|-----------------|----------------------|----------------------|
|          | F-RC    | MHz       | RC1        | RC3        | RC11       | FCH+SCH         | FCH             | (RTAP)               | (RETAP)              |
| Cellular | 1013    | 824.7     | 24.43      | 24.35      | 24.45      | 24.32           | 24.33           | 24.40                | 24.39                |
|          | 384     | 836.52    | 24.48      | 24.40      | 24.51      | 24.39           | 24.37           | 24.44                | 24.40                |
|          | 777     | 848.31    | 24.67      | 24.56      | 24.69      | 24.55           | 24.56           | 24.61                | 24.58                |
| PCS      | 25      | 1851.25   | 24.63      | 24.54      | 24.60      | 24.53           | 24.50           | 24.55                | 24.51                |
|          | 600     | 1880      | 24.59      | 24.49      | 24.56      | 24.49           | 24.46           | 24.52                | 24.46                |
|          | 1175    | 1908.75   | 24.65      | 24.55      | 24.61      | 24.54           | 24.53           | 24.54                | 24.52                |

**Table 9-2**  
**Reduced CDMA Conducted Powers with Hotspot Active**

| Band | Channel | Rule Part | Frequency | SO55 [dBm] | SO55 [dBm] | SO75 [dBm] | TDSO SO32 [dBm] | TDSO SO32 [dBm] | 1x EvDO Rev. 0 [dBm] | 1x EvDO Rev. A [dBm] |
|------|---------|-----------|-----------|------------|------------|------------|-----------------|-----------------|----------------------|----------------------|
|      | F-RC    |           | MHz       | RC1        | RC3        | RC11       | FCH+SCH         | FCH             | (RTAP)               | (RETAP)              |
| PCS  | 25      | 24E       | 1851.25   | 22.63      | 22.70      | 22.67      | 22.71           | 22.72           | 22.70                | 22.68                |
|      | 600     | 24E       | 1880      | 22.16      | 22.29      | 22.30      | 22.27           | 22.32           | 22.31                | 22.28                |
|      | 1175    | 24E       | 1908.75   | 22.51      | 22.56      | 22.60      | 22.54           | 22.56           | 22.55                | 22.52                |

Note: RC1 is only applicable for IS-95 compatibility.

Per KDB Publication 941225 D01v02:

1. Head SAR was tested with SO55 RC3. SO55 RC1 was not required since the average output power was not more than 0.25 dB than the SO55 RC3 powers.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. Ev-Do and TDSO / SO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO / SO32 FCH only powers.
3. Hotspot SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. If the average output power of Subtype 2 for Rev. A is less than the Rev. 0 power levels, then Rev. A SAR is not required. Otherwise, SAR is measured on the maximum output channel for Rev. A using the exposure configuration that results in the highest SAR for that RF channel in Rev. 0.
4. CDMA 1x-RTT SAR was additionally required to be evaluated for Hotspot exposure conditions to support simultaneous transmission capabilities.
5. Head SAR was additionally evaluated with EVDO Rev. A to determine compliance for held-to-ear VoIP operations.

Per KDB Publication 941225 D02v02:

1. CDMA 1X Advanced technology was not required for SAR since the maximum output powers for 1x Advanced was not more than 0.25 dB higher than the maximum measured powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg. See Section 8.3.2 for 1x Advanced test set up.



**Figure 9-1**  
**Power Measurement Setup**

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 24 of 79                                                                         |                                 |

## 9.2 LTE Conducted Powers

### 9.2.1 LTE Band 12

**Table 9-3**  
**LTE Band 12 Conducted Powers - 10 MHz Bandwidth**

|     | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Mid | 707.5           | 23095   | 10              | QPSK       | 1       | 0         | 23.08                 | 0                         | 0        |
|     | 707.5           | 23095   | 10              | QPSK       | 1       | 25        | 23.03                 | 0                         | 0        |
|     | 707.5           | 23095   | 10              | QPSK       | 1       | 49        | 23.04                 | 0                         | 0        |
|     | 707.5           | 23095   | 10              | QPSK       | 25      | 0         | 22.02                 | 0-1                       | 1        |
|     | 707.5           | 23095   | 10              | QPSK       | 25      | 12        | 21.98                 | 0-1                       | 1        |
|     | 707.5           | 23095   | 10              | QPSK       | 25      | 25        | 21.97                 | 0-1                       | 1        |
|     | 707.5           | 23095   | 10              | QPSK       | 50      | 0         | 21.93                 | 0-1                       | 1        |
|     | 707.5           | 23095   | 10              | 16QAM      | 1       | 0         | 21.87                 | 0-1                       | 1        |
|     | 707.5           | 23095   | 10              | 16QAM      | 1       | 25        | 22.03                 | 0-1                       | 1        |
|     | 707.5           | 23095   | 10              | 16QAM      | 1       | 49        | 21.87                 | 0-1                       | 1        |
|     | 707.5           | 23095   | 10              | 16QAM      | 25      | 0         | 21.01                 | 0-2                       | 2        |
|     | 707.5           | 23095   | 10              | 16QAM      | 25      | 12        | 20.88                 | 0-2                       | 2        |
|     | 707.5           | 23095   | 10              | 16QAM      | 25      | 25        | 20.90                 | 0-2                       | 2        |
|     | 707.5           | 23095   | 10              | 16QAM      | 50      | 0         | 20.84                 | 0-2                       | 2        |

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-4**  
**LTE Band 12 Conducted Powers - 5 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 701.5           | 23035   | 5               | QPSK       | 1       | 0         | 23.24                 | 0                         | 0        |
|      | 701.5           | 23035   | 5               | QPSK       | 1       | 12        | 23.22                 | 0                         | 0        |
|      | 701.5           | 23035   | 5               | QPSK       | 1       | 24        | 23.18                 | 0                         | 0        |
|      | 701.5           | 23035   | 5               | QPSK       | 12      | 0         | 22.05                 | 0-1                       | 1        |
|      | 701.5           | 23035   | 5               | QPSK       | 12      | 6         | 22.16                 | 0-1                       | 1        |
|      | 701.5           | 23035   | 5               | QPSK       | 12      | 13        | 22.06                 | 0-1                       | 1        |
|      | 701.5           | 23035   | 5               | QPSK       | 25      | 0         | 22.00                 | 0-1                       | 1        |
|      | 701.5           | 23035   | 5               | 16-QAM     | 1       | 0         | 22.20                 | 0-1                       | 1        |
|      | 701.5           | 23035   | 5               | 16-QAM     | 1       | 12        | 22.27                 | 0-1                       | 1        |
|      | 701.5           | 23035   | 5               | 16-QAM     | 1       | 24        | 22.16                 | 0-1                       | 1        |
|      | 701.5           | 23035   | 5               | 16-QAM     | 12      | 0         | 21.00                 | 0-2                       | 2        |
|      | 701.5           | 23035   | 5               | 16-QAM     | 12      | 6         | 21.11                 | 0-2                       | 2        |
|      | 701.5           | 23035   | 5               | 16-QAM     | 12      | 13        | 20.95                 | 0-2                       | 2        |
|      | 701.5           | 23035   | 5               | 16-QAM     | 25      | 0         | 21.03                 | 0-2                       | 2        |
|      | 707.5           | 23095   | 5               | QPSK       | 1       | 0         | 23.18                 | 0                         | 0        |
| Mid  | 707.5           | 23095   | 5               | QPSK       | 1       | 12        | 23.07                 | 0                         | 0        |
|      | 707.5           | 23095   | 5               | QPSK       | 1       | 24        | 23.11                 | 0                         | 0        |
|      | 707.5           | 23095   | 5               | QPSK       | 12      | 0         | 21.98                 | 0-1                       | 1        |
|      | 707.5           | 23095   | 5               | QPSK       | 12      | 6         | 21.94                 | 0-1                       | 1        |
|      | 707.5           | 23095   | 5               | QPSK       | 12      | 13        | 21.99                 | 0-1                       | 1        |
|      | 707.5           | 23095   | 5               | QPSK       | 25      | 0         | 21.96                 | 0-1                       | 1        |
|      | 707.5           | 23095   | 5               | 16-QAM     | 1       | 0         | 22.02                 | 0-1                       | 1        |
|      | 707.5           | 23095   | 5               | 16-QAM     | 1       | 12        | 22.10                 | 0-1                       | 1        |
|      | 707.5           | 23095   | 5               | 16-QAM     | 1       | 24        | 22.08                 | 0-1                       | 1        |
|      | 707.5           | 23095   | 5               | 16-QAM     | 12      | 0         | 20.87                 | 0-2                       | 2        |
|      | 707.5           | 23095   | 5               | 16-QAM     | 12      | 6         | 20.82                 | 0-2                       | 2        |
|      | 707.5           | 23095   | 5               | 16-QAM     | 12      | 13        | 20.93                 | 0-2                       | 2        |
|      | 707.5           | 23095   | 5               | 16-QAM     | 25      | 0         | 20.91                 | 0-2                       | 2        |
| High | 713.5           | 23155   | 5               | QPSK       | 1       | 0         | 23.16                 | 0                         | 0        |
|      | 713.5           | 23155   | 5               | QPSK       | 1       | 12        | 23.11                 | 0                         | 0        |
|      | 713.5           | 23155   | 5               | QPSK       | 1       | 24        | 22.91                 | 0                         | 0        |
|      | 713.5           | 23155   | 5               | QPSK       | 12      | 0         | 21.93                 | 0-1                       | 1        |
|      | 713.5           | 23155   | 5               | QPSK       | 12      | 6         | 21.93                 | 0-1                       | 1        |
|      | 713.5           | 23155   | 5               | QPSK       | 12      | 13        | 21.86                 | 0-1                       | 1        |
|      | 713.5           | 23155   | 5               | QPSK       | 25      | 0         | 21.84                 | 0-1                       | 1        |
|      | 713.5           | 23155   | 5               | 16-QAM     | 1       | 0         | 21.92                 | 0-1                       | 1        |
|      | 713.5           | 23155   | 5               | 16-QAM     | 1       | 12        | 21.78                 | 0-1                       | 1        |
|      | 713.5           | 23155   | 5               | 16-QAM     | 1       | 24        | 21.94                 | 0-1                       | 1        |
|      | 713.5           | 23155   | 5               | 16-QAM     | 12      | 0         | 20.82                 | 0-2                       | 2        |
|      | 713.5           | 23155   | 5               | 16-QAM     | 12      | 6         | 20.69                 | 0-2                       | 2        |
|      | 713.5           | 23155   | 5               | 16-QAM     | 12      | 13        | 20.70                 | 0-2                       | 2        |
|      | 713.5           | 23155   | 5               | 16-QAM     | 25      | 0         | 20.78                 | 0-2                       | 2        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 25 of 79                                                                         |                                 |

## 9.2.2 LTE Band 4 (AWS)

Table 9-5  
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

| Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low             | 1715    | 20000           | 10         | QPSK    | 1         | 0                     | 23.50                     | 0        |
|                 | 1715    | 20000           | 10         | QPSK    | 1         | 25                    | 23.47                     | 0        |
|                 | 1715    | 20000           | 10         | QPSK    | 1         | 49                    | 23.43                     | 0        |
|                 | 1715    | 20000           | 10         | QPSK    | 25        | 0                     | 22.36                     | 0-1      |
|                 | 1715    | 20000           | 10         | QPSK    | 25        | 12                    | 22.43                     | 0-1      |
|                 | 1715    | 20000           | 10         | QPSK    | 25        | 25                    | 22.31                     | 0-1      |
|                 | 1715    | 20000           | 10         | QPSK    | 50        | 0                     | 22.40                     | 0-1      |
|                 | 1715    | 20000           | 10         | 16QAM   | 1         | 0                     | 22.46                     | 0-1      |
|                 | 1715    | 20000           | 10         | 16QAM   | 1         | 25                    | 22.44                     | 0-1      |
|                 | 1715    | 20000           | 10         | 16QAM   | 1         | 49                    | 22.34                     | 0-1      |
|                 | 1715    | 20000           | 10         | 16QAM   | 25        | 0                     | 21.22                     | 0-2      |
|                 | 1715    | 20000           | 10         | 16QAM   | 25        | 12                    | 21.32                     | 0-2      |
|                 | 1715    | 20000           | 10         | 16QAM   | 25        | 25                    | 21.27                     | 0-2      |
|                 | 1715    | 20000           | 10         | 16QAM   | 50        | 0                     | 21.28                     | 0-2      |
|                 | 1715    | 20000           | 10         | 16QAM   | 50        | 0                     | 21.28                     | 0-2      |
| Mid             | 1732.5  | 20175           | 10         | QPSK    | 1         | 0                     | 23.40                     | 0        |
|                 | 1732.5  | 20175           | 10         | QPSK    | 1         | 25                    | 23.34                     | 0        |
|                 | 1732.5  | 20175           | 10         | QPSK    | 1         | 49                    | 23.42                     | 0        |
|                 | 1732.5  | 20175           | 10         | QPSK    | 25        | 0                     | 22.34                     | 0-1      |
|                 | 1732.5  | 20175           | 10         | QPSK    | 25        | 12                    | 22.22                     | 0-1      |
|                 | 1732.5  | 20175           | 10         | QPSK    | 25        | 25                    | 22.21                     | 0-1      |
|                 | 1732.5  | 20175           | 10         | QPSK    | 50        | 0                     | 22.24                     | 0-1      |
|                 | 1732.5  | 20175           | 10         | 16QAM   | 1         | 0                     | 22.33                     | 0-1      |
|                 | 1732.5  | 20175           | 10         | 16QAM   | 1         | 25                    | 22.16                     | 0-1      |
|                 | 1732.5  | 20175           | 10         | 16QAM   | 1         | 49                    | 22.41                     | 0-1      |
|                 | 1732.5  | 20175           | 10         | 16QAM   | 25        | 0                     | 21.20                     | 0-2      |
|                 | 1732.5  | 20175           | 10         | 16QAM   | 25        | 12                    | 21.22                     | 0-2      |
|                 | 1732.5  | 20175           | 10         | 16QAM   | 25        | 25                    | 21.18                     | 0-2      |
|                 | 1732.5  | 20175           | 10         | 16QAM   | 50        | 0                     | 21.26                     | 0-2      |
|                 | 1732.5  | 20175           | 10         | 16QAM   | 50        | 0                     | 21.26                     | 0-2      |
| High            | 1750    | 20350           | 10         | QPSK    | 1         | 0                     | 23.49                     | 0        |
|                 | 1750    | 20350           | 10         | QPSK    | 1         | 25                    | 23.33                     | 0        |
|                 | 1750    | 20350           | 10         | QPSK    | 1         | 49                    | 23.31                     | 0        |
|                 | 1750    | 20350           | 10         | QPSK    | 25        | 0                     | 22.30                     | 0-1      |
|                 | 1750    | 20350           | 10         | QPSK    | 25        | 12                    | 22.24                     | 0-1      |
|                 | 1750    | 20350           | 10         | QPSK    | 25        | 25                    | 22.17                     | 0-1      |
|                 | 1750    | 20350           | 10         | QPSK    | 50        | 0                     | 22.33                     | 0-1      |
|                 | 1750    | 20350           | 10         | 16QAM   | 1         | 0                     | 22.46                     | 0-1      |
|                 | 1750    | 20350           | 10         | 16QAM   | 1         | 25                    | 22.22                     | 0-1      |
|                 | 1750    | 20350           | 10         | 16QAM   | 1         | 49                    | 22.36                     | 0-1      |
|                 | 1750    | 20350           | 10         | 16QAM   | 25        | 0                     | 21.27                     | 0-2      |
|                 | 1750    | 20350           | 10         | 16QAM   | 25        | 12                    | 21.18                     | 0-2      |
|                 | 1750    | 20350           | 10         | 16QAM   | 25        | 25                    | 21.14                     | 0-2      |
|                 | 1750    | 20350           | 10         | 16QAM   | 50        | 0                     | 21.17                     | 0-2      |
|                 | 1750    | 20350           | 10         | 16QAM   | 50        | 0                     | 21.17                     | 0-2      |

Table 9-6  
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

| Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low             | 1712.5  | 19975           | 5          | QPSK    | 1         | 0                     | 23.43                     | 0        |
|                 | 1712.5  | 19975           | 5          | QPSK    | 1         | 12                    | 23.47                     | 0        |
|                 | 1712.5  | 19975           | 5          | QPSK    | 1         | 24                    | 23.49                     | 0        |
|                 | 1712.5  | 19975           | 5          | QPSK    | 12        | 0                     | 22.37                     | 0-1      |
|                 | 1712.5  | 19975           | 5          | QPSK    | 12        | 6                     | 22.26                     | 0-1      |
|                 | 1712.5  | 19975           | 5          | QPSK    | 12        | 13                    | 22.32                     | 0-1      |
|                 | 1712.5  | 19975           | 5          | QPSK    | 25        | 0                     | 22.39                     | 0-1      |
|                 | 1712.5  | 19975           | 5          | 16-QAM  | 1         | 0                     | 22.41                     | 0-1      |
|                 | 1712.5  | 19975           | 5          | 16-QAM  | 1         | 12                    | 22.20                     | 0-1      |
|                 | 1712.5  | 19975           | 5          | 16-QAM  | 1         | 24                    | 22.36                     | 0-1      |
|                 | 1712.5  | 19975           | 5          | 16-QAM  | 12        | 0                     | 21.24                     | 0-2      |
|                 | 1712.5  | 19975           | 5          | 16-QAM  | 12        | 6                     | 21.11                     | 0-2      |
|                 | 1712.5  | 19975           | 5          | 16-QAM  | 12        | 13                    | 21.15                     | 0-2      |
|                 | 1712.5  | 19975           | 5          | 16-QAM  | 25        | 0                     | 21.31                     | 0-2      |
|                 | 1712.5  | 19975           | 5          | 16-QAM  | 25        | 0                     | 21.31                     | 0-2      |
| Mid             | 1732.5  | 20175           | 5          | QPSK    | 1         | 0                     | 23.40                     | 0        |
|                 | 1732.5  | 20175           | 5          | QPSK    | 1         | 12                    | 23.34                     | 0        |
|                 | 1732.5  | 20175           | 5          | QPSK    | 1         | 24                    | 23.33                     | 0        |
|                 | 1732.5  | 20175           | 5          | QPSK    | 12        | 0                     | 22.18                     | 0-1      |
|                 | 1732.5  | 20175           | 5          | QPSK    | 12        | 6                     | 22.16                     | 0-1      |
|                 | 1732.5  | 20175           | 5          | QPSK    | 12        | 13                    | 22.24                     | 0-1      |
|                 | 1732.5  | 20175           | 5          | QPSK    | 25        | 0                     | 22.17                     | 0-1      |
|                 | 1732.5  | 20175           | 5          | 16-QAM  | 1         | 0                     | 22.37                     | 0-1      |
|                 | 1732.5  | 20175           | 5          | 16-QAM  | 1         | 12                    | 22.08                     | 0-1      |
|                 | 1732.5  | 20175           | 5          | 16-QAM  | 1         | 24                    | 22.29                     | 0-1      |
|                 | 1732.5  | 20175           | 5          | 16-QAM  | 12        | 0                     | 21.18                     | 0-2      |
|                 | 1732.5  | 20175           | 5          | 16-QAM  | 12        | 6                     | 21.08                     | 0-2      |
|                 | 1732.5  | 20175           | 5          | 16-QAM  | 12        | 13                    | 21.06                     | 0-2      |
|                 | 1732.5  | 20175           | 5          | 16-QAM  | 25        | 0                     | 21.01                     | 0-2      |
|                 | 1732.5  | 20175           | 5          | 16-QAM  | 25        | 0                     | 21.01                     | 0-2      |
| High            | 1752.5  | 20375           | 5          | QPSK    | 1         | 0                     | 23.49                     | 0        |
|                 | 1752.5  | 20375           | 5          | QPSK    | 1         | 12                    | 23.34                     | 0        |
|                 | 1752.5  | 20375           | 5          | QPSK    | 1         | 24                    | 23.39                     | 0        |
|                 | 1752.5  | 20375           | 5          | QPSK    | 12        | 0                     | 22.28                     | 0-1      |
|                 | 1752.5  | 20375           | 5          | QPSK    | 12        | 6                     | 22.16                     | 0-1      |
|                 | 1752.5  | 20375           | 5          | QPSK    | 12        | 13                    | 22.25                     | 0-1      |
|                 | 1752.5  | 20375           | 5          | QPSK    | 25        | 0                     | 22.18                     | 0-1      |
|                 | 1752.5  | 20375           | 5          | 16-QAM  | 1         | 0                     | 22.50                     | 0-1      |
|                 | 1752.5  | 20375           | 5          | 16-QAM  | 1         | 12                    | 22.10                     | 0-1      |
|                 | 1752.5  | 20375           | 5          | 16-QAM  | 1         | 24                    | 22.05                     | 0-1      |
|                 | 1752.5  | 20375           | 5          | 16-QAM  | 12        | 0                     | 21.19                     | 0-2      |
|                 | 1752.5  | 20375           | 5          | 16-QAM  | 12        | 6                     | 21.11                     | 0-2      |
|                 | 1752.5  | 20375           | 5          | 16-QAM  | 12        | 13                    | 21.10                     | 0-2      |
|                 | 1752.5  | 20375           | 5          | 16-QAM  | 25        | 0                     | 21.12                     | 0-2      |
|                 | 1752.5  | 20375           | 5          | 16-QAM  | 25        | 0                     | 21.12                     | 0-2      |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 26 of 79                   |

## 9.2.3

## LTE Band 2 / 25 (PCS)

**Table 9-7**  
**LTE Band 2 / 25 (PCS) Conducted Powers - 10 MHz Bandwidth**

|        | Operating Bands | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|--------|-----------------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low    | 2, 25           | 1855            | 26090   | 10              | QPSK       | 1       | 0         | 22.71                 | 0                         | 0        |
|        |                 | 1855            | 26090   | 10              | QPSK       | 1       | 25        | 23.21                 | 0                         | 0        |
|        |                 | 1855            | 26090   | 10              | QPSK       | 1       | 49        | 23.06                 | 0                         | 0        |
|        |                 | 1855            | 26090   | 10              | QPSK       | 25      | 0         | 22.02                 | 0-1                       | 1        |
|        |                 | 1855            | 26090   | 10              | QPSK       | 25      | 12        | 22.09                 | 0-1                       | 1        |
|        |                 | 1855            | 26090   | 10              | QPSK       | 25      | 25        | 22.09                 | 0-1                       | 1        |
|        |                 | 1855            | 26090   | 10              | QPSK       | 50      | 0         | 22.05                 | 0-1                       | 1        |
|        |                 | 1855            | 26090   | 10              | 16QAM      | 1       | 0         | 22.08                 | 0-1                       | 1        |
|        |                 | 1855            | 26090   | 10              | 16QAM      | 1       | 25        | 21.92                 | 0-1                       | 1        |
|        |                 | 1855            | 26090   | 10              | 16QAM      | 1       | 49        | 22.00                 | 0-1                       | 1        |
|        |                 | 1855            | 26090   | 10              | 16QAM      | 25      | 0         | 21.03                 | 0-2                       | 2        |
|        |                 | 1855            | 26090   | 10              | 16QAM      | 25      | 12        | 21.04                 | 0-2                       | 2        |
|        |                 | 1855            | 26090   | 10              | 16QAM      | 25      | 25        | 21.12                 | 0-2                       | 2        |
|        |                 | 1855            | 26090   | 10              | 16QAM      | 50      | 0         | 21.07                 | 0-2                       | 2        |
|        |                 | Mid             | 2, 25   | 1880.0          | 26340      | 10      | QPSK      | 1                     | 0                         | 23.12    |
| 1880.0 | 26340           |                 |         | 10              | QPSK       | 1       | 25        | 23.15                 | 0                         | 0        |
| 1880.0 | 26340           |                 |         | 10              | QPSK       | 1       | 49        | 23.22                 | 0                         | 0        |
| 1880.0 | 26340           |                 |         | 10              | QPSK       | 25      | 0         | 22.08                 | 0-1                       | 1        |
| 1880.0 | 26340           |                 |         | 10              | QPSK       | 25      | 12        | 22.09                 | 0-1                       | 1        |
| 1880.0 | 26340           |                 |         | 10              | QPSK       | 25      | 25        | 22.14                 | 0-1                       | 1        |
| 1880.0 | 26340           |                 |         | 10              | QPSK       | 50      | 0         | 22.14                 | 0-1                       | 1        |
| 1880.0 | 26340           |                 |         | 10              | 16QAM      | 1       | 0         | 22.00                 | 0-1                       | 1        |
| 1880.0 | 26340           |                 |         | 10              | 16QAM      | 1       | 25        | 21.98                 | 0-1                       | 1        |
| 1880.0 | 26340           |                 |         | 10              | 16QAM      | 1       | 49        | 22.12                 | 0-1                       | 1        |
| 1880.0 | 26340           |                 |         | 10              | 16QAM      | 25      | 0         | 21.12                 | 0-2                       | 2        |
| 1880.0 | 26340           |                 |         | 10              | 16QAM      | 25      | 12        | 21.14                 | 0-2                       | 2        |
| 1880.0 | 26340           |                 |         | 10              | 16QAM      | 25      | 25        | 21.11                 | 0-2                       | 2        |
| 1880.0 | 26340           |                 |         | 10              | 16QAM      | 50      | 0         | 21.11                 | 0-2                       | 2        |
| High   | 25              |                 |         | 1910            | 26640      | 10      | QPSK      | 1                     | 0                         | 23.35    |
|        |                 | 1910            | 26640   | 10              | QPSK       | 1       | 25        | 23.12                 | 0                         | 0        |
|        |                 | 1910            | 26640   | 10              | QPSK       | 1       | 49        | 23.10                 | 0                         | 0        |
|        |                 | 1910            | 26640   | 10              | QPSK       | 25      | 0         | 22.21                 | 0-1                       | 1        |
|        |                 | 1910            | 26640   | 10              | QPSK       | 25      | 12        | 22.11                 | 0-1                       | 1        |
|        |                 | 1910            | 26640   | 10              | QPSK       | 25      | 25        | 22.06                 | 0-1                       | 1        |
|        |                 | 1910            | 26640   | 10              | QPSK       | 50      | 0         | 22.18                 | 0-1                       | 1        |
|        |                 | 1910            | 26640   | 10              | 16QAM      | 1       | 0         | 22.31                 | 0-1                       | 1        |
|        |                 | 1910            | 26640   | 10              | 16QAM      | 1       | 25        | 22.16                 | 0-1                       | 1        |
|        |                 | 1910            | 26640   | 10              | 16QAM      | 1       | 49        | 22.23                 | 0-1                       | 1        |
|        |                 | 1910            | 26640   | 10              | 16QAM      | 25      | 0         | 21.22                 | 0-2                       | 2        |
|        |                 | 1910            | 26640   | 10              | 16QAM      | 25      | 12        | 21.21                 | 0-2                       | 2        |
|        |                 | 1910            | 26640   | 10              | 16QAM      | 25      | 25        | 21.23                 | 0-2                       | 2        |
|        |                 | 1910            | 26640   | 10              | 16QAM      | 50      | 0         | 21.16                 | 0-2                       | 2        |

**Table 9-8**  
**LTE Band 2 / 25 (PCS) Conducted Powers - 5 MHz Bandwidth**

|        | Operating Bands | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |   |   |
|--------|-----------------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|---|---|
| Low    | 2, 25           | 1852.5          | 26065   | 5               | QPSK       | 1       | 0         | 22.62                 | 0                         | 0        |   |   |
|        |                 | 1852.5          | 26065   | 5               | QPSK       | 1       | 12        | 22.79                 | 0                         | 0        |   |   |
|        |                 | 1852.5          | 26065   | 5               | QPSK       | 1       | 24        | 23.14                 | 0                         | 0        |   |   |
|        |                 | 1852.5          | 26065   | 5               | QPSK       | 12      | 0         | 21.69                 | 0-1                       | 1        |   |   |
|        |                 | 1852.5          | 26065   | 5               | QPSK       | 12      | 6         | 21.85                 | 0-1                       | 1        |   |   |
|        |                 | 1852.5          | 26065   | 5               | QPSK       | 12      | 13        | 22.16                 | 0-1                       | 1        |   |   |
|        |                 | 1852.5          | 26065   | 5               | QPSK       | 25      | 0         | 21.90                 | 0-1                       | 1        |   |   |
|        |                 | 1852.5          | 26065   | 5               | 16-QAM     | 1       | 0         | 21.88                 | 0-1                       | 1        |   |   |
|        |                 | 1852.5          | 26065   | 5               | 16-QAM     | 1       | 12        | 22.06                 | 0-1                       | 1        |   |   |
|        |                 | 1852.5          | 26065   | 5               | 16-QAM     | 1       | 24        | 21.93                 | 0-1                       | 1        |   |   |
|        |                 | 1852.5          | 26065   | 5               | 16-QAM     | 12      | 0         | 20.76                 | 0-2                       | 2        |   |   |
|        |                 | 1852.5          | 26065   | 5               | 16-QAM     | 12      | 6         | 20.84                 | 0-2                       | 2        |   |   |
|        |                 | 1852.5          | 26065   | 5               | 16-QAM     | 12      | 13        | 21.05                 | 0-2                       | 2        |   |   |
|        |                 | 1852.5          | 26065   | 5               | 16-QAM     | 25      | 0         | 20.88                 | 0-2                       | 2        |   |   |
|        |                 | 1880.0          | 26340   | 5               | QPSK       | 1       | 0         | 23.21                 | 0                         | 0        |   |   |
| Mid    | 2, 25           | 1880.0          | 26340   | 5               | QPSK       | 1       | 12        | 23.24                 | 0                         | 0        |   |   |
|        |                 | 1880.0          | 26340   | 5               | QPSK       | 1       | 24        | 23.26                 | 0                         | 0        |   |   |
|        |                 | 1880.0          | 26340   | 5               | QPSK       | 12      | 0         | 22.14                 | 0-1                       | 1        |   |   |
|        |                 | 1880.0          | 26340   | 5               | QPSK       | 12      | 6         | 22.13                 | 0-1                       | 1        |   |   |
|        |                 | 1880.0          | 26340   | 5               | QPSK       | 12      | 13        | 22.10                 | 0-1                       | 1        |   |   |
|        |                 | 1880.0          | 26340   | 5               | QPSK       | 25      | 0         | 22.06                 | 0-1                       | 1        |   |   |
|        |                 | 1880.0          | 26340   | 5               | 16-QAM     | 1       | 0         | 22.12                 | 0-1                       | 1        |   |   |
|        |                 | 1880.0          | 26340   | 5               | 16-QAM     | 1       | 12        | 22.11                 | 0-1                       | 1        |   |   |
|        |                 | 1880.0          | 26340   | 5               | 16-QAM     | 1       | 24        | 22.16                 | 0-1                       | 1        |   |   |
|        |                 | 1880.0          | 26340   | 5               | 16-QAM     | 12      | 0         | 21.06                 | 0-2                       | 2        |   |   |
|        |                 | 1880.0          | 26340   | 5               | 16-QAM     | 12      | 6         | 21.10                 | 0-2                       | 2        |   |   |
|        |                 | 1880.0          | 26340   | 5               | 16-QAM     | 12      | 13        | 21.01                 | 0-2                       | 2        |   |   |
|        |                 | 1880.0          | 26340   | 5               | 16-QAM     | 25      | 0         | 21.19                 | 0-2                       | 2        |   |   |
|        |                 | High            | 25      | 1912.5          | 26665      | 5       | QPSK      | 1                     | 0                         | 23.12    | 0 | 0 |
|        |                 |                 |         | 1912.5          | 26665      | 5       | QPSK      | 1                     | 12                        | 23.08    | 0 | 0 |
| 1912.5 | 26665           |                 |         | 5               | QPSK       | 1       | 24        | 23.07                 | 0                         | 0        |   |   |
| 1912.5 | 26665           |                 |         | 5               | QPSK       | 12      | 0         | 22.17                 | 0-1                       | 1        |   |   |
| 1912.5 | 26665           |                 |         | 5               | QPSK       | 12      | 6         | 22.12                 | 0-1                       | 1        |   |   |
| 1912.5 | 26665           |                 |         | 5               | QPSK       | 12      | 13        | 22.24                 | 0-1                       | 1        |   |   |
| 1912.5 | 26665           |                 |         | 5               | QPSK       | 25      | 0         | 22.17                 | 0-1                       | 1        |   |   |
| 1912.5 | 26665           |                 |         | 5               | 16-QAM     | 1       | 0         | 22.32                 | 0-1                       | 1        |   |   |
| 1912.5 | 26665           |                 |         | 5               | 16-QAM     | 1       | 12        | 22.25                 | 0-1                       | 1        |   |   |
| 1912.5 | 26665           |                 |         | 5               | 16-QAM     | 1       | 24        | 22.40                 | 0-1                       | 1        |   |   |
| 1912.5 | 26665           |                 |         | 5               | 16-QAM     | 12      | 0         | 21.15                 | 0-2                       | 2        |   |   |
| 1912.5 | 26665           |                 |         | 5               | 16-QAM     | 12      | 6         | 21.09                 | 0-2                       | 2        |   |   |
| 1912.5 | 26665           |                 |         | 5               | 16-QAM     | 12      | 13        | 21.17                 | 0-2                       | 2        |   |   |
| 1912.5 | 26665           |                 |         | 5               | 16-QAM     | 25      | 0         | 21.11                 | 0-2                       | 2        |   |   |

Note: LTE Bands 2 and 25 conducted powers were considered simultaneously when evaluating required SAR test channels/configurations.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 27 of 79                                                                         |                                 |

## 9.3 WLAN Conducted Powers

### 9.3.1 Maximum WLAN Conducted Powers

Per KDB 662911 D01v02r01, the individual spectra for each 2x2 MIMO WIFI Antenna were summed mathematically in linear power units for the MIMO output power measurements.

**Table 9-9**  
**IEEE 802.11b Average RF Power**

| Antenna   | Freq [MHz] | Channel | 802.11b Conducted Power [dBm] |       |       |       |
|-----------|------------|---------|-------------------------------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]              |       |       |       |
|           |            |         | 1                             | 2     | 5.5   | 11    |
| Antenna 1 | 2412       | 1*      | 16.57                         | 16.54 | 16.74 | 16.62 |
|           | 2437       | 6*      | 17.05                         | 17.02 | 17.22 | 17.10 |
|           | 2462       | 11*     | 16.81                         | 16.78 | 16.98 | 16.86 |
| Antenna 2 | 2412       | 1*      | 17.07                         | 17.24 | 17.29 | 17.17 |
|           | 2437       | 6*      | 16.54                         | 16.71 | 16.76 | 16.64 |
|           | 2462       | 11*     | 16.49                         | 16.66 | 16.71 | 16.59 |

**Table 9-10**  
**IEEE 802.11g Average RF Power**

| Antenna   | Freq [MHz] | Channel | 802.11g Conducted Power [dBm] |       |       |       |       |       |       |       |
|-----------|------------|---------|-------------------------------|-------|-------|-------|-------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]              |       |       |       |       |       |       |       |
|           |            |         | 6                             | 9     | 12    | 18    | 24    | 36    | 48    | 54    |
| Antenna 1 | 2412       | 1       | 14.09                         | 13.97 | 14.10 | 13.92 | 14.22 | 14.25 | 14.21 | 14.24 |
|           | 2437       | 6       | 13.90                         | 13.78 | 13.91 | 13.73 | 14.03 | 14.06 | 14.02 | 14.05 |
|           | 2462       | 11      | 13.54                         | 13.42 | 13.55 | 13.37 | 13.67 | 13.70 | 13.66 | 13.69 |
| Antenna 2 | 2412       | 1       | 13.82                         | 13.62 | 13.57 | 13.61 | 13.94 | 14.04 | 14.12 | 14.11 |
|           | 2437       | 6       | 13.64                         | 13.44 | 13.39 | 13.43 | 13.76 | 13.86 | 13.94 | 13.93 |
|           | 2462       | 11      | 13.37                         | 13.17 | 13.12 | 13.16 | 13.49 | 13.59 | 13.67 | 13.66 |

**Table 9-11**  
**IEEE 802.11n Average RF Power**

| Antenna   | Freq [MHz] | Channel | 802.11n (2.4GHz) Conducted Power [dBm] |       |       |       |       |       |       |       |
|-----------|------------|---------|----------------------------------------|-------|-------|-------|-------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]                       |       |       |       |       |       |       |       |
|           |            |         | 6.5                                    | 13    | 19.5  | 26    | 39    | 52    | 58.5  | 65    |
| Antenna 1 | 2412       | 1       | 13.14                                  | 13.34 | 13.17 | 13.39 | 13.34 | 13.42 | 13.45 | 13.24 |
|           | 2437       | 6       | 12.95                                  | 13.15 | 12.98 | 13.20 | 13.15 | 13.23 | 13.26 | 13.05 |
|           | 2462       | 11      | 12.81                                  | 13.01 | 12.84 | 13.06 | 13.01 | 13.09 | 13.12 | 12.91 |
| Antenna 2 | 2412       | 1       | 12.93                                  | 12.97 | 12.82 | 12.94 | 13.07 | 13.12 | 13.09 | 13.14 |
|           | 2437       | 6       | 12.85                                  | 12.89 | 12.74 | 12.86 | 12.99 | 13.04 | 13.01 | 13.06 |
|           | 2462       | 11      | 12.64                                  | 12.68 | 12.53 | 12.65 | 12.78 | 12.83 | 12.80 | 12.85 |

**Table 9-12**  
**MIMO IEEE 802.11n Average RF Power**

| Antenna | Freq [MHz] | Channel | 802.11n (2.4GHz) Conducted Power [dBm] |  |
|---------|------------|---------|----------------------------------------|--|
|         |            |         | Data Rate [Mbps]                       |  |
|         |            |         | 13                                     |  |
| MIMO    | 2412       | 1       | 13.87                                  |  |
|         | 2437       | 6       | 13.64                                  |  |
|         | 2462       | 11      | 13.48                                  |  |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 28 of 79                                                                         |                                 |

**Table 9-13**  
**IEEE 802.11a Average RF Power**

| Antenna   | Mode    | Freq [MHz] | Channel | 802.11a Conducted Power [dBm] |       |       |       |       |       |       |       |
|-----------|---------|------------|---------|-------------------------------|-------|-------|-------|-------|-------|-------|-------|
|           |         |            |         | Data Rate [Mbps]              |       |       |       |       |       |       |       |
|           |         |            |         | 6                             | 9     | 12    | 18    | 24    | 36    | 48    | 54    |
| Antenna 1 | 802.11a | 5180       | 36*     | 13.02                         | 12.76 | 12.89 | 12.84 | 13.11 | 13.18 | 13.24 | 13.17 |
|           | 802.11a | 5200       | 40      | 13.08                         | 12.82 | 12.95 | 12.90 | 13.17 | 13.24 | 13.30 | 13.23 |
|           | 802.11a | 5220       | 44      | 13.12                         | 12.86 | 12.99 | 12.94 | 13.21 | 13.28 | 13.34 | 13.27 |
|           | 802.11a | 5240       | 48*     | 12.93                         | 12.67 | 12.80 | 12.75 | 13.02 | 13.09 | 13.15 | 13.08 |
|           | 802.11a | 5260       | 52*     | 12.85                         | 12.78 | 13.04 | 12.99 | 12.67 | 12.54 | 12.68 | 12.65 |
|           | 802.11a | 5280       | 56      | 12.97                         | 12.90 | 13.16 | 13.11 | 12.79 | 12.66 | 12.80 | 12.77 |
|           | 802.11a | 5300       | 60      | 12.57                         | 12.50 | 12.76 | 12.71 | 12.39 | 12.26 | 12.40 | 12.37 |
|           | 802.11a | 5320       | 64*     | 12.54                         | 12.47 | 12.73 | 12.68 | 12.36 | 12.23 | 12.37 | 12.34 |
|           | 802.11a | 5500       | 100     | 13.33                         | 12.62 | 13.26 | 13.19 | 13.11 | 13.37 | 13.32 | 13.26 |
|           | 802.11a | 5520       | 104*    | 13.36                         | 12.65 | 13.29 | 13.22 | 13.14 | 13.40 | 13.35 | 13.29 |
|           | 802.11a | 5540       | 108     | 13.41                         | 12.70 | 13.34 | 13.27 | 13.19 | 13.45 | 13.40 | 13.34 |
|           | 802.11a | 5560       | 112     | 13.27                         | 12.56 | 13.20 | 13.13 | 13.05 | 13.31 | 13.26 | 13.20 |
|           | 802.11a | 5580       | 116*    | 13.40                         | 12.69 | 13.33 | 13.26 | 13.18 | 13.44 | 13.39 | 13.33 |
|           | 802.11a | 5600       | 120     | N/A                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 802.11a | 5620       | 124     | N/A                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 802.11a | 5640       | 128     | N/A                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 802.11a | 5660       | 132     | 13.19                         | 12.48 | 13.12 | 13.05 | 12.97 | 13.23 | 13.18 | 13.12 |
|           | 802.11a | 5680       | 136*    | 13.01                         | 12.30 | 12.94 | 12.87 | 12.79 | 13.05 | 13.00 | 12.94 |
|           | 802.11a | 5700       | 140     | 13.06                         | 12.35 | 12.99 | 12.92 | 12.84 | 13.10 | 13.05 | 12.99 |
|           | 802.11a | 5745       | 149*    | 13.31                         | 13.12 | 13.33 | 13.25 | 12.81 | 12.63 | 12.79 | 12.56 |
|           | 802.11a | 5765       | 153     | 13.21                         | 13.02 | 13.23 | 13.15 | 12.71 | 12.53 | 12.69 | 12.46 |
| Antenna 2 | 802.11a | 5785       | 157*    | 13.15                         | 12.96 | 13.17 | 13.09 | 12.65 | 12.47 | 12.63 | 12.40 |
|           | 802.11a | 5805       | 161     | 13.20                         | 13.01 | 13.22 | 13.14 | 12.70 | 12.52 | 12.68 | 12.45 |
|           | 802.11a | 5825       | 165*    | 12.98                         | 12.79 | 13.00 | 12.92 | 12.48 | 12.30 | 12.46 | 12.23 |
|           | 802.11a | 5180       | 36*     | 13.94                         | 13.87 | 13.97 | 13.37 | 13.72 | 13.92 | 13.34 | 13.48 |
|           | 802.11a | 5200       | 40      | 13.84                         | 13.77 | 13.87 | 13.27 | 13.62 | 13.82 | 13.24 | 13.38 |
|           | 802.11a | 5220       | 44      | 13.86                         | 13.79 | 13.89 | 13.29 | 13.64 | 13.84 | 13.26 | 13.40 |
|           | 802.11a | 5240       | 48*     | 13.74                         | 13.67 | 13.77 | 13.17 | 13.52 | 13.72 | 13.14 | 13.28 |
|           | 802.11a | 5260       | 52*     | 13.21                         | 12.91 | 12.98 | 12.92 | 13.42 | 13.35 | 13.10 | 13.44 |
|           | 802.11a | 5280       | 56      | 13.02                         | 12.72 | 12.79 | 12.73 | 13.23 | 13.16 | 12.91 | 13.25 |
|           | 802.11a | 5300       | 60      | 13.11                         | 12.81 | 12.88 | 12.82 | 13.32 | 13.25 | 13.00 | 13.34 |
|           | 802.11a | 5320       | 64*     | 12.99                         | 12.69 | 12.76 | 12.70 | 13.20 | 13.13 | 12.88 | 13.22 |
|           | 802.11a | 5500       | 100     | 13.26                         | 12.98 | 13.22 | 13.16 | 13.44 | 13.40 | 13.04 | 12.94 |
|           | 802.11a | 5520       | 104*    | 13.17                         | 12.89 | 13.13 | 13.07 | 13.35 | 13.31 | 12.95 | 12.85 |
|           | 802.11a | 5540       | 108     | 13.04                         | 12.76 | 13.00 | 12.94 | 13.22 | 13.18 | 12.82 | 12.72 |
|           | 802.11a | 5560       | 112     | 13.21                         | 12.93 | 13.17 | 13.11 | 13.39 | 13.35 | 12.99 | 12.89 |
|           | 802.11a | 5580       | 116*    | 12.91                         | 12.63 | 12.87 | 12.81 | 13.09 | 13.05 | 12.69 | 12.59 |
|           | 802.11a | 5600       | 120     | N/A                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 802.11a | 5620       | 124     | N/A                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 802.11a | 5640       | 128     | N/A                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 802.11a | 5660       | 132     | 13.01                         | 12.73 | 12.97 | 12.91 | 13.19 | 13.15 | 12.79 | 12.69 |
|           | 802.11a | 5680       | 136*    | 12.81                         | 12.53 | 12.77 | 12.71 | 12.99 | 12.95 | 12.59 | 12.49 |
|           | 802.11a | 5700       | 140     | 12.61                         | 12.33 | 12.57 | 12.51 | 12.79 | 12.75 | 12.39 | 12.29 |
|           | 802.11a | 5745       | 149*    | 13.37                         | 13.09 | 12.91 | 12.95 | 13.35 | 13.17 | 13.24 | 13.37 |
|           | 802.11a | 5765       | 153     | 13.44                         | 13.16 | 12.98 | 13.02 | 13.42 | 13.24 | 13.31 | 13.44 |
|           | 802.11a | 5785       | 157*    | 13.31                         | 13.03 | 12.85 | 12.89 | 13.29 | 13.11 | 13.18 | 13.31 |
|           | 802.11a | 5805       | 161     | 13.11                         | 12.83 | 12.65 | 12.69 | 13.09 | 12.91 | 12.98 | 13.11 |
|           | 802.11a | 5825       | 165*    | 13.25                         | 12.97 | 12.79 | 12.83 | 13.23 | 13.05 | 13.12 | 13.25 |

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(\*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power then the default channels, these “required channels” are considered for SAR testing instead of the default channels.

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 29 of 79                                                                         |                                        |

**Table 9-14**  
**IEEE 802.11n Average RF Power – 20 MHz Bandwidth**

| Antenna   | Freq [MHz] | Channel | 20MHz BW 802.11n (5GHz) Conducted Power [dBm] |       |       |       |       |       |       |       |
|-----------|------------|---------|-----------------------------------------------|-------|-------|-------|-------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]                              |       |       |       |       |       |       |       |
|           |            |         | 6.5                                           | 13    | 19.5  | 26    | 39    | 52    | 58.5  | 65    |
| Antenna 1 | 5180       | 36      | 12.89                                         | 13.27 | 12.81 | 12.92 | 13.24 | 13.35 | 13.21 | 13.28 |
|           | 5200       | 40      | 12.83                                         | 13.31 | 12.75 | 12.86 | 13.18 | 13.32 | 13.15 | 13.22 |
|           | 5220       | 44      | 12.92                                         | 13.30 | 12.84 | 12.95 | 13.27 | 13.34 | 13.24 | 13.31 |
|           | 5240       | 48      | 12.72                                         | 13.20 | 12.64 | 12.75 | 13.07 | 13.27 | 13.04 | 13.11 |
|           | 5260       | 52      | 13.09                                         | 12.57 | 12.75 | 13.21 | 13.14 | 12.92 | 13.02 | 13.14 |
|           | 5280       | 56      | 13.02                                         | 12.50 | 12.68 | 13.20 | 13.07 | 12.85 | 12.95 | 13.07 |
|           | 5300       | 60      | 12.91                                         | 12.39 | 12.57 | 13.19 | 12.96 | 12.74 | 12.84 | 12.96 |
|           | 5320       | 64      | 13.21                                         | 12.69 | 12.87 | 13.17 | 13.21 | 13.04 | 13.14 | 13.21 |
|           | 5500       | 100     | 13.14                                         | 13.28 | 13.21 | 13.39 | 13.33 | 12.97 | 13.02 | 13.07 |
|           | 5520       | 104     | 13.08                                         | 13.22 | 13.15 | 13.33 | 13.27 | 12.91 | 12.96 | 13.01 |
|           | 5540       | 108     | 13.25                                         | 13.39 | 13.32 | 13.48 | 13.44 | 13.08 | 13.13 | 13.18 |
|           | 5560       | 112     | 13.29                                         | 13.43 | 13.36 | 13.44 | 13.48 | 13.12 | 13.17 | 13.22 |
|           | 5580       | 116     | 13.21                                         | 13.35 | 13.28 | 13.46 | 13.40 | 13.04 | 13.09 | 13.14 |
|           | 5600       | 120     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5620       | 124     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5640       | 128     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5660       | 132     | 12.82                                         | 12.96 | 12.89 | 13.07 | 13.01 | 12.65 | 12.70 | 12.75 |
|           | 5680       | 136     | 13.04                                         | 13.18 | 13.11 | 13.29 | 13.23 | 12.87 | 12.92 | 12.97 |
|           | 5700       | 140     | 12.81                                         | 12.95 | 12.88 | 13.06 | 13.00 | 12.64 | 12.69 | 12.74 |
|           | 5745       | 149     | 12.74                                         | 12.95 | 13.14 | 13.21 | 13.15 | 13.01 | 12.94 | 13.08 |
|           | 5765       | 153     | 12.56                                         | 12.77 | 12.96 | 13.03 | 12.97 | 12.83 | 12.76 | 12.90 |
|           | 5785       | 157     | 12.72                                         | 12.93 | 13.12 | 13.19 | 13.13 | 12.99 | 12.92 | 13.06 |
|           | 5805       | 161     | 12.52                                         | 12.73 | 12.92 | 12.99 | 12.93 | 12.79 | 12.72 | 12.86 |
|           | 5825       | 165     | 12.74                                         | 12.95 | 13.14 | 13.21 | 13.15 | 13.01 | 12.94 | 13.08 |
| Antenna 2 | 5180       | 36      | 12.78                                         | 12.95 | 13.02 | 13.11 | 13.04 | 13.07 | 12.99 | 13.12 |
|           | 5200       | 40      | 12.96                                         | 13.13 | 13.20 | 13.29 | 13.22 | 13.25 | 13.17 | 13.30 |
|           | 5220       | 44      | 12.72                                         | 12.89 | 12.96 | 13.05 | 12.98 | 13.01 | 12.93 | 13.06 |
|           | 5240       | 48      | 12.84                                         | 13.01 | 13.08 | 13.17 | 13.10 | 13.13 | 13.05 | 13.18 |
|           | 5260       | 52      | 13.15                                         | 13.02 | 13.25 | 13.37 | 13.34 | 13.17 | 13.27 | 13.25 |
|           | 5280       | 56      | 13.04                                         | 12.91 | 13.14 | 13.26 | 13.23 | 13.06 | 13.16 | 13.14 |
|           | 5300       | 60      | 13.12                                         | 12.99 | 13.22 | 13.34 | 13.31 | 13.14 | 13.24 | 13.22 |
|           | 5320       | 64      | 12.89                                         | 12.76 | 12.99 | 13.11 | 13.08 | 12.91 | 13.01 | 12.99 |
|           | 5500       | 100     | 13.01                                         | 13.18 | 13.27 | 13.24 | 13.28 | 13.32 | 13.29 | 13.32 |
|           | 5520       | 104     | 13.18                                         | 13.35 | 13.44 | 13.41 | 13.45 | 13.44 | 13.46 | 13.42 |
|           | 5540       | 108     | 13.01                                         | 13.18 | 13.27 | 13.24 | 13.28 | 13.32 | 13.29 | 13.32 |
|           | 5560       | 112     | 13.09                                         | 13.26 | 13.35 | 13.32 | 13.36 | 13.40 | 13.37 | 13.40 |
|           | 5580       | 116     | 13.04                                         | 13.21 | 13.30 | 13.27 | 13.31 | 13.35 | 13.32 | 13.35 |
|           | 5600       | 120     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5620       | 124     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5640       | 128     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5660       | 132     | 12.82                                         | 12.99 | 13.08 | 13.05 | 13.09 | 13.13 | 13.10 | 13.13 |
|           | 5680       | 136     | 12.68                                         | 12.85 | 12.94 | 12.91 | 12.95 | 12.99 | 12.96 | 12.99 |
|           | 5700       | 140     | 12.60                                         | 12.77 | 12.86 | 12.83 | 12.87 | 12.91 | 12.88 | 12.91 |
|           | 5745       | 149     | 13.08                                         | 13.12 | 13.27 | 13.29 | 13.25 | 13.21 | 13.30 | 13.24 |
|           | 5765       | 153     | 13.11                                         | 13.15 | 13.30 | 13.32 | 13.28 | 13.24 | 13.33 | 13.27 |
|           | 5785       | 157     | 13.21                                         | 13.25 | 13.40 | 13.42 | 13.38 | 13.34 | 13.43 | 13.37 |
|           | 5805       | 161     | 13.25                                         | 13.29 | 13.44 | 13.46 | 13.42 | 13.38 | 13.47 | 13.41 |
|           | 5825       | 165     | 13.16                                         | 13.20 | 13.35 | 13.37 | 13.33 | 13.29 | 13.38 | 13.32 |

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 30 of 79                                                                         |                                        |



**Table 9-15**  
**MIMO IEEE 802.11n Average RF Power – 20 MHz Bandwidth**

| Antenna | Freq<br>[MHz] | Channel | 20MHz BW 802.11n (5GHz) Conducted Power<br>[dBm] |
|---------|---------------|---------|--------------------------------------------------|
|         |               |         | Data Rate [Mbps]                                 |
|         |               |         | 13                                               |
| MIMO    | 5180          | 36      | 12.63                                            |
|         | 5200          | 40      | 12.60                                            |
|         | 5220          | 44      | 12.62                                            |
|         | 5240          | 48      | 12.55                                            |
|         | 5260          | 52      | 12.75                                            |
|         | 5280          | 56      | 12.76                                            |
|         | 5300          | 60      | 12.77                                            |
|         | 5320          | 64      | 12.63                                            |
|         | 5500          | 100     | 12.30                                            |
|         | 5520          | 104     | 12.28                                            |
|         | 5540          | 108     | 12.25                                            |
|         | 5560          | 112     | 12.24                                            |
|         | 5580          | 116     | 12.18                                            |
|         | 5600          | 120     | N/A                                              |
|         | 5620          | 124     | N/A                                              |
|         | 5640          | 128     | N/A                                              |
|         | 5660          | 132     | 12.08                                            |
|         | 5680          | 136     | 12.12                                            |
|         | 5700          | 140     | 12.06                                            |
|         | 5745          | 149     | 13.44                                            |
|         | 5765          | 153     | 13.47                                            |
|         | 5785          | 157     | 13.44                                            |
|         | 5805          | 161     | 13.43                                            |
|         | 5825          | 165     | 13.41                                            |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 31 of 79                                                                         |                                        |

**Table 9-16**  
**IEEE 802.11n Average RF Power – 40 MHz Bandwidth**

| Antenna   | Freq [MHz] | Channel | 40MHz BW 802.11n (5GHz) Conducted Power [dBm] |       |       |       |       |       |       |       |
|-----------|------------|---------|-----------------------------------------------|-------|-------|-------|-------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]                              |       |       |       |       |       |       |       |
|           |            |         | 13.5                                          | 27    | 40.5  | 54    | 81    | 108   | 121.5 | 135   |
| Antenna 1 | 5190       | 38      | 11.42                                         | 12.05 | 12.24 | 12.28 | 11.93 | 12.12 | 12.38 | 12.24 |
|           | 5230       | 46      | 11.26                                         | 11.89 | 12.08 | 12.12 | 11.77 | 11.96 | 12.22 | 12.08 |
|           | 5270       | 54      | 11.29                                         | 11.85 | 12.09 | 12.35 | 12.14 | 12.36 | 12.04 | 12.12 |
|           | 5310       | 62      | 11.36                                         | 11.92 | 12.16 | 12.42 | 12.21 | 12.43 | 12.11 | 12.19 |
|           | 5510       | 102     | 11.45                                         | 11.48 | 11.65 | 11.84 | 11.67 | 11.95 | 11.72 | 11.62 |
|           | 5550       | 110     | 11.69                                         | 11.72 | 11.89 | 12.08 | 11.91 | 12.19 | 11.96 | 11.86 |
|           | 5590       | 118     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5630       | 126     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5670       | 134     | 11.51                                         | 11.54 | 11.71 | 11.90 | 11.73 | 12.01 | 11.78 | 11.68 |
|           | 5755       | 151     | 11.43                                         | 11.23 | 11.42 | 11.48 | 11.52 | 11.46 | 11.32 | 11.47 |
| Antenna 2 | 5795       | 159     | 11.29                                         | 11.09 | 11.28 | 11.34 | 11.38 | 11.32 | 11.18 | 11.33 |
|           | 5190       | 38      | 12.25                                         | 12.38 | 12.41 | 12.25 | 12.34 | 12.43 | 12.32 | 12.29 |
|           | 5230       | 46      | 12.17                                         | 12.30 | 12.33 | 12.17 | 12.26 | 12.35 | 12.24 | 12.21 |
|           | 5270       | 54      | 11.54                                         | 11.52 | 11.61 | 11.79 | 11.35 | 11.62 | 11.55 | 11.67 |
|           | 5310       | 62      | 11.41                                         | 11.39 | 11.48 | 11.66 | 11.22 | 11.49 | 11.42 | 11.54 |
|           | 5510       | 102     | 11.67                                         | 11.85 | 11.58 | 11.79 | 11.82 | 11.98 | 11.67 | 11.54 |
|           | 5550       | 110     | 11.61                                         | 11.79 | 11.52 | 11.73 | 11.76 | 11.92 | 11.61 | 11.48 |
|           | 5590       | 118     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5630       | 126     | N/A                                           | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   | N/A   |
|           | 5670       | 134     | 11.32                                         | 11.50 | 11.23 | 11.44 | 11.47 | 11.63 | 11.32 | 11.19 |
|           | 5755       | 151     | 11.74                                         | 11.84 | 11.81 | 12.02 | 12.05 | 11.98 | 11.90 | 11.84 |
|           | 5795       | 159     | 11.77                                         | 11.87 | 11.84 | 12.05 | 12.08 | 12.01 | 11.93 | 11.87 |

**Table 9-17**  
**MIMO IEEE 802.11n Average RF Power – 40 MHz Bandwidth**

| Antenna | Mode    | Freq [MHz] | Channel | 40MHz BW 802.11n (5GHz) Conducted Power [dBm] |
|---------|---------|------------|---------|-----------------------------------------------|
|         |         |            |         | Data Rate [Mbps]                              |
|         |         |            |         | 27                                            |
| MIMO    | 802.11n | 5190       | 38      | 11.63                                         |
|         | 802.11n | 5230       | 46      | 11.79                                         |
|         | 802.11n | 5270       | 54      | 11.58                                         |
|         | 802.11n | 5310       | 62      | 11.73                                         |
|         | 802.11n | 5510       | 102     | 12.33                                         |
|         | 802.11n | 5550       | 110     | 12.41                                         |
|         | 802.11n | 5590       | 118     | N/A                                           |
|         | 802.11n | 5630       | 126     | N/A                                           |
|         | 802.11n | 5670       | 134     | 12.14                                         |
|         | 802.11n | 5755       | 151     | 12.44                                         |
|         | 802.11n | 5795       | 159     | 12.28                                         |

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 32 of 79                                                                         |                                        |

**Table 9-18**  
**IEEE 802.11ac Average RF Power – 80 MHz Bandwidth**

| Antenna   | Freq [MHz] | Channel | 80MHz BW 802.11ac (5GHz) Conducted Power [dBm] |       |       |       |       |       |       |       |       |       |
|-----------|------------|---------|------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]                               |       |       |       |       |       |       |       |       |       |
|           |            |         | 29.3                                           | 58.5  | 87.8  | 117   | 175.5 | 234   | 263.3 | 292.5 | 351   | 390   |
| Antenna 1 | 5210       | 42      | 10.71                                          | 10.76 | 10.69 | 10.77 | 10.94 | 10.92 | 10.87 | 10.91 | 10.88 | 10.79 |
|           | 5290       | 58      | 10.77                                          | 10.81 | 10.72 | 10.60 | 10.98 | 10.87 | 10.91 | 10.82 | 10.87 | 10.97 |
|           | 5530       | 106     | 11.15                                          | 11.18 | 11.11 | 11.38 | 11.17 | 11.32 | 11.34 | 11.21 | 11.25 | 11.37 |
|           | 5775       | 155     | 11.25                                          | 11.14 | 10.94 | 11.09 | 11.32 | 10.92 | 11.10 | 11.17 | 10.89 | 10.52 |
| Antenna 2 | 5210       | 42      | 10.78                                          | 10.61 | 10.64 | 10.59 | 10.86 | 10.79 | 10.81 | 10.95 | 11.01 | 10.98 |
|           | 5290       | 58      | 10.94                                          | 10.75 | 10.74 | 10.93 | 11.05 | 11.01 | 11.12 | 11.07 | 10.95 | 11.18 |
|           | 5530       | 106     | 10.98                                          | 10.84 | 10.97 | 10.75 | 11.14 | 11.04 | 11.16 | 11.07 | 11.12 | 11.14 |
|           | 5775       | 155     | 11.26                                          | 11.23 | 11.14 | 11.24 | 11.37 | 11.24 | 11.42 | 11.38 | 11.27 | 11.35 |

**Table 9-19**  
**MIMO IEEE 802.11ac Average RF Power – 80 MHz Bandwidth**

| Antenna | Freq [MHz] | Channel | 80MHz BW 802.11ac (5GHz) Conducted Power [dBm] |
|---------|------------|---------|------------------------------------------------|
|         |            |         | Data Rate [Mbps]                               |
|         |            |         | 58.5                                           |
| MIMO    | 5210       | 42      | 11.23                                          |
|         | 5290       | 58      | 11.27                                          |
|         | 5530       | 106     | 10.89                                          |
|         | 5775       | 155     | 10.76                                          |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 33 of 79                                                                         |                                        |

### 9.3.2 Reduced WLAN Conducted Powers

Per KDB 662911 D01v02r01, the individual spectra for each 2x2 MIMO WIFI Antenna were summed mathematically in linear power units for the MIMO output power measurements.

**Table 9-20**  
**IEEE 802.11b Average RF Power**

| Antenna   | Freq [MHz] | Channel | 802.11b Conducted Power [dBm] |       |       |       |
|-----------|------------|---------|-------------------------------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]              |       |       |       |
|           |            |         | 1                             | 2     | 5.5   | 11    |
| Antenna 1 | 2412       | 1*      | 11.94                         | 12.03 | 12.09 | 12.08 |
|           | 2437       | 6*      | 11.23                         | 11.39 | 11.31 | 11.33 |
|           | 2462       | 11*     | 11.27                         | 11.36 | 11.39 | 11.48 |
| Antenna 2 | 2412       | 1*      | 11.74                         | 11.67 | 11.75 | 11.70 |
|           | 2437       | 6*      | 11.50                         | 11.43 | 11.35 | 11.44 |
|           | 2462       | 11*     | 11.39                         | 11.35 | 11.32 | 11.27 |

**Table 9-21**  
**IEEE 802.11g Average RF Power**

| Antenna   | Freq [MHz] | Channel | 802.11g Conducted Power [dBm] |       |       |       |       |       |       |       |
|-----------|------------|---------|-------------------------------|-------|-------|-------|-------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]              |       |       |       |       |       |       |       |
|           |            |         | 6                             | 9     | 12    | 18    | 24    | 36    | 48    | 54    |
| Antenna 1 | 2412       | 1       | 11.42                         | 11.55 | 11.52 | 11.41 | 11.46 | 11.44 | 11.40 | 11.38 |
|           | 2437       | 6       | 11.87                         | 11.92 | 11.93 | 11.87 | 11.98 | 11.93 | 11.92 | 11.94 |
|           | 2462       | 11      | 11.89                         | 11.71 | 11.75 | 11.79 | 11.82 | 11.82 | 11.81 | 11.81 |
| Antenna 2 | 2412       | 1       | 11.66                         | 11.78 | 11.61 | 11.76 | 11.75 | 11.73 | 11.59 | 11.78 |
|           | 2437       | 6       | 11.63                         | 11.62 | 11.80 | 11.77 | 11.69 | 11.76 | 11.75 | 11.76 |
|           | 2462       | 11      | 11.38                         | 11.51 | 11.49 | 11.43 | 11.44 | 11.50 | 11.47 | 11.45 |

**Table 9-22**  
**IEEE 802.11n Average RF Power**

| Antenna   | Freq [MHz] | Channel | 802.11n (2.4GHz) Conducted Power [dBm] |       |       |       |       |       |       |       |
|-----------|------------|---------|----------------------------------------|-------|-------|-------|-------|-------|-------|-------|
|           |            |         | Data Rate [Mbps]                       |       |       |       |       |       |       |       |
|           |            |         | 6.5                                    | 13    | 19.5  | 26    | 39    | 52    | 58.5  | 65    |
| Antenna 1 | 2412       | 1       | 11.25                                  | 11.25 | 11.30 | 11.18 | 11.24 | 11.24 | 11.32 | 11.31 |
|           | 2437       | 6       | 11.90                                  | 11.89 | 11.90 | 11.85 | 11.90 | 11.79 | 11.92 | 11.79 |
|           | 2462       | 11      | 11.66                                  | 11.78 | 11.78 | 11.64 | 11.81 | 11.70 | 11.75 | 11.70 |
| Antenna 2 | 2412       | 1       | 11.83                                  | 11.97 | 11.93 | 11.92 | 11.81 | 11.97 | 11.91 | 11.81 |
|           | 2437       | 6       | 11.73                                  | 11.70 | 11.69 | 11.79 | 11.82 | 11.78 | 11.83 | 11.69 |
|           | 2462       | 11      | 11.69                                  | 11.79 | 11.75 | 11.77 | 11.85 | 11.75 | 11.70 | 11.71 |

**Table 9-23**  
**MIMO IEEE 802.11n Average RF Power**

| Antenna | Freq [MHz] | Channel | 802.11n (2.4GHz) Conducted Power [dBm] |
|---------|------------|---------|----------------------------------------|
|         |            |         | Data Rate [Mbps]                       |
|         |            |         | 13                                     |
| MIMO    | 2412       | 1       | 11.85                                  |
|         | 2437       | 6       | 11.70                                  |
|         | 2462       | 11      | 11.34                                  |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 34 of 79                                                                         |                                 |

**Table 9-24**  
**IEEE 802.11a Average RF Power**

| Antenna   | Mode    | Freq [MHz] | Channel | 802.11a Conducted Power [dBm] |      |      |      |      |      |      |      |
|-----------|---------|------------|---------|-------------------------------|------|------|------|------|------|------|------|
|           |         |            |         | Data Rate [Mbps]              |      |      |      |      |      |      |      |
|           |         |            |         | 6                             | 9    | 12   | 18   | 24   | 36   | 48   | 54   |
| Antenna 1 | 802.11a | 5180       | 36*     | 6.74                          | 6.47 | 6.64 | 6.39 | 6.48 | 6.32 | 6.29 | 6.47 |
|           | 802.11a | 5200       | 40      | 6.66                          | 6.37 | 6.71 | 6.56 | 6.51 | 6.35 | 6.43 | 6.40 |
|           | 802.11a | 5220       | 44      | 6.74                          | 6.50 | 6.78 | 6.59 | 6.69 | 6.43 | 6.58 | 6.48 |
|           | 802.11a | 5240       | 48*     | 6.32                          | 6.63 | 6.47 | 6.22 | 6.27 | 6.62 | 6.39 | 6.31 |
|           | 802.11a | 5260       | 52*     | 6.69                          | 6.55 | 6.39 | 6.69 | 6.59 | 6.61 | 6.47 | 6.64 |
|           | 802.11a | 5280       | 56      | 6.58                          | 6.87 | 6.69 | 6.87 | 6.67 | 6.53 | 6.77 | 6.91 |
|           | 802.11a | 5300       | 60      | 6.53                          | 6.57 | 6.79 | 6.68 | 6.55 | 6.91 | 6.65 | 6.89 |
|           | 802.11a | 5320       | 64*     | 6.63                          | 6.84 | 6.47 | 6.63 | 6.69 | 6.89 | 6.86 | 6.46 |
|           | 802.11a | 5500       | 100     | 6.82                          | 6.48 | 6.44 | 6.82 | 6.67 | 6.67 | 6.77 | 6.65 |
|           | 802.11a | 5520       | 104*    | 6.74                          | 6.68 | 6.82 | 6.88 | 6.88 | 6.87 | 6.69 | 6.55 |
|           | 802.11a | 5540       | 108     | 6.45                          | 6.67 | 6.40 | 6.87 | 6.54 | 6.65 | 6.48 | 6.46 |
|           | 802.11a | 5560       | 112     | 6.66                          | 6.59 | 6.91 | 6.62 | 6.89 | 6.79 | 6.52 | 6.46 |
|           | 802.11a | 5580       | 116*    | 6.83                          | 6.62 | 6.45 | 6.39 | 6.75 | 6.63 | 6.82 | 6.37 |
|           | 802.11a | 5600       | 120     | N/A                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 802.11a | 5620       | 124     | N/A                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 802.11a | 5640       | 128     | N/A                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 802.11a | 5660       | 132     | 6.39                          | 6.55 | 6.64 | 6.73 | 6.44 | 6.46 | 6.82 | 6.80 |
|           | 802.11a | 5680       | 136*    | 6.56                          | 6.44 | 6.56 | 6.79 | 6.38 | 6.52 | 6.71 | 6.59 |
|           | 802.11a | 5700       | 140     | 6.33                          | 6.46 | 6.49 | 6.36 | 6.42 | 6.66 | 6.31 | 6.58 |
|           | 802.11a | 5745       | 149*    | 6.84                          | 6.88 | 6.55 | 6.64 | 6.92 | 6.63 | 6.81 | 6.78 |
|           | 802.11a | 5765       | 153     | 6.53                          | 6.69 | 6.67 | 6.41 | 6.58 | 6.49 | 6.69 | 6.76 |
| Antenna 2 | 802.11a | 5785       | 157*    | 6.87                          | 6.79 | 6.66 | 6.86 | 6.70 | 6.67 | 6.90 | 6.75 |
|           | 802.11a | 5805       | 161     | 6.56                          | 6.64 | 6.55 | 6.66 | 6.37 | 6.40 | 6.76 | 6.55 |
|           | 802.11a | 5825       | 165*    | 6.67                          | 6.70 | 6.27 | 6.53 | 6.56 | 6.47 | 6.55 | 6.25 |
|           | 802.11a | 5180       | 36*     | 6.65                          | 6.70 | 6.75 | 6.82 | 6.77 | 6.70 | 6.83 | 6.76 |
|           | 802.11a | 5200       | 40      | 6.72                          | 6.84 | 6.75 | 6.74 | 6.79 | 6.75 | 6.88 | 6.79 |
|           | 802.11a | 5220       | 44      | 6.86                          | 6.89 | 6.79 | 6.86 | 6.87 | 6.79 | 6.93 | 6.81 |
|           | 802.11a | 5240       | 48*     | 6.70                          | 6.63 | 6.64 | 6.63 | 6.74 | 6.72 | 6.77 | 6.81 |
|           | 802.11a | 5260       | 52*     | 6.95                          | 7.02 | 6.99 | 6.93 | 6.94 | 6.88 | 6.98 | 6.86 |
|           | 802.11a | 5280       | 56      | 6.83                          | 6.91 | 6.78 | 6.85 | 6.92 | 6.80 | 6.83 | 6.81 |
|           | 802.11a | 5300       | 60      | 6.83                          | 6.90 | 6.98 | 6.95 | 6.93 | 6.97 | 6.87 | 6.93 |
|           | 802.11a | 5320       | 64*     | 6.90                          | 6.90 | 6.85 | 6.70 | 6.83 | 6.83 | 6.81 | 6.90 |
|           | 802.11a | 5500       | 100     | 5.71                          | 5.77 | 5.69 | 5.76 | 5.77 | 5.81 | 5.75 | 5.67 |
|           | 802.11a | 5520       | 104*    | 5.79                          | 5.75 | 5.88 | 5.76 | 5.82 | 5.87 | 5.92 | 5.73 |
|           | 802.11a | 5540       | 108     | 5.81                          | 5.70 | 5.76 | 5.86 | 5.88 | 5.79 | 5.69 | 5.84 |
|           | 802.11a | 5560       | 112     | 5.83                          | 5.85 | 5.92 | 5.95 | 6.00 | 5.99 | 5.95 | 5.85 |
|           | 802.11a | 5580       | 116*    | 5.86                          | 5.80 | 5.94 | 5.96 | 5.93 | 5.95 | 5.90 | 5.82 |
|           | 802.11a | 5600       | 120     | N/A                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 802.11a | 5620       | 124     | N/A                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 802.11a | 5640       | 128     | N/A                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 802.11a | 5660       | 132     | 5.74                          | 5.86 | 5.84 | 5.87 | 5.87 | 5.87 | 5.89 | 5.77 |
|           | 802.11a | 5680       | 136*    | 6.01                          | 5.97 | 5.85 | 5.90 | 6.01 | 6.00 | 5.95 | 6.03 |
|           | 802.11a | 5700       | 140     | 5.91                          | 5.93 | 5.89 | 5.94 | 6.01 | 5.95 | 5.92 | 5.94 |
|           | 802.11a | 5745       | 149*    | 6.29                          | 6.43 | 6.31 | 6.31 | 6.42 | 6.25 | 6.44 | 6.31 |
|           | 802.11a | 5765       | 153     | 6.58                          | 6.66 | 6.50 | 6.66 | 6.57 | 6.57 | 6.57 | 6.62 |
|           | 802.11a | 5785       | 157*    | 6.47                          | 6.57 | 6.47 | 6.54 | 6.54 | 6.42 | 6.58 | 6.40 |
|           | 802.11a | 5805       | 161     | 6.37                          | 6.40 | 6.52 | 6.43 | 6.42 | 6.53 | 6.53 | 6.50 |
|           | 802.11a | 5825       | 165*    | 6.33                          | 6.41 | 6.44 | 6.37 | 6.46 | 6.47 | 6.36 | 6.33 |

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(\*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power then the default channels, these “required channels” are considered for SAR testing instead of the default channels.

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 35 of 79                                                                         |                                        |

**Table 9-25**  
**IEEE 802.11n Average RF Power – 20 MHz Bandwidth**

| Antenna   | Freq [MHz] | Channel | 20MHz BW 802.11n (5GHz) Conducted Power [dBm] |      |      |      |      |      |      |      |
|-----------|------------|---------|-----------------------------------------------|------|------|------|------|------|------|------|
|           |            |         | Data Rate [Mbps]                              |      |      |      |      |      |      |      |
|           |            |         | 6.5                                           | 13   | 19.5 | 26   | 39   | 52   | 58.5 | 65   |
| Antenna 1 | 5180       | 36      | 6.73                                          | 6.95 | 6.84 | 6.72 | 6.70 | 6.96 | 6.61 | 6.49 |
|           | 5200       | 40      | 6.92                                          | 6.46 | 6.87 | 6.92 | 6.65 | 6.80 | 6.83 | 6.66 |
|           | 5220       | 44      | 6.70                                          | 6.35 | 6.72 | 6.46 | 6.53 | 6.76 | 6.77 | 6.69 |
|           | 5240       | 48      | 6.36                                          | 6.36 | 6.65 | 6.54 | 6.33 | 6.50 | 6.37 | 6.55 |
|           | 5260       | 52      | 6.69                                          | 6.57 | 6.22 | 6.55 | 6.60 | 6.65 | 6.22 | 6.53 |
|           | 5280       | 56      | 6.56                                          | 6.41 | 6.33 | 6.60 | 6.35 | 6.48 | 6.61 | 6.50 |
|           | 5300       | 60      | 6.43                                          | 6.38 | 6.58 | 6.73 | 6.41 | 6.40 | 6.40 | 6.35 |
|           | 5320       | 64      | 6.39                                          | 6.66 | 6.74 | 6.44 | 6.65 | 6.60 | 6.79 | 6.68 |
|           | 5500       | 100     | 6.73                                          | 6.83 | 6.69 | 6.99 | 6.70 | 6.73 | 6.94 | 6.92 |
|           | 5520       | 104     | 6.92                                          | 6.66 | 6.49 | 6.63 | 6.60 | 6.68 | 6.60 | 6.96 |
|           | 5540       | 108     | 6.74                                          | 6.42 | 6.63 | 6.51 | 6.63 | 6.68 | 6.45 | 6.77 |
|           | 5560       | 112     | 6.58                                          | 6.58 | 7.00 | 6.92 | 6.75 | 6.67 | 6.82 | 6.88 |
|           | 5580       | 116     | 6.94                                          | 6.75 | 6.87 | 6.84 | 6.79 | 6.88 | 6.75 | 6.91 |
|           | 5600       | 120     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 5620       | 124     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 5640       | 128     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 5660       | 132     | 7.07                                          | 6.97 | 7.05 | 6.87 | 6.86 | 6.63 | 7.07 | 6.80 |
|           | 5680       | 136     | 6.92                                          | 6.90 | 6.48 | 6.88 | 6.45 | 6.96 | 6.74 | 6.47 |
|           | 5700       | 140     | 6.87                                          | 6.84 | 6.62 | 6.70 | 6.68 | 6.56 | 6.53 | 6.71 |
|           | 5745       | 149     | 6.49                                          | 6.72 | 6.62 | 6.54 | 6.80 | 6.95 | 6.56 | 6.68 |
|           | 5765       | 153     | 6.44                                          | 6.70 | 6.74 | 6.80 | 6.69 | 6.62 | 6.81 | 6.71 |
|           | 5785       | 157     | 6.49                                          | 6.65 | 6.64 | 6.83 | 6.66 | 6.59 | 6.47 | 6.77 |
|           | 5805       | 161     | 6.20                                          | 6.57 | 6.37 | 6.25 | 6.51 | 6.44 | 6.66 | 6.26 |
|           | 5825       | 165     | 6.58                                          | 6.63 | 6.53 | 6.31 | 6.70 | 6.30 | 6.75 | 6.59 |
| Antenna 2 | 5180       | 36      | 6.66                                          | 6.73 | 6.58 | 6.64 | 6.66 | 6.57 | 6.67 | 6.71 |
|           | 5200       | 40      | 6.84                                          | 6.91 | 6.98 | 6.99 | 6.88 | 6.98 | 6.86 | 6.90 |
|           | 5220       | 44      | 6.68                                          | 6.76 | 6.81 | 6.67 | 6.74 | 6.78 | 6.80 | 6.84 |
|           | 5240       | 48      | 6.76                                          | 6.74 | 6.81 | 6.83 | 6.81 | 6.77 | 6.85 | 6.79 |
|           | 5260       | 52      | 6.74                                          | 6.83 | 6.77 | 6.75 | 6.71 | 6.74 | 6.89 | 6.82 |
|           | 5280       | 56      | 6.83                                          | 6.67 | 6.76 | 6.67 | 6.71 | 6.81 | 6.73 | 6.70 |
|           | 5300       | 60      | 6.78                                          | 6.97 | 6.78 | 6.80 | 6.86 | 6.91 | 6.93 | 6.97 |
|           | 5320       | 64      | 6.69                                          | 6.74 | 6.83 | 6.79 | 6.78 | 6.81 | 6.84 | 6.85 |
|           | 5500       | 100     | 5.70                                          | 5.63 | 5.70 | 5.70 | 5.74 | 5.65 | 5.75 | 5.71 |
|           | 5520       | 104     | 5.92                                          | 5.97 | 5.90 | 5.90 | 5.98 | 5.90 | 5.95 | 5.93 |
|           | 5540       | 108     | 5.76                                          | 5.90 | 5.76 | 5.84 | 5.83 | 5.90 | 5.86 | 5.76 |
|           | 5560       | 112     | 6.04                                          | 5.97 | 5.90 | 5.95 | 5.96 | 5.95 | 5.97 | 6.02 |
|           | 5580       | 116     | 6.03                                          | 5.92 | 6.01 | 6.11 | 5.97 | 5.92 | 6.09 | 6.10 |
|           | 5600       | 120     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 5620       | 124     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 5640       | 128     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  | N/A  |
|           | 5660       | 132     | 5.91                                          | 5.95 | 5.85 | 5.88 | 5.84 | 5.92 | 5.82 | 5.90 |
|           | 5680       | 136     | 5.86                                          | 5.94 | 5.92 | 5.83 | 5.89 | 5.99 | 5.82 | 5.98 |
|           | 5700       | 140     | 5.78                                          | 5.82 | 5.93 | 5.92 | 5.91 | 5.90 | 5.83 | 5.78 |
|           | 5745       | 149     | 6.44                                          | 6.44 | 6.59 | 6.47 | 6.49 | 6.43 | 6.46 | 6.51 |
|           | 5765       | 153     | 6.60                                          | 6.61 | 6.56 | 6.66 | 6.65 | 6.69 | 6.73 | 6.69 |
|           | 5785       | 157     | 6.60                                          | 6.52 | 6.70 | 6.56 | 6.57 | 6.60 | 6.54 | 6.57 |
|           | 5805       | 161     | 6.65                                          | 6.66 | 6.59 | 6.63 | 6.64 | 6.57 | 6.60 | 6.63 |
|           | 5825       | 165     | 6.54                                          | 6.39 | 6.52 | 6.45 | 6.47 | 6.43 | 6.49 | 6.53 |

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 36 of 79                                                                         |                                        |

**Table 9-26**  
**MIMO IEEE 802.11n Average RF Power – 20 MHz Bandwidth**

| Antenna | Freq [MHz] | Channel | 20MHz BW 802.11n (5GHz) |
|---------|------------|---------|-------------------------|
|         |            |         | Conducted Power [dBm]   |
|         |            |         | Data Rate [Mbps]        |
|         |            |         | 13                      |
| MIMO    | 5180       | 36      | 5.98                    |
|         | 5200       | 40      | 6.02                    |
|         | 5220       | 44      | 6.04                    |
|         | 5240       | 48      | 6.06                    |
|         | 5260       | 52      | 5.64                    |
|         | 5280       | 56      | 5.62                    |
|         | 5300       | 60      | 5.67                    |
|         | 5320       | 64      | 5.62                    |
|         | 5500       | 100     | 7.38                    |
|         | 5520       | 104     | 7.31                    |
|         | 5540       | 108     | 7.33                    |
|         | 5560       | 112     | 7.30                    |
|         | 5580       | 116     | 7.36                    |
|         | 5600       | 120     | N/A                     |
|         | 5620       | 124     | N/A                     |
|         | 5640       | 128     | N/A                     |
|         | 5660       | 132     | 7.22                    |
|         | 5680       | 136     | 7.19                    |
|         | 5700       | 140     | 7.29                    |
|         | 5745       | 149     | 6.52                    |
|         | 5765       | 153     | 6.57                    |
|         | 5785       | 157     | 6.54                    |
|         | 5805       | 161     | 6.41                    |
|         | 5825       | 165     | 6.44                    |

**Table 9-27**  
**IEEE 802.11n Average RF Power – 40 MHz Bandwidth**

| Mode      | Freq [MHz] | Channel | 40MHz BW 802.11n (5GHz) Conducted Power [dBm] |      |      |      |      |      |       |      |
|-----------|------------|---------|-----------------------------------------------|------|------|------|------|------|-------|------|
|           |            |         | Data Rate [Mbps]                              |      |      |      |      |      |       |      |
|           |            |         | 13.5                                          | 27   | 40.5 | 54   | 81   | 108  | 121.5 | 135  |
| Antenna 1 | 5190       | 38      | 6.57                                          | 6.46 | 6.55 | 6.31 | 6.24 | 6.72 | 6.49  | 6.15 |
|           | 5230       | 46      | 6.54                                          | 6.97 | 6.18 | 6.14 | 6.91 | 6.71 | 6.80  | 6.66 |
|           | 5270       | 54      | 6.35                                          | 6.36 | 6.25 | 6.64 | 6.85 | 6.33 | 6.27  | 6.81 |
|           | 5310       | 62      | 6.39                                          | 6.33 | 6.24 | 6.84 | 6.82 | 6.63 | 6.02  | 6.86 |
|           | 5510       | 102     | 6.59                                          | 6.84 | 6.25 | 6.59 | 6.87 | 6.78 | 6.58  | 6.35 |
|           | 5550       | 110     | 6.64                                          | 6.69 | 6.85 | 7.07 | 6.27 | 6.69 | 6.87  | 7.02 |
|           | 5590       | 118     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A   | N/A  |
|           | 5630       | 126     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A   | N/A  |
|           | 5670       | 134     | 6.69                                          | 6.17 | 6.39 | 6.42 | 6.20 | 6.42 | 6.82  | 6.36 |
|           | 5755       | 151     | 6.77                                          | 6.74 | 6.76 | 6.80 | 6.25 | 6.05 | 5.92  | 6.29 |
|           | 5795       | 159     | 6.54                                          | 6.56 | 6.36 | 6.18 | 6.69 | 6.07 | 6.51  | 6.67 |
| Antenna 2 | 5190       | 38      | 6.63                                          | 6.73 | 6.66 | 6.80 | 6.67 | 6.72 | 6.69  | 6.76 |
|           | 5230       | 46      | 6.74                                          | 6.62 | 6.72 | 6.58 | 6.62 | 6.69 | 6.64  | 6.72 |
|           | 5270       | 54      | 6.72                                          | 6.67 | 6.58 | 6.64 | 6.72 | 6.65 | 6.67  | 6.60 |
|           | 5310       | 62      | 6.92                                          | 6.81 | 6.87 | 6.75 | 6.87 | 6.81 | 6.75  | 6.79 |
|           | 5510       | 102     | 5.56                                          | 5.67 | 5.62 | 5.58 | 5.52 | 5.59 | 5.57  | 5.52 |
|           | 5550       | 110     | 5.73                                          | 5.70 | 5.76 | 5.62 | 5.62 | 5.77 | 5.79  | 5.62 |
|           | 5590       | 118     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A   | N/A  |
|           | 5630       | 126     | N/A                                           | N/A  | N/A  | N/A  | N/A  | N/A  | N/A   | N/A  |
|           | 5670       | 134     | 5.63                                          | 5.57 | 5.73 | 5.71 | 5.66 | 5.65 | 5.58  | 5.63 |
|           | 5755       | 151     | 6.52                                          | 6.53 | 6.52 | 6.41 | 6.40 | 6.52 | 6.52  | 6.44 |
|           | 5795       | 159     | 6.44                                          | 6.41 | 6.40 | 6.42 | 6.46 | 6.30 | 6.37  | 6.43 |

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 37 of 79                                                                         |                                        |



**Table 9-28**  
**MIMO IEEE 802.11n Average RF Power – 40 MHz Bandwidth**

| Antenna | Freq [MHz] | Channel | 40MHz BW 802.11n (5GHz)<br>Conducted Power [dBm] |
|---------|------------|---------|--------------------------------------------------|
|         |            |         | Data Rate [Mbps]                                 |
|         |            |         | 27                                               |
| MIMO    | 5190       | 38      | 6.06                                             |
|         | 5230       | 46      | 6.09                                             |
|         | 5270       | 54      | 6.10                                             |
|         | 5310       | 62      | 6.08                                             |
|         | 5510       | 102     | 7.39                                             |
|         | 5550       | 110     | 7.33                                             |
|         | 5590       | 118     | N/A                                              |
|         | 5630       | 126     | N/A                                              |
|         | 5670       | 134     | 7.38                                             |
|         | 5755       | 151     | 5.90                                             |
|         | 5795       | 159     | 6.01                                             |

**Table 9-29**  
**IEEE 802.11ac Average RF Power – 80 MHz Bandwidth**

| Antenna   | Freq [MHz] | Channel | 80MHz BW 802.11ac (5GHz) Conducted Power [dBm] |      |      |      |       |      |       |       |      |      |
|-----------|------------|---------|------------------------------------------------|------|------|------|-------|------|-------|-------|------|------|
|           |            |         | Data Rate [Mbps]                               |      |      |      |       |      |       |       |      |      |
|           |            |         | 29.3                                           | 58.5 | 87.8 | 117  | 175.5 | 234  | 263.3 | 292.5 | 351  | 390  |
| Antenna 1 | 5210       | 42      | 6.56                                           | 6.50 | 6.64 | 6.61 | 6.50  | 6.46 | 6.59  | 6.39  | 6.40 | 6.50 |
|           | 5290       | 58      | 6.48                                           | 6.32 | 6.35 | 6.44 | 6.35  | 6.45 | 6.40  | 6.42  | 6.50 | 6.33 |
|           | 5530       | 106     | 6.51                                           | 6.57 | 6.40 | 6.33 | 6.45  | 6.47 | 6.50  | 6.39  | 6.34 | 6.54 |
|           | 5775       | 155     | 6.38                                           | 6.33 | 6.47 | 6.33 | 6.29  | 6.41 | 6.37  | 6.55  | 6.46 | 6.46 |
| Antenna 2 | 5210       | 42      | 6.63                                           | 6.58 | 6.60 | 6.59 | 6.54  | 6.52 | 6.53  | 6.52  | 6.61 | 6.51 |
|           | 5290       | 58      | 6.55                                           | 6.52 | 6.44 | 6.46 | 6.41  | 6.50 | 6.52  | 6.52  | 6.41 | 6.54 |
|           | 5530       | 106     | 5.57                                           | 5.44 | 5.50 | 5.61 | 5.48  | 5.53 | 5.61  | 5.46  | 5.60 | 5.46 |
|           | 5775       | 155     | 6.25                                           | 6.13 | 6.13 | 6.28 | 6.21  | 6.11 | 6.10  | 6.11  | 6.26 | 6.21 |

**Table 9-30**  
**MIMO IEEE 802.11ac Average RF Power – 80 MHz Bandwidth**

| Antenna | Freq [MHz] | Channel | 80MHz BW 802.11ac (5GHz) |
|---------|------------|---------|--------------------------|
|         |            |         | Data Rate [Mbps]         |
|         |            |         | 58.5                     |
| MIMO    | 5210       | 42      | 5.94                     |
|         | 5290       | 58      | 5.56                     |
|         | 5530       | 106     | 7.27                     |
|         | 5775       | 155     | 7.41                     |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 38 of 79                                                                         |                                        |

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- For SISO 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- For SISO 5 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11a were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
- For MIMO 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11n were selected for SAR evaluation.
- For MIMO 5 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11n were selected for SAR evaluation.
- Full SAR tests for all IEEE 802.11ac configurations were not required because the average output power was not more than 0.25 dB higher than IEEE 802.11a mode. IEEE 802.11ac was evaluated for the highest IEEE 802.11a position in each 5 GHz band and exposure condition.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.




**Figure 9-2**  
**Power Measurement Setup for Bandwidths < 50 MHz**




**Figure 9-3**  
**Power Measurement Setup for Bandwidths > 50 MHz**

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 39 of 79                                                                         |                                 |

# 10 SYSTEM VERIFICATION

## 10.1 Tissue Verification

**Table 10-1**  
**Measured Tissue Properties**

| Calibrated for Tests Performed on: | Tissue Type | Tissue Temp During Calibration (°C) | Measured Frequency (MHz) | Measured Conductivity, $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon$ | TARGET Conductivity, $\sigma$ (S/m) | TARGET Dielectric Constant, $\epsilon$ | % dev $\sigma$ | % dev $\epsilon$ |
|------------------------------------|-------------|-------------------------------------|--------------------------|---------------------------------------|------------------------------------------|-------------------------------------|----------------------------------------|----------------|------------------|
| 2/17/2014                          | 750H        | 22.6                                | 695                      | 0.883                                 | 44.059                                   | 0.889                               | 42.227                                 | -0.67%         | 4.34%            |
|                                    |             |                                     | 710                      | 0.894                                 | 43.792                                   | 0.890                               | 42.149                                 | 0.45%          | 3.90%            |
|                                    |             |                                     | 725                      | 0.904                                 | 43.648                                   | 0.891                               | 42.071                                 | 1.46%          | 3.75%            |
|                                    |             |                                     | 740                      | 0.920                                 | 43.468                                   | 0.893                               | 41.994                                 | 3.02%          | 3.51%            |
|                                    |             |                                     | 755                      | 0.933                                 | 43.196                                   | 0.894                               | 41.916                                 | 4.36%          | 3.05%            |
| 2/17/2014                          | 835H        | 22.8                                | 820                      | 0.892                                 | 41.437                                   | 0.899                               | 41.578                                 | -0.78%         | -0.34%           |
|                                    |             |                                     | 835                      | 0.906                                 | 41.195                                   | 0.900                               | 41.500                                 | 0.67%          | -0.73%           |
|                                    |             |                                     | 850                      | 0.919                                 | 40.975                                   | 0.916                               | 41.500                                 | 0.33%          | -1.27%           |
| 2/18/2014                          | 1750H       | 22.9                                | 1710                     | 1.359                                 | 38.666                                   | 1.348                               | 40.142                                 | 0.82%          | -3.68%           |
|                                    |             |                                     | 1750                     | 1.400                                 | 38.485                                   | 1.371                               | 40.079                                 | 2.12%          | -3.98%           |
|                                    |             |                                     | 1790                     | 1.441                                 | 38.294                                   | 1.394                               | 40.016                                 | 3.37%          | -4.30%           |
| 2/19/2014                          | 1900H       | 21.9                                | 1850                     | 1.395                                 | 38.419                                   | 1.400                               | 40.000                                 | -0.36%         | -3.95%           |
|                                    |             |                                     | 1880                     | 1.427                                 | 38.295                                   | 1.400                               | 40.000                                 | 1.93%          | -4.26%           |
|                                    |             |                                     | 1910                     | 1.459                                 | 38.171                                   | 1.400                               | 40.000                                 | 4.21%          | -4.57%           |
| 2/18/2014                          | 2450H       | 22.8                                | 2401                     | 1.822                                 | 38.991                                   | 1.756                               | 39.287                                 | 3.76%          | -0.75%           |
|                                    |             |                                     | 2450                     | 1.879                                 | 38.816                                   | 1.800                               | 39.200                                 | 4.39%          | -0.98%           |
|                                    |             |                                     | 2499                     | 1.935                                 | 38.638                                   | 1.853                               | 39.138                                 | 4.43%          | -1.28%           |
|                                    |             |                                     | 5180                     | 4.474                                 | 36.244                                   | 4.635                               | 36.009                                 | -3.47%         | 0.65%            |
|                                    |             |                                     | 5200                     | 4.508                                 | 36.214                                   | 4.655                               | 35.986                                 | -3.16%         | 0.63%            |
| 2/3/2014                           | 5200H-5800H | 23.0                                | 5220                     | 4.522                                 | 36.197                                   | 4.676                               | 35.963                                 | -3.29%         | 0.65%            |
|                                    |             |                                     | 5240                     | 4.538                                 | 36.162                                   | 4.696                               | 35.940                                 | -3.36%         | 0.62%            |
|                                    |             |                                     | 5260                     | 4.570                                 | 36.130                                   | 4.717                               | 35.917                                 | -3.12%         | 0.59%            |
|                                    |             |                                     | 5280                     | 4.590                                 | 36.108                                   | 4.737                               | 35.894                                 | -3.10%         | 0.60%            |
|                                    |             |                                     | 5300                     | 4.605                                 | 36.076                                   | 4.758                               | 35.871                                 | -3.22%         | 0.57%            |
|                                    |             |                                     | 5500                     | 4.822                                 | 35.798                                   | 4.963                               | 35.643                                 | -2.84%         | 0.43%            |
|                                    |             |                                     | 5520                     | 4.842                                 | 35.754                                   | 4.983                               | 35.620                                 | -2.83%         | 0.38%            |
|                                    |             |                                     | 5540                     | 4.868                                 | 35.725                                   | 5.004                               | 35.597                                 | -2.72%         | 0.36%            |
|                                    |             |                                     | 5580                     | 4.910                                 | 35.706                                   | 5.045                               | 35.551                                 | -2.68%         | 0.44%            |
|                                    |             |                                     | 5600                     | 4.925                                 | 35.697                                   | 5.065                               | 35.529                                 | -2.76%         | 0.47%            |
|                                    |             |                                     | 5680                     | 5.006                                 | 35.596                                   | 5.147                               | 35.437                                 | -2.74%         | 0.45%            |
|                                    |             |                                     | 5765                     | 5.088                                 | 35.493                                   | 5.234                               | 35.340                                 | -2.79%         | 0.43%            |
|                                    |             |                                     | 5785                     | 5.101                                 | 35.458                                   | 5.255                               | 35.317                                 | -2.93%         | 0.40%            |
|                                    |             |                                     | 5800                     | 5.112                                 | 35.479                                   | 5.270                               | 35.300                                 | -3.00%         | 0.51%            |
| 2/18/2014                          | 750B        | 21.0                                | 695                      | 0.928                                 | 55.021                                   | 0.959                               | 55.745                                 | -3.23%         | -1.30%           |
|                                    |             |                                     | 710                      | 0.941                                 | 54.929                                   | 0.960                               | 55.687                                 | -1.98%         | -1.36%           |
|                                    |             |                                     | 725                      | 0.956                                 | 54.753                                   | 0.961                               | 55.629                                 | -0.52%         | -1.57%           |
|                                    |             |                                     | 740                      | 0.967                                 | 54.564                                   | 0.963                               | 55.570                                 | 0.42%          | -1.81%           |
|                                    |             |                                     | 755                      | 0.980                                 | 54.460                                   | 0.964                               | 55.512                                 | 1.66%          | -1.90%           |
| 2/17/2014                          | 835B        | 19.9                                | 820                      | 0.958                                 | 55.243                                   | 0.969                               | 55.258                                 | -1.14%         | -0.03%           |
|                                    |             |                                     | 835                      | 0.976                                 | 55.109                                   | 0.970                               | 55.200                                 | 0.62%          | -0.16%           |
|                                    |             |                                     | 850                      | 0.992                                 | 54.892                                   | 0.988                               | 55.154                                 | 0.40%          | -0.48%           |
| 2/18/2014                          | 1750B       | 23.0                                | 1710                     | 1.466                                 | 54.473                                   | 1.463                               | 53.537                                 | 0.21%          | 1.75%            |
|                                    |             |                                     | 1750                     | 1.511                                 | 54.336                                   | 1.488                               | 53.432                                 | 1.55%          | 1.69%            |
|                                    |             |                                     | 1790                     | 1.554                                 | 54.171                                   | 1.514                               | 53.326                                 | 2.64%          | 1.58%            |
| 2/17/2014                          | 1900B       | 23.2                                | 1850                     | 1.489                                 | 53.263                                   | 1.520                               | 53.300                                 | -2.04%         | -0.07%           |
|                                    |             |                                     | 1880                     | 1.525                                 | 53.183                                   | 1.520                               | 53.300                                 | 0.33%          | -0.22%           |
|                                    |             |                                     | 1910                     | 1.558                                 | 53.102                                   | 1.520                               | 53.300                                 | 2.50%          | -0.37%           |
| 3/31/2014                          | 1900B       | 23.3                                | 1850                     | 1.510                                 | 51.115                                   | 1.520                               | 53.300                                 | -0.66%         | -4.10%           |
|                                    |             |                                     | 1880                     | 1.545                                 | 51.042                                   | 1.520                               | 53.300                                 | 1.64%          | -4.24%           |
|                                    |             |                                     | 1910                     | 1.581                                 | 50.925                                   | 1.520                               | 53.300                                 | 4.01%          | -4.46%           |
| 2/12/2014                          | 2450B       | 24.0                                | 2401                     | 1.872                                 | 51.518                                   | 1.903                               | 52.765                                 | -1.63%         | -2.36%           |
|                                    |             |                                     | 2450                     | 1.937                                 | 51.331                                   | 1.950                               | 52.700                                 | -0.67%         | -2.60%           |
|                                    |             |                                     | 2499                     | 1.998                                 | 51.123                                   | 2.019                               | 52.638                                 | -1.04%         | -2.88%           |
|                                    |             |                                     | 5180                     | 5.116                                 | 47.453                                   | 5.276                               | 49.041                                 | -3.03%         | -3.24%           |
|                                    |             |                                     | 5200                     | 5.147                                 | 47.331                                   | 5.299                               | 49.014                                 | -2.87%         | -3.43%           |
| 2/6/2014                           | 5200B-5800B | 24.3                                | 5220                     | 5.173                                 | 47.224                                   | 5.323                               | 48.987                                 | -2.82%         | -3.60%           |
|                                    |             |                                     | 5260                     | 5.256                                 | 47.134                                   | 5.369                               | 48.933                                 | -2.10%         | -3.68%           |
|                                    |             |                                     | 5280                     | 5.277                                 | 47.164                                   | 5.393                               | 48.906                                 | -2.15%         | -3.56%           |
|                                    |             |                                     | 5300                     | 5.298                                 | 47.170                                   | 5.416                               | 48.879                                 | -2.18%         | -3.50%           |
|                                    |             |                                     | 5500                     | 5.600                                 | 46.464                                   | 5.650                               | 48.607                                 | -0.88%         | -4.41%           |
|                                    |             |                                     | 5520                     | 5.646                                 | 46.503                                   | 5.673                               | 48.580                                 | -0.48%         | -4.28%           |
|                                    |             |                                     | 5540                     | 5.663                                 | 46.576                                   | 5.696                               | 48.553                                 | -0.58%         | -4.07%           |
|                                    |             |                                     | 5745                     | 5.980                                 | 45.916                                   | 5.936                               | 48.275                                 | 0.74%          | -4.89%           |
|                                    |             |                                     | 5765                     | 6.028                                 | 45.890                                   | 5.959                               | 48.248                                 | 1.16%          | -4.89%           |
|                                    |             |                                     | 5785                     | 6.055                                 | 45.952                                   | 5.982                               | 48.220                                 | 1.22%          | -4.70%           |
|                                    |             |                                     | 5800                     | 6.062                                 | 45.987                                   | 6.000                               | 48.200                                 | 1.03%          | -4.59%           |

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 40 of 79                                                                         |                                 |

## 10.2 Test System Verification

Prior to SAR assessment, the system is verified to  $\pm 10\%$  of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

**Table 10-2**  
**System Verification Results**

| System Verification<br>TARGET & MEASURED |                        |             |            |                |                  |                 |           |          |                                   |                                     |                                         |                             |
|------------------------------------------|------------------------|-------------|------------|----------------|------------------|-----------------|-----------|----------|-----------------------------------|-------------------------------------|-----------------------------------------|-----------------------------|
| SAR System #                             | Tissue Frequency (MHz) | Tissue Type | Date:      | Amb. Temp (°C) | Liquid Temp (°C) | Input Power (W) | Dipole SN | Probe SN | Measured SAR <sub>1g</sub> (W/kg) | 1 W Target SAR <sub>1g</sub> (W/kg) | 1 W Normalized SAR <sub>1g</sub> (W/kg) | Deviation <sub>1g</sub> (%) |
| B                                        | 750                    | HEAD        | 02/17/2014 | 23.2           | 22.6             | 0.100           | 1054      | 3288     | 0.856                             | 8.500                               | 8.560                                   | 0.71%                       |
| H                                        | 835                    | HEAD        | 02/17/2014 | 24.3           | 22.9             | 0.100           | 4d119     | 3318     | 0.935                             | 9.680                               | 9.350                                   | -3.41%                      |
| B                                        | 1750                   | HEAD        | 02/18/2014 | 23.4           | 22.9             | 0.100           | 1008      | 3288     | 3.550                             | 36.800                              | 35.500                                  | -3.53%                      |
| C                                        | 1900                   | HEAD        | 02/19/2014 | 23.7           | 21.9             | 0.100           | 5d141     | 3263     | 3.970                             | 40.800                              | 39.700                                  | -2.70%                      |
| K                                        | 2450                   | HEAD        | 02/18/2014 | 23.5           | 23.0             | 0.100           | 719       | 3287     | 5.180                             | 53.200                              | 51.800                                  | -2.63%                      |
| A                                        | 5200                   | HEAD        | 02/03/2014 | 24.4           | 23.0             | 0.100           | 1007      | 3920     | 7.720                             | 77.500                              | 77.200                                  | -0.39%                      |
| A                                        | 5300                   | HEAD        | 02/03/2014 | 24.4           | 23.1             | 0.100           | 1007      | 3920     | 7.900                             | 80.200                              | 79.000                                  | -1.50%                      |
| A                                        | 5500                   | HEAD        | 02/03/2014 | 24.2           | 23.2             | 0.100           | 1007      | 3920     | 7.740                             | 81.400                              | 77.400                                  | -4.91%                      |
| A                                        | 5600                   | HEAD        | 02/03/2014 | 24.5           | 23.3             | 0.100           | 1007      | 3920     | 7.900                             | 80.000                              | 79.000                                  | -1.25%                      |
| A                                        | 5800                   | HEAD        | 02/03/2014 | 24.3           | 23.3             | 0.100           | 1007      | 3920     | 7.680                             | 77.500                              | 76.800                                  | -0.90%                      |
| C                                        | 750                    | BODY        | 02/18/2014 | 19.9           | 20.6             | 0.100           | 1054      | 3263     | 0.882                             | 8.720                               | 8.820                                   | 1.15%                       |
| C                                        | 835                    | BODY        | 02/17/2014 | 19.7           | 19.7             | 0.100           | 4d133     | 3263     | 0.953                             | 9.610                               | 9.530                                   | -0.83%                      |
| B                                        | 1750                   | BODY        | 02/18/2014 | 23.4           | 23.0             | 0.100           | 1008      | 3288     | 3.760                             | 38.200                              | 37.600                                  | -1.57%                      |
| I                                        | 1900                   | BODY        | 02/17/2014 | 23.7           | 23.2             | 0.100           | 5d149     | 3319     | 3.830                             | 40.500                              | 38.300                                  | -5.43%                      |
| D                                        | 1900                   | BODY        | 03/31/2014 | 23.2           | 21.6             | 0.100           | 5d149     | 3022     | 4.200                             | 40.500                              | 42.000                                  | 3.70%                       |
| H                                        | 2450                   | BODY        | 02/12/2014 | 24.4           | 24.0             | 0.100           | 719       | 3318     | 5.410                             | 51.700                              | 54.100                                  | 4.64%                       |
| E                                        | 5200                   | BODY        | 02/06/2014 | 24.0           | 23.8             | 0.100           | 1120      | 3914     | 7.700                             | 76.600                              | 77.000                                  | 0.52%                       |
| E                                        | 5300                   | BODY        | 02/06/2014 | 24.0           | 23.8             | 0.100           | 1120      | 3914     | 7.650                             | 76.800                              | 76.500                                  | -0.39%                      |
| E                                        | 5500                   | BODY        | 02/06/2014 | 24.1           | 23.8             | 0.100           | 1120      | 3914     | 7.840                             | 79.800                              | 78.400                                  | -1.75%                      |
| E                                        | 5800                   | BODY        | 02/06/2014 | 24.1           | 23.7             | 0.100           | 1120      | 3914     | 7.170                             | 75.500                              | 71.700                                  | -5.03%                      |




**Figure 10-1**  
**System Verification Setup Diagram**



**Figure 10-2**  
**System Verification Setup Photo**

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 41 of 79                                                                         |                                        |

# 11 SAR DATA SUMMARY

## 11.1 Standalone Head SAR Data

Table 11-1  
Cell. CDMA/EVDO Head SAR

| MEASUREMENT RESULTS                                                                               |     |            |             |                             |                       |                  |       |                                                 |                   |                      |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|------------|-------------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|-------------------|----------------------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode/Band  | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Cover Type        | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |            |             |                             |                       |                  |       |                                                 |                   |                      |            | (W/kg)   |                | (W/kg)          |        |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.40                 | 0.05             | Right | Cheek                                           | Standard          | 32EF0                | 1:1        | 0.533    | 1.148          | 0.612           | A1     |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.40                 | 0.20             | Right | Cheek                                           | Wireless Charging | 32EF0                | 1:1        | 0.512    | 1.148          | 0.588           |        |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.40                 | 0.01             | Right | Tilt                                            | Standard          | 32EF0                | 1:1        | 0.306    | 1.148          | 0.351           |        |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.40                 | 0.02             | Left  | Cheek                                           | Standard          | 32EF0                | 1:1        | 0.398    | 1.148          | 0.457           |        |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.40                 | -0.02            | Left  | Tilt                                            | Standard          | 32EF0                | 1:1        | 0.265    | 1.148          | 0.304           |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.40                 | -0.04            | Right | Cheek                                           | Standard          | 32EF0                | 1:1        | 0.532    | 1.148          | 0.611           |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.40                 | -0.06            | Right | Cheek                                           | Wireless Charging | 32EF0                | 1:1        | 0.512    | 1.148          | 0.588           |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.40                 | -0.02            | Right | Tilt                                            | Standard          | 32EF0                | 1:1        | 0.285    | 1.148          | 0.327           |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.40                 | 0.01             | Left  | Cheek                                           | Standard          | 32EF0                | 1:1        | 0.430    | 1.148          | 0.494           |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.40                 | -0.01            | Left  | Tilt                                            | Standard          | 32EF0                | 1:1        | 0.290    | 1.148          | 0.333           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |            |             |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                   |                      |            |          |                |                 |        |

Table 11-2  
PCS CDMA/EVDO Head SAR

| MEASUREMENT RESULTS                                                                               |     |           |             |                             |                       |                  |       |                                                 |                   |                      |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|-----------|-------------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|-------------------|----------------------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode/Band | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Cover Type        | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |           |             |                             |                       |                  |       |                                                 |                   |                      |            | (W/kg)   |                | (W/kg)          |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.49                 | 0.01             | Right | Cheek                                           | Standard          | 32EC6                | 1:1        | 0.439    | 1.125          | 0.494           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.49                 | -0.05            | Right | Cheek                                           | Wireless Charging | 32EC6                | 1:1        | 0.500    | 1.125          | 0.563           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.49                 | -0.04            | Right | Tilt                                            | Standard          | 32EC6                | 1:1        | 0.232    | 1.125          | 0.261           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.49                 | -0.07            | Left  | Cheek                                           | Standard          | 32EC6                | 1:1        | 0.254    | 1.125          | 0.286           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.49                 | -0.01            | Left  | Tilt                                            | Standard          | 32EC6                | 1:1        | 0.179    | 1.125          | 0.201           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 23.0                        | 22.29                 | -0.02            | Right | Cheek                                           | Standard          | 3R725                | 1:1        | 0.294    | 1.178          | 0.346           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 23.0                        | 22.29                 | 0.13             | Right | Tilt                                            | Standard          | 3R725                | 1:1        | 0.111    | 1.178          | 0.131           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 23.0                        | 22.29                 | 0.12             | Left  | Cheek                                           | Standard          | 3R725                | 1:1        | 0.228    | 1.178          | 0.269           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 23.0                        | 22.29                 | 0.16             | Left  | Tilt                                            | Standard          | 3R725                | 1:1        | 0.082    | 1.178          | 0.097           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.46                 | -0.04            | Right | Cheek                                           | Standard          | 32EC6                | 1:1        | 0.465    | 1.132          | 0.526           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.46                 | 0.03             | Right | Cheek                                           | Wireless Charging | 32EC6                | 1:1        | 0.543    | 1.132          | 0.615           | A2     |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.46                 | 0.03             | Right | Tilt                                            | Standard          | 32EC6                | 1:1        | 0.227    | 1.132          | 0.257           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.46                 | -0.02            | Left  | Cheek                                           | Standard          | 32EC6                | 1:1        | 0.263    | 1.132          | 0.298           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.46                 | 0.13             | Left  | Tilt                                            | Standard          | 32EC6                | 1:1        | 0.188    | 1.132          | 0.213           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 23.0                        | 22.28                 | 0.00             | Right | Cheek                                           | Standard          | 3R725                | 1:1        | 0.298    | 1.180          | 0.352           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 23.0                        | 22.28                 | 0.03             | Right | Tilt                                            | Standard          | 3R725                | 1:1        | 0.117    | 1.180          | 0.138           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 23.0                        | 22.28                 | 0.00             | Left  | Cheek                                           | Standard          | 3R725                | 1:1        | 0.230    | 1.180          | 0.271           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 23.0                        | 22.28                 | -0.05            | Left  | Tilt                                            | Standard          | 3R725                | 1:1        | 0.094    | 1.180          | 0.111           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |           |             |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                   |                      |            |          |                |                 |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 42 of 79                                                                         |                                 |

**Table 11-3**  
**LTE Band 12 Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                 |            |                             |                       |                  |          |      |               |                                                 |         |           |                      |            |                 |                |                        |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|-----------------|------------|-----------------------------|-----------------------|------------------|----------|------|---------------|-------------------------------------------------|---------|-----------|----------------------|------------|-----------------|----------------|------------------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz] | Cover Type | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation                                      | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) (W/kg) | Scaling Factor | Scaled SAR (1g) (W/kg) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                 |            |                             |                       |                  |          |      |               |                                                 |         |           |                      |            |                 |                |                        |        |    |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 23.5                  | 23.08            | -0.02    | 0    | Right         | Cheek                                           | QPSK    | 1         | 0                    | 32EC6      | 1:1             | 0.238          | 1.102                  | 0.262  |    |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 22.5                  | 22.02            | 0.03     | 1    | Right         | Cheek                                           | QPSK    | 25        | 0                    | 32EC6      | 1:1             | 0.167          | 1.117                  | 0.187  |    |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 23.5                  | 23.08            | 0.14     | 0    | Right         | Tilt                                            | QPSK    | 1         | 0                    | 32EC6      | 1:1             | 0.167          | 1.102                  | 0.184  |    |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 22.5                  | 22.02            | -0.17    | 1    | Right         | Tilt                                            | QPSK    | 25        | 0                    | 32EC6      | 1:1             | 0.116          | 1.117                  | 0.130  |    |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 23.5                  | 23.08            | 0.06     | 0    | Left          | Cheek                                           | QPSK    | 1         | 0                    | 32EC6      | 1:1             | 0.305          | 1.102                  | 0.336  | A3 |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Wireless Charging           | 23.5                  | 23.08            | 0.17     | 0    | Left          | Cheek                                           | QPSK    | 1         | 0                    | 32EC6      | 1:1             | 0.227          | 1.102                  | 0.250  |    |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 22.5                  | 22.02            | 0.06     | 1    | Left          | Cheek                                           | QPSK    | 25        | 0                    | 32EC6      | 1:1             | 0.245          | 1.117                  | 0.274  |    |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 23.5                  | 23.08            | 0.08     | 0    | Left          | Tilt                                            | QPSK    | 1         | 0                    | 32EC6      | 1:1             | 0.163          | 1.102                  | 0.180  |    |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 22.5                  | 22.02            | 0.02     | 1    | Left          | Tilt                                            | QPSK    | 25        | 0                    | 32EC6      | 1:1             | 0.135          | 1.117                  | 0.151  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                 |            |                             |                       |                  |          |      |               | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |           |                      |            |                 |                |                        |        |    |

**Table 11-4**  
**LTE Band 4 (AWS) Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                  |            |                             |                       |                  |          |      |               |            |                                                 |           |                      |            |          |                |                 |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|------------|-----------------------------|-----------------------|------------------|----------|------|---------------|------------|-------------------------------------------------|-----------|----------------------|------------|----------|----------------|-----------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Cover Type | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation | RB Size                                         | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                  |            |                             |                       |                  |          |      |               |            |                                                 |           |                      |            | (W/kg)   |                | (W/kg)          |        |    |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 23.5                  | 23.50            | 0.00     | 0    | Right         | Cheek      | QPSK                                            | 1         | 0                    | 32EC6      | 1:1      | 0.132          | 1.000           | 0.132  |    |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 22.5                  | 22.43            | 0.13     | 1    | Right         | Cheek      | QPSK                                            | 25        | 12                   | 32EC6      | 1:1      | 0.147          | 1.016           | 0.149  |    |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 23.5                  | 23.50            | 0.19     | 0    | Right         | Tilt       | QPSK                                            | 1         | 0                    | 32EC6      | 1:1      | 0.138          | 1.000           | 0.138  |    |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 22.5                  | 22.43            | -0.03    | 1    | Right         | Tilt       | QPSK                                            | 25        | 12                   | 32EC6      | 1:1      | 0.141          | 1.016           | 0.143  |    |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 23.5                  | 23.50            | -0.04    | 0    | Left          | Cheek      | QPSK                                            | 1         | 0                    | 32EC6      | 1:1      | 0.382          | 1.000           | 0.382  | A4 |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Wireless Charging           | 23.5                  | 23.50            | -0.07    | 0    | Left          | Cheek      | QPSK                                            | 1         | 0                    | 32EC6      | 1:1      | 0.294          | 1.000           | 0.294  |    |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 22.5                  | 22.43            | -0.01    | 1    | Left          | Cheek      | QPSK                                            | 25        | 12                   | 32EC6      | 1:1      | 0.288          | 1.016           | 0.293  |    |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 23.5                  | 23.50            | -0.01    | 0    | Left          | Tilt       | QPSK                                            | 1         | 0                    | 32EC6      | 1:1      | 0.128          | 1.000           | 0.128  |    |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 22.5                  | 22.43            | -0.10    | 1    | Left          | Tilt       | QPSK                                            | 25        | 12                   | 32EC6      | 1:1      | 0.122          | 1.016           | 0.124  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |            |                             |                       |                  |          |      |               |            | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |           |                      |            |          |                |                 |        |    |

**Table 11-5**  
**LTE Band 25 (PCS) Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                   |            |                             |                       |                  |          |      |               |            |                                                 |           |                      |            |                 |                |                        |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|-------------------|------------|-----------------------------|-----------------------|------------------|----------|------|---------------|------------|-------------------------------------------------|-----------|----------------------|------------|-----------------|----------------|------------------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]   | Cover Type | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation | RB Size                                         | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) (W/kg) | Scaling Factor | Scaled SAR (1g) (W/kg) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                   |            |                             |                       |                  |          |      |               |            |                                                 |           |                      |            |                 |                |                        |        |    |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | -0.02    | 0    | Right         | Cheek      | QPSK                                            | 1         | 0                    | 32EC6      | 1:1             | 0.337          | 1.035                  | 0.349  |    |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | 0.01     | 1    | Right         | Cheek      | QPSK                                            | 25        | 0                    | 32EC6      | 1:1             | 0.265          | 1.069                  | 0.283  |    |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | 0.01     | 0    | Right         | Tilt       | QPSK                                            | 1         | 0                    | 32EC6      | 1:1             | 0.260          | 1.035                  | 0.269  |    |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | 0.00     | 1    | Right         | Tilt       | QPSK                                            | 25        | 0                    | 32EC6      | 1:1             | 0.201          | 1.069                  | 0.215  |    |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | 0.04     | 0    | Left          | Cheek      | QPSK                                            | 1         | 0                    | 32EC6      | 1:1             | 0.613          | 1.035                  | 0.634  | A5 |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Wireless Charging           | 23.5                  | 23.35            | 0.03     | 0    | Left          | Cheek      | QPSK                                            | 1         | 0                    | 32EC6      | 1:1             | 0.605          | 1.035                  | 0.626  |    |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | 0.02     | 1    | Left          | Cheek      | QPSK                                            | 25        | 0                    | 32EC6      | 1:1             | 0.469          | 1.069                  | 0.501  |    |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | 0.05     | 0    | Left          | Tilt       | QPSK                                            | 1         | 0                    | 32EC6      | 1:1             | 0.220          | 1.035                  | 0.228  |    |
| 1910.00                                                                                           | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | 0.07     | 1    | Left          | Tilt       | QPSK                                            | 25        | 0                    | 32EC6      | 1:1             | 0.159          | 1.069                  | 0.170  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                   |            |                             |                       |                  |          |      |               |            | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |           |                      |            |                 |                |                        |        |    |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 43 of 79                                                                         |                                 |

**Table 11-6  
DTS Head SAR**

| MEASUREMENT RESULTS                                                                               |     |               |         |                             |                       |                  |       |                                                 |         |                   |                      |                  |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|---------------|---------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|---------|-------------------|----------------------|------------------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode          | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Antenna | Cover Type        | Device Serial Number | Data Rate (Mbps) | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |               |         |                             |                       |                  |       |                                                 |         |                   |                      |                  |            | (W/kg)   |                | (W/kg)          |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.94                 | 0.20             | Right | Cheek                                           | 1       | Standard          | 328C6                | 1                | 1:1        | 0.163    | 1.138          | 0.185           | A6     |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.94                 | 0.02             | Right | Cheek                                           | 1       | Wireless Charging | 328C6                | 1                | 1:1        | 0.156    | 1.138          | 0.178           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.94                 | -0.04            | Right | Tilt                                            | 1       | Standard          | 328C6                | 1                | 1:1        | 0.158    | 1.138          | 0.180           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.94                 | 0.02             | Left  | Cheek                                           | 1       | Standard          | 328C6                | 1                | 1:1        | 0.129    | 1.138          | 0.147           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.94                 | 0.03             | Left  | Tilt                                            | 1       | Standard          | 328C6                | 1                | 1:1        | 0.128    | 1.138          | 0.146           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.74                 | 0.10             | Right | Cheek                                           | 2       | Standard          | 328C6                | 1                | 1:1        | 0.033    | 1.191          | 0.039           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.74                 | 0.12             | Right | Tilt                                            | 2       | Standard          | 328C6                | 1                | 1:1        | 0.007    | 1.191          | 0.008           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.74                 | 0.06             | Left  | Cheek                                           | 2       | Standard          | 328C6                | 1                | 1:1        | 0.009    | 1.191          | 0.011           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 12.5                        | 11.74                 | 0.20             | Left  | Tilt                                            | 2       | Standard          | 328C6                | 1                | 1:1        | 0.004    | 1.191          | 0.005           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 12.5                        | 11.85                 | -0.08            | Right | Cheek                                           | MIMO    | Standard          | 328C6                | 13               | 1:1        | 0.089    | 1.161          | 0.103           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 12.5                        | 11.85                 | -0.10            | Right | Tilt                                            | MIMO    | Standard          | 328C6                | 13               | 1:1        | 0.078    | 1.161          | 0.091           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 12.5                        | 11.85                 | 0.03             | Left  | Cheek                                           | MIMO    | Standard          | 328C6                | 13               | 1:1        | 0.104    | 1.161          | 0.121           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 12.5                        | 11.85                 | 0.03             | Left  | Tilt                                            | MIMO    | Standard          | 328C6                | 13               | 1:1        | 0.107    | 1.161          | 0.124           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 12.5                        | 11.85                 | -0.02            | Left  | Tilt                                            | MIMO    | Wireless Charging | 328C6                | 13               | 1:1        | 0.098    | 1.161          | 0.114           |        |
| 5785                                                                                              | 157 | IEEE 802.11a  | OFDM    | 7.5                         | 6.87                  | 0.06             | Right | Cheek                                           | 1       | Standard          | 31F35                | 6                | 1:1        | 0.014    | 1.156          | 0.016           |        |
| 5785                                                                                              | 157 | IEEE 802.11a  | OFDM    | 7.5                         | 6.87                  | 0.10             | Right | Tilt                                            | 1       | Standard          | 31F35                | 6                | 1:1        | 0.022    | 1.156          | 0.025           |        |
| 5775                                                                                              | 155 | IEEE 802.11ac | OFDM    | 7.5                         | 6.38                  | 0.04             | Right | Tilt                                            | 1       | Standard          | 31F35                | 29.3             | 1:1        | 0.013    | 1.294          | 0.017           |        |
| 5785                                                                                              | 157 | IEEE 802.11a  | OFDM    | 7.5                         | 6.87                  | 0.16             | Left  | Cheek                                           | 1       | Standard          | 31F35                | 6                | 1:1        | 0.011    | 1.156          | 0.013           |        |
| 5785                                                                                              | 157 | IEEE 802.11a  | OFDM    | 7.5                         | 6.87                  | 0.04             | Left  | Tilt                                            | 1       | Standard          | 31F35                | 6                | 1:1        | 0.014    | 1.156          | 0.016           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 7.5                         | 6.58                  | 0.06             | Right | Cheek                                           | 2       | Standard          | 31F35                | 6                | 1:1        | 0.134    | 1.236          | 0.166           | A7     |
| 5775                                                                                              | 155 | IEEE 802.11ac | OFDM    | 7.5                         | 6.25                  | 0.06             | Right | Cheek                                           | 2       | Standard          | 31F35                | 29.3             | 1:1        | 0.112    | 1.334          | 0.149           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 7.5                         | 6.58                  | 0.06             | Right | Tilt                                            | 2       | Standard          | 31F35                | 6                | 1:1        | 0.060    | 1.236          | 0.074           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 7.5                         | 6.58                  | 0.04             | Left  | Cheek                                           | 2       | Standard          | 31F35                | 6                | 1:1        | 0.037    | 1.236          | 0.046           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 7.5                         | 6.58                  | -0.07            | Left  | Tilt                                            | 2       | Standard          | 31F35                | 6                | 1:1        | 0.034    | 1.236          | 0.042           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 7.5                         | 6.57                  | -0.05            | Right | Cheek                                           | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.019    | 1.239          | 0.024           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 7.5                         | 6.57                  | 0.03             | Right | Tilt                                            | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.014    | 1.239          | 0.017           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 7.5                         | 6.57                  | 0.07             | Left  | Cheek                                           | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.016    | 1.239          | 0.020           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 7.5                         | 6.57                  | 0.05             | Left  | Tilt                                            | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.011    | 1.239          | 0.014           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |               |         |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |                   |                      |                  |            |          |                |                 |        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 44 of 79                     |                                                                                                                                                                                                        |                                 |



**Table 11-7  
NII Head SAR**

| MEASUREMENT RESULTS                      |     |               |         |                             |                       |                  |       |                      |         |                   |                      |                  |            |                 |                |                        |        |
|------------------------------------------|-----|---------------|---------|-----------------------------|-----------------------|------------------|-------|----------------------|---------|-------------------|----------------------|------------------|------------|-----------------|----------------|------------------------|--------|
| FREQUENCY                                |     | Mode          | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position        | Antenna | Cover Type        | Device Serial Number | Data Rate (Mbps) | Duty Cycle | SAR (1g) (W/kg) | Scaling Factor | Scaled SAR (1g) (W/kg) | Plot # |
| MHz                                      | Ch. |               |         |                             |                       |                  |       |                      |         |                   |                      |                  |            |                 |                |                        |        |
| 5180                                     | 36  | IEEE 802.11a  | OFDM    | 7.5                         | 6.74                  | 0.08             | Right | Cheek                | 1       | Standard          | 31F35                | 6                | 1:1        | 0.053           | 1.191          | 0.063                  |        |
| 5210                                     | 42  | IEEE 802.11ac | OFDM    | 7.5                         | 6.56                  | 0.02             | Right | Cheek                | 1       | Standard          | 31F35                | 29.3             | 1:1        | 0.039           | 1.242          | 0.048                  |        |
| 5180                                     | 36  | IEEE 802.11a  | OFDM    | 7.5                         | 6.74                  | 0.12             | Right | Tilt                 | 1       | Standard          | 31F35                | 6                | 1:1        | 0.052           | 1.191          | 0.062                  |        |
| 5180                                     | 36  | IEEE 802.11a  | OFDM    | 7.5                         | 6.74                  | -0.10            | Left  | Cheek                | 1       | Standard          | 31F35                | 6                | 1:1        | 0.035           | 1.191          | 0.042                  |        |
| 5180                                     | 36  | IEEE 802.11a  | OFDM    | 7.5                         | 6.74                  | -0.10            | Left  | Tilt                 | 1       | Standard          | 31F35                | 6                | 1:1        | 0.038           | 1.191          | 0.045                  |        |
| 5220                                     | 44  | IEEE 802.11a  | OFDM    | 7.5                         | 6.86                  | 0.07             | Right | Cheek                | 2       | Standard          | 31F35                | 6                | 1:1        | 0.022           | 1.159          | 0.025                  |        |
| 5210                                     | 42  | IEEE 802.11ac | OFDM    | 7.5                         | 6.63                  | 0.04             | Right | Cheek                | 2       | Standard          | 31F35                | 29.3             | 1:1        | 0.021           | 1.222          | 0.026                  |        |
| 5220                                     | 44  | IEEE 802.11a  | OFDM    | 7.5                         | 6.86                  | 0.09             | Right | Tilt                 | 2       | Standard          | 31F35                | 6                | 1:1        | 0.011           | 1.159          | 0.013                  |        |
| 5220                                     | 44  | IEEE 802.11a  | OFDM    | 7.5                         | 6.86                  | 0.00             | Left  | Cheek                | 2       | Standard          | 31F35                | 6                | 1:1        | 0.000           | 1.159          | 0.000                  |        |
| 5220                                     | 44  | IEEE 802.11a  | OFDM    | 7.5                         | 6.86                  | 0.00             | Left  | Tilt                 | 2       | Standard          | 31F35                | 6                | 1:1        | 0.000           | 1.159          | 0.000                  |        |
| 5240                                     | 48  | IEEE 802.11n  | OFDM    | 7.5                         | 6.06                  | 0.08             | Right | Cheek                | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.032           | 1.393          | 0.045                  |        |
| 5240                                     | 48  | IEEE 802.11n  | OFDM    | 7.5                         | 6.06                  | 0.07             | Right | Cheek                | MIMO    | Wireless Charging | 31F35                | 13               | 1:1        | 0.044           | 1.393          | 0.061                  |        |
| 5240                                     | 48  | IEEE 802.11n  | OFDM    | 7.5                         | 6.06                  | 0.11             | Right | Tilt                 | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.012           | 1.393          | 0.017                  |        |
| 5240                                     | 48  | IEEE 802.11n  | OFDM    | 7.5                         | 6.06                  | 0.21             | Left  | Cheek                | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.009           | 1.393          | 0.013                  |        |
| 5240                                     | 48  | IEEE 802.11n  | OFDM    | 7.5                         | 6.06                  | 0.06             | Left  | Tilt                 | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.009           | 1.393          | 0.013                  |        |
| 5260                                     | 52  | IEEE 802.11a  | OFDM    | 7.5                         | 6.69                  | 0.08             | Right | Cheek                | 1       | Standard          | 31F35                | 6                | 1:1        | 0.047           | 1.205          | 0.057                  |        |
| 5260                                     | 52  | IEEE 802.11a  | OFDM    | 7.5                         | 6.69                  | 0.12             | Right | Tilt                 | 1       | Standard          | 31F35                | 6                | 1:1        | 0.052           | 1.205          | 0.063                  |        |
| 5290                                     | 58  | IEEE 802.11ac | OFDM    | 7.5                         | 6.48                  | 0.07             | Right | Tilt                 | 1       | Standard          | 31F35                | 29.3             | 1:1        | 0.035           | 1.265          | 0.044                  |        |
| 5260                                     | 52  | IEEE 802.11a  | OFDM    | 7.5                         | 6.69                  | 0.06             | Left  | Cheek                | 1       | Standard          | 31F35                | 6                | 1:1        | 0.032           | 1.205          | 0.039                  |        |
| 5260                                     | 52  | IEEE 802.11a  | OFDM    | 7.5                         | 6.69                  | 0.06             | Left  | Tilt                 | 1       | Standard          | 31F35                | 6                | 1:1        | 0.041           | 1.205          | 0.049                  |        |
| 5260                                     | 52  | IEEE 802.11a  | OFDM    | 7.5                         | 6.95                  | 0.07             | Right | Cheek                | 2       | Standard          | 31F35                | 6                | 1:1        | 0.047           | 1.135          | 0.053                  |        |
| 5290                                     | 58  | IEEE 802.11ac | OFDM    | 7.5                         | 6.55                  | 0.11             | Right | Cheek                | 2       | Standard          | 31F35                | 29.3             | 1:1        | 0.036           | 1.245          | 0.045                  |        |
| 5260                                     | 52  | IEEE 802.11a  | OFDM    | 7.5                         | 6.95                  | -0.07            | Right | Tilt                 | 2       | Standard          | 31F35                | 6                | 1:1        | 0.013           | 1.135          | 0.015                  |        |
| 5260                                     | 52  | IEEE 802.11a  | OFDM    | 7.5                         | 6.95                  | 0.08             | Left  | Cheek                | 2       | Standard          | 31F35                | 6                | 1:1        | 0.007           | 1.135          | 0.008                  |        |
| 5260                                     | 52  | IEEE 802.11a  | OFDM    | 7.5                         | 6.95                  | -0.12            | Left  | Tilt                 | 2       | Standard          | 31F35                | 6                | 1:1        | 0.006           | 1.135          | 0.007                  |        |
| 5300                                     | 60  | IEEE 802.11n  | OFDM    | 7.5                         | 5.67                  | 0.00             | Right | Cheek                | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.009           | 1.524          | 0.014                  |        |
| 5300                                     | 60  | IEEE 802.11n  | OFDM    | 7.5                         | 5.67                  | 0.15             | Right | Tilt                 | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.010           | 1.524          | 0.015                  |        |
| 5300                                     | 60  | IEEE 802.11n  | OFDM    | 7.5                         | 5.67                  | 0.08             | Left  | Cheek                | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.009           | 1.524          | 0.014                  |        |
| 5300                                     | 60  | IEEE 802.11n  | OFDM    | 7.5                         | 5.67                  | 0.03             | Left  | Tilt                 | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.009           | 1.524          | 0.014                  |        |
| 5580                                     | 116 | IEEE 802.11a  | OFDM    | 7.5                         | 6.83                  | 0.08             | Right | Cheek                | 1       | Standard          | 31F35                | 6                | 1:1        | 0.022           | 1.167          | 0.026                  |        |
| 5580                                     | 116 | IEEE 802.11a  | OFDM    | 7.5                         | 6.83                  | 0.09             | Right | Tilt                 | 1       | Standard          | 31F35                | 6                | 1:1        | 0.029           | 1.167          | 0.034                  |        |
| 5530                                     | 106 | IEEE 802.11ac | OFDM    | 7.5                         | 6.51                  | 0.05             | Right | Tilt                 | 1       | Standard          | 31F35                | 29.3             | 1:1        | 0.044           | 1.256          | 0.055                  |        |
| 5580                                     | 116 | IEEE 802.11a  | OFDM    | 7.5                         | 6.83                  | 0.02             | Left  | Cheek                | 1       | Standard          | 31F35                | 6                | 1:1        | 0.016           | 1.167          | 0.019                  |        |
| 5580                                     | 116 | IEEE 802.11a  | OFDM    | 7.5                         | 6.83                  | 0.16             | Left  | Tilt                 | 1       | Standard          | 31F35                | 6                | 1:1        | 0.019           | 1.167          | 0.022                  |        |
| 5680                                     | 136 | IEEE 802.11a  | OFDM    | 7.5                         | 6.01                  | 0.02             | Right | Cheek                | 2       | Standard          | 31F35                | 6                | 1:1        | 0.154           | 1.409          | 0.217                  | A8     |
| 5680                                     | 136 | IEEE 802.11a  | OFDM    | 7.5                         | 6.01                  | 0.02             | Right | Cheek                | 2       | Wireless Charging | 31F35                | 6                | 1:1        | 0.133           | 1.409          | 0.187                  |        |
| 5530                                     | 106 | IEEE 802.11ac | OFDM    | 7.5                         | 5.57                  | 0.02             | Right | Cheek                | 2       | Standard          | 31F35                | 29.3             | 1:1        | 0.045           | 1.560          | 0.070                  |        |
| 5680                                     | 136 | IEEE 802.11a  | OFDM    | 7.5                         | 6.01                  | 0.06             | Right | Tilt                 | 2       | Standard          | 31F35                | 6                | 1:1        | 0.057           | 1.409          | 0.080                  |        |
| 5680                                     | 136 | IEEE 802.11a  | OFDM    | 7.5                         | 6.01                  | 0.14             | Left  | Cheek                | 2       | Standard          | 31F35                | 6                | 1:1        | 0.032           | 1.409          | 0.045                  |        |
| 5680                                     | 136 | IEEE 802.11a  | OFDM    | 7.5                         | 6.01                  | -0.08            | Left  | Tilt                 | 2       | Standard          | 31F35                | 6                | 1:1        | 0.031           | 1.409          | 0.044                  |        |
| 5500                                     | 100 | IEEE 802.11n  | OFDM    | 7.5                         | 7.38                  | 0.18             | Right | Cheek                | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.010           | 1.028          | 0.010                  |        |
| 5500                                     | 100 | IEEE 802.11n  | OFDM    | 7.5                         | 7.38                  | 0.07             | Right | Tilt                 | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.014           | 1.028          | 0.014                  |        |
| 5500                                     | 100 | IEEE 802.11n  | OFDM    | 7.5                         | 7.38                  | -0.20            | Left  | Cheek                | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.012           | 1.028          | 0.012                  |        |
| 5500                                     | 100 | IEEE 802.11n  | OFDM    | 7.5                         | 7.38                  | 0.19             | Left  | Tilt                 | MIMO    | Standard          | 31F35                | 13               | 1:1        | 0.011           | 1.028          | 0.011                  |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |     |               |         |                             |                       |                  |       | Head                 |         |                   |                      |                  |            |                 |                |                        |        |
| Spatial Peak                             |     |               |         |                             |                       |                  |       | 1.6 W/kg (mW/g)      |         |                   |                      |                  |            |                 |                |                        |        |
| Uncontrolled Exposure/General Population |     |               |         |                             |                       |                  |       | averaged over 1 gram |         |                   |                      |                  |            |                 |                |                        |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 45 of 79                   |



## 11.2 Standalone Body-Worn SAR Data

**Table 11-8**  
**CDMA Body-Worn SAR Data**

| MEASUREMENT RESULTS                                                                               |     |            |             |                             |                       |                  |                                                 |                   |                      |            |      |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|------------|-------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|-------------------|----------------------|------------|------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode       | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Cover Type        | Device Serial Number | Duty Cycle | Side | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |            |             |                             |                       |                  |                                                 |                   |                      |            |      | (W/kg)   |                | (W/kg)          |        |
| 836.52                                                                                            | 384 | Cell. CDMA | TDSO / SO32 | 25.0                        | 24.37                 | -0.04            | 10 mm                                           | Standard          | 32EF0                | 1:1        | back | 0.670    | 1.156          | 0.775           | A9     |
| 836.52                                                                                            | 384 | Cell. CDMA | TDSO / SO32 | 25.0                        | 24.37                 | 0.01             | 10 mm                                           | Wireless Charging | 32EF0                | 1:1        | back | 0.560    | 1.156          | 0.647           |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | TDSO / SO32 | 25.0                        | 24.46                 | -0.02            | 15 mm                                           | Standard          | 32EF0                | 1:1        | back | 0.465    | 1.132          | 0.526           | A11    |
| 1880.00                                                                                           | 600 | PCS CDMA   | TDSO / SO32 | 25.0                        | 24.46                 | -0.04            | 15 mm                                           | Wireless Charging | 32EF0                | 1:1        | back | 0.393    | 1.132          | 0.445           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |            |             |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                   |                      |            |      |          |                |                 |        |

**Table 11-9**  
**LTE Body-Worn SAR**

| MEASUREMENT RESULTS                                   |       |      |                   |            |                             |                       |                  |          |                      |                                                 |         |           |         |       |            |          |                |                 |        |     |
|-------------------------------------------------------|-------|------|-------------------|------------|-----------------------------|-----------------------|------------------|----------|----------------------|-------------------------------------------------|---------|-----------|---------|-------|------------|----------|----------------|-----------------|--------|-----|
| FREQUENCY                                             |       | Mode | Bandwidth [MHz]   | Cover Type | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number | Modulation                                      | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |     |
| MHz                                                   | Ch.   |      |                   |            |                             |                       |                  |          |                      |                                                 |         |           |         |       |            | (W/kg)   |                | (W/kg)          |        |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12       | 10         | Standard                    | 23.5                  | 23.08            | 0.01     | 0                    | 32EF0                                           | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.369          | 1.102           | 0.407  | A13 |
| 707.50                                                | 23095 | Mid  | LTE Band 12       | 10         | Wireless Charging           | 23.5                  | 23.08            | 0.01     | 0                    | 32EF0                                           | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.243          | 1.102           | 0.268  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12       | 10         | Standard                    | 22.5                  | 22.02            | 0.03     | 1                    | 32EF0                                           | QPSK    | 25        | 0       | 10 mm | back       | 1:1      | 0.271          | 1.117           | 0.303  |     |
| 1715.00                                               | 20000 | Low  | LTE Band 4 (AWS)  | 10         | Standard                    | 23.5                  | 23.50            | 0.00     | 0                    | 32EC6                                           | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.509          | 1.000           | 0.509  | A15 |
| 1715.00                                               | 20000 | Low  | LTE Band 4 (AWS)  | 10         | Wireless Charging           | 23.5                  | 23.50            | 0.05     | 0                    | 32EC6                                           | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.252          | 1.000           | 0.252  |     |
| 1715.00                                               | 20000 | Low  | LTE Band 4 (AWS)  | 10         | Standard                    | 22.5                  | 22.43            | -0.09    | 1                    | 32EC6                                           | QPSK    | 25        | 12      | 10 mm | back       | 1:1      | 0.321          | 1.016           | 0.326  |     |
| 1910.00                                               | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | -0.02    | 0                    | 32E32                                           | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.182          | 1.035           | 0.188  |     |
| 1910.00                                               | 26640 | High | LTE Band 25 (PCS) | 10         | Wireless Charging           | 23.5                  | 23.35            | 0.01     | 0                    | 32E32                                           | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.209          | 1.035           | 0.216  | A17 |
| 1910.00                                               | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | 0.09     | 1                    | 32E32                                           | QPSK    | 25        | 0       | 10 mm | back       | 1:1      | 0.176          | 1.069           | 0.188  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak |       |      |                   |            |                             |                       |                  |          |                      | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |           |         |       |            |          |                |                 |        |     |
| Uncontrolled Exposure/General Population              |       |      |                   |            |                             |                       |                  |          |                      |                                                 |         |           |         |       |            |          |                |                 |        |     |

**Table 11-10**  
**DTS Body-Worn SAR**

| MEASUREMENT RESULTS                                                                               |     |               |         |                             |                       |                  |                                                 |         |                   |                      |                  |      |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|---------------|---------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------|-------------------|----------------------|------------------|------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode          | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Antenna | Cover Type        | Device Serial Number | Data Rate (Mbps) | Side | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |               |         |                             |                       |                  |                                                 |         |                   |                      |                  |      |            | (W/kg)   |                | (W/kg)          |        |
| 2437                                                                                              | 6   | IEEE 802.11b  | DSSS    | 17.5                        | 17.05                 | -0.08            | 10 mm                                           | 1       | Standard          | 00F05                | 1                | back | 1:1        | 0.235    | 1.109          | 0.261           | A19    |
| 2437                                                                                              | 6   | IEEE 802.11b  | DSSS    | 17.5                        | 17.05                 | 0.16             | 10 mm                                           | 1       | Wireless Charging | 00F05                | 1                | back | 1:1        | 0.103    | 1.109          | 0.114           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 17.5                        | 17.07                 | 0.04             | 10 mm                                           | 2       | Standard          | 00F05                | 1                | back | 1:1        | 0.087    | 1.104          | 0.096           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 14.0                        | 13.87                 | 0.11             | 10 mm                                           | MIMO    | Standard          | 00F05                | 13               | back | 1:1        | 0.066    | 1.030          | 0.068           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 14.0                        | 13.87                 | 0.10             | 10 mm                                           | MIMO    | Wireless Charging | 00F05                | 13               | back | 1:1        | 0.053    | 1.030          | 0.055           |        |
| 5745                                                                                              | 149 | IEEE 802.11a  | OFDM    | 14.0                        | 13.31                 | 0.06             | 10 mm                                           | 1       | Standard          | 32712                | 6                | back | 1:1        | 0.138    | 1.172          | 0.162           |        |
| 5775                                                                                              | 155 | IEEE 802.11ac | OFDM    | 11.5                        | 11.25                 | 0.09             | 10 mm                                           | 1       | Standard          | 32712                | 29.3             | back | 1:1        | 0.041    | 1.059          | 0.043           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 14.0                        | 13.44                 | 0.10             | 10 mm                                           | 2       | Standard          | 15ECE                | 6                | back | 1:1        | 0.287    | 1.138          | 0.327           | A20    |
| 5775                                                                                              | 155 | IEEE 802.11ac | OFDM    | 11.5                        | 11.26                 | 0.03             | 10 mm                                           | 2       | Standard          | 15ECE                | 29.3             | back | 1:1        | 0.128    | 1.057          | 0.135           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 13.5                        | 13.47                 | 0.16             | 10 mm                                           | MIMO    | Standard          | 15ECE                | 13               | back | 1:1        | 0.220    | 1.007          | 0.222           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 13.5                        | 13.47                 | 0.00             | 10 mm                                           | MIMO    | Wireless Charging | 15ECE                | 13               | back | 1:1        | 0.121    | 1.007          | 0.122           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |               |         |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |                   |                      |                  |      |            |          |                |                 |        |

|                                   |                                                                                     |                               |  |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset |  | Page 46 of 79                                                                         |                                 |

**Table 11-11**  
**NII Body-Worn SAR**

| MEASUREMENT RESULTS                                                                               |     |               |         |                             |                       |                  |                                                 |         |                   |                      |                  |      |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|---------------|---------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------|-------------------|----------------------|------------------|------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode          | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Antenna | Cover Type        | Device Serial Number | Data Rate (Mbps) | Side | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |               |         |                             |                       |                  |                                                 |         |                   |                      |                  |      |            | (W/kg)   |                | (W/kg)          |        |
| 5220                                                                                              | 44  | IEEE 802.11a  | OFDM    | 14.0                        | 13.12                 | 0.06             | 10 mm                                           | 1       | Standard          | 32712                | 6                | back | 1:1        | 0.196    | 1.225          | 0.240           |        |
| 5210                                                                                              | 42  | IEEE 802.11ac | OFDM    | 11.5                        | 10.71                 | 0.09             | 10 mm                                           | 1       | Standard          | 32712                | 29.3             | back | 1:1        | 0.079    | 1.199          | 0.095           |        |
| 5180                                                                                              | 36  | IEEE 802.11a  | OFDM    | 14.0                        | 13.94                 | -0.12            | 10 mm                                           | 2       | Standard          | 15ECE                | 6                | back | 1:1        | 0.104    | 1.014          | 0.105           |        |
| 5210                                                                                              | 42  | IEEE 802.11ac | OFDM    | 11.5                        | 10.78                 | 0.18             | 10 mm                                           | 2       | Standard          | 15ECE                | 29.3             | back | 1:1        | 0.056    | 1.180          | 0.066           |        |
| 5180                                                                                              | 36  | IEEE 802.11n  | OFDM    | 13.5                        | 12.63                 | 0.07             | 10 mm                                           | MIMO    | Standard          | 15ECE                | 13               | back | 1:1        | 0.065    | 1.222          | 0.079           |        |
| 5280                                                                                              | 56  | IEEE 802.11a  | OFDM    | 14.0                        | 12.97                 | 0.10             | 10 mm                                           | 1       | Standard          | 32712                | 6                | back | 1:1        | 0.162    | 1.268          | 0.205           |        |
| 5290                                                                                              | 58  | IEEE 802.11ac | OFDM    | 11.5                        | 10.77                 | 0.04             | 10 mm                                           | 1       | Standard          | 32712                | 29.3             | back | 1:1        | 0.080    | 1.183          | 0.095           |        |
| 5260                                                                                              | 52  | IEEE 802.11a  | OFDM    | 14.0                        | 13.21                 | -0.04            | 10 mm                                           | 2       | Standard          | 15ECE                | 6                | back | 1:1        | 0.195    | 1.199          | 0.234           |        |
| 5290                                                                                              | 58  | IEEE 802.11ac | OFDM    | 11.5                        | 10.94                 | 0.08             | 10 mm                                           | 2       | Standard          | 15ECE                | 29.3             | back | 1:1        | 0.074    | 1.138          | 0.084           |        |
| 5300                                                                                              | 60  | IEEE 802.11n  | OFDM    | 13.5                        | 12.77                 | 0.09             | 10 mm                                           | MIMO    | Standard          | 15ECE                | 13               | back | 1:1        | 0.060    | 1.183          | 0.071           |        |
| 5540                                                                                              | 108 | IEEE 802.11a  | OFDM    | 14.0                        | 13.41                 | 0.05             | 10 mm                                           | 1       | Standard          | 32712                | 6                | back | 1:1        | 0.235    | 1.146          | 0.269           |        |
| 5530                                                                                              | 106 | IEEE 802.11ac | OFDM    | 11.5                        | 11.15                 | 0.03             | 10 mm                                           | 1       | Standard          | 32712                | 29.3             | back | 1:1        | 0.119    | 1.084          | 0.129           |        |
| 5500                                                                                              | 100 | IEEE 802.11a  | OFDM    | 14.0                        | 13.26                 | 0.03             | 10 mm                                           | 2       | Standard          | 15ECE                | 6                | back | 1:1        | 0.296    | 1.186          | 0.351           | A21    |
| 5500                                                                                              | 100 | IEEE 802.11a  | OFDM    | 14.0                        | 13.26                 | 0.03             | 10 mm                                           | 2       | Wireless Charging | 15ECE                | 6                | back | 1:1        | 0.167    | 1.186          | 0.198           |        |
| 5530                                                                                              | 106 | IEEE 802.11ac | OFDM    | 11.5                        | 10.98                 | -0.03            | 10 mm                                           | 2       | Standard          | 15ECE                | 29.3             | back | 1:1        | 0.099    | 1.127          | 0.112           |        |
| 5500                                                                                              | 100 | IEEE 802.11n  | OFDM    | 13.5                        | 12.30                 | 0.06             | 10 mm                                           | MIMO    | Standard          | 15ECE                | 13               | back | 1:1        | 0.075    | 1.318          | 0.099           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |               |         |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |                   |                      |                  |      |            |          |                |                 |        |

## 11.3 Standalone Wireless Router SAR Data

**Table 11-12**  
**CDMA/EVDO Hotspot SAR Data**

| MEASUREMENT RESULTS                                                                               |     |            |             |                             |                       |                  |                                                 |                   |                      |            |        |          |       |                |                        |        |
|---------------------------------------------------------------------------------------------------|-----|------------|-------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|-------------------|----------------------|------------|--------|----------|-------|----------------|------------------------|--------|
| FREQUENCY                                                                                         |     | Mode       | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Cover Type        | Device Serial Number | Duty Cycle | Side   | SAR (1g) |       | Scaling Factor | Scaled SAR (1g) (W/kg) | Plot # |
| MHz                                                                                               | Ch. |            |             |                             |                       |                  |                                                 |                   |                      |            |        | (W/kg)   |       |                |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | TDSO / SO32 | 25.0                        | 24.37                 | -0.04            | 10 mm                                           | Standard          | 32EF0                | 1:1        | back   | 0.670    | 1.156 | 0.775          |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | TDSO / SO32 | 25.0                        | 24.37                 | 0.03             | 10 mm                                           | Standard          | 32EF0                | 1:1        | front  | 0.596    | 1.156 | 0.689          |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | TDSO / SO32 | 25.0                        | 24.37                 | 0.04             | 10 mm                                           | Standard          | 32EF0                | 1:1        | bottom | 0.442    | 1.156 | 0.511          |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | TDSO / SO32 | 25.0                        | 24.37                 | -0.02            | 10 mm                                           | Standard          | 32EF0                | 1:1        | right  | 0.673    | 1.156 | 0.778          | A10                    |        |
| 836.52                                                                                            | 384 | Cell. CDMA | TDSO / SO32 | 25.0                        | 24.37                 | 0.05             | 10 mm                                           | Wireless Charging | 32EF0                | 1:1        | right  | 0.664    | 1.156 | 0.768          |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.44                 | -0.02            | 10 mm                                           | Standard          | 32EF0                | 1:1        | back   | 0.673    | 1.138 | 0.766          |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.44                 | 0.01             | 10 mm                                           | Wireless Charging | 32EF0                | 1:1        | back   | 0.560    | 1.138 | 0.637          |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.44                 | -0.01            | 10 mm                                           | Standard          | 32EF0                | 1:1        | front  | 0.600    | 1.138 | 0.683          |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.44                 | -0.04            | 10 mm                                           | Standard          | 32EF0                | 1:1        | bottom | 0.457    | 1.138 | 0.520          |                        |        |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.44                 | 0.00             | 10 mm                                           | Standard          | 32EF0                | 1:1        | right  | 0.672    | 1.138 | 0.765          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | TDSO / SO32 | 23.0                        | 22.32                 | -0.02            | 10 mm                                           | Standard          | 3R725                | 1:1        | back   | 0.482    | 1.169 | 0.563          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | TDSO / SO32 | 23.0                        | 22.32                 | -0.04            | 10 mm                                           | Wireless Charging | 3R725                | 1:1        | back   | 0.380    | 1.169 | 0.444          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | TDSO / SO32 | 23.0                        | 22.32                 | -0.01            | 10 mm                                           | Standard          | 3R725                | 1:1        | front  | 0.386    | 1.169 | 0.451          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | TDSO / SO32 | 23.0                        | 22.32                 | -0.01            | 10 mm                                           | Standard          | 3R725                | 1:1        | bottom | 0.370    | 1.169 | 0.433          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | TDSO / SO32 | 23.0                        | 22.32                 | 0.06             | 10 mm                                           | Standard          | 3R725                | 1:1        | right  | 0.303    | 1.169 | 0.354          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | EVDO Rev. 0 | 23.0                        | 22.31                 | 0.05             | 10 mm                                           | Standard          | 3R725                | 1:1        | back   | 0.489    | 1.172 | 0.573          | A12                    |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | EVDO Rev. 0 | 23.0                        | 22.31                 | -0.06            | 10 mm                                           | Wireless Charging | 3R725                | 1:1        | back   | 0.341    | 1.172 | 0.400          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | EVDO Rev. 0 | 23.0                        | 22.31                 | 0.01             | 10 mm                                           | Standard          | 3R725                | 1:1        | front  | 0.339    | 1.172 | 0.397          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | EVDO Rev. 0 | 23.0                        | 22.31                 | 0.02             | 10 mm                                           | Standard          | 3R725                | 1:1        | bottom | 0.394    | 1.172 | 0.462          |                        |        |
| 1880.00                                                                                           | 600 | PCS CDMA   | EVDO Rev. 0 | 23.0                        | 22.31                 | -0.01            | 10 mm                                           | Standard          | 3R725                | 1:1        | right  | 0.317    | 1.172 | 0.372          |                        |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |            |             |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                   |                      |            |        |          |       |                |                        |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 47 of 79                                                                         |                                 |

**Table 11-13**  
**LTE Band 12 Hotspot SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                 |            |                             |                       |                  |          |                                                 |            |         |           |         |       |            |                 |                |                        |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|-----------------|------------|-----------------------------|-----------------------|------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|-----------------|----------------|------------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz] | Cover Type | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                            | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) (W/kg) | Scaling Factor | Scaled SAR (1g) (W/kg) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                 |            |                             |                       |                  |          |                                                 |            |         |           |         |       |            |                 |                |                        |        |     |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 23.5                  | 23.08            | 0.01     | 0                                               | 32EF0      | QPSK    | 1         | 0       | 10 mm | back       | 1:1             | 0.369          | 1.102                  | 0.407  | A14 |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 22.5                  | 22.02            | 0.03     | 1                                               | 32EF0      | QPSK    | 25        | 0       | 10 mm | back       | 1:1             | 0.271          | 1.117                  | 0.303  |     |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 23.5                  | 23.08            | 0.01     | 0                                               | 32EF0      | QPSK    | 1         | 0       | 10 mm | front      | 1:1             | 0.467          | 1.102                  | 0.515  |     |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Wireless Charging           | 23.5                  | 23.08            | -0.01    | 0                                               | 32EF0      | QPSK    | 1         | 0       | 10 mm | front      | 1:1             | 0.382          | 1.102                  | 0.421  |     |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 22.5                  | 22.02            | 0.02     | 1                                               | 32EF0      | QPSK    | 25        | 0       | 10 mm | front      | 1:1             | 0.347          | 1.117                  | 0.388  |     |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 23.5                  | 23.08            | -0.03    | 0                                               | 32EF0      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1             | 0.313          | 1.102                  | 0.345  |     |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 22.5                  | 22.02            | -0.03    | 1                                               | 32EF0      | QPSK    | 25        | 0       | 10 mm | bottom     | 1:1             | 0.233          | 1.117                  | 0.260  |     |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 23.5                  | 23.08            | 0.00     | 0                                               | 32EF0      | QPSK    | 1         | 0       | 10 mm | left       | 1:1             | 0.316          | 1.102                  | 0.348  |     |
| 707.50                                                                                            | 23095 | Mid  | LTE Band 12     | 10         | Standard                    | 22.5                  | 22.02            | 0.05     | 1                                               | 32EF0      | QPSK    | 25        | 0       | 10 mm | left       | 1:1             | 0.239          | 1.117                  | 0.267  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                 |            |                             |                       |                  |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |                 |                |                        |        |     |

**Table 11-14**  
**LTE Band 4 (AWS) Hotspot SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                  |            |                             |                       |                  |          |                                                 |            |         |           |         |       |            |                 |                |                        |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|------------|-----------------------------|-----------------------|------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|-----------------|----------------|------------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Cover Type | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                            | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) (W/kg) | Scaling Factor | Scaled SAR (1g) (W/kg) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                  |            |                             |                       |                  |          |                                                 |            |         |           |         |       |            |                 |                |                        |        |     |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 23.5                  | 23.50            | 0.00     | 0                                               | 32EC6      | QPSK    | 1         | 0       | 10 mm | back       | 1:1             | 0.509          | 1.000                  | 0.509  | A16 |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 22.5                  | 22.43            | -0.09    | 1                                               | 32EC6      | QPSK    | 25        | 12      | 10 mm | back       | 1:1             | 0.321          | 1.016                  | 0.326  |     |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 23.5                  | 23.50            | -0.01    | 0                                               | 32EC6      | QPSK    | 1         | 0       | 10 mm | front      | 1:1             | 0.586          | 1.000                  | 0.586  |     |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Wireless Charging           | 23.5                  | 23.50            | 0.02     | 0                                               | 32EC6      | QPSK    | 1         | 0       | 10 mm | front      | 1:1             | 0.338          | 1.000                  | 0.338  |     |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 22.5                  | 22.43            | 0.02     | 1                                               | 32EC6      | QPSK    | 25        | 12      | 10 mm | front      | 1:1             | 0.389          | 1.016                  | 0.395  |     |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 23.5                  | 23.50            | -0.04    | 0                                               | 32EC6      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1             | 0.140          | 1.000                  | 0.140  |     |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 22.5                  | 22.43            | -0.03    | 1                                               | 32EC6      | QPSK    | 25        | 12      | 10 mm | bottom     | 1:1             | 0.141          | 1.016                  | 0.143  |     |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 23.5                  | 23.50            | -0.05    | 0                                               | 32EC6      | QPSK    | 1         | 0       | 10 mm | left       | 1:1             | 0.183          | 1.000                  | 0.183  |     |
| 1715.00                                                                                           | 20000 | Low  | LTE Band 4 (AWS) | 10         | Standard                    | 22.5                  | 22.43            | 0.03     | 1                                               | 32EC6      | QPSK    | 25        | 12      | 10 mm | left       | 1:1             | 0.148          | 1.016                  | 0.150  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |            |                             |                       |                  |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |                 |                |                        |        |     |

**Table 11-15**  
**LTE Band 25 (PCS) Hotspot SAR**

| MEASUREMENT RESULTS                      |       |      |                   |            |                             |                       |                  |          |                      |                      |         |           |         |       |            |                 |                |                        |        |     |
|------------------------------------------|-------|------|-------------------|------------|-----------------------------|-----------------------|------------------|----------|----------------------|----------------------|---------|-----------|---------|-------|------------|-----------------|----------------|------------------------|--------|-----|
| FREQUENCY                                |       | Mode | Bandwidth [MHz]   | Cover Type | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number | Modulation           | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) (W/kg) | Scaling Factor | Scaled SAR (1g) (W/kg) | Plot # |     |
| MHz                                      | Ch.   |      |                   |            |                             |                       |                  |          |                      |                      |         |           |         |       |            |                 |                |                        |        |     |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | -0.02    | 0                    | 32E32                | QPSK    | 1         | 0       | 10 mm | back       | 1:1             | 0.182          | 1.035                  | 0.188  | A18 |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | 0.09     | 1                    | 32E32                | QPSK    | 25        | 0       | 10 mm | back       | 1:1             | 0.176          | 1.069                  | 0.188  |     |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | -0.04    | 0                    | 32E32                | QPSK    | 1         | 0       | 10 mm | front      | 1:1             | 0.394          | 1.035                  | 0.408  |     |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Wireless Charging           | 23.5                  | 23.35            | 0.00     | 0                    | 32E32                | QPSK    | 1         | 0       | 10 mm | front      | 1:1             | 0.547          | 1.035                  | 0.566  |     |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | -0.02    | 1                    | 32E32                | QPSK    | 25        | 0       | 10 mm | front      | 1:1             | 0.359          | 1.069                  | 0.384  |     |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | 0.05     | 0                    | 32E32                | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1             | 0.098          | 1.035                  | 0.101  |     |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | 0.11     | 1                    | 32E32                | QPSK    | 25        | 0       | 10 mm | bottom     | 1:1             | 0.079          | 1.069                  | 0.084  |     |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 23.5                  | 23.35            | 0.04     | 0                    | 32E32                | QPSK    | 1         | 0       | 10 mm | left       | 1:1             | 0.244          | 1.035                  | 0.253  |     |
| 1910.00                                  | 26640 | High | LTE Band 25 (PCS) | 10         | Standard                    | 22.5                  | 22.21            | -0.05    | 1                    | 32E32                | QPSK    | 25        | 0       | 10 mm | left       | 1:1             | 0.239          | 1.069                  | 0.255  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |       |      |                   |            |                             |                       |                  |          |                      | Body                 |         |           |         |       |            |                 |                |                        |        |     |
| Spatial Peak                             |       |      |                   |            |                             |                       |                  |          |                      | 1.6 W/kg (mW/g)      |         |           |         |       |            |                 |                |                        |        |     |
| Uncontrolled Exposure/General Population |       |      |                   |            |                             |                       |                  |          |                      | averaged over 1 gram |         |           |         |       |            |                 |                |                        |        |     |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 48 of 79                                                                         |                                        |

**Table 11-16**  
**WLAN Hotspot SAR**

| MEASUREMENT RESULTS                                                                               |     |               |         |                             |                       |                  |                                                 |         |                   |                      |                  |       |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|---------------|---------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------|-------------------|----------------------|------------------|-------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode          | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Antenna | Cover Type        | Device Serial Number | Data Rate (Mbps) | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |               |         |                             |                       |                  |                                                 |         |                   |                      |                  |       |            | (W/kg)   |                | (W/kg)          |        |
| 2437                                                                                              | 6   | IEEE 802.11b  | DSSS    | 17.5                        | 17.05                 | -0.08            | 10 mm                                           | 1       | Standard          | 00F05                | 1                | back  | 1:1        | 0.235    | 1.109          | 0.261           | A19    |
| 2437                                                                                              | 6   | IEEE 802.11b  | DSSS    | 17.5                        | 17.05                 | 0.16             | 10 mm                                           | 1       | Wireless Charging | 00F05                | 1                | back  | 1:1        | 0.103    | 1.109          | 0.114           |        |
| 2437                                                                                              | 6   | IEEE 802.11b  | DSSS    | 17.5                        | 17.05                 | 0.06             | 10 mm                                           | 1       | Standard          | 00F05                | 1                | front | 1:1        | 0.193    | 1.109          | 0.214           |        |
| 2437                                                                                              | 6   | IEEE 802.11b  | DSSS    | 17.5                        | 17.05                 | 0.04             | 10 mm                                           | 1       | Standard          | 00F05                | 1                | top   | 1:1        | 0.114    | 1.109          | 0.126           |        |
| 2437                                                                                              | 6   | IEEE 802.11b  | DSSS    | 17.5                        | 17.05                 | 0.04             | 10 mm                                           | 1       | Standard          | 00F05                | 1                | left  | 1:1        | 0.111    | 1.109          | 0.123           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 17.5                        | 17.07                 | 0.04             | 10 mm                                           | 2       | Standard          | 00F05                | 1                | back  | 1:1        | 0.087    | 1.104          | 0.096           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 17.5                        | 17.07                 | 0.09             | 10 mm                                           | 2       | Standard          | 00F05                | 1                | front | 1:1        | 0.053    | 1.104          | 0.059           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 17.5                        | 17.07                 | 0.06             | 10 mm                                           | 2       | Standard          | 00F05                | 1                | top   | 1:1        | 0.022    | 1.104          | 0.024           |        |
| 2412                                                                                              | 1   | IEEE 802.11b  | DSSS    | 17.5                        | 17.07                 | 0.05             | 10 mm                                           | 2       | Standard          | 00F05                | 1                | left  | 1:1        | 0.077    | 1.104          | 0.085           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 14.0                        | 13.87                 | 0.11             | 10 mm                                           | MIMO    | Standard          | 00F05                | 13               | back  | 1:1        | 0.066    | 1.030          | 0.068           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 14.0                        | 13.87                 | 0.10             | 10 mm                                           | MIMO    | Wireless Charging | 00F05                | 13               | back  | 1:1        | 0.053    | 1.030          | 0.055           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 14.0                        | 13.87                 | 0.04             | 10 mm                                           | MIMO    | Standard          | 00F05                | 13               | front | 1:1        | 0.056    | 1.030          | 0.058           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 14.0                        | 13.87                 | 0.04             | 10 mm                                           | MIMO    | Standard          | 00F05                | 13               | top   | 1:1        | 0.037    | 1.030          | 0.038           |        |
| 2412                                                                                              | 1   | IEEE 802.11n  | OFDM    | 14.0                        | 13.87                 | 0.15             | 10 mm                                           | MIMO    | Standard          | 00F05                | 13               | left  | 1:1        | 0.029    | 1.030          | 0.030           |        |
| 5745                                                                                              | 149 | IEEE 802.11a  | OFDM    | 14.0                        | 13.31                 | 0.06             | 10 mm                                           | 1       | Standard          | 32712                | 6                | back  | 1:1        | 0.138    | 1.172          | 0.162           |        |
| 5745                                                                                              | 149 | IEEE 802.11a  | OFDM    | 14.0                        | 13.31                 | 0.12             | 10 mm                                           | 1       | Standard          | 32712                | 6                | front | 1:1        | 0.089    | 1.172          | 0.104           |        |
| 5745                                                                                              | 149 | IEEE 802.11a  | OFDM    | 14.0                        | 13.31                 | -0.02            | 10 mm                                           | 1       | Standard          | 32712                | 6                | top   | 1:1        | 0.260    | 1.172          | 0.305           |        |
| 5775                                                                                              | 155 | IEEE 802.11ac | OFDM    | 11.5                        | 11.25                 | 0.02             | 10 mm                                           | 1       | Standard          | 32712                | 29.3             | top   | 1:1        | 0.104    | 1.059          | 0.110           |        |
| 5745                                                                                              | 149 | IEEE 802.11a  | OFDM    | 14.0                        | 13.31                 | 0.05             | 10 mm                                           | 1       | Standard          | 32712                | 6                | left  | 1:1        | 0.025    | 1.172          | 0.029           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 14.0                        | 13.44                 | 0.10             | 10 mm                                           | 2       | Standard          | 15ECE                | 6                | back  | 1:1        | 0.287    | 1.138          | 0.327           | A20    |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 14.0                        | 13.44                 | 0.17             | 10 mm                                           | 2       | Wireless Charging | 15ECE                | 6                | back  | 1:1        | 0.204    | 1.138          | 0.232           |        |
| 5775                                                                                              | 155 | IEEE 802.11ac | OFDM    | 11.5                        | 11.26                 | 0.03             | 10 mm                                           | 2       | Standard          | 15ECE                | 29.3             | back  | 1:1        | 0.128    | 1.057          | 0.135           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 14.0                        | 13.44                 | 0.04             | 10 mm                                           | 2       | Standard          | 15ECE                | 6                | front | 1:1        | 0.078    | 1.138          | 0.089           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 14.0                        | 13.44                 | 0.04             | 10 mm                                           | 2       | Standard          | 15ECE                | 6                | top   | 1:1        | 0.066    | 1.138          | 0.075           |        |
| 5765                                                                                              | 153 | IEEE 802.11a  | OFDM    | 14.0                        | 13.44                 | 0.02             | 10 mm                                           | 2       | Standard          | 15ECE                | 6                | left  | 1:1        | 0.173    | 1.138          | 0.197           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 13.5                        | 13.47                 | 0.16             | 10 mm                                           | MIMO    | Standard          | 15ECE                | 13               | back  | 1:1        | 0.220    | 1.007          | 0.222           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 13.5                        | 13.47                 | 0.00             | 10 mm                                           | MIMO    | Wireless Charging | 15ECE                | 13               | back  | 1:1        | 0.121    | 1.007          | 0.122           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 13.5                        | 13.47                 | -0.01            | 10 mm                                           | MIMO    | Standard          | 15ECE                | 13               | front | 1:1        | 0.032    | 1.007          | 0.032           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 13.5                        | 13.47                 | 0.06             | 10 mm                                           | MIMO    | Standard          | 15ECE                | 13               | top   | 1:1        | 0.097    | 1.007          | 0.098           |        |
| 5765                                                                                              | 153 | IEEE 802.11n  | OFDM    | 13.5                        | 13.47                 | 0.03             | 10 mm                                           | MIMO    | Standard          | 15ECE                | 13               | left  | 1:1        | 0.060    | 1.007          | 0.060           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |               |         |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |                   |                      |                  |       |            |          |                |                 |        |

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 49 of 79                                                                         |                                        |

## 11.4 SAR Test Notes

### General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements. A specialized battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance. A test separation distance of 10 mm for body-worn SAR was also used for CDMA BC0, LTE Bands 12/4/25, and 2.4/5 GHz WLAN as it is more conservative.
7. Per FCC KDB Publication 648474 D04v01, SAR was evaluated without a headset connected to the device. Since the standalone reported SAR was  $\leq 1.2$  W/kg, no additional SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01 v01, variability SAR tests were not required since the measured SAR results for all frequency bands were less than 0.8 W/kg. Please see Section 13 for more information.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. This DUT may be used with a wireless charging cover. Per FCC KDB Publication 648474 D04, SAR was measured using the standard battery cover and then repeated with the wireless charging cover for the highest reported SAR for each wireless technology, frequency band, operating mode, and exposure condition. No other additional testing with the wireless charging battery cover was required since all reported SAR was under 1.2 W/kg.

### CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v02.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO and TDSO / SO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO / SO32 FCH only powers, per FCC KDB Publication 941225 D01v02.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01 procedures for data devices. Since the average output power of Subtype 2 for Rev. A is less than the Rev. 0 power levels, EVDO Rev. A SAR is not required.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.
6. This device applies power reduction for PCS CDMA modes when Hotspot is active. Therefore, PCS CDMA/EVDO modes were evaluated at hotspot reduced power levels. There is no power reduction applied to the Cellular CDMA/EVDO modes.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 50 of 79                                                                         |                                        |

7. CDMA 1x-RTT SAR was required to be evaluated for Hotspot exposure conditions to support simultaneous transmission capabilities.

#### LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r01. The general test procedures used for testing can be found in Section 8.4.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

#### WLAN Notes:

1. Justification for reduced test configurations for SISO WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
2. Justification for reduced test configurations for SISO WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 5 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11a. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz bandwidths) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
3. Per April 2013 TCB Workshop notes, full SAR tests for all IEEE 802.11ac configurations were not required because the average output power was not more than 0.25 dB higher than IEEE 802.11a mode. IEEE 802.11ac was evaluated for the highest IEEE 802.11a position in each 5 GHz band and exposure condition.
4. WIFI transmission was verified using an uncalibrated spectrum analyzer.
5. This device only supports Hotspot for 2.4 GHz and 5.8 GHz bands. Therefore all other bands were not evaluated for Hotspot SAR conditions.
6. Since the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other default channels was not required.
7. Per KDB 248227, SAR for MIMO was measured with both antennas transmitting simultaneously and was evaluated independently of SISO operation. For 2.4 GHz MIMO, 802.11n mode was evaluated for SAR. For 5 GHz MIMO, 802.11n 20 MHz Bandwidth mode was evaluated since the maximum allowed output power was higher than 802.11ac mode powers.
8. This device requires WIFI power reduction for SAR compliance. It always applies power reduction on the WIFI transmitter in voice or VOIP held-to-ear scenarios, and does not impact any other transmitter in the device. Therefore WIFI head SAR was evaluated at reduced power levels.
9. WLAN Body-Worn tests were performed at distance of 10 mm to represent a more conservative test configuration.

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 51 of 79                                                                         |                                        |



## 12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

### 12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g/n/ac and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

### 12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is  $\leq 1.6$  W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1**  
**Estimated SAR**

| Mode      | Frequency | Maximum Allowed Power | Separation Distance (Body) | Estimated SAR (Body) |
|-----------|-----------|-----------------------|----------------------------|----------------------|
|           | [MHz]     | [dBm]                 | [mm]                       | [W/kg]               |
| Bluetooth | 2441      | 10.00                 | 15                         | <b>0.139</b>         |

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

### 12.3 Head SAR Simultaneous Transmission Analysis

**Table 12-2**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 1 (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | Cell. EVDO SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|-----------------------------------|--------------|-----------|---------------|-----------------------|-----------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.612                 | 0.185                             | <b>0.797</b> | Head SAR  | Right Cheek   | 0.611                 | 0.185                             | <b>0.796</b> |
|           | Right Tilt    | 0.351                 | 0.180                             | 0.531        |           | Right Tilt    | 0.327                 | 0.180                             | 0.507        |
|           | Left Cheek    | 0.457                 | 0.147                             | 0.604        |           | Left Cheek    | 0.494                 | 0.147                             | 0.641        |
|           | Left Tilt     | 0.304                 | 0.146                             | 0.450        |           | Left Tilt     | 0.333                 | 0.146                             | 0.479        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg)   | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)   | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
| Head SAR  | Right Cheek   | 0.563                 | 0.185                             | <b>0.748</b> | Head SAR  | Right Cheek   | 0.352                 | 0.185                             | <b>0.537</b> |
|           | Right Tilt    | 0.261                 | 0.180                             | 0.441        |           | Right Tilt    | 0.138                 | 0.180                             | 0.318        |
|           | Left Cheek    | 0.286                 | 0.147                             | 0.433        |           | Left Cheek    | 0.271                 | 0.147                             | 0.418        |
|           | Left Tilt     | 0.201                 | 0.146                             | 0.347        |           | Left Tilt     | 0.111                 | 0.146                             | 0.257        |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 52 of 79                                                                         |                                        |

| Simult Tx | Configuration | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------|-----------------------------------|--------------|-----------|---------------|-----------------------------|-----------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.262                  | 0.185                             | 0.447        | Head SAR  | Right Cheek   | 0.149                       | 0.185                             | 0.334        |
|           | Right Tilt    | 0.184                  | 0.180                             | 0.364        |           | Right Tilt    | 0.143                       | 0.180                             | 0.323        |
|           | Left Cheek    | 0.336                  | 0.147                             | <b>0.483</b> |           | Left Cheek    | 0.382                       | 0.147                             | <b>0.529</b> |
|           | Left Tilt     | 0.180                  | 0.146                             | 0.326        |           | Left Tilt     | 0.128                       | 0.146                             | 0.274        |

| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|-----------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.349                        | 0.185                             | 0.534        |
|           | Right Tilt    | 0.269                        | 0.180                             | 0.449        |
|           | Left Cheek    | 0.634                        | 0.147                             | <b>0.781</b> |
|           | Left Tilt     | 0.228                        | 0.146                             | 0.374        |

**Table 12-3**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 2 (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | Cell. EVDO SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|-----------------------------------|--------------|-----------|---------------|-----------------------|-----------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.612                 | 0.039                             | <b>0.651</b> | Head SAR  | Right Cheek   | 0.611                 | 0.039                             | <b>0.650</b> |
|           | Right Tilt    | 0.351                 | 0.008                             | 0.359        |           | Right Tilt    | 0.327                 | 0.008                             | 0.335        |
|           | Left Cheek    | 0.457                 | 0.011                             | 0.468        |           | Left Cheek    | 0.494                 | 0.011                             | 0.505        |
|           | Left Tilt     | 0.304                 | 0.005                             | 0.309        |           | Left Tilt     | 0.333                 | 0.005                             | 0.338        |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|---------------------|-----------------------------------|--------------|-----------|---------------|---------------------|-----------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.563               | 0.039                             | <b>0.602</b> | Head SAR  | Right Cheek   | 0.352               | 0.039                             | <b>0.391</b> |
|           | Right Tilt    | 0.261               | 0.008                             | 0.269        |           | Right Tilt    | 0.138               | 0.008                             | 0.146        |
|           | Left Cheek    | 0.286               | 0.011                             | 0.297        |           | Left Cheek    | 0.271               | 0.011                             | 0.282        |
|           | Left Tilt     | 0.201               | 0.005                             | 0.206        |           | Left Tilt     | 0.111               | 0.005                             | 0.116        |

| Simult Tx | Configuration | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------|-----------------------------------|--------------|-----------|---------------|-----------------------------|-----------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.262                  | 0.039                             | 0.301        | Head SAR  | Right Cheek   | 0.149                       | 0.039                             | 0.188        |
|           | Right Tilt    | 0.184                  | 0.008                             | 0.192        |           | Right Tilt    | 0.143                       | 0.008                             | 0.151        |
|           | Left Cheek    | 0.336                  | 0.011                             | <b>0.347</b> |           | Left Cheek    | 0.382                       | 0.011                             | <b>0.393</b> |
|           | Left Tilt     | 0.180                  | 0.005                             | 0.185        |           | Left Tilt     | 0.128                       | 0.005                             | 0.133        |

| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|-----------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.349                        | 0.039                             | 0.388        |
|           | Right Tilt    | 0.269                        | 0.008                             | 0.277        |
|           | Left Cheek    | 0.634                        | 0.011                             | <b>0.645</b> |
|           | Left Tilt     | 0.228                        | 0.005                             | 0.233        |

|                                          |                                                                                                                                                  |                                      |                                                                                       |                                        |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br><small>ENGINEERING LABORATORY, INC.</small> | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                                        | <b>DUT Type:</b><br>Portable Handset | Page 53 of 79                                                                         |                                        |



**Table 12-4**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg)  | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)                 | Simult Tx                    | Configuration | Cell. EVDO SAR (W/kg)       | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------|------------------------------|------------------------------|------------------------------|---------------|-----------------------------|------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.612                  | 0.103                        | <b>0.715</b>                 | Head SAR                     | Right Cheek   | 0.611                       | 0.103                        | <b>0.714</b> |
|           | Right Tilt    | 0.351                  | 0.091                        | 0.442                        |                              | Right Tilt    | 0.327                       | 0.091                        | 0.418        |
|           | Left Cheek    | 0.457                  | 0.121                        | 0.578                        |                              | Left Cheek    | 0.494                       | 0.121                        | 0.615        |
|           | Left Tilt     | 0.304                  | 0.124                        | 0.428                        |                              | Left Tilt     | 0.333                       | 0.124                        | 0.457        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg)    | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)                 | Simult Tx                    | Configuration | PCS EVDO SAR (W/kg)         | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
| Head SAR  | Right Cheek   | 0.563                  | 0.103                        | <b>0.666</b>                 | Head SAR                     | Right Cheek   | 0.352                       | 0.103                        | <b>0.455</b> |
|           | Right Tilt    | 0.261                  | 0.091                        | 0.352                        |                              | Right Tilt    | 0.138                       | 0.091                        | 0.229        |
|           | Left Cheek    | 0.286                  | 0.121                        | 0.407                        |                              | Left Cheek    | 0.271                       | 0.121                        | 0.392        |
|           | Left Tilt     | 0.201                  | 0.124                        | 0.325                        |                              | Left Tilt     | 0.111                       | 0.124                        | 0.235        |
| Simult Tx | Configuration | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)                 | Simult Tx                    | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
| Head SAR  | Right Cheek   | 0.262                  | 0.103                        | 0.365                        | Head SAR                     | Right Cheek   | 0.149                       | 0.103                        | 0.252        |
|           | Right Tilt    | 0.184                  | 0.091                        | 0.275                        |                              | Right Tilt    | 0.143                       | 0.091                        | 0.234        |
|           | Left Cheek    | 0.336                  | 0.121                        | <b>0.457</b>                 |                              | Left Cheek    | 0.382                       | 0.121                        | <b>0.503</b> |
|           | Left Tilt     | 0.180                  | 0.124                        | 0.304                        |                              | Left Tilt     | 0.128                       | 0.124                        | 0.252        |
|           |               |                        |                              |                              |                              |               |                             |                              |              |
|           |               | Simult Tx              | Configuration                | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)  |                             |                              |              |
|           |               | Head SAR               | Right Cheek                  | 0.349                        | 0.103                        | 0.452         |                             |                              |              |
|           |               |                        | Right Tilt                   | 0.269                        | 0.091                        | 0.360         |                             |                              |              |
|           |               |                        | Left Cheek                   | 0.634                        | 0.121                        | <b>0.755</b>  |                             |                              |              |
|           |               |                        | Left Tilt                    | 0.228                        | 0.124                        | 0.352         |                             |                              |              |

**Table 12-5**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 1 (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | Cell. EVDO SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|---------------------------------|--------------|-----------|---------------|-----------------------|---------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.612                 | 0.063                           | <b>0.675</b> | Head SAR  | Right Cheek   | 0.611                 | 0.063                           | <b>0.674</b> |
|           | Right Tilt    | 0.351                 | 0.063                           | 0.414        |           | Right Tilt    | 0.327                 | 0.063                           | 0.390        |
|           | Left Cheek    | 0.457                 | 0.042                           | 0.499        |           | Left Cheek    | 0.494                 | 0.042                           | 0.536        |
|           | Left Tilt     | 0.304                 | 0.049                           | 0.353        |           | Left Tilt     | 0.333                 | 0.049                           | 0.382        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg)   | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)   | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
| Head SAR  | Right Cheek   | 0.563                 | 0.063                           | <b>0.626</b> | Head SAR  | Right Cheek   | 0.352                 | 0.063                           | <b>0.415</b> |
|           | Right Tilt    | 0.261                 | 0.063                           | 0.324        |           | Right Tilt    | 0.138                 | 0.063                           | 0.201        |
|           | Left Cheek    | 0.286                 | 0.042                           | 0.328        |           | Left Cheek    | 0.271                 | 0.042                           | 0.313        |
|           | Left Tilt     | 0.201                 | 0.049                           | 0.250        |           | Left Tilt     | 0.111                 | 0.049                           | 0.160        |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 54 of 79                                                                         |                                        |

| Simult Tx | Configuration | LTE Band 12 SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------|---------------------------------|--------------|-----------|---------------|-----------------------------|---------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.262                  | 0.063                           | 0.325        | Head SAR  | Right Cheek   | 0.149                       | 0.063                           | 0.212        |
|           | Right Tilt    | 0.184                  | 0.063                           | 0.247        |           | Right Tilt    | 0.143                       | 0.063                           | 0.206        |
|           | Left Cheek    | 0.336                  | 0.042                           | <b>0.378</b> |           | Left Cheek    | 0.382                       | 0.042                           | <b>0.424</b> |
|           | Left Tilt     | 0.180                  | 0.049                           | 0.229        |           | Left Tilt     | 0.128                       | 0.049                           | 0.177        |

| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|---------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.349                        | 0.063                           | 0.412        |
|           | Right Tilt    | 0.269                        | 0.063                           | 0.332        |
|           | Left Cheek    | 0.634                        | 0.042                           | <b>0.676</b> |
|           | Left Tilt     | 0.228                        | 0.049                           | 0.277        |

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

**Table 12-6**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 2 (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | Cell. EVDO SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|---------------------------------|--------------|-----------|---------------|-----------------------|---------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.612                 | 0.217                           | <b>0.829</b> | Head SAR  | Right Cheek   | 0.611                 | 0.217                           | <b>0.828</b> |
|           | Right Tilt    | 0.351                 | 0.080                           | 0.431        |           | Right Tilt    | 0.327                 | 0.080                           | 0.407        |
|           | Left Cheek    | 0.457                 | 0.046                           | 0.503        |           | Left Cheek    | 0.494                 | 0.046                           | 0.540        |
|           | Left Tilt     | 0.304                 | 0.044                           | 0.348        |           | Left Tilt     | 0.333                 | 0.044                           | 0.377        |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|---------------------|---------------------------------|--------------|-----------|---------------|---------------------|---------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.563               | 0.217                           | <b>0.780</b> | Head SAR  | Right Cheek   | 0.352               | 0.217                           | <b>0.569</b> |
|           | Right Tilt    | 0.261               | 0.080                           | 0.341        |           | Right Tilt    | 0.138               | 0.080                           | 0.218        |
|           | Left Cheek    | 0.286               | 0.046                           | 0.332        |           | Left Cheek    | 0.271               | 0.046                           | 0.317        |
|           | Left Tilt     | 0.201               | 0.044                           | 0.245        |           | Left Tilt     | 0.111               | 0.044                           | 0.155        |

| Simult Tx | Configuration | LTE Band 12 SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------|---------------------------------|--------------|-----------|---------------|-----------------------------|---------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.262                  | 0.217                           | <b>0.479</b> | Head SAR  | Right Cheek   | 0.149                       | 0.217                           | 0.366        |
|           | Right Tilt    | 0.184                  | 0.080                           | 0.264        |           | Right Tilt    | 0.143                       | 0.080                           | 0.223        |
|           | Left Cheek    | 0.336                  | 0.046                           | 0.382        |           | Left Cheek    | 0.382                       | 0.046                           | <b>0.428</b> |
|           | Left Tilt     | 0.180                  | 0.044                           | 0.224        |           | Left Tilt     | 0.128                       | 0.044                           | 0.172        |

| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|---------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.349                        | 0.217                           | 0.566        |
|           | Right Tilt    | 0.269                        | 0.080                           | 0.349        |
|           | Left Cheek    | 0.634                        | 0.046                           | <b>0.680</b> |
|           | Left Tilt     | 0.228                        | 0.044                           | 0.272        |

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 55 of 79                                                                         |                                        |

**Table 12-7**  
**Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg)        | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | Cell. EVDO SAR (W/kg)       | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|----------------------------|--------------|-----------|---------------|-----------------------------|----------------------------|--------------|
| Head SAR  | Right Cheek   | 0.612                        | 0.061                      | <b>0.673</b> | Head SAR  | Right Cheek   | 0.611                       | 0.061                      | <b>0.672</b> |
|           | Right Tilt    | 0.351                        | 0.017                      | 0.368        |           | Right Tilt    | 0.327                       | 0.017                      | 0.344        |
|           | Left Cheek    | 0.457                        | 0.020                      | 0.477        |           | Left Cheek    | 0.494                       | 0.020                      | 0.514        |
|           | Left Tilt     | 0.304                        | 0.014                      | 0.318        |           | Left Tilt     | 0.333                       | 0.014                      | 0.347        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg)          | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)         | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
| Head SAR  | Right Cheek   | 0.563                        | 0.061                      | <b>0.624</b> | Head SAR  | Right Cheek   | 0.352                       | 0.061                      | <b>0.413</b> |
|           | Right Tilt    | 0.261                        | 0.017                      | 0.278        |           | Right Tilt    | 0.138                       | 0.017                      | 0.155        |
|           | Left Cheek    | 0.286                        | 0.020                      | 0.306        |           | Left Cheek    | 0.271                       | 0.020                      | 0.291        |
|           | Left Tilt     | 0.201                        | 0.014                      | 0.215        |           | Left Tilt     | 0.111                       | 0.014                      | 0.125        |
| Simult Tx | Configuration | LTE Band 12 SAR (W/kg)       | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
| Head SAR  | Right Cheek   | 0.262                        | 0.061                      | 0.323        | Head SAR  | Right Cheek   | 0.149                       | 0.061                      | 0.210        |
|           | Right Tilt    | 0.184                        | 0.017                      | 0.201        |           | Right Tilt    | 0.143                       | 0.017                      | 0.160        |
|           | Left Cheek    | 0.336                        | 0.020                      | <b>0.356</b> |           | Left Cheek    | 0.382                       | 0.020                      | <b>0.402</b> |
|           | Left Tilt     | 0.180                        | 0.014                      | 0.194        |           | Left Tilt     | 0.128                       | 0.014                      | 0.142        |
| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |           |               |                             |                            |              |
| Head SAR  | Right Cheek   | 0.349                        | 0.061                      | 0.410        |           |               |                             |                            |              |
|           | Right Tilt    | 0.269                        | 0.017                      | 0.286        |           |               |                             |                            |              |
|           | Left Cheek    | 0.634                        | 0.020                      | <b>0.654</b> |           |               |                             |                            |              |
|           | Left Tilt     | 0.228                        | 0.014                      | 0.242        |           |               |                             |                            |              |

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

## 12.4 Body-Worn Simultaneous Transmission Analysis

Note: For SAR summation for body back side at 15 mm CDMA BC0, LTE Band 12/4/25, and WLAN SAR values for 10 mm were used since the 10 mm test distance was more conservative. "<" denotes that the 10 mm SAR values were used for the respective modes for summation purposes.

**Table 12-8**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 1 (Body-Worn at 1.5 cm)**

| Configuration | Mode              | CDMA/LTE SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg)      |
|---------------|-------------------|---------------------|-----------------------------------|-------------------|
| Back Side     | Cell. CDMA        | < 0.775             | < 0.261                           | <b>&lt; 1.036</b> |
| Back Side     | PCS CDMA          | 0.526               | < 0.261                           | < 0.787           |
| Back Side     | LTE Band 12       | < 0.407             | < 0.261                           | < 0.668           |
| Back Side     | LTE Band 4 (AWS)  | < 0.509             | < 0.261                           | < 0.770           |
| Back Side     | LTE Band 25 (PCS) | < 0.216             | < 0.261                           | < 0.477           |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 56 of 79                                                                         |                                        |

**Table 12-9**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 2 (Body-Worn at 1.5 cm)**

| Configuration | Mode              | CDMA/LTE SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|---------------|-------------------|---------------------|-----------------------------------|---------------------|
| Back Side     | Cell. CDMA        | < 0.775             | < 0.096                           | <b>&lt; 0.871</b>   |
| Back Side     | PCS CDMA          | 0.526               | < 0.096                           | < 0.622             |
| Back Side     | LTE Band 12       | < 0.407             | < 0.096                           | < 0.503             |
| Back Side     | LTE Band 4 (AWS)  | < 0.509             | < 0.096                           | < 0.605             |
| Back Side     | LTE Band 25 (PCS) | < 0.216             | < 0.096                           | < 0.312             |

**Table 12-10**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Body-Worn at 1.5 cm)**

| Configuration | Mode              | CDMA/LTE SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|---------------|-------------------|---------------------|------------------------------|---------------------|
| Back Side     | Cell. CDMA        | < 0.775             | < 0.068                      | <b>&lt; 0.843</b>   |
| Back Side     | PCS CDMA          | 0.526               | < 0.068                      | < 0.594             |
| Back Side     | LTE Band 12       | < 0.407             | < 0.068                      | < 0.475             |
| Back Side     | LTE Band 4 (AWS)  | < 0.509             | < 0.068                      | < 0.577             |
| Back Side     | LTE Band 25 (PCS) | < 0.216             | < 0.068                      | < 0.284             |

**Table 12-11**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 1 (Body-Worn at 1.5 cm)**

| Configuration | Mode              | CDMA/LTE SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|---------------|-------------------|---------------------|---------------------------------|---------------------|
| Back Side     | Cell. CDMA        | < 0.775             | < 0.269                         | <b>&lt; 1.044</b>   |
| Back Side     | PCS CDMA          | 0.526               | < 0.269                         | < 0.795             |
| Back Side     | LTE Band 12       | < 0.407             | < 0.269                         | < 0.676             |
| Back Side     | LTE Band 4 (AWS)  | < 0.509             | < 0.269                         | < 0.778             |
| Back Side     | LTE Band 25 (PCS) | < 0.216             | < 0.269                         | < 0.485             |

The worst case 5 GHz WIFI reported SAR for each body-worn configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 57 of 79                                                                         |                                        |

**Table 12-12**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 2 (Body-Worn at 1.5 cm)**

| Configuration | Mode              | CDMA/LTE SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|---------------|-------------------|---------------------|---------------------------------|---------------------|
| Back Side     | Cell. CDMA        | < 0.775             | < 0.351                         | < <b>1.126</b>      |
| Back Side     | PCS CDMA          | 0.526               | < 0.351                         | < 0.877             |
| Back Side     | LTE Band 12       | < 0.407             | < 0.351                         | < 0.758             |
| Back Side     | LTE Band 4 (AWS)  | < 0.509             | < 0.351                         | < 0.860             |
| Back Side     | LTE Band 25 (PCS) | < 0.216             | < 0.351                         | < 0.567             |

The worst case 5 GHz WIFI reported SAR for each body-worn configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

**Table 12-13**  
**Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Body-Worn at 1.5 cm)**

| Configuration | Mode              | CDMA/LTE SAR (W/kg) | 5 GHz WLAN MIMO SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|---------------|-------------------|---------------------|----------------------------|---------------------|
| Back Side     | Cell. CDMA        | < 0.775             | < 0.222                    | < <b>0.997</b>      |
| Back Side     | PCS CDMA          | 0.526               | < 0.222                    | < 0.748             |
| Back Side     | LTE Band 12       | < 0.407             | < 0.222                    | < 0.629             |
| Back Side     | LTE Band 4 (AWS)  | < 0.509             | < 0.222                    | < 0.731             |
| Back Side     | LTE Band 25 (PCS) | < 0.216             | < 0.222                    | < 0.438             |

The worst case 5 GHz WIFI reported SAR for each body-worn configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

**Table 12-14**  
**Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)**

| Configuration | Mode              | CDMA/LTE SAR (W/kg) | Bluetooth SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|---------------|-------------------|---------------------|----------------------|---------------------|
| Back Side     | Cell. CDMA        | < 0.775             | 0.139                | < <b>0.914</b>      |
| Back Side     | PCS CDMA          | 0.526               | 0.139                | < 0.665             |
| Back Side     | LTE Band 12       | < 0.407             | 0.139                | < 0.546             |
| Back Side     | LTE Band 4 (AWS)  | < 0.509             | 0.139                | < 0.648             |
| Back Side     | LTE Band 25 (PCS) | < 0.216             | 0.139                | < 0.355             |

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 58 of 79                                                                         |                                 |

## 12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR ("–").

**Table 12-15**  
**Simultaneous Transmission Scenario (2.4 GHz Hotspot Antenna 1 at 1.0 cm)**

| Simult Tx | Configuration | Cell. EVDO SAR (W/kg)        | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)         | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|-----------------------------------|--------------|-----------|---------------|-----------------------------|-----------------------------------|--------------|
| Body SAR  | Back          | 0.766                        | 0.261                             | 1.027        | Body SAR  | Back          | 0.573                       | 0.261                             | 0.834        |
|           | Front         | 0.683                        | 0.214                             | 0.897        |           | Front         | 0.397                       | 0.214                             | 0.611        |
|           | Top           | –                            | 0.126                             | 0.126        |           | Top           | –                           | 0.126                             | 0.126        |
|           | Bottom        | 0.520                        | –                                 | 0.520        |           | Bottom        | 0.462                       | –                                 | 0.462        |
|           | Right         | 0.765                        | –                                 | 0.765        |           | Right         | 0.372                       | –                                 | 0.372        |
|           | Left          | –                            | 0.123                             | 0.123        |           | Left          | –                           | 0.123                             | 0.123        |
| Simult Tx | Configuration | LTE Band 12 SAR (W/kg)       | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
| Body SAR  | Back          | 0.407                        | 0.261                             | 0.668        | Body SAR  | Back          | 0.509                       | 0.261                             | 0.770        |
|           | Front         | 0.515                        | 0.214                             | 0.729        |           | Front         | 0.586                       | 0.214                             | 0.800        |
|           | Top           | –                            | 0.126                             | 0.126        |           | Top           | –                           | 0.126                             | 0.126        |
|           | Bottom        | 0.345                        | –                                 | 0.345        |           | Bottom        | 0.143                       | –                                 | 0.143        |
|           | Right         | –                            | –                                 | 0.000        |           | Right         | –                           | –                                 | 0.000        |
|           | Left          | 0.348                        | 0.123                             | 0.471        |           | Left          | 0.183                       | 0.123                             | 0.306        |
| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |           |               |                             |                                   |              |
| Body SAR  | Back          | 0.188                        | 0.261                             | 0.449        |           |               |                             |                                   |              |
|           | Front         | 0.566                        | 0.214                             | 0.780        |           |               |                             |                                   |              |
|           | Top           | –                            | 0.126                             | 0.126        |           |               |                             |                                   |              |
|           | Bottom        | 0.101                        | –                                 | 0.101        |           |               |                             |                                   |              |
|           | Right         | –                            | –                                 | 0.000        |           |               |                             |                                   |              |
|           | Left          | 0.255                        | 0.123                             | 0.378        |           |               |                             |                                   |              |

**Table 12-16**  
**Simultaneous Transmission Scenario (2.4 GHz Hotspot Antenna 2 at 1.0 cm)**

| Simult Tx | Configuration | Cell. EVDO SAR (W/kg)        | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)         | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|-----------------------------------|--------------|-----------|---------------|-----------------------------|-----------------------------------|--------------|
| Body SAR  | Back          | 0.766                        | 0.096                             | 0.862        | Body SAR  | Back          | 0.573                       | 0.096                             | 0.669        |
|           | Front         | 0.683                        | 0.059                             | 0.742        |           | Front         | 0.397                       | 0.059                             | 0.456        |
|           | Top           | –                            | 0.024                             | 0.024        |           | Top           | –                           | 0.024                             | 0.024        |
|           | Bottom        | 0.520                        | –                                 | 0.520        |           | Bottom        | 0.462                       | –                                 | 0.462        |
|           | Right         | 0.765                        | –                                 | 0.765        |           | Right         | 0.372                       | –                                 | 0.372        |
|           | Left          | –                            | 0.085                             | 0.085        |           | Left          | –                           | 0.085                             | 0.085        |
| Simult Tx | Configuration | LTE Band 12 SAR (W/kg)       | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
| Body SAR  | Back          | 0.407                        | 0.096                             | 0.503        | Body SAR  | Back          | 0.509                       | 0.096                             | 0.605        |
|           | Front         | 0.515                        | 0.059                             | 0.574        |           | Front         | 0.586                       | 0.059                             | 0.645        |
|           | Top           | –                            | 0.024                             | 0.024        |           | Top           | –                           | 0.024                             | 0.024        |
|           | Bottom        | 0.345                        | –                                 | 0.345        |           | Bottom        | 0.143                       | –                                 | 0.143        |
|           | Right         | –                            | –                                 | 0.000        |           | Right         | –                           | –                                 | 0.000        |
|           | Left          | 0.348                        | 0.085                             | 0.433        |           | Left          | 0.183                       | 0.085                             | 0.268        |
| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |           |               |                             |                                   |              |
| Body SAR  | Back          | 0.188                        | 0.096                             | 0.284        |           |               |                             |                                   |              |
|           | Front         | 0.566                        | 0.059                             | 0.625        |           |               |                             |                                   |              |
|           | Top           | –                            | 0.024                             | 0.024        |           |               |                             |                                   |              |
|           | Bottom        | 0.101                        | –                                 | 0.101        |           |               |                             |                                   |              |
|           | Right         | –                            | –                                 | 0.000        |           |               |                             |                                   |              |
|           | Left          | 0.255                        | 0.085                             | 0.340        |           |               |                             |                                   |              |

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 59 of 79                                                                         |                                        |

**Table 12-17**  
**Simultaneous Transmission Scenario (2.4 GHz Hotspot MIMO at 1.0 cm)**

| Simult Tx | Configuration | Cell. EVDO SAR (W/kg)        | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)         | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|------------------------------|--------------|-----------|---------------|-----------------------------|------------------------------|--------------|
| Body SAR  | Back          | 0.766                        | 0.068                        | <b>0.834</b> | Body SAR  | Back          | 0.573                       | 0.068                        | <b>0.641</b> |
|           | Front         | 0.683                        | 0.058                        | 0.741        |           | Front         | 0.397                       | 0.058                        | 0.455        |
|           | Top           | -                            | 0.038                        | 0.038        |           | Top           | -                           | 0.038                        | 0.038        |
|           | Bottom        | 0.520                        | -                            | 0.520        |           | Bottom        | 0.462                       | -                            | 0.462        |
|           | Right         | 0.765                        | -                            | 0.765        |           | Right         | 0.372                       | -                            | 0.372        |
|           | Left          | -                            | 0.030                        | 0.030        |           | Left          | -                           | 0.030                        | 0.030        |
| Simult Tx | Configuration | LTE Band 12 SAR (W/kg)       | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
| Body SAR  | Back          | 0.407                        | 0.068                        | 0.475        | Body SAR  | Back          | 0.509                       | 0.068                        | 0.577        |
|           | Front         | 0.515                        | 0.058                        | <b>0.573</b> |           | Front         | 0.586                       | 0.058                        | <b>0.644</b> |
|           | Top           | -                            | 0.038                        | 0.038        |           | Top           | -                           | 0.038                        | 0.038        |
|           | Bottom        | 0.345                        | -                            | 0.345        |           | Bottom        | 0.143                       | -                            | 0.143        |
|           | Right         | -                            | -                            | 0.000        |           | Right         | -                           | -                            | 0.000        |
|           | Left          | 0.348                        | 0.030                        | 0.378        |           | Left          | 0.183                       | 0.030                        | 0.213        |
| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |           |               |                             |                              |              |
| Body SAR  | Back          | 0.188                        | 0.068                        | 0.256        |           |               |                             |                              |              |
|           | Front         | 0.566                        | 0.058                        | <b>0.624</b> |           |               |                             |                              |              |
|           | Top           | -                            | 0.038                        | 0.038        |           |               |                             |                              |              |
|           | Bottom        | 0.101                        | -                            | 0.101        |           |               |                             |                              |              |
|           | Right         | -                            | -                            | 0.000        |           |               |                             |                              |              |
|           | Left          | 0.255                        | 0.030                        | 0.285        |           |               |                             |                              |              |

**Table 12-18**  
**Simultaneous Transmission Scenario (5.8 GHz Hotspot Antenna 1 at 1.0 cm)**

| Simult Tx | Configuration | Cell. EVDO SAR (W/kg)        | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)         | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|-----------------------------------|--------------|-----------|---------------|-----------------------------|-----------------------------------|--------------|
| Body SAR  | Back          | 0.766                        | 0.162                             | <b>0.928</b> | Body SAR  | Back          | 0.573                       | 0.162                             | <b>0.735</b> |
|           | Front         | 0.683                        | 0.104                             | 0.787        |           | Front         | 0.397                       | 0.104                             | 0.501        |
|           | Top           | -                            | 0.305                             | 0.305        |           | Top           | -                           | 0.305                             | 0.305        |
|           | Bottom        | 0.520                        | -                                 | 0.520        |           | Bottom        | 0.462                       | -                                 | 0.462        |
|           | Right         | 0.765                        | -                                 | 0.765        |           | Right         | 0.372                       | -                                 | 0.372        |
|           | Left          | -                            | 0.029                             | 0.029        |           | Left          | -                           | 0.029                             | 0.029        |
| Simult Tx | Configuration | LTE Band 12 SAR (W/kg)       | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
| Body SAR  | Back          | 0.407                        | 0.162                             | 0.569        | Body SAR  | Back          | 0.509                       | 0.162                             | 0.671        |
|           | Front         | 0.515                        | 0.104                             | <b>0.619</b> |           | Front         | 0.586                       | 0.104                             | <b>0.690</b> |
|           | Top           | -                            | 0.305                             | 0.305        |           | Top           | -                           | 0.305                             | 0.305        |
|           | Bottom        | 0.345                        | -                                 | 0.345        |           | Bottom        | 0.143                       | -                                 | 0.143        |
|           | Right         | -                            | -                                 | 0.000        |           | Right         | -                           | -                                 | 0.000        |
|           | Left          | 0.348                        | 0.029                             | 0.377        |           | Left          | 0.183                       | 0.029                             | 0.212        |
| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |           |               |                             |                                   |              |
| Body SAR  | Back          | 0.188                        | 0.162                             | 0.350        |           |               |                             |                                   |              |
|           | Front         | 0.566                        | 0.104                             | <b>0.670</b> |           |               |                             |                                   |              |
|           | Top           | -                            | 0.305                             | 0.305        |           |               |                             |                                   |              |
|           | Bottom        | 0.101                        | -                                 | 0.101        |           |               |                             |                                   |              |
|           | Right         | -                            | -                                 | 0.000        |           |               |                             |                                   |              |
|           | Left          | 0.255                        | 0.029                             | 0.284        |           |               |                             |                                   |              |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 60 of 79                                                                         |                                        |



**Table 12-19**  
**Simultaneous Transmission Scenario (5.8 GHz Hotspot Antenna 2 at 1.0 cm)**

| Simult Tx | Configuration | Cell. EVDO SAR (W/kg)        | 5.8 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)         | 5.8 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|-----------------------------------|--------------|-----------|---------------|-----------------------------|-----------------------------------|--------------|
| Body SAR  | Back          | 0.766                        | 0.327                             | <b>1.093</b> | Body SAR  | Back          | 0.573                       | 0.327                             | <b>0.900</b> |
|           | Front         | 0.683                        | 0.089                             | 0.772        |           | Front         | 0.397                       | 0.089                             | 0.486        |
|           | Top           | -                            | 0.075                             | 0.075        |           | Top           | -                           | 0.075                             | 0.075        |
|           | Bottom        | 0.520                        | -                                 | 0.520        |           | Bottom        | 0.462                       | -                                 | 0.462        |
|           | Right         | 0.765                        | -                                 | 0.765        |           | Right         | 0.372                       | -                                 | 0.372        |
|           | Left          | -                            | 0.197                             | 0.197        |           | Left          | -                           | 0.197                             | 0.197        |
| Simult Tx | Configuration | LTE Band 12 SAR (W/kg)       | 5.8 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 5.8 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
| Body SAR  | Back          | 0.407                        | 0.327                             | <b>0.734</b> | Body SAR  | Back          | 0.509                       | 0.327                             | <b>0.836</b> |
|           | Front         | 0.515                        | 0.089                             | 0.604        |           | Front         | 0.586                       | 0.089                             | 0.675        |
|           | Top           | -                            | 0.075                             | 0.075        |           | Top           | -                           | 0.075                             | 0.075        |
|           | Bottom        | 0.345                        | -                                 | 0.345        |           | Bottom        | 0.143                       | -                                 | 0.143        |
|           | Right         | -                            | -                                 | 0.000        |           | Right         | -                           | -                                 | 0.000        |
|           | Left          | 0.348                        | 0.197                             | 0.545        |           | Left          | 0.183                       | 0.197                             | 0.380        |
| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 5.8 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |           |               |                             |                                   |              |
| Body SAR  | Back          | 0.188                        | 0.327                             | 0.515        |           |               |                             |                                   |              |
|           | Front         | 0.566                        | 0.089                             | <b>0.655</b> |           |               |                             |                                   |              |
|           | Top           | -                            | 0.075                             | 0.075        |           |               |                             |                                   |              |
|           | Bottom        | 0.101                        | -                                 | 0.101        |           |               |                             |                                   |              |
|           | Right         | -                            | -                                 | 0.000        |           |               |                             |                                   |              |
|           | Left          | 0.255                        | 0.197                             | 0.452        |           |               |                             |                                   |              |

**Table 12-20**  
**Simultaneous Transmission Scenario (5.8 GHz Hotspot MIMO at 1.0 cm)**

| Simult Tx | Configuration | Cell. EVDO SAR (W/kg)        | 5.8 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS EVDO SAR (W/kg)         | 5.8 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|------------------------------|------------------------------|--------------|-----------|---------------|-----------------------------|------------------------------|--------------|
| Body SAR  | Back          | 0.766                        | 0.222                        | <b>0.988</b> | Body SAR  | Back          | 0.573                       | 0.222                        | <b>0.795</b> |
|           | Front         | 0.683                        | 0.032                        | 0.715        |           | Front         | 0.397                       | 0.032                        | 0.429        |
|           | Top           | -                            | 0.098                        | 0.098        |           | Top           | -                           | 0.098                        | 0.098        |
|           | Bottom        | 0.520                        | -                            | 0.520        |           | Bottom        | 0.462                       | -                            | 0.462        |
|           | Right         | 0.765                        | -                            | 0.765        |           | Right         | 0.372                       | -                            | 0.372        |
|           | Left          | -                            | 0.060                        | 0.060        |           | Left          | -                           | 0.060                        | 0.060        |
| Simult Tx | Configuration | LTE Band 12 SAR (W/kg)       | 5.8 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 5.8 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
| Body SAR  | Back          | 0.407                        | 0.222                        | <b>0.629</b> | Body SAR  | Back          | 0.509                       | 0.222                        | <b>0.731</b> |
|           | Front         | 0.515                        | 0.032                        | 0.547        |           | Front         | 0.586                       | 0.032                        | 0.618        |
|           | Top           | -                            | 0.098                        | 0.098        |           | Top           | -                           | 0.098                        | 0.098        |
|           | Bottom        | 0.345                        | -                            | 0.345        |           | Bottom        | 0.143                       | -                            | 0.143        |
|           | Right         | -                            | -                            | 0.000        |           | Right         | -                           | -                            | 0.000        |
|           | Left          | 0.348                        | 0.060                        | 0.408        |           | Left          | 0.183                       | 0.060                        | 0.243        |
| Simult Tx | Configuration | LTE Band 25 (PCS) SAR (W/kg) | 5.8 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |           |               |                             |                              |              |
| Body SAR  | Back          | 0.188                        | 0.222                        | 0.410        |           |               |                             |                              |              |
|           | Front         | 0.566                        | 0.032                        | <b>0.598</b> |           |               |                             |                              |              |
|           | Top           | -                            | 0.098                        | 0.098        |           |               |                             |                              |              |
|           | Bottom        | 0.101                        | -                            | 0.101        |           |               |                             |                              |              |
|           | Right         | -                            | -                            | 0.000        |           |               |                             |                              |              |
|           | Left          | 0.255                        | 0.060                        | 0.315        |           |               |                             |                              |              |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 61 of 79                                                                         |                                        |

## 12.6 SVLTE Simultaneous Transmission Analysis

### Notes:

1. For SAR summation for body-worn back side at 15 mm CDMA BC0, LTE Band 12/4/25, and WLAN SAR values for 10 mm were used since the 10 mm test distance was more conservative. For these modes, "<" denotes that the 10 mm SAR values were used for summation purposes.
2. For summation for body-worn back side at 15 mm CDMA BC1 maximum output power SAR was used since it is more conservative than the reduced output power SAR. For CDMA BC1, "<" denotes that the maximum output power SAR was used for summation purposes.

**Table 12-21**  
**Simultaneous Transmission Scenario (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------------|--------------|-----------|---------------|---------------------|------------------------------|--------------|
| Head SAR  | Right Cheek   | 0.612                 | 0.262                        | <b>0.874</b> | Head SAR  | Right Cheek   | 0.563               | 0.262                        | <b>0.825</b> |
|           | Right Tilt    | 0.351                 | 0.184                        | 0.535        |           | Right Tilt    | 0.261               | 0.184                        | 0.445        |
|           | Left Cheek    | 0.457                 | 0.336                        | 0.793        |           | Left Cheek    | 0.286               | 0.336                        | 0.622        |
|           | Left Tilt     | 0.304                 | 0.180                        | 0.484        |           | Left Tilt     | 0.201               | 0.180                        | 0.381        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | Σ SAR (W/kg) |
| Head SAR  | Right Cheek   | 0.612                 | 0.149                        | 0.761        | Head SAR  | Right Cheek   | 0.563               | 0.149                        | <b>0.712</b> |
|           | Right Tilt    | 0.351                 | 0.143                        | 0.494        |           | Right Tilt    | 0.261               | 0.143                        | 0.404        |
|           | Left Cheek    | 0.457                 | 0.382                        | <b>0.839</b> |           | Left Cheek    | 0.286               | 0.382                        | 0.668        |
|           | Left Tilt     | 0.304                 | 0.128                        | 0.432        |           | Left Tilt     | 0.201               | 0.128                        | 0.329        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | Σ SAR (W/kg) |
| Head SAR  | Right Cheek   | 0.612                 | 0.349                        | 0.961        | Head SAR  | Right Cheek   | 0.563               | 0.349                        | 0.912        |
|           | Right Tilt    | 0.351                 | 0.269                        | 0.620        |           | Right Tilt    | 0.261               | 0.269                        | 0.530        |
|           | Left Cheek    | 0.457                 | 0.634                        | <b>1.091</b> |           | Left Cheek    | 0.286               | 0.634                        | <b>0.920</b> |
|           | Left Tilt     | 0.304                 | 0.228                        | 0.532        |           | Left Tilt     | 0.201               | 0.228                        | 0.429        |

**Table 12-22**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 1 (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)      | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)      | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|-----------------------------|-----------------------------------|--------------|-----------|---------------|---------------------|-----------------------------|-----------------------------------|--------------|
| Head SAR  | Tx Antenna    | 1                     | 2                           | 3                                 | 1+2+3        | Head SAR  | Tx Antenna    | 1                   | 2                           | 3                                 | 1+2+3        |
|           | Right Cheek   | 0.612                 | 0.262                       | 0.185                             | <b>1.059</b> |           | Right Cheek   | 0.346               | 0.262                       | 0.185                             | <b>0.793</b> |
|           | Right Tilt    | 0.351                 | 0.184                       | 0.180                             | 0.715        |           | Right Tilt    | 0.131               | 0.184                       | 0.180                             | 0.495        |
|           | Left Cheek    | 0.457                 | 0.336                       | 0.147                             | 0.940        |           | Left Cheek    | 0.269               | 0.336                       | 0.147                             | 0.752        |
| Head SAR  | Left Tilt     | 0.304                 | 0.180                       | 0.146                             | 0.630        |           | Left Tilt     | 0.097               | 0.180                       | 0.146                             | 0.423        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
| Head SAR  | Tx Antenna    | 1                     | 2                           | 3                                 | 1+2+3        | Head SAR  | Tx Antenna    | 1                   | 2                           | 3                                 | 1+2+3        |
|           | Right Cheek   | 0.612                 | 0.149                       | 0.185                             | 0.946        |           | Right Cheek   | 0.346               | 0.149                       | 0.185                             | 0.680        |
|           | Right Tilt    | 0.351                 | 0.143                       | 0.180                             | 0.674        |           | Right Tilt    | 0.131               | 0.143                       | 0.180                             | 0.454        |
|           | Left Cheek    | 0.457                 | 0.382                       | 0.147                             | <b>0.986</b> |           | Left Cheek    | 0.269               | 0.382                       | 0.147                             | <b>0.798</b> |
| Head SAR  | Left Tilt     | 0.304                 | 0.128                       | 0.146                             | 0.578        |           | Left Tilt     | 0.097               | 0.128                       | 0.146                             | 0.371        |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 62 of 79                                                                         |                                        |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------------|-----------------------------------|--------------|-----------|---------------|---------------------|------------------------------|-----------------------------------|--------------|
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        |           | Tx Antenna    | 1                   | 2                            | 3                                 | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.349                        | 0.185                             | 1.146        | Head SAR  | Right Cheek   | 0.346               | 0.349                        | 0.185                             | 0.880        |
|           | Right Tilt    | 0.351                 | 0.269                        | 0.180                             | 0.800        |           | Right Tilt    | 0.131               | 0.269                        | 0.180                             | 0.580        |
|           | Left Cheek    | 0.457                 | 0.634                        | 0.147                             | <b>1.238</b> |           | Left Cheek    | 0.269               | 0.634                        | 0.147                             | <b>1.050</b> |
|           | Left Tilt     | 0.304                 | 0.228                        | 0.146                             | 0.678        |           | Left Tilt     | 0.097               | 0.228                        | 0.146                             | 0.471        |

**Table 12-23**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 2 (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------------|-----------------------------------|--------------|-----------|---------------|---------------------|------------------------------|-----------------------------------|--------------|
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        |           | Tx Antenna    | 1                   | 2                            | 3                                 | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.262                        | 0.039                             | <b>0.913</b> | Head SAR  | Right Cheek   | 0.346               | 0.262                        | 0.039                             | <b>0.647</b> |
|           | Right Tilt    | 0.351                 | 0.184                        | 0.008                             | 0.543        |           | Right Tilt    | 0.131               | 0.184                        | 0.008                             | 0.323        |
|           | Left Cheek    | 0.457                 | 0.336                        | 0.011                             | 0.804        |           | Left Cheek    | 0.269               | 0.336                        | 0.011                             | 0.616        |
|           | Left Tilt     | 0.304                 | 0.180                        | 0.005                             | 0.489        |           | Left Tilt     | 0.097               | 0.180                        | 0.005                             | 0.282        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        |           | Tx Antenna    | 1                   | 2                            | 3                                 | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.149                        | 0.039                             | 0.800        | Head SAR  | Right Cheek   | 0.346               | 0.149                        | 0.039                             | 0.534        |
|           | Right Tilt    | 0.351                 | 0.143                        | 0.008                             | 0.502        |           | Right Tilt    | 0.131               | 0.143                        | 0.008                             | 0.282        |
|           | Left Cheek    | 0.457                 | 0.382                        | 0.011                             | <b>0.850</b> |           | Left Cheek    | 0.269               | 0.382                        | 0.011                             | <b>0.662</b> |
|           | Left Tilt     | 0.304                 | 0.128                        | 0.005                             | 0.437        |           | Left Tilt     | 0.097               | 0.128                        | 0.005                             | 0.230        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        |           | Tx Antenna    | 1                   | 2                            | 3                                 | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.349                        | 0.039                             | 1.000        | Head SAR  | Right Cheek   | 0.346               | 0.349                        | 0.039                             | 0.734        |
|           | Right Tilt    | 0.351                 | 0.269                        | 0.008                             | 0.628        |           | Right Tilt    | 0.131               | 0.269                        | 0.008                             | 0.408        |
|           | Left Cheek    | 0.457                 | 0.634                        | 0.011                             | <b>1.102</b> |           | Left Cheek    | 0.269               | 0.634                        | 0.011                             | <b>0.914</b> |
|           | Left Tilt     | 0.304                 | 0.228                        | 0.005                             | 0.537        |           | Left Tilt     | 0.097               | 0.228                        | 0.005                             | 0.330        |

**Table 12-24**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------|------------------------------|--------------|-----------|---------------|---------------------|------------------------|------------------------------|--------------|
|           | Tx Antenna    | 1                     | 2                      | 3                            | 1+2+3        |           | Tx Antenna    | 1                   | 2                      | 3                            | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.262                  | 0.103                        | <b>0.977</b> | Head SAR  | Right Cheek   | 0.346               | 0.262                  | 0.103                        | 0.711        |
|           | Right Tilt    | 0.351                 | 0.184                  | 0.091                        | 0.626        |           | Right Tilt    | 0.131               | 0.184                  | 0.091                        | 0.406        |
|           | Left Cheek    | 0.457                 | 0.336                  | 0.121                        | 0.914        |           | Left Cheek    | 0.269               | 0.336                  | 0.121                        | <b>0.726</b> |
|           | Left Tilt     | 0.304                 | 0.180                  | 0.124                        | 0.608        |           | Left Tilt     | 0.097               | 0.180                  | 0.124                        | 0.401        |

|                                   |                                                                                                                                   |                               |  |  |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|--|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  |  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                                                                | DUT Type:<br>Portable Handset |  |  | Page 63 of 79                                                                         |                                 |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------------|------------------------------|--------------|
|           | Tx Antenna    | 1                     | 2                            | 3                            | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.149                        | 0.103                        | 0.864        |
|           | Right Tilt    | 0.351                 | 0.143                        | 0.091                        | 0.585        |
|           | Left Cheek    | 0.457                 | 0.382                        | 0.121                        | <b>0.960</b> |
|           | Left Tilt     | 0.304                 | 0.128                        | 0.124                        | 0.556        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                            | 3                            | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.349                        | 0.103                        | 1.064        |
|           | Right Tilt    | 0.351                 | 0.269                        | 0.091                        | 0.711        |
|           | Left Cheek    | 0.457                 | 0.634                        | 0.121                        | <b>1.212</b> |
|           | Left Tilt     | 0.304                 | 0.228                        | 0.124                        | 0.656        |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|---------------------|------------------------------|------------------------------|--------------|
|           | Tx Antenna    | 1                   | 2                            | 3                            | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.149                        | 0.103                        | 0.598        |
|           | Right Tilt    | 0.131               | 0.143                        | 0.091                        | 0.365        |
|           | Left Cheek    | 0.269               | 0.382                        | 0.121                        | <b>0.772</b> |
|           | Left Tilt     | 0.097               | 0.128                        | 0.124                        | 0.349        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                   | 2                            | 3                            | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.349                        | 0.103                        | 0.798        |
|           | Right Tilt    | 0.131               | 0.269                        | 0.091                        | 0.491        |
|           | Left Cheek    | 0.269               | 0.634                        | 0.121                        | <b>1.024</b> |
|           | Left Tilt     | 0.097               | 0.228                        | 0.124                        | 0.449        |

**Table 12-25**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 1 (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------------|---------------------------------|--------------|
|           | Tx Antenna    | 1                     | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.262                        | 0.063                           | <b>0.937</b> |
|           | Right Tilt    | 0.351                 | 0.184                        | 0.063                           | 0.598        |
|           | Left Cheek    | 0.457                 | 0.336                        | 0.042                           | 0.835        |
|           | Left Tilt     | 0.304                 | 0.180                        | 0.049                           | 0.533        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.149                        | 0.063                           | 0.824        |
|           | Right Tilt    | 0.351                 | 0.143                        | 0.063                           | 0.557        |
|           | Left Cheek    | 0.457                 | 0.382                        | 0.042                           | <b>0.881</b> |
|           | Left Tilt     | 0.304                 | 0.128                        | 0.049                           | 0.481        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.349                        | 0.063                           | 1.024        |
|           | Right Tilt    | 0.351                 | 0.269                        | 0.063                           | 0.683        |
|           | Left Cheek    | 0.457                 | 0.634                        | 0.042                           | <b>1.133</b> |
|           | Left Tilt     | 0.304                 | 0.228                        | 0.049                           | 0.581        |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|---------------------|------------------------------|---------------------------------|--------------|
|           | Tx Antenna    | 1                   | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.262                        | 0.063                           | <b>0.671</b> |
|           | Right Tilt    | 0.131               | 0.184                        | 0.063                           | 0.378        |
|           | Left Cheek    | 0.269               | 0.336                        | 0.042                           | 0.647        |
|           | Left Tilt     | 0.097               | 0.180                        | 0.049                           | 0.326        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                   | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.149                        | 0.063                           | 0.558        |
|           | Right Tilt    | 0.131               | 0.143                        | 0.063                           | 0.337        |
|           | Left Cheek    | 0.269               | 0.382                        | 0.042                           | <b>0.693</b> |
|           | Left Tilt     | 0.097               | 0.128                        | 0.049                           | 0.274        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                   | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.349                        | 0.063                           | 0.758        |
|           | Right Tilt    | 0.131               | 0.269                        | 0.063                           | 0.463        |
|           | Left Cheek    | 0.269               | 0.634                        | 0.042                           | <b>0.945</b> |
|           | Left Tilt     | 0.097               | 0.228                        | 0.049                           | 0.374        |

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

**Table 12-26**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 2 (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------|---------------------------------|--------------|
|           | Tx Antenna    | 1                     | 2                      | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.262                  | 0.217                           | <b>1.091</b> |
|           | Right Tilt    | 0.351                 | 0.184                  | 0.080                           | 0.615        |
|           | Left Cheek    | 0.457                 | 0.336                  | 0.046                           | 0.839        |
|           | Left Tilt     | 0.304                 | 0.180                  | 0.044                           | 0.528        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg)   | LTE Band 12 SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                      | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346                 | 0.262                  | 0.217                           | <b>0.825</b> |
|           | Right Tilt    | 0.131                 | 0.184                  | 0.080                           | 0.395        |
|           | Left Cheek    | 0.269                 | 0.336                  | 0.046                           | 0.651        |
|           | Left Tilt     | 0.097                 | 0.180                  | 0.044                           | 0.321        |

|                                          |                                                                                                                                                                                                        |                                        |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                                                                                              | <b>DUT Type:</b><br>Portable Handset   |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------------|---------------------------------|--------------|
|           | Tx Antenna    | 1                     | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.149                        | 0.217                           | <b>0.978</b> |
|           | Right Tilt    | 0.351                 | 0.143                        | 0.080                           | 0.574        |
|           | Left Cheek    | 0.457                 | 0.382                        | 0.046                           | 0.885        |
|           | Left Tilt     | 0.304                 | 0.128                        | 0.044                           | 0.476        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.349                        | 0.217                           | <b>1.178</b> |
|           | Right Tilt    | 0.351                 | 0.269                        | 0.080                           | 0.700        |
|           | Left Cheek    | 0.457                 | 0.634                        | 0.046                           | 1.137        |
|           | Left Tilt     | 0.304                 | 0.228                        | 0.044                           | 0.576        |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|---------------------|------------------------------|---------------------------------|--------------|
|           | Tx Antenna    | 1                   | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.149                        | 0.217                           | <b>0.712</b> |
|           | Right Tilt    | 0.131               | 0.143                        | 0.080                           | 0.354        |
|           | Left Cheek    | 0.269               | 0.382                        | 0.046                           | 0.697        |
|           | Left Tilt     | 0.097               | 0.128                        | 0.044                           | 0.269        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                   | 2                            | 3                               | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.349                        | 0.217                           | 0.912        |
|           | Right Tilt    | 0.131               | 0.269                        | 0.080                           | 0.480        |
|           | Left Cheek    | 0.269               | 0.634                        | 0.046                           | <b>0.949</b> |
|           | Left Tilt     | 0.097               | 0.228                        | 0.044                           | 0.369        |

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

**Table 12-27**  
**Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|-----------------------|------------------------------|----------------------------|--------------|
|           | Tx Antenna    | 1                     | 2                            | 3                          | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.262                        | 0.061                      | <b>0.935</b> |
|           | Right Tilt    | 0.351                 | 0.184                        | 0.017                      | 0.552        |
|           | Left Cheek    | 0.457                 | 0.336                        | 0.020                      | 0.813        |
|           | Left Tilt     | 0.304                 | 0.180                        | 0.014                      | 0.498        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                            | 3                          | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.149                        | 0.061                      | 0.822        |
|           | Right Tilt    | 0.351                 | 0.143                        | 0.017                      | 0.511        |
|           | Left Cheek    | 0.457                 | 0.382                        | 0.020                      | <b>0.859</b> |
|           | Left Tilt     | 0.304                 | 0.128                        | 0.014                      | 0.446        |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                     | 2                            | 3                          | 1+2+3        |
| Head SAR  | Right Cheek   | 0.612                 | 0.349                        | 0.061                      | 1.022        |
|           | Right Tilt    | 0.351                 | 0.269                        | 0.017                      | 0.637        |
|           | Left Cheek    | 0.457                 | 0.634                        | 0.020                      | <b>1.111</b> |
|           | Left Tilt     | 0.304                 | 0.228                        | 0.014                      | 0.546        |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|-----------|---------------|---------------------|------------------------------|----------------------------|--------------|
|           | Tx Antenna    | 1                   | 2                            | 3                          | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.262                        | 0.061                      | <b>0.669</b> |
|           | Right Tilt    | 0.131               | 0.184                        | 0.017                      | 0.332        |
|           | Left Cheek    | 0.269               | 0.336                        | 0.020                      | 0.625        |
|           | Left Tilt     | 0.097               | 0.180                        | 0.014                      | 0.291        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                   | 2                            | 3                          | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.149                        | 0.061                      | 0.556        |
|           | Right Tilt    | 0.131               | 0.143                        | 0.017                      | 0.291        |
|           | Left Cheek    | 0.269               | 0.382                        | 0.020                      | <b>0.671</b> |
|           | Left Tilt     | 0.097               | 0.128                        | 0.014                      | 0.239        |
| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|           | Tx Antenna    | 1                   | 2                            | 3                          | 1+2+3        |
| Head SAR  | Right Cheek   | 0.346               | 0.349                        | 0.061                      | 0.756        |
|           | Right Tilt    | 0.131               | 0.269                        | 0.017                      | 0.417        |
|           | Left Cheek    | 0.269               | 0.634                        | 0.020                      | <b>0.923</b> |
|           | Left Tilt     | 0.097               | 0.228                        | 0.014                      | 0.339        |

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 65 of 79                                                                         |                                        |

**Table 12-28**  
**Simultaneous Transmission Scenario (Body-Worn at 1.5 cm)**

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | Σ SAR (W/kg)   | Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | Σ SAR (W/kg)   |
|---------------|------------|-----------------|------------------------|----------------|---------------|------------|-----------------|-----------------------------|----------------|
| Back Side     | Cell. CDMA | < 0.775         | < 0.407                | < <b>1.182</b> | Back Side     | Cell. CDMA | < 0.775         | < 0.509                     | < <b>1.284</b> |
| Back Side     | PCS CDMA   | 0.526           | < 0.407                | < 0.933        | Back Side     | PCS CDMA   | 0.526           | < 0.509                     | < 1.035        |

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | Σ SAR (W/kg)   |
|---------------|------------|-----------------|------------------------------|----------------|
| Back Side     | Cell. CDMA | < 0.775         | < 0.216                      | < <b>0.991</b> |
| Back Side     | PCS CDMA   | 0.526           | < 0.216                      | < 0.742        |

**Table 12-29**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 1 (Body-Worn at 1.5 cm)**

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|------------------------|-----------------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                      | 3                                 | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.407                | < 0.261                           | < <b>1.443</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.407                | < 0.261                           | < 1.194        | N/A   | N/A | N/A |

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|-----------------------------|-----------------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                           | 3                                 | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.509                     | < 0.261                           | < <b>1.545</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.509                     | < 0.261                           | < 1.296        | N/A   | N/A | N/A |

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|------------------------------|-----------------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                            | 3                                 | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.216                      | < 0.261                           | < <b>1.252</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.216                      | < 0.261                           | < 1.003        | N/A   | N/A | N/A |

**Table 12-30**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 2 (Body-Worn at 1.5 cm)**

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|------------------------|-----------------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                      | 3                                 | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.407                | < 0.096                           | < <b>1.278</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.407                | < 0.096                           | < 1.029        | N/A   | N/A | N/A |

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|-----------------------------|-----------------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                           | 3                                 | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.509                     | < 0.096                           | < <b>1.380</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.509                     | < 0.096                           | < 1.131        | N/A   | N/A | N/A |

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|------------------------------|-----------------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                            | 3                                 | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.216                      | < 0.096                           | < <b>1.087</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.216                      | < 0.096                           | < 0.838        | N/A   | N/A | N/A |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 66 of 79                                                                         |                                        |

**Table 12-31**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Body-Worn at 1.5 cm)**

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|------------------------------|------------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                            | 3                            | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.407                      | < 0.068                      | < <b>1.250</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.407                      | < 0.068                      | < 1.001        | N/A   | N/A | N/A |
| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|               | Tx Antenna | 1               | 2                            | 3                            | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.509                      | < 0.068                      | < <b>1.352</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.509                      | < 0.068                      | < 1.103        | N/A   | N/A | N/A |
| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|               | Tx Antenna | 1               | 2                            | 3                            | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.216                      | < 0.068                      | < <b>1.059</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.216                      | < 0.068                      | < 0.810        | N/A   | N/A | N/A |

**Table 12-32**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 1 (Body-Worn at 1.5 cm)**

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|------------------------------|---------------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                            | 3                               | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.407                      | < 0.269                         | < <b>1.451</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.407                      | < 0.269                         | < 1.202        | N/A   | N/A | N/A |
| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|               | Tx Antenna | 1               | 2                            | 3                               | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.509                      | < 0.269                         | < <b>1.553</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.509                      | < 0.269                         | < 1.304        | N/A   | N/A | N/A |
| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|               | Tx Antenna | 1               | 2                            | 3                               | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.216                      | < 0.269                         | < <b>1.260</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.216                      | < 0.269                         | < 1.011        | N/A   | N/A | N/A |

Notes: The worst case 5 GHz WIFI reported SAR for each body-worn configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

|                                   |                                                                                                                                   |                               |  |  |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|--|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  |  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                                                                | DUT Type:<br>Portable Handset |  |  | Page 67 of 79                                                                         |                                 |



**Table 12-33**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 2 (Body-Worn at 1.5 cm)**

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR  |        |        |
|---------------|------------|-----------------|------------------------------|---------------------------------|----------------|--------|--------|--------|
|               | Tx Antenna | 1               | 2                            | 3                               | 1+2+3          | 1+2    | 1+3    | 2+3    |
| Back Side     | Cell. CDMA | < 0.775         | < 0.407                      | < 0.351                         | < <b>1.533</b> | N/A    | N/A    | N/A    |
| Back Side     | PCS CDMA   | < 0.526         | < 0.407                      | < 0.351                         | < 1.284        | N/A    | N/A    | N/A    |
| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR  |        |        |
|               | Tx Antenna | 1               | 2                            | 3                               | 1+2+3          | 1+2    | 1+3    | 2+3    |
| Back Side     | Cell. CDMA | < 0.775         | < 0.509                      | < 0.351                         | See Note 1     | < 0.02 | < 0.03 | < 0.01 |
| Back Side     | PCS CDMA   | < 0.526         | < 0.509                      | < 0.351                         | < <b>1.386</b> | N/A    | N/A    | N/A    |
| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg)   | SPLSR  |        |        |
|               | Tx Antenna | 1               | 2                            | 3                               | 1+2+3          | 1+2    | 1+3    | 2+3    |
| Back Side     | Cell. CDMA | < 0.775         | < 0.216                      | < 0.351                         | < <b>1.342</b> | N/A    | N/A    | N/A    |
| Back Side     | PCS CDMA   | < 0.526         | < 0.216                      | < 0.351                         | < 1.093        | N/A    | N/A    | N/A    |

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not higher than 0.04 per FCC KDB Publication 447498 D01v05r01. See Section 12.7 for SPLS ratio analysis.
2. The worst case 5 GHz WIFI reported SAR for each body-worn configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

**Table 12-34**  
**Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Body-Worn at 1.5 cm)**

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|---------------|------------|-----------------|------------------------------|----------------------------|----------------|-------|-----|-----|
|               | Tx Antenna | 1               | 2                            | 3                          | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.407                      | < 0.222                    | < <b>1.404</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.407                      | < 0.222                    | < 1.155        | N/A   | N/A | N/A |
| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|               | Tx Antenna | 1               | 2                            | 3                          | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.509                      | < 0.222                    | < <b>1.506</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.509                      | < 0.222                    | < 1.257        | N/A   | N/A | N/A |
| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg)   | SPLSR |     |     |
|               | Tx Antenna | 1               | 2                            | 3                          | 1+2+3          | 1+2   | 1+3 | 2+3 |
| Back Side     | Cell. CDMA | < 0.775         | < 0.216                      | < 0.222                    | < <b>1.213</b> | N/A   | N/A | N/A |
| Back Side     | PCS CDMA   | < 0.526         | < 0.216                      | < 0.222                    | < 0.964        | N/A   | N/A | N/A |

Notes: The worst case 5 GHz WIFI reported SAR for each body-worn configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 68 of 79                                                                         |                                        |

**Table 12-35**  
**Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)**

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) | Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |
|---------------|------------|-----------------|------------------------|----------------------|--------------|---------------|------------|-----------------|-----------------------------|----------------------|--------------|
|               | Tx Antenna | 1               | 2                      | 3                    | 1+2+3        |               | Tx Antenna | 1               | 2                           | 3                    | 1+2+3        |
| Back Side     | Cell. CDMA | < 0.775         | < 0.407                | 0.139                | < 1.321      | Back Side     | Cell. CDMA | < 0.775         | < 0.509                     | 0.139                | < 1.423      |
| Back Side     | PCS CDMA   | 0.526           | < 0.407                | 0.139                | < 1.072      | Back Side     | PCS CDMA   | 0.526           | < 0.509                     | 0.139                | < 1.174      |

| Configuration | Mode       | CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |
|---------------|------------|-----------------|------------------------------|----------------------|--------------|
|               | Tx Antenna | 1               | 2                            | 3                    | 1+2+3        |
| Back Side     | Cell. CDMA | < 0.775         | < 0.216                      | 0.139                | < 1.130      |
| Back Side     | PCS CDMA   | 0.526           | < 0.216                      | 0.139                | < 0.881      |

Notes: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

**Table 12-36**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 1 (Hotspot at 1.0 cm)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|-----------------------|------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                     | 2                      | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.775                 | 0.407                  | 0.261                             | 1.443        | N/A   | N/A | N/A |  |
|           | Front         | 0.689                 | 0.515                  | 0.214                             | 1.418        | N/A   | N/A | N/A |  |
|           | Top           | -                     | -                      | 0.126                             | 0.126        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.511                 | 0.345                  | -                                 | 0.856        | N/A   | N/A | N/A |  |
|           | Right         | 0.778                 | -                      | -                                 | 0.778        | N/A   | N/A | N/A |  |
|           | Left          | -                     | 0.348                  | 0.123                             | 0.471        | N/A   | N/A | N/A |  |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|-----------------------|-----------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                     | 2                           | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.775                 | 0.509                       | 0.261                             | 1.545        | N/A   | N/A | N/A |  |
|           | Front         | 0.689                 | 0.586                       | 0.214                             | 1.489        | N/A   | N/A | N/A |  |
|           | Top           | -                     | -                           | 0.126                             | 0.126        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.511                 | 0.143                       | -                                 | 0.654        | N/A   | N/A | N/A |  |
|           | Right         | 0.778                 | -                           | -                                 | 0.778        | N/A   | N/A | N/A |  |
|           | Left          | -                     | 0.183                       | 0.123                             | 0.306        | N/A   | N/A | N/A |  |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|-----------------------|------------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.775                 | 0.188                        | 0.261                             | 1.224        | N/A   | N/A | N/A |  |
|           | Front         | 0.689                 | 0.586                        | 0.214                             | 1.489        | N/A   | N/A | N/A |  |
|           | Top           | -                     | -                            | 0.126                             | 0.126        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.511                 | 0.101                        | -                                 | 0.612        | N/A   | N/A | N/A |  |
|           | Right         | 0.778                 | -                            | -                                 | 0.778        | N/A   | N/A | N/A |  |
|           | Left          | -                     | 0.255                        | 0.123                             | 0.378        | N/A   | N/A | N/A |  |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|---------------------|------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                   | 2                      | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.563               | 0.407                  | 0.261                             | 1.231        | N/A   | N/A | N/A |  |
|           | Front         | 0.451               | 0.515                  | 0.214                             | 1.180        | N/A   | N/A | N/A |  |
|           | Top           | -                   | -                      | 0.126                             | 0.126        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.433               | 0.345                  | -                                 | 0.778        | N/A   | N/A | N/A |  |
|           | Right         | 0.354               | -                      | -                                 | 0.354        | N/A   | N/A | N/A |  |
|           | Left          | -                   | 0.348                  | 0.123                             | 0.471        | N/A   | N/A | N/A |  |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|---------------------|-----------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                   | 2                           | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.563               | 0.509                       | 0.261                             | 1.333        | N/A   | N/A | N/A |  |
|           | Front         | 0.451               | 0.586                       | 0.214                             | 1.251        | N/A   | N/A | N/A |  |
|           | Top           | -                   | -                           | 0.126                             | 0.126        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.433               | 0.143                       | -                                 | 0.576        | N/A   | N/A | N/A |  |
|           | Right         | 0.354               | -                           | -                                 | 0.354        | N/A   | N/A | N/A |  |
|           | Left          | -                   | 0.183                       | 0.123                             | 0.306        | N/A   | N/A | N/A |  |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|---------------------|------------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                   | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.563               | 0.188                        | 0.261                             | 1.012        | N/A   | N/A | N/A |  |
|           | Front         | 0.451               | 0.586                        | 0.214                             | 1.251        | N/A   | N/A | N/A |  |
|           | Top           | -                   | -                            | 0.126                             | 0.126        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.433               | 0.101                        | -                                 | 0.534        | N/A   | N/A | N/A |  |
|           | Right         | 0.354               | -                            | -                                 | 0.354        | N/A   | N/A | N/A |  |
|           | Left          | -                   | 0.255                        | 0.123                             | 0.378        | N/A   | N/A | N/A |  |

**Table 12-37**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 2 (Hotspot at 1.0 cm)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|-----------------------|------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                     | 2                      | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.775                 | 0.407                  | 0.096                             | 1.278        | N/A   | N/A | N/A |  |
|           | Front         | 0.689                 | 0.515                  | 0.059                             | 1.263        | N/A   | N/A | N/A |  |
|           | Top           | -                     | -                      | 0.024                             | 0.024        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.511                 | 0.345                  | -                                 | 0.856        | N/A   | N/A | N/A |  |
|           | Right         | 0.778                 | -                      | -                                 | 0.778        | N/A   | N/A | N/A |  |
|           | Left          | -                     | 0.348                  | 0.085                             | 0.433        | N/A   | N/A | N/A |  |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|-----------------------|-----------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                     | 2                           | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.775                 | 0.509                       | 0.096                             | 1.380        | N/A   | N/A | N/A |  |
|           | Front         | 0.689                 | 0.586                       | 0.059                             | 1.334        | N/A   | N/A | N/A |  |
|           | Top           | -                     | -                           | 0.024                             | 0.024        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.511                 | 0.143                       | -                                 | 0.654        | N/A   | N/A | N/A |  |
|           | Right         | 0.778                 | -                           | -                                 | 0.778        | N/A   | N/A | N/A |  |
|           | Left          | -                     | 0.183                       | 0.085                             | 0.268        | N/A   | N/A | N/A |  |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|---------------------|------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                   | 2                      | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.563               | 0.407                  | 0.096                             | 1.066        | N/A   | N/A | N/A |  |
|           | Front         | 0.451               | 0.515                  | 0.059                             | 1.025        | N/A   | N/A | N/A |  |
|           | Top           | -                   | -                      | 0.024                             | 0.024        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.433               | 0.345                  | -                                 | 0.778        | N/A   | N/A | N/A |  |
|           | Right         | 0.354               | -                      | -                                 | 0.354        | N/A   | N/A | N/A |  |
|           | Left          | -                   | 0.348                  | 0.085                             | 0.433        | N/A   | N/A | N/A |  |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|---------------------|-----------------------------|-----------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                   | 2                           | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.563               | 0.509                       | 0.096                             | 1.168        | N/A   | N/A | N/A |  |
|           | Front         | 0.451               | 0.586                       | 0.059                             | 1.096        | N/A   | N/A | N/A |  |
|           | Top           | -                   | -                           | 0.024                             | 0.024        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.433               | 0.143                       | -                                 | 0.576        | N/A   | N/A | N/A |  |
|           | Right         | 0.354               | -                           | -                                 | 0.354        | N/A   | N/A | N/A |  |
|           | Left          | -                   | 0.183                       | 0.085                             | 0.268        | N/A   | N/A | N/A |  |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 69 of 79                                                                         |                                 |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|-----------------------|------------------------------|-----------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.775                 | 0.188                        | 0.096                             | 1.059        | N/A   | N/A | N/A |
|           | Front         | 0.689                 | 0.566                        | 0.059                             | 1.314        | N/A   | N/A | N/A |
|           | Top           | -                     | -                            | 0.024                             | 0.024        | N/A   | N/A | N/A |
|           | Bottom        | 0.511                 | 0.101                        | -                                 | 0.612        | N/A   | N/A | N/A |
|           | Right         | 0.778                 | -                            | -                                 | 0.778        | N/A   | N/A | N/A |
|           | Left          | -                     | 0.255                        | 0.085                             | 0.340        | N/A   | N/A | N/A |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|---------------------|------------------------------|-----------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                   | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.563               | 0.188                        | 0.096                             | 0.847        | N/A   | N/A | N/A |
|           | Front         | 0.451               | 0.566                        | 0.059                             | 1.076        | N/A   | N/A | N/A |
|           | Top           | -                   | -                            | 0.024                             | 0.024        | N/A   | N/A | N/A |
|           | Bottom        | 0.433               | 0.101                        | -                                 | 0.534        | N/A   | N/A | N/A |
|           | Right         | 0.354               | -                            | -                                 | 0.354        | N/A   | N/A | N/A |
|           | Left          | -                   | 0.255                        | 0.085                             | 0.340        | N/A   | N/A | N/A |

**Table 12-38**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Hotspot at 1.0 cm)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|-----------------------|------------------------|------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                     | 2                      | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.775                 | 0.407                  | 0.068                        | 1.250        | N/A   | N/A | N/A |
|           | Front         | 0.689                 | 0.515                  | 0.058                        | 1.262        | N/A   | N/A | N/A |
|           | Top           | -                     | -                      | 0.038                        | 0.038        | N/A   | N/A | N/A |
|           | Bottom        | 0.511                 | 0.345                  | -                            | 0.856        | N/A   | N/A | N/A |
|           | Right         | 0.778                 | -                      | -                            | 0.778        | N/A   | N/A | N/A |
|           | Left          | -                     | 0.348                  | 0.030                        | 0.378        | N/A   | N/A | N/A |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|---------------------|------------------------|------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                   | 2                      | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.563               | 0.407                  | 0.068                        | 1.038        | N/A   | N/A | N/A |
|           | Front         | 0.451               | 0.515                  | 0.058                        | 1.024        | N/A   | N/A | N/A |
|           | Top           | -                   | -                      | 0.038                        | 0.038        | N/A   | N/A | N/A |
|           | Bottom        | 0.433               | 0.345                  | -                            | 0.778        | N/A   | N/A | N/A |
|           | Right         | 0.354               | -                      | -                            | 0.354        | N/A   | N/A | N/A |
|           | Left          | -                   | 0.348                  | 0.030                        | 0.378        | N/A   | N/A | N/A |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|-----------------------|-----------------------------|------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                     | 2                           | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.775                 | 0.509                       | 0.068                        | 1.352        | N/A   | N/A | N/A |
|           | Front         | 0.689                 | 0.586                       | 0.058                        | 1.333        | N/A   | N/A | N/A |
|           | Top           | -                     | -                           | 0.038                        | 0.038        | N/A   | N/A | N/A |
|           | Bottom        | 0.511                 | 0.143                       | -                            | 0.654        | N/A   | N/A | N/A |
|           | Right         | 0.778                 | -                           | -                            | 0.778        | N/A   | N/A | N/A |
|           | Left          | -                     | 0.183                       | 0.030                        | 0.213        | N/A   | N/A | N/A |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|---------------------|-----------------------------|------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                   | 2                           | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.563               | 0.509                       | 0.068                        | 1.140        | N/A   | N/A | N/A |
|           | Front         | 0.451               | 0.586                       | 0.058                        | 1.095        | N/A   | N/A | N/A |
|           | Top           | -                   | -                           | 0.038                        | 0.038        | N/A   | N/A | N/A |
|           | Bottom        | 0.433               | 0.143                       | -                            | 0.576        | N/A   | N/A | N/A |
|           | Right         | 0.354               | -                           | -                            | 0.354        | N/A   | N/A | N/A |
|           | Left          | -                   | 0.183                       | 0.030                        | 0.213        | N/A   | N/A | N/A |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|-----------------------|------------------------------|------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                     | 2                            | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.775                 | 0.188                        | 0.068                        | 1.031        | N/A   | N/A | N/A |
|           | Front         | 0.689                 | 0.566                        | 0.058                        | 1.313        | N/A   | N/A | N/A |
|           | Top           | -                     | -                            | 0.038                        | 0.038        | N/A   | N/A | N/A |
|           | Bottom        | 0.511                 | 0.101                        | -                            | 0.612        | N/A   | N/A | N/A |
|           | Right         | 0.778                 | -                            | -                            | 0.778        | N/A   | N/A | N/A |
|           | Left          | -                     | 0.255                        | 0.030                        | 0.285        | N/A   | N/A | N/A |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|---------------------|------------------------------|------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                   | 2                            | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.563               | 0.188                        | 0.068                        | 0.819        | N/A   | N/A | N/A |
|           | Front         | 0.451               | 0.566                        | 0.058                        | 1.075        | N/A   | N/A | N/A |
|           | Top           | -                   | -                            | 0.038                        | 0.038        | N/A   | N/A | N/A |
|           | Bottom        | 0.433               | 0.101                        | -                            | 0.534        | N/A   | N/A | N/A |
|           | Right         | 0.354               | -                            | -                            | 0.354        | N/A   | N/A | N/A |
|           | Left          | -                   | 0.255                        | 0.030                        | 0.285        | N/A   | N/A | N/A |

**Table 12-39**  
**Simultaneous Transmission Scenario (5.8 GHz Hotspot Antenna 1 at 1.0 cm)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|-----------------------|------------------------|-----------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                     | 2                      | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.775                 | 0.407                  | 0.162                             | 1.344        | N/A   | N/A | N/A |
|           | Front         | 0.689                 | 0.515                  | 0.104                             | 1.308        | N/A   | N/A | N/A |
|           | Top           | -                     | -                      | 0.305                             | 0.305        | N/A   | N/A | N/A |
|           | Bottom        | 0.511                 | 0.345                  | -                                 | 0.856        | N/A   | N/A | N/A |
|           | Right         | 0.778                 | -                      | -                                 | 0.778        | N/A   | N/A | N/A |
|           | Left          | -                     | 0.348                  | 0.029                             | 0.377        | N/A   | N/A | N/A |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg) | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|---------------------|------------------------|-----------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                   | 2                      | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.563               | 0.407                  | 0.162                             | 1.132        | N/A   | N/A | N/A |
|           | Front         | 0.451               | 0.515                  | 0.104                             | 1.070        | N/A   | N/A | N/A |
|           | Top           | -                   | -                      | 0.305                             | 0.305        | N/A   | N/A | N/A |
|           | Bottom        | 0.433               | 0.345                  | -                                 | 0.778        | N/A   | N/A | N/A |
|           | Right         | 0.354               | -                      | -                                 | 0.354        | N/A   | N/A | N/A |
|           | Left          | -                   | 0.348                  | 0.029                             | 0.377        | N/A   | N/A | N/A |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg) | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|-----------------------|-----------------------------|-----------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                     | 2                           | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.775                 | 0.509                       | 0.162                             | 1.446        | N/A   | N/A | N/A |
|           | Front         | 0.689                 | 0.586                       | 0.104                             | 1.379        | N/A   | N/A | N/A |
|           | Top           | -                     | -                           | 0.305                             | 0.305        | N/A   | N/A | N/A |
|           | Bottom        | 0.511                 | 0.143                       | -                                 | 0.654        | N/A   | N/A | N/A |
|           | Right         | 0.778                 | -                           | -                                 | 0.778        | N/A   | N/A | N/A |
|           | Left          | -                     | 0.183                       | 0.029                             | 0.212        | N/A   | N/A | N/A |

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|-----------------------|------------------------------|-----------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.775                 | 0.188                        | 0.162                             | 1.125        | N/A   | N/A | N/A |
|           | Front         | 0.689                 | 0.566                        | 0.104                             | 1.359        | N/A   | N/A | N/A |
|           | Top           | -                     | -                            | 0.305                             | 0.305        | N/A   | N/A | N/A |
|           | Bottom        | 0.511                 | 0.101                        | -                                 | 0.612        | N/A   | N/A | N/A |
|           | Right         | 0.778                 | -                            | -                                 | 0.778        | N/A   | N/A | N/A |
|           | Left          | -                     | 0.255                        | 0.029                             | 0.284        | N/A   | N/A | N/A |

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5.8 GHz WLAN Antenna 1 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |
|-----------|---------------|---------------------|------------------------------|-----------------------------------|--------------|-------|-----|-----|
|           | Tx Antenna    | 1                   | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3 | 2+3 |
| Body SAR  | Back          | 0.563               | 0.188                        | 0.162                             | 0.913        | N/A   | N/A | N/A |
|           | Front         | 0.451               | 0.566                        | 0.104                             | 1.121        | N/A   | N/A | N/A |
|           | Top           | -                   | -                            | 0.305                             | 0.305        | N/A   | N/A | N/A |
|           | Bottom        | 0.433               | 0.101                        | -                                 | 0.534        | N/A   | N/A | N/A |
|           | Right         | 0.354               | -                            | -                                 | 0.354        | N/A   | N/A | N/A |
|           | Left          | -                   | 0.255                        | 0.029                             | 0.284        | N/A   | N/A | N/A |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 70 of 79                     |                                                                                                                                                                                                        |                                 |

**Table 12-40**  
**Simultaneous Transmission Scenario (5.8 GHz Hotspot Antenna 2 at 1.0 cm)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5.8 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |      |      |  |
|-----------|---------------|-----------------------|------------------------------|-----------------------------------|--------------|-------|------|------|--|
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3  | 2+3  |  |
| Body SAR  | Back          | 0.775                 | 0.407                        | 0.327                             | 1.509        | N/A   | N/A  | N/A  |  |
|           | Front         | 0.689                 | 0.515                        | 0.089                             | 1.293        | N/A   | N/A  | N/A  |  |
|           | Top           | -                     | -                            | 0.075                             | 0.075        | N/A   | N/A  | N/A  |  |
|           | Bottom        | 0.511                 | 0.345                        | -                                 | 0.856        | N/A   | N/A  | N/A  |  |
|           | Right         | 0.778                 | -                            | -                                 | 0.778        | N/A   | N/A  | N/A  |  |
|           | Left          | -                     | 0.348                        | 0.197                             | 0.545        | N/A   | N/A  | N/A  |  |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5.8 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |      |      |  |
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3  | 2+3  |  |
| Body SAR  | Back          | 0.775                 | 0.509                        | 0.327                             | See note 1   | 0.02  | 0.03 | 0.01 |  |
|           | Front         | 0.689                 | 0.586                        | 0.089                             | 1.364        | N/A   | N/A  | N/A  |  |
|           | Top           | -                     | -                            | 0.075                             | 0.075        | N/A   | N/A  | N/A  |  |
|           | Bottom        | 0.511                 | 0.143                        | -                                 | 0.654        | N/A   | N/A  | N/A  |  |
|           | Right         | 0.778                 | -                            | -                                 | 0.778        | N/A   | N/A  | N/A  |  |
|           | Left          | -                     | 0.183                        | 0.197                             | 0.380        | N/A   | N/A  | N/A  |  |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5.8 GHz WLAN Antenna 2 SAR (W/kg) | Σ SAR (W/kg) | SPLSR |      |      |  |
|           | Tx Antenna    | 1                     | 2                            | 3                                 | 1+2+3        | 1+2   | 1+3  | 2+3  |  |
| Body SAR  | Back          | 0.775                 | 0.188                        | 0.327                             | 1.290        | N/A   | N/A  | N/A  |  |
|           | Front         | 0.689                 | 0.566                        | 0.089                             | 1.344        | N/A   | N/A  | N/A  |  |
|           | Top           | -                     | -                            | 0.075                             | 0.075        | N/A   | N/A  | N/A  |  |
|           | Bottom        | 0.511                 | 0.101                        | -                                 | 0.612        | N/A   | N/A  | N/A  |  |
|           | Right         | 0.778                 | -                            | -                                 | 0.778        | N/A   | N/A  | N/A  |  |
|           | Left          | -                     | 0.255                        | 0.197                             | 0.452        | N/A   | N/A  | N/A  |  |

**Table 12-41**  
**Simultaneous Transmission Scenario (5.8 GHz Hotspot MIMO at 1.0 cm)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 12 SAR (W/kg)       | 5.8 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|-----------|---------------|-----------------------|------------------------------|------------------------------|--------------|-------|-----|-----|--|
|           | Tx Antenna    | 1                     | 2                            | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.775                 | 0.407                        | 0.222                        | 1.404        | N/A   | N/A | N/A |  |
|           | Front         | 0.689                 | 0.515                        | 0.032                        | 1.236        | N/A   | N/A | N/A |  |
|           | Top           | -                     | -                            | 0.098                        | 0.098        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.511                 | 0.345                        | -                            | 0.856        | N/A   | N/A | N/A |  |
|           | Right         | 0.778                 | -                            | -                            | 0.778        | N/A   | N/A | N/A |  |
|           | Left          | -                     | 0.348                        | 0.060                        | 0.408        | N/A   | N/A | N/A |  |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 4 (AWS) SAR (W/kg)  | 5.8 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|           | Tx Antenna    | 1                     | 2                            | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.775                 | 0.509                        | 0.222                        | 1.506        | N/A   | N/A | N/A |  |
|           | Front         | 0.689                 | 0.586                        | 0.032                        | 1.307        | N/A   | N/A | N/A |  |
|           | Top           | -                     | -                            | 0.098                        | 0.098        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.511                 | 0.143                        | -                            | 0.654        | N/A   | N/A | N/A |  |
|           | Right         | 0.778                 | -                            | -                            | 0.778        | N/A   | N/A | N/A |  |
|           | Left          | -                     | 0.183                        | 0.060                        | 0.243        | N/A   | N/A | N/A |  |
| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | LTE Band 25 (PCS) SAR (W/kg) | 5.8 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) | SPLSR |     |     |  |
|           | Tx Antenna    | 1                     | 2                            | 3                            | 1+2+3        | 1+2   | 1+3 | 2+3 |  |
| Body SAR  | Back          | 0.775                 | 0.188                        | 0.222                        | 1.185        | N/A   | N/A | N/A |  |
|           | Front         | 0.689                 | 0.566                        | 0.032                        | 1.287        | N/A   | N/A | N/A |  |
|           | Top           | -                     | -                            | 0.098                        | 0.098        | N/A   | N/A | N/A |  |
|           | Bottom        | 0.511                 | 0.101                        | -                            | 0.612        | N/A   | N/A | N/A |  |
|           | Right         | 0.778                 | -                            | -                            | 0.778        | N/A   | N/A | N/A |  |
|           | Left          | -                     | 0.255                        | 0.060                        | 0.315        | N/A   | N/A | N/A |  |

## 12.7 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v05, when the sum of the standalone transmitters is more than 1.6 W/kg, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is  $\leq 0.04$ , simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

$$\text{SPLS Ratio} = \frac{(\text{SAR}_1 + \text{SAR}_2)^{1.5}}{R_i}$$

|                                   |                                                                                     |                               |                                                                                       |                                        |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>  |  | <b>Reviewed by:</b><br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset | Page 71 of 79                                                                         |                                        |

The sum of the standalone SAR values was above 1.6 W/kg for the hotspot back side configuration at a separation distance of 10 mm for Cell. CDMA and LTE Band 4 operating with 5 GHz WIFI Antenna 2.

Note: Since the standalone SAR values below were measured at a separation distance of 10 mm, then they are more conservative than the body-worn back side configuration SAR values at 15 mm for Cell. CDMA and LTE Band 4 operating with 5 GHz WIFI Antenna 2. Therefore, the SPLSR analysis below is more conservative. "<" in Table 12-33 denotes that the 10 mm SAR values were used for the respective modes for SPLSR analysis.




**Figure 12-1**  
**Peak SAR Location Plot of Cell. CDMA, LTE Band 4, and 5 GHz WLAN Antenna 2**

**Table 12-42**  
**Peak SAR Locations for Body Back Side at 1.5 cm Cell. CDMA, LTE Band 4, and 5 GHz WLAN Antenna 2**

| Mode/Band            | x (mm) | y (mm) |
|----------------------|--------|--------|
| Cell. CDMA           | -18.50 | 1.52   |
| LTE Band 4           | -6.52  | -55.50 |
| 5 GHz WLAN Antenna 2 | 13.00  | 37.00  |

**Table 12-43**  
**SAR Sum to Peak Location Separation Ratio Calculation**

| Antenna Pair         |                      | Standalone 1g SAR (W/kg) |       | Standalone SAR Sum (W/kg) | Peak SAR Separation Distance (mm) | SPLS Ratio            |
|----------------------|----------------------|--------------------------|-------|---------------------------|-----------------------------------|-----------------------|
| Ant "a"              | Ant "b"              | a                        | b     | a+b                       | $D_{a-b}$                         | $(a+b)^{1.5}/D_{a-b}$ |
| Cell. CDMA           | LTE Band 4           | 0.775                    | 0.509 | 1.284                     | 58.26                             | 0.02                  |
| LTE Band 4           | 5 GHz WLAN Antenna 2 | 0.509                    | 0.351 | 0.86                      | 94.54                             | 0.01                  |
| 5 GHz WLAN Antenna 2 | Cell. CDMA           | 0.351                    | 0.775 | 1.126                     | 47.45                             | 0.03                  |

## 12.8 Simultaneous Transmission Conclusion

The above numerical summed SAR and SPLSR analysis results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

|                                          |                                                                                     |                                      |                                                                                       |                                        |
|------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                           | <b>DUT Type:</b><br>Portable Handset | Page 72 of 79                                                                         |                                        |

## 13 SAR MEASUREMENT VARIABILITY

### 13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability is assessed when measured SAR is  $> 0.80$  W/kg. Since highest measured SAR for this device was  $< 0.80$  W/kg, measurement variability was not assessed.

### 13.2 Measurement Uncertainty

The measured SAR was  $< 1.5$  W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 73 of 79                                                                         |                                        |



# 14 EQUIPMENT LIST

| Manufacturer       | Model           | Description                                   | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|--------------------|-----------------|-----------------------------------------------|------------|--------------|------------|---------------|
| SPEAG              | ES3DV3          | SAR Probe                                     | 9/23/2013  | Annual       | 9/23/2014  | 3288          |
| SPEAG              | ES3DV3          | SAR Probe                                     | 4/29/2013  | Annual       | 4/29/2014  | 3318          |
| SPEAG              | ES3DV3          | SAR Probe                                     | 5/16/2013  | Annual       | 5/16/2014  | 3263          |
| SPEAG              | ES3DV3          | SAR Probe                                     | 11/20/2013 | Annual       | 11/20/2014 | 3287          |
| SPEAG              | EX3DV4          | SAR Probe                                     | 12/18/2013 | Annual       | 12/18/2014 | 3920          |
| SPEAG              | ES3DV3          | SAR Probe                                     | 4/29/2013  | Annual       | 4/29/2014  | 3319          |
| SPEAG              | ES3DV2          | SAR Probe                                     | 8/22/2013  | Annual       | 8/22/2014  | 3022          |
| SPEAG              | EX3DV4          | SAR Probe                                     | 10/23/2013 | Annual       | 10/23/2014 | 3914          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 9/17/2013  | Annual       | 9/17/2014  | 1323          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 4/22/2013  | Annual       | 4/22/2014  | 1364          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 5/13/2013  | Annual       | 5/13/2014  | 859           |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 11/19/2013 | Annual       | 11/19/2014 | 1408          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 12/12/2013 | Annual       | 12/12/2014 | 649           |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 4/22/2013  | Annual       | 4/22/2014  | 1368          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 8/21/2014  | Annual       | 8/21/2014  | 1322          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 11/19/2013 | Annual       | 11/19/2014 | 1333          |
| SPEAG              | D750V3          | 750 MHz Dipole                                | 3/18/2013  | Annual       | 3/18/2014  | 1054          |
| SPEAG              | D835V2          | 835 MHz SAR Dipole                            | 4/25/2013  | Annual       | 4/25/2014  | 4d119         |
| SPEAG              | D1765V2         | 1765 MHz SAR Dipole                           | 5/14/2013  | Annual       | 5/14/2014  | 1008          |
| SPEAG              | D1900V2         | 1900 MHz SAR Dipole                           | 5/2/2013   | Annual       | 5/2/2014   | 5d141         |
| SPEAG              | D2450V2         | 2450 MHz SAR Dipole                           | 8/23/2013  | Annual       | 8/23/2014  | 719           |
| SPEAG              | D5GHZV2         | 5 GHz SAR Dipole                              | 9/23/2013  | Annual       | 9/23/2014  | 1007          |
| SPEAG              | D835V2          | 835 MHz SAR Dipole                            | 7/17/2013  | Annual       | 7/17/2014  | 4d133         |
| SPEAG              | D1900V2         | 1900 MHz SAR Dipole                           | 7/22/2013  | Annual       | 7/22/2014  | 5d149         |
| SPEAG              | DAK-3.5         | Dielectric Assessment Kit                     | 11/13/2013 | Annual       | 11/13/2014 | 1091          |
| SPEAG              | D5GHZV2         | 5 GHz SAR Dipole                              | 2/14/2013  | Annual       | 2/14/2014  | 1120          |
| SPEAG              | DAKS-3.5        | Portable Dielectric Assessment Kit            | 8/18/2013  | Annual       | 8/18/2014  | 1008          |
| Agilent            | E5515C          | Wireless Communications Test Set              | 5/9/2013   | Biennial     | 5/9/2015   | GB43304447    |
| Agilent            | 8648D           | (9kHz-4GHz) Signal Generator                  | 4/17/2013  | Annual       | 4/17/2014  | 3629U00687    |
| Agilent            | 85047A          | S-Parameter Test Set                          | N/A        | N/A          | N/A        | 2904A00579    |
| Agilent            | 8753E           | (30kHz-6GHz) Network Analyzer                 | 7/23/2013  | Annual       | 7/23/2014  | US37390350    |
| Agilent            | N5182A          | MXG Vector Signal Generator                   | 10/28/2013 | Annual       | 10/28/2014 | US46240505    |
| Agilent            | 8753ES          | S-Parameter Network Analyzer                  | 10/29/2013 | Annual       | 10/29/2014 | US39170122    |
| Agilent            | E5515C          | Wireless Communications Test Set              | 10/18/2012 | Biennial     | 10/18/2014 | GB43193563    |
| Agilent            | 8753E           | (30kHz-6GHz) Network Analyzer                 | 4/16/2013  | Annual       | 4/16/2014  | JP38020182    |
| Agilent            | E8257D          | (250kHz-20GHz) Signal Generator               | 4/16/2013  | Annual       | 4/16/2014  | MY45470194    |
| Agilent            | 8594A           | (9kHz-2.9GHz) Spectrum Analyzer               | N/A        | N/A          | N/A        | 3051A00187    |
| Agilent            | N9020A          | MXA Signal Analyzer                           | 10/29/2013 | Annual       | 10/29/2014 | US46470561    |
| Amplifier Research | 551G4           | 5W, 800MHz-4.2GHz                             | CBT        | N/A          | CBT        | 21910         |
| Anritsu            | MA2481A         | Power Sensor                                  | 10/30/2013 | Annual       | 10/30/2014 | 5605          |
| Anritsu            | MA24106A        | USB Power Sensor                              | 1/3/2014   | Annual       | 1/3/2015   | 1344554       |
| Anritsu            | MA24106A        | USB Power Sensor                              | 1/3/2014   | Annual       | 1/3/2015   | 1344557       |
| Anritsu            | MT8820C         | Radio Communication Analyzer                  | 12/12/2013 | Annual       | 12/12/2014 | 6200901190    |
| Anritsu            | ML2495A         | Power Meter                                   | 10/31/2013 | Annual       | 10/31/2014 | 1039008       |
| Anritsu            | MA24106A        | USB Power Sensor                              | 1/3/2014   | Annual       | 1/3/2015   | 1349501       |
| Anritsu            | MA24106A        | USB Power Sensor                              | 1/3/2014   | Annual       | 1/3/2015   | 1349503       |
| Anritsu            | MT8820C         | Radio Communication Analyzer                  | 12/12/2013 | Annual       | 12/12/2014 | 6201300731    |
| Anritsu            | MT8820C         | Radio Communication Analyzer                  | 6/28/2013  | Annual       | 6/28/2014  | 6201240328    |
| Anritsu            | MA2411B         | Pulse Power Sensor                            | 11/14/2013 | Annual       | 11/14/2014 | 1126066       |
| COMTECH            | AR85729-5/5759B | Solid State Amplifier                         | CBT        | N/A          | CBT        | M3W1A00-1002  |
| Gigatronics        | 8651A           | Universal Power Meter                         | 10/30/2013 | Annual       | 10/30/2014 | 8650319       |
| Gigatronics        | 80701A          | (0.05-18GHz) Power Sensor                     | 10/30/2013 | Annual       | 10/30/2014 | 1833460       |
| MCL                | BW-N6W5+        | 6dB Attenuator                                | CBT        | N/A          | CBT        | 1139          |
| MiniCircuits       | VLF-6000+       | Low Pass Filter                               | CBT        | N/A          | CBT        | N/A           |
| MiniCircuits       | VLF-6000+       | Low Pass Filter                               | CBT        | N/A          | CBT        | N/A           |
| MiniCircuits       | SLP-2400+       | Low Pass Filter                               | CBT        | N/A          | CBT        | R8979500903   |
| Mini-Circuits      | NLP-2950+       | Low Pass Filter DC to 2700 MHz                | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | NLP-1200+       | Low Pass Filter DC to 1000 MHz                | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | BW-N20W5        | Power Attenuator                              | CBT        | N/A          | CBT        | 1226          |
| Mini-Circuits      | BW-N20W5+       | DC to 18 GHz Precision Fixed 20 dB Attenuator | CBT        | N/A          | CBT        | N/A           |
| Narda              | BW-S3W2         | Attenuator (3dB)                              | CBT        | N/A          | CBT        | 120           |
| Narda              | 4772-3          | Attenuator (3dB)                              | CBT        | N/A          | CBT        | 9406          |
| Narda              | 4014C-6         | 4 - 8 GHz SMA 6 dB Directional Coupler        | CBT        | N/A          | CBT        | N/A           |
| Pasternack         | PE2209-10       | Bidirectional Coupler                         | CBT        | N/A          | CBT        | N/A           |
| Pasternack         | PE2208-6        | Bidirectional Coupler                         | CBT        | N/A          | CBT        | N/A           |
| Rohde & Schwarz    | SME06           | Signal Generator                              | 10/30/2013 | Annual       | 10/30/2014 | 832026        |
| Rohde & Schwarz    | CMW500          | LTE Radio Communication Tester                | 10/4/2013  | Annual       | 10/4/2014  | 108798        |
| Rohde & Schwarz    | SMI030B         | Signal Generator                              | 4/17/2013  | Annual       | 4/17/2014  | DE27259       |
| Rohde & Schwarz    | CMW500          | LTE Radio Communication Tester                | 8/5/2011   | Annual       | 8/5/2012   | 112347        |
| Rohde & Schwarz    | NRVD            | Dual Channel Power Meter                      | 10/12/2012 | Biennial     | 10/12/2014 | 101695        |
| Rohde & Schwarz    | NRV-232         | Peak Power Sensor                             | 10/12/2012 | Biennial     | 10/12/2014 | 836019/013    |
| Rohde & Schwarz    | NRVS            | Single Channel Power Meter                    | 10/31/2013 | Annual       | 10/31/2014 | 835360/0079   |
| Seekonk            | NC-100          | Torque Wrench (8" lb)                         | 11/29/2011 | Triennial    | 11/29/2014 | 21053         |
| Seekonk            | NC-100          | Torque Wrench (8" lb)                         | 3/5/2012   | Triennial    | 3/5/2015   | N/A           |
| Seekonk            | NC-100          | Torque Wrench (8" lb)                         | 3/5/2012   | Triennial    | 3/5/2015   | N/A           |
| SPEAG              | DAK-3.5         | Dielectric Assessment Kit                     | 5/14/2013  | Annual       | 5/14/2014  | 1070          |
| Tektronix          | RSA6114A        | Real Time Spectrum Analyzer                   | 4/17/2013  | Annual       | 4/17/2014  | B010177       |
| VWR                | 23226-658       | Long Stem Thermometer                         | 6/27/2012  | Biennial     | 6/27/2014  | 122363923     |
| VWR                | 23226-658       | Long Stem Thermometer                         | 7/11/2012  | Biennial     | 7/11/2014  | 122389334     |
| VWR                | 36934-158       | Wall-Mounted Thermometer                      | 8/8/2013   | Annual       | 8/8/2014   | 130258636     |
| VWR                | 36934-158       | Wall-Mounted Thermometer                      | 8/8/2013   | Annual       | 8/8/2014   | 130477877     |

Note:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment was used solely within its valid calibration period.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7               |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1403190578.A3L | Test Dates:<br>02/03/14 - 03/31/14                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 74 of 79                   |



## 15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

| a                                                                                | b                    | c             | d              | e=<br>f(d,k) | f                     | g                        | h =<br>c x f/e                 | i =<br>c x g/e                   | k              |
|----------------------------------------------------------------------------------|----------------------|---------------|----------------|--------------|-----------------------|--------------------------|--------------------------------|----------------------------------|----------------|
| Uncertainty<br>Component                                                         | IEEE<br>1528<br>Sec. | Tol.<br>(± %) | Prob.<br>Dist. | Div.         | c <sub>i</sub><br>1gm | c <sub>i</sub><br>10 gms | 1gm<br>u <sub>i</sub><br>(± %) | 10gms<br>u <sub>i</sub><br>(± %) | v <sub>i</sub> |
| <b>Measurement System</b>                                                        |                      |               |                |              |                       |                          |                                |                                  |                |
| Probe Calibration                                                                | E.2.1                | 6.0           | N              | 1            | 1.0                   | 1.0                      | 6.0                            | 6.0                              | ∞              |
| Axial Isotropy                                                                   | E.2.2                | 0.25          | N              | 1            | 0.7                   | 0.7                      | 0.2                            | 0.2                              | ∞              |
| Hemishperical Isotropy                                                           | E.2.2                | 1.3           | N              | 1            | 1.0                   | 1.0                      | 1.3                            | 1.3                              | ∞              |
| Boundary Effect                                                                  | E.2.3                | 0.4           | N              | 1            | 1.0                   | 1.0                      | 0.4                            | 0.4                              | ∞              |
| Linearity                                                                        | E.2.4                | 0.3           | N              | 1            | 1.0                   | 1.0                      | 0.3                            | 0.3                              | ∞              |
| System Detection Limits                                                          | E.2.5                | 5.1           | N              | 1            | 1.0                   | 1.0                      | 5.1                            | 5.1                              | ∞              |
| Readout Electronics                                                              | E.2.6                | 1.0           | N              | 1            | 1.0                   | 1.0                      | 1.0                            | 1.0                              | ∞              |
| Response Time                                                                    | E.2.7                | 0.8           | R              | 1.73         | 1.0                   | 1.0                      | 0.5                            | 0.5                              | ∞              |
| Integration Time                                                                 | E.2.8                | 2.6           | R              | 1.73         | 1.0                   | 1.0                      | 1.5                            | 1.5                              | ∞              |
| RF Ambient Conditions                                                            | E.6.1                | 3.0           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Probe Positioner Mechanical Tolerance                                            | E.6.2                | 0.4           | R              | 1.73         | 1.0                   | 1.0                      | 0.2                            | 0.2                              | ∞              |
| Probe Positioning w/ respect to Phantom                                          | E.6.3                | 2.9           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Extrapolation, Interpolation & Integration algorithms for<br>Max. SAR Evaluation | E.5                  | 1.0           | R              | 1.73         | 1.0                   | 1.0                      | 0.6                            | 0.6                              | ∞              |
| <b>Test Sample Related</b>                                                       |                      |               |                |              |                       |                          |                                |                                  |                |
| Test Sample Positioning                                                          | E.4.2                | 6.0           | N              | 1            | 1.0                   | 1.0                      | 6.0                            | 6.0                              | 287            |
| Device Holder Uncertainty                                                        | E.4.1                | 3.32          | R              | 1.73         | 1.0                   | 1.0                      | 1.9                            | 1.9                              | ∞              |
| Output Power Variation - SAR drift measurement                                   | 6.6.2                | 5.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.9                            | 2.9                              | ∞              |
| <b>Phantom &amp; Tissue Parameters</b>                                           |                      |               |                |              |                       |                          |                                |                                  |                |
| Phantom Uncertainty (Shape & Thickness tolerances)                               | E.3.1                | 4.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.3                            | 2.3                              | ∞              |
| Liquid Conductivity - deviation from target values                               | E.3.2                | 5.0           | R              | 1.73         | 0.64                  | 0.43                     | 1.8                            | 1.2                              | ∞              |
| Liquid Conductivity - measurement uncertainty                                    | E.3.3                | 3.8           | N              | 1            | 0.64                  | 0.43                     | 2.4                            | 1.6                              | 6              |
| Liquid Permittivity - deviation from target values                               | E.3.2                | 5.0           | R              | 1.73         | 0.60                  | 0.49                     | 1.7                            | 1.4                              | ∞              |
| Liquid Permittivity - measurement uncertainty                                    | E.3.3                | 4.5           | N              | 1            | 0.60                  | 0.49                     | 2.7                            | 2.2                              | 6              |
| <b>Combined Standard Uncertainty (k=1)</b>                                       |                      |               |                |              |                       |                          | RSS                            | 12.1                             | 11.7           |
| <b>Expanded Uncertainty</b><br>(95% CONFIDENCE LEVEL)                            |                      |               |                |              |                       |                          | k=2                            | 24.2                             | 23.5           |
|                                                                                  |                      |               |                |              |                       |                          |                                |                                  | 299            |

The above measurement uncertainties are according to IEEE Std. 1528-2003

|                                          |                                                                                                                                   |                                      |  |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset |  |                                                                                       | Page 75 of 79                          |

Applicable for frequencies up to 6 GHz.

| a                                                                             | b                    | c             | d              | e=<br>f(d,k) | f                     | g                        | h =<br>c x f/e                 | i =<br>c x g/e                   | k              |
|-------------------------------------------------------------------------------|----------------------|---------------|----------------|--------------|-----------------------|--------------------------|--------------------------------|----------------------------------|----------------|
| Uncertainty<br>Component                                                      | IEEE<br>1528<br>Sec. | Tol.<br>(± %) | Prob.<br>Dist. | Div.         | c <sub>i</sub><br>1gm | c <sub>i</sub><br>10 gms | 1gm<br>u <sub>i</sub><br>(± %) | 10gms<br>u <sub>i</sub><br>(± %) | v <sub>i</sub> |
| <b>Measurement System</b>                                                     |                      |               |                |              |                       |                          |                                |                                  |                |
| Probe Calibration                                                             | E.2.1                | 6.55          | N              | 1            | 1.0                   | 1.0                      | 6.6                            | 6.6                              | ∞              |
| Axial Isotropy                                                                | E.2.2                | 0.25          | N              | 1            | 0.7                   | 0.7                      | 0.2                            | 0.2                              | ∞              |
| Hemishperical Isotropy                                                        | E.2.2                | 1.3           | N              | 1            | 1.0                   | 1.0                      | 1.3                            | 1.3                              | ∞              |
| Boundary Effect                                                               | E.2.3                | 0.4           | N              | 1            | 1.0                   | 1.0                      | 0.4                            | 0.4                              | ∞              |
| Linearity                                                                     | E.2.4                | 0.3           | N              | 1            | 1.0                   | 1.0                      | 0.3                            | 0.3                              | ∞              |
| System Detection Limits                                                       | E.2.5                | 5.1           | N              | 1            | 1.0                   | 1.0                      | 5.1                            | 5.1                              | ∞              |
| Readout Electronics                                                           | E.2.6                | 1.0           | N              | 1            | 1.0                   | 1.0                      | 1.0                            | 1.0                              | ∞              |
| Response Time                                                                 | E.2.7                | 0.8           | R              | 1.73         | 1.0                   | 1.0                      | 0.5                            | 0.5                              | ∞              |
| Integration Time                                                              | E.2.8                | 2.6           | R              | 1.73         | 1.0                   | 1.0                      | 1.5                            | 1.5                              | ∞              |
| RF Ambient Conditions                                                         | E.6.1                | 3.0           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Probe Positioner Mechanical Tolerance                                         | E.6.2                | 0.4           | R              | 1.73         | 1.0                   | 1.0                      | 0.2                            | 0.2                              | ∞              |
| Probe Positioning w/ respect to Phantom                                       | E.6.3                | 2.9           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation | E.5                  | 1.0           | R              | 1.73         | 1.0                   | 1.0                      | 0.6                            | 0.6                              | ∞              |
| <b>Test Sample Related</b>                                                    |                      |               |                |              |                       |                          |                                |                                  |                |
| Test Sample Positioning                                                       | E.4.2                | 6.0           | N              | 1            | 1.0                   | 1.0                      | 6.0                            | 6.0                              | 287            |
| Device Holder Uncertainty                                                     | E.4.1                | 3.32          | R              | 1.73         | 1.0                   | 1.0                      | 1.9                            | 1.9                              | ∞              |
| Output Power Variation - SAR drift measurement                                | 6.6.2                | 5.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.9                            | 2.9                              | ∞              |
| <b>Phantom &amp; Tissue Parameters</b>                                        |                      |               |                |              |                       |                          |                                |                                  |                |
| Phantom Uncertainty (Shape & Thickness tolerances)                            | E.3.1                | 4.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.3                            | 2.3                              | ∞              |
| Liquid Conductivity - deviation from target values                            | E.3.2                | 5.0           | R              | 1.73         | 0.64                  | 0.43                     | 1.8                            | 1.2                              | ∞              |
| Liquid Conductivity - measurement uncertainty                                 | E.3.3                | 3.8           | N              | 1            | 0.64                  | 0.43                     | 2.4                            | 1.6                              | 6              |
| Liquid Permittivity - deviation from target values                            | E.3.2                | 5.0           | R              | 1.73         | 0.60                  | 0.49                     | 1.7                            | 1.4                              | ∞              |
| Liquid Permittivity - measurement uncertainty                                 | E.3.3                | 4.5           | N              | 1            | 0.60                  | 0.49                     | 2.7                            | 2.2                              | 6              |
| <b>Combined Standard Uncertainty (k=1)</b>                                    |                      |               |                |              |                       |                          | RSS                            | 12.4                             | 12.0           |
| <b>Expanded Uncertainty</b><br>(95% CONFIDENCE LEVEL)                         |                      |               |                |              |                       |                          | k=2                            | 24.7                             | 24.0           |

The above measurement uncertainties are according to IEEE Std. 1528-2003

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG900R7                      |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 76 of 79                          |

## 16 CONCLUSION

### 16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 77 of 79                                                                         |                                        |

## 17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 78 of 79                                                                         |                                        |

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v01r02
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D02-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7               |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1403190578.A3L | <b>Test Dates:</b><br>02/03/14 - 03/31/14                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 79 of 79                                                                         |                                        |

## APPENDIX A: SAR TEST DATA

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EF0**

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$ ;  $\sigma = 0.907 \text{ S/m}$ ;  $\epsilon_r = 41.173$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-17-2014; Ambient Temp: 24.3°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3318; ConvF(6.33, 6.33, 6.33); Calibrated: 4/29/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 4/22/2013

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Mode: Cell. CDMA, Right Head, Cheek, Mid.ch, Standard Cover**


**Area Scan (8x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 24.868 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.664 W/kg

**SAR(1 g) = 0.533 W/kg**



0 dB = 0.561 W/kg = -2.51 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EC6**

Communication System: UID 0, PCS EVDO; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.427 \text{ S/m}$ ;  $\epsilon_r = 38.295$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-19-2014; Ambient Temp: 23.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3263; ConvF(5.11, 5.11, 5.11); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: PCS EVDO Rev. A, Right Head, Cheek, Mid.ch, Wireless Charging Cover**


**Area Scan (8x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 20.433 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.870 W/kg

**SAR(1 g) = 0.543 W/kg**



0 dB = 0.595 W/kg = -2.25 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EC6**

Communication System: UID 0, LTE RF; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$ ;  $\sigma = 0.892 \text{ S/m}$ ;  $\epsilon_r = 43.837$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-17-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3288; ConvF(6.56, 6.56, 6.56); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 12, Left Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Standard Cover**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 19.836 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.365 W/kg

**SAR(1 g) = 0.305 W/kg**



0 dB = 0.319 W/kg = -4.96 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EC6**

Communication System: UID 0, LTE RF; Frequency: 1715 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1715 \text{ MHz}$ ;  $\sigma = 1.364 \text{ S/m}$ ;  $\epsilon_r = 38.643$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-18-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3288; ConvF(5.67, 5.67, 5.67); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Low.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Standard Cover**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.145 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.563 W/kg

**SAR(1 g) = 0.382 W/kg**



0 dB = 0.410 W/kg = -3.87 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EC6**

Communication System: UID 0, LTE PCS 10 Mhz; Frequency: 1910 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1910 \text{ MHz}$ ;  $\sigma = 1.459 \text{ S/m}$ ;  $\epsilon_r = 38.171$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-19-2014; Ambient Temp: 23.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3263; ConvF(5.11, 5.11, 5.11); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 25 (PCS), Left Head, Cheek, High.Ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Standard Cover**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.020 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.942 W/kg

**SAR(1 g) = 0.613 W/kg**



0 dB = 0.663 W/kg = -1.78 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 328C6**

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$ ;  $\sigma = 1.835 \text{ S/m}$ ;  $\epsilon_r = 38.952$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-18-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3287; ConvF(4.43, 4.43, 4.43); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

**Mode: IEEE 802.11b, Right Head, Cheek, Ch 01, 1 Mbps,  
Antenna 1, Standard Cover**


**Area Scan (10x16x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 9.492 V/m; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 0.349 W/kg

**SAR(1 g) = 0.163 W/kg**





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 31F35**

Communication System: UID 0, IEEE 802.11a; Frequency: 5765 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used:

$f = 5765 \text{ MHz}$ ;  $\sigma = 5.088 \text{ S/m}$ ;  $\epsilon_r = 35.493$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-03-2014; Ambient Temp: 24.3°C; Tissue Temp: 23.3°C

Probe: EX3DV4 - SN3920; ConvF(4.11, 4.11, 4.11); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: IEEE 802.11a 5.8 GHz, Right Head, Cheek, Ch 153, 6 Mbps,  
Antenna 2, Standard Cover**


**Area Scan (13x16x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Reference Value = 5.548 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.650 W/kg

**SAR(1 g) = 0.134 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 31F35**

Communication System: UID 0, IEEE 802.11a; Frequency: 5680 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used:

$f = 5680 \text{ MHz}$ ;  $\sigma = 5.006 \text{ S/m}$ ;  $\epsilon_r = 35.596$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-03-2014; Ambient Temp: 24.5°C; Tissue Temp: 23.3°C

Probe: EX3DV4 - SN3920; ConvF(4.37, 4.37, 4.37); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: IEEE 802.11a 5.5 - 5.7 GHz, Right Head, Cheek, Ch 136, 6 Mbps,  
Antenna 2, Standard Cover**


**Area Scan (13x16x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Reference Value = 5.743 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.55 W/kg

**SAR(1 g) = 0.154 W/kg**



0 dB = 0.437 W/kg = -3.60 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EF0**

Communication System: UID 0, Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$ ;  $\sigma = 0.978 \text{ S/m}$ ;  $\epsilon_r = 55.087$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-17-2014; Ambient Temp: 19.7°C; Tissue Temp: 19.7°C

Probe: ES3DV3 - SN3263; ConvF(6.29, 6.29, 6.29); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: Cell. CDMA, Body SAR, Back side, Mid.ch, Standard Cover**


**Area Scan (8x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 28.284 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.816 W/kg

**SAR(1 g) = 0.670 W/kg**



0 dB = 0.702 W/kg = -1.54 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EF0**

Communication System: UID 0, Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$ ;  $\sigma = 0.978 \text{ S/m}$ ;  $\epsilon_r = 55.087$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-17-2014; Ambient Temp: 19.7°C; Tissue Temp: 19.7°C

Probe: ES3DV3 - SN3263; ConvF(6.29, 6.29, 6.29); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: Cell. CDMA, Body SAR, Right Edge, Mid.ch, Standard Cover**


**Area Scan (11x13x1):** Measurement grid:  $dx=5\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 29.196 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.904 W/kg

**SAR(1 g) = 0.673 W/kg**



0 dB = 0.719 W/kg = -1.43 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EF0**

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.545 \text{ S/m}$ ;  $\epsilon_r = 51.042$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-31-2014; Ambient Temp: 23.2°C; Tissue Temp: 21.6°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/22/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/21/2013

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Mode: PCS CDMA, Body SAR, Back side, Mid.ch, Standard Cover**


**Area Scan (8x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 18.043 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.719 W/kg

**SAR(1 g) = 0.465 W/kg**



0 dB = 0.494 W/kg = -3.06 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 3R725**

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.545 \text{ S/m}$ ;  $\epsilon_r = 51.042$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-31-2014; Ambient Temp: 23.2°C; Tissue Temp: 21.6°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/22/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/21/2013

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Mode: PCS EVDO Rev. 0, Body SAR, Back side, Mid.ch, Standard Cover**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (6x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 18.195 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.838 W/kg

**SAR(1 g) = 0.489 W/kg**



0 dB = 0.527 W/kg = -2.78 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EF0**

Communication System: UID 0, LTE RF; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$ ;  $\sigma = 0.939 \text{ S/m}$ ;  $\epsilon_r = 54.944$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-18-2014; Ambient Temp: 19.9°C; Tissue Temp: 20.6°C

Probe: ES3DV3 - SN3263; ConvF(6.37, 6.37, 6.37); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Standard Cover**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.675 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.515 W/kg

**SAR(1 g) = 0.369 W/kg**



0 dB = 0.390 W/kg = -4.09 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EF0**

Communication System: UID 0, LTE RF; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$ ;  $\sigma = 0.939 \text{ S/m}$ ;  $\epsilon_r = 54.944$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-18-2014; Ambient Temp: 19.9°C; Tissue Temp: 20.6°C

Probe: ES3DV3 - SN3263; ConvF(6.37, 6.37, 6.37); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 12, Body SAR, Front side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Standard Cover**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.722 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.817 W/kg

**SAR(1 g) = 0.467 W/kg**



0 dB = 0.518 W/kg = -2.86 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EC6**

Communication System: UID 0, LTE RF; Frequency: 1715 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1715 \text{ MHz}$ ;  $\sigma = 1.472 \text{ S/m}$ ;  $\epsilon_r = 54.456$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-18-2014; Ambient Temp: 23.4°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3288; ConvF(5.1, 5.1, 5.1); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Low.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Standard Cover**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.160 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.908 W/kg

**SAR(1 g) = 0.509 W/kg**



0 dB = 0.576 W/kg = -2.40 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32EC6**

Communication System: UID 0, LTE RF; Frequency: 1715 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1715 \text{ MHz}$ ;  $\sigma = 1.472 \text{ S/m}$ ;  $\epsilon_r = 54.456$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-18-2014; Ambient Temp: 23.4°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3288; ConvF(5.1, 5.1, 5.1); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 4 (AWS), Body SAR, Front side, Low.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Standard Cover**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.174 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.09 W/kg

**SAR(1 g) = 0.586 W/kg**



0 dB = 0.651 W/kg = -1.86 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32E32**

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1910 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1910 \text{ MHz}$ ;  $\sigma = 1.558 \text{ S/m}$ ;  $\epsilon_r = 53.102$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section: Space: 1.0 cm

Test Date: 02-17-2014; Ambient Temp: 23.7°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3319; ConvF(4.85, 4.85, 4.85); Calibrated: 4/29/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/22/2013

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Wireless Charging Cover**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.290 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.329 W/kg

**SAR(1 g) = 0.209 W/kg**



0 dB = 0.225 W/kg = -6.48 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 32E32**

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1910 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1910 \text{ MHz}$ ;  $\sigma = 1.558 \text{ S/m}$ ;  $\epsilon_r = 53.102$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-17-2014; Ambient Temp: 23.7°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3319; ConvF(4.85, 4.85, 4.85); Calibrated: 4/29/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/22/2013

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 25 (PCS), Body SAR, Front side, High.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset, Wireless Charging Cover**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.270 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.829 W/kg

**SAR(1 g) = 0.547 W/kg**



0 dB = 0.600 W/kg = -2.22 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 00F05**

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$ ;  $\sigma = 1.92 \text{ S/m}$ ;  $\epsilon_r = 51.381$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-12-2014; Ambient Temp: 24.4°C; Tissue Temp: 24.0°C

Probe: ES3DV3 - SN3318; ConvF(4.31, 4.31, 4.31); Calibrated: 4/29/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 4/22/2013

Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

**Mode: IEEE 802.11b, Body SAR, Ch 06, 1 Mbps, Back Side,  
Antenna 1, Standard Cover**


**Area Scan (10x16x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.646 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.434 W/kg

**SAR(1 g) = 0.235 W/kg**



0 dB = 0.289 W/kg = -5.39 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 15ECE**

Communication System: UID 0, IEEE 802.11a; Frequency: 5765 MHz; Duty Cycle: 1:1  
Medium: 5 GHz Body; Medium parameters used:

$$f = 5765 \text{ MHz}; \sigma = 6.028 \text{ S/m}; \epsilon_r = 45.89; \rho = 1000 \text{ kg/m}^3$$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2014; Ambient Temp: 24.1°C; Tissue Temp: 23.7°C

Probe: EX3DV4 - SN3914; ConvF(4.14, 4.14, 4.14); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Mode: IEEE 802.11a, 5.8 GHz, Body SAR, Ch 153, 6 Mbps, Back Side,  
Antenna 2, Standard Cover**


**Area Scan (11x18x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.488 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.47 W/kg

**SAR(1 g) = 0.287 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG900R7; Type: Portable Handset; Serial: 15ECE**

Communication System: UID 0, IEEE 802.11a; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5500 \text{ MHz}$ ;  $\sigma = 5.6 \text{ S/m}$ ;  $\epsilon_r = 46.464$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2014; Ambient Temp: 24.1°C; Tissue Temp: 23.8°C

Probe: EX3DV4 - SN3914; ConvF(4.07, 4.07, 4.07); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

**Mode: IEEE 802.11a, 5.5 - 5.7 GHz, Body SAR, Ch 100, 6 Mbps, Back Side,  
Antenna 2, Standard Cover**


**Area Scan (11x18x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.249 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.49 W/kg

**SAR(1 g) = 0.296 W/kg**



## APPENDIX B: SYSTEM VERIFICATION



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.929 \text{ S/m}$ ;  $\epsilon_r = 43.287$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-17-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3288; ConvF(6.56, 6.56, 6.56); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 750 MHz System Verification

**Area Scan (7x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.25 W/kg

**SAR(1 g) = 0.856 W/kg**

Deviation(1 g): 0.71%



0 dB = 0.925 W/kg = -0.34 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.906 \text{ S/m}$ ;  $\epsilon_r = 41.195$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-17-2014; Ambient Temp: 24.3°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3318; ConvF(6.33, 6.33, 6.33); Calibrated: 4/29/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 4/22/2013

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.40 W/kg

**SAR(1 g) = 0.935 W/kg**

Deviation(1 g): -3.41%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1765 MHz; Type: D1765V2; Serial: 1008**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.4 \text{ S/m}$ ;  $\epsilon_r = 38.485$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-18-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3288; ConvF(5.67, 5.67, 5.67); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 1750 MHz System Verification

**Area Scan (6x8x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.54 W/kg

**SAR(1 g) = 3.55 W/kg**

Deviation(1 g): -3.53%



0 dB = 3.96 W/kg = 5.98 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.448 \text{ S/m}$ ;  $\epsilon_r = 38.212$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-19-2014; Ambient Temp: 23.7°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3263; ConvF(5.11, 5.11, 5.11); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 1900 MHz System Verification

**Area Scan (5x7x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.52 W/kg

**SAR(1 g) = 3.97 W/kg**

Deviation(1 g): -2.70%



0 dB = 4.37 W/kg = 6.40 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 1.879 \text{ S/m}$ ;  $\epsilon_r = 38.816$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-18-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3287; ConvF(4.43, 4.43, 4.43); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 2450 MHz System Verification

**Area Scan (8x9x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 10.7 W/kg

**SAR(1 g) = 5.18 W/kg**

Deviation(1 g): -2.63%



0 dB = 6.70 W/kg = 8.26 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5200 \text{ MHz}$ ;  $\sigma = 4.508 \text{ S/m}$ ;  $\epsilon_r = 36.214$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2014; Ambient Temp: 24.4°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN3920; ConvF(4.87, 4.87, 4.87); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 5200 MHz System Verification

**Area Scan (7x9x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 31.73 W/kg

**SAR(1 g) = 7.72 W/kg**

Deviation(1 g): -0.39%



0 dB = 19.0 W/kg = 12.79 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5300 \text{ MHz}$ ;  $\sigma = 4.605 \text{ S/m}$ ;  $\epsilon_r = 36.076$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2014; Ambient Temp: 24.4°C; Tissue Temp: 23.1°C

Probe: EX3DV4 - SN3920; ConvF(4.66, 4.66, 4.66); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 5300 MHz System Verification

**Area Scan (7x9x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 33.47 W/kg

**SAR(1 g) = 7.9 W/kg**

Deviation(1 g): -1.50%



0 dB = 20.0 W/kg = 13.01 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5500 \text{ MHz}$ ;  $\sigma = 4.822 \text{ S/m}$ ;  $\epsilon_r = 35.798$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3920; ConvF(4.54, 4.54, 4.54); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 5500 MHz System Verification

**Area Scan (7x9x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 36.75 W/kg

**SAR(1 g) = 7.74 W/kg**

Deviation(1 g): -4.91%



0 dB = 19.3 W/kg = 12.86 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5600 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$ ;  $\sigma = 4.925 \text{ S/m}$ ;  $\epsilon_r = 35.697$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2014; Ambient Temp: 24.5°C; Tissue Temp: 23.3°C

Probe: EX3DV4 - SN3920; ConvF(4.37, 4.37, 4.37); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 5600 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.83 W/kg

**SAR(1 g) = 7.9 W/kg**

Deviation(1 g): -1.25%



0 dB = 19.9 W/kg = 12.99 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5800 \text{ MHz}$ ;  $\sigma = 5.112 \text{ S/m}$ ;  $\epsilon_r = 35.479$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2014; Ambient Temp: 24.3°C; Tissue Temp: 23.3°C

Probe: EX3DV4 - SN3920; ConvF(4.11, 4.11, 4.11); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 5800 MHz System Verification

**Area Scan (7x9x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.71 W/kg

**SAR(1 g) = 7.68 W/kg**

Deviation(1 g): -0.90%



0 dB = 19.2 W/kg = 12.83 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.976 \text{ S/m}$ ;  $\epsilon_r = 54.495$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-18-2014; Ambient Temp: 19.9°C; Tissue Temp: 20.6°C

Probe: ES3DV3 - SN3263; ConvF(6.37, 6.37, 6.37); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 750 MHz System Verification

**Area Scan (7x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.27 W/kg

**SAR(1 g) = 0.882 W/kg**

Deviation(1 g): 1.15%



0 dB = 0.960 W/kg = -0.18 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.976 \text{ S/m}$ ;  $\epsilon_r = 55.109$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-17-2014; Ambient Temp: 19.7°C; Tissue Temp: 19.7°C

Probe: ES3DV3 - SN3263; ConvF(6.29, 6.29, 6.29); Calibrated: 5/16/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/13/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 835 MHz System Verification

**Area Scan (7x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.39 W/kg

**SAR(1 g) = 0.953 W/kg**

Deviation(1 g): -0.83%



0 dB = 1.01 W/kg = 0.04 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1765 MHz; Type: D1765V2; Serial: 1008**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.511 \text{ S/m}$ ;  $\epsilon_r = 54.336$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-18-2014; Ambient Temp: 23.4°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3288; ConvF(5.1, 5.1, 5.1); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

## 1750 MHz System Verification

**Area Scan (6x8x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.81 W/kg

**SAR(1 g) = 3.76 W/kg**

Deviation(1 g): -1.57%



0 dB = 4.21 W/kg = 6.24 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d149**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.547 \text{ S/m}$ ;  $\epsilon_r = 53.129$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-17-2014; Ambient Temp: 23.7°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3319; ConvF(4.85, 4.85, 4.85); Calibrated: 4/29/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/22/2013

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.82 W/kg

**SAR(1 g) = 3.83 W/kg**

Deviation(1 g): -5.43%



0 dB = 4.31 W/kg = 6.34 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d149**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.569 \text{ S/m}$ ;  $\epsilon_r = 50.964$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-31-2014; Ambient Temp: 23.2°C; Tissue Temp: 21.6°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/22/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/21/2013

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.65 W/kg

**SAR(1 g) = 4.2 W/kg**

Deviation(1 g): 3.70%



0 dB = 4.73 W/kg = 6.75 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 1.937 \text{ S/m}$ ;  $\epsilon_r = 51.331$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-12-2014; Ambient Temp: 24.4°C; Tissue Temp: 24.0°C

Probe: ES3DV3 - SN3318; ConvF(4.31, 4.31, 4.31); Calibrated: 4/29/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 4/22/2013

Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 2450 MHz System Verification

**Area Scan (8x9x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 11.1 W/kg

**SAR(1 g) = 5.41 W/kg**

Deviation(1 g): 4.64%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5200 MHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5200 \text{ MHz}$ ;  $\sigma = 5.147 \text{ S/m}$ ;  $\epsilon_r = 47.331$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2014; Ambient Temp: 24.0°C; Tissue Temp: 23.8°C

Probe: EX3DV4 - SN3914; ConvF(4.52, 4.52, 4.52); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 5200 MHz System Verification

**Area Scan (7x8x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 32.9 W/kg

**SAR(1 g) = 7.7 W/kg**

Deviation(1 g): 0.52%



0 dB = 19.7 W/kg = 12.94 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5300 MHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5300 \text{ MHz}$ ;  $\sigma = 5.298 \text{ S/m}$ ;  $\epsilon_r = 47.17$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2014; Ambient Temp: 24.0°C; Tissue Temp: 23.8°C

Probe: EX3DV4 - SN3914; ConvF(4.32, 4.32, 4.32); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 5300 MHz System Verification

**Area Scan (7x8x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.0 W/kg

**SAR(1 g) = 7.65 W/kg**

Deviation(1 g): -0.39%



0 dB = 19.7 W/kg = 12.94 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5500 MHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5500 \text{ MHz}$ ;  $\sigma = 5.6 \text{ S/m}$ ;  $\epsilon_r = 46.464$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2014; Ambient Temp: 24.1°C; Tissue Temp: 23.8°C

Probe: EX3DV4 - SN3914; ConvF(4.07, 4.07, 4.07); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 5500 MHz System Verification

**Area Scan (7x8x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100mW)

Peak SAR (extrapolated) = 36.5 W/kg

**SAR(1 g) = 7.84 W/kg**

Deviation(1 g): -1.75%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5800 MHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5800 \text{ MHz}$ ;  $\sigma = 6.062 \text{ S/m}$ ;  $\epsilon_r = 45.987$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2014; Ambient Temp: 24.1°C; Tissue Temp: 23.7°C

Probe: EX3DV4 - SN3914; ConvF(4.14, 4.14, 4.14); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## 5800 MHz System Verification

**Area Scan (7x8x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 35.3 W/kg

**SAR(1 g) = 7.17 W/kg**

Deviation(1 g): -5.03%



## APPENDIX C: PROBE CALIBRATION





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3288\_Sep13/2**

## **CALIBRATION CERTIFICATE (Replacement of No: ES3-3288\_Sep13)**

Object **ES3DV3 - SN:3288**

CCV  
10/4/13

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **September 23, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 4-Sep-13 (No. DAE4-660_Sep13)     | Apr-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                                                                                                                 | Name           | Function              | Signature               |
|-----------------------------------------------------------------------------------------------------------------|----------------|-----------------------|-------------------------|
| Calibrated by:                                                                                                  | Jeton Kastrati | Laboratory Technician |                         |
| Approved by:                                                                                                    | Katja Pokovic  | Technical Manager     |                         |
|                                                                                                                 |                |                       | Issued: October 4, 2013 |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |                |                       |                         |

# Probe ES3DV3

## SN:3288

Manufactured: July 6, 2010  
Calibrated: September 23, 2013

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                       |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|-----------------------------------------------------------|----------|----------|----------|-----------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.87     | 0.97     | 0.75     | ± 10.1 %  |
| DCP (mV) <sup>B</sup>                                     | 103.3    | 103.2    | 100.2    |           |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 171.1    | ±3.5 %                    |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 135.0    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 154.3    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 41.9                               | 0.89                            | 6.56    | 6.56    | 6.56    | 0.32  | 1.89       | ± 12.0 %    |
| 835                  | 41.5                               | 0.90                            | 6.37    | 6.37    | 6.37    | 0.34  | 1.82       | ± 12.0 %    |
| 1750                 | 40.1                               | 1.37                            | 5.67    | 5.67    | 5.67    | 0.56  | 1.51       | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 5.47    | 5.47    | 5.47    | 0.80  | 1.29       | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 4.63    | 4.63    | 4.63    | 0.80  | 1.34       | ± 12.0 %    |
| 2600                 | 39.0                               | 1.96                            | 4.55    | 4.55    | 4.55    | 0.80  | 1.41       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

### Calibration Parameter Determined in Body Tissue Simulating Media


| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 55.5                               | 0.96                            | 6.25    | 6.25    | 6.25    | 0.70  | 1.27       | ± 12.0 %    |
| 835                  | 55.2                               | 0.97                            | 6.27    | 6.27    | 6.27    | 0.75  | 1.22       | ± 12.0 %    |
| 1750                 | 53.4                               | 1.49                            | 5.10    | 5.10    | 5.10    | 0.59  | 1.46       | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 4.82    | 4.82    | 4.82    | 0.53  | 1.54       | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 4.37    | 4.37    | 4.37    | 0.80  | 1.02       | ± 12.0 %    |
| 2600                 | 52.5                               | 2.16                            | 4.14    | 4.14    | 4.14    | 0.64  | 0.94       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)




Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )





## Receiving Pattern ( $\phi$ ), $\vartheta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

# Dynamic Range f(SAR<sub>head</sub>) (TEM cell , f = 900 MHz)





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$



## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -127.1     |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 10 mm      |
| Tip Diameter                                  | 4 mm       |
| Probe Tip to Sensor X Calibration Point       | 2 mm       |
| Probe Tip to Sensor Y Calibration Point       | 2 mm       |
| Probe Tip to Sensor Z Calibration Point       | 2 mm       |
| Recommended Measurement Distance from Surface | 3 mm       |



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **ES3-3318\_Apr13**

## CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3318**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-23.v4, QA CAL-25.v4**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **April 29, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 31-Jan-13 (No. DAE4-660_Jan13)    | Jan-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                                                                                                                 | Name          | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|---------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Dimce Iliev   | Laboratory Technician |           |
| Approved by:                                                                                                    | Katja Pokovic | Technical Manager     |           |
| Issued: April 29, 2013                                                                                          |               |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |               |                       |           |



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                       |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe ES3DV3

## SN:3318

Manufactured: January 10, 2012  
Calibrated: April 29, 2013

**Calibrated for DASY/EASY Systems**  
(Note: non-compatible with DASY2 system!)



## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|-----------------------------------------------------------|----------|----------|----------|-----------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 1.15     | 0.92     | 1.29     | ± 10.1 %  |
| DCP (mV) <sup>B</sup>                                     | 102.6    | 105.4    | 100.8    |           |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB/ $\mu\text{V}$ | C   | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                    | 1.0 | 0.00    | 153.6    | ±3.5 %                    |
|     |                           | Y | 0.0     | 0.0                    | 1.0 |         | 133.8    |                           |
|     |                           | Z | 0.0     | 0.0                    | 1.0 |         | 154.8    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 41.9                               | 0.89                            | 6.59    | 6.59    | 6.59    | 0.25  | 2.12       | ± 12.0 %    |
| 850                  | 41.5                               | 0.92                            | 6.33    | 6.33    | 6.33    | 0.57  | 1.25       | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 5.22    | 5.22    | 5.22    | 0.79  | 1.25       | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 4.59    | 4.59    | 4.59    | 0.80  | 1.30       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

### Calibration Parameter Determined in Body Tissue Simulating Media


| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 55.5                               | 0.96                            | 6.35    | 6.35    | 6.35    | 0.53  | 1.42       | ± 12.0 %    |
| 850                  | 55.2                               | 0.99                            | 6.21    | 6.21    | 6.21    | 0.57  | 1.38       | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 4.79    | 4.79    | 4.79    | 0.46  | 1.77       | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 4.31    | 4.31    | 4.31    | 0.80  | 1.09       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$

f=600 MHz, TEM




f=1800 MHz, R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

# Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$ )





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$





## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -103.8     |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 10 mm      |
| Tip Diameter                                  | 4 mm       |
| Probe Tip to Sensor X Calibration Point       | 2 mm       |
| Probe Tip to Sensor Y Calibration Point       | 2 mm       |
| Probe Tip to Sensor Z Calibration Point       | 2 mm       |
| Recommended Measurement Distance from Surface | 3 mm       |

## **Additional Conversion Factors**

**for Dosimetric E-Field Probe**

Type:

**ES3DV3**

Serial Number:

**3318**

Place of Assessment:

**Zurich**

Date of Assessment:

**June 19, 2013**


Probe Calibration Date:

**April 29, 2013**

✓  
Kox  
6/25/13

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. The evaluation is coupled with measured conversion factors (probe calibration date indicated above). The uncertainty of the numerical assessment is based on the extrapolation from measured value at 835 MHz or at 1900 MHz.

Assessed by:



## Dosimetric E-Field Probe ES3DV3 SN:3318

Conversion factor ( $\pm$  standard deviation)

1750  $\pm$  50 MHz      *ConvF*      5.59  $\pm$  7 %

$\epsilon_r = 40.1 \pm 5\%$   
 $\sigma = 1.37 \pm 5\%$  mho/m  
(head tissue)

1750  $\pm$  50 MHz      *ConvF*      5.22  $\pm$  7 %

$\epsilon_r = 53.4 \pm 5\%$   
 $\sigma = 1.49 \pm 5\%$  mho/m  
(body tissue)

### Important Note:

For numerically assessed probe conversion factors, parameters Alpha and Delta in the DASY software must have the following entries: Alpha = 0 and Delta = 1.

Please see also DASY Manual.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **ES3-3263\_May13**

## CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3263**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-23.v4, QA CAL-25.v4**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **May 16, 2013**

*✓ KOK  
5/23/13*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 31-Jan-13 (No. DAE4-660_Jan13)    | Jan-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                                                                                                                 | Name          | Function              | Signature            |
|-----------------------------------------------------------------------------------------------------------------|---------------|-----------------------|----------------------|
| Calibrated by:                                                                                                  | Leif Klysner  | Laboratory Technician | <i>Leif Klysner</i>  |
| Approved by:                                                                                                    | Katja Pokovic | Technical Manager     | <i>Katja Pokovic</i> |
| Issued: May 17, 2013                                                                                            |               |                       |                      |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |               |                       |                      |



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\varphi$   | $\varphi$ rotation around probe axis                                                                                                                    |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below *ConvF*).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* *frequency\_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe ES3DV3

## SN:3263

Manufactured: January 25, 2010  
Calibrated: May 16, 2013

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3263

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 1.21     | 1.25     | 1.12     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 101.2    | 100.2    | 103.7    |               |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 156.5    | $\pm 2.5 \%$              |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 153.2    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 147.2    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3263

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 41.9                               | 0.89                            | 6.51    | 6.51    | 6.51    | 0.21  | 2.29       | ± 12.0 %    |
| 835                  | 41.5                               | 0.90                            | 6.29    | 6.29    | 6.29    | 0.50  | 1.38       | ± 12.0 %    |
| 1750                 | 40.1                               | 1.37                            | 5.30    | 5.30    | 5.30    | 0.45  | 1.54       | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 5.11    | 5.11    | 5.11    | 0.57  | 1.38       | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 4.47    | 4.47    | 4.47    | 0.59  | 1.49       | ± 12.0 %    |
| 2600                 | 39.0                               | 1.96                            | 4.31    | 4.31    | 4.31    | 0.80  | 1.28       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.



## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3263

### Calibration Parameter Determined in Body Tissue Simulating Media


| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 55.5                               | 0.96                            | 6.37    | 6.37    | 6.37    | 0.34  | 1.82       | ± 12.0 %    |
| 835                  | 55.2                               | 0.97                            | 6.29    | 6.29    | 6.29    | 0.54  | 1.39       | ± 12.0 %    |
| 1750                 | 53.4                               | 1.49                            | 5.01    | 5.01    | 5.01    | 0.72  | 1.27       | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 4.78    | 4.78    | 4.78    | 0.53  | 1.56       | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 4.33    | 4.33    | 4.33    | 0.80  | 1.14       | ± 12.0 %    |
| 2600                 | 52.5                               | 2.16                            | 4.14    | 4.14    | 4.14    | 0.80  | 1.02       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

# Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$ )





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$



## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3263

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -116       |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 10 mm      |
| Tip Diameter                                  | 4 mm       |
| Probe Tip to Sensor X Calibration Point       | 2 mm       |
| Probe Tip to Sensor Y Calibration Point       | 2 mm       |
| Probe Tip to Sensor Z Calibration Point       | 2 mm       |
| Recommended Measurement Distance from Surface | 3 mm       |



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3287\_Nov13**

## CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3287**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **November 20, 2013**

CC  
11/20/2013

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 4-Sep-13 (No. DAE4-660_Sep13)     | Sep-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-13) | In house check: Oct-14 |

|                                                                                                                 | Name          | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|---------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Leif Klysner  | Laboratory Technician |           |
| Approved by:                                                                                                    | Kalja Pokovic | Technical Manager     |           |
| Issued: November 20, 2013                                                                                       |               |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |               |                       |           |



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                       |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |
| Connector Angle          | information used in DASY system to align probe sensor X to the robot coordinate system                                                                  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).



# Probe ES3DV3

## SN:3287

Manufactured: June 7, 2010  
Calibrated: November 20, 2013

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

# DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

## Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 1.31     | 1.25     | 1.25     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 102.6    | 102.5    | 100.4    |               |

## Modulation Calibration Parameters

| UID           | Communication System Name                |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C    | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|---------------|------------------------------------------|---|---------|------------------------------|------|---------|----------|---------------------------|
| 0             | CW                                       | X | 0.0     | 0.0                          | 1.0  | 0.00    | 157.3    | $\pm 2.7 \%$              |
|               |                                          | Y | 0.0     | 0.0                          | 1.0  |         | 159.9    |                           |
|               |                                          | Z | 0.0     | 0.0                          | 1.0  |         | 152.5    |                           |
| 10010-<br>CAA | SAR Validation (Square, 100ms, 10ms)     | X | 2.23    | 57.9                         | 9.9  | 10.00   | 45.7     | $\pm 1.4 \%$              |
|               |                                          | Y | 2.13    | 57.6                         | 9.8  |         | 46.6     |                           |
|               |                                          | Z | 3.31    | 61.1                         | 11.8 |         | 47.6     |                           |
| 10011-<br>CAA | UMTS-FDD (WCDMA)                         | X | 3.25    | 66.3                         | 17.9 | 2.91    | 124.8    | $\pm 0.5 \%$              |
|               |                                          | Y | 3.16    | 65.7                         | 17.4 |         | 127.4    |                           |
|               |                                          | Z | 3.15    | 65.5                         | 17.4 |         | 122.8    |                           |
| 10012-<br>CAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) | X | 3.08    | 68.7                         | 18.3 | 1.87    | 127.2    | $\pm 0.7 \%$              |
|               |                                          | Y | 3.03    | 68.2                         | 17.9 |         | 129.4    |                           |
|               |                                          | Z | 2.87    | 67.0                         | 17.3 |         | 126.5    |                           |
| 10021-<br>DAA | GSM-FDD (TDMA, GMSK)                     | X | 15.99   | 90.6                         | 25.0 | 9.39    | 99.9     | $\pm 1.2 \%$              |
|               |                                          | Y | 12.41   | 86.6                         | 23.6 |         | 101.5    |                           |
|               |                                          | Z | 29.18   | 99.9                         | 28.5 |         | 109.2    |                           |
| 10023-<br>DAA | GPRS-FDD (TDMA, GMSK, TN 0)              | X | 25.67   | 98.9                         | 27.8 | 9.57    | 97.9     | $\pm 1.7 \%$              |
|               |                                          | Y | 14.20   | 88.5                         | 24.3 |         | 100.6    |                           |
|               |                                          | Z | 27.68   | 99.8                         | 28.8 |         | 107.7    |                           |
| 10024-<br>DAA | GPRS-FDD (TDMA, GMSK, TN 0-1)            | X | 42.95   | 99.6                         | 24.9 | 6.56    | 124.4    | $\pm 1.4 \%$              |
|               |                                          | Y | 45.27   | 99.9                         | 24.8 |         | 128.8    |                           |
|               |                                          | Z | 42.64   | 99.6                         | 25.5 |         | 135.7    |                           |
| 10027-<br>DAA | GPRS-FDD (TDMA, GMSK, TN 0-1-2)          | X | 27.78   | 91.3                         | 21.1 | 4.80    | 136.0    | $\pm 1.4 \%$              |
|               |                                          | Y | 32.74   | 93.9                         | 21.9 |         | 146.6    |                           |
|               |                                          | Z | 23.93   | 89.5                         | 21.1 |         | 144.8    |                           |
| 10028-<br>DAA | GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)        | X | 59.17   | 99.6                         | 22.4 | 3.55    | 142.5    | $\pm 1.2 \%$              |
|               |                                          | Y | 78.76   | 99.7                         | 21.7 |         | 104.9    |                           |
|               |                                          | Z | 38.06   | 94.2                         | 21.4 |         | 148.8    |                           |
| 10032-<br>CAA | IEEE 802.15.1 Bluetooth (GFSK, DH5)      | X | 93.35   | 99.7                         | 19.5 | 1.16    | 108.1    | $\pm 0.9 \%$              |
|               |                                          | Y | 96.67   | 94.0                         | 16.9 |         | 114.7    |                           |
|               |                                          | Z | 98.17   | 96.2                         | 18.2 |         | 108.9    |                           |
| 10039-<br>CAA | CDMA2000 (1xRTT, RC1)                    | X | 4.84    | 66.7                         | 18.8 | 4.57    | 126.5    | $\pm 0.9 \%$              |
|               |                                          | Y | 4.83    | 66.6                         | 18.6 |         | 134.4    |                           |
|               |                                          | Z | 4.76    | 66.0                         | 18.3 |         | 125.9    |                           |
| 10081-<br>CAA | CDMA2000 (1xRTT, RC3)                    | X | 4.00    | 66.2                         | 18.5 | 3.97    | 121.9    | $\pm 0.7 \%$              |
|               |                                          | Y | 3.91    | 65.5                         | 17.9 |         | 128.9    |                           |
|               |                                          | Z | 3.88    | 65.2                         | 17.8 |         | 120.7    |                           |

|           |                                          |   |       |      |      |      |       |        |
|-----------|------------------------------------------|---|-------|------|------|------|-------|--------|
| 10098-CAA | UMTS-FDD (HSUPA, Subtest 2)              | X | 4.66  | 66.6 | 18.4 | 3.98 | 132.5 | ±0.7 % |
|           |                                          | Y | 4.66  | 66.5 | 18.2 |      | 141.3 |        |
|           |                                          | Z | 4.54  | 65.9 | 17.9 |      | 130.7 |        |
| 10100-CAB | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK) | X | 6.65  | 68.3 | 20.1 | 5.67 | 139.5 | ±1.4 % |
|           |                                          | Y | 6.69  | 68.3 | 19.9 |      | 148.9 |        |
|           |                                          | Z | 6.60  | 67.9 | 19.8 |      | 137.5 |        |
| 10108-CAB | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK) | X | 6.52  | 67.8 | 20.0 | 5.80 | 137.3 | ±1.4 % |
|           |                                          | Y | 6.53  | 67.6 | 19.7 |      | 147.5 |        |
|           |                                          | Z | 6.51  | 67.6 | 19.8 |      | 135.3 |        |
| 10110-CAB | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)  | X | 6.19  | 67.2 | 19.7 | 5.75 | 134.3 | ±1.2 % |
|           |                                          | Y | 6.24  | 67.3 | 19.6 |      | 142.9 |        |
|           |                                          | Z | 6.23  | 67.1 | 19.6 |      | 132.3 |        |
| 10151-CAB | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)  | X | 11.56 | 79.1 | 27.9 | 9.28 | 130.1 | ±3.0 % |
|           |                                          | Y | 11.01 | 76.8 | 26.2 |      | 141.9 |        |
|           |                                          | Z | 12.98 | 81.2 | 28.7 |      | 135.7 |        |
| 10154-CAB | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)  | X | 6.25  | 67.4 | 19.8 | 5.75 | 135.1 | ±1.2 % |
|           |                                          | Y | 6.17  | 66.9 | 19.3 |      | 143.6 |        |
|           |                                          | Z | 6.16  | 66.8 | 19.4 |      | 132.8 |        |
| 10160-CAB | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)  | X | 6.66  | 67.8 | 20.0 | 5.82 | 140.3 | ±1.4 % |
|           |                                          | Y | 6.72  | 67.9 | 19.9 |      | 148.8 |        |
|           |                                          | Z | 6.66  | 67.6 | 19.8 |      | 137.4 |        |
| 10169-CAB | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)    | X | 5.05  | 66.7 | 19.5 | 5.73 | 117.8 | ±0.9 % |
|           |                                          | Y | 4.93  | 66.0 | 18.9 |      | 125.0 |        |
|           |                                          | Z | 5.08  | 66.3 | 19.3 |      | 116.3 |        |
| 10172-CAB | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)    | X | 8.47  | 76.8 | 26.9 | 9.21 | 100.3 | ±2.2 % |
|           |                                          | Y | 8.06  | 74.6 | 25.3 |      | 107.5 |        |
|           |                                          | Z | 9.43  | 78.2 | 27.4 |      | 102.5 |        |
| 10175-CAB | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)    | X | 4.98  | 66.3 | 19.3 | 5.72 | 118.2 | ±0.9 % |
|           |                                          | Y | 4.96  | 66.1 | 19.0 |      | 119.9 |        |
|           |                                          | Z | 5.03  | 66.1 | 19.1 |      | 116.1 |        |
| 10181-CAB | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)    | X | 5.06  | 66.7 | 19.6 | 5.72 | 118.7 | ±0.9 % |
|           |                                          | Y | 4.97  | 66.2 | 19.1 |      | 120.0 |        |
|           |                                          | Z | 5.03  | 66.1 | 19.1 |      | 116.3 |        |
| 10225-CAA | UMTS-FDD (HSPA+)                         | X | 6.78  | 66.1 | 18.9 | 5.97 | 105.3 | ±1.2 % |
|           |                                          | Y | 6.68  | 65.7 | 18.6 |      | 106.8 |        |
|           |                                          | Z | 7.32  | 67.6 | 19.7 |      | 148.0 |        |
| 10237-CAB | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)    | X | 8.56  | 77.1 | 27.1 | 9.21 | 100.8 | ±1.9 % |
|           |                                          | Y | 8.33  | 75.8 | 26.1 |      | 103.8 |        |
|           |                                          | Z | 9.39  | 78.0 | 27.3 |      | 101.9 |        |
| 10252-CAB | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)  | X | 10.58 | 77.8 | 27.4 | 9.24 | 123.3 | ±2.5 % |
|           |                                          | Y | 10.48 | 76.9 | 26.5 |      | 128.1 |        |
|           |                                          | Z | 11.79 | 79.6 | 28.0 |      | 127.0 |        |
| 10267-CAB | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK) | X | 11.52 | 79.1 | 27.9 | 9.30 | 130.1 | ±2.7 % |
|           |                                          | Y | 11.24 | 77.7 | 26.9 |      | 136.0 |        |
|           |                                          | Z | 12.96 | 81.2 | 28.8 |      | 134.8 |        |

|           |                                                           |   |      |      |      |      |       |        |
|-----------|-----------------------------------------------------------|---|------|------|------|------|-------|--------|
| 10274-CAA | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)                 | X | 6.14 | 67.4 | 19.0 | 4.87 | 145.5 | ±1.2 % |
|           |                                                           | Y | 6.19 | 67.4 | 19.0 |      | 149.2 |        |
|           |                                                           | Z | 6.10 | 66.9 | 18.8 |      | 142.3 |        |
| 10275-CAA | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)                  | X | 4.41 | 66.4 | 18.3 | 3.96 | 126.4 | ±0.7 % |
|           |                                                           | Y | 4.43 | 66.3 | 18.2 |      | 130.4 |        |
|           |                                                           | Z | 4.36 | 65.9 | 18.0 |      | 123.8 |        |
| 10291-AAA | CDMA2000, RC3, SO55, Full Rate                            | X | 3.57 | 65.9 | 17.9 | 3.46 | 120.0 | ±0.5 % |
|           |                                                           | Y | 3.55 | 65.6 | 17.6 |      | 121.7 |        |
|           |                                                           | Z | 3.50 | 65.1 | 17.5 |      | 117.2 |        |
| 10292-AAA | CDMA2000, RC3, SO32, Full Rate                            | X | 3.55 | 66.1 | 18.0 | 3.39 | 121.3 | ±0.5 % |
|           |                                                           | Y | 3.54 | 66.0 | 17.8 |      | 123.6 |        |
|           |                                                           | Z | 3.45 | 65.2 | 17.4 |      | 118.9 |        |
| 10297-AAA | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)                   | X | 6.53 | 67.8 | 20.0 | 5.81 | 136.2 | ±1.2 % |
|           |                                                           | Y | 6.48 | 67.5 | 19.6 |      | 139.3 |        |
|           |                                                           | Z | 6.52 | 67.6 | 19.8 |      | 134.1 |        |
| 10311-AAA | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                  | X | 7.12 | 68.4 | 20.4 | 6.06 | 141.7 | ±1.4 % |
|           |                                                           | Y | 7.11 | 68.3 | 20.1 |      | 145.3 |        |
|           |                                                           | Z | 7.14 | 68.4 | 20.3 |      | 139.8 |        |
| 10315-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle) | X | 2.79 | 67.6 | 18.0 | 1.71 | 125.5 | ±0.5 % |
|           |                                                           | Y | 2.71 | 66.9 | 17.3 |      | 128.2 |        |
|           |                                                           | Z | 2.64 | 66.2 | 17.0 |      | 123.5 |        |
| 10403-AAA | CDMA2000 (1xEV-DO, Rev. 0)                                | X | 4.78 | 67.5 | 18.3 | 3.76 | 130.6 | ±0.5 % |
|           |                                                           | Y | 4.77 | 67.5 | 18.2 |      | 133.8 |        |
|           |                                                           | Z | 4.65 | 66.5 | 17.8 |      | 130.0 |        |
| 10404-AAA | CDMA2000 (1xEV-DO, Rev. A)                                | X | 4.83 | 68.2 | 18.6 | 3.77 | 129.2 | ±0.7 % |
|           |                                                           | Y | 4.68 | 67.4 | 18.0 |      | 131.9 |        |
|           |                                                           | Z | 4.52 | 66.3 | 17.7 |      | 128.7 |        |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 7 and 8).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750                  | 41.9                               | 0.89                            | 6.52    | 6.52    | 6.52    | 0.47               | 1.46                    | ± 12.0 %    |
| 835                  | 41.5                               | 0.90                            | 6.30    | 6.30    | 6.30    | 0.40               | 1.59                    | ± 12.0 %    |
| 1750                 | 40.1                               | 1.37                            | 5.27    | 5.27    | 5.27    | 0.63               | 1.34                    | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 5.08    | 5.08    | 5.08    | 0.62               | 1.37                    | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 4.43    | 4.43    | 4.43    | 0.79               | 1.28                    | ± 12.0 %    |
| 2600                 | 39.0                               | 1.96                            | 4.29    | 4.29    | 4.29    | 0.77               | 1.38                    | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750                  | 55.5                               | 0.96                            | 6.09    | 6.09    | 6.09    | 0.55               | 1.37                    | ± 12.0 %    |
| 835                  | 55.2                               | 0.97                            | 6.04    | 6.04    | 6.04    | 0.55               | 1.39                    | ± 12.0 %    |
| 1750                 | 53.4                               | 1.49                            | 4.93    | 4.93    | 4.93    | 0.39               | 1.73                    | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 4.67    | 4.67    | 4.67    | 0.38               | 1.75                    | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 4.17    | 4.17    | 4.17    | 0.60               | 1.20                    | ± 12.0 %    |
| 2600                 | 52.5                               | 2.16                            | 4.00    | 4.00    | 4.00    | 0.60               | 1.10                    | ± 12.0 %    |


<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$

f=600 MHz,TEM



f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )




# Dynamic Range f(SAR<sub>head</sub>)

(TEM cell , f = 900 MHz)





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$



**DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287****Other Probe Parameters**

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -15        |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 10 mm      |
| Tip Diameter                                  | 4 mm       |
| Probe Tip to Sensor X Calibration Point       | 2 mm       |
| Probe Tip to Sensor Y Calibration Point       | 2 mm       |
| Probe Tip to Sensor Z Calibration Point       | 2 mm       |
| Recommended Measurement Distance from Surface | 3 mm       |



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **EX3-3920\_Dec13**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3920**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **December 18, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 13-Dec-13 (No. DAE4-660_Dec13)    | Dec-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-13) | In house check: Oct-14 |

|                                                                                                                 | Name          | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|---------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Leif Klysner  | Laboratory Technician |           |
| Approved by:                                                                                                    | Katja Pokovic | Technical Manager     |           |
| Issued: December 19, 2013                                                                                       |               |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |               |                       |           |



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                       |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |
| Connector Angle          | information used in DASY system to align probe sensor X to the robot coordinate system                                                                  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below ConvF).
- NORM( $f$ )<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

# Probe EX3DV4

## SN:3920

Manufactured: December 18, 2012  
Calibrated: December 18, 2013

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3920

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.34     | 0.50     | 0.49     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 102.9    | 99.5     | 98.3     |               |

### Modulation Calibration Parameters

| UID       | Communication System Name                |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C    | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----------|------------------------------------------|---|---------|------------------------------|------|---------|----------|---------------------------|
| 0         | CW                                       | X | 0.0     | 0.0                          | 1.0  | 0.00    | 182.5    | $\pm 2.7 \%$              |
|           |                                          | Y | 0.0     | 0.0                          | 1.0  |         | 164.9    |                           |
|           |                                          | Z | 0.0     | 0.0                          | 1.0  |         | 153.0    |                           |
| 10010-CAA | SAR Validation (Square, 100ms, 10ms)     | X | 0.76    | 53.8                         | 6.5  | 10.00   | 44.1     | $\pm 2.2 \%$              |
|           |                                          | Y | 2.33    | 62.8                         | 11.4 |         | 43.7     |                           |
|           |                                          | Z | 1.15    | 55.6                         | 7.5  |         | 53.0     |                           |
| 10011-CAA | UMTS-FDD (WCDMA)                         | X | 3.36    | 66.5                         | 17.5 | 2.91    | 142.4    | $\pm 0.5 \%$              |
|           |                                          | Y | 3.15    | 65.0                         | 16.7 |         | 131.4    |                           |
|           |                                          | Z | 3.26    | 66.0                         | 17.7 |         | 121.6    |                           |
| 10012-CAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) | X | 2.69    | 66.4                         | 16.9 | 1.87    | 138.1    | $\pm 0.5 \%$              |
|           |                                          | Y | 2.56    | 65.1                         | 16.2 |         | 130.7    |                           |
|           |                                          | Z | 2.72    | 66.6                         | 17.2 |         | 121.4    |                           |
| 10021-DAA | GSM-FDD (TDMA, GMSK)                     | X | 2.06    | 63.4                         | 11.7 | 9.39    | 99.7     | $\pm 1.9 \%$              |
|           |                                          | Y | 2.43    | 66.1                         | 14.1 |         | 94.7     |                           |
|           |                                          | Z | 2.90    | 69.9                         | 16.1 |         | 121.8    |                           |
| 10023-DAA | GPRS-FDD (TDMA, GMSK, TN 0)              | X | 1.94    | 62.4                         | 11.3 | 9.57    | 95.1     | $\pm 1.9 \%$              |
|           |                                          | Y | 2.31    | 64.8                         | 13.1 |         | 90.1     |                           |
|           |                                          | Z | 2.98    | 70.4                         | 16.4 |         | 117.0    |                           |
| 10024-DAA | GPRS-FDD (TDMA, GMSK, TN 0-1)            | X | 2.19    | 67.1                         | 12.2 | 6.56    | 140.1    | $\pm 1.4 \%$              |
|           |                                          | Y | 2.35    | 67.0                         | 12.9 |         | 134.0    |                           |
|           |                                          | Z | 3.45    | 73.5                         | 16.1 |         | 131.4    |                           |
| 10027-DAA | GPRS-FDD (TDMA, GMSK, TN 0-1-2)          | X | 1.18    | 61.7                         | 8.5  | 4.80    | 121.6    | $\pm 1.2 \%$              |
|           |                                          | Y | 1.57    | 63.4                         | 10.0 |         | 116.0    |                           |
|           |                                          | Z | 1.57    | 65.5                         | 11.9 |         | 109.2    |                           |
| 10028-DAA | GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)        | X | 3.80    | 74.5                         | 13.3 | 3.55    | 130.3    | $\pm 0.9 \%$              |
|           |                                          | Y | 1.00    | 60.5                         | 8.0  |         | 123.9    |                           |
|           |                                          | Z | 1.58    | 66.1                         | 11.1 |         | 119.0    |                           |
| 10032-CAA | IEEE 802.15.1 Bluetooth (GFSK, DH5)      | X | 0.18    | 55.2                         | 3.4  | 1.16    | 111.6    | $\pm 0.7 \%$              |
|           |                                          | Y | 0.34    | 57.4                         | 4.4  |         | 143.6    |                           |
|           |                                          | Z | 0.40    | 59.2                         | 5.7  |         | 136.6    |                           |
| 10039-CAA | CDMA2000 (1xRTT, RC1)                    | X | 4.49    | 65.9                         | 18.1 | 4.57    | 131.8    | $\pm 0.9 \%$              |
|           |                                          | Y | 4.57    | 65.1                         | 17.5 |         | 123.0    |                           |
|           |                                          | Z | 4.66    | 65.9                         | 18.3 |         | 118.6    |                           |
| 10062-CAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps) | X | 10.09   | 68.6                         | 21.3 | 8.68    | 126.5    | $\pm 2.5 \%$              |
|           |                                          | Y | 10.31   | 68.5                         | 21.1 |         | 121.9    |                           |
|           |                                          | Z | 10.12   | 68.3                         | 21.3 |         | 115.8    |                           |

|           |                                               |   |       |      |      |      |       |        |
|-----------|-----------------------------------------------|---|-------|------|------|------|-------|--------|
| 10098-CAA | UMTS-FDD (HSUPA, Subtest 2)                   | X | 4.64  | 66.6 | 18.1 | 3.98 | 144.6 | ±0.7 % |
|           |                                               | Y | 4.54  | 65.4 | 17.4 |      | 133.9 |        |
|           |                                               | Z | 4.60  | 66.1 | 18.0 |      | 128.0 |        |
| 10100-CAB | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)      | X | 6.00  | 65.5 | 18.3 | 5.67 | 104.2 | ±1.4 % |
|           |                                               | Y | 6.44  | 66.7 | 18.8 |      | 138.2 |        |
|           |                                               | Z | 6.54  | 67.4 | 19.4 |      | 134.7 |        |
| 10108-CAB | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)      | X | 6.37  | 67.0 | 19.2 | 5.80 | 149.0 | ±1.4 % |
|           |                                               | Y | 6.40  | 66.6 | 18.9 |      | 141.2 |        |
|           |                                               | Z | 6.40  | 66.9 | 19.4 |      | 132.1 |        |
| 10110-CAB | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)       | X | 5.96  | 66.3 | 18.9 | 5.75 | 142.3 | ±1.4 % |
|           |                                               | Y | 6.05  | 66.1 | 18.7 |      | 136.6 |        |
|           |                                               | Z | 6.03  | 66.3 | 19.1 |      | 128.2 |        |
| 10114-CAA | IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK) | X | 10.28 | 68.7 | 20.9 | 8.10 | 137.3 | ±2.5 % |
|           |                                               | Y | 10.32 | 68.5 | 20.7 |      | 131.3 |        |
|           |                                               | Z | 10.24 | 68.5 | 20.9 |      | 124.5 |        |
| 10117-CAA | IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)      | X | 10.29 | 68.8 | 20.9 | 8.07 | 138.5 | ±2.5 % |
|           |                                               | Y | 10.34 | 68.6 | 20.8 |      | 131.9 |        |
|           |                                               | Z | 10.26 | 68.5 | 20.9 |      | 125.5 |        |
| 10151-CAB | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)       | X | 7.20  | 67.5 | 21.6 | 9.28 | 118.6 | ±2.2 % |
|           |                                               | Y | 7.59  | 67.9 | 21.6 |      | 116.7 |        |
|           |                                               | Z | 7.78  | 69.2 | 22.7 |      | 110.7 |        |
| 10154-CAB | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)       | X | 5.98  | 66.4 | 18.9 | 5.75 | 142.7 | ±1.2 % |
|           |                                               | Y | 5.97  | 65.7 | 18.4 |      | 132.7 |        |
|           |                                               | Z | 6.06  | 66.4 | 19.1 |      | 128.6 |        |
| 10160-CAB | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)       | X | 6.41  | 66.8 | 19.1 | 5.82 | 147.7 | ±1.4 % |
|           |                                               | Y | 6.48  | 66.5 | 18.8 |      | 137.3 |        |
|           |                                               | Z | 6.53  | 67.0 | 19.4 |      | 134.9 |        |
| 10169-CAB | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)         | X | 4.59  | 65.5 | 18.6 | 5.73 | 120.3 | ±1.2 % |
|           |                                               | Y | 4.76  | 65.0 | 18.2 |      | 113.9 |        |
|           |                                               | Z | 4.82  | 65.6 | 18.9 |      | 112.0 |        |
| 10172-CAB | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)         | X | 5.77  | 69.3 | 22.7 | 9.21 | 128.1 | ±1.9 % |
|           |                                               | Y | 6.15  | 69.3 | 22.6 |      | 123.8 |        |
|           |                                               | Z | 6.22  | 70.3 | 23.6 |      | 120.8 |        |
| 10175-CAB | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)         | X | 4.62  | 65.6 | 18.7 | 5.72 | 120.2 | ±0.9 % |
|           |                                               | Y | 4.75  | 65.0 | 18.2 |      | 113.5 |        |
|           |                                               | Z | 4.80  | 65.6 | 18.8 |      | 110.7 |        |
| 10181-CAB | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)         | X | 4.57  | 65.4 | 18.6 | 5.72 | 118.9 | ±0.9 % |
|           |                                               | Y | 4.72  | 64.8 | 18.1 |      | 113.1 |        |
|           |                                               | Z | 4.81  | 65.6 | 18.8 |      | 110.4 |        |
| 10193-CAA | IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)  | X | 9.77  | 68.3 | 20.8 | 8.09 | 128.1 | ±2.5 % |
|           |                                               | Y | 9.84  | 67.9 | 20.5 |      | 117.1 |        |
|           |                                               | Z | 9.80  | 68.1 | 20.8 |      | 116.6 |        |
| 10196-CAA | IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)       | X | 9.78  | 68.4 | 20.8 | 8.10 | 128.4 | ±2.5 % |
|           |                                               | Y | 9.86  | 68.0 | 20.5 |      | 120.3 |        |
|           |                                               | Z | 9.82  | 68.1 | 20.9 |      | 119.1 |        |



|           |                                                           |   |       |      |      |      |       |        |
|-----------|-----------------------------------------------------------|---|-------|------|------|------|-------|--------|
| 10219-CAA | IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)                   | X | 9.70  | 68.4 | 20.8 | 8.03 | 128.0 | ±2.5 % |
|           |                                                           | Y | 9.79  | 68.0 | 20.5 |      | 119.6 |        |
|           |                                                           | Z | 9.72  | 68.1 | 20.8 |      | 118.7 |        |
| 10222-CAA | IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)                    | X | 10.27 | 68.8 | 20.9 | 8.06 | 137.0 | ±2.5 % |
|           |                                                           | Y | 10.18 | 68.3 | 20.6 |      | 125.2 |        |
|           |                                                           | Z | 10.20 | 68.5 | 20.9 |      | 124.8 |        |
| 10225-CAA | UMTS-FDD (HSPA+)                                          | X | 6.64  | 66.1 | 18.7 | 5.97 | 108.8 | ±1.4 % |
|           |                                                           | Y | 7.23  | 67.1 | 19.1 |      | 148.9 |        |
|           |                                                           | Z | 7.31  | 67.7 | 19.7 |      | 146.5 |        |
| 10237-CAB | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)                     | X | 5.82  | 69.6 | 23.0 | 9.21 | 130.2 | ±1.9 % |
|           |                                                           | Y | 6.14  | 69.2 | 22.6 |      | 123.9 |        |
|           |                                                           | Z | 6.25  | 70.4 | 23.7 |      | 122.2 |        |
| 10252-CAB | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)                   | X | 6.85  | 67.5 | 21.7 | 9.24 | 112.9 | ±2.2 % |
|           |                                                           | Y | 7.54  | 69.0 | 22.4 |      | 149.2 |        |
|           |                                                           | Z | 7.80  | 70.6 | 23.7 |      | 147.3 |        |
| 10267-CAB | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)                  | X | 7.23  | 67.6 | 21.6 | 9.30 | 118.3 | ±2.2 % |
|           |                                                           | Y | 7.55  | 67.7 | 21.5 |      | 111.5 |        |
|           |                                                           | Z | 7.79  | 69.2 | 22.7 |      | 109.6 |        |
| 10274-CAA | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)                 | X | 5.64  | 65.9 | 18.1 | 4.87 | 105.5 | ±1.2 % |
|           |                                                           | Y | 6.04  | 66.4 | 18.2 |      | 142.6 |        |
|           |                                                           | Z | 6.09  | 66.9 | 18.7 |      | 138.4 |        |
| 10275-CAA | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)                  | X | 4.42  | 66.3 | 18.1 | 3.96 | 135.8 | ±0.7 % |
|           |                                                           | Y | 4.26  | 65.0 | 17.3 |      | 119.3 |        |
|           |                                                           | Z | 4.40  | 65.9 | 18.0 |      | 120.4 |        |
| 10291-AAA | CDMA2000, RC3, SO55, Full Rate                            | X | 3.62  | 66.7 | 18.1 | 3.46 | 123.6 | ±0.7 % |
|           |                                                           | Y | 3.38  | 64.3 | 16.7 |      | 112.5 |        |
|           |                                                           | Z | 3.59  | 66.0 | 17.9 |      | 114.3 |        |
| 10292-AAA | CDMA2000, RC3, SO32, Full Rate                            | X | 3.46  | 66.0 | 17.7 | 3.39 | 127.3 | ±0.5 % |
|           |                                                           | Y | 3.35  | 64.5 | 16.8 |      | 113.7 |        |
|           |                                                           | Z | 3.50  | 65.7 | 17.7 |      | 115.4 |        |
| 10297-AAA | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)                   | X | 6.35  | 66.9 | 19.2 | 5.81 | 145.7 | ±1.2 % |
|           |                                                           | Y | 6.26  | 66.1 | 18.7 |      | 129.2 |        |
|           |                                                           | Z | 6.42  | 67.0 | 19.4 |      | 131.3 |        |
| 10311-AAA | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                  | X | 6.45  | 65.9 | 18.7 | 6.06 | 103.7 | ±1.7 % |
|           |                                                           | Y | 6.90  | 66.9 | 19.1 |      | 137.2 |        |
|           |                                                           | Z | 7.04  | 67.7 | 19.8 |      | 137.5 |        |
| 10315-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle) | X | 2.85  | 67.8 | 17.7 | 1.71 | 135.6 | ±0.5 % |
|           |                                                           | Y | 2.45  | 64.7 | 16.0 |      | 121.4 |        |
|           |                                                           | Z | 2.75  | 67.3 | 17.6 |      | 122.1 |        |
| 10317-AAA | IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)   | X | 9.93  | 68.5 | 21.0 | 8.36 | 128.1 | ±2.7 % |
|           |                                                           | Y | 10.02 | 68.1 | 20.7 |      | 117.9 |        |
|           |                                                           | Z | 10.01 | 68.3 | 21.1 |      | 119.4 |        |
| 10400-AAA | IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)       | X | 10.09 | 68.8 | 21.2 | 8.37 | 134.9 | ±2.5 % |
|           |                                                           | Y | 10.16 | 68.3 | 20.8 |      | 119.8 |        |
|           |                                                           | Z | 10.14 | 68.5 | 21.2 |      | 121.0 |        |

|           |                                                     |   |       |      |      |      |       |        |
|-----------|-----------------------------------------------------|---|-------|------|------|------|-------|--------|
| 10402-AAA | IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle) | X | 11.18 | 69.8 | 21.5 | 8.53 | 147.1 | ±2.7 % |
|           |                                                     | Y | 10.79 | 68.6 | 20.8 |      | 126.5 |        |
|           |                                                     | Z | 11.17 | 69.6 | 21.6 |      | 131.4 |        |
| 10403-AAA | CDMA2000 (1xEV-DO, Rev. 0)                          | X | 4.83  | 69.6 | 18.9 | 3.76 | 139.6 | ±0.5 % |
|           |                                                     | Y | 4.70  | 67.1 | 17.6 |      | 128.1 |        |
|           |                                                     | Z | 4.90  | 68.4 | 18.6 |      | 127.8 |        |
| 10404-AAA | CDMA2000 (1xEV-DO, Rev. A)                          | X | 4.73  | 69.5 | 18.9 | 3.77 | 134.8 | ±0.5 % |
|           |                                                     | Y | 4.62  | 67.1 | 17.7 |      | 124.9 |        |
|           |                                                     | Z | 4.67  | 67.7 | 18.1 |      | 125.9 |        |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 8 and 9).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3920

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750                  | 41.9                               | 0.89                            | 10.05   | 10.05   | 10.05   | 0.27               | 1.13                    | ± 12.0 %    |
| 835                  | 41.5                               | 0.90                            | 9.69    | 9.69    | 9.69    | 0.50               | 0.76                    | ± 12.0 %    |
| 1750                 | 40.1                               | 1.37                            | 7.91    | 7.91    | 7.91    | 0.72               | 0.62                    | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 7.70    | 7.70    | 7.70    | 0.77               | 0.61                    | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 6.98    | 6.98    | 6.98    | 0.37               | 0.86                    | ± 12.0 %    |
| 2600                 | 39.0                               | 1.96                            | 6.74    | 6.74    | 6.74    | 0.34               | 0.97                    | ± 12.0 %    |
| 5200                 | 36.0                               | 4.66                            | 4.87    | 4.87    | 4.87    | 0.40               | 1.80                    | ± 13.1 %    |
| 5300                 | 35.9                               | 4.76                            | 4.66    | 4.66    | 4.66    | 0.40               | 1.80                    | ± 13.1 %    |
| 5500                 | 35.6                               | 4.96                            | 4.54    | 4.54    | 4.54    | 0.40               | 1.80                    | ± 13.1 %    |
| 5600                 | 35.5                               | 5.07                            | 4.37    | 4.37    | 4.37    | 0.40               | 1.80                    | ± 13.1 %    |
| 5800                 | 35.3                               | 5.27                            | 4.11    | 4.11    | 4.11    | 0.50               | 1.80                    | ± 13.1 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3920

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750                  | 55.5                               | 0.96                            | 9.54    | 9.54    | 9.54    | 0.32               | 1.07                    | ± 12.0 %    |
| 835                  | 55.2                               | 0.97                            | 9.47    | 9.47    | 9.47    | 0.45               | 0.85                    | ± 12.0 %    |
| 1750                 | 53.4                               | 1.49                            | 7.77    | 7.77    | 7.77    | 0.59               | 0.74                    | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 7.50    | 7.50    | 7.50    | 0.37               | 0.91                    | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 7.18    | 7.18    | 7.18    | 0.80               | 0.56                    | ± 12.0 %    |
| 2600                 | 52.5                               | 2.16                            | 6.91    | 6.91    | 6.91    | 0.80               | 0.57                    | ± 12.0 %    |
| 5200                 | 49.0                               | 5.30                            | 4.23    | 4.23    | 4.23    | 0.50               | 1.90                    | ± 13.1 %    |
| 5300                 | 48.9                               | 5.42                            | 4.11    | 4.11    | 4.11    | 0.50               | 1.90                    | ± 13.1 %    |
| 5500                 | 48.6                               | 5.65                            | 3.80    | 3.80    | 3.80    | 0.50               | 1.90                    | ± 13.1 %    |
| 5600                 | 48.5                               | 5.77                            | 3.62    | 3.62    | 3.62    | 0.50               | 1.90                    | ± 13.1 %    |
| 5800                 | 48.2                               | 6.00                            | 4.00    | 4.00    | 4.00    | 0.50               | 1.90                    | ± 13.1 %    |


<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$

$f=600$  MHz, TEM





$f=1800$  MHz, R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

# Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$ )





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$





## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3920

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -22.4      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 2 mm       |



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **ES3-3319\_Apr13**

## CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3319**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-23.v4, QA CAL-25.v4**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **April 29, 2013**

VCC  
6/14/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 31-Jan-13 (No. DAE4-660_Jan13)    | Jan-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                                                                                                                 |                     |                                   |               |
|-----------------------------------------------------------------------------------------------------------------|---------------------|-----------------------------------|---------------|
| Calibrated by:                                                                                                  | Name<br>Dimce Iliev | Function<br>Laboratory Technician | Signature<br> |
| Approved by:                                                                                                    | Katja Pokovic       | Technical Manager                 |               |
| Issued: April 29, 2013                                                                                          |                     |                                   |               |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |                     |                                   |               |



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                       |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe ES3DV3

## SN:3319

Manufactured: January 10, 2012  
Calibrated: April 29, 2013

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3319

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|-----------------------------------------------------------|----------|----------|----------|-----------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 1.12     | 1.20     | 1.22     | ± 10.1 %  |
| DCP (mV) <sup>B</sup>                                     | 100.7    | 102.6    | 102.4    |           |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB/ $\mu\text{V}$ | C   | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                    | 1.0 | 0.00    | 152.0    | ±3.8 %                    |
|     |                           | Y | 0.0     | 0.0                    | 1.0 |         | 159.0    |                           |
|     |                           | Z | 0.0     | 0.0                    | 1.0 |         | 149.8    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3319

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 41.9                               | 0.89                            | 6.49    | 6.49    | 6.49    | 0.28  | 1.97       | ± 12.0 %    |
| 850                  | 41.5                               | 0.92                            | 6.23    | 6.23    | 6.23    | 0.42  | 1.57       | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 5.22    | 5.22    | 5.22    | 0.80  | 1.24       | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 4.57    | 4.57    | 4.57    | 0.80  | 1.32       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3319


### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 55.5                               | 0.96                            | 6.30    | 6.30    | 6.30    | 0.45  | 1.53       | ± 12.0 %    |
| 850                  | 55.2                               | 0.99                            | 6.15    | 6.15    | 6.15    | 0.42  | 1.65       | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 4.85    | 4.85    | 4.85    | 0.63  | 1.49       | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 4.32    | 4.32    | 4.32    | 0.69  | 1.20       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)




Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )





## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



f=600 MHz,TEM



f=1800 MHz,R22


**Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )**

# Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$ )





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$



## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3319

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -104.1     |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 10 mm      |
| Tip Diameter                                  | 4 mm       |
| Probe Tip to Sensor X Calibration Point       | 2 mm       |
| Probe Tip to Sensor Y Calibration Point       | 2 mm       |
| Probe Tip to Sensor Z Calibration Point       | 2 mm       |
| Recommended Measurement Distance from Surface | 3 mm       |

## **Additional Conversion Factors**

**for Dosimetric E-Field Probe**

Type:

**ES3DV3**

Serial Number:

**3319**

Place of Assessment:

**Zurich**

Date of Assessment:


**June 19, 2013**

Probe Calibration Date:

**April 29, 2013**

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. The evaluation is coupled with measured conversion factors (probe calibration date indicated above). The uncertainty of the numerical assessment is based on the extrapolation from measured value at 835 MHz or at 1900 MHz.

Assessed by:



✓  
KOK  
6/25/13

## Dosimetric E-Field Probe ES3DV3 SN:3319

Conversion factor ( $\pm$  standard deviation)

1750  $\pm$  50 MHz      *ConvF*      5.59  $\pm$  7 %

$\epsilon_r = 40.1 \pm 5\%$   
 $\sigma = 1.37 \pm 5\%$  mho/m  
(head tissue)

1750  $\pm$  50 MHz      *ConvF*      5.22  $\pm$  7 %

$\epsilon_r = 53.4 \pm 5\%$   
 $\sigma = 1.49 \pm 5\%$  mho/m  
(body tissue)

### Important Note:

For numerically assessed probe conversion factors, parameters Alpha and Delta in the DASY software must have the following entries: Alpha = 0 and Delta = 1.

Please see also DASY Manual.



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3022\_Aug13**

## CALIBRATION CERTIFICATE

Object **ES3DV2 - SN:3022**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **August 22, 2013**

*UTC*  
*9/13/13*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 31-Jan-13 (No. DAE4-660_Jan13)    | Jan-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                                                                                                                 | Name           | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|----------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Jeton Kastrati | Laboratory Technician |           |
| Approved by:                                                                                                    | Katja Pokovic  | Technical Manager     |           |
| Issued: August 23, 2013                                                                                         |                |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |                |                       |           |



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\varphi$   | $\varphi$ rotation around probe axis                                                                                                                    |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.



# Probe ES3DV2

## SN:3022

Manufactured: April 15, 2003  
Calibrated: August 22, 2013

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

## DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|-----------------------------------------------------------|----------|----------|----------|-----------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 1.00     | 1.04     | 0.99     | ± 10.1 %  |
| DCP (mV) <sup>B</sup>                                     | 100.7    | 97.4     | 99.7     |           |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 178.6    | ±3.0 %                    |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 141.9    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 134.7    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 41.9                               | 0.89                            | 6.21    | 6.21    | 6.21    | 0.19  | 2.37       | ± 12.0 %    |
| 835                  | 41.5                               | 0.90                            | 6.09    | 6.09    | 6.09    | 0.30  | 1.70       | ± 12.0 %    |
| 1750                 | 40.1                               | 1.37                            | 5.19    | 5.19    | 5.19    | 0.65  | 1.23       | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 5.03    | 5.03    | 5.03    | 0.51  | 1.43       | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 4.36    | 4.36    | 4.36    | 0.51  | 1.51       | ± 12.0 %    |
| 2600                 | 39.0                               | 1.96                            | 4.16    | 4.16    | 4.16    | 0.74  | 1.29       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

### Calibration Parameter Determined in Body Tissue Simulating Media


| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha | Depth (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|-------|------------|-------------|
| 750                  | 55.5                               | 0.96                            | 5.92    | 5.92    | 5.92    | 0.24  | 1.99       | ± 12.0 %    |
| 835                  | 55.2                               | 0.97                            | 5.91    | 5.91    | 5.91    | 0.29  | 1.85       | ± 12.0 %    |
| 1750                 | 53.4                               | 1.49                            | 4.75    | 4.75    | 4.75    | 0.52  | 1.52       | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 4.49    | 4.49    | 4.49    | 0.49  | 1.56       | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 4.01    | 4.01    | 4.01    | 0.70  | 1.02       | ± 12.0 %    |
| 2600                 | 52.5                               | 2.16                            | 3.85    | 3.85    | 3.85    | 0.58  | 0.90       | ± 12.0 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

## Receiving Pattern ( $\phi$ ), $\vartheta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

# Dynamic Range f(SAR<sub>head</sub>) (TEM cell , f = 900 MHz)





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi$ ,  $\theta$ ),  $f = 900 \text{ MHz}$





## DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -83.1      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 10 mm      |
| Tip Diameter                                  | 4 mm       |
| Probe Tip to Sensor X Calibration Point       | 2 mm       |
| Probe Tip to Sensor Y Calibration Point       | 2 mm       |
| Probe Tip to Sensor Z Calibration Point       | 2 mm       |
| Recommended Measurement Distance from Surface | 3 mm       |



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **EX3-3914\_Oct13**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3914**

Calibration procedure(s) **QA CAL-01 v3, QA CAL-14 v4, QA CAL-23 v5, QA CAL-25 v6**  
 Calibration procedure for dosimetric E-field probes

Calibration date: **October 23, 2013**

*VCC*  
*11/20/2013*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 4-Sep-13 (No. DAE4-660_Sep13)     | Sep-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-13) | In house check: Oct-14 |

|                                                                                                                 | Name          | Function              | Signature            |
|-----------------------------------------------------------------------------------------------------------------|---------------|-----------------------|----------------------|
| Calibrated by:                                                                                                  | Leif Klysner  | Laboratory Technician | <i>Leif Klysner</i>  |
| Approved by:                                                                                                    | Katja Pokovic | Technical Manager     | <i>Katja Pokovic</i> |
| Issued: October 25, 2013                                                                                        |               |                       |                      |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |               |                       |                      |

*PCT # 81072*



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                       |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |
| Connector Angle          | information used in DASY system to align probe sensor X to the robot coordinate system                                                                  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below *ConvF*).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

# Probe EX3DV4

## SN:3914

Manufactured: December 18, 2012  
Calibrated: October 23, 2013

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

# DASY/EASY - Parameters of Probe: EX3DV4 - SN:3914

## Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.47     | 0.49     | 0.51     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 99.2     | 98.9     | 98.2     |               |

## Modulation Calibration Parameters

| UID       | Communication System Name                |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C    | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----------|------------------------------------------|---|---------|------------------------------|------|---------|----------|---------------------------|
| 0         | CW                                       | X | 0.0     | 0.0                          | 1.0  | 0.00    | 158.3    | $\pm 3.0 \%$              |
|           |                                          | Y | 0.0     | 0.0                          | 1.0  |         | 154.6    |                           |
|           |                                          | Z | 0.0     | 0.0                          | 1.0  |         | 170.8    |                           |
| 10010-CAA | SAR Validation (Square, 100ms, 10ms)     | X | 0.71    | 53.3                         | 6.1  | 10.00   | 48.4     | $\pm 2.5 \%$              |
|           |                                          | Y | 2.43    | 67.0                         | 13.8 |         | 39.9     |                           |
|           |                                          | Z | 4.18    | 68.7                         | 13.8 |         | 45.7     |                           |
| 10011-CAA | UMTS-FDD (WCDMA)                         | X | 3.05    | 64.4                         | 16.5 | 2.91    | 122.4    | $\pm 0.5 \%$              |
|           |                                          | Y | 3.31    | 66.5                         | 18.2 |         | 123.5    |                           |
|           |                                          | Z | 3.34    | 66.3                         | 17.8 |         | 136.6    |                           |
| 10012-CAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) | X | 2.49    | 64.8                         | 16.1 | 1.87    | 120.6    | $\pm 0.5 \%$              |
|           |                                          | Y | 2.94    | 68.6                         | 18.7 |         | 123.6    |                           |
|           |                                          | Z | 2.63    | 65.9                         | 17.0 |         | 135.4    |                           |
| 10021-DAA | GSM-FDD (TDMA, GMSK)                     | X | 1.52    | 61.5                         | 10.9 | 9.39    | 83.6     | $\pm 1.2 \%$              |
|           |                                          | Y | 2.22    | 67.4                         | 15.0 |         | 116.0    |                           |
|           |                                          | Z | 2.47    | 66.8                         | 14.7 |         | 95.9     |                           |
| 10023-DAA | GPRS-FDD (TDMA, GMSK, TN 0)              | X | 1.73    | 63.3                         | 11.9 | 9.57    | 81.5     | $\pm 1.7 \%$              |
|           |                                          | Y | 2.11    | 66.2                         | 14.2 |         | 111.8    |                           |
|           |                                          | Z | 2.76    | 69.0                         | 16.0 |         | 93.6     |                           |
| 10024-DAA | GPRS-FDD (TDMA, GMSK, TN 0-1)            | X | 1.34    | 62.1                         | 9.4  | 6.56    | 121.0    | $\pm 1.2 \%$              |
|           |                                          | Y | 4.24    | 78.6                         | 17.9 |         | 130.0    |                           |
|           |                                          | Z | 2.91    | 70.7                         | 14.9 |         | 141.4    |                           |
| 10027-DAA | GPRS-FDD (TDMA, GMSK, TN 0-1-2)          | X | 1.25    | 63.5                         | 9.7  | 4.80    | 143.5    | $\pm 1.4 \%$              |
|           |                                          | Y | 1.59    | 66.9                         | 12.2 |         | 149.7    |                           |
|           |                                          | Z | 2.98    | 71.5                         | 14.0 |         | 123.3    |                           |
| 10028-DAA | GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)        | X | 0.51    | 58.3                         | 7.4  | 3.55    | 113.4    | $\pm 1.2 \%$              |
|           |                                          | Y | 25.43   | 100.0                        | 22.6 |         | 121.3    |                           |
|           |                                          | Z | 38.67   | 97.5                         | 20.6 |         | 133.3    |                           |
| 10032-CAA | IEEE 802.15.1 Bluetooth (GFSK, DH5)      | X | 0.28    | 58.6                         | 5.3  | 1.16    | 134.7    | $\pm 0.9 \%$              |
|           |                                          | Y | 65.75   | 99.6                         | 18.6 |         | 141.3    |                           |
|           |                                          | Z | 0.20    | 55.6                         | 4.1  |         | 112.1    |                           |
| 10039-CAA | CDMA2000 (1xRTT, RC1)                    | X | 4.33    | 64.6                         | 17.4 | 4.57    | 113.8    | $\pm 0.7 \%$              |
|           |                                          | Y | 4.55    | 66.0                         | 18.6 |         | 120.8    |                           |
|           |                                          | Z | 4.85    | 66.2                         | 18.4 |         | 135.9    |                           |
| 10062-CAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps) | X | 9.83    | 67.6                         | 20.7 | 8.68    | 109.0    | $\pm 2.5 \%$              |
|           |                                          | Y | 10.06   | 68.4                         | 21.5 |         | 118.2    |                           |
|           |                                          | Z | 10.66   | 69.2                         | 21.7 |         | 134.0    |                           |

|           |                                               |   |       |      |      |      |       |        |
|-----------|-----------------------------------------------|---|-------|------|------|------|-------|--------|
| 10081-CAA | CDMA2000 (1xRTT, RC3)                         | X | 3.59  | 63.9 | 16.9 | 3.97 | 113.6 | ±0.7 % |
|           |                                               | Y | 3.84  | 65.6 | 18.2 |      | 119.6 |        |
|           |                                               | Z | 3.95  | 65.4 | 17.8 |      | 134.5 |        |
| 10098-CAA | UMTS-FDD (HSUPA, Subtest 2)                   | X | 4.41  | 65.2 | 17.3 | 3.98 | 126.0 | ±0.7 % |
|           |                                               | Y | 4.73  | 66.9 | 18.6 |      | 132.5 |        |
|           |                                               | Z | 4.51  | 65.5 | 17.7 |      | 105.6 |        |
| 10100-CAB | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)      | X | 6.26  | 66.2 | 18.6 | 5.67 | 130.5 | ±1.2 % |
|           |                                               | Y | 6.61  | 67.7 | 19.8 |      | 139.3 |        |
|           |                                               | Z | 6.21  | 66.0 | 18.7 |      | 107.7 |        |
| 10108-CAB | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)      | X | 6.13  | 65.8 | 18.6 | 5.80 | 126.3 | ±1.2 % |
|           |                                               | Y | 6.40  | 67.1 | 19.6 |      | 135.6 |        |
|           |                                               | Z | 6.10  | 65.5 | 18.5 |      | 107.4 |        |
| 10110-CAB | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)       | X | 5.78  | 65.3 | 18.3 | 5.75 | 123.1 | ±1.2 % |
|           |                                               | Y | 5.97  | 66.3 | 19.2 |      | 131.5 |        |
|           |                                               | Z | 5.86  | 65.3 | 18.4 |      | 104.9 |        |
| 10114-CAA | IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK) | X | 9.92  | 67.7 | 20.3 | 8.10 | 115.7 | ±2.5 % |
|           |                                               | Y | 10.25 | 68.7 | 21.2 |      | 126.8 |        |
|           |                                               | Z | 10.71 | 69.4 | 21.3 |      | 146.0 |        |
| 10117-CAA | IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)      | X | 9.95  | 67.8 | 20.3 | 8.07 | 116.6 | ±2.5 % |
|           |                                               | Y | 10.26 | 68.7 | 21.1 |      | 128.3 |        |
|           |                                               | Z | 10.70 | 69.4 | 21.3 |      | 146.9 |        |
| 10151-CAB | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)       | X | 7.19  | 67.3 | 21.5 | 9.28 | 145.0 | ±2.2 % |
|           |                                               | Y | 7.40  | 68.3 | 22.4 |      | 110.8 |        |
|           |                                               | Z | 7.79  | 68.4 | 22.0 |      | 128.0 |        |
| 10154-CAB | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)       | X | 5.79  | 65.3 | 18.3 | 5.75 | 124.2 | ±1.2 % |
|           |                                               | Y | 6.03  | 66.5 | 19.4 |      | 131.9 |        |
|           |                                               | Z | 6.29  | 66.9 | 19.3 |      | 149.7 |        |
| 10160-CAB | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)       | X | 6.23  | 65.9 | 18.6 | 5.82 | 128.3 | ±1.2 % |
|           |                                               | Y | 6.51  | 67.2 | 19.7 |      | 136.9 |        |
|           |                                               | Z | 6.24  | 65.7 | 18.6 |      | 107.3 |        |
| 10169-CAB | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)         | X | 4.83  | 66.0 | 18.9 | 5.73 | 147.5 | ±1.2 % |
|           |                                               | Y | 4.72  | 65.8 | 19.2 |      | 113.8 |        |
|           |                                               | Z | 5.03  | 66.1 | 19.1 |      | 129.7 |        |
| 10172-CAB | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)         | X | 5.83  | 69.2 | 22.8 | 9.21 | 149.9 | ±1.9 % |
|           |                                               | Y | 5.81  | 69.4 | 23.4 |      | 120.3 |        |
|           |                                               | Z | 6.38  | 70.0 | 23.2 |      | 137.2 |        |
| 10175-CAB | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)         | X | 4.86  | 66.1 | 18.9 | 5.72 | 149.8 | ±1.2 % |
|           |                                               | Y | 4.72  | 65.8 | 19.2 |      | 113.3 |        |
|           |                                               | Z | 5.09  | 66.4 | 19.1 |      | 126.0 |        |
| 10181-CAB | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)         | X | 4.83  | 66.0 | 18.9 | 5.72 | 146.3 | ±1.2 % |
|           |                                               | Y | 4.69  | 65.6 | 19.1 |      | 112.2 |        |
|           |                                               | Z | 5.02  | 66.1 | 19.0 |      | 125.1 |        |
| 10193-CAA | IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)  | X | 9.51  | 67.4 | 20.2 | 8.09 | 108.6 | ±2.5 % |
|           |                                               | Y | 9.72  | 68.1 | 20.9 |      | 118.2 |        |
|           |                                               | Z | 10.30 | 68.9 | 21.1 |      | 135.0 |        |

|           |                                                           |   |       |      |      |      |       |        |
|-----------|-----------------------------------------------------------|---|-------|------|------|------|-------|--------|
| 10196-CAA | IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)                   | X | 9.52  | 67.4 | 20.2 | 8.10 | 111.6 | ±2.5 % |
|           |                                                           | Y | 9.79  | 68.3 | 21.1 |      | 121.3 |        |
|           |                                                           | Z | 10.30 | 68.9 | 21.2 |      | 139.2 |        |
| 10219-CAA | IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)                   | X | 9.47  | 67.4 | 20.2 | 8.03 | 111.8 | ±2.2 % |
|           |                                                           | Y | 9.67  | 68.3 | 21.0 |      | 120.0 |        |
|           |                                                           | Z | 10.20 | 68.9 | 21.1 |      | 138.0 |        |
| 10222-CAA | IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)                    | X | 9.96  | 67.9 | 20.4 | 8.06 | 118.4 | ±2.5 % |
|           |                                                           | Y | 10.25 | 68.8 | 21.2 |      | 128.2 |        |
|           |                                                           | Z | 10.65 | 69.3 | 21.3 |      | 144.5 |        |
| 10225-CAA | UMTS-FDD (HSPA+)                                          | X | 6.96  | 66.7 | 18.9 | 5.97 | 140.0 | ±1.4 % |
|           |                                                           | Y | 7.23  | 67.9 | 20.0 |      | 148.9 |        |
|           |                                                           | Z | 7.03  | 66.4 | 18.9 |      | 115.6 |        |
| 10237-CAB | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)                     | X | 5.51  | 67.5 | 21.8 | 9.21 | 114.2 | ±1.9 % |
|           |                                                           | Y | 5.82  | 69.4 | 23.4 |      | 123.0 |        |
|           |                                                           | Z | 6.49  | 70.6 | 23.6 |      | 140.2 |        |
| 10252-CAB | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)                   | X | 6.83  | 67.1 | 21.4 | 9.24 | 136.6 | ±1.9 % |
|           |                                                           | Y | 7.30  | 69.4 | 23.2 |      | 147.3 |        |
|           |                                                           | Z | 7.36  | 68.1 | 22.0 |      | 117.5 |        |
| 10267-CAB | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)                  | X | 7.26  | 67.5 | 21.6 | 9.30 | 142.7 | ±1.9 % |
|           |                                                           | Y | 7.44  | 68.4 | 22.4 |      | 110.5 |        |
|           |                                                           | Z | 7.84  | 68.7 | 22.2 |      | 122.6 |        |
| 10274-CAA | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)                 | X | 5.86  | 66.2 | 18.2 | 4.87 | 135.4 | ±0.9 % |
|           |                                                           | Y | 6.12  | 67.5 | 19.2 |      | 142.3 |        |
|           |                                                           | Z | 5.91  | 65.9 | 18.2 |      | 107.6 |        |
| 10275-CAA | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)                  | X | 4.17  | 64.8 | 17.3 | 3.96 | 115.6 | ±0.7 % |
|           |                                                           | Y | 4.42  | 66.4 | 18.5 |      | 124.6 |        |
|           |                                                           | Z | 4.47  | 66.0 | 18.0 |      | 132.6 |        |
| 10291-AAA | CDMA2000, RC3, SO55, Full Rate                            | X | 3.36  | 64.7 | 17.1 | 3.46 | 109.4 | ±0.5 % |
|           |                                                           | Y | 3.55  | 66.2 | 18.3 |      | 118.2 |        |
|           |                                                           | Z | 3.60  | 65.6 | 17.7 |      | 120.9 |        |
| 10292-AAA | CDMA2000, RC3, SO32, Full Rate                            | X | 3.34  | 64.9 | 17.2 | 3.39 | 110.1 | ±0.5 % |
|           |                                                           | Y | 3.57  | 66.7 | 18.5 |      | 121.0 |        |
|           |                                                           | Z | 3.54  | 65.6 | 17.7 |      | 123.9 |        |
| 10297-AAA | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)                   | X | 6.14  | 65.8 | 18.6 | 5.81 | 125.1 | ±1.2 % |
|           |                                                           | Y | 6.44  | 67.2 | 19.7 |      | 135.7 |        |
|           |                                                           | Z | 6.52  | 67.0 | 19.3 |      | 142.2 |        |
| 10311-AAA | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                  | X | 6.76  | 66.6 | 19.1 | 6.06 | 131.8 | ±1.4 % |
|           |                                                           | Y | 7.03  | 67.8 | 20.0 |      | 142.5 |        |
|           |                                                           | Z | 7.15  | 67.7 | 19.7 |      | 148.6 |        |
| 10315-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle) | X | 2.42  | 64.6 | 16.1 | 1.71 | 116.8 | ±0.5 % |
|           |                                                           | Y | 3.00  | 69.3 | 19.0 |      | 126.9 |        |
|           |                                                           | Z | 2.61  | 66.3 | 17.2 |      | 128.2 |        |
| 10317-AAA | IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)   | X | 9.71  | 67.6 | 20.5 | 8.36 | 111.7 | ±2.5 % |
|           |                                                           | Y | 9.99  | 68.6 | 21.4 |      | 122.2 |        |
|           |                                                           | Z | 10.38 | 68.9 | 21.3 |      | 129.5 |        |

|           |                                                     |   |       |      |      |      |       |        |
|-----------|-----------------------------------------------------|---|-------|------|------|------|-------|--------|
| 10400-AAA | IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle) | X | 9.83  | 67.8 | 20.6 | 8.37 | 112.9 | ±2.5 % |
|           |                                                     | Y | 10.09 | 68.7 | 21.4 |      | 123.9 |        |
|           |                                                     | Z | 10.48 | 68.9 | 21.3 |      | 130.5 |        |
| 10402-AAA | IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle) | X | 10.61 | 68.3 | 20.7 | 8.53 | 121.1 | ±2.5 % |
|           |                                                     | Y | 11.25 | 70.0 | 21.9 |      | 135.4 |        |
|           |                                                     | Z | 11.15 | 69.4 | 21.4 |      | 137.4 |        |
| 10403-AAA | CDMA2000 (1xEV-DO, Rev. 0)                          | X | 4.51  | 67.4 | 17.8 | 3.76 | 119.2 | ±0.5 % |
|           |                                                     | Y | 4.91  | 69.5 | 19.3 |      | 128.3 |        |
|           |                                                     | Z | 4.84  | 67.5 | 18.1 |      | 135.4 |        |
| 10404-AAA | CDMA2000 (1xEV-DO, Rev. A)                          | X | 4.51  | 67.7 | 18.0 | 3.77 | 117.4 | ±0.5 % |
|           |                                                     | Y | 4.92  | 69.8 | 19.5 |      | 125.4 |        |
|           |                                                     | Z | 4.71  | 67.3 | 18.0 |      | 131.9 |        |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 8 and 9).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3914

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750                  | 41.9                               | 0.89                            | 9.70    | 9.70    | 9.70    | 0.34               | 1.01                    | ± 12.0 %    |
| 835                  | 41.5                               | 0.90                            | 9.34    | 9.34    | 9.34    | 0.67               | 0.67                    | ± 12.0 %    |
| 1750                 | 40.1                               | 1.37                            | 7.99    | 7.99    | 7.99    | 0.79               | 0.56                    | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 7.69    | 7.69    | 7.69    | 0.80               | 0.58                    | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 6.95    | 6.95    | 6.95    | 0.41               | 0.77                    | ± 12.0 %    |
| 2600                 | 39.0                               | 1.96                            | 6.79    | 6.79    | 6.79    | 0.40               | 0.82                    | ± 12.0 %    |
| 5200                 | 36.0                               | 4.66                            | 4.99    | 4.99    | 4.99    | 0.30               | 1.80                    | ± 13.1 %    |
| 5300                 | 35.9                               | 4.76                            | 4.82    | 4.82    | 4.82    | 0.30               | 1.80                    | ± 13.1 %    |
| 5500                 | 35.6                               | 4.96                            | 4.55    | 4.55    | 4.55    | 0.35               | 1.80                    | ± 13.1 %    |
| 5600                 | 35.5                               | 5.07                            | 4.37    | 4.37    | 4.37    | 0.35               | 1.80                    | ± 13.1 %    |
| 5800                 | 35.3                               | 5.27                            | 4.52    | 4.52    | 4.52    | 0.35               | 1.80                    | ± 13.1 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3914

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750                  | 55.5                               | 0.96                            | 9.39    | 9.39    | 9.39    | 0.63               | 0.74                    | ± 12.0 %    |
| 835                  | 55.2                               | 0.97                            | 9.31    | 9.31    | 9.31    | 0.56               | 0.76                    | ± 12.0 %    |
| 1750                 | 53.4                               | 1.49                            | 7.89    | 7.89    | 7.89    | 0.32               | 1.03                    | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 7.51    | 7.51    | 7.51    | 0.51               | 0.76                    | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 7.02    | 7.02    | 7.02    | 0.80               | 0.50                    | ± 12.0 %    |
| 2600                 | 52.5                               | 2.16                            | 6.81    | 6.81    | 6.81    | 0.80               | 0.50                    | ± 12.0 %    |
| 5200                 | 49.0                               | 5.30                            | 4.52    | 4.52    | 4.52    | 0.35               | 1.90                    | ± 13.1 %    |
| 5300                 | 48.9                               | 5.42                            | 4.32    | 4.32    | 4.32    | 0.35               | 1.90                    | ± 13.1 %    |
| 5500                 | 48.6                               | 5.65                            | 4.07    | 4.07    | 4.07    | 0.35               | 1.90                    | ± 13.1 %    |
| 5600                 | 48.5                               | 5.77                            | 3.97    | 3.97    | 3.97    | 0.35               | 1.90                    | ± 13.1 %    |
| 5800                 | 48.2                               | 6.00                            | 4.14    | 4.14    | 4.14    | 0.40               | 1.90                    | ± 13.1 %    |


<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## Frequency Response of E-Field


(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$

$f=600$  MHz, TEM





$f=1800$  MHz, R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

# Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$ )





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$



## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3914

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -24.3      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 2 mm       |



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D750V3-1054\_Mar13**

## CALIBRATION CERTIFICATE

Object **D750V3 - SN: 1054**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **March 18, 2013**

✓ KOK  
3/22/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 27-Mar-12 (No. 217-01530)         | Apr-13                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 27-Mar-12 (No. 217-01533)         | Apr-13                 |
| Reference Probe ES3DV3      | SN: 3205           | 28-Dec-12 (No. ES3-3205_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 27-Jun-12 (No. DAE4-601_Jun12)    | Jun-13                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                |                |                       |           |
|----------------|----------------|-----------------------|-----------|
|                | Name           | Function              | Signature |
| Calibrated by: | Israe El-Naouq | Laboratory Technician |           |
| Approved by:   | Katja Pokovic  | Technical Manager     |           |

Issued: March 18, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                        |             |
|-------------------------------------|------------------------|-------------|
| <b>DASY Version</b>                 | DASY5                  | V52.8.5     |
| <b>Extrapolation</b>                | Advanced Extrapolation |             |
| <b>Phantom</b>                      | Modular Flat Phantom   |             |
| <b>Distance Dipole Center - TSL</b> | 15 mm                  | with Spacer |
| <b>Zoom Scan Resolution</b>         | dx, dy, dz = 5 mm      |             |
| <b>Frequency</b>                    | 750 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 41.9           | 0.89 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 41.1 $\pm$ 6 % | 0.92 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.19 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>8.50 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.42 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>5.55 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Body TSL parameters</b>             | 22.0 °C             | 55.5           | 0.96 mho/m           |
| <b>Measured Body TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 54.2 $\pm$ 6 % | 1.00 mho/m $\pm$ 6 % |
| <b>Body TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.26 W/kg                                      |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>8.72 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.48 W/kg                                      |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>5.75 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 54.4 $\Omega$ - 0.9 j $\Omega$ |
| Return Loss                          | - 27.2 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.7 $\Omega$ - 2.7 j $\Omega$ |
| Return Loss                          | - 31.4 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.034 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | November 08, 2011 |

## DASY5 Validation Report for Head TSL

Date: 18.03.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1054**

Communication System: CW; Frequency: 750 MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.92 \text{ S/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.28, 6.28, 6.28); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

### **Dipole Calibration for Head Tissue/ $P_{in}=250 \text{ mW}$ , $d=15\text{mm}$ /Zoom Scan (7x7x7)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $52.772 \text{ V/m}$ ; Power Drift =  $0.03 \text{ dB}$

Peak SAR (extrapolated) =  $3.33 \text{ W/kg}$

**SAR(1 g) =  $2.19 \text{ W/kg}$ ; SAR(10 g) =  $1.42 \text{ W/kg}$**

Maximum value of SAR (measured) =  $2.55 \text{ W/kg}$




0 dB =  $2.55 \text{ W/kg}$  =  $4.07 \text{ dBW/kg}$

# Impedance Measurement Plot for Head TSL


18 Mar 2013 13:14:09  
**CH1** S11 1 U FS 1: 54.449  $\Omega$  -917.97 m $\Omega$  231.17 pF 750.000 000 MHz

\*  
 Del  
 CA  
 Avg  
 16  
 H1 d



CH2 S11 LOG 5 dB/REF -20 dB 1:-27.227 dB 750.000 000 MHz

CA  
 Avg  
 16  
 H1 d



## DASY5 Validation Report for Body TSL

Date: 18.03.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1054**

Communication System: CW; Frequency: 750 MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 1 \text{ S/m}$ ;  $\epsilon_r = 54.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.11, 6.11, 6.11); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

### **Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 52.772 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.32 W/kg

**SAR(1 g) = 2.26 W/kg; SAR(10 g) = 1.48 W/kg**


Maximum value of SAR (measured) = 2.61 W/kg



# Impedance Measurement Plot for Body TSL

18 Mar 2013 12:24:11  
 CH1 S11 1 U FS 1: 49.717  $\Delta$  -2.6553  $\Delta$  79.890 pF 750.000 000 MHz


\*  
 De1  
 CA



Av9  
 16  
 H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -31.444 dB 750.000 000 MHz

CA



Av9  
 16  
 H1d

START 550.000 000 MHz

STOP 950.000 000 MHz



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D835V2-4d119\_Apr13**

## CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d119**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **April 25, 2013**

✓  
KOK  
5/8/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 04-Apr-13 (No. 217-01736)         | Apr-14                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)         | Apr-14                 |
| Reference Probe ES3DV3      | SN: 3205           | 28-Dec-12 (No. ES3-3205_Dec12)    | Dec-13                 |
| DAE4                        | SN: 909            | 11-Sep-12 (No. DAE4-909_Sep12)    | Sep-13                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

Calibrated by: **Claudio Leubler** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Technical Manager

Signature

Issued: April 26, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                        |             |
|-------------------------------------|------------------------|-------------|
| <b>DASY Version</b>                 | DASY5                  | V52.8.6     |
| <b>Extrapolation</b>                | Advanced Extrapolation |             |
| <b>Phantom</b>                      | Modular Flat Phantom   |             |
| <b>Distance Dipole Center - TSL</b> | 15 mm                  | with Spacer |
| <b>Zoom Scan Resolution</b>         | dx, dy, dz = 5 mm      |             |
| <b>Frequency</b>                    | 835 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 41.5           | 0.90 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 40.8 $\pm$ 6 % | 0.94 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.51 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>9.68 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.62 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>6.30 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Body TSL parameters</b>             | 22.0 °C             | 55.2           | 0.97 mho/m           |
| <b>Measured Body TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 54.0 $\pm$ 6 % | 1.01 mho/m $\pm$ 6 % |
| <b>Body TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.47 W/kg                                      |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>9.54 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.62 W/kg                                      |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>6.31 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.1 $\Omega$ - 4.7 j $\Omega$ |
| Return Loss                          | - 26.6 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 45.8 $\Omega$ - 6.3 j $\Omega$ |
| Return Loss                          | - 22.1 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.385 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |               |
|-----------------|---------------|
| Manufactured by | SPEAG         |
| Manufactured on | June 29, 2010 |

## DASY5 Validation Report for Head TSL

Date: 25.04.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.94$  S/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.05, 6.05, 6.05); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 11.09.2012
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.387 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.86 W/kg

**SAR(1 g) = 2.51 W/kg; SAR(10 g) = 1.62 W/kg**

Maximum value of SAR (measured) = 2.93 W/kg



0 dB = 2.93 W/kg = 4.67 dBW/kg

# Impedance Measurement Plot for Head TSL

25 Apr 2013 09:11:06  
 CH1 S11 1 U FS 1: 50.061  $\Omega$  -4.6621  $\Omega$  40.884 pF 835.000 000 MHz


\*

Del

CA

Avg  
16

H1 d




CH2 S11 LOG 5 dB/REF -20 dB 1:-26.641 dB 835.000 000 MHz

CA

Avg  
16

H1 d



## DASY5 Validation Report for Body TSL

Date: 24.04.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 1.01 \text{ S/m}$ ;  $\epsilon_r = 54$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.04, 6.04, 6.04); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 11.09.2012
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

**Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.178 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.68 W/kg


**SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.62 W/kg**

Maximum value of SAR (measured) = 2.89 W/kg



0 dB = 2.89 W/kg = 4.61 dBW/kg

Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D1765V2-1008\_May13**

## CALIBRATION CERTIFICATE

Object **D1765V2 - SN: 1008**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **May 14, 2013**

*✓ 100K  
5/23/13*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 04-Apr-13 (No. 217-01736)         | Apr-14                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)         | Apr-14                 |
| Reference Probe ES3DV3      | SN: 3205           | 28-Dec-12 (No. ES3-3205_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 25-Apr-13 (No. DAE4-601_Apr13)    | Apr-14                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                |               |                       |                  |
|----------------|---------------|-----------------------|------------------|
|                | <b>Name</b>   | <b>Function</b>       | <b>Signature</b> |
| Calibrated by: | Jeton Kastrat | Laboratory Technician |                  |
| Approved by:   | Katja Pokovic | Technical Manager     |                  |

Issued: May 15, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- d) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                        |             |
|-------------------------------------|------------------------|-------------|
| <b>DASY Version</b>                 | DASY5                  | V52.8.6     |
| <b>Extrapolation</b>                | Advanced Extrapolation |             |
| <b>Phantom</b>                      | Modular Flat Phantom   |             |
| <b>Distance Dipole Center - TSL</b> | 10 mm                  | with Spacer |
| <b>Zoom Scan Resolution</b>         | dx, dy, dz = 5 mm      |             |
| <b>Frequency</b>                    | 1750 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 40.1           | 1.37 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 39.1 $\pm$ 6 % | 1.33 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 9.09 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>36.8 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 4.85 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>19.6 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Body TSL parameters</b>             | 22.0 °C             | 53.4           | 1.49 mho/m           |
| <b>Measured Body TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 51.7 $\pm$ 6 % | 1.47 mho/m $\pm$ 6 % |
| <b>Body TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 9.53 W/kg                                      |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>38.2 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 5.10 W/kg                                      |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>20.4 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 48.3 $\Omega$ - 6.4 j $\Omega$ |
| Return Loss                          | - 23.5 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 43.8 $\Omega$ - 6.1 j $\Omega$ |
| Return Loss                          | - 20.6 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.211 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                  |
|-----------------|------------------|
| Manufactured by | SPEAG            |
| Manufactured on | October 06, 2005 |

## DASY5 Validation Report for Head TSL

Date: 14.05.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1765 MHz; Type: D1765V2; Serial: D1765V2 - SN: 1008**

Communication System: UID 0 - CW ; Frequency: 1750 MHz

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.33$  S/m;  $\epsilon_r = 39.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.18, 5.18, 5.18); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.430 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 16.3 W/kg

**SAR(1 g) = 9.09 W/kg; SAR(10 g) = 4.85 W/kg**


Maximum value of SAR (measured) = 11.3 W/kg



Impedance Measurement Plot for Head TSL


14 May 2013 15:57:39  
[CH1] S11 1 U FS 1: 48.322  $\Omega$  -6.3848  $\Omega$  14.244 pF 1 750.000 000 MHz

\*  
De1  
CA  
Avg  
16  
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1:-23.476 dB 1 750.000 000 MHz

CA  
Avg  
16  
H1d



## DASY5 Validation Report for Body TSL

Date: 13.05.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1765 MHz; Type: D1765V2; Serial: D1765V2 - SN: 1008**

Communication System: UID 0 - CW ; Frequency: 1750 MHz

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.47$  S/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.83, 4.83, 4.83); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

### **Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.430 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 16.4 W/kg


**SAR(1 g) = 9.53 W/kg; SAR(10 g) = 5.1 W/kg**

Maximum value of SAR (measured) = 12.0 W/kg



0 dB = 12.0 W/kg = 10.79 dBW/kg

Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D1900V2-5d141\_May13**

## CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d141**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **May 02, 2013**

✓  
5/8/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 04-Apr-13 (No. 217-01736)         | Apr-14                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)         | Apr-14                 |
| Reference Probe ES3DV3      | SN: 3205           | 28-Dec-12 (No. ES3-3205_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 25-Apr-13 (No. DAE4-601_Apr13)    | Apr-14                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

Calibrated by: **Claudio Leubler**      Name: **Claudio Leubler**      Function: **Laboratory Technician**

Signature

Approved by: **Katja Pokovic**      Name: **Katja Pokovic**      Technical Manager

Issued: May 2, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                        |             |
|-------------------------------------|------------------------|-------------|
| <b>DASY Version</b>                 | DASY5                  | V52.8.6     |
| <b>Extrapolation</b>                | Advanced Extrapolation |             |
| <b>Phantom</b>                      | Modular Flat Phantom   |             |
| <b>Distance Dipole Center - TSL</b> | 10 mm                  | with Spacer |
| <b>Zoom Scan Resolution</b>         | dx, dy, dz = 5 mm      |             |
| <b>Frequency</b>                    | 1900 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 40.0           | 1.40 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 39.3 $\pm$ 6 % | 1.37 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 10.1 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>40.8 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 5.30 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>21.3 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Body TSL parameters</b>             | 22.0 °C             | 53.3           | 1.52 mho/m           |
| <b>Measured Body TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 54.0 $\pm$ 6 % | 1.51 mho/m $\pm$ 6 % |
| <b>Body TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 10.3 W/kg                                      |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>41.5 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 5.51 W/kg                                      |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>22.1 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $52.6 \Omega + 4.9 j\Omega$ |
| Return Loss                          | - 25.3 dB                   |

### Antenna Parameters with Body TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $48.3 \Omega + 5.9 j\Omega$ |
| Return Loss                          | - 24.1 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.199 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                |
|-----------------|----------------|
| Manufactured by | SPEAG          |
| Manufactured on | March 11, 2011 |

## DASY5 Validation Report for Head TSL

Date: 02.05.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d141**

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.37$  S/m;  $\epsilon_r = 39.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.98, 4.98, 4.98); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.124 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 18.2 W/kg

**SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.3 W/kg**

Maximum value of SAR (measured) = 12.5 W/kg




0 dB = 12.5 W/kg = 10.97 dBW/kg

# Impedance Measurement Plot for Head TSL

2 May 2013 15:38:50  
 [CH1] S11 1 U FS 1: 52.600  $\Omega$  4.9375  $\Omega$  413.59  $\mu$ H 1 900.000 000 MHz

\*  
 Del  
 Cor




Avg  
 4  
 H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-25.293 dB 1 900.000 000 MHz

Cor

Avg  
 4

H1d



## DASY5 Validation Report for Body TSL

Date: 02.05.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d141**

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.51$  S/m;  $\epsilon_r = 54$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.6, 4.6, 4.6); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

### **Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.124 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 17.6 W/kg

**SAR(1 g) = 10.3 W/kg; SAR(10 g) = 5.51 W/kg**

Maximum value of SAR (measured) = 13.0 W/kg



0 dB = 13.0 W/kg = 11.14 dBW/kg

# Impedance Measurement Plot for Body TSL

2 May 2013 15:38:04  
 [CH1] S11 1 U FS 1: 48.273  $\Omega$  5.9121  $\Omega$  495.23  $\mu$ H 1 900.000 000 MHz


\*

De1

Cor

Avg  
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1:-24.074 dB 1 900.000 000 MHz

Cor

Avg  
16

H1d





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D2450V2-719\_Aug13**

## CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 719**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **August 23, 2013**

✓cc  
9/13/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 04-Apr-13 (No. 217-01736)         | Apr-14                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)         | Apr-14                 |
| Reference Probe ES3DV3      | SN: 3205           | 28-Dec-12 (No. ES3-3205_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 25-Apr-13 (No. DAE4-601_Apr13)    | Apr-14                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

Calibrated by: **Jeton Kastrati** Name: **Jeton Kastrati** Function: **Laboratory Technician** Signature:

Approved by: **Katja Pokovic** Name: **Katja Pokovic** Function: **Technical Manager** Signature:

Issued: August 23, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.7     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2450 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.2           | 1.80 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 37.8 $\pm$ 6 % | 1.80 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                                                |
|-------------------------------------------------------|--------------------|------------------------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                                                |
| SAR measured                                          | 250 mW input power | 13.4 W/kg                                      |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | <b>53.2 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                         |                    |                                                |
|---------------------------------------------------------|--------------------|------------------------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                                                |
| SAR measured                                            | 250 mW input power | 6.23 W/kg                                      |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | <b>24.8 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.7           | 1.95 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 50.6 $\pm$ 6 % | 2.03 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                                                |
|-------------------------------------------------------|--------------------|------------------------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                                                |
| SAR measured                                          | 250 mW input power | 13.3 W/kg                                      |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | <b>51.7 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                         |                    |                                                |
|---------------------------------------------------------|--------------------|------------------------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                                                |
| SAR measured                                            | 250 mW input power | 6.14 W/kg                                      |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | <b>24.1 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $54.6 \Omega + 3.5 j\Omega$ |
| Return Loss                          | - 25.1 dB                   |

### Antenna Parameters with Body TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $51.1 \Omega + 5.4 j\Omega$ |
| Return Loss                          | - 25.3 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.149 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                    |
|-----------------|--------------------|
| Manufactured by | SPEAG              |
| Manufactured on | September 10, 2002 |

## DASY5 Validation Report for Head TSL

Date: 22.08.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 719**

Communication System: UID 0 - CW ; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.8$  S/m;  $\epsilon_r = 37.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.52, 4.52, 4.52); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 100.7 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 27.9 W/kg

**SAR(1 g) = 13.4 W/kg; SAR(10 g) = 6.23 W/kg**

Maximum value of SAR (measured) = 17.0 W/kg




0 dB = 17.0 W/kg = 12.30 dBW/kg

# Impedance Measurement Plot for Head TSL

22 Aug 2013 11:00:15  
 [CH1] S11 1 U FS 4: 54.639  $\Omega$  3.5215  $\Omega$  228.76  $\mu$ H 2 450.000 000 MHz

\*  
 Del  
 CA



Avg  
 16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 4: -25.093 dB 2 450.000 000 MHz

CA

Avg  
 16

H1d



## DASY5 Validation Report for Body TSL

Date: 23.08.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 719**

Communication System: UID 0 - CW ; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.03$  S/m;  $\epsilon_r = 50.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.42, 4.42, 4.42); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### **Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.688 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 27.9 W/kg

**SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.14 W/kg**

Maximum value of SAR (measured) = 17.2 W/kg




0 dB = 17.2 W/kg = 12.36 dBW/kg

# Impedance Measurement Plot for Body TSL

23 Aug 2013 09:00:38  
 [CH1] S11 1 U FS 3: 51.135  $\Omega$  5.3965  $\Omega$  350.56  $\mu$ H 2 450.000 000 MHz

#  
 Del  
 CA



Avg  
 16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 3:-25.274 dB 2 450.000 000 MHz

CA

Avg  
 16

H1d





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D5GHzV2-1007\_Sep13/2**

## CALIBRATION CERTIFICATE (Replacement of No: D5GHzV2-1007\_Sep13)

Object **D5GHzV2 - SN: 1007**

Calibration procedure(s) **QA CAL-22.v2**  
**Calibration procedure for dipole validation kits between 3-6 GHz**

CC✓  
 10/15/13

Calibration date: **September 23, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 04-Apr-13 (No. 217-01736)         | Apr-14                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)         | Apr-14                 |
| Reference Probe EX3DV4      | SN: 3503           | 28-Dec-12 (No. EX3-3503_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 25-Apr-13 (No. DAE4-601_Apr13)    | Apr-14                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                |                      |                                   |               |
|----------------|----------------------|-----------------------------------|---------------|
| Calibrated by: | Name<br>Leif Klysner | Function<br>Laboratory Technician | Signature<br> |
| Approved by:   | Katja Pokovic        | Technical Manager                 |               |

Issued: October 4, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEC 62209-2, "Evaluation of Human Exposure to Radio Frequency Fields from Handheld and Body-Mounted Wireless Communication Devices in the Frequency Range of 30 MHz to 6 GHz: Human models, Instrumentation, and Procedures"; Part 2: "Procedure to determine the Specific Absorption Rate (SAR) for including accessories and multiple transmitters", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"
- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                                                                                                                      |                                  |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <b>DASY Version</b>                 | DASY5                                                                                                                | V52.8.7                          |
| <b>Extrapolation</b>                | Advanced Extrapolation                                                                                               |                                  |
| <b>Phantom</b>                      | Modular Flat Phantom V5.0                                                                                            |                                  |
| <b>Distance Dipole Center - TSL</b> | 10 mm                                                                                                                | with Spacer                      |
| <b>Zoom Scan Resolution</b>         | dx, dy = 4.0 mm, dz = 1.4 mm                                                                                         | Graded Ratio = 1.4 (Z direction) |
| <b>Frequency</b>                    | 5200 MHz $\pm$ 1 MHz<br>5300 MHz $\pm$ 1 MHz<br>5500 MHz $\pm$ 1 MHz<br>5600 MHz $\pm$ 1 MHz<br>5800 MHz $\pm$ 1 MHz |                                  |

## Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 36.0           | 4.66 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 35.8 $\pm$ 6 % | 4.48 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL at 5200 MHz

| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                              |
|-------------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                                | 100 mW input power | 7.77 W/kg                    |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | 77.5 W/kg $\pm$ 19.9 % (k=2) |

| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                              |
|---------------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                                  | 100 mW input power | 2.23 W/kg                    |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | 22.2 W/kg $\pm$ 19.5 % (k=2) |

### Head TSL parameters at 5300 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.9         | 4.76 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 35.6 ± 6 %   | 4.62 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5300 MHz

|                                                             |                    |                                   |
|-------------------------------------------------------------|--------------------|-----------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                   |
| SAR measured                                                | 100 mW input power | 8.04 W/kg                         |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>80.2 W / kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.30 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>22.9 W/kg ± 19.5 % (k=2)</b> |

### Head TSL parameters at 5500 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.6         | 4.96 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 35.4 ± 6 %   | 4.76 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5500 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.17 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>81.4 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.32 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>23.1 W/kg ± 19.5 % (k=2)</b> |

### Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.5         | 5.07 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 35.2 ± 6 %   | 4.86 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5600 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.03 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>80.0 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.28 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>22.7 W/kg ± 19.5 % (k=2)</b> |

### Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.3         | 5.27 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 35.0 ± 6 %   | 5.07 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5800 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.78 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>77.5 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.20 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>21.9 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5200 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 49.0         | 5.30 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 48.3 ± 6 %   | 5.36 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5200 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.28 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>72.6 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.03 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>20.2 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5300 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.9         | 5.42 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 48.1 ± 6 %   | 5.56 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5300 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.49 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>74.7 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.09 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>20.8 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5500 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.6         | 5.65 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.8 ± 6 %   | 5.75 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5500 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.61 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>75.9 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.11 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>21.0 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.5         | 5.77 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.6 ± 6 %   | 5.88 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5600 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.75 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>77.3 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.16 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>21.5 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5800 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.2         | 6.00 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.3 ± 6 %   | 6.17 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5800 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.31 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>72.9 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.02 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>20.1 W/kg ± 19.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL at 5200 MHz

|                                      |                                 |
|--------------------------------------|---------------------------------|
| Impedance, transformed to feed point | 52.4 $\Omega$ - 11.0 j $\Omega$ |
| Return Loss                          | - 19.2 dB                       |

### Antenna Parameters with Head TSL at 5300 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 56.8 $\Omega$ - 4.4 j $\Omega$ |
| Return Loss                          | - 22.3 dB                      |

### Antenna Parameters with Head TSL at 5500 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 48.8 $\Omega$ - 5.4 j $\Omega$ |
| Return Loss                          | - 25.1 dB                      |

### Antenna Parameters with Head TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 57.3 $\Omega$ - 8.7 j $\Omega$ |
| Return Loss                          | - 19.5 dB                      |

### Antenna Parameters with Head TSL at 5800 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 56.9 $\Omega$ + 1.6 j $\Omega$ |
| Return Loss                          | - 23.5 dB                      |

### Antenna Parameters with Body TSL at 5200 MHz

|                                      |                                 |
|--------------------------------------|---------------------------------|
| Impedance, transformed to feed point | 53.1 $\Omega$ - 10.3 j $\Omega$ |
| Return Loss                          | - 19.7 dB                       |

### Antenna Parameters with Body TSL at 5300 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 54.3 $\Omega$ - 1.5 j $\Omega$ |
| Return Loss                          | - 27.2 dB                      |

### Antenna Parameters with Body TSL at 5500 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.7 $\Omega$ - 3.6 j $\Omega$ |
| Return Loss                          | - 28.7 dB                      |



### Antenna Parameters with Body TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 58.2 $\Omega$ - 5.2 j $\Omega$ |
| Return Loss                          | - 20.9 dB                      |

### Antenna Parameters with Body TSL at 5800 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 58.7 $\Omega$ + 3.9 j $\Omega$ |
| Return Loss                          | - 21.1 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.201 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                 |
|-----------------|-----------------|
| Manufactured by | SPEAG           |
| Manufactured on | August 28, 2003 |

## DASY5 Validation Report for Head TSL

Date: 23.09.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1007**

Communication System: UID 0 - CW ; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 4.48$  S/m;  $\epsilon_r = 35.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5300$  MHz;  $\sigma = 4.62$  S/m;  $\epsilon_r = 35.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5500$  MHz;  $\sigma = 4.76$  S/m;  $\epsilon_r = 35.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.86$  S/m;  $\epsilon_r = 35.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5800$  MHz;  $\sigma = 5.07$  S/m;  $\epsilon_r = 35$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.41, 5.41, 5.41); Calibrated: 28.12.2012, ConvF(5.1, 5.1, 5.1); Calibrated: 28.12.2012, ConvF(4.91, 4.91, 4.91); Calibrated: 28.12.2012, ConvF(4.76, 4.76, 4.76); Calibrated: 28.12.2012, ConvF(4.81, 4.81, 4.81); Calibrated: 28.12.2012;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.505 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 28.1 W/kg

**SAR(1 g) = 7.77 W/kg; SAR(10 g) = 2.23 W/kg**

Maximum value of SAR (measured) = 18.1 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.817 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 29.7 W/kg

**SAR(1 g) = 8.04 W/kg; SAR(10 g) = 2.3 W/kg**

Maximum value of SAR (measured) = 18.7 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.029 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 32.0 W/kg

**SAR(1 g) = 8.17 W/kg; SAR(10 g) = 2.32 W/kg**

Maximum value of SAR (measured) = 19.7 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.403 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 31.3 W/kg

**SAR(1 g) = 8.03 W/kg; SAR(10 g) = 2.28 W/kg**

Maximum value of SAR (measured) = 19.3 W/kg


**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 60.987 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 31.9 W/kg


**SAR(1 g) = 7.78 W/kg; SAR(10 g) = 2.2 W/kg**

Maximum value of SAR (measured) = 19.0 W/kg



0 dB = 19.0 W/kg = 12.79 dBW/kg

# Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 20.09.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1007**

Communication System: UID 0 - CW ; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.36$  S/m;  $\epsilon_r = 48.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.56$  S/m;  $\epsilon_r = 48.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5500$  MHz;  $\sigma = 5.75$  S/m;  $\epsilon_r = 47.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.88$  S/m;  $\epsilon_r = 47.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.17$  S/m;  $\epsilon_r = 47.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(4.91, 4.91, 4.91); Calibrated: 28.12.2012, ConvF(4.67, 4.67, 4.67); Calibrated: 28.12.2012, ConvF(4.43, 4.43, 4.43); Calibrated: 28.12.2012, ConvF(4.22, 4.22, 4.22); Calibrated: 28.12.2012, ConvF(4.38, 4.38, 4.38); Calibrated: 28.12.2012;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.606 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 28.6 W/kg

**SAR(1 g) = 7.28 W/kg; SAR(10 g) = 2.03 W/kg**

Maximum value of SAR (measured) = 17.2 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.305 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 30.3 W/kg

**SAR(1 g) = 7.49 W/kg; SAR(10 g) = 2.09 W/kg**

Maximum value of SAR (measured) = 17.8 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.471 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 32.4 W/kg

**SAR(1 g) = 7.61 W/kg; SAR(10 g) = 2.11 W/kg**

Maximum value of SAR (measured) = 18.5 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.333 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 33.8 W/kg

**SAR(1 g) = 7.75 W/kg; SAR(10 g) = 2.16 W/kg**

Maximum value of SAR (measured) = 19.1 W/kg


**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 55.389 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 34.1 W/kg

**SAR(1 g) = 7.31 W/kg; SAR(10 g) = 2.02 W/kg**

Maximum value of SAR (measured) = 18.3 W/kg




0 dB = 18.3 W/kg = 12.62 dBW/kg

Impedance Measurement Plot for Body TSL

19 Sep 2013 15:38:51  
[CH1] S11 1 U FS 1: 53.098  $\Omega$  -10.264  $\Omega$  2.9820 pF 5 200.000 000 MHz


\*  
De1  
Cor  
  
Avg  
0  
  
H1d



CH1 Markers  
2: 54.285  $\Omega$   
-1.5293  $\Omega$   
5.30000 GHz  
3: 49.717  $\Omega$   
-3.6367  $\Omega$   
5.50000 GHz  
4: 58.225  $\Omega$   
-5.2344  $\Omega$   
5.60000 GHz  
5: 58.725  $\Omega$   
3.9121  $\Omega$   
5.80000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -19.701 dB 5 200.000 000 MHz

Cor  
  
Avg  
0  
  
H1d



CH2 Markers  
2: -27.201 dB  
5.30000 GHz  
3: -28.741 dB  
5.50000 GHz  
4: -20.917 dB  
5.60000 GHz  
5: -21.121 dB  
5.80000 GHz



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D835V2-4d133\_Jul13**

## CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d133**

Calibration procedure(s) **QA CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **July 17, 2013**

✓  
KOK  
8/12/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 04-Apr-13 (No. 217-01736)         | Apr-14                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)         | Apr-14                 |
| Reference Probe ES3DV3      | SN: 3205           | 28-Dec-12 (No. ES3-3205_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 25-Apr-13 (No. DAE4-601_Apr13)    | Apr-14                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                |               |                       |           |
|----------------|---------------|-----------------------|-----------|
|                | Name          | Function              | Signature |
| Calibrated by: | Leif Klysner  | Laboratory Technician |           |
| Approved by:   | Katja Pokovic | Technical Manager     |           |

Issued: July 18, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- d) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.7     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 835 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.5           | 0.90 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 41.8 $\pm$ 6 % | 0.92 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.44 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>9.62 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.59 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>6.28 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.2           | 0.97 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 54.9 $\pm$ 6 % | 1.00 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.46 W/kg                                      |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>9.61 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.62 W/kg                                      |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>6.36 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.0 $\Omega$ - 1.8 j $\Omega$ |
| Return Loss                          | - 31.8 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 48.2 $\Omega$ - 3.6 j $\Omega$ |
| Return Loss                          | - 27.7 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.395 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |               |
|-----------------|---------------|
| Manufactured by | SPEAG         |
| Manufactured on | July 22, 2011 |

## DASY5 Validation Report for Head TSL

Date: 17.07.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d133**

Communication System: UID 0 - CW ; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.92 \text{ S/m}$ ;  $\epsilon_r = 41.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.05, 6.05, 6.05); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 57.188 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.66 W/kg

**SAR(1 g) = 2.44 W/kg; SAR(10 g) = 1.59 W/kg**

Maximum value of SAR (measured) = 2.84 W/kg




0 dB = 2.84 W/kg = 4.53 dBW/kg

Impedance Measurement Plot for Head TSL


18 Jul 2013 09:49:17  
[CH1] S11 1 U FS 1: 51.957  $\angle$  -1.7539  $\angle$  108.67 pF 835.000 000 MHz

\*  
De1  
CA  
Avg  
16  
H1d



CH2 S11 L00 5 dB/REF -20 dB 1:-31.772 dB 835.000 000 MHz

CA  
Avg  
16  
H1d



## DASY5 Validation Report for Body TSL

Date: 17.07.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d133**

Communication System: UID 0 - CW ; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 1 \text{ S/m}$ ;  $\epsilon_r = 54.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.04, 6.04, 6.04); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### **Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 55.351 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.59 W/kg

**SAR(1 g) = 2.46 W/kg; SAR(10 g) = 1.62 W/kg**

Maximum value of SAR (measured) = 2.86 W/kg




0 dB = 2.86 W/kg = 4.56 dBW/kg

Impedance Measurement Plot for Body TSL

18 Jul 2013 09:11:04  
[CH1] S11 1 U FS 1: 48.184  $\Omega$  -3.6035  $\Omega$  52.894 pF 835.000 000 MHz

\*  
De1  
CA




Avg  
16  
H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -27.734 dB 835.000 000 MHz

CA

Avg  
16  
H1d





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D1900V2-5d149\_Jul13**

## CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d149**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **July 22, 2013**

✓  
 KOK  
 8/19/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 04-Apr-13 (No. 217-01736)         | Apr-14                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)         | Apr-14                 |
| Reference Probe ES3DV3      | SN: 3205           | 28-Dec-12 (No. ES3-3205_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 25-Apr-13 (No. DAE4-601_Apr13)    | Apr-14                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                |                |                       |           |
|----------------|----------------|-----------------------|-----------|
|                | Name           | Function              | Signature |
| Calibrated by: | Jeton Kastrali | Laboratory Technician |           |
| Approved by:   | Katja Pokovic  | Technical Manager     |           |

Issued: July 22, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                        |             |
|-------------------------------------|------------------------|-------------|
| <b>DASY Version</b>                 | DASY5                  | V52.8.7     |
| <b>Extrapolation</b>                | Advanced Extrapolation |             |
| <b>Phantom</b>                      | Modular Flat Phantom   |             |
| <b>Distance Dipole Center - TSL</b> | 10 mm                  | with Spacer |
| <b>Zoom Scan Resolution</b>         | dx, dy, dz = 5 mm      |             |
| <b>Frequency</b>                    | 1900 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 40.0           | 1.40 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 38.9 $\pm$ 6 % | 1.36 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 9.99 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>40.4 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 5.28 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>21.3 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Body TSL parameters</b>             | 22.0 °C             | 53.3           | 1.52 mho/m           |
| <b>Measured Body TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 53.4 $\pm$ 6 % | 1.49 mho/m $\pm$ 6 % |
| <b>Body TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 10.0 W/kg                                      |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>40.5 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 5.36 W/kg                                      |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>21.6 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $52.9 \Omega + 6.0 j\Omega$ |
| Return Loss                          | - 23.8 dB                   |

### Antenna Parameters with Body TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $48.5 \Omega + 6.4 j\Omega$ |
| Return Loss                          | - 23.5 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.196 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                |
|-----------------|----------------|
| Manufactured by | SPEAG          |
| Manufactured on | March 11, 2011 |

## DASY5 Validation Report for Head TSL

Date: 22.07.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d149**

Communication System: UID 0 - CW ; Frequency: 1900 MHz

Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.36 \text{ S/m}$ ;  $\epsilon_r = 38.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.98, 4.98, 4.98); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**



Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 96.173 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 18.0 W/kg

**SAR(1 g) = 9.99 W/kg; SAR(10 g) = 5.28 W/kg**

Maximum value of SAR (measured) = 12.4 W/kg



0 dB = 12.4 W/kg = 10.93 dBW/kg


# Impedance Measurement Plot for Head TSL

22 Jul 2013 11:59:34  
 CH1 S11 1 U FS 1: 52.941  $\Omega$  6.0059  $\Omega$  503.09  $\mu$ H 1 900.000 000 MHz

\*  
 Del  
 CA

Avg  
 16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1:-23.758 dB 1 900.000 000 MHz

CA

Avg  
 16

H1d



## DASY5 Validation Report for Body TSL

Date: 22.07.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d149**

Communication System: UID 0 - CW ; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 53.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.6, 4.6, 4.6); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### **Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.173 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 17.0 W/kg

**SAR(1 g) = 10 W/kg; SAR(10 g) = 5.36 W/kg**

Maximum value of SAR (measured) = 12.6 W/kg




0 dB = 12.6 W/kg = 11.00 dBW/kg

## Impedance Measurement Plot for Body TSL

22 Jul 2013 11:32:14  
CH1 S11 1 U FS 1: 48.525  $\Delta$  6.3906  $\Delta$  535.32 pH 1 900.000 000 MHz

\*  
De1  
CA



Avg  
16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -23.547 dB 1 900.000 000 MHz

CA

Avg  
16

H1d





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D5GHzV2-1120\_Feb13**

## CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN: 1120**

Calibration procedure(s) **QA CAL-22.v2**  
**Calibration procedure for dipole validation kits between 3-6 GHz**

Calibration date: **February 14, 2013**

✓  
Kok  
2/2/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 27-Mar-12 (No. 217-01530)         | Apr-13                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 27-Mar-12 (No. 217-01533)         | Apr-13                 |
| Reference Probe EX3DV4      | SN: 3503           | 28-Dec-12 (No. EX3-3503_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 27-Jun-12 (No. DAE4-601_Jun12)    | Jun-13                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 100005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

Calibrated by: **Israe El-Naouq** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Technical Manager

Signature

*Israe El-Naouq*  
*Katja Pokovic*

Issued: February 14, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- a) IEC 62209-2, "Evaluation of Human Exposure to Radio Frequency Fields from Handheld and Body-Mounted Wireless Communication Devices in the Frequency Range of 30 MHz to 6 GHz: Human models, Instrumentation, and Procedures"; Part 2: "Procedure to determine the Specific Absorption Rate (SAR) for including accessories and multiple transmitters", March 2010
- b) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

### Additional Documentation:

- c) DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                                                                                                                      |                                  |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <b>DASY Version</b>                 | DASY5                                                                                                                | V52.8.5                          |
| <b>Extrapolation</b>                | Advanced Extrapolation                                                                                               |                                  |
| <b>Phantom</b>                      | Modular Flat Phantom V5.0                                                                                            |                                  |
| <b>Distance Dipole Center - TSL</b> | 10 mm                                                                                                                | with Spacer                      |
| <b>Zoom Scan Resolution</b>         | dx, dy = 4.0 mm, dz = 1.4 mm                                                                                         | Graded Ratio = 1.4 (Z direction) |
| <b>Frequency</b>                    | 5200 MHz $\pm$ 1 MHz<br>5300 MHz $\pm$ 1 MHz<br>5500 MHz $\pm$ 1 MHz<br>5600 MHz $\pm$ 1 MHz<br>5800 MHz $\pm$ 1 MHz |                                  |

## Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 36.0           | 4.66 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 34.7 $\pm$ 6 % | 4.47 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL at 5200 MHz

| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| SAR measured                                                | 100 mW input power | 7.67 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>76.0 W/kg <math>\pm</math> 19.9 % (k=2)</b> |

| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| SAR measured                                                  | 100 mW input power | 2.18 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>21.5 W/kg <math>\pm</math> 19.5 % (k=2)</b> |

### Head TSL parameters at 5300 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.9         | 4.76 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.5 ± 6 %   | 4.57 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5300 MHz

|                                                             |                    |                                   |
|-------------------------------------------------------------|--------------------|-----------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                   |
| SAR measured                                                | 100 mW input power | 7.94 W/kg                         |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>78.7 W / kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.27 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>22.4 W/kg ± 19.5 % (k=2)</b> |

### Head TSL parameters at 5500 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.6         | 4.96 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.2 ± 6 %   | 4.74 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5500 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.09 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>80.1 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.29 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>22.6 W/kg ± 19.5 % (k=2)</b> |

### Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.5         | 5.07 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.1 ± 6 %   | 4.83 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5600 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.08 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>79.9 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.28 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>22.5 W/kg ± 19.5 % (k=2)</b> |

### Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.3         | 5.27 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 33.9 ± 6 %   | 5.05 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5800 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.57 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>74.9 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.13 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>21.0 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5200 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 49.0         | 5.30 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.9 ± 6 %   | 5.36 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5200 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.73 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>76.6 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.17 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>21.5 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5300 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.9         | 5.42 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.7 ± 6 %   | 5.48 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5300 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.75 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>76.8 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.18 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>21.5 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5500 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.6         | 5.65 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.3 ± 6 %   | 5.71 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5500 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.06 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>79.8 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.24 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>22.1 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.5         | 5.77 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.2 ± 6 %   | 5.83 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5600 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.15 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>80.7 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.26 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>22.3 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5800 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.2         | 6.00 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 45.9 ± 6 %   | 6.12 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5800 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.62 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>75.5 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.12 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>20.9 W/kg ± 19.5 % (k=2)</b> |

## Appendix

### Antenna Parameters with Head TSL at 5200 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $53.8 \Omega - 6.3 j\Omega$ |
| Return Loss                          | - 23.0 dB                   |

### Antenna Parameters with Head TSL at 5300 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $50.1 \Omega + 0.5 j\Omega$ |
| Return Loss                          | - 45.3 dB                   |

### Antenna Parameters with Head TSL at 5500 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $51.0 \Omega - 0.9 j\Omega$ |
| Return Loss                          | - 37.9 dB                   |

### Antenna Parameters with Head TSL at 5600 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $55.3 \Omega - 0.9 j\Omega$ |
| Return Loss                          | - 25.8 dB                   |

### Antenna Parameters with Head TSL at 5800 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $53.5 \Omega + 3.3 j\Omega$ |
| Return Loss                          | - 26.7 dB                   |

### Antenna Parameters with Body TSL at 5200 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $53.7 \Omega - 4.8 j\Omega$ |
| Return Loss                          | - 24.8 dB                   |

### Antenna Parameters with Body TSL at 5300 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $50.2 \Omega + 2.4 j\Omega$ |
| Return Loss                          | - 32.5 dB                   |

### Antenna Parameters with Body TSL at 5500 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $51.6 \Omega - 1.5 j\Omega$ |
| Return Loss                          | - 33.3 dB                   |

### Antenna Parameters with Body TSL at 5600 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $57.4 \Omega + 0.9 j\Omega$ |
| Return Loss                          | - 23.2 dB                   |



## Antenna Parameters with Body TSL at 5800 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $53.5 \Omega + 3.2 j\Omega$ |
| Return Loss                          | - 26.7 dB                   |

## General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.206 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

## Additional EUT Data

|                 |                    |
|-----------------|--------------------|
| Manufactured by | SPEAG              |
| Manufactured on | September 08, 2011 |

## DASY5 Validation Report for Head TSL

Date: 08.02.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1120**

Communication System: CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 4.47$  S/m;  $\epsilon_r = 34.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5300$  MHz;  $\sigma = 4.57$  S/m;  $\epsilon_r = 34.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5500$  MHz;  $\sigma = 4.74$  S/m;  $\epsilon_r = 34.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.83$  S/m;  $\epsilon_r = 34.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5800$  MHz;  $\sigma = 5.05$  S/m;  $\epsilon_r = 33.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.41, 5.41, 5.41); Calibrated: 28.12.2012, ConvF(5.1, 5.1, 5.1); Calibrated: 28.12.2012, ConvF(4.91, 4.91, 4.91); Calibrated: 28.12.2012, ConvF(4.76, 4.76, 4.76); Calibrated: 28.12.2012, ConvF(4.81, 4.81, 4.81); Calibrated: 28.12.2012;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 61.561 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 28.8 W/kg

**SAR(1 g) = 7.67 W/kg; SAR(10 g) = 2.18 W/kg**

Maximum value of SAR (measured) = 17.7 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 62.429 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 30.3 W/kg

**SAR(1 g) = 7.94 W/kg; SAR(10 g) = 2.27 W/kg**

Maximum value of SAR (measured) = 18.5 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 61.998 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 32.7 W/kg

**SAR(1 g) = 8.09 W/kg; SAR(10 g) = 2.29 W/kg**

Maximum value of SAR (measured) = 19.3 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 62.540 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 33.3 W/kg

**SAR(1 g) = 8.08 W/kg; SAR(10 g) = 2.28 W/kg**

Maximum value of SAR (measured) = 19.5 W/kg


**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.600 V/m; Power Drift = 0.09 dB


Peak SAR (extrapolated) = 32.9 W/kg

**SAR(1 g) = 7.57 W/kg; SAR(10 g) = 2.13 W/kg**

Maximum value of SAR (measured) = 18.8 W/kg



Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 14.02.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1120**

Communication System: CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.36$  S/m;  $\epsilon_r = 46.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.48$  S/m;  $\epsilon_r = 46.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5500$  MHz;  $\sigma = 5.71$  S/m;  $\epsilon_r = 46.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.83$  S/m;  $\epsilon_r = 46.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.12$  S/m;  $\epsilon_r = 45.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(4.91, 4.91, 4.91); Calibrated: 28.12.2012, ConvF(4.67, 4.67, 4.67); Calibrated: 28.12.2012, ConvF(4.43, 4.43, 4.43); Calibrated: 28.12.2012, ConvF(4.22, 4.22, 4.22); Calibrated: 28.12.2012, ConvF(4.38, 4.38, 4.38); Calibrated: 28.12.2012;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 61.053 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 31.1 W/kg

**SAR(1 g) = 7.73 W/kg; SAR(10 g) = 2.17 W/kg**

Maximum value of SAR (measured) = 18.2 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 60.021 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 32.1 W/kg

**SAR(1 g) = 7.75 W/kg; SAR(10 g) = 2.18 W/kg**

Maximum value of SAR (measured) = 18.5 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 59.894 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 35.3 W/kg

**SAR(1 g) = 8.06 W/kg; SAR(10 g) = 2.24 W/kg**

Maximum value of SAR (measured) = 19.4 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 59.730 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 36.8 W/kg

**SAR(1 g) = 8.15 W/kg; SAR(10 g) = 2.26 W/kg**

Maximum value of SAR (measured) = 19.9 W/kg


**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 56.663 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 36.4 W/kg

**SAR(1 g) = 7.62 W/kg; SAR(10 g) = 2.12 W/kg**

Maximum value of SAR (measured) = 19.0 W/kg




0 dB = 19.0 W/kg = 12.79 dBW/kg

# Impedance Measurement Plot for Body TSL

14 Feb 2013 15:47:05  
 CH1 S11 1 U FS 1: 53.672  $\Omega$  -4.7539  $\Omega$  6.4382 pF 5 200.000 000 MHz


\*  
 Del  
 Cor  
 Avg  
 16  
 H1d



CH1 Markers  
 2: 50.250  $\Omega$   
 2.3555  $\Omega$   
 5.30000 GHz  
 3: 51.629  $\Omega$   
 -1.4824  $\Omega$   
 5.50000 GHz  
 4: 57.389  $\Omega$   
 0.9180  $\Omega$   
 5.60000 GHz  
 5: 53.543  $\Omega$   
 3.2441  $\Omega$   
 5.80000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -24.750 dB 5 200.000 000 MHz

Cor  
 Avg  
 16  
 H1d



CH2 Markers  
 2: -32.508 dB  
 5.30000 GHz  
 3: -33.267 dB  
 5.50000 GHz  
 4: -23.183 dB  
 5.60000 GHz  
 5: -26.672 dB  
 5.80000 GHz

## APPENDIX D: SAR TISSUE SPECIFICATIONS

Measurement Procedure for Tissue verification:

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the tissue. The tissue was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity  $\epsilon$  can be calculated from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where  $Y$  is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively,  $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$ ,  $\omega$  is the angular frequency, and  $j = \sqrt{-1}$ .

**Table D-I**  
**Composition of the Tissue Equivalent Matter**

| Frequency (MHz)           | 750           | 750      | 835   | 835   | 1750 | 1750 | 1900  | 1900  | 2450     | 2450 | 5200-5800 | 5200-5800 |
|---------------------------|---------------|----------|-------|-------|------|------|-------|-------|----------|------|-----------|-----------|
| Tissue                    | Head          | Body     | Head  | Body  | Head | Body | Head  | Body  | Head     | Body | Head      | Body      |
| Ingredients (% by weight) |               |          |       |       |      |      |       |       |          |      |           |           |
| Bactericide               |               |          | 0.1   | 0.1   |      |      |       |       |          |      |           |           |
| DGBE                      |               |          |       |       | 47   | 31   | 44.92 | 29.44 |          | 26.7 |           |           |
| HEC                       |               |          | 1     | 1     |      |      |       |       |          |      |           |           |
| NaCl                      | See pp. 2 - 3 | See p. 2 | 1.45  | 0.94  | 0.4  | 0.2  | 0.18  | 0.39  | See p. 4 | 0.1  | See p. 5  |           |
| Sucrose                   |               |          | 57    | 44.9  |      |      |       |       |          |      |           | 20        |
| Polysorbate (Tween) 80    |               |          |       |       |      |      |       |       |          |      |           | 80        |
| Water                     |               |          | 40.45 | 53.06 | 52.6 | 68.8 | 54.9  | 70.17 |          | 73.2 |           |           |

|                                           |                                                                                     |                              |                                                                                       |                                        |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMG900R7                |  | <b>SAR EVALUATION REPORT</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Dates:</b><br>02/03/14 - 03/31/14 | <b>DUT Type:</b><br>Portable Handset                                                |                              |                                                                                       | <b>APPENDIX D:</b><br>Page 1 of 5      |



## 2 Composition / Information on ingredients

The Item is composed of the following ingredients:

|                                                                  |                                                                                                                                                     |
|------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| H <sub>2</sub> O                                                 | Water, 35 – 58%                                                                                                                                     |
| Sucrose                                                          | Sugar, white, refined, 40 – 60%                                                                                                                     |
| NaCl                                                             | Sodium Chloride, 0 – 6%                                                                                                                             |
| Hydroxyethyl-cellulose                                           | Medium Viscosity (CAS# 9004-62-0), <0.3%                                                                                                            |
| Preventol-D7                                                     | Preservative: aqueous preparation, (CAS# 55965-84-9), containing 5-chloro-2-methyl-3(2H)-isothiazolone and 2-methyl-3(2H)-isothiazolone, 0.1 – 0.7% |
| Relevant for safety; Refer to the respective Safety Data Sheet*. |                                                                                                                                                     |

**Figure D-1**

### Composition of 750 MHz Head and Body Tissue Equivalent Matter

**Note:** 750MHz liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

#### Measurement Certificate / Material Test

|              |                                          |
|--------------|------------------------------------------|
| Item Name    | Body Tissue Simulating Liquid (MSL750V2) |
| Product No.  | SL AAM 075 AA (Charge: 130313-1)         |
| Manufacturer | SPEAG                                    |

#### Measurement Method

TSL dielectric parameters measured using calibrated OCP probe.

#### Setup Validation

Validation results were within  $\pm 2.5\%$  towards the target values of Methanol.

#### Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

#### Test Condition

|                 |                                                              |
|-----------------|--------------------------------------------------------------|
| Ambient         | Environment temperature ( $22 \pm 3$ )°C and humidity < 70%. |
| TSL Temperature | 22°C                                                         |
| Test Date       | 13-Mar-13                                                    |
| Operator        | IEN                                                          |

#### Additional Information

|                   |                         |
|-------------------|-------------------------|
| TSL Density       | 1.212 g/cm <sup>3</sup> |
| TSL Heat-capacity | 3.006 kJ/(kg*K)         |

| f [MHz] | Measured |       |       | Target |       | Diff. to Target [%] |                 |
|---------|----------|-------|-------|--------|-------|---------------------|-----------------|
|         | HP-e*    | HP-e* | sigma | eps    | sigma | $\Delta$ -eps       | $\Delta$ -sigma |
| 600     | 57.5     | 24.64 | 0.82  | 56.1   | 0.95  | 2.5                 | -13.6           |
| 625     | 57.2     | 24.31 | 0.84  | 56.0   | 0.95  | 2.1                 | -11.4           |
| 650     | 57.0     | 23.99 | 0.87  | 55.9   | 0.96  | 1.8                 | -9.2            |
| 675     | 56.7     | 23.69 | 0.89  | 55.8   | 0.96  | 1.5                 | -7.1            |
| 700     | 56.4     | 23.39 | 0.91  | 55.7   | 0.96  | 1.2                 | -5.1            |
| 725     | 56.2     | 23.18 | 0.93  | 55.6   | 0.96  | 1.0                 | -2.8            |
| 750     | 55.9     | 22.97 | 0.96  | 55.5   | 0.96  | 0.7                 | -0.5            |
| 775     | 55.7     | 22.78 | 0.98  | 55.4   | 0.97  | 0.4                 | 1.7             |
| 800     | 55.4     | 22.60 | 1.01  | 55.3   | 0.97  | 0.1                 | 4.0             |
| 825     | 55.2     | 22.44 | 1.03  | 55.2   | 0.98  | -0.2                | 5.3             |
| 850     | 55.0     | 22.36 | 1.04  | 55.2   | 0.98  | -0.3                | 5.9             |
| 875     | 54.9     | 22.28 | 1.05  | 55.2   | 0.99  | -0.4                | 6.6             |
| 900     | 54.7     | 22.16 | 1.08  | 55.1   | 1.02  | -0.7                | 5.8             |
| 925     | 54.5     | 22.03 | 1.10  | 55.0   | 1.05  | -1.0                | 5.1             |
| 950     | 54.2     | 21.93 | 1.13  | 55.0   | 1.06  | -1.3                | 6.2             |
| 975     | 54.0     | 21.82 | 1.15  | 54.9   | 1.08  | -1.7                | 7.2             |
| 1000    | 53.8     | 21.74 | 1.18  | 54.9   | 1.09  | -2.0                | 8.5             |
|         | 53.6     | 21.66 | 1.21  | 54.8   | 1.10  | -2.3                | 9.7             |





**Figure D-2**

### 750MHz Body Tissue Equivalent Matter

|                                    |                                                                                     |                            |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7                |  | SAR EVALUATION REPORT      |  | Reviewed by:<br>Quality Manager |
| Test Dates:<br>02/03/14 - 03/31/14 | DUT Type:<br>Portable Handset                                                       | APPENDIX D:<br>Page 2 of 5 |                                                                                       |                                 |

## Measurement Certificate / Material Test

Item Name **Head Tissue Simulating Liquid (HSL750V2)**  
 Product No. SL AAH 075 AA (Charge: 130312-4)  
 Manufacturer SPEAG

### Measurement Method

TSL dielectric parameters measured using calibrated OCP probe.

### Setup Validation

Validation results were within  $\pm 2.5\%$  towards the target values of Methanol.

### Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

### Test Condition

Ambient Environment temperatur ( $22 \pm 3$ )°C and humidity < 70%.  
 TSL Temperature 22°C  
 Test Date 13-Mar-13  
 Operator IEN

### Additional Information

TSL Density 1.284 g/cm<sup>3</sup>  
 TSL Heat-capacity 2.701 kJ/(kg\*K)

| f [MHz] | Measured |        |       | Target |       | Diff. to Target [%] |         |
|---------|----------|--------|-------|--------|-------|---------------------|---------|
|         | HP-e'    | HP-e'' | sigma | eps    | sigma | Δ-eps               | Δ-sigma |
| 600     | 44.6     | 23.25  | 0.78  | 42.7   | 0.88  | 4.3                 | -12.0   |
| 625     | 44.2     | 23.00  | 0.80  | 42.6   | 0.88  | 3.8                 | -9.5    |
| 650     | 43.8     | 22.76  | 0.82  | 42.5   | 0.89  | 3.2                 | -7.1    |
| 675     | 43.4     | 22.50  | 0.84  | 42.3   | 0.89  | 2.6                 | -4.9    |
| 700     | 43.1     | 22.24  | 0.87  | 42.2   | 0.89  | 2.1                 | -2.6    |
| 725     | 42.7     | 22.06  | 0.89  | 42.1   | 0.89  | 1.6                 | -0.2    |
| 750     | 42.4     | 21.88  | 0.91  | 41.9   | 0.89  | 1.1                 | 2.2     |
| 775     | 42.1     | 21.72  | 0.94  | 41.8   | 0.90  | 0.6                 | 4.6     |
| 800     | 41.7     | 21.55  | 0.96  | 41.7   | 0.90  | 0.1                 | 6.9     |
| 825     | 41.4     | 21.40  | 0.98  | 41.6   | 0.91  | -0.4                | 8.3     |
| 838     | 41.3     | 21.32  | 0.99  | 41.5   | 0.91  | -0.6                | 9.0     |
| 850     | 41.1     | 21.24  | 1.00  | 41.5   | 0.92  | -0.9                | 9.6     |
| 875     | 40.8     | 21.11  | 1.03  | 41.5   | 0.94  | -1.6                | 9.0     |
| 900     | 40.6     | 20.99  | 1.05  | 41.5   | 0.97  | -2.3                | 8.3     |
| 925     | 40.3     | 20.87  | 1.07  | 41.5   | 0.98  | -2.9                | 9.4     |
| 950     | 40.0     | 20.76  | 1.10  | 41.4   | 0.99  | -3.5                | 10.3    |
| 975     | 39.7     | 20.66  | 1.12  | 41.4   | 1.00  | -4.0                | 11.5    |
| 1000    | 39.5     | 20.57  | 1.14  | 41.3   | 1.01  | -4.5                | 12.7    |





Figure D-3  
 750MHz Head Tissue Equivalent Matter

|                                    |                                                                                                           |                                                                                       |                                 |
|------------------------------------|-----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7                |  SAR EVALUATION REPORT |  | Reviewed by:<br>Quality Manager |
| Test Dates:<br>02/03/14 - 03/31/14 | DUT Type:<br>Portable Handset                                                                             |                                                                                       | APPENDIX D:<br>Page 3 of 5      |

## 2 Composition / Information on ingredients

The Item is composed of the following ingredients:

|                                               |                                                                                                                                                                                           |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| H <sub>2</sub> O                              | Water, 52 – 75%                                                                                                                                                                           |
| C <sub>8</sub> H <sub>18</sub> O <sub>3</sub> | Diethylene glycol monobutyl ether (DGBE), 25 – 48%<br>(CAS-No. 112-34-5, EC-No. 203-961-6, EC-index-No. 603-096-00-8)<br>Relevant for safety; Refer to the respective Safety Data Sheet*. |
| NaCl                                          | Sodium Chloride, <1.0%                                                                                                                                                                    |

Figure D-4

### Composition of 2.4 GHz Head Tissue Equivalent Matter

**Note:** 2.4 GHz head liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

#### Measurement Certificate / Material Test

|              |                                           |
|--------------|-------------------------------------------|
| Item Name    | Head Tissue Simulating Liquid (HSL2450V2) |
| Product No.  | SL AAH 245 BA (Charge: 130212-2)          |
| Manufacturer | SPEAG                                     |

#### Measurement Method

TSL dielectric parameters measured using calibrated OCP probe.

#### Setup Validation

Validation results were within  $\pm 2.5\%$  towards the target values of Methanol.

#### Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

#### Test Condition

|                 |                                                           |
|-----------------|-----------------------------------------------------------|
| Ambient         | Environment temperatur (22 $\pm$ 3)°C and humidity < 70%. |
| TSL Temperature | 23°C                                                      |
| Test Date       | 13-Feb-13                                                 |
| Operator        | DI                                                        |

#### Additional Information

|                   |                         |
|-------------------|-------------------------|
| TSL Density       | 0.988 g/cm <sup>3</sup> |
| TSL Heat-capacity | 3.680 kJ/(kg°K)         |

| f (MHz) | Measured |        |       | Target |       | Diff. to Target [%] |         |
|---------|----------|--------|-------|--------|-------|---------------------|---------|
|         | HP-e'    | HP-e'' | sigma | eps    | sigma | Δ-eps               | Δ-sigma |
| 1900    | 40.4     | 11.94  | 1.26  | 40.0   | 1.40  | 1.0                 | -9.9    |
| 1925    | 40.3     | 12.02  | 1.29  | 40.0   | 1.40  | 0.7                 | -8.0    |
| 1950    | 40.2     | 12.11  | 1.31  | 40.0   | 1.40  | 0.5                 | -6.2    |
| 1975    | 40.1     | 12.20  | 1.34  | 40.0   | 1.40  | 0.2                 | -4.2    |
| 2000    | 40.0     | 12.29  | 1.37  | 40.0   | 1.40  | -0.1                | -2.3    |
| 2025    | 39.9     | 12.39  | 1.40  | 40.0   | 1.42  | -0.2                | -1.9    |
| 2050    | 39.8     | 12.49  | 1.42  | 39.9   | 1.44  | -0.4                | -1.4    |
| 2075    | 39.6     | 12.57  | 1.45  | 39.9   | 1.47  | -0.6                | -1.1    |
| 2100    | 39.5     | 12.65  | 1.48  | 39.8   | 1.48  | -0.7                | -0.7    |
| 2125    | 39.4     | 12.74  | 1.51  | 39.8   | 1.51  | -0.9                | -0.4    |
| 2150    | 39.3     | 12.82  | 1.53  | 39.7   | 1.53  | -1.0                | 0.0     |
| 2175    | 39.2     | 12.89  | 1.56  | 39.7   | 1.56  | -1.2                | 0.3     |
| 2200    | 39.1     | 12.97  | 1.59  | 39.6   | 1.58  | -1.3                | 0.6     |
| 2225    | 39.0     | 13.04  | 1.61  | 39.6   | 1.60  | -1.5                | 0.9     |
| 2250    | 38.9     | 13.11  | 1.64  | 39.6   | 1.62  | -1.7                | 1.2     |
| 2275    | 38.8     | 13.20  | 1.67  | 39.5   | 1.64  | -1.8                | 1.6     |
| 2300    | 38.7     | 13.28  | 1.70  | 39.5   | 1.67  | -2.0                | 2.0     |
| 2325    | 38.6     | 13.35  | 1.73  | 39.4   | 1.69  | -2.1                | 2.3     |
| 2350    | 38.5     | 13.42  | 1.75  | 39.4   | 1.71  | -2.3                | 2.6     |
| 2375    | 38.4     | 13.50  | 1.78  | 39.3   | 1.73  | -2.4                | 2.9     |
| 2400    | 38.3     | 13.58  | 1.81  | 39.3   | 1.76  | -2.6                | 3.3     |
| 2425    | 38.2     | 13.65  | 1.84  | 39.2   | 1.78  | -2.7                | 3.6     |
| 2450    | 38.1     | 13.73  | 1.87  | 39.2   | 1.80  | -2.9                | 4.0     |
| 2475    | 38.0     | 13.79  | 1.90  | 39.2   | 1.83  | -3.1                | 3.9     |
| 2500    | 37.9     | 13.85  | 1.93  | 39.1   | 1.85  | -3.3                | 3.9     |
| 2525    | 37.8     | 13.94  | 1.96  | 39.1   | 1.88  | -3.4                | 4.0     |
| 2550    | 37.7     | 14.02  | 1.99  | 39.1   | 1.91  | -3.6                | 4.2     |
| 2575    | 37.6     | 14.09  | 2.02  | 39.0   | 1.94  | -3.8                | 4.3     |
| 2600    | 37.5     | 14.17  | 2.05  | 39.0   | 1.96  | -4.0                | 4.4     |
| 2625    | 37.4     | 14.23  | 2.08  | 39.0   | 1.99  | -4.2                | 4.4     |
| 2650    | 37.3     | 14.29  | 2.11  | 38.9   | 2.02  | -4.3                | 4.4     |
| 2675    | 37.1     | 14.36  | 2.14  | 38.9   | 2.05  | -4.5                | 4.5     |
| 2700    | 37.0     | 14.43  | 2.17  | 38.9   | 2.07  | -4.8                | 4.6     |





Figure D-5

### 2.4 GHz Head Tissue Equivalent Matter

|                                    |                                                                                     |                            |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7                |  | SAR EVALUATION REPORT      |  | Reviewed by:<br>Quality Manager |
| Test Dates:<br>02/03/14 - 03/31/14 | DUT Type:<br>Portable Handset                                                       | APPENDIX D:<br>Page 4 of 5 |                                                                                       |                                 |

## 2 Composition / Information on ingredients

The Item is composed of the following ingredients:

|             |          |
|-------------|----------|
| Water       | 50 – 65% |
| Mineral oil | 10 – 30% |
| Emulsifiers | 8 – 25%  |
| Sodium salt | 0 – 1.5% |

**Figure D-6**  
**Composition of 5 GHz Head Tissue Equivalent Matter**

**Note:** 5GHz head liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

### Measurement Certificate / Material Test

|              |                                                 |
|--------------|-------------------------------------------------|
| Item Name    | Head Tissue Simulating Liquid (HBBL3500-5800V5) |
| Product No.  | SL AAH 502 AB (Charge: 120402-2)                |
| Manufacturer | SPEAG                                           |

### Measurement Method

TSL dielectric parameters measured using calibrated OCP probe (type DAK).

### Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

### Test Condition

Ambient Condition 22°C ; 30% humidity  
TSL Temperature 22°C  
Test Date 4-Apr-12

### Additional Information

TSL Density 0.985 g/cm<sup>3</sup>  
TSL Heat-capacity 3.383 kJ/(kg\*K)

### Results

| f [MHz] | Measured |       |       | Target |       | Diff.to Target (%) |         |
|---------|----------|-------|-------|--------|-------|--------------------|---------|
|         | HP-e     | sigma | sigma | eps    | sigma | Δ-eps              | Δ-sigma |
| 3400    | 38.7     | 14.96 | 2.83  | 38.0   | 2.81  | 1.8                | 0.7     |
| 3500    | 38.6     | 14.91 | 2.90  | 37.9   | 2.91  | 1.7                | -0.3    |
| 3600    | 38.5     | 14.92 | 2.99  | 37.8   | 3.02  | 1.7                | -0.9    |
| 3700    | 38.3     | 14.92 | 3.07  | 37.7   | 3.12  | 1.7                | -1.5    |
| 3800    | 38.2     | 14.94 | 3.16  | 37.6   | 3.22  | 1.7                | -1.9    |
| 3900    | 38.1     | 14.95 | 3.24  | 37.5   | 3.32  | 1.7                | -2.4    |
| 4000    | 38.0     | 15.00 | 3.34  | 37.4   | 3.43  | 1.8                | -2.5    |
| 4100    | 37.9     | 15.04 | 3.43  | 37.2   | 3.53  | 1.8                | -2.6    |
| 4200    | 37.8     | 15.08 | 3.52  | 37.1   | 3.63  | 1.8                | -2.9    |
| 4300    | 37.7     | 15.14 | 3.62  | 37.0   | 3.73  | 1.8                | -3.0    |
| 4400    | 37.5     | 15.18 | 3.71  | 36.9   | 3.84  | 1.7                | -3.1    |
| 4500    | 37.4     | 15.20 | 3.81  | 36.8   | 3.94  | 1.6                | -3.3    |
| 4600    | 37.3     | 15.29 | 3.91  | 36.7   | 4.04  | 1.6                | -3.2    |
| 4700    | 37.1     | 15.34 | 4.01  | 36.6   | 4.14  | 1.5                | -3.2    |
| 4800    | 37.0     | 15.39 | 4.11  | 36.4   | 4.25  | 1.4                | -3.2    |
| 4850    | 36.9     | 15.43 | 4.16  | 36.4   | 4.30  | 1.3                | -3.1    |
| 4900    | 36.8     | 15.45 | 4.21  | 36.3   | 4.35  | 1.3                | -3.1    |
| 4950    | 36.7     | 15.47 | 4.26  | 36.3   | 4.40  | 1.2                | -3.1    |
| 5000    | 36.7     | 15.50 | 4.31  | 36.2   | 4.45  | 1.2                | -3.1    |
| 5050    | 36.6     | 15.55 | 4.37  | 36.2   | 4.50  | 1.1                | -3.0    |
| 5100    | 36.5     | 15.60 | 4.43  | 36.1   | 4.55  | 1.1                | -2.8    |
| 5150    | 36.4     | 15.62 | 4.48  | 36.0   | 4.60  | 1.0                | -2.8    |
| 5200    | 36.4     | 15.65 | 4.53  | 36.0   | 4.66  | 1.0                | -2.8    |
| 5250    | 36.3     | 15.67 | 4.58  | 35.9   | 4.71  | 1.0                | -2.8    |
| 5300    | 36.2     | 15.70 | 4.63  | 35.9   | 4.76  | 1.0                | -2.7    |
| 5350    | 36.1     | 15.70 | 4.67  | 35.8   | 4.81  | 0.9                | -2.9    |
| 5400    | 36.1     | 15.74 | 4.73  | 35.8   | 4.86  | 0.8                | -2.7    |
| 5450    | 36.0     | 15.75 | 4.77  | 35.7   | 4.91  | 0.9                | -2.8    |
| 5500    | 35.9     | 15.75 | 4.82  | 35.6   | 4.96  | 0.8                | -2.9    |
| 5550    | 35.9     | 15.80 | 4.88  | 35.6   | 5.01  | 0.8                | -2.7    |
| 5600    | 35.8     | 15.82 | 4.93  | 35.5   | 5.07  | 0.7                | -2.7    |
| 5650    | 35.7     | 15.86 | 4.96  | 35.5   | 5.12  | 0.7                | -2.6    |
| 5700    | 35.7     | 15.88 | 5.03  | 35.4   | 5.17  | 0.7                | -2.6    |
| 5750    | 35.6     | 15.90 | 5.08  | 35.4   | 5.22  | 0.6                | -2.6    |
| 5800    | 35.5     | 15.94 | 5.14  | 35.3   | 5.27  | 0.6                | -2.4    |
| 5850    | 35.4     | 15.98 | 5.20  | 35.3   | 5.34  | 0.4                | -2.5    |
| 5900    | 35.4     | 16.02 | 5.26  | 35.3   | 5.40  | 0.2                | -2.6    |





**Figure D-7**  
**5GHz Head Tissue Equivalent Matter**

|                                    |                                                                                     |                       |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|-----------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7                |  | SAR EVALUATION REPORT |  | Reviewed by:<br>Quality Manager |
| Test Dates:<br>02/03/14 - 03/31/14 | DUT Type:<br>Portable Handset                                                       |                       |                                                                                       | APPENDIX D:<br>Page 5 of 5      |

## APPENDIX E: SAR SYSTEM VALIDATION

Per FCC KDB 865664 D02v01, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB 865664 D01 v01 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

**Table E-I**  
**SAR System Validation Summary**

| SAR SYSTEM # | FREQ. [MHz] | DATE      | PROBE SN | PROBE TYPE | PROBE CAL. POINT |      | COND.        | PERM.            | CW VALIDATION |                 |                | MOD. VALIDATION |             |      |
|--------------|-------------|-----------|----------|------------|------------------|------|--------------|------------------|---------------|-----------------|----------------|-----------------|-------------|------|
|              |             |           |          |            |                  |      | ( $\sigma$ ) | ( $\epsilon_r$ ) | SENSITIVITY   | PROBE LINEARITY | PROBE ISOTROPY | MOD. TYPE       | DUTY FACTOR | PAR  |
| B            | 750         | 11/5/2013 | 3288     | ES3DV3     | 750              | Head | 0.882        | 40.63            | PASS          | PASS            | PASS           | N/A             | N/A         | N/A  |
| H            | 835         | 6/20/2013 | 3318     | ES3DV3     | 835              | Head | 0.910        | 41.10            | PASS          | PASS            | PASS           | GMSK            | PASS        | N/A  |
| B            | 1750        | 11/6/2013 | 3288     | ES3DV3     | 1750             | Head | 1.406        | 40.47            | PASS          | PASS            | PASS           | N/A             | N/A         | N/A  |
| C            | 1900        | 8/13/2013 | 3263     | ES3DV3     | 1900             | Head | 1.458        | 38.68            | PASS          | PASS            | PASS           | GMSK            | PASS        | N/A  |
| K            | 2450        | 2/8/2014  | 3287     | ES3DV3     | 2450             | Head | 1.832        | 38.03            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| A            | 5200        | 1/15/2014 | 3920     | EX3DV4     | 5200             | Head | 4.529        | 36.23            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| A            | 5300        | 1/15/2014 | 3920     | EX3DV4     | 5300             | Head | 4.612        | 35.97            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| A            | 5500        | 1/15/2014 | 3920     | EX3DV4     | 5500             | Head | 4.788        | 35.63            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| A            | 5600        | 1/15/2014 | 3920     | EX3DV4     | 5600             | Head | 4.862        | 35.52            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| A            | 5800        | 1/15/2014 | 3920     | EX3DV4     | 5800             | Head | 5.122        | 35.25            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| C            | 750         | 8/14/2013 | 3263     | ES3DV3     | 750              | Body | 0.975        | 54.36            | PASS          | PASS            | PASS           | N/A             | N/A         | N/A  |
| C            | 835         | 8/14/2013 | 3263     | ES3DV3     | 835              | Body | 0.993        | 53.17            | PASS          | PASS            | PASS           | GMSK            | PASS        | N/A  |
| B            | 1750        | 11/6/2013 | 3288     | ES3DV3     | 1750             | Body | 1.534        | 51.18            | PASS          | PASS            | PASS           | N/A             | N/A         | N/A  |
| I            | 1900        | 7/1/2013  | 3319     | ES3DV3     | 1900             | Body | 1.502        | 52.10            | PASS          | PASS            | PASS           | GMSK            | PASS        | N/A  |
| D            | 1900        | 9/10/2013 | 3022     | ES3DV2     | 1900             | Body | 1.516        | 52.49            | PASS          | PASS            | PASS           | GMSK            | PASS        | N/A  |
| H            | 2450        | 6/21/2013 | 3318     | ES3DV3     | 2450             | Body | 2.006        | 51.66            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| E            | 5200        | 12/7/2013 | 3914     | EX3DV4     | 5200             | Body | 5.330        | 48.16            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| E            | 5300        | 12/7/2013 | 3914     | EX3DV4     | 5300             | Body | 5.481        | 47.91            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| E            | 5500        | 12/7/2013 | 3914     | EX3DV4     | 5500             | Body | 5.807        | 47.39            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |
| E            | 5800        | 12/7/2013 | 3914     | EX3DV4     | 5800             | Body | 6.240        | 46.70            | PASS          | PASS            | PASS           | OFDM            | N/A         | PASS |

NOTE: While the probes have been calibrated for both CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to KDB 865664.

|                                    |                                                                                     |                            |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG900R7                |  | SAR EVALUATION REPORT      |  | Reviewed by:<br>Quality Manager |
| Test Dates:<br>02/03/14 - 03/31/14 | DUT Type:<br>Portable Handset                                                       | APPENDIX E:<br>Page 1 of 1 |                                                                                       |                                 |