

FCC LTE REPORT

FCC Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Date of Issue:

June 05, 2015

Test Site/Location:

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil,
Majang-myeon, Icheon-si, Gyeonggi-do, Korea

Address:

129, Samsung-ro, Yeongtong-gu Suwon-si, Gyeonggi-do,
443-742 Rep. of Korea

Report No.: HCT-R-1506-F013

HCT FRN: 0005866421

FCC ID: A3LSMG9198

APPLICANT: SAMSUNG Electronics Co., Ltd.

FCC Model(s): SM-G9198

EUT Type: Mobile Phone

FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)

FCC Rule Part(s): §2 , §27

Folder open

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band41 (5)	2498.5 – 2687.5	4M50G7D	QPSK	0.161	22.07
		4M50W7D	16QAM	0.097	19.87
LTE – Band41 (10)	2501.0 – 2685.0	8M99G7D	QPSK	0.134	21.28
		8M96W7D	16QAM	0.107	20.31
LTE – Band41 (15)	2503.5 – 2682.5	13M5G7D	QPSK	0.133	21.24
		13M5W7D	16QAM	0.101	20.05
LTE – Band41 (20)	2506.0 – 2680.0	18M0G7D	QPSK	0.139	21.44
		17M9W7D	16QAM	0.109	20.38

Folder close

Mode (MHz)	Tx Frequency (MHz)	Modulation	EIRP	
			Max. Power (W)	Max. Power (dBm)
LTE – Band41 (5)	2498.5 – 2687.5	QPSK	0.093	19.69
		16QAM	0.075	18.76
LTE – Band41 (10)	2501.0 – 2685.0	QPSK	0.101	20.06
		16QAM	0.082	19.13
LTE – Band41 (15)	2503.5 – 2682.5	QPSK	0.101	20.03
		16QAM	0.078	18.92
LTE – Band41 (20)	2506.0 – 2680.0	QPSK	0.107	20.30
		16QAM	0.087	19.39

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a).



Report prepared by
: Kyounghoun Seo
Test engineer of RF Team



Approved by
: Sangjun Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1506-F013	June 05, 2015	- First Approval Report

Table of Contents

1. GENERAL INFORMATION	5
2. INTRODUCTION	6
2.1. EUT DESCRIPTION.....	6
2.2. MEASURING INSTRUMENT CALIBRATION	6
2.3. TEST FACILITY	6
3. DESCRIPTION OF TESTS	7
3.1 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	7
3.2 OCCUPIED BANDWIDTH.	8
3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	9
3.4 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	10
4. LIST OF TEST EQUIPMENT	11
5. SUMMARY OF TEST RESULTS	12
6. SAMPLE CALCULATION	13
7. TEST DATA	15
7.1 EQUIVALENT ISOTROPIC RADIATED POWER (Band 41)_Folder open	15
7.2 EQUIVALENT ISOTROPIC RADIATED POWER (Band 41)_Folder close.....	17
7.3 RADIATED SPURIOUS EMISSIONS_Folder open	19
7.3.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 41 LTE)	19
7.3.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 41 LTE).....	20
7.3.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 41 LTE).....	21
7.3.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 41 LTE).....	22
7.4 RADIATED SPURIOUS EMISSIONS_Folder close.....	23
7.4.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 41 LTE)	23
7.4.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 41 LTE).....	24
7.4.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 41 LTE).....	25
7.4.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 41 LTE).....	26
7.5 OCCUPIED BANDWIDTH	27
7.6 CONDUCTED SPURIOUS EMISSIONS	28
7.6.1 BAND EDGE.....	29
7.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	30
7.7.1 FREQUENCY STABILITY (5 MHz Band 41 LTE)	30
7.7.2 FREQUENCY STABILITY (10 MHz Band 41 LTE)	31
7.7.3 FREQUENCY STABILITY (15 MHz Band 41 LTE)	32
7.7.4 FREQUENCY STABILITY (20 MHz Band 41 LTE)	33
8. TEST PLOTS.....	34

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: SAMSUNG Electronics Co., Ltd.

Address: 129, Samsung-ro, Yeongtong-gu Suwon-si, Gyeonggi-do, 443-742 Rep. of Korea

FCC ID: A3LSMG9198

Application Type: Certification

FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)

FCC Rule Part(s): §2 , §27

EUT Type: Mobile Phone

FCC Model(s): SM-G9198

Tx Frequency: 2498.5 MHz – 2687.5 MHz (LTE – Band 41): 5 MHz
2501.0 MHz – 2685.0 MHz (LTE – Band 41): 10 MHz
2503.5 MHz – 2682.5 MHz (LTE – Band 41): 15 MHz
2506.0 MHz – 2680.0 MHz (LTE – Band 41): 20 MHz

Max. RF Output Power:

Folder open	
Band 41 (5 MHz) :	0.161 W (QPSK) (22.07 dBm) 0.097 W (16-QAM) (19.87 dBm)
Band 41 (10 MHz) :	0.134 W (QPSK) (21.28 dBm) 0.107 W (16-QAM) (20.31 dBm)
Band 41 (15 MHz) :	0.133 W (QPSK) (21.24 dBm) 0.101 W (16-QAM) (20.05 dBm)
Band 41 (20 MHz) :	0.139 W (QPSK) (21.44 dBm) 0.109 W (16-QAM) (20.38 dBm)
Folder close	
Band 41 (5 MHz) :	0.093 W (QPSK) (19.69 dBm) 0.075 W (16-QAM) (18.76 dBm)
Band 41 (10 MHz) :	0.101 W (QPSK) (20.06 dBm) 0.082 W (16-QAM) (19.13 dBm)
Band 41 (15 MHz) :	0.101 W (QPSK) (20.03 dBm) 0.078 W (16-QAM) (18.92 dBm)
Band 41 (20 MHz) :	0.107 W (QPSK) (20.30 dBm) 0.087 W (16-QAM) (19.39 dBm)

Emission Designator(s):

Band 41 (5 MHz) :	4M50G7D (QPSK) / 4M50W7D (16-QAM)
Band 41 (10 MHz) :	8M99G7D (QPSK) / 8M96W7D (16-QAM)
Band 41 (15 MHz) :	13M5G7D (QPSK) / 13M5W7D (16-QAM)
Band 41 (20 MHz) :	18M0G7D (QPSK) / 17M9W7D (16-QAM)

Date(s) of Tests: April 24, 2015 ~ June 04, 2015

Antenna Specification Manufacturer: RFTech Co., LTD.
Antenna type: Internal Antenna
Peak Gain: Band 41 : 2.542 dBi

2. INTRODUCTION

2.1. EUT DESCRIPTION

The SAMSUNG Electronics Co., Ltd. SM-G9198 Mobile Phone consists of LTE 41.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea.**

3. DESCRIPTION OF TESTS

3.1 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS

Note: EIRP(Equivalent Isotropic Radiated Power)

Test Procedure

Radiated emission measurements are performed in the Fully-anechoic chamber. The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-D-2010 Clause 2.2.17. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission. The level and position of the maximized emission is recorded with the spectrum analyzer using RMS detector.

A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss}_{(dB)} + \text{antenna gain}_{(dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.


The maximum EIRP is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

Radiated spurious emissions

1. Frequency Range : 30 MHz ~ 10th Harmonics of highest channel fundamental frequency.
2. Measured distance : 30 MHz ~ 11 GHz at 3 m
11 GHz ~ 27 GHz at 1m
3. The EUT was setup to maximum output power.
4. The high, low and a middle channel were tested for out of band measurements.

3.2 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

Test Procedure

OBW is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 4.2.

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels(low, middle and high operational range.)

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

Spurious and harmonic emissions at antenna terminal is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 6.0.

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power. The 1 MHz RBW was used to scan from 30 MHz to 26.5 GHz. And limit is -25 dBm. The high, low and a middle channel were tested for out of band measurements.


- Channel Edge Requirement : In the 1MHz bands immediately outside and adjacent to the channel, a resolution bandwidth of at least 2 % of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit is -10 dBm on all frequencies between the channel edge and 5 MHz from the channel edge, -13 dBm on all frequencies between 5 MHz and X MHz from the channel edge, -25 dBm on all frequencies more than X MHz from channel edge, where X is the greater of 6 MHz or the actual emission bandwidth. In addition, the attenuation factor shall not be less than -13 dBm on all frequencies between 2490.5 MHz and 2496 MHz and -25 dBm at below 2490.5 MHz.

NOTES: The analyzer plot offsets were determined by below conditions.

- For LTE Band 41, total offset 27.5 dBm = 20 dBm attenuator + 6 dBm Divider + 1.5 dBm RF cables.

3.4 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



* Nominal Operating Voltage

Test Procedure

Frequency stability is tested in accordance with ANSI/TIA-603-D-2010 section 2.2.2.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 100 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block(LTE Band41).

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
Agilent	N1921A/ Power Sensor	MY45241059	Annual	07/09/2015
Agilent	N1911A/ Power Meter	MY45100523	Annual	01/15/2016
MITEQ	AMF-6D-001180-35-20P/AMP	1081666	Annual	09/04/2015
Wainwright	WHK1.2/15G-10EF/H.P.F	4	Annual	04/27/2016
Wainwright	WRCJV2400/2483.5-2370/2520-60/12SS / B.R.F.	1	Annual	06/17/2015
Wainwright	WHK3.3/18G-10EF/H.P.F	2	Annual	04/27/2016
Hewlett Packard	11667B / Power Splitter	10545	Annual	02/22/2016
Hewlett Packard	11667B / Power Splitter	11275	Annual	04/29/2016
Digital	EP-3010/ Power Supply	3110117	Annual	10/29/2015
Schwarzbeck	UHAP/ Dipole Antenna	557	Biennial	03/23/2017
Schwarzbeck	UHAP/ Dipole Antenna	558	Biennial	03/23/2017
Korea Engineering	KR-1005L / Chamber	KRAC05063-3CH	Annual	10/29/2015
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	Biennial	09/01/2016
Schwarzbeck	BBHA 9120D/ Horn Antenna	1151	Biennial	07/05/2015
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170541	Biennial	07/05/2015
WEINSCHEL	ATTENUATOR	BR0592	Annual	10/22/2015
REOHDE&SCHWARZ	FSV40/Spectrum Analyzer	1307.9002K40-100931-NK	Annual	06/04/2016
Agilent	8960 (E5515C)/ Base Station	MY48360222	Annual	08/26/2015
Agilent	N9020A/ Signal Analyzer	MY51240695	Annual	02/12/2016
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6200863156	Annual	03/24/2016

5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 27.53(m)(4)	Band Edge / Conducted Spurious Emissions.	< 40 + 10log10 (P[Watts]) at Channel edges < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges		PASS
* 2.1046	Conducted Output Power	N/A		PASS
2.1055, 27.54	Frequency stability	Emission must remain in band		PASS
27.50(h)(2)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP	RADIATED	PASS
2.1053, 27.53(m)(4)	Undesirable Emissions	< 40 + 10log10 (P[Watts]) at Channel edges < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges		PASS

*See SAR Report

6. SAMPLE CALCULATION

A. EIRP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
	channel	Freq.(MHz)						W	dBm
LTE Band 41	40620.0	2,593.0	-16.35	18.26	10.72	1.38	V	0.575	27.60

$$\text{EIRP} = \text{SubstituteLEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a wooden tripod is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of Equivalent Isotropic Radiated Power (**EIRP**).

B. Emission Designator

QPSK Modulation

5 MHz Bandwidth

Emission Designator = 4M50G7D

LTE BW = 8.95 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

10 MHz Bandwidth

Emission Designator = 8M95G7D

LTE BW = 8.95 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

15 MHz Bandwidth

Emission Designator = 13M5G7D

LTE BW = 13.47 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

20 MHz Bandwidth

Emission Designator = 18M0G7D

LTE BW = 18.03 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

5 MHz Bandwidth

Emission Designator = 4M51W7D

LTE BW = 8.94 MHz

W = main carrier modulated in a combination of two
or more of the following modes;
amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

10 MHz Bandwidth

Emission Designator = 8M94W7D

LTE BW = 8.94 MHz

W = main carrier modulated in a combination of two
or more of the following modes;
amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

15 MHz Bandwidth

Emission Designator = 13M5W7D

LTE BW = 13.47MHz

W = main carrier modulated in a combination of two
or more of the following modes;
amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

20 MHz Bandwidth

Emission Designator = 18M0W7D

LTE BW = 18.03 MHz

W = main carrier modulated in a combination of two
or more of the following modes;
amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

7. TEST DATA

7.1 EQUIVALENT ISOTROPIC RADIATED POWER (Band 41)_Folder open

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2498.5	5 MHz	QPSK	-27.76	7.60	10.62	1.60	H	0.046	16.62
		16-QAM	-27.55	7.81	10.62	1.60	H	0.048	16.83
2593.0		QPSK	-25.80	9.98	10.72	1.62	H	0.081	19.08
		16-QAM	-27.55	8.23	10.72	1.62	H	0.054	17.33
2687.5		QPSK	-22.95	13.03	10.71	1.67	H	0.161	22.07
		16-QAM	-25.15	10.83	10.71	1.67	H	0.097	19.87

Equivalent Isotropic Radiated Power Data (5 MHz Band 41 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2501.0	10 MHz	QPSK	-27.47	7.88	10.63	1.60	H	0.049	16.91
		16-QAM	-28.42	6.93	10.63	1.60	H	0.039	15.96
2593.0		QPSK	-26.26	9.52	10.72	1.62	H	0.073	18.62
		16-QAM	-27.10	8.68	10.72	1.62	H	0.060	17.78
2685.0		QPSK	-23.73	12.24	10.71	1.67	H	0.134	21.28
		16-QAM	-24.70	11.27	10.71	1.67	H	0.107	20.31

Equivalent Isotropic Radiated Power Data (10 MHz Band 41 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2503.5	15 MHz	QPSK	-27.48	7.86	10.64	1.60	H	0.049	16.90
		16-QAM	-28.44	6.90	10.64	1.60	H	0.039	15.94
2593.0		QPSK	-25.96	9.82	10.72	1.62	H	0.078	18.92
		16-QAM	-27.19	8.59	10.72	1.62	H	0.059	17.69
2682.5		QPSK	-23.75	12.20	10.72	1.68	H	0.133	21.24
		16-QAM	-24.94	11.01	10.72	1.68	H	0.101	20.05

Equivalent Isotropic Radiated Power Data (15 MHz Band 41 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2506.0	20 MHz	QPSK	-27.55	7.80	10.64	1.61	H	0.048	16.83
		16-QAM	-28.40	6.95	10.64	1.61	H	0.040	15.98
2593.0		QPSK	-26.35	9.43	10.72	1.62	H	0.071	18.53
		16-QAM	-27.36	8.42	10.72	1.62	H	0.056	17.52
2680.0		QPSK	-23.53	12.40	10.72	1.68	H	0.139	21.44
		16-QAM	-24.59	11.34	10.72	1.68	H	0.109	20.38

Equivalent Isotropic Radiated Power Data (20 MHz Band 41 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. Turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For LTE signals, a peak detector is used, with $RBW \geq OBW$, $VBW \geq 3 \times RBW$. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is y plane in LTE mode. Also worst case of detecting Antenna is horizontal polarization in LTE mode.

7.2 EQUIVALENT ISOTROPIC RADIATED POWER (Band 41)_Folder close

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2498.5	5 MHz	QPSK	-24.98	10.38	10.62	1.60	H	0.087	19.40
		16-QAM	-25.81	9.55	10.62	1.60	H	0.072	18.57
2593.0		QPSK	-25.95	9.83	10.72	1.62	H	0.078	18.93
		16-QAM	-26.94	8.84	10.72	1.62	H	0.062	17.94
2687.5		QPSK	-25.33	10.65	10.71	1.67	H	0.093	19.69
		16-QAM	-26.26	9.72	10.71	1.67	H	0.075	18.76

Equivalent Isotropic Radiated Power Data (5 MHz Band 41 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2501.0	10 MHz	QPSK	-24.93	10.42	10.63	1.60	H	0.088	19.45
		16-QAM	-25.79	9.56	10.63	1.60	H	0.072	18.59
2593.0		QPSK	-25.96	9.82	10.72	1.62	H	0.078	18.92
		16-QAM	-26.72	9.06	10.72	1.62	H	0.065	18.16
2685.0		QPSK	-24.95	11.02	10.71	1.67	H	0.101	20.06
		16-QAM	-25.88	10.09	10.71	1.67	H	0.082	19.13

Equivalent Isotropic Radiated Power Data (10 MHz Band 41 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2503.5	15 MHz	QPSK	-24.87	10.47	10.64	1.60	H	0.089	19.51
		16-QAM	-25.83	9.51	10.64	1.60	H	0.072	18.55
2593.0		QPSK	-25.69	10.09	10.72	1.62	H	0.083	19.19
		16-QAM	-26.76	9.02	10.72	1.62	H	0.065	18.12
2682.5		QPSK	-24.96	10.99	10.72	1.68	H	0.101	20.03
		16-QAM	-26.07	9.88	10.72	1.68	H	0.078	18.92

Equivalent Isotropic Radiated Power Data (15 MHz Band 41 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2506.0	20 MHz	QPSK	-24.95	10.40	10.64	1.61	H	0.088	19.43
		16-QAM	-25.85	9.50	10.64	1.61	H	0.071	18.53
2593.0		QPSK	-25.88	9.90	10.72	1.62	H	0.079	19.00
		16-QAM	-26.79	8.99	10.72	1.62	H	0.064	18.09
2680.0		QPSK	-24.67	11.26	10.72	1.68	H	0.107	20.30
		16-QAM	-25.58	10.35	10.72	1.68	H	0.087	19.39

Equivalent Isotropic Radiated Power Data (20 MHz Band 41 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. Turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For LTE signals, a peak detector is used, with $RBW \geq OBW$, $VBW \geq 3 \times RBW$. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is x plane in LTE mode. Also worst case of detecting Antenna is horizontal polarization in LTE mode.

7.3 RADIATED SPURIOUS EMISSIONS_Folder open

7.3.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 41 LTE)

☒ OPERATING FREQUENCY : 2687.50 MHz
☒ MEASURED OUTPUT POWER: 22.07 dBm = 0.161 W
☒ MODULATION SIGNAL: 5 MHz QPSK
☒ DISTANCE: 3 meters
☒ LIMIT: $55 + 10 \log_{10}(W)$ = 35.07 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39675.0 (2,498.5)	4,997.0	-49.22	12.41	-48.40	2.40	H	-38.39	60.46
	7,495.5	-59.08	11.04	-49.85	2.96	H	-41.77	63.84
	9,994.0	-55.51	11.67	-40.28	3.64	V	-32.25	54.32
40620.0 (2,593.0)	5,186.0	-59.79	12.57	-58.06	2.42	V	-47.91	69.98
	7,779.0	-59.29	11.36	-49.99	3.07	V	-41.70	63.77
	10,372.0	-56.57	11.25	-40.74	3.81	V	-33.30	55.37
41565.0 (2,687.5)	5,375.0	-56.91	13.01	-56.05	2.45	V	-45.49	67.56
	8,062.5	-59.36	11.11	-47.79	3.20	V	-39.88	61.95
	10,750.0	-56.45	11.03	-40.53	3.79	V	-33.29	55.36

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

7.3.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 41 LTE)

■ OPERATING FREQUENCY : 2685.00 MHz
 ■ MEASURED OUTPUT POWER: 21.28 dBm = 0.134 W
 ■ MODULATION SIGNAL: 10 MHz QPSK
 ■ DISTANCE: 3 meters
 ■ LIMIT: $55 + 10 \log_{10}(W) = 34.28 \text{ dBc}$

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39700.0 (2,501.0)	5,002.0	-49.22	12.41	-48.27	2.40	V	-38.26	59.54
	7,503.0	-57.27	11.05	-48.15	2.97	H	-40.07	61.35
	10,004.0	-57.82	11.68	-42.97	3.68	H	-34.97	56.25
40620.0 (2,593.0)	5,186.0	-58.70	12.57	-56.97	2.42	H	-46.82	68.10
	7,779.0	-56.93	11.36	-47.63	3.07	H	-39.34	60.62
	10,372.0	-59.13	11.25	-43.30	3.81	H	-35.86	57.14
41540.0 (2,685.0)	5,370.0	-56.38	13.01	-55.49	2.44	V	-44.92	66.20
	8,055.0	-56.71	11.08	-44.95	3.23	H	-37.10	58.38
	10,740.0	-56.12	11.05	-39.66	3.85	V	-32.46	53.74

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

7.3.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 41 LTE)

☒ OPERATING FREQUENCY : 2682.50 MHz
☒ MEASURED OUTPUT POWER: 21.24 dBm = 0.133 W
☒ MODULATION SIGNAL: 15 MHz QPSK
☒ DISTANCE: 3 meters
☒ LIMIT: $55 + 10 \log_{10}(W) =$ 34.24 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39725.0 (2,503.5)	5,007.0	-49.90	12.40	-48.77	2.39	V	-38.76	60.00
	7,510.5	-56.83	11.07	-47.81	2.96	H	-39.70	60.94
	10,014.0	-55.50	11.68	-40.69	3.75	V	-32.76	54.00
40620.0 (2,593.0)	5,186.0	-57.39	12.57	-55.66	2.42	V	-45.51	66.75
	7,779.0	-57.51	11.36	-48.21	3.07	V	-39.92	61.16
	10,372.0	-57.13	11.25	-41.30	3.81	V	-33.86	55.10
41515.0 (2,682.5)	5,365.0	-57.85	13.01	-56.99	2.44	H	-46.42	67.66
	8,047.5	-56.39	11.06	-44.56	3.24	H	-36.74	57.98
	10,730.0	-57.16	11.07	-40.70	3.84	V	-33.47	54.71

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

7.3.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 41 LTE)

☒ OPERATING FREQUENCY : 2680.00 MHz
☒ MEASURED OUTPUT POWER: 21.44 dBm = 0.139 W
☒ MODULATION SIGNAL: 20 MHz QPSK
☒ DISTANCE: 3 meters
☒ LIMIT: $55 + 10 \log_{10}(W) =$ 34.44 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39750.0 (2,506.0)	5,012.0	-51.47	12.39	-50.26	2.38	V	-40.25	61.69
	7,518.0	-56.37	11.09	-47.49	3.02	V	-39.42	60.86
	10,024.0	-56.03	11.69	-41.15	3.81	V	-33.27	54.71
40620.0 (2,593.0)	5,186.0	-57.88	12.57	-56.15	2.42	H	-46.00	67.44
	7,779.0	-57.38	11.36	-48.08	3.07	V	-39.79	61.23
	10,372.0	-55.49	11.25	-39.66	3.81	V	-32.22	53.66
41490.0 (2,680.0)	5,360.0	-56.96	13.01	-56.13	2.43	V	-45.55	66.99
	8,040.0	-56.60	11.06	-44.98	3.23	H	-37.15	58.59
	10,720.0	-53.63	11.08	-37.69	3.84	V	-30.45	51.89

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

7.4 RADIATED SPURIOUS EMISSIONS_Folder close

7.4.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 41 LTE)

☒ OPERATING FREQUENCY : 2687.50 MHz
☒ MEASURED OUTPUT POWER: 19.69 dBm = 0.093 W
☒ MODULATION SIGNAL: 5 MHz QPSK
☒ DISTANCE: 3 meters
☒ LIMIT: $55 + 10 \log_{10}(W) = 32.69 \text{ dBc}$

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39675.0 (2,498.5)	4,997.0	-49.82	12.41	-49.00	2.40	V	-38.99	58.68
	7,495.5	-58.55	11.04	-49.32	2.96	V	-41.24	60.93
	9,994.0	-57.81	11.67	-42.58	3.64	V	-34.55	54.24
40620.0 (2,593.0)	5,186.0	-58.49	12.57	-56.76	2.42	H	-46.61	66.30
	7,779.0	-58.44	11.36	-49.14	3.07	H	-40.85	60.54
	10,372.0	-55.70	11.25	-39.87	3.81	H	-32.43	52.12
41565.0 (2,687.5)	5,375.0	-59.49	13.01	-58.63	2.45	H	-48.07	67.76
	8,062.5	-56.81	11.11	-45.24	3.20	V	-37.33	57.02
	10,750.0	-59.58	11.03	-43.66	3.79	V	-36.42	56.11

NOTES: 1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method

according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

- We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
- All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

7.4.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 41 LTE)

■ OPERATING FREQUENCY : 2685.00 MHz
 ■ MEASURED OUTPUT POWER: 20.06 dBm = 0.101 W
 ■ MODULATION SIGNAL: 10 MHz QPSK
 ■ DISTANCE: 3 meters
 ■ LIMIT: $55 + 10 \log_{10}(W) = 33.06 \text{ dBc}$

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39700.0 (2,501.0)	5,002.0	-52.34	12.41	-51.39	2.40	V	-41.38	61.44
	7,503.0	-58.35	11.05	-49.23	2.97	V	-41.15	61.21
	10,004.0	-59.93	11.68	-45.08	3.68	V	-37.08	57.14
40620.0 (2,593.0)	5,186.0	-58.62	12.57	-56.89	2.42	V	-46.74	66.80
	7,779.0	-59.28	11.36	-49.98	3.07	V	-41.69	61.75
	10,372.0	-59.64	11.25	-43.81	3.81	V	-36.37	56.43
41540.0 (2,685.0)	5,370.0	-57.50	13.01	-56.61	2.44	H	-46.04	66.10
	8,055.0	-60.20	11.08	-48.44	3.23	H	-40.59	60.65
	10,740.0	-57.79	11.05	-41.33	3.85	V	-34.13	54.19

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

7.4.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 41 LTE)

■ OPERATING FREQUENCY : 2682.50 MHz
 ■ MEASURED OUTPUT POWER: 20.03 dBm = 0.101 W
 ■ MODULATION SIGNAL: 15 MHz QPSK
 ■ DISTANCE: 3 meters
 ■ LIMIT: $55 + 10 \log_{10}(W) =$ 33.03 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39725.0 (2,503.5)	5,007.0	-49.82	12.40	-48.69	2.39	V	-38.68	58.71
	7,510.5	-58.57	11.07	-49.55	2.96	H	-41.44	61.47
	10,014.0	-58.61	11.68	-43.80	3.75	V	-35.87	55.90
40620.0 (2,593.0)	5,186.0	-59.77	12.57	-58.04	2.42	V	-47.89	67.92
	7,779.0	-59.23	11.36	-49.93	3.07	V	-41.64	61.67
	10,372.0	-56.12	11.25	-40.29	3.81	H	-32.85	52.88
41515.0 (2,682.5)	5,365.0	-56.25	13.01	-55.39	2.44	V	-44.82	64.85
	8,047.5	-58.40	11.06	-46.57	3.24	V	-38.75	58.78
	10,730.0	-57.90	11.07	-41.44	3.84	V	-34.21	54.24

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

7.4.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 41 LTE)

■ OPERATING FREQUENCY : 2680.00 MHz
 ■ MEASURED OUTPUT POWER: 20.30 dBm = 0.107 W
 ■ MODULATION SIGNAL: 20 MHz QPSK
 ■ DISTANCE: 3 meters
 ■ LIMIT: $55 + 10 \log_{10}(W) = 33.30 \text{ dBc}$

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39750.0 (2,506.0)	5,012.0	-50.64	12.39	-49.43	2.38	H	-39.42	59.72
	7,518.0	-57.08	11.09	-48.20	3.02	H	-40.13	60.43
	10,024.0	-56.32	11.69	-41.44	3.81	H	-33.56	53.86
40620.0 (2,593.0)	5,186.0	-57.73	12.57	-56.00	2.42	V	-45.85	66.15
	7,779.0	-57.24	11.36	-47.94	3.07	V	-39.65	59.95
	10,372.0	-57.34	11.25	-41.51	3.81	V	-34.07	54.37
41490.0 (2,680.0)	5,360.0	-58.36	13.01	-57.53	2.43	V	-46.95	67.25
	8,040.0	-56.59	11.06	-44.97	3.23	H	-37.14	57.44
	10,720.0	-56.98	11.08	-41.04	3.84	H	-33.80	54.10

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

7.5 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
Band 41	5 MHz	2593.0	QPSK	25	0	4.5044
			16-QAM	25	0	4.5004
	10 MHz		QPSK	50	0	8.9873
			16-QAM	50	0	8.9570
	15 MHz		QPSK	75	0	13.4730
			16-QAM	75	0	13.4620
	20 MHz		QPSK	100	0	17.9740
			16-QAM	100	0	17.9470

- Plots of the EUT's Occupied Bandwidth are shown Page 35 ~ 38

7.6 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Frequency of Maximum Harmonic (GHz)	Maximum Data [dBm]
Band 41	5	2498.5	QPSK	1	0	5.9158	-31.371
		2593.0		1	0	5.7328	-30.756
		2687.5		1	0	7.2044	-30.909
	10	2501.0		1	0	5.9911	-30.962
		2593.0		1	0	7.7468	-31.353
		2685.0		1	0	3.2957	-31.291
	15	2503.5		1	0	5.8325	-30.745
		2593.0		1	0	2.7907	-30.639
		2682.5		1	0	5.4427	-31.651
	20	2506.0		1	0	3.2174	-30.847
		2593.0		1	0	5.7672	-31.174
		2680.0		1	0	5.7548	-30.781

- Plots of the EUT's Conducted Spurious Emissions are shown Page 45 ~ 56

7.6.1 BAND EDGE

Band	Band Width (MHz)	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Channel Edge Data [dBm]					
						Channel Edge (Limit: -10 dBm)		5 MHz ~ X MHz from the Channel Edge (Limit: -13 dBm)		X MHz ~ from the Channel Edge (Limit: -25 dBm)	
						Lower	Upper	Lower	Upper	Lower	Upper
Band 41	5	2498.5	QPSK	25	0	-16.87	-15.26	-34.48	-32.42	-37.13	-35.38
		2593.0		25	0	-15.34	-16.20	-35.28	-35.75	-36.11	-36.57
		2687.5		25	0	-10.34	-11.24	-30.95	-33.29	-32.32	-34.39
	10	2501.0		50	0	-24.20	-18.69	-31.00	-25.05	-44.05	-37.05
		2593.0		50	0	-20.85	-22.08	-26.05	-27.72	-37.74	-38.94
		2685.0		50	0	-16.37	-19.13	-22.63	-27.43	-33.54	-37.25
	15	2503.5		75	0	-27.46	-21.73	-33.16	-25.51	-45.75	-40.10
		2593.0		75	0	-22.27	-23.71	-25.33	-26.91	-39.86	-53.71
		2682.5		75	0	-18.98	-22.87	-22.99	-28.98	-34.70	-48.30
	20	2506.0		100	0	-21.49	-17.61	-21.35	-18.14	-40.92	-28.39
		2593.0		100	0	-18.18	-19.72	-19.63	-21.15	-30.93	-31.33
		2680.0		100	0	-15.59	-20.47	-18.86	-24.45	-28.08	-32.66


- Plots of the EUT's Band Edge are shown Page 39 ~ 44

7.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

7.7.1 FREQUENCY STABILITY (5 MHz Band 41 LTE)

☒ OPERATING FREQUENCY: 2593.000,000 Hz
☒ CHANNEL: 40620 (5 MHz)
☒ REFERENCE VOLTAGE: 3.8 VDC
☒ DEVIATION LIMIT: -


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.80	+20(Ref)	2593 000 017	0	0.000 000	0.000
100%		-30	2592 999 998	-18.5	-0.000 001	-0.007
100%		-20	2593 000 000	-16.2	-0.000 001	-0.006
100%		-10	2592 999 996	-20.4	-0.000 001	-0.008
100%		0	2592 999 990	-26.4	-0.000 001	-0.010
100%		+10	2592 999 993	-23.3	-0.000 001	-0.009
100%		+30	2592 999 994	-22.4	-0.000 001	-0.009
100%		+40	2592 999 994	-22.6	-0.000 001	-0.009
100%		+50	2592 999 995	-21.3	-0.000 001	-0.008
Batt. Endpoint	3.23	+20	2593 000 000	-16.5	-0.000 001	-0.006



7.7.2 FREQUENCY STABILITY (10 MHz Band 41 LTE)

☒ OPERATING FREQUENCY: 2593.000,000 Hz
☒ CHANNEL: 40620 (10 MHz)
☒ REFERENCE VOLTAGE: 3.8 VDC
☒ DEVIATION LIMIT: -


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.80	+20(Ref)	2593 000 019	0	0.000 000	0.000
100%		-30	2593 000 001	-18.3	-0.000 001	-0.007
100%		-20	2592 999 996	-23.4	-0.000 001	-0.009
100%		-10	2593 000 000	-18.8	-0.000 001	-0.007
100%		0	2592 999 997	-22.0	-0.000 001	-0.008
100%		+10	2592 999 994	-25.1	-0.000 001	-0.010
100%		+30	2592 999 995	-24.2	-0.000 001	-0.009
100%		+40	2592 999 997	-22.3	-0.000 001	-0.009
100%		+50	2593 000 002	-17.5	-0.000 001	-0.007
Batt. Endpoint	3.23	+20	2592 999 998	-20.9	-0.000 001	-0.008



7.7.3 FREQUENCY STABILITY (15 MHz Band 41 LTE)

☒ OPERATING FREQUENCY: 2593.000,000 Hz
☒ CHANNEL: 40620 (15 MHz)
☒ REFERENCE VOLTAGE: 3.8 VDC
☒ DEVIATION LIMIT: -


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.80	+20(Ref)	2593 000 020	0	0.000 000	0.000
100%		-30	2593 000 001	-18.9	-0.000 001	-0.007
100%		-20	2593 000 000	-20.4	-0.000 001	-0.008
100%		-10	2593 000 006	-14.3	-0.000 001	-0.006
100%		0	2592 999 998	-22.6	-0.000 001	-0.009
100%		+10	2593 000 007	-13.2	-0.000 001	-0.005
100%		+30	2593 000 002	-18.3	-0.000 001	-0.007
100%		+40	2593 000 001	-19.6	-0.000 001	-0.008
100%		+50	2593 000 003	-17.3	-0.000 001	-0.007
Batt. Endpoint	3.23	+20	2592 999 998	-22.7	-0.000 001	-0.009



7.7.4 FREQUENCY STABILITY (20 MHz Band 41 LTE)


☒ OPERATING FREQUENCY: 2593.000,000 Hz
☒ CHANNEL: 40620 (20 MHz)
☒ REFERENCE VOLTAGE: 3.8 VDC
☒ DEVIATION LIMIT: -

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.80	+20(Ref)	2593 000 018	0	0.000 000	0.000
100%		-30	2593 000 001	-17.7	-0.000 001	-0.007
100%		-20	2593 000 002	-16.0	-0.000 001	-0.006
100%		-10	2593 000 005	-13.6	-0.000 001	-0.005
100%		0	2592 999 995	-23.8	-0.000 001	-0.009
100%		+10	2593 000 001	-17.5	-0.000 001	-0.007
100%		+30	2593 000 002	-16.2	-0.000 001	-0.006
100%		+40	2593 000 005	-13.7	-0.000 001	-0.005
100%		+50	2593 000 000	-18.3	-0.000 001	-0.007
Batt. Endpoint	3.23	+20	2592 999 998	-20.6	-0.000 001	-0.008




8. TEST PLOTS


BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40620 QPSK RB 25)




BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40620 16-QAM RB 25)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40620 QPSK RB 50)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40620 16-QAM RB 50)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40620 QPSK RB 75)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40620 16-QAM RB 75)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40620 QPSK RB 100)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40620 16-QAM RB 100)




BAND 41. Low Channel Edge Plot (5 MHz Ch.39675 QPSK RB 25)




BAND 41. Mid Channel Edge Plot (5 MHz Ch.40620 QPSK RB 25)




BAND 41. High Channel Edge Plot (5 MHz Ch.41565 QPSK RB 25)




BAND 41. Low Channel Edge Plot (10 MHz Ch.39700 QPSK RB 50)




BAND 41. Mid Channel Edge Plot (10 MHz Ch.40620 QPSK RB 50)




BAND 41. High Channel Edge Plot (10 MHz Ch.41540 QPSK RB 50)




BAND 41. Low Channel Edge Plot (15 MHz Ch.39725 QPSK RB 75)




BAND 41. Mid Channel Edge Plot (15 MHz Ch.40620 QPSK RB 75)




BAND 41. High Channel Edge Plot (15 MHz Ch.41515 QPSK RB 75)




BAND 41. Low Channel Edge Plot (20 MHz Ch.39750 QPSK RB 100)




BAND 41. Mid Channel Edge Plot (20 MHz Ch.40620 QPSK RB 100)




BAND 41. High Channel Edge Plot (20 MHz Ch.41490 QPSK RB 100)




BAND 41. Conducted Spurious Plot 1 (5 MHz Ch.39675 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 2 (5 MHz Ch. 39675 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 1 (5 MHz Ch.40620 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 2 (5 MHz Ch. 40620 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 1 (5 MHz Ch.41565 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 2 (5 MHz Ch. 41565 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 1 (10 MHz Ch.39700 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 2 (10 MHz Ch. 39700 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 1 (10 MHz Ch.40620 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 2 (10 MHz Ch. 40620 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 1 (10 MHz Ch.41540 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 2 (10 MHz Ch. 41540 QPSK RB 1, Offset 0)



BAND 41. Conducted Spurious Plot 1 (15 MHz Ch.39725 QPSK RB 1, Offset 0)



BAND 41. Conducted Spurious Plot 2 (15 MHz Ch. 39725 QPSK RB 1, Offset 0)



Agilent Spectrum Analyzer - Swept SA

RF 50 Ω AC SENSE:INT ALIGN: AUTO 10:07:39 AM Jun 04, 2015

PN0: Fast Trig: Free Run
IFGain: Low #Atten: 20 dB

#Avg Type: RMS

TRACE 1 2 3 4 5 6
TYPE IN WWWWWW
DET A N N N N N

Ref Offset 27.5 dB
Ref 35.00 dBm

Mkr1 2.790 7 GHz
-30.639 dBm

10 dB/div
Log

25.0
15.0
5.00
-5.00
-15.0
-25.0
-35.0
-45.0
-55.0

Start 30 MHz
#Res BW 1.0 MHz

Stop 10.000 GHz
#VBW 3.0 MHz
Sweep 17.3 ms (20001 pts)

Auto Tune
Center Freq
5.015000000 GHz
Start Freq
30.000000 MHz
Stop Freq
10.000000000 GHz
CF Step
997.000000 MHz
Auto Mar
Freq Offset
0 Hz

Agilent Spectrum Analyzer - Swept SA

RF 50 Ω AC SENSE:INT ALIGN:AUTO 10:21:17 AM Jun 04, 2015

#Avg Type: RMS

TRAC 1 2 3 4 5 6
TYPE: [M] [H] [A] [N] [P] [S] [T] [U] [V] [W] [X] [Y] [Z]
DET: A [N] [N] [N] [N] [N] [N]

PNO: Fast IFGain:Low Trig: Free Run #Atten: 10 dB

Ref Offset 27.5 dB
Ref 20.00 dBm

Mkr1 25.376 4 GHz
-34.167 dBm


10 dB/div
Log

Start 10.000 GHz
#Res BW 1.0 MHz
#VBW 3.0 MHz


Stop 26.000 GHz
Sweep 42.7 ms (40000 pts)

Auto Tune
Center Freq 18.000000000 GHz
Start Freq 10.000000000 GHz
Stop Freq 26.000000000 GHz
CF Step 1.600000000 GHz
Auto Mar
Freq Offset 0 Hz


BAND 41. Conducted Spurious Plot 1 (15 MHz Ch.41515 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 2 (15 MHz Ch. 41515 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 1 (20 MHz Ch.39750 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 2 (20 MHz Ch. 39750 QPSK RB 1, Offset 0)




BAND 41. Conducted Spurious Plot 1 (20 MHz Ch.40620 QPSK RB 1, Offset 0)



BAND 41. Conducted Spurious Plot 2 (20 MHz Ch. 40620 QPSK RB 1, Offset 0)



BAND 41. Conducted Spurious Plot 1 (20 MHz Ch.41490 QPSK RB 1, Offset 0)



BAND 41. Conducted Spurious Plot 2 (20 MHz Ch. 41490 QPSK RB 1, Offset 0)

