



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



MEASUREMENT REPORT FCC PART 15.249 ANT+

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:

1/20 - 2/6/2015

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

0Y1501290301.A3L

FCC ID:

A3LSMG925P

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model(s):

SM-G925P

EUT Type:

Portable Handset

Frequency Range:

2402 – 2480MHz

FCC Classification:

Low Power Communications Device Transmitter (DXX)

FCC Rule Part(s):

Part 15 Subpart C (15.249)

Test Procedure(s):

ANSI C63.10-2009, KDB 648474 D03 v01r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2009. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President



FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 1 of 22

TABLE OF CONTENTS

FCC PART 15.249 MEASUREMENT REPORT	3
1.0 INTRODUCTION.....	4
1.1 SCOPE.....	4
1.2 PCTEST TEST LOCATION.....	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION.....	5
2.2 DEVICE CAPABILITIES	5
2.3 TEST CONFIGURATION	5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....	5
3.0 DESCRIPTION OF TEST	6
3.1 EVALUATION PROCEDURE.....	6
3.2 AC LINE CONDUCTED EMISSIONS.....	6
3.3 RADIATED EMISSIONS	7
3.4 ENVIRONMENTAL CONDITIONS	7
4.0 ANTENNA REQUIREMENTS	8
5.0 TEST EQUIPMENT CALIBRATION DATA.....	9
6.0 TEST RESULTS	10
6.1 SUMMARY	10
6.2 OCCUPIED BANDWIDTH MEASUREMENT	11
6.3 DUTY CYCLE CALCULATION.....	12
6.4 FUNDAMENTAL FIELD STRENGTH LEVEL MEASUREMENT	14
6.5 RADIATED SPURIOUS EMISSION MEASUREMENTS.....	15
6.6 RADIATED RESTRICTED BAND EDGE MEASUREMENTS	18
6.7 LINE CONDUCTED MEASUREMENT DATA	20
7.0 CONCLUSION	22

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 2 of 22



MEASUREMENT REPORT

FCC Part 15.249





§ 2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.
APPLICANT ADDRESS: 129, Samsung-ro, Maetan dong,
 Yeongtong-gu, Suwon-si, Gyeonggi-do 443-742, Korea
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA
FCC RULE PART(S): Part 15 Subpart C (15.249)
MODEL: SM-G925P
FCC ID: A3LSMG925P
Test Device Serial No.: 234C3, 234F2, 234C9, ☐ Production ☒ Pre-Production ☐ Engineering
 234F1
FCC CLASSIFICATION: Low Power Communications Device Transmitter (DXX)
DATE(S) OF TEST: 1/20 - 2/6/2015
TEST REPORT S/N: 0Y1501290301.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 3 of 22

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See **Figure 1-1**).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.



Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSMG925P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 4 of 22

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMG925P**. The test data contained in this report pertains only to the emissions due to the EUT's ANT+ transmitter.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, 850/1900 (BC0, BC1, and BC10) CDMA/EvDO, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band. In addition, the circuitry for this device is electrically identical to a device bearing the FCC ID: A3LSMG925V. Thus, the data found within this report was taken from the A3LSMG925V device.

2.3 Test Configuration

The Samsung Portable Handset FCC ID: A3LSMG925P was tested per the guidance of ANSI C63.10-2009. ANSI C63.10-2009 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 6.2 for antenna port conducted emissions test setups.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r02. Additional radiated spurious emission measurements were performed with the EUT lying flat on a certified wireless charging pad while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 5 of 22

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009) was used in the measurement of the **Samsung Portable Handset FCC ID: A3LSMG925P**.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 6.7. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 6 of 22

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 7 of 22

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Samsung Portable Handset are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **Samsung Portable Handset FCC ID: A3LSMG925P** unit complies with the requirement of §15.203.

Ch.	Frequency (MHz)
00	2402
:	:
39	2441
:	:
78	2480

Table 4-1. Frequency/ Channel Operations

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 8 of 22

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	5/29/2014	Annual	5/29/2015	N/A
-	WL40-1	Conducted Cable Set (40GHz)	10/14/2014	Annual	10/14/2015	N/A
Agilent	8447D	Broadband Amplifier	5/30/2014	Annual	5/30/2015	2443A01900
Agilent	E4448A	PSA (3Hz-50GHz) Spectrum Analyzer	4/16/2014	Annual	4/16/2015	US42510244
Agilent	N9020A	MXA Signal Analyzer	10/27/2014	Annual	10/27/2015	US46470561
Agilent	N9038A	MXE EMI Receiver	3/3/2014	Annual	3/3/2015	MY51210133
Agilent	N9030A	PXA Signal Analyzer (26.5GHz)	5/8/2014	Annual	5/8/2015	MY49432391
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/17/2014	Annual	3/17/2015	MY52350166
Emco	3115	Horn Antenna (1-18GHz)	1/30/2014	Biennial	1/30/2016	9704-5182
Emco	6502	Active Loop Antenna (10k - 30 MHz)	6/24/2014	Biennial	6/24/2016	267
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/8/2014	Biennial	4/8/2016	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	6/17/2014	Biennial	6/17/2016	135427
Huber+Suhner	Sucoflex 102A	40GHz Radiated Cable	10/15/2014	Annual	10/15/2015	251425001
K & L	11SH10-3075/U18000	High Pass Filter	5/2/2014	Annual	5/2/2015	2
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/5/2014	Annual	3/5/2015	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/12/2014	Annual	3/12/2015	100040
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	5/21/2014	Annual	5/21/2015	100348
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
Solar Electronics	8012-50-R-24-BNC	Line Impedance Stabilization Network	6/20/2013	Biennial	6/20/2015	310233
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/28/2014	Biennial	1/28/2016	A051107

Table 5-1. Annual Test Equipment Calibration Schedule

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 9 of 22

6.0 TEST RESULTS

6.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMG925P
 Method/System: Frequency Hopping Spread Spectrum (FHSS)
 Number of Channels: 79

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (Tx)					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 6.2
15.35(c)	Duty Cycle Calculation	N/A	RADIATED	N/A	Section 6.3
15.249(a)(e)	Fundamental Field Strength Level	< 50 mV/m		PASS	Section 6.4
15.249(a)(e)	Harmonic Field Strength Level	< 500 μ V/m		PASS	Section 6.5
15.205, 15.209, 15.249(d)(e)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	< 15.209 limits (RSS-210 table 3 limits) or 50dB below the level of the fundamental		PASS	Sections 6.5, 6.6
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Section 6.7

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset	Page 10 of 22	

6.2 Occupied Bandwidth Measurement

\$2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The spectrum analyzers' "occupied bandwidth" measurement function was used to record the occupied bandwidth.

Frequency [MHz]	Channel No.	Operating Mode	Measured Bandwidth [kHz]
2441	39	ANT+ (non-hop)	1017.3

Table 6-2. Occupied Bandwidth Measurement



Figure 6-1. Test Instrument & Measurement Setup



Plot 6-1. Occupied Bandwidth Plot (ANT+ – Ch. 39)


FCC ID: A3LSMG925P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 11 of 22

6.3 Duty Cycle Calculation

§15.35(c)

Per FCC Part 15.35(c), an average radiated field strength can be determined by applying a duty cycle correction factor to a measured peak radiated field strength level. The duty cycle correction factor is determined based on the worst case operation over a 100ms time period on any given channel. Two plots are included below to determine the appropriate duty cycle correction factor.

In Plot 6-2 below, it is shown that the pulse width for one transmission burst of the ANT+ transmitter while operating in non-hopping mode is 240.0µs.




Plot 6-2. Pulse Width Measurement

FCC ID: A3LSMG925P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 12 of 22

Duty Cycle Calculation

§15.35(c)

In Plot 6-3 below, a video trigger is used to determine the maximum number of times the transmitter operates at maximum power over a 100ms period.



Plot 6-3. Worst Case 100ms Operation

Since it is determined that the transmitter burst appears a maximum of 2 times over a 100ms window with a pulse width of 240.0μs, then the appropriate duty cycle correction factor is determined from the following formula, based on 15.35(c):

$$\begin{aligned} \text{DCCF} &= 20\log_{10}(\text{number of hits} \times (\text{worst case 100ms operation} / 100\text{ms})) \\ &= 20\log_{10}(2 \times (0.2400\text{ms}/100\text{ms})) = -46.37\text{dB} \end{aligned}$$

DCCF = -46.37dB

FCC ID: A3LSMG925P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 13 of 22

6.4 Fundamental Field Strength Level Measurement

§15.249(a)(e)

Measurement is made while the EUT is operating in non-hopping transmission mode. The field strengths shown below were measured using a spectrum analyzer. Peak field strength measurements are performed in the analyzers' swept spectrum mode using a peak detector with RBW = 3MHz and VBW ≥ RBW. Average field strength data is determined by applying the duty cycle correction factor (DCCF) found in Section 6.3 to the measured peak field strength values.

The maximum permissible average field strength level is 50mV/m (93.98dBμV/m). The maximum permissible peak field strength level is 500mV/m (113.98 dBμV/m).

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB]	Field Strength [dBμV/m]	Duty Cycle Correction [dB]	Corrected Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
2402.00	-41.96	Peak	H	31.84	96.89	-46.37	50.52	93.98	-43.46
2402.00	-41.96	Peak	H	31.84	96.89	0.00	96.89	113.98	-17.09
2441.00	-40.64	Peak	H	31.95	98.31	-46.37	51.94	93.98	-42.04
2441.00	-40.64	Peak	H	31.95	98.31	0.00	98.31	113.98	-15.67
2480.00	-42.65	Peak	H	32.06	96.41	-46.37	50.04	93.98	-43.94
2480.00	-42.65	Peak	H	32.06	96.41	0.00	96.41	113.98	-17.57

Table 6-3. Field Strength Measurements

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 14 of 22

6.5 Radiated Spurious Emission Measurements

§15.205 §15.209 §15.249 (d)(e)

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-4. Radiated Limits

Sample Calculation

- o Avg. Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] = Analyzer Level [dBm] + 107 + AFCL [dB/m] + Duty Cycle Correction [dB]
- o Pk. Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- o AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- o Margin [dB] = Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] – Limit [$\text{dB}_{\mu\text{V/m}}$]

Test Notes

- The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. There were no non-harmonic emissions detected whose levels were within 20dB of the applicable limits so only harmonic emissions data is shown in this section.
- All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-4. Per 15.249(d), the radiated emissions limits from 15.209 were used since they were less than the limit of 50dB of attenuation from the measured fundamental field strength level.
- Peak measurements > 1GHz using RBW = 1MHz and VBW = 3MHz.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- This unit was tested with its standard battery.

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 15 of 22

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.249 (d)(e)

Worst Case Mode: ANT+ (non-hopping)
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB]	Field Strength [dBμV/m]	Duty Cycle Correction [dB]	Corrected Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	-101.98	Peak	H	38.29	43.31	-46.37	-3.06	53.98	-57.04
4804.00	-101.98	Peak	H	38.29	43.31	0.00	43.31	73.98	-30.67
12010.00	-104.47	Peak	H	49.01	51.55	-46.37	5.18	53.98	-48.80
12010.00	-104.47	Peak	H	49.01	51.55	0.00	51.55	73.98	-22.43

Table 6-5. Radiated Measurements

Worst Case Mode: ANT+ (non-hopping)
 Measurement Distance: 3 Meters
 Operating Frequency: 2441MHz
 Channel: 39

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB]	Field Strength [dBμV/m]	Duty Cycle Correction [dB]	Corrected Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	-100.34	Peak	H	38.60	45.26	-46.37	-1.11	53.98	-55.09
4882.00	-100.34	Peak	H	38.60	45.26	0.00	45.26	73.98	-28.72
7323.00	-101.86	Peak	H	43.80	48.94	-46.37	2.57	53.98	-51.41
7323.00	-101.86	Peak	H	43.80	48.94	0.00	48.94	73.98	-25.04
12205.00	-104.18	Peak	H	48.76	51.59	-46.37	5.22	53.98	-48.76
12205.00	-104.18	Peak	H	48.76	51.59	0.00	51.59	73.98	-22.39

Table 6-6. Radiated Measurements

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 16 of 22

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.249 (d)(e)

Worst Case Mode: ANT+ (non-hopping)
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB]	Field Strength [dBµV/m]	Duty Cycle Correction [dB]	Corrected Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4960.00	-100.81	Peak	H	38.91	45.10	-46.37	-1.27	53.98	-55.25
4960.00	-100.81	Peak	H	38.91	45.10	0.00	45.10	73.98	-28.88
7440.00	-102.28	Peak	H	43.92	48.64	-46.37	2.27	53.98	-51.71
7440.00	-102.28	Peak	H	43.92	48.64	0.00	48.64	73.98	-25.34
12400.00	-104.22	Peak	H	48.82	51.59	-46.37	5.22	53.98	-48.76
12400.00	-104.22	Peak	H	48.82	51.59	0.00	51.59	73.98	-22.39

Table 6-7. Radiated Measurements

Worst Case Mode: ANT+ (non-hopping)
 Measurement Distance: 3 Meters
 Operating Frequency: 2441MHz
 Channel: 39

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB]	Field Strength [dBµV/m]	Duty Cycle Correction [dB]	Corrected Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4882.00	-100.98	Peak	H	38.60	44.62	-46.37	-1.75	53.98	-55.73
4882.00	-100.98	Peak	H	38.60	44.62	0.00	44.62	73.98	-29.36
7323.00	-102.21	Peak	H	43.80	48.59	-46.37	2.22	53.98	-51.76
7323.00	-102.21	Peak	H	43.80	48.59	0.00	48.59	73.98	-25.39
12205.00	-104.24	Peak	H	48.76	51.53	-46.37	5.16	53.98	-48.82
12205.00	-104.24	Peak	H	48.76	51.53	0.00	51.53	73.98	-22.45

Table 6-8. Radiated Measurements w/ WCP

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 17 of 22

6.6 Radiated Restricted Band Edge Measurements

\$15.205 \$15.209 \$15.249 (d)

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting. Two different amplitude offsets were used depending on whether peak or average measurements were measured. The average measurements use a duty cycle correction factor (DCCF).

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss}) - \text{Preamplifier Gain} + \text{DCCF}$$


Worst Case Mode: ANT+ (non-hopping)

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Back Cover: Standard

Channel: 78



Date: 2.FEB.2015 18:02:59

Plot 6-4. Radiated Restricted Upper Band Edge Measurement (Average)


FCC ID: A3LSMG925P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 18 of 22

Radiated Restricted Band Edge Measurements

§15.205 §15.209 §15.249 (d)

The amplitude offset shown in the following plots for peak measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss}) - \text{Preamplifier Gain}$$




Date: 2.FEB.2015 18:06:04

Plot 6-5. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: A3LSMG925P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 19 of 22

6.7 Line Conducted Measurement Data

\$15.207



Plot 6-6. Line-Conducted Test Plot (L1)


Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMG925P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 20 of 22

Line Conducted Measurement Data

\$15.207



Plot 6-7. Line-Conducted Test Plot (N)

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMG925P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 21 of 22

7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG925P** is in compliance with Part 15 Subpart C (15.249) of the FCC Rules.

FCC ID: A3LSMG925P		FCC Pt. 15.249 ANT+ TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501290301.A3L	Test Dates: 1/20 - 2/6/2015	EUT Type: Portable Handset		Page 22 of 22