



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:

01/19/15 - 02/10/15

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

0Y1501200180.A3L

FCC ID:

A3LSMG925V

APPLICANT:

SAMSUNG ELECTRONICS, CO. LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SM-G925V

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.33	0.49	0.56
PCE	UMTS 850	826.40 - 846.60 MHz	0.27	0.38	0.48
PCE	Cell. CDMA/EVDO	824.70 - 848.31 MHz	0.40	0.55	0.62
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	< 0.1	0.36	0.54
PCE	UMTS 1900	1852.4 - 1907.6 MHz	< 0.1	0.40	0.65
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.17	0.45	0.96
PCE	LTE Band 13	779.5 - 784.5 MHz	0.25	0.32	0.32
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.32	0.17	0.34
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.16	0.54	0.54
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.15	0.39	0.64
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.27	0.14	0.14
Nil	U-NII-1	5180 - 5240 MHz		N/A	
Nil	U-NII-2A	5260 - 5320 MHz	0.22	0.10	
Nil	U-NII-2C < 5.65 GHz	5500 - 5580 MHz	0.31	< 0.1	
Nil	U-NII-2C > 5.65 GHz + U-NII-3	5660 - 5825 MHz	0.29	< 0.1	0.15
DSS/DTS	Bluetooth	2402 - 2480 MHz		N/A	
Simultaneous SAR per KDB 690783 D01v01r03:			0.88	0.77	1.17

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sar.tick@mmfai.info.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 1 of 90

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	11
3	INTRODUCTION	12
4	DOSIMETRIC ASSESSMENT	13
5	DEFINITION OF REFERENCE POINTS	14
6	TEST CONFIGURATION POSITIONS FOR HANDSETS	15
7	RF EXPOSURE LIMITS	18
8	FCC MEASUREMENT PROCEDURES.....	19
9	RF CONDUCTED POWERS.....	27
10	SYSTEM VERIFICATION.....	63
11	SAR DATA SUMMARY	65
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	76
13	SAR MEASUREMENT VARIABILITY	84
14	EQUIPMENT LIST	85
15	MEASUREMENT UNCERTAINTIES	86
16	CONCLUSION.....	88
17	REFERENCES	89
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 2 of 90	

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
Cell. CDMA/EVDO	Voice/Data	824.70 - 848.31 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
U-NII-1	Data	5180 - 5240 MHz
U-NII-2A	Data	5260 - 5320 MHz
U-NII-2C < 5.65 GHz	Data	5500 - 5580 MHz
U-NII-2C > 5.65 GHz + U-NII-3	Data	5660 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz
MST	Data	1 - 8.3 kHz

1.2 Power Reduction for SAR

This device utilizes two single step independent power reduction mechanisms for SAR compliance. For the main transmitter, the device utilizes power reduction under portable hotspot conditions for GPRS/EDGE 1900, UMTS B2, PCS CDMA/EVDO, and LTE B4/2. All hotspot SAR evaluations for this device were performed with the maximum allowed output power in hotspot mode. Additional evaluations at reduced output power conditions were considered for simultaneous transmission purposes. Additionally for the unlicensed transmitter, this device utilizes a proximity sensor to reduced the output power for 2.4 and 5 GHz WLAN during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528. The reduced powers for both mechanisms were confirmed via conducted power measurements at the RF port (See Section 9). Detailed descriptions of the hotspot power reduction and proximity sensor mechanisms are included in the operational description.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

1.3.1 Maximum Powers

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slot	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slot	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.5	33.5	31.5	30.0	28.5	27.5	26.5	25.0	24.0
	Nominal	33.0	33.0	31.0	29.5	28.0	27.0	26.0	24.5	23.5
GSM/GPRS/EDGE 1900	Maximum	30.5	30.5	29.5	27.5	26.5	26.0	25.0	23.5	22.5
	Nominal	30.0	30.0	29.0	27.0	26.0	25.5	24.5	23.0	22.0

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC. SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 3 of 90

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA Rel 99	3GPP HSDPA Rel 5	3GPP HSUPA Rel 6
UMTS Band 5 (850 MHz)	Maximum	23.5	23.5	23.5
	Nominal	23.0	23.0	23.0
UMTS Band 2 (1900 MHz)	Maximum	23.5	23.5	23.5
	Nominal	23.0	23.0	23.0

Mode / Band		Modulated Average (dBm)
Cell. CDMA/EVDO	Maximum	25.0
	Nominal	24.5
PCS CDMA/EVDO	Maximum	25.0
	Nominal	24.5

Mode / Band		Modulated Average (dBm)
LTE Band 13	Maximum	24.0
	Nominal	23.5
LTE Band 5 (Cell)	Maximum	24.5
	Nominal	24.0
LTE Band 4 (AWS)	Maximum	24.5
	Nominal	24.0
LTE Band 2 (PCS)	Maximum	24.5
	Nominal	24.0

Single Transmission Chain WLAN and Bluetooth

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	17.5
	Nominal	17.0
IEEE 802.11g (2.4 GHz)	Maximum	14.5
	Nominal	14.0
IEEE 802.11n (2.4 GHz)	Maximum	13.5
	Nominal	13.0
Bluetooth	Maximum	10.0
	Nominal	9.5
Bluetooth LE	Maximum	4.0
	Nominal	3.5

Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	14.5		
	Nominal	14.0		
IEEE 802.11n (5 GHz)	Maximum	13.5	12.5	
	Nominal	13.0	12.0	
IEEE 802.11ac (5 GHz)	Maximum	13.5	12.5	11.5
	Nominal	13.0	12.0	11.0

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 4 of 90

MIMO WLAN

Mode / Band		Modulated Average (dBm)		
IEEE 802.11n (2.4 GHz)	Maximum	16.5		
	Nominal	16.0		
Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11n (5 GHz)	Maximum	16.5	15.5	
	Nominal	16.0	15.0	
IEEE 802.11ac (5 GHz)	Maximum	16.5	15.5	14.5
	Nominal	16.0	15.0	14.0

1.3.2

Reduced Powers – Hotspot Active

Mode / Band		Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slot	2 TX Slots	3 TX Slots	4 TX Slots
GPRS/EDGE 1900	Maximum	28.5	27.5	25.5	24.5	24.0	23.0	21.5	20.5
	Nominal	28.0	27.0	25.0	24.0	23.5	22.5	21.0	20.0

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA Rel 99	3GPP HSDPA Rel 5	3GPP HSUPA Rel 6
UMTS Band 2 (1900 MHz)	Maximum	21.5	20.5	20.5
	Nominal	21.0	20.0	20.0

Mode / Band		Modulated Average (dBm)
PCS CDMA/EVDO	Maximum	20.5
	Nominal	20.0

Mode / Band		Modulated Average (dBm)
LTE Band 4 (AWS)	Maximum	20.5
	Nominal	20.0
LTE Band 2 (PCS)	Maximum	21.5
	Nominal	21.0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 5 of 90

1.3.3

Reduced Powers – Held-to-Ear

Single Transmission Chain WLAN

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	12.5
	Nominal	12.0
IEEE 802.11g (2.4 GHz)	Maximum	12.5
	Nominal	12.0
IEEE 802.11n (2.4 GHz)	Maximum	12.5
	Nominal	12.0

Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	8.5		
	Nominal	8.0		
IEEE 802.11n (5 GHz)	Maximum	8.5	8.5	
	Nominal	8.0	8.0	
IEEE 802.11ac (5 GHz)	Maximum	8.5	8.5	8.5
	Nominal	8.0	8.0	8.0

MIMO WLAN

Mode / Band		Modulated Average (dBm)
IEEE 802.11n (2.4 GHz)	Maximum	15.5
	Nominal	15.0

Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11n (5 GHz)	Maximum	11.5	11.5	
	Nominal	11.0	11.0	
IEEE 802.11ac (5 GHz)	Maximum	11.5	11.5	11.5
	Nominal	11.0	11.0	11.0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 6 of 90	

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is <160 mm and the diagonal display is <150 mm. A diagram showing the location of the device antennas can be found in Appendix F.

Table 1-1
Mobile Hotspot Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
Cell. EVDO	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	No	Yes
U-NII-3	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for Wireless Router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v01 guidance, page 2. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A & U-NII-2C WLAN operations are disabled. Therefore U-NII-1, U-NII-2A & U-NII-2C WLAN operations are not considered in this section.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC Operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 7 of 90

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	1x CDMA voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	
2	1x CDMA voice + 5 GHz Wi-Fi	Yes	Yes	N/A	
3	1x CDMA voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
4	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	
5	GSM voice + 5 GHz Wi-Fi	Yes	Yes	N/A	
6	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
7	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
8	UMTS + 5 GHz Wi-Fi	Yes	Yes	Yes	
9	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	
10	LTE + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
11	LTE + 5 GHz Wi-Fi	Yes	Yes	Yes	
12	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A	
13	CDMA/EVDO data + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	*-Pre-installed VOIP applications are considered.
14	CDMA/EVDO data + 5 GHz Wi-Fi	Yes*	Yes*	Yes	*-Pre-installed VOIP applications are considered.
15	CDMA/EVDO data + 2.4 GHz Bluetooth	N/A	Yes*	N/A	*-Pre-installed VOIP applications are considered.
16	GPRS/EDGE + 2.4 GHz Wi-Fi	N/A	N/A	Yes	
17	GPRS/EDGE + 5 GHz Wi-Fi	N/A	N/A	Yes	
18	1x CDMA voice + LTE + 2.4 GHz Wi-Fi	N/A	N/A	N/A	Not supported by HW
19	1x CDMA voice + LTE + 5 GHz Wi-Fi	N/A	N/A	N/A	Not supported by HW
20	1x CDMA voice + CDMA/EVDO data	N/A	N/A	N/A	Not supported by HW
21	1x CDMA voice + LTE	N/A	N/A	N/A	Not supported by HW
22	CDMA/EVDO data + LTE	N/A	N/A	N/A	Not supported by HW

- 2.4 GHz WLAN, 5 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
- This device supports 2x2 MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.
- This device supports VoLTE.

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 8 of 90	

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02.

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB 248227 D01 DR02-41929.

Since this device supports the band gap channels, the channels in the U-NII-2C band above 5.65 GHz were grouped with the channels in the U-NII-3 as a single aggregate band. The channels in U-NII-2C below 5.65 GHz were considered separately for SAR evaluation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) Band gap channels are supported

Per FCC KDB 447498 D01v05, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency (GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(10/15) * \sqrt{2.480}] = 1.0 < 3.0$. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r03.

This device supports inter-band LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r01, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset

1.8 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01v03, D05v02r03, D05Av01r01, D06v02 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01 DR02-41929 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05r02 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r03, D02v01r01 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.9 Device Serial Numbers

Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
GSM/GPRS/EDGE 850	234DC	234DC	234DC
UMTS 850	234DC	234DC	234DC
Cell. CDMA/EVDO	234F1	23503	23503
GSM/GRPS/EDGE 1900 Max	234DC	234DC	-
GRPS/EDGE 1900 Reduced	-	-	234C8
UMTS 1900 Max	234DC	234DC	-
UMTS 1900 Reduced	-	-	234C8
PCS CDMA/EVDO Max	234F1	234F1	-
PCS CDMA/EVDO Reduced	234C8	-	234C8
LTE Band 13	08FC4	23503	23503
LTE Band 5 (Cell)	234C9	23503	23503
LTE Band 4 (AWS) Max	23503	23503	-
LTE Band 4 (AWS) Reduced	-	-	234EB
LTE Band 2 (PCS) Max	23503	234DC	-
LTE Band 2 (PCS) Reduced	-	-	234EB
2.4 GHz WLAN	234B0	234B0	234B0
5 GHz WLAN	234B0	236B4	236B4

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 10 of 90

2

LTE INFORMATION

LTE Information									
FCC ID				A3LSMG925V					
Form Factor				Portable Handset					
Frequency Range of each LTE transmission band				LTE Band 13 (779.5 - 784.5 MHz)					
				LTE Band 5 (Cell) (824.7 - 848.3 MHz)					
				LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)					
				LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)					
Channel Bandwidths				LTE Band 13: 5 MHz, 10 MHz					
				LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz					
				LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz					
				LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz					
Channel Numbers and Frequencies (MHz)				Low	Mid	High			
LTE Band 13: 5 MHz				779.5 (23205)	782 (23230)	784.5 (23255)			
LTE Band 13: 10 MHz				782 (23230)	782 (23230)	782 (23230)			
LTE Band 5 (Cell): 1.4 MHz				824.7 (20407)	836.5 (20525)	848.3 (20643)			
LTE Band 5 (Cell): 3 MHz				825.5 (20415)	836.5 (20525)	847.5 (20635)			
LTE Band 5 (Cell): 5 MHz				826.5 (20425)	836.5 (20525)	846.5 (20625)			
LTE Band 5 (Cell): 10 MHz				829 (20450)	836.5 (20525)	844 (20600)			
LTE Band 4 (AWS): 1.4 MHz				1710.7 (19957)	1732.5 (20175)	1754.3 (20393)			
LTE Band 4 (AWS): 3 MHz				1711.5 (19965)	1732.5 (20175)	1753.5 (20385)			
LTE Band 4 (AWS): 5 MHz				1712.5 (19975)	1732.5 (20175)	1752.5 (20375)			
LTE Band 4 (AWS): 10 MHz				1715 (20000)	1732.5 (20175)	1750 (20350)			
LTE Band 4 (AWS): 15 MHz				1717.5 (20025)	1732.5 (20175)	1747.5 (20325)			
LTE Band 4 (AWS): 20 MHz				1720 (20050)	1732.5 (20175)	1745 (20300)			
LTE Band 2 (PCS): 1.4 MHz				1850.7 (18607)	1880 (18900)	1909.3 (19193)			
LTE Band 2 (PCS): 3 MHz				1851.5 (18615)	1880 (18900)	1908.5 (19185)			
LTE Band 2 (PCS): 5 MHz				1852.5 (18625)	1880 (18900)	1907.5 (19175)			
LTE Band 2 (PCS): 10 MHz				1855 (18650)	1880 (18900)	1905 (19150)			
LTE Band 2 (PCS): 15 MHz				1857.5 (18675)	1880 (18900)	1902.5 (19125)			
LTE Band 2 (PCS): 20 MHz				1860 (18700)	1880 (18900)	1900 (19100)			
UE Category				6					
Modulations Supported in UL				QPSK, 16QAM					
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3–6.2.5? (manufacturer attestation to be provided)				YES					
A-MPR (Additional MPR) disabled for SAR Testing?				YES					
LTE Carrier Aggregation Possible Combinations	B13 (PCC) + B4 (SCC)	B13 (PCC) + B2 (SCC)	B4 (PCC) + B13 (SCC)	B4 (PCC) + B4 (SCC)	B4 (PCC) + B2 (SCC)	B2 (PCC) + B13 (SCC)	B2 (PCC) + B4 (SCC)	B2 (PCC) + B2 (SCC)	
	10MHz (B13) + 5MHz (B4)	10MHz (B13) + 5MHz (B2)	5MHz (B4) + 10MHz (B13)	5MHz (B4) + 5MHz (B4)	5MHz (B4) + 5MHz (B2)	5MHz (B2) + 10MHz (B13)	5MHz (B2) + 5MHz (B4)	5MHz (B2) + 5MHz (B2)	
	10MHz (B13) + 10MHz (B4)	10MHz (B13) + 10MHz (B2)	10MHz (B4) + 10MHz (B13)	5MHz (B4) + 10MHz (B4)	5MHz (B4) + 10MHz (B2)	10MHz (B2) + 10MHz (B13)	5MHz (B2) + 10MHz (B4)	5MHz (B2) + 10MHz (B2)	
	10MHz (B13) + 15MHz (B4)	10MHz (B13) + 15MHz (B2)	15MHz (B4) + 10MHz (B13)	5MHz (B4) + 15MHz (B4)	5MHz (B4) + 15MHz (B2)	15MHz (B2) + 10MHz (B13)	5MHz (B2) + 15MHz (B4)	5MHz (B2) + 15MHz (B2)	
	10MHz (B13) + 20MHz (B4)	10MHz (B13) + 20MHz (B2)	20MHz (B4) + 10MHz (B13)	5MHz (B4) + 20MHz (B4)	5MHz (B4) + 20MHz (B2)	20MHz (B2) + 10MHz (B13)	5MHz (B2) + 20MHz (B4)	5MHz (B2) + 20MHz (B2)	
				10MHz (B4) + 5MHz (B4)	10MHz (B4) + 5MHz (B2)		10MHz (B2) + 5MHz (B4)	10MHz (B2) + 5MHz (B2)	
				10MHz (B4) + 10MHz (B4)	10MHz (B4) + 10MHz (B2)		10MHz (B2) + 10MHz (B4)	10MHz (B2) + 10MHz (B2)	
				10MHz (B4) + 15MHz (B4)	10MHz (B4) + 15MHz (B2)		10MHz (B2) + 15MHz (B4)	10MHz (B2) + 15MHz (B2)	
				10MHz (B4) + 20MHz (B4)	10MHz (B4) + 20MHz (B2)		10MHz (B2) + 20MHz (B4)	10MHz (B2) + 20MHz (B2)	
				15MHz (B4) + 5MHz (B4)	15MHz (B4) + 5MHz (B2)		15MHz (B2) + 5MHz (B4)	15MHz (B2) + 5MHz (B2)	
				15MHz (B4) + 10MHz (B4)	15MHz (B4) + 10MHz (B2)		15MHz (B2) + 10MHz (B4)	15MHz (B2) + 10MHz (B2)	
				15MHz (B4) + 15MHz (B4)	15MHz (B4) + 15MHz (B2)		15MHz (B2) + 15MHz (B4)	15MHz (B2) + 15MHz (B2)	
				15MHz (B4) + 20MHz (B4)	15MHz (B4) + 20MHz (B2)		15MHz (B2) + 20MHz (B4)	15MHz (B2) + 20MHz (B2)	
				20MHz (B4) + 5MHz (B4)	20MHz (B4) + 5MHz (B2)		20MHz (B2) + 5MHz (B4)	20MHz (B2) + 5MHz (B2)	
				20MHz (B4) + 10MHz (B4)	20MHz (B4) + 10MHz (B2)		20MHz (B2) + 10MHz (B4)	20MHz (B2) + 10MHz (B2)	
				20MHz (B4) + 15MHz (B4)	20MHz (B4) + 15MHz (B2)		20MHz (B2) + 15MHz (B4)	20MHz (B2) + 15MHz (B2)	
				20MHz (B4) + 20MHz (B4)	20MHz (B4) + 20MHz (B2)		20MHz (B2) + 20MHz (B4)	20MHz (B2) + 20MHz (B2)	
	LTE Carrier Aggregation Additional Information	This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. Due to carrier capability, only the combinations listed above are supported. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eIC, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.							

FCC ID: A3LSMG925V			SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 11 of 90		

3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 12 of 90

4

DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n-1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 13 of 90

5

DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 14 of 90

6

TEST CONFIGURATION POSITIONS FOR HANDSETS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position



2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:


1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 15 of 90



6.4 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v05 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.



Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 16 of 90

6.5 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 44798 D01v05 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v05, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.6 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

There is power reduction for GPRS/EDGE 1900, UMTS Band 2, PCS CDMA/EVDO, and LTE Band 2/4 in hotspot scenarios. There is no power reduction for GSM/GPRS/EDGE 850, GSM 1900, UMTS 850, Cell. CDMA/EVDO, and LTE Band13/5. The reduced powers were confirmed via conducted power measurements at the RF port (See Section 9). Detailed description of the hotspot power reduction mechanism are included in the operational description

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 17 of 90

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
		Page 18 of 90

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03 "3G SAR Measurement Procedures."

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 19 of 90

8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03 “3G SAR Measurement Procedures.”

8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

Table 8-1
Parameters for Max. Power for RC1

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 8-2
Parameters for Max. Power for RC3

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

8.4.3 Body-worn SAR Measurements

SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
		Page 20 of 90

8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with Ev-Do capabilities, the 3G SAR test reduction procedure is applied to Ev-Do Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For Ev-Do data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with Ev-Do Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

8.5 SAR Measurement Conditions for UMTS

8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
Page 21 of 90		

8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r03 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset

8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r03:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.6.5 Downlink Carrier Aggregation

LTE Carrier Aggregation (CA) measurements are made in accordance to 3GPP TS 36.521-1 V10.4.0 (2012-12). The RRC connection is only handled by one cell, the Primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds the Secondary component carrier (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to release 8 specifications on the PCC. Additional output powers are measured using two carriers in the downlink for the release 8 configurations with the highest output power among all channels, RB configurations and bandwidths for each uplink band. Per FCC KDB Publication 941225 D05A v01r01, no SAR measurements are required when the average output power with downlink carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink carrier aggregation inactive.

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 23 of 90

8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01 DR02-41929 for more details.

8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.7.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

8.7.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification.

Unless band gap channels are permanently disabled, SAR must be considered for these channels. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz are grouped with the 5.8 GHz channels in U-NII-3 band or §15.247 5.8 GHz band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are disabled, each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
		Page 24 of 90

8.7.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

8.7.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.7.6 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz and 5 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 25 of 90

8.7.7 Initial Test Configuration Procedure

For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, and lowest data rate. If the average RF output powers of the highest identical transmission modes are within 0.25 dB of each other, mid channel of the transmission mode with highest average RF output power is the initial test channel. Otherwise, the channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.6).

8.7.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

8.7.9 MIMO SAR considerations

Per KDB 248227 D01 DR02-41929, the simultaneous SAR provisions in KDB Publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is <1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
© 2015 PCTEST Engineering Laboratory, Inc.		Page 26 of 90

9 RF CONDUCTED POWERS

9.1 CDMA Conducted Powers

Table 9-1
Maximum Average RF Output Powers

Band	Channel	Frequency	SO55 [dBm]	SO55 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	RC1	RC3	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	1013	824.7	24.99	24.97	24.98	24.99	24.98	24.89
	384	836.52	24.98	25.00	24.97	25.00	25.00	24.90
	777	848.31	24.80	24.75	24.63	24.74	24.75	24.58
PCS	25	1851.25	24.65	24.58	24.57	24.66	24.66	24.45
	600	1880	24.20	24.18	24.21	24.26	24.25	24.16
	1175	1908.75	23.99	23.98	24.02	23.94	23.96	23.83

Note: RC1 is only applicable for IS-95 compatibility.

Table 9-2
Reduced Average RF Output Powers – Representing Hotspot Mode Active

Band	Channel	Frequency	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	FCH+SCH	FCH	(RTAP)	(RETAP)
PCS	25	1851.25	20.49	20.50	20.50	20.31
	600	1880	20.03	20.08	20.20	20.00
	1175	1908.75	20.08	20.03	20.23	20.18




Figure 9-1
Power Measurement Setup

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 27 of 90

9.2 GSM Conducted Powers

Table 9-3
Maximum Average RF Output Powers

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	33.19	32.74	31.41	29.60	28.02	27.40	26.08	24.06	23.84
	190	33.28	32.82	31.48	29.71	28.21	27.20	25.86	23.85	23.80
	251	33.20	32.77	31.50	29.72	27.63	26.93	25.50	23.46	23.21
GSM 1900	512	30.16	30.12	29.50	27.01	26.35	26.00	24.87	22.75	21.15
	661	30.25	30.22	29.18	26.97	25.64	25.95	24.50	22.35	20.73
	810	29.76	29.62	28.56	26.33	25.74	25.67	24.50	22.05	20.58
		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	24.16	23.71	25.39	25.34	25.01	18.37	20.06	19.80	20.83
	190	24.25	23.79	25.46	25.45	25.20	18.17	19.84	19.59	20.79
	251	24.17	23.74	25.48	25.46	24.62	17.90	19.48	19.20	20.20
GSM 1900	512	21.13	21.09	23.48	22.75	23.34	16.97	18.85	18.49	18.14
	661	21.22	21.19	23.16	22.71	22.63	16.92	18.48	18.09	17.72
	810	20.73	20.59	22.54	22.07	22.73	16.64	18.48	17.79	17.57
GSM 850	Frame	23.97	23.97	24.98	25.24	24.99	17.97	19.98	20.24	20.49
GSM 1900	Avg. Targets:	20.97	20.97	22.98	22.74	22.99	16.47	18.48	18.74	18.99

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 28 of 90

Table 9-4
Reduced Average RF Output Powers – Representing Hotspot Mode Active

		Maximum Burst-Averaged Output Power							
		GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	28.44	27.38	25.49	24.26	23.98	22.94	21.48	20.50
	661	28.25	27.50	25.31	23.85	23.19	22.16	20.97	20.38
	810	27.58	27.22	24.70	23.91	23.00	21.81	20.59	20.20
		Calculated Maximum Frame-Averaged Output Power							
		GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	19.41	21.36	21.23	21.25	14.95	16.92	17.22	17.49
	661	19.22	21.48	21.05	20.84	14.16	16.14	16.71	17.37
	810	18.55	21.20	20.44	20.90	13.97	15.79	16.33	17.19
GSM 1900	Frame Avg. Targets:	18.97	20.98	20.74	20.99	14.47	16.48	16.74	16.99

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33 (Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A



Figure 9-2
Power Measurement Setup

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 29 of 90

9.3 UMTS Conducted Powers

Table 9-5
Maximum Average RF Output Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	23.26	23.49	23.20	23.50	23.44	23.46	-
99		12.2 kbps AMR	23.20	23.11	23.01	23.36	23.20	23.44	-
6	HSDPA	Subtest 1	22.14	22.32	22.11	22.00	22.03	22.10	0
6		Subtest 2	22.30	22.41	22.39	22.04	22.10	22.28	0
6		Subtest 3	21.79	21.80	21.89	21.53	21.61	21.73	0.5
6		Subtest 4	21.71	21.80	21.93	21.53	21.76	21.79	0.5
6	HSUPA	Subtest 1	22.44	22.42	22.50	22.22	22.38	22.43	0
6		Subtest 2	20.72	21.00	21.51	20.34	20.69	21.22	2
6		Subtest 3	21.14	20.59	20.68	20.70	20.61	20.63	1
6		Subtest 4	21.70	21.59	21.67	21.21	21.36	21.60	2
6		Subtest 5	21.84	21.67	21.80	21.98	21.95	22.16	0

Table 9-6
Reduced Average RF Output Powers – Representing Hotspot Mode Active

3GPP Release Version	Mode	3GPP 34.121 Subtest	PCS Band [dBm]			3GPP MPR [dB]
			9262	9400	9538	
99	WCDMA	12.2 kbps RMC	20.94	20.65	20.29	-
99		12.2 kbps AMR	20.80	20.56	20.25	-
6	HSDPA	Subtest 1	19.79	19.69	19.25	0
6		Subtest 2	19.71	19.69	19.20	0
6		Subtest 3	19.19	19.06	18.81	0.5
6		Subtest 4	19.28	19.05	18.79	0.5
6	HSUPA	Subtest 1	19.25	19.02	19.23	0
6		Subtest 2	18.61	18.66	18.23	2
6		Subtest 3	18.44	18.51	18.15	1
6		Subtest 4	19.08	18.95	18.48	2
6		Subtest 5	19.35	19.56	19.22	0

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 9-3
Power Measurement Setup

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 30 of 90	

9.4 LTE Conducted Powers

9.4.1 LTE Band 13 – Maximum Output Power

Table 9-7
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	782.0	23230	10	QPSK	1	0	23.00	0	0
	782.0	23230	10	QPSK	1	25	23.48	0	0
	782.0	23230	10	QPSK	1	49	23.03	0	0
	782.0	23230	10	QPSK	25	0	22.11	0-1	1
	782.0	23230	10	QPSK	25	12	22.39	0-1	1
	782.0	23230	10	QPSK	25	25	22.78	0-1	1
	782.0	23230	10	QPSK	50	0	22.13	0-1	1
	782.0	23230	10	16QAM	1	0	22.81	0-1	1
	782.0	23230	10	16QAM	1	25	22.95	0-1	1
	782.0	23230	10	16QAM	1	49	22.83	0-1	1
	782.0	23230	10	16QAM	25	0	21.84	0-2	2
	782.0	23230	10	16QAM	25	12	21.92	0-2	2
	782.0	23230	10	16QAM	25	25	21.82	0-2	2
	782.0	23230	10	16QAM	50	0	21.95	0-2	2

Table 9-8
LTE Band 13 Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	782.0	23230	5	QPSK	1	0	23.36	0	0
	782.0	23230	5	QPSK	1	12	23.47	0	0
	782.0	23230	5	QPSK	1	24	23.33	0	0
	782.0	23230	5	QPSK	12	0	22.59	0-1	1
	782.0	23230	5	QPSK	12	6	22.50	0-1	1
	782.0	23230	5	QPSK	12	13	22.32	0-1	1
	782.0	23230	5	QPSK	25	0	22.39	0-1	1
	782.0	23230	5	16-QAM	1	0	22.28	0-1	1
	782.0	23230	5	16-QAM	1	12	22.52	0-1	1
	782.0	23230	5	16-QAM	1	24	22.37	0-1	1
	782.0	23230	5	16-QAM	12	0	21.44	0-2	2
	782.0	23230	5	16-QAM	12	6	21.52	0-2	2
	782.0	23230	5	16-QAM	12	13	21.46	0-2	2
	782.0	23230	5	16-QAM	25	0	21.50	0-2	2

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 31 of 90

9.4.2 LTE Band 5 (Cell) – Maximum Output Power

Table 9-9
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	836.5	20525	10	QPSK	1	0	24.08	0	0
	836.5	20525	10	QPSK	1	25	24.25	0	0
	836.5	20525	10	QPSK	1	49	23.81	0	0
	836.5	20525	10	QPSK	25	0	23.25	0-1	1
	836.5	20525	10	QPSK	25	12	23.07	0-1	1
	836.5	20525	10	QPSK	25	25	23.11	0-1	1
	836.5	20525	10	QPSK	50	0	22.92	0-1	1
	836.5	20525	10	16QAM	1	0	23.43	0-1	1
	836.5	20525	10	16QAM	1	25	23.33	0-1	1
	836.5	20525	10	16QAM	1	49	23.38	0-1	1
	836.5	20525	10	16QAM	25	0	22.27	0-2	2
	836.5	20525	10	16QAM	25	12	22.16	0-2	2
	836.5	20525	10	16QAM	25	25	22.12	0-2	2
	836.5	20525	10	16QAM	50	0	22.19	0-2	2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-10
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	826.5	20425	5	QPSK	1	0	23.88	0	0
	826.5	20425	5	QPSK	1	12	24.22	0	0
	826.5	20425	5	QPSK	1	24	23.94	0	0
	826.5	20425	5	QPSK	12	0	23.05	0-1	1
	826.5	20425	5	QPSK	12	6	23.08	0-1	1
	826.5	20425	5	QPSK	12	13	22.95	0-1	1
	826.5	20425	5	QPSK	25	0	22.87	0-1	1
	826.5	20425	5	16-QAM	1	0	23.47	0-1	1
	826.5	20425	5	16-QAM	1	12	23.15	0-1	1
	826.5	20425	5	16-QAM	1	24	23.30	0-1	1
	826.5	20425	5	16-QAM	12	0	22.29	0-2	2
	826.5	20425	5	16-QAM	12	6	22.28	0-2	2
	826.5	20425	5	16-QAM	12	13	21.97	0-2	2
	826.5	20425	5	16-QAM	25	0	22.01	0-2	2
	836.5	20525	5	QPSK	1	0	24.08	0	0
Mid	836.5	20525	5	QPSK	1	12	24.24	0	0
	836.5	20525	5	QPSK	1	24	24.18	0	0
	836.5	20525	5	QPSK	12	0	23.00	0-1	1
	836.5	20525	5	QPSK	12	6	23.29	0-1	1
	836.5	20525	5	QPSK	12	13	23.02	0-1	1
	836.5	20525	5	QPSK	25	0	22.99	0-1	1
	836.5	20525	5	16-QAM	1	0	23.18	0-1	1
	836.5	20525	5	16-QAM	1	12	23.21	0-1	1
	836.5	20525	5	16-QAM	1	24	23.25	0-1	1
	836.5	20525	5	16-QAM	12	0	22.38	0-2	2
	836.5	20525	5	16-QAM	12	6	22.44	0-2	2
	836.5	20525	5	16-QAM	12	13	21.77	0-2	2
	836.5	20525	5	16-QAM	25	0	21.83	0-2	2
	846.5	20625	5	QPSK	1	0	24.15	0	0
	846.5	20625	5	QPSK	1	12	24.24	0	0
	846.5	20625	5	QPSK	1	24	24.20	0	0
High	846.5	20625	5	QPSK	12	0	23.09	0-1	1
	846.5	20625	5	QPSK	12	6	23.23	0-1	1
	846.5	20625	5	QPSK	12	13	23.21	0-1	1
	846.5	20625	5	QPSK	25	0	23.00	0-1	1
	846.5	20625	5	16-QAM	1	0	23.25	0-1	1
	846.5	20625	5	16-QAM	1	12	23.32	0-1	1
	846.5	20625	5	16-QAM	1	24	23.17	0-1	1
	846.5	20625	5	16-QAM	12	0	22.35	0-2	2
	846.5	20625	5	16-QAM	12	6	22.47	0-2	2
	846.5	20625	5	16-QAM	12	13	21.69	0-2	2
	846.5	20625	5	16-QAM	25	0	21.99	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 32 of 90

Table 9-11
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	825.5	20415	3	QPSK	1	0	23.94	0	0
	825.5	20415	3	QPSK	1	7	24.09	0	0
	825.5	20415	3	QPSK	1	14	24.09	0	0
	825.5	20415	3	QPSK	8	0	23.22	0-1	1
	825.5	20415	3	QPSK	8	4	23.07	0-1	1
	825.5	20415	3	QPSK	8	7	23.03	0-1	1
	825.5	20415	3	QPSK	15	0	22.75	0-1	1
	825.5	20415	3	16-QAM	1	0	23.30	0-1	1
	825.5	20415	3	16-QAM	1	7	23.30	0-1	1
	825.5	20415	3	16-QAM	1	14	23.26	0-1	1
	825.5	20415	3	16-QAM	8	0	22.42	0-2	2
	825.5	20415	3	16-QAM	8	4	22.19	0-2	2
	825.5	20415	3	16-QAM	8	7	22.17	0-2	2
	825.5	20415	3	16-QAM	15	0	21.93	0-2	2
Mid	836.5	20525	3	QPSK	1	0	24.08	0	0
	836.5	20525	3	QPSK	1	7	24.28	0	0
	836.5	20525	3	QPSK	1	14	24.24	0	0
	836.5	20525	3	QPSK	8	0	22.95	0-1	1
	836.5	20525	3	QPSK	8	4	23.09	0-1	1
	836.5	20525	3	QPSK	8	7	22.82	0-1	1
	836.5	20525	3	QPSK	15	0	22.92	0-1	1
	836.5	20525	3	16-QAM	1	0	23.26	0-1	1
	836.5	20525	3	16-QAM	1	7	23.22	0-1	1
	836.5	20525	3	16-QAM	1	14	23.15	0-1	1
	836.5	20525	3	16-QAM	8	0	22.18	0-2	2
	836.5	20525	3	16-QAM	8	4	22.28	0-2	2
	836.5	20525	3	16-QAM	8	7	21.89	0-2	2
	836.5	20525	3	16-QAM	15	0	21.99	0-2	2
High	847.5	20635	3	QPSK	1	0	24.38	0	0
	847.5	20635	3	QPSK	1	7	24.38	0	0
	847.5	20635	3	QPSK	1	14	24.48	0	0
	847.5	20635	3	QPSK	8	0	23.26	0-1	1
	847.5	20635	3	QPSK	8	4	23.23	0-1	1
	847.5	20635	3	QPSK	8	7	23.06	0-1	1
	847.5	20635	3	QPSK	15	0	23.03	0-1	1
	847.5	20635	3	16-QAM	1	0	23.20	0-1	1
	847.5	20635	3	16-QAM	1	7	23.22	0-1	1
	847.5	20635	3	16-QAM	1	14	23.26	0-1	1
	847.5	20635	3	16-QAM	8	0	22.43	0-2	2
	847.5	20635	3	16-QAM	8	4	22.38	0-2	2
	847.5	20635	3	16-QAM	8	7	21.75	0-2	2
	847.5	20635	3	16-QAM	15	0	21.93	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 33 of 90	

Table 9-12
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	824.7	20407	1.4	QPSK	1	0	23.93	0	0
	824.7	20407	1.4	QPSK	1	2	24.23	0	0
	824.7	20407	1.4	QPSK	1	5	24.22	0	0
	824.7	20407	1.4	QPSK	3	0	24.24	0	0
	824.7	20407	1.4	QPSK	3	2	24.01	0	0
	824.7	20407	1.4	QPSK	3	3	24.11	0	0
	824.7	20407	1.4	QPSK	6	0	22.71	0-1	1
	824.7	20407	1.4	16-QAM	1	0	23.21	0-1	1
	824.7	20407	1.4	16-QAM	1	2	23.29	0-1	1
	824.7	20407	1.4	16-QAM	1	5	23.22	0-1	1
	824.7	20407	1.4	16-QAM	3	0	23.45	0-1	1
	824.7	20407	1.4	16-QAM	3	2	23.09	0-1	1
	824.7	20407	1.4	16-QAM	3	3	23.15	0-1	1
Mid	836.5	20525	1.4	QPSK	1	0	23.98	0	0
	836.5	20525	1.4	QPSK	1	2	24.17	0	0
	836.5	20525	1.4	QPSK	1	5	24.19	0	0
	836.5	20525	1.4	QPSK	3	0	24.12	0	0
	836.5	20525	1.4	QPSK	3	2	24.24	0	0
	836.5	20525	1.4	QPSK	3	3	23.90	0	0
	836.5	20525	1.4	QPSK	6	0	22.86	0-1	1
	836.5	20525	1.4	16-QAM	1	0	23.43	0-1	1
	836.5	20525	1.4	16-QAM	1	2	23.09	0-1	1
	836.5	20525	1.4	16-QAM	1	5	22.99	0-1	1
	836.5	20525	1.4	16-QAM	3	0	22.99	0-1	1
	836.5	20525	1.4	16-QAM	3	2	23.14	0-1	1
	836.5	20525	1.4	16-QAM	3	3	22.86	0-1	1
High	848.3	20643	1.4	QPSK	1	0	24.23	0	0
	848.3	20643	1.4	QPSK	1	2	24.22	0	0
	848.3	20643	1.4	QPSK	1	5	24.23	0	0
	848.3	20643	1.4	QPSK	3	0	24.09	0	0
	848.3	20643	1.4	QPSK	3	2	24.24	0	0
	848.3	20643	1.4	QPSK	3	3	24.09	0	0
	848.3	20643	1.4	QPSK	6	0	22.90	0-1	1
	848.3	20643	1.4	16-QAM	1	0	23.03	0-1	1
	848.3	20643	1.4	16-QAM	1	2	23.14	0-1	1
	848.3	20643	1.4	16-QAM	1	5	23.33	0-1	1
	848.3	20643	1.4	16-QAM	3	0	23.36	0-1	1
	848.3	20643	1.4	16-QAM	3	2	23.22	0-1	1
	848.3	20643	1.4	16-QAM	3	3	22.73	0-1	1
	848.3	20643	1.4	16-QAM	6	0	21.83	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 34 of 90	

9.4.3

LTE Band 4 (AWS)

9.4.3.1 Maximum Output Power

Table 9-13
Maximum LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	1732.5	20175	20	QPSK	1	0	24.40	0	0
	1732.5	20175	20	QPSK	1	50	23.83	0	0
	1732.5	20175	20	QPSK	1	99	23.77	0	0
	1732.5	20175	20	QPSK	50	0	23.16	0-1	1
	1732.5	20175	20	QPSK	50	25	23.21	0-1	1
	1732.5	20175	20	QPSK	50	50	22.95	0-1	1
	1732.5	20175	20	QPSK	100	0	23.19	0-1	1
	1732.5	20175	20	16QAM	1	0	23.50	0-1	1
	1732.5	20175	20	16QAM	1	50	23.24	0-1	1
	1732.5	20175	20	16QAM	1	99	23.47	0-1	1
	1732.5	20175	20	16QAM	50	0	22.36	0-2	2
	1732.5	20175	20	16QAM	50	25	22.00	0-2	2
	1732.5	20175	20	16QAM	50	50	22.03	0-2	2
	1732.5	20175	20	16QAM	100	0	22.19	0-2	2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-14
Maximum LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1717.5	20025	15	QPSK	1	0	24.02	0	0
	1717.5	20025	15	QPSK	1	36	23.91	0	0
	1717.5	20025	15	QPSK	1	74	23.55	0	0
	1717.5	20025	15	QPSK	36	0	23.42	0-1	1
	1717.5	20025	15	QPSK	36	18	22.96	0-1	1
	1717.5	20025	15	QPSK	36	37	22.94	0-1	1
	1717.5	20025	15	QPSK	75	0	23.35	0-1	1
	1717.5	20025	15	16QAM	1	0	23.27	0-1	1
	1717.5	20025	15	16QAM	1	36	23.30	0-1	1
	1717.5	20025	15	16QAM	1	74	23.30	0-1	1
	1717.5	20025	15	16QAM	36	0	22.21	0-2	2
	1717.5	20025	15	16QAM	36	18	21.71	0-2	2
	1717.5	20025	15	16QAM	36	37	21.92	0-2	2
	1717.5	20025	15	16QAM	75	0	22.30	0-2	2
	1732.5	20175	15	QPSK	1	0	24.22	0	0
	1732.5	20175	15	QPSK	1	36	23.65	0	0
Mid	1732.5	20175	15	QPSK	1	74	23.56	0	0
	1732.5	20175	15	QPSK	36	0	23.32	0-1	1
	1732.5	20175	15	QPSK	36	18	23.06	0-1	1
	1732.5	20175	15	QPSK	36	37	22.89	0-1	1
	1732.5	20175	15	QPSK	75	0	23.09	0-1	1
	1732.5	20175	15	16QAM	1	0	23.30	0-1	1
	1732.5	20175	15	16QAM	1	36	23.28	0-1	1
	1732.5	20175	15	16QAM	1	74	23.23	0-1	1
	1732.5	20175	15	16QAM	36	0	22.35	0-2	2
	1732.5	20175	15	16QAM	36	18	21.82	0-2	2
	1732.5	20175	15	16QAM	36	37	22.21	0-2	2
	1732.5	20175	15	16QAM	75	0	22.24	0-2	2
	1747.5	20325	15	QPSK	1	0	24.03	0	0
	1747.5	20325	15	QPSK	1	36	23.80	0	0
	1747.5	20325	15	QPSK	1	74	23.73	0	0
High	1747.5	20325	15	QPSK	36	0	23.37	0-1	1
	1747.5	20325	15	QPSK	36	18	23.16	0-1	1
	1747.5	20325	15	QPSK	36	37	22.80	0-1	1
	1747.5	20325	15	QPSK	75	0	23.23	0-1	1
	1747.5	20325	15	16QAM	1	0	23.42	0-1	1
	1747.5	20325	15	16QAM	1	36	23.33	0-1	1
	1747.5	20325	15	16QAM	1	74	23.11	0-1	1
	1747.5	20325	15	16QAM	36	0	22.32	0-2	2
	1747.5	20325	15	16QAM	36	18	21.78	0-2	2
	1747.5	20325	15	16QAM	36	37	22.21	0-2	2
	1747.5	20325	15	16QAM	75	0	22.07	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 35 of 90

Table 9-15
Maximum LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1715	20000	10	QPSK	1	0	23.89	0	0
	1715	20000	10	QPSK	1	25	23.97	0	0
	1715	20000	10	QPSK	1	49	23.56	0	0
	1715	20000	10	QPSK	25	0	23.40	0-1	1
	1715	20000	10	QPSK	25	12	22.85	0-1	1
	1715	20000	10	QPSK	25	25	22.96	0-1	1
	1715	20000	10	QPSK	50	0	23.32	0-1	1
	1715	20000	10	16QAM	1	0	23.16	0-1	1
	1715	20000	10	16QAM	1	25	23.11	0-1	1
	1715	20000	10	16QAM	1	49	23.12	0-1	1
	1715	20000	10	16QAM	25	0	22.35	0-2	2
	1715	20000	10	16QAM	25	12	21.90	0-2	2
	1715	20000	10	16QAM	25	25	21.74	0-2	2
	1715	20000	10	16QAM	50	0	22.21	0-2	2
Mid	1732.5	20175	10	QPSK	1	0	24.35	0	0
	1732.5	20175	10	QPSK	1	25	23.69	0	0
	1732.5	20175	10	QPSK	1	49	23.50	0	0
	1732.5	20175	10	QPSK	25	0	23.34	0-1	1
	1732.5	20175	10	QPSK	25	12	23.04	0-1	1
	1732.5	20175	10	QPSK	25	25	22.82	0-1	1
	1732.5	20175	10	QPSK	50	0	23.13	0-1	1
	1732.5	20175	10	16QAM	1	0	23.35	0-1	1
	1732.5	20175	10	16QAM	1	25	23.27	0-1	1
	1732.5	20175	10	16QAM	1	49	23.04	0-1	1
	1732.5	20175	10	16QAM	25	0	22.33	0-2	2
	1732.5	20175	10	16QAM	25	12	21.68	0-2	2
	1732.5	20175	10	16QAM	25	25	22.36	0-2	2
	1732.5	20175	10	16QAM	50	0	22.23	0-2	2
High	1750	20350	10	QPSK	1	0	24.00	0	0
	1750	20350	10	QPSK	1	25	23.83	0	0
	1750	20350	10	QPSK	1	49	23.75	0	0
	1750	20350	10	QPSK	25	0	23.42	0-1	1
	1750	20350	10	QPSK	25	12	23.17	0-1	1
	1750	20350	10	QPSK	25	25	22.91	0-1	1
	1750	20350	10	QPSK	50	0	23.40	0-1	1
	1750	20350	10	16QAM	1	0	23.46	0-1	1
	1750	20350	10	16QAM	1	25	23.22	0-1	1
	1750	20350	10	16QAM	1	49	23.29	0-1	1
	1750	20350	10	16QAM	25	0	22.13	0-2	2
	1750	20350	10	16QAM	25	12	21.83	0-2	2
	1750	20350	10	16QAM	25	25	22.26	0-2	2
	1750	20350	10	16QAM	50	0	21.99	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 36 of 90	

Table 9-16
Maximum LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1712.5	19975	5	QPSK	1	0	23.97	0	0
	1712.5	19975	5	QPSK	1	12	23.86	0	0
	1712.5	19975	5	QPSK	1	24	23.70	0	0
	1712.5	19975	5	QPSK	12	0	23.34	0-1	1
	1712.5	19975	5	QPSK	12	6	22.95	0-1	1
	1712.5	19975	5	QPSK	12	13	22.87	0-1	1
	1712.5	19975	5	QPSK	25	0	23.39	0-1	1
	1712.5	19975	5	16-QAM	1	0	23.35	0-1	1
	1712.5	19975	5	16-QAM	1	12	22.99	0-1	1
	1712.5	19975	5	16-QAM	1	24	23.03	0-1	1
	1712.5	19975	5	16-QAM	12	0	22.42	0-2	2
	1712.5	19975	5	16-QAM	12	6	21.72	0-2	2
	1712.5	19975	5	16-QAM	12	13	21.57	0-2	2
Mid	1732.5	20175	5	QPSK	1	0	24.30	0	0
	1732.5	20175	5	QPSK	1	12	23.88	0	0
	1732.5	20175	5	QPSK	1	24	23.64	0	0
	1732.5	20175	5	QPSK	12	0	23.16	0-1	1
	1732.5	20175	5	QPSK	12	6	22.87	0-1	1
	1732.5	20175	5	QPSK	12	13	22.86	0-1	1
	1732.5	20175	5	QPSK	25	0	23.28	0-1	1
	1732.5	20175	5	16-QAM	1	0	23.15	0-1	1
	1732.5	20175	5	16-QAM	1	12	23.26	0-1	1
	1732.5	20175	5	16-QAM	1	24	23.00	0-1	1
	1732.5	20175	5	16-QAM	12	0	22.18	0-2	2
	1732.5	20175	5	16-QAM	12	6	21.86	0-2	2
	1732.5	20175	5	16-QAM	12	13	22.45	0-2	2
	1732.5	20175	5	16-QAM	25	0	22.14	0-2	2
High	1752.5	20375	5	QPSK	1	0	23.92	0	0
	1752.5	20375	5	QPSK	1	12	23.64	0	0
	1752.5	20375	5	QPSK	1	24	23.63	0	0
	1752.5	20375	5	QPSK	12	0	23.26	0-1	1
	1752.5	20375	5	QPSK	12	6	23.23	0-1	1
	1752.5	20375	5	QPSK	12	13	23.01	0-1	1
	1752.5	20375	5	QPSK	25	0	23.45	0-1	1
	1752.5	20375	5	16-QAM	1	0	23.50	0-1	1
	1752.5	20375	5	16-QAM	1	12	23.28	0-1	1
	1752.5	20375	5	16-QAM	1	24	23.14	0-1	1
	1752.5	20375	5	16-QAM	12	0	22.02	0-2	2
	1752.5	20375	5	16-QAM	12	6	21.95	0-2	2
	1752.5	20375	5	16-QAM	12	13	22.45	0-2	2
	1752.5	20375	5	16-QAM	25	0	22.15	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 37 of 90	

Table 9-17
Maximum LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1711.5	19965	3	QPSK	1	0	23.91	0	0
	1711.5	19965	3	QPSK	1	7	23.87	0	0
	1711.5	19965	3	QPSK	1	14	23.71	0	0
	1711.5	19965	3	QPSK	8	0	23.46	0-1	1
	1711.5	19965	3	QPSK	8	4	23.13	0-1	1
	1711.5	19965	3	QPSK	8	7	22.99	0-1	1
	1711.5	19965	3	QPSK	15	0	23.20	0-1	1
	1711.5	19965	3	16-QAM	1	0	23.25	0-1	1
	1711.5	19965	3	16-QAM	1	7	22.80	0-1	1
	1711.5	19965	3	16-QAM	1	14	22.87	0-1	1
	1711.5	19965	3	16-QAM	8	0	22.15	0-2	2
	1711.5	19965	3	16-QAM	8	4	21.82	0-2	2
	1711.5	19965	3	16-QAM	8	7	22.22	0-2	2
Mid	1732.5	20175	3	QPSK	1	0	24.16	0	0
	1732.5	20175	3	QPSK	1	7	23.86	0	0
	1732.5	20175	3	QPSK	1	14	23.73	0	0
	1732.5	20175	3	QPSK	8	0	23.30	0-1	1
	1732.5	20175	3	QPSK	8	4	22.93	0-1	1
	1732.5	20175	3	QPSK	8	7	22.69	0-1	1
	1732.5	20175	3	QPSK	15	0	23.46	0-1	1
	1732.5	20175	3	16-QAM	1	0	23.33	0-1	1
	1732.5	20175	3	16-QAM	1	7	23.11	0-1	1
	1732.5	20175	3	16-QAM	1	14	23.01	0-1	1
	1732.5	20175	3	16-QAM	8	0	22.28	0-2	2
	1732.5	20175	3	16-QAM	8	4	21.89	0-2	2
	1732.5	20175	3	16-QAM	8	7	22.44	0-2	2
	1732.5	20175	3	16-QAM	15	0	21.98	0-2	2
High	1753.5	20385	3	QPSK	1	0	23.83	0	0
	1753.5	20385	3	QPSK	1	7	23.80	0	0
	1753.5	20385	3	QPSK	1	14	23.75	0	0
	1753.5	20385	3	QPSK	8	0	23.38	0-1	1
	1753.5	20385	3	QPSK	8	4	23.35	0-1	1
	1753.5	20385	3	QPSK	8	7	23.05	0-1	1
	1753.5	20385	3	QPSK	15	0	23.30	0-1	1
	1753.5	20385	3	16-QAM	1	0	23.45	0-1	1
	1753.5	20385	3	16-QAM	1	7	23.27	0-1	1
	1753.5	20385	3	16-QAM	1	14	23.33	0-1	1
	1753.5	20385	3	16-QAM	8	0	21.94	0-2	2
	1753.5	20385	3	16-QAM	8	4	22.15	0-2	2
	1753.5	20385	3	16-QAM	8	7	22.41	0-2	2
	1753.5	20385	3	16-QAM	15	0	22.01	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 38 of 90

Table 9-18
Maximum LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1710.7	19957	1.4	QPSK	1	0	23.87	0	0
	1710.7	19957	1.4	QPSK	1	2	24.00	0	0
	1710.7	19957	1.4	QPSK	1	5	23.58	0	0
	1710.7	19957	1.4	QPSK	3	0	24.20	0	0
	1710.7	19957	1.4	QPSK	3	2	24.28	0	0
	1710.7	19957	1.4	QPSK	3	3	24.05	0	0
	1710.7	19957	1.4	QPSK	6	0	23.46	0-1	1
	1710.7	19957	1.4	16-QAM	1	0	23.28	0-1	1
	1710.7	19957	1.4	16-QAM	1	2	22.65	0-1	1
	1710.7	19957	1.4	16-QAM	1	5	23.05	0-1	1
	1710.7	19957	1.4	16-QAM	3	0	23.38	0-1	1
	1710.7	19957	1.4	16-QAM	3	2	22.75	0-1	1
	1710.7	19957	1.4	16-QAM	3	3	22.54	0-1	1
Mid	1710.7	19957	1.4	16-QAM	6	0	22.25	0-2	2
	1732.5	20175	1.4	QPSK	1	0	24.07	0	0
	1732.5	20175	1.4	QPSK	1	2	23.87	0	0
	1732.5	20175	1.4	QPSK	1	5	23.92	0	0
	1732.5	20175	1.4	QPSK	3	0	24.25	0	0
	1732.5	20175	1.4	QPSK	3	2	24.11	0	0
	1732.5	20175	1.4	QPSK	3	3	23.96	0	0
	1732.5	20175	1.4	QPSK	6	0	23.33	0-1	1
	1732.5	20175	1.4	16-QAM	1	0	23.14	0-1	1
	1732.5	20175	1.4	16-QAM	1	2	23.20	0-1	1
	1732.5	20175	1.4	16-QAM	1	5	22.89	0-1	1
	1732.5	20175	1.4	16-QAM	3	0	23.29	0-1	1
	1732.5	20175	1.4	16-QAM	3	2	22.90	0-1	1
	1732.5	20175	1.4	16-QAM	3	3	23.37	0-1	1
High	1732.5	20175	1.4	16-QAM	6	0	22.03	0-2	2
	1754.3	20393	1.4	QPSK	1	0	23.88	0	0
	1754.3	20393	1.4	QPSK	1	2	23.80	0	0
	1754.3	20393	1.4	QPSK	1	5	23.74	0	0
	1754.3	20393	1.4	QPSK	3	0	23.71	0	0
	1754.3	20393	1.4	QPSK	3	2	24.26	0	0
	1754.3	20393	1.4	QPSK	3	3	24.00	0	0
	1754.3	20393	1.4	QPSK	6	0	23.48	0-1	1
	1754.3	20393	1.4	16-QAM	1	0	23.48	0-1	1
	1754.3	20393	1.4	16-QAM	1	2	23.17	0-1	1
	1754.3	20393	1.4	16-QAM	1	5	23.21	0-1	1
	1754.3	20393	1.4	16-QAM	3	0	23.11	0-1	1
	1754.3	20393	1.4	16-QAM	3	2	23.13	0-1	1
	1754.3	20393	1.4	16-QAM	3	3	23.35	0-1	1
	1754.3	20393	1.4	16-QAM	6	0	22.10	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 39 of 90	

9.4.3.2 Reduced Output Power - Representing Hotspot Mode Active

Table 9-19
Reduced LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	1732.5	20175	20	QPSK	1	0	20.43	0	0
	1732.5	20175	20	QPSK	1	50	19.62	0	0
	1732.5	20175	20	QPSK	1	99	19.99	0	0
	1732.5	20175	20	QPSK	50	0	19.97	0-1	0
	1732.5	20175	20	QPSK	50	25	19.74	0-1	0
	1732.5	20175	20	QPSK	50	50	19.68	0-1	0
	1732.5	20175	20	QPSK	100	0	19.84	0-1	0
	1732.5	20175	20	16QAM	1	0	20.00	0-1	0
	1732.5	20175	20	16QAM	1	50	20.50	0-1	0
	1732.5	20175	20	16QAM	1	99	20.25	0-1	0
	1732.5	20175	20	16QAM	50	0	19.98	0-2	0
	1732.5	20175	20	16QAM	50	25	19.75	0-2	0
	1732.5	20175	20	16QAM	50	50	19.65	0-2	0
	1732.5	20175	20	16QAM	100	0	19.84	0-2	0

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-20
Reduced LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1717.5	20025	15	QPSK	1	0	20.39	0	0
	1717.5	20025	15	QPSK	1	36	20.08	0	0
	1717.5	20025	15	QPSK	1	74	19.94	0	0
	1717.5	20025	15	QPSK	36	0	19.61	0-1	0
	1717.5	20025	15	QPSK	36	18	19.57	0-1	0
	1717.5	20025	15	QPSK	36	37	19.77	0-1	0
	1717.5	20025	15	QPSK	75	0	19.65	0-1	0
	1717.5	20025	15	16QAM	1	0	20.22	0-1	0
	1717.5	20025	15	16QAM	1	36	20.40	0-1	0
	1717.5	20025	15	16QAM	1	74	20.14	0-1	0
	1717.5	20025	15	16QAM	36	0	19.80	0-2	0
	1717.5	20025	15	16QAM	36	18	19.88	0-2	0
	1717.5	20025	15	16QAM	36	37	19.88	0-2	0
	1717.5	20025	15	16QAM	75	0	19.72	0-2	0
Mid	1732.5	20175	15	QPSK	1	0	20.22	0	0
	1732.5	20175	15	QPSK	1	36	20.17	0	0
	1732.5	20175	15	QPSK	1	74	20.09	0	0
	1732.5	20175	15	QPSK	36	0	19.79	0-1	0
	1732.5	20175	15	QPSK	36	18	19.72	0-1	0
	1732.5	20175	15	QPSK	36	37	19.75	0-1	0
	1732.5	20175	15	QPSK	75	0	19.81	0-1	0
	1732.5	20175	15	16QAM	1	0	20.14	0-1	0
	1732.5	20175	15	16QAM	1	36	20.22	0-1	0
	1732.5	20175	15	16QAM	1	74	20.31	0-1	0
	1732.5	20175	15	16QAM	36	0	19.94	0-2	0
	1732.5	20175	15	16QAM	36	18	19.72	0-2	0
	1732.5	20175	15	16QAM	36	37	19.75	0-2	0
	1732.5	20175	15	16QAM	75	0	19.81	0-2	0
High	1747.5	20325	15	QPSK	1	0	20.26	0	0
	1747.5	20325	15	QPSK	1	36	20.34	0	0
	1747.5	20325	15	QPSK	1	74	20.09	0	0
	1747.5	20325	15	QPSK	36	0	19.84	0-1	0
	1747.5	20325	15	QPSK	36	18	19.84	0-1	0
	1747.5	20325	15	QPSK	36	37	19.63	0-1	0
	1747.5	20325	15	QPSK	75	0	19.97	0-1	0
	1747.5	20325	15	16QAM	1	0	20.15	0-1	0
	1747.5	20325	15	16QAM	1	36	20.33	0-1	0
	1747.5	20325	15	16QAM	1	74	20.42	0-1	0
	1747.5	20325	15	16QAM	36	0	20.02	0-2	0
	1747.5	20325	15	16QAM	36	18	19.84	0-2	0
	1747.5	20325	15	16QAM	36	37	19.92	0-2	0
	1747.5	20325	15	16QAM	75	0	19.77	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 40 of 90

Table 9-21
Reduced LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1715	20000	10	QPSK	1	0	20.19	0	0
	1715	20000	10	QPSK	1	25	19.99	0	0
	1715	20000	10	QPSK	1	49	20.07	0	0
	1715	20000	10	QPSK	25	0	19.50	0-1	0
	1715	20000	10	QPSK	25	12	19.67	0-1	0
	1715	20000	10	QPSK	25	25	19.77	0-1	0
	1715	20000	10	QPSK	50	0	19.75	0-1	0
	1715	20000	10	16QAM	1	0	20.38	0-1	0
	1715	20000	10	16QAM	1	25	20.32	0-1	0
	1715	20000	10	16QAM	1	49	20.18	0-1	0
	1715	20000	10	16QAM	25	0	19.80	0-2	0
	1715	20000	10	16QAM	25	12	20.10	0-2	0
	1715	20000	10	16QAM	25	25	19.73	0-2	0
	1715	20000	10	16QAM	50	0	19.67	0-2	0
Mid	1732.5	20175	10	QPSK	1	0	20.27	0	0
	1732.5	20175	10	QPSK	1	25	20.00	0	0
	1732.5	20175	10	QPSK	1	49	20.37	0	0
	1732.5	20175	10	QPSK	25	0	19.68	0-1	0
	1732.5	20175	10	QPSK	25	12	19.91	0-1	0
	1732.5	20175	10	QPSK	25	25	19.59	0-1	0
	1732.5	20175	10	QPSK	50	0	19.94	0-1	0
	1732.5	20175	10	16QAM	1	0	20.31	0-1	0
	1732.5	20175	10	16QAM	1	25	19.93	0-1	0
	1732.5	20175	10	16QAM	1	49	20.04	0-1	0
	1732.5	20175	10	16QAM	25	0	20.13	0-2	0
	1732.5	20175	10	16QAM	25	12	19.76	0-2	0
	1732.5	20175	10	16QAM	25	25	19.80	0-2	0
	1732.5	20175	10	16QAM	50	0	19.97	0-2	0
High	1750	20350	10	QPSK	1	0	20.00	0	0
	1750	20350	10	QPSK	1	25	20.27	0	0
	1750	20350	10	QPSK	1	49	20.09	0	0
	1750	20350	10	QPSK	25	0	19.72	0-1	0
	1750	20350	10	QPSK	25	12	19.81	0-1	0
	1750	20350	10	QPSK	25	25	19.75	0-1	0
	1750	20350	10	QPSK	50	0	19.77	0-1	0
	1750	20350	10	16QAM	1	0	20.42	0-1	0
	1750	20350	10	16QAM	1	25	20.17	0-1	0
	1750	20350	10	16QAM	1	49	20.22	0-1	0
	1750	20350	10	16QAM	25	0	19.94	0-2	0
	1750	20350	10	16QAM	25	12	20.07	0-2	0
	1750	20350	10	16QAM	25	25	19.79	0-2	0
	1750	20350	10	16QAM	50	0	19.93	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 41 of 90

Table 9-22
Reduced LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1712.5	19975	5	QPSK	1	0	19.91	0	0
	1712.5	19975	5	QPSK	1	12	20.01	0	0
	1712.5	19975	5	QPSK	1	24	20.18	0	0
	1712.5	19975	5	QPSK	12	0	19.78	0-1	0
	1712.5	19975	5	QPSK	12	6	19.56	0-1	0
	1712.5	19975	5	QPSK	12	13	19.57	0-1	0
	1712.5	19975	5	QPSK	25	0	19.73	0-1	0
	1712.5	19975	5	16-QAM	1	0	20.42	0-1	0
	1712.5	19975	5	16-QAM	1	12	20.20	0-1	0
	1712.5	19975	5	16-QAM	1	24	20.12	0-1	0
	1712.5	19975	5	16-QAM	12	0	19.93	0-2	0
	1712.5	19975	5	16-QAM	12	6	20.39	0-2	0
	1712.5	19975	5	16-QAM	12	13	19.57	0-2	0
Mid	1732.5	20175	5	QPSK	1	0	20.42	0	0
	1732.5	20175	5	QPSK	1	12	20.03	0	0
	1732.5	20175	5	QPSK	1	24	20.40	0	0
	1732.5	20175	5	QPSK	12	0	19.53	0-1	0
	1732.5	20175	5	QPSK	12	6	19.61	0-1	0
	1732.5	20175	5	QPSK	12	13	19.64	0-1	0
	1732.5	20175	5	QPSK	25	0	19.93	0-1	0
	1732.5	20175	5	16-QAM	1	0	20.06	0-1	0
	1732.5	20175	5	16-QAM	1	12	19.99	0-1	0
	1732.5	20175	5	16-QAM	1	24	20.29	0-1	0
	1732.5	20175	5	16-QAM	12	0	20.03	0-2	0
	1732.5	20175	5	16-QAM	12	6	19.80	0-2	0
	1732.5	20175	5	16-QAM	12	13	20.03	0-2	0
	1732.5	20175	5	16-QAM	25	0	19.71	0-2	0
High	1752.5	20375	5	QPSK	1	0	20.29	0	0
	1752.5	20375	5	QPSK	1	12	20.38	0	0
	1752.5	20375	5	QPSK	1	24	19.92	0	0
	1752.5	20375	5	QPSK	12	0	19.58	0-1	0
	1752.5	20375	5	QPSK	12	6	20.09	0-1	0
	1752.5	20375	5	QPSK	12	13	19.72	0-1	0
	1752.5	20375	5	QPSK	25	0	19.68	0-1	0
	1752.5	20375	5	16-QAM	1	0	20.22	0-1	0
	1752.5	20375	5	16-QAM	1	12	20.16	0-1	0
	1752.5	20375	5	16-QAM	1	24	20.31	0-1	0
	1752.5	20375	5	16-QAM	12	0	20.15	0-2	0
	1752.5	20375	5	16-QAM	12	6	20.28	0-2	0
	1752.5	20375	5	16-QAM	12	13	19.75	0-2	0
	1752.5	20375	5	16-QAM	25	0	20.07	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 42 of 90

Table 9-23
Reduced LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1711.5	19965	3	QPSK	1	0	20.04	0	0
	1711.5	19965	3	QPSK	1	7	20.21	0	0
	1711.5	19965	3	QPSK	1	14	20.25	0	0
	1711.5	19965	3	QPSK	8	0	19.97	0-1	0
	1711.5	19965	3	QPSK	8	4	19.65	0-1	0
	1711.5	19965	3	QPSK	8	7	19.51	0-1	0
	1711.5	19965	3	QPSK	15	0	19.79	0-1	0
	1711.5	19965	3	16-QAM	1	0	20.32	0-1	0
	1711.5	19965	3	16-QAM	1	7	20.21	0-1	0
	1711.5	19965	3	16-QAM	1	14	20.25	0-1	0
	1711.5	19965	3	16-QAM	8	0	20.02	0-2	0
	1711.5	19965	3	16-QAM	8	4	20.27	0-2	0
	1711.5	19965	3	16-QAM	8	7	19.94	0-2	0
Mid	1732.5	20175	3	QPSK	1	0	20.33	0	0
	1732.5	20175	3	QPSK	1	7	19.84	0	0
	1732.5	20175	3	QPSK	1	14	20.21	0	0
	1732.5	20175	3	QPSK	8	0	19.67	0-1	0
	1732.5	20175	3	QPSK	8	4	19.73	0-1	0
	1732.5	20175	3	QPSK	8	7	19.69	0-1	0
	1732.5	20175	3	QPSK	15	0	19.93	0-1	0
	1732.5	20175	3	16-QAM	1	0	20.25	0-1	0
	1732.5	20175	3	16-QAM	1	7	19.84	0-1	0
	1732.5	20175	3	16-QAM	1	14	20.32	0-1	0
	1732.5	20175	3	16-QAM	8	0	20.01	0-2	0
	1732.5	20175	3	16-QAM	8	4	19.80	0-2	0
	1732.5	20175	3	16-QAM	8	7	20.23	0-2	0
	1732.5	20175	3	16-QAM	15	0	19.85	0-2	0
High	1753.5	20385	3	QPSK	1	0	20.35	0	0
	1753.5	20385	3	QPSK	1	7	20.42	0	0
	1753.5	20385	3	QPSK	1	14	19.94	0	0
	1753.5	20385	3	QPSK	8	0	19.70	0-1	0
	1753.5	20385	3	QPSK	8	4	20.05	0-1	0
	1753.5	20385	3	QPSK	8	7	19.54	0-1	0
	1753.5	20385	3	QPSK	15	0	19.91	0-1	0
	1753.5	20385	3	16-QAM	1	0	20.27	0-1	0
	1753.5	20385	3	16-QAM	1	7	20.01	0-1	0
	1753.5	20385	3	16-QAM	1	14	20.19	0-1	0
	1753.5	20385	3	16-QAM	8	0	20.10	0-2	0
	1753.5	20385	3	16-QAM	8	4	20.20	0-2	0
	1753.5	20385	3	16-QAM	8	7	19.51	0-2	0
	1753.5	20385	3	16-QAM	15	0	20.21	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 43 of 90

Table 9-24
Reduced LTE Band 4 (AWS) Conducted Powers – 1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1710.7	19957	1.4	QPSK	1	0	20.22	0	0
	1710.7	19957	1.4	QPSK	1	2	20.07	0	0
	1710.7	19957	1.4	QPSK	1	5	20.27	0	0
	1710.7	19957	1.4	QPSK	3	0	19.77	0	0
	1710.7	19957	1.4	QPSK	3	2	19.84	0	0
	1710.7	19957	1.4	QPSK	3	3	19.55	0	0
	1710.7	19957	1.4	QPSK	6	0	19.98	0-1	0
	1710.7	19957	1.4	16-QAM	1	0	20.42	0-1	0
	1710.7	19957	1.4	16-QAM	1	2	20.42	0-1	0
	1710.7	19957	1.4	16-QAM	1	5	20.04	0-1	0
	1710.7	19957	1.4	16-QAM	3	0	20.25	0-1	0
	1710.7	19957	1.4	16-QAM	3	2	20.41	0-1	0
	1710.7	19957	1.4	16-QAM	3	3	19.74	0-1	0
	1710.7	19957	1.4	16-QAM	6	0	19.57	0-2	0
Mid	1732.5	20175	1.4	QPSK	1	0	20.18	0	0
	1732.5	20175	1.4	QPSK	1	2	20.06	0	0
	1732.5	20175	1.4	QPSK	1	5	20.37	0	0
	1732.5	20175	1.4	QPSK	3	0	19.68	0	0
	1732.5	20175	1.4	QPSK	3	2	19.99	0	0
	1732.5	20175	1.4	QPSK	3	3	19.80	0	0
	1732.5	20175	1.4	QPSK	6	0	20.15	0-1	0
	1732.5	20175	1.4	16-QAM	1	0	20.42	0-1	0
	1732.5	20175	1.4	16-QAM	1	2	19.70	0-1	0
	1732.5	20175	1.4	16-QAM	1	5	20.26	0-1	0
	1732.5	20175	1.4	16-QAM	3	0	20.08	0-1	0
	1732.5	20175	1.4	16-QAM	3	2	19.64	0-1	0
	1732.5	20175	1.4	16-QAM	3	3	20.29	0-1	0
	1732.5	20175	1.4	16-QAM	6	0	19.79	0-2	0
High	1754.3	20393	1.4	QPSK	1	0	20.35	0	0
	1754.3	20393	1.4	QPSK	1	2	20.19	0	0
	1754.3	20393	1.4	QPSK	1	5	19.77	0	0
	1754.3	20393	1.4	QPSK	3	0	19.74	0	0
	1754.3	20393	1.4	QPSK	3	2	20.08	0	0
	1754.3	20393	1.4	QPSK	3	3	19.73	0	0
	1754.3	20393	1.4	QPSK	6	0	19.78	0-1	0
	1754.3	20393	1.4	16-QAM	1	0	20.37	0-1	0
	1754.3	20393	1.4	16-QAM	1	2	19.88	0-1	0
	1754.3	20393	1.4	16-QAM	1	5	20.00	0-1	0
	1754.3	20393	1.4	16-QAM	3	0	20.27	0-1	0
	1754.3	20393	1.4	16-QAM	3	2	19.95	0-1	0
	1754.3	20393	1.4	16-QAM	3	3	19.60	0-1	0
	1754.3	20393	1.4	16-QAM	6	0	20.03	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 44 of 90

9.4.4 LTE Band 2 (PCS)

9.4.4.1 Maximum Output Power

Table 9-25
Maximum LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1860	18700	20	QPSK	1	0	24.34	0	0
	1860	18700	20	QPSK	1	50	23.56	0	0
	1860	18700	20	QPSK	1	99	23.52	0	0
	1860	18700	20	QPSK	50	0	22.92	0-1	1
	1860	18700	20	QPSK	50	25	22.59	0-1	1
	1860	18700	20	QPSK	50	50	22.51	0-1	1
	1860	18700	20	QPSK	100	0	22.80	0-1	1
	1860	18700	20	16QAM	1	0	23.26	0-1	1
	1860	18700	20	16QAM	1	50	22.98	0-1	1
	1860	18700	20	16QAM	1	99	22.91	0-1	1
	1860	18700	20	16QAM	50	0	22.05	0-2	2
	1860	18700	20	16QAM	50	25	21.67	0-2	2
Mid	1860	18700	20	16QAM	50	50	21.63	0-2	2
	1860	18700	20	16QAM	100	0	21.84	0-2	2
	1880.0	18900	20	QPSK	1	0	24.12	0	0
	1880.0	18900	20	QPSK	1	50	23.70	0	0
	1880.0	18900	20	QPSK	1	99	23.52	0	0
	1880.0	18900	20	QPSK	50	0	22.88	0-1	1
	1880.0	18900	20	QPSK	50	25	22.61	0-1	1
	1880.0	18900	20	QPSK	50	50	22.65	0-1	1
	1880.0	18900	20	QPSK	100	0	22.83	0-1	1
	1880.0	18900	20	16QAM	1	0	23.28	0-1	1
	1880.0	18900	20	16QAM	1	50	22.80	0-1	1
	1880.0	18900	20	16QAM	1	99	23.09	0-1	1
High	1880.0	18900	20	16QAM	50	0	21.99	0-2	2
	1880.0	18900	20	16QAM	50	25	21.64	0-2	2
	1880.0	18900	20	16QAM	50	50	21.59	0-2	2
	1880.0	18900	20	16QAM	100	0	21.85	0-2	2
	1900	19100	20	QPSK	1	0	24.01	0	0
	1900	19100	20	QPSK	1	50	23.53	0	0
	1900	19100	20	QPSK	1	99	23.61	0	0
	1900	19100	20	QPSK	50	0	22.90	0-1	1
	1900	19100	20	QPSK	50	25	22.70	0-1	1
	1900	19100	20	QPSK	50	50	22.64	0-1	1
	1900	19100	20	QPSK	100	0	22.73	0-1	1
	1900	19100	20	16QAM	1	0	22.97	0-1	1
	1900	19100	20	16QAM	1	50	22.85	0-1	1
	1900	19100	20	16QAM	1	99	23.04	0-1	1
	1900	19100	20	16QAM	50	0	21.91	0-2	2
	1900	19100	20	16QAM	50	25	21.64	0-2	2
	1900	19100	20	16QAM	50	50	21.56	0-2	2
	1900	19100	20	16QAM	100	0	21.75	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 45 of 90

Table 9-26
Maximum LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1857.5	18675	15	QPSK	1	0	24.08	0	0
	1857.5	18675	15	QPSK	1	36	23.90	0	0
	1857.5	18675	15	QPSK	1	74	23.78	0	0
	1857.5	18675	15	QPSK	36	0	22.98	0-1	1
	1857.5	18675	15	QPSK	36	18	22.62	0-1	1
	1857.5	18675	15	QPSK	36	37	22.63	0-1	1
	1857.5	18675	15	QPSK	75	0	22.74	0-1	1
	1857.5	18675	15	16QAM	1	0	23.48	0-1	1
	1857.5	18675	15	16QAM	1	36	23.22	0-1	1
	1857.5	18675	15	16QAM	1	74	22.98	0-1	1
	1857.5	18675	15	16QAM	36	0	22.09	0-2	2
	1857.5	18675	15	16QAM	36	18	21.76	0-2	2
Mid	1857.5	18675	15	16QAM	36	37	21.59	0-2	2
	1857.5	18675	15	16QAM	75	0	21.75	0-2	2
	1880.0	18900	15	QPSK	1	0	24.21	0	0
	1880.0	18900	15	QPSK	1	36	23.74	0	0
	1880.0	18900	15	QPSK	1	74	23.52	0	0
	1880.0	18900	15	QPSK	36	0	23.18	0-1	1
	1880.0	18900	15	QPSK	36	18	22.51	0-1	1
	1880.0	18900	15	QPSK	36	37	22.60	0-1	1
	1880.0	18900	15	QPSK	75	0	23.09	0-1	1
	1880.0	18900	15	16QAM	1	0	23.20	0-1	1
	1880.0	18900	15	16QAM	1	36	23.04	0-1	1
	1880.0	18900	15	16QAM	1	74	23.02	0-1	1
High	1880.0	18900	15	16QAM	36	0	22.04	0-2	2
	1880.0	18900	15	16QAM	36	18	21.85	0-2	2
	1880.0	18900	15	16QAM	36	37	21.59	0-2	2
	1880.0	18900	15	16QAM	75	0	21.71	0-2	2
	1902.5	19125	15	QPSK	1	0	23.78	0	0
	1902.5	19125	15	QPSK	1	36	23.67	0	0
	1902.5	19125	15	QPSK	1	74	23.74	0	0
	1902.5	19125	15	QPSK	36	0	23.10	0-1	1
	1902.5	19125	15	QPSK	36	18	22.61	0-1	1
	1902.5	19125	15	QPSK	36	37	22.74	0-1	1
	1902.5	19125	15	QPSK	75	0	22.88	0-1	1
	1902.5	19125	15	16QAM	1	0	23.00	0-1	1
	1902.5	19125	15	16QAM	1	36	22.93	0-1	1
	1902.5	19125	15	16QAM	1	74	22.76	0-1	1
	1902.5	19125	15	16QAM	36	0	21.99	0-2	2
	1902.5	19125	15	16QAM	36	18	21.85	0-2	2
	1902.5	19125	15	16QAM	36	37	21.50	0-2	2
	1902.5	19125	15	16QAM	75	0	21.55	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 46 of 90	

Table 9-27
Maximum LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1855	18650	10	QPSK	1	0	23.87	0	0
	1855	18650	10	QPSK	1	25	23.50	0	0
	1855	18650	10	QPSK	1	49	23.77	0	0
	1855	18650	10	QPSK	25	0	22.86	0-1	1
	1855	18650	10	QPSK	25	12	22.71	0-1	1
	1855	18650	10	QPSK	25	25	22.54	0-1	1
	1855	18650	10	QPSK	50	0	22.60	0-1	1
	1855	18650	10	16QAM	1	0	22.95	0-1	1
	1855	18650	10	16QAM	1	25	23.37	0-1	1
	1855	18650	10	16QAM	1	49	22.88	0-1	1
	1855	18650	10	16QAM	25	0	22.34	0-2	2
	1855	18650	10	16QAM	25	12	21.85	0-2	2
	1855	18650	10	16QAM	25	25	21.55	0-2	2
Mid	1880.0	18900	10	QPSK	1	0	23.95	0	0
	1880.0	18900	10	QPSK	1	25	23.55	0	0
	1880.0	18900	10	QPSK	1	49	23.50	0	0
	1880.0	18900	10	QPSK	25	0	22.91	0-1	1
	1880.0	18900	10	QPSK	25	12	22.54	0-1	1
	1880.0	18900	10	QPSK	25	25	22.63	0-1	1
	1880.0	18900	10	QPSK	50	0	22.79	0-1	1
	1880.0	18900	10	16QAM	1	0	22.96	0-1	1
	1880.0	18900	10	16QAM	1	25	23.14	0-1	1
	1880.0	18900	10	16QAM	1	49	22.89	0-1	1
	1880.0	18900	10	16QAM	25	0	21.84	0-2	2
	1880.0	18900	10	16QAM	25	12	21.85	0-2	2
	1880.0	18900	10	16QAM	25	25	21.74	0-2	2
	1880.0	18900	10	16QAM	50	0	21.91	0-2	2
High	1905	19150	10	QPSK	1	0	23.91	0	0
	1905	19150	10	QPSK	1	25	23.74	0	0
	1905	19150	10	QPSK	1	49	23.66	0	0
	1905	19150	10	QPSK	25	0	23.05	0-1	1
	1905	19150	10	QPSK	25	12	22.67	0-1	1
	1905	19150	10	QPSK	25	25	22.77	0-1	1
	1905	19150	10	QPSK	50	0	22.90	0-1	1
	1905	19150	10	16QAM	1	0	23.16	0-1	1
	1905	19150	10	16QAM	1	25	22.84	0-1	1
	1905	19150	10	16QAM	1	49	22.85	0-1	1
	1905	19150	10	16QAM	25	0	21.98	0-2	2
	1905	19150	10	16QAM	25	12	21.82	0-2	2
	1905	19150	10	16QAM	25	25	21.79	0-2	2
	1905	19150	10	16QAM	50	0	21.55	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 47 of 90

Table 9-28
Maximum LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1852.5	18625	5	QPSK	1	0	23.99	0	0
	1852.5	18625	5	QPSK	1	12	23.52	0	0
	1852.5	18625	5	QPSK	1	24	23.78	0	0
	1852.5	18625	5	QPSK	12	0	22.93	0-1	1
	1852.5	18625	5	QPSK	12	6	22.90	0-1	1
	1852.5	18625	5	QPSK	12	13	22.80	0-1	1
	1852.5	18625	5	QPSK	25	0	22.84	0-1	1
	1852.5	18625	5	16-QAM	1	0	23.08	0-1	1
	1852.5	18625	5	16-QAM	1	12	23.32	0-1	1
	1852.5	18625	5	16-QAM	1	24	23.01	0-1	1
	1852.5	18625	5	16-QAM	12	0	22.48	0-2	2
	1852.5	18625	5	16-QAM	12	6	21.72	0-2	2
Mid	1852.5	18625	5	16-QAM	12	13	21.99	0-2	2
	1852.5	18625	5	16-QAM	25	0	21.81	0-2	2
	1880.0	18900	5	QPSK	1	0	23.87	0	0
	1880.0	18900	5	QPSK	1	12	23.60	0	0
	1880.0	18900	5	QPSK	1	24	23.60	0	0
	1880.0	18900	5	QPSK	12	0	22.69	0-1	1
	1880.0	18900	5	QPSK	12	6	22.62	0-1	1
	1880.0	18900	5	QPSK	12	13	22.53	0-1	1
	1880.0	18900	5	QPSK	25	0	22.74	0-1	1
	1880.0	18900	5	16-QAM	1	0	22.91	0-1	1
	1880.0	18900	5	16-QAM	1	12	23.16	0-1	1
	1880.0	18900	5	16-QAM	1	24	23.17	0-1	1
High	1880.0	18900	5	16-QAM	12	0	21.72	0-2	2
	1880.0	18900	5	16-QAM	12	6	22.05	0-2	2
	1880.0	18900	5	16-QAM	12	13	21.90	0-2	2
	1880.0	18900	5	16-QAM	25	0	21.93	0-2	2
	1907.5	19175	5	QPSK	1	0	24.06	0	0
	1907.5	19175	5	QPSK	1	12	23.69	0	0
	1907.5	19175	5	QPSK	1	24	23.93	0	0
	1907.5	19175	5	QPSK	12	0	23.05	0-1	1
	1907.5	19175	5	QPSK	12	6	22.93	0-1	1
	1907.5	19175	5	QPSK	12	13	22.92	0-1	1
	1907.5	19175	5	QPSK	25	0	23.00	0-1	1
	1907.5	19175	5	16-QAM	1	0	23.08	0-1	1
	1907.5	19175	5	16-QAM	1	12	22.57	0-1	1
	1907.5	19175	5	16-QAM	1	24	23.02	0-1	1
	1907.5	19175	5	16-QAM	12	0	21.78	0-2	2
	1907.5	19175	5	16-QAM	12	6	21.89	0-2	2
	1907.5	19175	5	16-QAM	12	13	21.89	0-2	2
	1907.5	19175	5	16-QAM	25	0	21.88	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 48 of 90	

Table 9-29
Maximum LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1851.5	18615	3	QPSK	1	0	24.14	0	0
	1851.5	18615	3	QPSK	1	7	23.62	0	0
	1851.5	18615	3	QPSK	1	14	23.83	0	0
	1851.5	18615	3	QPSK	8	0	22.75	0-1	1
	1851.5	18615	3	QPSK	8	4	22.75	0-1	1
	1851.5	18615	3	QPSK	8	7	22.94	0-1	1
	1851.5	18615	3	QPSK	15	0	22.91	0-1	1
	1851.5	18615	3	16-QAM	1	0	23.00	0-1	1
	1851.5	18615	3	16-QAM	1	7	23.11	0-1	1
	1851.5	18615	3	16-QAM	1	14	22.74	0-1	1
	1851.5	18615	3	16-QAM	8	0	22.33	0-2	2
	1851.5	18615	3	16-QAM	8	4	21.66	0-2	2
Mid	1851.5	18615	3	16-QAM	8	7	21.66	0-2	2
	1851.5	18615	3	16-QAM	15	0	21.63	0-2	2
	1880.0	18900	3	QPSK	1	0	23.57	0	0
	1880.0	18900	3	QPSK	1	7	23.63	0	0
	1880.0	18900	3	QPSK	1	14	23.64	0	0
	1880.0	18900	3	QPSK	8	0	22.51	0-1	1
	1880.0	18900	3	QPSK	8	4	22.63	0-1	1
	1880.0	18900	3	QPSK	8	7	22.56	0-1	1
	1880.0	18900	3	QPSK	15	0	22.99	0-1	1
	1880.0	18900	3	16-QAM	1	0	23.10	0-1	1
	1880.0	18900	3	16-QAM	1	7	23.01	0-1	1
	1880.0	18900	3	16-QAM	1	14	23.34	0-1	1
High	1880.0	18900	3	16-QAM	8	0	21.61	0-2	2
	1880.0	18900	3	16-QAM	8	4	21.89	0-2	2
	1880.0	18900	3	16-QAM	8	7	21.62	0-2	2
	1880.0	18900	3	16-QAM	15	0	21.69	0-2	2
	1908.5	19185	3	QPSK	1	0	24.20	0	0
	1908.5	19185	3	QPSK	1	7	23.83	0	0
	1908.5	19185	3	QPSK	1	14	24.12	0	0
	1908.5	19185	3	QPSK	8	0	22.96	0-1	1
	1908.5	19185	3	QPSK	8	4	22.62	0-1	1
	1908.5	19185	3	QPSK	8	7	23.03	0-1	1
	1908.5	19185	3	QPSK	15	0	23.09	0-1	1
	1908.5	19185	3	16-QAM	1	0	23.22	0-1	1
	1908.5	19185	3	16-QAM	1	7	22.50	0-1	1
	1908.5	19185	3	16-QAM	1	14	22.73	0-1	1
	1908.5	19185	3	16-QAM	8	0	21.77	0-2	2
	1908.5	19185	3	16-QAM	8	4	21.95	0-2	2
	1908.5	19185	3	16-QAM	8	7	22.05	0-2	2
	1908.5	19185	3	16-QAM	15	0	22.00	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 49 of 90	

Table 9-30
Maximum LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1850.7	18607	1.4	QPSK	1	0	24.33	0	0
	1850.7	18607	1.4	QPSK	1	2	24.25	0	0
	1850.7	18607	1.4	QPSK	1	5	23.97	0	0
	1850.7	18607	1.4	QPSK	3	0	23.54	0	0
	1850.7	18607	1.4	QPSK	3	2	23.72	0	0
	1850.7	18607	1.4	QPSK	3	3	23.69	0	0
	1850.7	18607	1.4	QPSK	6	0	22.80	0-1	1
	1850.7	18607	1.4	16-QAM	1	0	22.96	0-1	1
	1850.7	18607	1.4	16-QAM	1	2	23.14	0-1	1
	1850.7	18607	1.4	16-QAM	1	5	22.55	0-1	1
	1850.7	18607	1.4	16-QAM	3	0	23.10	0-1	1
	1850.7	18607	1.4	16-QAM	3	2	22.67	0-1	1
	1850.7	18607	1.4	16-QAM	3	3	22.57	0-1	1
Mid	1850.7	18607	1.4	16-QAM	6	0	21.56	0-2	2
	1880.0	18900	1.4	QPSK	1	0	23.73	0	0
	1880.0	18900	1.4	QPSK	1	2	24.20	0	0
	1880.0	18900	1.4	QPSK	1	5	24.17	0	0
	1880.0	18900	1.4	QPSK	3	0	23.81	0	0
	1880.0	18900	1.4	QPSK	3	2	23.92	0	0
	1880.0	18900	1.4	QPSK	3	3	23.67	0	0
	1880.0	18900	1.4	QPSK	6	0	23.00	0-1	1
	1880.0	18900	1.4	16-QAM	1	0	22.84	0-1	1
	1880.0	18900	1.4	16-QAM	1	2	23.16	0-1	1
	1880.0	18900	1.4	16-QAM	1	5	23.48	0-1	1
	1880.0	18900	1.4	16-QAM	3	0	23.34	0-1	1
	1880.0	18900	1.4	16-QAM	3	2	23.08	0-1	1
	1880.0	18900	1.4	16-QAM	3	3	22.75	0-1	1
High	1880.0	18900	1.4	16-QAM	6	0	21.90	0-2	2
	1909.3	19193	1.4	QPSK	1	0	24.26	0	0
	1909.3	19193	1.4	QPSK	1	2	23.66	0	0
	1909.3	19193	1.4	QPSK	1	5	24.05	0	0
	1909.3	19193	1.4	QPSK	3	0	23.90	0	0
	1909.3	19193	1.4	QPSK	3	2	23.86	0	0
	1909.3	19193	1.4	QPSK	3	3	24.16	0	0
	1909.3	19193	1.4	QPSK	6	0	22.93	0-1	1
	1909.3	19193	1.4	16-QAM	1	0	23.20	0-1	1
	1909.3	19193	1.4	16-QAM	1	2	23.08	0-1	1
	1909.3	19193	1.4	16-QAM	1	5	22.98	0-1	1
	1909.3	19193	1.4	16-QAM	3	0	23.10	0-1	1
	1909.3	19193	1.4	16-QAM	3	2	23.04	0-1	1
	1909.3	19193	1.4	16-QAM	3	3	22.87	0-1	1
	1909.3	19193	1.4	16-QAM	6	0	22.05	0-2	2

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 50 of 90

9.4.4.2 Reduced Output Power - Representing Hotspot Mode Active

Table 9-31
Reduced LTE Band 2 (PCS) Conducted Powers -20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1860	18700	20	QPSK	1	0	21.50	0	0
	1860	18700	20	QPSK	1	50	20.53	0	0
	1860	18700	20	QPSK	1	99	20.51	0	0
	1860	18700	20	QPSK	50	0	20.81	0-1	0
	1860	18700	20	QPSK	50	25	20.51	0-1	0
	1860	18700	20	QPSK	50	50	20.53	0-1	0
	1860	18700	20	QPSK	100	0	20.60	0-1	0
	1860	18700	20	16QAM	1	0	21.50	0-1	0
	1860	18700	20	16QAM	1	50	20.59	0-1	0
	1860	18700	20	16QAM	1	99	20.54	0-1	0
	1860	18700	20	16QAM	50	0	20.75	0-2	0
	1860	18700	20	16QAM	50	25	20.53	0-2	0
Mid	1880.0	18900	20	QPSK	1	0	21.28	0	0
	1880.0	18900	20	QPSK	1	50	20.50	0	0
	1880.0	18900	20	QPSK	1	99	20.58	0	0
	1880.0	18900	20	QPSK	50	0	20.75	0-1	0
	1880.0	18900	20	QPSK	50	25	20.51	0-1	0
	1880.0	18900	20	QPSK	50	50	20.50	0-1	0
	1880.0	18900	20	QPSK	100	0	20.53	0-1	0
	1880.0	18900	20	16QAM	1	0	21.36	0-1	0
	1880.0	18900	20	16QAM	1	50	20.58	0-1	0
	1880.0	18900	20	16QAM	1	99	20.59	0-1	0
	1880.0	18900	20	16QAM	50	0	20.73	0-2	0
	1880.0	18900	20	16QAM	50	25	20.52	0-2	0
High	1900	19100	20	QPSK	1	0	21.10	0	0
	1900	19100	20	QPSK	1	50	20.52	0	0
	1900	19100	20	QPSK	1	99	20.50	0	0
	1900	19100	20	QPSK	50	0	20.55	0-1	0
	1900	19100	20	QPSK	50	25	20.52	0-1	0
	1900	19100	20	QPSK	50	50	20.51	0-1	0
	1900	19100	20	QPSK	100	0	20.55	0-1	0
	1900	19100	20	16QAM	1	0	21.13	0-1	0
	1900	19100	20	16QAM	1	50	20.51	0-1	0
	1900	19100	20	16QAM	1	99	20.71	0-1	0
	1900	19100	20	16QAM	50	0	20.56	0-2	0
	1900	19100	20	16QAM	50	25	20.51	0-2	0
	1900	19100	20	16QAM	50	50	20.50	0-2	0
	1900	19100	20	16QAM	100	0	20.53	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 51 of 90

Table 9-32
Reduced LTE Band 2 (PCS) Conducted Powers -15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1857.5	18675	15	QPSK	1	0	21.29	0	0
	1857.5	18675	15	QPSK	1	36	20.66	0	0
	1857.5	18675	15	QPSK	1	74	20.94	0	0
	1857.5	18675	15	QPSK	36	0	20.77	0-1	0
	1857.5	18675	15	QPSK	36	18	20.64	0-1	0
	1857.5	18675	15	QPSK	36	37	20.66	0-1	0
	1857.5	18675	15	QPSK	75	0	20.73	0-1	0
	1857.5	18675	15	16QAM	1	0	21.32	0-1	0
	1857.5	18675	15	16QAM	1	36	20.86	0-1	0
	1857.5	18675	15	16QAM	1	74	20.67	0-1	0
	1857.5	18675	15	16QAM	36	0	20.66	0-2	0
	1857.5	18675	15	16QAM	36	18	20.64	0-2	0
	1857.5	18675	15	16QAM	36	37	20.61	0-2	0
Mid	1880.0	18900	15	QPSK	1	0	21.38	0	0
	1880.0	18900	15	QPSK	1	36	20.63	0	0
	1880.0	18900	15	QPSK	1	74	20.64	0	0
	1880.0	18900	15	QPSK	36	0	20.90	0-1	0
	1880.0	18900	15	QPSK	36	18	20.76	0-1	0
	1880.0	18900	15	QPSK	36	37	20.81	0-1	0
	1880.0	18900	15	QPSK	75	0	20.68	0-1	0
	1880.0	18900	15	16QAM	1	0	20.64	0-1	0
	1880.0	18900	15	16QAM	1	36	20.73	0-1	0
	1880.0	18900	15	16QAM	1	74	20.60	0-1	0
	1880.0	18900	15	16QAM	36	0	20.72	0-2	0
	1880.0	18900	15	16QAM	36	18	20.97	0-2	0
	1880.0	18900	15	16QAM	36	37	20.64	0-2	0
	1880.0	18900	15	16QAM	75	0	20.53	0-2	0
High	1902.5	19125	15	QPSK	1	0	21.48	0	0
	1902.5	19125	15	QPSK	1	36	20.60	0	0
	1902.5	19125	15	QPSK	1	74	20.54	0	0
	1902.5	19125	15	QPSK	36	0	20.94	0-1	0
	1902.5	19125	15	QPSK	36	18	20.73	0-1	0
	1902.5	19125	15	QPSK	36	37	20.71	0-1	0
	1902.5	19125	15	QPSK	75	0	20.87	0-1	0
	1902.5	19125	15	16QAM	1	0	21.19	0-1	0
	1902.5	19125	15	16QAM	1	36	20.87	0-1	0
	1902.5	19125	15	16QAM	1	74	20.94	0-1	0
	1902.5	19125	15	16QAM	36	0	20.54	0-2	0
	1902.5	19125	15	16QAM	36	18	20.62	0-2	0
	1902.5	19125	15	16QAM	36	37	20.66	0-2	0
	1902.5	19125	15	16QAM	75	0	20.78	0-2	0

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
Page 52 of 90		

Table 9-33
Reduced LTE Band 2 (PCS) Conducted Powers -10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1855	18650	10	QPSK	1	0	21.43	0	0
	1855	18650	10	QPSK	1	25	20.66	0	0
	1855	18650	10	QPSK	1	49	20.64	0	0
	1855	18650	10	QPSK	25	0	20.91	0-1	0
	1855	18650	10	QPSK	25	12	20.52	0-1	0
	1855	18650	10	QPSK	25	25	20.55	0-1	0
	1855	18650	10	QPSK	50	0	20.73	0-1	0
	1855	18650	10	16QAM	1	0	20.66	0-1	0
	1855	18650	10	16QAM	1	25	20.82	0-1	0
	1855	18650	10	16QAM	1	49	20.61	0-1	0
	1855	18650	10	16QAM	25	0	20.64	0-2	0
	1855	18650	10	16QAM	25	12	20.67	0-2	0
Mid	1880.0	18900	10	QPSK	1	0	21.34	0	0
	1880.0	18900	10	QPSK	1	25	21.00	0	0
	1880.0	18900	10	QPSK	1	49	20.93	0	0
	1880.0	18900	10	QPSK	25	0	20.94	0-1	0
	1880.0	18900	10	QPSK	25	12	20.58	0-1	0
	1880.0	18900	10	QPSK	25	25	20.69	0-1	0
	1880.0	18900	10	QPSK	50	0	20.67	0-1	0
	1880.0	18900	10	16QAM	1	0	21.18	0-1	0
	1880.0	18900	10	16QAM	1	25	20.60	0-1	0
	1880.0	18900	10	16QAM	1	49	20.70	0-1	0
	1880.0	18900	10	16QAM	25	0	20.63	0-2	0
	1880.0	18900	10	16QAM	25	12	20.58	0-2	0
High	1905	19150	10	QPSK	1	0	21.37	0	0
	1905	19150	10	QPSK	1	25	20.98	0	0
	1905	19150	10	QPSK	1	49	20.61	0	0
	1905	19150	10	QPSK	25	0	20.89	0-1	0
	1905	19150	10	QPSK	25	12	20.61	0-1	0
	1905	19150	10	QPSK	25	25	20.52	0-1	0
	1905	19150	10	QPSK	50	0	20.98	0-1	0
	1905	19150	10	16QAM	1	0	20.74	0-1	0
	1905	19150	10	16QAM	1	25	20.78	0-1	0
	1905	19150	10	16QAM	1	49	20.86	0-1	0
	1905	19150	10	16QAM	25	0	20.61	0-2	0
	1905	19150	10	16QAM	25	12	20.74	0-2	0
	1905	19150	10	16QAM	25	25	20.64	0-2	0
	1905	19150	10	16QAM	50	0	20.62	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 53 of 90

Table 9-34
Reduced LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1852.5	18625	5	QPSK	1	0	21.42	0	0
	1852.5	18625	5	QPSK	1	12	20.64	0	0
	1852.5	18625	5	QPSK	1	24	20.54	0	0
	1852.5	18625	5	QPSK	12	0	20.78	0-1	0
	1852.5	18625	5	QPSK	12	6	20.58	0-1	0
	1852.5	18625	5	QPSK	12	13	20.69	0-1	0
	1852.5	18625	5	QPSK	25	0	20.80	0-1	0
	1852.5	18625	5	16-QAM	1	0	20.52	0-1	0
	1852.5	18625	5	16-QAM	1	12	20.96	0-1	0
	1852.5	18625	5	16-QAM	1	24	20.79	0-1	0
	1852.5	18625	5	16-QAM	12	0	20.87	0-2	0
	1852.5	18625	5	16-QAM	12	6	20.64	0-2	0
	1852.5	18625	5	16-QAM	12	13	20.51	0-2	0
	1852.5	18625	5	16-QAM	25	0	20.66	0-2	0
Mid	1880.0	18900	5	QPSK	1	0	21.23	0	0
	1880.0	18900	5	QPSK	1	12	20.51	0	0
	1880.0	18900	5	QPSK	1	24	20.68	0	0
	1880.0	18900	5	QPSK	12	0	20.86	0-1	0
	1880.0	18900	5	QPSK	12	6	20.60	0-1	0
	1880.0	18900	5	QPSK	12	13	20.86	0-1	0
	1880.0	18900	5	QPSK	25	0	20.81	0-1	0
	1880.0	18900	5	16-QAM	1	0	21.30	0-1	0
	1880.0	18900	5	16-QAM	1	12	20.73	0-1	0
	1880.0	18900	5	16-QAM	1	24	20.59	0-1	0
	1880.0	18900	5	16-QAM	12	0	20.52	0-2	0
	1880.0	18900	5	16-QAM	12	6	20.68	0-2	0
	1880.0	18900	5	16-QAM	12	13	20.78	0-2	0
	1880.0	18900	5	16-QAM	25	0	20.68	0-2	0
High	1907.5	19175	5	QPSK	1	0	21.40	0	0
	1907.5	19175	5	QPSK	1	12	21.03	0	0
	1907.5	19175	5	QPSK	1	24	20.84	0	0
	1907.5	19175	5	QPSK	12	0	20.73	0-1	0
	1907.5	19175	5	QPSK	12	6	20.65	0-1	0
	1907.5	19175	5	QPSK	12	13	20.54	0-1	0
	1907.5	19175	5	QPSK	25	0	20.83	0-1	0
	1907.5	19175	5	16-QAM	1	0	20.59	0-1	0
	1907.5	19175	5	16-QAM	1	12	20.76	0-1	0
	1907.5	19175	5	16-QAM	1	24	20.96	0-1	0
	1907.5	19175	5	16-QAM	12	0	20.95	0-2	0
	1907.5	19175	5	16-QAM	12	6	20.87	0-2	0
	1907.5	19175	5	16-QAM	12	13	20.62	0-2	0
	1907.5	19175	5	16-QAM	25	0	20.77	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 54 of 90	

Table 9-35
Reduced LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1851.5	18615	3	QPSK	1	0	21.20	0	0
	1851.5	18615	3	QPSK	1	7	20.85	0	0
	1851.5	18615	3	QPSK	1	14	20.81	0	0
	1851.5	18615	3	QPSK	8	0	20.55	0-1	0
	1851.5	18615	3	QPSK	8	4	20.63	0-1	0
	1851.5	18615	3	QPSK	8	7	20.80	0-1	0
	1851.5	18615	3	QPSK	15	0	20.78	0-1	0
	1851.5	18615	3	16-QAM	1	0	20.64	0-1	0
	1851.5	18615	3	16-QAM	1	7	20.61	0-1	0
	1851.5	18615	3	16-QAM	1	14	21.00	0-1	0
	1851.5	18615	3	16-QAM	8	0	20.64	0-2	0
	1851.5	18615	3	16-QAM	8	4	20.63	0-2	0
	1851.5	18615	3	16-QAM	8	7	20.66	0-2	0
	1851.5	18615	3	16-QAM	15	0	20.54	0-2	0
Mid	1880.0	18900	3	QPSK	1	0	20.64	0	0
	1880.0	18900	3	QPSK	1	7	20.62	0	0
	1880.0	18900	3	QPSK	1	14	20.79	0	0
	1880.0	18900	3	QPSK	8	0	21.07	0-1	0
	1880.0	18900	3	QPSK	8	4	20.57	0-1	0
	1880.0	18900	3	QPSK	8	7	21.15	0-1	0
	1880.0	18900	3	QPSK	15	0	20.68	0-1	0
	1880.0	18900	3	16-QAM	1	0	21.04	0-1	0
	1880.0	18900	3	16-QAM	1	7	20.77	0-1	0
	1880.0	18900	3	16-QAM	1	14	20.72	0-1	0
	1880.0	18900	3	16-QAM	8	0	20.82	0-2	0
	1880.0	18900	3	16-QAM	8	4	20.55	0-2	0
	1880.0	18900	3	16-QAM	8	7	20.67	0-2	0
	1880.0	18900	3	16-QAM	15	0	20.84	0-2	0
High	1908.5	19185	3	QPSK	1	0	21.39	0	0
	1908.5	19185	3	QPSK	1	7	20.51	0	0
	1908.5	19185	3	QPSK	1	14	20.68	0	0
	1908.5	19185	3	QPSK	8	0	20.69	0-1	0
	1908.5	19185	3	QPSK	8	4	20.54	0-1	0
	1908.5	19185	3	QPSK	8	7	20.60	0-1	0
	1908.5	19185	3	QPSK	15	0	20.53	0-1	0
	1908.5	19185	3	16-QAM	1	0	20.64	0-1	0
	1908.5	19185	3	16-QAM	1	7	20.52	0-1	0
	1908.5	19185	3	16-QAM	1	14	20.98	0-1	0
	1908.5	19185	3	16-QAM	8	0	20.64	0-2	0
	1908.5	19185	3	16-QAM	8	4	20.52	0-2	0
	1908.5	19185	3	16-QAM	8	7	20.61	0-2	0
	1908.5	19185	3	16-QAM	15	0	20.59	0-2	0

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
Page 55 of 90		

Table 9-36
Reduced LTE Band 2 (PCS) Conducted Powers – 1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1850.7	18607	1.4	QPSK	1	0	21.16	0	0
	1850.7	18607	1.4	QPSK	1	2	20.75	0	0
	1850.7	18607	1.4	QPSK	1	5	20.81	0	0
	1850.7	18607	1.4	QPSK	3	0	20.91	0	0
	1850.7	18607	1.4	QPSK	3	2	20.80	0	0
	1850.7	18607	1.4	QPSK	3	3	20.70	0	0
	1850.7	18607	1.4	QPSK	6	0	20.75	0-1	0
	1850.7	18607	1.4	16-QAM	1	0	20.64	0-1	0
	1850.7	18607	1.4	16-QAM	1	2	20.70	0-1	0
	1850.7	18607	1.4	16-QAM	1	5	20.87	0-1	0
	1850.7	18607	1.4	16-QAM	3	0	20.50	0-1	0
	1850.7	18607	1.4	16-QAM	3	2	21.00	0-1	0
	1850.7	18607	1.4	16-QAM	3	3	20.98	0-1	0
Mid	1880.0	18900	1.4	QPSK	1	0	21.42	0	0
	1880.0	18900	1.4	QPSK	1	2	20.73	0	0
	1880.0	18900	1.4	QPSK	1	5	20.64	0	0
	1880.0	18900	1.4	QPSK	3	0	20.91	0	0
	1880.0	18900	1.4	QPSK	3	2	20.60	0	0
	1880.0	18900	1.4	QPSK	3	3	21.01	0	0
	1880.0	18900	1.4	QPSK	6	0	20.60	0-1	0
	1880.0	18900	1.4	16-QAM	1	0	20.74	0-1	0
	1880.0	18900	1.4	16-QAM	1	2	20.68	0-1	0
	1880.0	18900	1.4	16-QAM	1	5	20.54	0-1	0
	1880.0	18900	1.4	16-QAM	3	0	20.70	0-1	0
	1880.0	18900	1.4	16-QAM	3	2	20.69	0-1	0
	1880.0	18900	1.4	16-QAM	3	3	20.52	0-1	0
	1880.0	18900	1.4	16-QAM	6	0	20.94	0-2	0
High	1909.3	19193	1.4	QPSK	1	0	21.00	0	0
	1909.3	19193	1.4	QPSK	1	2	21.22	0	0
	1909.3	19193	1.4	QPSK	1	5	21.14	0	0
	1909.3	19193	1.4	QPSK	3	0	20.54	0	0
	1909.3	19193	1.4	QPSK	3	2	20.50	0	0
	1909.3	19193	1.4	QPSK	3	3	20.51	0	0
	1909.3	19193	1.4	QPSK	6	0	20.96	0-1	0
	1909.3	19193	1.4	16-QAM	1	0	20.81	0-1	0
	1909.3	19193	1.4	16-QAM	1	2	20.61	0-1	0
	1909.3	19193	1.4	16-QAM	1	5	20.70	0-1	0
	1909.3	19193	1.4	16-QAM	3	0	20.67	0-1	0
	1909.3	19193	1.4	16-QAM	3	2	20.85	0-1	0
	1909.3	19193	1.4	16-QAM	3	3	20.55	0-1	0
	1909.3	19193	1.4	16-QAM	6	0	20.51	0-2	0

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 56 of 90

9.4.5

LTE Carrier Aggregation Conducted Powers

Table 9-37

**LTE Carrier Aggregation Conducted Powers - Band 13 (PCC) 10MHz BW + Band 4 (SCC) 20MHz BW
Maximum Output Power**

Band 13 (PCC) 10 MHz BW + Band 4 (SCC) 20 MHz BW				
782 MHz / ch.23230 + 2132.5 MHz / ch. 2175	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B13 Rel. 8 Tx.Power (dBm)
	1	25	23.64	23.48

Table 9-38

**LTE Carrier Aggregation Conducted Powers - Band 13 (PCC) 10MHz BW + Band 2 (SCC) 20MHz BW
Maximum Output Power**

Band 13 (PCC) 10 MHz BW + Band 2 (SCC) 20 MHz BW				
782 MHz / ch.23230 + 1960.0 MHz / ch. 900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B13 Rel. 8 Tx.Power (dBm)
	1	25	23.68	23.48

Table 9-39

**Maximum LTE Carrier Aggregation Conducted Powers - Band 4 (PCC) 20MHz BW + Band 13 (SCC) 10MHz BW
Maximum Output Power**

Band 4 (PCC) 20 MHz BW + Band 13 (SCC) 10 MHz BW				
1732.5 MHz / ch.20175 + 751 MHz / ch. 5230	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	0	23.95	24.40

Table 9-40

**Reduced LTE Carrier Aggregation Conducted Powers - Band 4 (PCC) 20MHz BW + Band 13 (SCC) 10MHz BW
Reduced Output Power - Representing Hotspot Mode Active**

Band 4 (PCC) 20 MHz BW + Band 13 (SCC) 10 MHz BW				
1732.5 MHz / ch.20175 + 751 MHz / ch. 5230	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	0	20.40	20.43

Table 9-41

**Maximum LTE Carrier Aggregation Conducted Powers - Band 4 (PCC) 20MHz BW + Band 4 (SCC) 20MHz BW
Maximum Output Power**

Band 4 (PCC) 20 MHz BW + Band 4 (SCC) 20 MHz BW				
1720 MHz / ch.20050 + 2145 MHz / ch. 2300	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	0	24.16	24.40

Table 9-42

**Reduced LTE Carrier Aggregation Conducted Powers - Band 4 (PCC) 20MHz BW + Band 4 (SCC) 20MHz BW
Reduced Output Power – Representing Hotspot Mode Active**

Band 4 (PCC) 20 MHz BW + Band 4 (SCC) 20 MHz BW				
1720 MHz / ch.20050 + 2145 MHz / ch. 2300	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	0	20.39	20.43

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 57 of 90

Table 9-43

**Maximum LTE Carrier Aggregation Conducted Powers - Band 4 (PCC) 20MHz BW + Band 2 (SCC) 20MHz BW
Maximum Output Power**

Band 4 (PCC) 20 MHz BW + Band 2 (SCC) 20 MHz BW				
1732.5 MHz / ch.20175 + 1960.0 MHz / ch. 900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	0	24.10	24.40

Table 9-44

**Reduced LTE Carrier Aggregation Conducted Powers - Band 4 (PCC) 20MHz BW + Band 2 (SCC) 20MHz BW
Reduced Output Power - Representing Hotspot Mode Active**

Band 4 (PCC) 20 MHz BW + Band 2 (SCC) 20 MHz BW				
1732.5 MHz / ch.20175 + 1960.0 MHz / ch. 900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	0	20.37	20.43

Table 9-45

**Maximum LTE Carrier Aggregation Conducted Powers - Band 2 (PCC) 20MHz BW + Band 13 (SCC) 10MHz BW
Maximum Output Power**

Band 2 (PCC) 20 MHz BW + Band 13 (SCC) 10 MHz BW				
1860 MHz / ch.18700 + 751 MHz / ch. 5230	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	0	23.90	24.34

Table 9-46

**Reduced LTE Carrier Aggregation Conducted Powers - Band 2 (PCC) 20MHz BW + Band 13 (SCC) 10MHz BW
Reduced Output Power - Representing Hotspot Mode Active**

Band 2 (PCC) 20 MHz BW + Band 13 (SCC) 10 MHz BW				
1860 MHz / ch.18700 + 751 MHz / ch. 5230	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	0	21.47	21.50

Table 9-47

**Maximum LTE Carrier Aggregation Conducted Powers - Band 2 (PCC) 20MHz BW + Band 4 (SCC) 20MHz BW
Maximum Output Power**

Band 2 (PCC) 20 MHz BW + Band 4 (SCC) 20 MHz BW				
1860 MHz / ch.18700 + 2132.5 MHz / ch. 2175	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	0	23.94	24.34

Table 9-48

**Reduced LTE Carrier Aggregation Conducted Powers - Band 2 (PCC) 20MHz BW + Band 4 (SCC) 20MHz BW
Reduced Output Power - Representing Hotspot Mode Active**

Band 2 (PCC) 20 MHz BW + Band 4 (SCC) 20 MHz BW				
1860 MHz / ch.18700 + 2132.5 MHz / ch. 2175	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	0	21.48	21.50

Table 9-49

**Maximum LTE Carrier Aggregation Conducted Powers - Band 2 (PCC) 20MHz BW + Band 2 (SCC) 20MHz BW
Maximum Output Power**

Band 2 (PCC) 20 MHz BW + Band 2 (SCC) 20 MHz BW				
1860 MHz / ch.18700 + 1980 MHz / ch. 1100	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	0	24.10	24.34

FCC ID: A3LSMG925V			SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset			Page 58 of 90

Table 9-50
Reduced LTE Carrier Aggregation Conducted Powers - Band 2 (PCC) 20MHz BW + Band 2 (SCC) 20MHz BW
Reduced Output Power - Representing Hotspot Mode Active

Band 2 (PCC) 20 MHz BW + Band 2 (SCC) 20 MHz BW				
1860 MHz / ch.18700 +1980 MHz / ch. 1100	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	0	21.11	21.50

Notes:

1. The device does not support all Rel. 10 Carrier Aggregation features due to modem chipset limitation.
2. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. Power measurements were performed with two DL carriers for the Release 8 configuration that had the highest output power (across all bandwidths, channels and RB Configurations) for each band
3. This device supports intra band and inter-band CA with 2 carriers (B13+B4, B13+B2, B4+B13, B4+B4, B4+B2, B2+B13, B2+B4, B2+B2) with a maximum of 10 MHz of spectrum for LTE Band 13 and a maximum of 20 MHz of spectrum for LTE Band 4/2.
4. All control and acknowledge data is sent on uplink channels that operate identical to release 8 specifications.




Figure 9-4
Power Measurement Setup

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 59 of 90	

9.5 WLAN Conducted Powers

9.5.1 Maximum Conducted Powers

Table 9-51
2.4 GHz Average RF Power – Antenna 1

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11b
2412	1	17.31
2437	6	17.07
2462	11	16.60

Table 9-52
2.4 GHz Average RF Power – Antenna 2

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11b
2412	1	17.16
2437	6	17.37
2462	11	17.15

Table 9-53
5 GHz (20 MHz Bandwidth) Average RF Power – Antenna 1

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]
		IEEE Transmission Mode
		802.11a
5180	36	14.01
5200	40	13.96
5220	44	13.95
5240	48	13.94
5260	52	14.15
5280	56	14.25
5300	60	14.08
5320	64	14.21
5500	100	13.81
5540	108	13.52
5580	116	13.94
5660	132	14.09
5745	149	14.45
5825	165	14.24

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 60 of 90

Table 9-54
5 GHz (20 MHz Bandwidth) Average RF Power – Antenna 2

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]
		IEEE Transmission Mode
		802.11a
5180	36	14.31
5200	40	14.27
5220	44	14.31
5240	48	14.25
5260	52	14.01
5280	56	13.97
5300	60	13.98
5320	64	13.92
5500	100	14.45
5540	108	13.75
5580	116	14.17
5660	132	14.01
5745	149	14.43
5825	165	14.38

9.5.2 Reduced Conducted Powers – Held-to-Ear

Table 9-55
2.4 GHz Average RF Power – Antenna 1

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11b
2412	1	11.74
2437	6	11.80
2462	11	12.17

Table 9-56
2.4 GHz Average RF Power – Antenna 2

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11b
2412	1	11.75
2437	6	11.60
2462	11	11.99

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 61 of 90	

Table 9-57
5 GHz (80 MHz Bandwidth) Average RF Power – Antenna 1

5GHz (80MHz) Conducted Power		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	6.52
5290	58	6.55
5530	106	6.51
5690	138	6.45
5775	155	6.66

Table 9-58
5 GHz (80 MHz Bandwidth) Average RF Power – Antenna 2

5GHz (80MHz) Conducted Power		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	7.35
5290	58	7.27
5530	106	7.30
5690	138	5.83
5775	155	6.51

Justification for test configurations for WLAN per KDB Publication 248227 D01DR02-41929:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-5
Power Measurement Setup for Bandwidths < 50 MHz




Figure 9-6
Power Measurement Setup for Bandwidths > 50 MHz

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
Page 62 of 90		

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	%dev σ	%dev ϵ
01/22/2015	750H	19.5	725	0.881	41.203	0.891	42.071	-1.12%	-2.06%
			740	0.895	41.012	0.893	41.994	0.22%	-2.34%
			755	0.911	40.814	0.894	41.916	1.90%	-2.63%
			770	0.925	40.579	0.895	41.838	3.35%	-3.01%
			785	0.939	40.365	0.896	41.760	4.80%	-3.34%
01/19/2015	835H	22.0	820	0.917	43.652	0.899	41.578	2.00%	4.99%
			835	0.933	43.439	0.900	41.500	3.67%	4.67%
			850	0.944	43.224	0.916	41.500	3.06%	4.15%
01/22/2015	1750H	22.0	1710	1.305	38.634	1.348	40.142	-3.19%	-3.76%
			1750	1.344	38.466	1.371	40.079	-1.97%	-4.02%
			1790	1.385	38.286	1.394	40.016	-0.65%	-4.32%
01/19/2015	1900H	22.3	1850	1.363	39.524	1.400	40.000	-2.64%	-1.19%
			1880	1.390	39.392	1.400	40.000	-0.71%	-1.52%
			1910	1.419	39.232	1.400	40.000	1.36%	-1.92%
01/23/2015	2450H	22.6	2401	1.737	38.727	1.756	39.287	-1.08%	-1.43%
			2450	1.794	38.552	1.800	39.200	-0.33%	-1.65%
			2499	1.842	38.370	1.853	39.138	-0.59%	-1.96%
01/23/2015	5200H-5800H	20.1	5280	4.530	35.583	4.737	35.894	-4.37%	-0.87%
			5300	4.549	35.571	4.758	35.871	-4.39%	-0.84%
			5500	4.748	35.287	4.963	35.643	-4.33%	-1.00%
			5520	4.772	35.275	4.983	35.620	-4.23%	-0.97%
			5540	4.785	35.258	5.004	35.597	-4.38%	-0.95%
			5765	5.026	34.989	5.234	35.340	-3.97%	-0.99%
			5785	5.039	34.914	5.255	35.317	-4.11%	-1.14%
01/22/2015	750B	24.3	5800	5.054	34.890	5.270	35.300	-4.10%	-1.16%
			725	0.940	53.555	0.961	55.629	-2.19%	-3.73%
			740	0.955	53.372	0.963	55.570	-0.83%	-3.96%
			755	0.968	53.254	0.964	55.512	0.41%	-4.07%
			770	0.983	53.100	0.965	55.453	1.87%	-4.24%
01/22/2015	835B	22.4	785	0.998	52.910	0.966	55.395	3.31%	-4.49%
			820	0.998	55.428	0.969	55.258	2.99%	0.31%
			835	1.010	55.292	0.970	55.200	4.12%	0.17%
			850	1.023	55.175	0.988	55.154	3.54%	0.04%
			1710	1.418	51.678	1.463	53.537	-3.08%	-3.47%
01/19/2015	1750B	23.0	1750	1.461	51.563	1.488	53.432	-1.81%	-3.50%
			1790	1.498	51.358	1.514	53.326	-1.06%	-3.69%
			1710	1.418	51.754	1.463	53.537	-3.08%	-3.33%
02/04/2015	1750B	22.0	1750	1.462	51.586	1.488	53.432	-1.75%	-3.45%
			1790	1.498	51.414	1.514	53.326	-1.06%	-3.59%
			1850	1.488	51.809	1.520	53.300	-2.11%	-2.80%
01/22/2015	1900B	23.0	1880	1.522	51.716	1.520	53.300	0.13%	-2.97%
			1910	1.552	51.592	1.520	53.300	2.11%	-3.20%
			1850	1.494	52.412	1.520	53.300	-1.71%	-1.67%
01/29/2015	1900B	22.9	1880	1.527	52.312	1.520	53.300	0.46%	-1.85%
			1910	1.563	52.220	1.520	53.300	2.83%	-2.03%
			1850	1.525	52.464	1.520	53.300	0.33%	-1.57%
02/06/2015	1900B	22.1	1880	1.555	52.357	1.520	53.300	2.30%	-1.77%
			1910	1.591	52.250	1.520	53.300	4.67%	-1.97%
			1850	1.498	51.902	1.520	53.300	-1.45%	-2.62%
02/10/2015	1900B	22.9	1880	1.532	51.814	1.520	53.300	0.79%	-2.79%
			1910	1.564	51.698	1.520	53.300	2.89%	-3.01%
01/22/2015	2450B	23.8	2401	1.858	51.158	1.903	52.765	-2.36%	-3.05%
			2450	1.925	50.991	1.950	52.700	-1.28%	-3.24%
			2499	1.987	50.821	2.019	52.638	-1.58%	-3.45%
01/19/2015	5200B-5800B	22.6	5280	5.500	48.179	5.393	48.906	1.98%	-1.49%
			5300	5.542	48.230	5.416	48.879	2.33%	-1.33%
			5500	5.845	47.908	5.650	48.607	3.45%	-1.44%
			5580	5.899	47.646	5.743	48.499	2.72%	-1.76%
			5600	5.977	47.642	5.766	48.471	3.66%	-1.71%
			5745	6.176	47.389	5.936	48.275	4.04%	-1.84%
			5800	6.183	47.296	6.000	48.200	3.05%	-1.88%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 63 of 90

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-2
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
K	750	HEAD	01/22/2015	24.0	21.2	0.100	1054	3288	0.826	8.330	8.260	-0.84%
D	835	HEAD	01/19/2015	23.1	23.0	0.100	4d133	3263	0.971	9.200	9.710	5.54%
D	1750	HEAD	01/22/2015	23.0	22.9	0.100	1008	3263	3.450	36.900	34.500	-6.50%
G	1900	HEAD	01/19/2015	24.4	22.5	0.100	5d149	3258	4.150	40.200	41.500	3.23%
G	2450	HEAD	01/23/2015	21.3	22.2	0.100	719	3258	4.990	52.100	49.900	-4.22%
H	5300	HEAD	01/23/2015	23.4	21.5	0.100	1120	3920	7.740	83.400	77.400	-7.19%
H	5500	HEAD	01/23/2015	23.5	21.6	0.100	1120	3920	7.880	84.900	78.800	-7.18%
H	5800	HEAD	01/23/2015	23.5	21.6	0.100	1120	3920	7.800	79.100	78.000	-1.39%
E	750	BODY	01/22/2015	23.2	23.4	0.100	1054	3332	0.855	8.640	8.550	-1.04%
K	835	BODY	01/22/2015	24.2	22.4	0.100	4d133	3288	1.020	9.350	10.200	9.09%
D	1750	BODY	01/19/2015	23.0	23.0	0.100	1008	3263	3.690	37.600	36.900	-1.86%
G	1750	BODY	02/04/2015	23.9	22.0	0.100	1008	3213	3.750	37.600	37.500	-0.27%
G	1900	BODY	01/22/2015	23.9	23.0	0.100	5d149	3258	4.120	40.400	41.200	1.98%
G	1900	BODY	01/29/2015	24.0	22.9	0.100	5d141	3258	4.080	40.600	40.800	0.49%
E	1900	BODY	02/06/2015	23.8	22.1	0.100	5d149	3332	4.130	40.400	41.300	2.23%
J	1900	BODY	02/10/2015	23.5	22.9	0.100	5d149	3022	3.920	40.400	39.200	-2.97%
I	2450	BODY	01/22/2015	23.5	23.8	0.100	719	3209	5.200	51.800	52.000	0.39%
H	5300	BODY	01/19/2015	24.1	23.2	0.100	1191	3920	7.950	79.900	79.500	-0.50%
H	5500	BODY	01/19/2015	24.1	23.1	0.100	1191	3920	7.600	83.100	76.000	-8.54%
H	5600	BODY	01/19/2015	24.0	23.0	0.100	1191	3920	7.630	84.100	76.300	-9.27%
H	5800	BODY	01/19/2015	23.9	23.1	0.100	1191	3920	7.090	78.000	70.900	-9.10%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 64 of 90

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	33.28	-0.01	Right	Cheek	234DC	1	1:8.3	0.262	1.052	0.276	
836.60	190	GSM 850	GSM	33.5	33.28	0.05	Right	Tilt	234DC	1	1:8.3	0.174	1.052	0.183	
836.60	190	GSM 850	GSM	33.5	33.28	-0.05	Left	Cheek	234DC	1	1:8.3	0.311	1.052	0.327	A1
836.60	190	GSM 850	GSM	33.5	33.28	0.01	Left	Tilt	234DC	1	1:8.3	0.164	1.052	0.173	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-2
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.5	23.49	0.05	Right	Cheek	234DC	1:1	0.243	1.002	0.243	
836.60	4183	UMTS 850	RMC	23.5	23.49	0.07	Right	Tilt	234DC	1:1	0.164	1.002	0.164	
836.60	4183	UMTS 850	RMC	23.5	23.49	0.05	Left	Cheek	234DC	1:1	0.265	1.002	0.266	A2
836.60	4183	UMTS 850	RMC	23.5	23.49	0.02	Left	Tilt	234DC	1:1	0.146	1.002	0.146	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-3
Cell. CDMA Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	Cell. CDMA	RC3 / SO55	25.0	25.00	0.01	Right	Cheek	234F1	1:1	0.363	1.000	0.363	
836.52	384	Cell. CDMA	RC3 / SO55	25.0	25.00	-0.05	Right	Tilt	234F1	1:1	0.281	1.000	0.281	
836.52	384	Cell. CDMA	RC3 / SO55	25.0	25.00	0.05	Left	Cheek	234F1	1:1	0.402	1.000	0.402	A3
836.52	384	Cell. CDMA	RC3 / SO55	25.0	25.00	0.06	Left	Tilt	234F1	1:1	0.302	1.000	0.302	
836.52	384	Cell. CDMA	EVDO Rev. A	25.0	24.90	0.02	Right	Cheek	234F1	1:1	0.357	1.023	0.365	
836.52	384	Cell. CDMA	EVDO Rev. A	25.0	24.90	0.04	Right	Tilt	234F1	1:1	0.254	1.023	0.260	
836.52	384	Cell. CDMA	EVDO Rev. A	25.0	24.90	0.14	Left	Cheek	234F1	1:1	0.395	1.023	0.404	
836.52	384	Cell. CDMA	EVDO Rev. A	25.0	24.90	-0.01	Left	Tilt	234F1	1:1	0.298	1.023	0.305	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMG925V			SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15		DUT Type: Portable Handset		Page 65 of 90

Table 11-4
GSM 1900 Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.5	30.25	0.06	Right	Cheek	234DC	1	1:8.3	0.076	1.059	0.080	A4
1880.00	661	GSM 1900	GSM	30.5	30.25	0.03	Right	Tilt	234DC	1	1:8.3	0.026	1.059	0.028	
1880.00	661	GSM 1900	GSM	30.5	30.25	-0.03	Left	Cheek	234DC	1	1:8.3	0.055	1.059	0.058	
1880.00	661	GSM 1900	GSM	30.5	30.25	0.05	Left	Tilt	234DC	1	1:8.3	0.017	1.059	0.018	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-5
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	23.5	23.44	-0.20	Right	Cheek	234DC	1:1	0.080	1.014	0.081	A5
1880.00	9400	UMTS 1900	RMC	23.5	23.44	0.20	Right	Tilt	234DC	1:1	0.034	1.014	0.034	
1880.00	9400	UMTS 1900	RMC	23.5	23.44	0.02	Left	Cheek	234DC	1:1	0.065	1.014	0.066	
1880.00	9400	UMTS 1900	RMC	23.5	23.44	0.06	Left	Tilt	234DC	1:1	0.024	1.014	0.024	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-6
PCS CDMA Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1851.25	25	PCS CDMA	RC3 / SO55	25.0	24.58	0.17	Right	Cheek	234F1	1:1	0.139	1.102	0.153	
1851.25	25	PCS CDMA	RC3 / SO55	25.0	24.58	0.11	Right	Tilt	234F1	1:1	0.055	1.102	0.061	
1851.25	25	PCS CDMA	RC3 / SO55	25.0	24.58	0.04	Left	Cheek	234F1	1:1	0.120	1.102	0.132	
1851.25	25	PCS CDMA	RC3 / SO55	25.0	24.58	-0.14	Left	Tilt	234F1	1:1	0.031	1.102	0.034	
1851.25	25	PCS CDMA	EVDO Rev. A	25.0	24.45	-0.14	Right	Cheek	234F1	1:1	0.152	1.135	0.173	A6
1851.25	25	PCS CDMA	EVDO Rev. A	25.0	24.45	-0.02	Right	Tilt	234F1	1:1	0.067	1.135	0.076	
1851.25	25	PCS CDMA	EVDO Rev. A	25.0	24.45	0.10	Left	Cheek	234F1	1:1	0.140	1.135	0.159	
1851.25	25	PCS CDMA	EVDO Rev. A	25.0	24.45	0.01	Left	Tilt	234F1	1:1	0.051	1.135	0.058	
1880.00	600	PCS CDMA	EVDO Rev. A	20.5	20.00	0.03	Right	Cheek	234C8	1:1	0.093	1.122	0.104	
1880.00	600	PCS CDMA	EVDO Rev. A	20.5	20.00	-0.05	Right	Tilt	234C8	1:1	0.030	1.122	0.034	
1880.00	600	PCS CDMA	EVDO Rev. A	20.5	20.00	0.04	Left	Cheek	234C8	1:1	0.082	1.122	0.092	
1880.00	600	PCS CDMA	EVDO Rev. A	20.5	20.00	-0.06	Left	Tilt	234C8	1:1	0.024	1.122	0.027	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 66 of 90

Table 11-7
LTE Band 13 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.02	0	Right	Cheek	QPSK	1	25	08FC4	1:1	0.217	1.127	0.245	A7
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	-0.04	1	Right	Cheek	QPSK	25	25	08FC4	1:1	0.153	1.052	0.161	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.11	0	Right	Tilt	QPSK	1	25	08FC4	1:1	0.108	1.127	0.122	
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	0.06	1	Right	Tilt	QPSK	25	25	08FC4	1:1	0.070	1.052	0.074	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.20	0	Left	Cheek	QPSK	1	25	08FC4	1:1	0.167	1.127	0.188	
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	0.11	1	Left	Cheek	QPSK	25	25	08FC4	1:1	0.127	1.052	0.134	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.18	0	Left	Tilt	QPSK	1	25	08FC4	1:1	0.094	1.127	0.106	
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	-0.01	1	Left	Tilt	QPSK	25	25	08FC4	1:1	0.075	1.052	0.079	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-8
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	-0.10	0	Right	Cheek	QPSK	1	25	234C9	1:1	0.292	1.059	0.309	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.03	1	Right	Cheek	QPSK	25	0	234C9	1:1	0.232	1.059	0.246	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.00	0	Right	Tilt	QPSK	1	25	234C9	1:1	0.188	1.059	0.199	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.00	1	Right	Tilt	QPSK	25	0	234C9	1:1	0.152	1.059	0.161	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.02	0	Left	Cheek	QPSK	1	25	234C9	1:1	0.298	1.059	0.316	A8
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.03	1	Left	Cheek	QPSK	25	0	234C9	1:1	0.235	1.059	0.249	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.05	0	Left	Tilt	QPSK	1	25	234C9	1:1	0.174	1.059	0.184	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.05	1	Left	Tilt	QPSK	25	0	234C9	1:1	0.134	1.059	0.142	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-9
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.40	0.11	0	Right	Cheek	QPSK	1	0	23503	1:1	0.155	1.023	0.159	A9
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	23.21	-0.12	1	Right	Cheek	QPSK	50	25	23503	1:1	0.120	1.069	0.128	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.40	-0.09	0	Right	Tilt	QPSK	1	0	23503	1:1	0.121	1.023	0.124	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	23.21	0.07	1	Right	Tilt	QPSK	50	25	23503	1:1	0.120	1.069	0.128	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.40	-0.15	0	Left	Cheek	QPSK	1	0	23503	1:1	0.150	1.023	0.153	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	23.21	0.00	1	Left	Cheek	QPSK	50	25	23503	1:1	0.115	1.069	0.123	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.40	-0.08	0	Left	Tilt	QPSK	1	0	23503	1:1	0.103	1.023	0.105	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	23.21	0.15	1	Left	Tilt	QPSK	50	25	23503	1:1	0.074	1.069	0.079	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 67 of 90

Table 11-10
LTE Band 2 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.5	24.34	-0.20	0	Right	Cheek	QPSK	1	0	23503	1:1	0.146	1.038	0.152	A10
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	22.92	0.13	1	Right	Cheek	QPSK	50	0	23503	1:1	0.093	1.143	0.106	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.5	24.34	-0.04	0	Right	Tilt	QPSK	1	0	23503	1:1	0.064	1.038	0.066	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	22.92	0.10	1	Right	Tilt	QPSK	50	0	23503	1:1	0.037	1.143	0.042	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.5	24.34	0.11	0	Left	Cheek	QPSK	1	0	23503	1:1	0.143	1.038	0.148	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	22.92	0.05	1	Left	Cheek	QPSK	50	0	23503	1:1	0.086	1.143	0.098	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.5	24.34	0.20	0	Left	Tilt	QPSK	1	0	23503	1:1	0.048	1.038	0.050	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	22.92	0.03	1	Left	Tilt	QPSK	50	0	23503	1:1	0.026	1.143	0.030	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-11
DTS Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g) (W/kg)	Plot #
MHz	Ch.													W/kg					
2462	11	802.11b	DSSS	22	12.5	12.17	0.02	Right	Cheek	1	234B0	1	99.58	0.345	0.250	1.079	1.004	0.271	A11
2462	11	802.11b	DSSS	22	12.5	12.17	-	Right	Tilt	1	234B0	1	99.58	0.215	-	1.079	1.004	-	-
2462	11	802.11b	DSSS	22	12.5	12.17	-	Left	Cheek	1	234B0	1	99.58	0.131	-	1.079	1.004	-	-
2462	11	802.11b	DSSS	22	12.5	12.17	-	Left	Tilt	1	234B0	1	99.58	0.098	-	1.079	1.004	-	-
2462	11	802.11b	DSSS	22	12.5	11.99	0.11	Right	Cheek	2	234B0	1	99.26	0.149	0.130	1.125	1.007	0.147	-
2462	11	802.11b	DSSS	22	12.5	11.99	-	Right	Tilt	2	234B0	1	99.26	0.118	-	1.125	1.007	-	-
2462	11	802.11b	DSSS	22	12.5	11.99	-	Left	Cheek	2	234B0	1	99.26	0.093	-	1.125	1.007	-	-
2462	11	802.11b	DSSS	22	12.5	11.99	-	Left	Tilt	2	234B0	1	99.26	0.062	-	1.125	1.007	-	-
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Head										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										

Table 11-12
NII Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)				
5290	58	802.11ac	OFDM	80	8.5	6.55	0.08	Right	Cheek	1	234B0	29.3	98.18	0.268	0.136	1.567	1.019	0.217	
5290	58	802.11ac	OFDM	80	8.5	6.55	-	Right	Tilt	1	234B0	29.3	98.18	0.138	-	1.567	1.019	-	
5290	58	802.11ac	OFDM	80	8.5	6.55	-	Left	Cheek	1	234B0	29.3	98.18	0.104	-	1.567	1.019	-	
5290	58	802.11ac	OFDM	80	8.5	6.55	-	Left	Tilt	1	234B0	29.3	98.18	0.057	-	1.567	1.019	-	
5290	58	802.11ac	OFDM	80	8.5	7.27	0.07	Right	Cheek	2	234B0	29.3	98.11	0.198	0.089	1.327	1.019	0.120	
5290	58	802.11ac	OFDM	80	8.5	7.27	-	Right	Tilt	2	234B0	29.3	98.11	0.107	-	1.327	1.019	-	
5290	58	802.11ac	OFDM	80	8.5	7.27	-	Left	Cheek	2	234B0	29.3	98.11	0.108	-	1.327	1.019	-	
5290	58	802.11ac	OFDM	80	8.5	7.27	-	Left	Tilt	2	234B0	29.3	98.11	0.063	-	1.327	1.019	-	
5530	106	802.11ac	OFDM	80	8.5	6.51	0.03	Right	Cheek	1	234B0	29.3	98.18	0.275	0.190	1.581	1.019	0.306	A12
5530	106	802.11ac	OFDM	80	8.5	6.51	-	Right	Tilt	1	234B0	29.3	98.18	0.158	-	1.581	1.019	-	
5530	106	802.11ac	OFDM	80	8.5	6.51	-	Left	Cheek	1	234B0	29.3	98.18	0.151	-	1.581	1.019	-	
5530	106	802.11ac	OFDM	80	8.5	6.51	-	Left	Tilt	1	234B0	29.3	98.18	0.118	-	1.581	1.019	-	
5530	106	802.11ac	OFDM	80	8.5	7.30	0.02	Right	Cheek	2	234B0	29.3	98.11	0.160	0.075	1.318	1.019	0.101	
5530	106	802.11ac	OFDM	80	8.5	7.30	-	Right	Tilt	2	234B0	29.3	98.11	0.155	-	1.318	1.019	-	
5530	106	802.11ac	OFDM	80	8.5	7.30	-	Left	Cheek	2	234B0	29.3	98.11	0.096	-	1.318	1.019	-	
5530	106	802.11ac	OFDM	80	8.5	7.30	-	Left	Tilt	2	234B0	29.3	98.11	0.066	-	1.318	1.019	-	
5775	155	802.11ac	OFDM	80	8.5	6.66	0.07	Right	Cheek	1	234B0	29.3	98.18	0.440	0.184	1.528	1.019	0.286	
5775	155	802.11ac	OFDM	80	8.5	6.66	-	Right	Tilt	1	234B0	29.3	98.18	0.287	-	1.528	1.019	-	
5775	155	802.11ac	OFDM	80	8.5	6.66	-	Left	Cheek	1	234B0	29.3	98.18	0.207	-	1.528	1.019	-	
5775	155	802.11ac	OFDM	80	8.5	6.66	-	Left	Tilt	1	234B0	29.3	98.18	0.151	-	1.528	1.019	-	
5775	155	802.11ac	OFDM	80	8.5	6.51	0.04	Right	Cheek	2	234B0	29.3	98.11	0.121	0.105	1.581	1.019	0.169	
5775	155	802.11ac	OFDM	80	8.5	6.51	-	Right	Tilt	2	234B0	29.3	98.11	0.088	-	1.581	1.019	-	
5775	155	802.11ac	OFDM	80	8.5	6.51	-	Left	Cheek	2	234B0	29.3	98.11	0.052	-	1.581	1.019	-	
5775	155	802.11ac	OFDM	80	8.5	6.51	-	Left	Tilt	2	234B0	29.3	98.11	0.044	-	1.581	1.019	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Head										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 68 of 90

11.2 Standalone Body-Worn SAR Data

Table 11-13
GSM/UMTS/CDMA Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	33.28	0.04	10 mm	234DC	1	1:8.3	back	0.467	1.052	0.491	A13
836.60	4183	UMTS 850	RMC	23.5	23.49	0.01	10 mm	234DC	N/A	1:1	back	0.377	1.002	0.378	A15
836.52	384	Cell. CDMA	TDSO / SO32	25.0	25.00	-0.03	10 mm	23503	N/A	1:1	back	0.549	1.000	0.549	A17
1880.00	661	GSM 1900	GSM	30.5	30.25	-0.02	15 mm	234DC	1	1:8.3	back	0.341	1.059	0.361	A19
1880.00	9400	UMTS 1900	RMC	23.5	23.44	-0.05	15 mm	234DC	N/A	1:1	back	0.395	1.014	0.401	A21
1851.25	25	PCS CDMA	TDSO / SO32	25.0	24.66	0.02	15 mm	234F1	N/A	1:1	back	0.419	1.081	0.453	A23
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-14
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.08	0	23503	QPSK	1	25	10 mm	back	1:1	0.286	1.127	0.322	A25
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	0.06	1	23503	QPSK	25	25	10 mm	back	1:1	0.159	1.052	0.167	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.03	0	23503	QPSK	1	25	10 mm	back	1:1	0.161	1.059	0.170	A26
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.02	1	23503	QPSK	25	0	10 mm	back	1:1	0.137	1.059	0.145	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.40	0.01	0	23503	QPSK	1	0	15 mm	back	1:1	0.531	1.023	0.543	A28
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	23.21	-0.04	1	23503	QPSK	50	25	15 mm	back	1:1	0.379	1.069	0.405	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.5	24.34	0.04	0	234DC	QPSK	1	0	15 mm	back	1:1	0.378	1.038	0.392	A30
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	22.92	-0.02	1	234DC	QPSK	50	0	15 mm	back	1:1	0.297	1.143	0.339	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g) averaged over 1 gram									
Uncontrolled Exposure/General Population																			

Table 11-15
DTS Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	17.5	17.31	-0.17	10 mm	1	234B0	1	back	99.58	0.159	0.131	1.045	1.004	0.138	A32
2437	6	802.11b	DSSS	22	17.5	17.37	-0.02	10 mm	2	234B0	1	back	99.26	0.089	0.075	1.030	1.007	0.078	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-16
NII Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)	(Duty Cycle)	(W/kg)		
5280	56	802.11a	OFDM	20	14.5	14.25	0.08	10 mm	1	236B4	6	back	98.75	0.203	0.089	1.059	1.013	0.095	A33
5300	60	802.11a	OFDM	20	14.5	13.98	0.03	10 mm	2	236B4	6	back	98.81	0.155	0.072	1.127	1.012	0.082	
5580	116	802.11a	OFDM	20	14.5	13.94	0.20	10 mm	1	236B4	6	back	98.75	0.147	0.062	1.138	1.013	0.072	
5500	100	802.11a	OFDM	20	14.5	14.45	0.04	10 mm	2	236B4	6	back	98.81	0.159	0.064	1.012	1.012	0.066	
5745	149	802.11a	OFDM	20	14.5	14.45	-0.07	10 mm	1	236B4	6	back	98.75	0.142	0.054	1.012	1.013	0.056	
5745	149	802.11a	OFDM	20	14.5	14.43	0.04	10 mm	2	236B4	6	back	98.81	0.088	0.028	1.016	1.012	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

FCC ID: A3LSMG925V			SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15		DUT Type: Portable Handset		Page 69 of 90	

11.3 Standalone Wireless Router SAR Data

Table 11-17
GPRS/UMTS/CDMA Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	30.0	29.71	-0.19	10 mm	234DC	3	1:2.76	back	0.523	1.069	0.559	A14
836.60	190	GSM 850	GPRS	30.0	29.71	-0.15	10 mm	234DC	3	1:2.76	front	0.446	1.069	0.477	
836.60	190	GSM 850	GPRS	30.0	29.71	0.00	10 mm	234DC	3	1:2.76	bottom	0.101	1.069	0.108	
836.60	190	GSM 850	GPRS	30.0	29.71	0.08	10 mm	234DC	3	1:2.76	right	0.338	1.069	0.361	
836.60	190	GSM 850	GPRS	30.0	29.71	-0.02	10 mm	234DC	3	1:2.76	left	0.491	1.069	0.525	
836.60	4183	UMTS 850	RMC	23.5	23.49	0.01	10 mm	234DC	N/A	1:1	back	0.377	1.002	0.378	
836.60	4183	UMTS 850	RMC	23.5	23.49	0.01	10 mm	234DC	N/A	1:1	front	0.360	1.002	0.361	
836.60	4183	UMTS 850	RMC	23.5	23.49	0.00	10 mm	234DC	N/A	1:1	bottom	0.080	1.002	0.080	
836.60	4183	UMTS 850	RMC	23.5	23.49	-0.02	10 mm	234DC	N/A	1:1	right	0.349	1.002	0.350	
836.60	4183	UMTS 850	RMC	23.5	23.49	-0.02	10 mm	234DC	N/A	1:1	left	0.474	1.002	0.475	A16
836.52	384	Cell. CDMA	EVDO Rev.0	25.0	25.00	0.02	10 mm	23503	N/A	1:1	back	0.521	1.000	0.521	
836.52	384	Cell. CDMA	EVDO Rev.0	25.0	25.00	-0.01	10 mm	23503	N/A	1:1	front	0.515	1.000	0.515	
836.52	384	Cell. CDMA	EVDO Rev.0	25.0	25.00	-0.09	10 mm	23503	N/A	1:1	bottom	0.097	1.000	0.097	
836.52	384	Cell. CDMA	EVDO Rev.0	25.0	25.00	0.03	10 mm	23503	N/A	1:1	right	0.473	1.000	0.473	
836.52	384	Cell. CDMA	EVDO Rev.0	25.0	25.00	0.00	10 mm	23503	N/A	1:1	left	0.619	1.000	0.619	A18
1880.00	661	GSM 1900	GPRS	24.5	23.85	-0.05	10 mm	234C8	4	1:2.076	back	0.324	1.161	0.376	
1880.00	661	GSM 1900	GPRS	24.5	23.85	-0.04	10 mm	234C8	4	1:2.076	front	0.281	1.161	0.326	
1880.00	661	GSM 1900	GPRS	24.5	23.85	0.08	10 mm	234C8	4	1:2.076	bottom	0.467	1.161	0.542	A20
1880.00	661	GSM 1900	GPRS	24.5	23.85	0.06	10 mm	234C8	4	1:2.076	right	0.062	1.161	0.072	
1880.00	661	GSM 1900	GPRS	24.5	23.85	0.06	10 mm	234C8	4	1:2.076	left	0.146	1.161	0.170	
1852.40	9262	UMTS 1900	RMC	21.5	20.94	0.00	10 mm	234C8	N/A	1:1	back	0.350	1.138	0.398	
1852.40	9262	UMTS 1900	RMC	21.5	20.94	-0.01	10 mm	234C8	N/A	1:1	front	0.292	1.138	0.332	
1852.40	9262	UMTS 1900	RMC	21.5	20.94	-0.05	10 mm	234C8	N/A	1:1	bottom	0.569	1.138	0.648	A22
1852.40	9262	UMTS 1900	RMC	21.5	20.94	0.09	10 mm	234C8	N/A	1:1	right	0.025	1.138	0.028	
1852.40	9262	UMTS 1900	RMC	21.5	20.94	0.09	10 mm	234C8	N/A	1:1	left	0.091	1.138	0.104	
1880.00	600	PCS CDMA	EVDO Rev.0	20.5	20.20	0.03	10 mm	234C8	N/A	1:1	back	0.583	1.072	0.625	
1880.00	600	PCS CDMA	EVDO Rev.0	20.5	20.20	-0.01	10 mm	234C8	N/A	1:1	front	0.450	1.072	0.482	
1851.25	25	PCS CDMA	EVDO Rev.0	20.5	20.50	-0.02	10 mm	234C8	N/A	1:1	bottom	0.775	1.000	0.775	
1880.00	600	PCS CDMA	EVDO Rev.0	20.5	20.20	-0.02	10 mm	234C8	N/A	1:1	bottom	0.837	1.072	0.897	
1908.75	1175	PCS CDMA	EVDO Rev.0	20.5	20.23	-0.08	10 mm	234C8	N/A	1:1	bottom	0.899	1.064	0.957	A24
1880.00	600	PCS CDMA	EVDO Rev.0	20.5	20.20	0.15	10 mm	234C8	N/A	1:1	right	0.060	1.072	0.064	
1880.00	600	PCS CDMA	EVDO Rev.0	20.5	20.20	0.07	10 mm	234C8	N/A	1:1	left	0.118	1.072	0.126	
1908.75	1175	PCS CDMA	EVDO Rev.0	20.5	20.23	-0.08	10 mm	234C8	N/A	1:1	bottom	0.894	1.064	0.951	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body								
Spatial Peak							1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population							averaged over 1 gram								

Blue Entry represents Variability measurement.

FCC ID: A3LSMG925V			SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset			Page 70 of 90

Table 11-18
LTE Band 13 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.08	0	23503	QPSK	1	25	10 mm	back	1:1	0.286	1.127	0.322	A25
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	0.06	1	23503	QPSK	25	25	10 mm	back	1:1	0.159	1.052	0.167	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.01	0	23503	QPSK	1	25	10 mm	front	1:1	0.248	1.127	0.279	
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	0.07	1	23503	QPSK	25	25	10 mm	front	1:1	0.142	1.052	0.149	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.01	0	23503	QPSK	1	25	10 mm	bottom	1:1	0.069	1.127	0.078	
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	0.02	1	23503	QPSK	25	25	10 mm	bottom	1:1	0.042	1.052	0.044	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.02	0	23503	QPSK	1	25	10 mm	right	1:1	0.170	1.127	0.192	
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	0.06	1	23503	QPSK	25	25	10 mm	right	1:1	0.095	1.052	0.100	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.03	0	23503	QPSK	1	25	10 mm	left	1:1	0.150	1.127	0.169	
782.00	23230	Mid	LTE Band 13	10	23.0	22.78	0.08	1	23503	QPSK	25	25	10 mm	left	1:1	0.082	1.052	0.086	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-19
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
																(W/kg)		(W/kg)	
MHz	Ch.																		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.03	0	23503	QPSK	1	25	10 mm	back	1:1	0.161	1.059	0.170	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.02	1	23503	QPSK	25	0	10 mm	back	1:1	0.137	1.059	0.145	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.01	0	23503	QPSK	1	25	10 mm	front	1:1	0.148	1.059	0.157	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.03	1	23503	QPSK	25	0	10 mm	front	1:1	0.134	1.059	0.142	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.04	0	23503	QPSK	1	25	10 mm	bottom	1:1	0.083	1.059	0.088	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.04	1	23503	QPSK	25	0	10 mm	bottom	1:1	0.064	1.059	0.068	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.03	0	23503	QPSK	1	25	10 mm	right	1:1	0.318	1.059	0.337	A27
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.13	1	23503	QPSK	25	0	10 mm	right	1:1	0.268	1.059	0.284	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.25	0.11	0	23503	QPSK	1	25	10 mm	left	1:1	0.081	1.059	0.086	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.25	0.00	1	23503	QPSK	25	0	10 mm	left	1:1	0.075	1.059	0.079	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak								Body											
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-20
LTE Band 4 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	20.43	-0.09	0	234EB	QPSK	1	0	10 mm	back	1:1	0.400	1.016	0.406	A29
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	19.97	-0.02	0	234EB	QPSK	50	0	10 mm	back	1:1	0.356	1.130	0.402	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	20.43	0.03	0	234EB	QPSK	1	0	10 mm	front	1:1	0.337	1.016	0.342	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	19.97	-0.02	0	234EB	QPSK	50	0	10 mm	front	1:1	0.296	1.130	0.334	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	20.43	-0.01	0	234EB	QPSK	1	0	10 mm	bottom	1:1	0.533	1.016	0.542	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	19.97	-0.04	0	234EB	QPSK	50	0	10 mm	bottom	1:1	0.445	1.130	0.503	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	20.43	0.11	0	234EB	QPSK	1	0	10 mm	right	1:1	0.035	1.016	0.036	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	19.97	-0.06	0	234EB	QPSK	50	0	10 mm	right	1:1	0.030	1.130	0.034	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	20.43	-0.02	0	234EB	QPSK	1	0	10 mm	left	1:1	0.080	1.016	0.081	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.5	19.97	-0.04	0	234EB	QPSK	50	0	10 mm	left	1:1	0.069	1.130	0.078	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 71 of 90

Table 11-21
LTE Band 2 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	21.50	-0.01	0	234EB	QPSK	1	0	10 mm	back	1:1	0.514	1.000	0.514	A31
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	20.81	0.20	0	234EB	QPSK	50	0	10 mm	back	1:1	0.496	1.172	0.581	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	21.50	-0.15	0	234EB	QPSK	1	0	10 mm	front	1:1	0.535	1.000	0.535	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	20.81	-0.07	0	234EB	QPSK	50	0	10 mm	front	1:1	0.436	1.172	0.511	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	21.50	-0.11	0	234EB	QPSK	1	0	10 mm	bottom	1:1	0.643	1.000	0.643	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	20.81	-0.06	0	234EB	QPSK	50	0	10 mm	bottom	1:1	0.543	1.172	0.636	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	21.50	0.20	0	234EB	QPSK	1	0	10 mm	right	1:1	0.062	1.000	0.062	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	20.81	0.10	0	234EB	QPSK	50	0	10 mm	right	1:1	0.052	1.172	0.061	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	21.50	-0.04	0	234EB	QPSK	1	0	10 mm	left	1:1	0.126	1.000	0.126	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	20.81	0.04	0	234EB	QPSK	50	0	10 mm	left	1:1	0.076	1.172	0.089	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram											
Uncontrolled Exposure/General Population																			

Table 11-22
WLAN Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)		(W/kg)		
2412	1	802.11b	DSSS	22	17.5	17.31	-0.17	10 mm	1	234B0	1	back	99.58	0.159	0.131	1.045	1.004	0.138	A32
2412	1	802.11b	DSSS	22	17.5	17.31	-	10 mm	1	234B0	1	front	99.58	0.137	-	1.045	1.004	-	
2412	1	802.11b	DSSS	22	17.5	17.31	-	10 mm	1	234B0	1	top	99.58	0.073	-	1.045	1.004	-	
2412	1	802.11b	DSSS	22	17.5	17.31	-	10 mm	1	234B0	1	left	99.58	0.086	-	1.045	1.004	-	
2437	6	802.11b	DSSS	22	17.5	17.37	-0.02	10 mm	2	234B0	1	back	99.26	0.089	0.075	1.030	1.007	0.078	
2437	6	802.11b	DSSS	22	17.5	17.37	-	10 mm	2	234B0	1	front	99.26	0.060	-	1.030	1.007	-	
2437	6	802.11b	DSSS	22	17.5	17.37	-	10 mm	2	234B0	1	top	99.26	0.061	-	1.030	1.007	-	
2437	6	802.11b	DSSS	22	17.5	17.37	-	10 mm	2	234B0	1	left	99.26	0.006	-	1.030	1.007	-	
5745	149	802.11a	OFDM	20	14.5	14.45	-	10 mm	1	236B4	6	back	98.75	0.142	-	1.012	1.013	-	
5745	149	802.11a	OFDM	20	14.5	14.45	0.03	10 mm	1	236B4	6	front	98.75	0.320	0.149	1.012	1.013	0.153	A34
5745	149	802.11a	OFDM	20	14.5	14.45	-	10 mm	1	236B4	6	top	98.75	0.158	-	1.012	1.013	-	
5745	149	802.11a	OFDM	20	14.5	14.45	-	10 mm	1	236B4	6	left	98.75	0.082	-	1.012	1.013	-	
5745	149	802.11a	OFDM	20	14.5	14.43	0.04	10 mm	2	236B4	6	back	98.81	0.088	0.028	1.016	1.012	0.028	
5745	149	802.11a	OFDM	20	14.5	14.43	-	10 mm	2	236B4	6	front	98.81	0.060	-	1.016	1.012	-	
5745	149	802.11a	OFDM	20	14.5	14.43	-	10 mm	2	236B4	6	top	98.81	0.068	-	1.016	1.012	-	
5745	149	802.11a	OFDM	20	14.5	14.43	-	10 mm	2	236B4	6	left	98.81	0.004	-	1.016	1.012	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 72 of 90	

11.4 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance. A test separation distance of 10 mm for Body-worn SAR were also used for GSM 850, UMTS 850, Cell CDMA, LTE Band 13/5 and 2.4/5GHz WLAN as it is more conservative.
7. Per FCC KDB Publication 648474 D04v01, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.6 for more details).
10. This device utilizes power reduction for GPRS/EDGE 1900, UMTS Band 2, PCS CDMA/EVDO, and LTE Band 2/4 under portable hotspot conditions for SAR compliance. Therefore, these wireless router configurations were tested at reduced output power levels

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset
		Page 73 of 90

CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO and TDSO / SO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO / SO32 FCH only powers, per FCC KDB Publication 941225 D01v03.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03 procedures for data devices. Since the average output power of Subtype 2 for Rev. A is less than the Rev. 0 power levels, EVDO Rev. A SAR is not required. SAR is not required for 1x RTT for Ev-Do hotspot devices when the maximum average output of each channel is less than 1/4 dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r03. The general test procedures used for testing can be found in Section 8.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per KDB Publication 941225 D05Av01r01, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 74 of 90

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01DR02-41929 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01DR02-41929 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.7.6 for more information.
4. Per KDB Publication 248227 D01DR02-41929, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498. Please see Section 12 for complete analysis.
5. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
6. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
7. Only channels in the U-NII-2C (> 5.65 GHz WIFI) & U-NII-3 aggregate band that support wireless router were considered for hotspot SAR tests.
8. For SAR compliance, this device always uses power reduction when the device is in a held-to-ear RF exposure condition with WIFI data modes. Therefore, WIFI Head SAR was evaluated at reduced power levels.

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 75 of 90

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05r02 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	10.00	15	0.140

Note:

- Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.
- Since the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, MIMO SAR is determined by the sum of 1g single transmission chain SAR values because the summation represents higher output power and yields more conservative result per KDB 248227 D01 DR02-41929.
- The highest Reported SAR for each exposure condition is used for SAR summation purpose.

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 76 of 90

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN – Ant 1 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM/GPRS 850	0.327	0.271	0.598
	UMTS 850	0.266	0.271	0.537
	Cell. CDMA/EVDO	0.404	0.271	0.675
	GSM/GPRS 1900	0.080	0.271	0.351
	UMTS 1900	0.081	0.271	0.352
	PCS CDMA/EVDO	0.153	0.271	0.424
	LTE Band 13	0.245	0.271	0.516
	LTE Band 5 (Cell)	0.316	0.271	0.587
	LTE Band 4 (AWS)	0.159	0.271	0.430
	LTE Band 2 (PCS)	0.152	0.271	0.423

Table 12-3
Simultaneous Transmission Scenario with 2.4 GHz WLAN - Ant 2 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM/GPRS 850	0.327	0.147	0.474
	UMTS 850	0.266	0.147	0.413
	Cell. CDMA/EVDO	0.404	0.147	0.551
	GSM/GPRS 1900	0.080	0.147	0.227
	UMTS 1900	0.081	0.147	0.228
	PCS CDMA/EVDO	0.153	0.147	0.300
	LTE Band 13	0.245	0.147	0.392
	LTE Band 5 (Cell)	0.316	0.147	0.463
	LTE Band 4 (AWS)	0.159	0.147	0.306
	LTE Band 2 (PCS)	0.152	0.147	0.299

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM/GPRS 850	0.327	0.271	0.147	0.745
	UMTS 850	0.266	0.271	0.147	0.684
	Cell. CDMA/EVDO	0.404	0.271	0.147	0.822
	GSM/GPRS 1900	0.080	0.271	0.147	0.498
	UMTS 1900	0.081	0.271	0.147	0.499
	PCS CDMA/EVDO	0.153	0.271	0.147	0.571
	LTE Band 13	0.245	0.271	0.147	0.663
	LTE Band 5 (Cell)	0.316	0.271	0.147	0.734
	LTE Band 4 (AWS)	0.159	0.271	0.147	0.577
	LTE Band 2 (PCS)	0.152	0.271	0.147	0.570

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 77 of 90

Table 12-5
Simultaneous Transmission Scenario with 5 GHz WLAN - Ant 1 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM/GPRS 850	0.327	0.306	0.633
	UMTS 850	0.266	0.306	0.572
	Cell. CDMA/EVDO	0.404	0.306	0.710
	GSM/GPRS 1900	0.080	0.306	0.386
	UMTS 1900	0.081	0.306	0.387
	PCS CDMA/EVDO	0.153	0.306	0.459
	LTE Band 13	0.245	0.306	0.551
	LTE Band 5 (Cell)	0.316	0.306	0.622
	LTE Band 4 (AWS)	0.159	0.306	0.465
	LTE Band 2 (PCS)	0.152	0.306	0.458

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN - Ant 2 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM/GPRS 850	0.327	0.169	0.496
	UMTS 850	0.266	0.169	0.435
	Cell. CDMA/EVDO	0.404	0.169	0.573
	GSM/GPRS 1900	0.080	0.169	0.249
	UMTS 1900	0.081	0.169	0.250
	PCS CDMA/EVDO	0.153	0.169	0.322
	LTE Band 13	0.245	0.169	0.414
	LTE Band 5 (Cell)	0.316	0.169	0.485
	LTE Band 4 (AWS)	0.159	0.169	0.328
	LTE Band 2 (PCS)	0.152	0.169	0.321

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

Table 12-7
Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM/GPRS 850	0.327	0.306	0.169	0.802
	UMTS 850	0.266	0.306	0.169	0.741
	Cell. CDMA/EVDO	0.404	0.306	0.169	0.879
	GSM/GPRS 1900	0.080	0.306	0.169	0.555
	UMTS 1900	0.081	0.306	0.169	0.556
	PCS CDMA/EVDO	0.153	0.306	0.169	0.628
	LTE Band 13	0.245	0.306	0.169	0.720
	LTE Band 5 (Cell)	0.316	0.306	0.169	0.791
	LTE Band 4 (AWS)	0.159	0.306	0.169	0.634
	LTE Band 2 (PCS)	0.152	0.306	0.169	0.627

The worst case 5 GHz WIFI reported SAR for each head configuration was considered for simultaneous SAR exclusion via summation of standalone SAR, regardless of whether the WIFI channel has WIFI Hotspot capability, for simplicity to determine compliance. Please note that the actual simultaneous transmission SAR will not exceed the summed levels indicated.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 78 of 90	

12.4 Body-Worn Simultaneous Transmission Analysis

Notes:

1. For SAR summation for body-worn back side at 15mm, the SAR values at 10mm for some transmission modes were used since the 10mm test distance was more conservative. "<" denotes that the 10mm SAR values were used for summation purposes.
2. Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used for SAR summation for body-worn back side at 15mm to determine simultaneous transmission SAR test exclusion.

Table 12-8
Simultaneous Transmission Scenario with 2.4 GHz WLAN – Ant 1 (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	<0.491	<0.138	<0.629
	UMTS 850	<0.378	<0.138	<0.516
	Cell. CDMA	<0.549	<0.138	<0.687
	GSM 1900	0.361	<0.138	<0.499
	UMTS 1900	0.401	<0.138	<0.539
	PCS CDMA	0.453	<0.138	<0.591
	LTE Band 13	<0.322	<0.138	<0.460
	LTE Band 5 (Cell)	<0.170	<0.138	<0.308
	LTE Band 4 (AWS)	0.543	<0.138	<0.681
	LTE Band 2 (PCS)	0.392	<0.138	<0.530

Table 12-9
Simultaneous Transmission Scenario with 2.4 GHz WLAN - Ant 2 (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	<0.491	<0.078	<0.569
	UMTS 850	<0.378	<0.078	<0.456
	Cell. CDMA	<0.549	<0.078	<0.627
	GSM 1900	0.361	<0.078	<0.439
	UMTS 1900	0.401	<0.078	<0.479
	PCS CDMA	0.453	<0.078	<0.531
	LTE Band 13	<0.322	<0.078	<0.400
	LTE Band 5 (Cell)	<0.170	<0.078	<0.248
	LTE Band 4 (AWS)	0.543	<0.078	<0.621
	LTE Band 2 (PCS)	0.392	<0.078	<0.470

Table 12-10
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	<0.491	<0.138	<0.078	<0.707
	UMTS 850	<0.378	<0.138	<0.078	<0.594
	Cell. CDMA	<0.549	<0.138	<0.078	<0.765
	GSM 1900	0.361	<0.138	<0.078	<0.577
	UMTS 1900	0.401	<0.138	<0.078	<0.617
	PCS CDMA	0.453	<0.138	<0.078	<0.669
	LTE Band 13	<0.322	<0.138	<0.078	<0.538
	LTE Band 5 (Cell)	<0.170	<0.138	<0.078	<0.386
	LTE Band 4 (AWS)	0.543	<0.138	<0.078	<0.759
	LTE Band 2 (PCS)	0.392	<0.138	<0.078	<0.608

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 79 of 90

Table 12-11
Simultaneous Transmission Scenario with 5 GHz WLAN Ant 1 (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	<0.491	<0.095	<0.586
	UMTS 850	<0.378	<0.095	<0.473
	Cell. CDMA	<0.549	<0.095	<0.644
	GSM 1900	0.361	<0.095	<0.456
	UMTS 1900	0.401	<0.095	<0.496
	PCS CDMA	0.453	<0.095	<0.548
	LTE Band 13	<0.322	<0.095	<0.417
	LTE Band 5 (Cell)	<0.170	<0.095	<0.265
	LTE Band 4 (AWS)	0.543	<0.095	<0.638
	LTE Band 2 (PCS)	0.392	<0.095	<0.487

Table 12-12
Simultaneous Transmission Scenario with 5 GHz WLAN Ant 2 (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	<0.491	<0.082	<0.573
	UMTS 850	<0.378	<0.082	<0.460
	Cell. CDMA	<0.549	<0.082	<0.631
	GSM 1900	0.361	<0.082	<0.443
	UMTS 1900	0.401	<0.082	<0.483
	PCS CDMA	0.453	<0.082	<0.535
	LTE Band 13	<0.322	<0.082	<0.404
	LTE Band 5 (Cell)	<0.170	<0.082	<0.252
	LTE Band 4 (AWS)	0.543	<0.082	<0.625
	LTE Band 2 (PCS)	0.392	<0.082	<0.474

Table 12-13
Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	<0.491	<0.095	<0.082	<0.668
	UMTS 850	<0.378	<0.095	<0.082	<0.555
	Cell. CDMA	<0.549	<0.095	<0.082	<0.726
	GSM 1900	0.361	<0.095	<0.082	<0.538
	UMTS 1900	0.401	<0.095	<0.082	<0.578
	PCS CDMA	0.453	<0.095	<0.082	<0.630
	LTE Band 13	<0.322	<0.095	<0.082	<0.499
	LTE Band 5 (Cell)	<0.170	<0.095	<0.082	<0.347
	LTE Band 4 (AWS)	0.543	<0.095	<0.082	<0.720
	LTE Band 2 (PCS)	0.392	<0.095	<0.082	<0.569

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 80 of 90	

Table 12-14
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	<0.491	0.140	<0.631
	UMTS 850	<0.378	0.140	<0.518
	Cell. CDMA	<0.549	0.140	<0.689
	GSM 1900	0.361	0.140	0.501
	UMTS 1900	0.401	0.140	0.541
	PCS CDMA	0.453	0.140	0.593
	LTE Band 13	<0.322	0.140	<0.462
	LTE Band 5 (Cell)	<0.170	0.140	<0.310
	LTE Band 4 (AWS)	0.543	0.140	0.683
	LTE Band 2 (PCS)	0.392	0.140	0.532

12.5 Hotspot SAR Simultaneous Transmission Analysis

Table 12-15
Simultaneous Transmission Scenario with 2.4 GHz – Ant 1 (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.559	0.138	0.697
	UMTS 850	0.475	0.138	0.613
	Cell. EVDO	0.619	0.138	0.757
	GPRS 1900	0.542	0.138	0.680
	UMTS 1900	0.648	0.138	0.786
	PCS EVDO	0.957	0.138	1.095
	LTE Band 13	0.322	0.138	0.460
	LTE Band 5 (Cell)	0.337	0.138	0.475
	LTE Band 4 (AWS)	0.542	0.138	0.680
	LTE Band 2 (PCS)	0.643	0.138	0.781

Table 12-16
Simultaneous Transmission Scenario with 2.4 GHz WLAN - Ant 2 (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.559	0.078	0.637
	UMTS 850	0.475	0.078	0.553
	Cell. EVDO	0.619	0.078	0.697
	GPRS 1900	0.542	0.078	0.620
	UMTS 1900	0.648	0.078	0.726
	PCS EVDO	0.957	0.078	1.035
	LTE Band 13	0.322	0.078	0.400
	LTE Band 5 (Cell)	0.337	0.078	0.415
	LTE Band 4 (AWS)	0.542	0.078	0.620
	LTE Band 2 (PCS)	0.643	0.078	0.721

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 81 of 90	

Table 12-17
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.559	0.138	0.078	0.775
	UMTS 850	0.475	0.138	0.078	0.691
	Cell. EVDO	0.619	0.138	0.078	0.835
	GPRS 1900	0.542	0.138	0.078	0.758
	UMTS 1900	0.648	0.138	0.078	0.864
	PCS EVDO	0.957	0.138	0.078	1.173
	LTE Band 13	0.322	0.138	0.078	0.538
	LTE Band 5 (Cell)	0.337	0.138	0.078	0.553
	LTE Band 4 (AWS)	0.542	0.138	0.078	0.758
	LTE Band 2 (PCS)	0.643	0.138	0.078	0.859

Table 12-18
Simultaneous Transmission Scenario with 5 GHz WLAN - Ant 1 (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.559	0.153	0.712
	UMTS 850	0.475	0.153	0.628
	Cell. EVDO	0.619	0.153	0.772
	GPRS 1900	0.542	0.153	0.695
	UMTS 1900	0.648	0.153	0.801
	PCS EVDO	0.957	0.153	1.110
	LTE Band 13	0.322	0.153	0.475
	LTE Band 5 (Cell)	0.337	0.153	0.490
	LTE Band 4 (AWS)	0.542	0.153	0.695
	LTE Band 2 (PCS)	0.643	0.153	0.796

Table 12-19
Simultaneous Transmission Scenario with 5 GHz WLAN - Ant 2 (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.559	0.028	0.587
	UMTS 850	0.475	0.028	0.503
	Cell. EVDO	0.619	0.028	0.647
	GPRS 1900	0.542	0.028	0.570
	UMTS 1900	0.648	0.028	0.676
	PCS EVDO	0.957	0.028	0.985
	LTE Band 13	0.322	0.028	0.350
	LTE Band 5 (Cell)	0.337	0.028	0.365
	LTE Band 4 (AWS)	0.542	0.028	0.570
	LTE Band 2 (PCS)	0.643	0.028	0.671

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 82 of 90

Table 12-20
Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.559	0.153	0.028	0.740
	UMTS 850	0.475	0.153	0.028	0.656
	Cell. EVDO	0.619	0.153	0.028	0.800
	GPRS 1900	0.542	0.153	0.028	0.723
	UMTS 1900	0.648	0.153	0.028	0.829
	PCS EVDO	0.957	0.153	0.028	1.138
	LTE Band 13	0.322	0.153	0.028	0.503
	LTE Band 5 (Cell)	0.337	0.153	0.028	0.518
	LTE Band 4 (AWS)	0.542	0.153	0.028	0.723
	LTE Band 2 (PCS)	0.643	0.153	0.028	0.824

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 83 of 90

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1908.75	1175	PCS CDMA	EVDO Rev. 0	bottom	10 mm	0.899	0.894	1.01	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body							
Spatial Peak						1.6 W/kg (mW/g)							
Uncontrolled Exposure/General Population						averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 84 of 90

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/15/2014	Annual	4/15/2015	MY45470194
Agilent	8753E	(30kHz-6GHz) Network Analyzer	12/30/2014	Annual	12/30/2015	JP38020182
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8648D	(9kHz-4GHz) Signal Generator	4/15/2014	Annual	4/15/2015	3629J00687
Agilent	N9020A	MXA Signal Analyzer	10/27/2014	Annual	10/27/2015	US46470561
Agilent	E5515C	Wireless Communications Test Set	3/18/2014	Annual	3/18/2015	GB46110872
Anritsu	MA2411B	Pulse Power Sensor	11/17/2014	Annual	11/17/2015	1207364
Anritsu	ML2495A	Power Meter	10/31/2013	Biennial	10/31/2015	941001
Anritsu	MT8820C	Radio Communication Analyzer	8/28/2014	Annual	8/28/2015	6201240328
Anritsu	MT8820C	Radio Communication Analyzer	11/18/2014	Annual	11/18/2015	6201300731
Anritsu	MA24106A	USB Power Sensor	5/14/2014	Annual	5/14/2015	1231538
Anritsu	MA24106A	USB Power Sensor	5/14/2014	Annual	5/14/2015	1231535
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	61220-416	Long-Stem Thermometer	4/29/2014	Biennial	4/29/2016	111331323
Control Company	36934-158	Wall-Mounted Thermometer	4/29/2014	Biennial	4/29/2016	122014488
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/30/2014	Annual	10/30/2015	1833460
Gigatronics	8651A	Universal Power Meter	10/30/2014	Annual	10/30/2015	8650319
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-53W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	4/17/2014	Annual	4/17/2015	101699
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
SPEAG	D1765V2	1765 MHz SAR Dipole	5/7/2014	Annual	5/7/2015	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	4/9/2014	Annual	4/9/2015	5d141
SPEAG	D1900V2	1900 MHz SAR Dipole	7/23/2014	Annual	7/23/2015	5d149
SPEAG	D2450V2	2450 MHz SAR Dipole	8/11/2014	Annual	8/11/2015	719
SPEAG	D5GHZV2	5 GHz SAR Dipole	2/26/2014	Annual	2/26/2015	1120
SPEAG	D5GHZV2	5 GHz SAR Dipole	9/25/2014	Annual	9/25/2015	1191
SPEAG	D750V3	750 MHz Dipole	3/17/2014	Annual	3/17/2015	1054
SPEAG	D835V2	835 MHz SAR Dipole	7/24/2014	Annual	7/24/2015	4d133
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/26/2014	Annual	2/26/2015	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2014	Annual	3/17/2015	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2014	Annual	4/11/2015	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/14/2014	Annual	5/14/2015	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/12/2014	Annual	8/12/2015	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/17/2014	Annual	9/17/2015	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/18/2014	Annual	9/18/2015	1364
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/19/2015	Annual	1/19/2016	1407
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/6/2014	Annual	5/6/2015	1070
SPEAG	ES3DV3	SAR Probe	2/25/2014	Annual	2/25/2015	3258
SPEAG	ES3DV3	SAR Probe	3/19/2014	Annual	3/19/2015	3209
SPEAG	ES3DV3	SAR Probe	9/18/2014	Annual	9/18/2015	3332
SPEAG	ES3DV3	SAR Probe	5/15/2014	Annual	5/15/2015	3263
SPEAG	ES3DV2	SAR Probe	8/19/2014	Annual	8/19/2015	3022
SPEAG	ES3DV3	SAR Probe	9/24/2014	Annual	9/24/2015	3288
SPEAG	EX3DV4	SAR Probe	12/12/2014	Annual	12/12/2015	3920
SPEAG	ES3DV3	SAR Probe	1/20/2015	Annual	1/20/2016	3213
Tektronix	RSA6114A	Real Time Spectrum Analyzer	4/16/2014	Annual	4/16/2015	B010177

Note:

- CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
- All calibrated equipments are used in within their calibration period.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 85 of 90

15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.1	11.7
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.2	23.5

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 86 of 90

Applicable for frequencies up to 6 GHz.

a	b	c	d	e= f(d,k)	f	g	h= c x f/e	i= c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary E effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout E lectronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	E.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.4	12.0
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.7	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 87 of 90

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMG925V	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 88 of 90

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMG925V	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset	Page 89 of 90

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01 DR02-41929
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMG925V		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501200180.A3L	Test Dates: 01/19/15 - 02/10/15	DUT Type: Portable Handset		Page 90 of 90

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.934 \text{ S/m}$; $\epsilon_r = 43.416$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-19-2015; Ambient Temp: 23.1°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Left Head, Cheek, Mid.ch


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.99 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.398 W/kg

SAR(1 g) = 0.311 W/kg



0 dB = 0.345 W/kg = -4.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.934 \text{ S/m}$; $\epsilon_r = 43.416$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-19-2015; Ambient Temp: 23.1°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Left Head, Cheek, Mid.ch


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.51 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.341 W/kg

SAR(1 g) = 0.265 W/kg



0 dB = 0.293 W/kg = -5.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234F1

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.52$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 43.417$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Test Date: 01-19-2015; Ambient Temp: 23.1°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. CDMA, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.36 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.525 W/kg

SAR(1 g) = 0.402 W/kg



0 dB = 0.442 W/kg = -3.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.390 \text{ S/m}$; $\epsilon_r = 39.392$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-19-2015; Ambient Temp: 24.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3258; ConvF(5.04, 5.04, 5.04); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Right Head, Cheek, Mid.ch


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.788 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.117 W/kg

SAR(1 g) = 0.076 W/kg



0 dB = 0.0878 W/kg = -10.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.390 \text{ S/m}$; $\epsilon_r = 39.392$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-19-2015; Ambient Temp: 24.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3258; ConvF(5.04, 5.04, 5.04); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Right Head, Cheek, Mid.ch


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.030 V/m; Power Drift = -0.20 dB

Peak SAR (extrapolated) = 0.124 W/kg

SAR(1 g) = 0.080 W/kg



0 dB = 0.0940 W/kg = -10.27 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234F1

Communication System: UID 0, CDMA; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1851.25 \text{ MHz}$; $\sigma = 1.364 \text{ S/m}$; $\epsilon_r = 39.519$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-19-2015; Ambient Temp: 24.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3258; ConvF(5.04, 5.04, 5.04); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: PCS EVDO, Right Head, Cheek, Low.ch


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.79 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.239 W/kg

SAR(1 g) = 0.152 W/kg



0 dB = 0.181 W/kg = -7.42 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 08FC4

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.936 \text{ S/m}$; $\epsilon_r = 40.408$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-22-2015; Ambient Temp: 24.0°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3288; ConvF(6.81, 6.81, 6.81); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Right Head, Cheek, Mid.ch
QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.46 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.271 W/kg

SAR(1 g) = 0.217 W/kg



0 dB = 0.240 W/kg = -6.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234C9

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.934 \text{ S/m}$; $\epsilon_r = 43.418$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-19-2015; Ambient Temp: 23.1°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell), Left Head, Cheek, Mid.ch

QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.46 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.386 W/kg

SAR(1 g) = 0.298 W/kg



0 dB = 0.332 W/kg = -4.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 23503

Communication System: UID 0, LTE Band 4; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.327 \text{ S/m}$; $\epsilon_r = 38.539$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-22-2015; Ambient Temp: 23.0°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3263; ConvF(5.41, 5.41, 5.41); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Right Head, Cheek, Mid.ch
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.00 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.231 W/kg

SAR(1 g) = 0.155 W/kg



0 dB = 0.181 W/kg = -7.42 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 23503

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.372 \text{ S/m}$; $\epsilon_r = 39.480$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-19-2015; Ambient Temp: 24.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3258; ConvF(5.04, 5.04, 5.04); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Right Head, Cheek, Low.ch
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset



Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.97 V/m; Power Drift = -0.20 dB

Peak SAR (extrapolated) = 0.228 W/kg

SAR(1 g) = 0.146 W/kg



0 dB = 0.170 W/kg = -7.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234B0

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.806 \text{ S/m}$; $\epsilon_r = 38.507$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-23-2015; Ambient Temp: 21.3°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Ant 1
Right Head, Cheek, Ch 11, 1 Mbps


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.22 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.585 W/kg

SAR(1 g) = 0.250 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234B0

Communication System: UID 0, IEEE 802.11ac; Frequency: 5530 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5530 \text{ MHz}$; $\sigma = 4.778 \text{ S/m}$; $\epsilon_r = 35.267$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-23-2015; Ambient Temp: 23.5°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3920; ConvF(4.44, 4.44, 4.44); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM, Left; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11ac, 80 MHz Bandwidth, Ant 1
Right Head, Cheek, Ch 106, 29.3 Mbps


Area Scan (13x21x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 6.146 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.931 W/kg

SAR(1 g) = 0.190 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 55.280$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.25 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.619 W/kg

SAR(1 g) = 0.467 W/kg



0 dB = 0.520 W/kg = -2.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, GSM GPRS; Frequency: 836.6 MHz; Duty Cycle: 1:2.76

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 55.280$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Back Side, Mid.ch, 3 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.68 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.693 W/kg

SAR(1 g) = 0.523 W/kg



0 dB = 0.581 W/kg = -2.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 55.280$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.89 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.495 W/kg

SAR(1 g) = 0.377 W/kg



0 dB = 0.419 W/kg = -3.78 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 55.280$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Left Edge, Mid.ch


Area Scan (10x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.70 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.678 W/kg

SAR(1 g) = 0.474 W/kg



0 dB = 0.547 W/kg = -2.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 23503

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 55.280$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. CDMA, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.07 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.699 W/kg

SAR(1 g) = 0.549 W/kg



0 dB = 0.601 W/kg = -2.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 23503

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52$ MHz; $\sigma = 1.011$ S/m; $\epsilon_r = 55.280$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. EVDO, Body SAR, Left Edge, Mid.ch


Area Scan (10x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.94 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.872 W/kg

SAR(1 g) = 0.619 W/kg



0 dB = 0.708 W/kg = -1.50 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.522 \text{ S/m}$; $\epsilon_r = 51.716$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-22-2015; Ambient Temp: 23.9°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.00 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.575 W/kg

SAR(1 g) = 0.341 W/kg



0 dB = 0.408 W/kg = -3.89 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234C8

Communication System: UID 0, GSM GPRS; Frequency: 1880 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.527 \text{ S/m}$; $\epsilon_r = 52.312$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-29-2015; Ambient Temp: 24.0°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 4 Tx Slots


Area Scan (13x8x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.78 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.766 W/kg

SAR(1 g) = 0.467 W/kg



0 dB = 0.568 W/kg = -2.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.527 \text{ S/m}$; $\epsilon_r = 52.312$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-29-2015; Ambient Temp: 24.0°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.96 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.644 W/kg

SAR(1 g) = 0.395 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234C8

Communication System: UID 0, UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$; $\sigma = 1.527 \text{ S/m}$; $\epsilon_r = 52.455$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2015; Ambient Temp: 23.8°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3332; ConvF(4.64, 4.64, 4.64); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Bottom Edge, Low.ch


Area Scan (10x7x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.55 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.940 W/kg

SAR(1 g) = 0.569 W/kg



0 dB = 0.700 W/kg = -1.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234F1

Communication System: UID 0, CDMA; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated);

$f = 1851.25$ MHz; $\sigma = 1.489$ S/m; $\epsilon_r = 51.805$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-22-2015; Ambient Temp: 23.9°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: PCS CDMA, Body SAR, Back side, Low.ch


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.92 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.652 W/kg

SAR(1 g) = 0.419 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234C8

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated);

$f = 1908.75 \text{ MHz}$; $\sigma = 1.563 \text{ S/m}$; $\epsilon_r = 51.703$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-10-2015; Ambient Temp: 23.5°C; Tissue Temp: 22.9°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: PCS EVDO, Body SAR, Bottom Edge, High.ch


Area Scan (10x7x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.68 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.899 W/kg



0 dB = 1.08 W/kg = 0.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 23503

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 52.948$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 23.2°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3332; ConvF(6.24, 6.24, 6.24); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Body SAR, Back side, Mid.ch

QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.22 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.453 W/kg

SAR(1 g) = 0.286 W/kg



0 dB = 0.334 W/kg = -4.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 23503

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 55.280$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Body SAR, Back Side, Mid.ch
QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.10 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.277 W/kg

SAR(1 g) = 0.161 W/kg



0 dB = 0.187 W/kg = -7.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 23503

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 55.280$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Body SAR, Right Edge, Mid.ch
QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (11x13x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.55 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.452 W/kg

SAR(1 g) = 0.318 W/kg



0 dB = 0.364 W/kg = -4.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 23503

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.442 \text{ S/m}$; $\epsilon_r = 51.613$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-19-2015; Ambient Temp: 23.0°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3263; ConvF(4.98, 4.98, 4.98); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.75 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.811 W/kg

SAR(1 g) = 0.531 W/kg



0 dB = 0.627 W/kg = -2.03 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234EB

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.443 \text{ S/m}$; $\epsilon_r = 51.660$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-04-2015; Ambient Temp: 23.9°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3213; ConvF(4.93, 4.93, 4.93); Calibrated: 1/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 1/19/2015

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Bottom Edge, Mid.ch
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (13x9x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.63 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.873 W/kg

SAR(1 g) = 0.533 W/kg



0 dB = 0.653 W/kg = -1.85 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234DC

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.505 \text{ S/m}$; $\epsilon_r = 52.379$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-29-2015; Ambient Temp: 24.0°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Body SAR, Back side, Low.ch
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.94 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.604 W/kg

SAR(1 g) = 0.378 W/kg



0 dB = 0.456 W/kg = -3.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234EB

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.505 \text{ S/m}$; $\epsilon_r = 52.379$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-29-2015; Ambient Temp: 24.0°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Body SAR, Bottom Edge, Low.ch
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (10x7x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.38 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.643 W/kg



0 dB = 0.798 W/kg = -0.98 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 234B0

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$; $\sigma = 1.873 \text{ S/m}$; $\epsilon_r = 51.121$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 23.5°C; Tissue Temp: 23.8°C

Probe: ES3DV3 - SN3209; ConvF(4.2, 4.2, 4.2); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM left; Type: QD000P40CD; Serial: TP:1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Ant 1

Body SAR, Ch 01, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.769 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.269 W/kg

SAR(1 g) = 0.131 W/kg



0 dB = 0.166 W/kg = -7.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 236B4

Communication System: UID 0, 802.11a; Frequency: 5280 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5280 \text{ MHz}$; $\sigma = 5.500 \text{ S/m}$; $\epsilon_r = 48.179$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-19-2015; Ambient Temp: 24.1°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3920; ConvF(4.16, 4.16, 4.16); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 20 MHz Bandwidth, Ant 1

Body SAR, Ch 56, 6 Mbps, Back Side


Area Scan (13x19x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 4.071 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.532 W/kg

SAR(1 g) = 0.089 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG925V; Type: Portable Handset; Serial: 236B4

Communication System: UID 0, IEEE 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 6.176 \text{ S/m}$; $\epsilon_r = 47.389$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-19-2015; Ambient Temp: 23.9°C; Tissue Temp: 23.1°C

Probe: EX3DV4 - SN3920; ConvF(3.93, 3.93, 3.93); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 20 MHz Bandwidth, Ant 1

Body SAR, Ch 149, 6 Mbps, Front Side


Area Scan (13x19x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 4.722 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.621 W/kg

SAR(1 g) = 0.149 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.906 \text{ S/m}$; $\epsilon_r = 40.880$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-22-2015; Ambient Temp: 24.0°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3288; ConvF(6.81, 6.81, 6.81); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.826 W/kg

Deviation = -0.84%



0 dB = 0.973 W/kg = -0.12 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.933 \text{ S/m}$; $\epsilon_r = 43.439$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-19-2015; Ambient Temp: 23.1°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.47 W/kg

SAR(1 g) = 0.971 W/kg

Deviation = 5.54%



0 dB = 1.14 W/kg = 0.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.344 \text{ S/m}$; $\epsilon_r = 38.466$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 23.0°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3263; ConvF(5.41, 5.41, 5.41); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.16 W/kg

SAR(1 g) = 3.45 W/kg

Deviation = -6.50%



0 dB = 4.28 W/kg = 6.31 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.409 \text{ S/m}$; $\epsilon_r = 39.285$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-19-2015; Ambient Temp: 24.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3258; ConvF(5.04, 5.04, 5.04); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.59 W/kg

SAR(1 g) = 4.15 W/kg

Deviation = 3.23%



0 dB = 5.01 W/kg = 7.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.794 \text{ S/m}$; $\epsilon_r = 38.552$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-23-2015; Ambient Temp: 21.3°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 10.2 W/kg

SAR(1 g) = 4.99 W/kg

Deviation = -4.22%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 4.549 \text{ S/m}$; $\epsilon_r = 35.571$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-23-2015; Ambient Temp: 23.4°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3920; ConvF(4.69, 4.69, 4.69); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM, Left; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 32.2 W/kg

SAR(1 g) = 7.74 W/kg

Deviation = -7.19%



0 dB = 19.7 W/kg = 12.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 4.748 \text{ S/m}$; $\epsilon_r = 35.287$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-23-2015; Ambient Temp: 23.5°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3920; ConvF(4.44, 4.44, 4.44); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM, Left; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5500 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 34.0 W/kg

SAR(1 g) = 7.88 W/kg

Deviation = -7.18%



0 dB = 20.1 W/kg = 13.03 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 5.054 \text{ S/m}$; $\epsilon_r = 34.890$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-23-2015; Ambient Temp: 23.5°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3920; ConvF(4.27, 4.27, 4.27); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM, Left; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification

Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 34.3 W/kg

SAR(1 g) = 7.80 W/kg

Deviation = -1.39%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.964 \text{ S/m}$; $\epsilon_r = 53.293$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-22-2015; Ambient Temp: 23.2°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3332; ConvF(6.24, 6.24, 6.24); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.855 W/kg

Deviation = -1.04%



0 dB = 0.996 W/kg = -0.02 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.010 \text{ S/m}$; $\epsilon_r = 55.292$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-22-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3288; ConvF(6.32, 6.32, 6.32); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 1.02 W/kg

Deviation = 9.09%



0 dB = 1.19 W/kg = 0.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.461 \text{ S/m}$; $\epsilon_r = 51.563$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-19-2015; Ambient Temp: 23.0°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3263; ConvF(4.98, 4.98, 4.98); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.40 W/kg

SAR(1 g) = 3.69 W/kg

Deviation = -1.86%



0 dB = 4.57 W/kg = 6.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.462 \text{ S/m}$; $\epsilon_r = 51.586$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-04-2015; Ambient Temp: 23.9°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3213; ConvF(4.93, 4.93, 4.93); Calibrated: 1/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 1/19/2015

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.59 W/kg

SAR(1 g) = 3.75 W/kg

Deviation = -0.27%



0 dB = 4.63 W/kg = 6.66 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.542 \text{ S/m}$; $\epsilon_r = 51.633$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 23.9°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.02 W/kg

SAR(1 g) = 4.12 W/kg

Deviation = 1.98%



0 dB = 5.10 W/kg = 7.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900$ MHz; $\sigma = 1.551$ S/m; $\epsilon_r = 52.251$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-29-2015; Ambient Temp: 24.0°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3258; ConvF(4.61, 4.61, 4.61); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.05 W/kg

SAR(1 g) = 4.08 W/kg

Deviation = 0.49%



0 dB = 5.12 W/kg = 7.09 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900$ MHz; $\sigma = 1.579$ S/m; $\epsilon_r = 52.286$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2015; Ambient Temp: 23.8°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3332; ConvF(4.64, 4.64, 4.64); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.29 W/kg

SAR(1 g) = 4.13 W/kg

Deviation = 2.23%



0 dB = 5.14 W/kg = 7.11 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.553 \text{ S/m}$; $\epsilon_r = 51.737$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-10-2015; Ambient Temp: 23.5°C; Tissue Temp: 22.9°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.88 W/kg

SAR(1 g) = 3.92 W/kg

Deviation = -2.97%



0 dB = 4.96 W/kg = 6.95 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.925 \text{ S/m}$; $\epsilon_r = 50.991$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-22-2015; Ambient Temp: 23.5°C; Tissue Temp: 23.8°C

Probe: ES3DV3 - SN3209; ConvF(4.2, 4.2, 4.2); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM left; Type: QD000P40CD; Serial: TP:1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 11.2 W/kg

SAR(1 g) = 5.20 W/kg

Deviation = 0.39%



0 dB = 6.86 W/kg = 8.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.542 \text{ S/m}$; $\epsilon_r = 48.230$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-19-2015; Ambient Temp: 24.1°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3920; ConvF(4.16, 4.16, 4.16); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 32.4 W/kg

SAR(1 g) = 7.95 W/kg

Deviation = -0.50%



0 dB = 20.3 W/kg = 13.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5500$ MHz; $\sigma = 5.845$ S/m; $\epsilon_r = 47.908$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-19-2015; Ambient Temp: 24.1°C; Tissue Temp: 23.1°C

Probe: EX3DV4 - SN3920; ConvF(3.79, 3.79, 3.79); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5500 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 32.3 W/kg

SAR(1 g) = 7.60 W/kg

Deviation = -8.54%



0 dB = 19.7 W/kg = 12.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5600 MHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.977 \text{ S/m}$; $\epsilon_r = 47.642$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-19-2015; Ambient Temp: 24.0°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN3920; ConvF(3.66, 3.66, 3.66); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 32.4 W/kg

SAR(1 g) = 7.63 W/kg

Deviation = -9.27%



0 dB = 19.7 W/kg = 12.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 6.183 \text{ S/m}$; $\epsilon_r = 47.296$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-19-2015; Ambient Temp: 23.9°C; Tissue Temp: 23.1°C

Probe: EX3DV4 - SN3920; ConvF(3.93, 3.93, 3.93); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Power Input = 20 dBm (100 mW)

Peak SAR (extrapolated) = 32.9 W/kg

SAR(1 g) = 7.09 W/kg

Deviation = -9.10%



0 dB = 19.1 W/kg = 12.81 dBW/kg