



## SAR EVALUATION REPORT

**Applicant Name:**

Samsung Electronics, Co. Ltd.  
129, Samsung-ro, Maetan dong,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do 443-742, Korea

**Date of Testing:**

06/08/15 – 06/29/15

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Document Serial No.:**

0Y1506081055.A3L

**FCC ID:**
**A3LSMG928V**
**APPLICANT:**
**SAMSUNG ELECTRONICS, CO. LTD.**
**DUT Type:**

Portable Handset

**Application Type:**

Certification

**FCC Rule Part(s):**

CFR §2.1093

**Model(s):**

SM-G928V

| Equipment Class                                   | Band & Mode        | Tx Frequency          | SAR              |                       |                     |                        |
|---------------------------------------------------|--------------------|-----------------------|------------------|-----------------------|---------------------|------------------------|
|                                                   |                    |                       | 1 gm Head (W/kg) | 1 gm Body-Worn (W/kg) | 1 gm Hotspot (W/kg) | 10 gm Extremity (W/kg) |
| PCE                                               | GSM/GPRS/EDGE 850  | 824.20 - 848.80 MHz   | 0.26             | 0.41                  | 0.98                |                        |
| PCE                                               | UMTS 850           | 826.40 - 846.60 MHz   | 0.19             | 0.36                  | 0.62                |                        |
| PCE                                               | GSM/GPRS/EDGE 1900 | 1850.20 - 1909.80 MHz | 0.10             | 0.31                  | 1.02                | 2.98                   |
| PCE                                               | UMTS 1900          | 1852.4 - 1907.6 MHz   | 0.15             | 0.40                  | 1.04                | 2.80                   |
| PCE                                               | Cell. CDMA/EVDO    | 824.70 - 848.31 MHz   | 0.41             | 0.16                  | 0.97                |                        |
| PCE                                               | PCS CDMA/EVDO      | 1851.25 - 1908.75 MHz | 0.20             | 0.41                  | 1.03                | 2.64                   |
| PCE                                               | LTE Band 13        | 779.5 - 784.5 MHz     | 0.26             | 0.43                  | 0.70                |                        |
| PCE                                               | LTE Band 5 (Cell)  | 824.7 - 848.3 MHz     | 0.23             | 0.30                  | 0.74                |                        |
| PCE                                               | LTE Band 4 (AWS)   | 1710.7 - 1754.3 MHz   | 0.24             | 0.75                  | 0.90                | 3.11                   |
| PCE                                               | LTE Band 2 (PCS)   | 1850.7 - 1909.3 MHz   | 0.18             | 0.61                  | 0.95                | 3.23                   |
| DTS                                               | 2.4 GHz WLAN       | 2412 - 2462 MHz       | 0.54             | 0.19                  | 0.19                |                        |
| NII                                               | U-NII-1            | 5180 - 5240 MHz       | N/A              |                       |                     |                        |
| NII                                               | U-NII-2A           | 5260 - 5320 MHz       | 0.27             | < 0.1                 |                     | 0.46                   |
| NII                                               | U-NII-2C           | 5500 - 5720 MHz       | 0.38             | < 0.1                 |                     | 0.53                   |
| NII                                               | U-NII-3            | 5745 - 5825 MHz       | 0.40             | < 0.1                 | 0.21                |                        |
| DSS/DTS                                           | Bluetooth          | 2402 - 2480 MHz       | N/A              |                       |                     |                        |
| <b>Simultaneous SAR per KDB 690783 D01v01r03:</b> |                    |                       | 1.25             | 1.11                  | 1.42                | 3.97                   |

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

  
Randy Ortanez  
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: SARTICK@MMF.AI.INFO.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 1 of 119                                                                         |                                 |

# T A B L E O F C O N T E N T S

|                                                       |                                                  |     |
|-------------------------------------------------------|--------------------------------------------------|-----|
| 1                                                     | DEVICE UNDER TEST .....                          | 3   |
| 2                                                     | LTE INFORMATION .....                            | 12  |
| 3                                                     | INTRODUCTION .....                               | 13  |
| 4                                                     | DOSIMETRIC ASSESSMENT .....                      | 14  |
| 5                                                     | DEFINITION OF REFERENCE POINTS .....             | 15  |
| 6                                                     | TEST CONFIGURATION POSITIONS FOR HANDSETS .....  | 16  |
| 7                                                     | RF EXPOSURE LIMITS .....                         | 20  |
| 8                                                     | FCC MEASUREMENT PROCEDURES.....                  | 21  |
| 9                                                     | RF CONDUCTED POWERS.....                         | 29  |
| 10                                                    | SYSTEM VERIFICATION.....                         | 81  |
| 11                                                    | SAR DATA SUMMARY .....                           | 85  |
| 12                                                    | FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS..... | 101 |
| 13                                                    | SAR MEASUREMENT VARIABILITY .....                | 113 |
| 14                                                    | EQUIPMENT LIST .....                             | 114 |
| 15                                                    | MEASUREMENT UNCERTAINTIES .....                  | 115 |
| 16                                                    | CONCLUSION.....                                  | 117 |
| 17                                                    | REFERENCES .....                                 | 118 |
| APPENDIX A: SAR TEST PLOTS                            |                                                  |     |
| APPENDIX B: SAR DIPOLE VERIFICATION PLOTS             |                                                  |     |
| APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES |                                                  |     |
| APPENDIX D: SAR TISSUE SPECIFICATIONS                 |                                                  |     |
| APPENDIX E: SAR VALIDATION SUMMARY                    |                                                  |     |
| APPENDIX F: SAR TEST DIAGRAM AND PHOTOGRAPHS          |                                                  |     |
| APPENDIX G: SENSOR TRIGGERING DATA SUMMARY            |                                                  |     |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 2 of 119                                                                         |                                        |

# 1 DEVICE UNDER TEST

## 1.1 Device Overview

| Band & Mode        | Operating Modes | Tx Frequency          |
|--------------------|-----------------|-----------------------|
| GSM/GPRS/EDGE 850  | Voice/Data      | 824.20 - 848.80 MHz   |
| UMTS 850           | Voice/Data      | 826.40 - 846.60 MHz   |
| GSM/GPRS/EDGE 1900 | Voice/Data      | 1850.20 - 1909.80 MHz |
| UMTS 1900          | Voice/Data      | 1852.4 - 1907.6 MHz   |
| Cell. CDMA/EVDO    | Voice/Data      | 824.70 - 848.31 MHz   |
| PCS CDMA/EVDO      | Voice/Data      | 1851.25 - 1908.75 MHz |
| LTE Band 13        | Voice/Data      | 779.5 - 784.5 MHz     |
| LTE Band 5 (Cell)  | Voice/Data      | 824.7 - 848.3 MHz     |
| LTE Band 4 (AWS)   | Voice/Data      | 1710.7 - 1754.3 MHz   |
| LTE Band 2 (PCS)   | Voice/Data      | 1850.7 - 1909.3 MHz   |
| 2.4 GHz WLAN       | Data            | 2412 - 2462 MHz       |
| U-NII-1            | Data            | 5180 - 5240 MHz       |
| U-NII-2A           | Data            | 5260 - 5320 MHz       |
| U-NII-2C           | Data            | 5500 - 5720 MHz       |
| U-NII-3            | Data            | 5745 - 5825 MHz       |
| Bluetooth          | Data            | 2402 - 2480 MHz       |
| NFC                | Data            | 13.56 MHz             |
| ANT+               | Data            | 2402 - 2480 MHz       |
| MST                | Data            | 1-8.3 kHz             |

## 1.2 Power Reduction for SAR

This device utilizes independent power reduction mechanisms for SAR compliance for the licensed transmitter and the WLAN transmitter. For the main transmitter, the device utilizes power reduction for some exposure and use conditions as outlined in Section 1.3.

Additionally, this device uses an independent single-step fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528.

The reduced powers for the power reduction mechanisms were confirmed via conducted power measurements at the RF port (See Section 9). Detailed descriptions of the mechanisms are included in the operational description.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 3 of 119                                                                         |                                        |

### 1.3 RF Output Target Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

#### Main Band – GSM/GPRS/EDGE:

| Mode / Band |                   | Exposure Condition(s)    |         | Voice (dBm) | Burst Average GMSK (dBm) |            |            |            |            | Burst Average 8-PSK (dBm) |            |            |  |
|-------------|-------------------|--------------------------|---------|-------------|--------------------------|------------|------------|------------|------------|---------------------------|------------|------------|--|
|             |                   |                          |         | 1 TX Slot   | 1 TX Slots               | 2 TX Slots | 3 TX Slots | 4 TX Slots | 1 TX Slots | 2 TX Slots                | 3 TX Slots | 4 TX Slots |  |
| Maximum     | GSM/GPRS/EDGE 850 | Head, Body-Worn, Hotspot | Maximum | 33.5        | 33.5                     | 32.0       | 30.0       | 28.5       | 27.5       | 26.5                      | 23.5       | 22.5       |  |
|             |                   |                          | Nominal | 33.0        | 33.0                     | 31.5       | 29.5       | 28.0       | 27.0       | 26.0                      | 23.0       | 22.0       |  |

| Mode / Band |                    | Exposure Condition(s)      |         | Voice (dBm) | Burst Average GMSK (dBm) |            |            |            |            | Burst Average 8-PSK (dBm) |            |            |  |
|-------------|--------------------|----------------------------|---------|-------------|--------------------------|------------|------------|------------|------------|---------------------------|------------|------------|--|
|             |                    |                            |         | 1 TX Slot   | 1 TX Slots               | 2 TX Slots | 3 TX Slots | 4 TX Slots | 1 TX Slots | 2 TX Slots                | 3 TX Slots | 4 TX Slots |  |
| Maximum     | GSM/GPRS/EDGE 1900 | Head, Body-Worn, Extremity | Maximum | 30.5        | 30.5                     | 29.5       | 27.5       | 26.5       | 26.5       | 25.5                      | 22.5       | 21.5       |  |
|             |                    |                            | Nominal | 30.0        | 30.0                     | 29.0       | 27.0       | 26.0       | 26.0       | 25.0                      | 22.0       | 21.0       |  |
| Reduced     |                    | Hotspot, Extremity         | Maximum | 28.5        | 28.5                     | 25.5       | 23.5       | 22.0       | 26.5       | 25.5                      | 22.5       | 21.5       |  |
|             |                    |                            | Nominal | 28.0        | 28.0                     | 25.0       | 23.0       | 21.5       | 26.0       | 25.0                      | 22.0       | 21.0       |  |

#### Main Band – UMTS:

| Mode / Band |                       | Exposure Condition(s)    |         | Modulated Average (dBm) |                  |                  |
|-------------|-----------------------|--------------------------|---------|-------------------------|------------------|------------------|
|             |                       |                          |         | 3GPP WCDMA Rel 99       | 3GPP HSDPA Rel 5 | 3GPP HSUPA Rel 6 |
| Maximum     | UMTS Band 5 (850 MHz) | Head, Body-Worn, Hotspot | Maximum | 23.5                    | 23.5             | 22.5             |
|             |                       |                          | Nominal | 23.0                    | 23.0             | 22.0             |

| Mode / Band |                           | Exposure Condition(s)         |         | Modulated Average (dBm) |                        |                        |
|-------------|---------------------------|-------------------------------|---------|-------------------------|------------------------|------------------------|
|             |                           |                               |         | 3GPP<br>WCDMA<br>Rel 99 | 3GPP<br>HSDPA<br>Rel 5 | 3GPP<br>HSUPA<br>Rel 6 |
| Maximum     | UMTS Band 2<br>(1900 MHz) | Head, Body-Worn,<br>Extremity | Maximum | 23.5                    | 23.5                   | 22.5                   |
|             |                           |                               | Nominal | 23.0                    | 23.0                   | 22.0                   |
| Reduced     |                           | Hotspot, Extremity            | Maximum | 20.5                    | 20.5                   | 19.5                   |
|             |                           |                               | Nominal | 20.0                    | 20.0                   | 19.0                   |

#### Main Band – CDMA/EVDO:

| Mode / Band |                 | Exposure Condition(s)    |         | Modulated Average (dBm) |
|-------------|-----------------|--------------------------|---------|-------------------------|
| Maximum     | Cell. CDMA/EVDO | Head, Body-Worn, Hotspot | Maximum | 25.0                    |
|             |                 |                          | Nominal | 24.5                    |

| Mode / Band |               | Exposure Condition(s)      |         | Modulated Average (dBm) |
|-------------|---------------|----------------------------|---------|-------------------------|
| Maximum     | PCS CDMA/EVDO | Head, Body-Worn, Extremity | Maximum | 25.0                    |
|             |               |                            | Nominal | 24.5                    |
| Reduced     |               | Head, Hotspot, Extremity   | Maximum | 20.5                    |
|             |               |                            | Nominal | 20.0                    |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 4 of 119                                                                         |                                 |

## Main Band – LTE:

| Mode / Band |                   | Exposure Condition(s)    |         | Modulated Average (dBm) |
|-------------|-------------------|--------------------------|---------|-------------------------|
| Maximum     | LTE Band 13       | Head, Body-Worn, Hotspot | Maximum | 25.0                    |
|             |                   |                          | Nominal | 24.5                    |
|             | LTE Band 5 (Cell) | Head, Body-Worn, Hotspot | Maximum | 25.0                    |
|             |                   |                          | Nominal | 24.5                    |

| Mode / Band |                  | Exposure Condition(s)      |         | Modulated Average (dBm) |
|-------------|------------------|----------------------------|---------|-------------------------|
| Maximum     | LTE Band 4 (AWS) | Head, Body-Worn, Extremity | Maximum | 24.5                    |
|             |                  |                            | Nominal | 24.0                    |
| Reduced     | LTE Band 4 (AWS) | Hotspot                    | Maximum | 20.5                    |
|             |                  |                            | Nominal | 20.0                    |
|             | LTE Band 4 (AWS) | Extremity                  | Maximum | 21.5                    |
|             |                  |                            | Nominal | 21.0                    |

| Mode / Band |                  | Exposure Condition(s)      |         | Modulated Average (dBm) |
|-------------|------------------|----------------------------|---------|-------------------------|
| Maximum     | LTE Band 2 (PCS) | Head, Body-Worn, Extremity | Maximum | 24.5                    |
|             |                  |                            | Nominal | 24.0                    |
| Reduced     | LTE Band 2 (PCS) | Hotspot                    | Maximum | 20.0                    |
|             |                  |                            | Nominal | 19.5                    |
|             | LTE Band 2 (PCS) | Extremity                  | Maximum | 21.0                    |
|             |                  |                            | Nominal | 20.5                    |

## BT/WLAN - Maximum Power:

| Mode / Band                    |         | Modulated Average (dBm) |
|--------------------------------|---------|-------------------------|
| IEEE 802.11b<br>(2.4 GHz SISO) | Maximum | 17.5                    |
|                                | Nominal | 17.0                    |
| IEEE 802.11g<br>(2.4 GHz SISO) | Maximum | 14.5                    |
|                                | Nominal | 14.0                    |
| IEEE 802.11n<br>(2.4 GHz SISO) | Maximum | 13.5                    |
|                                | Nominal | 13.0                    |
| IEEE 802.11n<br>(2.4 GHz MIMO) | Maximum | 16.5                    |
|                                | Nominal | 16.0                    |
| Bluetooth                      | Maximum | 10.5                    |
|                                | Nominal | 10.0                    |
| Bluetooth LE                   | Maximum | 6.0                     |
|                                | Nominal | 5.5                     |

| Mode / Band           |         | Modulated Average - Single Tx Chain (dBm) |                  |                  |
|-----------------------|---------|-------------------------------------------|------------------|------------------|
|                       |         | 20 MHz Bandwidth                          | 40 MHz Bandwidth | 80 MHz Bandwidth |
| IEEE 802.11a (5 GHz)  | Maximum | 13.5                                      |                  |                  |
|                       | Nominal | 13.0                                      |                  |                  |
| IEEE 802.11n (5 GHz)  | Maximum | 13.5                                      | 12.5             |                  |
|                       | Nominal | 13.0                                      | 12.0             |                  |
| IEEE 802.11ac (5 GHz) | Maximum | 13.5                                      | 12.5             | 11.5             |
|                       | Nominal | 13.0                                      | 12.0             | 11.0             |
| Mode / Band           |         | Modulated Average - MIMO (dBm)            |                  |                  |
|                       |         | 20 MHz Bandwidth                          | 40 MHz Bandwidth | 80 MHz Bandwidth |
| IEEE 802.11n (5 GHz)  | Maximum | 16.5                                      | 15.5             |                  |
|                       | Nominal | 16.0                                      | 15.0             |                  |
| IEEE 802.11ac (5 GHz) | Maximum | 16.5                                      | 15.5             | 14.5             |
|                       | Nominal | 16.0                                      | 15.0             | 14.0             |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 5 of 119                                                                         |                                        |

**BT/WLAN - Reduced Power - Held to Ear:**

| Mode / Band                    |         | Modulated Average (dBm) |  |
|--------------------------------|---------|-------------------------|--|
| IEEE 802.11b<br>(2.4 GHz SISO) | Maximum | 15.5                    |  |
|                                | Nominal | 15.0                    |  |
| IEEE 802.11g<br>(2.4 GHz SISO) | Maximum | 13.5                    |  |
|                                | Nominal | 13.0                    |  |
| IEEE 802.11n<br>(2.4 GHz SISO) | Maximum | 13.5                    |  |
|                                | Nominal | 13.0                    |  |
| IEEE 802.11n<br>(2.4 GHz MIMO) | Maximum | 16.5                    |  |
|                                | Nominal | 16.0                    |  |

| Mode / Band           |         | Modulated Average (dBm) |                  |                  |
|-----------------------|---------|-------------------------|------------------|------------------|
|                       |         | 20 MHz Bandwidth        | 40 MHz Bandwidth | 80 MHz Bandwidth |
| IEEE 802.11a (5 GHz)  | Maximum | 10.5                    |                  |                  |
|                       | Nominal | 10.0                    |                  |                  |
| IEEE 802.11n (5 GHz)  | Maximum | 9.5                     | 9.5              |                  |
|                       | Nominal | 9.0                     | 9.0              |                  |
| IEEE 802.11ac (5 GHz) | Maximum | 9.5                     | 9.5              | 9.5              |
|                       | Nominal | 9.0                     | 9.0              | 9.0              |

| Mode / Band           |         | Modulated Average - MIMO (dBm) |                  |                  |
|-----------------------|---------|--------------------------------|------------------|------------------|
|                       |         | 20 MHz Bandwidth               | 40 MHz Bandwidth | 80 MHz Bandwidth |
| IEEE 802.11n (5 GHz)  | Maximum | 12.5                           | 12.5             |                  |
|                       | Nominal | 12.0                           | 12.0             |                  |
| IEEE 802.11ac (5 GHz) | Maximum | 12.5                           | 12.5             | 12.5             |
|                       | Nominal | 12.0                           | 12.0             | 12.0             |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 6 of 119                                                                         |                                        |

## 1.4 DUT Antenna Locations

Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC Filing. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.” A diagram showing the location of the device antennas can be found in appendix F.

**Table 1-1**  
**Mobile Sides for SAR Testing**

| Mode               | Condition         | Back | Front | Top | Bottom | Right | Left |
|--------------------|-------------------|------|-------|-----|--------|-------|------|
| GPRS 850           | Hotspot           | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| UMTS 850           | Hotspot           | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| GPRS 1900          | Hotspot/Extremity | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| UMTS 1900          | Hotspot/Extremity | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| Cell. EVDO         | Hotspot           | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| PCS EVDO           | Hotspot/Extremity | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| LTE Band 13        | Hotspot           | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| LTE Band 5 (Cell)  | Hotspot           | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| LTE Band 4 (AWS)   | Hotspot/Extremity | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| LTE Band 2 (PCS)   | Hotspot/Extremity | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| 2.4 GHz WLAN       | Hotspot           | Yes  | Yes   | Yes | No     | No    | Yes  |
| U-NII-2A, U-NII-2C | Extremity         | Yes  | Yes   | Yes | No     | No    | Yes  |
| U-NII-3            | Hotspot           | Yes  | Yes   | Yes | No     | No    | Yes  |

Note: Particular DUT edges were not required to be evaluated for Wireless Router SAR or Extremity SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02 guidance, page 2 and FCC KDB 648474 D04v01r02. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, and U-NII-2C WLAN operations are disabled.

## 1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in appendix F.

## 1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in

Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



**Figure 1-1**  
**Simultaneous Transmission Paths**

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 7 of 119                   |

**Table 1-2**  
**Simultaneous Transmission Scenarios**

| No. | Capable Transmit Configuration                         | Head | Body-Worn Accessory | Wireless Router | Extremity | Notes                                              |
|-----|--------------------------------------------------------|------|---------------------|-----------------|-----------|----------------------------------------------------|
| 1   | 1x CDMA voice + 2.4 GHz Wi-Fi                          | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 2   | 1x CDMA voice + 5 GHz Wi-Fi                            | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 3   | 1x CDMA voice + 2.4 GHz Bluetooth                      | N/A  | Yes                 | N/A             | Yes       |                                                    |
| 4   | 1x CDMA voice + 2.4 GHz WIFI MIMO                      | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 5   | 1x CDMA voice + 5 GHz WIFI MIMO                        | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 6   | 1x CDMA voice + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 2  | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 7   | 1x CDMA voice + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 1  | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 8   | GSM voice + 2.4 GHz Wi-Fi                              | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 9   | GSM voice + 5 GHz Wi-Fi                                | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 10  | GSM voice + 2.4 GHz Bluetooth                          | N/A  | Yes                 | N/A             | Yes       |                                                    |
| 11  | GSM voice + 2.4 GHz WIFI MIMO                          | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 12  | GSM voice + 5 GHz WIFI MIMO                            | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 13  | GSM voice + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 2      | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 14  | GSM voice + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 1      | Yes  | Yes                 | N/A             | Yes       |                                                    |
| 15  | UMTS + 2.4 GHz Wi-Fi                                   | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 16  | UMTS + 5 GHz Wi-Fi                                     | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 17  | UMTS + 2.4 GHz Bluetooth                               | N/A  | Yes                 | N/A             | Yes       |                                                    |
| 18  | UMTS + 2.4 GHz WIFI MIMO                               | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 19  | UMTS + 5 GHz WIFI MIMO                                 | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 20  | UMTS + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 2           | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 21  | UMTS + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 1           | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 22  | LTE + 2.4 GHz Wi-Fi                                    | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 23  | LTE + 5 GHz Wi-Fi                                      | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 24  | LTE + 2.4 GHz Bluetooth                                | N/A  | Yes                 | N/A             | Yes       |                                                    |
| 25  | LTE + 2.4 GHz WIFI MIMO                                | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 26  | LTE + 5 GHz WIFI MIMO                                  | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 27  | LTE + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 2            | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 28  | LTE + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 1            | Yes  | Yes                 | Yes             | Yes       |                                                    |
| 29  | CDMA/EVDO data + 2.4 GHz Wi-Fi                         | Yes* | Yes*                | Yes             | Yes       | * - Pre-installed VOIP applications are considered |
| 30  | CDMA/EVDO data + 5 GHz Wi-Fi                           | Yes* | Yes*                | Yes             | Yes       | * - Pre-installed VOIP applications are considered |
| 31  | CDMA/EVDO data + 2.4 GHz Bluetooth                     | N/A  | Yes*                | N/A             | Yes       | * - Pre-installed VOIP applications are considered |
| 32  | CDMA/EVDO data + 2.4 GHz WIFI MIMO                     | Yes* | Yes*                | Yes             | Yes       | * - Pre-installed VOIP applications are considered |
| 33  | CDMA/EVDO data + 5 GHz WIFI MIMO                       | Yes* | Yes*                | Yes             | Yes       | * - Pre-installed VOIP applications are considered |
| 34  | CDMA/EVDO data + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 2 | Yes* | Yes*                | Yes             | Yes       | * - Pre-installed VOIP applications are considered |
| 35  | CDMA/EVDO data + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 1 | Yes* | Yes*                | Yes             | Yes       | * - Pre-installed VOIP applications are considered |
| 36  | GPRS/EDGE + 2.4 GHz Wi-Fi                              | N/A  | N/A                 | Yes             | Yes       |                                                    |
| 37  | GPRS/EDGE + 5 GHz Wi-Fi                                | N/A  | N/A                 | Yes             | Yes       |                                                    |
| 38  | GPRS/EDGE + 2.4 GHz WIFI MIMO                          | N/A  | N/A                 | Yes             | Yes       |                                                    |
| 39  | GPRS/EDGE + 5 GHz WIFI MIMO                            | N/A  | N/A                 | Yes             | Yes       |                                                    |
| 40  | GPRS/EDGE + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 2      | N/A  | N/A                 | Yes             | Yes       |                                                    |
| 41  | GPRS/EDGE + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 1      | N/A  | N/A                 | Yes             | Yes       |                                                    |
| 42  | GSM voice + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 1      | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 43  | GSM voice + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 2      | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 44  | 1x CDMA voice + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 1  | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 45  | 1x CDMA voice + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 2  | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 46  | UMTS + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 1           | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 47  | UMTS + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 2           | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 48  | LTE + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 1            | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 49  | LTE + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 2            | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 50  | GPRS/EDGE + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 1      | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 51  | GPRS/EDGE + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 2      | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 52  | CDMA/EVDO data + 2.4 GHz WIFI Ant 1 + 5 GHz WIFI Ant 1 | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |
| 53  | CDMA/EVDO data + 2.4 GHz WIFI Ant 2 + 5 GHz WIFI Ant 2 | N/A  | N/A                 | N/A             | N/A       | Not Supported by HW                                |

1. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCC]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
2. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there is no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
3. 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
4. This device supports 2x2 MIMO Tx for IEEE 802.11n/ac.
5. 2.4 GHz WLAN, 5 GHz WLAN, and 2.4 GHz Bluetooth that share the same antenna path cannot transmit simultaneously.
6. All licensed modes share the same antenna and cannot transmit simultaneously.
7. This device supports VoLTE.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 8 of 119                   |

## 1.7 SAR Test Exclusions Applied

### (A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02.

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg for 1g SAR and is less than 3.0 W/kg for 10g SAR, SAR is not required for U-NII-1 band according to FCC KDB 248227 D01v02r01.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) Band gap channels are supported
- f) TDWR channels are supported

Per FCC KDB 447498 D01v05, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency (GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required;  $[(11/15) * \sqrt{2.480}] = 1.2 < 3.0$ . Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

Per FCC KDB 447498 D01v05, the 10g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency (GHz)}} \leq 7.5$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, extremity Bluetooth SAR was not required;  $[(11/5) * \sqrt{2.480}] = 3.5 < 7.5$ . Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

Per FCC KDB Publication 648474 D04v01r01, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode scaled to the maximum output power (including tolerance) is 1-g SAR > 1.2 W/kg.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 9 of 119                          |

## Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v02.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r03.

This device supports intra-band and inter-band LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r01, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

Per FCC KDB Publication 648474 D04v01r01, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode scaled to the maximum output power (including tolerance) is 1-g SAR > 1.2 W/kg. For some modes, Extremity SAR was additionally evaluated at maximum output power due to reduced power (See Section 6.7 for more information).

## 1.8 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01v03, D05v02r03, D06v02 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r01 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05r02 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r03, D02v01r01 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r02 (Phablet Procedures)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 10 of 119                         |

## 1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

|                    | Head<br>Serial Number | Body-Worn<br>Serial Number | Hotspot<br>Serial Number | Extremity Sensor<br>Not Active<br>Serial Number | Extremity Sensor<br>Active<br>Serial Number |
|--------------------|-----------------------|----------------------------|--------------------------|-------------------------------------------------|---------------------------------------------|
| GSM/GPRS/EDGE 850  | 96361                 | 9635F                      | 9635F                    | -                                               | -                                           |
| UMTS 850           | 96361                 | 9635F                      | 9635F                    | -                                               | -                                           |
| GSM/GPRS/EDGE 1900 | 9635F                 | 9635F                      | 930ED                    | 9635F                                           | 930ED                                       |
| UMTS 1900          | 9635F                 | 9635F                      | 930ED                    | 9635F                                           | 930ED                                       |
| Cell. CDMA/EVDO    | 96361                 | 9660B                      | 9660B                    | -                                               | -                                           |
| PCS CDMA/EVDO      | 9660B, 930ED          | 9660B                      | 930ED                    | 9660B                                           | 930ED                                       |
| LTE Band 13        | 96361                 | 96361                      | 96361                    | -                                               | -                                           |
| LTE Band 5 (Cell)  | 96361                 | 96361                      | 96361                    | -                                               | -                                           |
| LTE Band 4 (AWS)   | 96361                 | 96361                      | 930ED                    | 96361                                           | 930ED                                       |
| LTE Band 2 (PCS)   | 96361                 | 96361                      | 930ED                    | 96361                                           | 930ED                                       |
| 2.4 GHz WLAN       | 9587C                 | 9587C                      | 9587C                    | -                                               | -                                           |
| 5 GHz WLAN         | 9587C                 | 9587C                      | 9587C                    | 9587C                                           | -                                           |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 11 of 119                                                                        |                                        |

## 2

## LTE INFORMATION

| LTE Information                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                |                |
|-------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------------|
| FCC ID                                                                                                            | A3LSMG928V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                |                |
| Form Factor                                                                                                       | Portable Handset                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                |                |
| Frequency Range of each LTE transmission band                                                                     | LTE Band 13 (779.5 - 784.5 MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                |                |
|                                                                                                                   | LTE Band 5 (Cell) (824.7 - 848.3 MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                |                |
|                                                                                                                   | LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                |                |
|                                                                                                                   | LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                |                |
| Channel Bandwidths                                                                                                | LTE Band 13: 5 MHz, 10 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                |                |
|                                                                                                                   | LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                              |                |                |
|                                                                                                                   | LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz                                                                                                                                                                                                                                                                                                                                                                                                                               |                |                |
|                                                                                                                   | LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz                                                                                                                                                                                                                                                                                                                                                                                                                               |                |                |
| Channel Numbers and Frequencies (MHz)                                                                             | Low                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Mid            | High           |
| LTE Band 13: 5 MHz                                                                                                | 779.5 (23205)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 782 (23230)    | 784.5 (23255)  |
| LTE Band 13: 10 MHz                                                                                               | 782 (23230)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 782 (23230)    | 782 (23230)    |
| LTE Band 5 (Cell): 1.4 MHz                                                                                        | 824.7 (20407)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 836.5 (20525)  | 848.3 (20643)  |
| LTE Band 5 (Cell): 3 MHz                                                                                          | 825.5 (20415)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 836.5 (20525)  | 847.5 (20635)  |
| LTE Band 5 (Cell): 5 MHz                                                                                          | 826.5 (20425)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 836.5 (20525)  | 846.5 (20625)  |
| LTE Band 5 (Cell): 10 MHz                                                                                         | 829 (20450)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 836.5 (20525)  | 844 (20600)    |
| LTE Band 4 (AWS): 1.4 MHz                                                                                         | 1710.7 (19957)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1732.5 (20175) | 1754.3 (20393) |
| LTE Band 4 (AWS): 3 MHz                                                                                           | 1711.5 (19965)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1732.5 (20175) | 1753.5 (20385) |
| LTE Band 4 (AWS): 5 MHz                                                                                           | 1712.5 (19975)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1732.5 (20175) | 1752.5 (20375) |
| LTE Band 4 (AWS): 10 MHz                                                                                          | 1715 (20000)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1732.5 (20175) | 1750 (20350)   |
| LTE Band 4 (AWS): 15 MHz                                                                                          | 1717.5 (20025)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1732.5 (20175) | 1747.5 (20325) |
| LTE Band 4 (AWS): 20 MHz                                                                                          | 1720 (20050)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1732.5 (20175) | 1745 (20300)   |
| LTE Band 2 (PCS): 1.4 MHz                                                                                         | 1850.7 (18607)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1880 (18900)   | 1909.3 (19193) |
| LTE Band 2 (PCS): 3 MHz                                                                                           | 1851.5 (18615)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1880 (18900)   | 1908.5 (19185) |
| LTE Band 2 (PCS): 5 MHz                                                                                           | 1852.5 (18625)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1880 (18900)   | 1907.5 (19175) |
| LTE Band 2 (PCS): 10 MHz                                                                                          | 1855 (18650)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1880 (18900)   | 1905 (19150)   |
| LTE Band 2 (PCS): 15 MHz                                                                                          | 1857.5 (18675)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1880 (18900)   | 1902.5 (19125) |
| LTE Band 2 (PCS): 20 MHz                                                                                          | 1860 (18700)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1880 (18900)   | 1900 (19100)   |
| UE Category                                                                                                       | 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                |                |
| Modulations Supported in UL                                                                                       | QPSK, 16QAM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                |                |
| LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided) | YES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                |                |
| A-MPR (Additional MPR) disabled for SAR Testing?                                                                  | YES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                |                |
| LTE Carrier Aggregation Possible Combinations                                                                     | The technical description includes all possible carrier aggregation combinations.                                                                                                                                                                                                                                                                                                                                                                                                             |                |                |
| LTE Release 10 Additional Information                                                                             | This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. Due to carrier capability, only the combinations listed above are supported. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA. |                |                |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 12 of 119                                                                        |                                 |

### 3

## INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

### 3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1**  
**SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dv} \right)$$

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m<sup>3</sup>)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 13 of 119                         |

## 4 DOSIMETRIC ASSESSMENT

### 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.



**Figure 4-1**  
Sample SAR Area Scan

**Table 4-1**  
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01\*

| Frequency | Maximum Area Scan Resolution (mm)<br>( $\Delta x_{\text{area}}, \Delta y_{\text{area}}$ ) | Maximum Zoom Scan Resolution (mm)<br>( $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$ ) | Maximum Zoom Scan Spatial Resolution (mm)   |                               |                                     | Minimum Zoom Scan Volume (mm)<br>(x,y,z) |
|-----------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|---------------------------------------------|-------------------------------|-------------------------------------|------------------------------------------|
|           |                                                                                           |                                                                                           | Uniform Grid<br>$\Delta z_{\text{zoom}}(n)$ | Graded Grid                   |                                     |                                          |
|           |                                                                                           |                                                                                           |                                             | $\Delta z_{\text{zoom}}(1)^*$ | $\Delta z_{\text{zoom}}(n>1)^*$     |                                          |
| ≤2 GHz    | ≤15                                                                                       | ≤8                                                                                        | ≤5                                          | ≤4                            | ≤1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥30                                      |
| 2-3 GHz   | ≤12                                                                                       | ≤5                                                                                        | ≤5                                          | ≤4                            | ≤1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥30                                      |
| 3-4 GHz   | ≤12                                                                                       | ≤5                                                                                        | ≤4                                          | ≤3                            | ≤1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥28                                      |
| 4-5 GHz   | ≤10                                                                                       | ≤4                                                                                        | ≤3                                          | ≤2.5                          | ≤1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥25                                      |
| 5-6 GHz   | ≤10                                                                                       | ≤4                                                                                        | ≤2                                          | ≤2                            | ≤1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥22                                      |

\*Also compliant to IEEE 1528-2013 Table 6


|                                   |                                                                                     |                               |  |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |  | Page 14 of 119                                                                        |                                 |

## 5

## DEFINITION OF REFERENCE POINTS

### 5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




**Figure 5-1**  
Close-Up Side view  
of ERP

### 5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



**Figure 5-2**  
Front, back and side view of SAM Twin Phantom



**Figure 5-3**  
Handset Vertical Center & Horizontal Line Reference Points


|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 15 of 119                  |

### 6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ .

### 6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.



**Figure 6-1 Front, Side and Top View of Cheek Position**


2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

### 6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 16 of 119                         |



## 6.5 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v05 should be applied to determine SAR test requirements.

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04 v01r02 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna  $\leq 25$  mm from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode scaled to the maximum output power (including tolerance) is 1-g SAR > 1.2 W/kg.

## 6.6 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02 where SAR test considerations for handsets ( $L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$ ) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

There is power reduction for some bands and modes, as indicated in Section 1.3. The reduced powers were confirmed via conducted power measurements at the RF port (See Section 9). Detailed description of the hotspot power reduction mechanism are included in the operational description

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 18 of 119                  |

## 6.7 Additional Test Positions due to Proximity Conditions

This device uses a sensor to reduce output powers in extremity (hand-held) use conditions.

When the sensor detects a user is touching the device on or near to the antenna the device reduces the maximum allowed output power. However, the proximity sensor is not active when the device is moved beyond the sensor triggering distance and the maximum output power is no longer limited. Therefore, an additional exposure condition is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a non-reduced output power level.

FCC KDB 616217 D04 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional exposure conditions. The smallest separation distance determined by the sensor triggering and sensor coverage for each applicable edge, minus 1 mm, was used as the test separation distance for SAR testing. Sensor triggering distance summary data is included in Appendix G.

The proximity sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the proximity sensor entirely covers the antenna.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 19 of 119                         |

## 7 RF EXPOSURE LIMITS

### 7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1**  
**SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

| HUMAN EXPOSURE LIMITS                                               |                                                                           |                                                                   |
|---------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------|
|                                                                     | UNCONTROLLED ENVIRONMENT<br><i>General Population</i><br>(W/kg) or (mW/g) | CONTROLLED ENVIRONMENT<br><i>Occupational</i><br>(W/kg) or (mW/g) |
| <b>Peak Spatial Average SAR</b><br>Head                             | 1.6                                                                       | 8.0                                                               |
| <b>Whole Body SAR</b>                                               | 0.08                                                                      | 0.4                                                               |
| <b>Peak Spatial Average SAR</b><br>Hands, Feet, Ankle, Wrists, etc. | 4.0                                                                       | 20                                                                |

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 20 of 119                         |

### 8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

### 8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is  $\leq 0.25$  dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is  $\leq 1.2$  W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

### 8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

### 8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03 “3G SAR Measurement Procedures.”

#### 8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 21 of 119                  |

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH<sub>0</sub> and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH<sub>0</sub> data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

**Table 8-1**  
**Parameters for Max. Power for RC1**

| Parameter                    | Units        | Value |
|------------------------------|--------------|-------|
| $I_{or}$                     | dBm/1.23 MHz | -104  |
| $\frac{Pilot E_c}{I_{or}}$   | dB           | -7    |
| $\frac{Traffic E_c}{I_{or}}$ | dB           | -7.4  |

**Table 8-2**  
**Parameters for Max. Power for RC3**

| Parameter                    | Units        | Value |
|------------------------------|--------------|-------|
| $I_{or}$                     | dBm/1.23 MHz | -86   |
| $\frac{Pilot E_c}{I_{or}}$   | dB           | -7    |
| $\frac{Traffic E_c}{I_{or}}$ | dB           | -7.4  |

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

## 8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at fullrate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

## 8.4.3 Body-worn SAR Measurements

SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH<sub>n</sub>), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH<sub>n</sub>), with FCH at full rate and SCH<sub>0</sub> enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

## 8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with Ev-Do capabilities, the 3G SAR test reduction procedure is applied to Ev-Do Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 22 of 119                                                                        |                                 |

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

#### 8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For Ev-Do data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with Ev-Do Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

### 8.5 SAR Measurement Conditions for UMTS

#### 8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCH<sub>n</sub> and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

#### 8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

#### 8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH<sub>n</sub> configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH<sub>n</sub>, for the highest reported SAR configuration in 12.2 kbps RMC.

#### 8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 23 of 119                                                                        |                                 |

### 8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

## 8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r03 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### 8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

### 8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 24 of 119                                                                        |                                        |

## 8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r03:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $< 0.8$  W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to  $\frac{1}{2}$  dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.

## 8.6.5 Downlink Carrier Aggregation

LTE Carrier Aggregation (CA) measurements are made in accordance to 3GPP TS 36.521-1 V10.4.0 (2012-12). The RRC connection is only handled by one cell, the Primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds the Secondary component carrier (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to release 8 specifications on the PCC. Additional output powers are measured using two carriers in the downlink for the release 8 configurations with the highest output power among all channels, RB configurations and bandwidths for each uplink band. Per FCC KDB Publication 941225 D05A v01r01, no SAR measurements are required when the average output power with downlink carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink carrier aggregation inactive.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 25 of 119                         |

## 8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r01 for more details.

### 8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

### 8.7.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is  $> 1.2$  W/kg for 1g SAR or  $> 3.0$  for 10g SAR. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is  $> 1.2$  W/kg for 1g SAR or  $> 3.0$  for 10g SAR.

### 8.7.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification.

Unless band gap channels are permanently disabled, SAR must be considered for these channels

### 8.7.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg for 1g SAR or  $\leq 1.0$  W/kg for 10g SAR, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg for 1g SAR or  $\leq 2.0$  W/kg for 10g SAR or all test positions are measured.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 26 of 119                         |

### 8.7.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg for 1g SAR or  $\leq 2.0$  W/kg for 10g SAR, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is  $> 0.8$  W/kg for 1g SAR or  $> 2.0$  W/kg for 10g SAR, SAR is required for that position using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg for 1g SAR or  $> 3.0$  W/kg for 10g SAR, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is  $> 1.2$  W/kg for 1g SAR or  $> 3.0$  W/kg for 10g SAR. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

### 8.7.6 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz and 5 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate and lowest order 802.11a/g/n/ac mode. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 27 of 119                                                                        |                                        |

### 8.7.7 Initial Test Configuration Procedure

For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation and lowest data rate and lowest order 802.11a/g/n/ac mode. If the average RF output powers of the highest identical transmission modes are within 0.25 dB of each other, mid channel of the transmission mode with highest average RF output power is the initial test channel. Otherwise, the channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is  $\leq 0.8$  W/kg for 1g SAR or  $\leq 2.0$  W/kg for 10g SAR, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is  $\leq 1.2$  W/kg for 1g or  $\leq 3.0$  W/kg for 10g and all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.5).

### 8.7.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is  $\leq 1.2$  W/kg for 1g SAR and  $\leq 3.0$  W/kg for 10g SAR, no additional SAR tests for the subsequent test configurations are required.

### 8.7.9 MIMO SAR considerations

Per KDB 248227 D01v02r01, the simultaneous SAR provisions in KDB Publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is  $< 1.6$  W/kg for 1g SAR or  $\leq 4.0$  W/kg for 10g SAR, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 28 of 119                         |

## 9 RF CONDUCTED POWERS

### 9.1 GSM Conducted Powers

**Table 9-1**  
**Maximum Average RF Output Powers**

|          |                       | Maximum Burst-Averaged Output Power            |                            |                            |                            |                            |                            |                            |                            |                            |
|----------|-----------------------|------------------------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
|          |                       | Voice                                          | GPRS/EDGE Data (GMSK)      |                            |                            |                            | EDGE Data (8-PSK)          |                            |                            |                            |
| Band     | Channel               | GSM [dBm]<br>CS<br>(1 Slot)                    | GPRS [dBm]<br>1 Tx<br>Slot | GPRS [dBm]<br>2 Tx<br>Slot | GPRS [dBm]<br>3 Tx<br>Slot | GPRS [dBm]<br>4 Tx<br>Slot | EDGE [dBm]<br>1 Tx<br>Slot | EDGE [dBm]<br>2 Tx<br>Slot | EDGE [dBm]<br>3 Tx<br>Slot | EDGE [dBm]<br>4 Tx<br>Slot |
| GSM 850  | 128                   | 32.99                                          | 33.04                      | 31.60                      | 29.74                      | 27.30                      | 26.97                      | 25.41                      | 23.35                      | 22.10                      |
|          | 190                   | 33.12                                          | 33.16                      | 31.79                      | 29.97                      | 26.90                      | 27.17                      | 25.60                      | 23.49                      | 22.20                      |
|          | 251                   | 32.81                                          | 32.86                      | 31.89                      | 29.80                      | 27.20                      | 27.14                      | 25.53                      | 23.43                      | 22.40                      |
| GSM 1900 | 512                   | 29.62                                          | 29.72                      | 28.96                      | 26.23                      | 25.67                      | 25.60                      | 24.51                      | 22.50                      | 21.40                      |
|          | 661                   | 29.68                                          | 29.82                      | 29.04                      | 26.25                      | 25.64                      | 25.59                      | 24.62                      | 22.40                      | 21.42                      |
|          | 810                   | 29.65                                          | 29.75                      | 29.11                      | 26.22                      | 25.63                      | 25.69                      | 24.65                      | 22.30                      | 21.50                      |
|          |                       | Calculated Maximum Frame-Averaged Output Power |                            |                            |                            |                            |                            |                            |                            |                            |
|          |                       | Voice                                          | GPRS/EDGE Data (GMSK)      |                            |                            |                            | EDGE Data (8-PSK)          |                            |                            |                            |
| Band     | Channel               | GSM [dBm]<br>CS<br>(1 Slot)                    | GPRS [dBm]<br>1 Tx<br>Slot | GPRS [dBm]<br>2 Tx<br>Slot | GPRS [dBm]<br>3 Tx<br>Slot | GPRS [dBm]<br>4 Tx<br>Slot | EDGE [dBm]<br>1 Tx<br>Slot | EDGE [dBm]<br>2 Tx<br>Slot | EDGE [dBm]<br>3 Tx<br>Slot | EDGE [dBm]<br>4 Tx<br>Slot |
| GSM 850  | 128                   | 23.96                                          | 24.01                      | 25.58                      | 25.48                      | 24.29                      | 17.94                      | 19.39                      | 19.09                      | 19.09                      |
|          | 190                   | 24.09                                          | 24.13                      | 25.77                      | 25.71                      | 23.89                      | 18.14                      | 19.58                      | 19.23                      | 19.19                      |
|          | 251                   | 23.78                                          | 23.83                      | 25.87                      | 25.54                      | 24.19                      | 18.11                      | 19.51                      | 19.17                      | 19.39                      |
| GSM 1900 | 512                   | 20.59                                          | 20.69                      | 22.94                      | 21.97                      | 22.66                      | 16.57                      | 18.49                      | 18.24                      | 18.39                      |
|          | 661                   | 20.65                                          | 20.79                      | 23.02                      | 21.99                      | 22.63                      | 16.56                      | 18.60                      | 18.14                      | 18.41                      |
|          | 810                   | 20.62                                          | 20.72                      | 23.09                      | 21.96                      | 22.62                      | 16.66                      | 18.63                      | 18.04                      | 18.49                      |
| GSM 850  | Frame<br>Avg.Targets: | 23.97                                          | 23.97                      | 25.48                      | 25.24                      | 24.99                      | 17.97                      | 19.98                      | 18.74                      | 18.99                      |
| GSM 1900 |                       | 20.97                                          | 20.97                      | 22.98                      | 22.74                      | 22.99                      | 16.97                      | 18.98                      | 17.74                      | 17.99                      |

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 29 of 119                  |

**Table 9-2**  
**Reduced Average RF Output Powers – Hotspot, Extremity**

|          |                    | Maximum Burst-Averaged Output Power            |                         |                         |                         |                         |                         |                         |                         |                         |
|----------|--------------------|------------------------------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
|          |                    | Voice                                          | GPRS/EDGE Data (GMSK)   |                         |                         |                         | EDGE Data (8-PSK)       |                         |                         |                         |
| Band     | Channel            | GSM [dBm]<br>CS (1 Slot)                       | GPRS [dBm]<br>1 Tx Slot | GPRS [dBm]<br>2 Tx Slot | GPRS [dBm]<br>3 Tx Slot | GPRS [dBm]<br>4 Tx Slot | EDGE [dBm]<br>1 Tx Slot | EDGE [dBm]<br>2 Tx Slot | EDGE [dBm]<br>3 Tx Slot | EDGE [dBm]<br>4 Tx Slot |
| GSM 1900 | 512                | 27.80                                          | 27.86                   | 25.50                   | 22.99                   | 22.00                   | 26.29                   | 25.34                   | 22.30                   | 21.07                   |
|          | 661                | 27.66                                          | 27.65                   | 25.08                   | 23.13                   | 21.57                   | 26.15                   | 25.01                   | 22.02                   | 20.81                   |
|          | 810                | 27.71                                          | 27.75                   | 25.17                   | 22.70                   | 21.59                   | 26.17                   | 25.21                   | 22.06                   | 20.72                   |
|          |                    | Calculated Maximum Frame-Averaged Output Power |                         |                         |                         |                         |                         |                         |                         |                         |
|          |                    | Voice                                          | GPRS/EDGE Data (GMSK)   |                         |                         |                         | EDGE Data (8-PSK)       |                         |                         |                         |
| Band     | Channel            | GSM [dBm]<br>CS (1 Slot)                       | GPRS [dBm]<br>1 Tx Slot | GPRS [dBm]<br>2 Tx Slot | GPRS [dBm]<br>3 Tx Slot | GPRS [dBm]<br>4 Tx Slot | EDGE [dBm]<br>1 Tx Slot | EDGE [dBm]<br>2 Tx Slot | EDGE [dBm]<br>3 Tx Slot | EDGE [dBm]<br>4 Tx Slot |
| GSM 1900 | 512                | 18.77                                          | 18.83                   | 19.48                   | 18.73                   | 18.99                   | 17.26                   | 19.32                   | 18.04                   | 18.06                   |
|          | 661                | 18.63                                          | 18.62                   | 19.06                   | 18.87                   | 18.56                   | 17.12                   | 18.99                   | 17.76                   | 17.80                   |
|          | 810                | 18.68                                          | 18.72                   | 19.15                   | 18.44                   | 18.58                   | 17.14                   | 19.19                   | 17.80                   | 17.71                   |
| GSM 1900 | Frame Avg.Targets: | 18.97                                          | 18.97                   | 18.98                   | 18.74                   | 18.49                   | 16.97                   | 18.98                   | 17.74                   | 17.99                   |

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.
- GSM Voice Powers are supported with Hotspot Mode On.

**GSM Class: B**  
**GPRS Multislot class: 33 (Max 4 Tx uplink slots)**  
**EDGE Multislot class: 33 (Max 4 Tx uplink slots)**  
**DTM Multislot Class: N/A**



**Figure 9-1**  
**Power Measurement Setup**

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 30 of 119                                                                        |                                 |

## 9.2 UMTS Conducted Powers

**Table 9-3**  
**Maximum Average RF Output Powers**

| 3GPP Release Version | Mode  | 3GPP 34.121 Subtest | Cellular Band [dBm] |       |       | PCS Band [dBm] |       |       | 3GPP MPR [dB] |
|----------------------|-------|---------------------|---------------------|-------|-------|----------------|-------|-------|---------------|
|                      |       |                     | 4132                | 4183  | 4233  | 9262           | 9400  | 9538  |               |
| 99                   | WCDMA | 12.2 kbps RMC       | 23.31               | 23.38 | 23.26 | 23.34          | 23.22 | 23.12 | -             |
| 99                   |       | 12.2 kbps AMR       | 23.27               | 23.36 | 23.22 | 23.28          | 23.20 | 23.09 | -             |
| 6                    | HSDPA | Subtest 1           | 22.13               | 22.29 | 22.04 | 22.27          | 21.97 | 21.73 | 0             |
| 6                    |       | Subtest 2           | 22.18               | 22.31 | 22.04 | 22.24          | 21.96 | 21.77 | 0             |
| 6                    |       | Subtest 3           | 21.65               | 21.78 | 21.53 | 21.72          | 21.43 | 21.23 | 0.5           |
| 6                    |       | Subtest 4           | 21.64               | 21.75 | 21.52 | 21.75          | 21.43 | 21.22 | 0.5           |
| 6                    | HSUPA | Subtest 1           | 21.86               | 22.02 | 21.75 | 21.78          | 21.50 | 21.52 | 0             |
| 6                    |       | Subtest 2           | 20.82               | 20.68 | 20.46 | 21.05          | 20.80 | 20.61 | 2             |
| 6                    |       | Subtest 3           | 21.03               | 20.59 | 20.95 | 21.19          | 20.91 | 20.71 | 1             |
| 6                    |       | Subtest 4           | 21.15               | 21.79 | 21.54 | 21.27          | 21.50 | 21.31 | 2             |
| 6                    |       | Subtest 5           | 21.56               | 21.71 | 21.44 | 22.26          | 22.02 | 21.80 | 0             |

**Table 9-4**  
**Hotspot Reduced Average RF Output Powers – Hotspot, Extremity**

| 3GPP Release Version | Mode  | 3GPP 34.121 Subtest | PCS Band [dBm] |       |       | 3GPP MPR [dB] |
|----------------------|-------|---------------------|----------------|-------|-------|---------------|
|                      |       |                     | 9262           | 9400  | 9538  |               |
| 99                   | WCDMA | 12.2 kbps RMC       | 19.82          | 19.77 | 19.74 | -             |
| 99                   |       | 12.2 kbps AMR       | 19.84          | 19.79 | 19.75 | -             |
| 6                    | HSDPA | Subtest 1           | 18.69          | 18.70 | 18.70 | 0             |
| 6                    |       | Subtest 2           | 18.73          | 18.68 | 18.66 | 0             |
| 6                    |       | Subtest 3           | 18.19          | 18.08 | 18.13 | 0.5           |
| 6                    |       | Subtest 4           | 18.15          | 18.11 | 18.17 | 0.5           |
| 6                    | HSUPA | Subtest 1           | 18.59          | 18.71 | 18.09 | 0             |
| 6                    |       | Subtest 2           | 17.63          | 17.69 | 17.70 | 2             |
| 6                    |       | Subtest 3           | 17.56          | 17.46 | 17.50 | 1             |
| 6                    |       | Subtest 4           | 18.18          | 17.95 | 17.98 | 2             |
| 6                    |       | Subtest 5           | 18.48          | 18.57 | 18.60 | 0             |

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.



**Figure 9-2**  
**Power Measurement Setup**

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 31 of 119                                                                        |                                 |

### 9.3 CDMA2000 Conducted Powers

**Table 9-5**  
**Maximum Average RF Output Powers**

| Band     | Channel | Rule Part | Frequency | SO55 [dBm] | SO55 [dBm] | TDSO SO32 [dBm] | TDSO SO32 [dBm] | 1x EvDO Rev. 0 [dBm] | 1x EvDO Rev. A [dBm] |
|----------|---------|-----------|-----------|------------|------------|-----------------|-----------------|----------------------|----------------------|
|          | F-RC    |           | MHz       | RC1        | RC3        | FCH+SCH         | FCH             | (RTAP)               | (RETAP)              |
| Cellular | 1013    | 22H       | 824.7     | 24.71      | 24.73      | 24.80           | 24.81           | 24.85                | 24.83                |
|          | 384     | 22H       | 836.52    | 24.81      | 24.80      | 24.93           | 24.94           | 24.99                | 24.79                |
|          | 777     | 22H       | 848.31    | 24.87      | 24.91      | 24.92           | 24.94           | 24.95                | 24.79                |
| PCS      | 25      | 24E       | 1851.25   | 24.48      | 24.46      | 24.49           | 24.50           | 24.50                | 24.49                |
|          | 600     | 24E       | 1880      | 24.26      | 24.25      | 24.23           | 24.24           | 24.26                | 24.13                |
|          | 1175    | 24E       | 1908.75   | 24.46      | 24.44      | 24.42           | 24.49           | 24.45                | 24.42                |

Note: RC1 is only applicable for IS-95 compatibility.

**Table 9-6**  
**Reduced Average RF Output Powers – Head, Hotspot, Extremity**

| Band | Channel | Rule Part | Frequency | SO55 [dBm] | SO55 [dBm] | TDSO SO32 [dBm] | TDSO SO32 [dBm] | 1x EvDO Rev. 0 [dBm] | 1x EvDO Rev. A [dBm] |
|------|---------|-----------|-----------|------------|------------|-----------------|-----------------|----------------------|----------------------|
|      | F-RC    |           | MHz       | RC1        | RC3        | FCH+SCH         | FCH             | (RTAP)               | (RETAP)              |
| PCS  | 25      | 24E       | 1851.25   | 20.10      | 20.06      | 20.12           | 20.11           | 20.15                | 20.18                |
|      | 600     | 24E       | 1880      | 19.96      | 20.00      | 20.05           | 20.03           | 20.06                | 20.02                |
|      | 1175    | 24E       | 1908.75   | 19.99      | 19.82      | 19.96           | 19.94           | 19.99                | 20.03                |

Note: RC1 is only applicable for IS-95 compatibility.



**Figure 9-3**  
**Power Measurement Setup**

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 32 of 119                  |

## 9.4 Maximum LTE Conducted Powers

### 9.4.1 Maximum LTE Band 13 Conducted Powers

Table 9-7  
Maximum LTE Band 13 Conducted Powers - 10 MHz Bandwidth

|     | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Mid | 782.0           | 23230   | 10              | QPSK       | 1       | 0         | <b>24.34</b>          | 0                         | 0        |
|     | 782.0           | 23230   | 10              | QPSK       | 1       | 25        | 24.32                 | 0                         | 0        |
|     | 782.0           | 23230   | 10              | QPSK       | 1       | 49        | 24.15                 | 0                         | 0        |
|     | 782.0           | 23230   | 10              | QPSK       | 25      | 0         | <b>23.31</b>          | 0-1                       | 1        |
|     | 782.0           | 23230   | 10              | QPSK       | 25      | 12        | 23.18                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 10              | QPSK       | 25      | 25        | 23.17                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 10              | QPSK       | 50      | 0         | 23.28                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 10              | 16QAM      | 1       | 0         | 23.50                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 10              | 16QAM      | 1       | 25        | 23.47                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 10              | 16QAM      | 1       | 49        | 23.45                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 10              | 16QAM      | 25      | 0         | 22.31                 | 0-2                       | 2        |
|     | 782.0           | 23230   | 10              | 16QAM      | 25      | 12        | 22.18                 | 0-2                       | 2        |
|     | 782.0           | 23230   | 10              | 16QAM      | 25      | 25        | 22.20                 | 0-2                       | 2        |
|     | 782.0           | 23230   | 10              | 16QAM      | 50      | 0         | 22.27                 | 0-2                       | 2        |

Table 9-8  
Maximum LTE Band 13 Conducted Powers - 5 MHz Bandwidth

|     | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Mid | 782.0           | 23230   | 5               | QPSK       | 1       | 0         | 24.33                 | 0                         | 0        |
|     | 782.0           | 23230   | 5               | QPSK       | 1       | 12        | 24.17                 | 0                         | 0        |
|     | 782.0           | 23230   | 5               | QPSK       | 1       | 24        | 24.30                 | 0                         | 0        |
|     | 782.0           | 23230   | 5               | QPSK       | 12      | 0         | 23.19                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 5               | QPSK       | 12      | 6         | 23.18                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 5               | QPSK       | 12      | 13        | 23.17                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 5               | QPSK       | 25      | 0         | 23.18                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 5               | 16-QAM     | 1       | 0         | 23.50                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 5               | 16-QAM     | 1       | 12        | 23.45                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 5               | 16-QAM     | 1       | 24        | 23.42                 | 0-1                       | 1        |
|     | 782.0           | 23230   | 5               | 16-QAM     | 12      | 0         | 22.20                 | 0-2                       | 2        |
|     | 782.0           | 23230   | 5               | 16-QAM     | 12      | 6         | 22.19                 | 0-2                       | 2        |
|     | 782.0           | 23230   | 5               | 16-QAM     | 12      | 13        | 22.23                 | 0-2                       | 2        |
|     | 782.0           | 23230   | 5               | 16-QAM     | 25      | 0         | 22.21                 | 0-2                       | 2        |

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 33 of 119                  |

## 9.4.2 Maximum LTE Band 5 (Cell) Conducted Powers

Table 9-9  
Maximum LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

|     | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Mid | 836.5           | 20525   | 10              | QPSK       | 1       | 0         | 24.39                 | 0                         | 0        |
|     | 836.5           | 20525   | 10              | QPSK       | 1       | 25        | <b>24.48</b>          | 0                         | 0        |
|     | 836.5           | 20525   | 10              | QPSK       | 1       | 49        | 24.34                 | 0                         | 0        |
|     | 836.5           | 20525   | 10              | QPSK       | 25      | 0         | <b>23.44</b>          | 0-1                       | 1        |
|     | 836.5           | 20525   | 10              | QPSK       | 25      | 12        | 23.38                 | 0-1                       | 1        |
|     | 836.5           | 20525   | 10              | QPSK       | 25      | 25        | 23.31                 | 0-1                       | 1        |
|     | 836.5           | 20525   | 10              | QPSK       | 50      | 0         | 23.39                 | 0-1                       | 1        |
|     | 836.5           | 20525   | 10              | 16QAM      | 1       | 0         | 23.50                 | 0-1                       | 1        |
|     | 836.5           | 20525   | 10              | 16QAM      | 1       | 25        | 23.49                 | 0-1                       | 1        |
|     | 836.5           | 20525   | 10              | 16QAM      | 1       | 49        | 23.44                 | 0-1                       | 1        |
|     | 836.5           | 20525   | 10              | 16QAM      | 25      | 0         | 22.43                 | 0-2                       | 2        |
|     | 836.5           | 20525   | 10              | 16QAM      | 25      | 12        | 22.47                 | 0-2                       | 2        |
|     | 836.5           | 20525   | 10              | 16QAM      | 25      | 25        | 22.36                 | 0-2                       | 2        |
|     | 836.5           | 20525   | 10              | 16QAM      | 50      | 0         | 22.39                 | 0-2                       | 2        |

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 34 of 119                  |

**Table 9-10**  
**Maximum LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 826.5           | 20425   | 5               | QPSK       | 1       | 0         | 24.46                 | 0                         | 0        |
|      | 826.5           | 20425   | 5               | QPSK       | 1       | 12        | 24.31                 | 0                         | 0        |
|      | 826.5           | 20425   | 5               | QPSK       | 1       | 24        | 24.48                 | 0                         | 0        |
|      | 826.5           | 20425   | 5               | QPSK       | 12      | 0         | 23.44                 | 0-1                       | 1        |
|      | 826.5           | 20425   | 5               | QPSK       | 12      | 6         | 23.47                 | 0-1                       | 1        |
|      | 826.5           | 20425   | 5               | QPSK       | 12      | 13        | 23.45                 | 0-1                       | 1        |
|      | 826.5           | 20425   | 5               | QPSK       | 25      | 0         | 23.50                 | 0-1                       | 1        |
|      | 826.5           | 20425   | 5               | 16-QAM     | 1       | 0         | 23.24                 | 0-1                       | 1        |
|      | 826.5           | 20425   | 5               | 16-QAM     | 1       | 12        | 23.11                 | 0-1                       | 1        |
|      | 826.5           | 20425   | 5               | 16-QAM     | 1       | 24        | 23.17                 | 0-1                       | 1        |
|      | 826.5           | 20425   | 5               | 16-QAM     | 12      | 0         | 22.32                 | 0-2                       | 2        |
|      | 826.5           | 20425   | 5               | 16-QAM     | 12      | 6         | 22.37                 | 0-2                       | 2        |
|      | 826.5           | 20425   | 5               | 16-QAM     | 12      | 13        | 22.46                 | 0-2                       | 2        |
|      | 826.5           | 20425   | 5               | 16-QAM     | 25      | 0         | 22.41                 | 0-2                       | 2        |
| Mid  | 836.5           | 20525   | 5               | QPSK       | 1       | 0         | 24.40                 | 0                         | 0        |
|      | 836.5           | 20525   | 5               | QPSK       | 1       | 12        | 24.47                 | 0                         | 0        |
|      | 836.5           | 20525   | 5               | QPSK       | 1       | 24        | 24.34                 | 0                         | 0        |
|      | 836.5           | 20525   | 5               | QPSK       | 12      | 0         | 23.49                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 5               | QPSK       | 12      | 6         | 23.42                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 5               | QPSK       | 12      | 13        | 23.42                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 5               | QPSK       | 25      | 0         | 23.36                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 5               | 16-QAM     | 1       | 0         | 23.43                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 5               | 16-QAM     | 1       | 12        | 23.24                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 5               | 16-QAM     | 1       | 24        | 23.50                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 5               | 16-QAM     | 12      | 0         | 22.47                 | 0-2                       | 2        |
|      | 836.5           | 20525   | 5               | 16-QAM     | 12      | 6         | 22.31                 | 0-2                       | 2        |
|      | 836.5           | 20525   | 5               | 16-QAM     | 12      | 13        | 22.43                 | 0-2                       | 2        |
|      | 836.5           | 20525   | 5               | 16-QAM     | 25      | 0         | 22.48                 | 0-2                       | 2        |
| High | 846.5           | 20625   | 5               | QPSK       | 1       | 0         | 24.49                 | 0                         | 0        |
|      | 846.5           | 20625   | 5               | QPSK       | 1       | 12        | 24.32                 | 0                         | 0        |
|      | 846.5           | 20625   | 5               | QPSK       | 1       | 24        | 24.36                 | 0                         | 0        |
|      | 846.5           | 20625   | 5               | QPSK       | 12      | 0         | 23.50                 | 0-1                       | 1        |
|      | 846.5           | 20625   | 5               | QPSK       | 12      | 6         | 23.45                 | 0-1                       | 1        |
|      | 846.5           | 20625   | 5               | QPSK       | 12      | 13        | 23.44                 | 0-1                       | 1        |
|      | 846.5           | 20625   | 5               | QPSK       | 25      | 0         | 23.46                 | 0-1                       | 1        |
|      | 846.5           | 20625   | 5               | 16-QAM     | 1       | 0         | 23.37                 | 0-1                       | 1        |
|      | 846.5           | 20625   | 5               | 16-QAM     | 1       | 12        | 23.35                 | 0-1                       | 1        |
|      | 846.5           | 20625   | 5               | 16-QAM     | 1       | 24        | 23.25                 | 0-1                       | 1        |
|      | 846.5           | 20625   | 5               | 16-QAM     | 12      | 0         | 22.50                 | 0-2                       | 2        |
|      | 846.5           | 20625   | 5               | 16-QAM     | 12      | 6         | 22.40                 | 0-2                       | 2        |
|      | 846.5           | 20625   | 5               | 16-QAM     | 12      | 13        | 22.46                 | 0-2                       | 2        |
|      | 846.5           | 20625   | 5               | 16-QAM     | 25      | 0         | 22.43                 | 0-2                       | 2        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 35 of 119                                                                        |                                 |

**Table 9-11**  
**Maximum LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 825.5           | 20415   | 3               | QPSK       | 1       | 0         | 24.35                 | 0                         | 0        |
|      | 825.5           | 20415   | 3               | QPSK       | 1       | 7         | 24.43                 | 0                         | 0        |
|      | 825.5           | 20415   | 3               | QPSK       | 1       | 14        | 24.31                 | 0                         | 0        |
|      | 825.5           | 20415   | 3               | QPSK       | 8       | 0         | 23.37                 | 0-1                       | 1        |
|      | 825.5           | 20415   | 3               | QPSK       | 8       | 4         | 23.45                 | 0-1                       | 1        |
|      | 825.5           | 20415   | 3               | QPSK       | 8       | 7         | 23.49                 | 0-1                       | 1        |
|      | 825.5           | 20415   | 3               | QPSK       | 15      | 0         | 23.35                 | 0-1                       | 1        |
|      | 825.5           | 20415   | 3               | 16-QAM     | 1       | 0         | 23.09                 | 0-1                       | 1        |
|      | 825.5           | 20415   | 3               | 16-QAM     | 1       | 7         | 23.32                 | 0-1                       | 1        |
|      | 825.5           | 20415   | 3               | 16-QAM     | 1       | 14        | 23.26                 | 0-1                       | 1        |
|      | 825.5           | 20415   | 3               | 16-QAM     | 8       | 0         | 22.32                 | 0-2                       | 2        |
|      | 825.5           | 20415   | 3               | 16-QAM     | 8       | 4         | 22.29                 | 0-2                       | 2        |
|      | 825.5           | 20415   | 3               | 16-QAM     | 8       | 7         | 22.35                 | 0-2                       | 2        |
|      | 825.5           | 20415   | 3               | 16-QAM     | 15      | 0         | 22.30                 | 0-2                       | 2        |
| Mid  | 836.5           | 20525   | 3               | QPSK       | 1       | 0         | 24.43                 | 0                         | 0        |
|      | 836.5           | 20525   | 3               | QPSK       | 1       | 7         | 24.50                 | 0                         | 0        |
|      | 836.5           | 20525   | 3               | QPSK       | 1       | 14        | 24.46                 | 0                         | 0        |
|      | 836.5           | 20525   | 3               | QPSK       | 8       | 0         | 23.38                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 3               | QPSK       | 8       | 4         | 23.39                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 3               | QPSK       | 8       | 7         | 23.41                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 3               | QPSK       | 15      | 0         | 23.36                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 3               | 16-QAM     | 1       | 0         | 23.21                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 3               | 16-QAM     | 1       | 7         | 23.10                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 3               | 16-QAM     | 1       | 14        | 23.31                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 3               | 16-QAM     | 8       | 0         | 22.40                 | 0-2                       | 2        |
|      | 836.5           | 20525   | 3               | 16-QAM     | 8       | 4         | 22.41                 | 0-2                       | 2        |
|      | 836.5           | 20525   | 3               | 16-QAM     | 8       | 7         | 22.46                 | 0-2                       | 2        |
|      | 836.5           | 20525   | 3               | 16-QAM     | 15      | 0         | 22.39                 | 0-2                       | 2        |
| High | 847.5           | 20635   | 3               | QPSK       | 1       | 0         | 24.37                 | 0                         | 0        |
|      | 847.5           | 20635   | 3               | QPSK       | 1       | 7         | 24.36                 | 0                         | 0        |
|      | 847.5           | 20635   | 3               | QPSK       | 1       | 14        | 24.47                 | 0                         | 0        |
|      | 847.5           | 20635   | 3               | QPSK       | 8       | 0         | 23.40                 | 0-1                       | 1        |
|      | 847.5           | 20635   | 3               | QPSK       | 8       | 4         | 23.49                 | 0-1                       | 1        |
|      | 847.5           | 20635   | 3               | QPSK       | 8       | 7         | 23.35                 | 0-1                       | 1        |
|      | 847.5           | 20635   | 3               | QPSK       | 15      | 0         | 23.43                 | 0-1                       | 1        |
|      | 847.5           | 20635   | 3               | 16-QAM     | 1       | 0         | 23.31                 | 0-1                       | 1        |
|      | 847.5           | 20635   | 3               | 16-QAM     | 1       | 7         | 23.14                 | 0-1                       | 1        |
|      | 847.5           | 20635   | 3               | 16-QAM     | 1       | 14        | 23.27                 | 0-1                       | 1        |
|      | 847.5           | 20635   | 3               | 16-QAM     | 8       | 0         | 22.31                 | 0-2                       | 2        |
|      | 847.5           | 20635   | 3               | 16-QAM     | 8       | 4         | 22.36                 | 0-2                       | 2        |
|      | 847.5           | 20635   | 3               | 16-QAM     | 8       | 7         | 22.29                 | 0-2                       | 2        |
|      | 847.5           | 20635   | 3               | 16-QAM     | 15      | 0         | 22.30                 | 0-2                       | 2        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 36 of 119                  |

**Table 9-12**  
**Maximum LTE Band 5 (Cell) Conducted Powers – 1.4 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 824.7           | 20407   | 1.4             | QPSK       | 1       | 0         | 24.50                 | 0                         | 0        |
|      | 824.7           | 20407   | 1.4             | QPSK       | 1       | 2         | 24.38                 | 0                         | 0        |
|      | 824.7           | 20407   | 1.4             | QPSK       | 1       | 5         | 24.32                 | 0                         | 0        |
|      | 824.7           | 20407   | 1.4             | QPSK       | 3       | 0         | 24.41                 | 0                         | 0        |
|      | 824.7           | 20407   | 1.4             | QPSK       | 3       | 2         | 24.33                 | 0                         | 0        |
|      | 824.7           | 20407   | 1.4             | QPSK       | 3       | 3         | 24.36                 | 0                         | 0        |
|      | 824.7           | 20407   | 1.4             | QPSK       | 6       | 0         | 23.40                 | 0-1                       | 1        |
|      | 824.7           | 20407   | 1.4             | 16-QAM     | 1       | 0         | 23.42                 | 0-1                       | 1        |
|      | 824.7           | 20407   | 1.4             | 16-QAM     | 1       | 2         | 23.47                 | 0-1                       | 1        |
|      | 824.7           | 20407   | 1.4             | 16-QAM     | 1       | 5         | 23.42                 | 0-1                       | 1        |
|      | 824.7           | 20407   | 1.4             | 16-QAM     | 3       | 0         | 23.29                 | 0-1                       | 1        |
|      | 824.7           | 20407   | 1.4             | 16-QAM     | 3       | 2         | 23.37                 | 0-1                       | 1        |
|      | 824.7           | 20407   | 1.4             | 16-QAM     | 3       | 3         | 23.46                 | 0-1                       | 1        |
|      | 824.7           | 20407   | 1.4             | 16-QAM     | 6       | 0         | 22.42                 | 0-2                       | 2        |
| Mid  | 836.5           | 20525   | 1.4             | QPSK       | 1       | 0         | 24.48                 | 0                         | 0        |
|      | 836.5           | 20525   | 1.4             | QPSK       | 1       | 2         | 24.36                 | 0                         | 0        |
|      | 836.5           | 20525   | 1.4             | QPSK       | 1       | 5         | 24.34                 | 0                         | 0        |
|      | 836.5           | 20525   | 1.4             | QPSK       | 3       | 0         | 24.34                 | 0                         | 0        |
|      | 836.5           | 20525   | 1.4             | QPSK       | 3       | 2         | 24.37                 | 0                         | 0        |
|      | 836.5           | 20525   | 1.4             | QPSK       | 3       | 3         | 24.41                 | 0                         | 0        |
|      | 836.5           | 20525   | 1.4             | QPSK       | 6       | 0         | 23.30                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 1.4             | 16-QAM     | 1       | 0         | 23.22                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 1.4             | 16-QAM     | 1       | 2         | 23.15                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 1.4             | 16-QAM     | 1       | 5         | 23.10                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 1.4             | 16-QAM     | 3       | 0         | 23.38                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 1.4             | 16-QAM     | 3       | 2         | 23.31                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 1.4             | 16-QAM     | 3       | 3         | 23.33                 | 0-1                       | 1        |
|      | 836.5           | 20525   | 1.4             | 16-QAM     | 6       | 0         | 22.29                 | 0-2                       | 2        |
| High | 848.3           | 20643   | 1.4             | QPSK       | 1       | 0         | 24.46                 | 0                         | 0        |
|      | 848.3           | 20643   | 1.4             | QPSK       | 1       | 2         | 24.41                 | 0                         | 0        |
|      | 848.3           | 20643   | 1.4             | QPSK       | 1       | 5         | 24.32                 | 0                         | 0        |
|      | 848.3           | 20643   | 1.4             | QPSK       | 3       | 0         | 24.50                 | 0                         | 0        |
|      | 848.3           | 20643   | 1.4             | QPSK       | 3       | 2         | 24.36                 | 0                         | 0        |
|      | 848.3           | 20643   | 1.4             | QPSK       | 3       | 3         | 24.32                 | 0                         | 0        |
|      | 848.3           | 20643   | 1.4             | QPSK       | 6       | 0         | 23.16                 | 0-1                       | 1        |
|      | 848.3           | 20643   | 1.4             | 16-QAM     | 1       | 0         | 23.22                 | 0-1                       | 1        |
|      | 848.3           | 20643   | 1.4             | 16-QAM     | 1       | 2         | 23.24                 | 0-1                       | 1        |
|      | 848.3           | 20643   | 1.4             | 16-QAM     | 1       | 5         | 23.32                 | 0-1                       | 1        |
|      | 848.3           | 20643   | 1.4             | 16-QAM     | 3       | 0         | 23.18                 | 0-1                       | 1        |
|      | 848.3           | 20643   | 1.4             | 16-QAM     | 3       | 2         | 23.20                 | 0-1                       | 1        |
|      | 848.3           | 20643   | 1.4             | 16-QAM     | 3       | 3         | 23.26                 | 0-1                       | 1        |
|      | 848.3           | 20643   | 1.4             | 16-QAM     | 6       | 0         | 22.14                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

### 9.4.3 Maximum LTE Band 4 (AWS) Conducted Powers

**Table 9-13**  
**Maximum LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth**

|     | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Mid | 1732.5          | 20175   | 20              | QPSK       | 1       | 0         | <b>24.50</b>          | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 1       | 50        | 23.91                 | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 1       | 99        | 24.02                 | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 0         | <b>23.15</b>          | 0-1                       | 1        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 25        | 22.92                 | 0-1                       | 1        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 50        | 22.92                 | 0-1                       | 1        |
|     | 1732.5          | 20175   | 20              | QPSK       | 100     | 0         | 23.01                 | 0-1                       | 1        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 0         | 23.50                 | 0-1                       | 1        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 50        | 23.17                 | 0-1                       | 1        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 99        | 23.44                 | 0-1                       | 1        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 0         | 22.19                 | 0-2                       | 2        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 25        | 21.95                 | 0-2                       | 2        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 50        | 21.91                 | 0-2                       | 2        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 100     | 0         | 22.02                 | 0-2                       | 2        |

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

|                                   |                                                                                                                                                                                                        |                               |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset | Page 38 of 119                  |

**Table 9-14**  
**Maximum LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1717.5          | 20025   | 15              | QPSK       | 1       | 0         | 24.50                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 1       | 36        | 23.99                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 1       | 74        | 23.93                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 0         | 23.13                 | 0-1                       | 1        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 18        | 22.98                 | 0-1                       | 1        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 37        | 22.81                 | 0-1                       | 1        |
|      | 1717.5          | 20025   | 15              | QPSK       | 75      | 0         | 22.94                 | 0-1                       | 1        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 0         | 23.43                 | 0-1                       | 1        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 36        | 23.13                 | 0-1                       | 1        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 74        | 23.01                 | 0-1                       | 1        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 0         | 22.15                 | 0-2                       | 2        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 18        | 22.02                 | 0-2                       | 2        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 37        | 21.90                 | 0-2                       | 2        |
| Mid  | 1732.5          | 20175   | 15              | QPSK       | 1       | 0         | 24.47                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 1       | 36        | 24.13                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 1       | 74        | 23.96                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 0         | 23.02                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 18        | 22.90                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 37        | 22.89                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 15              | QPSK       | 75      | 0         | 22.77                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 0         | 23.39                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 36        | 23.26                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 74        | 23.37                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 0         | 22.11                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 18        | 21.86                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 37        | 21.75                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 75      | 0         | 21.90                 | 0-2                       | 2        |
| High | 1747.5          | 20325   | 15              | QPSK       | 1       | 0         | 24.38                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 1       | 36        | 24.07                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 1       | 74        | 24.03                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 0         | 22.97                 | 0-1                       | 1        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 18        | 22.86                 | 0-1                       | 1        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 37        | 22.75                 | 0-1                       | 1        |
|      | 1747.5          | 20325   | 15              | QPSK       | 75      | 0         | 22.80                 | 0-1                       | 1        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 0         | 23.02                 | 0-1                       | 1        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 36        | 22.84                 | 0-1                       | 1        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 74        | 22.93                 | 0-1                       | 1        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 0         | 21.93                 | 0-2                       | 2        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 18        | 21.79                 | 0-2                       | 2        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 37        | 21.72                 | 0-2                       | 2        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 75      | 0         | 21.83                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-15**  
**Maximum LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1715            | 20000   | 10              | QPSK       | 1       | 0         | 24.12                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 1       | 25        | 24.03                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 1       | 49        | 24.11                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 0         | 23.01                 | 0-1                       | 1        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 12        | 22.93                 | 0-1                       | 1        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 25        | 22.82                 | 0-1                       | 1        |
|      | 1715            | 20000   | 10              | QPSK       | 50      | 0         | 22.91                 | 0-1                       | 1        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 0         | 23.49                 | 0-1                       | 1        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 25        | 23.26                 | 0-1                       | 1        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 49        | 23.40                 | 0-1                       | 1        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 0         | 22.04                 | 0-2                       | 2        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 12        | 21.94                 | 0-2                       | 2        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 25        | 21.83                 | 0-2                       | 2        |
|      | 1715            | 20000   | 10              | 16QAM      | 50      | 0         | 21.87                 | 0-2                       | 2        |
| Mid  | 1732.5          | 20175   | 10              | QPSK       | 1       | 0         | 24.18                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 1       | 25        | 23.89                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 1       | 49        | 23.75                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 0         | 23.03                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 12        | 22.86                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 25        | 22.77                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 10              | QPSK       | 50      | 0         | 22.80                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 0         | 23.36                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 25        | 23.14                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 49        | 23.08                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 0         | 21.98                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 12        | 21.93                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 25        | 21.95                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 50      | 0         | 21.89                 | 0-2                       | 2        |
| High | 1750            | 20350   | 10              | QPSK       | 1       | 0         | 23.89                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 1       | 25        | 23.92                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 1       | 49        | 23.83                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 0         | 22.91                 | 0-1                       | 1        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 12        | 22.85                 | 0-1                       | 1        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 25        | 22.70                 | 0-1                       | 1        |
|      | 1750            | 20350   | 10              | QPSK       | 50      | 0         | 22.76                 | 0-1                       | 1        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 0         | 23.22                 | 0-1                       | 1        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 25        | 22.90                 | 0-1                       | 1        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 49        | 23.10                 | 0-1                       | 1        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 0         | 21.94                 | 0-2                       | 2        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 12        | 21.87                 | 0-2                       | 2        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 25        | 21.83                 | 0-2                       | 2        |
|      | 1750            | 20350   | 10              | 16QAM      | 50      | 0         | 21.96                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-16**  
**Maximum LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1712.5          | 19975   | 5               | QPSK       | 1       | 0         | 24.04                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 1       | 12        | 23.88                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 1       | 24        | 23.89                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 0         | 22.90                 | 0-1                       | 1        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 6         | 22.99                 | 0-1                       | 1        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 13        | 22.85                 | 0-1                       | 1        |
|      | 1712.5          | 19975   | 5               | QPSK       | 25      | 0         | 22.86                 | 0-1                       | 1        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 0         | 23.15                 | 0-1                       | 1        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 12        | 23.38                 | 0-1                       | 1        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 24        | 23.39                 | 0-1                       | 1        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 0         | 22.00                 | 0-2                       | 2        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 6         | 22.09                 | 0-2                       | 2        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 13        | 21.75                 | 0-2                       | 2        |
| Mid  | 1732.5          | 20175   | 5               | QPSK       | 1       | 0         | 24.10                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 1       | 12        | 23.99                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 1       | 24        | 24.04                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 0         | 22.87                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 6         | 22.85                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 13        | 22.79                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 5               | QPSK       | 25      | 0         | 22.74                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 0         | 23.37                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 12        | 23.30                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 24        | 23.16                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 0         | 21.84                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 6         | 21.90                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 13        | 21.83                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 25      | 0         | 21.91                 | 0-2                       | 2        |
| High | 1752.5          | 20375   | 5               | QPSK       | 1       | 0         | 23.96                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 1       | 12        | 24.41                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 1       | 24        | 24.32                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 0         | 22.91                 | 0-1                       | 1        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 6         | 22.84                 | 0-1                       | 1        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 13        | 22.77                 | 0-1                       | 1        |
|      | 1752.5          | 20375   | 5               | QPSK       | 25      | 0         | 22.68                 | 0-1                       | 1        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 0         | 23.25                 | 0-1                       | 1        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 12        | 23.05                 | 0-1                       | 1        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 24        | 23.11                 | 0-1                       | 1        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 0         | 21.93                 | 0-2                       | 2        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 6         | 21.95                 | 0-2                       | 2        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 13        | 21.87                 | 0-2                       | 2        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 25      | 0         | 21.84                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-17**  
**Maximum LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1711.5          | 19965   | 3               | QPSK       | 1       | 0         | 23.90                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 1       | 7         | 24.19                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 1       | 14        | 23.98                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 0         | 22.95                 | 0-1                       | 1        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 4         | 22.88                 | 0-1                       | 1        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 7         | 22.79                 | 0-1                       | 1        |
|      | 1711.5          | 19965   | 3               | QPSK       | 15      | 0         | 22.80                 | 0-1                       | 1        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 0         | 23.13                 | 0-1                       | 1        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 7         | 23.27                 | 0-1                       | 1        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 14        | 23.25                 | 0-1                       | 1        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 0         | 22.09                 | 0-2                       | 2        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 4         | 21.91                 | 0-2                       | 2        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 7         | 21.84                 | 0-2                       | 2        |
| Mid  | 1711.5          | 19965   | 3               | 16-QAM     | 15      | 0         | 21.87                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 3               | QPSK       | 1       | 0         | 23.91                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 1       | 7         | 24.10                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 1       | 14        | 23.94                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 0         | 22.96                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 4         | 22.75                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 7         | 22.92                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 3               | QPSK       | 15      | 0         | 22.83                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 0         | 23.36                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 7         | 22.77                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 14        | 23.26                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 0         | 21.84                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 4         | 21.75                 | 0-2                       | 2        |
| High | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 7         | 21.97                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 15      | 0         | 21.94                 | 0-2                       | 2        |
|      | 1753.5          | 20385   | 3               | QPSK       | 1       | 0         | 24.08                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 1       | 7         | 24.02                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 1       | 14        | 23.90                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 0         | 22.77                 | 0-1                       | 1        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 4         | 22.96                 | 0-1                       | 1        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 7         | 22.78                 | 0-1                       | 1        |
|      | 1753.5          | 20385   | 3               | QPSK       | 15      | 0         | 22.82                 | 0-1                       | 1        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 0         | 22.94                 | 0-1                       | 1        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 7         | 23.32                 | 0-1                       | 1        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 14        | 23.21                 | 0-1                       | 1        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 0         | 21.72                 | 0-2                       | 2        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 4         | 21.79                 | 0-2                       | 2        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 7         | 21.61                 | 0-2                       | 2        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 15      | 0         | 21.92                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-18**  
**Maximum LTE Band 4 (AWS) Conducted Powers – 1.4 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 0         | 24.21                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 2         | 24.11                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 5         | 23.97                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 0         | 23.77                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 2         | 23.88                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 3         | 23.80                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 6       | 0         | 22.85                 | 0-1                       | 1        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 0         | 22.94                 | 0-1                       | 1        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 2         | 22.97                 | 0-1                       | 1        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 5         | 23.01                 | 0-1                       | 1        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 0         | 22.99                 | 0-1                       | 1        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 2         | 22.86                 | 0-1                       | 1        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 3         | 22.90                 | 0-1                       | 1        |
| Mid  | 1710.7          | 19957   | 1.4             | 16-QAM     | 6       | 0         | 21.78                 | 0-2                       | 2        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 0         | 24.39                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 2         | 24.41                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 5         | 24.09                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 0         | 24.07                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 2         | 24.05                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 3         | 24.06                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 6       | 0         | 22.97                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 0         | 23.33                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 2         | 23.08                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 5         | 23.25                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 0         | 22.93                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 2         | 22.94                 | 0-1                       | 1        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 3         | 23.30                 | 0-1                       | 1        |
| High | 1732.5          | 20175   | 1.4             | 16-QAM     | 6       | 0         | 22.09                 | 0-2                       | 2        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 0         | 24.01                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 2         | 23.79                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 5         | 23.90                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 0         | 23.93                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 2         | 23.86                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 3         | 23.88                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 6       | 0         | 22.76                 | 0-1                       | 1        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 0         | 23.16                 | 0-1                       | 1        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 2         | 23.17                 | 0-1                       | 1        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 5         | 23.14                 | 0-1                       | 1        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 0         | 22.91                 | 0-1                       | 1        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 2         | 23.12                 | 0-1                       | 1        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 3         | 23.04                 | 0-1                       | 1        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 6       | 0         | 21.85                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

## 9.4.4 Maximum LTE Band 2 (PCS) Conducted Powers

**Table 9-19**  
**Maximum LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1860            | 18700   | 20              | QPSK       | 1       | 0         | <b>23.98</b>          | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 1       | 50        | 23.21                 | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 1       | 99        | 23.23                 | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 0         | <b>22.55</b>          | 0-1                       | 1        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 25        | 22.38                 | 0-1                       | 1        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 50        | 22.20                 | 0-1                       | 1        |
|      | 1860            | 18700   | 20              | QPSK       | 100     | 0         | 22.36                 | 0-1                       | 1        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 0         | 22.89                 | 0-1                       | 1        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 50        | 22.30                 | 0-1                       | 1        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 99        | 22.28                 | 0-1                       | 1        |
|      | 1860            | 18700   | 20              | 16QAM      | 50      | 0         | 21.25                 | 0-2                       | 2        |
|      | 1860            | 18700   | 20              | 16QAM      | 50      | 25        | 21.02                 | 0-2                       | 2        |
|      | 1860            | 18700   | 20              | 16QAM      | 50      | 50        | 21.00                 | 0-2                       | 2        |
| Mid  | 1860            | 18700   | 20              | 16QAM      | 100     | 0         | 21.21                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 0         | 23.88                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 50        | 23.15                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 99        | 23.22                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 0         | 22.38                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 25        | 22.27                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 50        | 22.23                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 20              | QPSK       | 100     | 0         | 22.20                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 0         | 22.85                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 50        | 22.31                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 99        | 22.45                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 50      | 0         | 21.47                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 50      | 25        | 21.20                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 50      | 50        | 21.28                 | 0-2                       | 2        |
| High | 1880.0          | 18900   | 20              | 16QAM      | 100     | 0         | 21.22                 | 0-2                       | 2        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 0         | 23.69                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 50        | 23.22                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 99        | 23.20                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 0         | 22.25                 | 0-1                       | 1        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 25        | 22.20                 | 0-1                       | 1        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 50        | 22.23                 | 0-1                       | 1        |
|      | 1900            | 19100   | 20              | QPSK       | 100     | 0         | 22.20                 | 0-1                       | 1        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 0         | 22.91                 | 0-1                       | 1        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 50        | 22.21                 | 0-1                       | 1        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 99        | 22.25                 | 0-1                       | 1        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 0         | 21.21                 | 0-2                       | 2        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 25        | 21.23                 | 0-2                       | 2        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 50        | 21.21                 | 0-2                       | 2        |
|      | 1900            | 19100   | 20              | 16QAM      | 100     | 0         | 21.26                 | 0-2                       | 2        |

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 44 of 119                  |

**Table 9-20**  
**Maximum LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1857.5          | 18675   | 15              | QPSK       | 1       | 0         | 24.00                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 1       | 36        | 23.57                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 1       | 74        | 23.63                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 0         | 22.58                 | 0-1                       | 1        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 18        | 22.36                 | 0-1                       | 1        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 37        | 22.21                 | 0-1                       | 1        |
|      | 1857.5          | 18675   | 15              | QPSK       | 75      | 0         | 22.38                 | 0-1                       | 1        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 0         | 23.00                 | 0-1                       | 1        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 36        | 22.55                 | 0-1                       | 1        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 74        | 22.59                 | 0-1                       | 1        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 36      | 0         | 21.59                 | 0-2                       | 2        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 36      | 18        | 21.34                 | 0-2                       | 2        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 36      | 37        | 21.19                 | 0-2                       | 2        |
| Mid  | 1857.5          | 18675   | 15              | 16QAM      | 75      | 0         | 21.37                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 0         | 23.95                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 36        | 23.37                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 74        | 23.38                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 0         | 22.46                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 18        | 22.24                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 37        | 22.12                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 15              | QPSK       | 75      | 0         | 22.23                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 0         | 23.00                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 36        | 22.45                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 74        | 22.38                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 36      | 0         | 21.45                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 36      | 18        | 21.27                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 36      | 37        | 21.12                 | 0-2                       | 2        |
| High | 1880.0          | 18900   | 15              | 16QAM      | 75      | 0         | 21.24                 | 0-2                       | 2        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 0         | 23.82                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 36        | 23.10                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 74        | 23.27                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 0         | 22.30                 | 0-1                       | 1        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 18        | 22.11                 | 0-1                       | 1        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 37        | 22.00                 | 0-1                       | 1        |
|      | 1902.5          | 19125   | 15              | QPSK       | 75      | 0         | 22.12                 | 0-1                       | 1        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 0         | 22.96                 | 0-1                       | 1        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 36        | 22.37                 | 0-1                       | 1        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 74        | 22.48                 | 0-1                       | 1        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 0         | 21.29                 | 0-2                       | 2        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 18        | 21.09                 | 0-2                       | 2        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 37        | 21.00                 | 0-2                       | 2        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 75      | 0         | 21.12                 | 0-2                       | 2        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 45 of 119                  |

**Table 9-21**  
**Maximum LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1855            | 18650   | 10              | QPSK       | 1       | 0         | 23.63                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 1       | 25        | 23.29                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 1       | 49        | 23.32                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 0         | 22.36                 | 0-1                       | 1        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 12        | 22.16                 | 0-1                       | 1        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 25        | 22.14                 | 0-1                       | 1        |
|      | 1855            | 18650   | 10              | QPSK       | 50      | 0         | 22.23                 | 0-1                       | 1        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 0         | 22.80                 | 0-1                       | 1        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 25        | 22.48                 | 0-1                       | 1        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 49        | 22.47                 | 0-1                       | 1        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 0         | 21.37                 | 0-2                       | 2        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 12        | 21.20                 | 0-2                       | 2        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 25        | 21.15                 | 0-2                       | 2        |
|      | 1855            | 18650   | 10              | 16QAM      | 50      | 0         | 21.16                 | 0-2                       | 2        |
| Mid  | 1880.0          | 18900   | 10              | QPSK       | 1       | 0         | 23.53                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 1       | 25        | 23.19                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 1       | 49        | 23.23                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 0         | 22.16                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 12        | 22.12                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 25        | 22.06                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 10              | QPSK       | 50      | 0         | 22.13                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 0         | 22.75                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 25        | 22.39                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 49        | 22.39                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 0         | 21.18                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 12        | 21.12                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 25        | 21.08                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 50      | 0         | 21.10                 | 0-2                       | 2        |
| High | 1905            | 19150   | 10              | QPSK       | 1       | 0         | 23.33                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 1       | 25        | 23.07                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 1       | 49        | 23.07                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 0         | 22.04                 | 0-1                       | 1        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 12        | 22.00                 | 0-1                       | 1        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 25        | 22.00                 | 0-1                       | 1        |
|      | 1905            | 19150   | 10              | QPSK       | 50      | 0         | 22.00                 | 0-1                       | 1        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 0         | 22.50                 | 0-1                       | 1        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 25        | 22.22                 | 0-1                       | 1        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 49        | 22.22                 | 0-1                       | 1        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 0         | 21.04                 | 0-2                       | 2        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 12        | 21.00                 | 0-2                       | 2        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 25        | 21.09                 | 0-2                       | 2        |
|      | 1905            | 19150   | 10              | 16QAM      | 50      | 0         | 21.05                 | 0-2                       | 2        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 46 of 119                  |

**Table 9-22**  
**Maximum LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1852.5          | 18625   | 5               | QPSK       | 1       | 0         | 23.54                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 1       | 12        | 23.26                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 1       | 24        | 23.44                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 0         | 22.37                 | 0-1                       | 1        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 6         | 22.40                 | 0-1                       | 1        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 13        | 22.35                 | 0-1                       | 1        |
|      | 1852.5          | 18625   | 5               | QPSK       | 25      | 0         | 22.36                 | 0-1                       | 1        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 0         | 22.98                 | 0-1                       | 1        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 12        | 22.45                 | 0-1                       | 1        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 24        | 22.93                 | 0-1                       | 1        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 0         | 21.37                 | 0-2                       | 2        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 6         | 21.41                 | 0-2                       | 2        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 13        | 21.35                 | 0-2                       | 2        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 25      | 0         | 21.37                 | 0-2                       | 2        |
| Mid  | 1880.0          | 18900   | 5               | QPSK       | 1       | 0         | 23.34                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 1       | 12        | 23.05                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 1       | 24        | 23.29                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 0         | 22.20                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 6         | 22.21                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 13        | 22.09                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 5               | QPSK       | 25      | 0         | 22.19                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 0         | 22.76                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 12        | 22.17                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 24        | 22.77                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 0         | 21.23                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 6         | 21.24                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 13        | 21.11                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 25      | 0         | 21.19                 | 0-2                       | 2        |
| High | 1907.5          | 19175   | 5               | QPSK       | 1       | 0         | 23.27                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 1       | 12        | 23.00                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 1       | 24        | 23.31                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 0         | 22.12                 | 0-1                       | 1        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 6         | 22.08                 | 0-1                       | 1        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 13        | 22.01                 | 0-1                       | 1        |
|      | 1907.5          | 19175   | 5               | QPSK       | 25      | 0         | 22.06                 | 0-1                       | 1        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 0         | 22.63                 | 0-1                       | 1        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 12        | 22.62                 | 0-1                       | 1        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 24        | 22.59                 | 0-1                       | 1        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 0         | 21.07                 | 0-2                       | 2        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 6         | 21.08                 | 0-2                       | 2        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 13        | 21.00                 | 0-2                       | 2        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 25      | 0         | 21.06                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-23**  
**Maximum LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1851.5          | 18615   | 3               | QPSK       | 1       | 0         | 23.09                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 1       | 7         | 23.05                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 1       | 14        | 23.07                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 0         | 22.71                 | 0-1                       | 1        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 4         | 22.76                 | 0-1                       | 1        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 7         | 22.72                 | 0-1                       | 1        |
|      | 1851.5          | 18615   | 3               | QPSK       | 15      | 0         | 22.35                 | 0-1                       | 1        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 0         | 22.24                 | 0-1                       | 1        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 7         | 22.19                 | 0-1                       | 1        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 14        | 22.07                 | 0-1                       | 1        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 0         | 21.80                 | 0-2                       | 2        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 4         | 21.80                 | 0-2                       | 2        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 7         | 21.65                 | 0-2                       | 2        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 15      | 0         | 21.16                 | 0-2                       | 2        |
| Mid  | 1880.0          | 18900   | 3               | QPSK       | 1       | 0         | 23.09                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 1       | 7         | 23.10                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 1       | 14        | 23.01                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 0         | 22.73                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 4         | 22.75                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 7         | 22.74                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 3               | QPSK       | 15      | 0         | 22.09                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 0         | 22.29                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 7         | 22.11                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 14        | 22.08                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 0         | 21.75                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 4         | 21.75                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 7         | 21.77                 | 0-2                       | 2        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 15      | 0         | 21.10                 | 0-2                       | 2        |
| High | 1908.5          | 19185   | 3               | QPSK       | 1       | 0         | 23.10                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 1       | 7         | 23.09                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 1       | 14        | 23.04                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 0         | 22.71                 | 0-1                       | 1        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 4         | 22.76                 | 0-1                       | 1        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 7         | 22.80                 | 0-1                       | 1        |
|      | 1908.5          | 19185   | 3               | QPSK       | 15      | 0         | 22.10                 | 0-1                       | 1        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 0         | 22.30                 | 0-1                       | 1        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 7         | 22.19                 | 0-1                       | 1        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 14        | 22.05                 | 0-1                       | 1        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 0         | 21.76                 | 0-2                       | 2        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 4         | 21.79                 | 0-2                       | 2        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 7         | 21.75                 | 0-2                       | 2        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 15      | 0         | 21.01                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-24**  
**Maximum LTE Band 2 (PCS) Conducted Powers – 1.4 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 0         | 23.02                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 2         | 23.08                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 5         | 23.04                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 0         | 23.12                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 2         | 23.06                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 3         | 23.11                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 6       | 0         | 22.21                 | 0-1                       | 1        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 0         | 22.49                 | 0-1                       | 1        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 2         | 22.59                 | 0-1                       | 1        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 5         | 22.19                 | 0-1                       | 1        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 0         | 22.15                 | 0-1                       | 1        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 2         | 22.16                 | 0-1                       | 1        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 3         | 22.09                 | 0-1                       | 1        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 6       | 0         | 21.14                 | 0-2                       | 2        |
| Mid  | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 0         | 23.09                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 2         | 23.08                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 5         | 23.15                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 0         | 23.19                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 2         | 23.31                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 3         | 23.25                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 6       | 0         | 22.19                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 0         | 22.39                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 2         | 22.49                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 5         | 22.50                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 0         | 22.17                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 2         | 22.21                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 3         | 22.09                 | 0-1                       | 1        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 6       | 0         | 21.14                 | 0-2                       | 2        |
| High | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 0         | 23.00                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 2         | 23.00                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 5         | 23.01                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 0         | 23.12                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 2         | 23.19                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 3         | 23.15                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 6       | 0         | 22.21                 | 0-1                       | 1        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 0         | 22.61                 | 0-1                       | 1        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 2         | 22.49                 | 0-1                       | 1        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 5         | 22.30                 | 0-1                       | 1        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 0         | 22.10                 | 0-1                       | 1        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 2         | 22.16                 | 0-1                       | 1        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 3         | 22.19                 | 0-1                       | 1        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 6       | 0         | 21.41                 | 0-2                       | 2        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 49 of 119                    |                                                                                                                                                                                                        |                                 |

## 9.5 Reduced Conducted Powers – Hotspot

### 9.5.1 LTE Band 4 (AWS) Conducted Powers – Hotspot

Table 9-25  
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

|     | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Mid | 1732.5          | 20175   | 20              | QPSK       | 1       | 0         | <b>20.23</b>          | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 1       | 50        | 19.86                 | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 1       | 99        | 19.74                 | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 0         | <b>19.88</b>          | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 25        | 19.64                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 50        | 19.54                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 100     | 0         | 19.71                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 0         | 20.22                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 50        | 19.78                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 99        | 19.97                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 0         | 19.84                 | 0-2                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 25        | 19.60                 | 0-2                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 50        | 19.52                 | 0-2                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 100     | 0         | 19.76                 | 0-2                       | 0        |

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 50 of 119                  |

**Table 9-26**  
**LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1717.5          | 20025   | 15              | QPSK       | 1       | 0         | 19.99                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 1       | 36        | 19.52                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 1       | 74        | 19.71                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 0         | 19.70                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 18        | 19.61                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 37        | 19.63                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 75      | 0         | 19.62                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 0         | 20.11                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 36        | 19.76                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 74        | 20.01                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 0         | 19.78                 | 0-2                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 18        | 19.65                 | 0-2                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 37        | 19.70                 | 0-2                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 75      | 0         | 19.64                 | 0-2                       | 0        |
| Mid  | 1732.5          | 20175   | 15              | QPSK       | 1       | 0         | 20.22                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 1       | 36        | 19.77                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 1       | 74        | 19.81                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 0         | 19.94                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 18        | 19.86                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 37        | 19.80                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 75      | 0         | 19.91                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 0         | 20.21                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 36        | 20.06                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 74        | 20.14                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 0         | 19.92                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 18        | 19.83                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 37        | 19.74                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 75      | 0         | 19.88                 | 0-2                       | 0        |
| High | 1747.5          | 20325   | 15              | QPSK       | 1       | 0         | 20.23                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 1       | 36        | 19.91                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 1       | 74        | 20.01                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 0         | 20.01                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 18        | 19.88                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 37        | 19.80                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 75      | 0         | 19.87                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 0         | 20.22                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 36        | 19.77                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 74        | 19.86                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 0         | 20.00                 | 0-2                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 18        | 19.85                 | 0-2                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 37        | 19.80                 | 0-2                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 75      | 0         | 20.02                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-27**  
**LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1715            | 20000   | 10              | QPSK       | 1       | 0         | 19.86                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 1       | 25        | 19.68                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 1       | 49        | 19.73                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 0         | 19.67                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 12        | 19.62                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 25        | 19.61                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 50      | 0         | 19.74                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 0         | 20.04                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 25        | 19.84                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 49        | 19.98                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 0         | 19.65                 | 0-2                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 12        | 19.62                 | 0-2                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 25        | 19.61                 | 0-2                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 50      | 0         | 19.65                 | 0-2                       | 0        |
| Mid  | 1732.5          | 20175   | 10              | QPSK       | 1       | 0         | 20.05                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 1       | 25        | 19.81                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 1       | 49        | 19.84                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 0         | 19.93                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 12        | 19.84                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 25        | 19.78                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 50      | 0         | 19.85                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 0         | 20.20                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 25        | 20.08                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 49        | 20.16                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 0         | 19.95                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 12        | 19.85                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 25        | 19.78                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 50      | 0         | 19.84                 | 0-2                       | 0        |
| High | 1750            | 20350   | 10              | QPSK       | 1       | 0         | 20.15                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 1       | 25        | 19.95                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 1       | 49        | 19.95                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 0         | 19.92                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 12        | 19.93                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 25        | 19.85                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 50      | 0         | 19.96                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 0         | 20.20                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 25        | 19.81                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 49        | 20.21                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 0         | 19.92                 | 0-2                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 12        | 19.95                 | 0-2                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 25        | 20.00                 | 0-2                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 50      | 0         | 20.04                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-28**  
**LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1712.5          | 19975   | 5               | QPSK       | 1       | 0         | 19.68                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 1       | 12        | 19.44                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 1       | 24        | 19.59                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 0         | 19.57                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 6         | 19.56                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 13        | 19.46                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 25      | 0         | 19.48                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 0         | 20.03                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 12        | 19.89                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 24        | 20.07                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 0         | 19.65                 | 0-2                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 6         | 19.64                 | 0-2                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 13        | 19.55                 | 0-2                       | 0        |
| Mid  | 1732.5          | 20175   | 5               | QPSK       | 1       | 0         | 19.92                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 1       | 12        | 19.71                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 1       | 24        | 19.83                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 0         | 19.78                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 6         | 19.82                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 13        | 19.71                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 25      | 0         | 19.74                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 0         | 20.21                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 12        | 19.91                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 24        | 20.04                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 0         | 19.83                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 6         | 19.83                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 13        | 19.77                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 25      | 0         | 19.72                 | 0-2                       | 0        |
| High | 1752.5          | 20375   | 5               | QPSK       | 1       | 0         | 20.17                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 1       | 12        | 19.83                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 1       | 24        | 19.96                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 0         | 19.93                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 6         | 19.97                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 13        | 19.88                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 25      | 0         | 19.94                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 0         | 20.21                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 12        | 20.06                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 24        | 20.22                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 0         | 20.00                 | 0-2                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 6         | 20.04                 | 0-2                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 13        | 19.95                 | 0-2                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 25      | 0         | 19.92                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 53 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 9-29**  
**LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1711.5          | 19965   | 3               | QPSK       | 1       | 0         | 19.58                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 1       | 7         | 19.63                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 1       | 14        | 19.54                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 0         | 19.46                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 4         | 19.61                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 7         | 19.49                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 15      | 0         | 19.51                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 0         | 19.78                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 7         | 20.02                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 14        | 19.98                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 0         | 19.53                 | 0-2                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 4         | 19.62                 | 0-2                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 7         | 19.58                 | 0-2                       | 0        |
| Mid  | 1732.5          | 20175   | 3               | QPSK       | 1       | 0         | 19.83                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 1       | 7         | 19.94                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 1       | 14        | 19.81                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 0         | 19.76                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 4         | 19.78                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 7         | 19.71                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 15      | 0         | 19.74                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 0         | 20.22                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 7         | 20.20                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 14        | 20.07                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 0         | 19.85                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 4         | 19.88                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 7         | 19.86                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 15      | 0         | 19.83                 | 0-2                       | 0        |
| High | 1753.5          | 20385   | 3               | QPSK       | 1       | 0         | 20.04                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 1       | 7         | 20.16                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 1       | 14        | 19.87                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 0         | 19.89                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 4         | 19.94                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 7         | 19.87                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 15      | 0         | 19.92                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 0         | 20.04                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 7         | 20.14                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 14        | 19.84                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 0         | 19.78                 | 0-2                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 4         | 19.82                 | 0-2                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 7         | 19.75                 | 0-2                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 15      | 0         | 19.86                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-30**  
**LTE Band 4 (AWS) Conducted Powers - 1.4 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 0         | 19.46                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 2         | 19.37                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 5         | 19.38                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 0         | 19.52                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 2         | 19.41                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 3         | 19.39                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 6       | 0         | 19.32                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 0         | 20.22                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 2         | 20.19                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 5         | 20.18                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 0         | 19.87                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 2         | 19.72                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 3         | 19.81                 | 0-1                       | 0        |
| Mid  | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 0         | 20.08                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 2         | 20.16                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 5         | 20.06                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 0         | 20.22                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 2         | 20.18                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 3         | 20.18                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 6       | 0         | 20.17                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 0         | 20.03                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 2         | 20.10                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 5         | 20.06                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 0         | 20.18                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 2         | 20.07                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 3         | 20.06                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 6       | 0         | 19.72                 | 0-2                       | 0        |
| High | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 0         | 19.79                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 2         | 19.84                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 5         | 19.94                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 0         | 19.81                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 2         | 19.96                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 3         | 19.88                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 6       | 0         | 19.82                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 0         | 19.96                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 2         | 20.19                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 5         | 19.96                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 0         | 19.98                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 2         | 20.01                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 3         | 19.98                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 6       | 0         | 19.81                 | 0-2                       | 0        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 55 of 119                                                                        |                                 |

## 9.5.2 LTE Band 2 (PCS) Conducted Powers – Hotspot

Table 9-31  
LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1860            | 18700   | 20              | QPSK       | 1       | 0         | 19.96                 | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 1       | 50        | 19.12                 | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 1       | 99        | 19.19                 | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 0         | 19.28                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 25        | 19.04                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 50        | 19.01                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 100     | 0         | 19.19                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 0         | 19.95                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 50        | 19.04                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 99        | 19.00                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 50      | 0         | 19.26                 | 0-2                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 50      | 25        | 19.03                 | 0-2                       | 0        |
| Mid  | 1860            | 18700   | 20              | 16QAM      | 50      | 50        | 19.12                 | 0-2                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 100     | 0         | 19.17                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 0         | 19.61                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 50        | 19.03                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 99        | 19.28                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 0         | 19.24                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 25        | 19.01                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 50        | 19.00                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 100     | 0         | 19.05                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 0         | 19.80                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 50        | 19.07                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 99        | 19.18                 | 0-1                       | 0        |
| High | 1880.0          | 18900   | 20              | 16QAM      | 50      | 0         | 19.23                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 50      | 25        | 19.02                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 50      | 50        | 19.00                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 100     | 0         | 19.05                 | 0-2                       | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 0         | 19.78                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 50        | 19.06                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 99        | 19.24                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 0         | 19.26                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 25        | 19.01                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 50        | 19.06                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 100     | 0         | 19.14                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 0         | 19.48                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 50        | 19.05                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 99        | 19.25                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 0         | 19.24                 | 0-2                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 25        | 19.02                 | 0-2                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 50        | 19.06                 | 0-2                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 100     | 0         | 19.08                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                               |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset | Page 56 of 119                  |

**Table 9-32**  
**LTE Band 2 (PCS) Conducted Powers – 15 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1857.5          | 18675   | 15              | QPSK       | 1       | 0         | 19.79                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 1       | 36        | 19.07                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 1       | 74        | 19.43                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 0         | 19.15                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 18        | 19.02                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 37        | 19.14                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 75      | 0         | 19.25                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 0         | 19.91                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 36        | 19.71                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 74        | 19.77                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 36      | 0         | 19.18                 | 0-2                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 36      | 18        | 19.45                 | 0-2                       | 0        |
| Mid  | 1857.5          | 18675   | 15              | 16QAM      | 36      | 37        | 19.03                 | 0-2                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 75      | 0         | 19.33                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 0         | 19.05                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 36        | 19.19                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 74        | 19.35                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 0         | 19.36                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 18        | 19.16                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 37        | 19.23                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 75      | 0         | 19.26                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 0         | 19.57                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 36        | 19.59                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 74        | 19.67                 | 0-1                       | 0        |
| High | 1880.0          | 18900   | 15              | 16QAM      | 36      | 0         | 19.14                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 36      | 18        | 19.40                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 36      | 37        | 19.05                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 75      | 0         | 19.17                 | 0-2                       | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 0         | 19.32                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 36        | 19.08                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 74        | 19.26                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 0         | 19.12                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 18        | 19.36                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 37        | 19.24                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 75      | 0         | 19.25                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 0         | 19.51                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 36        | 19.37                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 74        | 19.45                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 0         | 19.22                 | 0-2                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 18        | 19.31                 | 0-2                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 37        | 19.11                 | 0-2                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 75      | 0         | 19.34                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 57 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 9-33**  
**LTE Band 2 (PCS) Conducted Powers –10 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1855            | 18650   | 10              | QPSK       | 1       | 0         | 19.60                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 1       | 25        | 19.27                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 1       | 49        | 19.25                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 0         | 19.29                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 12        | 19.10                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 25        | 19.22                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 50      | 0         | 19.17                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 0         | 19.89                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 25        | 19.51                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 49        | 19.63                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 0         | 19.12                 | 0-2                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 12        | 19.33                 | 0-2                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 25        | 19.04                 | 0-2                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 50      | 0         | 19.28                 | 0-2                       | 0        |
| Mid  | 1880.0          | 18900   | 10              | QPSK       | 1       | 0         | 19.07                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 1       | 25        | 19.09                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 1       | 49        | 19.36                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 0         | 19.04                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 12        | 19.26                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 25        | 19.13                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 50      | 0         | 19.15                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 0         | 19.60                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 25        | 19.43                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 49        | 19.49                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 0         | 19.17                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 12        | 19.25                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 25        | 19.18                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 50      | 0         | 19.22                 | 0-2                       | 0        |
| High | 1905            | 19150   | 10              | QPSK       | 1       | 0         | 19.27                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 1       | 25        | 19.21                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 1       | 49        | 19.35                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 0         | 19.32                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 12        | 19.32                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 25        | 19.27                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 50      | 0         | 19.08                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 0         | 19.68                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 25        | 19.26                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 49        | 19.58                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 0         | 19.08                 | 0-2                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 12        | 19.23                 | 0-2                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 25        | 19.08                 | 0-2                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 50      | 0         | 19.29                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 58 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 9-34**  
**LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1852.5          | 18625   | 5               | QPSK       | 1       | 0         | 19.42                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 1       | 12        | 19.09                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 1       | 24        | 19.36                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 0         | 19.24                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 6         | 19.24                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 13        | 19.19                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 25      | 0         | 19.25                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 0         | 19.79                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 12        | 19.39                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 24        | 19.65                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 0         | 19.28                 | 0-2                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 6         | 19.26                 | 0-2                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 13        | 19.21                 | 0-2                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 25      | 0         | 19.24                 | 0-2                       | 0        |
| Mid  | 1880.0          | 18900   | 5               | QPSK       | 1       | 0         | 19.20                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 1       | 12        | 19.02                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 1       | 24        | 19.21                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 0         | 19.04                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 6         | 19.06                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 13        | 19.04                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 25      | 0         | 19.05                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 0         | 19.66                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 12        | 19.36                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 24        | 19.53                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 0         | 19.10                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 6         | 19.06                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 13        | 19.04                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 25      | 0         | 19.07                 | 0-2                       | 0        |
| High | 1907.5          | 19175   | 5               | QPSK       | 1       | 0         | 19.35                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 1       | 12        | 19.13                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 1       | 24        | 19.36                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 0         | 19.19                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 6         | 19.18                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 13        | 19.10                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 25      | 0         | 19.16                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 0         | 19.72                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 12        | 19.39                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 24        | 19.48                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 0         | 19.20                 | 0-2                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 6         | 19.17                 | 0-2                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 13        | 19.11                 | 0-2                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 25      | 0         | 19.17                 | 0-2                       | 0        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 59 of 119                  |

**Table 9-35**  
**LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1851.5          | 18615   | 3               | QPSK       | 1       | 0         | 19.33                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 1       | 7         | 19.59                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 1       | 14        | 19.24                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 0         | 19.22                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 4         | 19.24                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 7         | 19.17                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 15      | 0         | 19.22                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 0         | 19.50                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 7         | 19.94                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 14        | 19.44                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 0         | 19.27                 | 0-2                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 4         | 19.27                 | 0-2                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 7         | 19.23                 | 0-2                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 15      | 0         | 19.19                 | 0-2                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 15      | 0         | 19.19                 | 0-2                       | 0        |
| Mid  | 1880.0          | 18900   | 3               | QPSK       | 1       | 0         | 19.14                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 1       | 7         | 19.25                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 1       | 14        | 19.12                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 0         | 19.05                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 4         | 19.06                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 7         | 19.01                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 15      | 0         | 19.03                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 0         | 19.35                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 7         | 19.94                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 14        | 19.36                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 0         | 19.09                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 4         | 19.10                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 7         | 19.06                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 15      | 0         | 19.02                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 15      | 0         | 19.02                 | 0-2                       | 0        |
| High | 1908.5          | 19185   | 3               | QPSK       | 1       | 0         | 19.39                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 1       | 7         | 19.64                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 1       | 14        | 19.34                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 0         | 19.14                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 4         | 19.17                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 7         | 19.14                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 15      | 0         | 19.15                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 0         | 19.49                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 7         | 19.85                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 14        | 19.39                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 0         | 19.19                 | 0-2                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 4         | 19.18                 | 0-2                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 7         | 19.18                 | 0-2                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 15      | 0         | 19.15                 | 0-2                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 15      | 0         | 19.15                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 60 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 9-36**  
**LTE Band 2 (PCS) Conducted Powers - 1.4 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 0         | 19.48                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 2         | 19.42                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 5         | 19.50                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 0         | 19.14                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 2         | 19.22                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 3         | 19.14                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 6       | 0         | 19.14                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 0         | 19.49                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 2         | 19.20                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 5         | 19.58                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 0         | 19.28                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 2         | 19.28                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 3         | 19.23                 | 0-1                       | 0        |
| Mid  | 1850.7          | 18607   | 1.4             | 16-QAM     | 6       | 0         | 19.16                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 0         | 19.31                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 2         | 19.37                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 5         | 19.30                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 0         | 19.39                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 2         | 19.47                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 3         | 19.46                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 6       | 0         | 19.43                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 0         | 19.16                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 2         | 19.17                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 5         | 19.29                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 0         | 19.11                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 2         | 19.20                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 3         | 19.18                 | 0-1                       | 0        |
| High | 1880.0          | 18900   | 1.4             | 16-QAM     | 6       | 0         | 19.09                 | 0-2                       | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 0         | 19.75                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 2         | 19.62                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 5         | 19.81                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 0         | 19.53                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 2         | 19.24                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 3         | 19.19                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 6       | 0         | 19.12                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 0         | 19.88                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 2         | 19.68                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 5         | 19.95                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 0         | 19.31                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 2         | 19.30                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 3         | 19.29                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 6       | 0         | 19.17                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 61 of 119                    |                                                                                                                                                                                                        |                                 |

## 9.5.1 LTE Band 4 (AWS) Conducted Powers – Extremity

Table 9-37

LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

|     | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|-----|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Mid | 1732.5          | 20175   | 20              | QPSK       | 1       | 0         | 21.50                 | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 1       | 50        | 20.84                 | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 1       | 99        | 21.11                 | 0                         | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 0         | 21.39                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 25        | 20.84                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 50      | 50        | 20.90                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | QPSK       | 100     | 0         | 21.29                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 0         | 21.49                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 50        | 21.02                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 1       | 99        | 21.29                 | 0-1                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 0         | 21.10                 | 0-2                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 25        | 21.06                 | 0-2                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 50      | 50        | 20.99                 | 0-2                       | 0        |
|     | 1732.5          | 20175   | 20              | 16QAM      | 100     | 0         | 21.18                 | 0-2                       | 0        |

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 62 of 119                         |

**Table 9-38**  
**LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1717.5          | 20025   | 15              | QPSK       | 1       | 0         | 21.35                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 1       | 36        | 20.81                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 1       | 74        | 21.10                 | 0                         | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 0         | 21.03                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 18        | 20.91                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 36      | 37        | 20.92                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | QPSK       | 75      | 0         | 20.97                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 0         | 21.49                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 36        | 21.37                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 1       | 74        | 21.48                 | 0-1                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 0         | 21.08                 | 0-2                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 18        | 20.90                 | 0-2                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 36      | 37        | 20.91                 | 0-2                       | 0        |
|      | 1717.5          | 20025   | 15              | 16QAM      | 75      | 0         | 20.97                 | 0-2                       | 0        |
| Mid  | 1732.5          | 20175   | 15              | QPSK       | 1       | 0         | 21.50                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 1       | 36        | 21.10                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 1       | 74        | 21.26                 | 0                         | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 0         | 21.22                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 18        | 21.07                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 36      | 37        | 21.03                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | QPSK       | 75      | 0         | 21.08                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 0         | 21.50                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 36        | 21.06                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 1       | 74        | 21.18                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 0         | 21.21                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 18        | 21.09                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 36      | 37        | 21.05                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 15              | 16QAM      | 75      | 0         | 21.22                 | 0-2                       | 0        |
| High | 1747.5          | 20325   | 15              | QPSK       | 1       | 0         | 21.50                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 1       | 36        | 21.48                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 1       | 74        | 21.38                 | 0                         | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 0         | 21.38                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 18        | 21.23                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 36      | 37        | 21.20                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | QPSK       | 75      | 0         | 21.25                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 0         | 21.44                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 36        | 21.50                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 1       | 74        | 21.49                 | 0-1                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 0         | 21.44                 | 0-2                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 18        | 21.27                 | 0-2                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 36      | 37        | 21.13                 | 0-2                       | 0        |
|      | 1747.5          | 20325   | 15              | 16QAM      | 75      | 0         | 21.25                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-39**  
**LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1715            | 20000   | 10              | QPSK       | 1       | 0         | 21.03                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 1       | 25        | 20.84                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 1       | 49        | 20.89                 | 0                         | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 0         | 20.94                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 12        | 20.85                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 25      | 25        | 20.82                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | QPSK       | 50      | 0         | 20.88                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 0         | 21.27                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 25        | 20.97                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 1       | 49        | 21.21                 | 0-1                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 0         | 20.96                 | 0-2                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 12        | 20.89                 | 0-2                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 25      | 25        | 20.88                 | 0-2                       | 0        |
|      | 1715            | 20000   | 10              | 16QAM      | 50      | 0         | 20.90                 | 0-2                       | 0        |
| Mid  | 1732.5          | 20175   | 10              | QPSK       | 1       | 0         | 21.41                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 1       | 25        | 21.09                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 1       | 49        | 21.22                 | 0                         | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 0         | 21.16                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 12        | 21.03                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 25      | 25        | 21.03                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | QPSK       | 50      | 0         | 21.09                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 0         | 21.50                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 25        | 21.48                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 1       | 49        | 21.43                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 0         | 21.19                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 12        | 21.06                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 25      | 25        | 21.07                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 10              | 16QAM      | 50      | 0         | 21.11                 | 0-2                       | 0        |
| High | 1750            | 20350   | 10              | QPSK       | 1       | 0         | 21.50                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 1       | 25        | 21.12                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 1       | 49        | 21.20                 | 0                         | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 0         | 21.26                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 12        | 21.23                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 25      | 25        | 21.11                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | QPSK       | 50      | 0         | 21.22                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 0         | 21.30                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 25        | 21.20                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 1       | 49        | 21.47                 | 0-1                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 0         | 21.32                 | 0-2                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 12        | 21.28                 | 0-2                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 25      | 25        | 21.17                 | 0-2                       | 0        |
|      | 1750            | 20350   | 10              | 16QAM      | 50      | 0         | 21.23                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-40**  
**LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1712.5          | 19975   | 5               | QPSK       | 1       | 0         | 20.98                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 1       | 12        | 21.07                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 1       | 24        | 21.04                 | 0                         | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 0         | 20.82                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 6         | 20.84                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 12      | 13        | 20.78                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | QPSK       | 25      | 0         | 20.83                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 0         | 21.38                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 12        | 21.17                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 1       | 24        | 21.31                 | 0-1                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 0         | 20.86                 | 0-2                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 6         | 20.87                 | 0-2                       | 0        |
|      | 1712.5          | 19975   | 5               | 16-QAM     | 12      | 13        | 20.82                 | 0-2                       | 0        |
| Mid  | 1732.5          | 20175   | 5               | QPSK       | 1       | 0         | 21.49                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 1       | 12        | 21.13                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 1       | 24        | 21.14                 | 0                         | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 0         | 21.09                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 6         | 21.08                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 12      | 13        | 21.06                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | QPSK       | 25      | 0         | 21.03                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 0         | 21.50                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 12        | 21.03                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 1       | 24        | 21.43                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 0         | 21.07                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 6         | 21.05                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 12      | 13        | 21.08                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 5               | 16-QAM     | 25      | 0         | 21.02                 | 0-2                       | 0        |
| High | 1752.5          | 20375   | 5               | QPSK       | 1       | 0         | 21.34                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 1       | 12        | 21.26                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 1       | 24        | 21.14                 | 0                         | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 0         | 21.20                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 6         | 21.18                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 12      | 13        | 21.17                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | QPSK       | 25      | 0         | 21.17                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 0         | 21.28                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 12        | 21.46                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 1       | 24        | 21.46                 | 0-1                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 0         | 21.22                 | 0-2                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 6         | 21.19                 | 0-2                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 12      | 13        | 21.17                 | 0-2                       | 0        |
|      | 1752.5          | 20375   | 5               | 16-QAM     | 25      | 0         | 21.18                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-41**  
**LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1711.5          | 19965   | 3               | QPSK       | 1       | 0         | 20.76                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 1       | 7         | 21.07                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 1       | 14        | 20.76                 | 0                         | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 0         | 20.78                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 4         | 20.83                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 8       | 7         | 20.74                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | QPSK       | 15      | 0         | 20.77                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 0         | 21.37                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 7         | 21.48                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 1       | 14        | 21.41                 | 0-1                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 0         | 20.89                 | 0-2                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 4         | 20.90                 | 0-2                       | 0        |
|      | 1711.5          | 19965   | 3               | 16-QAM     | 8       | 7         | 20.87                 | 0-2                       | 0        |
| Mid  | 1711.5          | 19965   | 3               | 16-QAM     | 15      | 0         | 20.81                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 1       | 0         | 21.23                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 1       | 7         | 21.26                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 1       | 14        | 21.14                 | 0                         | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 0         | 21.00                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 4         | 21.04                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 8       | 7         | 21.07                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | QPSK       | 15      | 0         | 21.02                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 0         | 21.28                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 7         | 21.31                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 1       | 14        | 21.14                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 0         | 21.02                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 4         | 20.99                 | 0-2                       | 0        |
| High | 1732.5          | 20175   | 3               | 16-QAM     | 8       | 7         | 21.07                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 3               | 16-QAM     | 15      | 0         | 21.04                 | 0-2                       | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 1       | 0         | 21.17                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 1       | 7         | 21.49                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 1       | 14        | 21.15                 | 0                         | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 0         | 21.14                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 4         | 21.25                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 8       | 7         | 21.17                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | QPSK       | 15      | 0         | 21.24                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 0         | 21.37                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 7         | 21.43                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 1       | 14        | 21.30                 | 0-1                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 0         | 21.18                 | 0-2                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 4         | 21.23                 | 0-2                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 8       | 7         | 21.23                 | 0-2                       | 0        |
|      | 1753.5          | 20385   | 3               | 16-QAM     | 15      | 0         | 21.19                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 66 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 9-42**  
**LTE Band 4 (AWS) Conducted Powers - 1.4 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 0         | 21.04                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 2         | 20.86                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 1       | 5         | 21.03                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 0         | 20.73                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 2         | 20.83                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 3       | 3         | 20.72                 | 0                         | 0        |
|      | 1710.7          | 19957   | 1.4             | QPSK       | 6       | 0         | 20.74                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 0         | 20.84                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 2         | 20.70                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 1       | 5         | 20.84                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 0         | 20.88                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 2         | 20.91                 | 0-1                       | 0        |
|      | 1710.7          | 19957   | 1.4             | 16-QAM     | 3       | 3         | 20.99                 | 0-1                       | 0        |
| Mid  | 1710.7          | 19957   | 1.4             | 16-QAM     | 6       | 0         | 20.86                 | 0-2                       | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 0         | 21.26                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 2         | 21.17                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 1       | 5         | 21.30                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 0         | 21.03                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 2         | 21.11                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 3       | 3         | 21.10                 | 0                         | 0        |
|      | 1732.5          | 20175   | 1.4             | QPSK       | 6       | 0         | 21.02                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 0         | 21.43                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 2         | 21.38                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 1       | 5         | 21.50                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 0         | 21.18                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 2         | 21.28                 | 0-1                       | 0        |
|      | 1732.5          | 20175   | 1.4             | 16-QAM     | 3       | 3         | 21.27                 | 0-1                       | 0        |
| High | 1732.5          | 20175   | 1.4             | 16-QAM     | 6       | 0         | 21.13                 | 0-2                       | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 0         | 21.43                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 2         | 21.40                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 1       | 5         | 21.49                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 0         | 21.21                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 2         | 21.29                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 3       | 3         | 21.18                 | 0                         | 0        |
|      | 1754.3          | 20393   | 1.4             | QPSK       | 6       | 0         | 21.20                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 0         | 21.47                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 2         | 21.28                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 1       | 5         | 21.40                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 0         | 21.45                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 2         | 21.49                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 3       | 3         | 21.47                 | 0-1                       | 0        |
|      | 1754.3          | 20393   | 1.4             | 16-QAM     | 6       | 0         | 21.48                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

## 9.5.2 LTE Band 2 (PCS) Conducted Powers - Extremity

Table 9-43  
LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1860            | 18700   | 20              | QPSK       | 1       | 0         | 20.95                 | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 1       | 50        | 20.02                 | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 1       | 99        | 20.25                 | 0                         | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 0         | 20.36                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 25        | 20.09                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 50      | 50        | 20.00                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | QPSK       | 100     | 0         | 20.25                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 0         | 20.94                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 50        | 20.11                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 1       | 99        | 20.37                 | 0-1                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 50      | 0         | 20.30                 | 0-2                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 50      | 25        | 20.07                 | 0-2                       | 0        |
| Mid  | 1860            | 18700   | 20              | 16QAM      | 50      | 50        | 20.06                 | 0-2                       | 0        |
|      | 1860            | 18700   | 20              | 16QAM      | 100     | 0         | 20.22                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 0         | 20.88                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 50        | 20.03                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 1       | 99        | 20.14                 | 0                         | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 0         | 20.38                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 25        | 20.05                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 50      | 50        | 20.02                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | QPSK       | 100     | 0         | 20.19                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 0         | 20.96                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 50        | 20.16                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 1       | 99        | 20.22                 | 0-1                       | 0        |
| High | 1880.0          | 18900   | 20              | 16QAM      | 50      | 0         | 20.35                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 50      | 25        | 20.02                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 50      | 50        | 20.03                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 20              | 16QAM      | 100     | 0         | 20.16                 | 0-2                       | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 0         | 20.86                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 50        | 20.05                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 1       | 99        | 20.13                 | 0                         | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 0         | 20.26                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 25        | 20.05                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 50      | 50        | 20.02                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | QPSK       | 100     | 0         | 20.12                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 0         | 20.94                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 50        | 20.14                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 1       | 99        | 20.20                 | 0-1                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 0         | 20.25                 | 0-2                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 25        | 20.06                 | 0-2                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 50      | 50        | 20.02                 | 0-2                       | 0        |
|      | 1900            | 19100   | 20              | 16QAM      | 100     | 0         | 20.10                 | 0-2                       | 0        |

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 68 of 119                  |

**Table 9-44**  
**LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1857.5          | 18675   | 15              | QPSK       | 1       | 0         | 20.92                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 1       | 36        | 20.19                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 1       | 74        | 20.33                 | 0                         | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 0         | 20.49                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 18        | 20.23                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 36      | 37        | 20.19                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | QPSK       | 75      | 0         | 20.25                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 0         | 20.91                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 36        | 20.40                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 1       | 74        | 20.44                 | 0-1                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 36      | 0         | 20.51                 | 0-2                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 36      | 18        | 20.22                 | 0-2                       | 0        |
| Mid  | 1857.5          | 18675   | 15              | 16QAM      | 36      | 37        | 20.21                 | 0-2                       | 0        |
|      | 1857.5          | 18675   | 15              | 16QAM      | 75      | 0         | 20.29                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 0         | 20.98                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 36        | 20.38                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 1       | 74        | 20.45                 | 0                         | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 0         | 20.42                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 18        | 20.21                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 36      | 37        | 20.13                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | QPSK       | 75      | 0         | 20.25                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 0         | 20.98                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 36        | 20.42                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 1       | 74        | 20.39                 | 0-1                       | 0        |
| High | 1880.0          | 18900   | 15              | 16QAM      | 36      | 0         | 20.44                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 36      | 18        | 20.23                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 36      | 37        | 20.14                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 15              | 16QAM      | 75      | 0         | 20.24                 | 0-2                       | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 0         | 20.97                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 36        | 20.25                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 1       | 74        | 20.39                 | 0                         | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 0         | 20.34                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 18        | 20.14                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 36      | 37        | 20.05                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | QPSK       | 75      | 0         | 20.20                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 0         | 20.97                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 36        | 20.36                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 1       | 74        | 20.33                 | 0-1                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 0         | 20.36                 | 0-2                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 18        | 20.15                 | 0-2                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 36      | 37        | 20.03                 | 0-2                       | 0        |
|      | 1902.5          | 19125   | 15              | 16QAM      | 75      | 0         | 20.18                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 69 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 9-45**  
**LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1855            | 18650   | 10              | QPSK       | 1       | 0         | 20.67                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 1       | 25        | 20.47                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 1       | 49        | 20.43                 | 0                         | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 0         | 20.41                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 12        | 20.21                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 25      | 25        | 20.14                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | QPSK       | 50      | 0         | 20.23                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 0         | 20.86                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 25        | 20.44                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 1       | 49        | 20.42                 | 0-1                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 0         | 20.42                 | 0-2                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 12        | 20.20                 | 0-2                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 25      | 25        | 20.15                 | 0-2                       | 0        |
|      | 1855            | 18650   | 10              | 16QAM      | 50      | 0         | 20.19                 | 0-2                       | 0        |
| Mid  | 1880.0          | 18900   | 10              | QPSK       | 1       | 0         | 20.57                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 1       | 25        | 20.20                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 1       | 49        | 20.23                 | 0                         | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 0         | 20.13                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 12        | 20.09                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 25      | 25        | 20.01                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | QPSK       | 50      | 0         | 20.11                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 0         | 20.73                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 25        | 20.36                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 1       | 49        | 20.34                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 0         | 20.15                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 12        | 20.09                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 25      | 25        | 20.04                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 10              | 16QAM      | 50      | 0         | 20.03                 | 0-2                       | 0        |
| High | 1905            | 19150   | 10              | QPSK       | 1       | 0         | 20.60                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 1       | 25        | 20.24                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 1       | 49        | 20.28                 | 0                         | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 0         | 20.19                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 12        | 20.11                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 25      | 25        | 20.06                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | QPSK       | 50      | 0         | 20.16                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 0         | 20.68                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 25        | 20.38                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 1       | 49        | 20.33                 | 0-1                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 0         | 20.24                 | 0-2                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 12        | 20.14                 | 0-2                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 25      | 25        | 20.09                 | 0-2                       | 0        |
|      | 1905            | 19150   | 10              | 16QAM      | 50      | 0         | 20.13                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-46**  
**LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1852.5          | 18625   | 5               | QPSK       | 1       | 0         | 20.46                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 1       | 12        | 20.19                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 1       | 24        | 20.33                 | 0                         | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 0         | 20.30                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 6         | 20.31                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 12      | 13        | 20.23                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | QPSK       | 25      | 0         | 20.28                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 0         | 20.91                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 12        | 20.44                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 1       | 24        | 20.73                 | 0-1                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 0         | 20.29                 | 0-2                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 6         | 20.30                 | 0-2                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 12      | 13        | 20.24                 | 0-2                       | 0        |
|      | 1852.5          | 18625   | 5               | 16-QAM     | 25      | 0         | 20.30                 | 0-2                       | 0        |
| Mid  | 1880.0          | 18900   | 5               | QPSK       | 1       | 0         | 20.18                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 1       | 12        | 20.00                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 1       | 24        | 20.05                 | 0                         | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 0         | 20.04                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 6         | 20.06                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 12      | 13        | 20.04                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | QPSK       | 25      | 0         | 20.04                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 0         | 20.66                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 12        | 20.37                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 1       | 24        | 20.49                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 0         | 20.05                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 6         | 20.05                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 12      | 13        | 20.02                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 5               | 16-QAM     | 25      | 0         | 20.06                 | 0-2                       | 0        |
| High | 1907.5          | 19175   | 5               | QPSK       | 1       | 0         | 20.24                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 1       | 12        | 20.06                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 1       | 24        | 20.19                 | 0                         | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 0         | 20.16                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 6         | 20.11                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 12      | 13        | 20.06                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | QPSK       | 25      | 0         | 20.11                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 0         | 20.69                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 12        | 20.30                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 1       | 24        | 20.57                 | 0-1                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 0         | 20.15                 | 0-2                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 6         | 20.13                 | 0-2                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 12      | 13        | 20.04                 | 0-2                       | 0        |
|      | 1907.5          | 19175   | 5               | 16-QAM     | 25      | 0         | 20.10                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 71 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 9-47**  
**LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1851.5          | 18615   | 3               | QPSK       | 1       | 0         | 20.38                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 1       | 7         | 20.44                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 1       | 14        | 20.29                 | 0                         | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 0         | 20.30                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 4         | 20.27                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 8       | 7         | 20.21                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | QPSK       | 15      | 0         | 20.23                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 0         | 20.61                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 7         | 20.93                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 1       | 14        | 20.51                 | 0-1                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 0         | 20.33                 | 0-2                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 4         | 20.32                 | 0-2                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 8       | 7         | 20.29                 | 0-2                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 15      | 0         | 20.24                 | 0-2                       | 0        |
|      | 1851.5          | 18615   | 3               | 16-QAM     | 15      | 0         | 20.24                 | 0-2                       | 0        |
| Mid  | 1880.0          | 18900   | 3               | QPSK       | 1       | 0         | 20.09                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 1       | 7         | 20.28                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 1       | 14        | 20.07                 | 0                         | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 0         | 20.02                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 4         | 20.03                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 8       | 7         | 20.00                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | QPSK       | 15      | 0         | 20.01                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 0         | 20.32                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 7         | 20.62                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 1       | 14        | 20.35                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 0         | 20.05                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 4         | 20.07                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 8       | 7         | 20.02                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 15      | 0         | 20.00                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 3               | 16-QAM     | 15      | 0         | 20.00                 | 0-2                       | 0        |
| High | 1908.5          | 19185   | 3               | QPSK       | 1       | 0         | 20.16                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 1       | 7         | 20.38                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 1       | 14        | 20.16                 | 0                         | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 0         | 20.09                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 4         | 20.10                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 8       | 7         | 20.08                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | QPSK       | 15      | 0         | 20.08                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 0         | 20.41                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 7         | 20.78                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 1       | 14        | 20.43                 | 0-1                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 0         | 20.15                 | 0-2                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 4         | 20.14                 | 0-2                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 8       | 7         | 20.13                 | 0-2                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 15      | 0         | 20.08                 | 0-2                       | 0        |
|      | 1908.5          | 19185   | 3               | 16-QAM     | 15      | 0         | 20.08                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

**Table 9-48**  
**LTE Band 2 (PCS) Conducted Powers - 1.4 MHz Bandwidth**

|      | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|------|-----------------|---------|-----------------|------------|---------|-----------|-----------------------|---------------------------|----------|
| Low  | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 0         | 20.38                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 2         | 20.50                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 1       | 5         | 20.34                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 0         | 20.33                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 2         | 20.37                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 3       | 3         | 20.33                 | 0                         | 0        |
|      | 1850.7          | 18607   | 1.4             | QPSK       | 6       | 0         | 20.33                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 0         | 20.26                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 2         | 20.65                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 1       | 5         | 20.18                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 0         | 20.22                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 2         | 20.35                 | 0-1                       | 0        |
|      | 1850.7          | 18607   | 1.4             | 16-QAM     | 3       | 3         | 20.41                 | 0-1                       | 0        |
| Mid  | 1850.7          | 18607   | 1.4             | 16-QAM     | 6       | 0         | 20.37                 | 0-2                       | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 0         | 20.25                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 2         | 20.84                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 1       | 5         | 20.20                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 0         | 20.31                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 2         | 20.36                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 3       | 3         | 20.32                 | 0                         | 0        |
|      | 1880.0          | 18900   | 1.4             | QPSK       | 6       | 0         | 20.33                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 0         | 20.06                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 2         | 20.43                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 1       | 5         | 20.30                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 0         | 20.13                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 2         | 20.17                 | 0-1                       | 0        |
|      | 1880.0          | 18900   | 1.4             | 16-QAM     | 3       | 3         | 20.12                 | 0-1                       | 0        |
| High | 1880.0          | 18900   | 1.4             | 16-QAM     | 6       | 0         | 20.07                 | 0-2                       | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 0         | 20.48                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 2         | 20.30                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 1       | 5         | 20.31                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 0         | 20.02                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 2         | 20.11                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 3       | 3         | 20.00                 | 0                         | 0        |
|      | 1909.3          | 19193   | 1.4             | QPSK       | 6       | 0         | 20.16                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 0         | 20.18                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 2         | 20.32                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 1       | 5         | 20.16                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 0         | 20.12                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 2         | 20.21                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 3       | 3         | 20.17                 | 0-1                       | 0        |
|      | 1909.3          | 19193   | 1.4             | 16-QAM     | 6       | 0         | 20.13                 | 0-2                       | 0        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 73 of 119                    |                                                                                                                                                                                                        |                                 |

## 9.6 LTE Carrier Aggregation Conducted Powers

### 9.6.1 Maximum LTE Carrier Aggregation Conducted Powers

Table 9-49

| PCC      |                     |                          |                  |            |                  | SCC      |                     |                          |                  | Power                     |                           |
|----------|---------------------|--------------------------|------------------|------------|------------------|----------|---------------------|--------------------------|------------------|---------------------------|---------------------------|
| PCC Band | PCC Bandwidth [MHz] | PCC (UL) Frequency [MHz] | PCC (UL) Channel | PCC UL# RB | PCC UL RB Offset | SCC Band | SCC Bandwidth [MHz] | SCC (DL) Frequency [MHz] | SCC (DL) Channel | LTE Rel 10 Tx.Power (dBm) | LTE Rel. 8 Tx.Power (dBm) |
| LTE B13  | 10                  | 782                      | 23230            | 1          | 0                | LTE B4   | 20                  | 2132.5                   | 2175             | 24.42                     | 24.34                     |
| LTE B13  | 10                  | 782                      | 23230            | 1          | 0                | LTE B2   | 20                  | 1960                     | 900              | 24.44                     | 24.34                     |
| LTE B5   | 5                   | 846.5                    | 20625            | 1          | 0                | LTE B4   | 20                  | 2132.5                   | 2175             | 24.58                     | 24.49                     |
| LTE B5   | 5                   | 846.5                    | 20625            | 1          | 0                | LTE B2   | 20                  | 1960                     | 900              | 24.63                     | 24.49                     |
| LTE B4   | 15                  | 1717.5                   | 20025            | 1          | 0                | LTE B13  | 10                  | 751                      | 5230             | 24.44                     | 24.50                     |
| LTE B4   | 15                  | 1717.5                   | 20025            | 1          | 0                | LTE B5   | 10                  | 881.5                    | 2525             | 24.48                     | 24.50                     |
| LTE B4   | 15                  | 1717.5                   | 20025            | 1          | 0                | LTE B4   | 20                  | 2132.5                   | 2175             | 24.39                     | 24.50                     |
| LTE B4   | 15                  | 1717.5                   | 20025            | 1          | 0                | LTE B2   | 20                  | 1960                     | 900              | 24.43                     | 24.50                     |
| LTE B2   | 15                  | 1857.5                   | 18675            | 1          | 0                | LTE B13  | 10                  | 751                      | 5230             | 23.48                     | 24.00                     |
| LTE B2   | 15                  | 1857.5                   | 18675            | 1          | 0                | LTE B5   | 10                  | 881.5                    | 2525             | 23.56                     | 24.00                     |
| LTE B2   | 15                  | 1857.5                   | 18675            | 1          | 0                | LTE B4   | 20                  | 2132.5                   | 2175             | 23.65                     | 24.00                     |
| LTE B2   | 15                  | 1857.5                   | 18675            | 1          | 0                | LTE B2   | 20                  | 1960                     | 900              | 23.47                     | 24.00                     |

### 9.6.2 Reduced LTE Carrier Aggregation Conducted Powers – Hotspot

Table 9-50

| PCC      |                     |                          |                  |            |                  | SCC      |                     |                          |                  | Power                     |                           |
|----------|---------------------|--------------------------|------------------|------------|------------------|----------|---------------------|--------------------------|------------------|---------------------------|---------------------------|
| PCC Band | PCC Bandwidth [MHz] | PCC (UL) Frequency [MHz] | PCC (UL) Channel | PCC UL# RB | PCC UL RB Offset | SCC Band | SCC Bandwidth [MHz] | SCC (DL) Frequency [MHz] | SCC (DL) Channel | LTE Rel 10 Tx.Power (dBm) | LTE Rel. 8 Tx.Power (dBm) |
| LTE B4   | 15                  | 1747.5                   | 20325            | 1          | 0                | LTE B13  | 10                  | 751                      | 5230             | 20.21                     | 20.23                     |
| LTE B4   | 15                  | 1747.5                   | 20325            | 1          | 0                | LTE B5   | 10                  | 881.5                    | 2525             | 20.33                     | 20.23                     |
| LTE B4   | 15                  | 1747.5                   | 20325            | 1          | 0                | LTE B4   | 20                  | 2132.5                   | 2175             | 20.17                     | 20.23                     |
| LTE B4   | 15                  | 1747.5                   | 20325            | 1          | 0                | LTE B2   | 20                  | 1960                     | 900              | 20.47                     | 20.23                     |
| LTE B2   | 20                  | 1860                     | 18700            | 1          | 0                | LTE B13  | 10                  | 751                      | 5230             | 19.77                     | 19.96                     |
| LTE B2   | 20                  | 1860                     | 18700            | 1          | 0                | LTE B5   | 10                  | 881.5                    | 2525             | 19.89                     | 19.96                     |
| LTE B2   | 20                  | 1860                     | 18700            | 1          | 0                | LTE B4   | 20                  | 2132.5                   | 2175             | 19.78                     | 19.96                     |
| LTE B2   | 20                  | 1860                     | 18700            | 1          | 0                | LTE B2   | 20                  | 1960                     | 900              | 19.78                     | 19.96                     |

### 9.6.3 Reduced LTE Carrier Aggregation Conducted Powers – Extremity


Table 9-51

| PCC      |                     |                          |                  |            |                  | SCC      |                     |                          |                  | Power                     |                           |
|----------|---------------------|--------------------------|------------------|------------|------------------|----------|---------------------|--------------------------|------------------|---------------------------|---------------------------|
| PCC Band | PCC Bandwidth [MHz] | PCC (UL) Frequency [MHz] | PCC (UL) Channel | PCC UL# RB | PCC UL RB Offset | SCC Band | SCC Bandwidth [MHz] | SCC (DL) Frequency [MHz] | SCC (DL) Channel | LTE Rel 10 Tx.Power (dBm) | LTE Rel. 8 Tx.Power (dBm) |
| LTE B4   | 15                  | 1747.5                   | 20325            | 1          | 0                | LTE B13  | 10                  | 751                      | 5230             | 21.44                     | 21.50                     |
| LTE B4   | 15                  | 1747.5                   | 20325            | 1          | 0                | LTE B5   | 10                  | 881.5                    | 2525             | 21.47                     | 21.50                     |
| LTE B4   | 15                  | 1747.5                   | 20325            | 1          | 0                | LTE B4   | 20                  | 2132.5                   | 2175             | 21.43                     | 21.50                     |
| LTE B4   | 15                  | 1747.5                   | 20325            | 1          | 0                | LTE B2   | 20                  | 1960                     | 900              | 21.44                     | 21.50                     |
| LTE B2   | 15                  | 1880                     | 18900            | 1          | 0                | LTE B13  | 10                  | 751                      | 5230             | 20.62                     | 20.98                     |
| LTE B2   | 15                  | 1880                     | 18900            | 1          | 0                | LTE B5   | 10                  | 881.5                    | 2525             | 20.82                     | 20.98                     |
| LTE B2   | 15                  | 1880                     | 18900            | 1          | 0                | LTE B4   | 20                  | 2132.5                   | 2175             | 20.67                     | 20.98                     |
| LTE B2   | 15                  | 1880                     | 18900            | 1          | 0                | LTE B2   | 20                  | 1960                     | 900              | 20.60                     | 20.98                     |

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 74 of 119                  |

Notes:

1. The device does not support all Rel. 10 Carrier Aggregation features due to modem chipset limitation.
2. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. Power measurements were performed with two DL carriers for the Release 8 configuration that had the highest output power (across all bandwidths, channels and RB Configurations) for each band
3. This device supports inter-band CA and intra-band CA with 2 carriers.
4. All control and acknowledge data is sent on uplink channels that operate identical to release 8 specifications.



**Figure 9-4**  
**Power Measurement Setup**

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 75 of 119                         |

## 9.7 Maximum WLAN Conducted Powers

Table 9-52

2.4 GHz WLAN Maximum Average RF Power – Antenna 1

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |         |
|------------|---------|------------------------------|---------|
|            |         | IEEE Transmission Mode       |         |
|            |         | 802.11b                      | 802.11g |
| 2412       | 1       | 16.78                        | 13.82   |
| 2437       | 6       | 17.42                        | 14.46   |
| 2462       | 11      | 16.75                        | 14.00   |

Table 9-53

2.4 GHz WLAN Maximum Average RF Power – Antenna 2

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |         |
|------------|---------|------------------------------|---------|
|            |         | IEEE Transmission Mode       |         |
|            |         | 802.11b                      | 802.11g |
| 2412       | 1       | 16.85                        | 14.28   |
| 2437       | 6       | 16.45                        | 13.71   |
| 2462       | 11      | 16.76                        | 14.10   |

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 76 of 119                  |

**Table 9-54**  
**5 GHz WLAN Maximum Average RF Power – Antenna 1**

| Freq [MHz] | Channel | 5GHz (20MHz) Conducted Power [dBm] |         |          |
|------------|---------|------------------------------------|---------|----------|
|            |         | IEEE Transmission Mode             |         |          |
|            |         | 802.11a                            | 802.11n | 802.11ac |
| 5180       | 36      | 13.12                              | 12.89   | 13.08    |
| 5200       | 40      | 13.31                              | 13.01   | 13.00    |
| 5220       | 44      | 13.19                              | 12.99   | 12.92    |
| 5240       | 48      | 13.27                              | 12.89   | 12.93    |
| 5260       | 52      | 13.35                              | 12.98   | 12.89    |
| 5280       | 56      | 12.67                              | 13.00   | 12.82    |
| 5300       | 60      | 13.21                              | 12.76   | 12.80    |
| 5320       | 64      | 13.05                              | 12.83   | 12.77    |
| 5500       | 100     | 12.81                              | 13.40   | 13.36    |
| 5600       | 120     | 12.77                              | 12.75   | 13.38    |
| 5620       | 124     | 12.80                              | 12.68   | 13.26    |
| 5720       | 144     | 13.29                              | 12.71   | 12.67    |
| 5745       | 149     | 13.05                              | 13.24   | 13.14    |
| 5785       | 157     | 12.96                              | 13.23   | 13.24    |
| 5825       | 165     | 13.12                              | 13.10   | 13.16    |

**Table 9-55**  
**5 GHz WLAN Maximum Average RF Power – Antenna 2**

| Freq [MHz] | Channel | 5GHz (20MHz) Conducted Power [dBm] |         |          |
|------------|---------|------------------------------------|---------|----------|
|            |         | IEEE Transmission Mode             |         |          |
|            |         | 802.11a                            | 802.11n | 802.11ac |
| 5180       | 36      | 13.40                              | 13.30   | 13.25    |
| 5200       | 40      | 12.80                              | 13.25   | 13.26    |
| 5220       | 44      | 13.27                              | 13.36   | 13.30    |
| 5240       | 48      | 13.28                              | 13.31   | 13.43    |
| 5260       | 52      | 12.85                              | 13.41   | 13.25    |
| 5280       | 56      | 13.00                              | 13.25   | 13.22    |
| 5300       | 60      | 13.04                              | 13.33   | 13.18    |
| 5320       | 64      | 13.05                              | 13.28   | 13.38    |
| 5500       | 100     | 13.19                              | 13.14   | 13.23    |
| 5600       | 120     | 13.10                              | 12.79   | 13.13    |
| 5620       | 124     | 12.99                              | 12.81   | 13.06    |
| 5720       | 144     | 12.75                              | 12.79   | 13.19    |
| 5745       | 149     | 12.84                              | 12.89   | 13.14    |
| 5785       | 157     | 12.75                              | 13.00   | 13.07    |
| 5825       | 165     | 12.75                              | 12.93   | 13.00    |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 77 of 119                                                                        |                                 |

## 9.8 WLAN Conducted Powers – Held to Ear

Table 9-56

2.4 GHz WLAN Held to Ear Average RF Power – Antenna 1

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |         |         |
|------------|---------|------------------------------|---------|---------|
|            |         | IEEE Transmission Mode       |         |         |
|            |         | 802.11b                      | 802.11g | 802.11n |
| 2412       | 1       | 14.79                        | 13.33   | 13.08   |
| 2437       | 6       | 15.00                        | 13.28   | 12.50   |
| 2462       | 11      | 15.45                        | 13.17   | 12.92   |

Table 9-57

2.4 GHz WLAN Held to Ear Average RF Power – Antenna 2

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |         |         |
|------------|---------|------------------------------|---------|---------|
|            |         | IEEE Transmission Mode       |         |         |
|            |         | 802.11b                      | 802.11g | 802.11n |
| 2412       | 1       | 15.44                        | 13.46   | 13.49   |
| 2437       | 6       | 14.82                        | 13.49   | 12.11   |
| 2462       | 11      | 14.73                        | 13.47   | 13.40   |

Table 9-58

2.4 GHz WLAN Held to Ear Average RF Power – MIMO

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |
|------------|---------|------------------------------|
|            |         | MIMO                         |
| 2412       | 1       | 16.30                        |
| 2437       | 6       | 15.32                        |
| 2462       | 11      | 16.18                        |

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 78 of 119                  |

**Table 9-59**  
**5 GHz WLAN Held to Ear Average RF Power – Antenna 1**

| Freq [MHz] | Channel | 5GHz (20MHz)<br>Conducted<br>Power [dBm] |
|------------|---------|------------------------------------------|
|            |         | IEEE<br>Transmission<br>Mode             |
|            |         | 802.11a                                  |
| 5180       | 36      | 9.95                                     |
| 5200       | 40      | 10.03                                    |
| 5220       | 44      | 10.08                                    |
| 5240       | 48      | 10.06                                    |
| 5260       | 52      | 10.10                                    |
| 5280       | 56      | 10.13                                    |
| 5300       | 60      | 9.96                                     |
| 5320       | 64      | 9.98                                     |
| 5500       | 100     | 10.01                                    |
| 5600       | 120     | 9.74                                     |
| 5620       | 124     | 9.63                                     |
| 5720       | 144     | 9.50                                     |
| 5745       | 149     | 10.45                                    |
| 5785       | 157     | 10.06                                    |
| 5825       | 165     | 10.03                                    |


**Table 9-60**  
**5 GHz WLAN Held to Ear Average RF Power – Antenna 2**

| Freq [MHz] | Channel | 5GHz (20MHz)<br>Conducted<br>Power [dBm] |
|------------|---------|------------------------------------------|
|            |         | IEEE<br>Transmission<br>Mode             |
|            |         | 802.11a                                  |
| 5180       | 36      | 10.49                                    |
| 5200       | 40      | 10.44                                    |
| 5220       | 44      | 10.32                                    |
| 5240       | 48      | 10.41                                    |
| 5260       | 52      | 10.48                                    |
| 5280       | 56      | 10.26                                    |
| 5300       | 60      | 10.47                                    |
| 5320       | 64      | 10.44                                    |
| 5500       | 100     | 10.36                                    |
| 5600       | 120     | 10.24                                    |
| 5620       | 124     | 10.26                                    |
| 5720       | 144     | 10.11                                    |
| 5745       | 149     | 10.06                                    |
| 5785       | 157     | 10.32                                    |
| 5825       | 165     | 10.34                                    |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

Justification for test configurations for WLAN per KDB Publication 248227 D01DR02-41929:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.



**Figure 9-5**  
**Power Measurement Setup**

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 80 of 119                         |

## 10 SYSTEM VERIFICATION

### 10.1 Tissue Verification

**Table 10-1**  
**Measured Tissue Properties (Head)**

| Calibrated for Tests Performed on: | Tissue Type | Tissue Temp During Calibration (C°) | Measured Frequency (MHz) | Measured Conductivity, $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon$ | TARGET Conductivity, $\sigma$ (S/m) | TARGET Dielectric Constant, $\epsilon$ | % dev $\sigma$ | % dev $\epsilon$ |
|------------------------------------|-------------|-------------------------------------|--------------------------|---------------------------------------|------------------------------------------|-------------------------------------|----------------------------------------|----------------|------------------|
| 06/22/2015                         | 750H        | 24.5                                | 725                      | 0.873                                 | 42.294                                   | 0.891                               | 42.071                                 | -2.02%         | 0.53%            |
|                                    |             |                                     | 740                      | 0.886                                 | 42.137                                   | 0.893                               | 41.994                                 | -0.78%         | 0.34%            |
|                                    |             |                                     | 755                      | 0.900                                 | 41.969                                   | 0.894                               | 41.916                                 | 0.67%          | 0.13%            |
|                                    |             |                                     | 770                      | 0.913                                 | 41.789                                   | 0.895                               | 41.838                                 | 2.01%          | -0.12%           |
|                                    |             |                                     | 785                      | 0.927                                 | 41.587                                   | 0.896                               | 41.760                                 | 3.46%          | -0.41%           |
| 06/26/2015                         | 835H        | 22.0                                | 820                      | 0.866                                 | 40.164                                   | 0.899                               | 41.578                                 | -3.67%         | -3.40%           |
|                                    |             |                                     | 835                      | 0.880                                 | 39.963                                   | 0.900                               | 41.500                                 | -2.22%         | -3.70%           |
|                                    |             |                                     | 850                      | 0.894                                 | 39.772                                   | 0.916                               | 41.500                                 | -2.40%         | -4.16%           |
| 06/29/2015                         | 1750H       | 21.0                                | 1710                     | 1.343                                 | 40.258                                   | 1.348                               | 40.142                                 | -0.37%         | 0.29%            |
|                                    |             |                                     | 1750                     | 1.387                                 | 40.026                                   | 1.371                               | 40.079                                 | 1.17%          | -0.13%           |
|                                    |             |                                     | 1790                     | 1.432                                 | 39.872                                   | 1.394                               | 40.016                                 | 2.73%          | -0.36%           |
| 06/14/2015                         | 1900H       | 22.0                                | 1850                     | 1.364                                 | 39.792                                   | 1.400                               | 40.000                                 | -2.57%         | -0.52%           |
|                                    |             |                                     | 1880                     | 1.395                                 | 39.656                                   | 1.400                               | 40.000                                 | -0.36%         | -0.86%           |
|                                    |             |                                     | 1910                     | 1.429                                 | 39.558                                   | 1.400                               | 40.000                                 | 2.07%          | -1.11%           |
| 06/25/2015                         | 2400H       | 21.9                                | 2400                     | 1.817                                 | 39.448                                   | 1.756                               | 39.289                                 | 3.47%          | 0.40%            |
|                                    |             |                                     | 2450                     | 1.877                                 | 39.244                                   | 1.800                               | 39.200                                 | 4.28%          | 0.11%            |
|                                    |             |                                     | 2500                     | 1.934                                 | 39.049                                   | 1.855                               | 39.136                                 | 4.26%          | -0.22%           |
| 06/25/2015                         | 5200H-5800H | 21.6                                | 5260                     | 4.606                                 | 35.720                                   | 4.717                               | 35.917                                 | -2.35%         | -0.55%           |
|                                    |             |                                     | 5280                     | 4.611                                 | 35.693                                   | 4.737                               | 35.894                                 | -2.66%         | -0.56%           |
|                                    |             |                                     | 5300                     | 4.619                                 | 35.613                                   | 4.758                               | 35.871                                 | -2.92%         | -0.72%           |
|                                    |             |                                     | 5500                     | 4.835                                 | 35.320                                   | 4.963                               | 35.643                                 | -2.58%         | -0.91%           |
|                                    |             |                                     | 5745                     | 5.055                                 | 34.999                                   | 5.214                               | 35.363                                 | -3.05%         | -1.03%           |
|                                    |             |                                     | 5800                     | 5.134                                 | 34.874                                   | 5.270                               | 35.300                                 | -2.58%         | -1.21%           |
|                                    |             |                                     | 5825                     | 5.156                                 | 34.889                                   | 5.296                               | 35.271                                 | -2.64%         | -1.08%           |

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 81 of 119                         |

**Table 10-2**  
**Measured Tissue Properties (Body)**

| Calibrated for Tests Performed on: | Tissue Type | Tissue Temp During Calibration (C°) | Measured Frequency (MHz) | Measured Conductivity, $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon$ | TARGET Conductivity, $\sigma$ (S/m) | TARGET Dielectric Constant, $\epsilon$ | % dev $\sigma$ | % dev $\epsilon$ |
|------------------------------------|-------------|-------------------------------------|--------------------------|---------------------------------------|------------------------------------------|-------------------------------------|----------------------------------------|----------------|------------------|
| 06/22/2015                         | 750B        | 21.8                                | 725                      | 0.946                                 | 54.736                                   | 0.961                               | 55.629                                 | -1.56%         | -1.61%           |
|                                    |             |                                     | 740                      | 0.960                                 | 54.575                                   | 0.963                               | 55.570                                 | -0.31%         | -1.79%           |
|                                    |             |                                     | 755                      | 0.974                                 | 54.404                                   | 0.964                               | 55.512                                 | 1.04%          | -2.00%           |
|                                    |             |                                     | 770                      | 0.989                                 | 54.226                                   | 0.965                               | 55.453                                 | 2.49%          | -2.21%           |
|                                    |             |                                     | 785                      | 1.005                                 | 54.043                                   | 0.966                               | 55.395                                 | 4.04%          | -2.44%           |
| 06/25/2015                         | 750B        | 21.5                                | 725                      | 0.939                                 | 54.219                                   | 0.961                               | 55.629                                 | -2.29%         | -2.53%           |
|                                    |             |                                     | 740                      | 0.955                                 | 54.052                                   | 0.963                               | 55.570                                 | -0.83%         | -2.73%           |
|                                    |             |                                     | 755                      | 0.969                                 | 53.876                                   | 0.964                               | 55.512                                 | 0.52%          | -2.95%           |
|                                    |             |                                     | 770                      | 0.984                                 | 53.751                                   | 0.965                               | 55.453                                 | 1.97%          | -3.07%           |
|                                    |             |                                     | 785                      | 0.998                                 | 53.516                                   | 0.966                               | 55.395                                 | 3.31%          | -3.39%           |
| 06/22/2015                         | 835B        | 21.7                                | 820                      | 0.974                                 | 53.023                                   | 0.969                               | 55.258                                 | 0.52%          | -4.04%           |
|                                    |             |                                     | 835                      | 0.988                                 | 52.868                                   | 0.970                               | 55.200                                 | 1.86%          | -4.22%           |
|                                    |             |                                     | 850                      | 1.003                                 | 52.733                                   | 0.988                               | 55.154                                 | 1.52%          | -4.39%           |
| 06/29/2015                         | 835B        | 21.9                                | 820                      | 0.977                                 | 53.879                                   | 0.969                               | 55.258                                 | 0.83%          | -2.50%           |
|                                    |             |                                     | 835                      | 0.993                                 | 53.688                                   | 0.970                               | 55.200                                 | 2.37%          | -2.74%           |
|                                    |             |                                     | 850                      | 1.005                                 | 53.594                                   | 0.988                               | 55.154                                 | 1.72%          | -2.83%           |
| 06/24/2015                         | 1750B       | 21.8                                | 1710                     | 1.430                                 | 51.251                                   | 1.463                               | 53.537                                 | -2.26%         | -4.27%           |
|                                    |             |                                     | 1750                     | 1.483                                 | 51.234                                   | 1.488                               | 53.432                                 | -0.34%         | -4.11%           |
|                                    |             |                                     | 1790                     | 1.516                                 | 50.974                                   | 1.514                               | 53.326                                 | 0.13%          | -4.41%           |
| 06/29/2015                         | 1750B       | 21.8                                | 1710                     | 1.414                                 | 51.733                                   | 1.463                               | 53.537                                 | -3.35%         | -3.37%           |
|                                    |             |                                     | 1750                     | 1.460                                 | 51.572                                   | 1.488                               | 53.432                                 | -1.88%         | -3.48%           |
|                                    |             |                                     | 1790                     | 1.506                                 | 51.441                                   | 1.514                               | 53.326                                 | -0.53%         | -3.53%           |
| 06/18/2015                         | 1900B       | 22.0                                | 1850                     | 1.488                                 | 51.750                                   | 1.520                               | 53.300                                 | -2.11%         | -2.91%           |
|                                    |             |                                     | 1880                     | 1.518                                 | 51.673                                   | 1.520                               | 53.300                                 | -0.13%         | -3.05%           |
|                                    |             |                                     | 1910                     | 1.552                                 | 51.506                                   | 1.520                               | 53.300                                 | 2.11%          | -3.37%           |
| 06/22/2015                         | 1900B       | 21.8                                | 1850                     | 1.487                                 | 52.264                                   | 1.520                               | 53.300                                 | -2.17%         | -1.94%           |
|                                    |             |                                     | 1880                     | 1.524                                 | 52.155                                   | 1.520                               | 53.300                                 | 0.26%          | -2.15%           |
|                                    |             |                                     | 1910                     | 1.560                                 | 52.026                                   | 1.520                               | 53.300                                 | 2.63%          | -2.39%           |
| 06/24/2015                         | 1900B       | 21.5                                | 1850                     | 1.502                                 | 51.032                                   | 1.520                               | 53.300                                 | -1.18%         | -4.26%           |
|                                    |             |                                     | 1880                     | 1.534                                 | 50.951                                   | 1.520                               | 53.300                                 | 0.92%          | -4.41%           |
|                                    |             |                                     | 1910                     | 1.568                                 | 50.812                                   | 1.520                               | 53.300                                 | 3.16%          | -4.67%           |
| 06/29/2015                         | 1900B       | 21.5                                | 1850                     | 1.491                                 | 51.974                                   | 1.520                               | 53.300                                 | -1.91%         | -2.49%           |
|                                    |             |                                     | 1880                     | 1.525                                 | 51.838                                   | 1.520                               | 53.300                                 | 0.33%          | -2.74%           |
|                                    |             |                                     | 1910                     | 1.563                                 | 51.731                                   | 1.520                               | 53.300                                 | 2.83%          | -2.94%           |
| 06/09/2015                         | 2450B       | 21.9                                | 2401                     | 1.964                                 | 51.549                                   | 1.903                               | 52.765                                 | 3.21%          | -2.30%           |
|                                    |             |                                     | 2450                     | 2.032                                 | 51.385                                   | 1.950                               | 52.700                                 | 4.21%          | -2.50%           |
|                                    |             |                                     | 2499                     | 2.094                                 | 51.188                                   | 2.019                               | 52.638                                 | 3.71%          | -2.75%           |
| 06/08/2015                         | 5200B-5800B | 21.2                                | 5260                     | 5.392                                 | 47.859                                   | 5.369                               | 48.933                                 | 0.43%          | -2.19%           |
|                                    |             |                                     | 5300                     | 5.456                                 | 47.753                                   | 5.416                               | 48.879                                 | 0.74%          | -2.30%           |
|                                    |             |                                     | 5320                     | 5.484                                 | 47.726                                   | 5.439                               | 48.851                                 | 0.83%          | -2.30%           |
|                                    |             |                                     | 5500                     | 5.718                                 | 47.478                                   | 5.650                               | 48.607                                 | 1.20%          | -2.32%           |
|                                    |             |                                     | 5700                     | 6.005                                 | 47.115                                   | 5.883                               | 48.336                                 | 2.07%          | -2.53%           |
|                                    |             |                                     | 5745                     | 6.061                                 | 46.998                                   | 5.936                               | 48.275                                 | 2.11%          | -2.65%           |
|                                    |             |                                     | 5800                     | 6.145                                 | 46.937                                   | 6.000                               | 48.200                                 | 2.42%          | -2.62%           |
|                                    |             |                                     | 5825                     | 6.174                                 | 46.898                                   | 6.029                               | 48.166                                 | 2.41%          | -2.63%           |

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |

## 10.2 Test System Verification

Prior to SAR assessment, the system is verified to  $\pm 10\%$  of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.


**Table 10-3**  
**System Verification Results – 1g**

| System Verification<br>TARGET & MEASURED |                        |             |            |                |                  |                 |           |          |                                   |                                     |                                         |                             |
|------------------------------------------|------------------------|-------------|------------|----------------|------------------|-----------------|-----------|----------|-----------------------------------|-------------------------------------|-----------------------------------------|-----------------------------|
| SAR System #                             | Tissue Frequency (MHz) | Tissue Type | Date:      | Amb. Temp (°C) | Liquid Temp (°C) | Input Power (W) | Dipole SN | Probe SN | Measured SAR <sub>1g</sub> (W/kg) | 1 W Target SAR <sub>1g</sub> (W/kg) | 1 W Normalized SAR <sub>1g</sub> (W/kg) | Deviation <sub>1g</sub> (%) |
| K                                        | 750                    | HEAD        | 06/22/2015 | 22.3           | 23.5             | 0.200           | 1003      | 3288     | 1.750                             | 8.090                               | 8.750                                   | 8.16%                       |
| K                                        | 835                    | HEAD        | 06/26/2015 | 22.5           | 22.2             | 0.200           | 4d132     | 3288     | 1.960                             | 9.250                               | 9.800                                   | 5.95%                       |
| H                                        | 1750                   | HEAD        | 06/29/2015 | 21.1           | 21.0             | 0.100           | 1051      | 3263     | 3.710                             | 36.200                              | 37.100                                  | 2.49%                       |
| G                                        | 1900                   | HEAD        | 06/14/2015 | 22.5           | 22.0             | 0.100           | 5d141     | 3318     | 4.310                             | 39.900                              | 43.100                                  | 8.02%                       |
| G                                        | 2450                   | HEAD        | 06/25/2015 | 20.5           | 21.4             | 0.100           | 719       | 3318     | 5.300                             | 52.100                              | 53.000                                  | 1.73%                       |
| D                                        | 5300                   | HEAD        | 06/25/2015 | 23.1           | 21.6             | 0.050           | 1057      | 7357     | 3.990                             | 84.700                              | 79.800                                  | -5.79%                      |
| D                                        | 5500                   | HEAD        | 06/25/2015 | 23.1           | 21.6             | 0.050           | 1057      | 7357     | 4.030                             | 84.300                              | 80.600                                  | -4.39%                      |
| D                                        | 5800                   | HEAD        | 06/25/2015 | 23.1           | 21.6             | 0.050           | 1057      | 7357     | 4.070                             | 81.100                              | 81.400                                  | 0.37%                       |
| K                                        | 750                    | BODY        | 06/22/2015 | 22.3           | 22.0             | 0.200           | 1003      | 3288     | 1.810                             | 8.460                               | 9.050                                   | 6.97%                       |
| K                                        | 750                    | BODY        | 06/25/2015 | 22.7           | 21.8             | 0.200           | 1003      | 3288     | 1.720                             | 8.460                               | 8.600                                   | 1.65%                       |
| G                                        | 835                    | BODY        | 06/22/2015 | 22.7           | 21.4             | 0.200           | 4d133     | 3318     | 1.970                             | 9.350                               | 9.850                                   | 5.35%                       |
| G                                        | 835                    | BODY        | 06/29/2015 | 23.3           | 22.0             | 0.200           | 4d132     | 3318     | 1.880                             | 9.140                               | 9.400                                   | 2.84%                       |
| K                                        | 1750                   | BODY        | 06/24/2015 | 22.5           | 22.0             | 0.100           | 1051      | 3288     | 3.990                             | 37.100                              | 39.900                                  | 7.55%                       |
| K                                        | 1750                   | BODY        | 06/29/2015 | 22.5           | 21.8             | 0.100           | 1051      | 3288     | 3.970                             | 37.100                              | 39.700                                  | 7.01%                       |
| H                                        | 1900                   | BODY        | 06/18/2015 | 22.0           | 22.0             | 0.100           | 5d141     | 3263     | 4.300                             | 40.000                              | 43.000                                  | 7.50%                       |
| H                                        | 1900                   | BODY        | 06/22/2015 | 23.3           | 21.8             | 0.100           | 5d141     | 3263     | 4.170                             | 40.000                              | 41.700                                  | 4.25%                       |
| H                                        | 1900                   | BODY        | 06/24/2015 | 20.9           | 21.5             | 0.100           | 5d141     | 3263     | 4.290                             | 40.000                              | 42.900                                  | 7.25%                       |
| H                                        | 1900                   | BODY        | 06/29/2015 | 20.9           | 21.5             | 0.100           | 5d141     | 3263     | 4.250                             | 40.000                              | 42.500                                  | 6.25%                       |
| G                                        | 2450                   | BODY        | 06/09/2015 | 21.5           | 21.9             | 0.100           | 719       | 3318     | 5.370                             | 51.800                              | 53.700                                  | 3.67%                       |
| E                                        | 5300                   | BODY        | 06/08/2015 | 22.6           | 21.3             | 0.050           | 1057      | 3589     | 3.890                             | 74.200                              | 77.800                                  | 4.85%                       |
| E                                        | 5500                   | BODY        | 06/08/2015 | 22.6           | 21.3             | 0.050           | 1057      | 3589     | 3.760                             | 79.200                              | 75.200                                  | -5.05%                      |
| E                                        | 5800                   | BODY        | 06/08/2015 | 22.4           | 21.3             | 0.050           | 1057      | 3589     | 3.450                             | 75.100                              | 69.000                                  | -8.12%                      |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 83 of 119                         |

**Table 10-4**  
**System Verification Results – 10g**

| System Verification<br>TARGET & MEASURED |                        |             |            |                |                  |                 |           |          |                                    |                                      |                                          |                              |
|------------------------------------------|------------------------|-------------|------------|----------------|------------------|-----------------|-----------|----------|------------------------------------|--------------------------------------|------------------------------------------|------------------------------|
| SAR System #                             | Tissue Frequency (MHz) | Tissue Type | Date:      | Amb. Temp (°C) | Liquid Temp (°C) | Input Power (W) | Dipole SN | Probe SN | Measured SAR <sub>10g</sub> (W/kg) | 1 W Target SAR <sub>10g</sub> (W/kg) | 1 W Normalized SAR <sub>10g</sub> (W/kg) | Deviation <sub>10g</sub> (%) |
| K                                        | 1750                   | BODY        | 06/24/2015 | 22.5           | 22.0             | 0.100           | 1051      | 3288     | 2.110                              | 20.000                               | 21.100                                   | 5.50%                        |
| H                                        | 1900                   | BODY        | 06/18/2015 | 22.0           | 22.0             | 0.100           | 5d141     | 3263     | 2.250                              | 21.200                               | 22.500                                   | 6.13%                        |
| H                                        | 1900                   | BODY        | 06/22/2015 | 23.3           | 21.8             | 0.100           | 5d141     | 3263     | 2.180                              | 21.200                               | 21.800                                   | 2.83%                        |
| H                                        | 1900                   | BODY        | 06/29/2015 | 20.9           | 21.5             | 0.100           | 5d141     | 3263     | 2.210                              | 21.200                               | 22.100                                   | 4.25%                        |
| E                                        | 5300                   | BODY        | 06/08/2015 | 22.6           | 21.3             | 0.050           | 1057      | 3589     | 1.090                              | 20.900                               | 21.800                                   | 4.31%                        |
| E                                        | 5500                   | BODY        | 06/08/2015 | 22.6           | 21.3             | 0.050           | 1057      | 3589     | 1.050                              | 22.000                               | 21.000                                   | -4.55%                       |
| E                                        | 5800                   | BODY        | 06/08/2015 | 22.4           | 21.3             | 0.050           | 1057      | 3589     | 0.966                              | 20.600                               | 19.320                                   | -6.21%                       |



**Figure 10-1**  
**System Verification Setup Diagram**



**Figure 10-2**  
**System Verification Setup Photo**

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 84 of 119                                                                        |                                        |

# 11 SAR DATA SUMMARY

## 11.1 Standalone Head SAR Data

**Table 11-1**  
**GSM 850 Head SAR**

| MEASUREMENT RESULTS                                                                               |     |           |         |                             |                       |                  |       |                                                 |                      |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|-----------|---------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|----------------------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |           |         |                             |                       |                  |       |                                                 |                      |            | (W/kg)   |                | (W/kg)          |        |
| 836.60                                                                                            | 190 | GSM 850   | GSM     | 33.5                        | 33.12                 | 0.04             | Right | Cheek                                           | 96361                | 1:8.3      | 0.234    | 1.091          | 0.255           | A1     |
| 836.60                                                                                            | 190 | GSM 850   | GSM     | 33.5                        | 33.12                 | -0.09            | Right | Tilt                                            | 96361                | 1:8.3      | 0.106    | 1.091          | 0.116           |        |
| 836.60                                                                                            | 190 | GSM 850   | GSM     | 33.5                        | 33.12                 | 0.01             | Left  | Cheek                                           | 96361                | 1:8.3      | 0.174    | 1.091          | 0.190           |        |
| 836.60                                                                                            | 190 | GSM 850   | GSM     | 33.5                        | 33.12                 | -0.06            | Left  | Tilt                                            | 96361                | 1:8.3      | 0.099    | 1.091          | 0.108           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |           |         |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                      |            |          |                |                 |        |

**Table 11-2**  
**UMTS 850 Head SAR Data**

| MEASUREMENT RESULTS                      |      |           |         |                             |                       |                  |                      |               |                      |            |          |                |                 |        |
|------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|----------------------|---------------|----------------------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                |      | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side                 | Test Position | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                      | Ch.  |           |         |                             |                       |                  |                      |               |                      |            | (W/kg)   |                | (W/kg)          |        |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | 0.03             | Right                | Cheek         | 96361                | 1:1        | 0.182    | 1.028          | 0.187           | A2     |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | -0.01            | Right                | Tilt          | 96361                | 1:1        | 0.074    | 1.028          | 0.076           |        |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | -0.06            | Left                 | Cheek         | 96361                | 1:1        | 0.148    | 1.028          | 0.152           |        |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | 0.07             | Left                 | Tilt          | 96361                | 1:1        | 0.081    | 1.028          | 0.083           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |      |           |         |                             |                       |                  | Head                 |               |                      |            |          |                |                 |        |
| Spatial Peak                             |      |           |         |                             |                       |                  | 1.6 W/kg (mW/g)      |               |                      |            |          |                |                 |        |
| Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  | averaged over 1 gram |               |                      |            |          |                |                 |        |

**Table 11-3**  
**GSM 1900 Head SAR Data**

| MEASUREMENT RESULTS                                                                               |     |           |         |                                       |                             |                     |       |                                                 |                            |               |          |                   |                    |        |
|---------------------------------------------------------------------------------------------------|-----|-----------|---------|---------------------------------------|-----------------------------|---------------------|-------|-------------------------------------------------|----------------------------|---------------|----------|-------------------|--------------------|--------|
| FREQUENCY                                                                                         |     | Mode/Band | Service | Maxim um<br>Allowed<br>Power<br>[dBm] | Conducted<br>Power<br>[dBm] | Power<br>Drift [dB] | Side  | Test<br>Position                                | Device<br>Serial<br>Number | Duty<br>Cycle | SAR (1g) | Scaling<br>Factor | Scaled SAR<br>(1g) | Plot # |
| MHz                                                                                               | Ch. |           |         |                                       |                             |                     |       |                                                 |                            |               | (W/kg)   |                   | (W/kg)             |        |
| 1880.00                                                                                           | 661 | GSM 1900  | GSM     | 30.5                                  | 29.68                       | -0.04               | Right | Cheek                                           | 9635F                      | 1:8.3         | 0.085    | 1.208             | 0.103              | A3     |
| 1880.00                                                                                           | 661 | GSM 1900  | GSM     | 30.5                                  | 29.68                       | -0.03               | Right | Tilt                                            | 9635F                      | 1:8.3         | 0.076    | 1.208             | 0.092              |        |
| 1880.00                                                                                           | 661 | GSM 1900  | GSM     | 30.5                                  | 29.68                       | -0.07               | Left  | Cheek                                           | 9635F                      | 1:8.3         | 0.078    | 1.208             | 0.094              |        |
| 1880.00                                                                                           | 661 | GSM 1900  | GSM     | 30.5                                  | 29.68                       | 0.19                | Left  | Tilt                                            | 9635F                      | 1:8.3         | 0.074    | 1.208             | 0.089              |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |           |         |                                       |                             |                     |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                            |               |          |                   |                    |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 85 of 119                  |

**Table 11-4**  
**UMTS 1900 Head SAR Data**

| MEASUREMENT RESULTS                                                                               |      |           |         |                             |                       |                  |                                                 |               |                      |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------------|----------------------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |      | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side                                            | Test Position | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch.  |           |         |                             |                       |                  |                                                 |               |                      |            | (W/kg)   |                | (W/kg)          |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 23.5                        | 23.22                 | 0.16             | Right                                           | Cheek         | 9635F                | 1:1        | 0.137    | 1.067          | 0.146           | A4     |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 23.5                        | 23.22                 | -0.15            | Right                                           | Tilt          | 9635F                | 1:1        | 0.103    | 1.067          | 0.110           |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 23.5                        | 23.22                 | 0.05             | Left                                            | Cheek         | 9635F                | 1:1        | 0.101    | 1.067          | 0.108           |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 23.5                        | 23.22                 | 0.11             | Left                                            | Tilt          | 9635F                | 1:1        | 0.102    | 1.067          | 0.109           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |               |                      |            |          |                |                 |        |

**Table 11-5**  
**Cell. CDMA/EVDO Head SAR Data**

| MEASUREMENT RESULTS                                                                               |     |            |             |                             |                       |                  |       |                                                 |                      |            |          |                |                 |      |
|---------------------------------------------------------------------------------------------------|-----|------------|-------------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|----------------------|------------|----------|----------------|-----------------|------|
| FREQUENCY                                                                                         |     | Mode/Band  | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot |
| MHz                                                                                               | Ch. |            |             |                             |                       |                  |       |                                                 |                      |            | (W/kg)   |                | (W/kg)          |      |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.80                 | 0.08             | Right | Cheek                                           | 96361                | 1:1        | 0.389    | 1.047          | 0.407           | A5   |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.80                 | 0.00             | Right | Tilt                                            | 96361                | 1:1        | 0.181    | 1.047          | 0.190           |      |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.80                 | -0.05            | Left  | Cheek                                           | 96361                | 1:1        | 0.297    | 1.047          | 0.311           |      |
| 836.52                                                                                            | 384 | Cell. CDMA | RC3 / SO55  | 25.0                        | 24.80                 | -0.14            | Left  | Tilt                                            | 96361                | 1:1        | 0.187    | 1.047          | 0.196           |      |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.79                 | 0.11             | Right | Cheek                                           | 96361                | 1:1        | 0.336    | 1.050          | 0.353           |      |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.79                 | 0.06             | Right | Tilt                                            | 96361                | 1:1        | 0.168    | 1.050          | 0.176           |      |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.79                 | -0.01            | Left  | Cheek                                           | 96361                | 1:1        | 0.240    | 1.050          | 0.252           |      |
| 836.52                                                                                            | 384 | Cell. CDMA | EVDO Rev. A | 25.0                        | 24.79                 | -0.05            | Left  | Tilt                                            | 96361                | 1:1        | 0.178    | 1.050          | 0.187           |      |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |            |             |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                      |            |          |                |                 |      |

**Table 11-6**  
**PCS CDMA/EVDO Head SAR Data**

| MEASUREMENT RESULTS                                                                               |     |           |             |                             |                       |                  |                                                 |               |                      |            |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|-----|-----------|-------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------------|----------------------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode/Band | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side                                            | Test Position | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |           |             |                             |                       |                  |                                                 |               |                      |            | (W/kg)   |                | (W/kg)          |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.25                 | -0.10            | Right                                           | Cheek         | 9660B                | 1:1        | 0.165    | 1.189          | 0.196           | A6     |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.25                 | 0.10             | Right                                           | Tilt          | 9660B                | 1:1        | 0.155    | 1.189          | 0.184           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.25                 | 0.17             | Left                                            | Cheek         | 9660B                | 1:1        | 0.135    | 1.189          | 0.161           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | RC3 / SO55  | 25.0                        | 24.25                 | -0.01            | Left                                            | Tilt          | 9660B                | 1:1        | 0.129    | 1.189          | 0.153           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 20.5                        | 20.02                 | 0.18             | Right                                           | Cheek         | 930ED                | 1:1        | 0.108    | 1.117          | 0.121           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 20.5                        | 20.02                 | -0.09            | Right                                           | Tilt          | 930ED                | 1:1        | 0.058    | 1.117          | 0.065           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 20.5                        | 20.02                 | -0.13            | Left                                            | Cheek         | 930ED                | 1:1        | 0.093    | 1.117          | 0.104           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 20.5                        | 20.02                 | 0.02             | Left                                            | Tilt          | 930ED                | 1:1        | 0.040    | 1.117          | 0.045           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.13                 | -0.10            | Right                                           | Cheek         | 9660B                | 1:1        | 0.160    | 1.222          | 0.196           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.13                 | 0.12             | Right                                           | Tilt          | 9660B                | 1:1        | 0.149    | 1.222          | 0.182           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.13                 | 0.03             | Left                                            | Cheek         | 9660B                | 1:1        | 0.109    | 1.222          | 0.133           |        |
| 1880.00                                                                                           | 600 | PCS CDMA  | EVDO Rev. A | 25.0                        | 24.13                 | -0.04            | Left                                            | Tilt          | 9660B                | 1:1        | 0.083    | 1.222          | 0.101           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |           |             |                             |                       |                  | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |               |                      |            |          |                |                 |        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 86 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 11-7**  
**LTE Band 13 Head SAR Data**

| MEASUREMENT RESULTS                                                                               |       |      |                 |                             |                       |                  |          |      |               |                                                 |         |           |                      |            |          |                |                 |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|-----------------|-----------------------------|-----------------------|------------------|----------|------|---------------|-------------------------------------------------|---------|-----------|----------------------|------------|----------|----------------|-----------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation                                      | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                 |                             |                       |                  |          |      |               |                                                 |         |           |                      |            | (W/kg)   |                | (W/kg)          |        |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 25.0                  | 24.34            | 0.03     | 0    | Right         | Cheek                                           | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.223          | 1.164           | 0.260  | A7 |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 24.0                  | 23.31            | 0.05     | 1    | Right         | Cheek                                           | QPSK    | 25        | 0                    | 96361      | 1:1      | 0.192          | 1.172           | 0.225  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 25.0                  | 24.34            | -0.14    | 0    | Right         | Tilt                                            | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.101          | 1.164           | 0.118  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 24.0                  | 23.31            | -0.01    | 1    | Right         | Tilt                                            | QPSK    | 25        | 0                    | 96361      | 1:1      | 0.087          | 1.172           | 0.102  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 25.0                  | 24.34            | -0.10    | 0    | Left          | Cheek                                           | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.157          | 1.164           | 0.183  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 24.0                  | 23.31            | 0.02     | 1    | Left          | Cheek                                           | QPSK    | 25        | 0                    | 96361      | 1:1      | 0.121          | 1.172           | 0.142  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 25.0                  | 24.34            | -0.13    | 0    | Left          | Tilt                                            | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.087          | 1.164           | 0.101  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 24.0                  | 23.31            | 0.01     | 1    | Left          | Tilt                                            | QPSK    | 25        | 0                    | 96361      | 1:1      | 0.074          | 1.172           | 0.087  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                 |                             |                       |                  |          |      |               | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |           |                      |            |          |                |                 |        |    |

**Table 11-8**  
**LTE Band 5 (Cell) Head SAR Data**

| MEASUREMENT RESULTS                                                                               |       |      |                   |                             |                       |                  |          |      |               |                                                 |         |           |                      |            |          |                |                 |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|-------------------|-----------------------------|-----------------------|------------------|----------|------|---------------|-------------------------------------------------|---------|-----------|----------------------|------------|----------|----------------|-----------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]   | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation                                      | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                   |                             |                       |                  |          |      |               |                                                 |         |           |                      |            | (W/kg)   |                | (W/kg)          |        |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | -0.21    | 0    | Right         | Cheek                                           | QPSK    | 1         | 25                   | 96361      | 1:1      | 0.202          | 1.127           | 0.228  | A8 |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | -0.03    | 1    | Right         | Cheek                                           | QPSK    | 25        | 0                    | 96361      | 1:1      | 0.147          | 1.138           | 0.167  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | -0.04    | 0    | Right         | Tilt                                            | QPSK    | 1         | 25                   | 96361      | 1:1      | 0.105          | 1.127           | 0.118  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | 0.08     | 1    | Right         | Tilt                                            | QPSK    | 25        | 0                    | 96361      | 1:1      | 0.078          | 1.138           | 0.089  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | -0.04    | 0    | Left          | Cheek                                           | QPSK    | 1         | 25                   | 96361      | 1:1      | 0.158          | 1.127           | 0.178  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | 0.03     | 1    | Left          | Cheek                                           | QPSK    | 25        | 0                    | 96361      | 1:1      | 0.125          | 1.138           | 0.142  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | 0.01     | 0    | Left          | Tilt                                            | QPSK    | 1         | 25                   | 96361      | 1:1      | 0.110          | 1.127           | 0.124  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | 0.00     | 1    | Left          | Tilt                                            | QPSK    | 25        | 0                    | 96361      | 1:1      | 0.084          | 1.138           | 0.096  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                   |                             |                       |                  |          |      |               | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |           |                      |            |          |                |                 |        |    |

**Table 11-9**  
**LTE Band 4 (AWS) Head SAR Data**

| MEASUREMENT RESULTS                                                                               |       |      |                  |                             |                       |                  |          |      |               |                                                 |         |           |                      |            |          |                |                 |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|------|---------------|-------------------------------------------------|---------|-----------|----------------------|------------|----------|----------------|-----------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation                                      | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                  |                             |                       |                  |          |      |               |                                                 |         |           |                      |            | (W/kg)   |                | (W/kg)          |        |    |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | 0.16     | 0    | Right         | Cheek                                           | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.238          | 1.000           | 0.238  | A9 |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | 0.01     | 1    | Right         | Cheek                                           | QPSK    | 50        | 0                    | 96361      | 1:1      | 0.166          | 1.084           | 0.180  |    |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | -0.03    | 0    | Right         | Tilt                                            | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.143          | 1.000           | 0.143  |    |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | -0.12    | 1    | Right         | Tilt                                            | QPSK    | 50        | 0                    | 96361      | 1:1      | 0.108          | 1.084           | 0.117  |    |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | -0.14    | 0    | Left          | Cheek                                           | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.144          | 1.000           | 0.144  |    |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | 0.02     | 1    | Left          | Cheek                                           | QPSK    | 50        | 0                    | 96361      | 1:1      | 0.093          | 1.084           | 0.101  |    |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | 0.10     | 0    | Left          | Tilt                                            | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.178          | 1.000           | 0.178  |    |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | 0.11     | 1    | Left          | Tilt                                            | QPSK    | 50        | 0                    | 96361      | 1:1      | 0.132          | 1.084           | 0.143  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          |      |               | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |           |                      |            |          |                |                 |        |    |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 87 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 11-10**  
**LTE Band 2 (PCS) Head SAR Data**

| MEASUREMENT RESULTS                                                                               |       |      |                  |                             |                       |                  |          |      |               |                                                 |         |           |                      |            |          |                |                 |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|------|---------------|-------------------------------------------------|---------|-----------|----------------------|------------|----------|----------------|-----------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation                                      | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                  |                             |                       |                  |          |      |               |                                                 |         |           |                      |            | [W/kg]   |                | [W/kg]          |        |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | 0.02     | 0    | Right         | Cheek                                           | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.162          | 1.127           | 0.183  | A10 |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | -0.08    | 1    | Right         | Cheek                                           | QPSK    | 50        | 0                    | 96361      | 1:1      | 0.112          | 1.245           | 0.139  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | 0.05     | 0    | Right         | Tilt                                            | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.129          | 1.127           | 0.145  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | 0.02     | 1    | Right         | Tilt                                            | QPSK    | 50        | 0                    | 96361      | 1:1      | 0.090          | 1.245           | 0.112  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | -0.12    | 0    | Left          | Cheek                                           | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.125          | 1.127           | 0.141  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | -0.04    | 1    | Left          | Cheek                                           | QPSK    | 50        | 0                    | 96361      | 1:1      | 0.087          | 1.245           | 0.108  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | 0.00     | 0    | Left          | Tilt                                            | QPSK    | 1         | 0                    | 96361      | 1:1      | 0.115          | 1.127           | 0.130  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | -0.09    | 1    | Left          | Tilt                                            | QPSK    | 50        | 0                    | 96361      | 1:1      | 0.091          | 1.245           | 0.113  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          |      |               | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |           |                      |            |          |                |                 |        |     |

**Table 11-11**  
**DTS Head SAR Data**

| MEASUREMENT RESULTS                                                                               |     |         |         |                 |                             |                       |                  |       |               |                                                 |                      |                  |                |                       |          |                        |                             |                 |        |
|---------------------------------------------------------------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|-------|---------------|-------------------------------------------------|----------------------|------------------|----------------|-----------------------|----------|------------------------|-----------------------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position | Antenna Config.                                 | Device Serial Number | Data Rate (Mbps) | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |         |         |                 |                             |                       |                  |       |               |                                                 |                      |                  |                | W/kg                  | (W/kg)   |                        |                             | (W/kg)          |        |
| 2462                                                                                              | 11  | 802.11b | DSSS    | 22              | 15.5                        | 15.45                 | 0.08             | Right | Cheek         | 1                                               | 9587C                | 1                | 100.0          | 0.599                 | 0.537    | 1.012                  | 1.000                       | 0.543           | A11    |
| 2462                                                                                              | 11  | 802.11b | DSSS    | 22              | 15.5                        | 15.45                 | 0.03             | Right | Tilt          | 1                                               | 9587C                | 1                | 100.0          | 0.481                 | 0.422    | 1.012                  | 1.000                       | 0.427           |        |
| 2462                                                                                              | 11  | 802.11b | DSSS    | 22              | 15.5                        | 15.45                 | -                | Left  | Cheek         | 1                                               | 9587C                | 1                | 100.0          | 0.438                 | -        | 1.012                  | 1.000                       | -               |        |
| 2462                                                                                              | 11  | 802.11b | DSSS    | 22              | 15.5                        | 15.45                 | -                | Left  | Tilt          | 1                                               | 9587C                | 1                | 100.0          | 0.293                 | -        | 1.012                  | 1.000                       | -               |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 15.44                 | 0.02             | Right | Cheek         | 2                                               | 9587C                | 1                | 99.7           | 0.463                 | 0.435    | 1.014                  | 1.004                       | 0.443           |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 15.44                 | 0.03             | Right | Tilt          | 2                                               | 9587C                | 1                | 99.7           | 0.447                 | 0.408    | 1.014                  | 1.004                       | 0.416           |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 15.44                 | -                | Left  | Cheek         | 2                                               | 9587C                | 1                | 99.7           | 0.297                 | -        | 1.014                  | 1.004                       | -               |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 15.44                 | -                | Left  | Tilt          | 2                                               | 9587C                | 1                | 99.7           | 0.304                 | -        | 1.014                  | 1.004                       | -               |        |
| 2412                                                                                              | 1   | 802.11n | OFDM    | 20              | 16.5                        | 16.30                 | -0.06            | Right | Cheek         | MIMO                                            | 9587C                | 13               | 98.4           | 0.640                 | 0.476    | 1.102                  | 1.016                       | 0.533           |        |
| 2412                                                                                              | 1   | 802.11n | OFDM    | 20              | 16.5                        | 16.30                 | -0.06            | Right | Tilt          | MIMO                                            | 9587C                | 13               | 98.4           | 0.537                 | 0.395    | 1.102                  | 1.016                       | 0.442           |        |
| 2412                                                                                              | 1   | 802.11n | OFDM    | 20              | 16.5                        | 16.30                 | -                | Left  | Cheek         | MIMO                                            | 9587C                | 13               | 98.4           | 0.302                 | -        | 1.102                  | 1.016                       | -               |        |
| 2412                                                                                              | 1   | 802.11n | OFDM    | 20              | 16.5                        | 16.30                 | -                | Left  | Tilt          | MIMO                                            | 9587C                | 13               | 98.4           | 0.289                 | -        | 1.102                  | 1.016                       | -               |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  |       |               | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                      |                  |                |                       |          |                        |                             |                 |        |

|                                   |                                                                                                                                                                                                        |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset   |
| Page 88 of 119                    |                                                                                                                                                                                                        |                                 |

**Table 11-12**  
**NII Head SAR Data**

| MEASUREMENT RESULTS                                                                               |     |         |         |                 |                             |                       |                  |       |                                                 |                 |                      |                  |                |                       |          |                        |                             |                        |        |
|---------------------------------------------------------------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|-----------------|----------------------|------------------|----------------|-----------------------|----------|------------------------|-----------------------------|------------------------|--------|
| FREQUENCY                                                                                         |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Scaled SAR (1g) (W/kg) | Plot # |
| MHz                                                                                               | Ch. |         |         |                 |                             |                       |                  |       |                                                 |                 |                      |                  |                | W/kg                  | (W/kg)   |                        |                             |                        |        |
| 5280                                                                                              | 56  | 802.11a | OFDM    | 20              | 10.5                        | 10.13                 | 0.16             | Right | Cheek                                           | 1               | 9587C                | 6                | 99.3           | 0.350                 | 0.243    | 1.089                  | 1.008                       | 0.267                  |        |
| 5280                                                                                              | 56  | 802.11a | OFDM    | 20              | 10.5                        | 10.13                 | -                | Right | Tilt                                            | 1               | 9587C                | 6                | 99.3           | 0.221                 | -        | 1.089                  | 1.008                       | -                      |        |
| 5280                                                                                              | 56  | 802.11a | OFDM    | 20              | 10.5                        | 10.13                 | -                | Left  | Cheek                                           | 1               | 9587C                | 6                | 99.3           | 0.188                 | -        | 1.089                  | 1.008                       | -                      |        |
| 5280                                                                                              | 56  | 802.11a | OFDM    | 20              | 10.5                        | 10.13                 | -                | Left  | Tilt                                            | 1               | 9587C                | 6                | 99.3           | 0.159                 | -        | 1.089                  | 1.008                       | -                      |        |
| 5260                                                                                              | 52  | 802.11a | OFDM    | 20              | 10.5                        | 10.48                 | 0.13             | Right | Cheek                                           | 2               | 9587C                | 6                | 98.6           | 0.551                 | 0.241    | 1.005                  | 1.014                       | 0.245                  |        |
| 5260                                                                                              | 52  | 802.11a | OFDM    | 20              | 10.5                        | 10.48                 | -                | Right | Tilt                                            | 2               | 9587C                | 6                | 98.6           | 0.343                 | -        | 1.005                  | 1.014                       | -                      |        |
| 5260                                                                                              | 52  | 802.11a | OFDM    | 20              | 10.5                        | 10.48                 | -                | Left  | Cheek                                           | 2               | 9587C                | 6                | 98.6           | 0.273                 | -        | 1.005                  | 1.014                       | -                      |        |
| 5260                                                                                              | 52  | 802.11a | OFDM    | 20              | 10.5                        | 10.48                 | -                | Left  | Tilt                                            | 2               | 9587C                | 6                | 98.6           | 0.219                 | -        | 1.005                  | 1.014                       | -                      |        |
| 5500                                                                                              | 100 | 802.11a | OFDM    | 20              | 10.5                        | 10.01                 | 0.17             | Right | Cheek                                           | 1               | 9587C                | 6                | 99.3           | 0.695                 | 0.335    | 1.119                  | 1.008                       | 0.378                  |        |
| 5500                                                                                              | 100 | 802.11a | OFDM    | 20              | 10.5                        | 10.01                 | -                | Right | Tilt                                            | 1               | 9587C                | 6                | 99.3           | 0.392                 | -        | 1.119                  | 1.008                       | -                      |        |
| 5500                                                                                              | 100 | 802.11a | OFDM    | 20              | 10.5                        | 10.01                 | -                | Left  | Cheek                                           | 1               | 9587C                | 6                | 99.3           | 0.506                 | -        | 1.119                  | 1.008                       | -                      |        |
| 5500                                                                                              | 100 | 802.11a | OFDM    | 20              | 10.5                        | 10.01                 | -                | Left  | Tilt                                            | 1               | 9587C                | 6                | 99.3           | 0.394                 | -        | 1.119                  | 1.008                       | -                      |        |
| 5500                                                                                              | 100 | 802.11a | OFDM    | 20              | 10.5                        | 10.36                 | 0.12             | Right | Cheek                                           | 2               | 9587C                | 6                | 98.6           | 0.478                 | 0.206    | 1.033                  | 1.014                       | 0.216                  |        |
| 5500                                                                                              | 100 | 802.11a | OFDM    | 20              | 10.5                        | 10.36                 | -                | Right | Tilt                                            | 2               | 9587C                | 6                | 98.6           | 0.336                 | -        | 1.033                  | 1.014                       | -                      |        |
| 5500                                                                                              | 100 | 802.11a | OFDM    | 20              | 10.5                        | 10.36                 | -                | Left  | Cheek                                           | 2               | 9587C                | 6                | 98.6           | 0.164                 | -        | 1.033                  | 1.014                       | -                      |        |
| 5500                                                                                              | 100 | 802.11a | OFDM    | 20              | 10.5                        | 10.36                 | -                | Left  | Tilt                                            | 2               | 9587C                | 6                | 98.6           | 0.174                 | -        | 1.033                  | 1.014                       | -                      |        |
| 5745                                                                                              | 149 | 802.11a | OFDM    | 20              | 10.5                        | 10.45                 | 0.16             | Right | Cheek                                           | 1               | 9587C                | 6                | 99.3           | 0.645                 | 0.391    | 1.012                  | 1.008                       | 0.399                  | A12    |
| 5745                                                                                              | 149 | 802.11a | OFDM    | 20              | 10.5                        | 10.45                 | -                | Right | Tilt                                            | 1               | 9587C                | 6                | 99.3           | 0.438                 | -        | 1.012                  | 1.008                       | -                      |        |
| 5745                                                                                              | 149 | 802.11a | OFDM    | 20              | 10.5                        | 10.45                 | -                | Left  | Cheek                                           | 1               | 9587C                | 6                | 99.3           | 0.414                 | -        | 1.012                  | 1.008                       | -                      |        |
| 5745                                                                                              | 149 | 802.11a | OFDM    | 20              | 10.5                        | 10.45                 | -                | Left  | Tilt                                            | 1               | 9587C                | 6                | 99.3           | 0.330                 | -        | 1.012                  | 1.008                       | -                      |        |
| 5825                                                                                              | 165 | 802.11a | OFDM    | 20              | 10.5                        | 10.34                 | 0.13             | Right | Cheek                                           | 2               | 9587C                | 6                | 98.6           | 0.559                 | 0.263    | 1.038                  | 1.014                       | 0.277                  |        |
| 5825                                                                                              | 165 | 802.11a | OFDM    | 20              | 10.5                        | 10.34                 | -                | Right | Tilt                                            | 2               | 9587C                | 6                | 98.6           | 0.520                 | -        | 1.038                  | 1.014                       | -                      |        |
| 5825                                                                                              | 165 | 802.11a | OFDM    | 20              | 10.5                        | 10.34                 | -                | Left  | Cheek                                           | 2               | 9587C                | 6                | 98.6           | 0.462                 | -        | 1.038                  | 1.014                       | -                      |        |
| 5825                                                                                              | 165 | 802.11a | OFDM    | 20              | 10.5                        | 10.34                 | -                | Left  | Tilt                                            | 2               | 9587C                | 6                | 98.6           | 0.500                 | -        | 1.038                  | 1.014                       | -                      |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                 |                      |                  |                |                       |          |                        |                             |                        |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 89 of 119                  |

## 11.2 Standalone Body-Worn SAR Data

**Table 11-13**  
**GSM/UMTS/CDMA Body-Worn SAR Data**

| MEASUREMENT RESULTS                                                                               |      |            |             |                             |                       |                  |                                                 |                      |                 |            |      |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|------|------------|-------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|----------------------|-----------------|------------|------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |      | Mode       | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Device Serial Number | # of GPRS Slots | Duty Cycle | Side | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch.  |            |             |                             |                       |                  |                                                 |                      |                 |            |      | (W/kg)   |                | (W/kg)          |        |
| 836.60                                                                                            | 190  | GSM 850    | GSM         | 33.5                        | 33.12                 | -0.02            | 15 mm                                           | 9635F                | 1               | 1:8.3      | back | 0.376    | 1.091          | 0.410           | A13    |
| 836.60                                                                                            | 4183 | UMTS 850   | RMC         | 23.5                        | 23.38                 | -0.01            | 15 mm                                           | 9635F                | N/A             | 1:1        | back | 0.345    | 1.028          | 0.355           | A15    |
| 1880.00                                                                                           | 661  | GSM 1900   | GSM         | 30.5                        | 29.68                 | 0.02             | 15 mm                                           | 9635F                | 1               | 1:8.3      | back | 0.258    | 1.208          | 0.312           | A17    |
| 1880.00                                                                                           | 9400 | UMTS 1900  | RMC         | 23.5                        | 23.22                 | 0.00             | 15 mm                                           | 9635F                | N/A             | 1:1        | back | 0.378    | 1.067          | 0.403           | A19    |
| 836.52                                                                                            | 384  | Cell. CDMA | TDSS / SO32 | 25.0                        | 24.94                 | 0.04             | 15 mm                                           | 9660B                | N/A             | 1:1        | back | 0.159    | 1.014          | 0.161           | A21    |
| 1880.00                                                                                           | 600  | PCS CDMA   | TDSS / SO32 | 25.0                        | 24.24                 | 0.00             | 15 mm                                           | 9660B                | N/A             | 1:1        | back | 0.343    | 1.191          | 0.409           | A23    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |            |             |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                      |                 |            |      |          |                |                 |        |

**Table 11-14**  
**LTE Body-Worn SAR Data**

| MEASUREMENT RESULTS                                   |       |      |                   |                             |                       |                  |          |                      |                                                 |         |           |         |       |            |          |                |                 |        |     |
|-------------------------------------------------------|-------|------|-------------------|-----------------------------|-----------------------|------------------|----------|----------------------|-------------------------------------------------|---------|-----------|---------|-------|------------|----------|----------------|-----------------|--------|-----|
| FREQUENCY                                             |       | Mode | Bandwidth [MHz]   | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number | Modulation                                      | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |     |
| MHz                                                   | Ch.   |      |                   |                             |                       |                  |          |                      |                                                 |         |           |         |       |            | (W/kg)   |                | (W/kg)          |        |     |
| 782.00                                                | 23230 | Mid  | LTE Band 13       | 10                          | 25.0                  | 24.34            | -0.05    | 0                    | 96361                                           | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.373          | 1.164           | 0.434  | A25 |
| 782.00                                                | 23230 | Mid  | LTE Band 13       | 10                          | 24.0                  | 23.31            | -0.01    | 1                    | 96361                                           | QPSK    | 25        | 0       | 15 mm | back       | 1:1      | 0.299          | 1.172           | 0.350  |     |
| 836.50                                                | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | -0.18    | 0                    | 96361                                           | QPSK    | 1         | 25      | 15 mm | back       | 1:1      | 0.262          | 1.127           | 0.295  | A27 |
| 836.50                                                | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | -0.07    | 1                    | 96361                                           | QPSK    | 25        | 0       | 15 mm | back       | 1:1      | 0.198          | 1.138           | 0.225  |     |
| 1732.50                                               | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 24.5                  | 24.50            | -0.03    | 0                    | 96361                                           | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.751          | 1.000           | 0.751  | A29 |
| 1732.50                                               | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 23.5                  | 23.15            | -0.01    | 1                    | 96361                                           | QPSK    | 50        | 0       | 15 mm | back       | 1:1      | 0.546          | 1.084           | 0.592  |     |
| 1860.00                                               | 18700 | Low  | LTE Band 2 (PCS)  | 20                          | 24.5                  | 23.98            | 0.02     | 0                    | 96361                                           | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.540          | 1.127           | 0.609  | A31 |
| 1860.00                                               | 18700 | Low  | LTE Band 2 (PCS)  | 20                          | 23.5                  | 22.55            | -0.02    | 1                    | 96361                                           | QPSK    | 50        | 0       | 15 mm | back       | 1:1      | 0.361          | 1.245           | 0.449  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak |       |      |                   |                             |                       |                  |          |                      | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |         |           |         |       |            |          |                |                 |        |     |
| Uncontrolled Exposure/General Population              |       |      |                   |                             |                       |                  |          |                      |                                                 |         |           |         |       |            |          |                |                 |        |     |

**Table 11-15**  
**DTS Body-Worn SAR Data**

| MEASUREMENT RESULTS                                                                               |     |         |         |                 |                             |                       |                  |                                                 |                 |                      |                  |      |                |                       |          |                        |                             |                 |        |
|---------------------------------------------------------------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|-----------------|----------------------|------------------|------|----------------|-----------------------|----------|------------------------|-----------------------------|-----------------|--------|
| FREQUENCY                                                                                         |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Side | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |         |         |                 |                             |                       |                  |                                                 |                 |                      |                  |      |                | W/kg                  | W/kg     |                        |                             | W/kg            |        |
| 2437                                                                                              | 6   | 802.11b | DSSS    | 22              | 17.5                        | 17.42                 | 0.05             | 10 mm                                           | 1               | 9587C                | 1                | back | 100.0          | 0.185                 | 0.162    | 1.019                  | 1.000                       | 0.165           |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 17.5                        | 16.85                 | -0.13            | 10 mm                                           | 2               | 9587C                | 1                | back | 99.7           | 0.191                 | 0.164    | 1.161                  | 1.004                       | 0.191           | A33    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                 |                      |                  |      |                |                       |          |                        |                             |                 |        |

**Table 11-16**  
**NII Body-Worn SAR Data**

| MEASUREMENT RESULTS                      |     |         |         |                 |                             |                       |                  |                      |                 |                      |                  |      |                |                       |          |                        |                             |                 |        |
|------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|----------------------|-----------------|----------------------|------------------|------|----------------|-----------------------|----------|------------------------|-----------------------------|-----------------|--------|
| FREQUENCY                                |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing              | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Side | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Scaled SAR (1g) | Plot # |
| MHz                                      | Ch. |         |         |                 |                             |                       |                  |                      |                 |                      |                  |      |                | W/kg                  | W/kg     |                        |                             | W/kg            |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 13.5                        | 13.35                 | 0.10             | 10 mm                | 1               | 9587C                | 6                | back | 99.3           | 0.042                 | 0.024    | 1.035                  | 1.008                       | 0.025           |        |
| 5320                                     | 64  | 802.11a | OFDM    | 20              | 13.5                        | 13.05                 | 0.03             | 10 mm                | 2               | 9587C                | 6                | back | 98.6           | 0.048                 | 0.021    | 1.109                  | 1.014                       | 0.023           |        |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 13.5                        | 13.29                 | 0.06             | 10 mm                | 1               | 9587C                | 6                | back | 99.3           | 0.084                 | 0.029    | 1.050                  | 1.008                       | 0.030           |        |
| 5900                                     | 100 | 802.11a | OFDM    | 20              | 13.5                        | 13.19                 | 0.12             | 10 mm                | 2               | 9587C                | 6                | back | 98.6           | 0.052                 | 0.022    | 1.074                  | 1.014                       | 0.024           |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 13.5                        | 13.12                 | 0.05             | 10 mm                | 1               | 9587C                | 6                | back | 99.3           | 0.028                 | 0.004    | 1.091                  | 1.008                       | 0.004           |        |
| 5745                                     | 149 | 802.11a | OFDM    | 20              | 13.5                        | 12.84                 | 0.07             | 10 mm                | 2               | 9587C                | 6                | back | 98.6           | 0.096                 | 0.035    | 1.164                  | 1.014                       | 0.042           | A34    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |     |         |         |                 |                             |                       |                  | Body                 |                 |                      |                  |      |                |                       |          |                        |                             |                 |        |
| Spatial Peak                             |     |         |         |                 |                             |                       |                  | 1.6 W/kg (mW/g)      |                 |                      |                  |      |                |                       |          |                        |                             |                 |        |
| Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  | averaged over 1 gram |                 |                      |                  |      |                |                       |          |                        |                             |                 |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>OY1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 90 of 119                  |

## 11.3 Standalone Wireless Router SAR Data

Table 11-17  
GPRS/UMTS Hotspot SAR Data

| MEASUREMENT RESULTS                                                                               |      |           |         |                             |                       |                  |                                                 |                      |                 |            |        |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|-------------------------------------------------|----------------------|-----------------|------------|--------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |      | Mode      | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Device Serial Number | # of GPRS Slots | Duty Cycle | Side   | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch.  |           |         |                             |                       |                  |                                                 |                      |                 |            |        | (W/kg)   |                | (W/kg)          |        |
| 824.20                                                                                            | 128  | GSM 850   | GPRS    | 30.0                        | 29.74                 | 0.06             | 10 mm                                           | 9635F                | 3               | 1:2.76     | back   | 0.881    | 1.062          | 0.936           |        |
| 836.60                                                                                            | 190  | GSM 850   | GPRS    | 30.0                        | 29.97                 | -0.05            | 10 mm                                           | 9635F                | 3               | 1:2.76     | back   | 0.970    | 1.007          | 0.977           |        |
| 848.80                                                                                            | 251  | GSM 850   | GPRS    | 30.0                        | 29.80                 | -0.12            | 10 mm                                           | 9635F                | 3               | 1:2.76     | back   | 0.926    | 1.047          | 0.970           |        |
| 824.20                                                                                            | 128  | GSM 850   | GPRS    | 30.0                        | 29.74                 | -0.10            | 10 mm                                           | 9635F                | 3               | 1:2.76     | front  | 0.883    | 1.062          | 0.938           |        |
| 836.60                                                                                            | 190  | GSM 850   | GPRS    | 30.0                        | 29.97                 | -0.11            | 10 mm                                           | 9635F                | 3               | 1:2.76     | front  | 0.974    | 1.007          | 0.981           | A14    |
| 848.80                                                                                            | 251  | GSM 850   | GPRS    | 30.0                        | 29.80                 | -0.02            | 10 mm                                           | 9635F                | 3               | 1:2.76     | front  | 0.903    | 1.047          | 0.945           |        |
| 836.60                                                                                            | 190  | GSM 850   | GPRS    | 30.0                        | 29.97                 | -0.08            | 10 mm                                           | 9635F                | 3               | 1:2.76     | bottom | 0.485    | 1.007          | 0.488           |        |
| 836.60                                                                                            | 190  | GSM 850   | GPRS    | 30.0                        | 29.97                 | 0.08             | 10 mm                                           | 9635F                | 3               | 1:2.76     | right  | 0.471    | 1.007          | 0.474           |        |
| 836.60                                                                                            | 190  | GSM 850   | GPRS    | 30.0                        | 29.97                 | 0.03             | 10 mm                                           | 9635F                | 3               | 1:2.76     | left   | 0.168    | 1.007          | 0.169           |        |
| 836.60                                                                                            | 190  | GSM 850   | GPRS    | 30.0                        | 29.97                 | -0.10            | 10 mm                                           | 9635F                | 3               | 1:2.76     | front  | 0.935    | 1.007          | 0.942           |        |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | -0.06            | 10 mm                                           | 9635F                | N/A             | 1:1        | back   | 0.604    | 1.028          | 0.621           | A16    |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | 0.00             | 10 mm                                           | 9635F                | N/A             | 1:1        | front  | 0.548    | 1.028          | 0.563           |        |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | 0.02             | 10 mm                                           | 9635F                | N/A             | 1:1        | bottom | 0.328    | 1.028          | 0.337           |        |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | 0.04             | 10 mm                                           | 9635F                | N/A             | 1:1        | right  | 0.336    | 1.028          | 0.345           |        |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 23.5                        | 23.38                 | -0.02            | 10 mm                                           | 9635F                | N/A             | 1:1        | left   | 0.118    | 1.028          | 0.121           |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS    | 23.5                        | 23.13                 | -0.01            | 10 mm                                           | 930ED                | 3               | 1:2.76     | back   | 0.382    | 1.089          | 0.416           |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS    | 23.5                        | 23.13                 | -0.02            | 10 mm                                           | 930ED                | 3               | 1:2.76     | front  | 0.309    | 1.089          | 0.337           |        |
| 1850.20                                                                                           | 512  | GSM 1900  | GPRS    | 23.5                        | 22.99                 | -0.05            | 10 mm                                           | 930ED                | 3               | 1:2.76     | bottom | 0.904    | 1.125          | 1.017           |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS    | 23.5                        | 23.13                 | -0.04            | 10 mm                                           | 930ED                | 3               | 1:2.76     | bottom | 0.918    | 1.089          | 1.000           | A18    |
| 1909.80                                                                                           | 810  | GSM 1900  | GPRS    | 23.5                        | 22.70                 | 0.05             | 10 mm                                           | 930ED                | 3               | 1:2.76     | bottom | 0.753    | 1.202          | 0.905           |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS    | 23.5                        | 23.13                 | 0.04             | 10 mm                                           | 930ED                | 3               | 1:2.76     | right  | 0.064    | 1.089          | 0.070           |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS    | 23.5                        | 23.13                 | -0.01            | 10 mm                                           | 930ED                | 3               | 1:2.76     | left   | 0.221    | 1.089          | 0.241           |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 20.5                        | 19.77                 | -0.01            | 10 mm                                           | 930ED                | N/A             | 1:1        | back   | 0.360    | 1.183          | 0.426           |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 20.5                        | 19.77                 | -0.01            | 10 mm                                           | 930ED                | N/A             | 1:1        | front  | 0.311    | 1.183          | 0.368           |        |
| 1852.40                                                                                           | 9262 | UMTS 1900 | RMC     | 20.5                        | 19.82                 | 0.02             | 10 mm                                           | 930ED                | N/A             | 1:1        | bottom | 0.891    | 1.169          | 1.042           | A20    |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 20.5                        | 19.77                 | -0.01            | 10 mm                                           | 930ED                | N/A             | 1:1        | bottom | 0.861    | 1.183          | 1.019           |        |
| 1907.60                                                                                           | 9538 | UMTS 1900 | RMC     | 20.5                        | 19.74                 | 0.00             | 10 mm                                           | 930ED                | N/A             | 1:1        | bottom | 0.819    | 1.191          | 0.975           |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 20.5                        | 19.77                 | -0.01            | 10 mm                                           | 930ED                | N/A             | 1:1        | right  | 0.048    | 1.183          | 0.057           |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC     | 20.5                        | 19.77                 | 0.01             | 10 mm                                           | 930ED                | N/A             | 1:1        | left   | 0.177    | 1.183          | 0.209           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                      |                 |            |        |          |                |                 |        |

Note: Blue entries represent variability measurements.

|                                   |                                                                                                                                                                                                        |                               |  |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>SAR EVALUATION REPORT</b>  |                               |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                                                                                     | DUT Type:<br>Portable Handset |  | Page 91 of 119                  |

**Table 11-18**  
**EVDO Hotspot SAR Data**

| MEASUREMENT RESULTS                                                                               |      |            |             |                             |                       |                  |                                                 |                      |            |        |          |                |                 |        |
|---------------------------------------------------------------------------------------------------|------|------------|-------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|----------------------|------------|--------|----------|----------------|-----------------|--------|
| FREQUENCY                                                                                         |      | Mode       | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Device Serial Number | Duty Cycle | Side   | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                                                                               | Ch.  |            |             |                             |                       |                  |                                                 |                      |            |        | (W/kg)   |                | (W/kg)          |        |
| 824.70                                                                                            | 1013 | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.85                 | -0.04            | 10 mm                                           | 9660B                | 1:1        | back   | 0.587    | 1.035          | 0.608           |        |
| 836.52                                                                                            | 384  | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.99                 | -0.05            | 10 mm                                           | 9660B                | 1:1        | back   | 0.814    | 1.002          | 0.816           |        |
| 848.31                                                                                            | 777  | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.95                 | -0.04            | 10 mm                                           | 9660B                | 1:1        | back   | 0.842    | 1.012          | 0.852           |        |
| 824.70                                                                                            | 1013 | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.85                 | -0.06            | 10 mm                                           | 9660B                | 1:1        | front  | 0.736    | 1.035          | 0.762           |        |
| 836.52                                                                                            | 384  | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.99                 | -0.03            | 10 mm                                           | 9660B                | 1:1        | front  | 0.962    | 1.002          | 0.964           | A22    |
| 848.31                                                                                            | 777  | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.95                 | -0.04            | 10 mm                                           | 9660B                | 1:1        | front  | 0.955    | 1.012          | 0.966           |        |
| 836.52                                                                                            | 384  | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.99                 | 0.02             | 10 mm                                           | 9660B                | 1:1        | bottom | 0.619    | 1.002          | 0.620           |        |
| 836.52                                                                                            | 384  | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.99                 | 0.01             | 10 mm                                           | 9660B                | 1:1        | right  | 0.547    | 1.002          | 0.548           |        |
| 836.52                                                                                            | 384  | Cell. CDMA | EVDO Rev. 0 | 25.0                        | 24.99                 | -0.11            | 10 mm                                           | 9660B                | 1:1        | left   | 0.158    | 1.002          | 0.158           |        |
| 1880.00                                                                                           | 600  | PCS CDMA   | EVDO Rev. 0 | 20.5                        | 20.06                 | -0.02            | 10 mm                                           | 930ED                | 1:1        | back   | 0.315    | 1.107          | 0.349           |        |
| 1880.00                                                                                           | 600  | PCS CDMA   | EVDO Rev. 0 | 20.5                        | 20.06                 | -0.04            | 10 mm                                           | 930ED                | 1:1        | front  | 0.328    | 1.107          | 0.363           |        |
| 1851.25                                                                                           | 25   | PCS CDMA   | EVDO Rev. 0 | 20.5                        | 20.15                 | -0.02            | 10 mm                                           | 930ED                | 1:1        | bottom | 0.945    | 1.084          | 1.024           | A24    |
| 1880.00                                                                                           | 600  | PCS CDMA   | EVDO Rev. 0 | 20.5                        | 20.06                 | -0.01            | 10 mm                                           | 930ED                | 1:1        | bottom | 0.931    | 1.107          | 1.031           |        |
| 1908.75                                                                                           | 1175 | PCS CDMA   | EVDO Rev. 0 | 20.5                        | 19.99                 | -0.03            | 10 mm                                           | 930ED                | 1:1        | bottom | 0.837    | 1.125          | 0.942           |        |
| 1880.00                                                                                           | 600  | PCS CDMA   | EVDO Rev. 0 | 20.5                        | 20.06                 | 0.02             | 10 mm                                           | 930ED                | 1:1        | right  | 0.047    | 1.107          | 0.052           |        |
| 1880.00                                                                                           | 600  | PCS CDMA   | EVDO Rev. 0 | 20.5                        | 20.06                 | 0.03             | 10 mm                                           | 930ED                | 1:1        | left   | 0.173    | 1.107          | 0.192           |        |
| 1851.25                                                                                           | 25   | PCS CDMA   | EVDO Rev. 0 | 20.5                        | 20.15                 | 0.00             | 10 mm                                           | 930ED                | 1:1        | bottom | 0.944    | 1.084          | 1.023           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |            |             |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                      |            |        |          |                |                 |        |

Note: Blue entry represents variability measurement.

**Table 11-19**  
**LTE Band 13 Hotspot SAR Data**

| MEASUREMENT RESULTS                      |       |        |             |                 |                             |                       |                  |                      |                      |            |         |           |         |        |            |          |                |                 |        |
|------------------------------------------|-------|--------|-------------|-----------------|-----------------------------|-----------------------|------------------|----------------------|----------------------|------------|---------|-----------|---------|--------|------------|----------|----------------|-----------------|--------|
| FREQUENCY                                |       |        | Mode        | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB]             | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side   | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz                                      | Ch.   | (W/kg) |             |                 |                             |                       |                  |                      |                      |            |         |           |         |        |            | (W/kg)   |                |                 |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 25.0                        | 24.34                 | -0.13            | 0                    | 96361                | QPSK       | 1       | 0         | 10 mm   | back   | 1:1        | 0.598    | 1.164          | 0.696           | A26    |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 24.0                        | 23.31                 | -0.01            | 1                    | 96361                | QPSK       | 25      | 0         | 10 mm   | back   | 1:1        | 0.474    | 1.172          | 0.556           |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 25.0                        | 24.34                 | -0.12            | 0                    | 96361                | QPSK       | 1       | 0         | 10 mm   | front  | 1:1        | 0.533    | 1.164          | 0.620           |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 24.0                        | 23.31                 | -0.01            | 1                    | 96361                | QPSK       | 25      | 0         | 10 mm   | front  | 1:1        | 0.427    | 1.172          | 0.500           |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 25.0                        | 24.34                 | -0.16            | 0                    | 96361                | QPSK       | 1       | 0         | 10 mm   | bottom | 1:1        | 0.158    | 1.164          | 0.184           |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 24.0                        | 23.31                 | 0.12             | 1                    | 96361                | QPSK       | 25      | 0         | 10 mm   | bottom | 1:1        | 0.138    | 1.172          | 0.162           |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 25.0                        | 24.34                 | 0.07             | 0                    | 96361                | QPSK       | 1       | 0         | 10 mm   | right  | 1:1        | 0.292    | 1.164          | 0.340           |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 24.0                        | 23.31                 | 0.08             | 1                    | 96361                | QPSK       | 25      | 0         | 10 mm   | right  | 1:1        | 0.226    | 1.172          | 0.265           |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 25.0                        | 24.34                 | -0.02            | 0                    | 96361                | QPSK       | 1       | 0         | 10 mm   | left   | 1:1        | 0.188    | 1.164          | 0.219           |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 24.0                        | 23.31                 | 0.06             | 1                    | 96361                | QPSK       | 25      | 0         | 10 mm   | left   | 1:1        | 0.146    | 1.172          | 0.171           |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |       |        |             |                 |                             |                       |                  | Body                 |                      |            |         |           |         |        |            |          |                |                 |        |
| Spatial Peak                             |       |        |             |                 |                             |                       |                  | 1.6 W/kg (mW/g)      |                      |            |         |           |         |        |            |          |                |                 |        |
| Uncontrolled Exposure/General Population |       |        |             |                 |                             |                       |                  | averaged over 1 gram |                      |            |         |           |         |        |            |          |                |                 |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 92 of 119                  |

**Table 11-20**  
**LTE Band 5 (Cell) Hotspot SAR Data**

| MEASUREMENT RESULTS                                                                               |       |      |                   |                             |                       |                  |          |                                                 |            |         |           |         |       |            |          |                |                 |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|-------------------|-----------------------------|-----------------------|------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|-----------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]   | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                            | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                   |                             |                       |                  |          |                                                 |            |         |           |         |       |            | (W/kg)   |                | (W/kg)          |        |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | -0.08    | 0                                               | 96361      | QPSK    | 1         | 25      | 10 mm | back       | 1:1      | 0.628          | 1.127           | 0.708  | A28 |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | -0.11    | 1                                               | 96361      | QPSK    | 25        | 0       | 10 mm | back       | 1:1      | 0.450          | 1.138           | 0.512  |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | 0.00     | 0                                               | 96361      | QPSK    | 1         | 25      | 10 mm | front      | 1:1      | 0.659          | 1.127           | 0.743  |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | -0.04    | 1                                               | 96361      | QPSK    | 25        | 0       | 10 mm | front      | 1:1      | 0.486          | 1.138           | 0.553  |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | -0.17    | 0                                               | 96361      | QPSK    | 1         | 25      | 10 mm | bottom     | 1:1      | 0.446          | 1.127           | 0.503  |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | -0.17    | 1                                               | 96361      | QPSK    | 25        | 0       | 10 mm | bottom     | 1:1      | 0.310          | 1.138           | 0.353  |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | -0.02    | 0                                               | 96361      | QPSK    | 1         | 25      | 10 mm | right      | 1:1      | 0.299          | 1.127           | 0.337  |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | 0.03     | 1                                               | 96361      | QPSK    | 25        | 0       | 10 mm | right      | 1:1      | 0.236          | 1.138           | 0.269  |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.48            | 0.08     | 0                                               | 96361      | QPSK    | 1         | 25      | 10 mm | left       | 1:1      | 0.137          | 1.127           | 0.154  |     |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 23.44            | 0.13     | 1                                               | 96361      | QPSK    | 25        | 0       | 10 mm | left       | 1:1      | 0.117          | 1.138           | 0.133  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                   |                             |                       |                  |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |          |                |                 |        |     |

**Table 11-21**  
**LTE Band 4 (AWS) Hotspot SAR Data**

| MEASUREMENT RESULTS                                                                               |       |      |                  |                             |                       |                  |          |                                                 |            |         |           |         |       |            |          |                |                 |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|-----------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                            | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                  |                             |                       |                  |          |                                                 |            |         |           |         |       |            | (W/kg)   |                | (W/kg)          |        |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 20.23            | -0.05    | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.566          | 1.064           | 0.602  | A30 |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 19.88            | -0.05    | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | back       | 1:1      | 0.520          | 1.153           | 0.600  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 20.23            | 0.06     | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | front      | 1:1      | 0.517          | 1.064           | 0.550  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 19.88            | 0.01     | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | front      | 1:1      | 0.481          | 1.153           | 0.555  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 20.23            | -0.02    | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.800          | 1.064           | 0.851  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 19.88            | -0.06    | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | bottom     | 1:1      | 0.747          | 1.153           | 0.861  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 19.71            | -0.04    | 0                                               | 930ED      | QPSK    | 100       | 0       | 10 mm | bottom     | 1:1      | 0.751          | 1.199           | 0.900  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 20.23            | -0.06    | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | right      | 1:1      | 0.059          | 1.064           | 0.063  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 19.88            | 0.09     | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | right      | 1:1      | 0.052          | 1.153           | 0.060  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 20.23            | 0.00     | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | left       | 1:1      | 0.195          | 1.064           | 0.207  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 19.88            | -0.02    | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | left       | 1:1      | 0.188          | 1.153           | 0.217  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 20.5                  | 20.23            | -0.05    | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.800          | 1.064           | 0.851  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |          |                |                 |        |     |

Note: Blue entry represents variability measurement.

**Table 11-22**  
**LTE Band 2 (PCS) Hotspot SAR Data**

| MEASUREMENT RESULTS                                                                               |       |      |                  |                             |                       |                  |          |                                                 |            |         |           |         |       |            |          |                |                 |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|-----------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                            | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                  |                             |                       |                  |          |                                                 |            |         |           |         |       |            | (W/kg)   |                | (W/kg)          |        |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.96            | -0.05    | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.321          | 1.009           | 0.324  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.28            | -0.03    | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | back       | 1:1      | 0.330          | 1.180           | 0.389  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.96            | 0.02     | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | front      | 1:1      | 0.338          | 1.009           | 0.341  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.28            | 0.02     | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | front      | 1:1      | 0.285          | 1.180           | 0.336  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.96            | -0.01    | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.831          | 1.009           | 0.838  | A32 |
| 1880.00                                                                                           | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.61            | 0.01     | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.804          | 1.094           | 0.880  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.78            | 0.01     | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.785          | 1.052           | 0.826  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.28            | -0.01    | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | bottom     | 1:1      | 0.801          | 1.180           | 0.945  |     |
| 1880.00                                                                                           | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.24            | -0.02    | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | bottom     | 1:1      | 0.790          | 1.191           | 0.941  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.26            | -0.05    | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | bottom     | 1:1      | 0.745          | 1.186           | 0.884  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.19            | -0.02    | 0                                               | 930ED      | QPSK    | 100       | 0       | 10 mm | bottom     | 1:1      | 0.792          | 1.205           | 0.954  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.96            | -0.03    | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | right      | 1:1      | 0.044          | 1.009           | 0.044  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.28            | 0.01     | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | right      | 1:1      | 0.039          | 1.180           | 0.046  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.96            | -0.03    | 0                                               | 930ED      | QPSK    | 1         | 0       | 10 mm | left       | 1:1      | 0.221          | 1.009           | 0.223  |     |
| 1860.00                                                                                           | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 20.0                  | 19.28            | 0.00     | 0                                               | 930ED      | QPSK    | 50        | 0       | 10 mm | left       | 1:1      | 0.188          | 1.180           | 0.222  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |          |                |                 |        |     |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 93 of 119                  |

**Table 11-23**  
**WLAN Hotspot SAR Data**

| MEASUREMENT RESULTS                      |     |         |         |                 |                             |                       |                  |                      |                 |                      |                  |       |                |                       |          |                        |                             |                 |        |
|------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|----------------------|-----------------|----------------------|------------------|-------|----------------|-----------------------|----------|------------------------|-----------------------------|-----------------|--------|
| FREQUENCY                                |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing              | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Side  | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Scaled SAR (1g) | Plot # |
| MHz                                      | Ch. |         |         |                 |                             |                       |                  |                      |                 |                      |                  |       |                | W/kg                  | (W/kg)   |                        |                             | (W/kg)          |        |
| 2437                                     | 6   | 802.11b | DSSS    | 22              | 17.5                        | 17.42                 | 0.05             | 10 mm                | 1               | 9587C                | 1                | back  | 100.0          | 0.185                 | 0.162    | 1.019                  | 1.000                       | 0.165           |        |
| 2437                                     | 6   | 802.11b | DSSS    | 22              | 17.5                        | 17.42                 | -                | 10 mm                | 1               | 9587C                | 1                | front | 100.0          | 0.129                 | -        | 1.019                  | 1.000                       | -               |        |
| 2437                                     | 6   | 802.11b | DSSS    | 22              | 17.5                        | 17.42                 | -                | 10 mm                | 1               | 9587C                | 1                | top   | 100.0          | 0.145                 | -        | 1.019                  | 1.000                       | -               |        |
| 2437                                     | 6   | 802.11b | DSSS    | 22              | 17.5                        | 17.42                 | -                | 10 mm                | 1               | 9587C                | 1                | left  | 100.0          | 0.091                 | -        | 1.019                  | 1.000                       | -               |        |
| 2412                                     | 1   | 802.11b | DSSS    | 22              | 17.5                        | 16.85                 | -0.13            | 10 mm                | 2               | 9587C                | 1                | back  | 99.7           | 0.191                 | 0.164    | 1.161                  | 1.004                       | 0.191           | A33    |
| 2412                                     | 1   | 802.11b | DSSS    | 22              | 17.5                        | 16.85                 | -                | 10 mm                | 2               | 9587C                | 1                | front | 99.7           | 0.102                 | -        | 1.161                  | 1.004                       | -               |        |
| 2412                                     | 1   | 802.11b | DSSS    | 22              | 17.5                        | 16.85                 | -                | 10 mm                | 2               | 9587C                | 1                | top   | 99.7           | 0.163                 | -        | 1.161                  | 1.004                       | -               |        |
| 2412                                     | 1   | 802.11b | DSSS    | 22              | 17.5                        | 16.85                 | -                | 10 mm                | 2               | 9587C                | 1                | left  | 99.7           | 0.080                 | -        | 1.161                  | 1.004                       | -               |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 13.5                        | 13.12                 | -                | 10 mm                | 1               | 9587C                | 6                | back  | 99.3           | 0.028                 | -        | 1.091                  | 1.008                       | -               |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 13.5                        | 13.12                 | 0.04             | 10 mm                | 1               | 9587C                | 6                | front | 99.3           | 0.126                 | 0.061    | 1.091                  | 1.008                       | 0.068           |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 13.5                        | 13.12                 | -                | 10 mm                | 1               | 9587C                | 6                | top   | 99.3           | 0.029                 | -        | 1.091                  | 1.008                       | -               |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 13.5                        | 13.12                 | -                | 10 mm                | 1               | 9587C                | 6                | left  | 99.3           | 0.052                 | -        | 1.091                  | 1.008                       | -               |        |
| 5745                                     | 149 | 802.11a | OFDM    | 20              | 13.5                        | 12.84                 | -                | 10 mm                | 2               | 9587C                | 6                | back  | 98.6           | 0.096                 | -        | 1.164                  | 1.014                       | -               |        |
| 5745                                     | 149 | 802.11a | OFDM    | 20              | 13.5                        | 12.84                 | -0.04            | 10 mm                | 2               | 9587C                | 6                | front | 98.6           | 0.399                 | 0.181    | 1.164                  | 1.014                       | 0.214           | A35    |
| 5745                                     | 149 | 802.11a | OFDM    | 20              | 13.5                        | 12.84                 | -                | 10 mm                | 2               | 9587C                | 6                | top   | 98.6           | 0.268                 | -        | 1.164                  | 1.014                       | -               |        |
| 5745                                     | 149 | 802.11a | OFDM    | 20              | 13.5                        | 12.84                 | -                | 10 mm                | 2               | 9587C                | 6                | left  | 98.6           | 0.035                 | -        | 1.164                  | 1.014                       | -               |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |     |         |         |                 |                             |                       |                  | Body                 |                 |                      |                  |       |                |                       |          |                        |                             |                 |        |
| Spatial Peak                             |     |         |         |                 |                             |                       |                  | 1.6 W/kg (mW/g)      |                 |                      |                  |       |                |                       |          |                        |                             |                 |        |
| Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  | averaged over 1 gram |                 |                      |                  |       |                |                       |          |                        |                             |                 |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 94 of 119                  |

# 11.4 Standalone Extremity SAR Data

## Table 11-24 GPRS/UMTS/CDMA Extremity SAR

| MEASUREMENT RESULTS                                                                               |      |           |             |                             |                       |                  |                                                        |                      |                 |            |        |           |                |                  |        |
|---------------------------------------------------------------------------------------------------|------|-----------|-------------|-----------------------------|-----------------------|------------------|--------------------------------------------------------|----------------------|-----------------|------------|--------|-----------|----------------|------------------|--------|
| FREQUENCY                                                                                         |      | Mode      | Service     | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                                | Device Serial Number | # of GPRS Slots | Duty Cycle | Side   | SAR (10g) | Scaling Factor | Scaled SAR (10g) | Plot # |
| MHz                                                                                               | Ch.  |           |             |                             |                       |                  |                                                        |                      |                 |            |        | (W/kg)    |                | (W/kg)           |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS        | 26.5                        | 25.64                 | -0.03            | 3 mm                                                   | 9635F                | 4               | 1:2.076    | back   | 1.120     | 1.219          | 1.365            |        |
| 1850.20                                                                                           | 512  | GSM 1900  | GPRS        | 26.5                        | 25.67                 | 0.08             | 1 mm                                                   | 9635F                | 4               | 1:2.076    | front  | 2.460     | 1.211          | 2.979            | A36    |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS        | 26.5                        | 25.64                 | 0.06             | 1 mm                                                   | 9635F                | 4               | 1:2.076    | front  | 2.310     | 1.219          | 2.816            |        |
| 1909.80                                                                                           | 810  | GSM 1900  | GPRS        | 26.5                        | 25.63                 | 0.07             | 1 mm                                                   | 9635F                | 4               | 1:2.076    | front  | 2.050     | 1.222          | 2.505            |        |
| 1850.20                                                                                           | 512  | GSM 1900  | GPRS        | 26.5                        | 25.67                 | -0.01            | 4 mm                                                   | 9635F                | 4               | 1:2.076    | bottom | 2.290     | 1.211          | 2.773            |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS        | 26.5                        | 25.64                 | -0.02            | 4 mm                                                   | 9635F                | 4               | 1:2.076    | bottom | 2.330     | 1.219          | 2.840            |        |
| 1909.80                                                                                           | 810  | GSM 1900  | GPRS        | 26.5                        | 25.63                 | -0.01            | 4 mm                                                   | 9635F                | 4               | 1:2.076    | bottom | 1.940     | 1.222          | 2.371            |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS        | 26.5                        | 25.64                 | -0.21            | 0 mm                                                   | 9635F                | 4               | 1:2.076    | right  | 0.218     | 1.219          | 0.266            |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS        | 26.5                        | 25.64                 | -0.12            | 0 mm                                                   | 9635F                | 4               | 1:2.076    | left   | 0.924     | 1.219          | 1.126            |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS        | 23.5                        | 23.13                 | -0.01            | 0 mm                                                   | 930ED                | 3               | 1:2.76     | back   | 1.100     | 1.089          | 1.198            |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS        | 23.5                        | 23.13                 | -0.07            | 0 mm                                                   | 930ED                | 3               | 1:2.76     | front  | 1.070     | 1.089          | 1.165            |        |
| 1880.00                                                                                           | 661  | GSM 1900  | GPRS        | 23.5                        | 23.13                 | 0.02             | 0 mm                                                   | 930ED                | 3               | 1:2.76     | bottom | 1.310     | 1.089          | 1.427            |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC         | 23.5                        | 23.22                 | -0.03            | 3 mm                                                   | 9635F                | N/A             | 1:1        | back   | 0.990     | 1.067          | 1.056            |        |
| 1852.40                                                                                           | 9262 | UMTS 1900 | RMC         | 23.5                        | 23.34                 | 0.00             | 1 mm                                                   | 9635F                | N/A             | 1:1        | front  | 2.530     | 1.038          | 2.626            |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC         | 23.5                        | 23.22                 | -0.03            | 1 mm                                                   | 9635F                | N/A             | 1:1        | front  | 2.510     | 1.067          | 2.678            |        |
| 1907.60                                                                                           | 9538 | UMTS 1900 | RMC         | 23.5                        | 23.12                 | -0.03            | 1 mm                                                   | 9635F                | N/A             | 1:1        | front  | 2.490     | 1.091          | 2.717            |        |
| 1852.40                                                                                           | 9262 | UMTS 1900 | RMC         | 23.5                        | 23.34                 | -0.02            | 4 mm                                                   | 9635F                | N/A             | 1:1        | bottom | 2.700     | 1.038          | 2.803            | A37    |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC         | 23.5                        | 23.22                 | -0.03            | 4 mm                                                   | 9635F                | N/A             | 1:1        | bottom | 2.470     | 1.067          | 2.635            |        |
| 1907.60                                                                                           | 9538 | UMTS 1900 | RMC         | 23.5                        | 23.12                 | -0.04            | 4 mm                                                   | 9635F                | N/A             | 1:1        | bottom | 2.210     | 1.091          | 2.411            |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC         | 23.5                        | 23.22                 | -0.04            | 0 mm                                                   | 9635F                | N/A             | 1:1        | right  | 0.174     | 1.067          | 0.186            |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC         | 23.5                        | 23.22                 | 0.08             | 0 mm                                                   | 9635F                | N/A             | 1:1        | left   | 1.040     | 1.067          | 1.110            |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC         | 20.5                        | 19.77                 | -0.04            | 0 mm                                                   | 930ED                | N/A             | 1:1        | back   | 1.040     | 1.183          | 1.230            |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC         | 20.5                        | 19.77                 | 0.00             | 0 mm                                                   | 930ED                | N/A             | 1:1        | front  | 1.300     | 1.183          | 1.538            |        |
| 1880.00                                                                                           | 9400 | UMTS 1900 | RMC         | 20.5                        | 19.77                 | 0.02             | 0 mm                                                   | 930ED                | N/A             | 1:1        | bottom | 1.450     | 1.183          | 1.715            |        |
| 1880.00                                                                                           | 600  | PCS CDMA  | EVDO Rev. 0 | 25.0                        | 24.26                 | -0.04            | 3 mm                                                   | 9660B                | N/A             | 1:1        | back   | 1.250     | 1.186          | 1.483            |        |
| 1880.00                                                                                           | 600  | PCS CDMA  | EVDO Rev. 0 | 25.0                        | 24.26                 | -0.01            | 1 mm                                                   | 9660B                | N/A             | 1:1        | front  | 1.530     | 1.186          | 1.815            |        |
| 1851.25                                                                                           | 25   | PCS CDMA  | EVDO Rev. 0 | 25.0                        | 24.50                 | -0.01            | 4 mm                                                   | 9660B                | N/A             | 1:1        | bottom | 2.350     | 1.122          | 2.637            | A38    |
| 1880.00                                                                                           | 600  | PCS CDMA  | EVDO Rev. 0 | 25.0                        | 24.26                 | 0.02             | 4 mm                                                   | 9660B                | N/A             | 1:1        | bottom | 2.150     | 1.186          | 2.550            |        |
| 1908.75                                                                                           | 1175 | PCS CDMA  | EVDO Rev. 0 | 25.0                        | 24.45                 | 0.03             | 4 mm                                                   | 9660B                | N/A             | 1:1        | bottom | 2.180     | 1.135          | 2.474            |        |
| 1880.00                                                                                           | 600  | PCS CDMA  | EVDO Rev. 0 | 25.0                        | 24.26                 | 0.03             | 0 mm                                                   | 9660B                | N/A             | 1:1        | right  | 0.182     | 1.186          | 0.216            |        |
| 1880.00                                                                                           | 600  | PCS CDMA  | EVDO Rev. 0 | 25.0                        | 24.26                 | 0.09             | 0 mm                                                   | 9660B                | N/A             | 1:1        | left   | 1.000     | 1.186          | 1.186            |        |
| 1880.00                                                                                           | 600  | PCS CDMA  | EVDO Rev. 0 | 20.5                        | 20.06                 | -0.01            | 0 mm                                                   | 930ED                | N/A             | 1:1        | back   | 1.320     | 1.107          | 1.461            |        |
| 1880.00                                                                                           | 600  | PCS CDMA  | EVDO Rev. 0 | 20.5                        | 20.06                 | 0.05             | 0 mm                                                   | 930ED                | N/A             | 1:1        | front  | 1.270     | 1.107          | 1.406            |        |
| 1851.25                                                                                           | 25   | PCS CDMA  | EVDO Rev. 0 | 20.5                        | 20.15                 | 0.04             | 0 mm                                                   | 930ED                | N/A             | 1:1        | bottom | 1.930     | 1.084          | 2.092            |        |
| 1880.00                                                                                           | 600  | PCS CDMA  | EVDO Rev. 0 | 20.5                        | 20.06                 | 0.06             | 0 mm                                                   | 930ED                | N/A             | 1:1        | bottom | 1.860     | 1.107          | 2.059            |        |
| 1908.75                                                                                           | 1175 | PCS CDMA  | EVDO Rev. 0 | 20.5                        | 19.99                 | 0.08             | 0 mm                                                   | 930ED                | N/A             | 1:1        | bottom | 1.770     | 1.125          | 1.991            |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |           |             |                             |                       |                  | Extremity<br>4.0 W/kg (mW/g)<br>averaged over 10 grams |                      |                 |            |        |           |                |                  |        |

|                                   |                                                                                     |                               |                       |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|-----------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  |                               | SAR EVALUATION REPORT |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                       |                                                                                       | Page 95 of 119                  |

**Table 11-25**  
**LTE Extremity SAR**

| MEASUREMENT RESULTS                      |       |      |                  |                             |                       |                  |          |                        |            |         |           |         |      |            |           |                |                  |        |     |
|------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|------------------------|------------|---------|-----------|---------|------|------------|-----------|----------------|------------------|--------|-----|
| FREQUENCY                                |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number   | Modulation | RB Size | RB Offset | Spacing | Side | Duty Cycle | SAR (10g) | Scaling Factor | Scaled SAR (10g) | Plot # |     |
| MHz                                      | Ch.   |      |                  |                             |                       |                  |          |                        |            |         |           |         |      |            | (W/kg)    |                | (W/kg)           |        |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | -0.04    | 0                      | 96361      | QPSK    | 1         | 0       | 3 mm | back       | 1:1       | 2.580          | 1.000            | 2.580  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | -0.02    | 1                      | 96361      | QPSK    | 50        | 0       | 3 mm | back       | 1:1       | 1.900          | 1.084            | 2.060  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.01            | -0.02    | 1                      | 96361      | QPSK    | 100       | 0       | 3 mm | back       | 1:1       | 1.820          | 1.119            | 2.037  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | 0.11     | 0                      | 96361      | QPSK    | 1         | 0       | 1 mm | front      | 1:1       | 2.960          | 1.000            | 2.960  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | 0.00     | 1                      | 96361      | QPSK    | 50        | 0       | 1 mm | front      | 1:1       | 2.480          | 1.084            | 2.688  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.01            | -0.11    | 1                      | 96361      | QPSK    | 100       | 0       | 1 mm | front      | 1:1       | 2.360          | 1.119            | 2.641  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | -0.05    | 0                      | 96361      | QPSK    | 1         | 0       | 4 mm | bottom     | 1:1       | 2.510          | 1.000            | 2.510  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | -0.07    | 1                      | 96361      | QPSK    | 50        | 0       | 4 mm | bottom     | 1:1       | 1.870          | 1.084            | 2.027  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.01            | -0.06    | 1                      | 96361      | QPSK    | 100       | 0       | 4 mm | bottom     | 1:1       | 1.870          | 1.119            | 2.093  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | -0.06    | 0                      | 96361      | QPSK    | 1         | 0       | 0 mm | right      | 1:1       | 0.177          | 1.000            | 0.177  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | -0.02    | 1                      | 96361      | QPSK    | 50        | 0       | 0 mm | right      | 1:1       | 0.126          | 1.084            | 0.137  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 24.50            | -0.14    | 0                      | 96361      | QPSK    | 1         | 0       | 0 mm | left       | 1:1       | 1.230          | 1.000            | 1.230  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 23.15            | -0.17    | 1                      | 96361      | QPSK    | 50        | 0       | 0 mm | left       | 1:1       | 0.905          | 1.084            | 0.981  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.50            | 0.04     | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | back       | 1:1       | 2.150          | 1.000            | 2.150  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.39            | 0.02     | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | back       | 1:1       | 1.980          | 1.026            | 2.031  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.29            | 0.04     | 0                      | 930ED      | QPSK    | 100       | 0       | 0 mm | back       | 1:1       | 1.930          | 1.050            | 2.027  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.50            | -0.07    | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | front      | 1:1       | 1.740          | 1.000            | 1.740  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.39            | -0.02    | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | front      | 1:1       | 1.590          | 1.026            | 1.631  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.50            | -0.19    | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | bottom     | 1:1       | 3.040          | 1.000            | 3.040  | A39 |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.39            | -0.11    | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | bottom     | 1:1       | 3.030          | 1.026            | 3.109  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.29            | -0.08    | 0                      | 930ED      | QPSK    | 100       | 0       | 0 mm | bottom     | 1:1       | 2.680          | 1.050            | 2.814  |     |
| 1732.50                                  | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 21.50            | 0.02     | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | bottom     | 1:1       | 2.740          | 1.000            | 2.740  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | 0.02     | 0                      | 96361      | QPSK    | 1         | 0       | 3 mm | back       | 1:1       | 1.520          | 1.127            | 1.713  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | -0.05    | 1                      | 96361      | QPSK    | 50        | 0       | 3 mm | back       | 1:1       | 1.050          | 1.245            | 1.307  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | 0.11     | 0                      | 96361      | QPSK    | 1         | 0       | 1 mm | front      | 1:1       | 1.770          | 1.127            | 1.995  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | 0.10     | 1                      | 96361      | QPSK    | 50        | 0       | 1 mm | front      | 1:1       | 1.250          | 1.245            | 1.556  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | 0.12     | 0                      | 96361      | QPSK    | 1         | 0       | 4 mm | bottom     | 1:1       | 2.830          | 1.127            | 3.189  | A40 |
| 1880.00                                  | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.88            | 0.01     | 0                      | 96361      | QPSK    | 1         | 0       | 4 mm | bottom     | 1:1       | 2.800          | 1.153            | 3.228  |     |
| 1900.00                                  | 19100 | High | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.69            | -0.02    | 0                      | 96361      | QPSK    | 1         | 0       | 4 mm | bottom     | 1:1       | 2.650          | 1.205            | 3.193  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | 0.00     | 1                      | 96361      | QPSK    | 50        | 0       | 4 mm | bottom     | 1:1       | 2.010          | 1.245            | 2.502  |     |
| 1880.00                                  | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.38            | 0.00     | 1                      | 96361      | QPSK    | 50        | 0       | 4 mm | bottom     | 1:1       | 1.930          | 1.294            | 2.497  |     |
| 1900.00                                  | 19100 | High | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.25            | -0.01    | 1                      | 96361      | QPSK    | 50        | 0       | 4 mm | bottom     | 1:1       | 1.770          | 1.334            | 2.361  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.36            | -0.01    | 1                      | 96361      | QPSK    | 100       | 0       | 4 mm | bottom     | 1:1       | 1.980          | 1.300            | 2.574  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | 0.02     | 0                      | 96361      | QPSK    | 1         | 0       | 0 mm | right      | 1:1       | 0.194          | 1.127            | 0.219  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | 0.04     | 1                      | 96361      | QPSK    | 50        | 0       | 0 mm | right      | 1:1       | 0.140          | 1.245            | 0.174  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | -0.01    | 0                      | 96361      | QPSK    | 1         | 0       | 0 mm | left       | 1:1       | 1.190          | 1.127            | 1.341  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.55            | -0.07    | 1                      | 96361      | QPSK    | 50        | 0       | 0 mm | left       | 1:1       | 0.844          | 1.245            | 1.051  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.95            | -0.10    | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | back       | 1:1       | 2.500          | 1.012            | 2.530  |     |
| 1880.00                                  | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.88            | -0.03    | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | back       | 1:1       | 2.520          | 1.028            | 2.591  |     |
| 1900.00                                  | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.86            | -0.09    | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | back       | 1:1       | 2.620          | 1.033            | 2.706  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.36            | -0.01    | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | back       | 1:1       | 1.760          | 1.159            | 2.040  |     |
| 1880.00                                  | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.38            | 0.00     | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | back       | 1:1       | 1.830          | 1.153            | 2.110  |     |
| 1900.00                                  | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.26            | 0.01     | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | back       | 1:1       | 1.850          | 1.186            | 2.194  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.25            | 0.05     | 0                      | 930ED      | QPSK    | 100       | 0       | 0 mm | back       | 1:1       | 1.740          | 1.189            | 2.069  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.95            | -0.09    | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | front      | 1:1       | 1.520          | 1.012            | 1.538  |     |
| 1880.00                                  | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.38            | -0.04    | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | front      | 1:1       | 1.390          | 1.153            | 1.603  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.95            | -0.01    | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | bottom     | 1:1       | 2.580          | 1.012            | 2.611  |     |
| 1880.00                                  | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.88            | -0.03    | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | bottom     | 1:1       | 2.490          | 1.028            | 2.560  |     |
| 1900.00                                  | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.86            | 0.01     | 0                      | 930ED      | QPSK    | 1         | 0       | 0 mm | bottom     | 1:1       | 2.480          | 1.033            | 2.562  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.36            | 0.01     | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | bottom     | 1:1       | 1.830          | 1.159            | 2.121  |     |
| 1880.00                                  | 18900 | Mid  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.38            | 0.00     | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | bottom     | 1:1       | 1.800          | 1.153            | 2.075  |     |
| 1900.00                                  | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.26            | -0.01    | 0                      | 930ED      | QPSK    | 50        | 0       | 0 mm | bottom     | 1:1       | 1.730          | 1.186            | 2.052  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 21.0                  | 20.25            | -0.02    | 0                      | 930ED      | QPSK    | 100       | 0       | 0 mm | bottom     | 1:1       | 1.780          | 1.189            | 2.116  |     |
| 1860.00                                  | 18700 | Low  | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.98            | 0.19     | 0                      | 96361      | QPSK    | 1         | 0       | 4 mm | bottom     | 1:1       | 2.730          | 1.127            | 3.077  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |       |      |                  |                             |                       |                  |          | Extremity              |            |         |           |         |      |            |           |                |                  |        |     |
| Spatial Peak                             |       |      |                  |                             |                       |                  |          | 4.0 W/kg (mW/g)        |            |         |           |         |      |            |           |                |                  |        |     |
| Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          | averaged over 10 grams |            |         |           |         |      |            |           |                |                  |        |     |

Note: Blue entry represents variability measurement.

|                                   |                                                                                                                                                  |                               |                                                                                       |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br><small>ENGINEERING LABORATORY, INC.</small> | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                               | DUT Type:<br>Portable Handset |                                                                                       | Page 96 of 119                  |

**Table 11-26**  
**WLAN Extremity SAR**

| MEASUREMENT RESULTS                      |     |         |         |                 |                             |                       |                  |                        |                 |                      |                  |       |                |                       |           |                        |                             |                  |        |
|------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|------------------------|-----------------|----------------------|------------------|-------|----------------|-----------------------|-----------|------------------------|-----------------------------|------------------|--------|
| FREQUENCY                                |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Side  | Duty Cycle (%) | Peak SAR of Area Scan | SAR (10g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Scaled SAR (10g) | Plot # |
| MHz                                      | Ch. |         |         |                 |                             |                       |                  |                        |                 |                      |                  |       |                | W/kg                  | (W/kg)    |                        |                             | (W/kg)           |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 13.5                        | 13.35                 | -                | 0 mm                   | 1               | 9587C                | 6                | back  | 99.3           | 0.988                 | -         | 1.035                  | 1.008                       | -                |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 13.5                        | 13.35                 | -0.06            | 0 mm                   | 1               | 9587C                | 6                | front | 99.3           | 1.898                 | 0.400     | 1.035                  | 1.008                       | 0.417            |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 13.5                        | 13.35                 | -                | 0 mm                   | 1               | 9587C                | 6                | top   | 99.3           | 0.760                 | -         | 1.035                  | 1.008                       | -                |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 13.5                        | 13.35                 | -                | 0 mm                   | 1               | 9587C                | 6                | left  | 99.3           | 0.257                 | -         | 1.035                  | 1.008                       | -                |        |
| 5320                                     | 64  | 802.11a | OFDM    | 20              | 13.5                        | 13.05                 | -                | 0 mm                   | 2               | 9587C                | 6                | back  | 98.6           | 1.140                 | -         | 1.109                  | 1.014                       | -                |        |
| 5320                                     | 64  | 802.11a | OFDM    | 20              | 13.5                        | 13.05                 | 0.09             | 0 mm                   | 2               | 9587C                | 6                | front | 98.6           | 2.348                 | 0.410     | 1.109                  | 1.014                       | 0.461            |        |
| 5320                                     | 64  | 802.11a | OFDM    | 20              | 13.5                        | 13.05                 | -                | 0 mm                   | 2               | 9587C                | 6                | top   | 98.6           | 0.612                 | -         | 1.109                  | 1.014                       | -                |        |
| 5320                                     | 64  | 802.11a | OFDM    | 20              | 13.5                        | 13.05                 | -                | 0 mm                   | 2               | 9587C                | 6                | left  | 98.6           | 0.046                 | -         | 1.109                  | 1.014                       | -                |        |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 13.5                        | 13.29                 | -                | 0 mm                   | 1               | 9587C                | 6                | back  | 99.3           | 2.533                 | -         | 1.050                  | 1.008                       | -                |        |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 13.5                        | 13.29                 | 0.08             | 0 mm                   | 1               | 9587C                | 6                | front | 99.3           | 4.853                 | 0.499     | 1.050                  | 1.008                       | 0.528            | A41    |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 13.5                        | 13.29                 | -                | 0 mm                   | 1               | 9587C                | 6                | top   | 99.3           | 0.728                 | -         | 1.050                  | 1.008                       | -                |        |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 13.5                        | 13.29                 | -                | 0 mm                   | 1               | 9587C                | 6                | left  | 99.3           | 1.390                 | -         | 1.050                  | 1.008                       | -                |        |
| 5500                                     | 100 | 802.11a | OFDM    | 20              | 13.5                        | 13.19                 | 0.05             | 0 mm                   | 2               | 9587C                | 6                | back  | 98.6           | 1.649                 | 0.149     | 1.074                  | 1.014                       | 0.162            |        |
| 5500                                     | 100 | 802.11a | OFDM    | 20              | 13.5                        | 13.19                 | -                | 0 mm                   | 2               | 9587C                | 6                | front | 98.6           | 1.614                 | -         | 1.074                  | 1.014                       | -                |        |
| 5500                                     | 100 | 802.11a | OFDM    | 20              | 13.5                        | 13.19                 | -                | 0 mm                   | 2               | 9587C                | 6                | top   | 98.6           | 1.421                 | -         | 1.074                  | 1.014                       | -                |        |
| 5500                                     | 100 | 802.11a | OFDM    | 20.00           | 13.5                        | 13.19                 | -                | 0 mm                   | 2               | 9587C                | 6                | left  | 98.6           | 0.144                 | -         | 1.074                  | 1.014                       | -                |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |     |         |         |                 |                             |                       |                  | Extremity              |                 |                      |                  |       |                |                       |           |                        |                             |                  |        |
| Spatial Peak                             |     |         |         |                 |                             |                       |                  | 4.0 W/kg (mW/g)        |                 |                      |                  |       |                |                       |           |                        |                             |                  |        |
| Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  | averaged over 10 grams |                 |                      |                  |       |                |                       |           |                        |                             |                  |        |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 97 of 119                  |

## 11.5 SAR Test Notes

### General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was  $\leq 1.2$  W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg for 1g SAR and 2.0 W/kg for 10g SAR. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.6 for more details).
10. Per FCC KDB Publication 648474 D04v01r01, this device is considered a "phablet" since the diagonal dimension is  $> 160$  mm and  $< 200$  mm. Therefore, hand SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR (scaled to the maximum output power, including tolerance)  $> 1.2$  W/kg.
11. This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.
12. Additional SAR tests for extremity SAR were evaluated per KDB 616217 Section 6 (See Section 6.7 for more information).

### GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). 10g Extremity SAR measurements apply a factor of 2.5 to the procedures outlined above. When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 98 of 119                         |

#### CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO and TDSO / SO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO / SO32 FCH only powers, per FCC KDB Publication 941225 D01v03.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03 procedures for data devices. Since the average output power of Subtype 2 for Rev. A is less than the Rev. 0 power levels, EVDO Rev. A SAR is not required. SAR is not required for 1x RTT for Ev-Do hotspot devices when the maximum average output of each channel is less than 1/4 dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). 10g Extremity SAR measurements apply a factor of 2.5 to the procedures outlined above. When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

#### UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03. AMR and HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and 1g SAR was less than 1.2 W/kg or 10g SAR was less than 3.0 W/kg.
2. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). 10g Extremity SAR measurements apply a factor of 2.5 to the procedures outlined above. When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

#### LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r03. The general test procedures used for testing can be found in Section 8.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per KDB Publication 941225 D05Av01r01, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not  $>0.25$  dB higher than the maximum output power when downlink carrier aggregation was inactive.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 99 of 119                                                                        |                                 |

**WLAN Notes:**

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg for 1g SAR or  $\leq 1.0$  W/kg for 10g SAR, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01r02v01 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.4 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01r02v01 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.7.5 for more information. 10g Extremity SAR measurements apply a factor of 2.5 to the procedures outlined above.
4. Per KDB Publication 248227 D01r02v01, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 or by measuring MIMO SAR with both antennas transmitting simultaneously at the specified maximum output power in MIMO mode. Please see section 12 for complete analysis.
5. When the maximum reported averaged SAR is  $\leq 0.8$  W/kg for 1g SAR and  $\leq 2.0$  W/kg for 10g SAR, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was  $\leq 1.20$  W/kg for 1g SAR and  $\leq 3.0$  W/kg for 10g SAR or all test channels were measured.
6. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
7. For SAR compliance, this device always uses power reduction when the device is in a held-to-ear RF exposure condition with WIFI operations. Per FCC Guidance, WIFI Head SAR was evaluated at reduced power levels.

|                                   |                                                                                     |                               |                                                                                                                    |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  |                               | <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                                                    | Page 100 of 119                 |

## 12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

### 12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

### 12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is  $\leq 1.6$  W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equations must be used to estimate the standalone 1g SAR and 10g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated 1g SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

$$\text{Estimated 10g SAR} = \frac{\sqrt{f(\text{GHz})}}{18.75} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1**  
**Estimated SAR**

| Mode            | Frequency | Maximum Allowed Power | Separation Distance | Estimated SAR |
|-----------------|-----------|-----------------------|---------------------|---------------|
|                 | [MHz]     | [dBm]                 | [mm]                | [W/kg]        |
| Bluetooth (1g)  | 2480      | 10.50                 | 15                  | 0.154         |
| Bluetooth (10g) | 2480      | 10.50                 | 5                   | 0.185*        |

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

(\*) – Per FCC KDB Publication 447498, when the test separation distance is < 5 mm, a distance of 5 mm is applied to determine estimated SAR.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 101 of 119                        |

## 12.3 Head SAR Simultaneous Transmission Analysis

**Table 12-2**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 (Held to Ear)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|-------------------------------|--------------|
|                    |                   | 1                   | 2                             | 1+2          |
| Head SAR           | GSM 850           | 0.255               | 0.543                         | 0.798        |
|                    | UMTS 850          | 0.187               | 0.543                         | 0.730        |
|                    | GSM 1900          | 0.103               | 0.543                         | 0.646        |
|                    | UMTS 1900         | 0.146               | 0.543                         | 0.689        |
|                    | Cell. CDMA/EVDO   | 0.407               | 0.543                         | 0.950        |
|                    | PCS CDMA/EVDO     | 0.196               | 0.543                         | 0.739        |
|                    | LTE Band 13       | 0.260               | 0.543                         | 0.803        |
|                    | LTE Band 5 (Cell) | 0.228               | 0.543                         | 0.771        |
|                    | LTE Band 4 (AWS)  | 0.238               | 0.543                         | 0.781        |
|                    | LTE Band 2 (PCS)  | 0.183               | 0.543                         | 0.726        |

**Table 12-3**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 2 (Held to Ear)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|-------------------------------|--------------|
|                    |                   | 1                   | 2                             | 1+2          |
| Head SAR           | GSM 850           | 0.255               | 0.443                         | 0.698        |
|                    | UMTS 850          | 0.187               | 0.443                         | 0.630        |
|                    | GSM 1900          | 0.103               | 0.443                         | 0.546        |
|                    | UMTS 1900         | 0.146               | 0.443                         | 0.589        |
|                    | Cell. CDMA/EVDO   | 0.407               | 0.443                         | 0.850        |
|                    | PCS CDMA/EVDO     | 0.196               | 0.443                         | 0.639        |
|                    | LTE Band 13       | 0.260               | 0.443                         | 0.703        |
|                    | LTE Band 5 (Cell) | 0.228               | 0.443                         | 0.671        |
|                    | LTE Band 4 (AWS)  | 0.238               | 0.443                         | 0.681        |
|                    | LTE Band 2 (PCS)  | 0.183               | 0.443                         | 0.626        |

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 102 of 119                        |

**Table 12-4**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Held to Ear)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|------------------------------|--------------|
|                    |                   | 1                   | 2                            | 1+2          |
| Head SAR           | GSM 850           | 0.255               | 0.533                        | 0.788        |
|                    | UMTS 850          | 0.187               | 0.533                        | 0.720        |
|                    | GSM 1900          | 0.103               | 0.533                        | 0.636        |
|                    | UMTS 1900         | 0.146               | 0.533                        | 0.679        |
|                    | Cell. CDMA/EVDO   | 0.407               | 0.533                        | 0.940        |
|                    | PCS CDMA/EVDO     | 0.196               | 0.533                        | 0.729        |
|                    | LTE Band 13       | 0.260               | 0.533                        | 0.793        |
|                    | LTE Band 5 (Cell) | 0.228               | 0.533                        | 0.761        |
|                    | LTE Band 4 (AWS)  | 0.238               | 0.533                        | 0.771        |
|                    | LTE Band 2 (PCS)  | 0.183               | 0.533                        | 0.716        |

**Table 12-5**  
**Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |       |       |
|--------------------|-------------------|---------------------|-----------------------------|-----------------------------|--------------|-------|-------|
|                    |                   | 1                   | 2                           | 3                           | 1+2          | 1+3   | 1+2+3 |
| Head SAR           | GSM 850           | 0.255               | 0.399                       | 0.277                       | 0.654        | 0.532 | 0.931 |
|                    | UMTS 850          | 0.187               | 0.399                       | 0.277                       | 0.586        | 0.464 | 0.863 |
|                    | GSM 1900          | 0.103               | 0.399                       | 0.277                       | 0.502        | 0.380 | 0.779 |
|                    | UMTS 1900         | 0.146               | 0.399                       | 0.277                       | 0.545        | 0.423 | 0.822 |
|                    | Cell. CDMA/EVDO   | 0.407               | 0.399                       | 0.277                       | 0.806        | 0.684 | 1.083 |
|                    | PCS CDMA/EVDO     | 0.196               | 0.399                       | 0.277                       | 0.595        | 0.473 | 0.872 |
|                    | LTE Band 13       | 0.260               | 0.399                       | 0.277                       | 0.659        | 0.537 | 0.936 |
|                    | LTE Band 5 (Cell) | 0.228               | 0.399                       | 0.277                       | 0.627        | 0.505 | 0.904 |
|                    | LTE Band 4 (AWS)  | 0.238               | 0.399                       | 0.277                       | 0.637        | 0.515 | 0.914 |
|                    | LTE Band 2 (PCS)  | 0.183               | 0.399                       | 0.277                       | 0.582        | 0.460 | 0.859 |

Note: 1+2+3 denotes MIMO SAR Summations.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 103 of 119                                                                       |                                 |

**Table 12-6**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 and 5 GHz WLAN Ant 2**  
**(Held to Ear)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                   | 1                   | 2                             | 3                           | 1+2+3        |
| Head SAR           | GSM 850           | 0.255               | 0.543                         | 0.277                       | 1.075        |
|                    | UMTS 850          | 0.187               | 0.543                         | 0.277                       | 1.007        |
|                    | GSM 1900          | 0.103               | 0.543                         | 0.277                       | 0.923        |
|                    | UMTS 1900         | 0.146               | 0.543                         | 0.277                       | 0.966        |
|                    | Cell. CDMA/EVDO   | 0.407               | 0.543                         | 0.277                       | 1.227        |
|                    | PCS CDMA/EVDO     | 0.196               | 0.543                         | 0.277                       | 1.016        |
|                    | LTE Band 13       | 0.260               | 0.543                         | 0.277                       | 1.080        |
|                    | LTE Band 5 (Cell) | 0.228               | 0.543                         | 0.277                       | 1.048        |
|                    | LTE Band 4 (AWS)  | 0.238               | 0.543                         | 0.277                       | 1.058        |
|                    | LTE Band 2 (PCS)  | 0.183               | 0.543                         | 0.277                       | 1.003        |

**Table 12-7**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 2 and 5 GHz WLAN Ant 1**  
**(Held to Ear)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                   | 1                   | 2                             | 3                           | 1+2+3        |
| Head SAR           | GSM 850           | 0.255               | 0.443                         | 0.399                       | 1.097        |
|                    | UMTS 850          | 0.187               | 0.443                         | 0.399                       | 1.029        |
|                    | GSM 1900          | 0.103               | 0.443                         | 0.399                       | 0.945        |
|                    | UMTS 1900         | 0.146               | 0.443                         | 0.399                       | 0.988        |
|                    | Cell. CDMA/EVDO   | 0.407               | 0.443                         | 0.399                       | 1.249        |
|                    | PCS CDMA/EVDO     | 0.196               | 0.443                         | 0.399                       | 1.038        |
|                    | LTE Band 13       | 0.260               | 0.443                         | 0.399                       | 1.102        |
|                    | LTE Band 5 (Cell) | 0.228               | 0.443                         | 0.399                       | 1.070        |
|                    | LTE Band 4 (AWS)  | 0.238               | 0.443                         | 0.399                       | 1.080        |
|                    | LTE Band 2 (PCS)  | 0.183               | 0.443                         | 0.399                       | 1.025        |

|                                          |                                                                                                                                                  |                                      |                                                                                       |                                        |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br><small>ENGINEERING LABORATORY, INC.</small> | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                                        | <b>DUT Type:</b><br>Portable Handset | Page 104 of 119                                                                       |                                        |

## 12.4 Body-Worn Simultaneous Transmission Analysis

For SAR summations for body-worn back side at 15 mm, WLAN SAR values for 1.0 cm were used since the 1.0 cm test distance for WLAN was more conservative. “<” denotes that the 1.0 cm WLAN SAR values were used for summation purposes.

**Table 12-8**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |        |
|--------------------|-------------------|---------------------|-------------------------------|-------------------------------|---------------------|--------|--------|
|                    |                   | 1                   | 2                             | 3                             | 1+2                 | 1+3    | 1+2+3  |
| Body-Worn          | GSM 850           | 0.410               | <0.165                        | <0.191                        | <0.575              | <0.601 | <0.766 |
|                    | UMTS 850          | 0.355               | <0.165                        | <0.191                        | <0.520              | <0.546 | <0.711 |
|                    | GSM 1900          | 0.312               | <0.165                        | <0.191                        | <0.477              | <0.503 | <0.668 |
|                    | UMTS 1900         | 0.403               | <0.165                        | <0.191                        | <0.568              | <0.594 | <0.759 |
|                    | Cell. CDMA        | 0.161               | <0.165                        | <0.191                        | <0.326              | <0.352 | <0.517 |
|                    | PCS CDMA          | 0.409               | <0.165                        | <0.191                        | <0.574              | <0.600 | <0.765 |
|                    | LTE Band 13       | 0.434               | <0.165                        | <0.191                        | <0.599              | <0.625 | <0.790 |
|                    | LTE Band 5 (Cell) | 0.295               | <0.165                        | <0.191                        | <0.460              | <0.486 | <0.651 |
|                    | LTE Band 4 (AWS)  | 0.751               | <0.165                        | <0.191                        | <0.916              | <0.942 | <1.107 |
|                    | LTE Band 2 (PCS)  | 0.609               | <0.165                        | <0.191                        | <0.774              | <0.800 | <0.965 |

Note: 1+2+3 denotes MIMO SAR Summations.

**Table 12-9**  
**Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.5 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |        |
|--------------------|-------------------|---------------------|-----------------------------|-----------------------------|---------------------|--------|--------|
|                    |                   | 1                   | 2                           | 3                           | 1+2                 | 1+3    | 1+2+3  |
| Body-Worn          | GSM 850           | 0.410               | <0.030                      | <0.042                      | <0.440              | <0.452 | <0.482 |
|                    | UMTS 850          | 0.355               | <0.030                      | <0.042                      | <0.385              | <0.397 | <0.427 |
|                    | GSM 1900          | 0.312               | <0.030                      | <0.042                      | <0.342              | <0.354 | <0.384 |
|                    | UMTS 1900         | 0.403               | <0.030                      | <0.042                      | <0.433              | <0.445 | <0.475 |
|                    | Cell. CDMA        | 0.161               | <0.030                      | <0.042                      | <0.191              | <0.203 | <0.233 |
|                    | PCS CDMA          | 0.409               | <0.030                      | <0.042                      | <0.439              | <0.451 | <0.481 |
|                    | LTE Band 13       | 0.434               | <0.030                      | <0.042                      | <0.464              | <0.476 | <0.506 |
|                    | LTE Band 5 (Cell) | 0.295               | <0.030                      | <0.042                      | <0.325              | <0.337 | <0.367 |
|                    | LTE Band 4 (AWS)  | 0.751               | <0.030                      | <0.042                      | <0.781              | <0.793 | <0.823 |
|                    | LTE Band 2 (PCS)  | 0.609               | <0.030                      | <0.042                      | <0.639              | <0.651 | <0.681 |

Note: 1+2+3 denotes MIMO SAR Summations.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 105 of 119                 |

**Table 12-10**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 and 5 GHz WLAN Ant 2**  
**(Body-Worn at 1.5 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                   | 1                   | 2                             | 3                           | 1+2+3        |
| Body-Worn          | GSM 850           | 0.410               | <0.165                        | <0.042                      | <0.617       |
|                    | UMTS 850          | 0.355               | <0.165                        | <0.042                      | <0.562       |
|                    | GSM 1900          | 0.312               | <0.165                        | <0.042                      | <0.519       |
|                    | UMTS 1900         | 0.403               | <0.165                        | <0.042                      | <0.610       |
|                    | Cell. CDMA        | 0.161               | <0.165                        | <0.042                      | <0.368       |
|                    | PCS CDMA          | 0.409               | <0.165                        | <0.042                      | <0.616       |
|                    | LTE Band 13       | 0.434               | <0.165                        | <0.042                      | <0.641       |
|                    | LTE Band 5 (Cell) | 0.295               | <0.165                        | <0.042                      | <0.502       |
|                    | LTE Band 4 (AWS)  | 0.751               | <0.165                        | <0.042                      | <0.958       |
|                    | LTE Band 2 (PCS)  | 0.609               | <0.165                        | <0.042                      | <0.816       |

**Table 12-11**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 2 and 5 GHz WLAN Ant 1**  
**(Body-Worn at 1.5 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                   | 1                   | 2                             | 3                           | 1+2+3        |
| Body-Worn          | GSM 850           | 0.410               | <0.191                        | <0.030                      | <0.631       |
|                    | UMTS 850          | 0.355               | <0.191                        | <0.030                      | <0.576       |
|                    | GSM 1900          | 0.312               | <0.191                        | <0.030                      | <0.533       |
|                    | UMTS 1900         | 0.403               | <0.191                        | <0.030                      | <0.624       |
|                    | Cell. CDMA        | 0.161               | <0.191                        | <0.030                      | <0.382       |
|                    | PCS CDMA          | 0.409               | <0.191                        | <0.030                      | <0.630       |
|                    | LTE Band 13       | 0.434               | <0.191                        | <0.030                      | <0.655       |
|                    | LTE Band 5 (Cell) | 0.295               | <0.191                        | <0.030                      | <0.516       |
|                    | LTE Band 4 (AWS)  | 0.751               | <0.191                        | <0.030                      | <0.972       |
|                    | LTE Band 2 (PCS)  | 0.609               | <0.191                        | <0.030                      | <0.830       |

**Table 12-12**  
**Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|----------------------|--------------|
|                    |                   | 1                   | 2                    | 1+2          |
| Body-Worn          | GSM 850           | 0.410               | 0.154                | 0.564        |
|                    | UMTS 850          | 0.355               | 0.154                | 0.509        |
|                    | GSM 1900          | 0.312               | 0.154                | 0.466        |
|                    | UMTS 1900         | 0.403               | 0.154                | 0.557        |
|                    | Cell. CDMA        | 0.161               | 0.154                | 0.315        |
|                    | PCS CDMA          | 0.409               | 0.154                | 0.563        |
|                    | LTE Band 13       | 0.434               | 0.154                | 0.588        |
|                    | LTE Band 5 (Cell) | 0.295               | 0.154                | 0.449        |
|                    | LTE Band 4 (AWS)  | 0.751               | 0.154                | 0.905        |
|                    | LTE Band 2 (PCS)  | 0.609               | 0.154                | 0.763        |

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 106 of 119                                                                       |                                 |

## 12.5 Hotspot SAR Simultaneous Transmission Analysis

**Table 12-13**  
**Simultaneous Transmission Scenario (2.4 GHz WLAN at 1.0 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |       |       |
|--------------------|-------------------|---------------------|-------------------------------|-------------------------------|---------------------|-------|-------|
|                    |                   | 1                   | 2                             | 3                             | 1+2                 | 1+3   | 1+2+3 |
| Hotspot SAR        | GPRS 850          | 0.981               | 0.165                         | 0.191                         | 1.146               | 1.172 | 1.337 |
|                    | UMTS 850          | 0.621               | 0.165                         | 0.191                         | 0.786               | 0.812 | 0.977 |
|                    | GPRS 1900         | 1.017               | 0.165                         | 0.191                         | 1.182               | 1.208 | 1.373 |
|                    | UMTS 1900         | 1.042               | 0.165                         | 0.191                         | 1.207               | 1.233 | 1.398 |
|                    | Cell. EVDO        | 0.966               | 0.165                         | 0.191                         | 1.131               | 1.157 | 1.322 |
|                    | PCS EVDO          | 1.031               | 0.165                         | 0.191                         | 1.196               | 1.222 | 1.387 |
|                    | LTE Band 13       | 0.696               | 0.165                         | 0.191                         | 0.861               | 0.887 | 1.052 |
|                    | LTE Band 5 (Cell) | 0.743               | 0.165                         | 0.191                         | 0.908               | 0.934 | 1.099 |
|                    | LTE Band 4 (AWS)  | 0.900               | 0.165                         | 0.191                         | 1.065               | 1.091 | 1.256 |
|                    | LTE Band 2 (PCS)  | 0.954               | 0.165                         | 0.191                         | 1.119               | 1.145 | 1.310 |

Note: 1+2+3 denotes MIMO SAR Summations.

**Table 12-14**  
**Simultaneous Transmission Scenario (5 GHz WLAN 1.0 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |       |       |
|--------------------|-------------------|---------------------|-----------------------------|-----------------------------|---------------------|-------|-------|
|                    |                   | 1                   | 2                           | 3                           | 1+2                 | 1+3   | 1+2+3 |
| Hotspot SAR        | GPRS 850          | 0.981               | 0.068                       | 0.214                       | 1.049               | 1.195 | 1.263 |
|                    | UMTS 850          | 0.621               | 0.068                       | 0.214                       | 0.689               | 0.835 | 0.903 |
|                    | GPRS 1900         | 1.017               | 0.068                       | 0.214                       | 1.085               | 1.231 | 1.299 |
|                    | UMTS 1900         | 1.042               | 0.068                       | 0.214                       | 1.110               | 1.256 | 1.324 |
|                    | Cell. EVDO        | 0.966               | 0.068                       | 0.214                       | 1.034               | 1.180 | 1.248 |
|                    | PCS EVDO          | 1.031               | 0.068                       | 0.214                       | 1.099               | 1.245 | 1.313 |
|                    | LTE Band 13       | 0.696               | 0.068                       | 0.214                       | 0.764               | 0.910 | 0.978 |
|                    | LTE Band 5 (Cell) | 0.743               | 0.068                       | 0.214                       | 0.811               | 0.957 | 1.025 |
|                    | LTE Band 4 (AWS)  | 0.900               | 0.068                       | 0.214                       | 0.968               | 1.114 | 1.182 |
|                    | LTE Band 2 (PCS)  | 0.954               | 0.068                       | 0.214                       | 1.022               | 1.168 | 1.236 |

Note: 1+2+3 denotes MIMO SAR Summations.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 107 of 119                                                                       |                                        |

**Table 12-15**  
**Simultaneous Transmission Scenario**  
**(2.4 GHz WLAN Ant 1 and 5 GHz WLAN Ant 2 at 1.0 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                   | 1                   | 2                             | 3                           | 1+2+3        |
| Hotspot SAR        | GPRS 850          | 0.981               | 0.165                         | 0.214                       | 1.360        |
|                    | UMTS 850          | 0.621               | 0.165                         | 0.214                       | 1.000        |
|                    | GPRS 1900         | 1.017               | 0.165                         | 0.214                       | 1.396        |
|                    | UMTS 1900         | 1.042               | 0.165                         | 0.214                       | 1.421        |
|                    | Cell. EVDO        | 0.966               | 0.165                         | 0.214                       | 1.345        |
|                    | PCS EVDO          | 1.031               | 0.165                         | 0.214                       | 1.410        |
|                    | LTE Band 13       | 0.696               | 0.165                         | 0.214                       | 1.075        |
|                    | LTE Band 5 (Cell) | 0.743               | 0.165                         | 0.214                       | 1.122        |
|                    | LTE Band 4 (AWS)  | 0.900               | 0.165                         | 0.214                       | 1.279        |
|                    | LTE Band 2 (PCS)  | 0.954               | 0.165                         | 0.214                       | 1.333        |

**Table 12-16**  
**Simultaneous Transmission Scenario**  
**(2.4 GHz WLAN Ant 2 and 5 GHz WLAN Ant 1 at 1.0 cm)**

| Exposure Condition | Mode              | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                   | 1                   | 2                             | 3                           | 1+2+3        |
| Hotspot SAR        | GPRS 850          | 0.981               | 0.191                         | 0.068                       | 1.240        |
|                    | UMTS 850          | 0.621               | 0.191                         | 0.068                       | 0.880        |
|                    | GPRS 1900         | 1.017               | 0.191                         | 0.068                       | 1.276        |
|                    | UMTS 1900         | 1.042               | 0.191                         | 0.068                       | 1.301        |
|                    | Cell. EVDO        | 0.966               | 0.191                         | 0.068                       | 1.225        |
|                    | PCS EVDO          | 1.031               | 0.191                         | 0.068                       | 1.290        |
|                    | LTE Band 13       | 0.696               | 0.191                         | 0.068                       | 0.955        |
|                    | LTE Band 5 (Cell) | 0.743               | 0.191                         | 0.068                       | 1.002        |
|                    | LTE Band 4 (AWS)  | 0.900               | 0.191                         | 0.068                       | 1.159        |
|                    | LTE Band 2 (PCS)  | 0.954               | 0.191                         | 0.068                       | 1.213        |

|                                   |                                                                                                                                                  |                               |                                                                                       |                                 |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br><small>ENGINEERING LABORATORY, INC.</small> | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                               | DUT Type:<br>Portable Handset |                                                                                       | Page 108 of 119                 |

## 12.6 Extremity SAR Simultaneous Transmission Analysis

1. Per FCC KDB Publication 648474 D04 Handset SAR v01r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).
2. (\*) For WLAN devices edges with antennas less than 2.5 cm from edge that were not required to be evaluated for SAR, the worst case Extremity WLAN SAR was used as it is more conservative.
3. Extremity WLAN SAR values for 0.0 cm were used for all test distances since the 0.0 cm test distance was more conservative. “<” denotes that the 0.0 cm Extremity WLAN SAR values were used for summation purpose.
4. Per FCC KDB Publication 648474 D04 Handset SAR v01r02, hand SAR tests were not required when wireless router mode does not apply and if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore no further analysis was required to determine that SAR limit would not be exceed for all possible simultaneous scenarios, including those involving bands/modes not required to be evaluated for hand SAR.
5. Extremity WLAN SAR was not required for bottom edge; thus no additional simultaneous evaluation besides included in this section was required to determine that possible simultaneous scenarios would not exceed the SAR limit.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 109 of 119                                                                       |                                        |

**Table 12-17**  
**Simultaneous Transmission Scenario - 5 GHz WLAN (Extremity at 0.0 cm)**

| Simult Tx     | Configuration | GPRS 1900 SAR (W/kg)        | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |        |
|---------------|---------------|-----------------------------|-----------------------------|-----------------------------|---------------------|--------|--------|
|               |               | 1                           | 2                           | 3                           | 1+2                 | 1+3    | 1+2+3  |
| Extremity SAR | Back          | 1.198                       | 0.528*                      | 0.162                       | 1.726*              | 1.360  | 1.888* |
|               | Front         | 1.165                       | 0.528                       | 0.461                       | 1.693               | 1.626  | 2.154  |
|               | Top           | -                           | 0.528*                      | 0.461*                      | 0.528*              | 0.461* | 0.989* |
|               | Bottom        | 1.427                       | -                           | -                           | 1.427               | 1.427  | 1.427  |
|               | Right         | 0.266                       | -                           | -                           | 0.266               | 0.266  | 0.266  |
|               | Left          | 1.126                       | 0.528*                      | 0.461*                      | 1.654*              | 1.587* | 2.115* |
| Simult Tx     | Configuration | UMTS 1900 SAR (W/kg)        | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |        |
|               |               | 1                           | 2                           | 3                           | 1+2                 | 1+3    | 1+2+3  |
| Extremity SAR | Back          | 1.230                       | 0.528*                      | 0.162                       | 1.758*              | 1.392  | 1.920* |
|               | Front         | 1.538                       | 0.528                       | 0.461                       | 2.066               | 1.999  | 2.527  |
|               | Top           | -                           | 0.528*                      | 0.461*                      | 0.528*              | 0.461* | 0.989* |
|               | Bottom        | 1.715                       | -                           | -                           | 1.715               | 1.715  | 1.715  |
|               | Right         | 0.186                       | -                           | -                           | 0.186               | 0.186  | 0.186  |
|               | Left          | 1.110                       | 0.528*                      | 0.461*                      | 1.638*              | 1.571* | 2.099* |
| Simult Tx     | Configuration | PCS EVDO SAR (W/kg)         | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |        |
|               |               | 1                           | 2                           | 3                           | 1+2                 | 1+3    | 1+2+3  |
| Extremity SAR | Back          | 1.461                       | 0.528*                      | 0.162                       | 1.989*              | 1.623  | 2.151* |
|               | Front         | 1.406                       | 0.528                       | 0.461                       | 1.934               | 1.867  | 2.395  |
|               | Top           | -                           | 0.528*                      | 0.461*                      | 0.528*              | 0.461* | 0.989* |
|               | Bottom        | 2.092                       | -                           | -                           | 2.092               | 2.092  | 2.092  |
|               | Right         | 0.216                       | -                           | -                           | 0.216               | 0.216  | 0.216  |
|               | Left          | 1.186                       | 0.528*                      | 0.461*                      | 1.714*              | 1.647* | 2.175* |
| Simult Tx     | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |        |
|               |               | 1                           | 2                           | 3                           | 1+2                 | 1+3    | 1+2+3  |
| Extremity SAR | Back          | 2.150                       | 0.528*                      | 0.162                       | 2.678*              | 2.312  | 2.840* |
|               | Front         | 1.740                       | 0.528                       | 0.461                       | 2.268               | 2.201  | 2.729  |
|               | Top           | -                           | 0.528*                      | 0.461*                      | 0.528*              | 0.461* | 0.989* |
|               | Bottom        | 3.109                       | -                           | -                           | 3.109               | 3.109  | 3.109  |
|               | Right         | 0.177                       | -                           | -                           | 0.177               | 0.177  | 0.177  |
|               | Left          | 1.230                       | 0.528*                      | 0.461*                      | 1.758*              | 1.691* | 2.219* |
| Simult Tx     | Configuration | LTE Band 2 (PCS) SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |        |
|               |               | 1                           | 2                           | 3                           | 1+2                 | 1+3    | 1+2+3  |
| Extremity SAR | Back          | 2.706                       | 0.528*                      | 0.162                       | 3.234*              | 2.868  | 3.396* |
|               | Front         | 1.603                       | 0.528                       | 0.461                       | 2.131               | 2.064  | 2.592  |
|               | Top           | -                           | 0.528*                      | 0.461*                      | 0.528*              | 0.461* | 0.989* |
|               | Bottom        | 2.611                       | -                           | -                           | 2.611               | 2.611  | 2.611  |
|               | Right         | 0.219                       | -                           | -                           | 0.219               | 0.219  | 0.219  |
|               | Left          | 1.341                       | 0.528*                      | 0.461*                      | 1.869*              | 1.802* | 2.330* |

Note: 1+2+3 denotes MIMO SAR Summations.

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 110 of 119                 |

**Table 12-18**  
**Simultaneous Transmission Scenario - Bluetooth (Extremity at 0.0 cm)**

| Simult Tx     | Configuration | GPRS 1900 SAR (W/kg)        | Bluetooth SAR (W/kg) | Σ SAR (W/kg) | Simult Tx     | Configuration | UMTS 1900 SAR (W/kg)        | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |
|---------------|---------------|-----------------------------|----------------------|--------------|---------------|---------------|-----------------------------|----------------------|--------------|
|               |               | 1                           | 2                    | 1+2          |               |               | 1                           | 2                    | 1+2          |
| Extremity SAR | Back          | 1.198                       | 0.185                | 1.383        | Extremity SAR | Back          | 1.230                       | 0.185                | 1.415        |
|               | Front         | 1.165                       | 0.185                | 1.350        |               | Front         | 1.538                       | 0.185                | 1.723        |
|               | Top           | -                           | 0.185                | 0.185        |               | Top           | -                           | 0.185                | 0.185        |
|               | Bottom        | 1.427                       | -                    | 1.427        |               | Bottom        | 1.715                       | -                    | 1.715        |
|               | Right         | 0.266                       | -                    | 0.266        |               | Right         | 0.186                       | -                    | 0.186        |
|               | Left          | 1.126                       | 0.185                | 1.311        |               | Left          | 1.110                       | 0.185                | 1.295        |
| Simult Tx     | Configuration | PCS EVDO SAR (W/kg)         | Bluetooth SAR (W/kg) | Σ SAR (W/kg) | Simult Tx     | Configuration | LTE Band 4 (AWS) SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |
|               |               | 1                           | 2                    | 1+2          |               |               | 1                           | 2                    | 1+2          |
| Extremity SAR | Back          | 1.461                       | 0.185                | 1.646        | Extremity SAR | Back          | 2.150                       | 0.185                | 2.335        |
|               | Front         | 1.406                       | 0.185                | 1.591        |               | Front         | 1.740                       | 0.185                | 1.925        |
|               | Top           | -                           | 0.185                | 0.185        |               | Top           | -                           | 0.185                | 0.185        |
|               | Bottom        | 2.092                       | -                    | 2.092        |               | Bottom        | 3.109                       | -                    | 3.109        |
|               | Right         | 0.216                       | -                    | 0.216        |               | Right         | 0.177                       | -                    | 0.177        |
|               | Left          | 1.186                       | 0.185                | 1.371        |               | Left          | 1.230                       | 0.185                | 1.415        |
| Simult Tx     | Configuration | LTE Band 2 (PCS) SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |               |               |                             |                      |              |
|               |               | 1                           | 2                    | 1+2          |               |               |                             |                      |              |
| Extremity SAR | Back          | 2.706                       | 0.185                | 2.891        |               |               |                             |                      |              |
|               | Front         | 1.603                       | 0.185                | 1.788        |               |               |                             |                      |              |
|               | Top           | -                           | 0.185                | 0.185        |               |               |                             |                      |              |
|               | Bottom        | 2.611                       | -                    | 2.611        |               |               |                             |                      |              |
|               | Right         | 0.219                       | -                    | 0.219        |               |               |                             |                      |              |
|               | Left          | 1.341                       | 0.185                | 1.526        |               |               |                             |                      |              |

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 111 of 119                                                                       |                                 |

**Table 12-19**  
**Simultaneous Transmission Scenario - 5 GHz WLAN (Back at 0.3 cm)**

| Configuration | Mode             | 2G/3G/4G SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |         |
|---------------|------------------|---------------------|-----------------------------|-----------------------------|---------------------|--------|---------|
|               |                  | 1                   | 2                           | 3                           | 1+2                 | 1+3    | 1+2+3   |
| Back Side     | GSM 1900         | 1.365               | <0.528*                     | <0.162                      | <1.893*             | <1.527 | <2.055* |
|               | UMTS 1900        | 1.056               | <0.528*                     | <0.162                      | <1.584*             | <1.218 | <1.746* |
|               | PCS CDMA         | 1.483               | <0.528*                     | <0.162                      | <2.011*             | <1.645 | <2.173* |
|               | LTE Band 4 (AWS) | 2.580               | <0.528*                     | <0.162                      | <3.108*             | <2.742 | <3.270* |
|               | LTE Band 2 (PCS) | 1.713               | <0.528*                     | <0.162                      | <2.241*             | <1.875 | <2.403* |

Note: 1+2+3 denotes MIMO SAR Summations.

**Table 12-20**  
**Simultaneous Transmission Scenario - Bluetooth (Back at 0.3 cm)**

| Configuration | Mode             | 2G/3G/4G SAR (W/kg) | Bluetooth SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|---------------|------------------|---------------------|----------------------|---------------------|
|               |                  | 1                   | 2                    | 1+2                 |
| Back Side     | GSM 1900         | 1.365               | 0.185                | 1.550               |
|               | UMTS 1900        | 1.056               | 0.185                | 1.241               |
|               | PCS CDMA         | 1.483               | 0.185                | 1.668               |
|               | LTE Band 4 (AWS) | 2.580               | 0.185                | 2.765               |
|               | LTE Band 2 (PCS) | 1.713               | 0.185                | 1.898               |

**Table 12-21**  
**Simultaneous Transmission Scenario - 5 GHz WLAN (Front at 0.1 cm)**

| Configuration | Mode             | 2G/3G/4G SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |        |        |
|---------------|------------------|---------------------|-----------------------------|-----------------------------|---------------------|--------|--------|
|               |                  | 1                   | 2                           | 3                           | 1+2                 | 1+3    | 1+2+3  |
| Front Side    | GSM 1900         | 2.979               | <0.528                      | <0.461                      | <3.507              | <3.440 | <3.968 |
|               | UMTS 1900        | 2.717               | <0.528                      | <0.461                      | <3.245              | <3.178 | <3.706 |
|               | PCS CDMA         | 1.815               | <0.528                      | <0.461                      | <2.343              | <2.276 | <2.804 |
|               | LTE Band 4 (AWS) | 2.960               | <0.528                      | <0.461                      | <3.488              | <3.421 | <3.949 |
|               | LTE Band 2 (PCS) | 1.995               | <0.528                      | <0.461                      | <2.523              | <2.456 | <2.984 |

Note: 1+2+3 denotes MIMO SAR Summations.

**Table 12-22**  
**Simultaneous Transmission Scenario - Bluetooth (Front at 0.1 cm)**

| Configuration | Mode             | 2G/3G/4G SAR (W/kg) | SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|---------------|------------------|---------------------|------------|---------------------|
|               |                  | 1                   | 2          | 1+2                 |
| Front Side    | GSM 1900         | 2.979               | 0.185      | 3.164               |
|               | UMTS 1900        | 2.717               | 0.185      | 2.902               |
|               | PCS CDMA         | 1.815               | 0.185      | 2.000               |
|               | LTE Band 4 (AWS) | 2.960               | 0.185      | 3.145               |
|               | LTE Band 2 (PCS) | 1.995               | 0.185      | 2.180               |

## 12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset | Page 112 of 119                                                                       |                                 |

## 13 SAR MEASUREMENT VARIABILITY

### 13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

Per FCC KDB Publication 865664 D01v01, Extremity SAR measurement variability was assessed since measured 1g SAR for some frequency band was above 0.8 W/kg and measured 10g SAR for some frequency band was above 2.0 W/kg.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is  $\geq 0.80$  W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was  $> 1.20$  or when the original or repeated measurement was  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .
- 4) Repeated measurements are not required when the original highest measured SAR is  $< 0.80$  W/kg
- 5) 10g Extremity SAR measurement variability analysis applies a factor of 2.5 to the procedures outlined above.

**Table 13-1**  
**Body SAR Measurement Variability Results**

| BODY VARIABILITY RESULTS                 |           |       |                  |                         |                 |        |                      |                   |                       |       |                       |       |                       |       |
|------------------------------------------|-----------|-------|------------------|-------------------------|-----------------|--------|----------------------|-------------------|-----------------------|-------|-----------------------|-------|-----------------------|-------|
| Band                                     | FREQUENCY |       | Mode             | Service                 | # of GPRS Slots | Side   | Spacing              | Measured SAR (1g) | 1st Repeated SAR (1g) | Ratio | 2nd Repeated SAR (1g) | Ratio | 3rd Repeated SAR (1g) | Ratio |
|                                          | MHz       | Ch.   |                  |                         |                 |        |                      | (W/kg)            | (W/kg)                |       | (W/kg)                |       | (W/kg)                |       |
| 835                                      | 836.60    | 190   | GSM 850          | GPRS                    | 3               | front  | 10 mm                | 0.974             | 0.935                 | 1.04  | N/A                   | N/A   | N/A                   | N/A   |
| 1900                                     | 1851.25   | 25    | PCS CDMA         | EVDO Rev. 0             | N/A             | bottom | 10 mm                | 0.945             | 0.944                 | 1.00  | N/A                   | N/A   | N/A                   | N/A   |
| 1750                                     | 1732.50   | 20175 | LTE Band 4 (AWS) | QPSK, 1 RB, 0 RB Offset | N/A             | bottom | 10 mm                | 0.800             | 0.800                 | 1.00  | N/A                   | N/A   | N/A                   | N/A   |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |           |       |                  |                         |                 |        | Body                 |                   |                       |       |                       |       |                       |       |
| Spatial Peak                             |           |       |                  |                         |                 |        | 1.6 W/kg (mW/g)      |                   |                       |       |                       |       |                       |       |
| Uncontrolled Exposure/General Population |           |       |                  |                         |                 |        | averaged over 1 gram |                   |                       |       |                       |       |                       |       |

**Table 13-2**  
**Extremity SAR Measurement Variability Results**

| EXTREMITY VARIABILITY RESULTS            |           |       |                  |                         |        |                        |                    |                        |       |                        |       |                        |       |
|------------------------------------------|-----------|-------|------------------|-------------------------|--------|------------------------|--------------------|------------------------|-------|------------------------|-------|------------------------|-------|
| Band                                     | FREQUENCY |       | Mode             | Service                 | Side   | Spacing                | Measured SAR (10g) | 1st Repeated SAR (10g) | Ratio | 2nd Repeated SAR (10g) | Ratio | 3rd Repeated SAR (10g) | Ratio |
|                                          | MHz       | Ch.   |                  |                         |        |                        | (W/kg)             | (W/kg)                 |       | (W/kg)                 |       | (W/kg)                 |       |
| 1750                                     | 1732.50   | 20175 | LTE Band 4 (AWS) | QPSK, 1 RB, 0 RB Offset | bottom | 0 mm                   | 3.040              | 2.740                  | 1.11  | N/A                    | N/A   | N/A                    | N/A   |
| 1900                                     | 1860.00   | 18700 | LTE Band 2 (PCS) | QPSK, 1 RB, 0 RB Offset | bottom | 4 mm                   | 2.830              | 2.730                  | 1.04  | N/A                    | N/A   | N/A                    | N/A   |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |           |       |                  |                         |        | Extremity              |                    |                        |       |                        |       |                        |       |
| Spatial Peak                             |           |       |                  |                         |        | 4.0 W/kg (mW/g)        |                    |                        |       |                        |       |                        |       |
| Uncontrolled Exposure/General Population |           |       |                  |                         |        | averaged over 10 grams |                    |                        |       |                        |       |                        |       |

### 13.2 Measurement Uncertainty

The measured 1g SAR was  $< 1.5$  W/kg and 10g SAR was  $< 3.75$  W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

|                                   |                                                                                                                                   |                               |                                                                                       |                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                                                                | DUT Type:<br>Portable Handset |                                                                                       | Page 113 of 119                 |

# 14 EQUIPMENT LIST

| Manufacturer       | Model           | Description                                   | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|--------------------|-----------------|-----------------------------------------------|------------|--------------|------------|---------------|
| Agilent            | 8594A           | (9kHz-2.9GHz) Spectrum Analyzer               | N/A        | N/A          | N/A        | 3051A00187    |
| Agilent            | 8648D           | (9kHz-4GHz) Signal Generator                  | 3/15/2015  | Annual       | 3/15/2016  | 3629U00687    |
| Agilent            | 8753E           | (30kHz-6GHz) Network Analyzer                 | 12/30/2014 | Annual       | 12/30/2015 | JP38020182    |
| Agilent            | 8753ES          | S-Parameter Network Analyzer                  | 3/12/2015  | Annual       | 3/12/2016  | MY40000670    |
| Agilent            | 8753ES          | Network Analyzer                              | 3/20/2015  | Annual       | 3/20/2016  | MY40001472    |
| Agilent            | E4432B          | ESG-D Series Signal Generator                 | 3/16/2015  | Annual       | 3/16/2016  | US40053896    |
| Agilent            | E4438C          | ESG Vector Signal Generator                   | 3/13/2015  | Annual       | 3/13/2016  | MY42082385    |
| Agilent            | E4438C          | ESG Vector Signal Generator                   | 3/13/2015  | Annual       | 3/13/2016  | MY42082659    |
| Agilent            | E5515C          | Wireless Communications Test Set              | 2/23/2015  | Biennial     | 2/23/2017  | GB41450275    |
| Agilent            | E5515C          | Wireless Communications Test Set              | 11/20/2014 | Annual       | 11/20/2015 | GB42361078    |
| Agilent            | E8257D          | (250kHz-20GHz) Signal Generator               | 3/15/2015  | Annual       | 3/15/2016  | MY45470194    |
| Agilent            | N4010A          | Wireless Connectivity Test Set                | CBT        | N/A          | CBT        | GB44450273    |
| Agilent            | N5182A          | MXG Vector Signal Generator                   | 10/27/2014 | Annual       | 10/27/2015 | MY47420603    |
| Agilent            | N9020A          | MXA Signal Analyzer                           | 10/27/2014 | Annual       | 10/27/2015 | US46470561    |
| Amplifier Research | 1551G6          | Amplifier                                     | CBT        | N/A          | CBT        | 433971        |
| Amplifier Research | 1551G6          | Amplifier                                     | CBT        | N/A          | CBT        | 433972        |
| Amplifier Research | 1551G6          | Amplifier                                     | CBT        | N/A          | CBT        | 433974        |
| Anritsu            | MA24106A        | USB Power Sensor                              | 3/3/2015   | Annual       | 3/3/2016   | 1349501       |
| Anritsu            | MA24106A        | USB Power Sensor                              | 3/2/2015   | Annual       | 3/2/2016   | 1349503       |
| Anritsu            | MA24106A        | USB Power Sensor                              | 3/11/2015  | Annual       | 3/11/2016  | 1349509       |
| Anritsu            | MA24106A        | USB Power Sensor                              | 3/11/2015  | Annual       | 3/11/2016  | 1349514       |
| Anritsu            | MA2411B         | Pulse Power Sensor                            | 11/17/2014 | Annual       | 11/17/2015 | 1126066       |
| Anritsu            | MA2411B         | Pulse Power Sensor                            | 11/17/2014 | Annual       | 11/17/2015 | 1207364       |
| Anritsu            | MA2481A         | Power Sensor                                  | 3/10/2015  | Annual       | 3/10/2016  | 2400          |
| Anritsu            | MA2481A         | Power Sensor                                  | 3/11/2015  | Annual       | 3/11/2016  | 5318          |
| Anritsu            | ML2495A         | Power Meter                                   | 10/31/2013 | Biennial     | 10/31/2015 | 941001        |
| Anritsu            | ML2495A         | Power Meter                                   | 10/31/2013 | Biennial     | 10/31/2015 | 1039008       |
| Anritsu            | MT8820C         | Radio Communication Analyzer                  | 3/10/2015  | Annual       | 3/10/2016  | 6200901190    |
| Anritsu            | MT8820C         | Radio Communication Analyzer                  | 9/19/2014  | Annual       | 9/19/2015  | 6201144418    |
| COMTECH            | AR85729-5       | Solid State Amplifier                         | CBT        | N/A          | CBT        | M155A00-009   |
| COMTECH            | AR85729-5/5759B | Solid State Amplifier                         | CBT        | N/A          | CBT        | M3W1A00-1002  |
| Control Company    | 4040            | Digital Thermometer                           | 3/18/2015  | Biennial     | 3/18/2017  | 150194895     |
| Control Company    | 4040            | Digital Thermometer                           | 3/15/2015  | Biennial     | 3/15/2017  | 150195005     |
| Control Company    | 4052            | Long Stem Thermometer                         | 9/27/2013  | Biennial     | 9/27/2015  | 130567447     |
| Control Company    | 36934-158       | Wall-Mounted Thermometer                      | 4/29/2014  | Biennial     | 4/29/2016  | 122014488     |
| Fisher Scientific  | 15-077-960      | Digital Thermometer                           | 12/4/2013  | Biennial     | 12/4/2015  | 130764551     |
| Fisher Scientific  | 5407993         | Long Stem Thermometer                         | 11/4/2013  | Biennial     | 11/4/2015  | 130671801     |
| Gigatronics        | 80701A          | (0.05-18GHz) Power Sensor                     | 10/30/2014 | Annual       | 10/30/2015 | 1833460       |
| Gigatronics        | 8651A           | Universal Power Meter                         | 10/30/2014 | Annual       | 10/30/2015 | 8650319       |
| Keysight           | 772D            | Dual Directional Coupler                      | CBT        | N/A          | CBT        | MY52180215    |
| MCL                | BW-N6W5+        | 6dB Attenuator                                | CBT        | N/A          | CBT        | 1139          |
| MiniCircuits       | SLP-2400+       | Low Pass Filter                               | CBT        | N/A          | CBT        | R8979500903   |
| MiniCircuits       | VLF-6000+       | Low Pass Filter                               | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | BW-N20W5        | Power Attenuator                              | CBT        | N/A          | CBT        | 1226          |
| Mini-Circuits      | BW-N20W5+       | DC to 18 GHz Precision Fixed 20 dB Attenuator | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | NLP-1200+       | Low Pass Filter DC to 1000 MHz                | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | NLP-2950+       | Low Pass Filter DC to 2700 MHz                | CBT        | N/A          | CBT        | N/A           |
| Mitutoyo           | CD-6-CSX        | Digital Caliper                               | 5/8/2014   | Biennial     | 5/8/2016   | 13264162      |
| Narda              | 4014C-6         | 4 - 8 GHz SMA 6 dB Directional Coupler        | CBT        | N/A          | CBT        | N/A           |
| Narda              | 4772-3          | Attenuator (3dB)                              | CBT        | N/A          | CBT        | 9406          |
| Pasternack         | NC-100          | Torque Wrench                                 | CBT        | N/A          | CBT        | N/A           |
| Pasternack         | NC-100          | Torque Wrench                                 | 5/21/2015  | Biennial     | 5/21/2017  | N/A           |
| Pasternack         | PE2208-6        | Bidirectional Coupler                         | CBT        | N/A          | CBT        | N/A           |
| Pasternack         | PE2209-10       | Bidirectional Coupler                         | CBT        | N/A          | CBT        | N/A           |
| Pasternack         | NC-100          | Torque Wrench                                 | 5/21/2015  | Biennial     | 5/21/2017  | N/A           |
| Rohde & Schwarz    | CMU200          | Base Station Simulator                        | 6/3/2015   | Annual       | 6/3/2016   | 109892        |
| Rohde & Schwarz    | CMU200          | Base Station Simulator                        | 3/23/2015  | Annual       | 3/23/2016  | 836371/0079   |
| Rohde & Schwarz    | CMW500          | Radio Communication Tester                    | 10/3/2014  | Annual       | 10/3/2015  | 100976        |
| Rohde & Schwarz    | CMW500          | Radio Communication Tester                    | 4/22/2015  | Annual       | 4/22/2016  | 101699        |
| Seekonk            | NC-100          | Torque Wrench                                 | 3/18/2014  | Biennial     | 3/18/2016  | 22313         |
| SPEAG              | D750V3          | 750 MHz Dipole                                | 1/16/2015  | Annual       | 1/16/2016  | 1003          |
| SPEAG              | D835V2          | 835 MHz SAR Dipole                            | 1/16/2015  | Annual       | 1/16/2016  | 4d132         |
| SPEAG              | D835V2          | 835 MHz SAR Dipole                            | 7/24/2014  | Annual       | 7/24/2015  | 4d133         |
| SPEAG              | D1750V2         | 1750 MHz SAR Dipole                           | 4/15/2015  | Annual       | 4/15/2016  | 1051          |
| SPEAG              | D1900V2         | 1900 MHz SAR Dipole                           | 4/14/2015  | Annual       | 4/14/2016  | 5d141         |
| SPEAG              | D2450V2         | 2450 MHz SAR Dipole                           | 8/11/2014  | Annual       | 8/11/2015  | 719           |
| SPEAG              | D5GHZV2         | 5 GHz SAR Dipole                              | 1/21/2015  | Annual       | 1/21/2016  | 1057          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 1/14/2015  | Annual       | 1/14/2016  | 1272          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 9/17/2014  | Annual       | 9/17/2015  | 1323          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 3/13/2015  | Annual       | 3/13/2016  | 1334          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 9/18/2014  | Annual       | 9/18/2015  | 1364          |
| SPEAG              | DAE4            | Dasy Data Acquisition Electronics             | 10/23/2014 | Annual       | 10/23/2015 | 1408          |
| SPEAG              | DAK-3.5         | Dielectric Assessment Kit                     | 5/12/2015  | Annual       | 5/12/2016  | 1070          |
| SPEAG              | DAK-3.5         | Dielectric Assessment Kit                     | 10/21/2014 | Annual       | 10/21/2015 | 1091          |
| SPEAG              | ES3DV3          | SAR Probe                                     | 5/20/2015  | Annual       | 5/20/2016  | 3263          |
| SPEAG              | ES3DV3          | SAR Probe                                     | 9/24/2014  | Annual       | 9/24/2015  | 3288          |
| SPEAG              | ES3DV3          | SAR Probe                                     | 1/23/2015  | Annual       | 1/23/2016  | 3318          |
| SPEAG              | EX3DV4          | SAR Probe                                     | 1/22/2015  | Annual       | 1/22/2016  | 3589          |
| SPEAG              | EX3DV4          | SAR Probe                                     | 4/23/2015  | Annual       | 4/23/2016  | 7357          |
| VWR                | 36934-158       | Wall-Mounted Thermometer                      | 4/29/2014  | Biennial     | 4/29/2016  | 111859323     |

Note:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment item was used solely within its respective calibration period.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 114 of 119                        |

## 15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz:

| a                                                                             | b                    | c             | d              | e=<br>f(d,k) | f                     | g                        | h =<br>c x f/e                 | i =<br>c x g/e                   | k              |
|-------------------------------------------------------------------------------|----------------------|---------------|----------------|--------------|-----------------------|--------------------------|--------------------------------|----------------------------------|----------------|
| Uncertainty<br>Component                                                      | IEEE<br>1528<br>Sec. | Tol.<br>(± %) | Prob.<br>Dist. | Div.         | c <sub>i</sub><br>1gm | c <sub>i</sub><br>10 gms | 1gm<br>u <sub>i</sub><br>(± %) | 10gms<br>u <sub>i</sub><br>(± %) | v <sub>i</sub> |
| <b>Measurement System</b>                                                     |                      |               |                |              |                       |                          |                                |                                  |                |
| Probe Calibration                                                             | E.2.1                | 6.0           | N              | 1            | 1.0                   | 1.0                      | 6.0                            | 6.0                              | ∞              |
| Axial Isotropy                                                                | E.2.2                | 0.25          | N              | 1            | 0.7                   | 0.7                      | 0.2                            | 0.2                              | ∞              |
| Hemishperical Isotropy                                                        | E.2.2                | 1.3           | N              | 1            | 1.0                   | 1.0                      | 1.3                            | 1.3                              | ∞              |
| Boundary Effect                                                               | E.2.3                | 0.4           | N              | 1            | 1.0                   | 1.0                      | 0.4                            | 0.4                              | ∞              |
| Linearity                                                                     | E.2.4                | 0.3           | N              | 1            | 1.0                   | 1.0                      | 0.3                            | 0.3                              | ∞              |
| System Detection Limits                                                       | E.2.5                | 5.1           | N              | 1            | 1.0                   | 1.0                      | 5.1                            | 5.1                              | ∞              |
| Readout Electronics                                                           | E.2.6                | 1.0           | N              | 1            | 1.0                   | 1.0                      | 1.0                            | 1.0                              | ∞              |
| Response Time                                                                 | E.2.7                | 0.8           | R              | 1.73         | 1.0                   | 1.0                      | 0.5                            | 0.5                              | ∞              |
| Integration Time                                                              | E.2.8                | 2.6           | R              | 1.73         | 1.0                   | 1.0                      | 1.5                            | 1.5                              | ∞              |
| RF Ambient Conditions                                                         | E.6.1                | 3.0           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Probe Positioner Mechanical Tolerance                                         | E.6.2                | 0.4           | R              | 1.73         | 1.0                   | 1.0                      | 0.2                            | 0.2                              | ∞              |
| Probe Positioning w/ respect to Phantom                                       | E.6.3                | 2.9           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation | E.5                  | 1.0           | R              | 1.73         | 1.0                   | 1.0                      | 0.6                            | 0.6                              | ∞              |
| <b>Test Sample Related</b>                                                    |                      |               |                |              |                       |                          |                                |                                  |                |
| Test Sample Positioning                                                       | E.4.2                | 6.0           | N              | 1            | 1.0                   | 1.0                      | 6.0                            | 6.0                              | 287            |
| Device Holder Uncertainty                                                     | E.4.1                | 3.32          | R              | 1.73         | 1.0                   | 1.0                      | 1.9                            | 1.9                              | ∞              |
| Output Power Variation - SAR drift measurement                                | E.6.2                | 5.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.9                            | 2.9                              | ∞              |
| <b>Phantom &amp; Tissue Parameters</b>                                        |                      |               |                |              |                       |                          |                                |                                  |                |
| Phantom Uncertainty (Shape & Thickness tolerances)                            | E.3.1                | 4.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.3                            | 2.3                              | ∞              |
| Liquid Conductivity - deviation from target values                            | E.3.2                | 5.0           | R              | 1.73         | 0.64                  | 0.43                     | 1.8                            | 1.2                              | ∞              |
| Liquid Conductivity - measurement uncertainty                                 | E.3.3                | 3.8           | N              | 1            | 0.64                  | 0.43                     | 2.4                            | 1.6                              | 6              |
| Liquid Permittivity - deviation from target values                            | E.3.2                | 5.0           | R              | 1.73         | 0.60                  | 0.49                     | 1.7                            | 1.4                              | ∞              |
| Liquid Permittivity - measurement uncertainty                                 | E.3.3                | 4.5           | N              | 1            | 0.60                  | 0.49                     | 2.7                            | 2.2                              | 6              |
| <b>Combined Standard Uncertainty (k=1)</b>                                    |                      |               |                |              |                       |                          | RSS                            | 12.1                             | 11.7           |
| <b>Expanded Uncertainty</b><br>(95% CONFIDENCE LEVEL)                         |                      |               |                |              |                       |                          | k=2                            | 24.2                             | 23.5           |

The above measurement uncertainties are according to IEEE Std. 1528-2003

|                                   |                                                                                     |                               |                                                                                       |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset |                                                                                       | Page 115 of 119                 |

Applicable for frequencies up to 6 GHz:

| a                                                                             | b                    | c             | d              | e=<br>f(d,k) | f                     | g                        | h=<br>c x i/e                  | i=<br>c x g/e                    | k              |
|-------------------------------------------------------------------------------|----------------------|---------------|----------------|--------------|-----------------------|--------------------------|--------------------------------|----------------------------------|----------------|
| Uncertainty<br>Component                                                      | IEEE<br>1528<br>Sec. | Tol.<br>(± %) | Prob.<br>Dist. | Div.         | c <sub>i</sub><br>1gm | c <sub>i</sub><br>10 gms | 1gm<br>u <sub>i</sub><br>(± %) | 10gms<br>u <sub>i</sub><br>(± %) | v <sub>i</sub> |
| <b>Measurement System</b>                                                     |                      |               |                |              |                       |                          |                                |                                  |                |
| Probe Calibration                                                             | E.2.1                | 6.55          | N              | 1            | 1.0                   | 1.0                      | 6.6                            | 6.6                              | ∞              |
| Axial Isotropy                                                                | E.2.2                | 0.25          | N              | 1            | 0.7                   | 0.7                      | 0.2                            | 0.2                              | ∞              |
| Hemishperical Isotropy                                                        | E.2.2                | 1.3           | N              | 1            | 1.0                   | 1.0                      | 1.3                            | 1.3                              | ∞              |
| Boundary Effect                                                               | E.2.3                | 0.4           | N              | 1            | 1.0                   | 1.0                      | 0.4                            | 0.4                              | ∞              |
| Linearity                                                                     | E.2.4                | 0.3           | N              | 1            | 1.0                   | 1.0                      | 0.3                            | 0.3                              | ∞              |
| System Detection Limits                                                       | E.2.5                | 5.1           | N              | 1            | 1.0                   | 1.0                      | 5.1                            | 5.1                              | ∞              |
| Readout Electronics                                                           | E.2.6                | 1.0           | N              | 1            | 1.0                   | 1.0                      | 1.0                            | 1.0                              | ∞              |
| Response Time                                                                 | E.2.7                | 0.8           | R              | 1.73         | 1.0                   | 1.0                      | 0.5                            | 0.5                              | ∞              |
| Integration Time                                                              | E.2.8                | 2.6           | R              | 1.73         | 1.0                   | 1.0                      | 1.5                            | 1.5                              | ∞              |
| RF Ambient Conditions                                                         | E.6.1                | 3.0           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Probe Positioner Mechanical Tolerance                                         | E.6.2                | 0.4           | R              | 1.73         | 1.0                   | 1.0                      | 0.2                            | 0.2                              | ∞              |
| Probe Positioning w/ respect to Phantom                                       | E.6.3                | 2.9           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation | E.5                  | 1.0           | R              | 1.73         | 1.0                   | 1.0                      | 0.6                            | 0.6                              | ∞              |
| <b>Test Sample Related</b>                                                    |                      |               |                |              |                       |                          |                                |                                  |                |
| Test Sample Positioning                                                       | E.4.2                | 6.0           | N              | 1            | 1.0                   | 1.0                      | 6.0                            | 6.0                              | 287            |
| Device Holder Uncertainty                                                     | E.4.1                | 3.32          | R              | 1.73         | 1.0                   | 1.0                      | 1.9                            | 1.9                              | ∞              |
| Output Power Variation - SAR drift measurement                                | 6.6.2                | 5.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.9                            | 2.9                              | ∞              |
| <b>Phantom &amp; Tissue Parameters</b>                                        |                      |               |                |              |                       |                          |                                |                                  |                |
| Phantom Uncertainty (Shape & Thickness tolerances)                            | E.3.1                | 4.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.3                            | 2.3                              | ∞              |
| Liquid Conductivity - deviation from target values                            | E.3.2                | 5.0           | R              | 1.73         | 0.64                  | 0.43                     | 1.8                            | 1.2                              | ∞              |
| Liquid Conductivity - measurement uncertainty                                 | E.3.3                | 3.8           | N              | 1            | 0.64                  | 0.43                     | 2.4                            | 1.6                              | 6              |
| Liquid Permittivity - deviation from target values                            | E.3.2                | 5.0           | R              | 1.73         | 0.60                  | 0.49                     | 1.7                            | 1.4                              | ∞              |
| Liquid Permittivity - measurement uncertainty                                 | E.3.3                | 4.5           | N              | 1            | 0.60                  | 0.49                     | 2.7                            | 2.2                              | 6              |
| <b>Combined Standard Uncertainty (k=1)</b>                                    |                      |               |                |              |                       |                          | RSS                            | 12.4                             | 12.0           |
| <b>Expanded Uncertainty</b><br>(95% CONFIDENCE LEVEL)                         |                      |               |                |              |                       |                          | k=2                            | 24.7                             | 24.0           |

The above measurement uncertainties are according to IEEE Std. 1528-2003

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset | Page 116 of 119                                                                       |                                        |

## 16 CONCLUSION

### 16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>0Y1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 117 of 119                        |

## 17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1-124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

|                                          |                                                                                                                                   |                                      |                                                                                       |                                        |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMG928V                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>OY1506081055.A3L | <b>Test Dates:</b><br>06/08/15 – 06/29/15                                                                                         | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 118 of 119                        |

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01v02r01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

|                                   |                                                                                     |                               |                                                                                                                    |                                 |
|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMG928V                |  |                               | <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>0Y1506081055.A3L | Test Dates:<br>06/08/15 – 06/29/15                                                  | DUT Type:<br>Portable Handset | Page 119 of 119                                                                                                    |                                 |

## APPENDIX A: SAR TEST DATA

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head, Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.881 \text{ S/m}$ ;  $\epsilon_r = 39.943$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-26-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3288; ConvF(6.51, 6.51, 6.51); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 850, Right Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 16.94 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.294 W/kg

**SAR(1 g) = 0.234 W/kg**



0 dB = 0.254 W/kg = -5.95 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head, Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.881 \text{ S/m}$ ;  $\epsilon_r = 39.943$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-26-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3288; ConvF(6.51, 6.51, 6.51); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Right Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 14.92 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.226 W/kg

**SAR(1 g) = 0.182 W/kg**



0 dB = 0.196 W/kg = -7.08 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head, Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.395 \text{ S/m}$ ;  $\epsilon_r = 39.656$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-14-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3318; ConvF(5.05, 5.05, 5.05); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 1900, Right Head, Cheek, Mid.ch**


**Area Scan (8x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 8.274 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.126 W/kg

**SAR(1 g) = 0.085 W/kg**



0 dB = 0.0967 W/kg = -10.15 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head, Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.395 \text{ S/m}$ ;  $\epsilon_r = 39.656$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-14-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3318; ConvF(5.05, 5.05, 5.05); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Right Head, Cheek, Mid.ch**


**Area Scan (8x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 9.128 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.211 W/kg

**SAR(1 g) = 0.137 W/kg**



0 dB = 0.159 W/kg = -7.99 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1  
Medium: 835 Head, Medium parameters used (interpolated):  
 $f = 836.52 \text{ MHz}$ ;  $\sigma = 0.881 \text{ S/m}$ ;  $\epsilon_r = 39.944$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 06-26-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3288; ConvF(6.51, 6.51, 6.51); Calibrated: 9/24/2014;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1364; Calibrated: 9/18/2014  
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. CDMA, Right Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 21.63 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.488 W/kg

**SAR(1 g) = 0.389 W/kg**



0 dB = 0.422 W/kg = -3.75 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9660B**

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head, Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.395 \text{ S/m}$ ;  $\epsilon_r = 39.656$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-14-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3318; ConvF(5.05, 5.05, 5.05); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: PCS CDMA, Right Head, Cheek, Mid.ch**


**Area Scan (8x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 10.79 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.254 W/kg

**SAR(1 g) = 0.165 W/kg**



0 dB = 0.197 W/kg = -7.06 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head, Medium parameters used (interpolated):

$f = 782 \text{ MHz}$ ;  $\sigma = 0.924 \text{ S/m}$ ;  $\epsilon_r = 41.627$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-22-2015; Ambient Temp: 22.3°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3288; ConvF(6.81, 6.81, 6.81); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Right Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.26 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.281 W/kg

**SAR(1 g) = 0.223 W/kg**



0 dB = 0.244 W/kg = -6.13 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head, Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$ ;  $\sigma = 0.881 \text{ S/m}$ ;  $\epsilon_r = 39.944$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-26-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3288; ConvF(6.51, 6.51, 6.51); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (6x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.38 V/m; Power Drift = -0.21 dB

Peak SAR (extrapolated) = 0.248 W/kg

**SAR(1 g) = 0.202 W/kg**



0 dB = 0.219 W/kg = -6.60 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE RF Band 4; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
Medium: 1750 Head, Medium parameters used (interpolated):  
 $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.368 \text{ S/m}$ ;  $\epsilon_r = 40.128$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 06-29-2015; Ambient Temp: 21.1°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3263; ConvF(5.27, 5.27, 5.27); Calibrated: 5/20/2015;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Right Head, Cheek, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 14.46 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.356 W/kg

**SAR(1 g) = 0.238 W/kg**



0 dB = 0.280 W/kg = -5.53 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Head, Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$ ;  $\sigma = 1.374 \text{ S/m}$ ;  $\epsilon_r = 39.747$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-14-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3318; ConvF(5.05, 5.05, 5.05); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Right Head, Cheek, Low.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.79 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.247 W/kg

**SAR(1 g) = 0.162 W/kg**



0 dB = 0.188 W/kg = -7.26 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9587C**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2400 Head, Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$ ;  $\sigma = 1.891 \text{ S/m}$ ;  $\epsilon_r = 39.197$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-25-2015; Ambient Temp: 20.5°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(4.5, 4.5, 4.5); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, Antenna 1, 22 MHz Bandwidth,  
Right Head, Cheek, Ch 11, 1 Mbps**


**Area Scan (11x18x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 15.69 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.10 W/kg

**SAR(1 g) = 0.537 W/kg**



0 dB = 0.703 W/kg = -1.53 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9587C**

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head, Medium parameters used:

$f = 5745 \text{ MHz}$ ;  $\sigma = 5.055 \text{ S/m}$ ;  $\epsilon_r = 34.999$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-25-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7357; ConvF(4.41, 4.41, 4.41); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/13/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, Antenna 1, U-NII-3, 20 MHz Bandwidth,  
Right Head, Cheek, Ch 149, 6 Mbps**


**Area Scan (13x21x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.844 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 2.03 W/kg

**SAR(1 g) = 0.391 W/kg**



0 dB = 1.13 W/kg = 0.53 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.99 \text{ S/m}$ ;  $\epsilon_r = 52.854$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 850, Body SAR, Back side, Mid.ch**


**Area Scan (8x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 19.96 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.508 W/kg

**SAR(1 g) = 0.376 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, GPRS; 3 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.76

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6$  MHz;  $\sigma = 0.99$  S/m;  $\epsilon_r = 52.854$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 850, Body SAR, Front side, Mid.ch, 3 Tx Slots**


**Area Scan (8x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 33.11 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.66 W/kg

**SAR(1 g) = 0.974 W/kg**



0 dB = 1.18 W/kg = 0.72 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.99 \text{ S/m}$ ;  $\epsilon_r = 52.854$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.40 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.466 W/kg

**SAR(1 g) = 0.345 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6$  MHz;  $\sigma = 0.99$  S/m;  $\epsilon_r = 52.854$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.52 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.01 W/kg

**SAR(1 g) = 0.604 W/kg**



0 dB = 0.713 W/kg = -1.47 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880$  MHz;  $\sigma = 1.518$  S/m;  $\epsilon_r = 51.673$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-18-2015; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 1900, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.23 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.390 W/kg

**SAR(1 g) = 0.258 W/kg**



0 dB = 0.305 W/kg = -5.16 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 930ED**

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body Medium parameters used:

$f = 1880$  MHz;  $\sigma = 1.518$  S/m;  $\epsilon_r = 51.673$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-18-2015; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 3 Tx Slots**


**Area Scan (13x9x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.54 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.50 W/kg

**SAR(1 g) = 0.918 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.518 \text{ S/m}$ ;  $\epsilon_r = 51.673$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-18-2015; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 16.20 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.574 W/kg

**SAR(1 g) = 0.378 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 930ED**

Communication System: UID 0, UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Body medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$ ;  $\sigma = 1.49 \text{ S/m}$ ;  $\epsilon_r = 51.744$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-18-2015; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Body SAR, Bottom Edge, Low.ch**


**Area Scan (13x9x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.24 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.45 W/kg

**SAR(1 g) = 0.891 W/kg**



0 dB = 1.08 W/kg = 0.33 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9660B**

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$ ;  $\sigma = 0.99 \text{ S/m}$ ;  $\epsilon_r = 52.854$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. CDMA, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 12.68 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.291 W/kg

**SAR(1 g) = 0.159 W/kg**



0 dB = 0.193 W/kg = -7.14 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9660B**

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1  
Medium: 835 Body Medium parameters used (interpolated);  
 $f = 836.52 \text{ MHz}$ ;  $\sigma = 0.99 \text{ S/m}$ ;  $\epsilon_r = 52.854$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1272; Calibrated: 1/14/2015  
Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027  
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: Cell. EVDO Rev.0, Body SAR, Front side, Mid.ch**


**Area Scan (8x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 32.95 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.60 W/kg

**SAR(1 g) = 0.962 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9660B**

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880$  MHz;  $\sigma = 1.524$  S/m;  $\epsilon_r = 52.155$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 23.3°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: PCS. CDMA, Body SAR, Back side, Mid.ch**


**Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.28 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.517 W/kg

**SAR(1 g) = 0.343 W/kg**



0 dB = 0.398 W/kg = -4.00 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 930ED**

Communication System: UID 0, CDMA; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1851.25$  MHz;  $\sigma = 1.503$  S/m;  $\epsilon_r = 51.029$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-24-2015; Ambient Temp: 20.9°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: PCS. EVDO Rev.0, Body SAR, Bottom Edge, Low.ch**


**Area Scan (11x9x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.68 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.54 W/kg

**SAR(1 g) = 0.945 W/kg**



0 dB = 1.15 W/kg = 0.61 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$ ;  $\sigma = 1.002 \text{ S/m}$ ;  $\epsilon_r = 54.08$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 22.3°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3288; ConvF(6.38, 6.38, 6.38); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Body SAR, Back Side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.01 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.529 W/kg

**SAR(1 g) = 0.373 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$ ;  $\sigma = 0.995 \text{ S/m}$ ;  $\epsilon_r = 53.563$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-25-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(6.38, 6.38, 6.38); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.02 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.05 W/kg

**SAR(1 g) = 0.598 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5$  MHz;  $\sigma = 0.99$  S/m;  $\epsilon_r = 52.854$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


**Area Scan (8x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.01 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.344 W/kg

**SAR(1 g) = 0.262 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5$  MHz;  $\sigma = 0.99$  S/m;  $\epsilon_r = 52.854$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Front side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.26 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.16 W/kg

**SAR(1 g) = 0.659 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5$  MHz;  $\sigma = 1.46$  S/m;  $\epsilon_r = 51.241$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-24-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3288; ConvF(5.03, 5.03, 5.03); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.24 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.18 W/kg

**SAR(1 g) = 0.751 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 930ED**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5$  MHz;  $\sigma = 1.46$  S/m;  $\epsilon_r = 51.241$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-24-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3288; ConvF(5.03, 5.03, 5.03); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Bottom Edge, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (13x7x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.25 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.800 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$ ;  $\sigma = 1.499 \text{ S/m}$ ;  $\epsilon_r = 52.228$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 23.3°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, Low.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.11 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.816 W/kg

**SAR(1 g) = 0.540 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 930ED**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$ ;  $\sigma = 1.498 \text{ S/m}$ ;  $\epsilon_r = 51.724$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-18-2015; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Bottom Edge, Low.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (13x9x1):** Measurement grid:  $dx=5\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 21.34 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.34 W/kg

**SAR(1 g) = 0.831 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9587C**

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$ ;  $\sigma = 1.979 \text{ S/m}$ ;  $\epsilon_r = 51.512$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-09-2015; Ambient Temp: 21.5°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3318; ConvF(4.37, 4.37, 4.37); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, Antenna 2, 22 MHz Bandwidth,  
Body SAR, Back Side Ch 1, 1 Mbps**


**Area Scan (11x17x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.375 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.351 W/kg

**SAR(1 g) = 0.164 W/kg**



0 dB = 0.217 W/kg = -6.64 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9587C**

Communication System: UID 0, IEEE 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5745 \text{ MHz}$ ;  $\sigma = 6.061 \text{ S/m}$ ;  $\epsilon_r = 46.998$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-08-2015; Ambient Temp: 22.4°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.79, 3.79, 3.79); Calibrated: 1/22/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, U-NII-3, Antenna 2, 20 MHz Bandwidth,  
Body SAR, Back Side, Ch 149, 6 Mbps**


**Area Scan (13x22x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 1.812 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.307 W/kg

**SAR(1 g) = 0.035 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9587C**

Communication System: UID 0, IEEE 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5745 \text{ MHz}$ ;  $\sigma = 6.061 \text{ S/m}$ ;  $\epsilon_r = 46.998$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-08-2015; Ambient Temp: 22.4°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.79, 3.79, 3.79); Calibrated: 1/22/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, U-NII-3, Antenna 2, 20 MHz Bandwidth,  
Body SAR, Front Side, Ch 149, 6 Mbps**


**Area Scan (13x22x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 5.499 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.709 W/kg

**SAR(1 g) = 0.181 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, GPRS; 4 Tx slots; Frequency: 1850.2 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1850.2$  MHz;  $\sigma = 1.488$  S/m;  $\epsilon_r = 51.749$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 0.1 cm

Test Date: 06-18-2015; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 1900, Extremity SAR, Front side, Low.ch, 4 Tx Slots**


**Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (6x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 59.76 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 13.9 W/kg

**SAR(10 g) = 2.46 W/kg**



0 dB = 7.86 W/kg = 8.95 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9635F**

Communication System: UID 0, UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1852.4$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 51.744$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 0.4 cm

Test Date: 06-18-2015; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Extremity SAR, Bottom Edge, Low.ch**


**Area Scan (11x8x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 63.22 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 9.59 W/kg

**SAR(10 g) = 2.70 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9660B**

Communication System: UID 0, CDMA; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1851.25$  MHz;  $\sigma = 1.489$  S/m;  $\epsilon_r = 52.259$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 0.4 cm

Test Date: 06-22-2015; Ambient Temp: 23.3°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: PCS EVDO Rev.0, Extremity SAR, Bottom Edge, Low.ch**


**Area Scan (13x9x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 59.54 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 8.16 W/kg

**SAR(10 g) = 2.35 W/kg**



0 dB = 5.85 W/kg = 7.67 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 930ED**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5$  MHz;  $\sigma = 1.46$  S/m;  $\epsilon_r = 51.241$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-24-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3288; ConvF(5.03, 5.03, 5.03); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Extremity SAR, Bottom Edge, Mid.ch**  
**20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (13x7x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 69.88 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 12.7 W/kg

**SAR(10 g) = 3.04 W/kg**



0 dB = 8.48 W/kg = 9.28 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 96361**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$ ;  $\sigma = 1.499 \text{ S/m}$ ;  $\epsilon_r = 52.228$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.4 cm

Test Date: 06-22-2015; Ambient Temp: 23.3°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Extremity SAR, Bottom Edge, Low.ch**  
**20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (13x9x1):** Measurement grid:  $dx=5\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 65.92 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 9.79 W/kg

**SAR(10 g) = 2.83 W/kg**



0 dB = 7.11 W/kg = 8.52 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG928V; Type: Portable Handset; Serial: 9587C**

Communication System: UID 0, IEEE 802.11a; Frequency: 5720 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5720 \text{ MHz}$ ;  $\sigma = 6.03 \text{ S/m}$ ;  $\epsilon_r = 47.063$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-08-2015; Ambient Temp: 22.4°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.79, 3.79, 3.79); Calibrated: 1/22/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, U-NII-2C, Antenna 1, 20 MHz Bandwidth,  
Extremity SAR, Front Side, Ch 144, 6 Mbps**


**Area Scan (12x19x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 18.96 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 16.4 W/kg

**SAR(10 g) = 0.499 W/kg**



0 dB = 6.90 W/kg = 8.39 dBW/kg

## APPENDIX B: SYSTEM VERIFICATION

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.895 \text{ S/m}$ ;  $\epsilon_r = 42.025$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 22.3°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3288; ConvF(6.81, 6.81, 6.81); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification

**Area Scan (7x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 23.0 dBm (200 mW)

Peak SAR (extrapolated) = 2.60 W/kg

**SAR(1 g) = 1.75 W/kg**

Deviation(1 g) = 8.16%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.88 \text{ S/m}$ ;  $\epsilon_r = 39.963$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-26-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3288; ConvF(6.51, 6.51, 6.51); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 23.0 dBm (200 mW)

Peak SAR (extrapolated) = 2.96 W/kg

**SAR(1 g) = 1.96 W/kg**

Deviation(1 g) = 5.95%



0 dB = 2.30 W/kg = 3.62 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.387 \text{ S/m}$ ;  $\epsilon_r = 40.026$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-29-2015; Ambient Temp: 21.1°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3263; ConvF(5.27, 5.27, 5.27); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.75 W/kg

**SAR(1 g) = 3.71 W/kg**

Deviation(1 g) = 2.49%



0 dB = 4.66 W/kg = 6.68 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900$  MHz;  $\sigma = 1.418$  S/m;  $\epsilon_r = 39.591$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-14-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3318; ConvF(5.05, 5.05, 5.05); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.98 W/kg

**SAR(1 g) = 4.31 W/kg**

Deviation(1 g) = 8.02%



0 dB = 5.53 W/kg = 7.43 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2400 Head Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 1.877 \text{ S/m}$ ;  $\epsilon_r = 39.244$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-25-2015; Ambient Temp: 20.5°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(4.5, 4.5, 4.5); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification

**Area Scan (8x9x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 10.9 W/kg

**SAR(1 g) = 5.30 W/kg**

Deviation(1 g) = 1.73%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head, Medium parameters used:

$f = 5300 \text{ MHz}$ ;  $\sigma = 4.619 \text{ S/m}$ ;  $\epsilon_r = 35.613$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 06-25-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7357; ConvF(4.93, 4.93, 4.93); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/13/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5300 MHz System Verification

**Area Scan (7x8x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power = 17.0 dBm (50 mW)

Peak SAR (extrapolated) = 16.6 W/kg

**SAR(1 g) = 3.99 W/kg**

Deviation(1 g) = -5.79%



0 dB = 9.87 W/kg = 9.94 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head, Medium parameters used:

$f = 5500 \text{ MHz}$ ;  $\sigma = 4.835 \text{ S/m}$ ;  $\epsilon_r = 35.32$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-25-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7357; ConvF(4.7, 4.7, 4.7); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/13/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5500 MHz System Verification

**Area Scan (7x7x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power = 17.0 dBm (50 mW)

Peak SAR (extrapolated) = 17.4 W/kg

**SAR(1 g) = 4.03 W/kg**

Deviation(1 g) = -4.39%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head, Medium parameters used:

$f = 5800 \text{ MHz}$ ;  $\sigma = 5.134 \text{ S/m}$ ;  $\epsilon_r = 34.874$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-25-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7357; ConvF(4.41, 4.41, 4.41); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/13/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5800 MHz System Verification

**Area Scan (7x7x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power = 17.0 dBm (50 mW)

Peak SAR (extrapolated) = 18.2 W/kg

**SAR(1 g) = 4.07 W/kg**

Deviation(1 g) = 0.37%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body, Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.969 \text{ S/m}$ ;  $\epsilon_r = 54.461$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 22.3°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3288; ConvF(6.38, 6.38, 6.38); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification

**Area Scan (7x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 23.0 dBm (200 mW)

Peak SAR (extrapolated) = 2.64 W/kg

**SAR(1 g) = 1.81 W/kg**

Deviation(1 g) = 6.97%



0 dB = 2.11 W/kg = 3.24 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body, Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.988 \text{ S/m}$ ;  $\epsilon_r = 52.868$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2015; Ambient Temp: 22.7°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 23.0 dBm (200 mW)

Peak SAR (extrapolated) = 2.92 W/kg

**SAR(1 g) = 1.97 W/kg**

Deviation(1 g) = 5.35%



0 dB = 2.30 W/kg = 3.62 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body, Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.993 \text{ S/m}$ ;  $\epsilon_r = 53.688$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-29-2015; Ambient Temp: 23.3°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 23.0 dBm (200 mW)

Peak SAR (extrapolated) = 2.78 W/kg

**SAR(1 g) = 1.88 W/kg**

Deviation(1 g) = 2.84%



0 dB = 2.20 W/kg = 3.42 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body, Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.483 \text{ S/m}$ ;  $\epsilon_r = 51.234$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-24-2015; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3288; ConvF(5.03, 5.03, 5.03); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.08 W/kg

**SAR(1 g) = 3.99 W/kg; SAR(10 g) = 2.11 W/kg**

Deviation(1 g) = 7.55%; Deviation (10 g) = 5.50%



0 dB = 4.99 W/kg = 6.98 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body, Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.541 \text{ S/m}$ ;  $\epsilon_r = 51.562$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-18-2015; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(4.66, 4.66, 4.66); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/23/2014

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.54 W/kg

**SAR(1 g) = 4.30 W/kg; SAR(10 g) = 2.25 W/kg**

Deviation(1 g) = 7.50%; Deviation (10 g) = 6.13%



0 dB = 5.42 W/kg = 7.34 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body, Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 2.032 \text{ S/m}$ ;  $\epsilon_r = 51.385$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-09-2015; Ambient Temp: 21.5°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3318; ConvF(4.37, 4.37, 4.37); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification

**Area Scan (8x9x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 11.2 W/kg

**SAR(1 g) = 5.37 W/kg**

Deviation(1 g) = 3.67%



0 dB = 7.09 W/kg = 8.51 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body, Medium parameters used:

$f = 5300 \text{ MHz}$ ;  $\sigma = 5.456 \text{ S/m}$ ;  $\epsilon_r = 47.753$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-08-2015; Ambient Temp: 22.6°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.79, 3.79, 3.79); Calibrated: 1/22/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5300 MHz System Verification

**Area Scan (7x8x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power = 17.0 dBm (50 mW)

Peak SAR (extrapolated) = 16.3 W/kg

**SAR(1 g) = 3.89 W/kg; SAR(10 g) = 1.09 W/kg**

Deviation(1 g) = 4.85%; Deviation(10 g) = 4.31%



0 dB = 9.37 W/kg = 9.72 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body, Medium parameters used:

$f = 5500 \text{ MHz}$ ;  $\sigma = 5.718 \text{ S/m}$ ;  $\epsilon_r = 47.478$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-08-2015; Ambient Temp: 22.6°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.65, 3.65, 3.65); Calibrated: 1/22/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5500 MHz System Verification

**Area Scan (7x7x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power = 17.0 dBm (50 mW)

Peak SAR (extrapolated) = 16.5 W/kg

**SAR(1 g) = 3.76 W/kg; SAR(10 g) = 1.05 W/kg**

Deviation(1 g) = -5.05%; Deviation(10 g) = -4.55%



0 dB = 9.00 W/kg = 9.54 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body, Medium parameters used:

$f = 5800 \text{ MHz}$ ;  $\sigma = 6.145 \text{ S/m}$ ;  $\epsilon_r = 46.937$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-08-2015; Ambient Temp: 22.4°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.79, 3.79, 3.79); Calibrated: 1/22/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5800 MHz System Verification

**Area Scan (7x7x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Input Power = 17.0 dBm (50 mW)

Peak SAR (extrapolated) = 16.1 W/kg

**SAR(1 g) = 3.45 W/kg; SAR(10 g) = 0.966 W/kg**

Deviation(1 g) = -8.12%; Deviation(10 g) = -6.21%



0 dB = 8.51 W/kg = 9.30 dBW/kg