



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

12/20/15 - 01/20/16

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

0Y1512212182.A3L

FCC ID:

A3LSMG935F

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SM-G935F

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.27	0.46	0.74
PCE	UMTS 850	826.40 - 846.60 MHz	0.25	0.34	0.70
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.12	0.66	0.96
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	< 0.1	0.45	0.50
PCE	UMTS 1900	1852.4 - 1907.6 MHz	< 0.1	0.47	0.68
PCE	LTE Band 12	699.7 - 715.3 MHz	< 0.1	0.15	0.26
PCE	LTE Band 17	706.5 - 713.5 MHz			
PCE	LTE Band 13	779.5 - 784.5 MHz	< 0.1	0.19	0.29
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.23	0.32	0.65
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.15	0.23	0.42
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	< 0.1	0.51	0.59
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz			
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	< 0.1	0.40	0.96
PCE	LTE Band 41	2498.5 - 2687.5 MHz	< 0.1	0.26	0.51
DTS	2.4 GHz WLAN	2412 - 2472 MHz	0.38	0.15	0.38
NII	U-NII-1	5180 - 5240 MHz			
NII	U-NII-2A	5260 - 5320 MHz	0.21	0.32	
NII	U-NII-2C	5500 - 5720 MHz	0.29	0.34	
NII	U-NII-3	5745 - 5825 MHz	0.56	0.16	0.23
DSS/DTS	Bluetooth	2402 - 2480 MHz		N/A	
Simultaneous SAR per KDB 690783 D01v01r03:			1.17	1.14	1.59

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 1 of 77

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	11
3	INTRODUCTION	12
4	DOSIMETRIC ASSESSMENT	13
5	DEFINITION OF REFERENCE POINTS	14
6	TEST CONFIGURATION POSITIONS	15
7	RF EXPOSURE LIMITS	18
8	FCC MEASUREMENT PROCEDURES.....	19
9	RF CONDUCTED POWERS	25
10	SYSTEM VERIFICATION.....	46
11	SAR DATA SUMMARY	49
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	63
13	SAR MEASUREMENT VARIABILITY	71
14	ADDITIONAL TESTING PER FCC GUIDANCE	72
15	EQUIPMENT LIST	73
16	MEASUREMENT UNCERTAINTIES.....	74
17	CONCLUSION.....	75
18	REFERENCES	76
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMG935F	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset
		Page 2 of 77

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2472 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz
MST	Data	1 - 8.3 kHz

1.2 Power Reduction for SAR

This device utilizes a single step power reduction mechanism for SAR compliance under portable hotspot conditions for some wireless modes and bands. All hotspot SAR evaluations for this device were performed at the maximum allowed output power when hotspot is enabled.

Additionally, this device utilizes independent power reduction mechanisms for SAR compliance for the WLAN transmitter for held-to-ear exposure conditions as outlined in Section 1.3. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528.

The reduced powers for the power reduction mechanisms were confirmed via conducted power measurements at the RF port (See Section 9). Detailed descriptions of the mechanisms are included in the operational description.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 3 of 77

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum PCE Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)					Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	
GSM/GPRS/EDGE 850	Maximum	34.0	34.0	31.0	30.0	28.5	27.0	25.0	23.5	22.5	
	Nominal	33.5	33.5	30.5	29.5	28.0	26.5	24.5	23.0	22.0	
GSM/GPRS/EDGE 1900	Maximum	31.0	31.0	28.5	27.0	25.5	26.0	24.0	23.0	21.5	
	Nominal	30.5	30.5	28.0	26.5	25.0	25.5	23.5	22.5	21.0	

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	24.5	24.5	24.5	24.5
	Nominal	24.0	24.0	24.0	24.0
UMTS Band 4 (1750 MHz)	Maximum	23.5	23.5	23.5	23.5
	Nominal	23.0	23.0	23.0	23.0
UMTS Band 2 (1900 MHz)	Maximum	23.5	23.5	23.5	23.5
	Nominal	23.0	23.0	23.0	23.0

Mode / Band		Modulated Average (dBm)
LTE Band 17	Maximum	23.0
	Nominal	22.5
LTE Band 12	Maximum	23.0
	Nominal	22.5
LTE Band 13	Maximum	23.0
	Nominal	22.5
LTE Band 5 (Cell)	Maximum	24.5
	Nominal	24.0
LTE Band 26 (Cell)	Maximum	23.0
	Nominal	22.5
LTE Band 4 (AWS)	Maximum	23.0
	Nominal	22.5
LTE Band 2 (PCS)	Maximum	23.0
	Nominal	22.5
LTE Band 25 (PCS)	Maximum	23.0
	Nominal	22.5
LTE Band 41	Maximum	23.5
	Nominal	23.0

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 4 of 77

1.3.2 Maximum WLAN/BT Power

Mode / Band		Modulated Average - Single Tx Chain (dBm)		
		Ch. 1-11	Ch. 12	Ch. 13
IEEE 802.11b (2.4 GHz)	Maximum	19.5		
	Nominal	19.0		
IEEE 802.11g (2.4 GHz)	Maximum	17.5	15.5	9.5
	Nominal	17.0	15.0	9.0
IEEE 802.11n (2.4 GHz)	Maximum	17.5	15.5	9.5
	Nominal	17.0	15.0	9.0
Mode / Band		Modulated Average (dBm)		
Bluetooth	Maximum	10.5		
	Nominal	10.0		
Bluetooth LE	Maximum	6.0		
	Nominal	5.5		

Mode / Band		Modulated Average - Single Tx Chain (dBm)						
		20 MHz Bandwidth		40 MHz Bandwidth			80 MHz Bandwidth	
		Ch. 40-48, 52-60, 104-144, 149-165	Ch. 36, 64, 100					
IEEE 802.11a (5 GHz)	Maximum	16.5	15.5					
	Nominal	16.0	15.0					
		Ch. 40-48, 52-60, 104-144, 149-165	Ch. 36, 64, 100	Ch. 46, 54, 110-159	Ch. 38	Ch. 62, 102		
IEEE 802.11n (5 GHz)	Maximum	16.5	15.5	15.5	13.5	14.5		
	Nominal	16.0	15.0	15.0	13.0	14.0		
		Ch. 40-48, 52-60, 104-144, 149-165	Ch. 36, 64, 100	Ch. 46, 54, 110-159	Ch. 38	Ch. 62, 102	Ch. 58, 122 - 155	Ch. 42, 106
IEEE 802.11ac (5 GHz)	Maximum	16.5	15.5	15.5	13.5	14.5	13.5	12.5
	Nominal	16.0	15.0	15.0	13.0	14.0	13.0	12.0

Mode / Band		Modulated Average - MIMO (dBm)		
		Ch. 1-11	Ch. 12	Ch. 13
IEEE 802.11g (CDD) (2.4 GHz)	Maximum	17.5	15.5	9.5
	Nominal	17.0	15.0	9.0
IEEE 802.11n (CDD+SDM) (2.4 GHz)	Maximum	17.5	15.5	9.5
	Nominal	17.0	15.0	9.0

Mode / Band		Modulated Average - MIMO (dBm)						
		20 MHz Bandwidth		40 MHz Bandwidth			80 MHz Bandwidth	
		Ch. 40-48, 52-60, 104-144, 149-165	Ch. 36, 64, 100					
IEEE 802.11a (CDD) (5 GHz)	Maximum	16.5	15.5					
	Nominal	16.0	15.0					
		Ch. 40-48, 52-60, 104-144, 149-165	Ch. 36, 64, 100	Ch. 46, 54, 110-159	Ch. 38	Ch. 62, 102		
IEEE 802.11n (CDD + SDM) (5 GHz)	Maximum	16.5	15.5	15.5	13.5	14.5		
	Nominal	16.0	15.0	15.0	13.0	14.0		
		Ch. 40-48, 52-60, 104-144, 149-165	Ch. 36, 64, 100	Ch. 46, 54, 110-159	Ch. 38	Ch. 62, 102	Ch. 58, 122 - 155	Ch. 42, 106
IEEE 802.11ac (CDD+SDM) (5 GHz)	Maximum	16.5	15.5	15.5	13.5	14.5	13.5	12.5
	Nominal	16.0	15.0	15.0	13.0	14.0	13.0	12.0

1.3.3 Reduced PCE Power – Hotspot Mode Activated

Mode / Band		Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GPRS/EDGE 1900	Maximum	29.0	26.5	25.0	23.5	24.0	22.0	21.0	19.5
	Nominal	28.5	26.0	24.5	23.0	23.5	21.5	20.5	19.0

FCC ID: A3LSMG935F	 PCTEST ENGINEERING LABORATORY, INC.		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182 A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset			Page 5 of 77

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 4 (1750 MHz)	Maximum	22.0	22.0	22.0	22.0
	Nominal	21.5	21.5	21.5	21.5
UMTS Band 2 (1900 MHz)	Maximum	22.0	22.0	22.0	22.0
	Nominal	21.5	21.5	21.5	21.5

Mode / Band		Modulated Average (dBm)
LTE Band 2 (PCS)	Maximum	21.0
	Nominal	20.5
LTE Band 4 (AWS)	Maximum	20.0
	Nominal	19.5

1.3.4 Reduced WLAN Power – Proximity Sensor Active (Held to Ear)

Mode / Band		Modulated Average - Single Tx Chain (dBm)	
		Ch. 1-12	Ch. 13
IEEE 802.11b (2.4 GHz)	Maximum	13.5	
	Nominal	13.0	
IEEE 802.11g (2.4 GHz)	Maximum	13.5	9.5
	Nominal	13.0	9.0
IEEE 802.11n (2.4 GHz)	Maximum	13.5	9.5
	Nominal	13.0	9.0

Mode / Band		Modulated Average - Single Tx Chain (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	10.5		
	Nominal	10.0		
IEEE 802.11n (5 GHz)	Maximum	10.5	10.5	
	Nominal	10.0	10.0	
IEEE 802.11ac (5 GHz)	Maximum	10.5	10.5	10.5
	Nominal	10.0	10.0	10.0

Mode / Band		Modulated Average - MIMO (dBm)		
		Ch. 1-11	Ch. 12	Ch. 13
IEEE 802.11g (CDD) (2.4 GHz)	Maximum	16.5	15.5	9.5
	Nominal	16.0	15.0	9.0
IEEE 802.11n (CDD+SDM) (2.4 GHz)	Maximum	16.5	15.5	9.5
	Nominal	16.0	15.0	9.0

Mode / Band		Modulated Average - MIMO (dBm)			
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth	
IEEE 802.11a (CDD) (5 GHz)	Maximum	13.5			
	Nominal	13.0			
IEEE 802.11n (CDD + SDM) (5 GHz)	Maximum	13.5	13.5		
	Nominal	13.0	13.0		
				Ch. 58, 122 - 155	Ch. 42, 106
IEEE 802.11ac (CDD+SDM) (5 GHz)	Maximum	13.5	13.5	13.5	12.5
	Nominal	13.0	13.0	13.0	12.0

FCC ID: A3LSMG935F		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset			Page 6 of 77

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is ≤160 mm and the diagonal display is ≤150 mm. A diagram showing the location of the device antennas can be found in Appendix F.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 41	Yes	Yes	No	Yes	No	Yes
2.4 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
2.4 GHz WLAN Ant 2	Yes	Yes	Yes	No	Yes	Yes
5 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled. Therefore, U-NII-1, U-NII-2A, U-NII-2C operations are not considered in this section.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 7 of 77

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	
2	GSM voice + 5 GHz Wi-Fi	Yes	Yes	N/A	
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
4	GSM voice + 2.4 GHz Wi-Fi MIMO	Yes	Yes	N/A	
5	GSM voice + 5 GHz Wi-Fi MIMO	Yes	Yes	N/A	
6	GSM voice + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	Yes	Yes	N/A	
7	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
8	UMTS + 5 GHz Wi-Fi	Yes	Yes	Yes	
9	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	
10	UMTS + 2.4 GHz Wi-Fi MIMO	Yes	Yes	Yes	
11	UMTS + 5 GHz Wi-Fi MIMO	Yes	Yes	Yes	
12	UMTS + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	Yes	Yes	Yes	
13	LTE + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
14	LTE + 5 GHz Wi-Fi	Yes	Yes	Yes	
15	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A	
16	LTE + 2.4 GHz Wi-Fi MIMO	Yes	Yes	Yes	
17	LTE + 5 GHz Wi-Fi MIMO	Yes	Yes	Yes	
18	LTE + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	Yes	Yes	Yes	
19	GPRS/EDGE + 2.4 GHz Wi-Fi	N/A	N/A	Yes	
20	GPRS/EDGE + 5 GHz Wi-Fi	N/A	N/A	Yes	
21	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	N/A	N/A	
22	GPRS/EDGE + 2.4 GHz Wi-Fi MIMO	N/A	N/A	Yes	
23	GPRS/EDGE + 5 GHz Wi-Fi MIMO	N/A	N/A	Yes	
24	GPRS/EDGE + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	N/A	N/A	Yes	

1. All unlicensed modes cannot transmit from the same antenna simultaneously.
2. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
3. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
4. 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
5. This device supports 2x2 MIMO Tx for WLAN 802.11 a/g/n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.
6. This device supports VoLTE.
7. This device supports VoWIFI.
8. 2.4 GHz WLAN, 5 GHz WLAN and 2.4 GHz Bluetooth that share the same antenna path cannot transmit simultaneously.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 8 of 77

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg for 1g SAR, SAR is not required for U-NII-1 band according to FCC KDB 248227 D01v02r01.

This device supports channel 1-13 for 2.4 GHz WLAN. However, due to the reduced output power for channels 12 and 13, channels 1, 6, and 11 were considered for SAR testing per KDB 248227 D01v02r02.

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(11/15) * \sqrt{2.480}] = 1.2 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports both LTE B25 (PCS) and LTE B2 (PCS). Since the supported frequency span for LTE B2 (PCS) falls completely within the supported frequency span for LTE B25 (PCS), both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B25 (PCS).

This device supports both LTE B12 and LTE B17. Since the supported frequency span for LTE B17 falls completely within the supported frequency span for LTE B12, both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B12.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 9 of 77

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
GSM/GPRS/EDGE 850	80B93	80B93	80B93
UMTS 850	80B93	80B93	80B93
UMTS 1750	81029	81029	813EF
GSM/GPRS/EDGE 1900	80B93	80B93	813EF
UMTS 1900	81029	80B93	813EF
LTE Band 12	80B93	80B93	80B93
LTE Band 13	80B93	80B93	80B93
LTE Band 5 (Cell)	80B93	80B93	80B93
LTE Band 26 (Cell)	80B93	80B93	80B93
LTE Band 4 (AWS)	81029	81029	813EF
LTE Band 25 (PCS)	81029	80B93	80B93
LTE Band 41	8102F	0C6B5	81029
2.4 GHz WLAN	00580	0C6B5	0C6B5
5 GHz WLAN	0C6B5	00580	00580

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 10 of 77

2

LTE INFORMATION

LTE Information					
FCC ID	A3LSMG935F				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 17 (706.5 - 713.5 MHz)				
	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
Channel Bandwidths	LTE Band 17: 5 MHz, 10 MHz				
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 17: 5 MHz	706.5 (23755)		710 (23790)		713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)		710 (23790)		711 (23800)
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)
LTE Band 13: 5 MHz	779.5 (23205)		782 (23230)		784.5 (23255)
LTE Band 13: 10 MHz	N/A		782 (23230)		N/A
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)		831.5 (26865)		848.3 (27033)
LTE Band 26 (Cell): 3 MHz	815.5 (26705)		831.5 (26865)		847.5 (27025)
LTE Band 26 (Cell): 5 MHz	816.5 (26715)		831.5 (26865)		846.5 (27015)
LTE Band 26 (Cell): 10 MHz	819 (26740)		831.5 (26865)		844 (26990)
LTE Band 26 (Cell): 15 MHz	831.5 (26865)		836.5 (26915)		841.5 (26965)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)		1914.3 (26683)
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)		1913.5 (26675)
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)		1912.5 (26665)
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)		1910 (26640)
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)		1907.5 (26615)
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)		1905 (26590)
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	9				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	N/A				
LTE Release 10 Additional Information	This device does not support full CA features on 3GPP Release 10. The following LTE Release 10 Features are not supported: Carrier Aggregation, Relay, HetNet, Enhanced MIMO, eICl, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: A3LSMG935F		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 11 of 77		

3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMG935F	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset
		Page 12 of 77

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area
Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoomTV}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22


*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMG935F		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset			Page 13 of 77

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The “M” is the reference point for the center of the mouth, “LE” is the left ear reference (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The passing through the two ear canals and M is defined as the Reference Plane. The N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].



point
point
the
plane
line
the
N-F

Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 14 of 77

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 15 of 77




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 16 of 77

6.5 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.6 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 17 of 77	

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 18 of 77

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 19 of 77

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.4.6 SAR Measurement Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 20 of 77

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

FCC ID: A3LSMG935F	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset
		Page 21 of 77

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 22 of 77

8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz and 5 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.6.7 Initial Test Configuration Procedure

For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6).

8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 23 of 77

8.6.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is <1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 24 of 77	

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

Table 9-1
Maximum Conducted Powers

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	33.39	33.31	30.57	29.63	28.09	26.90	24.79	23.44	22.17
	190	33.29	33.36	30.74	29.68	28.21	26.74	24.63	23.48	22.06
	251	33.28	33.25	30.56	29.62	28.06	26.76	24.58	23.46	22.02
GSM 1900	512	30.52	30.59	28.05	26.62	25.10	25.93	23.81	22.77	21.48
	661	30.46	30.53	27.98	26.48	24.94	25.80	23.64	22.59	21.29
	810	30.32	30.38	28.09	26.31	24.77	25.58	23.58	22.29	21.03
		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	24.36	24.28	24.55	25.37	25.08	17.87	18.77	19.18	19.16
	190	24.26	24.33	24.72	25.42	25.20	17.71	18.61	19.22	19.05
	251	24.25	24.22	24.54	25.36	25.05	17.73	18.56	19.20	19.01
GSM 1900	512	21.49	21.56	22.03	22.36	22.09	16.90	17.79	18.51	18.47
	661	21.43	21.50	21.96	22.22	21.93	16.77	17.62	18.33	18.28
	810	21.29	21.35	22.07	22.05	21.76	16.55	17.56	18.03	18.02
GSM 850	Frame Avg. Targets:	24.47	24.47	24.48	25.24	24.99	17.47	18.48	18.74	18.99
GSM 1900		21.47	21.47	21.98	22.24	21.99	16.47	17.48	18.24	17.99

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 25 of 77

Table 9-2
Reduced Conducted Powers – Hotspot Mode Active

		Maximum Burst-Averaged Output Power							
		GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	28.81	26.44	24.89	23.42	23.66	22.00	20.76	19.50
	661	28.50	26.07	24.47	22.92	23.50	21.45	20.17	18.96
	810	28.38	25.92	24.23	22.69	23.28	21.25	20.00	18.81
		Calculated Maximum Frame-Averaged Output Power							
		GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	19.78	20.42	20.63	20.41	14.63	15.98	16.50	16.49
	661	19.47	20.05	20.21	19.91	14.47	15.43	15.91	15.95
	810	19.35	19.90	19.97	19.68	14.25	15.23	15.74	15.80
GSM 1900	Frame Avg.Targets:	19.47	19.98	20.24	19.99	14.47	15.48	16.24	15.99

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33 (Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A



Figure 9-1
Power Measurement Setup

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 26 of 77	

9.2 UMTS Conducted Powers

Table 9-3
Maximum Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	23.58	23.54	23.38	22.23	22.45	22.41	22.89	22.62	22.74	-
99		12.2 kbps AMR	23.61	23.58	23.38	22.23	22.46	22.41	22.80	22.66	22.70	-
6	HSDPA	Subtest 1	23.08	22.97	22.89	22.88	22.67	22.60	23.34	22.96	23.33	0
6		Subtest 2	23.05	22.99	22.88	22.90	22.68	22.61	23.36	22.94	23.32	0
6		Subtest 3	22.11	22.05	22.00	22.47	22.30	22.20	22.44	22.08	22.41	0.5
6		Subtest 4	22.06	22.04	22.00	22.49	22.26	22.19	22.46	22.06	22.44	0.5
6	HSUPA	Subtest 1	22.78	22.70	22.64	22.12	21.92	21.83	22.38	21.98	22.34	0
6		Subtest 2	21.20	21.10	21.02	19.68	19.50	19.52	19.89	19.58	19.98	2
6		Subtest 3	22.15	22.06	21.95	22.07	21.84	21.75	21.96	21.66	21.88	1
6		Subtest 4	21.19	21.13	21.02	19.67	19.50	19.50	19.87	19.62	19.96	2
6		Subtest 5	22.75	22.68	22.68	22.10	21.94	21.82	22.40	21.99	22.32	0
8	DC-HSDPA	Subtest 1	23.10	22.96	22.93	23.02	22.67	22.46	23.30	22.99	23.08	0
8		Subtest 2	23.07	22.94	23.06	23.03	22.68	22.49	23.23	22.97	23.01	0
8		Subtest 3	22.25	22.26	22.11	22.70	22.32	22.12	22.52	22.24	22.38	0.5
8		Subtest 4	22.05	22.02	22.00	22.59	22.20	22.08	22.33	22.06	22.25	0.5

Table 9-4
Reduced Conducted Powers – Hotspot Mode Active

3GPP Release Version	Mode	3GPP 34.121 Subtest	AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	21.80	21.76	21.59	22.00	21.50	21.79	-
99		12.2 kbps AMR	21.64	21.59	21.60	21.99	21.48	21.77	-
6	HSDPA	Subtest 1	21.49	21.46	21.33	21.76	21.48	21.75	0
6		Subtest 2	21.48	21.48	21.40	21.80	21.59	21.83	0
6		Subtest 3	21.40	21.46	21.45	20.82	20.48	20.77	0.5
6		Subtest 4	21.50	21.44	21.28	21.09	20.51	20.96	0.5
6	HSUPA	Subtest 1	20.86	20.65	20.80	20.85	20.53	20.79	0
6		Subtest 2	19.65	19.45	19.13	18.30	18.06	18.53	2
6		Subtest 3	20.71	20.66	20.76	20.42	20.26	20.43	1
6		Subtest 4	19.64	19.35	19.10	18.26	18.25	18.42	2
6		Subtest 5	21.50	21.48	21.49	20.87	20.62	20.85	0
8	DC-HSDPA	Subtest 1	21.91	21.83	21.56	21.76	21.57	21.64	0
8		Subtest 2	21.87	21.81	21.61	21.73	21.52	21.41	0
8		Subtest 3	21.87	21.91	21.57	21.14	20.80	20.88	0.5
8		Subtest 4	21.55	21.99	21.63	20.90	20.50	20.72	0.5

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 9-2
Power Measurement Setup

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 27 of 77

9.3 LTE Conducted Powers

9.3.1 LTE Band 12

Table 9-5
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.41	0	0
	1	25	22.40		0
	1	49	22.39		0
	25	0	21.40	0-1	1
	25	12	21.41		1
	25	25	21.38		1
16QAM	50	0	21.40	0-1	1
	1	0	21.22		1
	1	25	21.07		1
	1	49	21.22	0-2	1
	25	0	20.39		2
	25	12	20.40		2
	25	25	20.35		2
	50	0	20.44		2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-6
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth						
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)	
			Conducted Power [dBm]	Conducted Power [dBm]	Conducted Power [dBm]	
QPSK	1	0	22.65	22.59	22.53	0
	1	12	22.58	22.51	22.46	
	1	24	22.56	22.54	22.52	
	12	0	21.44	21.34	21.30	0-1
	12	6	21.43	21.32	21.29	
	12	13	21.42	21.32	21.30	
	25	0	21.42	21.32	21.29	
	25	0	21.42	21.32	21.29	
16QAM	1	0	21.47	21.38	21.54	0-1
	1	12	21.50	21.75	21.38	
	1	24	21.47	21.61	21.71	
	12	0	20.43	20.38	20.39	0-2
	12	6	20.45	20.30	20.32	
	12	13	20.45	20.40	20.32	
	25	0	20.43	20.33	20.30	
	25	0	20.43	20.33	20.30	

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 28 of 77

Table 9-7
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.53	22.42	22.44	0	0
	1	7	22.53	22.43	22.38		0
	1	14	22.48	22.42	22.42		0
	8	0	21.48	21.37	21.33	0-1	1
	8	4	21.45	21.38	21.33		1
	8	7	21.45	21.36	21.32		1
	15	0	21.41	21.33	21.27		1
16QAM	1	0	21.63	21.60	21.47	0-1	1
	1	7	21.51	21.53	21.52		1
	1	14	21.54	21.46	21.56		1
	8	0	20.57	20.44	20.39	0-2	2
	8	4	20.53	20.42	20.42		2
	8	7	20.43	20.39	20.37		2
	15	0	20.46	20.38	20.37		2

Table 9-8
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.38	22.32	22.21	0	0
	1	2	22.42	22.32	22.24		0
	1	5	22.39	22.26	22.26		0
	3	0	22.38	22.33	22.20		0
	3	2	22.39	22.48	22.23		0
	3	3	22.34	22.31	22.25		0
	6	0	21.39	21.29	21.26	0-1	1
16QAM	1	0	21.46	21.16	21.22	0-1	1
	1	2	21.36	21.24	21.03		1
	1	5	21.36	21.11	21.24		1
	3	0	21.37	21.43	21.31		1
	3	2	21.40	21.43	21.30		1
	3	3	21.43	21.30	21.32		1
	6	0	20.50	20.38	20.40	0-2	2

9.3.2 LTE Band 13

Table 9-9
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.30	0	0
	1	25	22.46		0
	1	49	22.32		0
	25	0	21.31	0-1	1
	25	12	21.31		1
	25	25	21.34		1
16QAM	50	0	21.30	0-1	1
	1	0	20.66		1
	1	25	20.63		1
	1	49	20.80	0-2	1
	25	0	20.31		2
	25	12	20.37		2
	25	25	20.38	0-2	2
	50	0	20.40		2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 29 of 77

Table 9-10
LTE Band 13 Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.24	0	0
	1	12	22.38		0
	1	24	22.28		0
	12	0	21.12	0-1	1
	12	6	21.16		1
	12	13	21.18		1
	25	0	21.11		1
16QAM	1	0	21.18	0-1	1
	1	12	21.29		1
	1	24	21.24		1
	12	0	20.10	0-2	2
	12	6	20.17		2
	12	13	20.24		2
	25	0	20.16		2

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

9.3.3 LTE Band 5 (Cell)

Table 9-11
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.91	0	0
	1	25	23.88		0
	1	49	23.80		0
	25	0	22.47	0-1	1
	25	12	22.41		1
	25	25	22.40		1
	50	0	22.38		1
16QAM	1	0	22.14	0-1	1
	1	25	22.36		1
	1	49	22.52		1
	25	0	21.97	0-2	2
	25	12	21.95		2
	25	25	21.93		2
	50	0	21.95		2

Note: LTE Band 5 at 10 MHz bandwidth is only supported for FCC Rule Part 22H. There are not three non overlapping channels within FCC Rule Part 22H. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 30 of 77

Table 9-12
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.72	23.82	23.91	0	0
	1	12	23.71	23.77	23.83		0
	1	24	23.70	23.75	23.72		0
	12	0	21.97	22.03	22.09	0-1	1
	12	6	21.96	22.04	22.08		1
	12	13	21.93	22.02	22.02		1
16QAM	25	0	21.96	22.02	22.06	0-1	1
	1	0	22.80	22.68	22.62		1
	1	12	22.69	22.69	22.58		1
	1	24	22.68	22.69	22.81	0-2	1
	12	0	21.48	21.60	21.62		2
	12	6	21.46	21.57	21.56		2
	12	13	21.45	21.57	21.52		2
	25	0	21.43	21.51	21.48		2

Table 9-13
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.61	23.72	23.76	0	0
	1	7	23.60	23.63	23.62		0
	1	14	23.61	23.59	23.65		0
	8	0	21.97	22.03	22.08	0-1	1
	8	4	21.98	22.05	22.04		1
	8	7	21.95	22.01	22.06		1
16QAM	15	0	21.92	22.01	22.02	0-1	1
	1	0	22.86	22.85	22.85		1
	1	7	22.88	22.79	22.90		1
	1	14	22.45	22.93	22.84	0-2	1
	8	0	21.46	21.56	21.69		2
	8	4	21.56	21.58	21.63		2
	8	7	21.49	21.58	21.55		2
	15	0	21.40	21.48	21.53		2

Table 9-14
LTE Band 5 (Cell) Conducted Powers – 1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.42	23.53	23.72	0	0
	1	2	23.47	23.56	23.75		0
	1	5	23.49	23.50	23.64		0
	3	0	23.55	23.59	23.85		0
	3	2	23.54	23.57	23.79		0
	3	3	23.56	23.70	23.72		0
	6	0	21.92	22.02	22.17		0-1
16QAM	1	0	22.33	22.30	22.68	0-1	1
	1	2	22.24	22.42	22.61		1
	1	5	22.34	22.43	22.47		1
	3	0	22.65	22.63	22.96		1
	3	2	22.65	22.60	22.84		1
	3	3	22.60	22.53	22.76		1
	6	0	21.53	21.56	21.72		0-2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 31 of 77

9.3.4

LTE Band 26 (Cell)

Table 9-15
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26915 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.51	0	0
	1	36	22.43		0
	1	74	22.36		0
	36	0	21.51	0-1	1
	36	18	21.50		1
	36	37	21.46		1
	75	0	21.48		1
16QAM	1	0	21.11		1
	1	36	21.13		1
	1	74	21.02		1
	36	0	20.40	0-2	2
	36	18	20.46		2
	36	37	20.43		2
	75	0	20.39		2

Note: LTE Band 26 at 15 MHz bandwidth is only supported for FCC Rule Part 22H. There are not three non overlapping channels within FCC Rule Part 22H. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-16
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth						
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)	
QPSK	1	0	22.23	22.09	22.17	0
	1	25	22.24	22.19	22.15	
	1	49	22.26	22.06	22.09	
	25	0	21.00	20.99	21.05	0-1
	25	12	20.97	21.01	21.05	
	25	25	20.99	20.99	21.01	
	50	0	20.99	20.96	21.02	
16QAM	1	0	21.33	21.06	21.11	
	1	25	21.10	21.09	21.06	
	1	49	21.21	21.00	21.05	
	25	0	20.19	20.17	20.28	0-2
	25	12	20.20	20.20	20.27	
	25	25	20.18	20.18	20.23	
	50	0	20.20	20.15	20.22	

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 32 of 77

Table 9-17
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.43	22.38	22.44	0	0
	1	12	22.32	22.26	22.48		0
	1	24	22.35	22.36	22.32		0
	12	0	21.07	21.06	21.22	0-1	1
	12	6	21.09	21.04	21.16		1
	12	13	21.01	21.03	21.12		1
	25	0	21.01	21.00	21.14		1
16QAM	1	0	21.26	21.22	21.12	0-1	1
	1	12	21.16	21.07	21.32		1
	1	24	21.00	21.19	21.27		1
	12	0	20.18	20.21	20.31	0-2	2
	12	6	20.14	20.18	20.26		2
	12	13	20.17	20.15	20.21		2
	25	0	20.17	20.10	20.21		2

Table 9-18
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.04	22.13	22.23	0	0
	1	7	22.14	22.14	22.26		0
	1	14	22.10	22.13	22.20		0
	8	0	21.02	21.02	21.19	0-1	1
	8	4	20.99	21.01	21.14		1
	8	7	21.03	20.98	21.14		1
	15	0	20.95	20.93	21.08		1
16QAM	1	0	21.20	21.28	21.39	0-1	1
	1	7	21.18	21.24	21.32		1
	1	14	21.22	21.31	21.11		1
	8	0	20.25	20.30	20.36	0-2	2
	8	4	20.18	20.29	20.36		2
	8	7	20.28	20.16	20.29		2
	15	0	20.18	20.18	20.26		2

Table 9-19
LTE Band 26 (Cell) Conducted Powers - 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.03	22.00	22.16	0	0
	1	2	22.02	21.99	22.14		0
	1	5	21.98	22.01	22.10		0
	3	0	22.05	22.00	22.29		0
	3	2	22.07	22.03	22.12		0
	3	3	22.09	22.05	22.11		0
	6	0	20.98	20.98	21.13	0-1	1
16QAM	1	0	21.00	20.82	20.95	0-1	1
	1	2	20.75	20.79	20.87		1
	1	5	20.91	20.80	20.95		1
	3	0	20.99	21.21	21.23		1
	3	2	20.94	21.17	21.21		1
	3	3	20.92	20.97	21.19		1
	6	0	20.10	20.23	20.26	0-2	2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 33 of 77

9.3.5

LTE Band 4 (AWS)

Table 9-20
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.42	0	0
	1	50	22.21		0
	1	99	22.13		0
	50	0	21.86	0-1	1
	50	25	21.81		1
	50	50	21.69		1
	100	0	21.80		1
16QAM	1	0	21.41	1	1
	1	50	21.34		1
	1	99	21.48		1
	50	0	20.98	0-2	2
	50	25	21.00		2
	50	50	20.99		2
	100	0	21.00		2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-21
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 4 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.09	22.10	21.95	0	0
	1	36	22.02	22.10	21.95		0
	1	74	22.00	22.04	21.97		0
	36	0	21.73	21.62	21.40	0-1	1
	36	18	21.66	21.60	21.35		1
	36	37	21.68	21.58	21.41		1
	75	0	21.75	21.64	21.42		1
16QAM	1	0	21.55	21.64	21.23	0-1	1
	1	36	21.50	21.63	21.22		1
	1	74	21.48	21.66	21.13		1
	36	0	20.97	21.00	20.91	0-2	2
	36	18	20.97	20.95	20.84		2
	36	37	20.98	20.94	20.86		2
	75	0	21.00	21.00	20.88		2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 34 of 77

Table 9-22
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 4 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.12	22.10	21.91	0	0
	1	25	22.06	22.06	21.89		0
	1	49	22.10	22.08	21.94		0
	25	0	21.74	21.55	21.34	0-1	1
	25	12	21.70	21.54	21.34		1
	25	25	21.71	21.53	21.33		1
	50	0	21.70	21.53	21.31		1
16QAM	1	0	21.52	21.60	21.12	0-1	1
	1	25	21.49	21.56	21.15		1
	1	49	21.51	21.54	21.13		1
	25	0	21.00	20.95	20.84	0-2	2
	25	12	20.98	20.98	20.87		2
	25	25	20.97	20.99	20.86		2
	50	0	20.97	21.00	20.88		2

Table 9-23
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 4 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.21	22.23	22.00	0	0
	1	12	22.20	22.21	21.97		0
	1	24	22.18	22.19	22.00		0
	12	0	21.64	21.62	21.41	0-1	1
	12	6	21.64	21.58	21.38		1
	12	13	21.67	21.58	21.36		1
16QAM	25	0	21.71	21.59	21.39	0-1	1
	1	0	21.64	21.40	21.46		1
	1	12	21.68	21.36	21.43		1
	1	24	21.62	21.40	21.50	0-2	1
	12	0	21.00	21.00	20.96		2
	12	6	20.99	20.97	20.95		2
	12	13	20.98	20.99	20.96		2
	25	0	21.00	20.99	20.89		2

Table 9-24
LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 4 (AWS) 3 MHzBandwidth							
Modulation	RB Size	RB Offset	Frequency [MHz]	Frequency [MHz]	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.11	22.00	22.00	0	0
	1	7	22.13	22.05	22.03		0
	1	14	22.13	22.06	22.04		0
	8	0	21.67	21.60	21.46	0-1	1
	8	4	21.68	21.56	21.48		1
	8	7	21.65	21.57	21.46		1
16QAM	15	0	21.64	21.52	21.42	0-1	1
	1	0	21.64	21.53	20.94		1
	1	7	21.50	21.50	20.97		1
	1	14	21.69	21.52	20.98	0-2	1
	8	0	20.99	20.98	20.94		2
	8	4	21.00	20.99	20.94		2
	8	7	20.99	20.99	20.94		2
	15	0	20.94	21.00	20.82		2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 35 of 77

Table 9-25
LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 4 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.02	22.03	21.87	0	0
	1	2	22.03	22.04	21.88		0
	1	5	22.02	22.01	21.86		0
	3	0	22.16	22.07	21.91		0
	3	2	22.13	22.06	21.92		0
	3	3	22.13	22.02	21.94		0
16QAM	6	0	21.67	21.62	21.54	0-1	1
	1	0	21.71	21.52	21.51	0-1	1
	1	2	21.76	21.61	21.64		1
	1	5	21.72	21.52	21.71		1
	3	0	21.52	21.42	21.38		1
	3	2	21.53	21.42	21.22		1
	3	3	21.57	21.38	21.42	1	
	6	0	21.00	21.00	20.80	0-2	2

Table 9-26
Reduced LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth – Hotspot Mode Active

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	20.00	0	0
	1	50	19.92		0
	1	99	19.66		0
	50	0	19.53		0
	50	25	19.58		0
	50	50	19.61		0
16QAM	100	0	19.59	0-1	0
	1	0	19.38		0
	1	50	19.47		0
	1	99	19.51		0
	50	0	19.02	0-2	0
	50	25	19.00		0
	50	50	19.00		0
	100	0	19.10		0

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-27
Reduced LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth – Hotspot Mode Active

LTE Band 4 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.83	19.91	20.00	0	0
	1	36	19.86	19.91	19.76		0
	1	74	19.62	19.47	19.70		0
	36	0	19.66	19.38	19.44	0-1	0
	36	18	19.54	19.60	19.65		0
	36	37	19.56	19.46	19.50		0
	75	0	19.66	19.54	19.71		0
16QAM	1	0	19.46	19.36	19.33	0-1	0
	1	36	19.57	19.42	19.50		0
	1	74	19.55	19.36	19.47		0
	36	0	19.08	18.97	19.25	0-2	0
	36	18	19.18	18.96	19.22		0
	36	37	19.03	19.14	19.10		0
	75	0	19.33	19.25	19.24		0

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 36 of 77	

Table 9-28
Reduced LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth – Hotspot Mode Active

LTE Band 4 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.97	19.84	19.81	0	0
	1	25	19.82	19.82	19.75		0
	1	49	19.74	19.58	19.68		0
	25	0	19.60	19.45	19.45	0-1	0
	25	12	19.71	19.65	19.47		0
	25	25	19.67	19.47	19.57		0
16QAM	50	0	19.59	19.44	19.57	0-1	0
	1	0	19.48	19.41	19.47		0
	1	25	19.56	19.31	19.42		0
	1	49	19.56	19.35	19.60	0-2	0
	25	0	19.09	19.15	19.15		0
	25	12	19.02	19.15	19.24		0
	25	25	19.12	18.94	19.16		0
	50	0	19.32	19.05	19.18		0

Table 9-29
Reduced LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth – Hotspot Mode Active

LTE Band 4 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.91	19.83	20.00	0	0
	1	12	19.84	19.88	19.76		0
	1	24	19.70	19.54	19.69		0
	12	0	19.62	19.54	19.47	0-1	0
	12	6	19.55	19.56	19.70		0
	12	13	19.56	19.45	19.61		0
16QAM	25	0	19.54	19.45	19.53	0-1	0
	1	0	19.52	19.53	19.45		0
	1	12	19.42	19.54	19.45		0
	1	24	19.67	19.50	19.54	0-2	0
	12	0	19.23	18.96	19.07		0
	12	6	19.18	19.02	19.15		0
	12	13	19.26	19.06	19.00		0
	25	0	19.23	19.09	19.24		0

Table 9-30
Reduced LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth – Hotspot Mode Active

LTE Band 4 (AWS) 3 MHzBandwidth							
Modulation	RB Size	RB Offset	Frequency [MHz]	Frequency [MHz]	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.86	19.80	19.85	0	0
	1	7	19.92	19.77	19.95		0
	1	14	19.62	19.71	19.59		0
	8	0	19.60	19.56	19.59	0-1	0
	8	4	19.72	19.65	19.67		0
	8	7	19.52	19.66	19.74		0
16QAM	15	0	19.51	19.59	19.59	0-1	0
	1	0	19.35	19.50	19.43		0
	1	7	19.50	19.40	19.41		0
	1	14	19.53	19.50	19.60	0-2	0
	8	0	19.20	19.06	19.12		0
	8	4	19.13	19.13	19.03		0
	8	7	19.10	18.96	19.16		0
	15	0	19.14	19.12	19.19		0

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 37 of 77

Table 9-31
Reduced LTE Band 4 (AWS) Conducted Powers – 1.4 MHz Bandwidth – Hotspot Mode Active

LTE Band 4 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.94	19.87	19.93	0	0
	1	2	19.91	19.78	19.88		0
	1	5	19.75	19.63	19.74		0
	3	0	19.51	19.46	19.51		0
	3	2	19.68	19.55	19.57		0
	3	3	19.52	19.59	19.50		0
	6	0	19.66	19.55	19.50		0
16QAM	1	0	19.58	19.45	19.35	0-1	0
	1	2	19.60	19.54	19.53		0
	1	5	19.54	19.40	19.55		0
	3	0	19.25	18.95	19.23		0
	3	2	19.04	19.13	19.10		0
	3	3	19.11	19.08	19.15		0
	6	0	19.32	19.10	19.25		0-2

9.3.6 LTE Band 25 (PCS)

Table 9-32
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.42	22.55	22.68	0	0
	1	50	22.31	22.36	22.43		0
	1	99	22.16	22.34	22.32		0
	50	0	21.15	21.25	21.24	0-1	1
	50	25	21.13	21.22	21.18		1
	50	50	21.09	21.16	21.17		1
	100	0	21.12	21.18	21.21		1
16QAM	1	0	21.00	20.99	20.88	0-1	1
	1	50	21.01	20.86	21.00		1
	1	99	20.73	21.06	20.92		1
	50	0	20.21	20.26	20.29	0-2	2
	50	25	20.18	20.24	20.23		2
	50	50	20.11	20.18	20.23		2
	100	0	20.14	20.21	20.22		2

Table 9-33
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.96	21.94	22.22	0	0
	1	36	21.91	21.87	22.09		0
	1	74	21.88	21.84	21.87		0
	36	0	20.84	20.80	21.03	0-1	1
	36	18	20.84	20.80	21.04		1
	36	37	20.84	20.77	21.02		1
	75	0	20.82	20.80	21.01		1
16QAM	1	0	20.88	21.15	21.19	0-1	1
	1	36	20.80	20.95	21.16		1
	1	74	20.96	20.81	21.00		1
	36	0	19.75	19.72	19.97	0-2	2
	36	18	19.76	19.73	20.00		2
	36	37	19.75	19.66	20.04		2
	75	0	19.75	19.68	19.97		2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 38 of 77

Table 9-34
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.12	21.94	22.22	0	0
	1	25	22.06	21.87	22.12		0
	1	49	22.05	21.84	22.05		0
	25	0	20.83	20.80	21.06	0-1	1
	25	12	20.84	20.78	21.06		1
	25	25	20.84	20.78	21.04		1
	50	0	20.83	20.77	20.98		1
16QAM	1	0	20.99	21.15	21.19	0-2	1
	1	25	21.10	20.95	21.18		1
	1	49	20.96	21.07	21.01		1
	25	0	19.75	19.67	19.97	0-2	2
	25	12	19.76	19.73	20.00		2
	25	25	19.75	19.66	20.04		2
	50	0	19.75	19.67	19.97		2

Table 9-35
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.03	22.01	22.41	0	0
	1	12	22.06	22.09	22.31		0
	1	24	22.05	22.09	22.24		0
	12	0	20.83	20.82	21.10	0-1	1
	12	6	20.82	20.81	21.09		1
	12	13	20.83	20.81	21.09		1
	25	0	20.85	20.80	21.06		1
16QAM	1	0	20.99	21.10	21.28	0-2	1
	1	12	20.87	20.94	21.20		1
	1	24	20.89	20.90	21.09		1
	12	0	19.75	19.74	20.02	0-2	2
	12	6	19.75	19.71	19.99		2
	12	13	19.74	19.73	20.01		2
	25	0	19.72	19.74	19.99		2

Table 9-36
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.93	21.91	22.18	0	0
	1	7	21.90	21.93	22.23		0
	1	14	21.92	21.88	22.16		0
	8	0	20.85	20.88	21.13	0-1	1
	8	4	20.90	20.86	21.10		1
	8	7	20.85	20.84	21.09		1
16QAM	15	0	20.80	20.79	21.04	0-1	1
	1	0	20.83	21.06	21.41		1
	1	7	21.02	20.99	21.23		1
	1	14	20.90	21.07	21.24	0-2	1
	8	0	19.78	19.79	20.21		2
	8	4	19.82	19.89	20.13		2
	8	7	19.79	19.75	20.13		2
		15	0	19.80	19.69	20.04	2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 39 of 77	

Table 9-37
LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.57	22.48	22.32	0	0
	1	2	22.59	22.44	22.32		0
	1	5	22.58	22.42	22.28		0
	3	0	22.52	22.42	22.32		0
	3	2	22.58	22.48	22.33		0
	3	3	22.51	22.43	22.30		0
	6	0	21.56	21.41	21.38		0-1
16QAM	1	0	21.55	21.33	21.29	0-1	1
	1	2	21.58	21.32	21.26		1
	1	5	21.56	21.29	21.24		1
	3	0	21.40	21.28	21.27		1
	3	2	21.52	21.39	21.41		1
	3	3	21.46	21.22	21.13		1
	6	0	20.56	20.49	20.46		0-2

9.3.7 LTE Band 41

Table 9-38
LTE Band 41 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.38	22.86	22.91	22.73	23.04	0	0
	1	50	23.27	22.91	22.90	22.77	23.13		0
	1	99	23.24	22.85	22.87	22.77	23.04		0
	50	0	22.31	21.94	22.05	21.85	22.06	1	
	50	25	22.28	21.91	22.07	21.87	22.05	1	
	50	50	22.24	21.91	22.04	21.89	22.07	1	
	100	0	22.29	21.93	22.03	21.86	22.08	1	
16QAM	1	0	21.85	21.81	21.84	21.58	21.80	0-1	1
	1	50	22.06	21.78	21.97	21.94	21.64		1
	1	99	22.07	21.75	21.51	21.66	21.84		1
	50	0	21.38	21.01	21.05	20.91	21.16	2	
	50	25	21.36	20.92	21.07	20.86	21.14	2	
	50	50	21.33	20.91	21.00	20.84	21.13	2	
	100	0	21.31	20.94	21.01	20.88	21.08	2	

Table 9-39
LTE Band 41 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.29	23.23	22.89	23.16	23.04	0	0
	1	36	23.24	23.21	22.89	23.14	23.08		0
	1	74	23.16	23.16	22.83	23.16	23.01		0
	36	0	22.41	22.26	21.93	22.18	22.17	0-1	1
	36	18	22.37	22.31	21.94	22.23	22.19		1
	36	37	22.37	22.24	21.95	22.25	22.16		1
	75	0	22.41	22.23	21.95	22.16	22.15		1
16QAM	1	0	22.36	21.83	21.57	22.13	22.07	0-1	1
	1	36	21.93	21.87	21.89	21.91	21.77		1
	1	74	21.82	21.71	21.65	21.93	22.17		1
	36	0	21.34	21.26	20.92	21.20	21.10	0-2	2
	36	18	21.35	21.24	20.93	21.17	21.09		2
	36	37	21.31	21.22	20.95	21.18	21.14		2
	75	0	21.31	21.30	20.94	21.23	21.00		2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 40 of 77

Table 9-40
LTE Band 41 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.25	23.04	22.82	23.04	23.09	0	0
	1	25	23.21	23.04	22.85	23.04	23.11		0
	1	49	23.21	23.03	22.84	23.09	23.07		0
	25	0	22.35	22.06	21.92	22.12	22.06	0-1	1
	25	12	22.34	22.02	21.90	22.11	22.05		1
	25	25	22.32	22.01	21.91	22.15	22.08		1
	50	0	22.33	22.06	21.91	22.16	22.11		1
16QAM	1	0	22.30	21.87	21.66	21.99	21.91	0-1	1
	1	25	22.25	21.77	21.63	22.03	21.87		1
	1	49	22.24	21.76	21.69	22.01	21.90		1
	25	0	21.31	21.08	20.95	21.10	21.11	0-2	2
	25	12	21.26	21.05	20.91	21.09	21.12		2
	25	25	21.26	21.06	20.95	21.11	21.14		2
	50	0	21.26	21.07	20.95	21.12	21.14		2

Table 9-41
LTE Band 41 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.27	22.88	23.00	23.11	22.94	0	0
	1	12	23.25	22.87	22.98	23.09	22.93		0
	1	24	23.25	22.85	23.00	23.11	22.94		0
	12	0	22.34	22.06	21.87	22.12	22.05	0-1	1
	12	6	22.31	22.03	21.90	22.12	22.04		1
	12	13	22.30	22.02	21.89	22.10	22.05		1
	25	0	22.31	22.02	21.89	22.10	22.06		1
16QAM	1	0	21.93	21.66	21.80	21.74	21.65	0-1	1
	1	12	21.92	21.63	21.74	21.74	21.64		1
	1	24	21.96	21.59	21.70	21.79	21.65		1
	12	0	21.30	21.07	20.93	21.11	21.06	0-2	2
	12	6	21.31	21.00	20.97	21.09	21.09		2
	12	13	21.33	21.06	20.97	21.10	21.08		2
	25	0	21.31	21.09	20.87	21.08	21.10		2

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 41 of 77

9.4 WLAN Conducted Powers

Table 9-42
2.4 GHz WLAN Maximum Average RF Power – Antenna 1

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	19.41	17.32	17.16
2437	6	18.75	17.23	17.08
2462	11	18.79	17.15	17.00

Table 9-43
2.4 GHz WLAN Maximum Average RF Power – Antenna 2

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	18.13	17.28	17.08
2437	6	18.93	16.91	16.80
2462	11	18.92	16.75	16.56

Table 9-44
2.4 GHz WLAN Reduced Average RF Power – Antenna 1 (Held to Ear)

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	12.59	12.42	13.43
2437	6	13.20	12.67	12.91
2462	11	13.06	12.60	12.56

Table 9-45
2.4 GHz WLAN Reduced Average RF Power – Antenna 2 (Held to Ear)

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	12.80	11.63	13.49
2437	6	13.40	12.72	12.75
2462	11	13.34	12.60	12.53

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 42 of 77

Table 9-46
5 GHz WLAN Maximum Average RF Power – Antenna 1

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	14.59	14.40	14.73
5200	40	16.03	15.85	16.10
5220	44	16.01	15.94	16.06
5240	48	15.92	15.87	16.02
5260	52	16.49	16.29	16.47
5280	56	16.48	16.22	16.43
5300	60	16.45	16.32	16.37
5320	64	14.77	14.71	14.87
5500	100	14.20	13.97	14.33
5520	104	15.81	15.57	15.70
5600	120	15.70	16.37	15.52
5620	124	15.57	16.40	15.53
5720	144	16.27	16.10	16.20
5745	149	15.58	16.40	16.45
5785	157	15.50	16.25	16.38
5825	165	16.31	16.22	16.13

Table 9-47
5 GHz WLAN Maximum Average RF Power – Antenna 2

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	14.57	14.49	15.17
5200	40	16.16	16.13	16.13
5220	44	16.13	16.08	16.18
5240	48	16.28	16.10	16.21
5260	52	16.44	16.28	16.37
5280	56	16.42	16.37	16.30
5300	60	16.43	16.29	16.36
5320	64	14.72	14.69	15.39
5500	100	14.63	14.66	15.47
5520	104	16.33	16.25	16.31
5600	120	16.08	15.97	16.03
5620	124	16.04	16.02	16.04
5720	144	15.85	15.68	15.90
5745	149	16.20	16.11	16.33
5785	157	16.05	16.05	16.31
5825	165	16.15	16.01	16.26

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 43 of 77	

Table 9-48
5 GHz WLAN Reduced Average RF Power – Antenna 1 (Held to Ear)

5GHz (80MHz) Conducted Power		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	9.57
5290	58	9.53
5530	106	10.49
5610	122	10.37
5690	138	10.20
5775	155	10.00

Table 9-49
5 GHz WLAN Reduced Average RF Power – Antenna 2 (Held to Ear)

5GHz (80MHz) Conducted Power		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	10.01
5290	58	10.49
5530	106	9.70
5610	122	9.60
5690	138	9.54
5775	155	10.44

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 44 of 77

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-3
Power Measurement Setup for Bandwidths < 50 MHz




Figure 9-4
Power Measurement Setup for Bandwidths > 50 MHz

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 45 of 77

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties – Head

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
12/21/2015	750H	22.0	700	0.849	42.469	0.889	42.201	-4.50%	0.64%
			710	0.853	42.251	0.890	42.149	-4.16%	0.24%
			720	0.862	42.125	0.891	42.097	-3.25%	0.07%
			740	0.884	41.816	0.893	41.994	-1.01%	-0.42%
			755	0.895	41.648	0.894	41.916	0.11%	-0.64%
			770	0.908	41.510	0.895	41.838	1.45%	-0.78%
			785	0.928	41.399	0.896	41.760	3.57%	-0.86%
12/20/2015	835H	21.0	820	0.890	40.571	0.899	41.578	-1.00%	-2.42%
			835	0.901	40.356	0.900	41.500	0.11%	-2.76%
			850	0.919	40.227	0.916	41.500	0.33%	-3.07%
12/23/2015	835H	22.7	820	0.896	40.019	0.899	41.578	-0.33%	-3.75%
			835	0.912	39.854	0.900	41.500	1.33%	-3.97%
			850	0.925	39.585	0.916	41.500	0.98%	-4.61%
12/30/2015	1750H	22.7	1710	1.301	38.668	1.348	40.142	-3.49%	-3.67%
			1750	1.340	38.480	1.371	40.079	-2.26%	-3.99%
			1790	1.378	38.306	1.394	40.016	-1.15%	-4.27%
12/28/2015	1900H	22.2	1850	1.378	39.010	1.400	40.000	-1.57%	-2.48%
			1880	1.411	38.874	1.400	40.000	0.79%	-2.81%
			1910	1.444	38.733	1.400	40.000	3.14%	-3.17%
12/30/2015	2450H	24.2	2450	1.844	39.649	1.800	39.200	2.44%	1.15%
			2500	1.903	39.459	1.855	39.136	2.59%	0.83%
			2550	1.963	39.249	1.909	39.073	2.83%	0.45%
1/15/2016	2450H	22.0	2400	1.763	38.856	1.756	39.289	0.40%	-1.10%
			2450	1.822	38.658	1.800	39.200	1.22%	-1.38%
			2500	1.877	38.465	1.855	39.136	1.19%	-1.71%
01/14/2016	5200H-5800H	21.7	5240	4.674	36.275	4.696	35.940	-0.47%	0.93%
			5260	4.696	36.211	4.717	35.917	-0.45%	0.82%
			5280	4.720	36.215	4.737	35.894	-0.36%	0.89%
			5300	4.737	36.167	4.758	35.871	-0.44%	0.83%
			5500	4.935	35.880	4.963	35.643	-0.56%	0.66%
			5520	4.959	35.886	4.983	35.620	-0.48%	0.75%
			5540	4.989	35.814	5.004	35.597	-0.30%	0.61%
			5600	5.043	35.740	5.065	35.529	-0.43%	0.59%
			5745	5.204	35.504	5.214	35.363	-0.19%	0.40%
			5765	5.224	35.488	5.235	35.335	-0.21%	0.43%
			5785	5.244	35.453	5.255	35.317	-0.21%	0.39%

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 46 of 77

Table 10-2
Measured Tissue Properties – Body

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
12/30/2015	750B	23.2	700	0.919	55.349	0.959	55.726	-4.17%	-0.68%
			710	0.929	55.268	0.960	55.687	-3.23%	-0.75%
			740	0.959	54.983	0.963	55.570	-0.42%	-1.06%
			755	0.973	54.801	0.964	55.512	0.93%	-1.28%
			770	0.988	54.619	0.965	55.453	2.38%	-1.50%
			785	1.002	54.454	0.966	55.395	3.73%	-1.70%
1/15/2016	750B	22.6	700	0.927	54.900	0.959	55.726	-3.34%	-1.48%
			710	0.937	54.860	0.960	55.687	-2.40%	-1.49%
			740	0.967	54.548	0.963	55.570	0.42%	-1.84%
			755	0.975	54.327	0.964	55.512	1.14%	-2.13%
			770	0.991	54.294	0.965	55.453	2.69%	-2.09%
			785	1.010	54.110	0.966	55.395	4.55%	-2.32%
12/21/2015	835B	21.6	820	0.991	54.923	0.969	55.258	2.27%	-0.61%
			835	1.010	54.664	0.970	55.200	4.12%	-0.97%
			850	1.020	54.558	0.988	55.154	3.24%	-1.08%
1/7/2016	835B	22.4	820	0.983	53.328	0.969	55.258	1.44%	-3.49%
			835	0.997	53.205	0.970	55.200	2.78%	-3.61%
			850	1.013	53.034	0.988	55.154	2.53%	-3.84%
1/17/2016	835B	21.6	820	0.989	55.503	0.969	55.258	2.06%	0.44%
			835	1.000	55.351	0.970	55.200	3.09%	0.27%
			850	1.019	55.298	0.988	55.154	3.14%	0.26%
1/19/2016	835B	20.1	820	0.992	56.185	0.969	55.258	2.37%	1.68%
			835	1.005	56.042	0.970	55.200	3.61%	1.53%
			850	1.021	55.874	0.988	55.154	3.34%	1.31%
1/6/2016	1750B	22.6	1710	1.446	51.788	1.463	53.537	-1.16%	-3.27%
			1750	1.487	51.690	1.488	53.432	-0.07%	-3.26%
			1790	1.526	51.559	1.514	53.326	0.79%	-3.31%
1/11/2016	1750B	22.7	1710	1.441	51.236	1.463	53.537	-1.50%	-4.30%
			1750	1.486	51.093	1.488	53.432	-0.13%	-4.38%
			1790	1.529	50.949	1.514	53.326	0.99%	-4.46%
1/14/2016	1750B	22.1	1710	1.465	51.998	1.463	53.537	0.14%	-2.87%
			1750	1.511	51.892	1.488	53.432	1.55%	-2.88%
			1790	1.553	51.741	1.514	53.326	2.58%	-2.97%
12/31/2015	1900B	22.8	1850	1.510	52.281	1.520	53.300	-0.66%	-1.91%
			1880	1.547	52.243	1.520	53.300	1.78%	-1.98%
			1910	1.574	52.134	1.520	53.300	3.55%	-2.19%
1/11/2016	1900B	21.5	1850	1.526	53.273	1.520	53.300	0.39%	-0.05%
			1880	1.560	53.175	1.520	53.300	2.63%	-0.23%
			1910	1.594	53.069	1.520	53.300	4.87%	-0.43%
1/20/2016	1900B	23.0	1850	1.525	52.176	1.520	53.300	0.33%	-2.11%
			1880	1.558	52.088	1.520	53.300	2.50%	-2.27%
			1910	1.589	51.949	1.520	53.300	4.54%	-2.53%
12/23/2015	2450B	23.5	2450	1.963	50.820	1.950	52.700	0.67%	-3.57%
			2500	2.048	50.824	2.021	52.636	1.34%	-3.44%
			2550	2.106	50.467	2.092	52.573	0.67%	-4.01%
1/12/2016	2450B	22.5	2400	1.920	52.493	1.902	52.767	0.95%	-0.52%
			2450	1.994	52.299	1.950	52.700	2.26%	-0.76%
			2500	2.062	52.082	2.021	52.636	2.03%	-1.05%
			2550	2.133	51.890	2.092	52.573	1.96%	-1.30%
			5180	5.293	48.792	5.276	49.041	0.32%	-0.51%
			5200	5.316	48.631	5.299	49.014	0.32%	-0.78%
01/12/2016	5200B-5800B	23.8	5220	5.331	48.636	5.323	48.987	0.15%	-0.72%
			5240	5.385	48.628	5.346	48.960	0.73%	-0.68%
			5260	5.406	48.575	5.369	48.933	0.69%	-0.73%
			5300	5.455	48.493	5.416	48.879	0.72%	-0.79%
			5500	5.711	48.227	5.650	48.607	1.08%	-0.78%
			5520	5.727	48.253	5.673	48.580	0.95%	-0.67%
			5700	5.981	47.920	5.883	48.336	1.67%	-0.86%
			5745	6.039	47.844	5.936	48.275	1.74%	-0.89%
			5800	6.135	47.714	6.000	48.200	2.25%	-1.01%
			5825	6.169	47.626	6.029	48.166	2.32%	-1.12%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 47 of 77	

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
K	750	HEAD	12/21/2015	24.5	22.0	0.200	1003	3022	1.660	8.090	8.300	2.60%
J	835	HEAD	12/20/2015	19.3	20.7	0.200	4d133	3319	1.810	9.130	9.050	-0.88%
J	835	HEAD	12/23/2015	23.5	22.7	0.200	4d133	3319	1.790	9.130	8.950	-1.97%
E	1750	HEAD	12/30/2015	24.1	22.2	0.100	1051	3351	3.740	36.200	37.400	3.31%
J	1900	HEAD	12/28/2015	24.2	22.2	0.100	5d149	3319	3.830	40.700	38.300	-5.90%
I	2450	HEAD	12/30/2015	24.0	24.2	0.100	719	3333	5.130	54.200	51.300	-5.35%
J	2450	HEAD	01/15/2016	22.7	22.0	0.100	719	3319	5.040	54.200	50.400	-7.01%
E	5250	HEAD	01/14/2016	24.2	22.0	0.050	1191	7308	3.940	82.500	78.800	-4.48%
E	5600	HEAD	01/14/2016	24.2	22.0	0.050	1191	7308	4.310	84.500	86.200	2.01%
E	5750	HEAD	01/14/2016	24.2	22.0	0.050	1191	7308	3.850	80.000	77.000	-3.75%
K	750	BODY	12/30/2015	23.8	23.2	0.200	1003	3022	1.710	8.460	8.550	1.06%
G	750	BODY	01/15/2016	24.5	23.9	0.200	1054	3334	1.790	8.530	8.950	4.92%
H	835	BODY	12/21/2015	22.0	21.8	0.200	4d133	3263	1.980	9.250	9.900	7.03%
H	835	BODY	01/07/2016	24.4	22.4	0.200	4d133	3263	1.970	9.250	9.850	6.49%
H	835	BODY	01/17/2016	21.3	21.6	0.200	4d119	3263	1.760	9.200	8.800	-4.35%
H	835	BODY	01/19/2016	22.5	20.8	0.200	4d133	3263	1.950	9.250	9.750	5.41%
I	1750	BODY	01/06/2016	24.2	22.6	0.100	1051	3333	3.860	37.100	38.600	4.04%
E	1750	BODY	01/11/2016	23.2	22.7	0.100	1051	3351	3.790	37.100	37.900	2.16%
G	1750	BODY	01/14/2016	24.4	22.4	0.100	1051	3334	3.890	37.100	38.900	4.85%
J	1900	BODY	12/31/2015	23.0	22.8	0.100	5d149	3319	4.030	40.400	40.300	-0.25%
I	1900	BODY	01/11/2016	22.8	21.5	0.100	5d141	3333	3.810	40.000	38.100	-4.75%
I	1900	BODY	01/20/2016	23.9	22.4	0.100	5d149	3333	4.160	40.400	41.600	2.97%
G	2450	BODY	12/23/2015	19.6	23.0	0.100	719	3334	5.140	51.900	51.400	-0.96%
J	2450	BODY	01/12/2016	22.1	22.5	0.100	719	3319	5.330	51.900	53.300	2.70%
D	5300	BODY	01/12/2016	23.8	23.6	0.050	1120	7357	3.770	75.200	75.400	0.27%
D	5500	BODY	01/12/2016	23.8	23.6	0.050	1120	7357	3.820	79.500	76.400	-3.90%
D	5800	BODY	01/12/2016	23.8	23.6	0.050	1120	7357	3.720	76.300	74.400	-2.49%




Figure 10-1

System Verification Setup Diagram



Figure 10-2

System Verification Setup Photo

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 48 of 77

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

**Table 11-1
GSM 850 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	34.0	33.29	0.05	Right	Cheek	80B93	1:8.3	0.227	1.178	0.267	A1
836.60	190	GSM 850	GSM	34.0	33.29	-0.03	Right	Tilt	80B93	1:8.3	0.088	1.178	0.104	
836.60	190	GSM 850	GSM	34.0	33.29	0.13	Left	Cheek	80B93	1:8.3	0.134	1.178	0.158	
836.60	190	GSM 850	GSM	34.0	33.29	0.14	Left	Tilt	80B93	1:8.3	0.077	1.178	0.091	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-2
UMTS 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	State	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	24.5	23.54	0.16	Right	Cheek	80B93	1:1	State 15	0.204	1.247	0.254	A2
836.60	4183	UMTS 850	RMC	24.5	23.54	0.17	Right	Tilt	80B93	1:1	State 15	0.078	1.247	0.097	
836.60	4183	UMTS 850	RMC	24.5	23.54	0.08	Left	Cheek	80B93	1:1	State 15	0.118	1.247	0.147	
836.60	4183	UMTS 850	RMC	24.5	23.54	0.11	Left	Tilt	80B93	1:1	State 15	0.063	1.247	0.079	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-3
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	23.5	22.45	0.01	Right	Cheek	81029	1:1	0.054	1.274	0.069	
1732.40	1412	UMTS 1750	RMC	23.5	22.45	0.02	Right	Tilt	81029	1:1	0.056	1.274	0.071	
1732.40	1412	UMTS 1750	RMC	23.5	22.45	0.01	Left	Cheek	81029	1:1	0.097	1.274	0.124	A3
1732.40	1412	UMTS 1750	RMC	23.5	22.45	0.14	Left	Tilt	81029	1:1	0.056	1.274	0.071	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 49 of 77

Table 11-4
GSM 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	31.0	30.46	0.13	Right	Cheek	80B93	1:8.3	0.031	1.132	0.035	
1880.00	661	GSM 1900	GSM	31.0	30.46	0.14	Right	Tilt	80B93	1:8.3	0.013	1.132	0.015	
1880.00	661	GSM 1900	GSM	31.0	30.46	0.06	Left	Cheek	80B93	1:8.3	0.059	1.132	0.067	A4
1880.00	661	GSM 1900	GSM	31.0	30.46	0.14	Left	Tilt	80B93	1:8.3	0.016	1.132	0.018	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-5
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	23.5	22.62	0.17	Right	Cheek	81029	1:1	0.038	1.225	0.047	
1880.00	9400	UMTS 1900	RMC	23.5	22.62	0.16	Right	Tilt	81029	1:1	0.014	1.225	0.017	
1880.00	9400	UMTS 1900	RMC	23.5	22.62	-0.02	Left	Cheek	81029	1:1	0.052	1.225	0.064	A5
1880.00	9400	UMTS 1900	RMC	23.5	22.62	0.07	Left	Tilt	81029	1:1	0.019	1.225	0.023	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-6
LTE Band 12 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	-0.01	0	Right	Cheek	QPSK	1	0	80B93	1:1	0.056	1.146	0.064	A6
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	0.12	1	Right	Cheek	QPSK	25	12	80B93	1:1	0.045	1.146	0.052	
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	0.19	0	Right	Tilt	QPSK	1	0	80B93	1:1	0.023	1.146	0.026	
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	0.11	1	Right	Tilt	QPSK	25	12	80B93	1:1	0.019	1.146	0.022	
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	0.07	0	Left	Cheek	QPSK	1	0	80B93	1:1	0.034	1.146	0.039	
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	0.14	1	Left	Cheek	QPSK	25	12	80B93	1:1	0.028	1.146	0.032	
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	0.11	0	Left	Tilt	QPSK	1	0	80B93	1:1	0.021	1.146	0.024	
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	0.17	1	Left	Tilt	QPSK	25	12	80B93	1:1	0.021	1.146	0.024	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 50 of 77

Table 11-7
LTE Band 13 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																(W/kg)		(W/kg)	
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	0.00	0	Right	Cheek	QPSK	1	25	80B93	1:1	0.078	1.132	0.088	A7
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.07	1	Right	Cheek	QPSK	25	25	80B93	1:1	0.060	1.164	0.070	
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	-0.18	0	Right	Tilt	QPSK	1	25	80B93	1:1	0.032	1.132	0.036	
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.15	1	Right	Tilt	QPSK	25	25	80B93	1:1	0.024	1.164	0.028	
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	0.10	0	Left	Cheek	QPSK	1	25	80B93	1:1	0.039	1.132	0.044	
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.15	1	Left	Cheek	QPSK	25	25	80B93	1:1	0.031	1.164	0.036	
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	0.20	0	Left	Tilt	QPSK	1	25	80B93	1:1	0.035	1.132	0.040	
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.07	1	Left	Tilt	QPSK	25	25	80B93	1:1	0.029	1.164	0.034	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-8
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	State	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot	
MHz	Ch.															(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	0.00	0	Right	Cheek	QPSK	1	0	80B93	1:1	State 15	0.197	1.146	0.226	A8
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	0.01	1	Right	Cheek	QPSK	25	0	80B93	1:1	State 15	0.143	1.268	0.181	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	0.12	0	Right	Tilt	QPSK	1	0	80B93	1:1	State 15	0.070	1.146	0.080	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	0.05	1	Right	Tilt	QPSK	25	0	80B93	1:1	State 15	0.056	1.268	0.071	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	0.14	0	Left	Cheek	QPSK	1	0	80B93	1:1	State 15	0.127	1.146	0.146	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	0.06	1	Left	Cheek	QPSK	25	0	80B93	1:1	State 15	0.090	1.268	0.114	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	0.17	0	Left	Tilt	QPSK	1	0	80B93	1:1	State 15	0.064	1.146	0.073	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	0.19	1	Left	Tilt	QPSK	25	0	80B93	1:1	State 15	0.044	1.268	0.056	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-9
LTE Band 26 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	0.13	0	Right	Cheek	QPSK	1	0	80B93	1:1	0.133	1.119	0.149	A9
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.00	1	Right	Cheek	QPSK	36	0	80B93	1:1	0.102	1.119	0.114	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	0.07	0	Right	Tilt	QPSK	1	0	80B93	1:1	0.058	1.119	0.065	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.18	1	Right	Tilt	QPSK	36	0	80B93	1:1	0.041	1.119	0.046	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	0.06	0	Left	Cheek	QPSK	1	0	80B93	1:1	0.103	1.119	0.115	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.19	1	Left	Cheek	QPSK	36	0	80B93	1:1	0.077	1.119	0.086	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	0.09	0	Left	Tilt	QPSK	1	0	80B93	1:1	0.049	1.119	0.055	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.16	1	Left	Tilt	QPSK	36	0	80B93	1:1	0.034	1.119	0.038	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 51 of 77

Table 11-10
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.42	0.02	0	Right	Cheek	QPSK	1	0	81029	1:1	0.047	1.143	0.054	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.86	0.04	1	Right	Cheek	QPSK	50	0	81029	1:1	0.040	1.033	0.041	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.42	-0.08	0	Right	Tilt	QPSK	1	0	81029	1:1	0.064	1.143	0.073	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.86	0.02	1	Right	Tilt	QPSK	50	0	81029	1:1	0.048	1.033	0.050	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.42	0.04	0	Left	Cheek	QPSK	1	0	81029	1:1	0.077	1.143	0.088	A10
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.86	0.01	1	Left	Cheek	QPSK	50	0	81029	1:1	0.074	1.033	0.076	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.42	-0.01	0	Left	Tilt	QPSK	1	0	81029	1:1	0.059	1.143	0.067	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.86	-0.01	1	Left	Tilt	QPSK	50	0	81029	1:1	0.050	1.033	0.052	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-11
LTE Band 25 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.04	0	Right	Cheek	QPSK	1	0	81029	1:1	0.045	1.076	0.048	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.18	1	Right	Cheek	QPSK	50	0	81029	1:1	0.031	1.189	0.037	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.11	0	Right	Tilt	QPSK	1	0	81029	1:1	0.014	1.076	0.015	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.17	1	Right	Tilt	QPSK	50	0	81029	1:1	0.010	1.189	0.012	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	-0.02	0	Left	Cheek	QPSK	1	0	81029	1:1	0.061	1.076	0.066	A11
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.05	1	Left	Cheek	QPSK	50	0	81029	1:1	0.043	1.189	0.051	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.18	0	Left	Tilt	QPSK	1	0	81029	1:1	0.023	1.076	0.025	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.10	1	Left	Tilt	QPSK	50	0	81029	1:1	0.016	1.189	0.019	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-12
LTE Band 41 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	0.16	0	Right	Cheek	QPSK	1	0	8102F	1:1.58	0.053	1.028	0.054	
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	0.11	1	Right	Cheek	QPSK	50	0	8102F	1:1.58	0.044	1.045	0.046	
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	0.12	0	Right	Tilt	QPSK	1	0	8102F	1:1.58	0.047	1.028	0.048	
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	0.13	1	Right	Tilt	QPSK	50	0	8102F	1:1.58	0.044	1.045	0.046	
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	0.06	0	Left	Cheek	QPSK	1	0	8102F	1:1.58	0.083	1.028	0.085	A12
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	-0.06	1	Left	Cheek	QPSK	50	0	8102F	1:1.58	0.062	1.045	0.065	
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	0.08	0	Left	Tilt	QPSK	1	0	8102F	1:1.58	0.034	1.028	0.035	
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	0.06	1	Left	Tilt	QPSK	50	0	8102F	1:1.58	0.024	1.045	0.025	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMG935F		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 52 of 77	

**Table 11-13
DTS Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR(1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	13.5	13.20	-0.01	Right	Cheek	1	00580	1	99.8	0.322	0.320	1.072	1.002	0.344	
2437	6	802.11b	DSSS	22	13.5	13.20	-	Right	Tilt	1	00580	1	99.8	0.207	-	1.072	1.002	-	
2437	6	802.11b	DSSS	22	13.5	13.20	-	Left	Cheek	1	00580	1	99.8	0.172	-	1.072	1.002	-	
2437	6	802.11b	DSSS	22	13.5	13.20	-	Left	Tilt	1	00580	1	99.8	0.135	-	1.072	1.002	-	
2437	6	802.11b	DSSS	22	13.5	13.40	-	Right	Cheek	2	00580	1	99.8	0.241	-	1.023	1.002	-	
2437	6	802.11b	DSSS	22	13.5	13.40	-	Right	Tilt	2	00580	1	99.8	0.215	-	1.023	1.002	-	
2437	6	802.11b	DSSS	22	13.5	13.40	0.00	Left	Cheek	2	00580	1	99.8	0.479	0.368	1.023	1.002	0.377	A13
2437	6	802.11b	DSSS	22	13.5	13.40	-	Left	Tilt	2	00580	1	99.8	0.426	-	1.023	1.002	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-14
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5290	58	802.11ac	OFDM	80	10.5	9.53	0.18	Right	Cheek	1	0C6B5	29.3	97.1	0.325	0.162	1.250	1.030	0.209	
5290	58	802.11ac	OFDM	80	10.5	9.53	-	Right	Tilt	1	0C6B5	29.3	97.1	0.210	-	1.250	1.030	-	
5290	58	802.11ac	OFDM	80	10.5	9.53	-	Left	Cheek	1	0C6B5	29.3	97.1	0.117	-	1.250	1.030	-	
5290	58	802.11ac	OFDM	80	10.5	9.53	-	Left	Tilt	1	0C6B5	29.3	97.1	0.073	-	1.250	1.030	-	
5290	58	802.11ac	OFDM	80	10.5	10.49	0.16	Right	Cheek	2	0C6B5	29.3	93.3	0.289	0.150	1.002	1.072	0.161	
5290	58	802.11ac	OFDM	80	10.5	10.49	-	Right	Tilt	2	0C6B5	29.3	93.3	0.224	-	1.002	1.072	-	
5290	58	802.11ac	OFDM	80	10.5	10.49	-	Left	Cheek	2	0C6B5	29.3	93.3	0.233	-	1.002	1.072	-	
5290	58	802.11ac	OFDM	80	10.5	10.49	-	Left	Tilt	2	0C6B5	29.3	93.3	0.233	-	1.002	1.072	-	
5530	106	802.11ac	OFDM	80	10.5	10.49	-0.19	Right	Cheek	1	0C6B5	29.3	97.1	0.425	0.128	1.002	1.030	0.132	
5530	106	802.11ac	OFDM	80	10.5	10.49	-	Right	Tilt	1	0C6B5	29.3	97.1	0.331	-	1.002	1.030	-	
5530	106	802.11ac	OFDM	80	10.5	10.49	-	Left	Cheek	1	0C6B5	29.3	97.1	0.173	-	1.002	1.030	-	
5530	106	802.11ac	OFDM	80	10.5	10.49	-	Left	Tilt	1	0C6B5	29.3	97.1	0.191	-	1.002	1.030	-	
5530	106	802.11ac	OFDM	80	10.5	9.70	-	Right	Cheek	2	0C6B5	29.3	93.3	0.534	-	1.202	1.072	-	
5530	106	802.11ac	OFDM	80	10.5	9.70	-	Right	Tilt	2	0C6B5	29.3	93.3	0.495	-	1.202	1.072	-	
5530	106	802.11ac	OFDM	80	10.5	9.70	-0.11	Left	Cheek	2	0C6B5	29.3	93.3	0.793	0.224	1.202	1.072	0.288	
5530	106	802.11ac	OFDM	80	10.5	9.70	-	Left	Tilt	2	0C6B5	29.3	93.3	0.779	-	1.202	1.072	-	
5775	155	802.11ac	OFDM	80	10.5	10.00	-	Right	Cheek	1	0C6B5	29.3	97.1	0.238	-	1.122	1.030	-	
5775	155	802.11ac	OFDM	80	10.5	10.00	-0.11	Right	Tilt	1	0C6B5	29.3	97.1	0.241	0.052	1.122	1.030	0.060	
5775	155	802.11ac	OFDM	80	10.5	10.00	-	Left	Cheek	1	0C6B5	29.3	97.1	0.090	-	1.122	1.030	-	
5775	155	802.11ac	OFDM	80	10.5	10.00	-	Left	Tilt	1	0C6B5	29.3	97.1	0.118	-	1.122	1.030	-	
5775	155	802.11ac	OFDM	80	10.5	10.44	-0.14	Right	Cheek	2	0C6B5	29.3	93.3	1.147	0.454	1.014	1.072	0.493	
5775	155	802.11ac	OFDM	80	10.5	10.44	-	Right	Tilt	2	0C6B5	29.3	93.3	0.743	-	1.014	1.072	-	
5775	155	802.11ac	OFDM	80	10.5	10.44	0.08	Left	Cheek	2	0C6B5	29.3	93.3	1.471	0.513	1.014	1.072	0.557	A14
5775	155	802.11ac	OFDM	80	10.5	10.44	-	Left	Tilt	2	0C6B5	29.3	93.3	0.411	-	1.014	1.072	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 53 of 77

11.1 Standalone Body-Worn SAR Data

Table 11-15
GSM/UMTS Body-Worn SAR Data

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	State	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	34.0	33.29	0.00	15 mm	80B93	1	1.8.3	back	N/A	0.389	1.178	0.458	A15
836.60	4183	UMTS 850	RMC	24.5	23.54	0.00	15 mm	80B93	N/A	1:1	back	State 15	0.276	1.247	0.344	A17
1732.40	1412	UMTS 1750	RMC	23.5	22.45	0.03	15 mm	81029	N/A	1:1	back	N/A	0.515	1.274	0.656	A19
1880.00	661	GSM 1900	GSM	31.0	30.46	0.14	15 mm	80B93	1	1.8.3	back	N/A	0.399	1.132	0.452	A21
1880.00	9400	UMTS 1900	RMC	23.5	22.62	0.02	15 mm	80B93	N/A	1:1	back	N/A	0.385	1.225	0.472	A23
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body								
Spatial Peak								1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population								averaged over 1 gram								

Table 11-16
LTE Body-Worn SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	State	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
Mhz	Ch.															(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	0.03	0	80B93	QPSK	1	0	15 mm	back	1:1	N/A	0.133	1.146	0.152	A25
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	0.10	1	80B93	QPSK	25	12	15 mm	back	1:1	N/A	0.104	1.146	0.119	
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	0.04	0	80B93	QPSK	1	25	15 mm	back	1:1	N/A	0.171	1.132	0.194	A27
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.07	1	80B93	QPSK	25	25	15 mm	back	1:1	N/A	0.139	1.164	0.162	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	-0.05	0	80B93	QPSK	1	0	15 mm	back	1:1	State 15	0.276	1.146	0.316	A29
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	-0.03	1	80B93	QPSK	25	0	15 mm	back	1:1	State 15	0.213	1.268	0.270	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	-0.01	0	80B93	QPSK	1	0	15 mm	back	1:1	N/A	0.202	1.119	0.226	A31
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.06	1	80B93	QPSK	36	0	15 mm	back	1:1	N/A	0.162	1.119	0.181	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.42	0.00	0	81029	QPSK	1	0	15 mm	back	1:1	N/A	0.445	1.143	0.509	A33
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.86	0.07	1	81029	QPSK	50	0	15 mm	back	1:1	N/A	0.419	1.033	0.433	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.09	0	80B93	QPSK	1	0	15 mm	back	1:1	N/A	0.370	1.076	0.398	A35
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.00	1	80B93	QPSK	50	0	15 mm	back	1:1	N/A	0.281	1.189	0.334	
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	0.04	0	0C6B5	QPSK	1	0	15 mm	back	1:1.58	N/A	0.252	1.028	0.259	A37
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	0.05	1	0C6B5	QPSK	50	0	15 mm	back	1:1.58	N/A	0.208	1.045	0.217	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body											
Spatial Peak									1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population									averaged over 1 gram											

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 54 of 77

**Table 11-17
DTS Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	19.5	19.41	0.09	15 mm	1	0C6B5	1	back	99.8	0.163	0.145	1.021	1.002	0.148	A39
2437	6	802.11b	DSSS	22	19.5	18.93	0.00	15 mm	2	0C6B5	1	back	99.8	0.124	0.107	1.140	1.002	0.122	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

**Table 11-18
NII Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	16.5	16.49	0.09	15 mm	1	80D08	6	back	98.7	0.261	0.151	1.002	1.013	0.153	
5260	52	802.11a	OFDM	20	16.5	16.44	0.15	15 mm	2	80D08	6	back	98.2	0.573	0.307	1.014	1.018	0.317	
5720	144	802.11a	OFDM	20	16.5	16.27	0.17	15 mm	1	80D08	6	back	98.7	0.133	0.082	1.054	1.013	0.087	
5520	104	802.11a	OFDM	20	16.5	16.33	0.18	15 mm	2	80D08	6	back	98.2	0.638	0.316	1.040	1.018	0.335	A41
5825	165	802.11a	OFDM	20	16.5	16.31	0.04	15 mm	1	80D08	6	back	98.7	0.176	0.100	1.045	1.013	0.106	
5745	149	802.11a	OFDM	20	16.5	16.20	0.11	15 mm	2	80D08	6	back	98.2	0.269	0.142	1.072	1.018	0.155	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 55 of 77

11.2 Standalone Hotspot SAR Data

Table 11-19
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	State	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	30.0	29.68	-0.10	10 mm	80B93	3	1:2.76	back	N/A	0.649	1.076	0.698	
836.60	190	GSM 850	GPRS	30.0	29.68	-0.14	10 mm	80B93	3	1:2.76	front	N/A	0.683	1.076	0.735	A16
836.60	190	GSM 850	GPRS	30.0	29.68	-0.01	10 mm	80B93	3	1:2.76	bottom	N/A	0.317	1.076	0.341	
836.60	190	GSM 850	GPRS	30.0	29.68	0.00	10 mm	80B93	3	1:2.76	right	N/A	0.389	1.076	0.419	
836.60	190	GSM 850	GPRS	30.0	29.68	-0.01	10 mm	80B93	3	1:2.76	left	N/A	0.097	1.076	0.104	
836.60	4183	UMTS 850	RMC	24.5	23.54	-0.01	10 mm	80B93	N/A	1:1	back	State 15	0.481	1.247	0.600	
836.60	4183	UMTS 850	RMC	24.5	23.54	0.00	10 mm	80B93	N/A	1:1	front	State 15	0.564	1.247	0.703	A18
836.60	4183	UMTS 850	RMC	24.5	23.54	-0.03	10 mm	80B93	N/A	1:1	bottom	State 15	0.267	1.247	0.333	
836.60	4183	UMTS 850	RMC	24.5	23.54	0.01	10 mm	80B93	N/A	1:1	right	State 15	0.328	1.247	0.409	
836.60	4183	UMTS 850	RMC	24.5	23.54	0.06	10 mm	80B93	N/A	1:1	left	State 15	0.082	1.247	0.102	
1712.40	1312	UMTS 1750	RMC	22.0	21.80	0.08	10 mm	813EF	N/A	1:1	back	N/A	0.912	1.047	0.955	A20
1732.40	1412	UMTS 1750	RMC	22.0	21.76	0.10	10 mm	813EF	N/A	1:1	back	N/A	0.906	1.057	0.958	
1752.60	1513	UMTS 1750	RMC	22.0	21.59	0.13	10 mm	813EF	N/A	1:1	back	N/A	0.793	1.099	0.872	
1732.40	1412	UMTS 1750	RMC	22.0	21.76	0.17	10 mm	813EF	N/A	1:1	front	N/A	0.642	1.057	0.679	
1732.40	1412	UMTS 1750	RMC	22.0	21.76	-0.07	10 mm	813EF	N/A	1:1	bottom	N/A	0.685	1.057	0.724	
1732.40	1412	UMTS 1750	RMC	22.0	21.76	-0.01	10 mm	813EF	N/A	1:1	right	N/A	0.186	1.057	0.197	
1732.40	1412	UMTS 1750	RMC	22.0	21.76	0.04	10 mm	813EF	N/A	1:1	left	N/A	0.035	1.057	0.037	
1712.40	1312	UMTS 1750	RMC	22.0	21.80	0.16	10 mm	813EF	N/A	1:1	back	N/A	0.776	1.047	0.812	
1850.20	512	GSM 1900	GPRS	25.0	24.89	-0.13	10 mm	813EF	3	1:2.76	back	N/A	0.488	1.026	0.501	A22
1850.20	512	GSM 1900	GPRS	25.0	24.89	-0.06	10 mm	813EF	3	1:2.76	front	N/A	0.410	1.026	0.421	
1850.20	512	GSM 1900	GPRS	25.0	24.89	0.07	10 mm	813EF	3	1:2.76	bottom	N/A	0.440	1.026	0.451	
1850.20	512	GSM 1900	GPRS	25.0	24.89	0.12	10 mm	813EF	3	1:2.76	right	N/A	0.115	1.026	0.118	
1850.20	512	GSM 1900	GPRS	25.0	24.89	0.15	10 mm	813EF	3	1:2.76	left	N/A	0.024	1.026	0.025	
1880.00	9400	UMTS 1900	RMC	22.0	21.50	0.08	10 mm	813EF	N/A	1:1	back	N/A	0.608	1.122	0.682	A24
1880.00	9400	UMTS 1900	RMC	22.0	21.50	-0.04	10 mm	813EF	N/A	1:1	front	N/A	0.439	1.122	0.493	
1880.00	9400	UMTS 1900	RMC	22.0	21.50	0.03	10 mm	813EF	N/A	1:1	bottom	N/A	0.434	1.122	0.487	
1880.00	9400	UMTS 1900	RMC	22.0	21.50	-0.07	10 mm	813EF	N/A	1:1	right	N/A	0.120	1.122	0.135	
1880.00	9400	UMTS 1900	RMC	22.0	21.50	0.14	10 mm	813EF	N/A	1:1	left	N/A	0.025	1.122	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body									
Spatial Peak							1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population							averaged over 1 gram									

Note: blue entry represents variability data

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 56 of 77

Table 11-20
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																	
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	-0.05	0	80B93	QPSK	1	0	10 mm	back	1:1	0.220	1.146	0.252
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	-0.04	1	80B93	QPSK	25	12	10 mm	back	1:1	0.173	1.146	0.198
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	0.06	0	80B93	QPSK	1	0	10 mm	front	1:1	0.229	1.146	0.262
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	0.03	1	80B93	QPSK	25	12	10 mm	front	1:1	0.206	1.146	0.236
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	0.13	0	80B93	QPSK	1	0	10 mm	bottom	1:1	0.108	1.146	0.124
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	0.19	1	80B93	QPSK	25	12	10 mm	bottom	1:1	0.081	1.146	0.093
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	0.07	0	80B93	QPSK	1	0	10 mm	right	1:1	0.056	1.146	0.064
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	0.00	1	80B93	QPSK	25	12	10 mm	right	1:1	0.052	1.146	0.060
707.50	23095	Mid	LTE Band 12	10	23.0	22.41	0.09	0	80B93	QPSK	1	0	10 mm	left	1:1	0.048	1.146	0.055
707.50	23095	Mid	LTE Band 12	10	22.0	21.41	-0.02	1	80B93	QPSK	25	12	10 mm	left	1:1	0.037	1.146	0.042
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-21
LTE Band 13 Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																	
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	0.09	0	80B93	QPSK	1	25	10 mm	back	1:1	0.241	1.132	0.273
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.01	1	80B93	QPSK	25	25	10 mm	back	1:1	0.189	1.164	0.220
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	0.02	0	80B93	QPSK	1	25	10 mm	front	1:1	0.255	1.132	0.289
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.01	1	80B93	QPSK	25	25	10 mm	front	1:1	0.200	1.164	0.233
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	0.00	0	80B93	QPSK	1	25	10 mm	bottom	1:1	0.122	1.132	0.138
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.06	1	80B93	QPSK	25	25	10 mm	bottom	1:1	0.099	1.164	0.115
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	-0.07	0	80B93	QPSK	1	25	10 mm	right	1:1	0.183	1.132	0.207
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.11	1	80B93	QPSK	25	25	10 mm	right	1:1	0.133	1.164	0.155
782.00	23230	Mid	LTE Band 13	10	23.0	22.46	-0.06	0	80B93	QPSK	1	25	10 mm	left	1:1	0.026	1.132	0.029
782.00	23230	Mid	LTE Band 13	10	22.0	21.34	0.12	1	80B93	QPSK	25	25	10 mm	left	1:1	0.017	1.164	0.020
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-22
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	State	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	-0.02	0	80B93	QPSK	1	0	10 mm	back	1:1	State 15	0.456	1.146	0.523	A30
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	-0.07	1	80B93	QPSK	25	0	10 mm	back	1:1	State 15	0.329	1.268	0.417	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	-0.02	0	80B93	QPSK	1	0	10 mm	front	1:1	State 15	0.566	1.146	0.649	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	-0.02	1	80B93	QPSK	25	0	10 mm	front	1:1	State 15	0.381	1.268	0.483	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	0.17	0	80B93	QPSK	1	0	10 mm	bottom	1:1	State 15	0.289	1.146	0.331	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	-0.09	1	80B93	QPSK	25	0	10 mm	bottom	1:1	State 15	0.201	1.268	0.255	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	-0.01	0	80B93	QPSK	1	0	10 mm	right	1:1	State 15	0.277	1.146	0.317	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	0.00	1	80B93	QPSK	25	0	10 mm	right	1:1	State 15	0.211	1.268	0.268	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.91	0.18	0	80B93	QPSK	1	0	10 mm	left	1:1	State 15	0.066	1.146	0.076	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.47	0.05	1	80B93	QPSK	25	0	10 mm	left	1:1	State 15	0.067	1.268	0.085	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram												

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 57 of 77

Table 11-23
LTE Band 26 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	-0.09	0	80B93	QPSK	1	0	10 mm	back	1:1	0.374	1.119	0.419	A32
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.07	1	80B93	QPSK	36	0	10 mm	back	1:1	0.308	1.119	0.345	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	-0.12	0	80B93	QPSK	1	0	10 mm	front	1:1	0.360	1.119	0.403	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.12	1	80B93	QPSK	36	0	10 mm	front	1:1	0.299	1.119	0.335	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	0.02	0	80B93	QPSK	1	0	10 mm	bottom	1:1	0.190	1.119	0.213	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.03	1	80B93	QPSK	36	0	10 mm	bottom	1:1	0.159	1.119	0.178	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	0.03	0	80B93	QPSK	1	0	10 mm	right	1:1	0.199	1.119	0.223	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.02	1	80B93	QPSK	36	0	10 mm	right	1:1	0.161	1.119	0.180	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.0	22.51	0.20	0	80B93	QPSK	1	0	10 mm	left	1:1	0.041	1.119	0.046	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.0	21.51	0.11	1	80B93	QPSK	36	0	10 mm	left	1:1	0.048	1.119	0.054	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-24
LTE Band 4 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	20.00	0.01	0	813EF	QPSK	1	0	10 mm	back	1:1	0.581	1.000	0.581	A34
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	19.61	0.10	0	813EF	QPSK	50	50	10 mm	back	1:1	0.535	1.094	0.585	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	20.00	0.01	0	813EF	QPSK	1	0	10 mm	front	1:1	0.449	1.000	0.449	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	19.61	0.03	0	813EF	QPSK	50	50	10 mm	front	1:1	0.405	1.094	0.443	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	20.00	0.05	0	813EF	QPSK	1	0	10 mm	bottom	1:1	0.390	1.000	0.390	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	19.61	0.02	0	813EF	QPSK	50	50	10 mm	bottom	1:1	0.356	1.094	0.389	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	20.00	0.00	0	813EF	QPSK	1	0	10 mm	right	1:1	0.130	1.000	0.130	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	19.61	0.03	0	813EF	QPSK	50	50	10 mm	right	1:1	0.112	1.094	0.123	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	20.00	0.09	0	813EF	QPSK	1	0	10 mm	left	1:1	0.024	1.000	0.024	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	20.0	19.61	-0.06	0	813EF	QPSK	50	50	10 mm	left	1:1	0.022	1.094	0.024	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 58 of 77

Table 11-25
LTE Band 25 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR(1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.0	22.42	0.10	0	80B93	QPSK	1	0	10 mm	back	1:1	0.828	1.143	0.946	A36
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.0	22.55	0.11	0	80B93	QPSK	1	0	10 mm	back	1:1	0.861	1.109	0.955	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.12	0	80B93	QPSK	1	0	10 mm	back	1:1	0.889	1.076	0.957	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.0	21.15	0.08	1	80B93	QPSK	50	0	10 mm	back	1:1	0.664	1.216	0.807	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.13	1	80B93	QPSK	50	0	10 mm	back	1:1	0.693	1.189	0.824	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.24	0.12	1	80B93	QPSK	50	0	10 mm	back	1:1	0.725	1.191	0.863	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.21	0.06	1	80B93	QPSK	100	0	10 mm	back	1:1	0.708	1.199	0.849	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.0	22.42	0.06	0	80B93	QPSK	1	0	10 mm	front	1:1	0.668	1.143	0.764	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.0	22.55	0.08	0	80B93	QPSK	1	0	10 mm	front	1:1	0.710	1.109	0.787	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.07	0	80B93	QPSK	1	0	10 mm	front	1:1	0.755	1.076	0.812	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.08	1	80B93	QPSK	50	0	10 mm	front	1:1	0.574	1.189	0.682	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.21	0.05	1	80B93	QPSK	100	0	10 mm	front	1:1	0.590	1.199	0.707	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.0	22.42	-0.04	0	80B93	QPSK	1	0	10 mm	bottom	1:1	0.742	1.143	0.848	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.0	22.55	-0.05	0	80B93	QPSK	1	0	10 mm	bottom	1:1	0.773	1.109	0.857	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.09	0	80B93	QPSK	1	0	10 mm	bottom	1:1	0.830	1.076	0.893	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	-0.01	1	80B93	QPSK	50	0	10 mm	bottom	1:1	0.606	1.189	0.721	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.21	-0.06	1	80B93	QPSK	100	0	10 mm	bottom	1:1	0.626	1.199	0.751	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	-0.04	0	80B93	QPSK	1	0	10 mm	right	1:1	0.206	1.076	0.222	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.04	1	80B93	QPSK	50	0	10 mm	right	1:1	0.160	1.189	0.190	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.11	0	80B93	QPSK	1	0	10 mm	left	1:1	0.042	1.076	0.045	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	21.25	0.14	1	80B93	QPSK	50	0	10 mm	left	1:1	0.032	1.189	0.038	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.68	0.07	0	80B93	QPSK	1	0	10 mm	back	1:1	0.849	1.076	0.914	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										

Note: blue entry represents variability data

Table 11-26
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	-0.06	0	81029	QPSK	1	0	10 mm	back	1:1.58	0.264	1.028	0.271	
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	0.03	1	81029	QPSK	50	0	10 mm	back	1:1.58	0.214	1.045	0.224	
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	-0.02	0	81029	QPSK	1	0	10 mm	front	1:1.58	0.250	1.028	0.257	
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	0.01	1	81029	QPSK	50	0	10 mm	front	1:1.58	0.198	1.045	0.207	
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	-0.04	0	81029	QPSK	1	0	10 mm	bottom	1:1.58	0.499	1.028	0.513	A38
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	-0.06	1	81029	QPSK	50	0	10 mm	bottom	1:1.58	0.396	1.045	0.414	
2506.00	39750	Low	LTE Band 41	20	23.5	23.38	-0.04	0	81029	QPSK	1	0	10 mm	left	1:1.58	0.108	1.028	0.111	
2506.00	39750	Low	LTE Band 41	20	22.5	22.31	0.05	1	81029	QPSK	50	0	10 mm	left	1:1.58	0.088	1.045	0.092	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 59 of 77

**Table 11-27
WLAN Hotspot SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)
MHz	Ch.													W/kg	(W/kg)			(W/kg)
2412	1	802.11b	DSSS	22	19.5	19.41	0.05	10 mm	1	0C6B5	1	back	99.8	0.448	0.366	1.021	1.002	0.375
2412	1	802.11b	DSSS	22	19.5	19.41	-	10 mm	1	0C6B5	1	front	99.8	0.285	-	1.021	1.002	-
2412	1	802.11b	DSSS	22	19.5	19.41	-	10 mm	1	0C6B5	1	top	99.8	0.064	-	1.021	1.002	-
2412	1	802.11b	DSSS	22	19.5	19.41	-	10 mm	1	0C6B5	1	left	99.8	0.090	-	1.021	1.002	-
2437	6	802.11b	DSSS	22	19.5	18.93	0.18	10 mm	2	0C6B5	1	back	99.8	0.256	0.228	1.140	1.002	0.261
2437	6	802.11b	DSSS	22	19.5	18.93	-	10 mm	2	0C6B5	1	front	99.8	0.188	-	1.140	1.002	-
2437	6	802.11b	DSSS	22	19.5	18.93	-	10 mm	2	0C6B5	1	top	99.8	0.204	-	1.140	1.002	-
2437	6	802.11b	DSSS	22	19.5	18.93	-	10 mm	2	0C6B5	1	right	99.8	0.009	-	1.140	1.002	-
2437	6	802.11b	DSSS	22	19.5	18.93	-	10 mm	2	0C6B5	1	left	99.8	0.015	-	1.140	1.002	-
5825	165	802.11a	OFDM	20	16.5	16.31	0.12	10 mm	1	00580	6	back	98.7	0.325	0.144	1.045	1.013	0.152
5825	165	802.11a	OFDM	20	16.5	16.31	-	10 mm	1	00580	6	front	98.7	0.090	-	1.045	1.013	-
5825	165	802.11a	OFDM	20	16.5	16.31	-	10 mm	1	00580	6	top	98.7	0.116	-	1.045	1.013	-
5825	165	802.11a	OFDM	20	16.5	16.31	-	10 mm	1	00580	6	left	98.7	0.104	-	1.045	1.013	-
5745	149	802.11a	OFDM	20	16.5	16.20	0.13	10 mm	2	00580	6	back	98.2	0.366	0.207	1.072	1.018	0.226
5745	149	802.11a	OFDM	20	16.5	16.20	-	10 mm	2	00580	6	front	98.2	0.301	-	1.072	1.018	-
5745	149	802.11a	OFDM	20	16.5	16.20	-	10 mm	2	00580	6	top	98.2	0.168	-	1.072	1.018	-
5745	149	802.11a	OFDM	20	16.5	16.20	-	10 mm	2	00580	6	left	98.2	0.032	-	1.072	1.018	-
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body										
Spatial Peak								1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 1 gram										

11.3 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
- During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.6 for more details).
- This device supports dynamic antenna tuning for some low frequency bands. Per FCC Guidance, SAR was measured according to the normally required SAR measurement configurations with the tuner active. The auto-tune state determined by the device was verified before and after each SAR measurement and is listed in the tables above. Please see Section 14 for supplemental data.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 60 of 77

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported (scaled) for LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 61 of 77

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.6.6 for more information.
4. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06. Please see Section 12 for complete analysis.
5. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
6. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 62 of 77

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	10.50	15	0.154

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 63 of 77

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.267	0.344	0.377	0.611	0.644	0.988
	UMTS 850	0.254	0.344	0.377	0.598	0.631	0.975
	UMTS 1750	0.124	0.344	0.377	0.468	0.501	0.845
	GSM 1900	0.067	0.344	0.377	0.411	0.444	0.788
	UMTS 1900	0.064	0.344	0.377	0.408	0.441	0.785
	LTE Band 12	0.064	0.344	0.377	0.408	0.441	0.785
	LTE Band 13	0.088	0.344	0.377	0.432	0.465	0.809
	LTE Band 5 (Cell)	0.226	0.344	0.377	0.570	0.603	0.947
	LTE Band 26 (Cell)	0.149	0.344	0.377	0.493	0.526	0.870
	LTE Band 4 (AWS)	0.088	0.344	0.377	0.432	0.465	0.809
	LTE Band 25 (PCS)	0.066	0.344	0.377	0.410	0.443	0.787
	LTE Band 41	0.085	0.344	0.377	0.429	0.462	0.806

Table 12-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.267	0.209	0.557	0.476	0.824	1.033
	UMTS 850	0.254	0.209	0.557	0.463	0.811	1.020
	UMTS 1750	0.124	0.209	0.557	0.333	0.681	0.890
	GSM 1900	0.067	0.209	0.557	0.276	0.624	0.833
	UMTS 1900	0.064	0.209	0.557	0.273	0.621	0.830
	LTE Band 12	0.064	0.209	0.557	0.273	0.621	0.830
	LTE Band 13	0.088	0.209	0.557	0.297	0.645	0.854
	LTE Band 5 (Cell)	0.226	0.209	0.557	0.435	0.783	0.992
	LTE Band 26 (Cell)	0.149	0.209	0.557	0.358	0.706	0.915
	LTE Band 4 (AWS)	0.088	0.209	0.557	0.297	0.645	0.854
	LTE Band 25 (PCS)	0.066	0.209	0.557	0.275	0.623	0.832
	LTE Band 41	0.085	0.209	0.557	0.294	0.642	0.851

FCC ID: A3LSMG935F		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset			Page 64 of 77

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.267	0.344	0.557	0.611	0.824	1.168
	UMTS 850	0.254	0.344	0.557	0.598	0.811	1.155
	UMTS 1750	0.124	0.344	0.557	0.468	0.681	1.025
	GSM 1900	0.067	0.344	0.557	0.411	0.624	0.968
	UMTS 1900	0.064	0.344	0.557	0.408	0.621	0.965
	LTE Band 12	0.064	0.344	0.557	0.408	0.621	0.965
	LTE Band 13	0.088	0.344	0.557	0.432	0.645	0.989
	LTE Band 5 (Cell)	0.226	0.344	0.557	0.570	0.783	1.127
	LTE Band 26 (Cell)	0.149	0.344	0.557	0.493	0.706	1.050
	LTE Band 4 (AWS)	0.088	0.344	0.557	0.432	0.645	0.989
	LTE Band 25 (PCS)	0.066	0.344	0.557	0.410	0.623	0.967
	LTE Band 41	0.085	0.344	0.557	0.429	0.642	0.986

Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz Ant 2 and 5 GHz Ant 1 WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.267	0.377	0.209	0.644	0.476	0.853
	UMTS 850	0.254	0.377	0.209	0.631	0.463	0.840
	UMTS 1750	0.124	0.377	0.209	0.501	0.333	0.710
	GSM 1900	0.067	0.377	0.209	0.444	0.276	0.653
	UMTS 1900	0.064	0.377	0.209	0.441	0.273	0.650
	LTE Band 12	0.064	0.377	0.209	0.441	0.273	0.650
	LTE Band 13	0.088	0.377	0.209	0.465	0.297	0.674
	LTE Band 5 (Cell)	0.226	0.377	0.209	0.603	0.435	0.812
	LTE Band 26 (Cell)	0.149	0.377	0.209	0.526	0.358	0.735
	LTE Band 4 (AWS)	0.088	0.377	0.209	0.465	0.297	0.674
	LTE Band 25 (PCS)	0.066	0.377	0.209	0.443	0.275	0.652
	LTE Band 41	0.085	0.377	0.209	0.462	0.294	0.671

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 65 of 77

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-6
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.458	0.148	0.122	0.606	0.580	0.728
	UMTS 850	0.344	0.148	0.122	0.492	0.466	0.614
	UMTS 1750	0.656	0.148	0.122	0.804	0.778	0.926
	GSM 1900	0.452	0.148	0.122	0.600	0.574	0.722
	UMTS 1900	0.472	0.148	0.122	0.620	0.594	0.742
	LTE Band 12	0.152	0.148	0.122	0.300	0.274	0.422
	LTE Band 13	0.194	0.148	0.122	0.342	0.316	0.464
	LTE Band 5 (Cell)	0.316	0.148	0.122	0.464	0.438	0.586
	LTE Band 26 (Cell)	0.226	0.148	0.122	0.374	0.348	0.496
	LTE Band 4 (AWS)	0.509	0.148	0.122	0.657	0.631	0.779
	LTE Band 25 (PCS)	0.398	0.148	0.122	0.546	0.520	0.668
	LTE Band 41	0.259	0.148	0.122	0.407	0.381	0.529

Table 12-7
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.458	0.153	0.335	0.611	0.793	0.946
	UMTS 850	0.344	0.153	0.335	0.497	0.679	0.832
	UMTS 1750	0.656	0.153	0.335	0.809	0.991	1.144
	GSM 1900	0.452	0.153	0.335	0.605	0.787	0.940
	UMTS 1900	0.472	0.153	0.335	0.625	0.807	0.960
	LTE Band 12	0.152	0.153	0.335	0.305	0.487	0.640
	LTE Band 13	0.194	0.153	0.335	0.347	0.529	0.682
	LTE Band 5 (Cell)	0.316	0.153	0.335	0.469	0.651	0.804
	LTE Band 26 (Cell)	0.226	0.153	0.335	0.379	0.561	0.714
	LTE Band 4 (AWS)	0.509	0.153	0.335	0.662	0.844	0.997
	LTE Band 25 (PCS)	0.398	0.153	0.335	0.551	0.733	0.886
	LTE Band 41	0.259	0.153	0.335	0.412	0.594	0.747

FCC ID: A3LSMG935F		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset			Page 66 of 77

Table 12-8

Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.458	0.148	0.335	0.606	0.793	0.941
	UMTS 850	0.344	0.148	0.335	0.492	0.679	0.827
	UMTS 1750	0.656	0.148	0.335	0.804	0.991	1.139
	GSM 1900	0.452	0.148	0.335	0.600	0.787	0.935
	UMTS 1900	0.472	0.148	0.335	0.620	0.807	0.955
	LTE Band 12	0.152	0.148	0.335	0.300	0.487	0.635
	LTE Band 13	0.194	0.148	0.335	0.342	0.529	0.677
	LTE Band 5 (Cell)	0.316	0.148	0.335	0.464	0.651	0.799
	LTE Band 26 (Cell)	0.226	0.148	0.335	0.374	0.561	0.709
	LTE Band 4 (AWS)	0.509	0.148	0.335	0.657	0.844	0.992
	LTE Band 25 (PCS)	0.398	0.148	0.335	0.546	0.733	0.881
	LTE Band 41	0.259	0.148	0.335	0.407	0.594	0.742

Table 12-9

Simultaneous Transmission Scenario with 2.4 GHz Ant 2 and 5 GHz Ant 1 WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.458	0.122	0.153	0.580	0.611	0.733
	UMTS 850	0.344	0.122	0.153	0.466	0.497	0.619
	UMTS 1750	0.656	0.122	0.153	0.778	0.809	0.931
	GSM 1900	0.452	0.122	0.153	0.574	0.605	0.727
	UMTS 1900	0.472	0.122	0.153	0.594	0.625	0.747
	LTE Band 12	0.152	0.122	0.153	0.274	0.305	0.427
	LTE Band 13	0.194	0.122	0.153	0.316	0.347	0.469
	LTE Band 5 (Cell)	0.316	0.122	0.153	0.438	0.469	0.591
	LTE Band 26 (Cell)	0.226	0.122	0.153	0.348	0.379	0.501
	LTE Band 4 (AWS)	0.509	0.122	0.153	0.631	0.662	0.784
	LTE Band 25 (PCS)	0.398	0.122	0.153	0.520	0.551	0.673
	LTE Band 41	0.259	0.122	0.153	0.381	0.412	0.534

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 67 of 77

Table 12-10
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 850	0.458	0.154	0.612
	UMTS 850	0.344	0.154	0.498
	UMTS 1750	0.656	0.154	0.810
	GSM 1900	0.452	0.154	0.606
	UMTS 1900	0.472	0.154	0.626
	LTE Band 12	0.152	0.154	0.306
	LTE Band 13	0.194	0.154	0.348
	LTE Band 5 (Cell)	0.316	0.154	0.470
	LTE Band 26 (Cell)	0.226	0.154	0.380
	LTE Band 4 (AWS)	0.509	0.154	0.663
	LTE Band 25 (PCS)	0.398	0.154	0.552
	LTE Band 41	0.259	0.154	0.413

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 68 of 77

12.5 Hotspot SAR Simultaneous Transmission Analysis

Table 12-11
Simultaneous Transmission Scenario 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.735	0.375	0.261	1.110	0.996	1.371
	UMTS 850	0.703	0.375	0.261	1.078	0.964	1.339
	UMTS 1750	0.958	0.375	0.261	1.333	1.219	1.594
	GPRS 1900	0.501	0.375	0.261	0.876	0.762	1.137
	UMTS 1900	0.682	0.375	0.261	1.057	0.943	1.318
	LTE Band 12	0.262	0.375	0.261	0.637	0.523	0.898
	LTE Band 13	0.289	0.375	0.261	0.664	0.550	0.925
	LTE Band 5 (Cell)	0.649	0.375	0.261	1.024	0.910	1.285
	LTE Band 26 (Cell)	0.419	0.375	0.261	0.794	0.680	1.055
	LTE Band 4 (AWS)	0.585	0.375	0.261	0.960	0.846	1.221
	LTE Band 25 (PCS)	0.957	0.375	0.261	1.332	1.218	1.593
	LTE Band 41	0.513	0.375	0.261	0.888	0.774	1.149

Table 12-12
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.735	0.152	0.226	0.887	0.961	1.113
	UMTS 850	0.703	0.152	0.226	0.855	0.929	1.081
	UMTS 1750	0.958	0.152	0.226	1.110	1.184	1.336
	GPRS 1900	0.501	0.152	0.226	0.653	0.727	0.879
	UMTS 1900	0.682	0.152	0.226	0.834	0.908	1.060
	LTE Band 12	0.262	0.152	0.226	0.414	0.488	0.640
	LTE Band 13	0.289	0.152	0.226	0.441	0.515	0.667
	LTE Band 5 (Cell)	0.649	0.152	0.226	0.801	0.875	1.027
	LTE Band 26 (Cell)	0.419	0.152	0.226	0.571	0.645	0.797
	LTE Band 4 (AWS)	0.585	0.152	0.226	0.737	0.811	0.963
	LTE Band 25 (PCS)	0.957	0.152	0.226	1.109	1.183	1.335
	LTE Band 41	0.513	0.152	0.226	0.665	0.739	0.891

FCC ID: A3LSMG935F		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset			Page 69 of 77

Table 12-13
Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.735	0.375	0.226	1.110	0.961	1.336
	UMTS 850	0.703	0.375	0.226	1.078	0.929	1.304
	UMTS 1750	0.958	0.375	0.226	1.333	1.184	1.559
	GPRS 1900	0.501	0.375	0.226	0.876	0.727	1.102
	UMTS 1900	0.682	0.375	0.226	1.057	0.908	1.283
	LTE Band 12	0.262	0.375	0.226	0.637	0.488	0.863
	LTE Band 13	0.289	0.375	0.226	0.664	0.515	0.890
	LTE Band 5 (Cell)	0.649	0.375	0.226	1.024	0.875	1.250
	LTE Band 26 (Cell)	0.419	0.375	0.226	0.794	0.645	1.020
	LTE Band 4 (AWS)	0.585	0.375	0.226	0.960	0.811	1.186
	LTE Band 25 (PCS)	0.957	0.375	0.226	1.332	1.183	1.558
	LTE Band 41	0.513	0.375	0.226	0.888	0.739	1.114

Table 12-14
Simultaneous Transmission Scenario with 2.4 GHz Ant 2 and 5 GHz Ant 1 WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.735	0.261	0.152	0.996	0.887	1.148
	UMTS 850	0.703	0.261	0.152	0.964	0.855	1.116
	UMTS 1750	0.958	0.261	0.152	1.219	1.110	1.371
	GPRS 1900	0.501	0.261	0.152	0.762	0.653	0.914
	UMTS 1900	0.682	0.261	0.152	0.943	0.834	1.095
	LTE Band 12	0.262	0.261	0.152	0.523	0.414	0.675
	LTE Band 13	0.289	0.261	0.152	0.550	0.441	0.702
	LTE Band 5 (Cell)	0.649	0.261	0.152	0.910	0.801	1.062
	LTE Band 26 (Cell)	0.419	0.261	0.152	0.680	0.571	0.832
	LTE Band 4 (AWS)	0.585	0.261	0.152	0.846	0.737	0.998
	LTE Band 25 (PCS)	0.957	0.261	0.152	1.218	1.109	1.370
	LTE Band 41	0.513	0.261	0.152	0.774	0.665	0.926

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 70 of 77

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1712.40	1312	UMTS 1750	RMC	back	10 mm	0.912	0.776	1.18	N/A	N/A	N/A	N/A
1900	1905.00	26590	LTE Band 25 (PCS), 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	back	10 mm	0.889	0.849	1.05	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body							
Spatial Peak						1.6 W/kg (mW/g)							
Uncontrolled Exposure/General Population						averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 71 of 77

14 ADDITIONAL TESTING PER FCC GUIDANCE

The following test procedures were followed to demonstrate that the SAR results in Section 11 represented the appropriate SAR test conditions. For bands with dynamic tuning implemented, SAR was measured according to the required FCC SAR test procedures with the dynamic tuner active to allow the device to automatically tune to the antenna state for the respective RF exposure test configurations. Additional single point SAR time-sweep measurements were evaluated for other tuner states to determine that the other tuner configurations would result in equivalent or lower SAR values. The additional tuner hardware has no influence to the antenna characteristics, other than impedance matching.

To evaluate all of the tuner states, the 25 tuner states were divided evenly among band, mode and exposure combinations so that at least one single point SAR measurement was measured among the configurations. Single point time-sweep measurements were performed at the peak SAR location determined by the zoom scan of the configuration with the highest reported SAR for each combination. While inserting and removing the USB cable between single point SAR measurements, the device was ensured to capture the same physical point SAR that generated the highest SAR.

The operational description contains more information about the design and implementation of the dynamic antenna tuning.

Table 14-1
Supplemental Head SAR Data

Mode	Service/ Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)							
									Auto-Tune (State 15)	Default (State 15)	State 1	State 6	State 16	State 19	State 24	State 25
LTE B5	QPSK	836.5	20525	1	0	Right Cheek	N/A	0.197	0.214	0.230	0.226	0.227	0.214	0.225	0.222	0.220
Mode	Service/ Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)							
									Auto-Tune (State 15)	Default (State 15)	State 2	State 4	State 9	State 12	State 13	State 21
UMTS B5	RMC	836.6	4183	N/A	N/A	Right Cheek	N/A	0.204	0.215	0.215	0.210	0.213	0.211	0.217	0.213	0.205

Table 14-2
Supplemental Body SAR Data

Mode	Service/ Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)							
									Auto-Tune (State 15)	Default (State 15)	State 3	State 7	State 11	State 17	State 20	State 22
LTE B5	QPSK	836.5	20525	1	0	Front Side	10 mm	0.566	0.681	0.710	0.665	0.706	0.677	0.686	0.664	0.674
Mode	Service/ Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)							
									Auto-Tune (State 15)	Default (State 15)	State 5	State 8	State 10	State 14	State 18	State 23
UMTS B5	RMC	836.6	4183	N/A	N/A	Front Side	10 mm	0.564	0.627	0.606	0.605	0.606	0.610	0.530	0.619	0.456

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 72 of 77

15 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8357D	(250MHz-20GHz) Signal Generator	3/15/2015	Annual	3/15/2016	MY45470194
Agilent	8994A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8648D	(9kHz-40GHz) Signal Generator	3/15/2015	Annual	3/15/2016	3629U00687
Agilent	E4438C	ESG Vector Signal Generator	3/13/2015	Annual	3/13/2016	MY42082385
Agilent	E4438C	ESG Vector Signal Generator	3/12/2015	Annual	3/12/2016	MY45090700
Agilent	N9020A	MXA Signal Analyzer	11/5/2015	Annual	11/5/2016	US46470561
Agilent	N5182A	MXG Vector Signal Generator	3/16/2015	Annual	3/16/2016	MY47420651
Agilent	N5182A	MXG Vector Signal Generator	3/16/2015	Annual	3/16/2016	MY47420800
Agilent	8753ES	Network Analyzer	3/20/2015	Annual	3/20/2016	MY40001472
Agilent	E5515C	Wireless Communications Test Set	6/18/2015	Biennial	6/18/2017	GB41450275
Agilent	E5515C	Wireless Communications Test Set	5/16/2015	Biennial	5/16/2017	GB43304447
Agilent	E5515C	Wireless Communications Test Set	4/13/2015	Annual	4/13/2016	GB43460554
Amplifier Research	1551G6	Amplifier	N/A	CBT	N/A	439971
Amplifier Research	1551G6	Amplifier	N/A	CBT	N/A	439972
Amplifier Research	1551G6	Amplifier	N/A	CBT	N/A	439977
Amplifier Research	1551G6	Amplifier	N/A	CBT	N/A	439978
Anritsu	ML2438A	Power Meter	3/13/2015	Annual	3/13/2016	1070030
Anritsu	ML2438A	Power Meter	3/13/2015	Annual	3/13/2016	1190013
Anritsu	MA2495A	Power Meter	10/16/2015	Biennial	10/15/2017	941001
Anritsu	MA2481A	Power Sensor	3/10/2015	Annual	3/10/2016	2400
Anritsu	MA2481A	Power Sensor	3/11/2015	Annual	3/11/2016	5318
Anritsu	MA2411B	Pulse Power Sensor	8/3/2015	Annual	8/3/2016	1126066
Anritsu	MA2411B	Pulse Power Sensor	3/13/2015	Annual	3/13/2016	1207470
Anritsu	MT8820C	Radio Communication Analyzer	7/24/2015	Annual	7/24/2016	6200901190
Anritsu	MT8820C	Radio Communication Analyzer	11/12/2015	Annual	11/12/2016	6201144418
Anritsu	MT8820C	Radio Communication Analyzer	12/4/2015	Annual	12/4/2016	6201300731
Anritsu	MA2410GA	USB Power Sensor	5/29/2015	Annual	5/29/2016	1231535
Anritsu	MA2410GA	USB Power Sensor	5/29/2015	Annual	5/29/2016	1231538
Anritsu	MA2410GA	USB Power Sensor	3/11/2015	Annual	3/11/2016	1349509
Anritsu	MA2410GA	USB Power Sensor	3/11/2015	Annual	3/11/2016	1349514
COMTECH	AR85729-5	Solid State Amplifier	N/A	CBT	N/A	M155A00-009
COMTECH	AR85729-5/57598	Solid State Amplifier	N/A	CBT	N/A	M3W1A00-1002
Control Company	4040	Digital Thermometer	3/18/2015	Biennial	3/18/2017	150194895
Control Company	4040	Digital Thermometer	3/18/2015	Biennial	3/18/2017	150194896
Control Company	4353	Long Stem Thermometer	3/5/2015	Biennial	3/5/2017	150149534
Control Company	4353	Long Stem Thermometer	3/5/2015	Biennial	3/5/2017	150149565
Keysight	772D	Dual Directional Coupler	N/A	CBT	N/A	MY52180215
MCL	BW-N6W5+	6dB Attenuator	N/A	CBT	N/A	1139
MiniCircuits	VLF-6000+	Low Pass Filter	N/A	CBT	N/A	N/A
MiniCircuits	SLP-2400+	Low Pass Filter	N/A	CBT	N/A	R8879500903
Mini-Circuits	BW-N 20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	N/A	CBT	N/A	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	N/A	CBT	N/A	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	N/A	CBT	N/A	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	N/A	CBT	N/A	1226
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264165
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	N/A	CBT	N/A	N/A
Narda	BW-S3W2	Attenuator (3dB)	N/A	CBT	N/A	120
Narda	4772-3	Attenuator (3dB)	N/A	CBT	N/A	9406
Pasternack	PE2208-6	Bidirectional Coupler	N/A	CBT	N/A	N/A
Pasternack	PE2209-10	Bidirectional Coupler	N/A	CBT	N/A	N/A
Pasternack	NC-100	Torque Wrench	N/A	CBT	N/A	N/A
Pasternack	NC-100	Torque Wrench	5/21/2015	Biennial	5/21/2017	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	6/3/2015	Annual	6/3/2016	109892
Rohde & Schwarz	CMU200	Base Station Simulator	12/2/2015	Annual	12/2/2016	833855/0010
Rohde & Schwarz	NIRV0	Dual Channel Power Meter	N/A	CBT	N/A	101695
Rohde & Schwarz	NIRV-232	Peak Power Sensor	N/A	CBT	N/A	836019/013
Rohde & Schwarz	CMW500	Radio Communication Tester	10/13/2015	Annual	10/13/2016	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	4/22/2015	Annual	4/22/2016	101699
Rohde & Schwarz	CMW500	Radio Communication Tester	3/18/2015	Annual	3/18/2016	128633
Rohde & Schwarz	CMW500	Radio Communication Tester	4/8/2015	Annual	4/8/2016	140148
Rohde & Schwarz	SMEO6	Signal Generator	N/A	CBT	N/A	832026
Rohde & Schwarz	SMQ03B	Signal Generator	N/A	CBT	N/A	DE27259
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	22313
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	N/A
SPEAG	D750V3	750 MHz SAR Dipole	1/16/2015	Annual	1/16/2016	1003
SPEAG	D750V3	750 MHz SAR Dipole	3/11/2015	Annual	3/11/2016	1054
SPEAG	D835V2	835 MHz SAR Dipole	7/23/2015	Annual	7/23/2016	44133
SPEAG	D835V2	835 MHz SAR Dipole	4/13/2015	Annual	4/13/2016	44119
SPEAG	D1900V2	1750 MHz SAR Dipole	4/15/2015	Annual	4/15/2016	1051
SPEAG	D1800V2	1900 MHz SAR Dipole	7/14/2015	Annual	7/14/2016	54149
SPEAG	D1900V2	1900 MHz SAR Dipole	4/14/2015	Annual	4/14/2016	54141
SPEAG	D2450V2	2450 MHz SAR Dipole	8/20/2015	Annual	8/20/2016	719
SPEAG	DS5GHV2	5 GHz SAR Dipole	9/16/2015	Annual	9/16/2016	1191
SPEAG	DS5GHV2	5 GHz SAR Dipole	2/17/2015	Annual	2/17/2016	1120
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/18/2015	Annual	2/18/2016	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/13/2015	Annual	3/13/2016	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/24/2015	Annual	8/24/2016	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/27/2015	Annual	10/27/2016	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/11/2015	Annual	11/11/2016	1415
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/17/2015	Annual	6/17/2016	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/20/2015	Annual	4/20/2016	1407
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/12/2015	Annual	5/12/2016	1070
SPEAG	DAK-3.5	Dielectric Assessment Kit	10/20/2015	Annual	10/20/2016	1091
SPEAG	ES30V2	SAR Probe	8/26/2015	Annual	8/26/2016	3022
SPEAG	ES30V3	SAR Probe	3/19/2015	Annual	3/19/2016	3319
SPEAG	ES30V3	SAR Probe	6/22/2015	Annual	6/22/2016	3351
SPEAG	ES30V3	SAR Probe	10/29/2015	Annual	10/29/2016	3333
SPEAG	ES30V4	SAR Probe	7/21/2015	Annual	7/21/2016	7308
SPEAG	ES30V3	SAR Probe	11/17/2015	Annual	11/17/2016	3334
SPEAG	ES30V3	SAR Probe	5/20/2015	Annual	5/20/2016	3263
SPEAG	ES30V4	SAR Probe	4/23/2015	Annual	4/23/2016	7357

Notes:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. All equipments were used within the respective calibration dates.

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by:
Document S/N:		DUT Type:		Quality Manager
0Y1512212182.A3L		Portable Handset		Page 73 of 77

16 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)						RSS	11.5	11.3
Expanded Uncertainty (95% CONFIDENCE LEVEL)						k=2	23.0	22.6

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 74 of 77

17 CONCLUSION

17.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMG935F		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset		Page 75 of 77

18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMG935F	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 76 of 77

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMG935F	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1512212182.A3L	Test Dates: 12/20/15 - 01/20/16	DUT Type: Portable Handset	Page 77 of 77

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.342$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-20-2015; Ambient Temp: 19.3°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.36 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.294 W/kg

SAR(1 g) = 0.227 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.342$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-20-2015; Ambient Temp: 19.3°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.34 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.265 W/kg

SAR(1 g) = 0.204 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 81029

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.323 \text{ S/m}$; $\epsilon_r = 38.563$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-30-2015; Ambient Temp: 24.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(5.24, 5.24, 5.24); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: AWS UMTS, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.840 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.145 W/kg

SAR(1 g) = 0.097 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.411 \text{ S/m}$; $\epsilon_r = 38.874$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-28-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(5.1, 5.1, 5.1); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.629 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.0860 W/kg

SAR(1 g) = 0.059 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 81029

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.411 \text{ S/m}$; $\epsilon_r = 38.874$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-28-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(5.1, 5.1, 5.1); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.223 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.0780 W/kg

SAR(1 g) = 0.052 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.852 \text{ S/m}$; $\epsilon_r = 42.306$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-21-2015; Ambient Temp: 24.5°C; Tissue Temp: 22.0°C

Probe: ES3DV2 - SN3022; ConvF(6.33, 6.33, 6.33); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/18/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Right Head, Cheek, Mid.ch
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.513 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.0660 W/kg

SAR(1 g) = 0.056 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.924 \text{ S/m}$; $\epsilon_r = 41.421$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-21-2015; Ambient Temp: 24.5°C; Tissue Temp: 22.0°C

Probe: ES3DV2 - SN3022; ConvF(6.33, 6.33, 6.33); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/18/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Right Head, Cheek, Mid.ch
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.738 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.0970 W/kg

SAR(1 g) = 0.078 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.913 \text{ S/m}$; $\epsilon_r = 39.827$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-23-2015; Ambient Temp: 23.5°C; Tissue Temp: 22.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.28 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.245 W/kg

SAR(1 g) = 0.197 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 26; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.913 \text{ S/m}$; $\epsilon_r = 39.827$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-23-2015; Ambient Temp: 23.5°C; Tissue Temp: 22.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 26 (Cell.), Right Head, Cheek, Mid.ch
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.78 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.166 W/kg

SAR(1 g) = 0.133 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 81029

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.323 \text{ S/m}$; $\epsilon_r = 38.562$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-30-2015; Ambient Temp: 24.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(5.24, 5.24, 5.24); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.470 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.114 W/kg

SAR(1 g) = 0.077 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 81029

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.439 \text{ S/m}$; $\epsilon_r = 38.756$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-28-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(5.1, 5.1, 5.1); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.379 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.0920 W/kg

SAR(1 g) = 0.061 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 8102F

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 1.91 \text{ S/m}$; $\epsilon_r = 39.439$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-30-2015; Ambient Temp: 24.0°C; Tissue Temp: 24.2°C

Probe: ES3DV3 - SN3333; ConvF(4.53, 4.53, 4.53); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 41, Left Head, Cheek, Low.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.726 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.153 W/kg

SAR(1 g) = 0.083 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 00580

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.807 \text{ S/m}$; $\epsilon_r = 38.709$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-15-2016; Ambient Temp: 22.7°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3319; ConvF(4.55, 4.55, 4.55); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Left Head,
Cheek, Ch 6, 1 Mbps, Ant 2**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.92 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.871 W/kg

SAR(1 g) = 0.368 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 0C6B5

Communication System: UID 0, IEEE 802.11ac; Frequency: 5775 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5775 \text{ MHz}$; $\sigma = 5.234 \text{ S/m}$; $\epsilon_r = 35.471$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-14-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7308; ConvF(4.86, 4.86, 4.86); Calibrated: 7/21/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11ac, U-NII-3, 80 MHz Bandwidth,
Left Head, Cheek, Ch 155, 29.3 Mbps, Ant2**


Area Scan 2 (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 9.586 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 3.30 W/kg

SAR(1 g) = 0.513 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.007 \text{ S/m}$; $\epsilon_r = 56.024$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-19-2016; Ambient Temp: 22.5°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.94 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.504 W/kg

SAR(1 g) = 0.389 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, GSM GPRS 3 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.76

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 54.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Front side, Mid.ch, 3 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 27.22 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.14 W/kg

SAR(1 g) = 0.683 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body, Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.002 \text{ S/m}$; $\epsilon_r = 55.345$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-17-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.92 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.384 W/kg

SAR(1 g) = 0.276 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 81031

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 54.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Front side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.05 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.934 W/kg

SAR(1 g) = 0.564 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 81029

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.469 \text{ S/m}$; $\epsilon_r = 51.733$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-06-2016; Ambient Temp: 24.2°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3333; ConvF(4.9, 4.9, 4.9); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: AWS UMTS, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.88 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.797 W/kg

SAR(1 g) = 0.515 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 813EF

Communication System: UID 0, UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1712.4 \text{ MHz}$; $\sigma = 1.448 \text{ S/m}$; $\epsilon_r = 51.782$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-06-2016; Ambient Temp: 24.2°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3333; ConvF(4.9, 4.9, 4.9); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: AWS UMTS, Body SAR, Back side, Low.ch


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.71 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.46 W/kg

SAR(1 g) = 0.912 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.56 \text{ S/m}$; $\epsilon_r = 53.175$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-11-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.51 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.657 W/kg

SAR(1 g) = 0.399 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 813EF

Communication System: UID 0, GSM GPRS 3 Tx slots; Frequency: 1850.2 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1850.2 \text{ MHz}$; $\sigma = 1.526 \text{ S/m}$; $\epsilon_r = 53.272$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-11-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Back side, Low.ch, 3 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.53 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.827 W/kg

SAR(1 g) = 0.488 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body, Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.56 \text{ S/m}$; $\epsilon_r = 53.175$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-11-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.12 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.630 W/kg

SAR(1 g) = 0.385 W/kg



0 dB = 0.451 W/kg = -3.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 813EF

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body, Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.56 \text{ S/m}$; $\epsilon_r = 53.175$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-11-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.96 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.608 W/kg



0 dB = 0.758 W/kg = -1.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body, Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.935 \text{ S/m}$; $\epsilon_r = 54.87$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-15-2016; Ambient Temp: 24.5°C; Tissue Temp: 23.9°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.38 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.191 W/kg

SAR(1 g) = 0.133 W/kg



0 dB = 0.150 W/kg = -8.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 55.288$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-30-2015; Ambient Temp: 23.8°C; Tissue Temp: 23.2°C

Probe: ES3DV2 - SN3022; ConvF(6.16, 6.16, 6.16); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/18/2015

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Body SAR, Front side, Mid.ch
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.10 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.403 W/kg

SAR(1 g) = 0.229 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body, Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 1.006 \text{ S/m}$; $\epsilon_r = 54.147$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-15-2016; Ambient Temp: 24.5°C; Tissue Temp: 23.9°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.39 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.230 W/kg

SAR(1 g) = 0.171 W/kg



0 dB = 0.191 W/kg = -7.19 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.999 \text{ S/m}$; $\epsilon_r = 54.487$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-30-2015; Ambient Temp: 23.8°C; Tissue Temp: 23.2°C

Probe: ES3DV2 - SN3022; ConvF(6.16, 6.16, 6.16); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/18/2015

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Body SAR, Front side, Mid.ch
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.44 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.429 W/kg

SAR(1 g) = 0.255 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body, Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.002 \text{ S/m}$; $\epsilon_r = 55.346$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-17-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.30 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.382 W/kg

SAR(1 g) = 0.276 W/kg



0 dB = 0.312 W/kg = -5.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body, Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.999 \text{ S/m}$; $\epsilon_r = 53.188$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-07-2016; Ambient Temp: 24.4°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Front side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.81 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.820 W/kg

SAR(1 g) = 0.566 W/kg



0 dB = 0.633 W/kg = -1.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 26; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body, Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.002 \text{ S/m}$; $\epsilon_r = 55.346$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-17-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.77 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.281 W/kg

SAR(1 g) = 0.202 W/kg



0 dB = 0.230 W/kg = -6.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 26; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body, Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 54.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.07 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.530 W/kg

SAR(1 g) = 0.374 W/kg



0 dB = 0.426 W/kg = -3.71 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 81029

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body, Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.491 \text{ S/m}$; $\epsilon_r = 51.938$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-14-2016; Ambient Temp: 24.4°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3334; ConvF(5.03, 5.03, 5.03); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.50 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.701 W/kg

SAR(1 g) = 0.445 W/kg



0 dB = 0.525 W/kg = -2.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 813EF

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body, Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.466 \text{ S/m}$; $\epsilon_r = 51.156$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-11-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.7°C

Probe: ES3DV3 - SN3351; ConvF(4.88, 4.88, 4.88); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.36 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.971 W/kg

SAR(1 g) = 0.581 W/kg



0 dB = 0.723 W/kg = -1.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.584 \text{ S/m}$; $\epsilon_r = 51.972$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-20-2016; Ambient Temp: 23.9°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.46 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.609 W/kg

SAR(1 g) = 0.370 W/kg



0 dB = 0.438 W/kg = -3.59 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80B93

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.569 \text{ S/m}$; $\epsilon_r = 52.152$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-31-2015; Ambient Temp: 23.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3319; ConvF(4.53, 4.53, 4.53); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.38 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 0.889 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 0C6B5

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body, Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.071 \text{ S/m}$; $\epsilon_r = 52.059$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-12-2016; Ambient Temp: 22.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.11, 4.11, 4.11); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Back side, Low.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.60 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.495 W/kg

SAR(1 g) = 0.252 W/kg



0 dB = 0.316 W/kg = -5.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 81029

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body, Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.055 \text{ S/m}$; $\epsilon_r = 50.781$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-23-2015; Ambient Temp: 19.6°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Bottom Edge, Low.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.82 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.00 W/kg

SAR(1 g) = 0.499 W/kg



0 dB = 0.645 W/kg = -1.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 0C6B5

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$; $\sigma = 1.938 \text{ S/m}$; $\epsilon_r = 52.446$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-12-2016; Ambient Temp: 22.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.11, 4.11, 4.11); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 01, 1 Mbps, Back Side, Ant 1


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.738 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.279 W/kg

SAR(1 g) = 0.145 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 0C6B5

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$; $\sigma = 1.938 \text{ S/m}$; $\epsilon_r = 52.446$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-12-2016; Ambient Temp: 22.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.11, 4.11, 4.11); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 01, 1 Mbps, Back Side, Ant 1


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.52 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.728 W/kg

SAR(1 g) = 0.366 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80D08

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5520 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5520 \text{ MHz}$; $\sigma = 5.727 \text{ S/m}$; $\epsilon_r = 48.253$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-12-2016; Ambient Temp: 23.8°C; Tissue Temp: 23.6°C

Probe: EX3DV4 - SN7357; ConvF(3.83, 3.83, 3.83); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, U-NII-2C, 20 MHz Bandwidth, Body SAR, Ch 104,
6 Mbps, Back Side, Ant 2**


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 7.566 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.316 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935F; Type: Portable Handset; Serial: 80D08

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 6.039 \text{ S/m}$; $\epsilon_r = 47.844$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-12-2016; Ambient Temp: 23.8°C; Tissue Temp: 23.6°C

Probe: EX3DV4 - SN7357; ConvF(3.82, 3.82, 3.82); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Body SAR, Ch 149,
6 Mbps, Back Side, Ant 2**


Area Scan (13x22x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 5.462 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.857 W/kg

SAR(1 g) = 0.207 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head, Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.891 \text{ S/m}$; $\epsilon_r = 41.704$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-21-2015; Ambient Temp: 24.5°C; Tissue Temp: 22.0°C

Probe: ES3DV2 - SN3022; ConvF(6.33, 6.33, 6.33); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/18/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.46 W/kg

SAR(1 g) = 1.66 W/kg

Deviation(1 g) = 2.60 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.912 \text{ S/m}$; $\epsilon_r = 39.854$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-23-2015; Ambient Temp: 23.5°C; Tissue Temp: 22.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.63 W/kg

SAR(1 g) = 1.79 W/kg

Deviation(1 g) = -1.97 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.34 \text{ S/m}$; $\epsilon_r = 38.48$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-30-2015; Ambient Temp: 24.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(5.24, 5.24, 5.24); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.76 W/kg

SAR(1 g) = 3.74 W/kg

Deviation(1 g) = 3.31 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.433 \text{ S/m}$; $\epsilon_r = 38.78$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-28-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(5.1, 5.1, 5.1); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.91 W/kg

SAR(1 g) = 3.83 W/kg

Deviation(1 g) = -5.90 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.844 \text{ S/m}$; $\epsilon_r = 39.649$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-30-2015; Ambient Temp: 24.0°C; Tissue Temp: 24.2°C

Probe: ES3DV3 - SN3333; ConvF(4.53, 4.53, 4.53); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.7 W/kg

SAR(1 g) = 5.13 W/kg

Deviation = -5.35 %



0 dB = 6.80 W/kg = 8.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.822 \text{ S/m}$; $\epsilon_r = 38.658$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-15-2016; Ambient Temp: 22.7°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3319; ConvF(4.55, 4.55, 4.55); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.6 W/kg

SAR(1 g) = 5.04 W/kg

Deviation(1 g) = -7.01%



0 dB = 6.71 W/kg = 8.27 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.685 \text{ S/m}$; $\epsilon_r = 36.243$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-14-2016; Ambient Temp: 24.2°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7308; ConvF(5.2, 5.2, 5.2); Calibrated: 7/21/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.8 W/kg

SAR(1 g) = 3.94 W/kg

Deviation(1 g) = -4.48%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.043 \text{ S/m}$; $\epsilon_r = 35.74$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-14-2016; Ambient Temp: 24.2°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7308; ConvF(4.65, 4.65, 4.65); Calibrated: 7/21/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.1 W/kg

SAR(1 g) = 4.31 W/kg

Deviation(1 g) = 2.01%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 5.209 \text{ S/m}$; $\epsilon_r = 35.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-14-2016; Ambient Temp: 24.2°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7308; ConvF(4.86, 4.86, 4.86); Calibrated: 7/21/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.8 W/kg

SAR(1 g) = 3.85 W/kg

Deviation(1 g) = -3.75%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.968 \text{ S/m}$; $\epsilon_r = 54.862$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-30-2015; Ambient Temp: 23.8°C; Tissue Temp: 23.2°C

Probe: ES3DV2 - SN3022; ConvF(6.16, 6.16, 6.16); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/18/2015

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.49 W/kg

SAR(1 g) = 1.71 W/kg

Deviation(1 g) = 1.06 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.972 \text{ S/m}$; $\epsilon_r = 54.401$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-15-2016; Ambient Temp: 24.5°C; Tissue Temp: 23.9°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.62 W/kg

SAR(1 g) = 1.79 W/kg

Deviation(1 g) = 4.92%



0 dB = 2.09 W/kg = 3.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.01 \text{ S/m}$; $\epsilon_r = 54.664$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.88 W/kg

SAR(1 g) = 1.98 W/kg

Deviation(1 g) = 7.03 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1 \text{ S/m}$; $\epsilon_r = 55.351$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-17-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.56 W/kg

SAR(1 g) = 1.76 W/kg

Deviation(1 g) = -4.35%



0 dB = 2.03 W/kg = 3.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.487 \text{ S/m}$; $\epsilon_r = 51.69$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-06-2016; Ambient Temp: 24.2°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3333; ConvF(4.9, 4.9, 4.9); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 6.67 W/kg

SAR(1 g) = 3.86 W/kg

Deviation(1 g) = 4.04 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.486 \text{ S/m}$; $\epsilon_r = 51.093$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-11-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.7°C

Probe: ES3DV3 - SN3351; ConvF(4.88, 4.88, 4.88); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.54 W/kg

SAR(1 g) = 3.79 W/kg

Deviation (1 g) = 2.16%



0 dB = 4.73 W/kg = 6.75 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.511 \text{ S/m}$; $\epsilon_r = 51.892$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-14-2016; Ambient Temp: 24.4°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3334; ConvF(5.03, 5.03, 5.03); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 6.80 W/kg

SAR(1 g) = 3.89 W/kg

Deviation(1 g) = 4.85%



0 dB = 4.79 W/kg = 6.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.565 \text{ S/m}$; $\epsilon_r = 52.17$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-31-2015; Ambient Temp: 23.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3319; ConvF(4.53, 4.53, 4.53); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.06 W/kg

SAR(1 g) = 4.03 W/kg

Deviation(1 g) = -0.25%



0 dB = 5.02 W/kg = 7.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.583 \text{ S/m}$; $\epsilon_r = 53.104$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-11-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.83 W/kg

SAR(1 g) = 3.81 W/kg

Deviation(1 g) = -4.75 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.579 \text{ S/m}$; $\epsilon_r = 51.995$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-20-2016; Ambient Temp: 23.9°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.50 W/kg

SAR(1 g) = 4.16 W/kg

Deviation(1 g) = 2.97%



0 dB = 5.24 W/kg = 7.19 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.963 \text{ S/m}$; $\epsilon_r = 50.82$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-23-2015; Ambient Temp: 19.6°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.8 W/kg

SAR(1 g) = 5.14 W/kg

Deviation(1 g) = -0.96 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.994 \text{ S/m}$; $\epsilon_r = 52.299$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-12-2016; Ambient Temp: 22.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.11, 4.11, 4.11); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.3 W/kg

SAR(1 g) = 5.33 W/kg

Deviation(1 g) = 2.70%



0 dB = 7.01 W/kg = 8.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.455 \text{ S/m}$; $\epsilon_r = 48.493$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-12-2016; Ambient Temp: 23.8°C; Tissue Temp: 23.6°C

Probe: EX3DV4 - SN7357; ConvF(4.11, 4.11, 4.11); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 14.9 W/kg

SAR(1 g) = 3.77 W/kg

Deviation = 0.27%



0 dB = 8.94 W/kg = 9.51 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 5.711 \text{ S/m}$; $\epsilon_r = 48.227$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-12-2016; Ambient Temp: 23.8°C; Tissue Temp: 23.6°C

Probe: EX3DV4 - SN7357; ConvF(3.83, 3.83, 3.83); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5500 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.9 W/kg

SAR(1 g) = 3.82 W/kg

Deviation = -3.90%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 6.135 \text{ S/m}$; $\epsilon_r = 47.714$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-12-2016; Ambient Temp: 23.8°C; Tissue Temp: 23.6°C

Probe: EX3DV4 - SN7357; ConvF(3.82, 3.82, 3.82); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.0 W/kg

SAR(1 g) = 3.72 W/kg

Deviation = -2.49%



0 dB = 9.02 W/kg = 9.55 dBW/kg