



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

12/19/15 - 12/31/15

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

0Y1512282261-R1.A3L

FCC ID:

A3LSMG935KOR

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SM-G935S, SM-G935K, SM-G935L

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	UMTS 850	826.40 - 846.60 MHz	0.16	0.40	0.40
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	< 0.1	0.20	0.40
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.18	0.53	1.02
PCE	LTE Band 12	699.7 - 715.3 MHz	< 0.1	0.16	0.17
PCE	LTE Band 17	706.5 - 713.5 MHz			
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.20	0.55	0.56
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.17	0.43	0.43
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.18	0.59	0.65
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz			
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.18	0.64	1.02
PCE	LTE Band 41	2498.5 - 2687.5 MHz	0.11	0.41	0.88
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.24	0.44	0.44
NII	U-NII-1	5180 - 5240 MHz			
NII	U-NII-2A	5260 - 5320 MHz	0.39	0.14	
NII	U-NII-2C	5500 - 5720 MHz	0.78	0.11	
NII	U-NII-3	5745 - 5825 MHz	0.73	0.20	0.25
DSS/DTS	Bluetooth	2402 - 2480 MHz		N/A	
Simultaneous SAR per KDB 690783 D01v01r03:			1.58	1.33	1.57

Note: This revised Test Report (S/N: 0Y1512282261-R1.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 1 of 75

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	10
3	INTRODUCTION	11
4	DOSIMETRIC ASSESSMENT	12
5	DEFINITION OF REFERENCE POINTS	13
6	TEST CONFIGURATION POSITIONS	14
7	RF EXPOSURE LIMITS	17
8	FCC MEASUREMENT PROCEDURES.....	18
9	RF CONDUCTED POWERS	23
10	SYSTEM VERIFICATION.....	46
11	SAR DATA SUMMARY	49
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	60
13	SAR MEASUREMENT VARIABILITY	70
14	EQUIPMENT LIST.....	71
15	MEASUREMENT UNCERTAINTIES.....	72
16	CONCLUSION.....	73
17	REFERENCES	74
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 2 of 75

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
UMTS 850	Voice/Data	826.40 - 846.60 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
U-NII-1	Data	5180 - 5240 MHz
U-NII-2A	Data	5260 - 5320 MHz
U-NII-2C	Data	5500 - 5720 MHz
U-NII-3	Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz
MST	Data	1 - 8.3 kHz

1.2 Power Reduction for SAR

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 3 of 75

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 1900	Maximum	30.0	30.0	27.0	25.5	24.5	26.5	24.5	22.5	21.5
	Nominal	29.5	29.5	26.5	25.0	24.0	26.0	24.0	22.0	21.0

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	23.5	23.5	23.5
	Nominal	23.0	23.0	23.0
UMTS Band 2 (1900 MHz)	Maximum	23.0	23.0	23.0
	Nominal	22.5	22.5	22.5

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	23.5
	Nominal	23.0
LTE Band 17	Maximum	23.5
	Nominal	23.0
LTE Band 5 (Cell) Ant A	Maximum	24.5
	Nominal	24.0
LTE Band 5 (Cell) Ant B	Maximum	23.5
	Nominal	23.0
LTE Band 26 (Cell)	Maximum	23.5
	Nominal	23.0
LTE Band 4 (AWS)	Maximum	23.5
	Nominal	23.0
LTE Band 2 (PCS)	Maximum	23.5
	Nominal	23.0
LTE Band 25 (PCS)	Maximum	23.5
	Nominal	23.0
LTE Band 41	Maximum	23.0
	Nominal	22.5

Mode / Band		Modulated Average - Single Tx Chain (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	18.5
	Nominal	18.0
IEEE 802.11g (2.4 GHz)	Maximum	17.5
	Nominal	17.0
IEEE 802.11n (2.4 GHz)	Maximum	15.5
	Nominal	15.0
Bluetooth	Maximum	12.0
	Nominal	11.5
Bluetooth LE	Maximum	5.5
	Nominal	5.0

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 4 of 75	

Mode / Band		Modulated Average - Single Tx Chain (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	15.5		
	Nominal	15.0		
IEEE 802.11n (5 GHz)	Maximum	15.5		
	Nominal	15.0		
IEEE 802.11ac (5 GHz)	Maximum	15.5	14.5	13.5
	Nominal	15.0	14.0	13.0

Mode / Band		Modulated Average - MIMO (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11g (2.4 GHz) (CDD)	Maximum	18.5		
	Nominal	18.0		
IEEE 802.11n (2.4 GHz) (CDD+SDM)	Maximum	18.5		
	Nominal	18.0		
IEEE 802.11a (5 GHz) (CDD)	Maximum	15.5		
	Nominal	15.0		
IEEE 802.11n (5 GHz) (CDD+SDM)	Maximum	15.5	14.5	
	Nominal	15.0	14.0	
IEEE 802.11ac (5 GHz) (CDD+SDM)	Maximum	15.5	14.5	9.5
	Nominal	15.0	14.0	9.0

1.3.2 Reduced Power – Proximity Sensor Active

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	14.5
	Nominal	14.0
IEEE 802.11g (2.4 GHz)	Maximum	14.5
	Nominal	14.0
IEEE 802.11n (2.4 GHz)	Maximum	14.5
	Nominal	14.0

Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	11.5		
	Nominal	11.0		
IEEE 802.11n (5 GHz)	Maximum	11.5		
	Nominal	11.0		
IEEE 802.11ac (5 GHz)	Maximum	11.5	11.5	11.5
	Nominal	11.0	11.0	11.0

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 5 of 75

Mode / Band		Modulated Average - MIMO (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11g (2.4 GHz) (CDD)	Maximum	17.5		
	Nominal	17.0		
IEEE 802.11n (2.4 GHz) (CDD+SDM)	Maximum	17.5		
	Nominal	17.0		
IEEE 802.11a (5 GHz) (CDD)	Maximum	14.5		
	Nominal	14.0		
IEEE 802.11n (5 GHz) (CDD+SDM)	Maximum	14.5	14.5	
	Nominal	14.0	14.0	
IEEE 802.11ac (5 GHz) (CDD+SDM)	Maximum	14.5	14.5	9.5
	Nominal	14.0	14.0	9.0

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is ≤160 mm and the diagonal display is ≤150 mm. A diagram showing the location of the device antennas can be found in Appendix F.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	No	Yes
UMTS 1900	Yes	Yes	No	Yes	No	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell) Ant A	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	No	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	No	Yes
LTE Band 41	Yes	Yes	No	Yes	No	Yes
LTE Band 5 (Cell) Ant B	Yes	Yes	Yes	No	Yes	Yes
2.4 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
2.4 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled. Therefore, U-NII-1, U-NII-2A, U-NII-2C operations are not considered in this section.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 6 of 75

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	
2	GSM voice + 5 GHz Wi-Fi	Yes	Yes	N/A	
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
4	GSM voice + 2.4 GHz Wi-Fi MIMO	Yes	Yes	N/A	
5	GSM voice + 5 GHz Wi-Fi MIMO	Yes	Yes	N/A	
6	GSM voice + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	Yes	Yes	N/A	
7	GSM voice + 2.4 GHz Wi-Fi Ant 2 + 5 GHz Wi-Fi Ant 1	Yes	Yes	N/A	
8	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
9	UMTS + 5 GHz Wi-Fi	Yes	Yes	Yes	
10	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	
11	UMTS + 2.4 GHz Wi-Fi MIMO	Yes	Yes	Yes	
12	UMTS + 5 GHz Wi-Fi MIMO	Yes	Yes	Yes	
13	UMTS + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	Yes	Yes	Yes	
14	UMTS + 2.4 GHz Wi-Fi Ant 2 + 5 GHz Wi-Fi Ant 1	Yes	Yes	Yes	
15	LTE + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
16	LTE + 5 GHz Wi-Fi	Yes	Yes	Yes	
17	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A	
18	LTE + 2.4 GHz Wi-Fi MIMO	Yes	Yes	Yes	
19	LTE + 5 GHz Wi-Fi MIMO	Yes	Yes	Yes	
20	LTE + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	Yes	Yes	Yes	
21	LTE + 2.4 GHz Wi-Fi Ant 2 + 5 GHz Wi-Fi Ant 1	Yes	Yes	Yes	
22	GPRS/EDGE + 2.4 GHz Wi-Fi	N/A	N/A	Yes	
23	GPRS/EDGE + 5 GHz Wi-Fi	N/A	N/A	Yes	
24	GPRS/EDGE + 2.4 GHz Wi-Fi MIMO	N/A	N/A	Yes	
25	GPRS/EDGE + 5 GHz Wi-Fi MIMO	N/A	N/A	Yes	
26	GPRS/EDGE + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	N/A	N/A	Yes	
27	GPRS/EDGE + 2.4 GHz Wi-Fi Ant 2 + 5 GHz Wi-Fi Ant 1	N/A	N/A	Yes	
28	GSM voice + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 1	N/A	N/A	N/A	Not Supported by HW
29	GSM voice + 2.4 GHz Wi-Fi Ant 2 + 5 GHz Wi-Fi Ant 2	N/A	N/A	N/A	Not Supported by HW
30	UMTS + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 1	N/A	N/A	N/A	Not Supported by HW
31	UMTS + 2.4 GHz Wi-Fi Ant 2 + 5 GHz Wi-Fi Ant 2	N/A	N/A	N/A	Not Supported by HW
32	LTE + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 1	N/A	N/A	N/A	Not Supported by HW
33	LTE + 2.4 GHz Wi-Fi Ant 2 + 5 GHz Wi-Fi Ant 2	N/A	N/A	N/A	Not Supported by HW
34	GPRS/EDGE + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 1	N/A	N/A	N/A	Not Supported by HW
35	GPRS/EDGE + 2.4 GHz Wi-Fi Ant 2 + 5 GHz Wi-Fi Ant 2	N/A	N/A	N/A	Not Supported by HW

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 7 of 75

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
3. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
4. 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
5. This device supports 2x2 MIMO Tx for WLAN 802.11g/a/n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.
6. This device supports VOLTE.

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(16/10) * \sqrt{2.480}] = 2.5 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 8 of 75

This device supports both LTE Band 12 and LTE Band 17. Since the supported frequency span for LTE Band 17 falls completely within the supported frequency span for LTE Band 12, both LTE bands have the same target power, and both LTE Bands share the same transmission path, SAR was only assessed for LTE Band 12.

This device supports both LTE Band 25 and LTE Band 2. Since the supported frequency span for LTE Band 2 falls completely within the supported frequency span for LTE Band 25, both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE Band 25.

LTE Band 5 Ant B is disabled for all held to ear scenarios. Therefore SAR was only assessed for body-worn accessory and wireless router conditions.

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
UMTS 850	7F4BD	7F539	7F539
GSM/GPRS/EDGE 1900	7F4BD	7F4C0	7F4C0
UMTS 1900	7F539	7F539	7F539
LTE Band 12	7F53C	7F53C	7F53C
LTE Band 5 (Cell) Ant A	7F4BD	7F53D	7F53D
LTE Band 5 (Cell) Ant B	-	7F537	7F537
LTE Band 26 (Cell)	7F4BD	7F53D	7F53D
LTE Band 4 (AWS)	7F538	7F4C0	7F4C0
LTE Band 25 (PCS)	7F539	7F4C0	7F4C0
LTE Band 41	7F4BD	7F53C	7F53C
2.4 GHz WLAN	7F4B7	7F4C0	7F4C0
5 GHz WLAN	7F4B7	7F4B7	7F4B7

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 9 of 75

2

LTE INFORMATION

LTE Information					
FCC ID	A3LSMG935KOR				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 17 (706.5 - 713.5 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 17: 5 MHz, 10 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)
LTE Band 17: 5 MHz	706.5 (23755)		710 (23790)		713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)		710 (23790)		711 (23800)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)		831.5 (26865)		848.3 (27033)
LTE Band 26 (Cell): 3 MHz	815.5 (26705)		831.5 (26865)		847.5 (27025)
LTE Band 26 (Cell): 5 MHz	816.5 (26715)		831.5 (26865)		846.5 (27015)
LTE Band 26 (Cell): 10 MHz	819 (26740)		831.5 (26865)		844 (26990)
LTE Band 26 (Cell): 15 MHz	831.5 (26865)		836.5 (26915)		841.5 (26965)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)		1914.3 (26683)
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)		1913.5 (26675)
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)		1912.5 (26665)
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)		1910 (26640)
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)		1907.5 (26615)
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)		1905 (26590)
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	10				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	Not supported in the US				
LTE Release 10 Additional Information	This device does not support full CA features on 3GPP Release 10. The following LTE Release 10 Features are not supported: Carrier Aggregation, Relay, HetNet, Enhanced MIMO, eICl, WIFI Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 10 of 75

3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 11 of 75

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid $\Delta z_{\text{zoom}}(n)$	Graded Grid		
				$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22


*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMG935KOR	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 12 of 75

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The “M” is the reference point for the center of the mouth, “LE” is the left ear reference (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The passing through the two ear canals and M is defined as the Reference Plane. The N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].



point
point
the
plane
line
the
N-F

Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 13 of 75

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 14 of 75

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 16 of 75

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 17 of 75

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 18 of 75

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 19 of 75

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 20 of 75

SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz and 5 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a,

FCC ID: A3LSMG935KOR	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset
		Page 21 of 75

802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.6.7 Initial Test Configuration Procedure

For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6).

8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

8.6.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 22 of 75

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	29.54	29.65	26.26	24.75	23.46	25.25	23.17	21.87	20.61
	661	29.33	29.50	26.01	24.52	23.24	24.92	22.82	21.79	20.39
	810	29.35	29.43	25.97	24.65	23.15	24.90	22.75	21.56	20.49
		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	20.51	20.62	20.24	20.49	20.45	16.22	17.15	17.61	17.60
	661	20.30	20.47	19.99	20.26	20.23	15.89	16.80	17.53	17.38
	810	20.32	20.40	19.95	20.39	20.14	15.87	16.73	17.30	17.48
GSM 1900	Frame Avg.Targets:	20.47	20.47	20.48	20.74	20.99	16.97	17.98	17.74	17.99

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.




Figure 9-1
Power Measurement Setup

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 23 of 75	

9.2 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.86	22.83	23.12	22.78	22.25	22.24	-
99		12.2 kbps AMR	22.89	22.81	23.17	22.68	22.26	22.22	-
6	HSDPA	Subtest 1	22.70	22.61	22.92	22.80	22.33	22.18	0
6		Subtest 2	22.65	22.63	22.93	22.69	22.31	22.19	0
6		Subtest 3	21.81	21.89	22.19	22.05	21.59	21.49	0.5
6		Subtest 4	21.86	21.83	22.20	22.04	21.57	21.45	0.5
6	HSUPA	Subtest 1	22.14	21.78	22.13	22.00	21.53	21.50	0
6		Subtest 2	21.13	21.10	21.36	20.88	20.59	20.35	2
6		Subtest 3	21.84	21.73	22.10	21.85	21.40	21.42	1
6		Subtest 4	21.11	21.08	21.33	20.74	20.49	20.47	2
6		Subtest 5	22.80	22.70	23.00	22.73	22.36	22.16	0

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 1 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.



Figure 9-2
Power Measurement Setup

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 24 of 75

9.3 LTE Conducted Powers

9.3.1 LTE Band 12

Table 9-1
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.74	0	0
	1	25	22.77		0
	1	49	22.78		0
	25	0	21.97	0-1	1
	25	12	22.02		1
	25	25	22.03		1
	50	0	21.97		1
16QAM	1	0	21.90	0-1	1
	1	25	22.09		1
	1	49	21.98		1
	25	0	21.03	0-2	2
	25	12	21.01		2
	25	25	21.00		2
	50	0	21.04		2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-2
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]	Conducted Power [dBm]	Conducted Power [dBm]		
QPSK	1	0	23.08	23.08	23.07	0	0
	1	12	23.14	23.00	23.11		0
	1	24	23.19	22.95	23.10		0
	12	0	21.92	21.89	21.92	0-1	1
	12	6	21.92	21.89	21.90		1
	12	13	21.91	21.89	21.90		1
	25	0	21.91	21.88	21.90		1
16QAM	1	0	21.99	22.20	22.20	0-1	1
	1	12	22.20	22.07	22.11		1
	1	24	22.15	22.16	22.14		1
	12	0	21.04	20.94	20.95	0-2	2
	12	6	20.95	20.91	20.94		2
	12	13	20.96	20.94	20.94		2
	25	0	20.99	20.92	20.91		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 25 of 75

Table 9-3
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.04	22.87	22.86	0	0
	1	7	23.06	22.95	22.87		0
	1	14	22.97	22.99	22.89		0
	8	0	22.04	21.93	21.88	0-1	1
	8	4	22.00	21.93	21.89		1
	8	7	21.99	21.93	21.89		1
	15	0	21.95	21.83	21.81		1
16QAM	1	0	22.20	22.20	22.07	0-1	1
	1	7	22.18	22.09	22.14		1
	1	14	22.20	21.99	22.17		1
	8	0	21.10	21.03	20.94	0-2	2
	8	4	21.12	20.96	20.96		2
	8	7	21.06	21.01	20.94		2
	15	0	21.00	20.94	20.82		2

Table 9-4
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.87	22.83	22.87	0	0
	1	2	22.90	22.74	22.84		0
	1	5	22.84	22.79	22.82		0
	3	0	22.96	22.80	22.80		0
	3	2	22.93	22.80	22.84		0
	3	3	22.90	22.77	22.85		0
	6	0	22.01	21.90	21.94	0-1	1
16QAM	1	0	22.02	22.00	22.06	0-1	1
	1	2	22.18	21.91	22.18		1
	1	5	22.11	21.80	21.86		1
	3	0	22.04	21.90	22.03		1
	3	2	22.09	21.94	21.92		1
	3	3	22.06	22.00	21.94		1
	6	0	21.10	21.00	21.02	0-2	2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 26 of 75	

9.3.2 LTE Band 5 (Cell)

Table 9-5
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth – Ant A

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.72	0	0
	1	25	23.68		0
	1	49	23.63		0
	25	0	22.75	0-1	1
	25	12	22.72		1
	25	25	22.71		1
	50	0	22.73		1
16QAM	1	0	22.74	0-1	1
	1	25	22.62		1
	1	49	22.61		1
	25	0	21.76	0-2	2
	25	12	21.73		2
	25	25	21.77		2
	50	0	21.78		2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-6
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth – Ant A

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.79	23.78	24.18	0	0
	1	12	23.77	23.80	24.16		0
	1	24	23.89	23.89	24.09		0
	12	0	22.60	22.62	22.97	0-1	1
	12	6	22.60	22.62	22.97		1
	12	13	22.60	22.62	22.94		1
	25	0	22.58	22.61	22.95		1
16QAM	1	0	22.81	22.87	23.11	0-1	1
	1	12	22.85	22.65	23.02		1
	1	24	22.83	22.71	23.14		1
	12	0	21.60	21.63	22.05	0-2	2
	12	6	21.69	21.61	22.01		2
	12	13	21.60	21.63	21.97		2
	25	0	21.59	21.61	21.97		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 27 of 75	

Table 9-7
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth – Ant A

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.67	23.67	24.08	0	0
	1	7	23.71	23.72	24.07		0
	1	14	23.64	23.72	24.01		0
	8	0	22.62	22.65	23.06	0-1	1
	8	4	22.61	22.66	23.03		1
	8	7	22.61	22.65	23.04		1
	15	0	22.52	22.58	22.98		1
16QAM	1	0	22.91	22.73	23.15	0-1	1
	1	7	22.84	23.02	23.20		1
	1	14	22.77	22.88	23.09		1
	8	0	21.67	21.69	22.15	0-2	2
	8	4	21.67	21.81	22.07		2
	8	7	21.71	21.68	22.08		2
	15	0	21.61	21.62	22.03		2

Table 9-8
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth – Ant A

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.61	23.55	24.03	0	0
	1	2	23.53	23.54	24.08		0
	1	5	23.60	23.57	23.95		0
	3	0	23.66	23.58	24.02		0
	3	2	23.68	23.60	24.03		0
	3	3	23.63	23.59	24.04		0
	6	0	22.64	22.63	23.07	0-1	1
16QAM	1	0	22.68	22.61	23.20	0-1	1
	1	2	22.72	22.64	23.11		1
	1	5	22.70	22.44	23.11		1
	3	0	22.72	22.72	23.14		1
	3	2	22.76	22.77	23.10		1
	3	3	22.68	22.69	23.06		1
	6	0	21.74	21.70	22.18	0-2	2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 28 of 75

Table 9-9
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth – Ant B

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.24	0	0
	1	25	22.20		0
	1	49	22.19		0
	25	0	21.36	0-1	1
	25	12	21.35		1
	25	25	21.34		1
	50	0	21.35		1
16QAM	1	0	22.28	0-1	0
	1	25	22.33		0
	1	49	22.22		0
	25	0	20.43	0-2	2
	25	12	20.41		2
	25	25	20.38		2
	50	0	20.41		2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-10
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth – Ant B

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.30	22.32	22.64	0	0
	1	12	22.27	22.31	22.52		0
	1	24	22.24	22.33	22.47		0
	12	0	21.40	21.44	21.72	0-1	1
	12	6	21.39	21.45	21.73		1
	12	13	21.34	21.46	21.68		1
	25	0	21.34	21.45	21.75		1
16QAM	1	0	22.56	22.45	22.69	0-1	0
	1	12	22.47	22.33	22.65		0
	1	24	22.46	22.48	22.59		0
	12	0	20.57	20.55	20.75	0-2	2
	12	6	20.54	20.46	20.74		2
	12	13	20.53	20.52	20.66		2
	25	0	20.49	20.54	20.82		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 29 of 75

Table 9-11
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth – Ant B

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.40	22.39	22.54	0	0
	1	7	22.36	22.34	22.45		0
	1	14	22.38	22.35	22.52		0
	8	0	21.30	21.31	21.67	0-1	1
	8	4	21.31	21.32	21.68		1
	8	7	21.29	21.30	21.65		1
	15	0	21.25	21.28	21.67		1
16QAM	1	0	22.47	22.66	22.68	0-1	0
	1	7	22.45	22.59	22.65		0
	1	14	22.51	22.62	22.72		0
	8	0	20.53	20.50	20.80	0-2	2
	8	4	20.51	20.52	20.81		2
	8	7	20.50	20.48	20.79		2
	15	0	20.42	20.46	20.66		2

Table 9-12
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth – Ant B

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.37	22.40	22.58	0	0
	1	2	22.34	22.42	22.56		0
	1	5	22.32	22.38	22.57		0
	3	0	22.21	22.19	22.72		0
	3	2	22.21	22.21	22.71		0
	3	3	22.22	22.18	22.67		0
	6	0	21.14	21.15	21.75	0-1	1
16QAM	1	0	22.28	22.27	22.68	0-1	0
	1	2	22.32	22.24	22.67		0
	1	5	22.31	22.22	22.58		0
	3	0	22.16	22.17	22.65		0
	3	2	22.15	22.19	22.66		0
	3	3	22.19	22.24	22.61		0
	6	0	20.27	20.39	20.70	0-2	2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 30 of 75	

9.3.3 LTE Band 26 (Cell)

Table 9-13
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26915 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.74	0	0
	1	36	22.66		0
	1	74	22.57		0
	36	0	21.72	0-1	1
	36	18	21.71		1
	36	37	21.66		1
	75	0	21.71		1
16QAM	1	0	21.72	0-2	1
	1	36	21.65		1
	1	74	21.48		1
	36	0	20.94	0-2	2
	36	18	20.87		2
	36	37	20.84		2
	75	0	20.90		2

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-14
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
QPSK	1	0	22.90	22.64	22.79	0	0
	1	25	22.82	22.57	22.83		0
	1	49	22.74	22.65	22.66		0
	25	0	21.62	21.56	21.70	0-1	1
	25	12	21.58	21.58	21.70		1
	25	25	21.58	21.55	21.66		1
	50	0	21.57	21.53	21.66		1
16QAM	1	0	21.72	21.53	21.78	0-2	1
	1	25	21.72	21.51	21.73		1
	1	49	21.61	21.54	21.67		1
	25	0	20.72	20.69	20.87	0-2	2
	25	12	20.71	20.67	20.84		2
	25	25	20.70	20.66	20.81		2
	50	0	20.73	20.67	20.85		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 31 of 75

Table 9-15
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.94	22.88	23.20	0	0
	1	12	22.94	22.85	23.12		0
	1	24	22.84	22.89	23.05		0
	12	0	21.63	21.56	21.91	0-1	1
	12	6	21.59	21.54	21.90		1
	12	13	21.57	21.56	21.86		1
	25	0	21.58	21.54	21.89		1
16QAM	1	0	21.68	21.75	22.10	0-2	1
	1	12	21.63	21.70	22.13		1
	1	24	21.51	21.62	21.86		1
	12	0	20.84	20.75	21.10	0-2	2
	12	6	20.82	20.70	21.04		2
	12	13	20.82	20.73	21.04		2
	25	0	20.75	20.72	21.04		2

Table 9-16
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.80	22.71	23.07	0	0
	1	7	22.68	22.69	23.05		0
	1	14	22.76	22.71	23.03		0
	8	0	21.62	21.58	21.93	0-1	1
	8	4	21.65	21.63	21.97		1
	8	7	21.62	21.58	21.91		1
	15	0	21.58	21.55	21.89		1
16QAM	1	0	21.85	21.85	22.36	0-2	1
	1	7	21.79	21.57	22.14		1
	1	14	21.75	21.53	22.11		1
	8	0	20.78	20.76	21.15	0-2	2
	8	4	20.82	20.77	21.22		2
	8	7	20.81	20.80	21.13		2
	15	0	20.72	20.70	21.07		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 32 of 75

Table 9-17
LTE Band 26 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.61	22.57	22.98	0	0
	1	2	22.57	22.53	22.90		0
	1	5	22.56	22.57	22.89		0
	3	0	22.62	22.62	22.93		0
	3	2	22.64	22.61	22.97		0
	3	3	22.63	22.53	22.95		0
	6	0	21.53	21.53	21.91	0-1	1
16QAM	1	0	21.52	21.42	21.93	0-1	1
	1	2	21.67	21.37	21.78		1
	1	5	21.63	21.28	21.86		1
	3	0	21.57	21.54	21.91		1
	3	2	21.55	21.53	22.13		1
	3	3	21.61	21.63	21.93		1
	6	0	20.81	20.71	21.17	0-2	2

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 33 of 75

9.3.4 LTE Band 4 (AWS)

Table 9-18
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.70	0	0
	1	50	22.68		0
	1	99	22.51		0
	50	0	21.69	0-1	1
	50	25	21.63		1
	50	50	21.57		1
	100	0	21.64		1
16QAM	1	0	21.45		1
	1	50	21.51		1
	1	99	21.32		1
	50	0	20.63	0-2	2
	50	25	20.62		2
	50	50	20.49		2
	100	0	20.61		2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-19
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 4 (AWS) 15 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.77	22.46	22.39	0	0
	1	36	22.70	22.49	22.34		0
	1	74	22.85	22.52	22.30		0
	36	0	21.75	21.45	21.29	0-1	1
	36	18	21.73	21.42	21.31		1
	36	37	21.74	21.41	21.28		1
	75	0	21.70	21.44	21.25		1
16QAM	1	0	21.93	21.55	21.34	0-1	1
	1	36	21.86	21.52	21.33		1
	1	74	21.88	21.62	21.33		1
	36	0	20.68	20.46	20.26	0-2	2
	36	18	20.69	20.39	20.21		2
	36	37	20.65	20.39	20.23		2
	75	0	20.69	20.42	20.18		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 34 of 75

Table 9-20
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 4 (AWS) 10 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.02	22.55	22.39	0	0
	1	25	22.84	22.58	22.36		0
	1	49	22.85	22.58	22.42		0
	25	0	21.75	21.48	21.29	0-1	1
	25	12	21.75	21.48	21.32		1
	25	25	21.74	21.47	21.29		1
	50	0	21.70	21.47	21.26		1
16QAM	1	0	21.94	21.63	21.39	0-1	1
	1	25	21.86	21.51	21.38		1
	1	49	21.88	21.62	21.48		1
	25	0	20.74	20.46	20.28	0-2	2
	25	12	20.72	20.41	20.29		2
	25	25	20.74	20.41	20.29		2
	50	0	20.71	20.41	20.28		2

Table 9-21
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 4 (AWS) 5 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.02	22.74	22.60	0	0
	1	12	23.01	22.71	22.66		0
	1	24	22.98	22.78	22.60		0
	12	0	21.74	21.51	21.34	0-1	1
	12	6	21.75	21.49	21.37		1
	12	13	21.74	21.50	21.33		1
	25	0	21.70	21.49	21.37		1
16QAM	1	0	21.94	21.66	21.39	0-1	1
	1	12	21.93	21.71	21.63		1
	1	24	21.69	21.56	21.56		1
	12	0	20.80	20.49	20.40	0-2	2
	12	6	20.77	20.50	20.37		2
	12	13	20.76	20.43	20.41		2
	25	0	20.74	20.41	20.33		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 35 of 75

Table 9-22
LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 4 (AWS) 3 MHzBandwidth							
Modulation	RB Size	RB Offset	Frequency [MHz]	Frequency [MHz]	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.81	22.53	22.39	0	0
	1	7	22.82	22.52	22.48		0
	1	14	22.84	22.54	22.41		0
	8	0	21.76	21.52	21.31	0-1	1
	8	4	21.75	21.53	21.32		1
	8	7	21.71	21.51	21.36		1
	15	0	21.68	21.47	21.29		1
16QAM	1	0	21.91	21.72	21.40	0-1	1
	1	7	21.73	21.72	21.46		1
	1	14	21.96	21.58	21.41		1
	8	0	20.78	20.48	20.37	0-2	2
	8	4	20.74	20.53	20.44		2
	8	7	20.74	20.47	20.36		2
	15	0	20.73	20.45	20.27		2

Table 9-23
LTE Band 4 (AWS) Conducted Powers - 1.4 MHz Bandwidth

LTE Band 4 (AWS) 1.4 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.71	22.54	22.71	0	0
	1	2	22.67	22.52	22.73		0
	1	5	22.51	22.55	22.66		0
	3	0	22.75	22.57	22.65		0
	3	2	22.76	22.61	22.68		0
	3	3	22.75	22.51	22.74		0
	6	0	21.62	21.51	21.65	0-1	1
16QAM	1	0	21.48	21.54	21.76	0-1	1
	1	2	21.33	21.72	21.76		1
	1	5	21.31	21.37	21.76		1
	3	0	21.68	21.50	21.73		1
	3	2	21.67	21.50	21.75		1
	3	3	21.70	21.56	21.69		1
	6	0	20.55	20.51	20.67	0-2	2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 36 of 75

9.3.5 LTE Band 25 (PCS)

Table 9-24
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.69	22.33	22.31	0	0
	1	50	22.78	22.24	22.25		0
	1	99	22.61	22.22	22.22		0
	50	0	21.58	21.29	21.27	0-1	1
	50	25	21.62	21.26	21.24		1
	50	50	21.60	21.28	21.23		1
	100	0	21.55	21.27	21.28		1
16QAM	1	0	21.72	21.34	21.31	0-2	1
	1	50	21.76	21.32	21.24		1
	1	99	21.54	21.24	21.22		1
	50	0	20.54	20.25	20.23	0-2	2
	50	25	20.61	20.23	20.20		2
	50	50	20.55	20.17	20.21		2
	100	0	20.46	20.14	20.17		2

Table 9-25
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.58	22.28	22.23	0	0
	1	36	22.45	22.32	22.13		0
	1	74	22.51	22.24	22.17		0
	36	0	21.45	21.26	21.15	0-1	1
	36	18	21.44	21.26	21.15		1
	36	37	21.40	21.23	21.15		1
	75	0	21.43	21.22	21.14		1
16QAM	1	0	21.44	21.46	21.24	1	1
	1	36	21.59	21.41	21.19		1
	1	74	21.63	21.33	21.11		1
	36	0	20.36	20.20	20.05	0-2	2
	36	18	20.40	20.24	20.11		2
	36	37	20.36	20.22	20.07		2
	75	0	20.34	20.22	20.15		2

FCC ID: A3LSMG935KOR	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 37 of 75

Table 9-26
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.72	22.35	22.25	0	0
	1	25	22.66	22.34	22.21		0
	1	49	22.58	22.31	22.17		0
	25	0	21.45	21.26	21.15	0-1	1
	25	12	21.45	21.26	21.13		1
	25	25	21.45	21.24	21.11		1
	50	0	21.43	21.23	21.07		1
16QAM	1	0	21.81	21.46	21.24	0-2	1
	1	25	21.68	21.41	21.14		1
	1	49	21.63	21.48	21.29		1
	25	0	20.37	20.20	20.03	0-2	2
	25	12	20.40	20.20	20.10		2
	25	25	20.39	20.17	20.09		2
	50	0	20.41	20.23	20.05		2

Table 9-27
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.72	22.47	22.45	0	0
	1	12	22.76	22.48	22.42		0
	1	24	22.75	22.45	22.40		0
	12	0	21.50	21.27	21.16	0-1	1
	12	6	21.51	21.27	21.15		1
	12	13	21.50	21.28	21.15		1
	25	0	21.50	21.26	21.14		1
16QAM	1	0	21.62	21.49	21.56	0-2	1
	1	12	21.72	21.44	21.41		1
	1	24	21.72	21.51	21.17		1
	12	0	20.52	20.29	20.17	0-2	2
	12	6	20.53	20.25	20.16		2
	12	13	20.51	20.21	20.18		2
	25	0	20.49	20.21	20.12		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 38 of 75

Table 9-28
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.66	22.36	22.19	0	0
	1	7	22.65	22.38	22.28		0
	1	14	22.57	22.37	22.20		0
	8	0	21.54	21.28	21.14	0-1	1
	8	4	21.56	21.31	21.18		1
	8	7	21.54	21.31	21.15		1
	15	0	21.48	21.24	21.08		1
16QAM	1	0	21.77	21.57	21.36	1	1
	1	7	21.94	21.39	21.37		1
	1	14	21.79	21.60	21.29		1
	8	0	20.52	20.31	20.18	0-2	2
	8	4	20.55	20.31	20.17		2
	8	7	20.55	20.30	20.16		2
	15	0	20.47	20.25	20.11		2

Table 9-29
LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.53	22.18	22.06	0	0
	1	2	22.48	22.24	22.04		0
	1	5	22.48	22.18	22.10		0
	3	0	22.46	22.30	22.13		0
	3	2	22.49	22.21	22.10		0
	3	3	22.49	22.24	22.08		0
	6	0	21.50	21.24	21.13	0-1	1
16QAM	1	0	21.56	21.17	21.05	0-1	1
	1	2	21.45	21.19	21.18		1
	1	5	21.36	21.25	21.03		1
	3	0	21.59	21.29	21.21		1
	3	2	21.79	21.38	21.19		1
	3	3	21.57	21.37	21.14		1
	6	0	20.46	20.32	20.16	0-2	2

FCC ID: A3LSMG935KOR



SAR EVALUATION REPORT



Reviewed by:
Quality Manager

Document S/N:
0Y1512282261-R1.A3L

Test Dates:
12/19/15 - 12/31/15

DUT Type:
Portable Handset

Page 39 of 75

9.3.6 LTE Band 41

Table 9-30
LTE Band 41 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.27	21.57	21.58	22.23	21.22	0	0
	1	50	22.26	21.56	21.56	22.18	21.92		0
	1	99	22.23	21.54	21.57	22.17	21.87		0
	50	0	21.22	20.48	20.74	21.07	20.80	0-1	1
	50	25	21.10	20.45	20.69	21.06	20.78		1
	50	50	21.08	20.48	20.72	21.09	20.82		1
	100	0	21.14	20.45	20.73	21.05	20.79		1
16QAM	1	0	21.16	20.57	20.64	20.96	21.02	0-1	1
	1	50	21.00	20.06	20.84	20.95	20.67		1
	1	99	21.05	20.55	20.57	21.06	20.71		1
	50	0	20.14	19.45	19.66	20.14	19.80	0-2	2
	50	25	20.11	19.47	19.62	20.13	19.77		2
	50	50	20.13	19.41	19.71	20.10	19.74		2
	100	0	20.15	19.53	19.66	20.12	19.80		2

Table 9-31
LTE Band 41 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.83	21.30	21.44	21.79	21.66	0	0
	1	36	21.80	21.30	21.43	21.77	21.67		0
	1	74	21.74	21.29	21.40	21.78	21.63		0
	36	0	20.96	20.27	20.52	20.78	20.66	0-1	1
	36	18	20.88	20.30	20.50	20.78	20.61		1
	36	37	20.89	20.27	20.51	20.78	20.63		1
	75	0	20.91	20.28	20.50	20.75	20.62		1
16QAM	1	0	20.64	20.22	20.35	20.73	20.36	0-1	1
	1	36	20.52	20.17	20.29	20.70	20.35		1
	1	74	20.52	20.10	20.25	20.71	20.35		1
	36	0	19.83	19.25	19.54	19.82	19.59	0-2	2
	36	18	19.79	19.28	19.46	19.77	19.54		2
	36	37	19.80	19.25	19.46	19.79	19.56		2
	75	0	19.81	19.22	19.50	19.83	19.52		2

Table 9-32
LTE Band 41 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.80	21.74	21.38	21.80	21.55	0	0
	1	25	21.79	21.76	21.41	21.81	21.56		0
	1	49	21.72	21.73	21.39	21.80	21.59		0
	25	0	20.82	20.70	20.39	20.76	20.58	1	
	25	12	20.83	20.68	20.36	20.75	20.60	1	
	25	25	20.84	20.66	20.38	20.77	20.60	1	
16QAM	50	0	20.81	20.68	20.39	20.80	20.59	0-1	1
	1	0	20.73	20.52	20.29	20.80	20.45		1
	1	25	20.65	20.41	20.32	20.85	20.50		1
	1	49	20.71	20.52	20.29	20.82	20.47	0-2	1
	25	0	19.74	19.73	19.38	19.80	19.47		2
	25	12	19.76	19.75	19.34	19.79	19.50		2
	25	25	19.72	19.70	19.38	19.76	19.51		2
	50	0	19.74	19.66	19.36	19.80	19.54		2

FCC ID: A3LSMG935KOR	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 40 of 75

Table 9-33
LTE Band 41 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.68	21.94	21.46	21.88	21.44	0	0
	1	12	21.67	21.91	21.43	21.85	21.46		0
	1	24	21.64	21.90	21.46	21.83	21.46		0
	12	0	20.81	20.77	20.46	20.82	20.61	0-1	1
	12	6	20.83	20.71	20.44	20.75	20.57		1
	12	13	20.81	20.73	20.46	20.78	20.57		1
	25	0	20.87	20.74	20.47	20.79	20.59		1
16QAM	1	0	20.43	20.74	20.25	20.55	20.31	0-1	1
	1	12	20.41	20.68	20.23	20.57	20.29		1
	1	24	20.38	20.74	20.23	20.56	20.31		1
	12	0	19.80	19.70	19.32	19.67	19.54	0-2	2
	12	6	19.81	19.71	19.36	19.64	19.52		2
	12	13	19.83	19.73	19.37	19.64	19.50		2
	25	0	19.90	19.72	19.39	19.69	19.54		2

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 41 of 75

9.4 WLAN Conducted Powers

Table 9-34
2.4 GHz WLAN Maximum Average RF Power – Antenna 1

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11b	802.11g
2412	1	17.67	16.70
2437	6	17.65	17.39
2462	11	18.36	16.76

Table 9-35
2.4 GHz WLAN Maximum Average RF Power – Antenna 2

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11b	802.11g
2412	1	17.71	16.67
2437	6	18.42	16.71
2462	11	18.37	16.63

Table 9-36
2.4 GHz WLAN Reduced Average RF Power – Antenna 1 (Held to Ear)

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	13.80	14.40	14.23
2437	6	13.90	13.94	13.75
2462	11	14.18	14.14	13.97

Table 9-37
2.4 GHz WLAN Reduced Average RF Power – Antenna 2 (Held to Ear)

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	14.02	14.40	14.36
2437	6	13.68	14.29	14.25
2462	11	13.72	13.98	14.26

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 42 of 75

Table 9-38
5 GHz WLAN Maximum Average RF Power – Antenna 1

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	14.71	14.80	14.78
5200	40	14.95	14.89	14.81
5220	44	14.89	14.72	14.90
5240	48	14.88	14.86	14.81
5260	52	14.60	15.39	14.42
5280	56	14.75	15.48	14.44
5300	60	15.49	15.47	15.42
5320	64	15.39	15.32	15.32
5500	100	15.10	15.16	15.11
5600	120	14.83	14.80	14.75
5620	124	14.79	14.70	14.58
5720	144	15.34	15.20	15.27
5745	149	14.82	14.68	14.66
5785	157	14.50	14.46	14.43
5825	165	15.35	15.31	15.24

Table 9-39
5 GHz WLAN Maximum Average RF Power – Antenna 2

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	15.38	15.20	15.37
5200	40	15.49	15.29	15.31
5220	44	15.44	15.14	15.21
5240	48	15.34	15.16	15.22
5260	52	15.46	15.15	15.30
5280	56	15.31	14.98	15.32
5300	60	15.28	15.01	15.06
5320	64	15.27	14.96	15.24
5500	100	14.93	14.70	14.95
5600	120	15.46	15.22	15.30
5620	124	15.21	15.17	14.95
5720	144	14.56	14.45	14.52
5745	149	15.48	14.50	15.42
5785	157	15.19	15.08	15.27
5825	165	14.90	15.00	15.01

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 43 of 75	

Table 9-40
5 GHz WLAN Reduced Average RF Power – Antenna 1 (Held to Ear)

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	11.40
5290	58	11.31
5530	106	11.23
5610	122	10.89
5690	138	11.34
5775	155	10.51

Table 9-41
5 GHz WLAN Reduced Average RF Power – Antenna 2 (Held to Ear)

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	11.32
5290	58	10.89
5530	106	11.48
5610	122	11.03
5690	138	10.71
5775	155	10.98

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 44 of 75	

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-3
Power Measurement Setup for Bandwidths < 50 MHz




Figure 9-4
Power Measurement Setup for Bandwidths > 50 MHz

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 45 of 75

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties – Head

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
12/19/2015	750H	22.0	700	0.847	42.411	0.889	42.201	-4.72%	0.50%
			710	0.856	42.327	0.890	42.149	-3.82%	0.42%
			740	0.881	42.008	0.893	41.994	-1.34%	0.03%
			755	0.896	41.782	0.894	41.916	0.22%	-0.32%
12/20/2015	835H	21.0	820	0.890	40.571	0.899	41.578	-1.00%	-2.42%
			835	0.901	40.356	0.900	41.500	0.11%	-2.76%
			850	0.919	40.227	0.916	41.500	0.33%	-3.07%
12/30/2015	1750H	22.7	1710	1.301	38.668	1.348	40.142	-3.49%	-3.67%
			1750	1.340	38.480	1.371	40.079	-2.26%	-3.99%
			1790	1.378	38.306	1.394	40.016	-1.15%	-4.27%
12/28/2015	1900H	22.2	1850	1.378	39.010	1.400	40.000	-1.57%	-2.48%
			1880	1.411	38.874	1.400	40.000	0.79%	-2.81%
			1910	1.444	38.733	1.400	40.000	3.14%	-3.17%
12/22/2015	2450H	24.5	2400	1.777	40.338	1.756	39.289	1.20%	2.67%
			2450	1.836	40.112	1.800	39.200	2.00%	2.33%
			2500	1.890	39.930	1.855	39.136	1.89%	2.03%
			2550	1.953	39.728	1.909	39.073	2.30%	1.68%
12/28/2015	5200H-5800H	21.3	5240	4.580	35.231	4.696	35.940	-2.47%	-1.97%
			5260	4.603	35.211	4.717	35.917	-2.42%	-1.97%
			5280	4.621	35.206	4.737	35.894	-2.45%	-1.92%
			5300	4.636	35.186	4.758	35.871	-2.56%	-1.91%
			5520	4.858	34.850	4.983	35.620	-2.51%	-2.16%
			5540	4.880	34.843	5.004	35.597	-2.48%	-2.12%
			5600	4.944	34.701	5.065	35.529	-2.39%	-2.33%
			5680	5.027	34.606	5.147	35.437	-2.33%	-2.35%
			5700	5.057	34.569	5.168	35.414	-2.15%	-2.39%
			5745	5.103	34.526	5.214	35.363	-2.13%	-2.37%
			5765	5.116	34.481	5.234	35.340	-2.25%	-2.43%
			5785	5.144	34.446	5.255	35.317	-2.11%	-2.47%

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 46 of 75

Table 10-2
Measured Tissue Properties – Body

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
12/22/2015	750B	23.6	700	0.914	54.596	0.959	55.726	-4.69%	-2.03%
			710	0.921	54.471	0.960	55.687	-4.06%	-2.18%
			740	0.951	54.221	0.963	55.570	-1.25%	-2.43%
			755	0.963	54.038	0.964	55.512	-0.10%	-2.66%
12/21/2015	835B	21.6	820	0.991	54.923	0.969	55.258	2.27%	-0.61%
			835	1.010	54.664	0.970	55.200	4.12%	-0.97%
			850	1.020	54.558	0.988	55.154	3.24%	-1.08%
12/28/2015	1750B	23.1	1710	1.428	51.389	1.463	53.537	-2.39%	-4.01%
			1750	1.473	51.284	1.488	53.432	-1.01%	-4.02%
			1790	1.513	51.147	1.514	53.326	-0.07%	-4.09%
12/21/2015	1900B	21.7	1850	1.509	54.252	1.520	53.300	-0.72%	1.79%
			1880	1.544	54.262	1.520	53.300	1.58%	1.80%
			1910	1.572	54.057	1.520	53.300	3.42%	1.42%
12/31/2015	1900B	22.8	1850	1.510	52.281	1.520	53.300	-0.66%	-1.91%
			1880	1.547	52.243	1.520	53.300	1.78%	-1.98%
			1910	1.574	52.134	1.520	53.300	3.55%	-2.19%
12/20/2015	2400B-2600B	21.8	2400	1.948	51.491	1.902	52.767	2.42%	-2.42%
			2450	2.021	51.272	1.950	52.700	3.64%	-2.71%
			2500	2.088	51.045	2.021	52.636	3.32%	-3.02%
			2550	2.164	50.883	2.092	52.573	3.44%	-3.21%
			2600	2.222	50.717	2.163	52.509	2.73%	-3.41%
			2650	2.304	50.477	2.234	52.445	3.13%	-3.75%
			2700	2.371	50.254	2.305	52.382	2.86%	-4.06%
12/24/2015	5200B-5800B	21.2	5260	5.519	47.638	5.369	48.933	2.79%	-2.65%
			5300	5.575	47.558	5.416	48.879	2.94%	-2.70%
			5600	5.985	47.029	5.766	48.471	3.80%	-2.97%
			5700	6.118	46.883	5.883	48.336	3.99%	-3.01%
			5745	6.183	46.841	5.936	48.275	4.16%	-2.97%
			5800	6.256	46.704	6.000	48.200	4.27%	-3.10%
			5825	6.277	46.645	6.029	48.166	4.11%	-3.16%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 47 of 75	

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
K	750	HEAD	12/19/2015	23.2	22.0	0.200	1003	3022	1.650	8.090	8.250	1.98%
J	835	HEAD	12/20/2015	19.3	20.7	0.200	4d133	3319	1.810	9.130	9.050	-0.88%
E	1750	HEAD	12/30/2015	24.1	22.2	0.100	1051	3351	3.740	36.200	37.400	3.31%
J	1900	HEAD	12/28/2015	24.2	22.2	0.100	5d149	3319	3.830	40.700	38.300	-5.90%
I	2450	HEAD	12/22/2015	24.5	24.5	0.100	719	3333	5.040	54.200	50.400	-7.01%
E	5250	HEAD	12/28/2015	23.6	21.3	0.050	1191	7308	3.810	82.500	76.200	-7.64%
E	5600	HEAD	12/28/2015	23.6	21.3	0.050	1191	7308	3.950	84.500	79.000	-6.51%
E	5750	HEAD	12/28/2015	23.6	21.3	0.050	1191	7308	3.730	80.000	74.600	-6.75%
G	750	BODY	12/22/2015	20.9	23.0	0.200	1003	3334	1.690	8.460	8.450	-0.12%
H	835	BODY	12/21/2015	22.0	21.8	0.200	4d133	3263	1.980	9.250	9.900	7.03%
G	1750	BODY	12/28/2015	22.4	23.1	0.100	1051	3334	3.530	37.100	35.300	-4.85%
I	1900	BODY	12/21/2015	22.2	21.7	0.100	5d141	3333	4.070	40.000	40.700	1.75%
J	1900	BODY	12/31/2015	23.0	22.8	0.100	5d149	3319	4.030	40.400	40.300	-0.25%
G	2450	BODY	12/20/2015	23.1	21.8	0.100	719	3334	5.180	51.900	51.800	-0.19%
G	2600	BODY	12/20/2016	23.1	21.8	0.100	1004	3334	5.480	56.200	54.800	-2.49%
D	5300	BODY	12/24/2015	21.5	21.1	0.050	1057	7357	3.870	74.200	77.400	4.31%
D	5600	BODY	12/24/2015	21.5	21.1	0.050	1057	7357	4.140	77.700	82.800	6.56%
D	5800	BODY	12/24/2015	21.5	21.1	0.050	1057	7357	3.900	75.100	78.000	3.86%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMG935KOR	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 48 of 75

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.5	22.83	0.07	Right	Cheek	7F4BD	1:1	0.133	1.167	0.155	A1
836.60	4183	UMTS 850	RMC	23.5	22.83	0.21	Right	Tilt	7F4BD	1:1	0.049	1.167	0.057	
836.60	4183	UMTS 850	RMC	23.5	22.83	0.08	Left	Cheek	7F4BD	1:1	0.085	1.167	0.099	
836.60	4183	UMTS 850	RMC	23.5	22.83	0.17	Left	Tilt	7F4BD	1:1	0.042	1.167	0.049	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-2
GSM 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.0	29.33	0.07	Right	Cheek	7F4BD	1:8.3	0.037	1.167	0.043	
1880.00	661	GSM 1900	GSM	30.0	29.33	0.21	Right	Tilt	7F4BD	1:8.3	0.027	1.167	0.032	
1880.00	661	GSM 1900	GSM	30.0	29.33	0.13	Left	Cheek	7F4BD	1:8.3	0.052	1.167	0.061	A2
1880.00	661	GSM 1900	GSM	30.0	29.33	0.09	Left	Tilt	7F4BD	1:8.3	0.024	1.167	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-3
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1852.40	9262	UMTS 1900	RMC	23.0	22.78	-0.10	Right	Cheek	7F539	1:1	0.106	1.052	0.112	
1852.40	9262	UMTS 1900	RMC	23.0	22.78	-0.01	Right	Tilt	7F539	1:1	0.077	1.052	0.081	
1852.40	9262	UMTS 1900	RMC	23.0	22.78	-0.06	Left	Cheek	7F539	1:1	0.166	1.052	0.175	A3
1852.40	9262	UMTS 1900	RMC	23.0	22.78	0.04	Left	Tilt	7F539	1:1	0.062	1.052	0.065	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 49 of 75

Table 11-4
LTE Band 12 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	0.19	0	Right	Cheek	QPSK	1	49	7F53C	1:1	0.041	1.180	0.048	A4
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	0.17	1	Right	Cheek	QPSK	25	25	7F53C	1:1	0.033	1.114	0.037	
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	0.16	0	Right	Tilt	QPSK	1	49	7F53C	1:1	0.016	1.180	0.019	
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	0.17	1	Right	Tilt	QPSK	25	25	7F53C	1:1	0.013	1.114	0.014	
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	0.21	0	Left	Cheek	QPSK	1	49	7F53C	1:1	0.033	1.180	0.039	
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	0.11	1	Left	Cheek	QPSK	25	25	7F53C	1:1	0.026	1.114	0.029	
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	0.04	0	Left	Tilt	QPSK	1	49	7F53C	1:1	0.021	1.180	0.025	
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	0.13	1	Left	Tilt	QPSK	25	25	7F53C	1:1	0.017	1.114	0.019	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-5
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Antenna Config.	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	-0.07	0	Right	Cheek	A	QPSK	1	0	7F4BD	1:1	0.165	1.197	0.198	A5
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	0.13	1	Right	Cheek	A	QPSK	25	0	7F4BD	1:1	0.126	1.189	0.150	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	0.18	0	Right	Tilt	A	QPSK	1	0	7F4BD	1:1	0.060	1.197	0.072	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	0.14	1	Right	Tilt	A	QPSK	25	0	7F4BD	1:1	0.046	1.189	0.055	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	0.12	0	Left	Cheek	A	QPSK	1	0	7F4BD	1:1	0.113	1.197	0.135	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	0.18	1	Left	Cheek	A	QPSK	25	0	7F4BD	1:1	0.089	1.189	0.106	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	0.09	0	Left	Tilt	A	QPSK	1	0	7F4BD	1:1	0.066	1.197	0.079	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	0.03	1	Left	Tilt	A	QPSK	25	0	7F4BD	1:1	0.049	1.189	0.058	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-6
LTE Band 26 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.11	0	Right	Cheek	QPSK	1	0	7F4BD	1:1	0.139	1.191	0.166	A6
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	0.17	1	Right	Cheek	QPSK	36	0	7F4BD	1:1	0.105	1.197	0.126	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.15	0	Right	Tilt	QPSK	1	0	7F4BD	1:1	0.055	1.191	0.066	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	0.19	1	Right	Tilt	QPSK	36	0	7F4BD	1:1	0.040	1.197	0.048	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.05	0	Left	Cheek	QPSK	1	0	7F4BD	1:1	0.092	1.191	0.110	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	0.01	1	Left	Cheek	QPSK	36	0	7F4BD	1:1	0.072	1.197	0.086	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.11	0	Left	Tilt	QPSK	1	0	7F4BD	1:1	0.045	1.191	0.054	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	0.17	1	Left	Tilt	QPSK	36	0	7F4BD	1:1	0.039	1.197	0.047	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 50 of 75

Table 11-7
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	-0.11	0	Right	Cheek	QPSK	1	0	7F538	1:1	0.110	1.202	0.132	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.69	-0.05	1	Right	Cheek	QPSK	50	0	7F538	1:1	0.087	1.205	0.105	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	0.08	0	Right	Tilt	QPSK	1	0	7F538	1:1	0.083	1.202	0.100	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.69	0.07	1	Right	Tilt	QPSK	50	0	7F538	1:1	0.069	1.205	0.083	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	-0.10	0	Left	Cheek	QPSK	1	0	7F538	1:1	0.146	1.202	0.175	A7
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.69	-0.06	1	Left	Cheek	QPSK	50	0	7F538	1:1	0.117	1.205	0.141	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	-0.01	0	Left	Tilt	QPSK	1	0	7F538	1:1	0.079	1.202	0.095	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.69	-0.02	1	Left	Tilt	QPSK	50	0	7F538	1:1	0.061	1.205	0.074	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-8
LTE Band 25 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
Mhz	Ch.														(W/kg)		(W/kg)		
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.78	0.02	0	Right	Cheek	QPSK	1	50	7F539	1:1	0.086	1.180	0.101	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.62	-0.04	1	Right	Cheek	QPSK	50	25	7F539	1:1	0.073	1.225	0.089	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.78	0.04	0	Right	Tilt	QPSK	1	50	7F539	1:1	0.069	1.180	0.081	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.62	0.07	1	Right	Tilt	QPSK	50	25	7F539	1:1	0.061	1.225	0.075	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.78	-0.04	0	Left	Cheek	QPSK	1	50	7F539	1:1	0.156	1.180	0.184	A8
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.62	-0.01	1	Left	Cheek	QPSK	50	25	7F539	1:1	0.120	1.225	0.147	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.78	0.17	0	Left	Tilt	QPSK	1	50	7F539	1:1	0.075	1.180	0.089	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.62	0.06	1	Left	Tilt	QPSK	50	25	7F539	1:1	0.055	1.225	0.067	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-9
LTE Band 41 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2506.00	39750	Low	LTE Band 41	20	23.0	22.27	0.11	0	Right	Cheek	QPSK	1	0	7F4BD	1:1.58	0.054	1.183	0.064	
2506.00	39750	Low	LTE Band 41	20	22.0	21.22	0.10	1	Right	Cheek	QPSK	50	0	7F4BD	1:1.58	0.044	1.197	0.053	
2506.00	39750	Low	LTE Band 41	20	23.0	22.27	0.19	0	Right	Tilt	QPSK	1	0	7F4BD	1:1.58	0.055	1.183	0.065	
2506.00	39750	Low	LTE Band 41	20	22.0	21.22	0.05	1	Right	Tilt	QPSK	50	0	7F4BD	1:1.58	0.042	1.197	0.050	
2506.00	39750	Low	LTE Band 41	20	23.0	22.27	-0.20	0	Left	Cheek	QPSK	1	0	7F4BD	1:1.58	0.093	1.183	0.110	A9
2506.00	39750	Low	LTE Band 41	20	22.0	21.22	0.08	1	Left	Cheek	QPSK	50	0	7F4BD	1:1.58	0.067	1.197	0.080	
2506.00	39750	Low	LTE Band 41	20	23.0	22.27	0.12	0	Left	Tilt	QPSK	1	0	7F4BD	1:1.58	0.033	1.183	0.039	
2506.00	39750	Low	LTE Band 41	20	22.0	21.22	0.15	1	Left	Tilt	QPSK	50	0	7F4BD	1:1.58	0.023	1.197	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 51 of 75

**Table 11-10
DTS Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	14.5	14.18	-0.15	Right	Cheek	1	7F4B7	1	99.8	0.178	0.153	1.076	1.002	0.165	
2462	11	802.11b	DSSS	22	14.5	14.18	-	Right	Tilt	1	7F4B7	1	99.8	0.133	-	1.076	1.002	-	
2462	11	802.11b	DSSS	22	14.5	14.18	-	Left	Cheek	1	7F4B7	1	99.8	0.146	-	1.076	1.002	-	
2462	11	802.11b	DSSS	22	14.5	14.18	-	Left	Tilt	1	7F4B7	1	99.8	0.099	-	1.076	1.002	-	
2412	1	802.11b	DSSS	22	14.5	14.02	0.10	Right	Cheek	2	7F4B7	1	99.8	0.295	0.213	1.117	1.002	0.238	A10
2412	1	802.11b	DSSS	22	14.5	14.02	-	Right	Tilt	2	7F4B7	1	99.8	0.246	-	1.117	1.002	-	
2412	1	802.11b	DSSS	22	14.5	14.02	-	Left	Cheek	2	7F4B7	1	99.8	0.109	-	1.117	1.002	-	
2412	1	802.11b	DSSS	22	14.5	14.02	-	Left	Tilt	2	7F4B7	1	99.8	0.087	-	1.117	1.002	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-11
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5290	58	802.11ac	OFDM	80	11.5	11.31	0.15	Right	Cheek	1	7F4B7	29.3	94.3	0.420	0.198	1.045	1.060	0.219	
5290	58	802.11ac	OFDM	80	11.5	11.31	-	Right	Tilt	1	7F4B7	29.3	94.3	0.335	-	1.045	1.060	-	
5290	58	802.11ac	OFDM	80	11.5	11.31	-	Left	Cheek	1	7F4B7	29.3	94.3	0.216	-	1.045	1.060	-	
5290	58	802.11ac	OFDM	80	11.5	11.31	-	Left	Tilt	1	7F4B7	29.3	94.3	0.187	-	1.045	1.060	-	
5290	58	802.11ac	OFDM	80	11.5	10.89	-	Right	Cheek	2	7F4B7	29.3	94.3	0.646	-	1.151	1.060	-	
5290	58	802.11ac	OFDM	80	11.5	10.89	-	Right	Tilt	2	7F4B7	29.3	94.3	0.596	-	1.151	1.060	-	
5290	58	802.11ac	OFDM	80	11.5	10.89	0.12	Left	Cheek	2	7F4B7	29.3	94.3	0.887	0.320	1.151	1.060	0.390	
5290	58	802.11ac	OFDM	80	11.5	10.89	-	Left	Tilt	2	7F4B7	29.3	94.3	0.655	-	1.151	1.060	-	
5690	138	802.11ac	OFDM	80	11.5	11.34	0.12	Right	Cheek	1	7F4B7	29.3	94.3	0.827	0.350	1.038	1.060	0.385	
5690	138	802.11ac	OFDM	80	11.5	11.34	-	Right	Tilt	1	7F4B7	29.3	94.3	0.699	-	1.038	1.060	-	
5690	138	802.11ac	OFDM	80	11.5	11.34	-	Left	Cheek	1	7F4B7	29.3	94.3	0.461	-	1.038	1.060	-	
5690	138	802.11ac	OFDM	80	11.5	11.34	-	Left	Tilt	1	7F4B7	29.3	94.3	0.412	-	1.038	1.060	-	
5530	106	802.11ac	OFDM	80	11.5	11.48	0.06	Right	Cheek	2	7F4B7	29.3	94.3	1.463	0.594	1.005	1.060	0.633	
5530	106	802.11ac	OFDM	80	11.5	11.48	-	Right	Tilt	2	7F4B7	29.3	94.3	1.165	-	1.005	1.060	-	
5530	106	802.11ac	OFDM	80	11.5	11.48	-0.08	Left	Cheek	2	7F4B7	29.3	94.3	2.407	0.729	1.005	1.060	0.777	A11
5530	106	802.11ac	OFDM	80	11.5	11.48	-	Left	Tilt	2	7F4B7	29.3	94.3	1.170	-	1.005	1.060	-	
5775	155	802.11ac	OFDM	80	11.5	10.51	0.17	Right	Cheek	1	7F4B7	29.3	94.3	1.002	0.455	1.256	1.060	0.605	
5775	155	802.11ac	OFDM	80	11.5	10.51	0.17	Right	Tilt	1	7F4B7	29.3	94.3	0.874	0.356	1.256	1.060	0.474	
5775	155	802.11ac	OFDM	80	11.5	10.51	-	Left	Cheek	1	7F4B7	29.3	94.3	0.509	-	1.256	1.060	-	
5775	155	802.11ac	OFDM	80	11.5	10.51	-	Left	Tilt	1	7F4B7	29.3	94.3	0.444	-	1.256	1.060	-	
5775	155	802.11ac	OFDM	80	11.5	10.98	-	Right	Cheek	2	7F4B7	29.3	94.3	0.910	-	1.127	1.060	-	
5775	155	802.11ac	OFDM	80	11.5	10.98	-	Right	Tilt	2	7F4B7	29.3	94.3	1.042	-	1.127	1.060	-	
5775	155	802.11ac	OFDM	80	11.5	10.98	0.12	Left	Cheek	2	7F4B7	29.3	94.3	2.057	0.608	1.127	1.060	0.726	
5775	155	802.11ac	OFDM	80	11.5	10.98	0.21	Left	Tilt	2	7F4B7	29.3	94.3	1.313	0.450	1.127	1.060	0.537	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 52 of 75

11.2 Standalone Body-Worn SAR Data

Table 11-12
GSM/UMTS/ Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.5	22.83	0.02	10 mm	7F539	N/A	1:1	back	0.345	1.167	0.403	A12
1880.00	661	GSM 1900	GSM	30.0	29.33	0.00	10 mm	7F4C0	1	1:8.3	back	0.173	1.167	0.202	A13
1852.40	9262	UMTS 1900	RMC	23.0	22.78	0.00	10 mm	7F539	N/A	1:1	back	0.508	1.052	0.534	A15
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body								
Spatial Peak							1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population							averaged over 1 gram								

Table 11-13
LTE Body-Worn SAR

MEASUREMENT RESULTS																					
FREQUENCY			Mode	Bandwidth [MHz]	Accessory	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																		(W/kg)		(W/kg)	
707.50	23095	Mid	LTE Band 12	10	None	23.5	22.78	-0.08	0	A	7F53C	QPSK	1	49	10 mm	back	1:1	0.134	1.180	0.158	A17
707.50	23095	Mid	LTE Band 12	10	None	22.5	22.03	0.07	1	A	7F53C	QPSK	25	25	10 mm	back	1:1	0.102	1.114	0.114	
836.50	20525	Mid	LTE Band 5 (Cell)	10	None	24.5	23.72	0.06	0	A	7F53D	QPSK	1	0	10 mm	back	1:1	0.460	1.197	0.551	A19
836.50	20525	Mid	LTE Band 5 (Cell)	10	None	23.5	22.75	-0.03	1	A	7F53D	QPSK	25	0	10 mm	back	1:1	0.365	1.189	0.434	
836.50	20525	Mid	LTE Band 5 (Cell)	10	Headphones	24.5	23.72	0.00	0	A	7F53D	QPSK	1	0	10 mm	back	1:1	0.354	1.197	0.424	
836.50	20525	Mid	LTE Band 5 (Cell)	10	Headphones	23.5	22.75	0.03	1	A	7F53D	QPSK	25	0	10 mm	back	1:1	0.287	1.189	0.341	
836.50	20525	Mid	LTE Band 5 (Cell)	10	None	23.5	22.24	-0.06	0	B	7F537	QPSK	1	0	10 mm	back	1:1	0.278	1.337	0.372	
836.50	20525	Mid	LTE Band 5 (Cell)	10	None	22.5	21.36	-0.02	1	B	7F537	QPSK	25	0	10 mm	back	1:1	0.239	1.300	0.311	
836.50	26915	Mid	LTE Band 26 (Cell)	15	None	23.5	22.74	0.01	0	A	7F53D	QPSK	1	0	10 mm	back	1:1	0.357	1.191	0.425	A21
836.50	26915	Mid	LTE Band 26 (Cell)	15	None	22.5	21.72	-0.01	1	A	7F53D	QPSK	36	0	10 mm	back	1:1	0.296	1.197	0.354	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	None	23.5	22.70	-0.05	0	C	7F4C0	QPSK	1	0	10 mm	back	1:1	0.490	1.202	0.589	A23
1732.50	20175	Mid	LTE Band 4 (AWS)	20	None	22.5	21.69	0.01	1	C	7F4C0	QPSK	50	0	10 mm	back	1:1	0.389	1.205	0.469	
1860.00	26140	Low	LTE Band 25 (PCS)	20	None	23.5	22.78	-0.04	0	C	7F4C0	QPSK	1	50	10 mm	back	1:1	0.542	1.180	0.640	A25
1860.00	26140	Low	LTE Band 25 (PCS)	20	None	22.5	21.62	-0.05	1	C	7F4C0	QPSK	50	25	10 mm	back	1:1	0.427	1.225	0.523	
2506.00	39750	Low	LTE Band 41	20	None	23.0	22.27	0.01	0	C	7F53C	QPSK	1	0	10 mm	back	1:1.58	0.348	1.183	0.412	A27
2506.00	39750	Low	LTE Band 41	20	None	22.0	21.22	0.04	1	C	7F53C	QPSK	50	0	10 mm	back	1:1.58	0.264	1.197	0.316	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak											Body 1.6 W/kg (mW/g) averaged over 1 gram										
Uncontrolled Exposure/General Population																					

Table 11-14
DTS Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	18.5	18.36	-0.03	10 mm	1	7F4C0	1	back	99.8	0.490	0.425	1.033	1.002	0.440	A29
2437	6	802.11b	DSSS	22	18.5	18.42	-0.16	10 mm	2	7F4C0	1	back	99.8	0.307	0.248	1.019	1.002	0.254	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 53 of 75

Table 11-15
NII Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5300	60	802.11a	OFDM	20	15.5	15.49	0.13	10 mm	1	7F4B7	6	back	98.9	0.293	0.135	1.002	1.011	0.136	
5280	52	802.11a	OFDM	20	15.5	15.46	-0.10	10 mm	2	7F4B7	6	back	98.9	0.104	0.050	1.009	1.011	0.051	
5720	144	802.11a	OFDM	20	15.5	15.34	0.18	10 mm	1	7F4B7	6	back	98.9	0.214	0.107	1.038	1.011	0.112	
5600	120	802.11a	OFDM	20	15.5	15.46	-0.10	10 mm	2	7F4B7	6	back	98.9	0.224	0.092	1.009	1.011	0.094	
5825	165	802.11a	OFDM	20	15.5	15.35	0.04	10 mm	1	7F4B7	6	back	98.9	0.355	0.187	1.035	1.011	0.196	A30
5745	149	802.11a	OFDM	20	15.5	15.48	0.21	10 mm	2	7F4B7	6	back	98.9	0.229	0.081	1.005	1.011	0.082	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

11.3 Standalone Hotspot SAR Data

Table 11-16
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.5	22.83	0.02	10 mm	7F539	N/A	1:1	back	0.345	1.167	0.403	A12
836.60	4183	UMTS 850	RMC	23.5	22.83	0.07	10 mm	7F539	N/A	1:1	front	0.340	1.167	0.397	
836.60	4183	UMTS 850	RMC	23.5	22.83	0.03	10 mm	7F539	N/A	1:1	bottom	0.176	1.167	0.205	
836.60	4183	UMTS 850	RMC	23.5	22.83	0.02	10 mm	7F539	N/A	1:1	right	0.233	1.167	0.272	
836.60	4183	UMTS 850	RMC	23.5	22.83	0.02	10 mm	7F539	N/A	1:1	left	0.054	1.167	0.063	
1880.00	661	GSM 1900	GPRS	24.5	23.24	-0.02	10 mm	7F4C0	4	1:2.076	back	0.169	1.337	0.226	
1880.00	661	GSM 1900	GPRS	24.5	23.24	0.03	10 mm	7F4C0	4	1:2.076	front	0.181	1.337	0.242	
1880.00	661	GSM 1900	GPRS	24.5	23.24	-0.02	10 mm	7F4C0	4	1:2.076	bottom	0.302	1.337	0.404	A14
1880.00	661	GSM 1900	GPRS	24.5	23.24	-0.08	10 mm	7F4C0	4	1:2.076	left	0.082	1.337	0.110	
1852.40	9262	UMTS 1900	RMC	23.0	22.78	0.00	10 mm	7F539	N/A	1:1	back	0.508	1.052	0.534	
1852.40	9262	UMTS 1900	RMC	23.0	22.78	0.05	10 mm	7F539	N/A	1:1	front	0.531	1.052	0.559	
1852.40	9262	UMTS 1900	RMC	23.0	22.78	-0.03	10 mm	7F539	N/A	1:1	bottom	0.868	1.052	0.913	
1880.00	9400	UMTS 1900	RMC	23.0	22.25	-0.01	10 mm	7F539	N/A	1:1	bottom	0.860	1.189	1.023	
1907.60	9538	UMTS 1900	RMC	23.0	22.24	-0.04	10 mm	7F539	N/A	1:1	bottom	0.798	1.191	0.950	
1852.40	9262	UMTS 1900	RMC	23.0	22.78	0.01	10 mm	7F539	N/A	1:1	left	0.269	1.052	0.283	
1852.40	9262	UMTS 1900	RMC	23.0	22.78	-0.11	10 mm	7F539	N/A	1:1	bottom	0.875	1.052	0.921	A16
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body								
Spatial Peak							1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population							averaged over 1 gram								

Note: Blue entry represents variability measurement.

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 54 of 75

Table 11-17
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	-0.08	0	7F53C	QPSK	1	49	10 mm	back	1:1	0.134	1.180	0.158	A18
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	0.07	1	7F53C	QPSK	25	25	10 mm	back	1:1	0.102	1.114	0.114	
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	-0.08	0	7F53C	QPSK	1	49	10 mm	front	1:1	0.145	1.180	0.171	
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	-0.03	1	7F53C	QPSK	25	25	10 mm	front	1:1	0.112	1.114	0.125	
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	-0.10	0	7F53C	QPSK	1	49	10 mm	bottom	1:1	0.075	1.180	0.089	
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	0.01	1	7F53C	QPSK	25	25	10 mm	bottom	1:1	0.057	1.114	0.063	
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	-0.17	0	7F53C	QPSK	1	49	10 mm	right	1:1	0.079	1.180	0.093	
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	0.09	1	7F53C	QPSK	25	25	10 mm	right	1:1	0.057	1.114	0.063	
707.50	23095	Mid	LTE Band 12	10	23.5	22.78	0.00	0	7F53C	QPSK	1	49	10 mm	left	1:1	0.028	1.180	0.033	
707.50	23095	Mid	LTE Band 12	10	22.5	22.03	0.16	1	7F53C	QPSK	25	25	10 mm	left	1:1	0.022	1.114	0.025	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-18
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode		Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.																(W/kg)		(W/kg)	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	0.06	0	A	7F53D	QPSK	1	0	10 mm	back	1:1	0.460	1.197	0.551	A20
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	-0.03	1	A	7F53D	QPSK	25	0	10 mm	back	1:1	0.365	1.189	0.434	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	0.06	0	A	7F53D	QPSK	1	0	10 mm	front	1:1	0.469	1.197	0.561	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	-0.03	1	A	7F53D	QPSK	25	0	10 mm	front	1:1	0.362	1.189	0.430	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	0.09	0	A	7F53D	QPSK	1	0	10 mm	bottom	1:1	0.252	1.197	0.302	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	0.08	1	A	7F53D	QPSK	25	0	10 mm	bottom	1:1	0.191	1.189	0.227	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	0.04	0	A	7F53D	QPSK	1	0	10 mm	right	1:1	0.264	1.197	0.316	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	0.07	1	A	7F53D	QPSK	25	0	10 mm	right	1:1	0.222	1.189	0.264	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.72	0.13	0	A	7F53D	QPSK	1	0	10 mm	left	1:1	0.060	1.197	0.072	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.75	0.07	1	A	7F53D	QPSK	25	0	10 mm	left	1:1	0.054	1.189	0.064	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.24	-0.06	0	B	7F537	QPSK	1	0	10 mm	back	1:1	0.278	1.337	0.372	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.36	-0.02	1	B	7F537	QPSK	25	0	10 mm	back	1:1	0.239	1.300	0.311	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.24	-0.07	0	B	7F537	QPSK	1	0	10 mm	front	1:1	0.262	1.337	0.350	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.36	-0.01	1	B	7F537	QPSK	25	0	10 mm	front	1:1	0.221	1.300	0.287	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.24	0.03	0	B	7F537	QPSK	1	0	10 mm	top	1:1	0.146	1.337	0.195	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.36	0.02	1	B	7F537	QPSK	25	0	10 mm	top	1:1	0.120	1.300	0.156	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.24	0.02	0	B	7F537	QPSK	1	0	10 mm	right	1:1	0.046	1.337	0.062	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.36	0.03	1	B	7F537	QPSK	25	0	10 mm	right	1:1	0.041	1.300	0.053	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.24	-0.09	0	B	7F537	QPSK	1	0	10 mm	left	1:1	0.145	1.337	0.194	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.36	0.01	1	B	7F537	QPSK	25	0	10 mm	left	1:1	0.121	1.300	0.157	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram												

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 55 of 75	

Table 11-19
LTE Band 26 (Cell) Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR(1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.														(W/kg)		(W/kg)	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.01	0	7F53D	QPSK	1	0	10 mm	back	1:1	1.191	0.425	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	-0.01	1	7F53D	QPSK	36	0	10 mm	back	1:1	1.197	0.354	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	-0.01	0	7F53D	QPSK	1	0	10 mm	front	1:1	1.191	0.431	A22
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	-0.02	1	7F53D	QPSK	36	0	10 mm	front	1:1	1.197	0.360	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	-0.08	0	7F53D	QPSK	1	0	10 mm	bottom	1:1	1.191	0.241	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	0.03	1	7F53D	QPSK	36	0	10 mm	bottom	1:1	1.197	0.193	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.03	0	7F53D	QPSK	1	0	10 mm	right	1:1	1.191	0.274	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	-0.03	1	7F53D	QPSK	36	0	10 mm	right	1:1	1.197	0.225	
836.50	26915	Mid	LTE Band 26 (Cell)	15	23.5	22.74	-0.13	0	7F53D	QPSK	1	0	10 mm	left	1:1	1.191	0.067	
836.50	26915	Mid	LTE Band 26 (Cell)	15	22.5	21.72	0.04	1	7F53D	QPSK	36	0	10 mm	left	1:1	1.197	0.057	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-20
LTE Band 4 (AWS) Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR(1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.														(W/kg)		(W/kg)	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	-0.05	0	7F4C0	QPSK	1	0	10 mm	back	1:1	1.202	0.589	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.69	0.01	1	7F4C0	QPSK	50	0	10 mm	back	1:1	1.205	0.469	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	-0.10	0	7F4C0	QPSK	1	0	10 mm	front	1:1	1.202	0.653	A24
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.69	0.00	1	7F4C0	QPSK	50	0	10 mm	front	1:1	1.205	0.516	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	0.01	0	7F4C0	QPSK	1	0	10 mm	bottom	1:1	1.202	0.577	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.69	0.02	1	7F4C0	QPSK	50	0	10 mm	bottom	1:1	1.205	0.493	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	-0.06	0	7F4C0	QPSK	1	0	10 mm	left	1:1	1.202	0.440	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.69	-0.04	1	7F4C0	QPSK	50	0	10 mm	left	1:1	1.205	0.341	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-21
LTE Band 25 (PCS) Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR(1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.														(W/kg)		(W/kg)	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.78	-0.04	0	7F4C0	QPSK	1	50	10 mm	back	1:1	1.180	0.640	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.62	-0.05	1	7F4C0	QPSK	50	25	10 mm	back	1:1	1.225	0.523	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.78	0.12	0	7F4C0	QPSK	1	50	10 mm	front	1:1	1.180	0.627	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.62	0.17	1	7F4C0	QPSK	50	25	10 mm	front	1:1	1.225	0.506	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.78	-0.15	0	7F4C0	QPSK	1	50	10 mm	bottom	1:1	1.180	0.884	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.5	22.33	0.13	0	7F4C0	QPSK	1	0	10 mm	bottom	1:1	1.309	1.018	A26
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.31	-0.07	0	7F4C0	QPSK	1	0	10 mm	bottom	1:1	1.315	0.994	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.62	-0.07	1	7F4C0	QPSK	50	25	10 mm	bottom	1:1	1.225	0.730	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.55	-0.05	1	7F4C0	QPSK	100	0	10 mm	bottom	1:1	1.245	0.737	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.78	0.01	0	7F4C0	QPSK	1	50	10 mm	left	1:1	1.180	0.329	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.5	21.62	-0.15	1	7F4C0	QPSK	50	25	10 mm	left	1:1	1.225	0.229	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset	Page 56 of 75	

Table 11-22
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.														(W/kg)		(W/kg)	
2506.00	39750	Low	LTE Band 41	20	23.0	22.27	0.01	0	7F53C	QPSK	1	0	10 mm	back	1:1.58	0.348	1.183	0.412
2506.00	39750	Low	LTE Band 41	20	22.0	21.22	0.04	1	7F53C	QPSK	50	0	10 mm	back	1:1.58	0.264	1.197	0.316
2506.00	39750	Low	LTE Band 41	20	23.0	22.27	0.08	0	7F53C	QPSK	1	0	10 mm	front	1:1.58	0.317	1.183	0.375
2506.00	39750	Low	LTE Band 41	20	22.0	21.22	0.07	1	7F53C	QPSK	50	0	10 mm	front	1:1.58	0.243	1.197	0.291
2506.00	39750	Low	LTE Band 41	20	23.0	22.27	-0.06	0	7F53C	QPSK	1	0	10 mm	bottom	1:1.58	0.654	1.183	0.774
2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.57	0.07	0	7F53C	QPSK	1	0	10 mm	bottom	1:1.58	0.617	1.390	0.858
2593.00	40620	Mid	LTE Band 41	20	23.0	21.58	-0.06	0	7F53C	QPSK	1	0	10 mm	bottom	1:1.58	0.631	1.387	0.875
2636.50	41055	Mid-High	LTE Band 41	20	23.0	22.23	-0.14	0	7F53C	QPSK	1	0	10 mm	bottom	1:1.58	0.493	1.194	0.589
2680.00	41490	High	LTE Band 41	20	23.0	21.92	0.00	0	7F53C	QPSK	1	50	10 mm	bottom	1:1.58	0.483	1.282	0.619
2506.00	39750	Low	LTE Band 41	20	22.0	21.22	-0.08	1	7F53C	QPSK	50	0	10 mm	bottom	1:1.58	0.500	1.197	0.599
2506.00	39750	Low	LTE Band 41	20	22.0	21.14	-0.04	1	7F53C	QPSK	100	0	10 mm	bottom	1:1.58	0.538	1.219	0.656
2506.00	39750	Low	LTE Band 41	20	23.0	22.27	0.04	0	7F53C	QPSK	1	0	10 mm	left	1:1.58	0.173	1.183	0.205
2506.00	39750	Low	LTE Band 41	20	22.0	21.22	-0.04	1	7F53C	QPSK	50	0	10 mm	left	1:1.58	0.130	1.197	0.156
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-23
WLAN Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.													W/kg	(W/kg)				
2462	11	802.11b	DSSS	22	18.5	18.36	-0.03	10 mm	1	7F4C0	1	back	99.8	0.490	0.425	1.033	1.002	0.440	A29
2462	11	802.11b	DSSS	22	18.5	18.36	-0.16	10 mm	1	7F4C0	1	front	99.8	0.315	0.258	1.033	1.002	0.268	
2462	11	802.11b	DSSS	22	18.5	18.36	-	10 mm	1	7F4C0	1	top	99.8	0.201	-	1.033	1.002	-	
2462	11	802.11b	DSSS	22	18.5	18.36	-	10 mm	1	7F4C0	1	left	99.8	0.128	-	1.033	1.002	-	
2437	6	802.11b	DSSS	22	18.5	18.42	-	10 mm	2	7F4C0	1	back	99.8	0.307	-	1.019	1.002	-	
2437	6	802.11b	DSSS	22	18.5	18.42	-	10 mm	2	7F4C0	1	front	99.8	0.248	-	1.019	1.002	-	
2437	6	802.11b	DSSS	22	18.5	18.42	-0.07	10 mm	2	7F4C0	1	top	99.8	0.381	0.286	1.019	1.002	0.292	
2437	6	802.11b	DSSS	22	18.5	18.42	-	10 mm	2	7F4C0	1	left	99.8	0.076	-	1.019	1.002	-	
5825	165	802.11a	OFDM	20	15.5	15.35	0.04	10 mm	1	7F4B7	6	back	98.9	0.355	0.187	1.035	1.011	0.196	
5825	165	802.11a	OFDM	20	15.5	15.35	-	10 mm	1	7F4B7	6	front	98.9	0.325	-	1.035	1.011	-	
5825	165	802.11a	OFDM	20	15.5	15.35	-	10 mm	1	7F4B7	6	top	98.9	0.178	-	1.035	1.011	-	
5825	165	802.11a	OFDM	20	15.5	15.35	-	10 mm	1	7F4B7	6	left	98.9	0.108	-	1.035	1.011	-	
5745	149	802.11a	OFDM	20	15.5	15.48	-	10 mm	2	7F4B7	6	back	98.9	0.229	-	1.005	1.011	-	
5745	149	802.11a	OFDM	20	15.5	15.48	0.19	10 mm	2	7F4B7	6	front	98.9	0.535	0.248	1.005	1.011	0.252	A31
5745	149	802.11a	OFDM	20	15.5	15.48	-	10 mm	2	7F4B7	6	top	98.9	0.144	-	1.005	1.011	-	
5745	149	802.11a	OFDM	20	15.5	15.48	-	10 mm	2	7F4B7	6	left	98.9	0.076	-	1.005	1.011	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 57 of 75

11.4 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. Ant B is disabled in all held to ear scenarios. Therefore Ant B was only tested for body-worn accessory and wireless router conditions.

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 58 of 75

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported (scaled) for LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
6. Body-worn SAR for LTE Band 5 was additionally evaluated with headphones to evaluate a static antenna tuning configuration. The antenna tuning and operating parameters are implemented using a fixed table look-up mechanism and remains unchanged for the same device operating configurations. The operational description contains more information about the static tuning mechanism.

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.6.6 for more information.
4. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06. Please see Section 12 for complete analysis. Per KDB Publication 248227 D01v02r02, MIMO SAR was measured with both antennas transmitting simultaneously at the specified maximum output power in MIMO mode following the initial test configuration procedures.
5. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
6. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 59 of 75

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	12.00	10	0.336

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 60 of 75

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	UMTS 850	0.155	0.165	0.238	0.320	0.393	0.558
	GSM 1900	0.061	0.165	0.238	0.226	0.299	0.464
	UMTS 1900	0.175	0.165	0.238	0.340	0.413	0.578
	LTE Band 12	0.048	0.165	0.238	0.213	0.286	0.451
	LTE Band 5 (Cell)	0.198	0.165	0.238	0.363	0.436	0.601
	LTE Band 26 (Cell)	0.166	0.165	0.238	0.331	0.404	0.569
	LTE Band 4 (AWS)	0.175	0.165	0.238	0.340	0.413	0.578
	LTE Band 25 (PCS)	0.184	0.165	0.238	0.349	0.422	0.587
	LTE Band 41	0.110	0.165	0.238	0.275	0.348	0.513

Table 12-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	UMTS 850	0.155	0.605	0.777	0.760	0.932	1.537
	GSM 1900	0.061	0.605	0.777	0.666	0.838	1.443
	UMTS 1900	0.175	0.605	0.777	0.780	0.952	1.557
	LTE Band 12	0.048	0.605	0.777	0.653	0.825	1.430
	LTE Band 5 (Cell)	0.198	0.605	0.777	0.803	0.975	1.580
	LTE Band 26 (Cell)	0.166	0.605	0.777	0.771	0.943	1.548
	LTE Band 4 (AWS)	0.175	0.605	0.777	0.780	0.952	1.557
	LTE Band 25 (PCS)	0.184	0.605	0.777	0.789	0.961	1.566
	LTE Band 41	0.110	0.605	0.777	0.715	0.887	1.492

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 61 of 75

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 and 5 GHz WLAN Ant 2 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	UMTS 850	0.155	0.165	0.777	0.320	0.932	1.097
	GSM 1900	0.061	0.165	0.777	0.226	0.838	1.003
	UMTS 1900	0.175	0.165	0.777	0.340	0.952	1.117
	LTE Band 12	0.048	0.165	0.777	0.213	0.825	0.990
	LTE Band 5 (Cell)	0.198	0.165	0.777	0.363	0.975	1.140
	LTE Band 26 (Cell)	0.166	0.165	0.777	0.331	0.943	1.108
	LTE Band 4 (AWS)	0.175	0.165	0.777	0.340	0.952	1.117
	LTE Band 25 (PCS)	0.184	0.165	0.777	0.349	0.961	1.126
	LTE Band 41	0.110	0.165	0.777	0.275	0.887	1.052

Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 2 and 5 GHz WLAN Ant 1 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	UMTS 850	0.155	0.238	0.605	0.393	0.760	0.998
	GSM 1900	0.061	0.238	0.605	0.299	0.666	0.904
	UMTS 1900	0.175	0.238	0.605	0.413	0.780	1.018
	LTE Band 12	0.048	0.238	0.605	0.286	0.653	0.891
	LTE Band 5 (Cell)	0.198	0.238	0.605	0.436	0.803	1.041
	LTE Band 26 (Cell)	0.166	0.238	0.605	0.404	0.771	1.009
	LTE Band 4 (AWS)	0.175	0.238	0.605	0.413	0.780	1.018
	LTE Band 25 (PCS)	0.184	0.238	0.605	0.422	0.789	1.027
	LTE Band 41	0.110	0.238	0.605	0.348	0.715	0.953

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 62 of 75

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-6
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	UMTS 850	0.403	0.440	0.254	0.843	0.657	1.097
	GSM 1900	0.202	0.440	0.254	0.642	0.456	0.896
	UMTS 1900	0.534	0.440	0.254	0.974	0.788	1.228
	LTE Band 12	0.158	0.440	0.254	0.598	0.412	0.852
	LTE Band 5 (Cell)	0.551	0.440	0.254	0.991	0.805	1.245
	LTE Band 26 (Cell)	0.425	0.440	0.254	0.865	0.679	1.119
	LTE Band 4 (AWS)	0.589	0.440	0.254	1.029	0.843	1.283
	LTE Band 25 (PCS)	0.640	0.440	0.254	1.080	0.894	1.334
	LTE Band 41	0.412	0.440	0.254	0.852	0.666	1.106

Table 12-7
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	UMTS 850	0.403	0.196	0.094	0.599	0.497	0.693
	GSM 1900	0.202	0.196	0.094	0.398	0.296	0.492
	UMTS 1900	0.534	0.196	0.094	0.730	0.628	0.824
	LTE Band 12	0.158	0.196	0.094	0.354	0.252	0.448
	LTE Band 5 (Cell)	0.551	0.196	0.094	0.747	0.645	0.841
	LTE Band 26 (Cell)	0.425	0.196	0.094	0.621	0.519	0.715
	LTE Band 4 (AWS)	0.589	0.196	0.094	0.785	0.683	0.879
	LTE Band 25 (PCS)	0.640	0.196	0.094	0.836	0.734	0.930
	LTE Band 41	0.412	0.196	0.094	0.608	0.506	0.702

FCC ID: A3LSMG935KOR	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 63 of 75

Table 12-8
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 and 5 GHz WLAN Ant 2
(Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	UMTS 850	0.403	0.440	0.094	0.843	0.497	0.937
	GSM 1900	0.202	0.440	0.094	0.642	0.296	0.736
	UMTS 1900	0.534	0.440	0.094	0.974	0.628	1.068
	LTE Band 12	0.158	0.440	0.094	0.598	0.252	0.692
	LTE Band 5 (Cell)	0.551	0.440	0.094	0.991	0.645	1.085
	LTE Band 26 (Cell)	0.425	0.440	0.094	0.865	0.519	0.959
	LTE Band 4 (AWS)	0.589	0.440	0.094	1.029	0.683	1.123
	LTE Band 25 (PCS)	0.640	0.440	0.094	1.080	0.734	1.174
	LTE Band 41	0.412	0.440	0.094	0.852	0.506	0.946

Table 12-9
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 2 and 5 GHz WLAN Ant 1
(Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	UMTS 850	0.403	0.254	0.196	0.657	0.599	0.853
	GSM 1900	0.202	0.254	0.196	0.456	0.398	0.652
	UMTS 1900	0.534	0.254	0.196	0.788	0.730	0.984
	LTE Band 12	0.158	0.254	0.196	0.412	0.354	0.608
	LTE Band 5 (Cell)	0.551	0.254	0.196	0.805	0.747	1.001
	LTE Band 26 (Cell)	0.425	0.254	0.196	0.679	0.621	0.875
	LTE Band 4 (AWS)	0.589	0.254	0.196	0.843	0.785	1.039
	LTE Band 25 (PCS)	0.640	0.254	0.196	0.894	0.836	1.090
	LTE Band 41	0.412	0.254	0.196	0.666	0.608	0.862

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 64 of 75

Table 12-10
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	UMTS 850	0.403	0.336	0.739
	GSM 1900	0.202	0.336	0.538
	UMTS 1900	0.534	0.336	0.870
	LTE Band 12	0.158	0.336	0.494
	LTE Band 5 (Cell)	0.551	0.336	0.887
	LTE Band 26 (Cell)	0.425	0.336	0.761
	LTE Band 4 (AWS)	0.589	0.336	0.925
	LTE Band 25 (PCS)	0.640	0.336	0.976
	LTE Band 41	0.412	0.336	0.748

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

Table 12-11
Simultaneous Transmission Scenario 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	UMTS 850	0.403	0.440	0.292	0.843	0.695	1.135
	GPRS 1900	0.404	0.440	0.292	0.844	0.696	1.136
	UMTS 1900	1.023	0.440	0.292	1.463	1.315	See Table 12- 12
	LTE Band 12	0.171	0.440	0.292	0.611	0.463	0.903
	LTE Band 5 (Cell)	0.561	0.440	0.292	1.001	0.853	1.293
	LTE Band 26 (Cell)	0.431	0.440	0.292	0.871	0.723	1.163
	LTE Band 4 (AWS)	0.653	0.440	0.292	1.093	0.945	1.385
	LTE Band 25 (PCS)	1.018	0.440	0.292	1.458	1.310	See Table 12- 12
	LTE Band 41	0.875	0.440	0.292	1.315	1.167	See Table 12- 12

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 65 of 75

Table 12-12
Simultaneous Transmission Scenario 2.4 GHz WLAN (Hotspot at 1.0 cm)

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	Back	0.534	0.440	0.292*	0.974	0.826	1.266
	Front	0.559	0.268	0.292*	0.827	0.851	1.119
	Top	-	0.440*	0.292	0.440	0.292	0.732
	Bottom	1.023	-	-	1.023	1.023	1.023
	Right	-	-	-	0.000	0.000	0.000
	Left	0.283	0.440*	0.292*	0.723	0.575	1.015
Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	Back	0.640	0.440	0.292*	1.080	0.932	1.372
	Front	0.627	0.268	0.292*	0.895	0.919	1.187
	Top	-	0.440*	0.292	0.440	0.292	0.732
	Bottom	1.018	-	-	1.018	1.018	1.018
	Right	-	-	-	0.000	0.000	0.000
	Left	0.329	0.440*	0.292*	0.769	0.621	1.061
Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	Back	0.412	0.440	0.292*	0.852	0.704	1.144
	Front	0.375	0.268	0.292*	0.643	0.667	0.935
	Top	-	0.440*	0.292	0.440	0.292	0.732
	Bottom	0.875	-	-	0.875	0.875	0.875
	Right	-	-	-	0.000	0.000	0.000
	Left	0.205	0.440*	0.292*	0.645	0.497	0.937

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 66 of 75

Table 12-13
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	UMTS 850	0.403	0.196	0.252	0.599	0.655	0.851
	GPRS 1900	0.404	0.196	0.252	0.600	0.656	0.852
	UMTS 1900	1.023	0.196	0.252	1.219	1.275	1.471
	LTE Band 12	0.171	0.196	0.252	0.367	0.423	0.619
	LTE Band 5 (Cell)	0.561	0.196	0.252	0.757	0.813	1.009
	LTE Band 26 (Cell)	0.431	0.196	0.252	0.627	0.683	0.879
	LTE Band 4 (AWS)	0.653	0.196	0.252	0.849	0.905	1.101
	LTE Band 25 (PCS)	1.018	0.196	0.252	1.214	1.270	1.466
	LTE Band 41	0.875	0.196	0.252	1.071	1.127	1.323

Table 12-14
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 and 5 GHz WLAN Ant 2
(Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	UMTS 850	0.403	0.440	0.252	0.843	0.655	1.095
	GPRS 1900	0.404	0.440	0.252	0.844	0.656	1.096
	UMTS 1900	1.023	0.440	0.252	1.463	1.275	See Table 12- 15
	LTE Band 12	0.171	0.440	0.252	0.611	0.423	0.863
	LTE Band 5 (Cell)	0.561	0.440	0.252	1.001	0.813	1.253
	LTE Band 26 (Cell)	0.431	0.440	0.252	0.871	0.683	1.123
	LTE Band 4 (AWS)	0.653	0.440	0.252	1.093	0.905	1.345
	LTE Band 25 (PCS)	1.018	0.440	0.252	1.458	1.270	See Table 12- 15
	LTE Band 41	0.875	0.440	0.252	1.315	1.127	1.567

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 67 of 75

Table 12-15
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 and 5 GHz WLAN Ant 2
(Hotspot at 1.0 cm)

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	Back	0.534	0.440	0.252*	0.974	0.786	1.226
	Front	0.559	0.268	0.252	0.827	0.811	1.079
	Top	-	0.440*	0.252*	0.440	0.252	0.692
	Bottom	1.023	-	-	1.023	1.023	1.023
	Right	-	-	-	0.000	0.000	0.000
	Left	0.283	0.440*	0.252*	0.723	0.535	0.975
Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	Back	0.640	0.440	0.252*	1.080	0.892	1.332
	Front	0.627	0.268	0.252	0.895	0.879	1.147
	Top	-	0.440*	0.252*	0.440	0.252	0.692
	Bottom	1.018	-	-	1.018	1.018	1.018
	Right	-	-	-	0.000	0.000	0.000
	Left	0.329	0.440*	0.252*	0.769	0.581	1.021

Table 12-16
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 2 and 5 GHz WLAN Ant 1
(Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	UMTS 850	0.403	0.292	0.196	0.695	0.599	0.891
	GPRS 1900	0.404	0.292	0.196	0.696	0.600	0.892
	UMTS 1900	1.023	0.292	0.196	1.315	1.219	1.511
	LTE Band 12	0.171	0.292	0.196	0.463	0.367	0.659
	LTE Band 5 (Cell)	0.561	0.292	0.196	0.853	0.757	1.049
	LTE Band 26 (Cell)	0.431	0.292	0.196	0.723	0.627	0.919
	LTE Band 4 (AWS)	0.653	0.292	0.196	0.945	0.849	1.141
	LTE Band 25 (PCS)	1.018	0.292	0.196	1.310	1.214	1.506
	LTE Band 41	0.875	0.292	0.196	1.167	1.071	1.363

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 68 of 75

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 69 of 75

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS															
Band	FREQUENCY		Mode	Service	# of Time Slots	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.							(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1852.40	9262	UMTS 1900	RMC	N/A	N/A	bottom	10 mm	0.868	0.875	1.01	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 70 of 75

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8648D	(9kHz-4GHz) Signal Generator	3/15/2015	Annual	3/15/2016	3629U00687
Agilent	8753ES	S-Parameter Network Analyzer	3/12/2015	Annual	3/12/2016	MY40000670
Agilent	8753ES	Network Analyzer	3/20/2015	Annual	3/20/2016	MY40001472
Agilent	E4432B	ESG-D Series Signal Generator	3/16/2015	Annual	3/16/2016	US40053896
Agilent	E4438C	ESG Vector Signal Generator	3/15/2015	Annual	3/15/2016	MY45091346
Agilent	E5515C	Wireless Communications Test Set	11/4/2014	Biennial	11/4/2016	GB43193563
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/15/2015	Annual	3/15/2016	MY45470194
Agilent	N5182A	MXG Vector Signal Generator	3/16/2015	Annual	3/16/2016	MY47420800
Agilent	N9020A	MXA Signal Analyzer	11/5/2015	Annual	11/5/2016	US46470561
Amplifier Research	1551G6	Amplifier	N/A	CBT	N/A	433971
Anritsu	MA24106A	USB Power Sensor	3/2/2015	Annual	3/2/2016	1344555
Anritsu	MA24106A	USB Power Sensor	3/2/2015	Annual	3/2/2016	1344556
Anritsu	MA2411B	Pulse Power Sensor	3/13/2015	Annual	3/13/2016	1207470
Anritsu	MA2411B	Pulse Power Sensor	8/3/2015	Annual	8/3/2016	1126066
Anritsu	MA2481A	Power Sensor	3/10/2015	Annual	3/10/2016	5821
Anritsu	MA2481A	Power Sensor	3/10/2015	Annual	3/10/2016	5605
Anritsu	ML2438A	Power Meter	3/13/2015	Annual	3/13/2016	1190013
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	941001
Anritsu	ML2496A	Power Meter	3/13/2015	Annual	3/13/2016	1351001
Anritsu	MT8820C	Radio Communication Analyzer	6/12/2015	Annual	6/12/2016	6201240328
COMTECH	AR85729-5	Solid State Amplifier	N/A	CBT	N/A	M155A00-009
COMTECH	AR85729-5/57598	Solid State Amplifier	N/A	CBT	N/A	M3W1A00-1002
Control Company	4040	Digital Thermometer	3/15/2015	Biennial	3/15/2017	150194929
Control Company	4353	Long Stem Thermometer	1/22/2015	Biennial	1/22/2017	150053081
Keysight	772D	Dual Directional Coupler	N/A	CBT	N/A	MY52180215
MCL	BW-N6W5+	GdB Attenuator	N/A	CBT	N/A	1139
MiniCircuits	SLP-2400+	Low Pass Filter	N/A	CBT	N/A	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	N/A	CBT	N/A	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	N/A	CBT	N/A	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	N/A	CBT	N/A	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	N/A	CBT	N/A	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	N/A	CBT	N/A	N/A
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264162
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	N/A	CBT	N/A	N/A
Narda	4772-3	Attenuator (3dB)	N/A	CBT	N/A	9406
Pasternack	NC-100	Torque Wrench	5/21/2015	Biennial	5/21/2017	N/A
Pasternack	PE2208-6	Bidirectional Coupler	N/A	CBT	N/A	N/A
Pasternack	PE2209-10	Bidirectional Coupler	N/A	CBT	N/A	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	3/18/2015	Annual	3/18/2016	128633
Rohde & Schwarz	NRVD	Dual Channel Power Meter	N/A	CBT	N/A	101695
Rohde & Schwarz	NRV-Z32	Peak Power Sensor	N/A	CBT	N/A	836019/013
Rohde & Schwarz	SME06	Signal Generator	N/A	CBT	N/A	832026
Rohde & Schwarz	SMIQ03B	Signal Generator	N/A	CBT	N/A	DE27259
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	N/A
SPEAG	D1750V2	1750 MHz SAR Dipole	4/15/2015	Annual	4/15/2016	1051
SPEAG	D1900V2	1900 MHz SAR Dipole	4/14/2015	Annual	4/14/2016	5d141
SPEAG	D1900V2	1900 MHz SAR Dipole	7/14/2015	Annual	7/14/2016	5d149
SPEAG	D2450V2	2450 MHz SAR Dipole	8/20/2015	Annual	8/20/2016	719
SPEAG	D2600V2	2600 MHz SAR Dipole	4/14/2015	Annual	4/14/2016	1004
SPEAG	D5GHzV2	5 GHz SAR Dipole	1/21/2015	Annual	1/21/2016	1057
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/16/2015	Annual	9/16/2016	1191
SPEAG	D750V3	750 MHz SAR Dipole	1/16/2015	Annual	1/16/2016	1003
SPEAG	D835V2	835 MHz SAR Dipole	7/23/2015	Annual	7/23/2016	4d133
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/17/2015	Annual	6/17/2016	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/18/2015	Annual	2/18/2016	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/13/2015	Annual	3/13/2016	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/20/2015	Annual	4/20/2016	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/24/2015	Annual	8/24/2016	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/27/2015	Annual	10/27/2016	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/11/2015	Annual	11/11/2016	1415
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/12/2015	Annual	5/12/2016	1070
SPEAG	DAKS_VNA R140	VNA for Portable DAK	8/16/2015	Annual	8/16/2016	80513
SPEAG	DAKS-3.5	Portable Dielectric Assessment Kit	7/14/2015	Annual	7/14/2016	1039
SPEAG	ES3DV2	SAR Probe	8/26/2015	Annual	8/26/2016	3022
SPEAG	ES3DV3	SAR Probe	3/19/2015	Annual	3/19/2016	3319
SPEAG	ES3DV3	SAR Probe	5/20/2015	Annual	5/20/2016	3263
SPEAG	ES3DV3	SAR Probe	6/22/2015	Annual	6/22/2016	3351
SPEAG	ES3DV3	SAR Probe	10/29/2015	Annual	10/29/2016	3333
SPEAG	ES3DV3	SAR Probe	11/17/2015	Annual	11/17/2016	3334
SPEAG	EX3DV4	SAR Probe	4/23/2015	Annual	4/23/2016	7357
SPEAG	EX3DV4	SAR Probe	7/21/2015	Annual	7/21/2016	7308

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 71 of 75

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 72 of 75

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 73 of 75

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 74 of 75

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMG935KOR		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1512282261-R1.A3L	Test Dates: 12/19/15 - 12/31/15	DUT Type: Portable Handset		Page 75 of 75

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4BD

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.342$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-20-2015; Ambient Temp: 19.3°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.34 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.171 W/kg

SAR(1 g) = 0.133 W/kg



0 dB = 0.147 W/kg = -8.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4BD

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.411 \text{ S/m}$; $\epsilon_r = 38.874$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-28-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(5.1, 5.1, 5.1); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.003 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.0770 W/kg

SAR(1 g) = 0.052 W/kg



0 dB = 0.0602 W/kg = -12.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F539

Communication System: UID 0, UMTS (0); Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$; $\sigma = 1.381 \text{ S/m}$; $\epsilon_r = 38.999$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-28-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(5.1, 5.1, 5.1); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Left Head, Cheek, Low.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.89 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.256 W/kg

SAR(1 g) = 0.166 W/kg



0 dB = 0.198 W/kg = -7.03 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53C

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head; Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.854 \text{ S/m}$; $\epsilon_r = 42.348$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-19-2015; Ambient Temp: 23.2°C; Tissue Temp: 22.0°C

Probe: ES3DV2 - SN3022; ConvF(6.33, 6.33, 6.33); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/18/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch, 10 MHz Bandwidth
QPSK, 1 RB, 49 RB Offset**


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.169 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.0500 W/kg

SAR(1 g) = 0.041 W/kg



0 dB = 0.0444 W/kg = -13.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4BD

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.343$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-20-2015; Ambient Temp: 19.3°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch, 10 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.60 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.209 W/kg

SAR(1 g) = 0.165 W/kg



0 dB = 0.179 W/kg = -7.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4BD

Communication System: UID 0, LTE Band 26; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.343$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-20-2015; Ambient Temp: 19.3°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Right Head, Cheek, Mid.ch, 15 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.10 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.180 W/kg

SAR(1 g) = 0.139 W/kg



0 dB = 0.155 W/kg = -8.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F538

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.323 \text{ S/m}$; $\epsilon_r = 38.562$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-30-2015; Ambient Temp: 24.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(5.24, 5.24, 5.24); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch, 20 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.44 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.218 W/kg

SAR(1 g) = 0.146 W/kg



0 dB = 0.170 W/kg = -7.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F539

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.389 \text{ S/m}$; $\epsilon_r = 38.965$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-28-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(5.1, 5.1, 5.1); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Left Head, Cheek, Low.ch, 20 MHz Bandwidth
QPSK, 1 RB, 50 RB Offset**


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.26 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.240 W/kg

SAR(1 g) = 0.156 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4BD

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Head; Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 1.898 \text{ S/m}$; $\epsilon_r = 39.906$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-22-2015; Ambient Temp: 24.5°C; Tissue Temp: 24.5°C

Probe: ES3DV3 - SN3333; ConvF(4.53, 4.53, 4.53); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Left Head, Cheek, Low.ch, 20 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.096 V/m; Power Drift = -0.20 dB

Peak SAR (extrapolated) = 0.168 W/kg

SAR(1 g) = 0.093 W/kg



0 dB = 0.115 W/kg = -9.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4B7

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$; $\sigma = 1.791 \text{ S/m}$; $\epsilon_r = 40.284$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 12-22-2015; Ambient Temp: 24.5°C; Tissue Temp: 24.5°C

Probe: ES3DV3 - SN3333; ConvF(4.53, 4.53, 4.53); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Right Head, Cheek
Ant 2, Ch 1, 1 Mbps


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.42 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.547 W/kg

SAR(1 g) = 0.213 W/kg



0 dB = 0.310 W/kg = -5.09 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4B7

Communication System: UID 0, IEEE 802.11ac; Frequency: 5530 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5530 \text{ MHz}$; $\sigma = 4.869 \text{ S/m}$; $\epsilon_r = 34.847$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 12-28-2015; Ambient Temp: 23.6°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN7308; ConvF(4.65, 4.65, 4.65); Calibrated: 7/21/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11ac, U-NII-2C, 80 MHz Bandwidth, Left Head, Cheek
Ant 2, Ch 106, 29.3 Mbps


Area Scan (13x22x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 14.81 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 4.04 W/kg

SAR(1 g) = 0.729 W/kg



0 dB = 2.38 W/kg = 3.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F539

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 54.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.25 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.462 W/kg

SAR(1 g) = 0.345 W/kg



0 dB = 0.386 W/kg = -4.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4C0

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.544 \text{ S/m}$; $\epsilon_r = 54.262$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.05 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.271 W/kg

SAR(1 g) = 0.173 W/kg



0 dB = 0.205 W/kg = -6.88 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4C0

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.544 \text{ S/m}$; $\epsilon_r = 54.262$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 4 Tx Slots


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.04 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.499 W/kg

SAR(1 g) = 0.302 W/kg



0 dB = 0.375 W/kg = -4.26 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F539

Communication System: UID 0, UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$; $\sigma = 1.512 \text{ S/m}$; $\epsilon_r = 54.253$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Low.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.66 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.794 W/kg

SAR(1 g) = 0.508 W/kg



0 dB = 0.616 W/kg = -2.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F539

Communication System: UID 0, UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$; $\sigma = 1.513 \text{ S/m}$; $\epsilon_r = 52.278$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-31-2015; Ambient Temp: 23.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3319; ConvF(4.53, 4.53, 4.53); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Bottom Edge, Low.ch


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.24 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.875 W/kg



0 dB = 1.09 W/kg = 0.37 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53C

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.919 \text{ S/m}$; $\epsilon_r = 54.502$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-22-2015; Ambient Temp: 20.9°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch, 10 MHz Bandwidth
QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.37 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.220 W/kg

SAR(1 g) = 0.134 W/kg



0 dB = 0.118 W/kg = -9.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53C

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.919 \text{ S/m}$; $\epsilon_r = 54.502$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-22-2015; Ambient Temp: 20.9°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Front side, Mid.ch, 10 MHz Bandwidth
QPSK, 1 RB, 49 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.27 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.246 W/kg

SAR(1 g) = 0.145 W/kg



0 dB = 0.130 W/kg = -8.86 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53D

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 54.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch, 10 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset, Ant A**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.20 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.617 W/kg

SAR(1 g) = 0.460 W/kg



0 dB = 0.511 W/kg = -2.92 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53D

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 54.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Front side, Mid.ch, 10 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset, Ant A**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.85 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.661 W/kg

SAR(1 g) = 0.469 W/kg



0 dB = 0.531 W/kg = -2.75 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53D

Communication System: UID 0, LTE Band 26; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 54.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch, 15 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.41 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.475 W/kg

SAR(1 g) = 0.357 W/kg



0 dB = 0.399 W/kg = -3.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53D

Communication System: UID 0, LTE Band 26; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.011 \text{ S/m}$; $\epsilon_r = 54.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Front side, Mid.ch, 15 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.62 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.509 W/kg

SAR(1 g) = 0.362 W/kg



0 dB = 0.404 W/kg = -3.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4C0

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.453 \text{ S/m}$; $\epsilon_r = 51.33$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-28-2015; Ambient Temp: 22.4°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3334; ConvF(5.03, 5.03, 5.03); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch, 20 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.45 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.782 W/kg

SAR(1 g) = 0.490 W/kg



0 dB = 0.591 W/kg = -2.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4C0

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.453 \text{ S/m}$; $\epsilon_r = 51.33$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-28-2015; Ambient Temp: 22.4°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3334; ConvF(5.03, 5.03, 5.03); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**LTE Band 4 (AWS), Body SAR, Front side, Mid.ch, 20 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.60 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.850 W/kg

SAR(1 g) = 0.543 W/kg



0 dB = 0.645 W/kg = -1.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4C0

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.521 \text{ S/m}$; $\epsilon_r = 54.255$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, Low.ch, 20 MHz Bandwidth
QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.76 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.868 W/kg

SAR(1 g) = 0.542 W/kg



0 dB = 0.657 W/kg = -1.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4C0

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1882.5 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1882.5 \text{ MHz}$; $\sigma = 1.546 \text{ S/m}$; $\epsilon_r = 54.245$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Body SAR, Bottom Edge, Mid.ch, 20 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x9x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.21 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.778 W/kg



0 dB = 0.929 W/kg = -0.32 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53C

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.097 \text{ S/m}$; $\epsilon_r = 51.026$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-20-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Back side, Low.ch, 20 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.82 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.677 W/kg

SAR(1 g) = 0.348 W/kg



0 dB = 0.440 W/kg = -3.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F53C

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.097 \text{ S/m}$; $\epsilon_r = 51.026$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-20-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Bottom Edge, Low.ch, 20 MHz Bandwidth
QPSK, 1 RB, 0 RB Offset**


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.23 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.32 W/kg

SAR(1 g) = 0.654 W/kg



0 dB = 0.848 W/kg = -0.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4C0

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.037 \text{ S/m}$; $\epsilon_r = 51.218$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-20-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR

Ant 1, Ch 11, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.70 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.864 W/kg

SAR(1 g) = 0.425 W/kg



0 dB = 0.546 W/kg = -2.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4B7

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5825 \text{ MHz}$; $\sigma = 6.277 \text{ S/m}$; $\epsilon_r = 46.645$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-24-2015; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(3.82, 3.82, 3.82); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Body SAR

Ant 1, Ch 165, 6 Mbps, Back Side


Area Scan (12x17x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 8.815 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.777 W/kg

SAR(1 g) = 0.187 W/kg



0 dB = 0.463 W/kg = -3.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG935KOR; Type: Portable Handset; Serial: 7F4B7

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 6.183 \text{ S/m}$; $\epsilon_r = 46.841$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-24-2015; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(3.82, 3.82, 3.82); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Body SAR

Ant 2, Ch 149, 6 Mbps, Front Side


Area Scan (12x18x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 6.285 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.248 W/kg



0 dB = 0.630 W/kg = -2.01 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.891 \text{ S/m}$; $\epsilon_r = 41.857$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-19-2015; Ambient Temp: 23.2°C; Tissue Temp: 22.0°C

Probe: ES3DV2 - SN3022; ConvF(6.33, 6.33, 6.33); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/18/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.44 W/kg

SAR(1 g) = 1.65 W/kg

Deviation(1 g) = 1.98%



0 dB = 1.92 W/kg = 2.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.901 \text{ S/m}$; $\epsilon_r = 40.356$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-20-2015; Ambient Temp: 19.3°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.57 W/kg

SAR(1 g) = 1.81 W/kg

Deviation(1 g) = -0.88%



0 dB = 2.11 W/kg = 3.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.34 \text{ S/m}$; $\epsilon_r = 38.48$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-30-2015; Ambient Temp: 24.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(5.24, 5.24, 5.24); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.76 W/kg

SAR(1 g) = 3.74 W/kg

Deviation(1 g) = 3.31%



0 dB = 4.66 W/kg = 6.68 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.433 \text{ S/m}$; $\epsilon_r = 38.78$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-28-2015; Ambient Temp: 24.2°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(5.1, 5.1, 5.1); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.91 W/kg

SAR(1 g) = 3.83 W/kg

Deviation(1 g) = -5.90%



0 dB = 4.76 W/kg = 6.78 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.836 \text{ S/m}$; $\epsilon_r = 40.112$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-22-2015; Ambient Temp: 24.5°C; Tissue Temp: 24.5°C

Probe: ES3DV3 - SN3333; ConvF(4.53, 4.53, 4.53); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.3 W/kg

SAR(1 g) = 5.04 W/kg

Deviation(1 g) = -7.01%



0 dB = 6.65 W/kg = 8.23 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.591 \text{ S/m}$; $\epsilon_r = 35.221$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-28-2015; Ambient Temp: 23.6°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN7308; ConvF(5.2, 5.2, 5.2); Calibrated: 7/21/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.3 W/kg

SAR(1 g) = 3.81 W/kg

Deviation(1 g) = -7.64%



0 dB = 8.83 W/kg = 9.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.944 \text{ S/m}$; $\epsilon_r = 34.701$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-28-2015; Ambient Temp: 23.6°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN7308; ConvF(4.65, 4.65, 4.65); Calibrated: 7/21/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.6 W/kg

SAR(1 g) = 3.95 W/kg

Deviation(1 g) = -6.51%



0 dB = 9.29 W/kg = 9.68 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 5.106 \text{ S/m}$; $\epsilon_r = 34.515$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-28-2015; Ambient Temp: 23.6°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN7308; ConvF(4.86, 4.86, 4.86); Calibrated: 7/21/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.2 W/kg

SAR(1 g) = 3.73 W/kg

Deviation(1 g) = -6.75%



0 dB = 8.81 W/kg = 9.45 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.959 \text{ S/m}$; $\epsilon_r = 54.099$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-22-2015; Ambient Temp: 20.9°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.42 W/kg

SAR(1 g) = 1.69 W/kg

Deviation(1 g) = -0.12%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.01 \text{ S/m}$; $\epsilon_r = 54.664$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 12-21-2015; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3263; ConvF(6.08, 6.08, 6.08); Calibrated: 5/20/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 6/17/2015

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.88 W/kg

SAR(1 g) = 1.98 W/kg

Deviation(1 g) = 7.03%



0 dB = 2.31 W/kg = 3.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.473 \text{ S/m}$; $\epsilon_r = 51.284$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-28-2015; Ambient Temp: 22.4°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3334; ConvF(5.03, 5.03, 5.03); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: ELI v6.0; Type: QDOVA003AA; Serial: TP:2027

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.17 W/kg

SAR(1 g) = 3.53 W/kg

Deviation(1 g) = -4.85%



0 dB = 4.36 W/kg = 6.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.563 \text{ S/m}$; $\epsilon_r = 54.125$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-21-2015; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(4.7, 4.7, 4.7); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.21 W/kg

SAR(1 g) = 4.07 W/kg

Deviation(1 g) = 1.75%



0 dB = 5.10 W/kg = 7.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.565 \text{ S/m}$; $\epsilon_r = 52.17$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-31-2015; Ambient Temp: 23.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3319; ConvF(4.53, 4.53, 4.53); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.06 W/kg

SAR(1 g) = 4.03 W/kg

Deviation(1 g) = -0.25%



0 dB = 5.02 W/kg = 7.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.021$ S/m; $\epsilon_r = 51.272$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-20-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.9 W/kg

SAR(1 g) = 5.18 W/kg

Deviation(1 g) = -0.19%



0 dB = 6.81 W/kg = 8.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1004

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body; Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.222 \text{ S/m}$; $\epsilon_r = 50.717$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-20-2015; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3334; ConvF(4.29, 4.29, 4.29); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 12.1 W/kg

SAR(1 g) = 5.48 W/kg

Deviation(1 g) = -2.49%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.575 \text{ S/m}$; $\epsilon_r = 47.558$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-24-2015; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(4.11, 4.11, 4.11); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.5 W/kg

SAR(1 g) = 3.87 W/kg

Deviation = 4.31%



0 dB = 9.03 W/kg = 9.56 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.985 \text{ S/m}$; $\epsilon_r = 47.029$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-24-2015; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(3.72, 3.72, 3.72); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.2 W/kg

SAR(1 g) = 4.14 W/kg

Deviation = 6.56%



0 dB = 10.1 W/kg = 10.04 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 6.256 \text{ S/m}$; $\epsilon_r = 46.704$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-24-2015; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(3.82, 3.82, 3.82); Calibrated: 4/23/2015;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/20/2015

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.1 W/kg

SAR(1 g) = 3.9 W/kg

Deviation = 3.86%



0 dB = 9.75 W/kg = 9.89 dBW/kg

APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **ES3-3022_Aug15**

CALIBRATION CERTIFICATE

Object **ES3DV2 - SN:3022**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **August 26, 2015**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

*BN ✓
9/3/2015*

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	01-Apr-15 (No. 217-02128)	Mar-16
Power sensor E4412A	MY41498087	01-Apr-15 (No. 217-02128)	Mar-16
Reference 3 dB Attenuator	SN: S5054 (3c)	01-Apr-15 (No. 217-02129)	Mar-16
Reference 20 dB Attenuator	SN: S5277 (20x)	01-Apr-15 (No. 217-02132)	Mar-16
Reference 30 dB Attenuator	SN: S5129 (30b)	01-Apr-15 (No. 217-02133)	Mar-16
Reference Probe ES3DV2	SN: 3013	30-Dec-14 (No. ES3-3013_Dec14)	Dec-15
DAE4	SN: 660	14-Jan-15 (No. DAE4-660_Jan15)	Jan-16
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-14)	In house check: Oct-15

Calibrated by:	Name Michael Weber	Function Laboratory Technician	Signature <i>M. Weber</i>
Approved by:	Katja Pokovic	Technical Manager	<i>[Signature]</i>

Issued: August 27, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV2

SN:3022

Manufactured: April 15, 2003
Calibrated: August 26, 2015

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.00	1.03	0.95	$\pm 10.1 \%$
DCP (mV) ^B	99.9	99.7	100.9	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	179.6	$\pm 3.3 \%$
		Y	0.0	0.0	1.0		183.9	
		Z	0.0	0.0	1.0		179.0	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	3.60	65.9	14.2	10.00	43.5	$\pm 2.2 \%$
		Y	2.84	63.5	13.0		43.3	
		Z	2.76	63.7	12.7		41.7	
10011-CAB	UMTS-FDD (WCDMA)	X	3.32	67.0	18.7	2.91	144.4	$\pm 0.7 \%$
		Y	3.24	66.3	18.0		147.3	
		Z	3.19	66.3	18.0		143.5	
10012-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	3.15	69.9	19.5	1.87	146.1	$\pm 0.7 \%$
		Y	2.88	67.7	18.0		147.9	
		Z	2.78	67.4	17.8		145.6	
10013-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	11.40	71.3	23.8	9.46	144.9	$\pm 3.3 \%$
		Y	11.15	70.5	23.1		146.9	
		Z	10.95	70.5	23.3		140.3	
10021-DAB	GSM-FDD (TDMA, GMSK)	X	20.66	99.8	29.2	9.39	132.6	$\pm 2.2 \%$
		Y	14.36	93.3	26.6		145.3	
		Z	17.17	97.2	27.8		145.4	
10023-DAB	GPRS-FDD (TDMA, GMSK, TN 0)	X	17.22	96.5	28.2	9.57	125.4	$\pm 1.9 \%$
		Y	11.06	88.6	25.0		136.0	
		Z	8.71	84.6	23.4		130.7	
10024-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	31.05	99.5	25.9	6.56	135.2	$\pm 2.2 \%$
		Y	25.28	97.4	25.0		132.5	
		Z	21.58	95.7	24.5		144.4	
10027-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	42.88	99.9	24.0	4.80	129.5	$\pm 1.9 \%$
		Y	40.80	99.6	23.7		124.9	
		Z	38.42	99.7	23.7		137.8	
10028-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	44.48	100.0	23.2	3.55	138.2	$\pm 1.9 \%$
		Y	44.03	99.7	22.8		133.0	
		Z	41.36	99.8	22.8		147.5	
10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	16.08	99.5	23.3	1.16	127.5	$\pm 1.4 \%$
		Y	79.69	99.6	19.3		146.2	
		Z	45.81	99.9	20.4		138.2	
10100-CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.43	67.4	19.8	5.67	138.7	$\pm 1.4 \%$
		Y	6.27	66.8	19.2		134.9	
		Z	6.16	66.6	19.2		127.6	

10103-CAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	10.13	75.0	25.9	9.29	129.4	±3.3 %
		Y	9.46	73.0	24.5		131.8	
		Z	9.52	74.0	25.4		137.0	
10108-CAC	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.27	66.9	19.7	5.80	137.0	±1.7 %
		Y	6.24	66.7	19.3		140.0	
		Z	6.06	66.3	19.2		127.1	
10117-CAB	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	10.16	68.7	21.3	8.07	127.7	±2.2 %
		Y	9.99	68.2	20.9		131.5	
		Z	10.22	69.1	21.4		141.6	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	9.34	73.4	25.2	9.28	125.0	±3.3 %
		Y	8.92	72.2	24.3		127.2	
		Z	8.95	73.1	25.1		131.9	
10154-CAC	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	5.95	66.4	19.4	5.75	134.4	±1.4 %
		Y	5.92	66.2	19.1		137.0	
		Z	5.98	66.7	19.5		146.8	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.39	66.9	19.6	5.82	139.9	±1.7 %
		Y	6.35	66.7	19.3		141.9	
		Z	6.15	66.2	19.2		128.4	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	4.96	66.6	19.8	5.73	137.3	±1.4 %
		Y	4.85	66.1	19.3		139.8	
		Z	4.85	66.6	19.7		146.7	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	8.75	78.7	28.3	9.21	138.9	±3.0 %
		Y	7.69	75.1	26.1		140.1	
		Z	7.80	76.6	27.2		144.0	
10175-CAC	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	4.88	66.2	19.6	5.72	132.0	±1.4 %
		Y	4.77	65.8	19.1		132.6	
		Z	4.83	66.5	19.6		146.0	
10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	4.91	66.3	19.7	5.72	131.7	±1.4 %
		Y	4.82	66.0	19.2		138.4	
		Z	4.86	66.7	19.7		145.7	
10196-CAB	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	10.04	69.1	21.7	8.10	140.9	±2.2 %
		Y	9.62	67.9	20.8		125.2	
		Z	9.74	68.6	21.3		133.3	
10225-CAB	UMTS-FDD (HSPA+)	X	7.01	67.1	19.6	5.97	143.7	±1.4 %
		Y	6.78	66.2	19.0		129.3	
		Z	6.80	66.7	19.3		136.5	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	8.55	78.0	27.9	9.21	134.6	±3.0 %
		Y	7.79	75.6	26.3		141.6	
		Z	7.89	76.9	27.4		145.2	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	9.30	74.8	26.1	9.24	134.8	±3.3 %
		Y	8.65	72.5	24.5		136.4	
		Z	8.33	72.3	24.8		126.6	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	10.20	76.2	26.8	9.30	144.8	±3.3 %
		Y	9.41	73.7	25.1		145.9	
		Z	9.18	73.9	25.6		138.6	

10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	4.45	66.7	18.9	3.96	147.0	±0.9 %
		Y	4.21	65.5	17.9		126.5	
		Z	4.36	66.5	18.5		148.0	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	3.57	66.3	18.5	3.46	134.3	±0.7 %
		Y	3.48	65.6	17.8		136.8	
		Z	3.51	66.2	18.3		136.4	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	3.53	66.4	18.6	3.39	135.8	±0.7 %
		Y	3.45	65.8	17.9		140.4	
		Z	3.50	66.5	18.5		137.0	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.18	66.5	19.5	5.81	129.4	±1.4 %
		Y	6.15	66.3	19.1		133.6	
		Z	6.13	66.5	19.3		131.2	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.77	67.2	19.9	6.06	134.8	±1.7 %
		Y	6.81	67.3	19.7		144.8	
		Z	6.68	67.1	19.7		136.7	
10400-AAC	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	10.30	69.4	22.0	8.37	142.0	±2.5 %
		Y	9.90	68.2	21.1		126.8	
		Z	10.15	69.3	21.9		142.6	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	4.72	68.1	18.9	3.76	147.8	±0.7 %
		Y	4.56	67.5	18.2		133.6	
		Z	4.61	68.2	18.7		147.4	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	4.57	67.8	18.8	3.77	144.3	±0.7 %
		Y	4.43	67.3	18.1		131.3	
		Z	4.57	68.3	18.8		145.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	2.64	67.9	18.7	1.54	142.1	±0.5 %
		Y	2.36	65.4	16.8		130.3	
		Z	2.50	66.7	17.7		145.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	10.04	69.0	21.7	8.23	138.8	±2.2 %
		Y	9.71	68.0	20.9		125.6	
		Z	9.94	69.0	21.6		140.4	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 7 and 8).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	41.9	0.89	6.33	6.33	6.33	0.46	1.43	± 12.0 %
835	41.5	0.90	6.11	6.11	6.11	0.24	2.08	± 12.0 %
1750	40.1	1.37	5.08	5.08	5.08	0.45	1.47	± 12.0 %
1900	40.0	1.40	4.93	4.93	4.93	0.59	1.25	± 12.0 %
2300	39.5	1.67	4.63	4.63	4.63	0.55	1.39	± 12.0 %
2450	39.2	1.80	4.30	4.30	4.30	0.51	1.47	± 12.0 %
2600	39.0	1.96	4.12	4.12	4.12	0.57	1.46	± 12.0 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	55.5	0.96	6.16	6.16	6.16	0.50	1.34	± 12.0 %
835	55.2	0.97	6.13	6.13	6.13	0.25	2.16	± 12.0 %
1750	53.4	1.49	4.79	4.79	4.79	0.61	1.33	± 12.0 %
1900	53.3	1.52	4.56	4.56	4.56	0.31	2.02	± 12.0 %
2300	52.9	1.81	4.32	4.32	4.32	0.79	1.19	± 12.0 %
2450	52.7	1.95	4.08	4.08	4.08	0.80	1.12	± 12.0 %
2600	52.5	2.16	3.96	3.96	3.96	0.80	1.10	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz, TEM





f=1800 MHz, R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f_{\text{eval}} = 1900 \text{ MHz}$)




Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), f = 900 MHz



DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	98.5
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **ES3-3319_Mar15**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3319**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **March 19, 2015**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	03-Apr-14 (No. 217-01911)	Apr-15
Power sensor E4412A	MY41498087	03-Apr-14 (No. 217-01911)	Apr-15
Reference 3 dB Attenuator	SN: S5054 (3c)	03-Apr-14 (No. 217-01915)	Apr-15
Reference 20 dB Attenuator	SN: S5277 (20x)	03-Apr-14 (No. 217-01919)	Apr-15
Reference 30 dB Attenuator	SN: S5129 (30b)	03-Apr-14 (No. 217-01920)	Apr-15
Reference Probe ES3DV2	SN: 3013	30-Dec-14 (No. ES3-3013_Dec14)	Dec-15
DAE4	SN: 660	14-Jan-15 (No. DAE4-660_Jan15)	Jan-16
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-14)	In house check: Oct-15

Calibrated by:	Name Israe Elnaouq	Function Laboratory Technician	Signature
Approved by:	Katja Pokovic	Technical Manager	

Issued: March 19, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV3

SN:3319

Manufactured: January 10, 2012
Calibrated: March 19, 2015

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3319

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$) ^A	1.12	1.08	1.15	± 10.1 %
DCP (mV) ^B	104.4	106.0	104.4	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu V}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	176.1	±3.3 %
		Y	0.0	0.0	1.0		192.7	
		Z	0.0	0.0	1.0		174.6	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	3.26	64.8	13.4	10.00	41.7	±1.9 %
		Y	2.66	62.2	11.7		39.5	
		Z	3.51	64.8	13.2		42.1	
10011-CAB	UMTS-FDD (WCDMA)	X	3.47	68.1	19.1	2.91	142.9	±0.5 %
		Y	3.37	67.9	19.1		133.0	
		Z	3.57	68.7	19.4		138.6	
10012-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	3.48	71.8	20.2	1.87	143.9	±0.7 %
		Y	3.23	70.9	19.9		134.6	
		Z	3.68	72.8	20.6		140.5	
10013-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	11.18	70.5	23.1	9.46	143.4	±3.3 %
		Y	10.98	70.5	23.2		129.9	
		Z	11.19	70.6	23.1		138.8	
10021-DAB	GSM-FDD (TDMA, GMSK)	X	15.55	92.7	26.1	9.39	126.5	±1.7 %
		Y	21.21	98.0	27.2		142.0	
		Z	19.50	96.1	27.0		125.4	
10023-DAB	GPRS-FDD (TDMA, GMSK, TN 0)	X	23.54	100.0	28.4	9.57	142.6	±2.2 %
		Y	23.24	99.9	28.0		137.4	
		Z	23.57	99.6	28.2		139.7	
10024-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	17.00	90.2	22.7	6.56	128.9	±2.2 %
		Y	35.20	99.7	24.9		148.2	
		Z	33.12	99.6	25.4		123.8	
10027-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	44.20	99.6	23.6	4.80	146.0	±1.9 %
		Y	49.99	99.9	23.0		136.6	
		Z	41.43	99.6	23.9		141.4	
10028-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	46.56	99.7	22.7	3.55	127.7	±2.2 %
		Y	58.11	99.8	21.9		145.3	
		Z	55.65	99.6	22.2		124.3	
10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	34.25	99.4	21.1	1.16	140.3	±1.7 %
		Y	40.72	100.0	20.6		135.7	
		Z	45.39	100.0	20.8		136.4	
10100-CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.30	67.1	19.5	5.67	127.4	±1.4 %
		Y	6.58	68.4	20.3		149.0	
		Z	6.55	68.0	19.9		146.3	

10103-CAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	10.47	75.6	25.8	9.29	146.6	±3.0 %
		Y	10.18	75.8	26.3		136.2	
		Z	10.38	75.3	25.6		140.8	
10108-CAC	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.18	66.6	19.4	5.80	126.9	±1.4 %
		Y	6.40	67.8	20.1		147.0	
		Z	6.44	67.6	19.9		145.7	
10117-CAB	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	10.24	69.0	21.3	8.07	142.7	±2.5 %
		Y	10.25	69.2	21.5		136.7	
		Z	10.16	68.8	21.2		136.6	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	9.85	74.8	25.6	9.28	140.8	±3.0 %
		Y	9.49	74.7	25.9		130.5	
		Z	9.90	74.8	25.6		136.8	
10154-CAC	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	6.13	67.1	19.7	5.75	146.6	±1.4 %
		Y	6.11	67.4	19.9		147.7	
		Z	6.12	67.1	19.7		142.3	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.33	66.7	19.4	5.82	128.9	±1.4 %
		Y	6.33	67.1	19.7		128.7	
		Z	6.57	67.6	19.9		147.4	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	4.89	66.4	19.5	5.73	127.5	±1.2 %
		Y	4.99	67.5	20.2		149.3	
		Z	5.09	67.3	20.0		145.1	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	7.99	75.8	26.3	9.21	127.6	±2.7 %
		Y	9.29	81.7	29.6		149.8	
		Z	8.04	75.8	26.3		123.6	
10175-CAC	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	5.08	67.3	20.0	5.72	149.3	±1.4 %
		Y	5.00	67.6	20.3		145.0	
		Z	5.09	67.3	20.0		145.0	
10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	5.08	67.3	20.0	5.72	148.5	±1.4 %
		Y	5.06	67.9	20.4		147.1	
		Z	5.11	67.4	20.0		144.8	
10196-CAB	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	9.89	68.7	21.2	8.10	134.6	±2.2 %
		Y	9.84	68.9	21.4		130.4	
		Z	9.82	68.5	21.1		130.4	
10225-CAB	UMTS-FDD (HSPA+)	X	7.02	67.1	19.5	5.97	138.0	±1.4 %
		Y	6.88	67.0	19.5		133.2	
		Z	7.01	67.1	19.5		134.6	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	8.01	75.9	26.4	9.21	128.0	±2.7 %
		Y	9.39	82.1	29.9		149.7	
		Z	8.34	76.9	26.9		129.1	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	9.05	73.6	25.1	9.24	130.6	±3.0 %
		Y	8.76	73.7	25.5		123.6	
		Z	9.10	73.6	25.1		127.8	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	9.81	74.7	25.6	9.30	139.3	±3.0 %
		Y	9.50	74.8	25.9		130.7	
		Z	9.81	74.6	25.5		135.0	

10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	4.49	67.1	18.9	3.96	140.1	±0.7 %
		Y	4.46	67.2	19.0		137.6	
		Z	4.52	67.1	18.9		137.1	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	3.68	67.0	18.8	3.46	129.3	±0.7 %
		Y	3.64	67.3	19.0		130.3	
		Z	3.84	67.9	19.2		148.6	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	3.64	67.2	18.8	3.39	131.8	±0.5 %
		Y	3.60	67.4	19.1		128.2	
		Z	3.71	67.5	19.0		128.0	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.43	67.5	19.9	5.81	147.2	±1.7 %
		Y	6.39	67.7	20.0		145.4	
		Z	6.42	67.5	19.8		143.2	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.73	67.1	19.7	6.06	129.7	±1.4 %
		Y	6.75	67.5	19.9		130.8	
		Z	6.75	67.3	19.7		126.2	
10400-AAB	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	10.14	68.9	21.5	8.37	136.7	±2.5 %
		Y	10.23	69.5	22.0		136.5	
		Z	10.13	68.9	21.5		132.8	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	4.97	69.2	19.3	3.76	143.5	±0.5 %
		Y	4.87	69.3	19.4		141.0	
		Z	5.02	69.2	19.3		139.6	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	4.91	69.3	19.4	3.77	139.8	±0.7 %
		Y	4.67	68.9	19.1		138.9	
		Z	4.89	69.1	19.3		137.1	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	2.93	70.1	19.6	1.54	137.8	±0.7 %
		Y	2.84	69.8	19.6		138.2	
		Z	3.04	70.8	19.9		134.2	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	9.94	68.7	21.3	8.23	134.6	±2.2 %
		Y	10.00	69.1	21.7		134.1	
		Z	9.89	68.5	21.2		130.1	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 7 and 8).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3319

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	6.69	6.69	6.69	0.40	1.70	± 12.0 %
835	41.5	0.90	6.41	6.41	6.41	0.43	1.62	± 12.0 %
1750	40.1	1.37	5.29	5.29	5.29	0.80	1.16	± 12.0 %
1900	40.0	1.40	5.10	5.10	5.10	0.80	1.24	± 12.0 %
2300	39.5	1.67	4.77	4.77	4.77	0.64	1.38	± 12.0 %
2450	39.2	1.80	4.55	4.55	4.55	0.80	1.29	± 12.0 %
2600	39.0	1.96	4.39	4.39	4.39	0.80	1.31	± 12.0 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3319

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth (mm) ^G	Unct. (k=2)
750	55.5	0.96	6.10	6.10	6.10	0.34	1.80	± 12.0 %
835	55.2	0.97	6.07	6.07	6.07	0.47	1.56	± 12.0 %
1750	53.4	1.49	4.83	4.83	4.83	0.70	1.36	± 12.0 %
1900	53.3	1.52	4.53	4.53	4.53	0.71	1.39	± 12.0 %
2300	52.9	1.81	4.24	4.24	4.24	0.80	1.26	± 12.0 %
2450	52.7	1.95	4.11	4.11	4.11	0.80	1.10	± 12.0 %
2600	52.5	2.16	3.90	3.90	3.90	0.80	1.11	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range f(SAR_{head})
(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3319**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	-120.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm