



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



MEASUREMENT REPORT FCC Part 22 & 90

Applicant:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

12/27/2016 - 2/16/2017

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

1M1701030006-13.A3L

FCC ID:

A3LSMG950F

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

Applicant Type:

Certification

Model:

SM-G950F

Additional Model(s):

SM-G950FD, SM-G950X

EUT Type

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part:

§2.1049 §22(H) §90.691

Test Procedure(s):

ANSI/TIA-603-D-2010, KDB 971168 D01 v02r02, KDB 648474 D03
v01r04

Test Device Serial No.:

identical prototype [S/N: 1FA85, 1EF00]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortner
President



FCC ID: A3LSMG950F	 PCTEST ENGINEERING LABORATORY, INC.		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 1 of 44

© 2017 PCTEST Engineering Laboratory, Inc.


V 6.0
12/23/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

TABLE OF CONTENTS

FCC PART 22(H) & 90 MEASUREMENT REPORT	3
1.0 INTRODUCTION	5
1.1 Scope	5
1.2 Testing Facility	5
2.0 PRODUCT INFORMATION	6
2.1 Equipment Description	6
2.2 Device Capabilities	6
2.3 Test Configuration	6
2.4 EMI Suppression Device(s)/Modifications	6
3.0 DESCRIPTION OF TESTS	7
3.1 Evaluation Procedure	7
3.2 Occupied Bandwidth	7
3.3 Spurious and Harmonic Emissions at Antenna Terminal	7
3.4 Radiated Power and Radiated Spurious Emissions	8
3.5 Frequency Stability / Temperature Variation	9
4.0 MEASUREMENT UNCERTAINTY	10
5.0 TEST EQUIPMENT CALIBRATION DATA	11
6.0 SAMPLE CALCULATIONS	12
7.0 TEST RESULTS	13
7.1 Summary	13
7.2 Occupied Bandwidth	14
7.3 Spurious and Harmonic Emissions at Antenna Terminal	27
7.4 Band Edge Emissions at Antenna Terminal	30
7.5 Conducted Power Output Data	35
7.6 Radiated Power (ERP)	36
7.7 Radiated Spurious Emissions Measurements	38
7.8 Frequency Stability / Temperature Variation	41
8.0 CONCLUSION	44

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 2 of 44



MEASUREMENT REPORT

FCC Part 22(H) & 90




§2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.
APPLICANT ADDRESS: 129, Samsung-ro,
 Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21045 USA
BASE MODEL: SM-G950F
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
MODE: LTE
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: 1FA85, 1EF00 ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: 12/27/2016 - 2/16/2017
TEST REPORT S/N: 1M1701030006-13.A3L


Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab. located in Columbia, MD 21046, U.S.A.




- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LSMG950F	 Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 3 of 44



MEASUREMENT REPORT

FCC Part 22(H) & 90



Mode	Tx Frequency (MHz)	Emission Designator	Measurement	Max. Power (W)	Max. Power (dBm)	Modulation
LTE Band 26	814.7 - 823.3	1M09G7D	Conducted	0.182	22.61	QPSK
LTE Band 26	814.7 - 823.3	1M09W7D	Conducted	0.146	21.63	16-QAM
LTE Band 26	814.7 - 823.3	1M09W7D	Conducted	0.114	20.58	64-QAM
LTE Band 26	815.5 - 822.5	2M71G7D	Conducted	0.179	22.54	QPSK
LTE Band 26	815.5 - 822.5	2M70W7D	Conducted	0.144	21.57	16-QAM
LTE Band 26	815.5 - 822.5	2M70W7D	Conducted	0.115	20.61	64-QAM
LTE Band 26	816.5 - 821.5	4M54G7D	Conducted	0.182	22.61	QPSK
LTE Band 26	816.5 - 821.5	4M52W7D	Conducted	0.141	21.49	16-QAM
LTE Band 26	816.5 - 821.5	4M52W7D	Conducted	0.110	20.43	64-QAM
LTE Band 26	819	8M98G7D	Conducted	0.176	22.46	QPSK
LTE Band 26	819	8M99W7D	Conducted	0.151	21.80	16-QAM
LTE Band 26	819	8M99W7D	Conducted	0.114	20.58	64-QAM
LTE Band 26	821.5	13M5G7D	Conducted	0.195	22.90	QPSK
LTE Band 26	821.5	13M5W7D	Conducted	0.152	21.81	16-QAM
LTE Band 26	821.5	13M5W7D	Conducted	0.114	20.58	64-QAM
LTE Band 26	821.5	13M5G7D	ERP	0.083	19.18	QPSK
LTE Band 26	821.5	13M5W7D	ERP	0.061	17.82	16-QAM
LTE Band 26	821.5	13M5W7D	ERP	0.036	15.53	64-QAM

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager	
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 4 of 44	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSMG950F	 Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 5 of 44

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMG950F**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 22(H) and 90.691.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on a certified wireless charging pad (WCP) while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 6 of 44

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-D-2010) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

3.2 Occupied Bandwidth

§2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The spectrum analyzers’ “occupied bandwidth” measurement function was used to record the occupied bandwidth in accordance with KDB 971168 D01 v02r02.

3.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, §90.691

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.

Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		 Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 7 of 44

3.4 Radiated Power and Radiated Spurious Emissions

\$2.1053, \$90.635, \$90.691

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v02r02.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$ specified in 90.691.

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v02r02 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-D-2010.

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 8 of 44

3.5 Frequency Stability / Temperature Variation

§2.1055, 90.213(a)

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – For Part 90.213, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 9 of 44

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 10 of 44

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx3	Licensed Transmitter Cable Set	7/12/2016	Annual	7/12/2017	LTx3
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	7/11/2016	Annual	7/11/2017	RE1
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/1/2016	Annual	3/1/2017	MY52350166
Agilent	N9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	7/11/2016	Annual	7/11/2017	441128
Emco	6502	Active Loop Antenna (10k - 30 MHz)	8/9/2016	Biennial	8/9/2018	2936
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
Espec	ESX-2CA	Environmental Chamber	3/4/2016	Annual	3/4/2017	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128337
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	8/23/2016	Biennial	8/23/2018	135427
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/4/2016	Annual	3/4/2017	11401010036
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
PCTEST	-	EMC Switch System	7/11/2016	Annual	7/11/2017	NM1
PCTEST	-	EMC Switch System	7/6/2016	Annual	7/6/2017	NM2
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	7/27/2016	Annual	7/27/2017	103200
Rohde & Schwarz	CMW500	Radio Communication Tester	10/20/2016	Annual	10/20/2017	100976
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/15/2016	Annual	7/15/2017	100348
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/18/2015	Biennial	11/18/2017	91052523RX
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

Notes:

- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMG950F	 Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 11 of 44

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

16QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (–24.80).

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 12 of 44

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMG950F
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE
 Band: Band 26

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 90.691	Conducted Band Edge / Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except $> 50 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge		PASS	Sections 7.3, 7.4
2.1055 90.213	Frequency Stability	< 2.5 ppm		PASS	Section 7.8
2.1046 90.635	Conducted Power	< 100 Watts		PASS	Section 7.5
22.913(a.2)	Effective Radiated Power (Band 26)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
2.1053 90.691	Radiated Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except $> 50 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.7.

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 13 of 44	

7.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 14 of 44




Plot 7-1. Occupied Bandwidth Plot (1.4MHz QPSK – RB Size 6– Low Channel)




Plot 7-2. Occupied Bandwidth Plot (1.4MHz 16-QAM – RB Size 6– Low Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 15 of 44	




Plot 7-3. Occupied Bandwidth Plot (1.4MHz 64-QAM – RB Size 6– Low Channel)




Plot 7-4. Occupied Bandwidth Plot (1.4MHz QPSK – RB Size 6– High Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 16 of 44




Plot 7-5. Occupied Bandwidth Plot (1.4MHz 16-QAM – RB Size 6– High Channel)




Plot 7-6. Occupied Bandwidth Plot (1.4MHz 64-QAM – RB Size 6– High Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 17 of 44




Plot 7-7. Occupied Bandwidth Plot (3MHz QPSK – RB Size 15– Low Channel)




Plot 7-8. Occupied Bandwidth Plot (3MHz 16-QAM – RB Size 15– Low Channel)

FCC ID: A3LSMG950F	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 18 of 44




Plot 7-9. Occupied Bandwidth Plot (3MHz 64-QAM – RB Size 15– Low Channel)




Plot 7-10. Occupied Bandwidth Plot (3MHz QPSK – RB Size 15– High Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 19 of 44




Plot 7-11. Occupied Bandwidth Plot (3MHz 16-QAM – RB Size 15– High Channel)




Plot 7-12. Occupied Bandwidth Plot (3MHz 64-QAM – RB Size 15– High Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 20 of 44




Plot 7-13. Occupied Bandwidth Plot (5MHz QPSK – RB Size 25– Low Channel)



Plot 7-14. Occupied Bandwidth Plot (5MHz 16-QAM – RB Size 25– Low Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 21 of 44




Plot 7-15. Occupied Bandwidth Plot (5MHz 64-QAM – RB Size 25– Low Channel)




Plot 7-16. Occupied Bandwidth Plot (5MHz QPSK – RB Size 25– High Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 22 of 44	




Plot 7-17. Occupied Bandwidth Plot (5MHz 16-QAM – RB Size 25– High Channel)




Plot 7-18. Occupied Bandwidth Plot (5MHz 64-QAM – RB Size 25– High Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 23 of 44



Plot 7-19. Occupied Bandwidth Plot (10MHz QPSK – RB Size 50)




Plot 7-20. Occupied Bandwidth Plot (10MHz 16-QAM – RB Size 50)

FCC ID: A3LSMG950F	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 24 of 44




Plot 7-21. Occupied Bandwidth Plot (10MHz 64-QAM – RB Size 50)




Plot 7-22. Occupied Bandwidth Plot (15MHz QPSK – RB Size 75)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 25 of 44



Plot 7-23. Occupied Bandwidth Plot (15MHz 16-QAM – RB Size 75)



Plot 7-24. Occupied Bandwidth Plot (15MHz 64-QAM – RB Size 75)

FCC ID: A3LSMG950F	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 26 of 44

7.3 Spurious and Harmonic Emissions at Antenna Terminal

\$2.1051 \$90.691

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW $\geq$ 1MHz
3. VBW $\geq$ 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup


Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMG950F	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 27 of 44




Plot 7-25. Conducted Spurious Plot (5MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-26. Conducted Spurious Plot (5MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: A3LSMG950F	 Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 28 of 44



Plot 7-27. Conducted Spurious Plot (5MHz QPSK – RB Size 1, RB Offset 0 – High Channel)



Plot 7-28. Conducted Spurious Plot (5MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 29 of 44

7.4 Band Edge Emissions at Antenna Terminal

~~\$2.1051~~ ~~\$90.691~~

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by greater than 37.5 kHz is $43 + \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by up to and including 37.5 kHz is $50 + 10 \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup

Test Notes


For channel edge emission, the signal analyzer's "ACP" measurement capability is used.

Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION			Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 30 of 44




Plot 7-29. Channel Edge Plot (1.4MHz QPSK – RB Size 6– Low Channel)




Plot 7-30. Channel Edge Plot (1.4MHz QPSK – RB Size 6 – High Channel)

FCC ID: A3LSMG950F	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 31 of 44




Plot 7-31. Channel Edge Plot (3MHz QPSK – RB Size 15– Low Channel)




Plot 7-32. Channel Edge Plot (3MHz QPSK – RB Size 15 – High Channel)

FCC ID: A3LSMG950F	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 32 of 44




Plot 7-33. Channel Edge Plot (5MHz QPSK – RB Size 25– Low Channel)




Plot 7-34. Channel Edge Plot (5MHz QPSK – RB Size 25 – High Channel)

FCC ID: A3LSMG950F	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 33 of 44



Plot 7-35. Channel Edge Plot (10MHz QPSK – RB Size 50)



Plot 7-36. Channel Edge Plot (15MHz QPSK – RB Size 75)

FCC ID: A3LSMG950F	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 34 of 44

7.5 Conducted Power Output Data

\$90.635

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Cond. PWR [dBm]	Cond. PWR [Watts]	Cond. PWR Limit [dBm]	Margin [dB]
814.70	1.4	QPSK	22.61	0.182	50.00	-27.39
823.30	1.4	QPSK	22.39	0.173	50.00	-27.61
814.70	1.4	16-QAM	21.63	0.146	50.00	-28.37
823.30	1.4	16-QAM	21.12	0.129	50.00	-28.88
814.70	1.4	64-QAM	20.58	0.114	50.00	-29.42
823.30	1.4	64-QAM	20.33	0.108	50.00	-29.67
815.50	3	QPSK	22.54	0.179	50.00	-27.46
822.50	3	QPSK	22.50	0.178	50.00	-27.50
815.50	3	16-QAM	21.57	0.144	50.00	-28.43
822.50	3	16-QAM	21.21	0.132	50.00	-28.79
815.50	3	64-QAM	20.61	0.115	50.00	-29.39
822.50	3	64-QAM	20.21	0.105	50.00	-29.79
816.50	5	QPSK	22.61	0.182	50.00	-27.39
821.50	5	QPSK	22.53	0.179	50.00	-27.47
816.50	5	16-QAM	21.49	0.141	50.00	-28.51
821.50	5	16-QAM	21.31	0.135	50.00	-28.69
816.50	5	64-QAM	20.43	0.110	50.00	-29.57
821.50	5	64-QAM	20.30	0.107	50.00	-29.70
819.00	10	QPSK	22.46	0.176	50.00	-27.54
819.00	10	16-QAM	21.80	0.151	50.00	-28.20
819.00	10	64-QAM	20.58	0.114	50.00	-29.42
821.50	15	QPSK	22.90	0.195	50.00	-27.10
821.50	15	16-QAM	21.81	0.152	50.00	-28.19
821.50	15	64-QAM	20.58	0.114	50.00	-29.42

Table 7-2. LTE Band 26 Conducted Power Output Data

NOTES:

1. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
2. This unit was tested with its standard battery.

FCC ID: A3LSMG950F	 Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 35 of 44

7.6 Radiated Power (ERP)

§22.913(a.2)

Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMG950F	 Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 36 of 44

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Radiated Test Setup <1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
821.50	15	QPSK	H	150	73	1 / 74	19.83	-0.65	19.18	38.45	-19.27
821.50	15	16-QAM	H	150	73	1 / 74	18.47	-0.65	17.82	38.45	-20.63
821.50	15	64-QAM	H	150	100	1 / 74	16.18	-0.65	15.53	38.45	-22.92
821.50	15	QPSK	V	150	73	1 / 74	16.61	-0.65	15.96	38.45	-22.49
821.50	15(WCP)	QPSK	H	150	73	1 / 74	16.68	-0.65	16.03	38.45	-22.42

Table 7-37. ERP Data (Band 26)

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset			Page 37 of 44

7.7 Radiated Spurious Emissions Measurements

\$2.1053 \$90.691

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 38 of 44

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

Test Notes

1. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
4. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMG950F	PCTEST ENGINEERING LABORATORY, INC.	Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 39 of 44

OPERATING FREQUENCY: 819.00 MHz
 CHANNEL: 26740
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Margin [dB]
1638.00	H	H	H	-77.13	6.69	-70.43	-57.4

Table 7-3. Radiated Spurious Data (Ch. 26783)

OPERATING FREQUENCY: 819.00 MHz
 CHANNEL: 26740
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Margin [dB]
1638.00	H	-	-	-77.01	6.69	-70.31	-57.3

Table 7-4. Radiated Spurious Data with WCP (Ch. 26783)

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION					Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset				Page 40 of 44	

7.8 Frequency Stability / Temperature Variation

\$2.1055 \$90.213

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Test Procedure Used

ANSI/TIA-603-D-2010

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMG950F	 Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		 Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 41 of 44

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.0
12/23/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

Frequency Stability / Temperature Variation

\$2.1055, \$90.213

OPERATING FREQUENCY: 819,000,000 Hz
 CHANNEL: 26740
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	817,900,000	-199	-0.0000243
100 %		- 30	817,900,000	-131	-0.0000160
100 %		- 20	817,900,000	-139	-0.0000170
100 %		- 10	817,900,000	-84	-0.0000103
100 %		0	817,900,000	-59	-0.0000071
100 %		+ 10	817,900,000	-179	-0.0000218
100 %		+ 20	817,900,000	-163	-0.0000199
100 %		+ 30	817,900,000	-47	-0.0000057
100 %		+ 40	817,900,000	-36	-0.0000044
100 %		+ 50	817,900,000	-79	-0.0000097
BATT. ENDPOINT	3.45	+ 20	817,900,000	-55	-0.0000067

Table 7-5. LTE Band 26 Frequency Stability Data (Ch. 26697)

FCC ID: A3LSMG950F	 Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION 		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 42 of 44

Frequency Stability / Temperature Variation

\$2.1055, \$90.213




Table 7-6. LTE Band 26 Frequency Stability Data (Ch. 26697)

FCC ID: A3LSMG950F			Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION 	Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset		Page 43 of 44

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG950F** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: A3LSMG950F		Part 22(H) & 90 LTE MEASUREMENT REPORT CERTIFICATION		Approved by: Quality Manager
Test Report S/N: 1M1701030006-13.A3L	Test Dates: 12/27/2016 - 2/16/2017	EUT Type: Portable Handset	Page 44 of 44	