



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

03/06/17 - 03/23/17

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M1703100104-01.A3L

FCC ID:

A3LSMG955N

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Class II Permissive Change

FCC Rule Part(s):

CFR §2.1093

Model:

SM-G955N

Original Grant Date:

3-10-2017

Permissive Change(s):

See FCC Change Document

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)	10 gm Phablet (W/kg)
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	< 0.1	< 0.1	0.24	N/A
PCE	UMTS 850	826.40 - 846.60 MHz	0.13	0.20	0.30	N/A
PCE	UMTS 1900	1852.4 - 1907.6 MHz	< 0.1	0.20	0.40	N/A
PCE	LTE Band 12	699.7 - 715.3 MHz	< 0.1	0.16	0.25	N/A
PCE	LTE Band 17	706.5 - 713.5 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 13	779.5 - 784.5 MHz	0.10	0.22	0.36	N/A
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.14	0.23	0.39	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.19	0.31	0.53	N/A
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.13	0.47	1.02	N/A
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.10	0.25	0.50	N/A
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 41	2498.5 - 2687.5 MHz	< 0.1	0.22	1.10	N/A
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.24	< 0.1	0.14	N/A
NII	U-NII-1	5180 - 5240 MHz	N/A	N/A	N/A	N/A
NII	U-NII-2A	5260 - 5320 MHz	0.25	0.16	N/A	1.13
NII	U-NII-2C	5500 - 5720 MHz	0.18	0.32	N/A	1.44
NII	U-NII-3	5745 - 5825 MHz	0.37	0.18	0.29	N/A
DSS	Bluetooth	2402 - 2480 MHz	<0.1	<0.1	<0.1	0.50
Simultaneous SAR per KDB 690783 D01v01r03:			1.22	1.00	1.48	1.99

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 1 of 92

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	13
3	INTRODUCTION	14
4	DOSIMETRIC ASSESSMENT	15
5	DEFINITION OF REFERENCE POINTS	16
6	TEST CONFIGURATION POSITIONS	17
7	RF EXPOSURE LIMITS	21
8	FCC MEASUREMENT PROCEDURES.....	22
9	RF CONDUCTED POWERS	27
10	SYSTEM VERIFICATION.....	57
11	SAR DATA SUMMARY	61
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	76
13	SAR MEASUREMENT VARIABILITY	84
14	EQUIPMENT LIST.....	85
15	MEASUREMENT UNCERTAINTIES.....	89
16	CONCLUSION.....	90
17	REFERENCES	91
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 2 of 92

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
U-NII-1	Data	5180 - 5240 MHz
U-NII-2A	Data	5260 - 5320 MHz
U-NII-2C	Data	5500 - 5720 MHz
U-NII-3	Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz
MST	Data	555Hz - 8.33 kHz

1.2 Power Reduction for SAR

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 3 of 92

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Max Power:

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)					Burst Average 8-PSK (dBm)			
			1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 1900	Maximum	30.2	30.2	27.5	25.0	24.5		26.0	24.0	22.0	21.0
	Nominal	29.7	29.7	27.0	24.5	24.0		25.5	23.5	21.5	20.5

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	22.5	22.5	22.5
	Nominal	22.0	22.0	22.0
UMTS Band 2 (1900 MHz)	Maximum	22.5	22.5	22.5
	Nominal	22.0	22.0	22.0

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 4 of 92

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	23.5
	Nominal	23.0
LTE Band 17	Maximum	23.5
	Nominal	23.0
LTE Band 13	Maximum	24.0
	Nominal	23.5
LTE Band 26 (Cell)	Maximum	23.5
	Nominal	23.0
LTE Band 5 (Cell) Ant A	Maximum	24.5
	Nominal	24.0
LTE Band 5 (Cell) Ant E	Maximum	22.0
	Nominal	21.5
LTE Band 4 (AWS)	Maximum	23.5
	Nominal	23.0
LTE Band 25 (PCS)	Maximum	23.5
	Nominal	23.0
LTE Band 2 (PCS)	Maximum	23.5
	Nominal	23.0
LTE Band 41	Maximum	23.5
	Nominal	23.0
Mode / Band		Modulated Average - Single Tx Chain (Antenna 1 and 2) (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	19.5
	Nominal	19.0
IEEE 802.11g (2.4 GHz)	Maximum	15.5
	Nominal	15.0
IEEE 802.11n (2.4 GHz)	Maximum	14.5
	Nominal	14.0

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 5 of 92

Mode / Band		Modulated Average - Single Tx Chain (Antenna 2) (dBm)
Bluetooth (1 Mbps)	Maximum	15.5
	Nominal	15.0
Bluetooth (EDR)	Maximum	9.5
	Nominal	9.0
Bluetooth LE	Maximum	7.5
	Nominal	7.0
Bluetooth LE (2 Mbps, v5.0)	Maximum	8.0
	Nominal	7.5

Mode / Band		Modulated Average - Single Tx Chain (Antenna 1 and 2) (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	14.5		
	Nominal	14.0		
IEEE 802.11n (5 GHz)	Maximum	14.5		
	Nominal	14.0		
IEEE 802.11ac (5 GHz)	Maximum	12.5	12.5	12.5
	Nominal	12.0	12.0	12.0
Mode / Band		Modulated Average - MIMO (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11g (2.4 GHz)	Maximum	18.5		
	Nominal	18.0		
IEEE 802.11n (2.4 GHz)	Maximum	17.5		
	Nominal	17.0		
IEEE 802.11a (5 GHz)	Maximum	17.5		
	Nominal	17.0		
IEEE 802.11n (5 GHz)	Maximum	17.5	16.5	
	Nominal	17.0	16.0	
IEEE 802.11ac (5 GHz)	Maximum	15.5	15.5	15.5
	Nominal	15.0	15.0	15.0

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 6 of 92

1.3.2 WLAN Reduced Power (Held to Ear):

Mode / Band		Modulated Average - Single Tx Chain (Antenna 1 and 2) (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	15.5
	Nominal	15.0
IEEE 802.11g (2.4 GHz)	Maximum	15.5
	Nominal	15.0
IEEE 802.11n (2.4 GHz)	Maximum	14.5
	Nominal	14.0

Mode / Band		Modulated Average - Single Tx Chain (Antenna 1 and 2) (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	12.5		
	Nominal	12.0		
IEEE 802.11n (5 GHz)	Maximum	12.5		
	Nominal	12.0		
IEEE 802.11ac (5 GHz)	Maximum	12.5	12.5	12.5
	Nominal	12.0	12.0	12.0

Mode / Band		Modulated Average - MIMO (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11g (2.4 GHz)	Maximum	18.5		
	Nominal	18.0		
IEEE 802.11n (2.4 GHz)	Maximum	17.5		
	Nominal	17.0		
IEEE 802.11a (5 GHz)	Maximum	15.5		
	Nominal	15.0		
IEEE 802.11n (5 GHz)	Maximum	15.5	15.5	
	Nominal	15.0	15.0	
IEEE 802.11ac (5 GHz)	Maximum	15.5	15.5	
	Nominal	15.0	15.0	

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 7 of 92

1.3.3 Maximum Powers During Conditions with Simultaneous 2.4 GHz and 5 GHz WLAN:

	# Tx	5 GHz WIFI [dBm]		2.4 GHz WIFI [dBm]		802.11 Modes
		Ant1	Ant2	Ant1	Ant2	
2.4 GHz + 5 GHz	2	A	-	-	B	2.4 GHz: b,g,n 5 GHz: a,n,ac
	2	-	A	B	-	
	2	A	-	B	-	
	2	-	A	-	B	
	3	A	A	B	-	2.4 GHz: b, g, n 5 GHz: n, ac, a (CDD + STBC only)
	3	A	A	-	B	
	3	A	-	B	B	2.4 GHz: n, g (CDD + STBC only) 5 GHz: a, n, ac
	3	-	A	B	B	
	4	A	A	B	B	2.4 GHz: n, g (CDD + STBC only) 5 GHz: n, ac, a (CDD + STBC only)

A = 12 dBm

B = 12 dBm

(Upper tolerance: target + 0.5 dB)

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 1900 Ant B	Yes	Yes	No	Yes	No	Yes
UMTS 850 Ant A	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900 Ant B	Yes	Yes	No	Yes	No	Yes
LTE Band 12 Ant A	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13 Ant A	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell) Ant A	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell) Ant A	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell) Ant E	Yes	Yes	Yes	No	Yes	Yes
LTE Band 4 (AWS) Ant B	Yes	Yes	No	Yes	No	Yes
LTE Band 25 (PCS) Ant B	Yes	Yes	No	Yes	No	Yes
LTE Band 41 Ant B	Yes	Yes	No	Yes	No	Yes
2.4 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
2.4 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes
Bluetooth WLAN Ant 2	Yes	Yes	Yes	No	No	Yes

FCC ID: A3LSMG955N		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 8 of 92	

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled. Therefore, U-NII-1, U-NII-2A, U-NII-2C operations are not considered in this section.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 9 of 92

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet	Notes
1	GSM voice + 2.4 GHz W-Fi	Yes	Yes	N/A	Yes	
2	GSM voice + 5 GHz W-Fi	Yes	Yes	N/A	Yes	
3	GSM voice + 2.4 GHz Bluetooth	Yes*	Yes	N/A	Yes	* BT Tethering Applications are Considered
4	GSM voice + 2.4 GHz W-Fi MIMO	Yes	Yes	N/A	Yes	
5	GSM voice + 5 GHz W-Fi MIMO	Yes	Yes	N/A	Yes	
6	GSM voice + 2.4 GHz W-Fi + 5 GHz W-Fi	Yes	Yes	N/A	Yes	
7	GSM voice + 2.4 GHz W-Fi MIMO + 5 GHz W-Fi MIMO	Yes	Yes	N/A	Yes	
8	UMTS + 2.4 GHz W-Fi	Yes	Yes	Yes	Yes	
9	UMTS + 5 GHz W-Fi	Yes	Yes	Yes	Yes	
10	UMTS + 2.4 GHz Bluetooth	Yes*	Yes	Yes*	Yes	* BT Tethering Applications are Considered
11	UMTS + 2.4 GHz W-Fi MIMO	Yes	Yes	Yes	Yes	
12	UMTS + 5 GHz W-Fi MIMO	Yes	Yes	Yes	Yes	
13	UMTS + 2.4 GHz W-Fi + 5 GHz W-Fi	Yes	Yes	Yes	Yes	
14	UMTS + 2.4 GHz W-Fi MIMO + 5 GHz W-Fi MIMO	Yes	Yes	Yes	Yes	
15	LTE + 2.4 GHz W-Fi	Yes	Yes	Yes	Yes	
16	LTE + 5 GHz W-Fi	Yes	Yes	Yes	Yes	
17	LTE + 2.4 GHz Bluetooth	Yes*	Yes	Yes*	Yes	* BT Tethering Applications are Considered
18	LTE + 2.4 GHz W-Fi MIMO	Yes	Yes	Yes	Yes	
19	LTE + 5 GHz W-Fi MIMO	Yes	Yes	Yes	Yes	
20	LTE + 2.4 GHz W-Fi + 5 GHz W-Fi	Yes	Yes	Yes	Yes	
21	LTE + 2.4 GHz W-Fi MIMO + 5 GHz W-Fi MIMO	Yes	Yes	Yes	Yes	
22	GPRS/EDGE + 2.4 GHz W-Fi	N/A	N/A	Yes	Yes	
23	GPRS/EDGE + 5 GHz W-Fi	N/A	N/A	Yes	Yes	
24	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	N/A	Yes*	Yes	* BT Tethering Applications are Considered
25	GPRS/EDGE + 2.4 GHz W-Fi MIMO	N/A	N/A	Yes	Yes	
26	GPRS/EDGE + 5 GHz W-Fi MIMO	N/A	N/A	Yes	Yes	
27	GPRS/EDGE + 2.4 GHz W-Fi + 5 GHz W-Fi	N/A	N/A	Yes	Yes	
28	GPRS/EDGE + 2.4 GHz W-Fi MIMO + 5 GHz W-Fi MIMO	N/A	N/A	Yes	Yes	

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
3. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
4. 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
5. This device supports 2x2 MIMO Tx for WLAN 802.11a/g/n/ac supports CDD and STBC and 802.11n/ac additionally supports SDM.
6. This device supports Bluetooth tethering for EDR packet only.

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB Publication 941225 D06v02r01.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 10 of 92	

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-1, U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for 2.4 GHz and U-NII-3 WLAN operations since wireless router 1g SAR was < 1.2 W/kg

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was not evaluated for licensed technologies since wireless router 1g SAR was < 1.2 W/kg for these modes.

This device supports both LTE B12 and LTE B17. Since the supported frequency span for LTE B17 falls completely within the supported frequency span for LTE B12, both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B12.

This device supports both LTE B25 (PCS) and LTE B2 (PCS). Since the supported frequency span for LTE B2 (PCS) falls completely within the supported frequency span for LTE B25 (PCS), both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B25 (PCS).

LTE Band 5 Ant E is disabled for all held to ear scenarios. Therefore SAR was only assessed for body-worn accessory and wireless router conditions.

LTE with 64QAM in the uplink is permanently disabled for US operations.

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 11 of 92

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number	Phablet Serial Number
GSM/GPRS/EDGE 1900	E57E5	E57BB	E57BB	-
UMTS 850	E559F	E4A6F	E4A6F	-
UMTS 1900	E57E5	E57BB	E57BB	-
LTE Band 12	E57E5	E57E3	E57E3	-
LTE Band 13	E5667	E57E3	E57E3	-
LTE Band 26 (Cell)	E559F	E4A6F	E4A6F	-
LTE Band 5 (Cell)	E559F	E559F/E57E3	E559F/E57E3	-
LTE Band 4 (AWS)	E559F	E57E3	E57E3	-
LTE Band 25 (PCS)	E57E5	E57BB	E57BB	-
LTE Band 41	E57BB	E559F	E559F	-
2.4 GHz WLAN	CD7B8	CD7B8	CD7B8	-
5 GHz WLAN	CD7B8	D6265	D6265	D6265
Bluetooth	D6265	CD7B8	CD7B8	CD7B8

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 12 of 92

2

LTE INFORMATION

LTE Information					
FCC ID	A3LSMG955N				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 17 (706.5 - 713.5 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
Channel Bandwidths	LTE Band 41 (2498.5 - 2687.5 MHz)				
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 17: 5 MHz, 10 MHz				
	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	Low	Low-Mid	Mid	Mid-High	High
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)
LTE Band 17: 5 MHz	706.5 (23755)		710 (23790)		713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)		710 (23790)		711 (23800)
LTE Band 13: 5 MHz	779.5 (23205)		782 (23230)		784.5 (23255)
LTE Band 13: 10 MHz	N/A		782 (23230)		N/A
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)		831.5 (26865)		848.3 (27033)
LTE Band 26 (Cell): 3 MHz	815.5 (26705)		831.5 (26865)		847.5 (27025)
LTE Band 26 (Cell): 5 MHz	816.5 (26715)		831.5 (26865)		846.5 (27015)
LTE Band 26 (Cell): 10 MHz	819 (26740)		831.5 (26865)		844 (26990)
LTE Band 26 (Cell): 15 MHz	821.5 (26765)		831.5 (26865)		841.5 (26965)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)		1914.3 (26683)
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)		1913.5 (26675)
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)		1912.5 (26665)
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)		1910 (26640)
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)		1907.5 (26615)
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)		1905 (26590)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	6				
DL UE Category	16				
UL UE Category	5				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Release 12 Additional Information	This device does not support full CA features on 3GPP Release 12. All uplink communications are identical to the Release 8 Specifications. The following LTE Release 12 Features are not supported: Carrier Aggregation, Relay, HetNet, Enhanced MIMO, eICIC, WiFi Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: A3LSMG955N		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 13 of 92		

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 14 of 92

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area
Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMG955N		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset			Page 15 of 92

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 16 of 92

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 17 of 92




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 18 of 92

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 19 of 92

6.8 Phablet Configurations

For smart phones with a display diagonal dimension > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna ≤ 25 mm from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 20 of 92

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 21 of 92

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 22 of 92

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 23 of 92

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 24 of 92

achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 25 of 92 REV 18.2 M 11/28/2016

8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.6.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6). When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 26 of 92

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

Maximum Burst-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	29.00	29.02	26.69	25.00	23.51	25.06	23.00	21.31	20.10
	661	29.20	29.03	27.00	25.00	23.52	25.02	23.00	21.64	20.36
	810	29.47	29.50	27.18	24.98	24.06	25.66	23.43	22.00	20.61
Calculated Maximum Frame-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	19.97	19.99	20.67	20.74	20.50	16.03	16.98	17.05	17.09
	661	20.17	20.00	20.98	20.74	20.51	15.99	16.98	17.38	17.35
	810	20.44	20.47	21.16	20.72	21.05	16.63	17.41	17.74	17.60
GSM 1900	Frame Avg. Targets:	20.67	20.67	20.98	20.24	20.99	16.47	17.48	17.24	17.49

FCC ID: A3LSMG955N		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset			Page 27 of 92

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33 (Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A




Figure 9-1
Power Measurement Setup

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 28 of 92

9.2 UMTS Conducted Powers

Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
		4132	4183	4233	9262	9400	9538	
WCDMA	12.2 kbps RMC	22.02	22.22	22.09	21.92	21.90	22.19	-
	12.2 kbps AMR	21.98	22.16	22.00	21.87	21.87	22.00	-
HSDPA	Subtest 1	21.67	21.77	21.69	21.95	22.01	22.15	0
	Subtest 2	22.25	22.22	22.23	21.02	21.05	21.28	0
	Subtest 3	21.81	21.90	21.79	21.61	21.67	21.76	0.5
	Subtest 4	20.73	20.99	20.79	20.70	20.78	20.91	0.5
HSUPA	Subtest 1	20.64	20.81	20.71	20.59	20.57	20.74	0
	Subtest 2	20.74	20.86	20.76	20.68	20.71	20.85	2
	Subtest 3	21.37	21.51	21.39	20.78	20.85	20.99	1
	Subtest 4	20.76	20.89	20.78	20.56	20.68	20.91	2
	Subtest 5	22.07	22.24	22.12	21.92	22.08	22.11	0

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.



Figure 9-2
Power Measurement Setup

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 29 of 92

9.3 LTE Conducted Powers

9.3.1

LTE Band 12

Table 9-1
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.76	0	0
	1	25	22.71		0
	1	49	22.67		0
	25	0	21.72	0-1	1
	25	12	21.66		1
	25	25	21.64		1
	50	0	21.64		1
16QAM	1	0	21.70	0-1	1
	1	25	21.66		1
	1	49	21.65		1
	25	0	20.73	0-2	2
	25	12	20.63		2
	25	25	20.60		2
	50	0	20.61		2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 30 of 92

Table 9-2
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.21	22.86	23.16	0	0
	1	12	23.15	22.93	23.16		0
	1	24	23.21	22.83	23.15		0
	12	0	22.07	21.89	22.06	0-1	1
	12	6	22.09	21.89	22.06		1
	12	13	22.13	21.90	22.03		1
	25	0	22.11	21.88	22.06		1
16QAM	1	0	22.10	21.89	21.98	0-1	1
	1	12	21.98	21.92	22.14		1
	1	24	21.96	21.92	22.16		1
	12	0	21.18	20.93	21.09	0-2	2
	12	6	21.10	20.88	21.08		2
	12	13	21.21	20.93	21.07		2
	25	0	21.18	20.87	21.08		2

Table 9-3
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.20	22.93	23.02	0	0
	1	7	23.19	22.87	22.96		0
	1	14	23.16	22.88	23.02		0
	8	0	22.15	21.87	21.96	0-1	1
	8	4	22.16	21.89	21.98		1
	8	7	22.12	21.89	21.95		1
	15	0	22.13	21.89	21.94		1
16QAM	1	0	22.11	22.09	22.01	0-1	1
	1	7	22.04	21.86	22.06		1
	1	14	22.05	21.77	21.99		1
	8	0	21.27	20.87	20.99	0-2	2
	8	4	21.15	20.86	20.95		2
	8	7	21.14	20.85	20.99		2
	15	0	21.19	20.88	21.02		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 31 of 92

Table 9-4
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.16	22.98	22.98	0	0
	1	2	23.17	22.93	22.94		0
	1	5	23.18	23.00	23.03		0
	3	0	23.13	22.92	22.96		0
	3	2	23.13	22.89	22.96		0
	3	3	23.13	22.89	22.94		0
	6	0	22.08	21.90	21.93	0-1	1
16QAM	1	0	22.40	21.84	22.04	0-1	1
	1	2	22.05	22.15	22.08		1
	1	5	22.05	21.97	22.09		1
	3	0	22.08	21.79	21.90		1
	3	2	22.01	21.93	21.77		1
	3	3	22.11	21.78	21.94		1
	6	0	21.24	20.89	21.04	0-2	2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 32 of 92	

9.3.2

LTE Band 13

Table 9-5
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.82	0	0
	1	25	22.71		0
	1	49	22.81		0
	25	0	21.88	0-1	1
	25	12	21.79		1
	25	25	21.76		1
	50	0	21.80		1
16QAM	1	0	21.84	0-1	1
	1	25	21.80		1
	1	49	21.75		1
	25	0	20.83	0-2	2
	25	12	20.81		2
	25	25	20.72		2
	50	0	20.63		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset			Page 33 of 92

Table 9-6
LTE Band 13 Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.69	0	0
	1	12	22.63		0
	1	24	22.65		0
	12	0	21.81	0-1	1
	12	6	21.73		1
	12	13	21.71		1
	25	0	21.73		1
16QAM	1	0	21.74	0-1	1
	1	12	21.63		1
	1	24	21.69		1
	12	0	20.66	0-2	2
	12	6	20.58		2
	12	13	20.59		2
	25	0	20.66		2

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG955N	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 34 of 92	

9.3.3

LTE Band 26 (Cell)

Table 9-7
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26865 (831.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.74	0	0
	1	36	22.64		0
	1	74	22.50		0
	36	0	21.62	0-1	1
	36	18	21.61		1
	36	37	21.55		1
	75	0	21.54		1
16QAM	1	0	21.43	0-1	1
	1	36	21.38		1
	1	74	21.35		1
	36	0	20.86	0-2	2
	36	18	20.49		2
	36	37	20.42		2
	75	0	20.41		2

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 35 of 92

Table 9-8
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
QPSK	1	0	22.79	22.95	23.04	0	0
	1	25	22.88	22.89	23.01		0
	1	49	22.76	22.82	22.95		0
	25	0	21.80	21.88	22.08	0-1	1
	25	12	21.80	21.88	22.07		1
	25	25	21.78	21.81	22.11		1
	50	0	21.78	21.87	22.08		1
16QAM	1	0	21.90	21.73	22.15	0-1	1
	1	25	21.91	21.73	22.05		1
	1	49	21.81	21.66	21.96		1
	25	0	20.72	20.78	20.94	0-2	2
	25	12	20.69	20.74	20.95		2
	25	25	20.69	20.74	20.93		2
	50	0	20.62	20.68	20.98		2

Table 9-9
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.77	23.02	22.92	0	0
	1	12	22.93	22.95	22.90		0
	1	24	22.78	22.97	22.87		0
	12	0	21.63	21.87	21.98	0-1	1
	12	6	21.67	21.88	21.96		1
	12	13	21.63	21.87	21.95		1
	25	0	21.65	21.89	21.99		1
16QAM	1	0	21.56	21.92	22.13	0-1	1
	1	12	21.47	21.79	21.93		1
	1	24	21.76	21.73	22.02		1
	12	0	20.51	20.80	20.88	0-2	2
	12	6	20.41	20.79	20.84		2
	12	13	20.46	20.73	20.81		2
	25	0	20.49	20.72	20.88		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 36 of 92	

Table 9-10
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.79	22.92	22.91	0	0
	1	7	22.80	22.89	22.88		0
	1	14	22.88	22.90	22.84		0
	8	0	21.77	21.91	21.94	0-1	1
	8	4	21.74	21.88	21.93		1
	8	7	21.79	21.87	21.93		1
	15	0	21.72	21.84	21.92		1
16QAM	1	0	21.90	21.99	21.86	0-1	1
	1	7	21.86	21.96	21.98		1
	1	14	21.67	21.87	21.86		1
	8	0	20.74	20.64	20.80	0-2	2
	8	4	20.70	20.74	20.86		2
	8	7	20.64	20.69	20.80		2
	15	0	20.53	20.65	20.84		2

Table 9-11
LTE Band 26 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.94	22.94	22.89	0	0
	1	2	22.88	22.97	22.88		0
	1	5	22.94	22.96	22.93		0
	3	0	22.88	22.88	22.89		0
	3	2	22.91	22.87	22.88		0
	3	3	22.87	22.85	22.87		0
	6	0	21.84	21.83	21.95	0-1	1
16QAM	1	0	21.87	21.96	22.14	0-1	1
	1	2	21.91	22.14	22.02		1
	1	5	21.98	21.89	22.01		1
	3	0	21.85	21.75	22.02		1
	3	2	21.80	21.80	22.03		1
	3	3	21.82	21.82	22.05		1
	6	0	20.77	20.71	20.83	0-2	2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 37 of 92

9.3.4

LTE Band 5 (Cell) – Antenna A

Table 9-12
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.09	0	0
	1	25	23.02		0
	1	49	23.00		0
	25	0	22.14	0-1	1
	25	12	22.03		1
	25	25	22.05		1
	50	0	22.11		1
16QAM	1	0	22.01	0-1	1
	1	25	22.05		1
	1	49	21.94		1
	25	0	21.01	0-2	2
	25	12	21.17		2
	25	25	21.03		2
	50	0	21.07		2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-13
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.41	22.98	23.36	0	0
	1	12	23.45	23.00	23.33		0
	1	24	23.32	22.93	23.19		0
	12	0	22.30	21.88	22.39	0-1	1
	12	6	22.33	21.88	22.36		1
	12	13	22.34	21.84	22.33		1
	25	0	22.30	21.85	22.36		1
16QAM	1	0	22.16	21.66	22.36	0-1	1
	1	12	22.17	21.63	22.32		1
	1	24	22.22	21.96	22.47		1
	12	0	21.33	20.80	21.36	0-2	2
	12	6	21.32	20.87	21.34		2
	12	13	21.41	20.87	21.38		2
	25	0	21.33	20.85	21.36		2

FCC ID: A3LSMG955N



SAR EVALUATION REPORT



Approved by:
Quality Manager

Document S/N:

Test Dates:

DUT Type:

1M1703100104-01.A3L

03/06/17 - 03/23/17

Portable Handset

Page 38 of 92

Table 9-14
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.32	22.82	23.46	0	0
	1	7	23.37	22.76	23.42		0
	1	14	23.38	22.84	23.39		0
	8	0	22.39	21.88	22.34	0-1	1
	8	4	22.32	21.87	22.33		1
	8	7	22.36	21.86	22.33		1
	15	0	22.30	21.84	22.35		1
16QAM	1	0	22.26	21.93	22.19	0-1	1
	1	7	22.15	22.09	22.25		1
	1	14	22.41	21.81	22.14		1
	8	0	21.33	20.83	21.32	0-2	2
	8	4	21.35	20.76	21.31		2
	8	7	21.26	20.80	21.40		2
	15	0	21.24	20.78	21.32		2

Table 9-15
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.39	22.94	23.44	0	0
	1	2	23.34	22.89	23.39		0
	1	5	23.45	22.94	23.39		0
	3	0	23.34	22.87	23.35		0
	3	2	23.35	22.85	23.32		0
	3	3	23.35	22.88	23.31		0
	6	0	22.29	21.90	22.40	0-1	1
16QAM	1	0	22.42	21.87	22.47	0-1	1
	1	2	22.22	21.85	22.48		1
	1	5	22.38	22.09	22.34		1
	3	0	22.27	21.85	22.40		1
	3	2	22.23	21.80	22.34		1
	3	3	22.34	21.80	22.37		1
	6	0	21.41	20.93	21.39	0-2	2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 39 of 92	

9.3.5

LTE Band 5 (Cell) – Antenna E

Table 9-16
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	20.58	0	0
	1	25	20.55		0
	1	49	20.52		0
	25	0	19.66	0-1	1
	25	12	19.56		1
	25	25	19.54		1
	50	0	19.56		1
16QAM	1	0	19.63	0-1	1
	1	25	19.62		1
	1	49	19.57		1
	25	0	18.59	0-2	2
	25	12	18.50		2
	25	25	18.54		2
	50	0	18.51		2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-17
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.63	20.59	20.54	0	0
	1	12	20.56	20.59	20.66		0
	1	24	20.51	20.67	20.68		0
	12	0	19.80	19.84	20.03	0-1	1
	12	6	19.86	19.86	19.66		1
	12	13	19.56	19.60	19.68		1
	25	0	19.60	19.72	19.64		1
16QAM	1	0	19.66	19.67	19.74	0-1	1
	1	12	19.64	19.70	19.71		1
	1	24	19.60	19.74	19.52		1
	12	0	18.67	18.66	18.59	0-2	2
	12	6	18.63	18.74	18.88		2
	12	13	18.69	18.76	18.75		2
	25	0	18.64	18.79	18.69		2

FCC ID: A3LSMG955N				Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 40 of 92

Table 9-18
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.62	20.55	20.55	0	0
	1	7	20.70	20.62	20.75		0
	1	14	20.67	20.78	20.65		0
	8	0	19.87	19.76	20.05	0-1	1
	8	4	19.65	19.85	19.77		1
	8	7	19.63	19.66	19.65		1
	15	0	19.58	19.71	19.70		1
16QAM	1	0	19.62	19.70	19.79	0-1	1
	1	7	19.88	19.59	19.76		1
	1	14	19.61	19.69	19.58		1
	8	0	18.66	18.76	18.60	0-2	2
	8	4	18.56	18.83	18.90		2
	8	7	18.70	18.63	18.75		2
	15	0	18.65	18.81	18.67		2

Table 9-19
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.56	20.66	20.63	0	0
	1	2	20.59	20.71	20.77		0
	1	5	20.62	20.59	20.56		0
	3	0	20.85	20.85	20.55		0
	3	2	20.75	20.65	20.68		0
	3	3	20.56	20.52	20.72		0
	6	0	19.74	19.73	19.60	0-1	1
16QAM	1	0	19.53	19.60	19.92	0-1	1
	1	2	19.61	19.67	19.73		1
	1	5	19.56	19.67	19.57		1
	3	0	19.55	19.67	19.64		1
	3	2	19.65	19.68	19.79		1
	3	3	19.64	19.81	19.70		1
	6	0	18.63	18.80	18.78	0-2	2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 41 of 92

9.3.6

LTE Band 4 (AWS)

Table 9-20
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.51	0	0
	1	50	22.43		0
	1	99	22.43		0
	50	0	21.58	0-1	1
	50	25	21.46		1
	50	50	21.40		1
	100	0	21.52		1
16QAM	1	0	21.88	0-1	1
	1	50	21.68		1
	1	99	21.69		1
	50	0	20.68	0-2	2
	50	25	20.46		2
	50	50	20.48		2
	100	0	20.50		2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 42 of 92

Table 9-21
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 4 (AWS) 15 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.71	22.46	22.94	0	0
	1	36	22.69	22.39	22.93		0
	1	74	22.66	22.43	22.89		0
	36	0	21.68	21.51	21.87	0-1	1
	36	18	21.70	21.49	21.86		1
	36	37	21.71	21.49	21.85		1
	75	0	21.69	21.53	21.88		1
16QAM	1	0	21.62	21.62	21.82	0-1	1
	1	36	21.67	21.55	21.74		1
	1	74	21.52	21.34	21.75		1
	36	0	20.68	20.52	20.91	0-2	2
	36	18	20.66	20.59	20.89		2
	36	37	20.63	20.53	20.93		2
	75	0	20.67	20.54	20.94		2

Table 9-22
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 4 (AWS) 10 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.62	22.48	22.86	0	0
	1	25	22.69	22.44	22.93		0
	1	49	22.60	22.45	22.95		0
	25	0	21.58	21.50	21.87	0-1	1
	25	12	21.60	21.48	21.85		1
	25	25	21.60	21.44	21.85		1
	50	0	21.58	21.47	21.86		1
16QAM	1	0	21.65	21.76	21.74	0-1	1
	1	25	21.68	21.58	21.74		1
	1	49	21.61	21.46	21.77		1
	25	0	20.57	20.44	20.96	0-2	2
	25	12	20.60	20.59	20.95		2
	25	25	20.60	20.53	20.92		2
	50	0	20.57	20.47	20.94		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 43 of 92	

Table 9-23
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 4 (AWS) 5 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.62	22.56	22.88	0	0
	1	12	22.34	22.57	22.89		0
	1	24	22.50	22.55	22.92		0
	12	0	21.52	21.54	21.84	0-1	1
	12	6	21.52	21.46	21.83		1
	12	13	21.52	21.48	21.83		1
	25	0	21.51	21.46	21.84		1
16QAM	1	0	21.44	21.49	21.68	0-1	1
	1	12	21.45	21.58	21.83		1
	1	24	21.55	21.49	21.85		1
	12	0	20.48	20.46	20.82	0-2	2
	12	6	20.48	20.40	20.83		2
	12	13	20.54	20.40	20.83		2
	25	0	20.53	20.44	20.85		2

Table 9-24
LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 4 (AWS) 3 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.40	22.46	22.97	0	0
	1	7	22.40	22.41	22.93		0
	1	14	22.47	22.44	22.95		0
	8	0	21.44	21.49	21.90	0-1	1
	8	4	21.45	21.50	21.87		1
	8	7	21.39	21.46	21.86		1
	15	0	21.40	21.47	21.90		1
16QAM	1	0	21.52	21.52	22.09	0-1	1
	1	7	21.56	21.62	21.90		1
	1	14	21.40	21.60	21.94		1
	8	0	20.43	20.46	20.90	0-2	2
	8	4	20.43	20.46	20.85		2
	8	7	20.40	20.50	20.80		2
	15	0	20.34	20.42	20.86		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 44 of 92	

Table 9-25
LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 4 (AWS) 1.4 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.45	22.45	22.97	0	0
	1	2	22.38	22.53	22.92		0
	1	5	22.38	22.58	22.98		0
	3	0	22.37	22.49	22.88		0
	3	2	22.39	22.41	22.90		0
	3	3	22.35	22.44	22.89		0
	6	0	21.47	21.54	21.90	0-1	1
16QAM	1	0	21.55	21.62	21.96	0-1	1
	1	2	21.40	21.52	22.05		1
	1	5	21.62	21.49	21.95		1
	3	0	21.30	21.46	21.89		1
	3	2	21.40	21.41	21.77		1
	3	3	21.33	21.45	21.86		1
	6	0	20.51	20.40	20.92	0-2	2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 45 of 92

9.3.7

LTE Band 25 (PCS)

Table 9-26
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.40	22.62	22.68	0	0
	1	50	22.36	22.50	22.62		0
	1	99	22.34	22.45	22.65		0
	50	0	21.56	21.58	21.82	0-1	1
	50	25	21.47	21.52	21.70		1
	50	50	21.45	21.41	21.68		1
16QAM	100	0	21.43	21.46	21.70	0-1	1
	1	0	21.40	21.80	21.98		1
	1	50	21.42	21.71	21.92		1
	1	99	21.43	21.70	21.95	0-2	1
	50	0	20.61	20.63	20.86		2
	50	25	20.49	20.46	20.75		2
	50	50	20.44	20.42	20.76		2
	100	0	20.42	20.48	20.78		2

Table 9-27
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.35	22.49	22.86	0	0
	1	36	22.37	22.48	22.85		0
	1	74	22.33	22.41	22.80		0
	36	0	21.35	21.46	21.76	0-1	1
	36	18	21.33	21.46	21.79		1
	36	37	21.32	21.44	21.76		1
	75	0	21.34	21.44	21.76		1
16QAM	1	0	21.21	21.41	21.66	0-1	1
	1	36	21.17	21.45	21.75		1
	1	74	21.20	21.48	21.83		1
	36	0	20.33	20.41	20.85	0-2	2
	36	18	20.28	20.43	20.83		2
	36	37	20.30	20.40	20.79		2
	75	0	20.32	20.45	20.83		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 46 of 92

Table 9-28
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.20	22.49	22.91	0	0
	1	25	22.21	22.48	22.76		0
	1	49	22.18	22.41	22.83		0
	25	0	21.79	21.45	21.79	0-1	1
	25	12	21.22	21.48	21.77		1
	25	25	21.22	21.44	21.78		1
	50	0	21.16	21.41	21.75		1
16QAM	1	0	21.01	21.56	21.66	0-1	1
	1	25	21.06	21.51	21.66		1
	1	49	21.07	21.48	21.83		1
	25	0	20.15	20.45	20.85	0-2	2
	25	12	20.10	20.41	20.78		2
	25	25	20.12	20.41	20.78		2
	50	0	20.13	20.39	20.78		2

Table 9-29
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.10	22.32	23.03	0	0
	1	12	22.10	22.38	22.99		0
	1	24	22.11	22.37	22.94		0
	12	0	21.02	21.41	21.85	0-1	1
	12	6	21.02	21.41	21.84		1
	12	13	21.02	21.42	21.87		1
	25	0	21.00	21.38	21.82		1
16QAM	1	0	20.94	21.42	21.89	0-1	1
	1	12	20.72	21.29	21.84		1
	1	24	20.90	21.38	22.04		1
	12	0	20.06	20.38	20.83	0-2	2
	12	6	20.04	20.39	20.84		2
	12	13	20.01	20.39	20.80		2
	25	0	20.07	20.43	20.89		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 47 of 92	

Table 9-30
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.09	22.53	22.94	0	0
	1	7	22.05	22.59	22.99		0
	1	14	22.08	22.53	23.00		0
	8	0	21.08	21.50	21.96	0-1	1
	8	4	21.06	21.48	21.90		1
	8	7	21.09	21.46	21.89		1
	15	0	21.08	21.45	21.85		1
16QAM	1	0	21.29	21.53	21.96	0-1	1
	1	7	21.20	21.50	22.03		1
	1	14	21.04	21.46	21.94		1
	8	0	19.95	20.37	20.87	0-2	2
	8	4	20.10	20.45	20.95		2
	8	7	20.08	20.47	20.90		2
	15	0	20.08	20.43	20.88		2

Table 9-31
LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.16	22.49	23.01	0	0
	1	2	22.15	22.54	22.99		0
	1	5	22.13	22.54	23.04		0
	3	0	22.09	22.43	22.92		0
	3	2	22.10	22.49	22.93		0
	3	3	22.10	22.41	22.90		0
	6	0	21.13	21.47	21.93	0-1	1
16QAM	1	0	21.17	21.77	22.01	0-1	1
	1	2	21.19	21.48	21.88		1
	1	5	21.34	21.69	21.88		1
	3	0	21.23	21.40	21.90		1
	3	2	21.08	21.42	21.88		1
	3	3	21.16	21.40	21.88		1
	6	0	20.18	20.41	20.92	0-2	2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 48 of 92	

9.3.8

LTE Band 41

Table 9-32
LTE Band 41 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.59	22.87	22.93	22.76	22.89	0	0
	1	50	22.59	22.86	22.63	22.74	22.91		0
	1	99	22.63	22.91	22.57	22.84	22.97		0
	50	0	21.65	21.94	21.75	21.88	22.16	0-1	1
	50	25	21.61	21.85	21.76	21.85	22.10		1
	50	50	21.58	21.92	21.77	21.86	22.13		1
16QAM	100	0	21.62	21.90	21.75	21.87	22.07	0-1	1
	1	0	21.56	21.77	21.94	21.92	22.26		1
	1	50	21.52	21.77	21.98	21.95	22.27		1
	1	99	21.55	21.76	21.95	21.97	22.28	0-2	1
	50	0	20.70	20.96	20.83	20.86	21.15		2
	50	25	20.63	20.94	20.71	20.89	21.09		2
	50	50	20.63	20.93	20.74	20.87	21.03		2
	100	0	20.61	20.89	20.72	20.88	21.04		2

Table 9-33
LTE Band 41 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.88	23.00	22.65	22.88	22.90	0	0
	1	36	22.90	23.14	22.63	22.86	22.85		0
	1	74	22.80	23.10	22.59	22.77	22.86		0
	36	0	21.85	22.20	21.80	21.82	21.94	0-1	1
	36	18	21.79	22.10	21.75	21.85	21.77		1
	36	37	21.85	22.19	21.77	21.83	21.80		1
16QAM	75	0	21.84	22.18	21.81	21.83	21.86	0-1	1
	1	0	21.77	22.02	21.76	21.96	21.85		1
	1	36	21.80	22.06	21.60	21.74	21.90		1
	1	74	21.94	22.05	21.66	21.76	21.88	0-2	1
	36	0	20.80	21.12	20.86	20.82	20.90		2
	36	18	20.81	21.10	20.79	20.79	20.81		2
	36	37	20.85	21.06	20.79	20.77	20.88		2
	75	0	20.80	21.11	20.78	20.82	20.84		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 49 of 92

Table 9-34
LTE Band 41 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.74	23.00	22.84	22.85	22.89	0	0
	1	25	22.80	22.99	22.68	22.90	22.94		0
	1	49	22.89	23.06	22.79	22.84	22.94		0
	25	0	21.97	22.03	21.60	21.89	21.94	0-1	1
	25	12	21.98	22.10	21.95	21.88	21.96		1
	25	25	21.94	22.06	21.80	21.90	21.90		1
	50	0	21.85	22.10	21.96	21.95	21.97		1
16QAM	1	0	21.96	22.06	21.88	21.78	21.86	0-1	1
	1	25	21.99	21.95	21.86	21.85	21.70		1
	1	49	21.89	21.89	21.95	21.84	21.77		1
	25	0	20.90	21.06	20.84	20.68	20.70	0-2	2
	25	12	21.06	20.98	20.87	20.80	20.79		2
	25	25	21.00	20.94	20.90	20.76	20.88		2
	50	0	21.00	20.96	20.95	20.80	20.84		2

Table 9-35
LTE Band 41 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.83	23.00	22.89	22.80	23.04	0	0
	1	12	22.81	22.92	22.89	22.94	22.78		0
	1	24	23.02	22.93	22.71	22.96	23.00		0
	12	0	22.18	22.27	21.66	21.87	21.97	0-1	1
	12	6	21.90	22.09	21.96	21.79	22.00		1
	12	13	21.78	22.27	21.85	21.89	22.04		1
	25	0	21.97	22.11	21.99	21.92	22.04		1
16QAM	1	0	21.97	21.97	21.86	21.71	21.73	0-1	1
	1	12	21.94	21.81	21.76	21.84	21.73		1
	1	24	22.05	21.91	21.95	21.90	21.98		1
	12	0	20.73	20.86	20.64	20.54	20.91	0-2	2
	12	6	20.90	20.78	20.73	20.73	20.81		2
	12	13	20.90	20.99	20.81	20.73	20.95		2
	25	0	20.97	21.03	20.82	21.01	20.90		2

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 50 of 92

9.4 WLAN Conducted Powers

Table 9-36
2.4 GHz Max Average RF Power- Ant 1

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11b	802.11g
2412	1	19.36	15.49
2437	6	18.88	15.12
2462	11	18.65	15.13

Table 9-37
2.4 GHz Max Average RF Power- Ant 2

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11b	802.11g
2412	1	18.87	15.28
2437	6	19.49	14.84
2462	11	19.25	14.50

Table 9-38
2.4 GHz Reduced Average RF Power (Held to Ear)- Ant 1

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11b	802.11g
2412	1	14.95	15.49
2437	6	14.66	15.12
2462	11	15.34	15.13

Table 9-39
2.4 GHz Reduced Average RF Power (Held to Ear)- Ant 2

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11b	802.11g
2412	1	15.19	15.28
2437	6	15.39	14.84
2462	11	15.09	14.50

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 51 of 92

Table 9-40
5 GHz Max Average RF Power – Ant 1

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11a	802.11n
5180	36	13.57	13.54
5200	40	13.56	13.51
5220	44	13.67	13.50
5240	48	13.58	13.58
5260	52	13.82	13.71
5280	56	13.80	13.78
5300	60	13.67	13.84
5320	64	13.97	13.95
5500	100	13.97	13.93
5600	120	13.93	13.84
5620	124	13.86	13.85
5720	144	13.63	13.70
5745	149	13.47	13.66
5785	157	13.54	13.60
5825	165	13.53	13.55

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 52 of 92	

Table 9-41
5 GHz Max Average RF Power – Ant 2

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11a	802.11n
5180	36	13.73	13.68
5200	40	13.71	13.55
5220	44	13.79	13.65
5240	48	13.99	13.78
5260	52	13.90	13.77
5280	56	13.88	13.82
5300	60	13.90	13.88
5320	64	14.06	14.02
5500	100	13.81	13.85
5600	120	13.58	13.55
5620	124	13.59	13.56
5720	144	14.38	14.13
5745	149	13.63	13.66
5785	157	13.74	13.53
5825	165	13.81	13.51

Table 9-42
5 GHz Reduced Average RF Power (Held to Ear) – Ant 1

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	12.16
5290	58	12.50
5530	106	12.25
5610	122	11.63
5690	138	11.61
5775	155	12.29

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 53 of 92

Table 9-43
5 GHz Reduced Average RF Power (Held to Ear) – Ant 2

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	11.71
5290	58	12.13
5530	106	11.76
5610	122	12.39
5690	138	12.40
5775	155	12.49

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-3
Power Measurement Setup for Bandwidths < 50 MHz




Figure 9-4
Power Measurement Setup for Bandwidths > 50 MHz

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 54 of 92

9.5 Bluetooth Conducted Powers

Table 9-44
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	14.58	28.720
2441	1.0	39	15.23	33.315
2480	1.0	78	12.86	19.310
2402	2.0	0	9.03	7.999
2441	2.0	39	8.81	7.601
2480	2.0	78	6.49	4.459
2402	3.0	0	9.10	8.123
2441	3.0	39	8.91	7.772
2480	3.0	78	6.64	4.614

Note: The bolded data rate and channel above were tested for SAR.




Figure 9-5
Bluetooth Transmission Plot

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 55 of 92

Equation 1
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = Pulse\ \frac{Width}{Period} * 100\% = \frac{2.890ms}{3.750ms} * 100\% = 77.1\%$$




Figure 9-6
Power Measurement Setup

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 56 of 92	

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties (Head)

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	%dev σ	%dev ϵ
3/16/2017	750H	21.3	700	0.849	41.108	0.889	42.201	-4.50%	-2.59%
			710	0.859	40.934	0.890	42.149	-3.48%	-2.88%
			740	0.890	40.520	0.893	41.994	-0.34%	-3.51%
			755	0.905	40.329	0.894	41.916	1.23%	-3.79%
			770	0.918	40.144	0.895	41.838	2.57%	-4.05%
			785	0.930	39.919	0.896	41.760	3.79%	-4.41%
3/20/2017	835H	20.5	820	0.882	40.635	0.899	41.578	-1.89%	-2.27%
			835	0.896	40.456	0.900	41.500	-0.44%	-2.52%
			850	0.909	40.372	0.916	41.500	-0.76%	-2.72%
3/22/2017	1750H	21.0	1710	1.296	39.083	1.348	40.142	-3.86%	-2.64%
			1750	1.338	38.950	1.371	40.079	-2.41%	-2.82%
			1790	1.382	38.737	1.394	40.016	-0.86%	-3.20%
3/20/2017	1900H	21.1	1850	1.400	39.561	1.400	40.000	0.00%	-1.10%
			1880	1.428	39.495	1.400	40.000	2.00%	-1.26%
			1910	1.461	39.306	1.400	40.000	4.36%	-1.74%
3/6/2017	2400H	21.9	2400	1.795	38.923	1.756	39.289	2.22%	-0.93%
			2450	1.856	38.730	1.800	39.200	3.11%	-1.20%
			2500	1.910	38.538	1.855	39.136	2.96%	-1.53%
3/9/2017	2400H	23.2	2400	1.818	37.901	1.756	39.289	3.53%	-3.53%
			2450	1.871	37.716	1.800	39.200	3.94%	-3.79%
			2500	1.929	37.527	1.855	39.136	3.99%	-4.11%
3/15/2017	2600H	22.5	2600	2.035	37.642	1.964	39.009	3.62%	-3.50%
			2650	2.106	37.467	2.018	38.945	4.36%	-3.80%
			2700	2.149	37.305	2.073	38.882	3.67%	-4.06%
03/13/2017	5200H-5800H	21.5	5240	4.776	35.747	4.696	35.940	1.70%	-0.54%
			5260	4.776	35.722	4.717	35.917	1.25%	-0.54%
			5280	4.795	35.783	4.737	35.894	1.22%	-0.31%
			5300	4.816	35.706	4.758	35.871	1.22%	-0.46%
			5520	5.038	35.394	4.983	35.620	1.10%	-0.63%
			5540	5.037	35.317	5.004	35.597	0.66%	-0.79%
			5600	5.144	35.182	5.065	35.529	1.56%	-0.98%
			5680	5.227	35.049	5.147	35.437	1.55%	-1.09%
			5700	5.241	35.065	5.168	35.414	1.41%	-0.99%
			5745	5.275	35.041	5.214	35.363	1.17%	-0.91%
			5765	5.327	34.910	5.234	35.340	1.78%	-1.22%
			5785	5.335	34.956	5.255	35.317	1.52%	-1.02%

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 57 of 92

Table 10-2
Measured Tissue Properties (Body)

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	%dev σ	%dev ϵ
3/16/2017	750B	21.6	700	0.914	54.952	0.959	55.726	-4.69%	-1.39%
			710	0.924	54.826	0.960	55.687	-3.75%	-1.55%
			740	0.954	54.531	0.963	55.570	-0.93%	-1.87%
			755	0.968	54.429	0.964	55.512	0.41%	-1.95%
			770	0.983	54.301	0.965	55.453	1.87%	-2.08%
3/23/2017	835B	22.6	785	0.997	54.133	0.966	55.395	3.21%	-2.28%
			820	0.977	55.218	0.969	55.258	0.83%	-0.07%
			835	0.994	55.069	0.970	55.200	2.47%	-0.24%
3/14/2017	1750B	21.7	850	1.007	54.928	0.988	55.154	1.92%	-0.41%
			1710	1.440	51.216	1.463	53.537	-1.57%	-4.34%
			1750	1.479	50.941	1.488	53.432	-0.60%	-4.66%
3/22/2017	1750B	23.0	1790	1.531	50.849	1.514	53.326	1.12%	-4.65%
			1710	1.444	52.594	1.463	53.537	-1.30%	-1.76%
			1750	1.484	52.380	1.488	53.432	-0.27%	-1.97%
3/20/2017	1900B	22.1	1790	1.531	52.162	1.514	53.326	1.12%	-2.18%
			1850	1.518	54.002	1.520	53.300	-0.13%	1.32%
			1880	1.552	53.942	1.520	53.300	2.11%	1.20%
3/15/2017	2450B	22.6	1910	1.588	53.819	1.520	53.300	4.47%	0.97%
			2400	1.958	53.010	1.902	52.767	2.94%	0.46%
			2450	2.029	52.810	1.950	52.700	4.05%	0.21%
3/15/2017	2600B	22.6	2500	2.094	52.628	2.021	52.636	3.61%	-0.02%
			2550	2.162	52.435	2.092	52.573	3.35%	-0.26%
			2600	2.234	52.254	2.163	52.509	3.28%	-0.49%
			2650	2.295	52.057	2.234	52.445	2.73%	-0.74%
			2700	2.367	51.859	2.305	52.382	2.69%	-1.00%
03/20/2017	5200B-5800B	20.8	5240	5.520	47.071	5.346	48.960	3.25%	-3.86%
			5260	5.528	47.004	5.369	48.933	2.96%	-3.94%
			5320	5.632	46.957	5.439	48.851	3.55%	-3.88%
			5500	5.844	46.679	5.650	48.607	3.43%	-3.97%
			5600	6.009	46.520	5.766	48.471	4.21%	-4.03%
			5700	6.141	46.308	5.883	48.336	4.39%	-4.20%
			5745	6.198	46.289	5.936	48.275	4.41%	-4.11%
			5765	6.219	46.283	5.959	48.248	4.36%	-4.07%
			5785	6.232	46.219	5.982	48.220	4.18%	-4.15%
			5825	6.308	46.089	6.029	48.166	4.63%	-4.31%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 58 of 92	

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results (1 g)

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
G	750	HEAD	03/16/2017	21.1	21.3	0.200	1161	3287	1.580	8.170	7.900	-3.30%
E	835	HEAD	03/20/2017	22.3	20.5	0.200	4d047	7406	1.920	9.130	9.600	5.15%
H	1750	HEAD	03/22/2017	24.1	22.0	0.100	1008	3318	3.490	36.700	34.900	-4.90%
H	1900	HEAD	03/20/2017	22.0	21.3	0.100	5d149	3318	3.870	40.100	38.700	-3.49%
G	2450	HEAD	03/06/2017	23.6	20.8	0.100	797	3287	5.320	52.100	53.200	2.11%
G	2450	HEAD	03/09/2017	20.9	22.1	0.100	797	3287	5.480	52.100	54.800	5.18%
G	2600	HEAD	03/15/2017	22.1	22.5	0.100	1126	3287	6.070	56.300	60.700	7.82%
J	5250	HEAD	03/13/2017	20.2	19.9	0.050	1120	3914	3.930	83.200	78.600	-5.53%
J	5600	HEAD	03/13/2017	20.2	19.9	0.050	1120	3914	3.970	85.800	79.400	-7.46%
J	5750	HEAD	03/13/2017	20.2	19.9	0.050	1120	3914	4.050	81.800	81.000	-0.98%
I	750	BODY	03/16/2017	22.1	21.6	0.200	1003	3213	1.700	8.790	8.500	-3.30%
H	835	BODY	03/23/2017	22.8	22.6	0.200	4d133	3318	1.990	9.500	9.950	4.74%
I	1750	BODY	03/14/2017	23.6	23.0	0.100	1008	3213	3.690	37.300	36.900	-1.07%
I	1750	BODY	03/22/2017	24.5	23.0	0.100	1008	3213	3.710	37.300	37.100	-0.54%
G	1900	BODY	03/20/2017	22.6	22.2	0.100	5d149	3287	3.910	39.900	39.100	-2.01%
E	2450	BODY	03/15/2017	22.9	22.6	0.100	981	7406	4.830	50.800	48.300	-4.92%
E	2600	BODY	03/15/2017	22.9	22.6	0.100	1071	7406	5.590	54.200	55.900	3.14%
K	5250	BODY	03/20/2017	23.1	21.0	0.050	1237	7308	3.680	74.800	73.600	-1.60%
K	5600	BODY	03/20/2017	23.1	21.0	0.050	1237	7308	4.060	77.000	81.200	5.45%
K	5750	BODY	03/20/2017	23.1	21.0	0.050	1237	7308	3.530	75.400	70.600	-6.37%

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 59 of 92

Table 10-4
System Verification Results (10 g)

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{10g} (W/kg)	1 W Target SAR _{10g} (W/kg)	1 W Normalized SAR _{10g} (W/kg)	Deviation _{10g} (%)
E	2450	BODY	03/15/2017	22.9	22.6	0.100	981	7406	2.200	23.800	22.000	-7.56%
K	5250	BODY	03/20/2017	23.1	21.0	0.050	1237	7308	1.020	21.000	20.400	-2.86%
K	5600	BODY	03/20/2017	23.1	21.0	0.050	1237	7308	1.120	21.500	22.400	4.19%
K	5750	BODY	03/20/2017	23.1	21.0	0.050	1237	7308	0.970	20.900	19.400	-7.18%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMG955N	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 60 of 92	

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

**Table 11-1
GSM 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.2	29.20	0.07	Right	Cheek	E57E5	1:8.3	0.022	1.259	0.028	A1
1880.00	661	GSM 1900	GSM	30.2	29.20	0.06	Right	Tilt	E57E5	1:8.3	0.009	1.259	0.011	
1880.00	661	GSM 1900	GSM	30.2	29.20	0.03	Left	Cheek	E57E5	1:8.3	0.021	1.259	0.026	
1880.00	661	GSM 1900	GSM	30.2	29.20	0.17	Left	Tilt	E57E5	1:8.3	0.007	1.259	0.009	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-2
UMTS 850 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	22.5	22.22	0.02	Right	Cheek	E559F	1:1	0.119	1.067	0.127	A2
836.60	4183	UMTS 850	RMC	22.5	22.22	0.03	Right	Tilt	E559F	1:1	0.051	1.067	0.054	
836.60	4183	UMTS 850	RMC	22.5	22.22	0.02	Left	Cheek	E559F	1:1	0.085	1.067	0.091	
836.60	4183	UMTS 850	RMC	22.5	22.22	0.00	Left	Tilt	E559F	1:1	0.041	1.067	0.044	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-3
UMTS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	22.5	21.90	0.03	Right	Cheek	E57E5	1:1	0.045	1.148	0.052	
1880.00	9400	UMTS 1900	RMC	22.5	21.90	0.15	Right	Tilt	E57E5	1:1	0.022	1.148	0.025	
1880.00	9400	UMTS 1900	RMC	22.5	21.90	0.14	Left	Cheek	E57E5	1:1	0.050	1.148	0.057	A3
1880.00	9400	UMTS 1900	RMC	22.5	21.90	0.05	Left	Tilt	E57E5	1:1	0.017	1.148	0.020	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 61 of 92

Table 11-4
LTE Band 12 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	0.13	0	Right	Cheek	QPSK	1	0	E57E5	1:1	0.063	1.186	0.075	A4
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	0.07	1	Right	Cheek	QPSK	25	0	E57E5	1:1	0.053	1.197	0.063	
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	0.15	0	Right	Tilt	QPSK	1	0	E57E5	1:1	0.029	1.186	0.034	
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	0.03	1	Right	Tilt	QPSK	25	0	E57E5	1:1	0.023	1.197	0.028	
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	-0.17	0	Left	Cheek	QPSK	1	0	E57E5	1:1	0.050	1.186	0.059	
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	0.15	1	Left	Cheek	QPSK	25	0	E57E5	1:1	0.036	1.197	0.043	
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	0.04	0	Left	Tilt	QPSK	1	0	E57E5	1:1	0.046	1.186	0.055	
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	0.11	1	Left	Tilt	QPSK	25	0	E57E5	1:1	0.032	1.197	0.038	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-5
LTE Band 13 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	-0.05	0	Right	Cheek	QPSK	1	0	E5667	1:1	0.073	1.312	0.096	A5
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	0.14	1	Right	Cheek	QPSK	25	0	E5667	1:1	0.055	1.294	0.071	
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	0.20	0	Right	Tilt	QPSK	1	0	E5667	1:1	0.041	1.312	0.054	
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	0.08	1	Right	Tilt	QPSK	25	0	E5667	1:1	0.029	1.294	0.038	
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	0.11	0	Left	Cheek	QPSK	1	0	E5667	1:1	0.067	1.312	0.088	
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	0.02	1	Left	Cheek	QPSK	25	0	E5667	1:1	0.044	1.294	0.057	
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	0.03	0	Left	Tilt	QPSK	1	0	E5667	1:1	0.063	1.312	0.083	
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	0.15	1	Left	Tilt	QPSK	25	0	E5667	1:1	0.048	1.294	0.062	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-6
LTE Band 26 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.11	0	Right	Cheek	QPSK	1	0	E559F	1:1	0.121	1.191	0.144	A6
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	0.02	1	Right	Cheek	QPSK	36	0	E559F	1:1	0.093	1.225	0.114	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.15	0	Right	Tilt	QPSK	1	0	E559F	1:1	0.050	1.191	0.060	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	0.06	1	Right	Tilt	QPSK	36	0	E559F	1:1	0.039	1.225	0.048	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.05	0	Left	Cheek	QPSK	1	0	E559F	1:1	0.082	1.191	0.098	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	0.02	1	Left	Cheek	QPSK	36	0	E559F	1:1	0.066	1.225	0.081	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.11	0	Left	Tilt	QPSK	1	0	E559F	1:1	0.042	1.191	0.050	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	0.12	1	Left	Tilt	QPSK	36	0	E559F	1:1	0.033	1.225	0.040	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 62 of 92

Table 11-7
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Antenna State	Power Drift [dB]	MPR [dB]	Side	Test Position	Antenna	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.09	1	0.17	0	Right	Cheek	Ant A	QPSK	1	0	E559F	1:1	0.136	1.384	0.188	A7
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.14	1	-0.03	1	Right	Cheek	Ant A	QPSK	25	0	E559F	1:1	0.115	1.368	0.157	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.09	1	0.15	0	Right	Tilt	Ant A	QPSK	1	0	E559F	1:1	0.060	1.384	0.083	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.14	1	0.17	1	Right	Tilt	Ant A	QPSK	25	0	E559F	1:1	0.051	1.368	0.070	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.09	1	0.00	0	Left	Cheek	Ant A	QPSK	1	0	E559F	1:1	0.102	1.384	0.141	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.14	1	0.08	1	Left	Cheek	Ant A	QPSK	25	0	E559F	1:1	0.078	1.368	0.107	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.09	1	0.10	0	Left	Tilt	Ant A	QPSK	1	0	E559F	1:1	0.049	1.384	0.068	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.14	1	0.13	1	Left	Tilt	Ant A	QPSK	25	0	E559F	1:1	0.037	1.368	0.051	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-8
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
Mhz	Ch.	(W/kg)														(W/kg)			
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	-0.03	0	Right	Cheek	QPSK	1	0	E559F	1:1	0.085	1.256	0.107	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.58	0.09	1	Right	Cheek	QPSK	50	0	E559F	1:1	0.068	1.236	0.084	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	-0.04	0	Right	Tilt	QPSK	1	0	E559F	1:1	0.052	1.256	0.065	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.58	0.16	1	Right	Tilt	QPSK	50	0	E559F	1:1	0.044	1.236	0.054	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	0.01	0	Left	Cheek	QPSK	1	0	E559F	1:1	0.104	1.256	0.131	A8
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.58	0.07	1	Left	Cheek	QPSK	50	0	E559F	1:1	0.095	1.236	0.117	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	-0.08	0	Left	Tilt	QPSK	1	0	E559F	1:1	0.050	1.256	0.063	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.58	0.07	1	Left	Tilt	QPSK	50	0	E559F	1:1	0.042	1.236	0.052	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-9
LTE Band 25 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.68	0.07	0	Right	Cheek	QPSK	1	0	E57E5	1:1	0.065	1.208	0.079	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.82	0.03	1	Right	Cheek	QPSK	50	0	E57E5	1:1	0.048	1.169	0.056	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.68	0.16	0	Right	Tilt	QPSK	1	0	E57E5	1:1	0.032	1.208	0.039	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.82	0.21	1	Right	Tilt	QPSK	50	0	E57E5	1:1	0.027	1.169	0.032	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.68	0.04	0	Left	Cheek	QPSK	1	0	E57E5	1:1	0.085	1.208	0.103	A9
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.82	0.05	1	Left	Cheek	QPSK	50	0	E57E5	1:1	0.057	1.169	0.067	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.68	0.13	0	Left	Tilt	QPSK	1	0	E57E5	1:1	0.025	1.208	0.030	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.82	0.04	1	Left	Tilt	QPSK	50	0	E57E5	1:1	0.018	1.169	0.021	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 63 of 92

Table 11-10
LTE Band 41 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2680.00	41490	High	LTE Band 41	20	23.5	22.97	0.02	0	Right	Cheek	QPSK	1	99	E57BB	1:1.58	0.042	1.130	0.047	
2680.00	41490	High	LTE Band 41	20	22.5	22.16	0.15	1	Right	Cheek	QPSK	50	0	E57BB	1:1.58	0.032	1.081	0.035	
2680.00	41490	High	LTE Band 41	20	23.5	22.97	0.03	0	Right	Tilt	QPSK	1	99	E57BB	1:1.58	0.039	1.130	0.044	
2680.00	41490	High	LTE Band 41	20	22.5	22.16	0.14	1	Right	Tilt	QPSK	50	0	E57BB	1:1.58	0.034	1.081	0.037	
2680.00	41490	High	LTE Band 41	20	23.5	22.97	0.02	0	Left	Cheek	QPSK	1	99	E57BB	1:1.58	0.058	1.130	0.066	A10
2680.00	41490	High	LTE Band 41	20	22.5	22.16	0.03	1	Left	Cheek	QPSK	50	0	E57BB	1:1.58	0.043	1.081	0.046	
2680.00	41490	High	LTE Band 41	20	23.5	22.97	-0.04	0	Left	Tilt	QPSK	1	99	E57BB	1:1.58	0.035	1.130	0.040	
2680.00	41490	High	LTE Band 41	20	22.5	22.16	0.03	1	Left	Tilt	QPSK	50	0	E57BB	1:1.58	0.027	1.081	0.029	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-11
DTS Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	15.5	15.34	0.06	Right	Cheek	1	CD7B8	1	99.8	0.279	0.232	1.038	1.002	0.241	A11
2462	11	802.11b	DSSS	22	15.5	15.34	0.03	Right	Tilt	1	CD7B8	1	99.8	0.247	-	1.038	1.002	-	
2462	11	802.11b	DSSS	22	15.5	15.34	0.08	Left	Cheek	1	CD7B8	1	99.8	0.118	-	1.038	1.002	-	
2462	11	802.11b	DSSS	22	15.5	15.34	0.05	Left	Tilt	1	CD7B8	1	99.8	0.151	-	1.038	1.002	-	
2437	6	802.11b	DSSS	22	15.5	15.39	-0.18	Right	Cheek	2	CD7B8	1	99.8	0.175	0.165	1.026	1.002	0.170	
2437	6	802.11b	DSSS	22	15.5	15.39	-0.03	Right	Tilt	2	CD7B8	1	99.8	0.110	-	1.026	1.002	-	
2437	6	802.11b	DSSS	22	15.5	15.39	0.08	Left	Cheek	2	CD7B8	1	99.8	0.085	-	1.026	1.002	-	
2437	6	802.11b	DSSS	22	15.5	15.39	0.09	Left	Tilt	2	CD7B8	1	99.8	0.063	-	1.026	1.002	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 64 of 92

**Table 11-12
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5290	58	802.11ac	OFDM	80	12.5	12.50	0.05	Right	Cheek	1	CD7B8	29.3	96.3	0.304	0.126	1.000	1.038	0.131	
5290	58	802.11ac	OFDM	80	12.5	12.50	0.03	Right	Tilt	1	CD7B8	29.3	96.3	0.276	-	1.000	1.038	-	
5290	58	802.11ac	OFDM	80	12.5	12.50	-0.03	Left	Cheek	1	CD7B8	29.3	96.3	0.107	-	1.000	1.038	-	
5290	58	802.11ac	OFDM	80	12.5	12.50	0.01	Left	Tilt	1	CD7B8	29.3	96.3	0.093	-	1.000	1.038	-	
5290	58	802.11ac	OFDM	80	12.5	12.13	0.17	Right	Cheek	2	CD7B8	29.3	96.3	0.509	0.223	1.089	1.038	0.252	
5290	58	802.11ac	OFDM	80	12.5	12.13	0.02	Right	Tilt	2	CD7B8	29.3	96.3	0.411	-	1.089	1.038	-	
5290	58	802.11ac	OFDM	80	12.5	12.13	0.03	Left	Cheek	2	CD7B8	29.3	96.3	0.144	-	1.089	1.038	-	
5290	58	802.11ac	OFDM	80	12.5	12.13	0.02	Left	Tilt	2	CD7B8	29.3	96.3	0.151	-	1.089	1.038	-	
5530	106	802.11ac	OFDM	80	12.5	12.25	0.18	Right	Cheek	1	CD7B8	29.3	96.3	0.253	-	1.059	1.038	-	
5530	106	802.11ac	OFDM	80	12.5	12.25	0.16	Right	Tilt	1	CD7B8	29.3	96.3	0.220	-	1.059	1.038	-	
5530	106	802.11ac	OFDM	80	12.5	12.25	0.07	Left	Cheek	1	CD7B8	29.3	96.3	0.357	0.104	1.059	1.038	0.114	
5530	106	802.11ac	OFDM	80	12.5	12.25	0.02	Left	Tilt	1	CD7B8	29.3	96.3	0.170	-	1.059	1.038	-	
5690	138	802.11ac	OFDM	80	12.5	12.40	0.15	Right	Cheek	2	CD7B8	29.3	96.3	0.347	0.166	1.023	1.038	0.176	
5690	138	802.11ac	OFDM	80	12.5	12.40	0.08	Right	Tilt	2	CD7B8	29.3	96.3	0.307	-	1.023	1.038	-	
5690	138	802.11ac	OFDM	80	12.5	12.40	0.04	Left	Cheek	2	CD7B8	29.3	96.3	0.237	-	1.023	1.038	-	
5690	138	802.11ac	OFDM	80	12.5	12.40	0.03	Left	Tilt	2	CD7B8	29.3	96.3	0.189	-	1.023	1.038	-	
5775	155	802.11ac	OFDM	80	12.5	12.29	0.04	Right	Cheek	1	CD7B8	29.3	96.3	0.572	0.336	1.050	1.038	0.366	A12
5775	155	802.11ac	OFDM	80	12.5	12.29	0.06	Right	Tilt	1	CD7B8	29.3	96.3	0.320	-	1.050	1.038	-	
5775	155	802.11ac	OFDM	80	12.5	12.29	0.03	Left	Cheek	1	CD7B8	29.3	96.3	0.564	-	1.050	1.038	-	
5775	155	802.11ac	OFDM	80	12.5	12.29	0.02	Left	Tilt	1	CD7B8	29.3	96.3	0.360	-	1.050	1.038	-	
5775	155	802.11ac	OFDM	80	12.5	12.49	-0.16	Right	Cheek	2	CD7B8	29.3	96.3	0.367	0.140	1.002	1.038	0.146	
5775	155	802.11ac	OFDM	80	12.5	12.49	0.09	Right	Tilt	2	CD7B8	29.3	96.3	0.230	-	1.002	1.038	-	
5775	155	802.11ac	OFDM	80	12.5	12.49	0.03	Left	Cheek	2	CD7B8	29.3	96.3	0.192	-	1.002	1.038	-	
5775	155	802.11ac	OFDM	80	12.5	12.49	0.05	Left	Tilt	2	CD7B8	29.3	96.3	0.138	-	1.002	1.038	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-13
DSSS Head SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle %	SAR (1 g)	Scaling Factor (Conducted Power)	Scaling Factor (Duty Cycle)	Reported SAR (1 g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2402	0	Bluetooth	FHSS	9.5	9.03	0.04	Right	Cheek	D6265	2	77.1	0.031	1.114	1.297	0.045	A13
2402	0	Bluetooth	FHSS	9.5	9.03	-0.04	Right	Tilt	D6265	2	77.1	0.019	1.114	1.297	0.027	
2402	0	Bluetooth	FHSS	9.5	9.03	-0.06	Left	Cheek	D6265	2	77.1	0.008	1.114	1.297	0.012	
2402	0	Bluetooth	FHSS	9.5	9.03	0.18	Left	Tilt	D6265	2	77.1	0.009	1.114	1.297	0.013	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 65 of 92

11.2 Standalone Body-Worn SAR Data

Table 11-14
GSM/UMTS Body-Worn SAR Data

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.2	29.20	-0.06	15 mm	Ant B	E57BB	1	1:8.3	back	0.058	1.259	0.073	A14
836.60	4183	UMTS 850	RMC	22.5	22.22	0.01	15 mm	Ant A	E4A6F	N/A	1:1	back	0.188	1.067	0.201	A16
1880.00	9400	UMTS 1900	RMC	22.5	21.90	0.02	15 mm	Ant B	E57BB	N/A	1:1	back	0.176	1.148	0.202	A18
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-15
LTE Body-Worn SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Bandwidth [MHz]	Antenna State	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	N/A	23.5	22.76	0.01	0	Ant A	E57E3	QPSK	1	0	15 mm	back	1:1	0.138	1.186	0.164	A20
707.50	23095	Mid	LTE Band 12	10	N/A	22.5	21.72	0.03	1	Ant A	E57E3	QPSK	25	0	15 mm	back	1:1	0.107	1.197	0.128	
782.00	23230	Mid	LTE Band 13	10	N/A	24.0	22.82	-0.11	0	Ant A	E57E3	QPSK	1	0	15 mm	back	1:1	0.164	1.312	0.215	A22
782.00	23230	Mid	LTE Band 13	10	N/A	23.0	21.88	-0.02	1	Ant A	E57E3	QPSK	25	0	15 mm	back	1:1	0.122	1.294	0.158	
831.50	26865	Mid	LTE Band 26 (Cell)	15	N/A	23.5	22.74	-0.09	0	Ant A	E4A6F	QPSK	1	0	15 mm	back	1:1	0.190	1.191	0.226	A24
831.50	26865	Mid	LTE Band 26 (Cell)	15	N/A	22.5	21.62	0.00	1	Ant A	E4A6F	QPSK	36	0	15 mm	back	1:1	0.156	1.225	0.191	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	24.5	23.09	0.17	0	Ant A	E559F	QPSK	1	0	15 mm	back	1:1	0.225	1.384	0.311	A26
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	23.5	22.14	0.10	1	Ant A	E559F	QPSK	25	0	15 mm	back	1:1	0.180	1.368	0.246	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	22.0	20.58	-0.02	0	Ant E	E57E3	QPSK	1	0	15 mm	back	1:1	0.155	1.387	0.215	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	21.0	19.66	0.00	1	Ant E	E57E3	QPSK	25	0	15 mm	back	1:1	0.122	1.361	0.166	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	N/A	23.5	22.51	-0.02	0	Ant B	E57E3	QPSK	1	0	15 mm	back	1:1	0.377	1.256	0.474	A28
1732.50	20175	Mid	LTE Band 4 (AWS)	20	N/A	22.5	21.58	-0.03	1	Ant B	E57E3	QPSK	50	0	15 mm	back	1:1	0.318	1.236	0.393	
1905.00	26590	High	LTE Band 25 (PCS)	20	N/A	23.5	22.68	0.01	0	Ant B	E57BB	QPSK	1	0	15 mm	back	1:1	0.203	1.208	0.245	A30
1905.00	26590	High	LTE Band 25 (PCS)	20	N/A	22.5	21.82	0.00	1	Ant B	E57BB	QPSK	50	0	15 mm	back	1:1	0.161	1.169	0.188	
2680.00	41490	High	LTE Band 41	20	N/A	23.5	22.97	-0.04	0	Ant B	E559F	QPSK	1	99	15 mm	back	1:1.58	0.190	1.130	0.215	A32
2680.00	41490	High	LTE Band 41	20	N/A	22.5	22.16	0.08	1	Ant B	E559F	QPSK	50	0	15 mm	back	1:1.58	0.149	1.081	0.161	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT											Body										
Spatial Peak											1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population											averaged over 1 gram										

Table 11-16
DTS Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	19.5	19.36	0.08	15 mm	1	CD7B8	1	back	99.8	0.072	0.051	1.033	1.002	0.053	A34
2437	6	802.11b	DSSS	22	19.5	19.49	0.19	15 mm	2	CD7B8	1	back	99.8	0.075	0.049	1.002	1.002	0.049	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 66 of 92

Table 11-17
NII Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5320	64	802.11a	OFDM	20	14.5	13.97	-0.04	15 mm	1	D6265	6	back	98.8	0.337	0.141	1.130	1.012	0.161	
5320	64	802.11a	OFDM	20	14.5	14.06	-0.03	15 mm	2	D6265	6	back	98.8	0.188	0.091	1.107	1.012	0.102	
5500	100	802.11a	OFDM	20	14.5	13.97	-0.16	15 mm	1	D6265	6	back	98.8	0.588	0.281	1.130	1.012	0.321	A36
5720	144	802.11a	OFDM	20	14.5	14.38	-0.17	15 mm	2	D6265	6	back	98.8	0.106	0.054	1.028	1.012	0.056	
5785	157	802.11a	OFDM	20	14.5	13.54	-0.02	15 mm	1	D6265	6	back	98.8	0.326	0.141	1.247	1.012	0.178	
5825	165	802.11a	OFDM	20	14.5	13.81	-0.06	15 mm	2	D6265	6	back	98.8	0.097	0.045	1.172	1.012	0.053	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

Table 11-18
DSSS Body-Worn SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor (Conducted Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.															
2441	39	Bluetooth	FHSS	15.5	15.23	0.10	15 mm	CD7B8	1	back	77.1	0.033	1.064	1.297	0.046	A38
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram								

11.3 Standalone Hotspot SAR Data

Table 11-19
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.															
1909.80	810	GSM 1900	GPRS	24.5	24.06	0.00	10 mm	Ant B	E57BB	4	1:2.076	back	0.195	1.107	0.216	
1909.80	810	GSM 1900	GPRS	24.5	24.06	-0.03	10 mm	Ant B	E57BB	4	1:2.076	front	0.156	1.107	0.173	
1909.80	810	GSM 1900	GPRS	24.5	24.06	-0.10	10 mm	Ant B	E57BB	4	1:2.076	bottom	0.218	1.107	0.241	A15
1909.80	810	GSM 1900	GPRS	24.5	24.06	-0.12	10 mm	Ant B	E57BB	4	1:2.076	left	0.115	1.107	0.127	
836.60	4183	UMTS 850	RMC	22.5	22.22	0.00	10 mm	Ant A	E4A6F	N/A	1:1	back	0.281	1.067	0.300	A17
836.60	4183	UMTS 850	RMC	22.5	22.22	0.03	10 mm	Ant A	E4A6F	N/A	1:1	front	0.258	1.067	0.275	
836.60	4183	UMTS 850	RMC	22.5	22.22	0.00	10 mm	Ant A	E4A6F	N/A	1:1	bottom	0.179	1.067	0.191	
836.60	4183	UMTS 850	RMC	22.5	22.22	0.00	10 mm	Ant A	E4A6F	N/A	1:1	right	0.155	1.067	0.165	
836.60	4183	UMTS 850	RMC	22.5	22.22	0.13	10 mm	Ant A	E4A6F	N/A	1:1	left	0.067	1.067	0.071	
1880.00	9400	UMTS 1900	RMC	22.5	21.90	0.05	10 mm	Ant B	E57BB	N/A	1:1	back	0.271	1.148	0.311	
1880.00	9400	UMTS 1900	RMC	22.5	21.90	0.01	10 mm	Ant B	E57BB	N/A	1:1	front	0.233	1.148	0.267	
1880.00	9400	UMTS 1900	RMC	22.5	21.90	0.05	10 mm	Ant B	E57BB	N/A	1:1	bottom	0.345	1.148	0.396	A19
1880.00	9400	UMTS 1900	RMC	22.5	21.90	-0.01	10 mm	Ant B	E57BB	N/A	1:1	left	0.164	1.148	0.188	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 67 of 92

Table 11-20
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	-0.06	0	Ant A	E57E3	QPSK	1	0	10 mm	back	1:1	0.212	1.186	0.251	A21
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	-0.07	1	Ant A	E57E3	QPSK	25	0	10 mm	back	1:1	0.166	1.197	0.199	
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	0.00	0	Ant A	E57E3	QPSK	1	0	10 mm	front	1:1	0.180	1.186	0.213	
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	0.01	1	Ant A	E57E3	QPSK	25	0	10 mm	front	1:1	0.142	1.197	0.170	
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	-0.09	0	Ant A	E57E3	QPSK	1	0	10 mm	bottom	1:1	0.105	1.186	0.125	
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	0.02	1	Ant A	E57E3	QPSK	25	0	10 mm	bottom	1:1	0.083	1.197	0.099	
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	-0.03	0	Ant A	E57E3	QPSK	1	0	10 mm	right	1:1	0.132	1.186	0.157	
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	0.01	1	Ant A	E57E3	QPSK	25	0	10 mm	right	1:1	0.105	1.197	0.126	
707.50	23095	Mid	LTE Band 12	10	23.5	22.76	-0.06	0	Ant A	E57E3	QPSK	1	0	10 mm	left	1:1	0.041	1.186	0.049	
707.50	23095	Mid	LTE Band 12	10	22.5	21.72	0.10	1	Ant A	E57E3	QPSK	25	0	10 mm	left	1:1	0.029	1.197	0.035	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram												
Uncontrolled Exposure/General Population																				

Table 11-21
LTE Band 13 Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	0.01	0	Ant A	E57E3	QPSK	1	0	10 mm	back	1:1	0.275	1.312	0.361	A23
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	-0.02	1	Ant A	E57E3	QPSK	25	0	10 mm	back	1:1	0.213	1.294	0.276	
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	0.07	0	Ant A	E57E3	QPSK	1	0	10 mm	front	1:1	0.247	1.312	0.324	
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	0.12	1	Ant A	E57E3	QPSK	25	0	10 mm	front	1:1	0.180	1.294	0.233	
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	0.02	0	Ant A	E57E3	QPSK	1	0	10 mm	bottom	1:1	0.174	1.312	0.228	
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	0.00	1	Ant A	E57E3	QPSK	25	0	10 mm	bottom	1:1	0.133	1.294	0.172	
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	0.02	0	Ant A	E57E3	QPSK	1	0	10 mm	right	1:1	0.204	1.312	0.268	
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	-0.02	1	Ant A	E57E3	QPSK	25	0	10 mm	right	1:1	0.148	1.294	0.192	
782.00	23230	Mid	LTE Band 13	10	24.0	22.82	0.03	0	Ant A	E57E3	QPSK	1	0	10 mm	left	1:1	0.042	1.312	0.055	
782.00	23230	Mid	LTE Band 13	10	23.0	21.88	0.15	1	Ant A	E57E3	QPSK	25	0	10 mm	left	1:1	0.027	1.294	0.035	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body												
Spatial Peak								1.6 W/kg (mW/g)												
Uncontrolled Exposure/General Population								averaged over 1 gram												

Table 11-22
LTE Band 26 (Cell) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	-0.01	0	Ant A	E4A6F	QPSK	1	0	10 mm	back	1:1	0.304	1.191	0.362	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	0.06	1	Ant A	E4A6F	QPSK	36	0	10 mm	back	1:1	0.244	1.225	0.299	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	-0.10	0	Ant A	E4A6F	QPSK	1	0	10 mm	front	1:1	0.325	1.191	0.387	A25
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	0.02	1	Ant A	E4A6F	QPSK	36	0	10 mm	front	1:1	0.260	1.225	0.319	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	-0.07	0	Ant A	E4A6F	QPSK	1	0	10 mm	bottom	1:1	0.189	1.191	0.225	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	-0.08	1	Ant A	E4A6F	QPSK	36	0	10 mm	bottom	1:1	0.154	1.225	0.189	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	-0.04	0	Ant A	E4A6F	QPSK	1	0	10 mm	right	1:1	0.150	1.191	0.179	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	-0.04	1	Ant A	E4A6F	QPSK	36	0	10 mm	right	1:1	0.114	1.225	0.140	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.74	0.21	0	Ant A	E4A6F	QPSK	1	0	10 mm	left	1:1	0.053	1.191	0.063	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.62	-0.01	1	Ant A	E4A6F	QPSK	36	0	10 mm	left	1:1	0.047	1.225	0.058	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body												
Spatial Peak								1.6 W/kg (mW/g)												
Uncontrolled Exposure/General Population								averaged over 1 gram												

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 68 of 92

Table 11-23
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Bandwidth [MHz]	Antenna State	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	24.5	23.09	-0.13	0	Ant A	E559F	QPSK	1	0	10 mm	back	1:1	0.383	1.384	0.530	A27
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	23.5	22.14	-0.21	1	Ant A	E559F	QPSK	25	0	10 mm	back	1:1	0.302	1.368	0.413	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	24.5	23.09	-0.02	0	Ant A	E559F	QPSK	1	0	10 mm	front	1:1	0.342	1.384	0.473	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	23.5	22.14	0.07	1	Ant A	E559F	QPSK	25	0	10 mm	front	1:1	0.270	1.368	0.369	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	24.5	23.09	0.00	0	Ant A	E559F	QPSK	1	0	10 mm	bottom	1:1	0.227	1.384	0.314	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	23.5	22.14	0.04	1	Ant A	E559F	QPSK	25	0	10 mm	bottom	1:1	0.176	1.368	0.241	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	24.5	23.09	-0.08	0	Ant A	E559F	QPSK	1	0	10 mm	right	1:1	0.216	1.384	0.299	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	23.5	22.14	0.08	1	Ant A	E559F	QPSK	25	0	10 mm	right	1:1	0.176	1.368	0.241	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	24.5	23.09	0.04	0	Ant A	E559F	QPSK	1	0	10 mm	left	1:1	0.082	1.384	0.113	
836.50	20525	Mid	LTE Band 5 (Cell)	10	1	23.5	22.14	0.00	1	Ant A	E559F	QPSK	25	0	10 mm	left	1:1	0.065	1.368	0.089	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	22.0	20.58	0.06	0	Ant E	E57E3	QPSK	1	0	10 mm	back	1:1	0.297	1.387	0.412	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	21.0	19.66	-0.05	1	Ant E	E57E3	QPSK	25	0	10 mm	back	1:1	0.231	1.361	0.314	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	22.0	20.58	-0.08	0	Ant E	E57E3	QPSK	1	0	10 mm	front	1:1	0.337	1.387	0.467	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	21.0	19.66	-0.01	1	Ant E	E57E3	QPSK	25	0	10 mm	front	1:1	0.262	1.361	0.357	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	22.0	20.58	-0.02	0	Ant E	E57E3	QPSK	1	0	10 mm	top	1:1	0.160	1.387	0.222	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	21.0	19.66	-0.09	1	Ant E	E57E3	QPSK	25	0	10 mm	top	1:1	0.120	1.361	0.163	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	22.0	20.58	0.06	0	Ant E	E57E3	QPSK	1	0	10 mm	right	1:1	0.028	1.387	0.039	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	21.0	19.66	0.10	1	Ant E	E57E3	QPSK	25	0	10 mm	right	1:1	0.022	1.361	0.030	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	22.0	20.58	0.01	0	Ant E	E57E3	QPSK	1	0	10 mm	left	1:1	0.138	1.387	0.191	
836.50	20525	Mid	LTE Band 5 (Cell)	10	N/A	21.0	19.66	0.02	1	Ant E	E57E3	QPSK	25	0	10 mm	left	1:1	0.106	1.361	0.144	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body												
Spatial Peak									1.6 W/kg (mW/g)												
Uncontrolled Exposure/General Population									averaged over 1 gram												

Table 11-24
LTE Band 4 (AWS) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	0.00	0	Ant B	E57E3	QPSK	1	0	10 mm	back	1:1	0.662	1.256	0.831	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.58	-0.04	1	Ant B	E57E3	QPSK	50	0	10 mm	back	1:1	0.535	1.236	0.661	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.52	-0.03	1	Ant B	E57E3	QPSK	100	0	10 mm	back	1:1	0.548	1.253	0.687	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	-0.04	0	Ant B	E57E3	QPSK	1	0	10 mm	front	1:1	0.565	1.256	0.710	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.58	-0.04	1	Ant B	E57E3	QPSK	50	0	10 mm	front	1:1	0.457	1.236	0.565	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	0.00	0	Ant B	E57E3	QPSK	1	0	10 mm	bottom	1:1	0.808	1.256	1.015	A29
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.58	0.07	1	Ant B	E57E3	QPSK	50	0	10 mm	bottom	1:1	0.650	1.236	0.803	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.52	0.03	1	Ant B	E57E3	QPSK	100	0	10 mm	bottom	1:1	0.661	1.253	0.828	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	-0.08	0	Ant B	E57E3	QPSK	1	0	10 mm	left	1:1	0.269	1.256	0.338	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.58	0.03	1	Ant B	E57E3	QPSK	50	0	10 mm	left	1:1	0.204	1.236	0.252	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.51	0.01	0	Ant B	E57E3	QPSK	1	0	10 mm	bottom	1:1	0.773	1.256	0.971	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body											
Spatial Peak									1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population									averaged over 1 gram											

Note: Variability Measurement is Highlighted in Blue

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 69 of 92

Table 11-25
LTE Band 25 (PCS) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.68	0.01	0	Ant B	E57BB	QPSK	1	0	10 mm	back	1:1	0.348	1.208	0.420	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.82	0.05	1	Ant B	E57BB	QPSK	50	0	10 mm	back	1:1	0.273	1.169	0.319	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.68	-0.01	0	Ant B	E57BB	QPSK	1	0	10 mm	front	1:1	0.298	1.208	0.360	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.82	-0.01	1	Ant B	E57BB	QPSK	50	0	10 mm	front	1:1	0.229	1.169	0.268	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.68	0.14	0	Ant B	E57BB	QPSK	1	0	10 mm	bottom	1:1	0.416	1.208	0.503	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.82	0.11	1	Ant B	E57BB	QPSK	50	0	10 mm	bottom	1:1	0.337	1.169	0.394	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.68	-0.14	0	Ant B	E57BB	QPSK	1	0	10 mm	left	1:1	0.185	1.208	0.223	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.82	0.01	1	Ant B	E57BB	QPSK	50	0	10 mm	left	1:1	0.146	1.169	0.171	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram												

Table 11-26
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
2680.00	41490	High	LTE Band 41	20	23.5	22.97	-0.06	0	Ant B	E559F	QPSK	1	99	10 mm	back	1:1.58	0.356	1.130	0.402	
2680.00	41490	High	LTE Band 41	20	22.5	22.16	-0.02	1	Ant B	E559F	QPSK	50	0	10 mm	back	1:1.58	0.279	1.081	0.302	
2680.00	41490	High	LTE Band 41	20	23.5	22.97	0.04	0	Ant B	E559F	QPSK	1	99	10 mm	front	1:1.58	0.377	1.130	0.426	
2680.00	41490	High	LTE Band 41	20	22.5	22.16	-0.05	1	Ant B	E559F	QPSK	50	0	10 mm	front	1:1.58	0.294	1.081	0.318	
2506.00	39750	Low	LTE Band 41	20	23.5	22.63	-0.03	0	Ant B	E559F	QPSK	1	99	10 mm	bottom	1:1.58	0.712	1.222	0.870	
2549.50	40185	Low-Mid	LTE Band 41	20	23.5	22.91	0.02	0	Ant B	E559F	QPSK	1	99	10 mm	bottom	1:1.58	0.876	1.146	1.004	
2593.00	40620	Mid	LTE Band 41	20	23.5	22.93	-0.03	0	Ant B	E559F	QPSK	1	0	10 mm	bottom	1:1.58	0.962	1.140	1.097	A33
2636.50	41055	Mid-High	LTE Band 41	20	23.5	22.84	0.04	0	Ant B	E559F	QPSK	1	99	10 mm	bottom	1:1.58	0.755	1.164	0.879	
2680.00	41490	High	LTE Band 41	20	23.5	22.97	0.03	0	Ant B	E559F	QPSK	1	99	10 mm	bottom	1:1.58	0.672	1.130	0.759	
2506.00	39750	Low	LTE Band 41	20	22.5	21.65	-0.09	1	Ant B	E559F	QPSK	50	0	10 mm	bottom	1:1.58	0.557	1.216	0.677	
2549.50	40185	Low-Mid	LTE Band 41	20	22.5	21.94	-0.02	1	Ant B	E559F	QPSK	50	0	10 mm	bottom	1:1.58	0.701	1.138	0.798	
2593.00	40620	Mid	LTE Band 41	20	22.5	21.77	0.07	1	Ant B	E559F	QPSK	50	50	10 mm	bottom	1:1.58	0.778	1.183	0.920	
2636.50	41055	Mid-High	LTE Band 41	20	22.5	21.88	0.00	1	Ant B	E559F	QPSK	50	0	10 mm	bottom	1:1.58	0.657	1.153	0.758	
2680.00	41490	High	LTE Band 41	20	22.5	22.16	-0.04	1	Ant B	E559F	QPSK	50	0	10 mm	bottom	1:1.58	0.576	1.081	0.623	
2680.00	41490	High	LTE Band 41	20	22.5	22.07	0.04	1	Ant B	E559F	QPSK	100	0	10 mm	bottom	1:1.58	0.562	1.104	0.620	
2680.00	41490	High	LTE Band 41	20	23.5	22.97	0.12	0	Ant B	E559F	QPSK	1	99	10 mm	left	1:1.58	0.148	1.130	0.167	
2680.00	41490	High	LTE Band 41	20	22.5	22.16	-0.02	1	Ant B	E559F	QPSK	50	0	10 mm	left	1:1.58	0.135	1.081	0.146	
2593.00	40620	Mid	LTE Band 41	20	23.5	22.93	-0.05	0	Ant B	E559F	QPSK	1	0	10 mm	bottom	1:1.58	0.953	1.140	1.086	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																				
Spatial Peak								Body												
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g) averaged over 1 gram												

Note: Variability Measurement is Highlighted in Blue

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 70 of 92

Table 11-27
WLAN Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	19.5	19.36	-0.08	10 mm	1	CD7B8	1	back	99.8	0.174	0.115	1.033	1.002	0.119	
2412	1	802.11b	DSSS	22	19.5	19.36	0.06	10 mm	1	CD7B8	1	front	99.8	0.096	-	1.033	1.002	-	
2412	1	802.11b	DSSS	22	19.5	19.36	0.05	10 mm	1	CD7B8	1	top	99.8	0.187	0.126	1.033	1.002	0.130	
2412	1	802.11b	DSSS	22	19.5	19.36	0.21	10 mm	1	CD7B8	1	left	99.8	0.093	-	1.033	1.002	-	
2437	6	802.11b	DSSS	22	19.5	19.49	0.06	10 mm	2	CD7B8	1	back	99.8	0.201	0.140	1.002	1.002	0.141	A35
2437	6	802.11b	DSSS	22	19.5	19.49	0.14	10 mm	2	CD7B8	1	front	99.8	0.060	-	1.002	1.002	-	
2437	6	802.11b	DSSS	22	19.5	19.49	0.13	10 mm	2	CD7B8	1	top	99.8	0.019	-	1.002	1.002	-	
2437	6	802.11b	DSSS	22	19.5	19.49	0.19	10 mm	2	CD7B8	1	left	99.8	0.052	-	1.002	1.002	-	
5785	157	802.11a	OFDM	20	14.5	13.54	-0.08	10 mm	1	D6265	6	back	98.8	0.541	0.233	1.247	1.012	0.294	A37
5785	157	802.11a	OFDM	20	14.5	13.54	0.03	10 mm	1	D6265	6	front	98.8	0.162	-	1.247	1.012	-	
5785	157	802.11a	OFDM	20	14.5	13.54	-0.18	10 mm	1	D6265	6	top	98.8	0.228	-	1.247	1.012	-	
5785	157	802.11a	OFDM	20	14.5	13.54	-0.14	10 mm	1	D6265	6	left	98.8	0.027	-	1.247	1.012	-	
5825	165	802.11a	OFDM	20	14.5	13.81	-0.17	10 mm	2	D6265	6	back	98.8	0.157	0.076	1.172	1.012	0.090	
5825	165	802.11a	OFDM	20	14.5	13.81	0.13	10 mm	2	D6265	6	front	98.8	0.088	-	1.172	1.012	-	
5825	165	802.11a	OFDM	20	14.5	13.81	0.04	10 mm	2	D6265	6	top	98.8	0.083	-	1.172	1.012	-	
5825	165	802.11a	OFDM	20	14.5	13.81	0.12	10 mm	2	D6265	6	left	98.8	0.033	-	1.172	1.012	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

Table 11-28
DSSS Hotspot SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle%	SAR (1 g)	Scaling Factor (Conducted Power)	Scaling Factor (Duty Cycle)	Reported SAR (1 g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2402	0	Bluetooth	FHSS	9.5	9.03	0.02	10 mm	CD7B8	2	back	77.1	0.007	1.114	1.297	0.010	A39
2402	0	Bluetooth	FHSS	9.5	9.03	0.12	10 mm	CD7B8	2	front	77.1	0.003	1.114	1.297	0.004	
2402	0	Bluetooth	FHSS	9.5	9.03	0.08	10 mm	CD7B8	2	top	77.1	0.002	1.114	1.297	0.003	
2402	0	Bluetooth	FHSS	9.5	9.03	-0.15	10 mm	CD7B8	2	left	77.1	0.002	1.114	1.297	0.003	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body									
Spatial Peak							1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population							averaged over 1 gram									

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 71 of 92

11.4 Standalone Phablet SAR Data

Table 11-29
WLAN Phablet SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5320	64	802.11a	OFDM	20	14.5	13.97	0.19	0 mm	1	D6265	6	back	98.8	15.491	0.991	1.130	1.012	1.133	
5320	64	802.11a	OFDM	20	14.5	13.97	0.03	0 mm	1	D6265	6	front	98.8	1.483	0.123	1.130	1.012	0.141	
5320	64	802.11a	OFDM	20	14.5	13.97	0.10	0 mm	1	D6265	6	top	98.8	1.024	-	1.130	1.012	-	
5320	64	802.11a	OFDM	20	14.5	13.97	-0.10	0 mm	1	D6265	6	left	98.8	0.099	-	1.130	1.012	-	
5320	64	802.11a	OFDM	20	14.5	14.06	-0.12	0 mm	2	D6265	6	back	98.8	6.482	0.491	1.107	1.012	0.550	
5320	64	802.11a	OFDM	20	14.5	14.06	-0.17	0 mm	2	D6265	6	front	98.8	2.617	-	1.107	1.012	-	
5320	64	802.11a	OFDM	20	14.5	14.06	0.14	0 mm	2	D6265	6	top	98.8	2.275	-	1.107	1.012	-	
5320	64	802.11a	OFDM	20	14.5	14.06	0.03	0 mm	2	D6265	6	left	98.8	0.449	-	1.107	1.012	-	
5500	100	802.11a	OFDM	20	14.5	13.97	0.03	0 mm	1	D6265	6	back	98.8	9.673	1.260	1.130	1.012	1.441	A40
5500	100	802.11a	OFDM	20	14.5	13.97	0.02	0 mm	1	D6265	6	front	98.8	1.722	0.196	1.130	1.012	0.224	
5500	100	802.11a	OFDM	20	14.5	13.97	0.02	0 mm	1	D6265	6	top	98.8	1.428	-	1.130	1.012	-	
5500	100	802.11a	OFDM	20	14.5	13.97	0.02	0 mm	1	D6265	6	left	98.8	0.101	-	1.130	1.012	-	
5720	144	802.11a	OFDM	20	14.5	14.38	0.09	0 mm	2	D6265	6	back	98.8	3.233	0.275	1.028	1.012	0.286	
5720	144	802.11a	OFDM	20	14.5	14.38	0.02	0 mm	2	D6265	6	front	98.8	1.358	-	1.028	1.012	-	
5720	144	802.11a	OFDM	20	14.5	14.38	-0.05	0 mm	2	D6265	6	top	98.8	1.258	-	1.028	1.012	-	
5720	144	802.11a	OFDM	20	14.5	14.38	0.11	0 mm	2	D6265	6	left	98.8	0.269	-	1.028	1.012	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Phablet											
Spatial Peak								4.0 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 10 grams											

Table 11-30
DSSS Phablet SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle %	SAR (10g)	Scaling Factor (Conducted Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441	39	Bluetooth	FHSS	15.5	15.23	-0.02	0 mm	CD7B8	1	back	77.1	0.362	1.064	1.297	0.500	A41
2441	39	Bluetooth	FHSS	15.5	15.23	-0.04	0 mm	CD7B8	1	front	77.1	0.162	1.064	1.297	0.224	
2441	39	Bluetooth	FHSS	15.5	15.23	-0.06	0 mm	CD7B8	1	top	77.1	0.058	1.064	1.297	0.080	
2441	39	Bluetooth	FHSS	15.5	15.23	0.18	0 mm	CD7B8	1	left	77.1	0.068	1.064	1.297	0.094	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Phablet								
Spatial Peak								4.0 W/kg (mW/g)								
Uncontrolled Exposure/General Population								averaged over 10 gram								

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 72 of 92

11.5 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.
11. This device supports dynamic antenna tuning for some bands. Per FCC Guidance, SAR was measured according to the normally required SAR measurement configurations with tuner active. The auto-tune state determined by the device was verified before and after each SAR measurement and is listed in tables above. Please see Section 14 for supplemental data.

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 73 of 92

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported (scaled) for LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
6. LTE Band 5 Ant E is disabled for all held to ear scenarios. Therefore SAR was only assessed for body-worn accessory and wireless router conditions.

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.6.6 for more information.
4. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06. Please see Section 12 for complete analysis.
5. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 74 of 92

6. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.
7. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes:

1. Body Worn and phablet Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9-5 for the time-domain plot and calculation for the duty factor of the device.
2. Head and Hotspot Bluetooth SAR is supported for BT EDR tethering applications.
3. Head and Hotspot Bluetooth SAR were measured with the device connected to a call box with hopping disabled with 2DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9-5 for the time-domain plot and calculation for the duty factor of the device.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 75 of 92

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB Publication 248227, the worst case WLAN SAR result for applicable exposure conditions was used for simultaneous transmission analysis.

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 1900	0.028	0.241	0.170	0.269	0.198	0.439
	UMTS 850	0.127	0.241	0.170	0.368	0.297	0.538
	UMTS 1900	0.057	0.241	0.170	0.298	0.227	0.468
	LTE Band 12	0.075	0.241	0.170	0.316	0.245	0.486
	LTE Band 13	0.096	0.241	0.170	0.337	0.266	0.507
	LTE Band 26 (Cell)	0.144	0.241	0.170	0.385	0.314	0.555
	LTE Band 5 (Cell)	0.188	0.241	0.170	0.429	0.358	0.599
	LTE Band 4 (AWS)	0.131	0.241	0.170	0.372	0.301	0.542
	LTE Band 25 (PCS)	0.103	0.241	0.170	0.344	0.273	0.514
	LTE Band 41	0.066	0.241	0.170	0.307	0.236	0.477

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 76 of 92

Table 12-2
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 1900	0.028	0.366	0.252	0.394	0.280	0.646
	UMTS 850	0.127	0.366	0.252	0.493	0.379	0.745
	UMTS 1900	0.057	0.366	0.252	0.423	0.309	0.675
	LTE Band 12	0.075	0.366	0.252	0.441	0.327	0.693
	LTE Band 13	0.096	0.366	0.252	0.462	0.348	0.714
	LTE Band 26 (Cell)	0.144	0.366	0.252	0.510	0.396	0.762
	LTE Band 5 (Cell)	0.188	0.366	0.252	0.554	0.440	0.806
	LTE Band 4 (AWS)	0.131	0.366	0.252	0.497	0.383	0.749
	LTE Band 25 (PCS)	0.103	0.366	0.252	0.469	0.355	0.721
	LTE Band 41	0.066	0.366	0.252	0.432	0.318	0.684

Table 12-3
Simultaneous Transmission Scenario with 2.4 GHz and 5 GHz (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	4	5	1+2+3+4+5
Head SAR	GSM 1900	0.028	0.241	0.170	0.366	0.252	1.057
	UMTS 850	0.127	0.241	0.170	0.366	0.252	1.156
	UMTS 1900	0.057	0.241	0.170	0.366	0.252	1.086
	LTE Band 12	0.075	0.241	0.170	0.366	0.252	1.104
	LTE Band 13	0.096	0.241	0.170	0.366	0.252	1.125
	LTE Band 26 (Cell)	0.144	0.241	0.170	0.366	0.252	1.173
	LTE Band 5 (Cell)	0.188	0.241	0.170	0.366	0.252	1.217
	LTE Band 4 (AWS)	0.131	0.241	0.170	0.366	0.252	1.160
	LTE Band 25 (PCS)	0.103	0.241	0.170	0.366	0.252	1.132
	LTE Band 41	0.066	0.241	0.170	0.366	0.252	1.095

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 77 of 92

Table 12-4
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 1900	0.028	0.045	0.073
	UMTS 850	0.127	0.045	0.172
	UMTS 1900	0.057	0.045	0.102
	LTE Band 12	0.075	0.045	0.120
	LTE Band 13	0.096	0.045	0.141
	LTE Band 26 (Cell)	0.144	0.045	0.189
	LTE Band 5 (Cell)	0.188	0.045	0.233
	LTE Band 4 (AWS)	0.131	0.045	0.176
	LTE Band 25 (PCS)	0.103	0.045	0.148
	LTE Band 41	0.066	0.045	0.111

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 1900	0.073	0.053	0.049	0.126	0.122	0.175
	UMTS 850	0.201	0.053	0.049	0.254	0.250	0.303
	UMTS 1900	0.202	0.053	0.049	0.255	0.251	0.304
	LTE Band 12	0.164	0.053	0.049	0.217	0.213	0.266
	LTE Band 13	0.215	0.053	0.049	0.268	0.264	0.317
	LTE Band 26 (Cell)	0.226	0.053	0.049	0.279	0.275	0.328
	LTE Band 5 (Cell)	0.311	0.053	0.049	0.364	0.360	0.413
	LTE Band 4 (AWS)	0.474	0.053	0.049	0.527	0.523	0.576
	LTE Band 25 (PCS)	0.245	0.053	0.049	0.298	0.294	0.347
	LTE Band 41	0.215	0.053	0.049	0.268	0.264	0.317

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 78 of 92

Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 1900	0.073	0.321	0.102	0.394	0.175	0.496
	UMTS 850	0.201	0.321	0.102	0.522	0.303	0.624
	UMTS 1900	0.202	0.321	0.102	0.523	0.304	0.625
	LTE Band 12	0.164	0.321	0.102	0.485	0.266	0.587
	LTE Band 13	0.215	0.321	0.102	0.536	0.317	0.638
	LTE Band 26 (Cell)	0.226	0.321	0.102	0.547	0.328	0.649
	LTE Band 5 (Cell)	0.311	0.321	0.102	0.632	0.413	0.734
	LTE Band 4 (AWS)	0.474	0.321	0.102	0.795	0.576	0.897
	LTE Band 25 (PCS)	0.245	0.321	0.102	0.566	0.347	0.668
	LTE Band 41	0.215	0.321	0.102	0.536	0.317	0.638

Table 12-7
Simultaneous Transmission Scenario with 2.4 GHz and 5 GHz (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	4	5	1+2+3+4+5
Body-Worn	GSM 1900	0.073	0.053	0.049	0.321	0.102	0.598
	UMTS 850	0.201	0.053	0.049	0.321	0.102	0.726
	UMTS 1900	0.202	0.053	0.049	0.321	0.102	0.727
	LTE Band 12	0.164	0.053	0.049	0.321	0.102	0.689
	LTE Band 13	0.215	0.053	0.049	0.321	0.102	0.740
	LTE Band 26 (Cell)	0.226	0.053	0.049	0.321	0.102	0.751
	LTE Band 5 (Cell)	0.311	0.053	0.049	0.321	0.102	0.836
	LTE Band 4 (AWS)	0.474	0.053	0.049	0.321	0.102	0.999
	LTE Band 25 (PCS)	0.245	0.053	0.049	0.321	0.102	0.770
	LTE Band 41	0.215	0.053	0.049	0.321	0.102	0.740

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 79 of 92

Table 12-8
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 1900	0.073	0.046	0.119
	UMTS 850	0.201	0.046	0.247
	UMTS 1900	0.202	0.046	0.248
	LTE Band 12	0.164	0.046	0.210
	LTE Band 13	0.215	0.046	0.261
	LTE Band 26 (Cell)	0.226	0.046	0.272
	LTE Band 5 (Cell)	0.311	0.046	0.357
	LTE Band 4 (AWS)	0.474	0.046	0.520
	LTE Band 25 (PCS)	0.245	0.046	0.291
	LTE Band 41	0.215	0.046	0.261

12.5 Hotspot SAR Simultaneous Transmission Analysis

Table 12-9
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 1900	0.241	0.130	0.141	0.371	0.382	0.512
	UMTS 850	0.300	0.130	0.141	0.430	0.441	0.571
	UMTS 1900	0.396	0.130	0.141	0.526	0.537	0.667
	LTE Band 12	0.251	0.130	0.141	0.381	0.392	0.522
	LTE Band 13	0.361	0.130	0.141	0.491	0.502	0.632
	LTE Band 26 (Cell)	0.387	0.130	0.141	0.517	0.528	0.658
	LTE Band 5 (Cell)	0.530	0.130	0.141	0.660	0.671	0.801
	LTE Band 4 (AWS)	1.015	0.130	0.141	1.145	1.156	1.286
	LTE Band 25 (PCS)	0.503	0.130	0.141	0.633	0.644	0.774
	LTE Band 41	1.097	0.130	0.141	1.227	1.238	1.368

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 80 of 92

Table 12-10
Simultaneous Transmission Scenario with 5.8 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 1900	0.241	0.294	0.090	0.535	0.331	0.625
	UMTS 850	0.300	0.294	0.090	0.594	0.390	0.684
	UMTS 1900	0.396	0.294	0.090	0.690	0.486	0.780
	LTE Band 12	0.251	0.294	0.090	0.545	0.341	0.635
	LTE Band 13	0.361	0.294	0.090	0.655	0.451	0.745
	LTE Band 26 (Cell)	0.387	0.294	0.090	0.681	0.477	0.771
	LTE Band 5 (Cell)	0.530	0.294	0.090	0.824	0.620	0.914
	LTE Band 4 (AWS)	1.015	0.294	0.090	1.309	1.105	1.399
	LTE Band 25 (PCS)	0.503	0.294	0.090	0.797	0.593	0.887
	LTE Band 41	1.097	0.294	0.090	1.391	1.187	1.481

Table 12-11
Simultaneous Transmission Scenario with 2.4 GHz and 5.8 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	4	5	1+2+3+4+5
Hotspot SAR	GPRS 1900	0.241	0.130	0.141	0.294	0.090	0.896
	UMTS 850	0.300	0.130	0.141	0.294	0.090	0.955
	UMTS 1900	0.396	0.130	0.141	0.294	0.090	1.051
	LTE Band 12	0.251	0.130	0.141	0.294	0.090	0.906
	LTE Band 13	0.361	0.130	0.141	0.294	0.090	1.016
	LTE Band 26 (Cell)	0.387	0.130	0.141	0.294	0.090	1.042
	LTE Band 5 (Cell)	0.530	0.130	0.141	0.294	0.090	1.185
	LTE Band 4 (AWS)	1.015	0.130	0.141	0.294	0.090	See Table Below
	LTE Band 25 (PCS)	0.503	0.130	0.141	0.294	0.090	1.158
	LTE Band 41	1.097	0.130	0.141	0.294	0.090	See Table Below

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 81 of 92

Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	4	5	1+2+3+4+5
Hotspot SAR	Back	0.831	0.119	0.141	0.294	0.090	1.475
	Front	0.710	0.130*	0.141*	0.294*	0.090*	1.365
	Top	-	0.130	0.141*	0.294*	0.090*	0.655
	Bottom	1.015	-	-	-	-	1.015
	Right	-	-	-	-	-	0.000
	Left	0.338	0.130*	0.141*	0.294*	0.090*	0.993

Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	4	5	1+2+3+4+5
Hotspot SAR	Back	0.402	0.119	0.141	0.294	0.090	1.046
	Front	0.426	0.130*	0.141*	0.294*	0.090*	1.081
	Top	-	0.130	0.141*	0.294*	0.090*	0.655
	Bottom	1.097	-	-	-	-	1.097
	Right	-	-	-	-	-	0.000
	Left	0.167	0.130*	0.141*	0.294*	0.090*	0.822

FCC ID: A3LSMG955N		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset			Page 82 of 92

Table 12-12
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 1900	0.241	0.010	0.251
	UMTS 850	0.300	0.010	0.310
	UMTS 1900	0.396	0.010	0.406
	LTE Band 12	0.251	0.010	0.261
	LTE Band 13	0.361	0.010	0.371
	LTE Band 26 (Cell)	0.387	0.010	0.397
	LTE Band 5 (Cell)	0.530	0.010	0.540
	LTE Band 4 (AWS)	1.015	0.010	1.025
	LTE Band 25 (PCS)	0.503	0.010	0.513
	LTE Band 41	1.097	0.010	1.107

12.6 Phablet SAR Simultaneous Transmission Analysis

Main antenna SAR testing was not required for phablet exposure conditions per FCC KDB 648474 D04v01r03. Therefore, no further analysis was required to determine that possible simultaneous scenarios would not exceed the SAR limit.

Table 12-13
Simultaneous Transmission Scenario 5 GHz WLAN (Phablet at 0.0 cm)

Exposure Condition	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Phablet SAR	1.441	0.550	1.991

12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset	Page 83 of 92	

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS												
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)
1750	1732.50	20175	LTE Band 4 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	bottom	10 mm	0.808	0.773	1.05	N/A	N/A	N/A
2600	2593.00	40620	LTE Band 41, 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	bottom	10 mm	0.962	0.953	1.01	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 84 of 92

14 ADDITIONAL TESTING PER FCC GUIDANCE

14.1 Tuner Testing

The following test procedures were followed to demonstrate that the SAR results in Section 11 represented the appropriate SAR test conditions. For bands with dynamic tuning implemented, SAR was measured according to the required FCC SAR test procedures with the dynamic tuner active to allow the device to automatically tune to the antenna state for the respective RF exposure test configurations. Additional single point SAR time-sweep measurements were evaluated for other tuner states to determine that the other tuner configurations would result in equivalent or lower SAR values. The additional tuner hardware has no influence to the antenna characteristics, other than impedance matching.

To evaluate all of the tuner states, the 25 tuner states were divided evenly among band, mode and exposure combinations so that at least one single point SAR measurement was measured among the configurations. Single point time-sweep measurements were performed at the peak SAR location determined by the zoom scan of the configuration with the highest reported SAR for each combination. While inserting and removing the USB cable between single point SAR measurements, the device was ensured to capture the same physical point SAR that generated the highest SAR. The SAR probe remained stationary at the same position throughout the entire series of single point measurements for each combination.

The operational description contains more information about the design and implementation of the dynamic antenna tuning.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 85 of 92

Table 14-1
LTE Supplemental Head SAR Data

Supplemental Head SAR Data	
LTE Band 5 Ant A	
QPSK, 10MHz Bandwidth, 1 RB, 0 RB Offset	
Test Position	Right Cheek
Frequency (MHz)	836.5
Channel	20525
Measured 1g SAR (W/kg)	0.136
Average Value of Time Sweep (W/kg)	
Auto-tune (State 1)	0.145
Default (State 1)	0.145
State 2	0.122
State 4	0.119
State 6	0.114
State 8	0.091
State 10	0.120
State 12	0.103
State 14	0.093
State 16	0.080
State 18	0.122
State 19	0.121
State 20	0.100
State 22	0.055
State 24	0.049

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 86 of 92

Table 14-2
LTE Supplemental Body SAR Data

Supplemental Body SAR Data	
LTE Band 5 Ant A	
QPSK, 10MHz Bandwidth, 1 RB, 0 RB Offset	
Test Position	Back Side
Spacing	10 mm
Frequency (MHz)	836.5
Channel	20525
Measured 1g SAR (W/kg)	0.383
Average Value of Time Sweep (W/kg)	
Auto-tune (State 1)	0.509
Default (State 1)	0.508
State 1	0.508
State 3	0.358
State 5	0.451
State 7	0.419
State 9	0.371
State 11	0.316
State 13	0.407
State 15	0.305
State 17	0.421
State 19	0.406
State 21	0.285
State 23	0.248
State 25	0.408

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 87 of 92

15 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	E5515C	Wireless Communications Test Set	12/12/2016	Annual	12/12/2017	GB44400860
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB44450273
Agilent	N5182A	MXG Vector Signal Generator	10/27/2016	Annual	10/27/2017	MY47420603
Agilent	N9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433971
Anritsu	MA24106A	USB Power Sensor	6/2/2016	Annual	6/2/2017	1231535
Anritsu	MA24106A	USB Power Sensor	6/2/2016	Annual	6/2/2017	1231538
Anritsu	MA2411B	Pulse Power Sensor	8/18/2016	Annual	8/18/2017	1126066
Anritsu	MA2411B	Pulse Power Sensor	8/18/2016	Annual	8/18/2017	1207470
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	941001
Anritsu	MT8820C	Radio Communication Analyzer	9/15/2016	Annual	9/15/2017	6200901190
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6"CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264162
Mitutoyo	CD-6"CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264165
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	NC-100	Torque Wrench	11/6/2015	Biennial	11/6/2017	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	10/20/2016	Annual	10/20/2017	100976
Seekonk	NC-100	Torque Wrench	11/6/2015	Biennial	11/6/2017	22313
SPEAG	D750V3	750 MHz SAR Dipole	1/11/2017	Annual	1/11/2018	1003
SPEAG	D1765V2	1765 MHz SAR Dipole	5/11/2016	Annual	5/11/2017	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	7/15/2016	Annual	7/15/2017	5d149
SPEAG	D2450V2	2450 MHz SAR Dipole	9/13/2016	Annual	9/13/2017	797
SPEAG	D2450V2	2450 MHz SAR Dipole	7/25/2016	Annual	7/25/2017	981
SPEAG	D2600V2	2600 MHz SAR Dipole	9/13/2016	Annual	9/13/2017	1071
SPEAG	D2600V2	2600 MHz SAR Dipole	7/25/2016	Annual	7/25/2017	1126
SPEAG	D5GHzV2	5 GHz SAR Dipole	2/13/2017	Annual	2/13/2018	1120
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/2/2016	Annual	8/2/2017	1237
SPEAG	D750V3	750 MHz SAR Dipole	7/13/2016	Annual	7/13/2017	1161
SPEAG	D835V2	835 MHz SAR Dipole	7/13/2016	Annual	7/13/2017	4d047
SPEAG	D835V2	835 MHz SAR Dipole	7/14/2016	Annual	7/14/2017	4d133
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2017	Annual	2/9/2018	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/11/2016	Annual	5/11/2017	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2017	Annual	2/9/2018	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/11/2016	Annual	11/11/2017	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/14/2016	Annual	4/14/2017	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/14/2016	Annual	9/14/2017	1408
SPEAG	ES3DV3	SAR Probe	2/10/2017	Annual	2/10/2018	3213
SPEAG	ES3DV3	SAR Probe	9/19/2016	Annual	9/19/2017	3287
SPEAG	ES3DV3	SAR Probe	2/10/2017	Annual	2/10/2018	3318
SPEAG	EX3DV4	SAR Probe	2/13/2017	Annual	2/13/2018	3914
SPEAG	EX3DV4	SAR Probe	7/21/2016	Annual	7/21/2017	7308
SPEAG	EX3DV4	SAR Probe	4/19/2016	Annual	4/19/2017	7406
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/10/2016	Annual	5/10/2017	1070

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 88 of 92

16 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)						RSS	11.5	11.3
Expanded Uncertainty (95% CONFIDENCE LEVEL)						k=2	23.0	22.6

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 89 of 92

17 CONCLUSION

17.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 90 of 92

18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 91 of 92

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMG955N		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1703100104-01.A3L	Test Dates: 03/06/17 - 03/23/17	DUT Type: Portable Handset		Page 92 of 92

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E5

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.428 \text{ S/m}$; $\epsilon_r = 39.495$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-20-2017; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3318; ConvF(5.31, 5.31, 5.31); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.002 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.0330 W/kg

SAR(1 g) = 0.022 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E559F

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.897 \text{ S/m}$; $\epsilon_r = 40.447$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-20-2017; Ambient Temp: 22.3°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.69 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.149 W/kg

SAR(1 g) = 0.119 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E5

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.428 \text{ S/m}$; $\epsilon_r = 39.495$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-20-2017; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3318; ConvF(5.31, 5.31, 5.31); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.161 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.0780 W/kg

SAR(1 g) = 0.050 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E5

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.856 \text{ S/m}$; $\epsilon_r = 40.977$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-16-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3287; ConvF(6.96, 6.96, 6.96); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Left; Type: QD000P40CA; Serial: TP:82355

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.207 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.0830 W/kg

SAR(1 g) = 0.063 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E5667

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ S/m}$; $\epsilon_r = 39.964$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-16-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3287; ConvF(6.96, 6.96, 6.96); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Left; Type: QD000P40CA; Serial: TP:82355

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.567 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.0940 W/kg

SAR(1 g) = 0.073 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E559F

Communication System: UID 0, LTE Band 26 (0); Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.893 \text{ S/m}$; $\epsilon_r = 40.498$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-20-2017; Ambient Temp: 22.3°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Right Head, Cheek, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.19 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.149 W/kg

SAR(1 g) = 0.121 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E559F

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.897 \text{ S/m}$; $\epsilon_r = 40.448$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-20-2017; Ambient Temp: 22.3°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch,
Antenna A, 10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.75 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.169 W/kg

SAR(1 g) = 0.136 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E559F

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.32 \text{ S/m}$; $\epsilon_r = 39.008$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-22-2017; Ambient Temp: 24.1°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3318; ConvF(5.49, 5.49, 5.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.677 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.152 W/kg

SAR(1 g) = 0.104 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E5

Communication System: UID 0, LTE Band 25 (PCS) (0); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.456 \text{ S/m}$; $\epsilon_r = 39.337$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-20-2017; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3318; ConvF(5.31, 5.31, 5.31); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.544 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.131 W/kg

SAR(1 g) = 0.085 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57BB

Communication System: UID 0, LTE Band 41(0); Frequency: 2680 MHz; Duty Cycle: 1:1.58

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2680 \text{ MHz}$; $\sigma = 2.132 \text{ S/m}$; $\epsilon_r = 37.37$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-15-2017; Ambient Temp: 22.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3287; ConvF(4.41, 4.41, 4.41); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Left Head, Cheek, High.ch, QPSK,
20 MHz Bandwidth, 1 RB, 99 RB Offset**


Area Scan (10x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.847 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.105 W/kg

SAR(1 g) = 0.058 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: CD7B8

Communication System: UID 0, IEEE 802.11b (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2400 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.869 \text{ S/m}$; $\epsilon_r = 38.684$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-06-2017; Ambient Temp: 23.6°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3287; ConvF(4.54, 4.54, 4.54); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Antenna 1,
Right Head, Cheek, Ch 11, 1 Mbps**


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.40 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.568 W/kg

SAR(1 g) = 0.232 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: CD7B8

Communication System: UID 0, 802.11ac 5.2-5.8 GHz Band (0); Frequency: 5775 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5775 \text{ MHz}$; $\sigma = 5.331 \text{ S/m}$; $\epsilon_r = 34.933$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-13-2017; Ambient Temp: 20.2°C; Tissue Temp: 19.9°C

Probe: EX3DV4 - SN3914; ConvF(4.91, 4.91, 4.91); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11ac, U-NII-3, 80 MHz Bandwidth, Antenna 1,
Right Head, Cheek, Ch 155, 29.3 Mbps**


Area Scan (13x22x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 8.015 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.34 W/kg

SAR(1 g) = 0.336 W/kg



0 dB = 1.11 W/kg = 0.45 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: D6265

Communication System: UID 0, Bluetooth (0); Frequency: 2402 MHz; Duty Cycle: 1:1.297

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2402 \text{ MHz}$; $\sigma = 1.82 \text{ S/m}$; $\epsilon_r = 37.894$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-09-2017; Ambient Temp: 20.9°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3287; ConvF(4.54, 4.54, 4.54); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: Bluetooth, Head SAR, Ch 0, 2 Mbps, Right Cheek


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (11x9x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.451 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.183 W/kg

SAR(1 g) = 0.031 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57BB

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.552 \text{ S/m}$; $\epsilon_r = 53.942$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-20-2017; Ambient Temp: 22.6°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.505 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.0890 W/kg

SAR(1 g) = 0.058 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57BB

Communication System: UID 0, GSM GPRS; 4 Tx slots (0); Frequency: 1909.8 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body Medium parameters used:

$f = 1909.8 \text{ MHz}$; $\sigma = 1.588 \text{ S/m}$; $\epsilon_r = 53.82$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 22.6°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Bottom Edge, High.ch, 4 Tx Slots


Area Scan (10x7x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.72 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.364 W/kg

SAR(1 g) = 0.218 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E4A6F

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 55.054$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-23-2017; Ambient Temp: 22.8°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.40 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.254 W/kg

SAR(1 g) = 0.188 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E4A6F

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 55.054$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-23-2017; Ambient Temp: 22.8°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.89 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.451 W/kg

SAR(1 g) = 0.281 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57BB

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.552 \text{ S/m}$; $\epsilon_r = 53.942$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-20-2017; Ambient Temp: 22.6°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.23 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.274 W/kg

SAR(1 g) = 0.176 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57BB

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.552 \text{ S/m}$; $\epsilon_r = 53.942$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 22.6°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Bottom Edge, Mid.ch


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.98 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.574 W/kg

SAR(1 g) = 0.345 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E3

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5$ MHz; $\sigma = 0.921$ S/m; $\epsilon_r = 54.858$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-16-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.66 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.186 W/kg

SAR(1 g) = 0.138 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E3

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.921 \text{ S/m}$; $\epsilon_r = 54.858$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 03-16-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.50 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.360 W/kg

SAR(1 g) = 0.212 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E3

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.994 \text{ S/m}$; $\epsilon_r = 54.167$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-16-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.31 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.213 W/kg

SAR(1 g) = 0.164 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E3

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.994 \text{ S/m}$; $\epsilon_r = 54.167$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-16-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (8x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.68 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.472 W/kg

SAR(1 g) = 0.275 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E4A6F

Communication System: UID 0, LTE Band 26 (0); Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.99 \text{ S/m}$; $\epsilon_r = 55.104$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-23-2017; Ambient Temp: 22.8°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.60 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.259 W/kg

SAR(1 g) = 0.190 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E4A6F

Communication System: UID 0, LTE Band 26 (0); Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.99 \text{ S/m}$; $\epsilon_r = 55.104$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 03-23-2017; Ambient Temp: 22.8°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Front side, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.33 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.536 W/kg

SAR(1 g) = 0.325 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E559F

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 55.055$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-23-2017; Ambient Temp: 22.8°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
Antenna A, 10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.64 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.299 W/kg

SAR(1 g) = 0.225 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E559F

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 55.055$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 03-23-2017; Ambient Temp: 22.8°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
Antenna A, 10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.32 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.633 W/kg

SAR(1 g) = 0.383 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E3

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.462 \text{ S/m}$; $\epsilon_r = 51.061$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-14-2017; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3213; ConvF(5.09, 5.09, 5.09); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.96 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.562 W/kg

SAR(1 g) = 0.377 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57E3

Communication System: UID 0, LTE Band 4 (AWS) (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.462 \text{ S/m}$; $\epsilon_r = 51.061$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-14-2017; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3213; ConvF(5.09, 5.09, 5.09); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Bottom Edge, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.40 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.808 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57BB

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.582 \text{ S/m}$; $\epsilon_r = 53.84$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-20-2017; Ambient Temp: 22.6°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.00 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.317 W/kg

SAR(1 g) = 0.203 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E57BB

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.582 \text{ S/m}$; $\epsilon_r = 53.84$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 22.6°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Body SAR, Bottom Edge, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x9x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.41 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.696 W/kg

SAR(1 g) = 0.416 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E559F

Communication System: UID 0, LTE Band 41 (0); Frequency: 2680 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2680 \text{ MHz}$; $\sigma = 2.338 \text{ S/m}$; $\epsilon_r = 51.938$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB,99 RB Offset**


Area Scan (10x16x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.429 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.380 W/kg

SAR(1 g) = 0.190 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: E559F

Communication System: UID 0, LTE Band 41 (0); Frequency: 2593 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2593 \text{ MHz}$; $\sigma = 2.224 \text{ S/m}$; $\epsilon_r = 52.279$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 41, Body SAR, Bottom Edge, Mid.ch,

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (10x9x1): Measurement grid: $dx=5\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.95 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.99 W/kg

SAR(1 g) = 0.962 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: CD7B8

Communication System: UID 0, IEEE 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$; $\sigma = 1.975 \text{ S/m}$; $\epsilon_r = 52.962$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Antenna 1,
Body SAR, Ch 1, 1 Mbps, Back Side**


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.445 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.0990 W/kg

SAR(1 g) = 0.051 W/Kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: CD7B8

Communication System: UID 0, IEEE 802.11b (0); Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.011 \text{ S/m}$; $\epsilon_r = 52.862$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Antenna 2,
Body SAR, Ch 6, 1 Mbps, Back Side**


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.616 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.315 W/kg

SAR(1 g) = 0.140 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: D6265

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band (0); Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 5.844 \text{ S/m}$; $\epsilon_r = 46.679$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-20-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(3.75, 3.75, 3.75); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, UNII-2C, 20 MHz Bandwidth, Antenna 1,
Body SAR, Ch 100, 6 Mbps, Back Side**


Area Scan (11x20x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 7.631 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.981 W/kg

SAR(1 g) = 0.281 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: D6265

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band (0); Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used:

$f = 5785 \text{ MHz}$; $\sigma = 6.232 \text{ S/m}$; $\epsilon_r = 46.219$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(4.04, 4.04, 4.04); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, UNII-3, 20 MHz Bandwidth, Antenna 1,
Body SAR, Ch 157, 6 Mbps, Back Side**


Area Scan (11x20x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.695 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.974 W/kg

SAR(1 g) = 0.233 W/kg



0 dB = 0.600 W/kg = -2.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: CD7B8

Communication System: UID 0, Bluetooth (0); Frequency: 2441 MHz; Duty Cycle: 1:1.297

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 2.016 \text{ S/m}$; $\epsilon_r = 52.846$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.315 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.0660 W/kg

SAR(1 g) = 0.033 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: CD7B8

Communication System: UID 0, Bluetooth (0); Frequency: 2402 MHz; Duty Cycle: 1:1.297

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2402 \text{ MHz}$; $\sigma = 1.961 \text{ S/m}$; $\epsilon_r = 53.002$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: Bluetooth, Body SAR, Ch 0, 2 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.117 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.0140 W/kg

SAR(1 g) = 0.007 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: D6265

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band (0); Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 5.844 \text{ S/m}$; $\epsilon_r = 46.679$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 03-20-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(3.75, 3.75, 3.75); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-2C, 20 MHz Bandwidth, Antenna 1

Phablet SAR, Ch 100, 6 Mbps, Back Side


Area Scan (13x21x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 2.995 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 49.6 W/kg

SAR(10 g) = 1.26 W/kg



0 dB = 22.8 W/kg = 13.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG955N; Type: Portable Handset; Serial: CD7B8

Communication System: UID 0, Bluetooth (0); Frequency: 2441 MHz; Duty Cycle: 1:1.297

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 2.016 \text{ S/m}$; $\epsilon_r = 52.846$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: Bluetooth, Phablet SAR, Ch 39, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.67 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 4.39 W/kg

SAR(10 g) = 0.362 W/kg



0 dB = 2.96 W/kg = 4.71 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1161

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.9 \text{ S/m}$; $\epsilon_r = 40.393$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-16-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3287; ConvF(6.96, 6.96, 6.96); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Left; Type: QD000P40CA; Serial: TP:82355

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.35 W/kg

SAR(1 g) = 1.58 W/kg

Deviation(1 g) = -3.30%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.896 \text{ S/m}$; $\epsilon_r = 40.456$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 03-20-2017; Ambient Temp: 22.3°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 04/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 04/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.88 W/kg

SAR(1 g) = 1.92 W/kg

Deviation(1 g) = 5.15%;



0 dB = 2.57 W/kg = 4.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.338 \text{ S/m}$; $\epsilon_r = 38.95$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-22-2017; Ambient Temp: 24.1°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3318; ConvF(5.49, 5.49, 5.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 6.33 W/kg

SAR(1 g) = 3.49 W/kg

Deviation(1 g) = -4.90%



0 dB = 4.34 W/kg = 6.37 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.45 \text{ S/m}$; $\epsilon_r = 39.369$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3318; ConvF(5.31, 5.31, 5.31); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.08 W/kg

SAR(1 g) = 3.87 W/kg

Deviation(1 g) = -3.49%



0 dB = 4.90 W/kg = 6.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.871 \text{ S/m}$; $\epsilon_r = 37.716$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 03-09-2017; Ambient Temp: 20.9°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3287; ConvF(4.54, 4.54, 4.54); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.7 W/kg

SAR(1 g) = 5.48 W/kg

Deviation(1 g) = 5.18%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2600$ MHz; $\sigma = 2.035$ S/m; $\epsilon_r = 37.642$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-15-2017; Ambient Temp: 22.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3287; ConvF(4.41, 4.41, 4.41); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 13.5 W/kg

SAR(1 g) = 6.07 W/kg

Deviation(1 g) = 7.82%



0 dB = 8.12 W/kg = 9.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.776 \text{ S/m}$; $\epsilon_r = 35.735$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-13-2017; Ambient Temp: 20.2°C; Tissue Temp: 19.9°C

Probe: EX3DV4 - SN3914; ConvF(5.49, 5.49, 5.49); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 3.93 W/kg

Deviation(1 g) = -5.53%



0 dB = 9.43 W/kg = 9.75 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.144 \text{ S/m}$; $\epsilon_r = 35.182$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-13-2017; Ambient Temp: 20.2°C; Tissue Temp: 19.9°C

Probe: EX3DV4 - SN3914; ConvF(4.94, 4.94, 4.94); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.3 W/kg

SAR(1 g) = 3.97 W/kg

Deviation(1 g) = -7.46%



0 dB = 10.0 W/kg = 10.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 5.288 \text{ S/m}$; $\epsilon_r = 35.008$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-13-2017; Ambient Temp: 20.2°C; Tissue Temp: 19.9°C

Probe: EX3DV4 - SN3914; ConvF(4.91, 4.91, 4.91); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 19.5 W/kg

SAR(1 g) = 4.05 W/kg

Deviation(1 g) = -0.98%



0 dB = 10.4 W/kg = 10.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 54.463$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-16-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.51 W/kg

SAR(1 g) = 1.70 W/kg

Deviation(1 g) = -3.30%



0 dB = 1.99 W/kg = 2.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.994 \text{ S/m}$; $\epsilon_r = 55.069$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-23-2017; Ambient Temp: 22.8°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.88 W/kg

SAR(1 g) = 1.99 W/kg

Deviation(1 g) = 4.74%



0 dB = 2.32 W/kg = 3.65 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750$ MHz; $\sigma = 1.479$ S/m; $\epsilon_r = 50.941$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-14-2017; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3213; ConvF(5.09, 5.09, 5.09); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.57 W/kg

SAR(1 g) = 3.69 W/kg

Deviation(1 g) = -1.07%



0 dB = 4.58 W/kg = 6.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.576 \text{ S/m}$; $\epsilon_r = 53.86$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 22.6°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.94, 4.94, 4.94); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 6.96 W/kg

SAR(1 g) = 3.91 W/kg

Deviation(1 g) = -2.01%



0 dB = 4.96 W/kg = 6.95 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.029$ S/m; $\epsilon_r = 52.81$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.1 W/kg

SAR(1 g) = 4.83 W/kg; SAR (10 g) = 2.20 W/kg

Deviation(1 g) = -4.92%; Deviation(10 g) = -7.56%



0 dB = 8.13 W/kg = 9.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body Medium parameters used:

$f = 2600$ MHz; $\sigma = 2.234$ S/m; $\epsilon_r = 52.254$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-15-2017; Ambient Temp: 22.9°C; Tissue Temp: 22.6°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 12.7 W/kg

SAR(1 g) = 5.59 W/kg

Deviation(1 g) = 3.14%



0 dB = 9.80 W/kg = 9.91 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.524 \text{ S/m}$; $\epsilon_r = 47.038$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(4.45, 4.45, 4.45); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.1 W/kg

SAR(1 g) = 3.68 W/kg; SAR(10 g) = 1.02 W/kg

Deviation(1 g) = -1.60%; Deviation(10 g) = -2.86%



0 dB = 8.99 W/kg = 9.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 6.009 \text{ S/m}$; $\epsilon_r = 46.52$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(3.75, 3.75, 3.75); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.8 W/kg

SAR(1 g) = 4.06 W/kg; SAR(10 g) = 1.12 W/kg

Deviation(1 g) = 5.45%; Deviation(10 g) = 4.19%



0 dB = 9.61 W/kg = 9.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.203 \text{ S/m}$; $\epsilon_r = 46.288$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-20-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(4.04, 4.04, 4.04); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.3 W/kg

SAR(1 g) = 3.53 W/kg; SAR (10 g) = 0.97 W/kg

Deviation(1 g) = -6.37%; Deviation(10 g) = -7.18%



0 dB = 8.68 W/kg = 9.39 dBW/kg