



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

10/20/2017 - 11/15/2017

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M1710020264-01.A3L

FCC ID:

A3LSMG960F

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model:

SM-G960F

Additional Models:

SM-G960F/DS, SM-G960X

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1g Head (W/kg)	1g Body-Worn (W/kg)	1g Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.24	0.36	0.96
PCE	UMTS 850	826.40 - 846.60 MHz	0.26	0.44	0.77
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.16	0.57	0.99
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	< 0.1	0.31	0.79
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.13	0.51	0.59
PCE	LTE Band 12	699.7 - 715.3 MHz	< 0.1	0.15	0.22
PCE	LTE Band 17	706.5 - 713.5 MHz	N/A	N/A	N/A
PCE	LTE Band 13	779.5 - 784.5 MHz	0.16	0.30	0.43
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.16	0.27	0.45
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.19	0.35	0.59
PCE	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	0.24	1.00	1.04
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A	N/A
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.15	0.47	0.74
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A	N/A
PCE	LTE Band 7	2502.5 - 2567.5 MHz	0.18	0.85	0.96
PCE	LTE Band 41	2498.5 - 2687.5 MHz	< 0.1	0.22	0.60
PCE	LTE Band 38	2572.5 - 2617.5 MHz	N/A	N/A	N/A
DTS	2.4 GHz WLAN	2412 - 2472 MHz	1.00	0.14	0.38
NII	U-NII-1	5180 - 5240 MHz	N/A	N/A	N/A
NII	U-NII-2A	5260 - 5320 MHz	0.17	0.24	N/A
NII	U-NII-2C	5500 - 5720 MHz	0.21	0.19	N/A
NII	U-NII-3	5745 - 5825 MHz	0.22	0.21	0.38
DSS/DTS	Bluetooth	2402 - 2480 MHz	0.64	< 0.1	0.12
Simultaneous SAR per KDB 690783 D01v01r03:			1.42	1.48	1.56

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sar tick@mmfai.info.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 1 of 107	

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	14
3	INTRODUCTION	15
4	DOSIMETRIC ASSESSMENT	16
5	DEFINITION OF REFERENCE POINTS	17
6	TEST CONFIGURATION POSITIONS	18
7	RF EXPOSURE LIMITS	21
8	FCC MEASUREMENT PROCEDURES.....	22
9	RF CONDUCTED POWERS.....	28
10	SYSTEM VERIFICATION.....	68
11	SAR DATA SUMMARY	72
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	89
13	SAR MEASUREMENT VARIABILITY	100
14	ADDITIONAL TESTING PER FCC GUIDANCE	101
15	EQUIPMENT LIST	103
16	MEASUREMENT UNCERTAINTIES.....	104
17	CONCLUSION.....	105
18	REFERENCES	106
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: CONDUCTED POWERS FOR 4X4 DL MIMO		
APPENDIX H: POWER REDUCTION VERIFICATION		

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 2 of 107

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 17	Data	706.5 - 713.5 MHz
LTE Band 13	Data	779.5 - 784.5 MHz
LTE Band 26 (Cell)	Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
LTE Band 7	Data	2502.5 - 2567.5 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
LTE Band 38	Data	2572.5 - 2617.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2472 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz
MST	Data	555 Hz - 8.33 kHz

1.2 Power Reduction for SAR

This device utilizes a single step power reduction mechanism for SAR compliance under portable hotspot conditions for some wireless modes and bands. All hotspot SAR evaluations for this device were performed at the maximum allowed output power when hotspot is enabled. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 3 of 107

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

A. Maximum PCE Targets

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.5	33.5	32.2	30.0	28.7	27.0	25.0	23.7	22.5
	Nominal	33.0	33.0	31.7	29.5	28.2	26.5	24.5	23.2	22.0
GSM/GPRS/EDGE 1900	Maximum	30.5	30.5	27.6	25.9	23.9	26.0	23.7	22.5	20.8
	Nominal	30.0	30.0	27.1	25.4	23.4	25.5	23.2	22.0	20.3

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	25.0	24.0	24.0	23.5
	Nominal	24.5	23.5	23.5	23.0
UMTS Band 4 (1750 MHz)	Maximum	23.5	23.5	23.5	23.5
	Nominal	23.0	23.0	23.0	23.0
UMTS Band 2 (1900 MHz)	Maximum	23.5	22.5	22.5	22.5
	Nominal	23.0	22.0	22.0	22.0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 4 of 107

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	23.5
	Nominal	23.0
LTE Band 17	Maximum	23.5
	Nominal	23.0
LTE Band 13	Maximum	23.5
	Nominal	23.0
LTE Band 26 (Cell)	Maximum	23.5
	Nominal	23.0
LTE Band 5 (Cell)	Maximum	24.5
	Nominal	24.0
LTE Band 66 (AWS)	Maximum	24.0
	Nominal	23.5
LTE Band 4 (AWS)	Maximum	24.0
	Nominal	23.5
LTE Band 25 (PCS)	Maximum	23.5
	Nominal	23.0
LTE Band 2 (PCS)	Maximum	23.5
	Nominal	23.0
LTE Band 7	Maximum	24.5
	Nominal	24.0
LTE Band 41	Maximum	23.5
	Nominal	23.0
LTE Band 38	Maximum	23.5
	Nominal	23.0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 5 of 107

B. Reduced PCE Targets

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC- HSDPA
UMTS Band 4 (1750 MHz)	Maximum	22.0	22.0	20.0	22.0
	Nominal	21.5	21.5	19.5	21.5
UMTS Band 2 (1900 MHz)	Maximum	21.0	21.0	20.5	21.0
	Nominal	20.5	20.5	20.0	20.5

Mode / Band		Modulated Average (dBm)
LTE Band 66 (AWS)	Maximum	21.0
	Nominal	20.5
LTE Band 4 (AWS)	Maximum	21.0
	Nominal	20.5
LTE Band 25 (PCS)	Maximum	20.5
	Nominal	20.0
LTE Band 2 (PCS)	Maximum	20.5
	Nominal	20.0
LTE Band 7	Maximum	21.5
	Nominal	21.0

C. Maximum Bluetooth and SISO and MIMO WLAN Targets

Mode / Band		Modulated Average (dBm)				
		Ch. 1	Ch. 2-10	Ch. 11	Ch. 12	Ch. 13
IEEE 802.11b (2.4 GHz)	Maximum	18.5			10.5	6.5
	Nominal	18.0			10.0	6.0
IEEE 802.11g (2.4 GHz)	Maximum	14.5	17.5	15.5	10.5	6.5
	Nominal	14.0	17.0	15.0	10.0	6.0
IEEE 802.11n (2.4 GHz)	Maximum	14.5	17.5	15.5	10.5	6.5
	Nominal	14.0	17.0	15.0	10.0	6.0

FCC ID: A3LSMG960F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	
		Page 6 of 107	

Mode / Band		Modulated Average - Single Tx Chain (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	17.5		
	Nominal	17.0		
IEEE 802.11n (5 GHz)	Maximum	17.5		
	Nominal	17.0		
IEEE 802.11ac (5 GHz)	Maximum	17.5	16.5	15.5
	Nominal	17.0	16.0	15.0

Mode / Band		Modulated Average - MIMO (dBm)				
		Ch. 1	Ch. 2-10	Ch. 11	Ch. 12	Ch. 13
IEEE 802.11g (2.4 GHz)	Maximum	17.5	20.5	18.5	13.5	9.5
	Nominal	17.0	20.0	18.0	13.0	9.0
IEEE 802.11n (2.4 GHz)	Maximum	17.5	20.5	18.5	13.5	9.5
	Nominal	17.0	20.0	18.0	13.0	9.0

Mode / Band		Modulated Average - MIMO (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	20.5		
	Nominal	20.0		
IEEE 802.11n (5 GHz)	Maximum	20.5		
	Nominal	20.0		
IEEE 802.11ac (5 GHz)	Maximum	20.5	19.5	18.5
	Nominal	20.0	19.0	18.0

Mode / Band		Modulated Average - Single Tx Chain (dBm)
Bluetooth	Maximum	15.0
	Nominal	14.5
Bluetooth LE	Maximum	9.5
	Nominal	9.0
Bluetooth EDR	Maximum	6.5
	Nominal	6.0

FCC ID: A3LSMG960F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 7 of 107

D. Reduced SISO and MIMO WLAN Targets

Mode / Band		Modulated Average - Single Tx Chain (dBm)				
		Ch. 1	Ch. 2-10	Ch. 11	Ch. 12	Ch. 13
IEEE 802.11b (2.4 GHz)	Maximum	16.5			10.5	6.5
	Nominal	16.0			10.0	6.0
IEEE 802.11g (2.4 GHz)	Maximum	14.5	16.5	15.5	10.5	6.5
	Nominal	14.0	16.0	15.0	10.0	6.0
IEEE 802.11n (2.4 GHz)	Maximum	14.5	16.5	15.5	10.5	6.5
	Nominal	14.0	16.0	15.0	10.0	6.0

Mode / Band		Modulated Average - Single Tx Chain (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	13.5		
	Nominal	13.0		
IEEE 802.11n (5 GHz)	Maximum	13.5	13.5	
	Nominal	13.0	13.0	
IEEE 802.11ac (5 GHz)	Maximum	13.5	13.5	13.5
	Nominal	13.0	13.0	13.0

Mode / Band		Modulated Average - MIMO (dBm)				
		Ch. 1	Ch. 2-10	Ch. 11	Ch. 12	Ch. 13
IEEE 802.11g (2.4 GHz)	Maximum	17.5	19.5	18.5	13.5	9.5
	Nominal	17.0	19.0	18.0	13.0	9.0
IEEE 802.11n (2.4 GHz)	Maximum	17.5	19.5	18.5	13.5	9.5
	Nominal	17.0	19.0	18.0	13.0	9.0

Mode / Band		Modulated Average - MIMO (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	16.5		
	Nominal	16.0		
IEEE 802.11n (5 GHz)	Maximum	16.5	16.5	
	Nominal	16.0	16.0	
IEEE 802.11ac (5 GHz)	Maximum	16.5	16.5	16.5
	Nominal	16.0	16.0	16.0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 8 of 107

E. Maximum Powers During Conditions with Simultaneous 2.4 GHz and 5 GHz WLAN

	# Tx	5 GHz WiFi [dBm]		2.4 GHz WiFi [dBm]		802.11 Modes
		Ant1	Ant2	Ant1	Ant2	
2.4 GHz + 5 GHz	2	A	-	-	B	2.4 GHz: b,g,n 5 GHz: a,n,ac
	2	-	A	B	-	
	2	A	-	B	-	
	2	-	A	-	B	
	3	A	A	B	-	2.4 GHz: b, g, n 5 GHz: n, ac, a (CDD + STBC only)
	3	A	A	-	B	
	3	A	-	B	B	2.4 GHz: n, g (CDD + STBC only) 5 GHz: a, n, ac
	3	-	A	B	B	
	4	A	A	B	B	2.4 GHz: n, g (CDD + STBC only) 5 GHz: n, ac, a (CDD + STBC only)

A = 13 dBm

B = 13 dBm

2.4 GHz WLAN Channel 12 will operate with a Single Tx target power of 10 dBm.

2.4 GHz WLAN Channel 13 will operate with a Single Tx target power of 6 dBm.

(Upper tolerance: target + 0.5 dB)

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 9 of 107

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is ≤160 mm and the diagonal display is ≤150 mm. A diagram showing the location of the device antennas can be found in Appendix F.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 66 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 7	Yes	Yes	No	Yes	Yes	Yes
LTE Band 41	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
2.4 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes
Bluetooth	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled. Therefore, U-NII-1, U-NII-2A, U-NII-2C operations are not considered in this section.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 10 of 107

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	
2	GSM voice + 5 GHz Wi-Fi	Yes	Yes	N/A	
3	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	^ Bluetooth Tethering is considered
4	GSM voice + 2.4 GHz Wi-Fi MIMO	Yes	Yes	N/A	
5	GSM voice + 5 GHz Wi-Fi MIMO	Yes	Yes	N/A	
6	GSM voice + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	Yes	Yes	N/A	
7	GSM voice + 2.4 GHz Wi-Fi MIMO + 5 GHz Wi-Fi MIMO	Yes	Yes	N/A	
8	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
9	UMTS + 5 GHz Wi-Fi	Yes	Yes	Yes	
10	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	^ Bluetooth Tethering is considered
11	UMTS + 2.4 GHz Wi-Fi MIMO	Yes	Yes	Yes	
12	UMTS + 5 GHz Wi-Fi MIMO	Yes	Yes	Yes	
13	UMTS + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	Yes	Yes	Yes	
14	UMTS + 2.4 GHz Wi-Fi MIMO + 5 GHz Wi-Fi MIMO	Yes	Yes	Yes	
15	LTE + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
16	LTE + 5 GHz Wi-Fi	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
17	LTE + 2.4 GHz Bluetooth	Yes*	Yes*	Yes^	^ Bluetooth Tethering is considered * Pre-installed VOIP applications are considered
18	LTE + 2.4 GHz Wi-Fi MIMO	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
19	LTE + 5 GHz Wi-Fi MIMO	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
20	LTE + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
21	LTE + 2.4 GHz Wi-Fi MIMO + 5 GHz Wi-Fi MIMO	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
22	GPRS/EDGE + 2.4 GHz Wi-Fi	N/A	N/A	Yes	
23	GPRS/EDGE + 5 GHz Wi-Fi	N/A	N/A	Yes	
24	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	N/A	Yes^	^ Bluetooth Tethering is considered
25	GPRS/EDGE + 2.4 GHz Wi-Fi MIMO	N/A	N/A	Yes	
26	GPRS/EDGE + 5 GHz Wi-Fi MIMO	N/A	N/A	Yes	
27	GPRS/EDGE + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	N/A	N/A	Yes	
28	GPRS/EDGE + 2.4 GHz Wi-Fi MIMO + 5 GHz Wi-Fi MIMO	N/A	N/A	Yes	

1. Bluetooth and WLAN cannot transmit simultaneously.
2. All licensed modes share the same antenna path and cannot transmit simultaneously.
3. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
4. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
5. 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
6. This device supports 2x2 MIMO Tx for WLAN. 802.11a/g/n/ac supports CDD and STBC and 802.11n/ac additionally supports SDM.
7. This device supports Bluetooth tethering.
8. This device supports VoWIFI.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 11 of 107

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

This device supports channel 1-13 for 2.4 GHz WLAN. However, due to the reduced output power for channels 12 and 13, channels 1, 6, and 11 were considered for SAR testing per KDB 248227 D01v02r02.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports 64QAM on the uplink and 256QAM on the downlink for LTE Operations. Conducted powers for 64QAM uplink configurations were measured per Section 5.1 of FCC KDB Publication 941225 D05v02r05. SAR was not required for 64QAM since the highest maximum output power for 64 QAM is $\leq \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg, per Section 5.2.4 of FCC KDB Publication 941225 D05v02r05.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

This device supports downlink 4x4 MIMO operations for some LTE Bands. Per May 2017 TBC Workshop Notes, SAR for downlink 4x4 MIMO was not needed since the maximum average output power in 4x4 downlink MIMO mode was not > 0.25 dB higher than the maximum output power with downlink 4x4 MIMO inactive.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 12 of 107

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- May 2017 TCB Workshop Notes (LTE 4x4 Downlink MIMO)
- Fall 2017 TCB Workshop Notes (LTE Carrier Aggregation)

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 13 of 107

LTE Information					
FCC ID	A3LSMG960F				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 17 (706.5 - 713.5 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 7 (2502.5 - 2567.5 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
	LTE Band 38 (2572.5 - 2617.5 MHz)				
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 17: 5 MHz, 10 MHz				
Channel Bandwidths	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 38: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)	715.3 (23173)	
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)	714.5 (23165)	
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)	713.5 (23155)	
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)	711 (23130)	
LTE Band 17: 5 MHz	706.5 (23755)		710 (23790)	713.5 (23825)	
LTE Band 17: 10 MHz	709 (23780)		710 (23790)	711 (23800)	
LTE Band 13: 5 MHz	779.5 (23205)		782 (23230)	784.5 (23255)	
LTE Band 13: 10 MHz	N/A		782 (23230)	N/A	
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)		831.5 (26865)	848.3 (27033)	
LTE Band 26 (Cell): 3 MHz	815.5 (26705)		831.5 (26865)	847.5 (27025)	
LTE Band 26 (Cell): 5 MHz	816.5 (26715)		831.5 (26865)	846.5 (27015)	
LTE Band 26 (Cell): 10 MHz	819 (26740)		831.5 (26865)	844 (26990)	
LTE Band 26 (Cell): 15 MHz	821.5 (26765)		831.5 (26865)	841.5 (26965)	
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)	848.3 (20643)	
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)	847.5 (20635)	
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)	846.5 (20625)	
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)	844 (20600)	
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)		1745 (132322)	1779.3 (132665)	
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)		1745 (132322)	1778.5 (132657)	
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)		1745 (132322)	1777.5 (132647)	
LTE Band 66 (AWS): 10 MHz	1715 (132022)		1745 (132322)	1775 (132622)	
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)		1745 (132322)	1772.5 (132597)	
LTE Band 66 (AWS): 20 MHz	1720 (132072)		1745 (132322)	1770 (132572)	
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)	1754.3 (20393)	
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)	1753.5 (20385)	
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)	1752.5 (20375)	
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)	1750 (20350)	
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)	1747.5 (20325)	
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)	1745 (20300)	
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)	1914.3 (26683)	
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)	1913.5 (26675)	
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)	1912.5 (26665)	
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)	1910 (26640)	
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)	1907.5 (26615)	
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)	1905 (26590)	
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)	1909.3 (19193)	
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)	1908.5 (19185)	
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)	1907.5 (19175)	
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)	1905 (19150)	
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)	1902.5 (19125)	
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)	1900 (19100)	
LTE Band 7: 5 MHz	2502.5 (20775)		2535 (21100)	2567.5 (21425)	
LTE Band 7: 10 MHz	2505 (20800)		2535 (21100)	2565 (21400)	
LTE Band 7: 15 MHz	2507.5 (20825)		2535 (21100)	2562.5 (21375)	
LTE Band 7: 20 MHz	2510 (20850)		2535 (21100)	2560 (21350)	
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 38: 5 MHz			2572.5 (37775)	2595 (38000)	2617.5 (38225)
LTE Band 38: 10 MHz			2575 (37800)	2595 (38000)	2615 (38200)
LTE Band 38: 15 MHz			2577.5 (37825)	2595 (38000)	2612.5 (38175)
LTE Band 38: 20 MHz			2580 (37850)	2595 (38000)	2610 (38150)
UE Category	DL UE CAT 16 (QPSK, 16QAM, 64QAM, 256QAM), UL UE Cat 5 (QPSK, 16QAM, 64QAM)				
Modulations Supported in UL	QPSK, 16QAM, 64QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations				
LTE Additional Information	This device does not support full CA features on 3GPP Release 13. It supports carrier aggregation feature as shown in Section 9. All other uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC unless otherwise specified. The following LTE Release 13 Features are not supported: Relay, HetNet, Enhanced MIMO, eCIC, WiFi Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: A3LSMG960F		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 14 of 107		

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 15 of 107

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMG960F		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset			Page 16 of 107

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 17 of 107

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.



Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 18 of 107




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 19 of 107

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1g body and 10g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 20 of 107

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 21 of 107

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 22 of 107

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.4.6 SAR Measurement Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 23 of 107

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.5.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 24 of 107

carrier aggregation is inactive on the PCC. For every supported combination of downlink only carrier aggregation, additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 25 of 107

positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.6.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6).

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 26 of 107

8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

8.6.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is <1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 27 of 107

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

Table 9-1
Maximum Conducted Power

Maximum Burst-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	33.14	33.06	31.21	29.84	28.69	26.97	24.95	23.70	22.49
	190	33.18	33.10	31.07	29.74	28.67	26.92	24.68	23.56	22.01
	251	33.23	33.18	31.17	29.62	28.44	26.89	24.73	23.60	22.09
GSM 1900	512	29.22	29.18	26.75	23.95	22.78	25.24	23.28	21.54	20.35
	661	29.33	29.45	27.03	24.14	22.96	25.23	23.24	21.50	20.26
	810	29.84	29.82	27.53	24.54	23.50	25.77	23.62	22.14	20.80

Calculated Maximum Frame-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	24.11	24.03	25.19	25.58	25.68	17.94	18.93	19.44	19.48
	190	24.15	24.07	25.05	25.48	25.66	17.89	18.66	19.30	19.00
	251	24.20	24.15	25.15	25.36	25.43	17.86	18.71	19.34	19.08
GSM 1900	512	20.19	20.15	20.73	19.69	19.77	16.21	17.26	17.28	17.34
	661	20.30	20.42	21.01	19.88	19.95	16.20	17.22	17.24	17.25
	810	20.81	20.79	21.51	20.28	20.49	16.74	17.60	17.88	17.79

GSM 850	Frame Avg.Targets:	23.97	23.97	25.68	25.24	25.19	17.47	18.48	18.94	18.99
GSM 1900		20.97	20.97	21.08	21.14	20.39	16.47	17.18	17.74	17.29

FCC ID: A3LSMG960F			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset			Page 28 of 107

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.




Figure 9-1
Power Measurement Setup

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 29 of 107

9.2 UMTS Conducted Powers

Table 9-2
Maximum Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	24.33	24.12	24.11	23.24	23.25	23.15	22.42	22.17	22.91	-
99		12.2 kbps AMR	24.33	24.18	24.11	23.15	23.27	23.19	22.41	22.19	22.91	-
6	HSDPA	Subtest 1	23.19	23.04	23.08	22.89	22.88	22.91	22.12	21.90	22.50	0
6		Subtest 2	22.43	22.29	22.34	22.84	22.90	22.91	21.55	21.62	22.04	0
6		Subtest 3	22.21	21.97	22.10	21.88	21.96	21.93	21.16	21.00	21.30	0.5
6		Subtest 4	21.52	21.53	21.63	21.82	21.96	21.91	20.04	20.00	20.57	0.5
6	HSUPA	Subtest 1	23.20	23.03	23.09	21.69	21.80	21.82	21.32	21.10	21.50	0
6		Subtest 2	21.15	20.96	21.05	19.52	19.72	19.68	20.36	20.21	20.50	2
6		Subtest 3	22.07	21.90	22.00	21.15	20.50	21.32	21.50	21.30	21.48	1
6		Subtest 4	21.13	20.96	21.05	19.52	19.72	19.70	20.44	20.22	20.49	2
6		Subtest 5	24.00	23.99	23.88	22.12	22.38	22.21	22.42	22.26	22.50	0
8	DC-HSDPA	Subtest 1	23.14	23.15	23.02	23.50	23.44	23.27	22.46	22.47	22.48	0
8		Subtest 2	22.62	22.36	22.41	23.44	23.38	23.17	21.72	21.68	22.13	0
8		Subtest 3	21.86	21.80	21.89	22.53	22.71	22.79	21.25	21.68	21.30	0.5
8		Subtest 4	21.22	21.22	21.20	22.51	22.61	22.62	20.43	20.26	20.93	0.5

Table 9-3
Reduced Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	21.27	21.38	21.44	20.53	20.45	20.96	-
99		12.2 kbps AMR	21.30	21.42	21.44	20.62	20.39	20.98	-
6	HSDPA	Subtest 1	21.32	21.39	21.40	20.51	20.36	20.99	0
6		Subtest 2	21.35	21.42	21.47	20.65	20.46	21.00	0
6		Subtest 3	21.41	21.49	21.51	20.55	20.49	21.00	0.5
6		Subtest 4	21.43	21.53	21.56	20.71	20.50	20.98	0.5
6	HSUPA	Subtest 1	18.17	18.36	18.38	19.89	19.68	20.23	0
6		Subtest 2	18.18	18.37	18.40	18.82	19.20	19.13	2
6		Subtest 3	18.17	18.37	18.39	18.69	18.89	19.24	1
6		Subtest 4	18.21	18.36	18.40	19.64	19.93	20.29	2
6		Subtest 5	19.15	19.49	19.48	19.66	19.91	20.28	0
8	DC-HSDPA	Subtest 1	21.25	21.45	21.42	20.58	20.46	20.94	0
8		Subtest 2	21.14	21.41	21.38	20.47	20.41	20.89	0
8		Subtest 3	21.21	21.42	21.43	20.52	20.40	20.91	0.5
8		Subtest 4	21.17	21.41	21.42	20.48	20.43	20.94	0.5

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 30 of 107

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.



Figure 9-2
Power Measurement Setup

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 31 of 107

9.3 LTE Conducted Powers

9.3.1 LTE Band 12

Table 9-4
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.68	0	0
	1	25	22.75		0
	1	49	22.94		0
	25	0	21.81	0-1	1
	25	12	21.89		1
	25	25	21.90		1
	50	0	21.88		1
16QAM	1	0	21.89	0-1	1
	1	25	21.95		1
	1	49	22.06		1
	25	0	20.84	0-2	2
	25	12	20.87		2
	25	25	20.90		2
	50	0	20.86		2
64QAM	1	0	20.91	0-2	2
	1	25	20.98		2
	1	49	20.92		2
	25	0	19.79	0-3	3
	25	12	19.85		3
	25	25	19.89		3
	50	0	19.94		3

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 32 of 107

Table 9-5
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.82	22.71	22.77	0	0
	1	12	22.81	22.68	22.80		0
	1	24	23.03	22.88	22.95		0
	12	0	21.97	21.87	21.79	0-1	1
	12	6	21.92	21.81	21.75		1
	12	13	21.95	21.89	21.78		1
	25	0	21.94	21.83	21.78		1
16QAM	1	0	22.12	22.07	22.08	0-1	1
	1	12	21.77	22.17	22.14		1
	1	24	22.10	22.22	22.25		1
	12	0	20.89	20.91	20.88	0-2	2
	12	6	20.85	20.83	20.82		2
	12	13	20.91	20.86	20.87		2
	25	0	20.93	20.81	20.75		2
64QAM	1	0	20.88	20.64	20.49	0-2	2
	1	12	20.86	20.63	20.30		2
	1	24	21.00	20.61	20.58		2
	12	0	19.81	19.74	19.70	0-3	3
	12	6	19.82	19.73	19.63		3
	12	13	19.77	19.72	19.61		3
	25	0	19.83	19.76	19.69		3

Table 9-6
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.05	22.82	22.89	0	0
	1	7	22.96	22.89	22.99		0
	1	14	23.15	22.96	23.03		0
	8	0	21.94	21.91	21.75	0-1	1
	8	4	21.98	21.81	21.63		1
	8	7	21.96	21.94	21.74		1
	15	0	21.94	21.84	21.71		1
16QAM	1	0	22.18	22.16	22.09	0-1	1
	1	7	22.36	22.18	21.78		1
	1	14	22.27	22.22	21.91		1
	8	0	20.87	20.92	20.79	0-2	2
	8	4	20.83	20.88	20.75		2
	8	7	20.86	20.90	20.72		2
	15	0	20.95	20.87	20.74		2
64QAM	1	0	20.90	20.73	20.86	0-2	2
	1	7	20.74	20.64	20.62		2
	1	14	20.85	20.81	20.79		2
	8	0	19.85	19.67	19.71	0-3	3
	8	4	19.80	19.67	19.65		3
	8	7	19.78	19.71	19.70		3
	15	0	19.80	19.65	19.64		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 33 of 107	

Table 9-7
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.87	23.11	22.81	0	0
	1	2	22.54	23.01	22.72		0
	1	5	22.75	23.04	22.71		0
	3	0	22.62	22.82	22.69		0
	3	2	22.71	22.84	22.68		0
	3	3	22.72	22.86	22.59	0	
	6	0	21.84	21.83	21.74	0-1	1
16QAM	1	0	21.96	21.94	22.09	0-1	1
	1	2	21.94	21.61	21.88		1
	1	5	21.85	21.80	21.98		1
	3	0	21.82	21.72	21.64		1
	3	2	21.71	21.60	21.61		1
	3	3	21.79	21.68	21.63	1	
	6	0	20.62	20.79	20.72	0-2	2
64QAM	1	0	20.77	20.76	20.45	0-2	2
	1	2	20.65	20.75	20.73		2
	1	5	20.70	20.85	20.78		2
	3	0	20.77	20.77	20.61		2
	3	2	20.65	20.78	20.63		2
	3	3	20.57	20.63	20.57	2	
	6	0	19.66	19.73	19.66	0-3	3

9.3.2 LTE Band 13

Table 9-8
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.56	0	0
	1	25	22.53		0
	1	49	22.59		0
	25	0	21.58	0-1	1
	25	12	21.66		1
	25	25	21.69		1
16QAM	50	0	21.65	0-1	1
	1	0	21.89		1
	1	25	21.82		1
	1	49	21.94	0-2	1
	25	0	20.60		2
	25	12	20.63		2
64QAM	25	25	20.68	0-2	2
	50	0	20.64		2
	1	0	20.71	0-2	2
	1	25	20.67		2
	1	49	20.55		2
	25	0	19.50	0-3	3
64QAM	25	12	19.55		3
	25	25	19.52		3
	50	0	19.63		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 34 of 107

Table 9-9
LTE Band 13 Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.53	0	0
	1	12	22.58		0
	1	24	22.72		0
	12	0	21.67	0-1	1
	12	6	21.66		1
	12	13	21.69		1
	25	0	21.64		1
16QAM	1	0	21.89	0-1	1
	1	12	21.92		1
	1	24	22.00		1
	12	0	20.63	0-2	2
	12	6	20.58		2
	12	13	20.62		2
	25	0	20.68		2
64QAM	1	0	20.68	0-2	2
	1	12	20.54		2
	1	24	20.73		2
	12	0	19.65	0-3	3
	12	6	19.58		3
	12	13	19.55		3
	25	0	19.56		3

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 35 of 107	

9.3.3

LTE Band 26 (Cell)

Table 9-10
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26865 (831.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.70	0	0
	1	36	22.80		0
	1	74	22.79		0
	36	0	21.80	0-1	1
	36	18	21.83		1
	36	37	21.80		1
	75	0	21.82		1
16QAM	1	0	21.76	0-1	1
	1	36	21.75		1
	1	74	21.79		1
	36	0	20.77	0-2	2
	36	18	20.83		2
	36	37	20.68		2
	75	0	20.72		2
64QAM	1	0	20.97	0-2	2
	1	36	21.03		2
	1	74	21.01		2
	36	0	19.77	0-3	3
	36	18	19.85		3
	36	37	19.79		3
	75	0	19.80		3

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 36 of 107

Table 9-11
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.64	22.71	22.73	0	0
	1	25	22.73	22.83	22.82		0
	1	49	22.78	22.85	22.78		0
	25	0	21.69	21.76	21.60	0-1	1
	25	12	21.74	21.81	21.83		1
	25	25	21.73	21.82	21.83		1
16QAM	50	0	21.75	21.86	21.67	0-1	1
	1	0	21.84	21.95	21.78		1
	1	25	21.68	22.07	22.00		1
	1	49	21.89	22.04	22.12	0-2	1
	25	0	20.69	20.78	20.78		2
	25	12	20.72	20.74	20.82		2
64QAM	25	25	20.70	20.78	20.80	0-2	2
	50	0	20.76	20.77	20.81		2
	1	0	20.98	21.04	20.93		2
	1	25	20.64	21.08	21.05	0-2	2
	1	49	20.66	21.03	20.86		2
	25	0	19.65	19.81	19.82		0-3
25	12	19.64	19.82	19.84	3		
25	25	19.64	19.77	19.68	3		
50	0	19.74	19.88	19.88		3	

Table 9-12
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.53	22.69	22.75	0	0
	1	12	22.31	22.48	22.43		0
	1	24	22.53	22.79	22.72		0
	12	0	21.70	21.78	21.89	0-1	1
	12	6	21.70	21.87	21.90		1
	12	13	21.66	21.86	21.85		1
	25	0	21.66	21.84	21.84		1
16QAM	1	0	21.83	21.89	21.83	0-1	1
	1	12	21.72	21.78	21.77		1
	1	24	21.68	21.97	21.93		1
	12	0	20.71	20.93	20.91	0-2	2
	12	6	20.66	20.87	20.87		2
	12	13	20.63	20.81	20.86		2
	25	0	20.66	20.81	20.79		2
64QAM	1	0	20.54	20.93	20.84	0-2	2
	1	12	20.35	20.84	20.83		2
	1	24	20.66	20.95	21.01		2
	12	0	19.73	19.85	19.96	0-3	3
	12	6	19.70	19.84	19.93		3
	12	13	19.66	19.81	19.88		3
	25	0	19.66	19.90	19.93		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 37 of 107

Table 9-13
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.66	22.80	22.74	0	0
	1	7	22.36	22.53	22.41		0
	1	14	22.63	22.82	22.71		0
	8	0	21.67	21.87	21.78	0-1	1
	8	4	21.69	21.85	21.79		1
	8	7	21.67	21.84	21.76		1
	15	0	21.68	21.82	21.76		1
16QAM	1	0	21.73	22.05	21.86	0-1	1
	1	7	21.54	21.88	21.67		1
	1	14	21.82	21.97	21.78		1
	8	0	20.74	20.90	20.77	0-2	2
	8	4	20.68	20.92	20.82		2
	8	7	20.73	20.91	20.86		2
	15	0	20.31	20.79	20.77		2
64QAM	1	0	20.99	21.08	20.55	0-2	2
	1	7	20.60	20.72	20.22		2
	1	14	20.82	20.95	20.47		2
	8	0	19.76	19.93	19.83	0-3	3
	8	4	19.69	19.85	19.78		3
	8	7	19.71	19.93	19.79		3
	15	0	19.70	19.85	19.72		3

Table 9-14
LTE Band 26 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.48	22.85	22.73	0	0
	1	2	22.40	22.73	22.56		0
	1	5	22.46	22.68	22.63		0
	3	0	22.54	22.83	22.72		0
	3	2	22.55	22.84	22.74		0
	3	3	22.40	22.82	22.72		0
	6	0	21.45	21.84	21.69	0-1	1
16QAM	1	0	21.44	21.67	22.04	0-1	1
	1	2	21.36	21.88	21.77		1
	1	5	21.63	22.08	21.91		1
	3	0	21.63	21.86	21.85		1
	3	2	21.62	21.90	21.85		1
	3	3	21.55	21.83	21.69		1
	6	0	20.65	20.84	20.76	0-2	2
64QAM	1	0	20.54	20.87	20.93	0-2	2
	1	2	20.36	20.82	20.64		2
	1	5	20.53	21.12	20.82		2
	3	0	20.66	20.96	20.71		2
	3	2	20.79	20.91	20.65		2
	3	3	20.65	20.90	20.64		2
	6	0	19.53	19.75	19.77	0-3	3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 38 of 107	

9.3.4

LTE Band 5 (Cell)

Table 9-15
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.74	0	0
	1	25	23.76		0
	1	49	23.73		0
	25	0	22.77	0-1	1
	25	12	22.83		1
	25	25	22.81		1
	50	0	22.82		1
16QAM	1	0	23.18	0-1	1
	1	25	23.20		1
	1	49	23.15		1
	25	0	21.77	0-2	2
	25	12	21.84		2
	25	25	21.81		2
	50	0	21.90		2
64QAM	1	0	21.90	0-2	2
	1	25	21.88		2
	1	49	22.06		2
	25	0	20.75	0-3	3
	25	12	20.79		3
	25	25	20.78		3
	50	0	20.83		3

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 39 of 107

Table 9-16
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.89	23.64	23.87	0	0
	1	12	23.95	23.73	23.84		0
	1	24	24.08	23.78	24.00		0
	12	0	23.03	22.86	22.87	0-1	1
	12	6	23.01	22.81	22.81		1
	12	13	23.00	22.83	22.83		1
	25	0	22.98	22.81	22.85		1
16QAM	1	0	23.08	22.79	23.03	0-1	1
	1	12	22.91	22.60	22.80		1
	1	24	23.29	22.99	23.18		1
	12	0	21.99	21.83	21.91	0-2	2
	12	6	21.92	21.78	21.87		2
	12	13	21.97	21.80	21.89		2
	25	0	22.01	21.85	21.83		2
64QAM	1	0	21.83	21.58	21.60	0-2	2
	1	12	21.74	21.62	21.39		2
	1	24	21.98	21.78	21.45		2
	12	0	20.86	20.73	20.66	0-3	3
	12	6	20.87	20.72	20.63		3
	12	13	20.84	20.67	20.71		3
	25	0	20.79	20.68	20.75		3

Table 9-17
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.99	23.79	23.88	0	0
	1	7	23.66	23.65	23.88		0
	1	14	23.86	23.83	23.99		0
	8	0	23.02	22.78	22.90	0-1	1
	8	4	22.93	22.79	22.91		1
	8	7	22.99	22.88	22.88		1
	15	0	22.95	22.82	22.90		1
16QAM	1	0	23.37	22.97	23.04	0-1	1
	1	7	23.32	22.81	22.89		1
	1	14	23.28	23.09	23.07		1
	8	0	21.97	21.83	21.82	0-2	2
	8	4	22.02	21.86	21.86		2
	8	7	22.01	21.84	21.81		2
	15	0	21.91	21.86	21.87		2
64QAM	1	0	21.60	21.85	21.85	0-2	2
	1	7	21.61	21.76	21.64		2
	1	14	21.69	21.84	21.72		2
	8	0	20.58	20.66	20.76	0-3	3
	8	4	20.80	20.67	20.77		3
	8	7	20.78	20.68	20.77		3
	15	0	20.83	20.63	20.63		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 40 of 107	

Table 9-18
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.86	23.94	23.98	0	0
	1	2	23.64	23.63	23.83		0
	1	5	23.77	23.82	23.86		0
	3	0	23.55	23.65	23.88		0
	3	2	23.50	23.59	23.90		0
	3	3	23.58	23.81	23.81		0
	6	0	22.62	22.88	22.92	0-1	1
16QAM	1	0	22.97	23.09	23.19	0-1	1
	1	2	22.65	23.13	22.92		1
	1	5	22.81	23.06	23.06		1
	3	0	22.63	22.99	22.88		1
	3	2	22.43	22.78	22.69		1
	3	3	22.65	22.97	22.89		1
	6	0	21.63	21.83	22.01	0-2	2
64QAM	1	0	21.46	21.78	22.00	0-2	2
	1	2	21.31	21.74	21.49		2
	1	5	21.42	21.81	21.59		2
	3	0	21.59	21.72	21.82		2
	3	2	21.63	21.72	21.73		2
	3	3	21.54	21.67	21.64		2
	6	0	20.46	20.73	20.73	0-3	3

9.3.5 LTE Band 66 (AWS)

Table 9-19
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.64	23.39	23.44	0	0
	1	50	22.96	23.12	23.50		0
	1	99	23.70	23.58	23.61		0
	50	0	22.54	22.49	22.46	0-1	1
	50	25	22.64	22.55	22.54		1
	50	50	22.58	22.58	22.51		1
16QAM	100	0	22.63	22.63	22.59	0-1	1
	1	0	22.78	22.59	22.74		1
	1	50	22.85	22.78	22.81		1
	1	99	22.82	22.92	22.91	0-2	1
	50	0	21.57	21.47	21.48		2
	50	25	21.64	21.57	21.53		2
64QAM	50	50	21.58	21.59	21.49	0-2	2
	100	0	21.63	21.62	21.58		2
	1	0	21.63	21.44	21.61		0-2
	1	50	21.68	21.52	21.50	2	
	1	99	21.59	21.61	21.38	2	
	50	0	20.38	20.33	20.26	0-3	3
50	25	20.48	20.44	20.31	3		
50	50	20.42	20.38	20.29	3		
64QAM	100	0	20.46	20.42	20.34		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 41 of 107	

Table 9-20
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.29	23.42	23.35	0	0
	1	36	23.40	23.55	23.38		0
	1	74	23.43	23.60	23.31		0
	36	0	22.49	22.45	22.44	0-1	1
	36	18	22.51	22.51	22.41		1
	36	37	22.47	22.53	22.48		1
	75	0	22.55	22.56	22.52		1
16QAM	1	0	22.52	22.41	22.50	0-1	1
	1	36	22.63	22.60	22.53		1
	1	74	22.66	22.72	22.60		1
	36	0	21.27	21.50	21.42	0-2	2
	36	18	21.35	21.45	21.47		2
	36	37	21.38	21.48	21.43		2
	75	0	21.41	21.50	21.46		2
64QAM	1	0	21.57	21.69	21.64	0-2	2
	1	36	21.56	21.82	21.71		2
	1	74	21.60	21.95	21.75		2
	36	0	20.33	20.48	20.44	0-3	3
	36	18	20.17	20.49	20.48		3
	36	37	20.21	20.52	20.39		3
	75	0	20.22	20.50	20.48		3

Table 9-21
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.34	23.41	23.24	0	0
	1	25	23.43	23.48	23.33		0
	1	49	23.44	23.52	23.28		0
	25	0	22.43	22.56	22.30	0-1	1
	25	12	22.44	22.51	22.36		1
	25	25	22.49	22.59	22.29		1
	50	0	22.53	22.60	22.38		1
16QAM	1	0	22.52	22.66	22.40	0-1	1
	1	25	22.60	22.53	22.43		1
	1	49	22.64	22.69	22.49		1
	25	0	21.49	21.42	21.31	0-2	2
	25	12	21.44	21.56	21.32		2
	25	25	21.50	21.53	21.29		2
	50	0	21.52	21.62	21.38		2
64QAM	1	0	21.55	21.58	21.39	0-2	2
	1	25	21.51	21.49	21.37		2
	1	49	21.42	21.66	21.53		2
	25	0	20.46	20.52	20.33	0-3	3
	25	12	20.53	20.57	20.31		3
	25	25	20.50	20.55	20.29		3
	50	0	20.51	20.59	20.33		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 42 of 107	

Table 9-22
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.41	23.52	23.41	0	0
	1	12	23.33	23.36	23.34		0
	1	24	23.44	23.54	23.49		0
	12	0	22.61	22.67	22.57	0-1	1
	12	6	22.66	22.66	22.48		1
	12	13	22.60	22.64	22.53		1
16QAM	25	0	22.66	22.57	22.56	0-1	1
	1	0	22.57	22.69	22.57		1
	1	12	22.49	22.58	22.63		1
	1	24	22.55	22.59	22.58	0-2	1
	12	0	21.58	21.66	21.56		2
	12	6	21.64	21.61	21.49		2
64QAM	12	13	21.60	21.66	21.46	0-2	2
	25	0	21.55	21.58	21.41		2
	1	0	21.59	21.67	21.61	0-2	2
	1	12	21.44	21.73	21.55		2
	1	24	21.48	21.77	21.63		2
	64QAM	12	0	20.64	20.68	20.54	0-3
12		6	20.56	20.64	20.61	3	
12		13	20.53	20.61	20.50	3	
25		0	20.60	20.69	20.53	3	

Table 9-23
LTE Band 66 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.45	23.54	23.36	0	0
	1	7	23.25	23.34	23.17		0
	1	14	23.44	23.54	23.32		0
	8	0	22.57	22.56	22.44	0-1	1
	8	4	22.49	22.52	22.38		1
	8	7	22.54	22.55	22.44		1
	15	0	22.49	22.48	22.39		1
16QAM	1	0	22.59	22.74	22.66	0-1	1
	1	7	22.58	22.86	22.57		1
	1	14	22.53	22.81	22.58		1
	8	0	21.47	21.52	21.47	0-2	2
	8	4	21.46	21.51	21.40		2
	8	7	21.48	21.53	21.38		2
	15	0	21.35	21.41	21.28		2
64QAM	1	0	21.76	21.64	21.55	0-2	2
	1	7	21.61	21.39	21.40		2
	1	14	21.43	21.47	21.54		2
	8	0	20.55	20.50	20.51	0-3	3
	8	4	20.53	20.49	20.48		3
	8	7	20.58	20.62	20.50		3
	15	0	20.49	20.49	20.40		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 43 of 107	

Table 9-24
LTE Band 66 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.06	23.50	23.45	0	0
	1	2	23.04	23.47	23.43		0
	1	5	22.98	23.46	23.36		0
	3	0	23.08	23.51	23.46		0
	3	2	23.09	23.52	23.51		0
	3	3	23.05	23.40	23.43		0
	6	0	21.98	22.40	22.42	0-1	1
16QAM	1	0	22.06	22.70	22.44	0-1	1
	1	2	21.98	22.62	22.51		1
	1	5	22.08	22.61	22.60		1
	3	0	22.07	22.46	22.55		1
	3	2	22.15	22.51	22.52		1
	3	3	22.26	22.63	22.40		1
	6	0	21.11	21.60	21.45	0-2	2
64QAM	1	0	21.18	21.30	21.50	0-2	2
	1	2	21.16	21.32	21.47		2
	1	5	21.21	21.24	21.54		2
	3	0	21.36	21.63	21.64		2
	3	2	21.12	21.49	21.59		2
	3	3	21.14	21.67	21.58		2
	6	0	20.25	20.57	20.65	0-3	3

Table 9-25
LTE Band 66 (AWS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.33	20.42	20.32	0	0
	1	50	20.43	20.53	20.34		0
	1	99	20.45	20.71	20.36		0
	50	0	20.37	20.61	20.39	0-1	0
	50	25	20.42	20.60	20.47		0
	50	50	20.37	20.65	20.40		0
	100	0	20.47	20.64	20.52		0
16QAM	1	0	20.43	20.61	20.53	0-1	0
	1	50	20.45	20.69	20.45		0
	1	99	20.62	20.83	20.53		0
	50	0	20.35	20.59	20.40	0-2	0
	50	25	20.46	20.61	20.45		0
	50	50	20.40	20.60	20.39		0
	100	0	20.43	20.65	20.49		0
64QAM	1	0	20.45	20.63	20.59	0-2	0
	1	50	20.51	20.64	20.40		0
	1	99	20.65	20.89	20.53		0
	50	0	20.37	20.51	20.36	0-3	0
	50	25	20.45	20.64	20.47		0
	50	50	20.38	20.60	20.37		0
	100	0	20.44	20.64	20.52		0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 44 of 107

Table 9-26
LTE Band 66 (AWS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.55	20.36	20.41	0	0
	1	36	20.54	20.47	20.46		0
	1	74	20.47	20.49	20.32		0
	36	0	20.40	20.54	20.49	0-1	0
	36	18	20.44	20.55	20.51		0
	36	37	20.39	20.52	20.48		0
	75	0	20.45	20.59	20.52		0
16QAM	1	0	20.56	20.69	20.43	0-1	0
	1	36	20.65	20.78	20.38		0
	1	74	20.66	20.81	20.29		0
	36	0	20.49	20.48	20.55	0-2	0
	36	18	20.47	20.49	20.57		0
	36	37	20.42	20.47	20.50		0
	75	0	20.41	20.52	20.57		0
64QAM	1	0	20.58	20.65	20.81	0-2	0
	1	36	20.56	20.66	20.76		0
	1	74	20.59	20.75	20.79		0
	36	0	20.52	20.51	20.45	0-3	0
	36	18	20.41	20.52	20.45		0
	36	37	20.36	20.50	20.41		0
	75	0	20.38	20.51	20.43		0

Table 9-27
LTE Band 66 (AWS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.08	20.50	20.27	0	0
	1	25	20.14	20.19	20.25		0
	1	49	20.12	20.47	20.29		0
	25	0	20.17	20.55	20.36	0-1	0
	25	12	20.21	20.60	20.39		0
	25	25	20.20	20.58	20.35		0
	50	0	20.23	20.59	20.39		0
16QAM	1	0	20.32	20.68	20.27	0-1	0
	1	25	20.27	20.87	20.44		0
	1	49	20.40	20.69	20.32		0
	25	0	20.16	20.54	20.38	0-2	0
	25	12	20.23	20.58	20.37		0
	25	25	20.21	20.59	20.37		0
	50	0	20.21	20.55	20.36		0
64QAM	1	0	20.27	20.43	20.51	0-2	0
	1	25	20.35	20.53	20.44		0
	1	49	20.35	20.35	20.35		0
	25	0	20.16	20.34	20.36	0-3	0
	25	12	20.22	20.43	20.37		0
	25	25	20.19	20.41	20.31		0
	50	0	20.22	20.48	20.44		0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 45 of 107	

Table 9-28
LTE Band 66 (AWS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.13	20.31	20.29	0	0
	1	12	19.91	20.13	20.01		0
	1	24	20.11	20.34	20.22		0
	12	0	20.33	20.45	20.41	0-1	0
	12	6	20.30	20.44	20.39		0
	12	13	20.26	20.42	20.35		0
	25	0	20.28	20.43	20.36		0
16QAM	1	0	20.60	20.51	20.43	0-1	0
	1	12	20.52	20.33	20.35		0
	1	24	20.67	20.55	20.36		0
	12	0	20.29	20.52	20.45	0-2	0
	12	6	20.32	20.47	20.42		0
	12	13	20.31	20.48	20.41		0
	25	0	20.32	20.41	20.35		0
64QAM	1	0	20.14	20.36	20.29	0-2	0
	1	12	20.28	20.36	20.33		0
	1	24	20.40	20.61	20.46		0
	12	0	20.31	20.54	20.42	0-3	0
	12	6	20.26	20.53	20.43		0
	12	13	20.25	20.41	20.44		0
	25	0	20.28	20.42	20.43		0

Table 9-29
LTE Band 66 (AWS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.27	20.37	20.25	0	0
	1	7	19.94	20.11	19.95		0
	1	14	20.26	20.34	20.22		0
	8	0	20.27	20.43	20.33	0-1	0
	8	4	20.25	20.40	20.30		0
	8	7	20.25	20.41	20.31		0
	15	0	20.24	20.37	20.34		0
16QAM	1	0	20.41	20.64	20.54	0-1	0
	1	7	20.32	20.56	20.45		0
	1	14	20.34	20.60	20.48		0
	8	0	20.33	20.42	20.37	0-2	0
	8	4	20.39	20.45	20.41		0
	8	7	20.41	20.46	20.39		0
	15	0	20.27	20.38	20.30		0
64QAM	1	0	20.52	20.59	20.61	0-2	0
	1	7	20.30	20.56	20.50		0
	1	14	20.47	20.59	20.31		0
	8	0	20.34	20.42	20.33	0-3	0
	8	4	20.28	20.47	20.32		0
	8	7	20.33	20.48	20.34		0
	15	0	20.27	20.44	20.26		0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 46 of 107	

Table 9-30
LTE Band 66 (AWS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.13	20.28	20.21	0	0
	1	2	20.04	20.24	20.20		0
	1	5	20.07	20.26	20.24		0
	3	0	20.16	20.39	20.32		0
	3	2	20.17	20.40	20.33		0
	3	3	19.98	20.21	20.17		0
	6	0	20.03	20.26	20.24	0-1	0
16QAM	1	0	20.28	20.46	20.44	0-1	0
	1	2	20.03	20.19	20.12		0
	1	5	20.35	20.48	20.34		0
	3	0	20.13	20.40	20.23		0
	3	2	20.21	20.48	20.29		0
	3	3	20.09	20.33	20.22		0
	6	0	20.22	20.42	20.31	0-2	0
64QAM	1	0	20.21	20.46	20.42	0-2	0
	1	2	20.30	20.52	20.50		0
	1	5	20.31	20.54	20.46		0
	3	0	20.39	20.59	20.42		0
	3	2	20.33	20.55	20.39		0
	3	3	20.22	20.42	20.32		0
	6	0	20.17	20.37	20.31	0-3	0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 47 of 107

9.3.6

LTE Band 25 (PCS)

Table 9-31
LTE Band 25 (PCS) Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.16	22.20	22.47	0	0
	1	50	22.15	21.64	22.21		0
	1	99	22.22	22.39	22.35		0
	50	0	21.17	21.09	21.54	0-1	1
	50	25	21.22	21.13	21.62		1
	50	50	21.19	21.25	21.48		1
	100	0	21.28	21.19	21.58		1
16QAM	1	0	21.46	21.35	21.65	0-1	1
	1	50	21.06	21.29	21.93		1
	1	99	21.44	21.56	21.65		1
	50	0	20.13	20.04	20.48	0-2	2
	50	25	20.16	20.11	20.58		2
	50	50	20.13	20.13	20.51		2
	100	0	20.25	20.20	20.60		2
64QAM	1	0	20.42	20.10	20.73	0-2	2
	1	50	20.34	20.07	20.75		2
	1	99	20.43	20.41	20.71		2
	50	0	19.12	18.97	19.44	0-3	3
	50	25	19.18	19.09	19.52		3
	50	50	19.09	19.14	19.43		3
	100	0	19.15	19.13	19.50		3

Table 9-32
LTE Band 25 (PCS) Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.13	22.06	22.20	0	0
	1	36	22.14	22.29	22.14		0
	1	74	22.03	22.39	21.96		0
	36	0	21.45	21.33	21.03	0-1	1
	36	18	21.37	21.32	20.97		1
	36	37	21.30	21.35	20.91		1
	75	0	21.36	21.37	20.99		1
16QAM	1	0	21.49	21.41	21.22	0-1	1
	1	36	21.45	21.61	21.29		1
	1	74	21.47	21.73	21.16		1
	36	0	20.47	20.33	20.01	0-2	2
	36	18	20.43	20.27	19.89		2
	36	37	20.36	20.34	19.81		2
	75	0	20.42	20.36	19.89		2
64QAM	1	0	20.51	20.51	20.23	0-2	2
	1	36	20.47	20.59	20.27		2
	1	74	20.42	20.63	20.18		2
	36	0	19.48	19.32	18.95	0-3	3
	36	18	19.42	19.34	18.87		3
	36	37	19.36	19.36	18.73		3
	75	0	19.37	19.33	18.89		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 48 of 107

Table 9-33
LTE Band 25 (PCS) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.33	22.05	22.87	0	0
	1	25	21.89	21.65	22.66		0
	1	49	22.27	22.15	22.85		0
	25	0	21.37	21.10	21.90	0-1	1
	25	12	21.42	21.17	21.88		1
	25	25	21.35	21.02	21.85		1
	50	0	21.39	21.18	21.92		1
16QAM	1	0	21.78	21.39	22.01	0-1	1
	1	25	21.70	21.52	22.18		1
	1	49	21.64	21.10	22.02		1
	25	0	20.38	20.22	20.94	0-2	2
	25	12	20.30	20.32	20.95		2
	25	25	20.32	20.34	20.89		2
	50	0	20.38	20.35	20.85		2
64QAM	1	0	20.82	20.18	21.00	0-2	2
	1	25	20.89	19.94	21.18		2
	1	49	20.85	20.21	21.06		2
	25	0	19.48	19.27	19.98	0-3	3
	25	12	19.35	19.35	19.95		3
	25	25	19.32	19.36	19.91		3
	50	0	19.34	19.32	19.96		3

Table 9-34
LTE Band 25 (PCS) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.44	22.31	22.76	0	0
	1	12	21.91	22.33	22.77		0
	1	24	22.55	22.50	22.83		0
	12	0	21.57	21.35	21.90	0-1	1
	12	6	21.52	21.31	21.86		1
	12	13	21.53	21.34	21.82		1
	25	0	21.54	21.31	21.88		1
16QAM	1	0	21.73	21.42	22.24	0-1	1
	1	12	21.33	21.14	21.61		1
	1	24	21.83	21.66	22.06		1
	12	0	20.54	20.36	20.89	0-2	2
	12	6	20.51	20.37	20.87		2
	12	13	20.53	20.36	20.81		2
	25	0	20.50	20.24	20.87		2
64QAM	1	0	20.67	20.40	21.21	0-2	2
	1	12	20.67	19.96	20.90		2
	1	24	20.77	20.45	21.27		2
	12	0	19.56	19.34	20.01	0-3	3
	12	6	19.53	19.32	19.99		3
	12	13	19.51	19.31	19.92		3
	25	0	19.53	19.28	19.88		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 49 of 107

Table 9-35
LTE Band 25 (PCS) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	22.58	22.37	22.76	0	0	
	1	7	22.59	21.69	22.42		0	
	1	14	22.63	22.29	22.88		0	
	8	0	21.57	21.37	21.73	0-1	1	
	8	4	21.59	21.29	21.74		1	
	8	7	21.58	21.38	21.85		1	
16QAM	15	0	21.59	21.33	21.78	0-1	1	
	1	0	21.90	21.69	22.02		0-1	1
	1	7	21.68	21.36	21.83			1
	1	14	21.95	21.55	22.10	0-2		1
	8	0	20.57	20.33	20.82		2	
	8	4	20.58	20.36	20.80		2	
64QAM	8	7	20.46	20.38	20.84	0-2	2	
	15	0	20.53	20.36	20.80		2	
	1	0	20.58	20.61	20.86		0-2	2
	1	7	20.54	20.51	20.22	2		
	1	14	20.67	20.69	20.69	0-3		2
	8	0	19.61	19.35	19.75		3	
8	4	19.62	19.38	19.84	3			
	8	7	19.63	19.30	19.80	0-3	3	
	15	0	19.64	19.29	19.74		3	

Table 9-36
LTE Band 25 (PCS) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.83	22.53	22.96	0	0
	1	2	22.52	22.40	22.83		0
	1	5	22.70	22.46	22.92		0
	3	0	22.69	22.31	22.68		0
	3	2	22.70	22.27	22.70		0
	3	3	22.58	22.33	22.73		0
	6	0	21.70	21.30	21.74	0-1	1
16QAM	1	0	22.13	21.54	22.05	0-1	1
	1	2	21.82	21.29	22.01		1
	1	5	21.96	21.37	21.91		1
	3	0	21.57	21.22	21.69		1
	3	2	21.36	21.09	21.54		1
	3	3	21.52	21.23	21.76		1
	6	0	20.78	20.38	20.84	0-2	2
64QAM	1	0	20.74	20.67	21.23	0-2	2
	1	2	20.56	20.52	21.13		2
	1	5	20.85	20.47	21.11		2
	3	0	20.68	20.28	20.93		2
	3	2	20.71	20.40	20.82		2
	3	3	20.73	20.33	20.85		2
	6	0	19.55	19.27	19.80	0-3	3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 50 of 107

Table 9-37
LTE Band 25 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.27	19.08	19.59	0	0
	1	50	19.27	19.23	19.78		0
	1	99	19.16	19.37	19.56		0
	50	0	19.31	19.10	19.70	0-1	0
	50	25	19.35	19.24	19.78		0
	50	50	19.23	19.25	19.63		0
	100	0	19.34	19.28	19.73		0
16QAM	1	0	19.49	19.18	19.84	0-1	0
	1	50	19.12	19.02	19.52		0
	1	99	19.33	19.49	19.75		0
	50	0	19.28	19.07	19.70	0-2	0
	50	25	19.32	19.19	19.75		0
	50	50	19.21	19.23	19.65		0
	100	0	19.32	19.24	19.76		0
64QAM	1	0	19.50	19.19	19.87	0-2	0
	1	50	19.45	19.01	19.93		0
	1	99	19.40	19.46	19.77		0
	50	0	19.30	19.07	19.73	0-3	0
	50	25	19.34	19.20	19.78		0
	50	50	19.24	19.22	19.65		0
	100	0	19.32	19.24	19.77		0

Table 9-38
LTE Band 25 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.10	19.01	19.76	0	0
	1	36	19.19	19.11	19.71		0
	1	74	19.11	19.21	19.56		0
	36	0	19.23	19.02	19.77	0-1	0
	36	18	19.25	19.07	19.76		0
	36	37	19.19	19.08	19.64		0
	75	0	19.23	19.13	19.73		0
16QAM	1	0	19.56	19.29	19.95	0-1	0
	1	36	19.62	19.44	19.90		0
	1	74	19.59	19.58	19.76		0
	36	0	19.24	19.12	19.80	0-2	0
	36	18	19.19	19.07	19.79		0
	36	37	19.16	19.11	19.71		0
	75	0	19.24	19.10	19.72		0
64QAM	1	0	19.66	19.19	20.00	0-2	0
	1	36	19.61	19.33	19.99		0
	1	74	19.54	19.44	19.97		0
	36	0	19.27	19.03	19.84	0-3	0
	36	18	19.26	19.02	19.79		0
	36	37	19.21	19.04	19.70		0
	75	0	19.24	19.09	19.77		0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 51 of 107	

Table 9-39
LTE Band 25 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.11	18.99	19.65	0	0
	1	25	19.01	18.72	19.61		0
	1	49	19.14	19.05	19.65		0
	25	0	19.19	18.99	19.68	0-1	0
	25	12	19.21	19.05	19.67		0
	25	25	19.18	19.08	19.62		0
	50	0	19.20	19.06	19.69		0
16QAM	1	0	19.33	19.45	19.93	0-1	0
	1	25	19.56	19.43	19.90		0
	1	49	19.41	19.53	19.91		0
	25	0	19.19	18.95	19.72	0-2	0
	25	12	19.23	18.98	19.66		0
	25	25	19.18	19.05	19.64		0
	50	0	19.19	19.07	19.69		0
64QAM	1	0	19.41	19.23	20.00	0-2	0
	1	25	19.65	19.59	19.73		0
	1	49	19.50	19.49	19.86		0
	25	0	19.22	19.02	19.75	0-3	0
	25	12	19.23	19.00	19.74		0
	25	25	19.24	19.07	19.69		0
	50	0	19.25	19.11	19.71		0

Table 9-40
LTE Band 25 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.34	18.94	19.57	0	0
	1	12	19.44	18.60	19.76		0
	1	24	19.45	19.09	19.70		0
	12	0	19.34	19.09	19.67	0-1	0
	12	6	19.35	19.06	19.65		0
	12	13	19.33	19.09	19.60		0
	25	0	19.31	19.04	19.77		0
16QAM	1	0	19.57	19.29	19.42	0-1	0
	1	12	19.78	19.15	19.70		0
	1	24	19.67	19.44	19.64		0
	12	0	19.41	19.08	19.61	0-2	0
	12	6	19.38	19.06	19.59		0
	12	13	19.35	19.09	19.61		0
	25	0	19.34	19.01	19.59		0
64QAM	1	0	19.65	18.94	19.76	0-2	0
	1	12	19.24	19.20	19.13		0
	1	24	19.46	19.18	19.82		0
	12	0	19.34	18.96	19.75	0-3	0
	12	6	19.33	18.93	19.68		0
	12	13	19.30	18.95	19.67		0
	25	0	19.32	19.02	19.62		0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 52 of 107	

Table 9-41
LTE Band 25 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.38	19.12	19.50	0	0
	1	7	19.54	18.51	19.31		0
	1	14	19.40	19.01	19.60		0
	8	0	19.34	19.12	19.49	0-1	0
	8	4	19.37	18.99	19.44		0
	8	7	19.34	19.07	19.58		0
	15	0	19.33	19.05	19.50		0
16QAM	1	0	19.45	19.49	19.77	0-1	0
	1	7	19.27	19.36	19.99		0
	1	14	19.55	19.33	19.83		0
	8	0	19.35	19.07	19.60	0-2	0
	8	4	19.30	19.12	19.59		0
	8	7	19.31	19.06	19.55		0
	15	0	19.33	19.05	19.54		0
64QAM	1	0	19.53	19.13	19.77	0-2	0
	1	7	19.40	19.31	19.00		0
	1	14	19.56	19.23	19.61		0
	8	0	19.32	19.09	19.52	0-3	0
	8	4	19.30	19.13	19.50		0
	8	7	19.33	19.06	19.51		0
	15	0	19.36	18.98	19.49		0

Table 9-42
LTE Band 25 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.58	19.27	19.62	0	0
	1	2	19.24	19.20	19.61		0
	1	5	19.48	19.17	19.48		0
	3	0	19.32	19.01	19.50		0
	3	2	19.23	19.05	19.54		0
	3	3	19.46	19.02	19.47		0
	6	0	19.51	18.95	19.53	0-1	0
16QAM	1	0	19.60	19.20	19.99	0-1	0
	1	2	19.30	19.01	19.79		0
	1	5	19.45	19.07	19.89		0
	3	0	19.52	18.93	19.39		0
	3	2	19.40	18.89	19.41		0
	3	3	19.45	19.07	19.36		0
	6	0	19.60	19.02	19.54	0-2	0
64QAM	1	0	19.85	19.66	19.79	0-2	0
	1	2	19.81	19.63	19.69		0
	1	5	19.60	19.44	19.92		0
	3	0	19.56	19.08	19.58		0
	3	2	19.57	18.88	19.53		0
	3	3	19.43	19.06	19.57		0
	6	0	19.49	19.10	19.54	0-3	0

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 53 of 107

9.3.7

LTE Band 7

Table 9-43
LTE Band 7 Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.16	22.82	22.54	0	0
	1	50	23.32	23.02	22.50		0
	1	99	23.64	23.07	22.72		0
	50	0	22.36	21.86	21.61	0-1	1
	50	25	22.41	21.92	21.66		1
	50	50	22.49	21.91	21.70		1
	100	0	22.48	21.94	21.73		1
16QAM	1	0	22.40	22.09	21.68	0-1	1
	1	50	22.51	21.98	21.85		1
	1	99	22.75	22.24	21.98		1
	50	0	21.30	20.83	20.58	0-2	2
	50	25	21.40	20.89	20.65		2
	50	50	21.43	20.89	20.67		2
	100	0	21.46	20.93	20.68		2
64QAM	1	0	21.76	21.18	20.88	0-2	2
	1	50	21.67	20.83	20.96		2
	1	99	21.93	21.23	21.02		2
	50	0	20.32	19.82	19.60	0-3	3
	50	25	20.39	19.85	19.66		3
	50	50	20.45	19.88	19.70		3
	100	0	20.44	19.91	19.66		3

Table 9-44
LTE Band 7 Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.34	23.10	22.84	0	0
	1	36	23.51	23.19	22.89		0
	1	74	23.64	23.14	22.96		0
	36	0	22.60	22.11	21.97	0-1	1
	36	18	22.65	22.12	21.85		1
	36	37	22.64	22.09	21.88		1
	75	0	22.69	22.19	21.93		1
16QAM	1	0	22.73	22.34	21.96	0-1	1
	1	36	22.85	22.41	22.08		1
	1	74	22.88	22.45	22.16		1
	36	0	21.68	21.08	20.82	0-2	2
	36	18	21.69	21.10	20.84		2
	36	37	21.70	21.05	20.85		2
	75	0	21.71	21.10	20.87		2
64QAM	1	0	21.93	21.43	20.92	0-2	2
	1	36	21.96	21.51	21.05		2
	1	74	22.02	21.48	21.20		2
	36	0	20.73	19.92	19.80	0-3	3
	36	18	20.68	19.94	19.82		3
	36	37	20.69	19.93	19.80		3
	75	0	20.68	19.96	19.86		3

FCC ID: A3LSMG960F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 54 of 107

Table 9-45
LTE Band 7 Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.68	23.07	22.72	0	0
	1	25	23.77	23.04	22.88		0
	1	49	23.89	23.07	22.99		0
	25	0	22.70	22.08	21.83	0-1	1
	25	12	22.77	22.15	21.89		1
	25	25	22.81	22.12	21.91		1
	50	0	22.79	22.13	21.90		1
16QAM	1	0	22.81	22.43	21.81	0-1	1
	1	25	23.08	22.32	21.99		1
	1	49	23.04	22.37	22.07		1
	25	0	21.70	21.13	20.86	0-2	2
	25	12	21.80	21.14	20.90		2
	25	25	21.79	21.10	20.92		2
	50	0	21.77	21.13	20.90		2
64QAM	1	0	21.94	21.20	20.95	0-2	2
	1	25	22.30	21.41	20.83		2
	1	49	22.21	21.36	21.02		2
	25	0	20.74	20.06	19.85	0-3	3
	25	12	20.79	20.12	19.95		3
	25	25	20.81	20.11	19.93		3
	50	0	20.79	20.12	19.88		3

Table 9-46
LTE Band 7 Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.80	23.03	22.58	0	0
	1	12	24.05	23.17	22.94		0
	1	24	23.98	23.18	22.83		0
	12	0	22.71	22.18	21.73	0-1	1
	12	6	22.68	22.15	21.68		1
	12	13	22.66	22.14	21.70		1
	25	0	22.70	22.12	21.65		1
16QAM	1	0	23.02	22.36	21.84	0-1	1
	1	12	23.30	22.37	21.90		1
	1	24	23.22	22.53	21.84		1
	12	0	21.84	21.15	20.70	0-2	2
	12	6	21.75	21.11	20.66		2
	12	13	21.76	21.10	20.67		2
	25	0	21.70	21.12	20.68		2
64QAM	1	0	21.77	21.09	20.74	0-2	2
	1	12	22.03	21.27	21.07		2
	1	24	21.84	21.30	21.02		2
	12	0	20.72	20.10	19.74	0-3	3
	12	6	20.65	20.06	19.73		3
	12	13	20.68	20.09	19.75		3
	25	0	20.77	20.12	19.66		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 55 of 107	

Table 9-47
LTE Band 7 Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.01	20.95	20.58	0	0
	1	50	21.19	20.97	20.65		0
	1	99	21.36	21.02	20.78		0
	50	0	19.54	19.35	19.05	0-1	1
	50	25	19.73	19.48	19.14		1
	50	50	19.70	19.39	19.11		1
16QAM	100	0	19.69	19.47	19.19	0-1	1
	1	0	19.59	19.48	19.17		1
	1	50	19.39	19.36	19.14		1
	1	99	19.85	19.51	19.38	0-2	1
	50	0	18.48	18.26	18.00		2
	50	25	18.64	18.37	18.07		2
64QAM	50	50	18.62	18.35	18.08	0-2	2
	100	0	18.62	18.42	18.14		2
	1	0	18.58	18.46	18.15		0-2
	1	50	18.53	18.34	18.12	2	
	1	99	18.87	18.54	18.35	2	
	50	0	17.45	17.28	17.02	0-3	3
50	25	17.62	17.36	17.10	3		
50	50	17.59	17.32	17.09	3		
	100	0	17.67	17.37	17.19		3

Table 9-48
LTE Band 7 Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.18	20.83	20.25	0	0
	1	36	21.18	20.86	20.40		0
	1	74	21.35	20.83	20.50		0
	36	0	19.67	19.34	18.79	0-1	1
	36	18	19.75	19.34	18.82		1
	36	37	19.76	19.29	18.79		1
	75	0	19.73	19.32	18.80		1
16QAM	1	0	19.66	19.26	19.00	0-1	1
	1	36	19.78	19.24	19.00		1
	1	74	19.87	19.17	19.20		1
	36	0	18.69	18.12	17.74	0-2	2
	36	18	18.71	18.14	17.75		2
	36	37	18.67	18.09	17.76		2
	75	0	18.66	18.11	17.73		2
64QAM	1	0	18.73	18.27	17.77	0-2	2
	1	36	18.83	18.27	17.84		2
	1	74	19.05	18.33	17.91		2
	36	0	17.86	17.20	16.74	0-3	3
	36	18	17.71	17.15	16.81		3
	36	37	17.71	17.10	16.79		3
	75	0	17.70	17.16	16.83		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 56 of 107	

Table 9-49
LTE Band 7 Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.31	20.62	20.23	0	0
	1	25	21.44	20.73	20.36		0
	1	49	21.47	20.71	20.43		0
	25	0	19.84	19.14	18.79	0-1	1
	25	12	19.87	19.17	18.83		1
	25	25	19.89	19.16	18.86		1
	50	0	19.90	19.16	18.90		1
16QAM	1	0	20.01	19.39	18.73	0-1	1
	1	25	19.92	19.25	18.64		1
	1	49	20.03	19.32	18.88		1
	25	0	18.83	18.14	17.75	0-2	2
	25	12	18.88	18.15	17.82		2
	25	25	18.86	18.09	17.85		2
	50	0	18.87	18.23	17.91		2
64QAM	1	0	18.97	18.28	17.86	0-2	2
	1	25	18.68	18.18	17.84		2
	1	49	18.72	18.22	18.03		2
	25	0	17.78	17.12	16.72	0-3	3
	25	12	17.83	17.15	16.78		3
	25	25	17.81	17.12	16.81		3
	50	0	17.86	17.21	16.88		3

Table 9-50
LTE Band 7 Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.26	20.75	20.22	0	0
	1	12	21.07	20.50	20.00		0
	1	24	21.32	20.74	20.25		0
	12	0	19.85	19.26	18.79	0-1	1
	12	6	19.85	19.26	18.79		1
	12	13	19.82	19.22	18.76		1
	25	0	19.82	19.21	18.72		1
16QAM	1	0	19.90	19.40	18.62	0-1	1
	1	12	19.85	19.30	18.96		1
	1	24	19.95	19.37	19.14		1
	12	0	18.88	18.30	17.69	0-2	2
	12	6	18.90	18.21	17.76		2
	12	13	18.88	18.20	17.80		2
	25	0	18.80	18.22	17.76		2
64QAM	1	0	18.92	18.39	17.68	0-2	2
	1	12	18.41	18.02	17.51		2
	1	24	18.76	18.35	17.87		2
	12	0	17.78	17.28	16.73	0-3	3
	12	6	17.77	17.23	16.68		3
	12	13	17.75	17.21	16.70		3
	25	0	17.76	17.18	16.69		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 57 of 107

9.3.8

LTE Band 41

Table 9-51
LTE Band 41 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.10	22.55	22.43	22.74	22.80	0	0
	1	50	23.17	22.60	22.51	22.69	22.62		0
	1	99	23.35	22.72	22.71	22.72	22.75		0
	50	0	22.16	21.62	21.43	21.74	21.90	0-1	1
	50	25	22.29	21.70	21.56	21.80	21.93		1
	50	50	22.27	21.65	21.55	21.71	21.81		1
	100	0	22.28	21.75	21.59	21.79	21.98		1
16QAM	1	0	22.34	21.61	21.72	22.08	22.05	0-1	1
	1	50	22.41	21.84	21.83	21.98	21.99		1
	1	99	22.46	22.01	22.07	22.05	22.04		1
	50	0	21.18	20.68	20.46	20.79	20.95	0-2	2
	50	25	21.31	20.71	20.59	20.80	20.94		2
	50	50	21.29	20.69	20.58	20.73	20.85		2
	100	0	21.36	20.78	20.67	20.84	21.00		2
64QAM	1	0	21.18	20.34	20.20	20.51	20.64	0-2	2
	1	50	21.01	20.43	20.23	20.43	20.50		2
	1	99	21.09	20.54	20.43	20.48	20.67		2
	50	0	20.19	19.60	19.45	19.76	19.88	0-3	3
	50	25	20.26	19.68	19.54	19.75	19.87		3
	50	50	20.27	19.66	19.53	19.69	19.81		3
	100	0	20.29	19.73	19.60	19.81	19.96		3

Table 9-52
LTE Band 41 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.20	22.67	22.51	22.66	22.71	0	0
	1	36	23.36	22.78	22.60	22.74	22.75		0
	1	74	23.37	22.79	22.58	22.69	22.64		0
	36	0	22.32	21.78	21.59	21.77	21.83	0-1	1
	36	18	22.37	21.80	21.61	21.76	21.79		1
	36	37	22.36	21.77	21.55	21.70	21.69		1
	75	0	22.38	21.83	21.64	21.79	21.80		1
16QAM	1	0	22.41	21.97	21.76	21.87	21.89	0-1	1
	1	36	22.47	22.08	21.83	21.93	21.84		1
	1	74	22.45	22.05	21.82	21.91	21.80		1
	36	0	21.30	20.80	20.62	20.77	20.83	0-2	2
	36	18	21.35	20.79	20.59	20.76	20.79		2
	36	37	21.33	20.76	20.55	20.71	20.72		2
	75	0	21.35	20.82	20.61	20.77	20.80		2
64QAM	1	0	21.02	20.50	20.36	20.48	20.58	0-2	2
	1	36	21.19	20.64	20.45	20.49	20.59		2
	1	74	21.20	20.61	20.37	20.44	20.51		2
	36	0	20.27	19.76	19.56	19.75	19.79	0-3	3
	36	18	20.32	19.78	19.55	19.71	19.77		3
	36	37	20.31	19.76	19.53	19.67	19.71		3
	75	0	20.33	19.80	19.59	19.74	19.80		3

FCC ID: A3LSMG960F			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset			Page 58 of 107

Table 9-53
LTE Band 41 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.48	22.76	22.43	22.75	22.78	0	0
	1	25	23.36	22.69	22.35	22.61	22.52		0
	1	49	23.45	22.85	22.50	22.73	22.66		0
	25	0	22.43	21.84	21.52	21.79	21.74	0-1	1
	25	12	22.47	21.88	21.47	21.82	21.75		1
	25	25	22.46	21.89	21.54	21.80	21.76		1
	50	0	22.43	21.95	21.60	21.89	21.83		1
16QAM	1	0	22.41	21.94	21.63	21.87	21.84	0-1	1
	1	25	22.49	21.92	21.73	21.83	21.72		1
	1	49	22.48	22.01	21.75	21.82	21.78		1
	25	0	21.45	20.78	20.48	20.72	20.68	0-2	2
	25	12	21.50	20.82	20.53	20.73	20.67		2
	25	25	21.49	20.83	20.54	20.74	20.66		2
	50	0	21.50	20.95	20.65	20.88	20.83		2
64QAM	1	0	21.30	20.60	20.29	20.56	20.52	0-2	2
	1	25	21.23	20.49	20.19	20.32	20.41		2
	1	49	21.44	20.67	20.39	20.42	20.49		2
	25	0	20.46	19.79	19.54	19.76	19.71	0-3	3
	25	12	20.49	19.81	19.57	19.74	19.69		3
	25	25	20.48	19.85	19.58	19.75	19.70		3
	50	0	20.50	19.90	19.63	19.85	19.80		3

Table 9-54
LTE Band 41 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.27	22.81	22.52	22.73	22.79	0	0
	1	12	23.24	22.80	22.42	22.70	22.71		0
	1	24	23.32	22.86	22.55	22.74	22.76		0
	12	0	22.39	21.97	21.67	21.88	21.92	0-1	1
	12	6	22.37	21.90	21.62	21.79	21.88		1
	12	13	22.38	21.93	21.61	21.81	21.85		1
	25	0	22.37	21.94	21.68	21.80	21.87		1
16QAM	1	0	22.43	22.02	21.70	21.91	21.95	0-1	1
	1	12	22.33	21.95	21.55	21.85	21.77		1
	1	24	22.50	22.09	21.72	21.95	21.97		1
	12	0	21.40	20.91	20.62	20.84	20.89	0-2	2
	12	6	21.37	20.84	20.61	20.75	20.84		2
	12	13	21.38	20.85	20.57	20.76	20.81		2
	25	0	21.33	20.83	20.56	20.74	20.80		2
64QAM	1	0	21.02	20.54	20.37	20.53	20.46	0-2	2
	1	12	20.91	20.46	20.17	20.35	20.40		2
	1	24	21.11	20.60	20.38	20.47	20.48		2
	12	0	20.34	19.91	19.65	19.79	19.88	0-3	3
	12	6	20.32	19.85	19.61	19.74	19.84		3
	12	13	20.31	19.86	19.57	19.72	19.79		3
	25	0	20.39	19.87	19.63	19.79	19.87		3

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 59 of 107	

9.3.9 LTE Carrier Aggregation Conducted Powers

Table 9-55
Two Component Carrier Maximum Conducted Powers

Combination	PCC								SCC				Power		
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-2A	LTE B2	10	19150	1905	QPSK	1	0	1150	1985	LTE B2	20	700	1940	22.74	22.87
CA_2A-4A (2)	LTE B2	10	19150	1905	QPSK	1	0	1150	1985	LTE B4	20	2175	2132.5	22.75	22.87
CA_2A-12A (1)	LTE B2	10	19150	1905	QPSK	1	0	1150	1985	LTE B12	10	5095	737.5	22.85	22.87
CA_4A-4A	LTE B4	20	20050	1720	QPSK	1	99	2050	2120	LTE B4	20	2300	2145	23.68	23.70
CA_4C	LTE B4	20	20050	1720	QPSK	1	99	2050	2120	LTE B4	20	2248	2139.8	23.69	23.70
CA_2A-4A (2)	LTE B4	20	20050	1720	QPSK	1	99	2050	2120	LTE B2	20	900	1960	23.61	23.70
CA_4A-5A (1)	LTE B4	20	20050	1720	QPSK	1	99	2050	2120	LTE B5	10	2525	881.5	23.70	23.70
CA_4A-12A (2)	LTE B4	20	20050	1720	QPSK	1	99	2050	2120	LTE B12	10	5095	737.5	23.74	23.70
CA_4A-13A	LTE B4	20	20050	1720	QPSK	1	99	2050	2120	LTE B13	10	5230	751	23.71	23.70
CA_4A-17A	LTE B4	5	20300	1745	QPSK	1	24	2300	2145	LTE B17	10	5790	740	23.45	23.54
CA_66A-66A	LTE B66	20	132072	1720	QPSK	1	99	66536	2120	LTE B66	20	67236	2190	23.77	23.70
CA_66B	LTE B66	15	132322	1745	QPSK	1	74	66786	2145	LTE B66	5	66693	2135.7	23.66	23.60
CA_66C	LTE B66	20	132072	1720	QPSK	1	99	66536	2120	LTE B66	20	66734	2139.8	23.79	23.70
CA_12A-66A (2)	LTE B66	20	132072	1720	QPSK	1	99	66536	2120	LTE B12	10	5095	737.5	23.76	23.70
CA_17A-66A	LTE B66	20	132072	1720	QPSK	1	99	66536	2120	LTE B17	10	5790	740	23.80	23.70
CA_4A-13A	LTE B13	10	23230	782	QPSK	1	49	5230	751	LTE B4	20	2175	2132.5	22.69	22.59
CA_4A-5A (1)	LTE B5	5	20425	826.5	QPSK	1	24	2425	871.5	LTE B4	20	2175	2132.5	24.19	24.08
CA_12A-12A	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B12	5	5155	743.5	22.90	23.03
CA_12B	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B12	10	5107	738.7	22.92	23.03
CA_2A-12A (1)	LTE B12	3	23025	700.5	QPSK	1	14	5025	730.5	LTE B2	20	900	1960	22.94	23.15
CA_41A-41A (1)	LTE B41	10	39750	2506	QPSK	1	0	39750	2506	LTE B41	20	41490	2680	23.27	23.48
CA_41C (1)	LTE B41	10	39750	2506	QPSK	1	0	39750	2506	LTE B41	20	39894	2520.4	23.28	23.48

Table 9-56
Three Component Carrier Maximum Conducted Powers

Combination	PCC									SCC 1				SCC 2				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 4A-12A-12A	LTE B4	20	20050	1720	QPSK	1	99	2050	2120	LTE B12	5	5095	737.5	LTE B12	5	5035	731.5	23.66	23.70
CA 4A-12B	LTE B4	20	20050	1720	QPSK	1	99	2050	2120	LTE B12	5	5095	737.5	LTE B12	5	5047	732.7	23.65	23.70
CA 12A-66A-66A	LTE B66	20	132072	1720	QPSK	1	99	66536	2120	LTE B66	20	67236	2190	LTE B12	10	5095	737.5	23.71	23.70
CA 12A-66B	LTE B66	15	132322	1745	QPSK	1	74	66786	2145	LTE B66	5	66693	2135.7	LTE B12	10	5095	737.5	23.66	23.60
CA 12A-66C	LTE B66	20	132072	1720	QPSK	1	99	66536	2120	LTE B66	20	66734	2139.8	LTE B12	10	5095	737.5	23.69	23.70
CA 17A-66A-66A	LTE B66	20	132072	1720	QPSK	1	99	66536	2120	LTE B66	20	67236	2190	LTE B17	10	5790	740	23.70	23.70
CA 17A-66B	LTE B66	15	132322	1745	QPSK	1	74	66786	2145	LTE B66	5	66693	2135.7	LTE B17	10	5790	740	23.68	23.60
CA 17A-66C	LTE B66	20	132072	1720	QPSK	1	99	66536	2120	LTE B66	20	66734	2139.8	LTE B17	10	5790	740	23.69	23.70
CA 41A-41C	LTE B41	10	39750	2506	QPSK	1	0	39750	2506	LTE B41	20	41292	2660.2	LTE B41	20	41490	2680	23.25	23.48
CA 41C-41A	LTE B41	10	39750	2506	QPSK	1	0	39750	2506	LTE B41	20	39894	2520.4	LTE B41	20	41490	2680	23.26	23.48
CA 41D	LTE B41	10	39750	2506	QPSK	1	0	39750	2506	LTE B41	20	39894	2520.4	LTE B41	20	40092	2540.2	23.29	23.48

Table 9-57
Four Component Carrier Maximum Conducted Powers

Combination	PCC									SCC 1				SCC 2				SCC 3				Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_41A-41D	LTE B41	10	39750	2506	QPSK	1	0	39750	2506	LTE B41	20	41094	2640.4	LTE B41	20	41292	2660.2	LTE B41	20	41490	2680	23.30	23.48
CA_41D-41A	LTE B41	10	39750	2506	QPSK	1	0	39750	2506	LTE B41	20	39894	2520.4	LTE B41	20	40092	2540.2	LTE B41	20	41490	2680	23.31	23.48
CA_41C-41C	LTE B41	10	39750	2506	QPSK	1	0	39750	2506	LTE B41	20	39894	2520.4	LTE B41	20	41292	2660.2	LTE B41	20	41490	2680	23.29	23.48
CA_41E	LTE B41	15	39750	2506	QPSK	1	74	39750	2506	LTE B41	20	39921	2523.1	LTE B41	20	40092	2540.2	LTE B41	20	40290	2560	23.47	23.37

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 60 of 107

Table 9-58
Two Component Carrier Reduced Conducted Powers

Combination	PCC									SCC				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-2A	LTE B2	15	19125	1902.5	64QAM	1	0	1125	1982.5	LTE B2	20	700	1940	19.82	20.00
CA_2A-4A (2)	LTE B2	15	19125	1902.5	64QAM	1	0	1125	1982.5	LTE B4	20	2175	2132.5	19.78	20.00
CA_2A-12A (1)	LTE B2	15	19125	1902.5	64QAM	1	0	1125	1982.5	LTE B12	10	5095	737.5	19.75	20.00
CA_4A-4A	LTE B4	20	20300	1745	64QAM	1	99	2300	2145	LTE B4	20	2050	2120	21.00	20.89
CA_4C	LTE B4	20	20300	1745	64QAM	1	99	2300	2145	LTE B4	20	2102	2125.2	20.98	20.89
CA_2A-4A (2)	LTE B4	20	20300	1745	64QAM	1	99	2300	2145	LTE B2	20	900	1960	20.90	20.89
CA_4A-5A (1)	LTE B4	20	20300	1745	64QAM	1	99	2300	2145	LTE B5	10	2525	881.5	21.00	20.89
CA_4A-12A (2)	LTE B4	20	20300	1745	64QAM	1	99	2300	2145	LTE B12	10	5095	737.5	20.99	20.89
CA_4A-13A	LTE B4	20	20300	1745	64QAM	1	99	2300	2145	LTE B13	10	5230	751	20.97	20.89
CA_4A-17A	LTE B4	10	20300	1745	16QAM	1	25	2300	2145	LTE B17	10	5790	740	20.73	20.87
CA_66A-66A	LTE B66	20	132322	1745	64QAM	1	99	66786	2145	LTE B66	20	67236	2190	20.88	20.89
CA_66B	LTE B66	10	132322	1745	16QAM	1	25	66786	2145	LTE B66	10	66687	2135.1	20.68	20.87
CA_66C	LTE B66	20	132322	1745	64QAM	1	99	66786	2145	LTE B66	20	66588	2125.2	20.99	20.89
CA_12A-66A (2)	LTE B66	20	132322	1745	64QAM	1	99	66786	2145	LTE B12	10	5095	737.5	20.96	20.89
CA_17A-66A	LTE B66	20	132322	1745	64QAM	1	99	66786	2145	LTE B17	10	5790	740	20.95	20.89

Table 9-59
Three Component Carrier Reduced Conducted Powers

Combination	PCC									SCC 1				SCC 2				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_4A-12A-12A	LTE B4	20	20300	1745	64QAM	1	99	2300	2145	LTE B12	5	5095	737.5	LTE B12	5	5035	731.5	20.83	20.89
CA_4A-12B	LTE B4	20	20300	1745	64QAM	1	99	2300	2145	LTE B12	5	5095	737.5	LTE B12	5	5047	732.7	20.73	20.89
CA_12A-66A-66A	LTE B66	20	132322	1745	64QAM	1	99	66786	2145	LTE B66	20	67236	2190	LTE B12	10	5095	737.5	20.80	20.89
CA_12A-66B	LTE B66	10	132322	1745	16QAM	1	25	66786	2145	LTE B66	10	66687	2135.1	LTE B12	10	5095	737.5	20.62	20.87
CA_12A-66C	LTE B66	20	132322	1745	64QAM	1	99	66786	2145	LTE B66	20	66588	2125.2	LTE B12	10	5095	737.5	20.76	20.89
CA_17A-66A-66A	LTE B66	20	132322	1745	64QAM	1	99	66786	2145	LTE B66	20	67236	2190	LTE B17	10	5790	740	20.81	20.89
CA_17A-66B	LTE B66	10	132322	1745	16QAM	1	25	66786	2145	LTE B66	10	66687	2135.1	LTE B17	10	5790	740	20.64	20.87
CA_17A-66C	LTE B66	20	132322	1745	64QAM	1	99	66786	2145	LTE B66	20	66588	2125.2	LTE B17	10	5790	740	20.79	20.89

Notes:

- For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.
- All control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- For downlink carrier aggregation combinations, PCC uplink channel was selected based on section C)3)b)ii) of KBD 941225 D05 V01r02. The downlink PCC channel was paired with the selected PCC uplink channel according to normal configurations without carrier aggregation. For inter-band CA, the SCC downlink channels were selected near the middle of their transmission bands. For contiguous intra-band CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing defined in section 5.4.1A of 3GPP TS 36.521. For non-contiguous intra-band CA, the downlink channel spacing between the component carriers was set to be larger than the nominal channel spacing and provided maximum separation between the component carriers. All selected downlink channels remained fully within the downlink transmission band of the respective component carrier.
- This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.




Figure 9-3
Power Measurement Setup

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 61 of 107	

9.4 WLAN Conducted Powers

Table 9-60
2.4 GHz WLAN Maximum Average RF Power – Antenna 1

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	17.74	14.06	13.86
2437	6	17.52	17.30	17.46
2462	11	17.64	14.93	14.76

Table 9-61
2.4 GHz WLAN Maximum Average RF Power – Antenna 2

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	17.80	14.43	14.20
2437	6	18.26	16.92	16.66
2462	11	17.50	15.08	14.92

Table 9-62
5 GHz WLAN Maximum Average RF Power – Ant 1

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
		Average	Average	Average
5180	36	17.23	17.15	17.10
5200	40	17.21	17.06	17.23
5220	44	17.19	17.14	17.26
5240	48	17.25	17.16	17.20
5260	52	17.30	17.24	17.28
5280	56	17.27	17.24	17.28
5300	60	17.26	17.29	17.22
5320	64	17.18	17.28	17.25
5500	100	16.71	16.73	16.71
5600	120	16.77	16.71	16.76
5620	124	16.74	16.67	16.73
5720	144	16.71	16.71	16.65
5745	149	16.81	16.74	16.68
5785	157	16.72	16.79	16.69
5825	165	16.77	16.69	16.58

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 62 of 107	

Table 9-63
5 GHz WLAN Maximum Average RF Power – Ant 2

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
		Average	Average	Average
5180	36	16.92	16.97	16.69
5200	40	17.05	17.09	16.70
5220	44	17.01	17.08	16.82
5240	48	17.12	17.10	16.80
5260	52	16.98	16.95	16.68
5280	56	17.03	17.01	16.72
5300	60	16.95	17.03	16.68
5320	64	17.10	16.90	16.72
5500	100	17.25	17.25	17.08
5600	120	17.23	17.19	16.92
5620	124	17.10	17.03	17.03
5720	144	17.00	16.88	16.77
5745	149	17.20	17.11	16.92
5785	157	17.11	17.04	16.88
5825	165	17.05	17.01	17.06

Table 9-64
2.4 GHz WLAN Reduced Average RF Power – Antenna 1

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	16.31	14.06	13.86
2437	6	15.85	15.64	16.49
2462	11	15.79	14.93	14.76

Table 9-65
2.4 GHz WLAN Reduced Average RF Power – Antenna 2

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	15.97	14.43	14.20
2437	6	15.99	15.67	16.39
2462	11	15.60	15.08	14.92

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 63 of 107

Table 9-66
5 GHz WLAN Reduced Average RF Power – Ant 1

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5210	42	12.70
5290	58	13.02
5530	106	12.91
5610	122	13.07
5690	138	13.08
5775	155	13.46

Table 9-67
5 GHz WLAN Reduced Average RF Power – Ant 2

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5210	42	12.81
5290	58	13.00
5530	106	12.81
5610	122	12.76
5690	138	13.47
5775	155	13.46

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 64 of 107

Table 9-68
5 GHz WLAN Maximum Average RF Power – MIMO

5GHz (20MHz) 802.11n Conducted Power [dBm]				
Freq [MHz]	Channel	ANT1	ANT2	MIMO
5180	36	17.15	16.97	20.07
5200	40	17.06	17.09	20.09
5220	44	17.14	17.08	20.12
5240	48	17.16	17.10	20.14
5260	52	17.24	16.95	20.11
5280	56	17.24	17.01	20.14
5300	60	17.29	17.03	20.17
5320	64	17.28	16.90	20.10
5500	100	16.73	17.25	20.01
5600	120	16.71	17.19	19.97
5620	124	16.67	17.03	19.86
5720	144	16.71	16.88	19.81
5745	149	16.74	17.11	19.94
5785	157	16.79	17.04	19.93
5825	165	16.69	17.01	19.86

Table 9-69
Maximum Output Powers During Conditions with 2.4 GHz and 5 GHz WLAN

2.4GHz 802.11n Conducted Power [dBm]			
Freq [MHz]	Channel	ANT1	ANT2
2412	1	13.21	13.04
2437	6	12.81	12.96
2462	11	12.91	13.35
5GHz (80MHz) 802.11ac Conducted Power [dBm]			
Freq [MHz]	Channel	ANT1	ANT2
5210	42	12.70	12.81
5290	58	13.02	13.00
5530	106	12.91	12.81
5610	122	13.07	12.76
5690	138	13.08	13.47
5775	155	13.46	13.46

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 65 of 107	

- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-4

Power Measurement Setup for Bandwidths < 50 MHz




Figure 9-5

Power Measurement Setup for Bandwidths > 50 MHz

9.5 Bluetooth Conducted Powers

Table 9-70
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	13.54	22.570
2441	1.0	39	14.96	31.331
2480	1.0	78	13.89	24.464
2402	2.0	0	5.57	3.603
2441	2.0	39	6.00	3.980
2480	2.0	78	5.12	3.250
2402	3.0	0	5.10	3.235
2441	3.0	39	6.11	4.081
2480	3.0	78	5.21	3.322

Note: The bolded data rates and channel above were tested for SAR.

FCC ID: A3LSMG960F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 66 of 107




Figure 9-6
Bluetooth Transmission Plot

Equation 9-1
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{2.890ms}{3.740ms} * 100\% = 77.3\%$$




Figure 9-7
Power Measurement Setup

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 67 of 107

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Head Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
10/23/2017	750H	20.8	700	0.850	41.370	0.889	42.201	-4.39%	-1.97%
			710	0.859	41.220	0.890	42.149	-3.48%	-2.20%
			740	0.897	40.763	0.893	41.994	0.45%	-2.93%
			755	0.914	40.537	0.894	41.916	2.24%	-3.29%
			770	0.928	40.335	0.895	41.838	3.69%	-3.59%
			785	0.938	40.160	0.896	41.760	4.69%	-3.83%
10/23/2017	835H	20.9	820	0.891	42.148	0.899	41.578	-0.89%	1.37%
			835	0.906	41.946	0.900	41.500	0.67%	1.07%
			850	0.920	41.758	0.916	41.500	0.44%	0.62%
10/23/2017	1750H	21.0	1710	1.343	39.959	1.348	40.142	-0.37%	-0.46%
			1750	1.384	39.785	1.371	40.079	0.95%	-0.73%
			1790	1.425	39.595	1.394	40.016	2.22%	-1.05%
10/23/2017	1900H	22.0	1850	1.379	39.882	1.400	40.000	-1.50%	-0.30%
			1880	1.413	39.747	1.400	40.000	0.93%	-0.63%
			1910	1.443	39.603	1.400	40.000	3.07%	-0.99%
10/30/2017	2450H	21.9	2400	1.812	39.175	1.756	39.289	3.19%	-0.29%
			2450	1.868	38.996	1.800	39.200	3.78%	-0.52%
			2500	1.925	38.785	1.855	39.136	3.77%	-0.90%
			2550	1.984	38.605	1.909	39.073	3.93%	-1.20%
11/1/2017	2450H	21.9	2400	1.808	39.320	1.756	39.289	2.96%	0.08%
			2450	1.865	39.143	1.800	39.200	3.61%	-0.15%
			2500	1.920	38.943	1.855	39.136	3.50%	-0.49%
			2550	1.978	38.752	1.909	39.073	3.61%	-0.82%
10/25/2017	5200H-5800H	21.2	5240	4.597	35.561	4.696	35.940	-2.11%	-1.05%
			5260	4.614	35.559	4.717	35.917	-2.18%	-1.00%
			5280	4.626	35.522	4.737	35.894	-2.34%	-1.04%
			5300	4.657	35.467	4.758	35.871	-2.12%	-1.13%
			5320	4.671	35.476	4.778	35.849	-2.24%	-1.04%
			5500	4.860	35.204	4.963	35.643	-2.08%	-1.23%
			5520	4.879	35.167	4.983	35.620	-2.09%	-1.27%
			5540	4.907	35.115	5.004	35.597	-1.94%	-1.35%
			5560	4.922	35.101	5.024	35.574	-2.03%	-1.33%
			5580	4.947	35.073	5.045	35.551	-1.94%	-1.34%
			5600	4.960	35.069	5.065	35.529	-2.07%	-1.29%
			5620	4.997	35.018	5.086	35.506	-1.75%	-1.37%
			5640	5.020	34.980	5.106	35.483	-1.68%	-1.42%
			5660	5.034	34.964	5.127	35.460	-1.81%	-1.40%
			5680	5.050	34.918	5.147	35.437	-1.88%	-1.46%
			5700	5.072	34.907	5.168	35.414	-1.86%	-1.43%
			5745	5.124	34.820	5.214	35.363	-1.73%	-1.54%
			5765	5.152	34.801	5.234	35.340	-1.57%	-1.53%
			5785	5.165	34.775	5.255	35.317	-1.71%	-1.53%
			5800	5.170	34.786	5.270	35.300	-1.90%	-1.46%
			5805	5.174	34.780	5.275	35.294	-1.91%	-1.46%
			5825	5.199	34.729	5.296	35.271	-1.83%	-1.54%

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 68 of 107

Table 10-2
Measured Body Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
10/25/2017	750B	21.1	700	0.929	56.261	0.959	55.726	-3.13%	0.96%
			710	0.938	56.151	0.960	55.687	-2.29%	0.83%
			740	0.968	55.847	0.963	55.570	0.52%	0.50%
			755	0.982	55.678	0.964	55.512	1.87%	0.30%
			770	0.996	55.514	0.965	55.453	3.21%	0.11%
			785	1.011	55.361	0.966	55.395	4.66%	-0.06%
11/1/2017	835B	21.6	820	0.965	54.790	0.969	55.258	-0.41%	-0.85%
			835	0.980	54.661	0.970	55.200	1.03%	-0.98%
			850	0.995	54.517	0.988	55.154	0.71%	-1.15%
11/12/2017	835B	19.1	820	0.978	53.354	0.969	55.258	0.93%	-3.45%
			835	0.993	53.210	0.970	55.200	2.37%	-3.61%
			850	1.008	53.052	0.988	55.154	2.02%	-3.81%
11/14/2017	835B	21.1	820	0.987	54.370	0.969	55.258	1.86%	-1.61%
			835	1.001	54.237	0.970	55.200	3.20%	-1.74%
			850	1.015	54.098	0.988	55.154	2.73%	-1.91%
11/15/2017	835B	21.6	820	0.957	52.994	0.969	55.258	-1.24%	-4.10%
			835	0.974	52.846	0.970	55.200	0.41%	-4.26%
			850	0.989	52.697	0.988	55.154	0.10%	-4.45%
10/20/2017	1750B	21.8	1710	1.449	52.286	1.463	53.537	-0.96%	-2.34%
			1750	1.492	52.159	1.488	53.432	0.27%	-2.38%
			1790	1.538	52.013	1.514	53.326	1.59%	-2.46%
10/23/2017	1750B	20.7	1710	1.481	51.583	1.463	53.537	1.23%	-3.65%
			1750	1.526	51.467	1.488	53.432	2.55%	-3.68%
			1790	1.571	51.357	1.514	53.326	3.76%	-3.69%
11/8/2017	1750B	21.3	1710	1.452	52.798	1.463	53.537	-0.75%	-1.38%
			1750	1.493	52.613	1.488	53.432	0.34%	-1.53%
			1790	1.534	52.453	1.514	53.326	1.32%	-1.64%
10/20/2017	1900B	21.6	1850	1.521	52.899	1.520	53.300	0.07%	-0.75%
			1880	1.555	52.799	1.520	53.300	2.30%	-0.94%
			1910	1.590	52.697	1.520	53.300	4.61%	-1.13%
10/23/2017	1900B	22.3	1850	1.499	53.834	1.520	53.300	-1.38%	1.00%
			1880	1.532	53.738	1.520	53.300	0.79%	0.82%
			1910	1.566	53.658	1.520	53.300	3.03%	0.67%
10/25/2017	2450B	21.6	2400	1.952	52.222	1.902	52.767	2.63%	-1.03%
			2450	2.020	52.049	1.950	52.700	3.59%	-1.24%
			2500	2.094	51.857	2.021	52.636	3.61%	-1.48%
			2550	2.163	51.651	2.092	52.573	3.39%	-1.75%
			2600	2.239	51.447	2.163	52.509	3.51%	-2.02%
			2650	2.310	51.250	2.234	52.445	3.40%	-2.28%
10/29/2017	2450B	22.0	2700	2.379	51.010	2.305	52.382	3.21%	-2.62%
			2400	1.971	51.351	1.902	52.767	3.63%	-2.68%
			2450	2.038	51.157	1.950	52.700	4.51%	-2.93%
			2500	2.106	50.938	2.021	52.636	4.21%	-3.23%
			2550	2.176	50.741	2.092	52.573	4.02%	-3.48%
			2600	2.245	50.545	2.163	52.509	3.79%	-3.74%
11/1/2017	2600B	22.3	2550	2.144	52.279	2.092	52.573	2.49%	-0.56%
			2600	2.211	52.087	2.163	52.509	2.22%	-0.80%
			2650	2.285	51.892	2.234	52.445	2.28%	-1.05%
			2700	2.359	51.705	2.305	52.382	2.34%	-1.29%
			5240	5.425	47.585	5.346	48.960	1.48%	-2.81%
			5260	5.435	47.511	5.369	48.933	1.23%	-2.91%
11/15/2017	5200B-5800B	21.6	5280	5.467	47.505	5.393	48.906	1.37%	-2.86%
			5300	5.487	47.474	5.416	48.879	1.31%	-2.87%
			5320	5.517	47.405	5.439	48.851	1.43%	-2.96%
			5500	5.754	47.162	5.650	48.607	1.84%	-2.97%
			5520	5.798	47.107	5.673	48.580	2.20%	-3.03%
			5540	5.812	47.078	5.696	48.553	2.04%	-3.04%
			5560	5.844	47.017	5.720	48.526	2.17%	-3.11%
			5580	5.862	46.998	5.743	48.499	2.07%	-3.09%
			5600	5.895	46.927	5.766	48.471	2.24%	-3.19%
			5620	5.921	46.976	5.790	48.444	2.26%	-3.03%
			5640	5.928	46.922	5.813	48.417	1.98%	-3.09%
			5660	5.977	46.844	5.837	48.390	2.40%	-3.19%
			5680	6.000	46.850	5.860	48.363	2.39%	-3.13%
			5700	6.034	46.778	5.883	48.336	2.57%	-3.22%
			5745	6.113	46.682	5.936	48.275	2.98%	-3.30%
			5765	6.142	46.671	5.959	48.248	3.07%	-3.27%
			5785	6.177	46.666	5.982	48.220	3.26%	-3.22%
			5800	6.197	46.632	6.000	48.200	3.28%	-3.25%
			5805	6.200	46.621	6.006	48.193	3.23%	-3.26%
			5825	6.208	46.571	6.029	48.166	2.97%	-3.31%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 69 of 107	

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
I	750	HEAD	10/23/2017	23.4	20.8	0.200	1003	3213	1.640	8.390	8.200	-2.26%
H	835	HEAD	10/23/2017	22.6	20.9	0.200	4d133	7410	1.860	9.520	9.300	-2.31%
J	1750	HEAD	10/23/2017	22.7	21.0	0.100	1150	3209	3.620	36.100	36.200	0.28%
I	1900	HEAD	10/23/2017	21.6	21.5	0.100	5d080	3213	4.020	39.300	40.200	2.29%
G	2450	HEAD	10/30/2017	21.7	20.7	0.100	981	3332	5.400	52.800	54.000	2.27%
G	2450	HEAD	11/01/2017	21.5	21.1	0.100	981	3332	5.230	52.800	52.300	-0.95%
H	5250	HEAD	10/25/2017	22.8	21.2	0.050	1191	3914	3.840	78.900	76.800	-2.66%
H	5600	HEAD	10/25/2017	22.8	21.2	0.050	1191	3914	4.060	83.600	81.200	-2.87%
H	5750	HEAD	10/25/2017	22.8	21.2	0.050	1191	3914	3.710	79.100	74.200	-6.19%
I	750	BODY	10/25/2017	23.4	21.1	0.200	1003	3213	1.730	8.790	8.650	-1.59%
J	835	BODY	11/01/2017	20.6	21.6	0.200	4d132	3209	2.030	9.800	10.150	3.57%
K	835	BODY	11/12/2017	21.9	18.9	0.200	4d132	7406	2.100	9.800	10.500	7.14%
G	835	BODY	11/14/2017	23.1	21.2	0.200	4d047	3332	2.020	9.570	10.100	5.54%
J	835	BODY	11/15/2017	24.1	21.5	0.200	4d133	3209	1.960	9.410	9.800	4.14%
K	1750	BODY	10/20/2017	23.5	21.8	0.100	1150	7406	3.820	36.500	38.200	4.66%
K	1750	BODY	10/23/2017	22.1	20.7	0.100	1148	7406	3.690	37.000	36.900	-0.27%
J	1750	BODY	11/08/2017	21.7	21.3	0.100	1148	3209	3.840	37.000	38.400	3.78%
J	1900	BODY	10/20/2017	22.1	21.5	0.100	5d080	3209	4.060	39.100	40.600	3.84%
J	1900	BODY	10/23/2017	21.7	22.5	0.100	5d080	3209	4.030	39.100	40.300	3.07%
E	2450	BODY	10/25/2017	23.7	21.6	0.100	719	3319	5.100	50.100	51.000	1.80%
E	2600	BODY	10/25/2017	23.7	21.6	0.100	1064	3319	5.830	54.700	58.300	6.58%
E	2450	BODY	10/29/2017	20.4	20.1	0.100	719	3319	4.940	50.100	49.400	-1.40%
E	2600	BODY	10/29/2017	20.4	20.1	0.100	1064	3319	5.630	54.700	56.300	2.93%
E	2600	BODY	11/01/2017	22.3	22.3	0.100	1064	3319	5.560	54.700	55.600	1.65%
D	5250	BODY	11/15/2017	22.1	21.7	0.050	1237	7308	3.680	76.900	73.600	-4.29%
D	5600	BODY	11/15/2017	22.1	21.7	0.050	1237	7308	3.860	78.500	77.200	-1.66%
D	5750	BODY	11/15/2017	22.1	21.7	0.050	1237	7308	3.690	77.100	73.800	-4.28%

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 70 of 107




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 71 of 107

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	33.18	-0.04	Right	Cheek	0E2DD	1:8.3	0.219	1.076	0.236	A1
836.60	190	GSM 850	GSM	33.5	33.18	0.01	Right	Tilt	0E2DD	1:8.3	0.103	1.076	0.111	
836.60	190	GSM 850	GSM	33.5	33.18	0.01	Left	Cheek	0E2DD	1:8.3	0.153	1.076	0.165	
836.60	190	GSM 850	GSM	33.5	33.18	0.01	Left	Tilt	0E2DD	1:8.3	0.137	1.076	0.147	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-2
UMTS 850 Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Ant State	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	25.0	24.12	-0.06	Right	Cheek	13	0E2DD	1:1	0.210	1.225	0.257	A2
836.60	4183	UMTS 850	RMC	25.0	24.12	0.04	Right	Tilt	13	0E2DD	1:1	0.074	1.225	0.091	
836.60	4183	UMTS 850	RMC	25.0	24.12	0.06	Left	Cheek	13	0E2DD	1:1	0.123	1.225	0.151	
836.60	4183	UMTS 850	RMC	25.0	24.12	0.01	Left	Tilt	13	0E2DD	1:1	0.084	1.225	0.103	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-3
UMTS 1750 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	23.5	23.25	0.01	Right	Cheek	0E2D1	1:1	0.112	1.059	0.119	
1732.40	1412	UMTS 1750	RMC	23.5	23.25	0.07	Right	Tilt	0E2D1	1:1	0.089	1.059	0.094	
1732.40	1412	UMTS 1750	RMC	23.5	23.25	0.02	Left	Cheek	0E2D1	1:1	0.151	1.059	0.160	A3
1732.40	1412	UMTS 1750	RMC	23.5	23.25	0.07	Left	Tilt	0E2D1	1:1	0.078	1.059	0.083	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 72 of 107

Table 11-4
GSM 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1909.80	810	GSM 1900	GSM	30.5	29.84	0.10	Right	Cheek	0E339	1:8.3	0.053	1.164	0.062	
1909.80	810	GSM 1900	GSM	30.5	29.84	0.16	Right	Tilt	0E339	1:8.3	0.026	1.164	0.030	
1909.80	810	GSM 1900	GSM	30.5	29.84	0.07	Left	Cheek	0E339	1:8.3	0.073	1.164	0.085	A4
1909.80	810	GSM 1900	GSM	30.5	29.84	0.12	Left	Tilt	0E339	1:8.3	0.025	1.164	0.029	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-5
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1907.60	9538	UMTS 1900	RMC	23.5	22.91	-0.06	Right	Cheek	0E339	1:1	0.081	1.146	0.093	
1907.60	9538	UMTS 1900	RMC	23.5	22.91	0.09	Right	Tilt	0E339	1:1	0.042	1.146	0.048	
1907.60	9538	UMTS 1900	RMC	23.5	22.91	0.04	Left	Cheek	0E339	1:1	0.114	1.146	0.131	A5
1907.60	9538	UMTS 1900	RMC	23.5	22.91	0.10	Left	Tilt	0E339	1:1	0.034	1.146	0.039	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-6
LTE Band 12 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																(W/kg)		(W/kg)	
MHz	Ch.																		
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	0.15	0	Right	Cheek	QPSK	1	49	0E302	1:1	0.065	1.138	0.074	A6
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	0.07	1	Right	Cheek	QPSK	25	25	0E302	1:1	0.048	1.148	0.055	
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	-0.07	0	Right	Tilt	QPSK	1	49	0E302	1:1	0.052	1.138	0.059	
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	0.06	1	Right	Tilt	QPSK	25	25	0E302	1:1	0.040	1.148	0.046	
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	-0.02	0	Left	Cheek	QPSK	1	49	0E302	1:1	0.054	1.138	0.061	
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	0.14	1	Left	Cheek	QPSK	25	25	0E302	1:1	0.044	1.148	0.051	
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	0.09	0	Left	Tilt	QPSK	1	49	0E302	1:1	0.056	1.138	0.064	
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	0.13	1	Left	Tilt	QPSK	25	25	0E302	1:1	0.045	1.148	0.052	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 73 of 107

Table 11-7
LTE Band 13 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	0.06	0	Right	Cheek	QPSK	1	49	0E2D1	1:1	0.129	1.233	0.159	A7
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	0.10	1	Right	Cheek	QPSK	25	25	0E2D1	1:1	0.107	1.205	0.129	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	0.19	0	Right	Tilt	QPSK	1	49	0E2D1	1:1	0.057	1.233	0.070	
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	0.17	1	Right	Tilt	QPSK	25	25	0E2D1	1:1	0.045	1.205	0.054	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	0.04	0	Left	Cheek	QPSK	1	49	0E2D1	1:1	0.126	1.233	0.155	
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	0.10	1	Left	Cheek	QPSK	25	25	0E2D1	1:1	0.092	1.205	0.111	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	0.13	0	Left	Tilt	QPSK	1	49	0E2D1	1:1	0.062	1.233	0.076	
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	0.16	1	Left	Tilt	QPSK	25	25	0E2D1	1:1	0.041	1.205	0.049	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak										Head									
Uncontrolled Exposure/General Population										1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-8
LTE Band 26 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	-0.04	0	Right	Cheek	QPSK	1	36	0E2DD	1:1	0.137	1.175	0.161	A8
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	0.01	1	Right	Cheek	QPSK	36	18	0E2DD	1:1	0.111	1.167	0.130	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	0.02	0	Right	Tilt	QPSK	1	36	0E2DD	1:1	0.060	1.175	0.071	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	0.08	1	Right	Tilt	QPSK	36	18	0E2DD	1:1	0.048	1.167	0.056	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	0.05	0	Left	Cheek	QPSK	1	36	0E2DD	1:1	0.099	1.175	0.116	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	0.14	1	Left	Cheek	QPSK	36	18	0E2DD	1:1	0.076	1.167	0.089	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	0.04	0	Left	Tilt	QPSK	1	36	0E2DD	1:1	0.090	1.175	0.106	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	0.09	1	Left	Tilt	QPSK	36	18	0E2DD	1:1	0.070	1.167	0.082	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-9
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																				
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Ant State	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																	(W/kg)		(W/kg)	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	-0.02	0	Right	Cheek	13	QPSK	1	25	0E2DD	1:1	0.163	1.186	0.193	A9
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	0.03	1	Right	Cheek	13	QPSK	25	12	0E2DD	1:1	0.124	1.167	0.145	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	0.08	0	Right	Tilt	13	QPSK	1	25	0E2DD	1:1	0.065	1.186	0.077	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	0.12	1	Right	Tilt	13	QPSK	25	12	0E2DD	1:1	0.046	1.167	0.054	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	0.02	0	Left	Cheek	13	QPSK	1	25	0E2DD	1:1	0.129	1.186	0.153	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	0.09	1	Left	Cheek	13	QPSK	25	12	0E2DD	1:1	0.087	1.167	0.102	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	0.04	0	Left	Tilt	13	QPSK	1	25	0E2DD	1:1	0.100	1.186	0.119	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	0.00	1	Left	Tilt	13	QPSK	25	12	0E2DD	1:1	0.069	1.167	0.081	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 74 of 107

Table 11-10
LTE Band 66 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.0	23.70	0.02	0	Right	Cheek	QPSK	1	99	0E2D1	1:1	0.165	1.072	0.177	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.64	0.08	1	Right	Cheek	QPSK	50	25	0E2D1	1:1	0.141	1.086	0.153	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.0	23.70	0.19	0	Right	Tilt	QPSK	1	99	0E2D1	1:1	0.094	1.072	0.101	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.64	0.00	1	Right	Tilt	QPSK	50	25	0E2D1	1:1	0.080	1.086	0.087	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.0	23.70	0.00	0	Left	Cheek	QPSK	1	99	0E2D1	1:1	0.221	1.072	0.237	A10
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.64	-0.02	1	Left	Cheek	QPSK	50	25	0E2D1	1:1	0.183	1.086	0.199	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.0	23.70	-0.11	0	Left	Tilt	QPSK	1	99	0E2D1	1:1	0.087	1.072	0.093	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.64	0.01	1	Left	Tilt	QPSK	50	25	0E2D1	1:1	0.073	1.086	0.079	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-11
LTE Band 25 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.47	0.00	0	Right	Cheek	QPSK	1	0	0E34C	1:1	0.071	1.268	0.090	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.62	0.08	1	Right	Cheek	QPSK	50	25	0E34C	1:1	0.066	1.225	0.081	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.47	0.18	0	Right	Tilt	QPSK	1	0	0E34C	1:1	0.035	1.268	0.044	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.62	0.09	1	Right	Tilt	QPSK	50	25	0E34C	1:1	0.032	1.225	0.039	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.47	0.02	0	Left	Cheek	QPSK	1	0	0E34C	1:1	0.114	1.268	0.145	A11
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.62	0.04	1	Left	Cheek	QPSK	50	25	0E34C	1:1	0.101	1.225	0.124	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.47	0.03	0	Left	Tilt	QPSK	1	0	0E34C	1:1	0.051	1.268	0.065	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.62	0.15	1	Left	Tilt	QPSK	50	25	0E34C	1:1	0.033	1.225	0.040	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-12
LTE Band 7 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																(W/kg)		(W/kg)	
2510.00	20850	Low	LTE Band 7	20	24.5	23.64	0.13	0	Right	Cheek	QPSK	1	99	0E30E	1:1	0.111	1.219	0.135	
2510.00	20850	Low	LTE Band 7	20	23.5	22.49	-0.17	1	Right	Cheek	QPSK	50	50	0E30E	1:1	0.072	1.262	0.091	
2510.00	20850	Low	LTE Band 7	20	24.5	23.64	0.13	0	Right	Tilt	QPSK	1	99	0E30E	1:1	0.148	1.219	0.180	
2510.00	20850	Low	LTE Band 7	20	23.5	22.49	0.07	1	Right	Tilt	QPSK	50	50	0E30E	1:1	0.085	1.262	0.107	
2510.00	20850	Low	LTE Band 7	20	24.5	23.64	0.01	0	Left	Cheek	QPSK	1	99	0E30E	1:1	0.150	1.219	0.183	A12
2510.00	20850	Low	LTE Band 7	20	23.5	22.49	0.19	1	Left	Cheek	QPSK	50	50	0E30E	1:1	0.096	1.262	0.121	
2510.00	20850	Low	LTE Band 7	20	24.5	23.64	0.16	0	Left	Tilt	QPSK	1	99	0E30E	1:1	0.077	1.219	0.094	
2510.00	20850	Low	LTE Band 7	20	23.5	22.49	0.19	1	Left	Tilt	QPSK	50	50	0E30E	1:1	0.058	1.262	0.073	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 75 of 107

Table 11-13
LTE Band 41 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																(W/kg)		(W/kg)	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	0.20	0	Right	Cheek	QPSK	1	99	0E2DD	1:1.58	0.047	1.035	0.049	
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	0.18	1	Right	Cheek	QPSK	50	25	0E2DD	1:1.58	0.041	1.050	0.043	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	0.18	0	Right	Tilt	QPSK	1	99	0E2DD	1:1.58	0.052	1.035	0.054	
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	0.21	1	Right	Tilt	QPSK	50	25	0E2DD	1:1.58	0.039	1.050	0.041	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	0.06	0	Left	Cheek	QPSK	1	99	0E2DD	1:1.58	0.070	1.035	0.072	A13
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	0.20	1	Left	Cheek	QPSK	50	25	0E2DD	1:1.58	0.052	1.050	0.055	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	0.14	0	Left	Tilt	QPSK	1	99	0E2DD	1:1.58	0.042	1.035	0.043	
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	0.15	1	Left	Tilt	QPSK	50	25	0E2DD	1:1.58	0.028	1.050	0.029	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-14
DTS Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	16.5	16.31	0.21	Right	Cheek	1	0E34C	1	99.9	0.162	0.160	1.045	1.001	0.167	
2412	1	802.11b	DSSS	22	16.5	16.31	0.11	Right	Tilt	1	0E34C	1	99.9	0.138	-	1.045	1.001	-	
2412	1	802.11b	DSSS	22	16.5	16.31	-0.12	Left	Cheek	1	0E34C	1	99.9	0.093	-	1.045	1.001	-	
2412	1	802.11b	DSSS	22	16.5	16.31	0.18	Left	Tilt	1	0E34C	1	99.9	0.098	-	1.045	1.001	-	
2412	1	802.11b	DSSS	22	16.5	15.97	0.07	Right	Cheek	2	0E34C	1	99.9	1.055	0.752	1.130	1.001	0.851	
2437	6	802.11b	DSSS	22	16.5	15.99	0.03	Right	Cheek	2	0E34C	1	99.9	1.177	0.818	1.125	1.001	0.921	
2462	11	802.11b	DSSS	22	16.5	15.60	0.01	Right	Cheek	2	0E34C	1	99.9	0.500	0.432	1.230	1.001	0.532	
2437	6	802.11b	DSSS	22	16.5	15.99	0.12	Right	Tilt	2	0E34C	1	99.9	0.898	0.651	1.125	1.001	0.733	
2437	6	802.11b	DSSS	22	16.5	15.99	0.11	Left	Cheek	2	0E34C	1	99.9	0.423	-	1.125	1.001	-	
2437	6	802.11b	DSSS	22	16.5	15.99	0.08	Left	Tilt	2	0E34C	1	99.9	0.358	-	1.125	1.001	-	
2437	6	802.11b	DSSS	22	16.5	15.99	0.04	Right	Cheek	2	0E34C	1	99.9	1.192	0.886	1.125	1.001	0.998	A14
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Note: Blue entry represents variability measurement.

Table 11-15
DTS MIMO Head SAR for Conditions with 2.4 GHz and 5 GHz WLAN SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.															W/kg	(W/kg)		(W/kg)		
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	0.04	Right	Cheek	MIMO	0E34C	13	99.0	0.405	0.265	1.146	1.010	0.307	
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	0.18	Right	Tilt	MIMO	0E34C	13	99.0	0.262	-	1.146	1.010	-	
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	-0.11	Left	Cheek	MIMO	0E34C	13	99.0	0.186	-	1.146	1.010	-	
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	0.21	Left	Tilt	MIMO	0E34C	13	99.0	0.137	-	1.146	1.010	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram											

Note: DTS MIMO was additionally evaluated at the maximum allowed output power during operations with Simultaneous 2.4 GHz and 5 GHz WLAN. 5 GHz WIFI was not transmitting during the above evaluations.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 76 of 107

**Table 11-16
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5290	58	802.11ac	OFDM	80	13.5	13.02	0.13	Right	Cheek	1	0E302	29.3	85.3	0.088	0.052	1.117	1.172	0.068	
5290	58	802.11ac	OFDM	80	13.5	13.02	0.15	Right	Tilt	1	0E302	29.3	85.3	0.081	-	1.117	1.172	-	
5290	58	802.11ac	OFDM	80	13.5	13.02	0.16	Left	Cheek	1	0E302	29.3	85.3	0.044	-	1.117	1.172	-	
5290	58	802.11ac	OFDM	80	13.5	13.02	0.08	Left	Tilt	1	0E302	29.3	85.3	0.045	-	1.117	1.172	-	
5290	58	802.11ac	OFDM	80	13.5	13.00	0.19	Right	Cheek	2	0E302	29.3	85.5	0.361	0.126	1.122	1.170	0.165	
5290	58	802.11ac	OFDM	80	13.5	13.00	-0.13	Right	Tilt	2	0E302	29.3	85.5	0.275	-	1.122	1.170	-	
5290	58	802.11ac	OFDM	80	13.5	13.00	0.18	Left	Cheek	2	0E302	29.3	85.5	0.239	-	1.122	1.170	-	
5290	58	802.11ac	OFDM	80	13.5	13.00	0.21	Left	Tilt	2	0E302	29.3	85.5	0.189	-	1.122	1.170	-	
5690	138	802.11ac	OFDM	80	13.5	13.08	0.04	Right	Cheek	1	0E302	29.3	85.3	0.080	-	1.102	1.172	-	
5690	138	802.11ac	OFDM	80	13.5	13.08	0.13	Right	Tilt	1	0E302	29.3	85.3	0.116	0.054	1.102	1.172	0.070	
5690	138	802.11ac	OFDM	80	13.5	13.08	0.21	Left	Cheek	1	0E302	29.3	85.3	0.048	-	1.102	1.172	-	
5690	138	802.11ac	OFDM	80	13.5	13.08	0.18	Left	Tilt	1	0E302	29.3	85.3	0.059	-	1.102	1.172	-	
5690	138	802.11ac	OFDM	80	13.5	13.47	0.20	Right	Cheek	2	0E302	29.3	85.5	0.417	0.178	1.007	1.170	0.210	
5690	138	802.11ac	OFDM	80	13.5	13.47	0.14	Right	Tilt	2	0E302	29.3	85.5	0.254	-	1.007	1.170	-	
5690	138	802.11ac	OFDM	80	13.5	13.47	0.05	Left	Cheek	2	0E302	29.3	85.5	0.185	-	1.007	1.170	-	
5690	138	802.11ac	OFDM	80	13.5	13.47	0.16	Left	Tilt	2	0E302	29.3	85.5	0.109	-	1.007	1.170	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	0.14	Right	Cheek	1	0E302	29.3	85.3	0.128	-	1.009	1.172	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	0.06	Right	Tilt	1	0E302	29.3	85.3	0.103	-	1.009	1.172	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	0.10	Left	Cheek	1	0E302	29.3	85.3	0.110	-	1.009	1.172	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	0.12	Left	Tilt	1	0E302	29.3	85.3	0.133	0.054	1.009	1.172	0.064	
5775	155	802.11ac	OFDM	80	13.5	13.46	0.03	Right	Cheek	2	0E302	29.3	85.5	0.415	0.186	1.009	1.170	0.220	A15
5775	155	802.11ac	OFDM	80	13.5	13.46	0.21	Right	Tilt	2	0E302	29.3	85.5	0.270	-	1.009	1.170	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	0.16	Left	Cheek	2	0E302	29.3	85.5	0.242	-	1.009	1.170	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	0.17	Left	Tilt	2	0E302	29.3	85.5	0.143	-	1.009	1.170	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak									Head										
Uncontrolled Exposure/General Population									1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-17
DSS Head SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle %	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2402.00	0	Bluetooth	FHSS	15.0	13.54	0.02	Right	Cheek	0E34C	1	77.3	0.319	1.400	1.294	0.578	
2441.00	39	Bluetooth	FHSS	15.0	14.96	-0.15	Right	Cheek	0E34C	1	77.3	0.487	1.009	1.294	0.636	A16
2480.00	78	Bluetooth	FHSS	15.0	13.89	0.21	Right	Cheek	0E34C	1	77.3	0.262	1.291	1.294	0.438	
2441.00	39	Bluetooth	FHSS	15.0	14.96	-0.17	Right	Tilt	0E34C	1	77.3	0.316	1.009	1.294	0.413	
2441.00	39	Bluetooth	FHSS	15.0	14.96	0.06	Left	Cheek	0E34C	1	77.3	0.199	1.009	1.294	0.260	
2441.00	39	Bluetooth	FHSS	15.0	14.96	0.06	Left	Tilt	0E34C	1	77.3	0.176	1.009	1.294	0.230	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 77 of 107

11.2 Standalone Body-Worn SAR Data

Table 11-18
GSM/UMTS Body-Worn SAR Data

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Ant State	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	33.18	0.02	15 mm	N/A	0E2D1	1	1:8.3	back	0.337	1.076	0.363	A17
836.60	4183	UMTS 850	RMC	25.0	24.12	-0.02	15 mm	13	0E30E	N/A	1:1	back	0.362	1.225	0.443	A19
1732.40	1412	UMTS 1750	RMC	23.5	23.25	0.03	15 mm	N/A	0E302	N/A	1:1	back	0.535	1.059	0.567	A21
1909.80	810	GSM 1900	GSM	30.5	29.84	-0.04	15 mm	N/A	0E339	1	1:8.3	back	0.268	1.164	0.312	A23
1907.60	9538	UMTS 1900	RMC	23.5	22.91	0.03	15 mm	N/A	0E339	N/A	1:1	back	0.443	1.146	0.508	A25
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-19
LTE Body-Worn SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Ant State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	-0.09	0	N/A	0E302	QPSK	1	49	15 mm	back	1:1	0.135	1.138	0.154	A27
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	-0.03	1	N/A	0E302	QPSK	25	25	15 mm	back	1:1	0.102	1.148	0.117	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	-0.01	0	N/A	0E2D1	QPSK	1	49	15 mm	back	1:1	0.246	1.233	0.303	A29
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	-0.01	1	N/A	0E2D1	QPSK	25	25	15 mm	back	1:1	0.188	1.205	0.227	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	-0.01	0	N/A	0E302	QPSK	1	36	15 mm	back	1:1	0.226	1.175	0.266	A31
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	0.01	1	N/A	0E302	QPSK	36	18	15 mm	back	1:1	0.180	1.167	0.210	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	0.14	0	13	0E30E	QPSK	1	25	15 mm	back	1:1	0.296	1.186	0.351	A33
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	-0.01	1	13	0E30E	QPSK	25	12	15 mm	back	1:1	0.225	1.167	0.263	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.0	23.70	-0.01	0	N/A	0E30E	QPSK	1	99	15 mm	back	1:1	0.794	1.072	0.851	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.58	0.14	0	N/A	0E30E	QPSK	1	99	15 mm	back	1:1	0.903	1.102	0.995	A35
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.61	-0.02	0	N/A	0E30E	QPSK	1	99	15 mm	back	1:1	0.782	1.094	0.856	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.64	-0.03	1	N/A	0E30E	QPSK	50	25	15 mm	back	1:1	0.629	1.086	0.683	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.63	0.00	1	N/A	0E30E	QPSK	100	0	15 mm	back	1:1	0.525	1.089	0.572	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.47	0.01	0	N/A	0E339	QPSK	1	0	15 mm	back	1:1	0.367	1.268	0.465	A37
1905.00	26590	High	LTE Band 25 (PCS)	20	22.5	21.62	0.01	1	N/A	0E339	QPSK	50	25	15 mm	back	1:1	0.320	1.225	0.392	
2510.00	20850	Low	LTE Band 7	20	24.5	23.64	0.10	0	N/A	0E30E	QPSK	1	99	15 mm	back	1:1	0.516	1.219	0.629	
2535.00	21100	Mid	LTE Band 7	20	24.5	23.07	0.02	0	N/A	0E30E	QPSK	1	99	15 mm	back	1:1	0.497	1.390	0.691	
2560.00	21350	High	LTE Band 7	20	24.5	22.72	0.13	0	N/A	0E30E	QPSK	1	99	15 mm	back	1:1	0.563	1.507	0.848	A39
2510.00	20850	Low	LTE Band 7	20	23.5	22.49	-0.01	1	N/A	0E30E	QPSK	50	50	15 mm	back	1:1	0.346	1.262	0.437	
2510.00	20850	Low	LTE Band 7	20	23.5	22.48	0.13	1	N/A	0E30E	QPSK	100	0	15 mm	back	1:1	0.317	1.265	0.401	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	0.02	0	N/A	0E30E	QPSK	1	99	15 mm	back	1:1.58	0.215	1.035	0.223	A41
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	-0.05	1	N/A	0E30E	QPSK	50	25	15 mm	back	1:1.58	0.162	1.050	0.170	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 78 of 107

Table 11-20
DTS Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	18.5	17.74	0.13	15 mm	1	0E339	1	back	99.9	0.035	0.029	1.191	1.001	0.035	
2437	6	802.11b	DSSS	22	18.5	18.26	-0.03	15 mm	2	0E339	1	back	99.9	0.145	0.128	1.057	1.001	0.135	A43
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-21
DTS MIMO Body-Worn SAR for Conditions with 2.4 GHz and 5 GHz WLAN SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.															W/kg	(W/kg)			(W/kg)	
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	0.12	15 mm	MIMO	0E339	13	back	99.0	0.030	0.024	1.146	1.010	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: DTS MIMO was additionally evaluated at the maximum allowed output power during operations with Simultaneous 2.4 GHz and 5 GHz WLAN. 5 GHz WIFI was not transmitting during the above evaluations.

Table 11-22
NII Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	17.5	17.30	-0.03	15 mm	1	0E2D1	6	back	98.6	0.456	0.228	1.047	1.014	0.242	A45
5320	64	802.11a	OFDM	20	17.5	17.10	-0.01	15 mm	2	0E2D1	6	back	98.6	0.446	0.176	1.096	1.014	0.196	
5600	120	802.11a	OFDM	20	17.5	16.77	-0.19	15 mm	1	0E2D1	6	back	98.6	0.364	0.159	1.183	1.014	0.191	
5500	100	802.11a	OFDM	20	17.5	17.25	0.01	15 mm	2	0E2D1	6	back	98.6	0.296	0.139	1.059	1.014	0.149	
5745	149	802.11a	OFDM	20	17.5	16.81	0.17	15 mm	1	0E2D1	6	back	98.6	0.381	0.160	1.172	1.014	0.190	
5745	149	802.11a	OFDM	20	17.5	17.20	0.08	15 mm	2	0E2D1	6	back	98.6	0.414	0.194	1.072	1.014	0.211	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body 1.6 W/kg (mW/g) averaged over 1 gram											
Spatial Peak Uncontrolled Exposure/General Population																			

Table 11-23
DSS Body-Worn SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441	39	Bluetooth	FHSS	15.0	14.96	0.01	15 mm	0E339	1	back	77.3	0.036	1.009	1.294	0.047	A47
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 79 of 107

11.3 Standalone Hotspot SAR Data

Table 11-24
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Ant State	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
824.20	128	GSM 850	GPRS	32.2	31.21	0.07	10 mm	N/A	0E2D1	2	1:4.15	back	0.627	1.256	0.788	
836.60	190	GSM 850	GPRS	32.2	31.07	-0.17	10 mm	N/A	0E2D1	2	1:4.15	back	0.689	1.297	0.894	
848.80	251	GSM 850	GPRS	32.2	31.17	0.13	10 mm	N/A	0E2D1	2	1:4.15	back	0.754	1.268	0.956	A18
836.60	190	GSM 850	GPRS	32.2	31.07	-0.06	10 mm	N/A	0E2D1	2	1:4.15	front	0.567	1.297	0.735	
836.60	190	GSM 850	GPRS	32.2	31.07	-0.04	10 mm	N/A	0E2D1	2	1:4.15	bottom	0.460	1.297	0.597	
836.60	190	GSM 850	GPRS	32.2	31.07	0.00	10 mm	N/A	0E2D1	2	1:4.15	right	0.490	1.297	0.636	
836.60	190	GSM 850	GPRS	32.2	31.07	-0.14	10 mm	N/A	0E2D1	2	1:4.15	left	0.122	1.297	0.158	
826.40	4132	UMTS 850	RMC	25.0	24.33	-0.10	10 mm	13	0E30E	N/A	1:1	back	0.541	1.167	0.631	
836.60	4183	UMTS 850	RMC	25.0	24.12	-0.10	10 mm	13	0E30E	N/A	1:1	back	0.611	1.225	0.748	
846.60	4233	UMTS 850	RMC	25.0	24.11	-0.13	10 mm	13	0E30E	N/A	1:1	back	0.624	1.227	0.766	A20
836.60	4183	UMTS 850	RMC	25.0	24.12	-0.03	10 mm	13	0E30E	N/A	1:1	front	0.522	1.225	0.639	
836.60	4183	UMTS 850	RMC	25.0	24.12	-0.01	10 mm	13	0E30E	N/A	1:1	bottom	0.374	1.225	0.458	
836.60	4183	UMTS 850	RMC	25.0	24.12	-0.01	10 mm	13	0E30E	N/A	1:1	right	0.382	1.225	0.468	
836.60	4183	UMTS 850	RMC	25.0	24.12	0.02	10 mm	13	0E30E	N/A	1:1	left	0.090	1.225	0.110	
1732.40	1412	UMTS 1750	RMC	22.0	21.38	0.03	10 mm	N/A	0E302	N/A	1:1	back	0.503	1.153	0.580	
1732.40	1412	UMTS 1750	RMC	22.0	21.38	-0.01	10 mm	N/A	0E302	N/A	1:1	front	0.401	1.153	0.462	
1712.40	1312	UMTS 1750	RMC	22.0	21.27	-0.10	10 mm	N/A	0E302	N/A	1:1	bottom	0.641	1.183	0.758	
1732.40	1412	UMTS 1750	RMC	22.0	21.38	-0.05	10 mm	N/A	0E302	N/A	1:1	bottom	0.726	1.153	0.837	
1752.60	1513	UMTS 1750	RMC	22.0	21.44	-0.12	10 mm	N/A	0E302	N/A	1:1	bottom	0.866	1.138	0.986	A22
1732.40	1412	UMTS 1750	RMC	22.0	21.38	0.00	10 mm	N/A	0E302	N/A	1:1	right	0.077	1.153	0.089	
1732.40	1412	UMTS 1750	RMC	22.0	21.38	0.03	10 mm	N/A	0E302	N/A	1:1	left	0.093	1.153	0.107	
1909.80	810	GSM 1900	GPRS	25.9	24.54	-0.01	10 mm	N/A	0E339	3	1:2.76	back	0.377	1.368	0.516	
1909.80	810	GSM 1900	GPRS	25.9	24.54	0.10	10 mm	N/A	0E339	3	1:2.76	front	0.289	1.368	0.395	
1850.20	512	GSM 1900	GPRS	25.9	23.95	-0.07	10 mm	N/A	0E339	3	1:2.76	bottom	0.492	1.567	0.771	
1880.00	661	GSM 1900	GPRS	25.9	24.14	-0.05	10 mm	N/A	0E339	3	1:2.76	bottom	0.467	1.500	0.701	
1909.80	810	GSM 1900	GPRS	25.9	24.54	-0.05	10 mm	N/A	0E339	3	1:2.76	bottom	0.576	1.368	0.788	A24
1909.80	810	GSM 1900	GPRS	25.9	24.54	-0.04	10 mm	N/A	0E339	3	1:2.76	right	0.036	1.368	0.049	
1909.80	810	GSM 1900	GPRS	25.9	24.54	0.08	10 mm	N/A	0E339	3	1:2.76	left	0.065	1.368	0.089	
1907.60	9538	UMTS 1900	RMC	21.0	20.96	-0.02	10 mm	N/A	0E339	N/A	1:1	back	0.438	1.009	0.442	
1907.60	9538	UMTS 1900	RMC	21.0	20.96	0.04	10 mm	N/A	0E339	N/A	1:1	front	0.313	1.009	0.316	
1907.60	9538	UMTS 1900	RMC	21.0	20.96	-0.02	10 mm	N/A	0E339	N/A	1:1	bottom	0.580	1.009	0.585	A26
1907.60	9538	UMTS 1900	RMC	21.0	20.96	0.06	10 mm	N/A	0E339	N/A	1:1	right	0.042	1.009	0.042	
1907.60	9538	UMTS 1900	RMC	21.0	20.96	0.06	10 mm	N/A	0E339	N/A	1:1	left	0.069	1.009	0.070	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 80 of 107

Table 11-25
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	-0.04	0	0E302	QPSK	1	49	10 mm	back	1:1	0.192	1.138	0.218	A28
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	-0.02	1	0E302	QPSK	25	25	10 mm	back	1:1	0.148	1.148	0.170	
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	0.01	0	0E302	QPSK	1	49	10 mm	front	1:1	0.157	1.138	0.179	
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	0.02	1	0E302	QPSK	25	25	10 mm	front	1:1	0.120	1.148	0.138	
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	-0.03	0	0E302	QPSK	1	49	10 mm	bottom	1:1	0.104	1.138	0.118	
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	-0.01	1	0E302	QPSK	25	25	10 mm	bottom	1:1	0.081	1.148	0.093	
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	0.01	0	0E302	QPSK	1	49	10 mm	right	1:1	0.158	1.138	0.180	
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	0.01	1	0E302	QPSK	25	25	10 mm	right	1:1	0.123	1.148	0.141	
707.50	23095	Mid	LTE Band 12	10	23.5	22.94	-0.01	0	0E302	QPSK	1	49	10 mm	left	1:1	0.098	1.138	0.112	
707.50	23095	Mid	LTE Band 12	10	22.5	21.90	0.01	1	0E302	QPSK	25	25	10 mm	left	1:1	0.074	1.148	0.085	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-26
LTE Band 13 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	-0.07	0	0E2D1	QPSK	1	49	10 mm	back	1:1	0.350	1.233	0.432	A30
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	0.00	1	0E2D1	QPSK	25	25	10 mm	back	1:1	0.273	1.205	0.329	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	0.00	0	0E2D1	QPSK	1	49	10 mm	front	1:1	0.291	1.233	0.359	
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	0.04	1	0E2D1	QPSK	25	25	10 mm	front	1:1	0.228	1.205	0.275	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	-0.05	0	0E2D1	QPSK	1	49	10 mm	bottom	1:1	0.170	1.233	0.210	
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	-0.03	1	0E2D1	QPSK	25	25	10 mm	bottom	1:1	0.133	1.205	0.160	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	0.08	0	0E2D1	QPSK	1	49	10 mm	right	1:1	0.262	1.233	0.323	
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	0.02	1	0E2D1	QPSK	25	25	10 mm	right	1:1	0.195	1.205	0.235	
782.00	23230	Mid	LTE Band 13	10	23.5	22.59	0.00	0	0E2D1	QPSK	1	49	10 mm	left	1:1	0.184	1.233	0.227	
782.00	23230	Mid	LTE Band 13	10	22.5	21.69	0.00	1	0E2D1	QPSK	25	25	10 mm	left	1:1	0.141	1.205	0.170	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 81 of 107

Table 11-27
LTE Band 26 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	-0.04	0	0E302	QPSK	1	36	10 mm	back	1:1	0.385	1.175	0.452	A32
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	-0.05	1	0E302	QPSK	36	18	10 mm	back	1:1	0.311	1.167	0.363	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	0.00	0	0E302	QPSK	1	36	10 mm	front	1:1	0.328	1.175	0.385	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	-0.02	1	0E302	QPSK	36	18	10 mm	front	1:1	0.263	1.167	0.307	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	-0.06	0	0E302	QPSK	1	36	10 mm	bottom	1:1	0.243	1.175	0.286	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	-0.04	1	0E302	QPSK	36	18	10 mm	bottom	1:1	0.197	1.167	0.230	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	-0.01	0	0E302	QPSK	1	36	10 mm	right	1:1	0.263	1.175	0.309	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	-0.01	1	0E302	QPSK	36	18	10 mm	right	1:1	0.212	1.167	0.247	
831.50	26865	Mid	LTE Band 26 (Cell)	15	23.5	22.80	0.06	0	0E302	QPSK	1	36	10 mm	left	1:1	0.056	1.175	0.066	
831.50	26865	Mid	LTE Band 26 (Cell)	15	22.5	21.83	-0.02	1	0E302	QPSK	36	18	10 mm	left	1:1	0.045	1.167	0.053	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-28
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Ant State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	-0.10	0	13	0E30E	QPSK	1	25	10 mm	back	1:1	0.496	1.186	0.588	A34
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	-0.12	1	13	0E30E	QPSK	25	12	10 mm	back	1:1	0.375	1.167	0.438	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	0.02	0	13	0E30E	QPSK	1	25	10 mm	front	1:1	0.478	1.186	0.567	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	0.02	1	13	0E30E	QPSK	25	12	10 mm	front	1:1	0.348	1.167	0.406	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	-0.06	0	13	0E30E	QPSK	1	25	10 mm	bottom	1:1	0.354	1.186	0.420	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	-0.09	1	13	0E30E	QPSK	25	12	10 mm	bottom	1:1	0.253	1.167	0.295	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	-0.11	0	13	0E30E	QPSK	1	25	10 mm	right	1:1	0.331	1.186	0.393	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	0.01	1	13	0E30E	QPSK	25	12	10 mm	right	1:1	0.244	1.167	0.285	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	23.76	-0.10	0	13	0E30E	QPSK	1	25	10 mm	left	1:1	0.086	1.186	0.102	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.83	0.00	1	13	0E30E	QPSK	25	12	10 mm	left	1:1	0.062	1.167	0.072	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram												

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 82 of 107

Table 11-29
LTE Band 66 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.71	0.03	0	0E30E	QPSK	1	99	10 mm	back	1:1	0.574	1.069	0.614	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.65	-0.03	0	0E30E	QPSK	50	50	10 mm	back	1:1	0.572	1.084	0.620	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.71	0.05	0	0E30E	QPSK	1	99	10 mm	front	1:1	0.482	1.069	0.515	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.65	0.02	0	0E30E	QPSK	50	50	10 mm	front	1:1	0.476	1.084	0.516	
1720.00	132072	Low	LTE Band 66 (AWS)	20	21.0	20.45	-0.04	0	0E30E	QPSK	1	99	10 mm	bottom	1:1	0.656	1.135	0.745	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.71	-0.02	0	0E30E	QPSK	1	99	10 mm	bottom	1:1	0.907	1.069	0.970	
1770.00	132572	High	LTE Band 66 (AWS)	20	21.0	20.36	-0.05	0	0E30E	QPSK	1	99	10 mm	bottom	1:1	0.895	1.159	1.037	
1720.00	132072	Low	LTE Band 66 (AWS)	20	21.0	20.42	-0.01	0	0E30E	QPSK	50	25	10 mm	bottom	1:1	0.827	1.143	0.945	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.65	-0.02	0	0E30E	QPSK	50	50	10 mm	bottom	1:1	0.840	1.084	0.911	
1770.00	132572	High	LTE Band 66 (AWS)	20	21.0	20.47	0.01	0	0E30E	QPSK	50	25	10 mm	bottom	1:1	0.871	1.130	0.984	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.64	-0.01	0	0E30E	QPSK	100	0	10 mm	bottom	1:1	0.828	1.086	0.899	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.71	0.12	0	0E30E	QPSK	1	99	10 mm	right	1:1	0.074	1.069	0.079	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.65	0.02	0	0E30E	QPSK	50	50	10 mm	right	1:1	0.074	1.084	0.080	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.71	-0.06	0	0E30E	QPSK	1	99	10 mm	left	1:1	0.150	1.069	0.160	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.65	0.00	0	0E30E	QPSK	50	50	10 mm	left	1:1	0.144	1.084	0.156	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	21.0	20.71	-0.05	0	0E30E	QPSK	1	99	10 mm	bottom	1:1	0.943	1.069	1.008	A36
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry represents variability measurement.

Table 11-30
LTE Band 25 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	0.08	0	0E339	QPSK	1	50	10 mm	back	1:1	0.376	1.180	0.444	
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	-0.05	0	0E339	QPSK	50	25	10 mm	back	1:1	0.392	1.180	0.463	
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	0.00	0	0E339	QPSK	1	50	10 mm	front	1:1	0.310	1.180	0.366	
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	0.04	0	0E339	QPSK	50	25	10 mm	front	1:1	0.318	1.180	0.375	
1860.00	26140	Low	LTE Band 25 (PCS)	20	20.5	19.27	0.00	0	0E339	QPSK	1	50	10 mm	bottom	1:1	0.435	1.327	0.577	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	20.5	19.37	-0.08	0	0E339	QPSK	1	99	10 mm	bottom	1:1	0.567	1.297	0.735	
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	0.07	0	0E339	QPSK	1	50	10 mm	bottom	1:1	0.569	1.180	0.671	A38
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	-0.03	0	0E339	QPSK	50	25	10 mm	bottom	1:1	0.564	1.180	0.666	
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	0.17	0	0E339	QPSK	1	50	10 mm	right	1:1	0.031	1.180	0.037	
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	0.01	0	0E339	QPSK	50	25	10 mm	right	1:1	0.035	1.180	0.041	
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	-0.01	0	0E339	QPSK	1	50	10 mm	left	1:1	0.054	1.180	0.064	
1905.00	26590	High	LTE Band 25 (PCS)	20	20.5	19.78	0.05	0	0E339	QPSK	50	25	10 mm	left	1:1	0.059	1.180	0.070	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 83 of 107

Table 11-31
LTE Band 7 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
2510.00	20850	Low	LTE Band 7	20	21.5	21.36	0.06	0	0E30E	QPSK	1	99	10 mm	back	1:1	0.403	1.033	0.416	
2510.00	20850	Low	LTE Band 7	20	20.5	19.73	-0.07	1	0E30E	QPSK	50	25	10 mm	back	1:1	0.292	1.194	0.349	
2510.00	20850	Low	LTE Band 7	20	21.5	21.36	0.04	0	0E30E	QPSK	1	99	10 mm	front	1:1	0.464	1.033	0.479	
2510.00	20850	Low	LTE Band 7	20	20.5	19.73	0.01	1	0E30E	QPSK	50	25	10 mm	front	1:1	0.316	1.194	0.377	
2510.00	20850	Low	LTE Band 7	20	21.5	21.36	-0.01	0	0E30E	QPSK	1	99	10 mm	bottom	1:1	0.774	1.033	0.800	
2535.00	21100	Mid	LTE Band 7	20	21.5	21.02	-0.01	0	0E30E	QPSK	1	99	10 mm	bottom	1:1	0.766	1.117	0.856	
2560.00	21350	High	LTE Band 7	20	21.5	20.78	-0.01	0	0E30E	QPSK	1	99	10 mm	bottom	1:1	0.810	1.180	0.956	A40
2510.00	20850	Low	LTE Band 7	20	20.5	19.73	-0.03	1	0E30E	QPSK	50	25	10 mm	bottom	1:1	0.542	1.194	0.647	
2510.00	20850	Low	LTE Band 7	20	20.5	19.69	-0.05	1	0E30E	QPSK	100	0	10 mm	bottom	1:1	0.540	1.205	0.651	
2510.00	20850	Low	LTE Band 7	20	21.5	21.36	0.06	0	0E30E	QPSK	1	99	10 mm	right	1:1	0.123	1.033	0.127	
2510.00	20850	Low	LTE Band 7	20	20.5	19.73	0.02	1	0E30E	QPSK	50	25	10 mm	right	1:1	0.081	1.194	0.097	
2510.00	20850	Low	LTE Band 7	20	21.5	21.36	-0.03	0	0E30E	QPSK	1	99	10 mm	left	1:1	0.224	1.033	0.231	
2510.00	20850	Low	LTE Band 7	20	20.5	19.73	0.00	1	0E30E	QPSK	50	25	10 mm	left	1:1	0.157	1.194	0.187	
2560.00	21350	High	LTE Band 7	20	21.5	20.78	-0.13	0	0E30E	QPSK	1	99	10 mm	bottom	1:1	0.810	1.180	0.956	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry represents variability measurement.

Table 11-32
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	-0.01	0	0E30E	QPSK	1	99	10 mm	back	1:1.58	0.348	1.035	0.360	
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	-0.02	1	0E30E	QPSK	50	25	10 mm	back	1:1.58	0.272	1.050	0.286	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	0.02	0	0E30E	QPSK	1	99	10 mm	front	1:1.58	0.318	1.035	0.329	
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	0.02	1	0E30E	QPSK	50	25	10 mm	front	1:1.58	0.248	1.050	0.260	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	-0.10	0	0E30E	QPSK	1	99	10 mm	bottom	1:1.58	0.576	1.035	0.596	A42
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	-0.07	1	0E30E	QPSK	50	25	10 mm	bottom	1:1.58	0.441	1.050	0.463	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	0.01	0	0E30E	QPSK	1	99	10 mm	right	1:1.58	0.119	1.035	0.123	
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	0.10	1	0E30E	QPSK	50	25	10 mm	right	1:1.58	0.094	1.050	0.099	
2506.00	39750	Low	LTE Band 41	20	23.5	23.35	-0.11	0	0E30E	QPSK	1	99	10 mm	left	1:1.58	0.148	1.035	0.153	
2506.00	39750	Low	LTE Band 41	20	22.5	22.29	-0.13	1	0E30E	QPSK	50	25	10 mm	left	1:1.58	0.116	1.050	0.122	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 84 of 107

Table 11-33
WLAN Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	18.5	17.74	0.06	10 mm	1	0E339	1	back	99.9	0.090	0.076	1.191	1.001	0.091	
2412	1	802.11b	DSSS	22	18.5	17.74	0.19	10 mm	1	0E339	1	front	99.9	0.025	-	1.191	1.001	-	
2412	1	802.11b	DSSS	22	18.5	17.74	0.17	10 mm	1	0E339	1	top	99.9	0.060	-	1.191	1.001	-	
2412	1	802.11b	DSSS	22	18.5	17.74	-0.13	10 mm	1	0E339	1	left	99.9	0.020	-	1.191	1.001	-	
2437	6	802.11b	DSSS	22	18.5	18.26	0.10	10 mm	2	0E339	1	back	99.9	0.359	-	1.057	1.001	-	
2437	6	802.11b	DSSS	22	18.5	18.26	0.06	10 mm	2	0E339	1	front	99.9	0.277	-	1.057	1.001	-	
2437	6	802.11b	DSSS	22	18.5	18.26	0.02	10 mm	2	0E339	1	top	99.9	0.449	0.355	1.057	1.001	0.376	A44
2437	6	802.11b	DSSS	22	18.5	18.26	0.19	10 mm	2	0E339	1	left	99.9	0.176	-	1.057	1.001	-	
5745	149	802.11a	OFDM	20	17.5	16.81	-0.06	10 mm	1	0E2D1	6	back	98.6	0.577	0.252	1.172	1.014	0.299	
5745	149	802.11a	OFDM	20	17.5	16.81	0.00	10 mm	1	0E2D1	6	front	98.6	0.022	-	1.172	1.014	-	
5745	149	802.11a	OFDM	20	17.5	16.81	0.20	10 mm	1	0E2D1	6	top	98.6	0.200	-	1.172	1.014	-	
5745	149	802.11a	OFDM	20	17.5	16.81	0.00	10 mm	1	0E2D1	6	left	98.6	0.045	-	1.172	1.014	-	
5745	149	802.11a	OFDM	20	17.5	17.20	0.08	10 mm	2	0E2D1	6	back	98.6	0.909	0.352	1.072	1.014	0.383	
5745	149	802.11a	OFDM	20	17.5	17.20	-0.15	10 mm	2	0E2D1	6	front	98.6	0.052	-	1.072	1.014	-	
5745	149	802.11a	OFDM	20	17.5	17.20	0.13	10 mm	2	0E2D1	6	top	98.6	0.080	-	1.072	1.014	-	
5745	149	802.11a	OFDM	20	17.5	17.20	0.17	10 mm	2	0E2D1	6	left	98.6	0.150	-	1.072	1.014	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

Table 11-34
WLAN MIMO Hotspot SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.															W/kg	(W/kg)			(W/kg)	
5745	149	802.11n	OFDM	20	17.5	16.74	17.5	17.11	0.12	10 mm	MIMO	0E2D1	13	back	96.6	1.296	0.497	1.191	1.035	0.613	
5785	157	802.11n	OFDM	20	17.5	16.79	17.5	17.04	-0.10	10 mm	MIMO	0E2D1	13	back	96.6	1.585	0.596	1.178	1.035	0.727	
5825	165	802.11n	OFDM	20	17.5	16.69	17.5	17.01	0.02	10 mm	MIMO	0E2D1	13	back	96.6	1.416	0.618	1.205	1.035	0.771	A46
5745	149	802.11n	OFDM	20	17.5	16.74	17.5	17.11	0.19	10 mm	MIMO	0E2D1	13	front	96.6	0.049	-	1.191	1.035	-	
5745	149	802.11n	OFDM	20	17.5	16.74	17.5	17.11	0.17	10 mm	MIMO	0E2D1	13	top	96.6	0.219	0.083	1.191	1.035	0.102	
5745	149	802.11n	OFDM	20	17.5	16.74	17.5	17.11	0.15	10 mm	MIMO	0E2D1	13	left	96.6	0.129	-	1.191	1.035	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body											
Spatial Peak										1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population										averaged over 1 gram											

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 85 of 107

Table 11-35
MIMO Hotspot SAR for Conditions with 2.4 GHz and 5 GHz WLAN SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.															W/kg	(W/kg)			(W/kg)	
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	0.17	10 mm	MIMO	0E339	13	back	99.0	0.075	-	1.146	1.010	-	
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	-0.04	10 mm	MIMO	0E339	13	front	99.0	0.058	-	1.146	1.010	-	
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	0.03	10 mm	MIMO	0E339	13	top	99.0	0.091	0.074	1.146	1.010	0.086	
2462	11	802.11n	OFDM	20	13.5	12.91	13.5	13.35	-0.19	10 mm	MIMO	0E339	13	left	99.0	0.034	-	1.146	1.010	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	13.5	13.46	0.05	10 mm	MIMO	0E2D1	58.5	back	88.8	0.444	0.240	1.009	1.126	0.273	
5775	155	802.11ac	OFDM	80	13.5	13.46	13.5	13.46	0.00	10 mm	MIMO	0E2D1	58.5	front	88.8	0.018	-	1.009	1.126	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	13.5	13.46	0.19	10 mm	MIMO	0E2D1	58.5	top	88.8	0.098	-	1.009	1.126	-	
5775	155	802.11ac	OFDM	80	13.5	13.46	13.5	13.46	0.14	10 mm	MIMO	0E2D1	58.5	left	88.8	0.053	-	1.009	1.126	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																					
Spatial Peak										Body											
Uncontrolled Exposure/General Population										1.6 W/kg (mW/g)											
										averaged over 1 gram											

Note: DTS and NII MIMO were additionally evaluated at the maximum allowed output power during operations with Simultaneous 2.4 GHz and 5 GHz WLAN. 5 GHz WLAN was not transmitting during 2.4 GHz WLAN evaluations, and 2.4 GHz WLAN was not transmitting during 5 GHz WLAN evaluations.

Table 11-36
DSS Hotspot SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441	39	Bluetooth	FHSS	15.0	14.96	-0.17	10 mm	0E339	1	back	77.3	0.073	1.009	1.294	0.095	
2441	39	Bluetooth	FHSS	15.0	14.96	-0.09	10 mm	0E339	1	front	77.3	0.061	1.009	1.294	0.080	
2441	39	Bluetooth	FHSS	15.0	14.96	-0.19	10 mm	0E339	1	top	77.3	0.092	1.009	1.294	0.120	A48
2441	39	Bluetooth	FHSS	15.0	14.96	-0.03	10 mm	0E339	1	left	77.3	0.036	1.009	1.294	0.047	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

11.4 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 86 of 107

9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. This device supports dynamic antenna tuning for some bands. Per FCC Guidance, SAR was measured according to the normally required SAR measurement configurations with tuner active. The auto-tune state determined by the device was verified before and after each SAR measurement and is listed in tables above. Please see Section 14 for supplemental data.
11. This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported (scaled) for LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg for 1g evaluations, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 87 of 107

- Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

WLAN Notes:

- For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g evaluations, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.
- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 8.6.6 for more information.
- Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06 by either evaluating the sum of the 1g SAR values of each antenna transmitting independently or making a SAR measurement with both antennas transmitting simultaneously. Please see Section 12 for complete analysis.
- When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
- The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

- Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9.5 for the time domain plot and calculation for the duty factor of the device.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 88 of 107

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.236	0.167	0.998	0.403	1.234	1.401
	UMTS 850	0.257	0.167	0.998	0.424	1.255	1.422
	UMTS 1750	0.160	0.167	0.998	0.327	1.158	1.325
	GSM 1900	0.085	0.167	0.998	0.252	1.083	1.250
	UMTS 1900	0.131	0.167	0.998	0.298	1.129	1.296
	LTE Band 12	0.074	0.167	0.998	0.241	1.072	1.239
	LTE Band 13	0.159	0.167	0.998	0.326	1.157	1.324
	LTE Band 26 (Cell)	0.161	0.167	0.998	0.328	1.159	1.326
	LTE Band 5 (Cell)	0.193	0.167	0.998	0.360	1.191	1.358
	LTE Band 66 (AWS)	0.237	0.167	0.998	0.404	1.235	1.402
	LTE Band 25 (PCS)	0.145	0.167	0.998	0.312	1.143	1.310
	LTE Band 7	0.183	0.167	0.998	0.350	1.181	1.348
	LTE Band 41	0.072	0.167	0.998	0.239	1.070	1.237

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 89 of 107

Table 12-2
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.236	0.070	0.220	0.306	0.456	0.526
	UMTS 850	0.257	0.070	0.220	0.327	0.477	0.547
	UMTS 1750	0.160	0.070	0.220	0.230	0.380	0.450
	GSM 1900	0.085	0.070	0.220	0.155	0.305	0.375
	UMTS 1900	0.131	0.070	0.220	0.201	0.351	0.421
	LTE Band 12	0.074	0.070	0.220	0.144	0.294	0.364
	LTE Band 13	0.159	0.070	0.220	0.229	0.379	0.449
	LTE Band 26 (Cell)	0.161	0.070	0.220	0.231	0.381	0.451
	LTE Band 5 (Cell)	0.193	0.070	0.220	0.263	0.413	0.483
	LTE Band 66 (AWS)	0.237	0.070	0.220	0.307	0.457	0.527
	LTE Band 25 (PCS)	0.145	0.070	0.220	0.215	0.365	0.435
	LTE Band 7	0.183	0.070	0.220	0.253	0.403	0.473
	LTE Band 41	0.072	0.070	0.220	0.142	0.292	0.362

Table 12-3
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO and 5 GHz WLAN MIMO (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN MIMO at 13 dBm SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			
		1	2	3	4	1+2	1+3	1+2+3	1+2+3+4
Head SAR	GSM 850	0.236	0.307	0.070	0.220	0.543	0.306	0.613	0.833
	UMTS 850	0.257	0.307	0.070	0.220	0.564	0.327	0.634	0.854
	UMTS 1750	0.160	0.307	0.070	0.220	0.467	0.230	0.537	0.757
	GSM 1900	0.085	0.307	0.070	0.220	0.392	0.155	0.462	0.682
	UMTS 1900	0.131	0.307	0.070	0.220	0.438	0.201	0.508	0.728
	LTE Band 12	0.074	0.307	0.070	0.220	0.381	0.144	0.451	0.671
	LTE Band 13	0.159	0.307	0.070	0.220	0.466	0.229	0.536	0.756
	LTE Band 26 (Cell)	0.161	0.307	0.070	0.220	0.468	0.231	0.538	0.758
	LTE Band 5 (Cell)	0.193	0.307	0.070	0.220	0.500	0.263	0.570	0.790
	LTE Band 66 (AWS)	0.237	0.307	0.070	0.220	0.544	0.307	0.614	0.834
	LTE Band 25 (PCS)	0.145	0.307	0.070	0.220	0.452	0.215	0.522	0.742
	LTE Band 7	0.183	0.307	0.070	0.220	0.490	0.253	0.560	0.780
	LTE Band 41	0.072	0.307	0.070	0.220	0.379	0.142	0.449	0.669

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 90 of 107

Table 12-4
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM 850	0.236	0.636	0.872
	UMTS 850	0.257	0.636	0.893
	UMTS 1750	0.160	0.636	0.796
	GSM 1900	0.085	0.636	0.721
	UMTS 1900	0.131	0.636	0.767
	LTE Band 12	0.074	0.636	0.710
	LTE Band 13	0.159	0.636	0.795
	LTE Band 26 (Cell)	0.161	0.636	0.797
	LTE Band 5 (Cell)	0.193	0.636	0.829
	LTE Band 66 (AWS)	0.237	0.636	0.873
	LTE Band 25 (PCS)	0.145	0.636	0.781
	LTE Band 7	0.183	0.636	0.819
	LTE Band 41	0.072	0.636	0.708

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 91 of 107

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.363	0.035	0.135	0.398	0.498	0.533
	UMTS 850	0.443	0.035	0.135	0.478	0.578	0.613
	UMTS 1750	0.567	0.035	0.135	0.602	0.702	0.737
	GSM 1900	0.312	0.035	0.135	0.347	0.447	0.482
	UMTS 1900	0.508	0.035	0.135	0.543	0.643	0.678
	LTE Band 12	0.154	0.035	0.135	0.189	0.289	0.324
	LTE Band 13	0.303	0.035	0.135	0.338	0.438	0.473
	LTE Band 26 (Cell)	0.266	0.035	0.135	0.301	0.401	0.436
	LTE Band 5 (Cell)	0.351	0.035	0.135	0.386	0.486	0.521
	LTE Band 66 (AWS)	0.995	0.035	0.135	1.030	1.130	1.165
	LTE Band 25 (PCS)	0.465	0.035	0.135	0.500	0.600	0.635
	LTE Band 7	0.848	0.035	0.135	0.883	0.983	1.018
	LTE Band 41	0.223	0.035	0.135	0.258	0.358	0.393

Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.363	0.242	0.211	0.605	0.574	0.816
	UMTS 850	0.443	0.242	0.211	0.685	0.654	0.896
	UMTS 1750	0.567	0.242	0.211	0.809	0.778	1.020
	GSM 1900	0.312	0.242	0.211	0.554	0.523	0.765
	UMTS 1900	0.508	0.242	0.211	0.750	0.719	0.961
	LTE Band 12	0.154	0.242	0.211	0.396	0.365	0.607
	LTE Band 13	0.303	0.242	0.211	0.545	0.514	0.756
	LTE Band 26 (Cell)	0.266	0.242	0.211	0.508	0.477	0.719
	LTE Band 5 (Cell)	0.351	0.242	0.211	0.593	0.562	0.804
	LTE Band 66 (AWS)	0.995	0.242	0.211	1.237	1.206	1.448
	LTE Band 25 (PCS)	0.465	0.242	0.211	0.707	0.676	0.918
	LTE Band 7	0.848	0.242	0.211	1.090	1.059	1.301
	LTE Band 41	0.223	0.242	0.211	0.465	0.434	0.676

FCC ID: A3LSMG960F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 92 of 107

Table 12-7
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO and 5 GHz WLAN MIMO (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN MIMO at 13 dBm SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	4	1+2+3+4
Body-Worn	GSM 850	0.363	0.028	0.242	0.211	0.844
	UMTS 850	0.443	0.028	0.242	0.211	0.924
	UMTS 1750	0.567	0.028	0.242	0.211	1.048
	GSM 1900	0.312	0.028	0.242	0.211	0.793
	UMTS 1900	0.508	0.028	0.242	0.211	0.989
	LTE Band 12	0.154	0.028	0.242	0.211	0.635
	LTE Band 13	0.303	0.028	0.242	0.211	0.784
	LTE Band 26 (Cell)	0.266	0.028	0.242	0.211	0.747
	LTE Band 5 (Cell)	0.351	0.028	0.242	0.211	0.832
	LTE Band 66 (AWS)	0.995	0.028	0.242	0.211	1.476
	LTE Band 25 (PCS)	0.465	0.028	0.242	0.211	0.946
	LTE Band 7	0.848	0.028	0.242	0.211	1.329
	LTE Band 41	0.223	0.028	0.242	0.211	0.704

Table 12-8
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 850	0.363	0.047	0.410
	UMTS 850	0.443	0.047	0.490
	UMTS 1750	0.567	0.047	0.614
	GSM 1900	0.312	0.047	0.359
	UMTS 1900	0.508	0.047	0.555
	LTE Band 12	0.154	0.047	0.201
	LTE Band 13	0.303	0.047	0.350
	LTE Band 26 (Cell)	0.266	0.047	0.313
	LTE Band 5 (Cell)	0.351	0.047	0.398
	LTE Band 66 (AWS)	0.995	0.047	1.042
	LTE Band 25 (PCS)	0.465	0.047	0.512
	LTE Band 7	0.848	0.047	0.895
	LTE Band 41	0.223	0.047	0.270

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 93 of 107

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for applicable exposure conditions was used for simultaneous transmission analysis.

Table 12-9
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.956	0.091	0.376	1.047	1.332	1.423
	UMTS 850	0.766	0.091	0.376	0.857	1.142	1.233
	UMTS 1750	0.986	0.091	0.376	1.077	1.362	1.453
	GPRS 1900	0.788	0.091	0.376	0.879	1.164	1.255
	UMTS 1900	0.585	0.091	0.376	0.676	0.961	1.052
	LTE Band 12	0.218	0.091	0.376	0.309	0.594	0.685
	LTE Band 13	0.432	0.091	0.376	0.523	0.808	0.899
	LTE Band 26 (Cell)	0.452	0.091	0.376	0.543	0.828	0.919
	LTE Band 5 (Cell)	0.588	0.091	0.376	0.679	0.964	1.055
	LTE Band 66 (AWS)	1.037	0.091	0.376	1.128	1.413	1.504
	LTE Band 25 (PCS)	0.735	0.091	0.376	0.826	1.111	1.202
	LTE Band 7	0.956	0.091	0.376	1.047	1.332	1.423
	LTE Band 41	0.596	0.091	0.376	0.687	0.972	1.063

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 94 of 107

Table 12-10
Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 1 (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.956	0.299	1.255
	UMTS 850	0.766	0.299	1.065
	UMTS 1750	0.986	0.299	1.285
	GPRS 1900	0.788	0.299	1.087
	UMTS 1900	0.585	0.299	0.884
	LTE Band 12	0.218	0.299	0.517
	LTE Band 13	0.432	0.299	0.731
	LTE Band 26 (Cell)	0.452	0.299	0.751
	LTE Band 5 (Cell)	0.588	0.299	0.887
	LTE Band 66 (AWS)	1.037	0.299	1.336
	LTE Band 25 (PCS)	0.735	0.299	1.034
	LTE Band 7	0.956	0.299	1.255
	LTE Band 41	0.596	0.299	0.895

Table 12-11
Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 2 (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.956	0.383	1.339
	UMTS 850	0.766	0.383	1.149
	UMTS 1750	0.986	0.383	1.369
	GPRS 1900	0.788	0.383	1.171
	UMTS 1900	0.585	0.383	0.968
	LTE Band 12	0.218	0.383	0.601
	LTE Band 13	0.432	0.383	0.815
	LTE Band 26 (Cell)	0.452	0.383	0.835
	LTE Band 5 (Cell)	0.588	0.383	0.971
	LTE Band 66 (AWS)	1.037	0.383	1.420
	LTE Band 25 (PCS)	0.735	0.383	1.118
	LTE Band 7	0.956	0.383	1.339
	LTE Band 41	0.596	0.383	0.979

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 95 of 107

Table 12-12
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN MIMO at 17 dBm SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.956	0.771	See Table Below
	UMTS 850	0.766	0.771	1.537
	UMTS 1750	0.986	0.771	See Table Below
	GPRS 1900	0.788	0.771	1.559
	UMTS 1900	0.585	0.771	1.356
	LTE Band 12	0.218	0.771	0.989
	LTE Band 13	0.432	0.771	1.203
	LTE Band 26 (Cell)	0.452	0.771	1.223
	LTE Band 5 (Cell)	0.588	0.771	1.359
	LTE Band 66 (AWS)	1.037	0.771	See Table Below
	LTE Band 25 (PCS)	0.735	0.771	1.506
	LTE Band 7	0.956	0.771	See Table Below
	LTE Band 41	0.596	0.771	1.367

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	5 GHz WLAN MIMO at 17 dBm SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Hotspot SAR	Back	0.956	0.771	See Note 1	0.02
	Front	0.735	0.771*	1.506	N/A
	Top	-	0.102	0.102	N/A
	Bottom	0.597	-	0.597	N/A
	Right	0.636	-	0.636	N/A
	Left	0.158	0.771*	0.929	N/A

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN MIMO at 17 dBm SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	Back	0.580	0.771	1.351
	Front	0.462	0.771*	1.233
	Top	-	0.102	0.102
	Bottom	0.986	-	0.986
	Right	0.089	-	0.089
	Left	0.107	0.771*	0.878

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	5 GHz WLAN MIMO at 17 dBm SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	Back	0.620	0.771	1.391
	Front	0.516	0.771*	1.287
	Top	-	0.102	0.102
	Bottom	1.037	-	1.037
	Right	0.080	-	0.080
	Left	0.160	0.771*	0.931

Simult Tx	Configuration	LTE Band 7 SAR (W/kg)	5 GHz WLAN MIMO at 17 dBm SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	Back	0.416	0.771	1.187
	Front	0.479	0.771*	1.250
	Top	-	0.102	0.102
	Bottom	0.956	-	0.956
	Right	0.127	-	0.127
	Left	0.231	0.771*	1.002

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset	Page 96 of 107	

Table 12-13
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO and 5 GHz WLAN MIMO
(Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN MIMO at 13 dBm SAR (W/kg)	5 GHz WLAN MIMO at 13 dBm SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Hotspot SAR	GPRS 850	0.956	0.086	0.273	1.315
	UMTS 850	0.766	0.086	0.273	1.125
	UMTS 1750	0.986	0.086	0.273	1.345
	GPRS 1900	0.788	0.086	0.273	1.147
	UMTS 1900	0.585	0.086	0.273	0.944
	LTE Band 12	0.218	0.086	0.273	0.577
	LTE Band 13	0.432	0.086	0.273	0.791
	LTE Band 26 (Cell)	0.452	0.086	0.273	0.811
	LTE Band 5 (Cell)	0.588	0.086	0.273	0.947
	LTE Band 66 (AWS)	1.037	0.086	0.273	1.396
	LTE Band 25 (PCS)	0.735	0.086	0.273	1.094
	LTE Band 7	0.956	0.086	0.273	1.315
	LTE Band 41	0.596	0.086	0.273	0.955

Table 12-14
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.956	0.120	1.076
	UMTS 850	0.766	0.120	0.886
	UMTS 1750	0.986	0.120	1.106
	GPRS 1900	0.788	0.120	0.908
	UMTS 1900	0.585	0.120	0.705
	LTE Band 12	0.218	0.120	0.338
	LTE Band 13	0.432	0.120	0.552
	LTE Band 26 (Cell)	0.452	0.120	0.572
	LTE Band 5 (Cell)	0.588	0.120	0.708
	LTE Band 66 (AWS)	1.037	0.120	1.157
	LTE Band 25 (PCS)	0.735	0.120	0.855
	LTE Band 7	0.956	0.120	1.076
	LTE Band 41	0.596	0.120	0.716

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 97 of 107

12.6 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more 1.6 W/kg for 1g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 for 1g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

12.6.1 Back Side SPLSR Evaluation and Analysis


Table 12-15
Peak SAR Locations for Body Back Side (Body at 1.0 cm)

Mode/Band	x (mm)	y (mm)	Reported SAR (W/kg)
5 GHz WLAN MIMO	3.00	64.00	0.771
GPRS 850	-15.50	-75.00	0.956

Table 12-16
Back Side SAR to Peak Location Separation Ratio Calculations (Body at 1.0 cm)

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}	
5 GHz WLAN MIMO	GPRS 850	0.771	0.956	1.727	140.23	0.02	1

Table 12-17
Back Side SAR to Peak Location Separation Ratio Plots (Body at 1.0 cm)



FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 98 of 107

12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 99 of 107

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Head SAR Measurement Variability Results

HEAD VARIABILITY RESULTS														
Band	FREQUENCY		Mode/Band	Service	Side	Test Position	Data Rate (Mbps)	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)		(W/kg)	
2450	2437.00	6	802.11b, 22 MHz Bandwidth	DSSS , ANT 2	Right	Cheek	1	0.818	0.886	1.08	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Head 1.6 W/kg (mW/g) averaged over 1 gram								

Table 13-2
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1745.00	132322	LTE Band 66 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 99 RB Offset	bottom	10 mm	0.907	0.943	1.04	N/A	N/A	N/A	N/A
2600	2560.00	21350	LTE Band 7, 20 MHz Bandwidth	QPSK, 1 RB, 99 RB Offset	bottom	10 mm	0.810	0.810	1.00	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 100 of 107

14 ADDITIONAL TESTING PER FCC GUIDANCE

14.1 Tuner Testing

The following test procedures were followed to demonstrate that the SAR results in Section 11 represented the appropriate SAR test conditions. For bands with dynamic tuning implemented, SAR was measured according to the required FCC SAR test procedures with the dynamic tuner active to allow the device to automatically tune to the antenna state for the respective RF exposure test configurations. Additional single point SAR time-sweep measurements were evaluated for other tuner states to determine that the other tuner configurations would result in equivalent or lower SAR values. The additional tuner hardware has no influence to the antenna characteristics, other than impedance matching.

To evaluate all of the tuner states, the 25 tuner states were divided evenly among band, mode and exposure combinations so that at least one single point SAR measurement was measured among the configurations. Single point time-sweep measurements were performed at the peak SAR location determined by the zoom scan of the configuration with the highest reported SAR for each combination. While inserting and removing the USB cable between single point SAR measurements, the device was ensured to capture the same physical point SAR that generated the highest SAR. The SAR probe remained stationary at the same position throughout the entire series of single point measurements for each combination.

The operational description contains more information about the design and implementation of the dynamic antenna tuning.

**Table 14-1
Supplemental Head SAR Data**

Supplemental Head SAR Data			
LTE Band 5		UMTS 850	
QPSK, 10MHz Bandwidth, 1 RB, 25 RB Offset		RMC	
Test Position	Right Cheek	Test Position	Right Cheek
Frequency (MHz)	836.5	Frequency (MHz)	836.6
Channel	20525	Channel	4183
Measured 1g SAR (W/kg)	0.163	Measured 1g SAR (W/kg)	0.21
Average Value of Time Sweep (W/kg)		Average Value of Time Sweep (W/kg)	
Auto-tune (State 13)	0.254	Auto-tune (State 13)	0.292
Default (State 13)	0.262	Default (State 13)	0.270
State 1	0.149	State 2	0.092
State 5	0.152	State 6	0.169
State 9	0.079	State 10	0.166
State 13	0.262	State 13	0.270
State 19	0.085	State 14	0.168
State 21	0.242	State 18	0.070
State 25	0.082	State 22	0.283

FCC ID: A3LSMG960F	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset
Page 101 of 107		

Table 14-2
Supplemental Body SAR Data

Supplemental Body SAR Data			
LTE Band 5		UMTS 850	
QPSK, 10MHz Bandwidth, 1 RB, 25 RB Offset		RMC	
Test Position	Back Side	Test Position	Back Side
Spacing	10 mm	Spacing	10 mm
Frequency (MHz)	836.5	Frequency (MHz)	846.6
Channel	20525	Channel	4233
Measured 1g SAR (W/kg)	0.496	Measured 1g SAR (W/kg)	0.624
Average Value of Time Sweep (W/kg)		Average Value of Time Sweep (W/kg)	
Auto-tune (State 13)	0.873	Auto-tune (State 13)	0.732
Default (State 13)	0.897	Default (State 13)	0.764
State 3	0.580	State 4	0.540
State 7	0.605	State 8	0.279
State 11	0.583	State 12	0.517
State 13	0.897	State 13	0.764
State 15	0.359	State 16	0.257
State 17	0.298	State 20	0.368
State 23	0.594	State 24	0.253

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 102 of 107

15 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/22/2017	Annual	3/22/2018	MY45470194
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433971
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433972
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-53W2	Attenuator (3dB)	CBT	N/A	CBT	120
Rohde & Schwarz	CMU200	Base Station Simulator	4/11/2017	Annual	4/11/2018	836371/0079
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/10/2017	Annual	5/10/2018	1070
Mitutoyo	CD-6"CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264165
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Agilent	E4438C	ESG Vector Signal Generator	3/21/2017	Biennial	3/21/2019	MY45090700
Agilent	E4432B	ESG-D Series Signal Generator	3/24/2017	Annual	3/24/2018	US40053896
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Agilent	N9020A	MXA Signal Analyzer	12/28/2016	Annual	12/28/2017	US46470561
Agilent	N5182A	MXG Vector Signal Generator	2/28/2017	Annual	2/28/2018	MY47420800
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Anritsu	ML2495A	Power Meter	10/22/2017	Annual	10/22/2018	941001
Anritsu	ML2496A	Power Meter	3/28/2017	Annual	3/28/2018	1351001
Anritsu	ML2496A	Power Meter	4/20/2017	Annual	4/20/2018	1306009
Anritsu	MA2411B	Pulse Power Sensor	2/10/2017	Annual	2/10/2018	1207364
Anritsu	MA2411B	Pulse Power Sensor	2/10/2017	Annual	2/10/2018	1339018
Anritsu	MT8820C	Radio Communication Analyzer	5/23/2017	Annual	5/23/2018	6201240328
Rohde & Schwarz	CMW500	Radio Communication Tester	5/4/2017	Annual	5/4/2018	112347
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Agilent	8753ES	S-Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/17/2017	Annual	8/17/2018	MY40003841
Control Company	4040	Therm./Clock/Humidity Monitor	3/31/2017	Biennial	3/31/2019	170232394
Pasternack	NC-100	Torque Wrench	3/8/2017	Annual	3/8/2018	N/A
Pasternack	NC-100	Torque Wrench	3/8/2017	Annual	3/8/2018	N/A
Seekonk	NC-100	Torque Wrench (8" lb)	8/30/2016	Biennial	8/30/2018	N/A
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Control Company	4352	Ultra Long Stem Thermometer	3/8/2016	Biennial	3/8/2018	160261694
Control Company	4352	Ultra Long Stem Thermometer	5/2/2017	Biennial	5/2/2019	170330147
Anritsu	MA24106A	USB Power Sensor	6/7/2017	Annual	6/7/2018	1231538
Anritsu	MA24106A	USB Power Sensor	6/7/2017	Annual	6/7/2018	1231535
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/20/2017	Annual	7/20/2018	132885
Agilent	E5515C	Wireless Communications Test Set	5/31/2017	Annual	5/31/2018	GB43304278
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB46170464
SPEAG	ES3DV3	SAR Probe	2/10/2017	Annual	2/10/2018	3213
SPEAG	ES3DV3	SAR Probe	3/14/2017	Annual	3/14/2018	3209
SPEAG	EX3DV4	SAR Probe	2/13/2017	Annual	2/13/2018	3914
SPEAG	ES3DV3	SAR Probe	3/14/2017	Annual	3/14/2018	3319
SPEAG	ES3DV3	SAR Probe	8/14/2017	Annual	8/14/2018	3332
SPEAG	EX3DV4	SAR Probe	8/16/2017	Annual	8/16/2018	7308
SPEAG	EX3DV4	SAR Probe	4/18/2017	Annual	4/18/2018	7406
SPEAG	EX3DV4	SAR Probe	7/17/2017	Annual	7/17/2018	7410
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2017	Annual	2/9/2018	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2017	Annual	2/9/2018	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/9/2017	Annual	8/9/2018	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/13/2017	Annual	7/13/2018	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/14/2017	Annual	6/14/2018	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/8/2017	Annual	3/8/2018	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/13/2017	Annual	3/13/2018	1415
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2017	Annual	4/11/2018	1407
SPEAG	D1750V2	1750 MHz SAR Dipole	5/9/2017	Annual	5/9/2018	1148
SPEAG	D1750V2	1750 MHz SAR Dipole	7/14/2016	Biennial	7/14/2018	1150
SPEAG	D1900V2	1900 MHz SAR Dipole	7/8/2016	Biennial	7/8/2018	56080
SPEAG	D2450V2	2450 MHz SAR Dipole	8/17/2017	Annual	8/17/2018	719
SPEAG	D2450V2	2450 MHz SAR Dipole	7/25/2016	Biennial	7/25/2018	981
SPEAG	D2600V2	2600 MHz SAR Dipole	6/7/2017	Annual	6/7/2018	1064
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/21/2016	Biennial	9/21/2018	1191
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/15/2017	Annual	8/15/2018	1237
SPEAG	D750V3	750 MHz SAR Dipole	1/11/2017	Annual	1/11/2018	1003
SPEAG	D835V2	835 MHz SAR Dipole	7/13/2016	Biennial	7/13/2018	46047
SPEAG	D835V2	835 MHz SAR Dipole	7/11/2017	Annual	7/11/2018	46133
SPEAG	D835V2	835 MHz SAR Dipole	1/11/2017	Annual	1/11/2018	46132

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements. Each equipment was used solely within its calibration period.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 103 of 107

16 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)						RSS	11.5	11.3
Expanded Uncertainty (95% CONFIDENCE LEVEL)						k=2	23.0	22.6

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 104 of 107

17 CONCLUSION

17.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 105 of 107

18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 106 of 107

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)

FCC ID: A3LSMG960F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1710020264-01.A3L	Test Dates: 10/20/17 - 11/15/17	DUT Type: Portable Handset		Page 107 of 107

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2DD

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6$ MHz; $\sigma = 0.907$ S/m; $\epsilon_r = 41.926$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 10-23-2017; Ambient Temp: 22.6°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7410; ConvF(10.08, 10.08, 10.08); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.87 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.277 W/kg

SAR(1 g) = 0.219 W/kg



0 dB = 0.252 W/kg = -5.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2DD

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.907 \text{ S/m}$; $\epsilon_r = 41.926$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 10-23-2017; Ambient Temp: 22.6°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7410; ConvF(10.08, 10.08, 10.08); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.27 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.258 W/kg

SAR(1 g) = 0.210 W/kg



0 dB = 0.240 W/kg = -6.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.366 \text{ S/m}$; $\epsilon_r = 39.862$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 10-23-2017; Ambient Temp: 22.7°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3209; ConvF(5.5, 5.5, 5.5); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.09 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.230 W/kg

SAR(1 g) = 0.151 W/kg



0 dB = 0.179 W/kg = -7.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, GSM; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1910$ MHz; $\sigma = 1.443$ S/m; $\epsilon_r = 39.603$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Test Date: 10-23-2017; Ambient Temp: 21.6°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3213; ConvF(5.29, 5.29, 5.29); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 1900, Left Head, Cheek, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.556 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.112 W/kg

SAR(1 g) = 0.073 W/kg



0 dB = 0.0866 W/kg = -10.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1907.6$ MHz; $\sigma = 1.441$ S/m; $\epsilon_r = 39.615$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Test Date: 10-23-2017; Ambient Temp: 21.6°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3213; ConvF(5.29, 5.29, 5.29); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Left Head, Cheek, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.430 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.176 W/kg

SAR(1 g) = 0.114 W/kg



0 dB = 0.135 W/kg = -8.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E302

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.857 \text{ S/m}$; $\epsilon_r = 41.258$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 10-23-2017; Ambient Temp: 23.4°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3213; ConvF(6.85, 6.85, 6.85); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.415 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.0820 W/kg

SAR(1 g) = 0.065 W/kg



0 dB = 0.0703 W/kg = -11.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.936 \text{ S/m}$; $\epsilon_r = 40.195$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 10-23-2017; Ambient Temp: 23.4°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3213; ConvF(6.85, 6.85, 6.85); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 13, Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.74 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.163 W/kg

SAR(1 g) = 0.129 W/kg



0 dB = 0.142 W/kg = -8.48 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2DD

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 831.5$ MHz; $\sigma = 0.903$ S/m; $\epsilon_r = 41.993$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 10-23-2017; Ambient Temp: 22.6°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7410; ConvF(10.08, 10.08, 10.08); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 26 (Cell.), Right Head, Cheek, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 36 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.82 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.162 W/kg

SAR(1 g) = 0.137 W/kg



0 dB = 0.153 W/kg = -8.15 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2DD

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5$ MHz; $\sigma = 0.907$ S/m; $\epsilon_r = 41.927$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 10-23-2017; Ambient Temp: 22.6°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7410; ConvF(10.08, 10.08, 10.08); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.96 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.199 W/kg

SAR(1 g) = 0.163 W/kg



0 dB = 0.185 W/kg = -7.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1720 \text{ MHz}$; $\sigma = 1.353 \text{ S/m}$; $\epsilon_r = 39.915$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 10-23-2017; Ambient Temp: 22.7°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3209; ConvF(5.5, 5.5, 5.5); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Left Head, Cheek, Low.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.31 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.335 W/kg

SAR(1 g) = 0.221 W/kg



0 dB = 0.261 W/kg = -5.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E34C

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.438 \text{ S/m}$; $\epsilon_r = 39.627$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 10-23-2017; Ambient Temp: 21.6°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3213; ConvF(5.29, 5.29, 5.29); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.01 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.178 W/kg

SAR(1 g) = 0.114 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 7; Frequency: 2510 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2510 \text{ MHz}$; $\sigma = 1.932 \text{ S/m}$; $\epsilon_r = 38.905$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 11-01-2017; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Left Head, Cheek, Low.ch, QPSK,
20 MHz Bandwidth, 1 RB, 99 RB Offset**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.09 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.260 W/kg

SAR(1 g) = 0.150 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2DD

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 1.932 \text{ S/m}$; $\epsilon_r = 38.763$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 10-30-2017; Ambient Temp: 21.7°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 41, Left Head, Cheek, Low.ch, QPSK,
20 MHz Bandwidth, 1 RB, 99 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.048 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.129 W/kg

SAR(1 g) = 0.070 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E34C

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.85 \text{ S/m}$; $\epsilon_r = 39.189$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 11-01-2017; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, Antenna 2, 22 MHz Bandwidth,
Right Head, Cheek, Ch 6, 1 Mbps**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (8x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.69 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.08 W/kg

SAR(1 g) = 0.886 W/kg



0 dB = 1.21 W/kg = 0.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E302

Communication System: UID 0, IEEE 802.11ac; Frequency: 5775 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used (interpolated):

$f = 5775 \text{ MHz}$; $\sigma = 5.158 \text{ S/m}$; $\epsilon_r = 34.788$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 10-25-2017; Ambient Temp: 22.8°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN3914; ConvF(4.91, 4.91, 4.91); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11ac, U-NII-3, 80 MHz Bandwidth, Right Head, Cheek,
Ch 155, 29.3 Mbps, Antenna 2**


Area Scan (13x21x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 1.985 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.896 W/kg

SAR(1 g) = 0.186 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E34C

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.294

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.855 \text{ S/m}$; $\epsilon_r = 39.175$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 11-01-2017; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Right Head, Cheek, Ch 39, 1Mbps


Area Scan (11x19x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.86 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.487 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 53.193$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-12-2017; Ambient Temp: 21.9°C; Tissue Temp: 18.9°C

Probe: EX3DV4 - SN7406; ConvF(9.77, 9.77, 9.77); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

GSM 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.66 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.467 W/kg

SAR(1 g) = 0.337 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 848.8 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 848.8 \text{ MHz}$; $\sigma = 1.007 \text{ S/m}$; $\epsilon_r = 53.065$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-12-2017; Ambient Temp: 21.9°C; Tissue Temp: 18.9°C

Probe: EX3DV4 - SN7406; ConvF(9.77, 9.77, 9.77); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 850, Body SAR, Back side, High.ch, 2 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 28.22 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.754 W/kg



0 dB = 1.04 W/kg = 0.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.002 \text{ S/m}$; $\epsilon_r = 54.222$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-14-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(6.47, 6.47, 6.47); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.75 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.480 W/kg

SAR(1 g) = 0.362 W/kg



0 dB = 0.398 W/kg = -4.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, UMTS; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 846.6 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 52.731$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-15-2017; Ambient Temp: 24.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(6.36, 6.36, 6.36); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back side, High.ch


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.82 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.624 W/kg



0 dB = 0.730 W/kg = -1.37 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E302

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.473 \text{ S/m}$; $\epsilon_r = 52.215$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-20-2017; Ambient Temp: 23.5°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN7406; ConvF(8.08, 8.08, 8.08); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.87 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.839 W/kg

SAR(1 g) = 0.535 W/kg



0 dB = 0.735 W/kg = -1.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E302

Communication System: UID 0, UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1752.6 \text{ MHz}$; $\sigma = 1.495 \text{ S/m}$; $\epsilon_r = 52.15$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-20-2017; Ambient Temp: 23.5°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN7406; ConvF(8.08, 8.08, 8.08); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Body SAR, Bottom Edge, High.ch


Area Scan (10x7x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.52 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.866 W/kg



0 dB = 1.28 W/kg = 1.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, GSM; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1910 \text{ MHz}$; $\sigma = 1.566 \text{ S/m}$; $\epsilon_r = 53.658$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-23-2017; Ambient Temp: 21.7°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 1900, Body SAR, Back side, High.ch


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.10 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.432 W/kg

SAR(1 g) = 0.268 W/kg



0 dB = 0.327 W/kg = -4.85 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 1909.8 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body Medium parameters used:

$f = 1910 \text{ MHz}$; $\sigma = 1.566 \text{ S/m}$; $\epsilon_r = 53.658$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-23-2017; Ambient Temp: 21.7°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 1900, Body SAR, Bottom Edge, High.ch, 3 Tx Slots


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.85 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.984 W/kg

SAR(1 g) = 0.576 W/kg



0 dB = 0.724 W/kg = -1.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.587 \text{ S/m}$; $\epsilon_r = 52.705$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-20-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Back side, High.ch


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.90 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.710 W/kg

SAR(1 g) = 0.443 W/kg



0 dB = 0.538 W/kg = -2.69 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, UMTS, Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.587 \text{ S/m}$; $\epsilon_r = 52.705$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-20-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Bottom Edge, High.ch


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.79 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.987 W/kg

SAR(1 g) = 0.580 W/kg



0 dB = 0.727 W/kg = -1.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E302

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.936 \text{ S/m}$; $\epsilon_r = 56.179$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-25-2017; Ambient Temp: 23.4°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.54 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.188 W/kg

SAR(1 g) = 0.135 W/kg



0 dB = 0.153 W/kg = -8.15 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E302

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.936 \text{ S/m}$; $\epsilon_r = 56.179$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 23.4°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x8x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.61 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.304 W/kg

SAR(1 g) = 0.192 W/kg



0 dB = 0.218 W/kg = -6.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 1.008 \text{ S/m}$; $\epsilon_r = 55.392$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-25-2017; Ambient Temp: 23.4°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.28 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.341 W/kg

SAR(1 g) = 0.246 W/kg



0 dB = 0.278 W/kg = -5.56 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 1.008 \text{ S/m}$; $\epsilon_r = 55.392$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 23.4°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x9x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.06 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.572 W/kg

SAR(1 g) = 0.350 W/kg



0 dB = 0.400 W/kg = -3.98 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E302

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.976 \text{ S/m}$; $\epsilon_r = 54.691$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-01-2017; Ambient Temp: 20.6°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3209; ConvF(6.36, 6.36, 6.36); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 36 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.84 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.299 W/kg

SAR(1 g) = 0.226 W/kg



0 dB = 0.252 W/kg = -5.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E302

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.976 \text{ S/m}$; $\epsilon_r = 54.691$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-01-2017; Ambient Temp: 20.6°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3209; ConvF(6.36, 6.36, 6.36); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 36 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.29 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.647 W/kg

SAR(1 g) = 0.385 W/kg



0 dB = 0.478 W/kg = -3.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.002 \text{ S/m}$; $\epsilon_r = 54.223$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-14-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(6.47, 6.47, 6.47); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 0.6540 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.394 W/kg

SAR(1 g) = 0.296 W/kg



0 dB = 0.328 W/kg = -4.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5$ MHz; $\sigma = 1.002$ S/m; $\epsilon_r = 54.223$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-14-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(6.47, 6.47, 6.47); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.29 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.830 W/kg

SAR(1 g) = 0.496 W/kg



0 dB = 0.595 W/kg = -2.25 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1745 \text{ MHz}$; $\sigma = 1.52 \text{ S/m}$; $\epsilon_r = 51.482$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-23-2017; Ambient Temp: 22.1°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7406; ConvF(8.08, 8.08, 8.08); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.93 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.903 W/kg



0 dB = 1.25 W/kg = 0.97 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1745 \text{ MHz}$; $\sigma = 1.488 \text{ S/m}$; $\epsilon_r = 52.636$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-08-2017; Ambient Temp: 21.7°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3209; ConvF(5.13, 5.13, 5.13); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Body SAR, Bottom Edge, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (10x8x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.26 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 0.943 W/kg



0 dB = 1.16 W/kg = 0.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.584 \text{ S/m}$; $\epsilon_r = 52.714$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-20-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.32 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.586 W/kg

SAR(1 g) = 0.367 W/kg



0 dB = 0.444 W/kg = -3.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.584 \text{ S/m}$; $\epsilon_r = 52.714$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-20-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Body SAR, Bottom Edge, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.51 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.966 W/kg

SAR(1 g) = 0.569 W/kg



0 dB = 0.714 W/kg = -1.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 7; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2560 \text{ MHz}$; $\sigma = 2.178 \text{ S/m}$; $\epsilon_r = 51.61$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.18, 4.18, 4.18); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.44 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.563 W/kg



0 dB = 0.697 W/kg = -1.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 7; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2560$ MHz; $\sigma = 2.19$ S/m; $\epsilon_r = 50.702$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-29-2017; Ambient Temp: 20.4°C; Tissue Temp: 20.1°C

Probe: ES3DV3 - SN3319; ConvF(4.18, 4.18, 4.18); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Body SAR, Bottom Edge, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (10x11x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.74 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.60 W/kg

SAR(1 g) = 0.810 W/kg



0 dB = 1.04 W/kg = 0.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.114 \text{ S/m}$; $\epsilon_r = 50.914$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-29-2017; Ambient Temp: 20.4°C; Tissue Temp: 20.1°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 41, Body SAR, Back side, Low.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (10x16x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.66 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.394 W/kg

SAR(1 g) = 0.215 W/kg



0 dB = 0.263 W/kg = -5.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E30E

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2506$ MHz; $\sigma = 2.114$ S/m; $\epsilon_r = 50.914$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-29-2017; Ambient Temp: 20.4°C; Tissue Temp: 20.1°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 41, Body SAR, Bottom Edge, Low.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.92 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.576 W/kg



0 dB = 0.736 W/kg = -1.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.002 \text{ S/m}$; $\epsilon_r = 52.094$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Antenna 2, Body SAR,
Ch 6, 1 Mbps, Back Side**


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.635 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.240 W/kg

SAR(1 g) = 0.128 W/kg



0 dB = 0.162 W/kg = -7.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.002 \text{ S/m}$; $\epsilon_r = 52.094$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Antenna 2, Body SAR,
Ch 6, 1 Mbps, Top Edge**


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.20 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.675 W/kg

SAR(1 g) = 0.355 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5260 \text{ MHz}$; $\sigma = 5.435 \text{ S/m}$; $\epsilon_r = 47.511$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-15-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7308; ConvF(4.84, 4.84, 4.84); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11a, UNII-2A, 20 MHz Bandwidth, Antenna 1, Body SAR,
Ch 52, 6 Mbps, Back Side**


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.716 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.937 W/kg

SAR(1 g) = 0.228 W/kg



0 dB = 0.529 W/kg = -2.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E2D1

Communication System: UID 0, 802.11n 5.2-5.8 GHz Band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5825 \text{ MHz}$; $\sigma = 6.208 \text{ S/m}$; $\epsilon_r = 46.571$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-15-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11n, UNII-3, 20 MHz Bandwidth, MIMO, Body SAR,
Ch 165, 13 Mbps, Back Side**


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 10.49 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.89 W/kg

SAR(1 g) = 0.618 W/kg



0 dB = 1.59 W/kg = 2.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.294

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 2.008 \text{ S/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.613 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.0710 W/kg

SAR(1 g) = 0.036 W/kg



0 dB = 0.0463 W/kg = -13.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG960F; Type: Portable Handset; Serial: 0E339

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.294

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 2.008 \text{ S/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Top Edge


Area Scan (10x11x1): Measurement grid: $dx=5\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.389 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.193 W/kg

SAR(1 g) = 0.092 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.908 \text{ S/m}$; $\epsilon_r = 40.612$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-23-2017; Ambient Temp: 23.4°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3213; ConvF(6.85, 6.85, 6.85); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.48 W/kg

SAR(1 g) = 1.64 W/kg

Deviation(1 g) = -2.26%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.906 \text{ S/m}$; $\epsilon_r = 41.946$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-23-2017; Ambient Temp: 22.6°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7410; ConvF(10.08, 10.08, 10.08); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.74 W/kg

SAR(1 g) = 1.86 W/kg

Deviation(1 g) = -2.31%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1150

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.384 \text{ S/m}$; $\epsilon_r = 39.785$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-23-2017; Ambient Temp: 22.7°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3209; ConvF(5.5, 5.5, 5.5); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 6.56 W/kg

SAR(1 g) = 3.62 W/kg

Deviation(1 g) = 0.28%



0 dB = 4.48 W/kg = 6.51 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.433 \text{ S/m}$; $\epsilon_r = 39.651$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-23-2017; Ambient Temp: 21.6°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3213; ConvF(5.29, 5.29, 5.29); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.48 W/kg

SAR(1 g) = 4.02 W/kg

Deviation(1 g) = 2.29%



0 dB = 5.09 W/kg = 7.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.868 \text{ S/m}$; $\epsilon_r = 38.996$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-30-2017; Ambient Temp: 21.7°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.2 W/kg

SAR(1 g) = 5.4 W/kg

Deviation(1 g) = 2.27%



0 dB = 6.69 W/kg = 8.25 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.606 \text{ S/m}$; $\epsilon_r = 35.56$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 22.8°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN3914; ConvF(5.49, 5.49, 5.49); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.3 W/kg

SAR(1 g) = 3.84 W/kg

Deviation(1 g) = -2.66%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.96 \text{ S/m}$; $\epsilon_r = 35.069$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 22.8°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN3914; ConvF(4.94, 4.94, 4.94); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.7 W/kg

SAR(1 g) = 4.06 W/kg

Deviation(1 g) = -2.87%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 5.131 \text{ S/m}$; $\epsilon_r = 34.815$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 22.8°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN3914; ConvF(4.91, 4.91, 4.91); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 3.71 W/kg

Deviation(1 g) = -6.19%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.977 \text{ S/m}$; $\epsilon_r = 55.734$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-25-2017; Ambient Temp: 23.4°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.54 W/kg

SAR(1 g) = 1.73 W/kg

Deviation(1 g) = -1.59%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.98 \text{ S/m}$; $\epsilon_r = 54.661$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-01-2017; Ambient Temp: 20.6°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3209; ConvF(6.36, 6.36, 6.36); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.94 W/kg

SAR(1 g) = 2.03 W/kg

Deviation(1 g) = 3.57%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.993 \text{ S/m}$; $\epsilon_r = 53.21$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-12-2017; Ambient Temp: 21.9°C; Tissue Temp: 18.9°C

Probe: EX3DV4 - SN7406; ConvF(9.77, 9.77, 9.77); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.22 W/kg

SAR(1 g) = 2.1 W/kg

Deviation(1 g) = 7.14%



0 dB = 2.76 W/kg = 4.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.001 \text{ S/m}$; $\epsilon_r = 54.237$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-14-2017; Ambient Temp: 23.1°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(6.47, 6.47, 6.47); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.92 W/kg

SAR(1 g) = 2.02 W/kg

Deviation(1 g) = 5.54%



0 dB = 2.15 W/kg = 3.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.974 \text{ S/m}$; $\epsilon_r = 52.846$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-15-2017; Ambient Temp: 24.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(6.36, 6.36, 6.36); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.82 W/kg

SAR(1 g) = 1.96 W/kg

Deviation(1 g) = 4.14%



0 dB = 2.26 W/kg = 3.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1150

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.492 \text{ S/m}$; $\epsilon_r = 52.159$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-20-2017; Ambient Temp: 23.5°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN7406; ConvF(8.08, 8.08, 8.08); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.03 W/kg

SAR(1 g) = 3.82 W/kg

Deviation(1 g) = 4.66%



0 dB = 5.80 W/kg = 7.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.526 \text{ S/m}$; $\epsilon_r = 51.467$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-23-2017; Ambient Temp: 22.1°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7406; ConvF(8.08, 8.08, 8.08); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.70 W/kg

SAR(1 g) = 3.69 W/kg

Deviation(1 g) = -0.27%



0 dB = 5.59 W/kg = 7.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.493 \text{ S/m}$; $\epsilon_r = 52.613$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-08-2017; Ambient Temp: 21.7°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3209; ConvF(5.13, 5.13, 5.13); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 6.74 W/kg

SAR(1 g) = 3.84 W/kg

Deviation(1 g) = 3.78%



0 dB = 4.75 W/kg = 6.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.578 \text{ S/m}$; $\epsilon_r = 52.731$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-20-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM Left; Type: QD000P40CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.24 W/kg

SAR(1 g) = 4.06 W/kg

Deviation(1 g) = 3.84%



0 dB = 5.16 W/kg = 7.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.02 \text{ S/m}$; $\epsilon_r = 52.049$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.6 W/kg

SAR(1 g) = 5.1 W/kg

Deviation(1 g) = 1.80%



0 dB = 6.72 W/kg = 8.27 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1064

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.239 \text{ S/m}$; $\epsilon_r = 51.447$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.18, 4.18, 4.18); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 12.7 W/kg

SAR(1 g) = 5.83 W/kg

Deviation(1 g) = 6.58%



0 dB = 7.85 W/kg = 8.95 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.43 \text{ S/m}$; $\epsilon_r = 47.548$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-15-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7308; ConvF(4.84, 4.84, 4.84); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.6 W/kg

SAR(1 g) = 3.68 W/kg

Deviation(1 g) = -4.29%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.895 \text{ S/m}$; $\epsilon_r = 46.927$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-15-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7308; ConvF(4.23, 4.23, 4.23); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 3.86 W/kg

Deviation(1 g) = -1.66%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.12 \text{ S/m}$; $\epsilon_r = 46.679$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-15-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.4 W/kg

SAR(1 g) = 3.69 W/kg

Deviation(1 g) = -4.28%



APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **ES3-3213_Feb17**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3213**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

Calibration date: **February 10, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Bny
03-01-2017

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	06-Apr-16 (No. 217-02288/02289)	Apr-17
Power sensor NRP-Z91	SN: 103244	06-Apr-16 (No. 217-02288)	Apr-17
Power sensor NRP-Z91	SN: 103245	06-Apr-16 (No. 217-02289)	Apr-17
Reference 20 dB Attenuator	SN: S5277 (20x)	05-Apr-16 (No. 217-02293)	Apr-17
Reference Probe ES3DV2	SN: 3013	31-Dec-16 (No. ES3-3013_Dec16)	Dec-17
DAE4	SN: 660	7-Dec-16 (No. DAE4-660_Dec16)	Dec-17
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Name** Claudio Leubler **Function** Laboratory Technician **Signature**

Approved by: **Name** Katja Pokovic **Function** Technical Manager **Signature**

Issued: February 13, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV3

SN:3213

Manufactured: October 14, 2008
Calibrated: February 10, 2017

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3213

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.44	1.32	1.29	$\pm 10.1 \%$
DCP (mV) ^B	101.3	102.3	101.6	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	228.2	$\pm 3.5 \%$
		Y	0.0	0.0	1.0		230.0	
		Z	0.0	0.0	1.0		221.7	

Note: For details on UID parameters see Appendix.

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $\text{ms} \cdot \text{V}^{-2}$	T2 $\text{ms} \cdot \text{V}^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	56.23	407.2	35.93	28.85	2.251	5.1	1.129	0.439	1.012
Y	55.47	400.7	35.87	28.65	2.277	5.1	1.321	0.386	1.013
Z	51.67	374.7	36	28.45	2.103	5.1	0.358	0.504	1.009

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3213

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	41.9	0.89	6.85	6.85	6.85	0.80	1.18	± 12.0 %
835	41.5	0.90	6.49	6.49	6.49	0.49	1.52	± 12.0 %
1750	40.1	1.37	5.49	5.49	5.49	0.60	1.35	± 12.0 %
1900	40.0	1.40	5.29	5.29	5.29	0.68	1.27	± 12.0 %
2300	39.5	1.67	4.95	4.95	4.95	0.70	1.28	± 12.0 %
2450	39.2	1.80	4.70	4.70	4.70	0.80	1.24	± 12.0 %
2600	39.0	1.96	4.52	4.52	4.52	0.78	1.28	± 12.0 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3213

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	55.5	0.96	6.38	6.38	6.38	0.60	1.31	± 12.0 %
835	55.2	0.97	6.28	6.28	6.28	0.80	1.20	± 12.0 %
1750	53.4	1.49	5.09	5.09	5.09	0.66	1.33	± 12.0 %
1900	53.3	1.52	4.94	4.94	4.94	0.40	1.85	± 12.0 %
2300	52.9	1.81	4.69	4.69	4.69	0.80	1.24	± 12.0 %
2450	52.7	1.95	4.53	4.53	4.53	0.72	1.28	± 12.0 %
2600	52.5	2.16	4.32	4.32	4.32	0.80	1.20	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz, TEM





f=1800 MHz, R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3213

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	98.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

Appendix: Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu V}$	C	D dB	VR mV	Max Unc ^E (k=2)
0	CW	X	0.00	0.00	1.00	0.00	228.2	$\pm 3.5 \%$
		Y	0.00	0.00	1.00		230.0	
		Z	0.00	0.00	1.00		221.7	
10010- CAA	SAR Validation (Square, 100ms, 10ms)	X	11.07	84.26	20.62	10.00	25.0	$\pm 9.6 \%$
		Y	10.49	83.36	20.27		25.0	
		Z	11.03	84.22	20.43		25.0	
10011- CAB	UMTS-FDD (WCDMA)	X	1.04	66.65	14.82	0.00	150.0	$\pm 9.6 \%$
		Y	1.16	69.13	16.33		150.0	
		Z	1.01	66.30	14.54		150.0	
10012- CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	1.30	64.60	15.49	0.41	150.0	$\pm 9.6 \%$
		Y	1.33	65.49	16.22		150.0	
		Z	1.28	64.47	15.36		150.0	
10013- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	5.14	67.15	17.39	1.46	150.0	$\pm 9.6 \%$
		Y	5.14	67.35	17.57		150.0	
		Z	5.09	67.17	17.37		150.0	
10021- DAC	GSM-FDD (TDMA, GMSK)	X	62.94	114.81	31.61	9.39	50.0	$\pm 9.6 \%$
		Y	41.95	107.82	29.66		50.0	
		Z	94.76	121.25	33.03		50.0	
10023- DAC	GPRS-FDD (TDMA, GMSK, TN 0)	X	46.50	109.76	30.33	9.57	50.0	$\pm 9.6 \%$
		Y	33.70	104.15	28.69		50.0	
		Z	62.69	114.46	31.37		50.0	
10024- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	100.00	119.19	30.75	6.56	60.0	$\pm 9.6 \%$
		Y	100.00	118.97	30.64		60.0	
		Z	100.00	118.83	30.48		60.0	
10025- DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	X	18.95	107.68	41.29	12.57	50.0	$\pm 9.6 \%$
		Y	31.91	124.81	47.58		50.0	
		Z	17.05	104.98	40.36		50.0	
10026- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	X	20.29	105.23	36.57	9.56	60.0	$\pm 9.6 \%$
		Y	28.92	114.92	39.99		60.0	
		Z	20.11	105.49	36.71		60.0	
10027- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	100.00	118.17	29.38	4.80	80.0	$\pm 9.6 \%$
		Y	100.00	118.12	29.34		80.0	
		Z	100.00	117.81	29.12		80.0	
10028- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	100.00	118.40	28.68	3.55	100.0	$\pm 9.6 \%$
		Y	100.00	118.60	28.76		100.0	
		Z	100.00	118.00	28.41		100.0	
10029- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	X	12.78	94.46	31.72	7.80	80.0	$\pm 9.6 \%$
		Y	16.27	100.85	34.22		80.0	
		Z	12.37	94.11	31.64		80.0	
10030- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	X	100.00	117.61	29.45	5.30	70.0	$\pm 9.6 \%$
		Y	100.00	117.52	29.40		70.0	
		Z	100.00	117.17	29.14		70.0	
10031- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	X	100.00	119.11	27.47	1.88	100.0	$\pm 9.6 \%$
		Y	100.00	120.30	27.96		100.0	
		Z	100.00	118.27	27.02		100.0	

10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	100.00	123.13	28.10	1.17	100.0	± 9.6 %
		Y	100.00	125.86	29.19		100.0	
		Z	100.00	121.81	27.46		100.0	
10033-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	X	19.81	99.27	27.58	5.30	70.0	± 9.6 %
		Y	23.75	102.32	28.48		70.0	
		Z	20.10	99.19	27.31		70.0	
10034-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	X	6.18	84.61	21.36	1.88	100.0	± 9.6 %
		Y	8.74	90.01	23.19		100.0	
		Z	6.07	84.02	20.83		100.0	
10035-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	X	3.50	78.04	18.75	1.17	100.0	± 9.6 %
		Y	4.77	82.88	20.59		100.0	
		Z	3.40	77.42	18.19		100.0	
10036-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	X	25.06	103.36	28.83	5.30	70.0	± 9.6 %
		Y	30.48	106.66	29.76		70.0	
		Z	25.78	103.46	28.61		70.0	
10037-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	X	5.91	84.02	21.13	1.88	100.0	± 9.6 %
		Y	8.37	89.43	22.97		100.0	
		Z	5.74	83.28	20.55		100.0	
10038-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	X	3.58	78.59	19.05	1.17	100.0	± 9.6 %
		Y	4.93	83.62	20.94		100.0	
		Z	3.47	77.94	18.48		100.0	
10039-CAB	CDMA2000 (1xRTT, RC1)	X	1.75	70.49	15.41	0.00	150.0	± 9.6 %
		Y	2.11	73.63	16.88		150.0	
		Z	1.63	69.80	14.78		150.0	
10042-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	X	100.00	117.99	30.44	7.78	50.0	± 9.6 %
		Y	100.00	117.70	30.30		50.0	
		Z	100.00	117.57	30.13		50.0	
10044-CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	X	0.01	92.86	0.28	0.00	150.0	± 9.6 %
		Y	0.00	128.30	10.22		150.0	
		Z	0.01	91.94	0.27		150.0	
10048-CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	X	16.43	91.36	26.72	13.80	25.0	± 9.6 %
		Y	14.26	88.55	25.69		25.0	
		Z	18.21	93.36	27.20		25.0	
10049-CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	X	21.81	96.95	27.09	10.79	40.0	± 9.6 %
		Y	18.36	93.74	25.99		40.0	
		Z	24.94	99.20	27.59		40.0	
10056-CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	X	16.12	92.43	26.40	9.03	50.0	± 9.6 %
		Y	16.40	92.69	26.46		50.0	
		Z	16.84	93.23	26.48		50.0	
10058-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	X	9.13	87.64	28.49	6.55	100.0	± 9.6 %
		Y	10.85	92.11	30.40		100.0	
		Z	8.80	87.14	28.33		100.0	
10059-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	X	1.45	66.53	16.46	0.61	110.0	± 9.6 %
		Y	1.51	67.75	17.33		110.0	
		Z	1.43	66.36	16.31		110.0	
10060-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	X	71.32	126.43	32.69	1.30	110.0	± 9.6 %
		Y	100.00	133.00	34.47		110.0	
		Z	56.46	122.77	31.74		110.0	

10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	X	7.70	91.83	25.70	2.04	110.0	± 9.6 %
		Y	12.85	101.15	28.77		110.0	
		Z	7.42	91.30	25.47		110.0	
10062-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	X	4.86	66.91	16.67	0.49	100.0	± 9.6 %
		Y	4.87	67.10	16.85		100.0	
		Z	4.81	66.91	16.64		100.0	
10063-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	X	4.90	67.06	16.81	0.72	100.0	± 9.6 %
		Y	4.91	67.26	16.99		100.0	
		Z	4.85	67.06	16.78		100.0	
10064-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	X	5.22	67.40	17.08	0.86	100.0	± 9.6 %
		Y	5.23	67.59	17.25		100.0	
		Z	5.16	67.38	17.04		100.0	
10065-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	X	5.12	67.42	17.25	1.21	100.0	± 9.6 %
		Y	5.13	67.61	17.43		100.0	
		Z	5.06	67.40	17.21		100.0	
10066-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	X	5.18	67.55	17.48	1.46	100.0	± 9.6 %
		Y	5.19	67.76	17.66		100.0	
		Z	5.11	67.52	17.44		100.0	
10067-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	X	5.50	67.74	17.95	2.04	100.0	± 9.6 %
		Y	5.51	67.96	18.15		100.0	
		Z	5.44	67.76	17.93		100.0	
10068-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	X	5.63	68.06	18.32	2.55	100.0	± 9.6 %
		Y	5.64	68.30	18.53		100.0	
		Z	5.56	68.03	18.28		100.0	
10069-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	X	5.71	68.03	18.50	2.67	100.0	± 9.6 %
		Y	5.72	68.29	18.74		100.0	
		Z	5.64	68.03	18.48		100.0	
10071-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	X	5.28	67.38	17.78	1.99	100.0	± 9.6 %
		Y	5.29	67.59	17.97		100.0	
		Z	5.23	67.40	17.76		100.0	
10072-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	X	5.33	67.91	18.09	2.30	100.0	± 9.6 %
		Y	5.34	68.14	18.30		100.0	
		Z	5.28	67.91	18.07		100.0	
10073-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	X	5.46	68.24	18.51	2.83	100.0	± 9.6 %
		Y	5.48	68.51	18.74		100.0	
		Z	5.40	68.25	18.50		100.0	
10074-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	X	5.49	68.30	18.76	3.30	100.0	± 9.6 %
		Y	5.51	68.58	19.00		100.0	
		Z	5.44	68.31	18.74		100.0	
10075-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	X	5.63	68.74	19.25	3.82	90.0	± 9.6 %
		Y	5.66	69.06	19.51		90.0	
		Z	5.57	68.71	19.21		90.0	
10076-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	X	5.64	68.56	19.38	4.15	90.0	± 9.6 %
		Y	5.68	68.89	19.66		90.0	
		Z	5.60	68.57	19.36		90.0	
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	X	5.68	68.64	19.49	4.30	90.0	± 9.6 %
		Y	5.71	68.99	19.77		90.0	
		Z	5.64	68.66	19.47		90.0	

10081-CAB	CDMA2000 (1xRTT, RC3)	X	0.88	65.55	12.70	0.00	150.0	± 9.6 %
		Y	1.01	67.94	14.05		150.0	
		Z	0.82	64.98	12.07		150.0	
10082-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	X	2.05	63.91	8.77	4.77	80.0	± 9.6 %
		Y	2.06	64.02	8.81		80.0	
		Z	1.95	63.58	8.48		80.0	
10090-DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	X	100.00	119.26	30.80	6.56	60.0	± 9.6 %
		Y	100.00	119.04	30.70		60.0	
		Z	100.00	118.90	30.53		60.0	
10097-CAB	UMTS-FDD (HSDPA)	X	1.83	67.01	15.38	0.00	150.0	± 9.6 %
		Y	1.91	68.15	16.11		150.0	
		Z	1.80	66.92	15.21		150.0	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	1.79	66.97	15.34	0.00	150.0	± 9.6 %
		Y	1.88	68.14	16.10		150.0	
		Z	1.76	66.87	15.18		150.0	
10099-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	X	20.23	105.10	36.53	9.56	60.0	± 9.6 %
		Y	28.70	114.68	39.91		60.0	
		Z	20.06	105.38	36.67		60.0	
10100-CAC	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	3.16	69.99	16.45	0.00	150.0	± 9.6 %
		Y	3.31	71.03	17.06		150.0	
		Z	3.09	69.73	16.33		150.0	
10101-CAC	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	3.32	67.51	15.87	0.00	150.0	± 9.6 %
		Y	3.38	68.00	16.23		150.0	
		Z	3.27	67.36	15.78		150.0	
10102-CAC	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	3.43	67.46	15.96	0.00	150.0	± 9.6 %
		Y	3.47	67.89	16.28		150.0	
		Z	3.37	67.33	15.88		150.0	
10103-CAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	8.65	78.54	21.48	3.98	65.0	± 9.6 %
		Y	8.85	79.12	21.77		65.0	
		Z	8.48	78.45	21.46		65.0	
10104-CAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	8.46	76.91	21.67	3.98	65.0	± 9.6 %
		Y	8.66	77.60	22.06		65.0	
		Z	8.34	76.89	21.66		65.0	
10105-CAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	7.58	74.70	20.99	3.98	65.0	± 9.6 %
		Y	7.79	75.45	21.40		65.0	
		Z	7.31	74.25	20.79		65.0	
10108-CAD	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	2.79	69.24	16.28	0.00	150.0	± 9.6 %
		Y	2.91	70.28	16.91		150.0	
		Z	2.71	69.00	16.16		150.0	
10109-CAD	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	2.98	67.28	15.76	0.00	150.0	± 9.6 %
		Y	3.03	67.83	16.15		150.0	
		Z	2.92	67.15	15.65		150.0	
10110-CAD	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	2.28	68.31	15.91	0.00	150.0	± 9.6 %
		Y	2.39	69.47	16.63		150.0	
		Z	2.21	68.09	15.75		150.0	
10111-CAD	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	2.66	67.75	15.94	0.00	150.0	± 9.6 %
		Y	2.72	68.40	16.37		150.0	
		Z	2.60	67.66	15.80		150.0	

10112-CAD	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	3.11	67.26	15.82	0.00	150.0	± 9.6 %
		Y	3.15	67.75	16.17		150.0	
		Z	3.05	67.15	15.72		150.0	
10113-CAD	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	2.82	67.88	16.07	0.00	150.0	± 9.6 %
		Y	2.87	68.46	16.46		150.0	
		Z	2.76	67.81	15.94		150.0	
10114-CAB	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	5.24	67.28	16.46	0.00	150.0	± 9.6 %
		Y	5.25	67.46	16.63		150.0	
		Z	5.20	67.29	16.46		150.0	
10115-CAB	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	X	5.61	67.64	16.65	0.00	150.0	± 9.6 %
		Y	5.61	67.79	16.81		150.0	
		Z	5.52	67.52	16.58		150.0	
10116-CAB	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	X	5.36	67.55	16.52	0.00	150.0	± 9.6 %
		Y	5.37	67.74	16.69		150.0	
		Z	5.32	67.53	16.51		150.0	
10117-CAB	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	5.22	67.23	16.45	0.00	150.0	± 9.6 %
		Y	5.23	67.39	16.61		150.0	
		Z	5.17	67.16	16.41		150.0	
10118-CAB	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	X	5.69	67.85	16.77	0.00	150.0	± 9.6 %
		Y	5.70	68.02	16.93		150.0	
		Z	5.63	67.79	16.73		150.0	
10119-CAB	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	X	5.34	67.49	16.51	0.00	150.0	± 9.6 %
		Y	5.35	67.67	16.67		150.0	
		Z	5.29	67.47	16.49		150.0	
10140-CAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	3.47	67.47	15.89	0.00	150.0	± 9.6 %
		Y	3.51	67.91	16.21		150.0	
		Z	3.41	67.34	15.80		150.0	
10141-CAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	3.59	67.54	16.05	0.00	150.0	± 9.6 %
		Y	3.63	67.94	16.35		150.0	
		Z	3.53	67.43	15.97		150.0	
10142-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	2.05	68.16	15.60	0.00	150.0	± 9.6 %
		Y	2.17	69.48	16.39		150.0	
		Z	1.97	67.92	15.36		150.0	
10143-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	2.51	68.28	15.68	0.00	150.0	± 9.6 %
		Y	2.59	69.11	16.17		150.0	
		Z	2.43	68.15	15.43		150.0	
10144-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	2.35	66.54	14.37	0.00	150.0	± 9.6 %
		Y	2.42	67.28	14.84		150.0	
		Z	2.27	66.32	14.07		150.0	
10145-CAD	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	1.37	65.72	12.66	0.00	150.0	± 9.6 %
		Y	1.46	66.99	13.37		150.0	
		Z	1.25	64.89	11.82		150.0	
10146-CAD	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	3.11	71.69	15.06	0.00	150.0	± 9.6 %
		Y	3.87	74.93	16.48		150.0	
		Z	2.20	67.57	12.72		150.0	
10147-CAD	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	3.99	75.14	16.65	0.00	150.0	± 9.6 %
		Y	5.26	79.21	18.27		150.0	
		Z	2.59	69.69	13.85		150.0	

10149-CAC	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	2.99	67.34	15.80	0.00	150.0	± 9.6 %
		Y	3.04	67.88	16.19		150.0	
		Z	2.93	67.20	15.70		150.0	
10150-CAC	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	3.11	67.30	15.85	0.00	150.0	± 9.6 %
		Y	3.16	67.79	16.21		150.0	
		Z	3.05	67.19	15.76		150.0	
10151-CAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	9.14	80.78	22.44	3.98	65.0	± 9.6 %
		Y	9.49	81.66	22.85		65.0	
		Z	9.14	81.08	22.55		65.0	
10152-CAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	8.08	77.12	21.52	3.98	65.0	± 9.6 %
		Y	8.33	77.95	21.96		65.0	
		Z	7.95	77.09	21.46		65.0	
10153-CAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	8.46	77.89	22.17	3.98	65.0	± 9.6 %
		Y	8.68	78.63	22.56		65.0	
		Z	8.36	77.94	22.15		65.0	
10154-CAD	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	2.33	68.67	16.15	0.00	150.0	± 9.6 %
		Y	2.44	69.83	16.86		150.0	
		Z	2.25	68.43	15.98		150.0	
10155-CAD	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	2.66	67.76	15.95	0.00	150.0	± 9.6 %
		Y	2.72	68.41	16.38		150.0	
		Z	2.60	67.68	15.82		150.0	
10156-CAD	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	1.90	68.21	15.44	0.00	150.0	± 9.6 %
		Y	2.03	69.70	16.30		150.0	
		Z	1.81	67.89	15.12		150.0	
10157-CAD	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	2.18	67.00	14.41	0.00	150.0	± 9.6 %
		Y	2.26	67.93	14.96		150.0	
		Z	2.09	66.73	14.04		150.0	
10158-CAD	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	2.82	67.92	16.11	0.00	150.0	± 9.6 %
		Y	2.87	68.51	16.50		150.0	
		Z	2.76	67.86	15.98		150.0	
10159-CAD	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	2.28	67.39	14.67	0.00	150.0	± 9.6 %
		Y	2.36	68.28	15.19		150.0	
		Z	2.18	67.11	14.29		150.0	
10160-CAC	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	2.82	68.45	16.16	0.00	150.0	± 9.6 %
		Y	2.91	69.30	16.70		150.0	
		Z	2.76	68.35	16.07		150.0	
10161-CAC	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	3.01	67.20	15.78	0.00	150.0	± 9.6 %
		Y	3.05	67.71	16.14		150.0	
		Z	2.95	67.10	15.68		150.0	
10162-CAC	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	3.11	67.31	15.88	0.00	150.0	± 9.6 %
		Y	3.16	67.80	16.23		150.0	
		Z	3.06	67.24	15.78		150.0	
10166-CAD	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	3.96	70.63	19.76	3.01	150.0	± 9.6 %
		Y	4.08	71.58	20.41		150.0	
		Z	3.69	69.63	19.19		150.0	
10167-CAD	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	5.16	74.36	20.54	3.01	150.0	± 9.6 %
		Y	5.47	75.92	21.41		150.0	
		Z	4.54	72.52	19.67		150.0	

10168-CAD	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	5.71	76.55	21.79	3.01	150.0	± 9.6 %
		Y	6.04	78.08	22.60		150.0	
		Z	4.98	74.53	20.87		150.0	
10169-CAC	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	3.56	71.66	20.23	3.01	150.0	± 9.6 %
		Y	3.72	73.10	21.16		150.0	
		Z	3.12	69.36	19.09		150.0	
10170-CAC	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	5.50	79.49	23.11	3.01	150.0	± 9.6 %
		Y	6.14	82.25	24.43		150.0	
		Z	4.23	74.96	21.26		150.0	
10171-AAC	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	4.39	74.63	20.21	3.01	150.0	± 9.6 %
		Y	4.87	77.16	21.52		150.0	
		Z	3.55	71.26	18.74		150.0	
10172-CAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	36.90	115.61	35.71	6.02	65.0	± 9.6 %
		Y	89.16	134.58	40.97		65.0	
		Z	21.04	105.02	32.65		65.0	
10173-CAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	54.93	117.26	34.23	6.02	65.0	± 9.6 %
		Y	100.00	128.92	37.35		65.0	
		Z	30.85	107.44	31.57		65.0	
10174-CAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	39.60	109.76	31.68	6.02	65.0	± 9.6 %
		Y	70.95	120.74	34.73		65.0	
		Z	23.48	101.22	29.25		65.0	
10175-CAD	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	3.51	71.32	19.98	3.01	150.0	± 9.6 %
		Y	3.68	72.77	20.92		150.0	
		Z	3.08	69.09	18.87		150.0	
10176-CAD	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	5.51	79.52	23.12	3.01	150.0	± 9.6 %
		Y	6.15	82.28	24.44		150.0	
		Z	4.23	74.98	21.27		150.0	
10177-CAF	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	3.54	71.49	20.08	3.01	150.0	± 9.6 %
		Y	3.71	72.93	21.01		150.0	
		Z	3.11	69.22	18.95		150.0	
10178-CAD	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	5.43	79.21	22.98	3.01	150.0	± 9.6 %
		Y	6.06	81.97	24.30		150.0	
		Z	4.19	74.78	21.16		150.0	
10179-CAD	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	4.90	76.90	21.51	3.01	150.0	± 9.6 %
		Y	5.47	79.59	22.84		150.0	
		Z	3.86	73.02	19.88		150.0	
10180-CAD	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	4.38	74.54	20.15	3.01	150.0	± 9.6 %
		Y	4.86	77.07	21.46		150.0	
		Z	3.54	71.20	18.69		150.0	
10181-CAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	3.54	71.47	20.07	3.01	150.0	± 9.6 %
		Y	3.70	72.91	21.00		150.0	
		Z	3.10	69.21	18.95		150.0	
10182-CAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	5.42	79.19	22.97	3.01	150.0	± 9.6 %
		Y	6.05	81.94	24.29		150.0	
		Z	4.19	74.76	21.15		150.0	
10183-AAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	4.37	74.51	20.14	3.01	150.0	± 9.6 %
		Y	4.85	77.04	21.45		150.0	
		Z	3.53	71.17	18.68		150.0	

10184-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	3.55	71.52	20.09	3.01	150.0	± 9.6 %
		Y	3.72	72.96	21.02		150.0	
		Z	3.11	69.25	18.97		150.0	
10185-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	5.45	79.27	23.00	3.01	150.0	± 9.6 %
		Y	6.09	82.03	24.33		150.0	
		Z	4.20	74.82	21.19		150.0	
10186-AAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	4.39	74.59	20.17	3.01	150.0	± 9.6 %
		Y	4.88	77.13	21.49		150.0	
		Z	3.55	71.24	18.71		150.0	
10187-CAD	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	3.56	71.57	20.15	3.01	150.0	± 9.6 %
		Y	3.73	73.01	21.08		150.0	
		Z	3.12	69.30	19.03		150.0	
10188-CAD	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	5.67	80.08	23.42	3.01	150.0	± 9.6 %
		Y	6.33	82.86	24.73		150.0	
		Z	4.33	75.42	21.53		150.0	
10189-AAD	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	4.51	75.09	20.47	3.01	150.0	± 9.6 %
		Y	5.01	77.67	21.79		150.0	
		Z	3.62	71.63	18.97		150.0	
10193-CAB	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	4.64	66.65	16.17	0.00	150.0	± 9.6 %
		Y	4.65	66.84	16.35		150.0	
		Z	4.59	66.64	16.13		150.0	
10194-CAB	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	X	4.82	67.00	16.30	0.00	150.0	± 9.6 %
		Y	4.83	67.19	16.48		150.0	
		Z	4.76	66.96	16.26		150.0	
10195-CAB	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	X	4.87	67.02	16.31	0.00	150.0	± 9.6 %
		Y	4.87	67.22	16.49		150.0	
		Z	4.81	67.00	16.28		150.0	
10196-CAB	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	4.65	66.74	16.20	0.00	150.0	± 9.6 %
		Y	4.66	66.93	16.38		150.0	
		Z	4.59	66.71	16.15		150.0	
10197-CAB	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	X	4.84	67.02	16.31	0.00	150.0	± 9.6 %
		Y	4.85	67.22	16.49		150.0	
		Z	4.78	66.99	16.27		150.0	
10198-CAB	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	X	4.87	67.04	16.32	0.00	150.0	± 9.6 %
		Y	4.88	67.24	16.50		150.0	
		Z	4.81	67.01	16.29		150.0	
10219-CAB	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	4.60	66.74	16.16	0.00	150.0	± 9.6 %
		Y	4.61	66.94	16.34		150.0	
		Z	4.54	66.71	16.11		150.0	
10220-CAB	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	X	4.84	67.00	16.31	0.00	150.0	± 9.6 %
		Y	4.84	67.20	16.48		150.0	
		Z	4.77	66.96	16.26		150.0	
10221-CAB	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	X	4.88	66.97	16.31	0.00	150.0	± 9.6 %
		Y	4.89	67.16	16.49		150.0	
		Z	4.82	66.95	16.28		150.0	
10222-CAB	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	5.20	67.24	16.45	0.00	150.0	± 9.6 %
		Y	5.21	67.41	16.61		150.0	
		Z	5.15	67.17	16.40		150.0	

10223-CAB	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	X	5.54	67.51	16.61	0.00	150.0	± 9.6 %
		Y	5.54	67.65	16.76		150.0	
		Z	5.46	67.41	16.55		150.0	
10224-CAB	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	X	5.24	67.33	16.42	0.00	150.0	± 9.6 %
		Y	5.25	67.50	16.58		150.0	
		Z	5.19	67.27	16.38		150.0	
10225-CAB	UMTS-FDD (HSPA+)	X	2.89	66.01	15.34	0.00	150.0	± 9.6 %
		Y	2.91	66.41	15.64		150.0	
		Z	2.83	65.96	15.20		150.0	
10226-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	60.00	119.05	34.79	6.02	65.0	± 9.6 %
		Y	100.00	129.10	37.47		65.0	
		Z	33.08	108.86	32.05		65.0	
10227-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	44.36	111.89	32.33	6.02	65.0	± 9.6 %
		Y	77.77	122.52	35.25		65.0	
		Z	27.85	104.26	30.19		65.0	
10228-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	40.71	118.07	36.50	6.02	65.0	± 9.6 %
		Y	92.59	135.95	41.44		65.0	
		Z	26.22	109.78	34.13		65.0	
10229-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	54.96	117.26	34.24	6.02	65.0	± 9.6 %
		Y	100.00	128.91	37.35		65.0	
		Z	30.93	107.47	31.58		65.0	
10230-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	41.37	110.53	31.89	6.02	65.0	± 9.6 %
		Y	71.92	120.98	34.79		65.0	
		Z	26.25	103.12	29.80		65.0	
10231-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	37.97	116.54	36.00	6.02	65.0	± 9.6 %
		Y	84.76	133.97	40.88		65.0	
		Z	24.71	108.49	33.69		65.0	
10232-CAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	54.99	117.28	34.24	6.02	65.0	± 9.6 %
		Y	100.00	128.92	37.35		65.0	
		Z	30.92	107.48	31.58		65.0	
10233-CAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	41.40	110.55	31.90	6.02	65.0	± 9.6 %
		Y	72.14	121.04	34.81		65.0	
		Z	26.24	103.13	29.80		65.0	
10234-CAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	35.49	114.97	35.47	6.02	65.0	± 9.6 %
		Y	77.34	131.82	40.23		65.0	
		Z	23.39	107.20	33.21		65.0	
10235-CAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	55.28	117.39	34.27	6.02	65.0	± 9.6 %
		Y	100.00	128.93	37.36		65.0	
		Z	31.03	107.56	31.61		65.0	
10236-CAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	41.91	110.74	31.95	6.02	65.0	± 9.6 %
		Y	73.33	121.30	34.87		65.0	
		Z	26.52	103.28	29.84		65.0	
10237-CAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	38.41	116.80	36.08	6.02	65.0	± 9.6 %
		Y	86.80	134.49	41.01		65.0	
		Z	24.91	108.68	33.74		65.0	
10238-CAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	55.05	117.31	34.25	6.02	65.0	± 9.6 %
		Y	100.00	128.93	37.35		65.0	
		Z	30.91	107.49	31.58		65.0	

10239-CAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	41.42	110.58	31.91	6.02	65.0	± 9.6 %
		Y	72.33	121.11	34.83		65.0	
		Z	26.22	103.13	29.80		65.0	
10240-CAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	38.25	116.72	36.05	6.02	65.0	± 9.6 %
		Y	86.28	134.37	40.98		65.0	
		Z	24.82	108.62	33.73		65.0	
10241-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	12.92	88.42	28.30	6.98	65.0	± 9.6 %
		Y	14.47	91.50	29.64		65.0	
		Z	11.71	86.68	27.54		65.0	
10242-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	12.30	87.28	27.78	6.98	65.0	± 9.6 %
		Y	13.91	90.55	29.21		65.0	
		Z	10.78	84.84	26.74		65.0	
10243-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	9.57	83.58	27.27	6.98	65.0	± 9.6 %
		Y	10.70	86.76	28.80		65.0	
		Z	8.63	81.57	26.33		65.0	
10244-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	9.97	81.73	21.53	3.98	65.0	± 9.6 %
		Y	10.43	82.64	21.91		65.0	
		Z	8.76	79.58	20.36		65.0	
10245-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	9.75	81.12	21.26	3.98	65.0	± 9.6 %
		Y	10.17	81.97	21.61		65.0	
		Z	8.56	78.97	20.07		65.0	
10246-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	9.14	83.08	21.95	3.98	65.0	± 9.6 %
		Y	9.72	84.22	22.38		65.0	
		Z	8.89	82.67	21.56		65.0	
10247-CAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	7.53	77.68	20.47	3.98	65.0	± 9.6 %
		Y	7.73	78.28	20.74		65.0	
		Z	7.33	77.37	20.13		65.0	
10248-CAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	7.50	77.17	20.25	3.98	65.0	± 9.6 %
		Y	7.71	77.80	20.54		65.0	
		Z	7.27	76.81	19.89		65.0	
10249-CAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	10.17	85.08	23.35	3.98	65.0	± 9.6 %
		Y	10.94	86.52	23.90		65.0	
		Z	10.18	85.27	23.26		65.0	
10250-CAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	8.40	79.60	22.53	3.98	65.0	± 9.6 %
		Y	8.67	80.38	22.90		65.0	
		Z	8.32	79.67	22.46		65.0	
10251-CAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	7.96	77.51	21.40	3.98	65.0	± 9.6 %
		Y	8.23	78.35	21.83		65.0	
		Z	7.84	77.49	21.29		65.0	
10252-CAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	9.91	84.03	23.67	3.98	65.0	± 9.6 %
		Y	10.54	85.36	24.22		65.0	
		Z	9.99	84.47	23.78		65.0	
10253-CAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	7.87	76.54	21.30	3.98	65.0	± 9.6 %
		Y	8.11	77.33	21.72		65.0	
		Z	7.77	76.53	21.24		65.0	
10254-CAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	8.25	77.30	21.90	3.98	65.0	± 9.6 %
		Y	8.47	78.02	22.29		65.0	
		Z	8.16	77.35	21.86		65.0	

10255-CAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	8.82	80.37	22.51	3.98	65.0	± 9.6 %
		Y	9.18	81.32	22.95		65.0	
		Z	8.82	80.67	22.60		65.0	
10256-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	8.67	79.06	19.69	3.98	65.0	± 9.6 %
		Y	9.00	79.76	19.98		65.0	
		Z	7.35	76.40	18.22		65.0	
10257-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	8.39	78.18	19.27	3.98	65.0	± 9.6 %
		Y	8.67	78.82	19.53		65.0	
		Z	7.11	75.57	17.80		65.0	
10258-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	7.67	79.80	20.11	3.98	65.0	± 9.6 %
		Y	7.97	80.50	20.36		65.0	
		Z	7.13	78.64	19.35		65.0	
10259-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	7.87	78.36	21.19	3.98	65.0	± 9.6 %
		Y	8.11	79.04	21.50		65.0	
		Z	7.72	78.21	20.96		65.0	
10260-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	7.88	78.07	21.09	3.98	65.0	± 9.6 %
		Y	8.10	78.72	21.39		65.0	
		Z	7.71	77.89	20.85		65.0	
10261-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	9.63	83.94	23.25	3.98	65.0	± 9.6 %
		Y	10.30	85.33	23.81		65.0	
		Z	9.64	84.17	23.22		65.0	
10262-CAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	8.39	79.56	22.49	3.98	65.0	± 9.6 %
		Y	8.66	80.34	22.86		65.0	
		Z	8.31	79.62	22.42		65.0	
10263-CAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	7.95	77.50	21.40	3.98	65.0	± 9.6 %
		Y	8.22	78.34	21.82		65.0	
		Z	7.83	77.47	21.29		65.0	
10264-CAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	9.83	83.88	23.59	3.98	65.0	± 9.6 %
		Y	10.46	85.22	24.15		65.0	
		Z	9.91	84.30	23.70		65.0	
10265-CAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	8.08	77.12	21.52	3.98	65.0	± 9.6 %
		Y	8.33	77.96	21.96		65.0	
		Z	7.95	77.09	21.47		65.0	
10266-CAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	8.45	77.88	22.16	3.98	65.0	± 9.6 %
		Y	8.68	78.62	22.55		65.0	
		Z	8.36	77.93	22.14		65.0	
10267-CAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	9.12	80.75	22.43	3.98	65.0	± 9.6 %
		Y	9.47	81.62	22.84		65.0	
		Z	9.12	81.04	22.54		65.0	
10268-CAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	8.54	76.63	21.68	3.98	65.0	± 9.6 %
		Y	8.73	77.26	22.04		65.0	
		Z	8.44	76.63	21.67		65.0	
10269-CAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	8.47	76.21	21.58	3.98	65.0	± 9.6 %
		Y	8.64	76.83	21.94		65.0	
		Z	8.37	76.22	21.56		65.0	
10270-CAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	8.62	78.00	21.50	3.98	65.0	± 9.6 %
		Y	8.81	78.56	21.80		65.0	
		Z	8.57	78.16	21.57		65.0	

10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	2.63	66.22	15.16	0.00	150.0	± 9.6 %
		Y	2.68	66.76	15.56		150.0	
		Z	2.60	66.20	15.05		150.0	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	1.63	67.34	15.24	0.00	150.0	± 9.6 %
		Y	1.75	68.91	16.21		150.0	
		Z	1.59	67.10	15.04		150.0	
10277-CAA	PHS (QPSK)	X	5.23	69.17	13.58	9.03	50.0	± 9.6 %
		Y	5.23	69.14	13.54		50.0	
		Z	4.94	68.42	12.95		50.0	
10278-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.5)	X	9.44	80.92	21.03	9.03	50.0	± 9.6 %
		Y	9.27	80.52	20.82		50.0	
		Z	8.80	79.60	20.21		50.0	
10279-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.38)	X	9.60	81.11	21.12	9.03	50.0	± 9.6 %
		Y	9.45	80.75	20.93		50.0	
		Z	8.93	79.76	20.30		50.0	
10290-AAB	CDMA2000, RC1, SO55, Full Rate	X	1.49	68.14	14.07	0.00	150.0	± 9.6 %
		Y	1.71	70.53	15.29		150.0	
		Z	1.38	67.47	13.43		150.0	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	0.87	65.35	12.59	0.00	150.0	± 9.6 %
		Y	0.98	67.67	13.90		150.0	
		Z	0.81	64.81	11.96		150.0	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	1.01	68.28	14.43	0.00	150.0	± 9.6 %
		Y	1.28	72.37	16.47		150.0	
		Z	0.94	67.61	13.77		150.0	
10293-AAB	CDMA2000, RC3, SO3, Full Rate	X	1.31	72.09	16.62	0.00	150.0	± 9.6 %
		Y	1.86	78.07	19.28		150.0	
		Z	1.24	71.48	16.00		150.0	
10295-AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	X	11.68	86.43	25.21	9.03	50.0	± 9.6 %
		Y	12.34	87.51	25.61		50.0	
		Z	12.30	87.31	25.27		50.0	
10297-AAB	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	2.80	69.32	16.34	0.00	150.0	± 9.6 %
		Y	2.92	70.37	16.97		150.0	
		Z	2.72	69.08	16.22		150.0	
10298-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	1.65	67.43	14.29	0.00	150.0	± 9.6 %
		Y	1.78	69.00	15.16		150.0	
		Z	1.54	66.87	13.72		150.0	
10299-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	3.71	73.80	16.79	0.00	150.0	± 9.6 %
		Y	4.50	76.98	18.19		150.0	
		Z	2.80	70.24	14.88		150.0	
10300-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	2.66	68.22	13.61	0.00	150.0	± 9.6 %
		Y	2.97	70.07	14.57		150.0	
		Z	2.16	65.95	12.13		150.0	
10301-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	X	5.56	67.67	18.53	4.17	80.0	± 9.6 %
		Y	5.78	68.72	19.18		80.0	
		Z	5.51	67.68	18.44		80.0	
10302-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	X	6.08	68.43	19.36	4.96	80.0	± 9.6 %
		Y	6.31	69.64	20.14		80.0	
		Z	6.00	68.40	19.26		80.0	

10303-AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	X	5.91	68.44	19.38	4.96	80.0	± 9.6 %
		Y	6.17	69.77	20.23		80.0	
		Z	5.83	68.37	19.25		80.0	
10304-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	X	5.57	67.76	18.57	4.17	80.0	± 9.6 %
		Y	5.77	68.85	19.27		80.0	
		Z	5.49	67.73	18.47		80.0	
10305-AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	X	7.72	78.82	24.99	6.02	50.0	± 9.6 %
		Y	9.80	85.05	27.90		50.0	
		Z	7.68	78.78	24.73		50.0	
10306-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	X	6.19	70.81	21.17	6.02	50.0	± 9.6 %
		Y	6.78	73.45	22.69		50.0	
		Z	6.09	70.68	20.96		50.0	
10307-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	X	6.23	71.39	21.28	6.02	50.0	± 9.6 %
		Y	6.93	74.34	22.91		50.0	
		Z	6.66	74.17	22.78		50.0	
10308-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	X	6.84	74.87	23.29	6.02	50.0	± 9.6 %
		Y	7.04	74.94	23.20		50.0	
		Z	6.77	74.83	23.10		50.0	
10309-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	X	6.29	71.13	21.36	6.02	50.0	± 9.6 %
		Y	6.92	73.87	22.92		50.0	
		Z	6.18	70.98	21.13		50.0	
10310-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	X	6.19	71.01	21.18	6.02	50.0	± 9.6 %
		Y	6.82	73.78	22.75		50.0	
		Z	6.55	73.55	22.58		50.0	
10311-AAB	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	3.15	68.64	16.01	0.00	150.0	± 9.6 %
		Y	3.28	69.57	16.56		150.0	
		Z	3.07	68.40	15.89		150.0	
10313-AAA	iDEN 1:3	X	7.93	80.00	19.43	6.99	70.0	± 9.6 %
		Y	8.50	81.06	19.83		70.0	
		Z	7.91	80.08	19.40		70.0	
10314-AAA	iDEN 1:6	X	10.36	86.77	24.35	10.00	30.0	± 9.6 %
		Y	11.09	87.90	24.72		30.0	
		Z	10.57	87.37	24.52		30.0	
10315-AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	1.16	64.08	15.18	0.17	150.0	± 9.6 %
		Y	1.19	64.95	15.92		150.0	
		Z	1.15	63.96	15.05		150.0	
10316-AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	X	4.74	66.85	16.40	0.17	150.0	± 9.6 %
		Y	4.75	67.05	16.58		150.0	
		Z	4.69	66.84	16.36		150.0	
10317-AAB	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	X	4.74	66.85	16.40	0.17	150.0	± 9.6 %
		Y	4.75	67.05	16.58		150.0	
		Z	4.69	66.84	16.36		150.0	
10400-AAC	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	4.83	67.07	16.30	0.00	150.0	± 9.6 %
		Y	4.84	67.29	16.50		150.0	
		Z	4.76	67.04	16.26		150.0	
10401-AAC	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	X	5.51	67.29	16.49	0.00	150.0	± 9.6 %
		Y	5.53	67.49	16.67		150.0	
		Z	5.49	67.36	16.51		150.0	

10402-AAC	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	X	5.79	67.69	16.53	0.00	150.0	± 9.6 %
		Y	5.79	67.83	16.67		150.0	
		Z	5.72	67.60	16.48		150.0	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	1.49	68.14	14.07	0.00	115.0	± 9.6 %
		Y	1.71	70.53	15.29		115.0	
		Z	1.38	67.47	13.43		115.0	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	1.49	68.14	14.07	0.00	115.0	± 9.6 %
		Y	1.71	70.53	15.29		115.0	
		Z	1.38	67.47	13.43		115.0	
10406-AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	X	100.00	122.23	31.08	0.00	100.0	± 9.6 %
		Y	100.00	122.94	31.38		100.0	
		Z	21.98	102.39	26.35		100.0	
10410-AAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	121.68	31.26	3.23	80.0	± 9.6 %
		Y	100.00	122.54	31.65		80.0	
		Z	100.00	121.97	31.19		80.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	1.03	62.73	14.35	0.00	150.0	± 9.6 %
		Y	1.04	63.46	15.05		150.0	
		Z	1.02	62.64	14.23		150.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	4.64	66.69	16.23	0.00	150.0	± 9.6 %
		Y	4.65	66.89	16.41		150.0	
		Z	4.59	66.68	16.20		150.0	
10417-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	X	4.64	66.69	16.23	0.00	150.0	± 9.6 %
		Y	4.65	66.89	16.41		150.0	
		Z	4.59	66.68	16.20		150.0	
10418-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	X	4.63	66.83	16.23	0.00	150.0	± 9.6 %
		Y	4.64	67.04	16.42		150.0	
		Z	4.58	66.82	16.21		150.0	
10419-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	X	4.65	66.79	16.24	0.00	150.0	± 9.6 %
		Y	4.66	66.99	16.43		150.0	
		Z	4.60	66.78	16.21		150.0	
10422-AAA	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	X	4.78	66.81	16.27	0.00	150.0	± 9.6 %
		Y	4.78	67.00	16.45		150.0	
		Z	4.72	66.79	16.24		150.0	
10423-AAA	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	X	4.96	67.16	16.40	0.00	150.0	± 9.6 %
		Y	4.97	67.35	16.58		150.0	
		Z	4.89	67.12	16.36		150.0	
10424-AAA	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	X	4.88	67.10	16.36	0.00	150.0	± 9.6 %
		Y	4.88	67.30	16.54		150.0	
		Z	4.81	67.07	16.33		150.0	
10425-AAA	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	X	5.49	67.52	16.59	0.00	150.0	± 9.6 %
		Y	5.50	67.70	16.76		150.0	
		Z	5.44	67.51	16.58		150.0	
10426-AAA	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	X	5.49	67.54	16.59	0.00	150.0	± 9.6 %
		Y	5.50	67.71	16.76		150.0	
		Z	5.45	67.53	16.59		150.0	

10427-AAA	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	X	5.50	67.50	16.57	0.00	150.0	± 9.6 %
		Y	5.51	67.67	16.73		150.0	
		Z	5.45	67.48	16.56		150.0	
10430-AAA	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	X	4.25	70.00	17.85	0.00	150.0	± 9.6 %
		Y	4.23	70.09	17.93		150.0	
		Z	4.19	70.14	17.80		150.0	
10431-AAA	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	X	4.34	67.20	16.23	0.00	150.0	± 9.6 %
		Y	4.36	67.46	16.45		150.0	
		Z	4.27	67.18	16.16		150.0	
10432-AAA	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	X	4.64	67.12	16.31	0.00	150.0	± 9.6 %
		Y	4.65	67.34	16.50		150.0	
		Z	4.57	67.09	16.26		150.0	
10433-AAA	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	X	4.89	67.13	16.38	0.00	150.0	± 9.6 %
		Y	4.90	67.33	16.56		150.0	
		Z	4.82	67.10	16.34		150.0	
10434-AAA	W-CDMA (BS Test Model 1, 64 DPCH)	X	4.31	70.67	17.79	0.00	150.0	± 9.6 %
		Y	4.30	70.79	17.87		150.0	
		Z	4.25	70.82	17.71		150.0	
10435-AAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	121.51	31.18	3.23	80.0	± 9.6 %
		Y	100.00	122.37	31.57		80.0	
		Z	100.00	121.79	31.11		80.0	
10447-AAA	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.63	67.13	15.60	0.00	150.0	± 9.6 %
		Y	3.66	67.50	15.86		150.0	
		Z	3.54	67.07	15.44		150.0	
10448-AAA	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	4.17	66.96	16.08	0.00	150.0	± 9.6 %
		Y	4.19	67.23	16.30		150.0	
		Z	4.10	66.94	16.02		150.0	
10449-AAA	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	4.44	66.92	16.19	0.00	150.0	± 9.6 %
		Y	4.45	67.15	16.39		150.0	
		Z	4.38	66.90	16.14		150.0	
10450-AAA	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.63	66.87	16.23	0.00	150.0	± 9.6 %
		Y	4.64	67.08	16.41		150.0	
		Z	4.58	66.85	16.19		150.0	
10451-AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	X	3.53	67.33	15.28	0.00	150.0	± 9.6 %
		Y	3.57	67.74	15.55		150.0	
		Z	3.43	67.21	15.05		150.0	
10456-AAA	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	X	6.35	68.11	16.76	0.00	150.0	± 9.6 %
		Y	6.36	68.24	16.90		150.0	
		Z	6.31	68.06	16.74		150.0	
10457-AAA	UMTS-FDD (DC-HSDPA)	X	3.86	65.32	15.94	0.00	150.0	± 9.6 %
		Y	3.86	65.52	16.13		150.0	
		Z	3.83	65.31	15.89		150.0	
10458-AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	X	3.37	66.71	14.79	0.00	150.0	± 9.6 %
		Y	3.41	67.16	15.08		150.0	
		Z	3.26	66.61	14.51		150.0	
10459-AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	X	4.52	65.23	15.77	0.00	150.0	± 9.6 %
		Y	4.60	65.75	16.11		150.0	
		Z	4.38	65.07	15.54		150.0	

10460-AAA	UMTS-FDD (WCDMA, AMR)	X	0.89	66.92	15.35	0.00	150.0	± 9.6 %
		Y	1.01	69.93	17.18		150.0	
		Z	0.86	66.57	15.06		150.0	
10461-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	125.62	33.15	3.29	80.0	± 9.6 %
		Y	100.00	127.39	33.94		80.0	
		Z	100.00	125.16	32.74		80.0	
10462-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	110.62	25.96	3.23	80.0	± 9.6 %
		Y	100.00	111.65	26.39		80.0	
		Z	84.76	108.06	25.05		80.0	
10463-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	107.62	24.51	3.23	80.0	± 9.6 %
		Y	100.00	108.53	24.89		80.0	
		Z	14.33	86.37	18.99		80.0	
10464-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	123.78	32.14	3.23	80.0	± 9.6 %
		Y	100.00	125.58	32.94		80.0	
		Z	100.00	123.19	31.67		80.0	
10465-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	110.13	25.71	3.23	80.0	± 9.6 %
		Y	100.00	111.18	26.15		80.0	
		Z	35.58	97.99	22.58		80.0	
10466-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	95.39	106.65	24.18	3.23	80.0	± 9.6 %
		Y	100.00	108.07	24.67		80.0	
		Z	9.21	81.47	17.50		80.0	
10467-AAB	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	123.99	32.23	3.23	80.0	± 9.6 %
		Y	100.00	125.80	33.04		80.0	
		Z	100.00	123.41	31.77		80.0	
10468-AAB	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	110.29	25.79	3.23	80.0	± 9.6 %
		Y	100.00	111.34	26.23		80.0	
		Z	43.78	100.42	23.20		80.0	
10469-AAB	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	99.99	107.17	24.29	3.23	80.0	± 9.6 %
		Y	100.00	108.09	24.67		80.0	
		Z	9.38	81.68	17.56		80.0	
10470-AAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	124.02	32.24	3.23	80.0	± 9.6 %
		Y	100.00	125.83	33.05		80.0	
		Z	100.00	123.44	31.77		80.0	
10471-AAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	110.24	25.76	3.23	80.0	± 9.6 %
		Y	100.00	111.29	26.20		80.0	
		Z	43.76	100.38	23.18		80.0	
10472-AAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	107.12	24.26	3.23	80.0	± 9.6 %
		Y	100.00	108.04	24.64		80.0	
		Z	9.36	81.64	17.53		80.0	
10473-AAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	123.99	32.23	3.23	80.0	± 9.6 %
		Y	100.00	125.81	33.03		80.0	
		Z	100.00	123.41	31.76		80.0	
10474-AAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	110.25	25.76	3.23	80.0	± 9.6 %
		Y	100.00	111.30	26.20		80.0	
		Z	42.90	100.17	23.13		80.0	
10475-AAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	99.25	107.05	24.25	3.23	80.0	± 9.6 %
		Y	100.00	108.06	24.65		80.0	
		Z	9.24	81.52	17.50		80.0	

10477-AAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	110.09	25.68	3.23	80.0	± 9.6 %
		Y	100.00	111.14	26.12		80.0	
		Z	37.23	98.47	22.68		80.0	
10478-AAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	95.92	106.64	24.15	3.23	80.0	± 9.6 %
		Y	100.00	108.00	24.62		80.0	
		Z	9.13	81.36	17.44		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	15.99	96.17	26.79	3.23	80.0	± 9.6 %
		Y	25.94	104.65	29.40		80.0	
		Z	12.83	92.51	25.34		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	19.48	93.48	24.25	3.23	80.0	± 9.6 %
		Y	30.64	100.38	26.28		80.0	
		Z	12.85	87.46	22.08		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	16.00	89.85	22.83	3.23	80.0	± 9.6 %
		Y	23.58	95.63	24.59		80.0	
		Z	10.55	84.00	20.64		80.0	
10482-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.04	76.94	19.04	2.23	80.0	± 9.6 %
		Y	6.02	79.79	20.13		80.0	
		Z	4.78	76.30	18.55		80.0	
10483-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	9.12	82.48	20.94	2.23	80.0	± 9.6 %
		Y	10.77	85.20	21.94		80.0	
		Z	6.99	78.47	19.09		80.0	
10484-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	8.29	80.89	20.40	2.23	80.0	± 9.6 %
		Y	9.58	83.28	21.31		80.0	
		Z	6.43	77.10	18.60		80.0	
10485-AAB	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.28	77.72	20.08	2.23	80.0	± 9.6 %
		Y	6.19	80.50	21.18		80.0	
		Z	5.13	77.51	19.85		80.0	
10486-AAB	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.51	72.42	17.68	2.23	80.0	± 9.6 %
		Y	4.81	73.61	18.21		80.0	
		Z	4.36	72.13	17.34		80.0	
10487-AAB	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.47	71.97	17.49	2.23	80.0	± 9.6 %
		Y	4.74	73.05	17.98		80.0	
		Z	4.32	71.65	17.14		80.0	
10488-AAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.28	76.23	20.05	2.23	80.0	± 9.6 %
		Y	5.88	78.28	20.95		80.0	
		Z	5.13	76.06	19.94		80.0	
10489-AAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.61	71.60	18.35	2.23	80.0	± 9.6 %
		Y	4.82	72.56	18.83		80.0	
		Z	4.51	71.52	18.23		80.0	
10490-AAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.69	71.33	18.26	2.23	80.0	± 9.6 %
		Y	4.87	72.22	18.72		80.0	
		Z	4.59	71.26	18.14		80.0	
10491-AAB	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.21	74.00	19.31	2.23	80.0	± 9.6 %
		Y	5.57	75.36	19.96		80.0	
		Z	5.08	73.85	19.24		80.0	
10492-AAB	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.87	70.59	18.20	2.23	80.0	± 9.6 %
		Y	5.02	71.33	18.60		80.0	
		Z	4.77	70.51	18.12		80.0	

10493-AAB	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.93	70.41	18.14	2.23	80.0	± 9.6 %
		Y	5.07	71.11	18.53		80.0	
		Z	4.83	70.34	18.06		80.0	
10494-AAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.74	75.68	19.79	2.23	80.0	± 9.6 %
		Y	6.23	77.26	20.51		80.0	
		Z	5.57	75.46	19.70		80.0	
10495-AAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.94	71.08	18.40	2.23	80.0	± 9.6 %
		Y	5.11	71.86	18.83		80.0	
		Z	4.84	70.96	18.32		80.0	
10496-AAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.99	70.71	18.29	2.23	80.0	± 9.6 %
		Y	5.14	71.42	18.69		80.0	
		Z	4.89	70.61	18.21		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.95	73.39	16.94	2.23	80.0	± 9.6 %
		Y	4.59	75.63	17.82		80.0	
		Z	3.56	72.03	16.04		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.99	67.14	13.42	2.23	80.0	± 9.6 %
		Y	3.17	68.04	13.81		80.0	
		Z	2.58	65.48	12.27		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.90	66.50	13.01	2.23	80.0	± 9.6 %
		Y	3.06	67.30	13.36		80.0	
		Z	2.49	64.82	11.82		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.14	76.64	19.91	2.23	80.0	± 9.6 %
		Y	5.86	79.02	20.91		80.0	
		Z	5.00	76.51	19.75		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.55	72.03	17.90	2.23	80.0	± 9.6 %
		Y	4.80	73.10	18.41		80.0	
		Z	4.43	71.87	17.67		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.59	71.80	17.77	2.23	80.0	± 9.6 %
		Y	4.83	72.81	18.25		80.0	
		Z	4.47	71.64	17.53		80.0	
10503-AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.22	76.03	19.96	2.23	80.0	± 9.6 %
		Y	5.81	78.08	20.86		80.0	
		Z	5.07	75.86	19.85		80.0	
10504-AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.59	71.52	18.30	2.23	80.0	± 9.6 %
		Y	4.80	72.48	18.79		80.0	
		Z	4.49	71.43	18.18		80.0	
10505-AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.66	71.24	18.21	2.23	80.0	± 9.6 %
		Y	4.85	72.13	18.67		80.0	
		Z	4.56	71.17	18.09		80.0	
10506-AAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.69	75.54	19.72	2.23	80.0	± 9.6 %
		Y	6.18	77.12	20.44		80.0	
		Z	5.52	75.31	19.63		80.0	
10507-AAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.93	71.03	18.37	2.23	80.0	± 9.6 %
		Y	5.09	71.81	18.80		80.0	
		Z	4.82	70.90	18.29		80.0	

10508-AAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.98	70.65	18.25	2.23	80.0	± 9.6 %
		Y	5.12	71.36	18.65		80.0	
		Z	4.87	70.54	18.17		80.0	
10509-AAB	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.75	73.61	18.99	2.23	80.0	± 9.6 %
		Y	6.04	74.62	19.49		80.0	
		Z	5.61	73.42	18.92		80.0	
10510-AAB	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.37	70.52	18.25	2.23	80.0	± 9.6 %
		Y	5.50	71.12	18.60		80.0	
		Z	5.26	70.38	18.18		80.0	
10511-AAB	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	5.39	70.20	18.16	2.23	80.0	± 9.6 %
		Y	5.51	70.76	18.50		80.0	
		Z	5.29	70.08	18.10		80.0	
10512-AAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	6.17	75.45	19.55	2.23	80.0	± 9.6 %
		Y	6.61	76.77	20.16		80.0	
		Z	5.99	75.18	19.45		80.0	
10513-AAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.29	70.93	18.40	2.23	80.0	± 9.6 %
		Y	5.44	71.61	18.78		80.0	
		Z	5.18	70.76	18.31		80.0	
10514-AAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	5.26	70.42	18.25	2.23	80.0	± 9.6 %
		Y	5.39	71.03	18.61		80.0	
		Z	5.16	70.27	18.17		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	0.99	62.88	14.39	0.00	150.0	± 9.6 %
		Y	1.01	63.69	15.14		150.0	
		Z	0.98	62.78	14.25		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	0.57	67.90	15.77	0.00	150.0	± 9.6 %
		Y	0.79	74.76	19.51		150.0	
		Z	0.54	67.33	15.34		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.83	64.48	14.80	0.00	150.0	± 9.6 %
		Y	0.88	66.11	16.05		150.0	
		Z	0.82	64.26	14.59		150.0	
10518-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.64	66.76	16.21	0.00	150.0	± 9.6 %
		Y	4.64	66.97	16.39		150.0	
		Z	4.58	66.75	16.17		150.0	
10519-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.84	67.04	16.35	0.00	150.0	± 9.6 %
		Y	4.85	67.24	16.53		150.0	
		Z	4.77	67.00	16.30		150.0	
10520-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.69	67.00	16.26	0.00	150.0	± 9.6 %
		Y	4.70	67.20	16.45		150.0	
		Z	4.62	66.95	16.22		150.0	
10521-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.62	66.99	16.24	0.00	150.0	± 9.6 %
		Y	4.63	67.20	16.43		150.0	
		Z	4.55	66.94	16.20		150.0	
10522-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.67	67.03	16.31	0.00	150.0	± 9.6 %
		Y	4.69	67.25	16.50		150.0	
		Z	4.61	67.03	16.28		150.0	

10523-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.55	66.89	16.15	0.00	150.0	± 9.6 %
		Y	4.56	67.11	16.34		150.0	
		Z	4.49	66.88	16.12		150.0	
10524-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.62	66.97	16.28	0.00	150.0	± 9.6 %
		Y	4.63	67.19	16.48		150.0	
		Z	4.56	66.95	16.25		150.0	
10525-AAA	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.59	65.99	15.86	0.00	150.0	± 9.6 %
		Y	4.60	66.20	16.05		150.0	
		Z	4.54	65.98	15.83		150.0	
10526-AAA	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.77	66.38	16.01	0.00	150.0	± 9.6 %
		Y	4.79	66.60	16.20		150.0	
		Z	4.71	66.35	15.98		150.0	
10527-AAA	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.69	66.34	15.95	0.00	150.0	± 9.6 %
		Y	4.71	66.56	16.15		150.0	
		Z	4.63	66.30	15.91		150.0	
10528-AAA	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.71	66.36	15.99	0.00	150.0	± 9.6 %
		Y	4.72	66.58	16.18		150.0	
		Z	4.65	66.32	15.95		150.0	
10529-AAA	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.71	66.36	15.99	0.00	150.0	± 9.6 %
		Y	4.72	66.58	16.18		150.0	
		Z	4.65	66.32	15.95		150.0	
10531-AAA	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.71	66.48	16.01	0.00	150.0	± 9.6 %
		Y	4.73	66.71	16.20		150.0	
		Z	4.64	66.43	15.96		150.0	
10532-AAA	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.56	66.33	15.94	0.00	150.0	± 9.6 %
		Y	4.58	66.56	16.14		150.0	
		Z	4.50	66.27	15.89		150.0	
10533-AAA	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.72	66.39	15.97	0.00	150.0	± 9.6 %
		Y	4.73	66.61	16.16		150.0	
		Z	4.65	66.36	15.93		150.0	
10534-AAA	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	5.24	66.54	16.07	0.00	150.0	± 9.6 %
		Y	5.25	66.71	16.24		150.0	
		Z	5.19	66.49	16.04		150.0	
10535-AAA	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	5.31	66.70	16.14	0.00	150.0	± 9.6 %
		Y	5.33	66.88	16.31		150.0	
		Z	5.26	66.68	16.13		150.0	
10536-AAA	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	5.18	66.65	16.10	0.00	150.0	± 9.6 %
		Y	5.19	66.84	16.27		150.0	
		Z	5.12	66.60	16.07		150.0	
10537-AAA	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	5.24	66.63	16.10	0.00	150.0	± 9.6 %
		Y	5.25	66.81	16.26		150.0	
		Z	5.19	66.58	16.06		150.0	
10538-AAA	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	5.35	66.69	16.17	0.00	150.0	± 9.6 %
		Y	5.36	66.87	16.33		150.0	
		Z	5.28	66.62	16.12		150.0	
10540-AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	5.26	66.66	16.17	0.00	150.0	± 9.6 %
		Y	5.27	66.85	16.34		150.0	
		Z	5.21	66.63	16.14		150.0	

10541-AAA	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	5.23	66.53	16.10	0.00	150.0	± 9.6 %
		Y	5.24	66.71	16.26		150.0	
		Z	5.18	66.49	16.06		150.0	
10542-AAA	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.39	66.62	16.16	0.00	150.0	± 9.6 %
		Y	5.40	66.79	16.32		150.0	
		Z	5.34	66.57	16.12		150.0	
10543-AAA	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.48	66.66	16.19	0.00	150.0	± 9.6 %
		Y	5.49	66.83	16.36		150.0	
		Z	5.42	66.63	16.18		150.0	
10544-AAA	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.54	66.65	16.07	0.00	150.0	± 9.6 %
		Y	5.55	66.80	16.22		150.0	
		Z	5.50	66.61	16.04		150.0	
10545-AAA	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.76	67.11	16.24	0.00	150.0	± 9.6 %
		Y	5.77	67.28	16.40		150.0	
		Z	5.71	67.07	16.23		150.0	
10546-AAA	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.63	66.91	16.16	0.00	150.0	± 9.6 %
		Y	5.64	67.07	16.32		150.0	
		Z	5.57	66.84	16.12		150.0	
10547-AAA	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.72	67.00	16.20	0.00	150.0	± 9.6 %
		Y	5.72	67.16	16.35		150.0	
		Z	5.65	66.88	16.14		150.0	
10548-AAA	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	6.07	68.22	16.78	0.00	150.0	± 9.6 %
		Y	6.08	68.42	16.96		150.0	
		Z	5.98	68.06	16.70		150.0	
10550-AAA	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.65	66.89	16.16	0.00	150.0	± 9.6 %
		Y	5.66	67.05	16.31		150.0	
		Z	5.60	66.86	16.14		150.0	
10551-AAA	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.65	66.93	16.14	0.00	150.0	± 9.6 %
		Y	5.66	67.09	16.29		150.0	
		Z	5.60	66.87	16.11		150.0	
10552-AAA	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.56	66.71	16.04	0.00	150.0	± 9.6 %
		Y	5.57	66.86	16.19		150.0	
		Z	5.51	66.66	16.01		150.0	
10553-AAA	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.65	66.77	16.10	0.00	150.0	± 9.6 %
		Y	5.66	66.92	16.25		150.0	
		Z	5.60	66.70	16.07		150.0	
10554-AAA	IEEE 1602.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.95	67.04	16.18	0.00	150.0	± 9.6 %
		Y	5.96	67.19	16.31		150.0	
		Z	5.91	66.99	16.15		150.0	
10555-AAA	IEEE 1602.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	6.09	67.37	16.32	0.00	150.0	± 9.6 %
		Y	6.11	67.53	16.46		150.0	
		Z	6.05	67.32	16.29		150.0	
10556-AAA	IEEE 1602.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	6.11	67.40	16.33	0.00	150.0	± 9.6 %
		Y	6.12	67.56	16.47		150.0	
		Z	6.07	67.36	16.30		150.0	
10557-AAA	IEEE 1602.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	6.08	67.33	16.31	0.00	150.0	± 9.6 %
		Y	6.09	67.48	16.45		150.0	
		Z	6.03	67.26	16.27		150.0	

10558-AAA	IEEE 1602.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	6.14	67.52	16.42	0.00	150.0	± 9.6 %
		Y	6.15	67.67	16.56		150.0	
		Z	6.09	67.43	16.37		150.0	
10560-AAA	IEEE 1602.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	6.13	67.34	16.37	0.00	150.0	± 9.6 %
		Y	6.14	67.49	16.51		150.0	
		Z	6.07	67.26	16.33		150.0	
10561-AAA	IEEE 1602.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	6.05	67.31	16.39	0.00	150.0	± 9.6 %
		Y	6.06	67.47	16.54		150.0	
		Z	6.00	67.24	16.36		150.0	
10562-AAA	IEEE 1602.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	6.21	67.80	16.64	0.00	150.0	± 9.6 %
		Y	6.22	67.97	16.79		150.0	
		Z	6.14	67.67	16.57		150.0	
10563-AAA	IEEE 1602.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	6.60	68.52	16.95	0.00	150.0	± 9.6 %
		Y	6.61	68.70	17.11		150.0	
		Z	6.44	68.18	16.78		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	4.98	66.92	16.42	0.46	150.0	± 9.6 %
		Y	4.99	67.12	16.60		150.0	
		Z	4.93	66.90	16.38		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	5.22	67.37	16.73	0.46	150.0	± 9.6 %
		Y	5.23	67.55	16.90		150.0	
		Z	5.16	67.34	16.69		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	5.06	67.23	16.56	0.46	150.0	± 9.6 %
		Y	5.06	67.43	16.74		150.0	
		Z	4.99	67.19	16.51		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	5.08	67.57	16.87	0.46	150.0	± 9.6 %
		Y	5.08	67.74	17.03		150.0	
		Z	5.01	67.53	16.84		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	4.98	67.03	16.35	0.46	150.0	± 9.6 %
		Y	4.99	67.26	16.56		150.0	
		Z	4.91	67.01	16.31		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	5.02	67.62	16.91	0.46	150.0	± 9.6 %
		Y	5.03	67.78	17.06		150.0	
		Z	4.97	67.61	16.89		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	5.07	67.49	16.86	0.46	150.0	± 9.6 %
		Y	5.07	67.68	17.03		150.0	
		Z	5.00	67.48	16.83		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.33	65.38	15.85	0.46	130.0	± 9.6 %
		Y	1.37	66.42	16.66		130.0	
		Z	1.31	65.23	15.71		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.35	65.94	16.19	0.46	130.0	± 9.6 %
		Y	1.40	67.08	17.03		130.0	
		Z	1.33	65.79	16.04		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	2.45	84.59	22.30	0.46	130.0	± 9.6 %
		Y	10.53	109.30	30.18		130.0	
		Z	2.23	83.07	21.66		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.51	71.42	18.78	0.46	130.0	± 9.6 %
		Y	1.69	74.14	20.31		130.0	
		Z	1.47	71.09	18.56		130.0	

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.80	66.79	16.52	0.46	130.0	± 9.6 %
		Y	4.80	66.99	16.70		130.0	
		Z	4.74	66.78	16.48		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.82	66.93	16.57	0.46	130.0	± 9.6 %
		Y	4.83	67.13	16.75		130.0	
		Z	4.77	66.93	16.54		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	5.04	67.25	16.75	0.46	130.0	± 9.6 %
		Y	5.04	67.43	16.92		130.0	
		Z	4.97	67.22	16.71		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	4.93	67.39	16.83	0.46	130.0	± 9.6 %
		Y	4.93	67.57	17.00		130.0	
		Z	4.87	67.36	16.79		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.71	66.78	16.21	0.46	130.0	± 9.6 %
		Y	4.73	67.02	16.43		130.0	
		Z	4.65	66.73	16.16		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.76	66.79	16.23	0.46	130.0	± 9.6 %
		Y	4.77	67.05	16.45		130.0	
		Z	4.69	66.76	16.18		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.83	67.44	16.78	0.46	130.0	± 9.6 %
		Y	4.84	67.63	16.95		130.0	
		Z	4.77	67.41	16.74		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.66	66.56	16.03	0.46	130.0	± 9.6 %
		Y	4.68	66.83	16.26		130.0	
		Z	4.59	66.51	15.97		130.0	
10583-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.80	66.79	16.52	0.46	130.0	± 9.6 %
		Y	4.80	66.99	16.70		130.0	
		Z	4.74	66.78	16.48		130.0	
10584-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.82	66.93	16.57	0.46	130.0	± 9.6 %
		Y	4.83	67.13	16.75		130.0	
		Z	4.77	66.93	16.54		130.0	
10585-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	5.04	67.25	16.75	0.46	130.0	± 9.6 %
		Y	5.04	67.43	16.92		130.0	
		Z	4.97	67.22	16.71		130.0	
10586-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	4.93	67.39	16.83	0.46	130.0	± 9.6 %
		Y	4.93	67.57	17.00		130.0	
		Z	4.87	67.36	16.79		130.0	
10587-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.71	66.78	16.21	0.46	130.0	± 9.6 %
		Y	4.73	67.02	16.43		130.0	
		Z	4.65	66.73	16.16		130.0	
10588-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.76	66.79	16.23	0.46	130.0	± 9.6 %
		Y	4.77	67.05	16.45		130.0	
		Z	4.69	66.76	16.18		130.0	
10589-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.83	67.44	16.78	0.46	130.0	± 9.6 %
		Y	4.84	67.63	16.95		130.0	
		Z	4.77	67.41	16.74		130.0	
10590-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.66	66.56	16.03	0.46	130.0	± 9.6 %
		Y	4.68	66.83	16.26		130.0	
		Z	4.59	66.51	15.97		130.0	

10591-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.94	66.84	16.61	0.46	130.0	± 9.6 %
		Y	4.95	67.02	16.78		130.0	
		Z	4.89	66.83	16.58		130.0	
10592-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	5.11	67.18	16.74	0.46	130.0	± 9.6 %
		Y	5.11	67.36	16.91		130.0	
		Z	5.05	67.16	16.71		130.0	
10593-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	5.04	67.12	16.64	0.46	130.0	± 9.6 %
		Y	5.04	67.31	16.81		130.0	
		Z	4.97	67.08	16.60		130.0	
10594-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	5.09	67.26	16.77	0.46	130.0	± 9.6 %
		Y	5.09	67.44	16.95		130.0	
		Z	5.02	67.24	16.74		130.0	
10595-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	5.06	67.23	16.68	0.46	130.0	± 9.6 %
		Y	5.07	67.42	16.86		130.0	
		Z	4.99	67.20	16.64		130.0	
10596-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	5.00	67.23	16.68	0.46	130.0	± 9.6 %
		Y	5.01	67.44	16.87		130.0	
		Z	4.93	67.20	16.65		130.0	
10597-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	4.95	67.15	16.58	0.46	130.0	± 9.6 %
		Y	4.96	67.36	16.77		130.0	
		Z	4.88	67.11	16.54		130.0	
10598-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	4.92	67.37	16.82	0.46	130.0	± 9.6 %
		Y	4.93	67.55	16.99		130.0	
		Z	4.86	67.32	16.78		130.0	
10599-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.62	67.44	16.83	0.46	130.0	± 9.6 %
		Y	5.62	67.59	16.99		130.0	
		Z	5.57	67.41	16.81		130.0	
10600-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.83	68.08	17.13	0.46	130.0	± 9.6 %
		Y	5.83	68.26	17.31		130.0	
		Z	5.75	67.98	17.08		130.0	
10601-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.67	67.70	16.95	0.46	130.0	± 9.6 %
		Y	5.68	67.87	17.12		130.0	
		Z	5.61	67.65	16.92		130.0	
10602-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.76	67.70	16.88	0.46	130.0	± 9.6 %
		Y	5.77	67.88	17.05		130.0	
		Z	5.71	67.69	16.87		130.0	
10603-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.83	67.96	17.13	0.46	130.0	± 9.6 %
		Y	5.84	68.14	17.30		130.0	
		Z	5.78	67.93	17.11		130.0	
10604-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.62	67.40	16.84	0.46	130.0	± 9.6 %
		Y	5.63	67.56	17.00		130.0	
		Z	5.57	67.37	16.81		130.0	
10605-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.75	67.79	17.04	0.46	130.0	± 9.6 %
		Y	5.76	67.98	17.22		130.0	
		Z	5.71	67.80	17.04		130.0	
10606-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.50	67.17	16.59	0.46	130.0	± 9.6 %
		Y	5.51	67.36	16.78		130.0	
		Z	5.45	67.15	16.57		130.0	

10607-AAA	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.77	66.11	16.20	0.46	130.0	± 9.6 %
		Y	4.78	66.31	16.38		130.0	
		Z	4.72	66.10	16.17		130.0	
10608-AAA	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	4.97	66.53	16.37	0.46	130.0	± 9.6 %
		Y	4.98	66.73	16.55		130.0	
		Z	4.91	66.51	16.34		130.0	
10609-AAA	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.86	66.39	16.22	0.46	130.0	± 9.6 %
		Y	4.87	66.61	16.41		130.0	
		Z	4.80	66.37	16.19		130.0	
10610-AAA	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.91	66.54	16.37	0.46	130.0	± 9.6 %
		Y	4.92	66.75	16.55		130.0	
		Z	4.85	66.52	16.34		130.0	
10611-AAA	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.83	66.37	16.24	0.46	130.0	± 9.6 %
		Y	4.84	66.58	16.42		130.0	
		Z	4.77	66.34	16.20		130.0	
10612-AAA	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.85	66.53	16.28	0.46	130.0	± 9.6 %
		Y	4.86	66.77	16.48		130.0	
		Z	4.78	66.50	16.25		130.0	
10613-AAA	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.86	66.45	16.19	0.46	130.0	± 9.6 %
		Y	4.87	66.68	16.39		130.0	
		Z	4.79	66.40	16.14		130.0	
10614-AAA	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.79	66.59	16.39	0.46	130.0	± 9.6 %
		Y	4.80	66.80	16.57		130.0	
		Z	4.72	66.55	16.34		130.0	
10615-AAA	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.84	66.22	16.03	0.46	130.0	± 9.6 %
		Y	4.85	66.46	16.24		130.0	
		Z	4.77	66.19	15.99		130.0	
10616-AAA	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.43	66.66	16.42	0.46	130.0	± 9.6 %
		Y	5.44	66.83	16.58		130.0	
		Z	5.38	66.62	16.39		130.0	
10617-AAA	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.49	66.80	16.46	0.46	130.0	± 9.6 %
		Y	5.50	66.99	16.63		130.0	
		Z	5.45	66.83	16.47		130.0	
10618-AAA	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.38	66.84	16.49	0.46	130.0	± 9.6 %
		Y	5.39	67.01	16.65		130.0	
		Z	5.33	66.80	16.47		130.0	
10619-AAA	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.41	66.69	16.36	0.46	130.0	± 9.6 %
		Y	5.42	66.88	16.53		130.0	
		Z	5.36	66.66	16.34		130.0	
10620-AAA	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.51	66.76	16.45	0.46	130.0	± 9.6 %
		Y	5.52	66.94	16.61		130.0	
		Z	5.45	66.69	16.40		130.0	
10621-AAA	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.49	66.80	16.57	0.46	130.0	± 9.6 %
		Y	5.49	66.95	16.72		130.0	
		Z	5.43	66.76	16.55		130.0	
10622-AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.50	66.97	16.65	0.46	130.0	± 9.6 %
		Y	5.51	67.14	16.81		130.0	
		Z	5.46	66.96	16.64		130.0	

10623-AAA	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	5.38	66.52	16.31	0.46	130.0	± 9.6 %
		Y	5.39	66.70	16.48		130.0	
		Z	5.33	66.49	16.29		130.0	
10624-AAA	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.58	66.73	16.48	0.46	130.0	± 9.6 %
		Y	5.59	66.90	16.64		130.0	
		Z	5.52	66.69	16.46		130.0	
10625-AAA	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	6.03	67.94	17.14	0.46	130.0	± 9.6 %
		Y	6.04	68.15	17.32		130.0	
		Z	5.94	67.84	17.08		130.0	
10626-AAA	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.70	66.70	16.37	0.46	130.0	± 9.6 %
		Y	5.71	66.85	16.51		130.0	
		Z	5.66	66.67	16.35		130.0	
10627-AAA	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	5.98	67.34	16.65	0.46	130.0	± 9.6 %
		Y	5.99	67.51	16.80		130.0	
		Z	5.93	67.32	16.64		130.0	
10628-AAA	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.76	66.88	16.35	0.46	130.0	± 9.6 %
		Y	5.78	67.04	16.51		130.0	
		Z	5.72	66.82	16.32		130.0	
10629-AAA	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.85	66.94	16.38	0.46	130.0	± 9.6 %
		Y	5.86	67.11	16.54		130.0	
		Z	5.81	66.93	16.37		130.0	
10630-AAA	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	6.47	68.96	17.39	0.46	130.0	± 9.6 %
		Y	6.50	69.20	17.59		130.0	
		Z	6.37	68.78	17.30		130.0	
10631-AAA	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	6.25	68.39	17.28	0.46	130.0	± 9.6 %
		Y	6.25	68.53	17.42		130.0	
		Z	6.15	68.22	17.20		130.0	
10632-AAA	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.93	67.33	16.77	0.46	130.0	± 9.6 %
		Y	5.93	67.47	16.90		130.0	
		Z	5.89	67.32	16.77		130.0	
10633-AAA	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.83	67.02	16.45	0.46	130.0	± 9.6 %
		Y	5.83	67.17	16.59		130.0	
		Z	5.76	66.93	16.40		130.0	
10634-AAA	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.80	67.01	16.50	0.46	130.0	± 9.6 %
		Y	5.81	67.15	16.64		130.0	
		Z	5.75	66.94	16.47		130.0	
10635-AAA	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.71	66.44	15.97	0.46	130.0	± 9.6 %
		Y	5.72	66.63	16.15		130.0	
		Z	5.64	66.35	15.92		130.0	
10636-AAA	IEEE 1602.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	6.12	67.11	16.48	0.46	130.0	± 9.6 %
		Y	6.13	67.25	16.62		130.0	
		Z	6.09	67.07	16.46		130.0	
10637-AAA	IEEE 1602.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	6.30	67.52	16.67	0.46	130.0	± 9.6 %
		Y	6.31	67.68	16.81		130.0	
		Z	6.26	67.49	16.65		130.0	
10638-AAA	IEEE 1602.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	6.30	67.50	16.63	0.46	130.0	± 9.6 %
		Y	6.31	67.65	16.78		130.0	
		Z	6.26	67.46	16.61		130.0	

10639-AAA	IEEE 1602.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	6.28	67.46	16.65	0.46	130.0	± 9.6 %
		Y	6.28	67.59	16.79		130.0	
		Z	6.23	67.38	16.62		130.0	
10640-AAA	IEEE 1602.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	6.30	67.54	16.64	0.46	130.0	± 9.6 %
		Y	6.31	67.70	16.79		130.0	
		Z	6.24	67.43	16.59		130.0	
10641-AAA	IEEE 1602.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	6.31	67.32	16.55	0.46	130.0	± 9.6 %
		Y	6.32	67.48	16.70		130.0	
		Z	6.28	67.31	16.54		130.0	
10642-AAA	IEEE 1602.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	6.36	67.59	16.84	0.46	130.0	± 9.6 %
		Y	6.36	67.71	16.97		130.0	
		Z	6.31	67.52	16.81		130.0	
10643-AAA	IEEE 1602.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	6.20	67.31	16.61	0.46	130.0	± 9.6 %
		Y	6.21	67.47	16.77		130.0	
		Z	6.16	67.26	16.58		130.0	
10644-AAA	IEEE 1602.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	6.42	67.97	16.97	0.46	130.0	± 9.6 %
		Y	6.43	68.15	17.13		130.0	
		Z	6.34	67.82	16.88		130.0	
10645-AAA	IEEE 1602.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.93	69.02	17.44	0.46	130.0	± 9.6 %
		Y	6.97	69.27	17.65		130.0	
		Z	6.82	68.81	17.34		130.0	
10646-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	47.20	124.94	41.34	9.30	60.0	± 9.6 %
		Y	100.00	143.87	46.72		60.0	
		Z	42.87	123.31	40.85		60.0	
10647-AAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	47.80	126.16	41.84	9.30	60.0	± 9.6 %
		Y	100.00	144.94	47.17		60.0	
		Z	42.80	124.20	41.27		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	0.75	63.57	11.13	0.00	150.0	± 9.6 %
		Y	0.80	64.99	12.02		150.0	
		Z	0.70	63.11	10.54		150.0	

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.