Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5260MHz
Channel: 52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10520.00	Peak	H	-	-	-72.46	19.25	0.00	53.79	68.20	-14.41
*	15780.00	Average	H	-	-	-85.01	27.22	0.00	49.21	53.98	-4.77
*	15780.00	Peak	H	-	-	-73.45	27.22	0.00	60.77	73.98	-13.21
*	21040.00	Average	H	-	-	-81.09	17.32	-9.54	33.69	53.98	-20.29
*	21040.00	Peak	H	-	-	-70.06	17.32	-9.54	44.72	73.98	-29.26
	26300.00	Peak	H	-	-	-68.27	20.12	-9.54	49.31	68.20	-18.89

Table 7-122. Radiated Measurements SISO ANT1 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5280MHz
Channel: 56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10560.00	Peak	H	-	-	-71.72	19.37	0.00	54.65	68.20	-13.55
*	15840.00	Average	H	-	-	-84.94	27.28	0.00	49.34	53.98	-4.64
*	15840.00	Peak	H	-	-	-73.24	27.28	0.00	61.04	73.98	-12.94
*	21120.00	Average	H	-	-	-81.02	17.26	-9.54	33.70	53.98	-20.28
*	21120.00	Peak	H	-	-	-69.87	17.26	-9.54	44.85	73.98	-29.13
	26400.00	Peak	H	-	-	-67.77	19.67	-9.54	49.36	68.20	-18.84

Table 7-123. Radiated Measurements SISO ANT1 (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5320MHz
Channel: 64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	H	-	-	-83.37	20.07	0.00	43.70	53.98	-10.28
*	10640.00	Peak	H	-	-	-72.26	20.07	0.00	54.81	73.98	-19.17
*	15960.00	Average	H	-	-	-85.00	27.42	0.00	49.42	53.98	-4.56
*	15960.00	Peak	H	-	-	-73.95	27.42	0.00	60.47	73.98	-13.51
*	21280.00	Average	H	-	-	-81.21	17.51	-9.54	33.76	53.98	-20.22
*	21280.00	Peak	H	-	-	-69.50	17.51	-9.54	45.47	73.98	-28.51
	26600.00	Peak	H	-	-	-49.95	1.44	-9.54	48.95	68.20	-19.25

Table 7-124. Radiated Measurements SISO ANT1 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5260MHz
Channel: 52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	H	-	-	-83.67	20.07	0.00	43.40	53.98	-10.58
*	10640.00	Peak	H	-	-	-72.38	20.07	0.00	54.69	73.98	-19.29
*	15960.00	Average	H	-	-	-84.97	27.42	0.00	49.45	53.98	-4.53
*	15960.00	Peak	H	-	-	-74.30	27.42	0.00	60.12	73.98	-13.86
*	21280.00	Average	H	-	-	-81.67	17.51	-9.54	33.30	53.98	-20.68
*	21280.00	Peak	H	-	-	-70.38	17.51	-9.54	44.59	73.98	-29.39

Table 7-125. Radiated Measurements SISO ANT1 (106 Tones)with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5500MHz
Channel: 100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11000.00	Average	H	-	-	-84.02	20.71	0.00	43.69	53.98	-10.29
*	11000.00	Peak	H	-	-	-73.84	20.71	0.00	53.87	73.98	-20.11
	16500.00	Peak	H	-	-	-73.17	28.80	0.00	62.63	68.20	-5.57
	22000.00	Peak	H	-	-	-68.94	18.25	-9.54	46.77	68.20	-21.43
	27500.00	Peak	H	-	-	-49.94	0.12	-9.54	47.64	68.20	-20.56

Table 7-126. Radiated Measurements SISO ANT1 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5600MHz
Channel: 120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-83.53	20.02	0.00	43.49	53.98	-10.49
*	11200.00	Peak	H	-	-	-72.63	20.02	0.00	54.39	73.98	-19.59
	16800.00	Peak	H	-	-	-73.89	28.89	0.00	62.00	68.20	-6.20
*	22400.00	Average	H	-	-	-80.90	19.00	-9.54	35.56	53.98	-18.42
*	22400.00	Peak	H	-	-	-69.45	19.00	-9.54	47.01	73.98	-26.97
	28000.00	Peak	H	-	-	-49.97	0.74	-9.54	48.22	68.20	-19.98

Table 7-127. Radiated Measurements SISO ANT1 (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5720MHz
Channel: 144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11440.00	Average	H	-	-	-84.21	20.76	0.00	43.55	53.98	-10.43
*	11440.00	Peak	H	-	-	-72.73	20.76	0.00	55.03	73.98	-18.95
	17160.00	Peak	H	-	-	-73.88	29.65	0.00	62.77	68.20	-5.43
*	22880.00	Average	H	-	-	-81.21	18.40	-9.54	34.65	53.98	-19.33
*	22880.00	Peak	H	-	-	-70.09	18.40	-9.54	45.77	73.98	-28.21
	28600.00	Peak	H	-	-	-50.05	0.41	-9.54	47.82	68.20	-20.38

Table 7-128. Radiated Measurements SISO ANT1 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5600MHz
Channel: 120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-82.67	20.02	0.00	44.35	53.98	-9.63
*	11200.00	Peak	H	-	-	-73.28	20.02	0.00	53.74	73.98	-20.24
	16800.00	Peak	H	-	-	-76.00	28.89	0.00	59.89	68.20	-8.31
*	22400.00	Average	H	-	-	-80.67	19.00	-9.54	35.79	53.98	-18.19
*	22400.00	Peak	H	-	-	-68.81	19.00	-9.54	47.65	73.98	-26.33
	28000.00	Peak	H	-	-	-49.77	0.74	-9.54	48.42	68.20	-19.78

Table 7-129. Radiated Measurements SISO ANT1 (106 Tones)with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5745MHz
Channel: 149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11490.00	Average	H	-	-	-83.83	20.29	0.00	43.46	53.98	-10.52
*	11490.00	Peak	H	-	-	-73.02	20.29	0.00	54.27	73.98	-19.71
	17235.00	Peak	H	-	-	-72.97	29.45	0.00	63.48	68.20	-4.72
*	22980.00	Average	H	-	-	-81.42	17.92	-9.54	33.96	53.98	-20.02
*	22980.00	Peak	H	-	-	-70.10	17.92	-9.54	45.28	73.98	-28.70
	28725.00	Peak	H	-	-	-50.14	0.67	-9.54	47.99	68.20	-20.21

Table 7-130. Radiated Measurements SISO ANT1 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5785MHz
Channel: 157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	H	-	-	-83.67	20.87	0.00	44.20	53.98	-9.78
*	11570.00	Peak	H	-	-	-72.58	20.87	0.00	55.29	73.98	-18.69
	17355.00	Peak	H	-	-	-73.40	29.88	0.00	63.48	68.20	-4.72
	23140.00	Peak	H	-	-	-69.81	18.32	-9.54	45.97	68.20	-22.23
	28925.00	Peak	H	-	-	-49.54	0.75	-9.54	48.67	68.20	-19.53

Table 7-131. Radiated Measurements SISO ANT1 (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5825MHz
Channel:	165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11650.00	Average	H	-	-	-83.66	21.73	0.00	45.07	53.98	-8.91
*	11650.00	Peak	H	-	-	-71.78	21.73	0.00	56.95	73.98	-17.03
	17475.00	Peak	H	-	-	-73.21	30.16	0.00	63.95	68.20	-4.25
	23300.00	Peak	H	-	-	-70.08	18.77	-9.54	46.15	68.20	-22.05
	29125.00	Peak	H	-	-	-49.82	-0.12	-9.54	47.52	68.20	-20.68

Table 7-132. Radiated Measurements SISO ANT1 (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	H	-	-	-84.28	20.87	0.00	43.59	53.98	-10.39
*	11570.00	Peak	H	-	-	-73.37	20.87	0.00	54.50	73.98	-19.48
	17355.00	Peak	H	-	-	-74.08	29.88	0.00	62.80	68.20	-5.40
	23140.00	Peak	H	-	-	-70.01	18.32	-9.54	45.77	68.20	-22.43
	28925.00	Peak	H	-	-	-49.68	0.75	-9.54	48.53	68.20	-19.67

Table 7-133. Radiated Measurements SISO ANT1 (106 Tones)with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

242 Tones



Plot 7-631. Radiated Spurious Plot above 1GHz SISO ANT1 (802.11ax – U1 Ch. 40 – 242 Tones)



Plot 7-632. Radiated Spurious Plot above 1GHz SISO ANT1 (802.11ax – U2A Ch. 56 – 242 Tones)



Plot 7-633. Radiated Spurious Plot above 1GHz SISO ANT1 (802.11ax – U2C Ch. 120 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.



Plot 7-634. Radiated Spurious Plot above 1GHz SISO ANT1 (802.11ax – U3 Ch. 157 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

SISO Antenna-1 Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-635. Radiated Spurious Plot 18GHz - 26.5GHz SISO ANT1 (802.11ax – 242 Tones)



Plot 7-636. Radiated Spurious Plot 26.5GHz - 40GHz SISO ANT1 (802.11ax – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

SISO Antenna-1 Radiated Spurious Emission Measurements (242 Tones)

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5180MHz
Channel: 36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10360.00	Peak	H	-	-	-72.07	18.99	0.00	53.92	68.20	-14.28
*	15540.00	Average	H	-	-	-85.14	27.73	0.00	49.59	53.98	-4.39
*	15540.00	Peak	H	-	-	-74.43	27.73	0.00	60.30	73.98	-13.68
*	20720.00	Average	H	-	-	-81.41	16.92	-9.54	32.97	53.98	-21.01
*	20720.00	Peak	H	-	-	-70.13	16.92	-9.54	44.25	73.98	-29.73
	25900.00	Peak	H	-	-	-68.04	19.39	-9.54	48.81	68.20	-19.39

Table 7-134. Radiated Measurements SISO ANT1 (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5200MHz
Channel: 40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10400.00	Peak	H	-	-	-72.42	19.36	0.00	53.94	68.20	-14.26
*	15600.00	Average	H	-	-	-85.46	27.61	0.00	49.15	53.98	-4.83
*	15600.00	Peak	H	-	-	-74.08	27.61	0.00	60.53	73.98	-13.45
*	20800.00	Average	H	-	-	-81.28	17.39	-9.54	33.56	53.98	-20.41
*	20800.00	Peak	H	-	-	-69.98	17.39	-9.54	44.86	73.98	-29.11
	26000.00	Peak	H	-	-	-67.99	19.98	-9.54	49.44	68.20	-18.76

Table 7-135. Radiated Measurements SISO ANT1 (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5240MHz
Channel:	48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10480.00	Peak	H	-	-	-72.45	19.72	0.00	54.27	68.20	-13.93
*	15720.00	Average	H	-	-	-86.01	27.41	0.00	48.40	53.98	-5.58
*	15720.00	Peak	H	-	-	-73.38	27.41	0.00	61.03	73.98	-12.95
*	20960.00	Average	H	-	-	-81.42	17.29	-9.54	33.33	53.98	-20.65
*	20960.00	Peak	H	-	-	-70.28	17.29	-9.54	44.47	73.98	-29.51
	26200.00	Peak	H	-	-	-68.12	19.80	-9.54	49.14	68.20	-19.06

Table 7-136. Radiated Measurements SISO ANT1 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10360.00	Peak	H	-	-	-73.18	18.99	0.00	52.81	68.20	-15.39
*	15540.00	Average	H	-	-	-84.39	27.73	0.00	50.34	53.98	-3.64
*	15540.00	Peak	H	-	-	-75.07	27.73	0.00	59.66	73.98	-14.32
*	20720.00	Average	H	-	-	-81.32	17.39	-9.54	33.52	53.98	-20.45
*	20720.00	Peak	H	-	-	-70.57	17.39	-9.54	44.27	73.98	-29.70
	25900.00	Peak	H	-	-	-67.75	19.98	-9.54	49.68	68.20	-18.52

Table 7-137. Radiated Measurements SISO ANT1 with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5260MHz
Channel: 52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10520.00	Peak	H	-	-	-72.45	19.44	0.00	53.99	68.20	-14.21
*	15780.00	Average	H	-	-	-85.54	27.10	0.00	48.56	53.98	-5.42
*	15780.00	Peak	H	-	-	-74.44	27.10	0.00	59.66	73.98	-14.32
*	21040.00	Average	H	-	-	-81.27	17.32	-9.54	33.51	53.98	-20.47
*	21040.00	Peak	H	-	-	-69.87	17.32	-9.54	44.91	73.98	-29.07
	26300.00	Peak	H	-	-	-68.97	20.12	-9.54	48.61	68.20	-19.59

Table 7-138. Radiated Measurements SISO ANT1 (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5280MHz
Channel: 56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10560.00	Peak	H	-	-	-72.88	19.62	0.00	53.74	68.20	-14.46
*	15840.00	Average	H	-	-	-85.52	27.05	0.00	48.53	53.98	-5.45
*	15840.00	Peak	H	-	-	-73.84	27.05	0.00	60.21	73.98	-13.77
*	21120.00	Average	H	-	-	-80.98	17.26	-9.54	33.74	53.98	-20.24
*	21120.00	Peak	H	-	-	-69.17	17.26	-9.54	45.55	73.98	-28.43
	26400.00	Peak	H	-	-	-68.08	19.67	-9.54	49.05	68.20	-19.15

Table 7-139. Radiated Measurements SISO ANT1 (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5320MHz
Channel:	64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	H	-	-	-83.65	19.97	0.00	43.32	53.98	-10.66
*	10640.00	Peak	H	-	-	-72.33	19.97	0.00	54.64	73.98	-19.34
*	15960.00	Average	H	-	-	-85.57	27.35	0.00	48.78	53.98	-5.20
*	15960.00	Peak	H	-	-	-73.49	27.35	0.00	60.86	73.98	-13.12
*	21280.00	Average	H	-	-	-80.68	17.51	-9.54	34.29	53.98	-19.69
*	21280.00	Peak	H	-	-	-69.48	17.51	-9.54	45.49	73.98	-28.49
	26600.00	Peak	H	-	-	-49.82	1.44	-9.54	49.08	68.20	-19.12

Table 7-140. Radiated Measurements SISO ANT1 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5320MHz
Channel:	64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	H	-	-	-84.31	19.97	0.00	42.66	53.98	-11.32
*	10640.00	Peak	H	-	-	-72.64	19.97	0.00	54.33	73.98	-19.65
*	15960.00	Average	H	-	-	-85.06	27.35	0.00	49.29	53.98	-4.69
*	15960.00	Peak	H	-	-	-74.07	27.35	0.00	60.28	73.98	-13.70
*	21280.00	Average	H	-	-	-82.75	17.51	-9.54	32.22	53.98	-21.76
*	21280.00	Peak	H	-	-	-70.24	17.51	-9.54	44.73	73.98	-29.25
	26600.00	Peak	H	-	-	-80.34	1.44	-9.54	18.56	68.20	-49.64

Table 7-141. Radiated Measurements SISO ANT1 with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11000.00	Average	H	-	-	-84.71	20.31	0.00	42.60	53.98	-11.38
*	11000.00	Peak	H	-	-	-73.18	20.31	0.00	54.13	73.98	-19.85
	16500.00	Peak	H	-	-	-72.83	28.49	0.00	62.66	68.20	-5.54
	22000.00	Peak	H	-	-	-69.66	18.25	-9.54	46.05	68.20	-22.15
	27500.00	Peak	H	-	-	-48.48	0.12	-9.54	49.10	68.20	-19.10

Table 7-142. Radiated Measurements SISO ANT1 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5600MHz
Channel:	120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-84.38	19.97	0.00	42.59	53.98	-11.39
*	11200.00	Peak	H	-	-	-72.53	19.97	0.00	54.44	73.98	-19.54
	16800.00	Peak	H	-	-	-73.53	28.82	0.00	62.29	68.20	-5.91
*	22400.00	Average	H	-	-	-81.49	19.00	-9.54	34.97	53.98	-19.01
*	22400.00	Peak	H	-	-	-70.16	19.00	-9.54	46.30	73.98	-27.68
	28000.00	Peak	H	-	-	-49.62	0.74	-9.54	48.57	68.20	-19.63

Table 7-143. Radiated Measurements SISO ANT1 (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5720MHz
Channel:	144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11440.00	Average	H	-	-	-84.33	20.26	0.00	42.93	53.98	-11.05
*	11440.00	Peak	H	-	-	-72.66	20.26	0.00	54.60	73.98	-19.38
	17160.00	Peak	H	-	-	-73.66	29.62	0.00	62.96	68.20	-5.24
*	22880.00	Average	H	-	-	-81.67	18.40	-9.54	34.19	53.98	-19.79
*	22880.00	Peak	H	-	-	-69.96	18.40	-9.54	45.90	73.98	-28.08
	28600.00	Peak	H	-	-	-48.73	0.41	-9.54	49.14	68.20	-19.06

Table 7-144. Radiated Measurements SISO ANT1 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5600MHz
Channel:	120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-83.61	19.97	0.00	43.36	53.98	-10.62
*	11200.00	Peak	H	-	-	-73.27	19.97	0.00	53.70	73.98	-20.28
	16800.00	Peak	H	-	-	-74.36	28.82	0.00	61.46	68.20	-6.74
*	22400.00	Average	H	-	-	-80.47	19.00	-9.54	35.99	69.20	-33.21
*	22400.00	Peak	H	-	-	-69.97	19.00	-9.54	46.49	70.20	-23.71
	28000.00	Peak	H	-	-	-49.14	0.74	-9.54	49.05	71.20	-22.15

Table 7-145. Radiated Measurements SISO ANT1 with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5745MHz
Channel:	149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11490.00	Average	H	-	-	-84.51	20.36	0.00	42.85	53.98	-11.13
*	11490.00	Peak	H	-	-	-72.43	20.36	0.00	54.93	73.98	-19.05
	17235.00	Peak	H	-	-	-72.77	29.51	0.00	63.74	68.20	-4.46
*	22980.00	Average	H	-	-	-81.67	17.92	-9.54	33.71	53.98	-20.27
*	22980.00	Peak	H	-	-	-70.65	17.92	-9.54	44.73	73.98	-29.25
	28725.00	Peak	H	-	-	-49.90	0.67	-9.54	48.23	68.20	-19.97

Table 7-146. Radiated Measurements SISO ANT1 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	H	-	-	-84.53	21.02	0.00	43.49	53.98	-10.49
*	11570.00	Peak	H	-	-	-73.37	21.02	0.00	54.65	73.98	-19.33
	17355.00	Peak	H	-	-	-72.88	29.63	0.00	63.75	68.20	-4.45
	23140.00	Peak	H	-	-	-69.54	18.32	-9.54	46.24	68.20	-21.96
	28925.00	Peak	H	-	-	-49.33	0.75	-9.54	48.88	68.20	-19.32

Table 7-147. Radiated Measurements SISO ANT1 (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5825MHz
Channel:	165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11650.00	Average	H	-	-	-84.63	21.21	0.00	43.58	53.98	-10.40
*	11650.00	Peak	H	-	-	-72.82	21.21	0.00	55.39	73.98	-18.59
	17475.00	Peak	H	-	-	-74.34	29.76	0.00	62.42	68.20	-5.78
	23300.00	Peak	H	-	-	-70.39	18.77	-9.54	45.84	68.20	-22.36
	29125.00	Peak	H	-	-	-48.70	-0.12	-9.54	48.64	68.20	-19.56

Table 7-148. Radiated Measurements SISO ANT1 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	H	-	-	-84.61	21.02	0.00	43.41	68.20	-24.79
*	11570.00	Peak	H	-	-	-74.95	21.02	0.00	53.07	69.20	-16.13
	17355.00	Peak	H	-	-	-73.08	29.63	0.00	63.55	70.20	-6.65
	23140.00	Peak	H	-	-	-70.29	18.32	-9.54	45.49	71.20	-25.71
	28925.00	Peak	H	-	-	-49.53	0.75	-9.54	48.68	72.20	-23.52

Table 7-149. Radiated Measurements SISO ANT1 with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.2 SISO Antenna-2 Radiated Spurious Emission Measurements (106 Tones)



Plot 7-637. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11ax – U1 Ch. 40 – 106 Tones)



Plot 7-638. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11ax – U2A Ch. 56 – 106 Tones)



Plot 7-639. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11ax – U2C Ch. 120 – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.



Plot 7-640. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11ax – U3 Ch. 157 – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

SISO Antenna-2 Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-641. Radiated Spurious Plot 18GHz - 26.5GHz SISO ANT2 (802.11ax – 106 Tones)



Plot 7-642. Radiated Spurious Plot 26.5GHz - 40GHz SISO ANT2 (802.11ax – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

SISO Antenna-2 Radiated Spurious Emission Measurements (106 Tones)

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10360.00	Peak	H	-	-	-71.15	18.75	0.00	54.60	68.20	-13.60
*	15540.00	Average	H	-	-	-84.96	28.13	0.00	50.17	53.98	-3.81
*	15540.00	Peak	H	-	-	-73.51	28.13	0.00	61.62	73.98	-12.36
*	20720.00	Average	H	-	-	-81.51	16.92	-9.54	32.87	53.98	-21.11
*	20720.00	Peak	H	-	-	-70.23	16.92	-9.54	44.15	73.98	-29.83
	25900.00	Peak	H	-	-	-68.50	19.39	-9.54	48.35	68.20	-19.85

Table 7-150. Radiated Measurements SISO ANT2 (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5200MHz
Channel:	40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10400.00	Peak	H	-	-	-71.92	19.45	0.00	54.53	68.20	-13.67
*	15600.00	Average	H	-	-	-84.94	27.65	0.00	49.71	53.98	-4.27
*	15600.00	Peak	H	-	-	-74.45	27.65	0.00	60.20	73.98	-13.78
*	20800.00	Average	H	-	-	-81.39	17.39	-9.54	33.45	53.98	-20.52
*	20800.00	Peak	H	-	-	-70.14	17.39	-9.54	44.70	73.98	-29.27
	26000.00	Peak	H	-	-	-68.08	19.98	-9.54	49.35	68.20	-18.85

Table 7-151. Radiated Measurements SISO ANT2 (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5240MHz
Channel: 48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10480.00	Peak	H	-	-	-72.16	19.76	0.00	54.60	68.20	-13.60
*	15720.00	Average	H	-	-	-84.99	27.55	0.00	49.56	53.98	-4.42
*	15720.00	Peak	H	-	-	-74.58	27.55	0.00	59.97	73.98	-14.01
*	20960.00	Average	H	-	-	-81.24	17.29	-9.54	33.51	53.98	-20.47
*	20960.00	Peak	H	-	-	-70.48	17.29	-9.54	44.27	73.98	-29.71
	26200.00	Peak	H	-	-	-68.41	19.80	-9.54	48.85	68.20	-19.35

Table 7-152. Radiated Measurements SISO ANT2 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5200MHz
Channel: 40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10400.00	Peak	H	-	-	-72.05	19.45	0.00	54.40	68.20	-13.80
*	15600.00	Average	H	-	-	-83.97	27.65	0.00	50.68	53.98	-3.30
*	15600.00	Peak	H	-	-	-75.31	27.65	0.00	59.34	73.98	-14.64
*	20800.00	Average	H	-	-	-81.21	17.39	-9.54	33.63	53.98	-20.34
*	20800.00	Peak	H	-	-	-70.16	17.39	-9.54	44.68	73.98	-29.29
	26000.00	Peak	H	-	-	-68.17	19.98	-9.54	49.26	68.20	-18.94

Table 7-153. Radiated Measurements SISO ANT2 (106 Tones)with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5260MHz
Channel: 52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10520.00	Peak	H	-	-	-73.09	19.25	0.00	53.16	68.20	-15.04
*	15780.00	Average	H	-	-	-84.85	27.22	0.00	49.37	53.98	-4.61
*	15780.00	Peak	H	-	-	-73.68	27.22	0.00	60.54	73.98	-13.44
*	21040.00	Average	H	-	-	-81.09	17.32	-9.54	33.69	53.98	-20.29
*	21040.00	Peak	H	-	-	-70.06	17.32	-9.54	44.72	73.98	-29.26
	26300.00	Peak	H	-	-	-68.27	20.12	-9.54	49.31	68.20	-18.89

Table 7-154. Radiated Measurements SISO ANT2 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5280MHz
Channel: 56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10560.00	Peak	H	-	-	-71.67	19.37	0.00	54.70	68.20	-13.50
*	15840.00	Average	H	-	-	-84.88	27.28	0.00	49.40	53.98	-4.58
*	15840.00	Peak	H	-	-	-73.67	27.28	0.00	60.61	73.98	-13.37
*	21120.00	Average	H	-	-	-81.02	17.26	-9.54	33.70	53.98	-20.28
*	21120.00	Peak	H	-	-	-69.87	17.26	-9.54	44.85	73.98	-29.13
	26400.00	Peak	H	-	-	-67.77	19.67	-9.54	49.36	68.20	-18.84

Table 7-155. Radiated Measurements SISO ANT2 (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5320MHz
Channel: 64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	H	-	-	-83.13	20.07	0.00	43.94	53.98	-10.04
*	10640.00	Peak	H	-	-	-72.07	20.07	0.00	55.00	73.98	-18.98
*	15960.00	Average	H	-	-	-85.05	27.42	0.00	49.37	53.98	-4.61
*	15960.00	Peak	H	-	-	-73.85	27.42	0.00	60.57	73.98	-13.41
*	21280.00	Average	H	-	-	-81.21	17.51	-9.54	33.76	53.98	-20.22
*	21280.00	Peak	H	-	-	-69.50	17.51	-9.54	45.47	73.98	-28.51
	26600.00	Peak	H	-	-	-49.95	1.44	-9.54	48.95	68.20	-19.25

Table 7-156. Radiated Measurements SISO ANT2 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5260MHz
Channel: 52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10560.00	Peak	H	-	-	-73.18	19.37	0.00	53.19	68.20	-15.01
*	15840.00	Average	H	-	-	-84.99	27.28	0.00	49.29	53.98	-4.69
*	15840.00	Peak	H	-	-	-74.23	27.28	0.00	60.06	73.98	-13.92
*	21120.00	Average	H	-	-	-82.39	17.26	-9.54	32.33	53.98	-21.65
*	21120.00	Peak	H	-	-	-70.22	17.26	-9.54	44.50	73.98	-29.48
	26400.00	Peak	H	-	-	-68.99	19.67	-9.54	48.14	68.20	-20.06

Table 7-157. Radiated Measurements SISO ANT2 (106 Tones) with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11000.00	Average	H	-	-	-84.98	20.71	0.00	42.73	53.98	-11.25
*	11000.00	Peak	H	-	-	-72.11	20.71	0.00	55.60	73.98	-18.38
	16500.00	Peak	H	-	-	-72.97	28.80	0.00	62.83	68.20	-5.37
	22000.00	Peak	H	-	-	-69.29	18.25	-9.54	46.42	68.20	-21.78
	27500.00	Peak	H	-	-	-48.81	0.12	-9.54	48.77	68.20	-19.43

Table 7-158. Radiated Measurements SISO ANT2 (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5600MHz
Channel:	120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-84.47	20.02	0.00	42.55	53.98	-11.43
*	11200.00	Peak	H	-	-	-72.36	20.02	0.00	54.66	73.98	-19.32
	16800.00	Peak	H	-	-	-73.71	28.89	0.00	62.18	68.20	-6.02
*	22400.00	Average	H	-	-	-80.33	19.00	-9.54	36.13	53.98	-17.85
*	22400.00	Peak	H	-	-	-69.60	19.00	-9.54	46.86	73.98	-27.12
	28000.00	Peak	H	-	-	-48.75	0.74	-9.54	49.44	68.20	-18.76

Table 7-159. Radiated Measurements SISO ANT2 (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5720MHz
Channel:	144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11440.00	Average	H	-	-	-83.83	20.76	0.00	43.93	53.98	-10.05
*	11440.00	Peak	H	-	-	-73.22	20.76	0.00	54.54	73.98	-19.44
	17160.00	Peak	H	-	-	-73.58	29.65	0.00	63.07	68.20	-5.13
*	22880.00	Average	H	-	-	-80.52	18.40	-9.54	35.34	53.98	-18.64
*	22880.00	Peak	H	-	-	-68.86	18.40	-9.54	47.00	73.98	-26.98
	28600.00	Peak	H	-	-	-49.08	0.41	-9.54	48.79	68.20	-19.41

Table 7-160. Radiated Measurements SISO ANT2 (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5600MHz
Channel:	120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-84.67	20.02	0.00	42.35	53.98	-11.63
*	11200.00	Peak	H	-	-	-73.37	20.02	0.00	53.65	73.98	-20.33
	16800.00	Peak	H	-	-	-74.80	28.89	0.00	61.09	68.20	-7.11
*	22400.00	Average	H	-	-	-80.48	19.00	-9.54	35.98	53.98	-18.00
*	22400.00	Peak	H	-	-	-69.17	19.00	-9.54	47.29	73.98	-26.69
	28000.00	Peak	H	-	-	-48.96	0.74	-9.54	49.23	68.20	-18.97

Table 7-161. Radiated Measurements SISO ANT2 (106 Tones) with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5745MHz
Channel: 149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11490.00	Average	H	-	-	-83.55	20.29	0.00	43.74	53.98	-10.24
*	11490.00	Peak	H	-	-	-72.96	20.29	0.00	54.33	73.98	-19.65
	17235.00	Peak	H	-	-	-72.33	29.45	0.00	64.12	68.20	-4.08
*	22980.00	Average	H	-	-	-81.57	17.92	-9.54	33.81	53.98	-20.17
*	22980.00	Peak	H	-	-	-71.34	17.92	-9.54	44.04	73.98	-29.94
	28725.00	Peak	H	-	-	-49.89	0.67	-9.54	48.24	68.20	-19.96

Table 7-162. Radiated Measurements SISO ANT2 (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5785MHz
Channel: 157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	H	-	-	-83.62	20.87	0.00	44.25	53.98	-9.73
*	11570.00	Peak	H	-	-	-72.18	20.87	0.00	55.69	73.98	-18.29
	17355.00	Peak	H	-	-	-72.84	29.88	0.00	64.04	68.20	-4.16
	23140.00	Peak	H	-	-	-69.31	18.32	-9.54	46.47	68.20	-21.73
	28925.00	Peak	H	-	-	-50.27	0.75	-9.54	47.94	68.20	-20.26

Table 7-163. Radiated Measurements SISO ANT2 (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5825MHz
Channel:	165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11650.00	Average	H	-	-	-84.30	21.73	0.00	44.43	53.98	-9.55
*	11650.00	Peak	H	-	-	-72.14	21.73	0.00	56.59	73.98	-17.39
	17475.00	Peak	H	-	-	-73.73	30.16	0.00	63.43	68.20	-4.77
	23300.00	Peak	H	-	-	-70.67	18.77	-9.54	45.56	68.20	-22.64
	29125.00	Peak	H	-	-	-50.76	-0.12	-9.54	46.58	68.20	-21.62

Table 7-164. Radiated Measurements SISO ANT2 (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5745MHz
Channel:	149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11490.00	Average	H	-	-	-84.58	20.29	0.00	42.71	53.98	-11.27
*	11490.00	Peak	H	-	-	-73.08	20.29	0.00	54.21	73.98	-19.77
	17235.00	Peak	H	-	-	-73.10	29.45	0.00	63.35	68.20	-4.85
*	22980.00	Average	H	-	-	-80.91	17.92	-9.54	34.47	53.98	-19.51
*	22980.00	Peak	H	-	-	-69.87	17.92	-9.54	45.51	73.98	-28.47
	28725.00	Peak	H	-	-	-49.01	0.67	-9.54	49.12	68.20	-19.08

Table 7-165. Radiated Measurements SISO ANT2 (106 Tones) with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

242 Tones



Plot 7-643. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11ax – U1 Ch. 40 – 242 Tones)



Plot 7-644. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11ax – U2A Ch. 56 – 242 Tones)



Plot 7-645. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11ax – U2C Ch. 120 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.



Plot 7-646. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11ax – U3 Ch. 157 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

SISO Antenna-2 Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-647. Radiated Spurious Plot 18GHz - 26.5GHz SISO ANT2 (802.11ax – 242 Tones)



Plot 7-648. Radiated Spurious Plot 26.5GHz - 40GHz SISO ANT2 (802.11ax – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

SISO Antenna-2 Radiated Spurious Emission Measurements (242 Tones)

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10360.00	Peak	V	-	-	-72.68	18.99	0.00	53.31	68.20	-14.89
*	15540.00	Average	V	-	-	-84.67	27.73	0.00	50.06	53.98	-3.92
*	15540.00	Peak	V	-	-	-75.21	27.73	0.00	59.52	73.98	-14.46
*	20720.00	Average	V	-	-	-82.03	16.92	-9.54	32.35	53.98	-21.63
*	20720.00	Peak	V	-	-	-71.28	16.92	-9.54	43.10	73.98	-30.88
	25900.00	Peak	V	-	-	-69.81	19.39	-9.54	47.04	68.20	-21.16

Table 7-166. Radiated Measurements SISO ANT2 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5200MHz
Channel:	40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10400.00	Peak	V	-	-	-70.61	19.36	0.00	55.75	68.20	-12.45
*	15600.00	Average	V	-	-	-84.67	27.61	0.00	49.94	53.98	-4.04
*	15600.00	Peak	V	-	-	-75.08	27.61	0.00	59.53	73.98	-14.45
*	20800.00	Average	V	-	-	-82.97	17.39	-9.54	31.87	53.98	-22.10
*	20800.00	Peak	V	-	-	-70.94	17.39	-9.54	43.90	73.98	-30.07
	26000.00	Peak	V	-	-	-68.34	19.98	-9.54	49.09	68.20	-19.11

Table 7-167. Radiated Measurements SISO ANT2 (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5240MHz
Channel:	48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10480.00	Peak	V	-	-	-73.08	19.72	0.00	53.64	68.20	-14.56
*	15720.00	Average	V	-	-	-85.74	27.41	0.00	48.67	53.98	-5.31
*	15720.00	Peak	V	-	-	-74.61	27.41	0.00	59.80	73.98	-14.18
*	20960.00	Average	V	-	-	-83.13	17.29	-9.54	31.62	53.98	-22.36
*	20960.00	Peak	V	-	-	-69.18	17.29	-9.54	45.57	73.98	-28.41
	26200.00	Peak	V	-	-	-68.94	19.80	-9.54	48.32	68.20	-19.88

Table 7-168. Radiated Measurements SISO ANT2 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10360.00	Peak	V	-	-	-73.08	18.99	0.00	52.91	68.20	-15.29
*	15540.00	Average	V	-	-	-85.34	27.73	0.00	49.39	53.98	-4.59
*	15540.00	Peak	V	-	-	-74.37	27.73	0.00	60.36	73.98	-13.62
*	20720.00	Average	V	-	-	-83.01	16.92	-9.54	31.37	53.98	-22.61
*	20720.00	Peak	V	-	-	-72.04	16.92	-9.54	42.34	73.98	-31.64
	25900.00	Peak	V	-	-	-70.20	19.39	-9.54	46.65	68.20	-21.55

Table 7-169. Radiated Measurements SISO ANT2 with WCP(242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5260MHz
Channel: 52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10520.00	Peak	V	-	-	-73.87	19.44	0.00	52.57	68.20	-15.63
*	15780.00	Average	V	-	-	-84.95	27.10	0.00	49.15	53.98	-4.83
*	15780.00	Peak	V	-	-	-75.37	27.10	0.00	58.73	73.98	-15.25
*	21040.00	Average	V	-	-	-80.38	17.32	-9.54	34.40	53.98	-19.58
*	21040.00	Peak	V	-	-	-70.35	17.32	-9.54	44.43	73.98	-29.55
	26300.00	Peak	V	-	-	-69.08	20.12	-9.54	48.50	68.20	-19.70

Table 7-170. Radiated Measurements SISO ANT2 (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5280MHz
Channel: 56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10560.00	Peak	V	-	-	-74.30	19.62	0.00	52.32	68.20	-15.88
*	15840.00	Average	V	-	-	-84.88	27.05	0.00	49.17	53.98	-4.81
*	15840.00	Peak	V	-	-	-74.27	27.05	0.00	59.78	73.98	-14.20
*	21120.00	Average	V	-	-	-81.38	17.26	-9.54	33.34	53.98	-20.64
*	21120.00	Peak	V	-	-	-70.21	17.26	-9.54	44.51	73.98	-29.47
	26400.00	Peak	V	-	-	-69.80	19.67	-9.54	47.33	68.20	-20.87

Table 7-171. Radiated Measurements SISO ANT2 (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5320MHz
Channel:	64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	V	-	-	-83.97	19.97	0.00	43.00	53.98	-10.98
*	10640.00	Peak	V	-	-	-71.64	19.97	0.00	55.33	73.98	-18.65
*	15960.00	Average	V	-	-	-84.91	27.35	0.00	49.44	53.98	-4.54
*	15960.00	Peak	V	-	-	-74.08	27.35	0.00	60.27	73.98	-13.71
*	21280.00	Average	V	-	-	-80.20	17.51	-9.54	34.77	53.98	-19.21
*	21280.00	Peak	V	-	-	-69.84	17.51	-9.54	45.13	73.98	-28.85
	26600.00	Peak	V	-	-	-50.32	1.44	-9.54	48.58	68.20	-19.62

Table 7-172. Radiated Measurements SISO ANT2 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5320MHz
Channel:	64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	V	-	-	-84.34	19.97	0.00	42.63	53.98	-11.35
*	10640.00	Peak	V	-	-	-72.91	19.97	0.00	54.06	73.98	-19.92
*	15960.00	Average	V	-	-	-85.03	27.35	0.00	49.32	53.98	-4.66
*	15960.00	Peak	V	-	-	-73.67	27.35	0.00	60.68	73.98	-13.30
*	21280.00	Average	V	-	-	-80.61	17.51	-9.54	34.36	53.98	-19.62
*	21280.00	Peak	V	-	-	-69.16	17.51	-9.54	45.81	73.98	-28.17
	26600.00	Peak	V	-	-	-49.61	1.44	-9.54	49.29	68.20	-18.91

Table 7-173. Radiated Measurements SISO ANT2 with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11000.00	Average	V	-	-	-85.27	20.31	0.00	42.04	53.98	-11.94
*	11000.00	Peak	V	-	-	-74.65	20.31	0.00	52.66	73.98	-21.32
	16500.00	Peak	V	-	-	-72.81	28.49	0.00	62.68	68.20	-5.52
	22000.00	Peak	V	-	-	-70.24	18.25	-9.54	45.47	68.20	-22.73
	27500.00	Peak	V	-	-	-50.31	0.12	-9.54	47.27	68.20	-20.93

Table 7-174. Radiated Measurements SISO ANT2 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5600MHz
Channel:	120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	V	-	-	-85.94	19.97	0.00	41.03	53.98	-12.95
*	11200.00	Peak	V	-	-	-73.48	19.97	0.00	53.49	73.98	-20.49
	16800.00	Peak	V	-	-	-73.91	28.82	0.00	61.91	68.20	-6.29
*	22400.00	Average	V	-	-	-80.84	19.00	-9.54	35.62	53.98	-18.36
*	22400.00	Peak	V	-	-	-71.02	19.00	-9.54	45.44	73.98	-28.54
	28000.00	Peak	V	-	-	-50.61	0.74	-9.54	47.58	68.20	-20.62

Table 7-175. Radiated Measurements SISO ANT2 (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5720MHz
Channel: 144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11440.00	Average	V	-	-	-84.87	20.26	0.00	42.39	53.98	-11.59
*	11440.00	Peak	V	-	-	-73.28	20.26	0.00	53.98	73.98	-20.00
	17160.00	Peak	V	-	-	-74.67	29.62	0.00	61.95	68.20	-6.25
*	22880.00	Average	V	-	-	-82.05	18.40	-9.54	33.81	53.98	-20.17
*	22880.00	Peak	V	-	-	-70.21	18.40	-9.54	45.65	73.98	-28.33
	28600.00	Peak	V	-	-	-49.20	0.41	-9.54	48.67	68.20	-19.53

Table 7-176. Radiated Measurements SISO ANT2 (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5500MHz
Channel: 100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11000.00	Average	V	-	-	-84.09	20.31	0.00	43.22	53.98	-10.76
*	11000.00	Peak	V	-	-	-75.61	20.31	0.00	51.70	73.98	-22.28
	16500.00	Peak	V	-	-	-73.38	28.49	0.00	62.11	68.20	-6.09
	22000.00	Peak	V	-	-	-72.05	19.00	-9.54	44.41	68.20	-23.79
	27500.00	Peak	V	-	-	-69.97	19.00	-9.54	46.49	68.20	-21.71

Table 7-177. Radiated Measurements SISO ANT2 with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5745MHz
Channel:	149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11490.00	Average	V	-	-	-84.34	20.36	0.00	43.02	53.98	-10.96
*	11490.00	Peak	V	-	-	-73.67	20.36	0.00	53.69	73.98	-20.29
	17235.00	Peak	V	-	-	-73.09	29.51	0.00	63.42	68.20	-4.78
*	22980.00	Average	V	-	-	-80.34	17.92	-9.54	35.04	53.98	-18.94
*	22980.00	Peak	V	-	-	-71.97	17.92	-9.54	43.41	73.98	-30.57
	28725.00	Peak	V	-	-	-50.08	0.67	-9.54	48.05	68.20	-20.15

Table 7-178. Radiated Measurements SISO ANT2 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	V	-	-	-85.27	21.02	0.00	42.75	53.98	-11.23
*	11570.00	Peak	V	-	-	-74.38	21.02	0.00	53.64	73.98	-20.34
	17355.00	Peak	V	-	-	-73.64	29.63	0.00	62.99	68.20	-5.21
	23140.00	Peak	V	-	-	-70.01	18.32	-9.54	45.77	68.20	-22.43
	28925.00	Peak	V	-	-	-50.27	0.75	-9.54	47.94	68.20	-20.26

Table 7-179. Radiated Measurements SISO ANT2 (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5825MHz
Channel:	165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11650.00	Average	V	-	-	-85.07	21.21	0.00	43.14	53.98	-10.84
*	11650.00	Peak	V	-	-	-73.64	21.21	0.00	54.57	73.98	-19.41
	17475.00	Peak	V	-	-	-75.31	29.76	0.00	61.45	68.20	-6.75
	23300.00	Peak	V	-	-	-72.84	18.77	-9.54	43.39	68.20	-24.81
	29125.00	Peak	V	-	-	-49.20	-0.12	-9.54	48.14	68.20	-20.06

Table 7-180. Radiated Measurements SISO ANT2 (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5745MHz
Channel:	149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11490.00	Average	V	-	-	-84.97	20.36	0.00	42.39	53.98	-11.59
*	11490.00	Peak	V	-	-	-73.61	20.36	0.00	53.75	73.98	-20.23
	17235.00	Peak	V	-	-	-74.38	29.51	0.00	62.13	68.20	-6.07
*	22980.00	Average	V	-	-	-84.30	17.92	-9.54	31.08	53.98	-22.90
*	22980.00	Peak	V	-	-	-71.29	17.92	-9.54	44.09	73.98	-29.89
	28725.00	Peak	V	-	-	-50.27	0.67	-9.54	47.86	68.20	-20.34

Table 7-181. Radiated Measurements SISO ANT2 with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.3 MIMO Radiated Spurious Emission Measurements (106 Tones)



Plot 7-649. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 106 Tones)



Plot 7-650. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 106 Tones)



Plot 7-651. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.



Plot 7-652. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

MIMO Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-653. Radiated Spurious Plot 18GHz - 26.5GHz MIMO (802.11ax – 106 Tones)



Plot 7-654. Radiated Spurious Plot 26.5GHz - 40GHz MIMO (802.11ax – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

MIMO Radiated Spurious Emission Measurements (106 Tones)

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5180MHz
Channel: 36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10360.00	Peak	H	-	-	-72.11	18.75	0.00	53.64	68.20	-14.56
*	15540.00	Average	H	-	-	-85.21	28.13	0.00	49.92	53.98	-4.06
*	15540.00	Peak	H	-	-	-73.63	28.13	0.00	61.50	73.98	-12.48
*	20720.00	Average	H	-	-	-82.04	16.92	-9.54	32.34	53.98	-21.64
*	20720.00	Peak	H	-	-	-71.61	16.92	-9.54	42.77	73.98	-31.21
	25900.00	Peak	H	-	-	-69.34	19.39	-9.54	47.51	68.20	-20.69

Table 7-182. Radiated Measurements MIMO (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5200MHz
Channel: 40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10400.00	Peak	H	-	-	-72.37	19.45	0.00	54.08	68.20	-14.12
*	15600.00	Average	H	-	-	-85.10	27.65	0.00	49.55	53.98	-4.43
*	15600.00	Peak	H	-	-	-74.02	27.65	0.00	60.63	73.98	-13.35
*	20800.00	Average	H	-	-	-82.07	17.39	-9.54	32.77	53.98	-21.20
*	20800.00	Peak	H	-	-	-71.54	17.39	-9.54	43.30	73.98	-30.67
	26000.00	Peak	H	-	-	-69.31	19.98	-9.54	48.12	68.20	-20.08

Table 7-183. Radiated Measurements MIMO (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5240MHz
Channel:	48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10480.00	Peak	H	-	-	-72.89	19.76	0.00	53.87	68.20	-14.33
*	15720.00	Average	H	-	-	-85.06	27.55	0.00	49.49	53.98	-4.49
*	15720.00	Peak	H	-	-	-73.83	27.55	0.00	60.72	73.98	-13.26
*	20960.00	Average	H	-	-	-81.37	17.29	-9.54	33.38	53.98	-20.60
*	20960.00	Peak	H	-	-	-71.27	17.29	-9.54	43.48	73.98	-30.50
	26200.00	Peak	H	-	-	-69.33	19.80	-9.54	47.93	68.20	-20.27

Table 7-184. Radiated Measurements MIMO (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5200MHz
Channel:	40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10400.00	Peak	H	-	-	-72.67	19.45	0.00	53.78	68.20	-14.42
*	15600.00	Average	H	-	-	-84.68	27.65	0.00	49.97	53.98	-4.01
*	15600.00	Peak	H	-	-	-75.01	27.65	0.00	59.64	73.98	-14.34
*	20800.00	Average	H	-	-	-83.23	17.39	-9.54	31.61	53.98	-22.36
*	20800.00	Peak	H	-	-	-72.57	17.39	-9.54	42.27	73.98	-31.70
	26000.00	Peak	H	-	-	-70.27	19.98	-9.54	47.16	68.20	-21.04

Table 7-185. Radiated Measurements MIMO (106 Tones)with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5260MHz
Channel: 52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10520.00	Peak	H	-	-	-73.48	19.25	0.00	52.77	68.20	-15.43
*	15780.00	Average	H	-	-	-85.03	27.22	0.00	49.19	53.98	-4.79
*	15780.00	Peak	H	-	-	-74.03	27.22	0.00	60.19	73.98	-13.79
*	21040.00	Average	H	-	-	-82.07	17.32	-9.54	32.71	53.98	-21.27
*	21040.00	Peak	H	-	-	-71.64	17.32	-9.54	43.14	73.98	-30.84
	26300.00	Peak	H	-	-	-69.49	20.12	-9.54	48.09	68.20	-20.11

Table 7-186. Radiated Measurements MIMO (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5280MHz
Channel: 56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10560.00	Peak	H	-	-	-71.86	19.37	0.00	54.51	68.20	-13.69
*	15840.00	Average	H	-	-	-84.96	27.28	0.00	49.32	53.98	-4.66
*	15840.00	Peak	H	-	-	-73.76	27.28	0.00	60.52	73.98	-13.46
*	21120.00	Average	H	-	-	-80.79	17.26	-9.54	33.93	53.98	-20.05
*	21120.00	Peak	H	-	-	-70.28	17.26	-9.54	44.44	73.98	-29.54
	26400.00	Peak	H	-	-	-68.26	19.67	-9.54	48.87	68.20	-19.33

Table 7-187. Radiated Measurements MIMO (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5320MHz
Channel: 64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	H	-	-	-83.15	20.07	0.00	43.92	53.98	-10.06
*	10640.00	Peak	H	-	-	-72.36	20.07	0.00	54.71	73.98	-19.27
*	15960.00	Average	H	-	-	-84.81	27.42	0.00	49.61	53.98	-4.37
*	15960.00	Peak	H	-	-	-73.02	27.42	0.00	61.40	73.98	-12.58
*	21280.00	Average	H	-	-	-82.64	17.51	-9.54	32.33	53.98	-21.65
*	21280.00	Peak	H	-	-	-70.49	17.51	-9.54	44.48	73.98	-29.50
	26600.00	Peak	H	-	-	-50.94	1.44	-9.54	47.96	68.20	-20.24

Table 7-188. Radiated Measurements MIMO (106 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 53
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5320MHz
Channel: 64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	H	-	-	-82.97	20.07	0.00	44.10	53.98	-9.88
*	10640.00	Peak	H	-	-	-73.38	20.07	0.00	53.69	73.98	-20.29
*	15960.00	Average	H	-	-	-85.34	27.42	0.00	49.08	53.98	-4.90
*	15960.00	Peak	H	-	-	-73.19	27.42	0.00	61.23	73.98	-12.75
*	21280.00	Average	H	-	-	-83.27	17.51	-9.54	31.70	53.98	-22.28
*	21280.00	Peak	H	-	-	-70.46	17.51	-9.54	44.51	73.98	-29.47

Table 7-189. Radiated Measurements MIMO (106 Tones)with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11000.00	Average	H	-	-	-85.24	20.71	0.00	42.47	53.98	-11.51
*	11000.00	Peak	H	-	-	-72.90	20.71	0.00	54.81	73.98	-19.17
	16500.00	Peak	H	-	-	-74.24	28.80	0.00	61.56	68.20	-6.64
	22000.00	Peak	H	-	-	-70.34	18.25	-9.54	45.37	68.20	-22.83
	27500.00	Peak	H	-	-	-49.20	0.12	-9.54	48.38	68.20	-19.82

Table 7-190. Radiated Measrements MIMO (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5600MHz
Channel:	120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-83.50	20.02	0.00	43.52	53.98	-10.46
*	11200.00	Peak	H	-	-	-73.58	20.02	0.00	53.44	73.98	-20.54
	16800.00	Peak	H	-	-	-74.28	28.89	0.00	61.61	68.20	-6.59
*	22400.00	Average	H	-	-	-79.87	19.00	-9.54	36.59	53.98	-17.39
*	22400.00	Peak	H	-	-	-70.38	19.00	-9.54	46.08	73.98	-27.90
	28000.00	Peak	H	-	-	-79.20	0.74	-9.54	18.99	68.20	-49.21

Table 7-191. Radiated Measurements MIMO (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5720MHz
Channel:	144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11440.00	Average	H	-	-	-85.07	20.76	0.00	42.69	53.98	-11.29
*	11440.00	Peak	H	-	-	-73.02	20.76	0.00	54.74	73.98	-19.24
	17160.00	Peak	H	-	-	-73.11	29.65	0.00	63.54	68.20	-4.66
*	22880.00	Average	H	-	-	-79.88	18.40	-9.54	35.98	53.98	-18.00
*	22880.00	Peak	H	-	-	-69.37	18.40	-9.54	46.49	73.98	-27.49
	28600.00	Peak	H	-	-	-50.31	0.41	-9.54	47.56	68.20	-20.64

Table 7-192. Radiated Measurements MIMO (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5600MHz
Channel:	120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-84.08	20.02	0.00	42.94	53.98	-11.04
*	11200.00	Peak	H	-	-	-74.06	20.02	0.00	52.96	73.98	-21.02
	16800.00	Peak	H	-	-	-75.37	28.89	0.00	60.52	68.20	-7.68
*	22400.00	Average	H	-	-	-80.48	19.00	-9.54	35.98	53.98	-18.00
*	22400.00	Peak	H	-	-	-69.17	19.00	-9.54	47.29	73.98	-26.69
	28000.00	Peak	H	-	-	-48.96	0.74	-9.54	49.23	68.20	-18.97

Table 7-193. Radiated Measurements MIMO (106 Tones)with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5745MHz
Channel:	149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11490.00	Average	H	-	-	-83.89	20.29	0.00	43.40	53.98	-10.58
*	11490.00	Peak	H	-	-	-72.81	20.29	0.00	54.48	73.98	-19.50
	17235.00	Peak	H	-	-	-73.42	29.45	0.00	63.03	68.20	-5.17
*	22980.00	Average	H	-	-	-82.08	17.92	-9.54	33.30	53.98	-20.68
*	22980.00	Peak	H	-	-	-71.34	17.92	-9.54	44.04	73.98	-29.94
	28725.00	Peak	H	-	-	-49.31	0.67	-9.54	48.82	69.20	-20.38

Table 7-194. Radiated Measurements MIMO (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	H	-	-	-83.72	20.87	0.00	44.15	53.98	-9.83
*	11570.00	Peak	H	-	-	-71.88	20.87	0.00	55.99	73.98	-17.99
	17355.00	Peak	H	-	-	-73.28	29.88	0.00	63.60	68.20	-4.60
	23140.00	Peak	H	-	-	-70.60	18.32	-9.54	45.18	68.20	-23.02
	28925.00	Peak	H	-	-	-50.38	0.75	-9.54	47.83	68.20	-20.37

Table 7-195. Radiated Measurements MIMO (106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5825MHz
Channel:	165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11650.00	Average	H	-	-	-83.78	21.73	0.00	44.95	53.98	-9.03
*	11650.00	Peak	H	-	-	-72.37	21.73	0.00	56.36	73.98	-17.62
	17475.00	Peak	H	-	-	-73.46	30.16	0.00	63.70	68.20	-4.50
	23300.00	Peak	H	-	-	-70.38	18.77	-9.54	45.85	68.20	-22.35
	29125.00	Peak	H	-	-	-50.21	-0.12	-9.54	47.13	68.20	-21.07

Table 7-196. Radiated Measurements MIMO (106 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5825MHz
Channel:	165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11650.00	Average	H	-	-	-83.51	21.73	0.00	45.22	53.98	-8.76
*	11650.00	Peak	H	-	-	-72.31	21.73	0.00	56.42	73.98	-17.56
	17475.00	Peak	H	-	-	-73.94	30.16	0.00	63.22	68.20	-4.98
	23300.00	Peak	H	-	-	-71.29	18.77	-9.54	44.94	68.20	-23.26
	29125.00	Peak	H	-	-	-51.02	-0.12	-9.54	46.32	68.20	-21.88

Table 7-197. Radiated Measurements MIMO (106 Tones)with WCP

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

242 Tones



Plot 7-655. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 242 Tones)



Plot 7-656. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 242 Tones)



Plot 7-657. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.



Plot 7-658. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

MIMO Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-659. Radiated Spurious Plot 18GHz - 26.5GHz MIMO (802.11ax – 242 Tones)



Plot 7-660. Radiated Spurious Plot 26.5GHz - 40GHz MIMO (802.11ax – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

MIMO Radiated Spurious Emission Measurements (242 Tones)

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5180MHz
Channel: 36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10360.00	Peak	H	-	-	-73.21	18.99	0.00	52.78	68.20	-15.42
*	15540.00	Average	H	-	-	-84.97	27.73	0.00	49.76	53.98	-4.22
*	15540.00	Peak	H	-	-	-74.68	27.73	0.00	60.05	73.98	-13.93
*	20720.00	Average	H	-	-	-77.83	16.92	-9.54	36.55	53.98	-17.43
*	20720.00	Peak	H	-	-	-66.40	16.92	-9.54	47.98	73.98	-26.00
	25900.00	Peak	H	-	-	-65.20	19.39	-9.54	51.65	68.20	-16.55

Table 7-198. Radiated Measurements MIMO (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
Worst Case Transfer Rate: MCS0
RU Index: 61
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5200MHz
Channel: 40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10400.00	Peak	H	-	-	-71.08	19.36	0.00	55.28	68.20	-12.92
*	15600.00	Average	H	-	-	-85.39	27.61	0.00	49.22	53.98	-4.76
*	15600.00	Peak	H	-	-	-74.97	27.61	0.00	59.64	73.98	-14.34
*	20800.00	Average	H	-	-	-77.92	17.39	-9.54	36.92	53.98	-17.05
*	20800.00	Peak	H	-	-	-66.94	17.39	-9.54	47.90	73.98	-26.07
	26000.00	Peak	H	-	-	-65.39	19.98	-9.54	52.04	68.20	-16.16

Table 7-199. Radiated Measurements MIMO (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5240MHz
Channel:	48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10480.00	Peak	H	-	-	-72.28	19.72	0.00	54.44	68.20	-13.76
*	15720.00	Average	H	-	-	-84.97	27.41	0.00	49.44	53.98	-4.54
*	15720.00	Peak	H	-	-	-75.36	27.41	0.00	59.05	73.98	-14.93
*	20960.00	Average	H	-	-	-77.81	17.29	-9.54	36.94	53.98	-17.04
*	20960.00	Peak	H	-	-	-66.67	17.29	-9.54	48.08	73.98	-25.90
	26200.00	Peak	H	-	-	-65.19	19.80	-9.54	52.07	68.20	-16.13

Table 7-200. Radiated Measurements MIMO (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10360.00	Peak	H	-	-	-74.08	18.99	0.00	51.91	68.20	-16.29
*	15540.00	Average	H	-	-	-85.37	27.73	0.00	49.36	53.98	-4.62
*	15540.00	Peak	H	-	-	-75.68	27.73	0.00	59.05	73.98	-14.93
*	20720.00	Average	H	-	-	-77.79	17.29	-9.54	36.96	53.98	-17.02
*	20720.00	Peak	H	-	-	-66.84	17.29	-9.54	47.91	73.98	-26.07
	25900.00	Peak	H	-	-	-65.29	19.80	-9.54	51.97	68.20	-16.23

Table 7-201. Radiated Measurements MIMO With WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5260MHz
Channel:	52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10520.00	Peak	H	-	-	-73.57	19.44	0.00	52.87	68.20	-15.33
*	15780.00	Average	H	-	-	-84.55	27.10	0.00	49.55	53.98	-4.43
*	15780.00	Peak	H	-	-	-74.06	27.10	0.00	60.04	73.98	-13.94
*	21040.00	Average	H	-	-	-77.52	17.32	-9.54	37.26	53.98	-16.72
*	21040.00	Peak	H	-	-	-66.65	17.32	-9.54	48.13	73.98	-25.85
	26300.00	Peak	H	-	-	-64.44	20.12	-9.54	53.14	68.20	-15.06

Table 7-202. Radiated Measurements MIMO (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5280MHz
Channel:	56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10560.00	Peak	H	-	-	-74.67	19.62	0.00	51.95	68.20	-16.25
*	15840.00	Average	H	-	-	-84.78	27.05	0.00	49.27	53.98	-4.71
*	15840.00	Peak	H	-	-	-75.31	27.05	0.00	58.74	73.98	-15.24
*	21120.00	Average	H	-	-	-77.41	17.26	-9.54	37.31	53.98	-16.67
*	21120.00	Peak	H	-	-	-66.49	17.26	-9.54	48.23	73.98	-25.75
	26400.00	Peak	H	-	-	-65.10	19.67	-9.54	52.03	68.20	-16.17

Table 7-203. Radiated Measurements MIMO (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5320MHz
Channel:	64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	10640.00	Average	H	-	-	-84.57	19.97	0.00	42.40	53.98	-11.58
*	10640.00	Peak	H	-	-	-72.64	19.97	0.00	54.33	73.98	-19.65
*	15960.00	Average	H	-	-	-84.82	27.35	0.00	49.53	53.98	-4.45
*	15960.00	Peak	H	-	-	-75.30	27.35	0.00	59.05	73.98	-14.93
*	21280.00	Average	H	-	-	-77.58	17.51	-9.54	37.39	53.98	-16.59
*	21280.00	Peak	H	-	-	-66.38	17.51	-9.54	48.59	73.98	-25.39
	26600.00	Peak	H	-	-	-49.31	1.44	-9.54	49.59	68.20	-18.61

Table 7-204. Radiated Measurements MIMO (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5260MHz
Channel:	52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
	10520.00	Peak	V	-	-	-74.24	19.44	0.00	52.20	68.20	-16.00
*	15780.00	Average	V	-	-	-83.41	27.10	0.00	50.69	53.98	-3.29
*	15780.00	Peak	V	-	-	-73.87	27.10	0.00	60.23	73.98	-13.75
*	21040.00	Average	V	-	-	-77.63	17.32	-9.54	37.15	53.98	-16.83
*	21040.00	Peak	V	-	-	-66.49	17.32	-9.54	48.29	73.98	-25.69
	26300.00	Peak	V	-	-	-64.81	20.12	-9.54	52.77	68.20	-15.43

Table 7-205. Radiated Measurements MIMO with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11000.00	Average	H	-	-	-84.68	20.31	0.00	42.63	53.98	-11.35
*	11000.00	Peak	H	-	-	-75.21	20.31	0.00	52.10	73.98	-21.88
	16500.00	Peak	H	-	-	-73.67	28.49	0.00	61.82	68.20	-6.38
	22000.00	Peak	H	-	-	-66.37	18.25	-9.54	49.34	68.20	-18.86
	27500.00	Peak	H	-	-	-48.80	0.12	-9.54	48.78	68.20	-19.42

Table 7-206. Radiated Measurements MIMO (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5600MHz
Channel:	120

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11200.00	Average	H	-	-	-84.79	19.97	0.00	42.18	53.98	-11.80
*	11200.00	Peak	H	-	-	-75.34	19.97	0.00	51.63	73.98	-22.35
	16800.00	Peak	H	-	-	-74.61	28.82	0.00	61.21	68.20	-6.99
*	22400.00	Average	H	-	-	-77.65	19.00	-9.54	38.81	53.98	-15.17
*	22400.00	Peak	H	-	-	-66.78	19.00	-9.54	49.68	73.98	-24.30
	28000.00	Peak	H	-	-	-48.52	0.74	-9.54	49.67	68.20	-18.53

Table 7-207. Radiated Measurements MIMO (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5720MHz
Channel:	144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11440.00	Average	H	-	-	-85.96	20.26	0.00	41.30	53.98	-12.68
*	11440.00	Peak	H	-	-	-74.37	20.26	0.00	52.89	73.98	-21.09
	17160.00	Peak	H	-	-	-75.64	29.62	0.00	60.98	68.20	-7.22
*	22880.00	Average	H	-	-	-77.29	18.40	-9.54	38.57	53.98	-15.41
*	22880.00	Peak	H	-	-	-66.40	18.40	-9.54	49.46	73.98	-24.52
	28600.00	Peak	H	-	-	-48.53	0.41	-9.54	49.34	68.20	-18.86

Table 7-208. Radiated Measurements MIMO (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11000.00	Average	H	-	-	-85.21	20.31	0.00	42.10	53.98	-11.88
*	11000.00	Peak	H	-	-	-76.31	20.31	0.00	51.00	73.98	-22.98
	16500.00	Peak	H	-	-	-74.38	28.49	0.00	61.11	68.20	-7.09
	22000.00	Peak	H	-	-	-66.56	19.00	-9.54	49.90	68.20	-18.30
	27500.00	Peak	H	-	-	-48.32	0.74	-9.54	49.87	68.20	-18.33

Table 7-209. Radiated Measurements MIMO with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5745MHz
Channel:	149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11490.00	Average	H	-	-	-85.34	20.36	0.00	42.02	53.98	-11.96
*	11490.00	Peak	H	-	-	-74.37	20.36	0.00	52.99	73.98	-20.99
	17235.00	Peak	H	-	-	-74.61	29.51	0.00	61.90	68.20	-6.30
*	22980.00	Average	H	-	-	-77.88	17.92	-9.54	37.50	53.98	-16.48
*	22980.00	Peak	H	-	-	-66.42	17.92	-9.54	48.96	73.98	-25.02
	28725.00	Peak	H	-	-	-49.17	0.67	-9.54	48.96	69.20	-20.24

Table 7-210. Radiated Measurements MIMO (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	H	-	-	-84.31	21.02	0.00	43.71	53.98	-10.27
*	11570.00	Peak	H	-	-	-75.38	21.02	0.00	52.64	73.98	-21.34
	17355.00	Peak	H	-	-	-74.06	29.63	0.00	62.57	68.20	-5.63
	23140.00	Peak	H	-	-	-66.68	18.32	-9.54	49.10	68.20	-19.10
	28925.00	Peak	H	-	-	-48.38	0.75	-9.54	49.83	68.20	-18.37

Table 7-211. Radiated Measurements MIMO (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5825MHz
Channel:	165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11650.00	Average	H	-	-	-84.37	21.21	0.00	43.84	53.98	-10.14
*	11650.00	Peak	H	-	-	-75.37	21.21	0.00	52.84	73.98	-21.14
	17475.00	Peak	H	-	-	-74.30	29.76	0.00	62.46	68.20	-5.74
	23300.00	Peak	H	-	-	-66.46	18.77	-9.54	49.77	68.20	-18.43
	29125.00	Peak	H	-	-	-48.98	-0.12	-9.54	48.36	68.20	-19.84

Table 7-212. Radiated Measurements MIMO (242 Tones)

Worst Case Mode:	802.11ax (20MHz BW)
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	1 & 3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV /m]	Limit [dBµV /m]	Margin [dB]
*	11570.00	Average	H	-	-	-83.97	21.02	0.00	44.05	53.98	-9.93
*	11570.00	Peak	H	-	-	-74.61	21.02	0.00	53.41	73.98	-20.57
	17355.00	Peak	H	-	-	-73.49	29.63	0.00	63.14	68.20	-5.06
	23140.00	Peak	H	-	-	-66.39	18.32	-9.54	49.39	68.20	-18.81
	28925.00	Peak	H	-	-	-48.87	0.75	-9.54	49.34	68.20	-18.86

Table 7-213. Radiated Measurements MIMO with WCP (242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.4 SISO Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]; RSS-Gen [8.9]

106 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	53
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36



Plot 7-661. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 1 – 106 Tones)



Plot 7-662. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 1 – 106 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	54
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-663. Radiated Upper Band Edge Plot SISO ANT1 (Average – UNII Band 2A – 106 Tones)



Plot 7-664. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 2A – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	53
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100



Plot 7-665. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 2C – 106 Tones)



Plot 7-666. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 2C – 106 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	54
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165



Plot 7-667. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 3 – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

242 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36



Plot 7-668. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 1 – 242 Tones)



Plot 7-669. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 1 – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-670. Radiated Upper Band Edge Plot SISO ANT1 (Average – UNII Band 2A – 242 Tones)



Plot 7-671. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 2A – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100



Plot 7-672. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 2C – 242 Tones)



Plot 7-673. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 2C – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165



Plot 7-674. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 3 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-675. Radiated Band Edge Plot SISO ANT1 (Average – WCP – 242 Tones)



Plot 7-676. Radiated Band Edge Plot SISO ANT1 (Peak – WCP – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.5 SISO Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

242 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38



Plot 7-677. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 1 – 242 Tones)



Plot 7-678. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 1 – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	62
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-679. Radiated Upper Band Edge Plot SISO ANT1 (Average – UNII Band 2A – 242 Tones)



Plot 7-680. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 2A – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102



Plot 7-681. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 2C – 242 Tones)



Plot 7-682. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 2C – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	62
Distance of Measurements:	3 Meters
Operating Frequency:	5795MHz
Channel:	159



Plot 7-683. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 3 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

484 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38



Plot 7-684. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 1 – 484 Tones)



Plot 7-685. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 1 – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-686. Radiated Upper Band Edge Plot SISO ANT1 (Average – UNII Band 2A – 484 Tones)



Plot 7-687. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 2A – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102



Plot 7-688. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 2C – 484 Tones)



Plot 7-689. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 2C – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5795MHz
Channel:	159



Plot 7-690. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 3 – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-691. Radiated Band Edge Plot SISO ANT1 (Average – WCP – 484 Tones)



Plot 7-692. Radiated Band Edge Plot SISO ANT1 (Peak – WCP – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.6 SISO Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

484 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42



Plot 7-693. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 1 – 484 Tones)



Plot 7-694. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 1 – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	66
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-695. Radiated Upper Band Edge Plot SISO ANT1 (Average – UNII Band 2A – 484 Tones)



Plot 7-696. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 2A – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106



Plot 7-697. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 2C – 484 Tones)



Plot 7-698. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 2C – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	66
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-699. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 3 – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

996 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42



Plot 7-700. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 1 – 996 Tones)



Plot 7-701. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 1 – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-702. Radiated Upper Band Edge Plot SISO ANT1 (Average – UNII Band 2A – 996 Tones)



Plot 7-703. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 2A – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106



Plot 7-704. Radiated Lower Band Edge Plot SISO ANT1 (Average – UNII Band 2C – 996 Tones)



Plot 7-705. Radiated Lower Band Edge Plot SISO ANT1 (Peak – UNII Band 2C – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-706. Radiated Upper Band Edge Plot SISO ANT1 (Peak – UNII Band 3 – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-707. Radiated Band Edge Plot SISO ANT1 (Average – WCP – 996 Tones)



Plot 7-708. Radiated Band Edge Plot SISO ANT1 (Peak – WCP – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.7 SISO Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]; RSS-Gen [8.9]

106 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	53
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36



Plot 7-709. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1 – 106 Tones)



Plot 7-710. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1 – 106 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	54
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-711. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A – 106 Tones)



Plot 7-712. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	53
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100



Plot 7-713. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C – 106 Tones)



Plot 7-714. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C – 106 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	54
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165



Plot 7-715. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3 – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

242 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36



Plot 7-716. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1 – 242 Tones)



Plot 7-717. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1 – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-718. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A – 242 Tones)



Plot 7-719. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100



Plot 7-720. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C – 242 Tones)



Plot 7-721. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165



Plot 7-722. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100



Plot 7-723. Radiated Band Edge Plot SISO ANT2 (Average – WCP – 242 Tones)



Plot 7-724. Radiated Band Edge Plot SISO ANT2 (Peak – WCP – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.8 SISO Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

242 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38



Plot 7-725. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1 – 242 Tones)



Plot 7-726. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1 – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	62
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-727. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A – 242 Tones)



Plot 7-728. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102



Plot 7-729. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C – 242 Tones)



Plot 7-730. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	62
Distance of Measurements:	3 Meters
Operating Frequency:	5795MHz
Channel:	159



Plot 7-731. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

484 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38



Plot 7-732. Radiated Band Edge Plot SISO ANT2 (Average – WCP – 484 Tones)



Plot 7-733. Radiated Band Edge Plot SISO ANT2 (Peak – WCP – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-734. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A – 484 Tones)



Plot 7-735. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102



Plot 7-736. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C – 484 Tones)



Plot 7-737. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5795MHz
Channel:	159



Plot 7-738. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3 – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-739. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1 – 484 Tones)



Plot 7-740. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1 – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.9 SISO Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

484 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42



Plot 7-741. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1 – 484 Tones)



Plot 7-742. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1 – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	66
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-743. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A – 484 Tones)



Plot 7-744. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106



Plot 7-745. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C – 484 Tones)



Plot 7-746. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	66
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-747. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3 – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

996 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42



Plot 7-748. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 1 – 996 Tones)



Plot 7-749. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 1 – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-750. Radiated Upper Band Edge Plot SISO ANT2 (Average – UNII Band 2A – 996 Tones)



Plot 7-751. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 2A – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106



Plot 7-752. Radiated Lower Band Edge Plot SISO ANT2 (Average – UNII Band 2C – 996 Tones)



Plot 7-753. Radiated Lower Band Edge Plot SISO ANT2 (Peak – UNII Band 2C – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-754. Radiated Upper Band Edge Plot SISO ANT2 (Peak – UNII Band 3 – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-755. Radiated Band Edge Plot SISO ANT2 (Average – WCP – 996 Tones)



Plot 7-756. Radiated Band Edge Plot SISO ANT2 (Peak – WCP – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.10 MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]; RSS-Gen [8.9]

106 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	53
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36



Plot 7-757. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 106 Tones)



Plot 7-758. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 106 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	54
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-759. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 106 Tones)



Plot 7-760. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	53
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100



Plot 7-761. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 106 Tones)



Plot 7-762. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 106 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	54
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165



Plot 7-763. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 106 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

242 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36



Plot 7-764. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 242 Tones)



Plot 7-765. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-766. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 242 Tones)



Plot 7-767. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100



Plot 7-768. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 242 Tones)



Plot 7-769. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165



Plot 7-770. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-771. Radiated Band Edge Plot MIMO (Average – WCP – 242 Tones)



Plot 7-772. Radiated Band Edge Plot MIMO (Peak – WCP – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.11 MIMO Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

242 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38



Plot 7-773. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 242 Tones)



Plot 7-774. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	62
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-775. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 242 Tones)



Plot 7-776. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102



Plot 7-777. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 242 Tones)



Plot 7-778. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	62
Distance of Measurements:	3 Meters
Operating Frequency:	5795MHz
Channel:	159



Plot 7-779. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 242 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

484 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38



Plot 7-780. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 484 Tones)



Plot 7-781. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-782. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 484 Tones)



Plot 7-783. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102



Plot 7-784. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 484 Tones)



Plot 7-785. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5795MHz
Channel:	159



Plot 7-786. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-787. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 484 Tones)



Plot 7-788. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.6.12 MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

484 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42



Plot 7-789. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 484 Tones)



Plot 7-790. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	66
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-791. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 484 Tones)



Plot 7-792. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106



Plot 7-793. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 484 Tones)



Plot 7-794. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	66
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-795. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 484 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

996 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42



Plot 7-796. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 996 Tones)



Plot 7-797. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-798. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 996 Tones)



Plot 7-799. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106



Plot 7-800. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 996 Tones)



Plot 7-801. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-802. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-803. Radiated Band Edge Plot MIMO (Average – WCP – 996 Tones)



Plot 7-804. Radiated Band Edge Plot MIMO (Peak – WCP – 996 Tones)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.7 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-202 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [µV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-214. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



Figure 7-6. Radiated Test Setup < 30MHz



Figure 7-7. Radiated Test Setup < 1GHz

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-202.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

SISO Antenna-1 Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-805. Radiated Spurious Plot below 1GHz SISO ANT1 (802.11ax – 106 Tones – U3 Ch. 157)



Plot 7-806. Radiated Spurious Plot below 1GHz SISO ANT1 (802.11ax – 242 Tones – U3 Ch. 157)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

SISO Antenna-2 Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-807. Radiated Spurious Plot below 1GHz SISO ANT2 (802.11ax – 106 Tones – U3 Ch. 157)



Plot 7-808. Radiated Spurious Plot below 1GHz SISO ANT2 (802.11ax – 242 Tones – U3 Ch. 157)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

MIMO Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-809. Radiated Spurious Plot below 1GHz MIMO (802.11ax – 106 Tones – U3 Ch. 157)



Plot 7-810. Radiated Spurious Plot below 1GHz MIMO (802.11ax – 242 Tones – U3 Ch. 157)

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG975U** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.