

EMC TEST REPORT

Project No.	LBE201812247	Issue No.	0
Applicant	Name of organization	Samsung Electronics Co., Ltd.	
	Address	(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea	
	Date of application	January 16, 2019	
EUT	Type of device	☒ All other Receivers subject to part15 ☒ Class B Personal Computers and peripherals ☒ Other Class B digital devices and peripherals ☒ FM Broadcast Receiver	
	Equipment authorization	☒ Certification ☐ Supplier's Declaration of Conformity	
	FCC ID	A3LSMG977KOR	
	Kind of product	Mobile Phone	
	Model No.	SM-G977N	
	Variant Model No.	Refer to clause 4.6	
	Manufacturer	SAMSUNG ELECTRONICS CO., LTD 94-1, Imsu-dong, Gumi-si, Gyengsangbuk-do, 730-722, Republic of Korea SAMSUNG ELECTRONICS HUIZHOU CO.,LTD. 516229, Chenjiang Town, HuiZhou City, Guangdong Province, China	
Applied Standards		47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014	
Test Period		January 16, 2019 ~ February 08, 2019	
Issue date		March 11, 2019	
Test result : Complied The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.)			
Tested by : Soo-Joon Kim 		Reviewed by : Young-Hun Kim 	
The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS Center.			
Global CS Center of Samsung Electronics Co., Ltd. (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea			

Table of contents

1. Report Information

1.1 Revision history	3
----------------------------	---

2. Summary of test results

2.1 Emission	3
--------------------	---

3. General Information

3.1 Test facility	3
-------------------------	---

4. Test Configuration

4.1 Test Peripherals	4
4.2 EUT operating mode	5
4.3 Details of Sampling	5
4.4 Used cable description	6
4.5 Test arrangement	7
4.6 EUT Description	11
4.7 EUT Frequencies	11
4.8 Test configuration and condition	12
4.9 Measurement uncertainty	12

5. Result of individual tests

5.1 Conducted disturbance	13
5.2 Radiated disturbance	19

1. Report Information

1.1 Revision history

No.	Revised detailed information
Issue 0	There are no revisions and this version is basic test report.

1.2 RSE test report no.

No.	Remark
1M1901160006-13	The cellular receiver mode refers to the radiated spurious emissions test report.

2. Summary of test results

2.1 Emission

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result
☒	Conducted Disturbance (Mains port)	47 CFR Part 15 Subpart B / ANSI C63.4-2014 (Class B)	Complied
☒	Radiated Disturbance		Complied

3. General Information

3.1 Test facility

The Global CS Center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea. All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms. And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS Center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Mark	Description	Model No.	Serial No.	Manufacturer / Trademark	FCC ID
A	Mobile Phone	SM-G977N	-	SAMSUNG	A3LSMG977KOR
B	Battery	EB-BG977ABU	-	SAMSUNG	-
C	Headset	EO-IG955	-	SAMSUNG	-
D	Data Cable	EP-DG977	-	SAMSUNG	-
E	Travel Adapter	EP-TA800	R37M1KK0JS1SE3	SAMSUNG	-
F	Laptop Computer	Latitude5580	1CHRYM2	Dell	-
		DM300S	D3HRYM2	Dell	-
G	Router	DIR-806A	RF0F1D5000688	D-Link	-
		RT-AX88U	J9IAHP000940	ASUS	-
H	Mouse	AA-SM7PCP	BDV8J48P4393	SAMSUNG	-
		SC-1000	1034000281	SAMSUNG	-
I	Laptop AC Adapter	LA65NM130	5D77	Dell	-
			5DEA	Dell	-
			DIKD1245096576	Delta	-
J	Router AC Adapter	ADP-45BW	18154	ASUS	-
K	DP Data Cable	JCA141	BW1B1607001082	J5create	-
L	Monitor	27UD88	605NTHM9B769	LG	-
M	Monitor AC Adaptor	LCAP31	EG3VN629490050658	LG	-
N	USB memory stick	64GB	-	Sandisk	-
O	OTG Gender	EE-UG970	-	SAMSUNG	-

4.2 EUT operating mode

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

4.2.1 Conducted Emission

No.	Operating mode
1	Camera (rear) + Charging (w/ TA) + Cellular receiver (GSM850 Center Frequency) + FM (Low Ch.)
2	Camera (front) + Charging (w/ TA) + FM (Mid Ch.)
3	Charging (w/ TA) + FM (High Ch.)
4	Video + Audio playback from internal memory data + Charging (w/ TA)
5	USB Data Communication with PC (from external memory data)

4.2.2 Radiated Emission

No.	Operating mode
1	Camera (rear) + Charging (w/ TA) + FM (Low Ch.)
2	Camera (front) +USB OTG (USB memory stick) + FM (Mid Ch.)
3	FM (High Ch.)
4	Video + Audio playback from internal memory data + Display out(Direct DP Cable)
5	USB Data Communication with PC (from external memory data)

4.3 Details of Sampling

Customer selected, single unit.


4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:


No.	Connected cable	Length [m]	Shielded [Y/N]	Note
1	Data Cable	1.0	Yes	From EUT to Desk-Top Computer
2	DP Cable	1.1	Yes	From EUT to DP Monitor
3	Headset	1.2	No	For EUT
4	Power	1.8	No	From Laptop Computer to AC Adapter
5	Power	1.2	No	From Monitor to AC Adapter
6	Power	2.2	No	From ASUS Router to AC Adapter
7	Power	1.5	No	For Laptop AC Adapter
8	Power	1.8	No	For ASUS Router AC Adapter
9	Power	1.8	No	For Monitor AC Adpater
10	LAN	1.5	No	From Laptop Computer to Router
11	USB	0.8	Yes	From Laptop Computer PC to Router
12	USB	1.8	Yes	From Laptop Computer to Mouse

4.5 Test arrangement

4.5.1 Conducted Emission




[Mode 1 - 4]



[Mode 5]


4.5.2 Radiated Emission




[Mode 1]




[Mode 2]



[Mode 3]



[Mode 4]



[Mode 5]

4.6 EUT Description

The EUT is a bar type mobile phone which can operate on GSM850/900/1800/1900, WCDMA FDD1/2/4/5/8, LTE FDD1/2/3/4/5/7/8/12/13/17/18/19/20/25/26/28/66, LTE TDD38/39/40/41/, TD-SCDMA B34/B39 bands and incorporates a Camera, Bluetooth, ANT+, Wi-Fi, FM Radio, T-DMB, GNSS, NFC, Wireless Charging, MST, OTG, DP and MP3/MP4 player.

4.6.1 The variant models

- None

4.7 EUT Frequencies

The highest frequencies (Generated and used)	Frequency [MHz]
Wi-Fi	5 825

4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables. All the external I/O ports are exercised, as well as internal and the external SD card, by writing and reading arbitrary data or charging with TA.

The EUT was investigated in three orientations and the worst case orientation is reported.

RX mode(850MHz) testing was performed with the GSM850 RX Test mode at center frequency. All licensed communication (850MHz) RX mode, GSM/WCDMA/LTE, test results are not significantly different.

The FM radio mode radiated testing was performed with the Low/Mid/High channel.

The video and music were repetitively played connected to the earphone.

The video and music were played on monitor through Display Out function using direct DP Cable or DP converter.

The EUT was connected to USB memory stick using USB OTG gender

The camera of the EUT was operated continuously.

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4-2 and UKAS M3003)

4.9.1 Emission

Test type		Measurement uncertainty (C.L. 95 %, k = 2)
Conducted disturbance	AC Mains	3.52 dB
Radiated Disturbance (Below 1 GHz)	Horizontal	4.99 dB
	Vertical	4.90 dB
Radiated Disturbance (Above 1 GHz)	Horizontal	5.33 dB
	Vertical	5.32 dB

5. Results of individual test

5.1 Conducted disturbance

The EUT was connected to the Desk-Top Computer which was powered from one LISN for the measurements. The support equipment power cables were connected to a second LISN.

Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Limits for conducted disturbance at the mains ports of Class B ITE

Frequency range Limits [MHz]	Resolution Bandwidth [kHz]	Limits [dB(μV)]	
		Quasi-peak	Average
0,15 to 0,50	9	66 to 56	56 to 46
0,50 to 5	9	56	46
5 to 30	9	60	50

NOTE 1 The lower limit shall apply at the transition frequency.
NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.1.1 Test instrumentation


EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-109	Universal Radio Communicator	CMU200	R&S	110431	2018-12-10	12
E5I-043	LISN	ENV216	R&S	101630	2018-08-17	12
E5I-123	EMI Test Receiver	ESU8	R&S	100475	2018-05-13	12
E5I-127	LISN	ENV216	R&S	102061	2018-07-23	12
-	Test software	EMC32	R&S	Ver 9.26.01	-	-

5.1.2 Temperature and humidity condition

Test date	2019-01-16 ~ 2019-01-24	Test engineer	Soo-Joon Kim
Climate condition	Ambient temperature	(22.6 ~ 22.9) °C	Limit (15.0 to 35.0) °C
	Relative humidity	(37.8 ~ 38.9) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(101.3 ~ 101.6) kPa	Limit (86.0 to 106.0) kPa
Test place	Shield Room (SR8)		

5.1.3 Test results

☐ Operating Mode 1: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.154	40.3	---	65.8	25.5	N	9.9
0.464	---	32.5	46.6	14.1	L1	10.2
0.469	35.3	---	56.5	21.2	L1	10.2
1.386	---	21.3	46.0	24.7	L1	10.0
1.898	---	23.1	46.0	22.9	L1	10.0
2.885	---	21.7	46.0	24.3	L1	10.0
4.827	31.4	---	56.0	24.6	N	9.9
4.884	---	24.3	46.0	21.7	L1	10.0
9.433	49.1	---	60.0	10.9	N	10.2
9.547	---	42.8	50.0	7.2	N	10.2
18.925	32.6	---	60.0	27.4	N	10.6
26.038	33.4	---	60.0	26.6	N	10.8

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor


☐ Operating Mode 2: AC Mains


Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.150	41.8	---	66.0	24.2	N	9.9
0.468	---	32.1	46.5	14.4	L1	10.2
0.469	35.5	---	56.5	21.0	L1	10.2
1.901	---	21.5	46.0	24.5	L1	10.0
4.874	29.4	---	56.0	26.6	N	9.9
4.964	---	23.2	46.0	22.8	L1	10.0
9.503	49.4	---	60.0	10.6	N	10.2
9.554	---	41.8	50.0	8.2	N	10.2
9.752	48.2	---	60.0	11.8	N	10.2
26.229	32.7	---	60.0	27.3	N	10.8
29.057	---	23.7	50.0	26.3	L1	10.8
0.150	41.8	---	66.0	24.2	N	9.9

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 3: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.251	40.0	---	61.7	21.7	N	9.7
0.253	---	31.4	51.7	20.3	L1	9.8
0.325	---	29.8	49.6	19.8	L1	10.1
0.448	34.3	---	56.9	22.6	L1	10.2
0.452	36.2	---	56.8	20.6	L1	10.2
0.466	---	33.7	46.6	12.9	L1	10.2
0.723	---	24.1	46.0	21.9	L1	10.1
3.841	---	26.6	46.0	19.4	L1	10.0
3.919	32.8	---	56.0	23.2	N	9.9
5.028	32.0	---	60.0	28.0	N	9.9
9.362	52.3	---	60.0	7.7	N	10.2
9.484	---	45.3	50.0	4.7	N	10.2

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 4: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:


Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.150	46.0	---	66.0	20.0	N	9.9
0.253	---	32.3	51.7	19.4	L1	9.8
0.325	---	30.4	49.6	19.2	L1	10.1
0.331	38.4	---	59.4	21.1	L1	10.1
0.401	---	26.3	47.8	21.6	L1	10.2
0.404	36.4	---	57.8	21.4	L1	10.2
0.469	---	33.3	46.5	13.2	L1	10.2
0.470	38.2	---	56.5	18.3	L1	10.2
3.920	---	27.2	46.0	18.8	L1	10.0
3.991	33.4	---	56.0	22.6	N	9.9
9.363	52.4	---	60.0	7.6	N	10.2
9.471	---	45.5	50.0	4.5	N	10.2

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 5: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.150	---	36.3	56.0	19.7	L1	9.8
0.150	57.2	---	66.0	8.8	L1	9.8
0.215	43.8	---	63.0	19.2	N	9.8
0.261	---	26.2	51.4	25.2	L1	9.7
0.522	---	28.5	46.0	17.5	L1	10.0
0.526	38.8	---	56.0	17.2	L1	10.0
3.527	---	23.4	46.0	22.6	L1	9.8
3.589	33.1	---	56.0	22.9	L1	9.8
3.947	---	24.8	46.0	21.2	L1	9.8
3.975	35.7	---	56.0	20.3	L1	9.8
9.725	35.1	---	60.0	24.9	L1	9.8
9.813	---	30.5	50.0	19.5	L1	9.8

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

Antenna Height [cm]	Antenna Polarisation	Resolution Bandwidth [kHz]	Video Bandwidth [kHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	120	300	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operate or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

Antenna Height [cm]	Antenna Polarisation	Resolution Bandwidth [MHz]	Video Bandwidth [MHz]	Turntable position
100 ~ 400	Horizontal, Vertical	1	3	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and CISPR-average detectors.

Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m

Frequency range Limits [MHz]	Field Strength		
	3 m [$\mu\text{V/m}$]	3 m [dB($\mu\text{V/m}$)]	10 m [dB($\mu\text{V/m}$)]
30 to 88	100	40.0	29.5
88 to 216	150	43.5	33.0
216 to 960	200	46.0	35.5
Above 960	500	54.0	43.5

Results checked manually; and points close to the limit line were re-measured.

5.2.1 Test instrumentation

EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-002	Universal Radio Communicator	CMU200	R&S	100612	2018-08-31	12
E5I-021	EMI Test Receiver	ESU40	R&S	100376	2019-01-30	12
E5I-016	EMI Test Receiver	ESU8	R&S	100482	2018-06-08	12
E5I-149	Horn Antenna	HF907	R&S	102525	2018-06-15	24
E5I-039	Signal Conditioning Unit	SCU-18	R&S	10211	2019-01-22	12
E5I-037	Wide Band Horn Antenna	WBH 18-40K	R&S	11201	2017-10-13	24
E5I-042	Signal Conditioning Unit	SCU-40A	R&S	10004	2018-09-05	12
E5I-120	BiLog Antenna	CBL6112D	TESEQ	36997	2018-04-23	24
E5I-072	BiLog Antenna	CBL6112D	TESEQ	36009	2018-04-23	24
E5I-075	Preamplifier	310N	SONOMA	332018	2018-05-25	12
E5I-076	Preamplifier	310N	SONOMA	332019	2018-05-25	12
-	Test software	EP7RE	TOYO	Ver 5.8.2	-	-
-	Test software	EMC32	R&S	Ver 9.25.00	-	-


5.2.2 Temperature and humidity condition

Test date	2019-01-31 ~ 2019-02-08	Test engineer	Soo-Joon Kim
Climate condition	Ambient temperature	(22.8 ~ 23.1) °C	Limit (15.0 to 35.0) °C
	Relative humidity	(46.7 ~ 49.5) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(101.9 ~ 102.7) kPa	Limit (86.0 to 106.0) kPa
Test place	Semi-Anechoic Chamber (SAC4)		

5.2.3 Test results

☐ Operating Mode 1

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	32.454	V	27.9	-7.3	20.6	29.5	8.9	101	241	2
2	88.079	V	38.7	-16.2	22.5	33.0	10.5	100	104	2
3	99.668	V	37.1	-14.0	23.1	33.0	9.9	149	0	2
4	398.672	H	36.8	-7.6	29.2	35.5	6.3	181	37	1
5	498.319	H	34.6	-5.6	29.0	35.5	6.5	190	44	1
6	597.997	H	33.2	-4.0	29.2	35.5	6.3	154	43	1
7	896.999	H	32.1	-0.6	31.5	35.5	4.0	100	7	1

* Radiated emissions (Rx frequency 88.079 MHz) from the transceiver shall be ignored


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dBμV/m)	CAV (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
3 020.500	41.4	---	74.0	32.6	100.0	H	24.0	0.8
3 020.500	---	38.5	54.0	15.5	100.0	H	24.0	0.8

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions


Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 2**- Frequencies below 1 GHz**

Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	80.170	V	37.4	-17.5	19.9	29.5	9.6	167	56	2
2	98.021	V	35.3	-14.3	21.0	33.0	12.0	100	66	2
3	160.344	V	40.7	-14.2	26.5	33.0	6.5	100	251	2
4	240.490	V	34.6	-11.5	23.1	35.5	12.4	100	75	2
5	320.636	V	33.4	-9.4	24.0	35.5	11.5	100	216	2
6	912.094	V	18.9	-0.3	18.6	35.5	16.9	200	171	2

* Radiated emissions (Rx frequency 98.021 MHz) from the transceiver shall be ignored


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dBμV/m)	CAV (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
3 020.500	---	35.8	54.0	18.2	100.0	H	87.0	0.8
3 020.500	41.3	---	74.0	32.7	100.0	H	87.0	0.8

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions


Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 3**- Frequencies below 1 GHz**

Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	30.537	V	22.7	-7.7	15.0	29.5	14.5	274	360	2
2	32.143	H	23.1	-8.1	15.0	29.5	14.5	399	360	1
3	108.048	V	33.5	-13.0	20.5	33.0	12.5	111	360	2
4	263.216	V	21.1	-10.5	10.6	35.5	24.9	292	360	2
5	538.683	V	20.8	-3.5	17.3	35.5	18.2	170	114	2
6	996.198	H	20.2	1.0	21.2	43.5	22.3	305	360	1

* Radiated emissions (Rx frequency 108.048 MHz) from the transceiver shall be ignored

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 4

- Frequencies below 1 GHz



Final Result

No.	Frequency (P)	Reading	c.f	Result	Limit	Margin	Height	Angle	System
	[MHz]	QP [dB(uV)]	[dB(1/m)]	QP [dB(uV/m)]	QP [dB(uV/m)]	QP [dB]	[cm]	[deg]	
1	84.078	V 34.1	-17.2	16.9	29.5	12.6	200	260	2
2	391.931	V 29.8	-7.3	22.5	35.5	13.0	100	164	2
3	401.268	H 36.8	-7.6	29.2	35.5	6.3	200	269	1
4	498.995	H 32.7	-5.9	26.8	35.5	8.7	200	232	1
5	608.484	H 32.3	-4.4	27.9	35.5	7.6	100	245	1
6	742.101	H 33.0	-3.0	30.0	35.5	5.5	100	230	1


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dBμV/m)	CAV (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 176.4	---	39.3	54.0	14.7	100.0	H	236.0	6.6
1 177.6	49.1	---	74.0	24.9	100.0	H	236.0	6.6
3 260.5	48.1	---	74.0	25.9	100.0	H	226.0	1.2
3 267.0	---	38.4	54.0	15.6	100.0	H	226.0	1.2
5 399.5	---	47.6	54.0	6.4	100.0	H	131.0	6.5
5 399.5	49.8	---	74.0	24.2	100.0	H	131.0	6.5
17 831.5	51.0	---	74.0	23.0	100.0	H	226.0	34.7
17 851.5	---	45.3	54.0	8.7	100.0	H	143.0	34.4

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions


Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 5**- Frequencies below 1 GHz**

Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	479.988	H	35.5	-6.2	29.3	35.5	6.2	210	73	1
2	61.120	V	37.5	-18.8	18.7	29.5	10.8	297	41	2
3	62.253	V	31.9	-18.8	13.1	29.5	16.4	297	89	2
4	191.384	V	31.3	-15.0	16.3	33.0	16.7	100	358	2
5	179.865	V	31.0	-14.7	16.3	33.0	16.7	100	342	2
6	240.005	H	23.6	-12.1	11.5	35.5	24.0	400	11	1


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dBμV/m)	CAV (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 591.600	---	27.7	54.0	26.3	100.0	V	122.0	9.8
1 597.200	40.5	---	74.0	33.5	100.0	V	86.0	9.8
1 860.400	---	30.7	54.0	23.3	100.0	V	0.0	11.7
1 863.600	44.2	---	74.0	29.8	100.0	V	172.0	11.7
2 124.800	---	34.1	54.0	19.9	100.0	V	23.0	12.9
2 124.800	51.6	---	74.0	22.4	100.0	V	23.0	12.9
2 713.200	43.0	---	74.0	31.0	100.0	V	359.0	15.7
2 727.200	---	31.3	54.0	22.7	100.0	H	341.0	15.6
7 660.000	42.1	---	74.0	31.9	100.0	V	193.0	12.7
7 660.000	---	37.5	54.0	16.5	100.0	V	193.0	12.7
17 827.000	50.9	---	74.0	23.1	100.0	H	173.0	34.8
17 975.500	---	45.9	54.0	8.1	100.0	V	279.0	34.9

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor