



MEASUREMENT REPORT

LTE

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

10/11/2019 - 3/10/2020

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M2001240012-03.A3L

FCC ID:

A3LSMG986JPN

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SC-52A

Additional Model(s):

SCG02, SM-G986DS

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):

22 & 27

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01,
KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President




FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 1 of 138

TABLE OF CONTENTS


1.0	INTRODUCTION	5
1.1	Scope	5
1.2	PCTEST Test Location.....	5
1.3	Test Facility / Accreditations.....	5
2.0	PRODUCT INFORMATION.....	6
2.1	Equipment Description	6
2.2	Device Capabilities.....	6
2.3	Test Configuration	6
2.4	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Measurement Procedure.....	7
3.2	Radiated Power and Radiated Spurious Emissions	7
4.0	MEASUREMENT UNCERTAINTY	8
5.0	TEST EQUIPMENT CALIBRATION DATA	9
6.0	SAMPLE CALCULATIONS	10
7.0	TEST RESULTS	11
7.1	Summary	11
7.2	Occupied Bandwidth	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal	44
7.4	Band Edge Emissions at Antenna Terminal	67
7.5	Peak-Average Ratio	97
7.6	Radiated Power (ERP/EIRP).....	107
7.7	Radiated Spurious Emissions Measurements	113
7.8	Frequency Stability / Temperature Variation	127
8.0	CONCLUSION	138

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 2 of 138



MEASUREMENT REPORT

FCC Part 22 & 27



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)		
LTE Band 12	27	699.7 - 715.3	0.038	15.75	0.062	17.90	1M10G7D	QPSK
LTE Band 12	27	699.7 - 715.3	0.033	15.18	0.054	17.33	1M10W7D	16QAM
LTE Band 12	27	699.7 - 715.3	0.025	14.04	0.042	16.19	1M10W7D	64QAM
LTE Band 12	27	700.5 - 714.5	0.039	15.89	0.064	18.04	2M70G7D	QPSK
LTE Band 12	27	700.5 - 714.5	0.031	14.93	0.051	17.08	2M72W7D	16QAM
LTE Band 12	27	700.5 - 714.5	0.025	14.06	0.042	16.21	2M71W7D	64QAM
LTE Band 12	27	701.5 - 713.5	0.039	15.96	0.065	18.11	4M50G7D	QPSK
LTE Band 12	27	701.5 - 713.5	0.033	15.21	0.054	17.36	4M51W7D	16QAM
LTE Band 12	27	701.5 - 713.5	0.027	14.26	0.044	16.41	4M52W7D	64QAM
LTE Band 12	27	704 - 711	0.045	16.53	0.074	18.68	9M01G7D	QPSK
LTE Band 12	27	704 - 711	0.038	15.77	0.062	17.92	8M97W7D	16QAM
LTE Band 12	27	704 - 711	0.029	14.67	0.048	16.82	8M99W7D	64QAM
LTE Band 13	27	779.5 - 784.5	0.042	16.28	0.070	18.43	4M51G7D	QPSK
LTE Band 13	27	779.5 - 784.5	0.036	15.60	0.060	17.75	4M50W7D	16QAM
LTE Band 13	27	779.5 - 784.5	0.033	15.20	0.054	17.35	4M52W7D	64QAM
LTE Band 13	27	782	0.047	16.74	0.077	18.89	8M97G7D	QPSK
LTE Band 13	27	782	0.040	16.01	0.065	18.16	8M99W7D	16QAM
LTE Band 13	27	782	0.031	14.91	0.051	17.06	8M97W7D	64QAM
LTE Band 5	22H	824.7 - 848.3	0.044	16.47	0.073	18.62	1M09G7D	QPSK
LTE Band 5	22H	824.7 - 848.3	0.038	15.77	0.062	17.92	1M10W7D	16QAM
LTE Band 5	22H	824.7 - 848.3	0.030	14.77	0.049	16.92	1M09W7D	64QAM
LTE Band 5	22H	825.5 - 847.5	0.045	16.53	0.074	18.68	2M71G7D	QPSK
LTE Band 5	22H	825.5 - 847.5	0.038	15.78	0.062	17.93	2M71W7D	16QAM
LTE Band 5	22H	825.5 - 847.5	0.030	14.76	0.049	16.91	2M71W7D	64QAM
LTE Band 5	22H	826.5 - 846.5	0.046	16.60	0.075	18.75	4M56G7D	QPSK
LTE Band 5	22H	826.5 - 846.5	0.040	15.97	0.065	18.12	4M52W7D	16QAM
LTE Band 5	22H	826.5 - 846.5	0.031	14.87	0.050	17.02	4M54W7D	64QAM
LTE Band 5	22H	829 - 844	0.053	17.22	0.086	19.37	9M02G7D	QPSK
LTE Band 5	22H	829 - 844	0.044	16.40	0.072	18.55	9M00W7D	16QAM
LTE Band 5	22H	829 - 844	0.035	15.46	0.058	17.61	8M99W7D	64QAM

EUT Overview (<1 GHz)

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 3 of 138

Mode	FCC Rule Part	Tx Frequency (MHz)	EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)		
LTE Band 4	27	1710.7 - 1754.3	0.155	21.90	1M10G7D	QPSK
LTE Band 4	27	1710.7 - 1754.3	0.115	20.59	1M11W7D	16QAM
LTE Band 4	27	1710.7 - 1754.3	0.094	19.71	1M09W7D	64QAM
LTE Band 4	27	1711.5 - 1753.5	0.155	21.91	2M70G7D	QPSK
LTE Band 4	27	1711.5 - 1753.5	0.129	21.12	2M71W7D	16QAM
LTE Band 4	27	1711.5 - 1753.5	0.098	19.90	2M71W7D	64QAM
LTE Band 4	27	1712.5 - 1752.5	0.159	22.02	4M57G7D	QPSK
LTE Band 4	27	1712.5 - 1752.5	0.138	21.39	4M53W7D	16QAM
LTE Band 4	27	1712.5 - 1752.5	0.103	20.12	4M53W7D	64QAM
LTE Band 4	27	1715 - 1750	0.159	22.01	9M01G7D	QPSK
LTE Band 4	27	1715 - 1750	0.137	21.37	9M02W7D	16QAM
LTE Band 4	27	1715 - 1750	0.110	20.43	8M99W7D	64QAM
LTE Band 4	27	1717.5 - 1747.5	0.174	22.40	13M5G7D	QPSK
LTE Band 4	27	1717.5 - 1747.5	0.137	21.37	13M5W7D	16QAM
LTE Band 4	27	1717.5 - 1747.5	0.109	20.38	13M5W7D	64QAM
LTE Band 4	27	1720 - 1745	0.178	22.49	18M0G7D	QPSK
LTE Band 4	27	1720 - 1745	0.151	21.78	18M0W7D	16QAM
LTE Band 4	27	1720 - 1745	0.120	20.78	18M0W7D	64QAM

EUT Overview (Mid Bands)

Mode	FCC Rule Part	Tx Frequency (MHz)	EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)		
LTE Band 41 (PC3)	27	2498.5 - 2687.5	0.254	24.04	4M52G7D	QPSK
LTE Band 41 (PC3)	27	2498.5 - 2687.5	0.208	23.18	4M52W7D	16QAM
LTE Band 41 (PC3)	27	2498.5 - 2687.5	0.163	22.12	4M53W7D	64QAM
LTE Band 41 (PC3)	27	2501 - 2685	0.255	24.07	8M93G7D	QPSK
LTE Band 41 (PC3)	27	2501 - 2685	0.182	22.59	8M85W7D	16QAM
LTE Band 41 (PC3)	27	2501 - 2685	0.143	21.56	8M99W7D	64QAM
LTE Band 41 (PC3)	27	2503.5 - 2682.5	0.251	24.00	13M5G7D	QPSK
LTE Band 41 (PC3)	27	2503.5 - 2682.5	0.212	23.27	13M5W7D	16QAM
LTE Band 41 (PC3)	27	2503.5 - 2682.5	0.160	22.03	13M5W7D	64QAM
LTE Band 41 (PC3)	27	2506 - 2680	0.256	24.07	18M0G7D	QPSK
LTE Band 41 (PC3)	27	2506 - 2680	0.192	22.83	18M0W7D	16QAM
LTE Band 41 (PC3)	27	2506 - 2680	0.159	22.00	17M9W7D	64QAM

EUT Overview (High Bands)

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset	Page 4 of 138	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 5 of 138

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMG986JPN**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

Test Device Serial No.: 0730M, 0384M, 0464M, 0375M, 0387M, 0378M, 1154M, 1157M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE), NFC, ANT+, Wireless Power Transfer

This device uses a tuner circuit that dynamically updates the antenna impedance parameters to optimize antenna performance for certain bands and modes of operation. The tuner for this device was set to simulate a "free space" condition where the transmit antenna is matched to the medium into which it is transmitting and, thus, the power is at its maximum level.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 6 of 138

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-E-2016) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10 \log_{10}(\text{Power [Watts]})$. For Band 41, the calculated P_d levels are compared to the absolute spurious emission limit of -25dBm which is equivalent to the required minimum attenuation of $55 + 10 \log_{10}(\text{Power [Watts]})$.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 7 of 138

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 8 of 138

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX1	Licensed Transmitter Cable Set	6/4/2019	Annual	6/4/2020	LTX1
-	LTX3	Licensed Transmitter Cable Set	10/30/2019	Annual	10/30/2020	LTX3
Agilent	N9020A	MXA Signal Analyzer	4/20/2019	Annual	4/20/2020	US46470561
Agilent	N9038A	MXE EMI Receiver	7/17/2019	Annual	7/17/2020	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	6/12/2019	Annual	6/12/2020	MY52350166
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	5/10/2019	Annual	5/10/2020	441112
Espec	ESX-2CA	Environmental Chamber	6/13/2019	Annual	6/13/2020	17620
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	PWR-SEN-4RMS	USB Power Sensor	4/20/2019	Annual	4/20/2020	11210140001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11403100002
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			100976
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			102060
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	6/5/2019	Annual	6/5/2020	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/23/2019	Annual	9/23/2020	100348
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/11/2019	Annual	7/11/2020	102134
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	4/30/2018	Biennial	4/30/2020	9105-2403
Sunol	DRH-118	Horn Antenna (1-18GHz)	10/3/2019	Biennial	10/3/2021	A050307

Table 5-1. Test Equipment

Notes:

1. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset	Page 9 of 138	

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 10 of 138

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMG986JPN
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 27.53(c) 27.53(g) 27.53(h)	Out of Band Emissions	$> 43 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions			Section 7.3, 7.4
27.53(m)	Out of Band Emissions	Undesirable emissions must meet the limits detailed in 27.53(m)			Section 7.3, 7.4
27.53(a)	Out of Band Emissions	Undesirable emissions must meet the limits detailed in 27.53(a)			Section 7.3, 7.4
27.50(d)	Peak-Average Ratio	$< 13 \text{ dB}$			Section 7.5
2.1046	Transmitter Conducted Output Power	N/A			See RF Exposure Report
2.1055 22.355 27.54	Frequency Stability	$< 2.5 \text{ ppm}$ (Part 22) and fundamental emissions stay within authorized frequency block (Part 27)			Section 7.8

Table 7-1. Summary of Conducted Test Results

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 11 of 138

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
22.913(a)(5)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 5)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
27.50(b)(10) 27.50(c)(10)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 12/13)	< 3 Watts max. ERP			Section 7.6
27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 41)	< 2 Watts max. EIRP			Section 7.6
27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	< 1 Watts max. EIRP			Section 7.6
2.1053 22.917(a) 27.53(c) 27.53(g) 27.53(h)	Undesirable Emissions (Band 12/13/5/4)	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions			Section 7.7
27.53(f)	Undesirable Emissions (Band 13)	< -70 dBW/MHz (for wideband signals) < -80 dBW (for discrete emissions less than 700Hz BW) For all emissions in the band 1559 – 1610 MHz			Section 7.7
27.53(m)	Undesirable Emissions (Band 41)	Undesirable emissions must meet the limits detailed in 27.53(m)			Section 7.7
27.53(m)	Uplink Carrier Aggregation	Undesirable emissions must meet the limits detailed in 27.53(m)			Section 7.7

Table 7-2. Summary of Radiated Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots (Sections 7.2, 7.3, 7.4, 7.5) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 5.3.

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset	Page 12 of 138	

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 13 of 138

Band 12




Plot 7-1. Occupied Bandwidth Plot (Band 12 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-2. Occupied Bandwidth Plot (Band 12 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 14 of 138




Plot 7-3. Occupied Bandwidth Plot (Band 12 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (Band 12 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 15 of 138




Plot 7-5. Occupied Bandwidth Plot (Band 12 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (Band 12 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 16 of 138




Plot 7-7. Occupied Bandwidth Plot (Band 12 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (Band 12 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 17 of 138




Plot 7-9. Occupied Bandwidth Plot (Band 12 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (Band 12 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 18 of 138




Plot 7-11. Occupied Bandwidth Plot (Band 12 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-12. Occupied Bandwidth Plot (Band 12 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 19 of 138

Band 13




Plot 7-13. Occupied Bandwidth Plot (Band 13 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (Band 13 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 20 of 138




Plot 7-15. Occupied Bandwidth Plot (Band 13 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-16. Occupied Bandwidth Plot (Band 13 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 21 of 138



Plot 7-17. Occupied Bandwidth Plot (Band 13 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-18. Occupied Bandwidth Plot (Band 13 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 22 of 138

Band 5




Plot 7-19. Occupied Bandwidth Plot (Band 5 – 1.4MHz QPSK - Full RB Configuration)




Plot 7-20. Occupied Bandwidth Plot (Band 5 – 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 23 of 138




Plot 7-21. Occupied Bandwidth Plot (Band 5 – 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-22. Occupied Bandwidth Plot (Band 5 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 24 of 138




Plot 7-23. Occupied Bandwidth Plot (Band 5 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-24. Occupied Bandwidth Plot (Band 5 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 25 of 138




Plot 7-25. Occupied Bandwidth Plot (Band 5 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-26. Occupied Bandwidth Plot (Band 5 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 26 of 138




Plot 7-27. Occupied Bandwidth Plot (Band 5 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-28. Occupied Bandwidth Plot (Band 5 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 27 of 138




Plot 7-29. Occupied Bandwidth Plot (Band 5 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-30. Occupied Bandwidth Plot (Band 5 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 28 of 138

Band 4




Plot 7-31. Occupied Bandwidth Plot (Band 4 – 1.4MHz QPSK - Full RB Configuration)




Plot 7-32. Occupied Bandwidth Plot (Band 4 – 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 29 of 138




Plot 7-33. Occupied Bandwidth Plot (Band 4 – 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-34. Occupied Bandwidth Plot (Band 4 – 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 30 of 138




Plot 7-35. Occupied Bandwidth Plot (Band 4 – 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-36. Occupied Bandwidth Plot (Band 4 – 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 31 of 138




Plot 7-37. Occupied Bandwidth Plot (Band 4 – 5.0MHz QPSK - Full RB Configuration)




Plot 7-38. Occupied Bandwidth Plot (Band 4 – 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 32 of 138




Plot 7-39. Occupied Bandwidth Plot (Band 4 – 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-40. Occupied Bandwidth Plot (Band 4 – 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 33 of 138




Plot 7-41. Occupied Bandwidth Plot (Band 4 – 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-42. Occupied Bandwidth Plot (Band 4 – 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 34 of 138




Plot 7-43. Occupied Bandwidth Plot (Band 4 – 15.0MHz QPSK - Full RB Configuration)




Plot 7-44. Occupied Bandwidth Plot (Band 4 – 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 35 of 138




Plot 7-45. Occupied Bandwidth Plot (Band 4 – 15.0MHz 64-QAM - Full RB Configuration)




Plot 7-46. Occupied Bandwidth Plot (Band 4 – 20.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 36 of 138




Plot 7-47. Occupied Bandwidth Plot (Band 4 – 20.0MHz 16-QAM - Full RB Configuration)




Plot 7-48. Occupied Bandwidth Plot (Band 4 – 20.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 37 of 138

Band 41




Plot 7-49. Occupied Bandwidth Plot (Band 41 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-50. Occupied Bandwidth Plot (Band 41 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 38 of 138




Plot 7-51. Occupied Bandwidth Plot (Band 41 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-52. Occupied Bandwidth Plot (Band 41 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 39 of 138




Plot 7-53. Occupied Bandwidth Plot (Band 41 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-54. Occupied Bandwidth Plot (Band 41 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 40 of 138




Plot 7-55. Occupied Bandwidth Plot (Band 41 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-56. Occupied Bandwidth Plot (Band 41 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 41 of 138




Plot 7-57. Occupied Bandwidth Plot (Band 41 - 15.0MHz 64-QAM - Full RB Configuration)




Plot 7-58. Occupied Bandwidth Plot (Band 41 - 20.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 42 of 138



Plot 7-59. Occupied Bandwidth Plot (Band 41 - 20.0MHz 16-QAM - Full RB Configuration)



Plot 7-60. Occupied Bandwidth Plot (Band 41 - 20.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 43 of 138

7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

For Band 41, the minimum permissible attenuation level of any spurious emission is $55 + 10 \log_{10}(P_{[Watts]})$.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to at least 10 * the fundamental frequency (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz and 1 MHz or greater for frequencies greater than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 44 of 138

Band 12




Plot 7-61. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-62. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 45 of 138




Plot 7-63. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-64. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 46 of 138




Plot 7-65. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-66. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 47 of 138




Plot 7-67. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-68. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: A3LSMG986JPN	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset	Page 48 of 138




Plot 7-69. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 49 of 138

Band 13




Plot 7-70. Conducted Spurious Plot (Band 13 - 10.0MHz QPSK - RB Size 1, RB Offset 0)



Plot 7-71. Conducted Spurious Plot (Band 13 - 10.0MHz QPSK - RB Size 1, RB Offset 0)


FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 50 of 138




Plot 7-72. Conducted Spurious Plot (Band 13 - 10.0MHz QPSK - RB Size 1, RB Offset 0)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 51 of 138

Band 5




Plot 7-73. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-74. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 52 of 138





Plot 7-75. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-76. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 53 of 138






Plot 7-79. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-80. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 55 of 138




Plot 7-81. Conducted Spurious Plot (Band 5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMG986JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 56 of 138

Band 4




Plot 7-82. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-83. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 57 of 138




Plot 7-84. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-85. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 58 of 138



Plot 7-88. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-89. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMG986JPN	PCTEST	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2001240012-03.A3L	Test Dates: 10/11/2019 - 3/10/2020	EUT Type: Portable Handset		Page 60 of 138