

FCC ID:	A3LSMG988U
Date:	1/3/2020
Test Procedure:	KDB 680106 D01 v03

E Measurements (V/m)	10% Battery		50% Battery		70% Battery		Limit (V/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.280	0.262	0.300	0.280	0.712	0.428	614.00
B (Right)	0.319	0.262	0.358	0.292	0.362	0.289	614.00
C (Top)	0.300	0.271	0.336	0.271	0.740	0.440	614.00
D (Left)	0.262	0.271	0.369	0.289	0.392	0.280	614.00
E (Front)	0.670	0.428	0.712	0.440	0.428	0.665	614.00
F (Back)	0.698	0.466	0.708	0.428	0.440	0.646	614.00

Table 1. E-field Measurement by distance/battery level (D2D)

H Measurements (A/m)	10% Battery		50% Battery		70% Battery		Limit (A/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.109	0.011	0.012	0.010	0.019	0.013	1.63
B (Right)	0.023	0.015	0.020	0.013	0.021	0.016	1.63
C (Top)	0.011	0.011	0.012	0.011	0.018	0.013	1.63
D (Left)	0.022	0.011	0.020	0.014	0.020	0.015	1.63
E (Front)	0.019	0.013	0.018	0.012	0.018	0.012	1.63
F (Back)	0.018	0.013	0.018	0.013	0.017	0.131	1.63

Table 2. H-field Measurement by distance/battery level (D2D)

Note:

The right and left edge are determined with the EUT screen facing the user.

Description of Test Setup

- o Testing was performed with a calibrated field probe.
- o Measurement was performed on each side of the EUT as described per Table 4.
- o Testing was performed at the distances and different battery level as indicated on Table 1 and Table 2.
- o Measurement procedure was performed per FCC Guidance.

Test Equipment

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Narda	EHP-200AC	Electric & Magnetic Field Probe	6/27/2019	Annual	6/27/2020	170WX60209