

EMC TEST REPORT

Project No.	LBE20220313	Issue No.	1
Applicant	Name of organization	Samsung Electronics Co., Ltd.	
	Address	(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea	
	Date of receipt	May 30, 2022	
EUT	Type of device	☒ All other receivers subject to Part 15 ☒ Class B personal computers and peripherals ☒ Other Class B digital devices and peripherals ☐ FM Broadcast Receiver	
	Equipment authorization	☒ Certification ☐ Supplier's Declaration of Conformity	
	FCC ID	A3LSMG990B2	
	Kind of product	Mobile Phone	
	Model No.	SM-G990B2/DS	
	Variant Model No.	Refer to clause 4.6	
	Manufacturer	Samsung Electronics Vietnam Thai Nguyen Co., Ltd. Yen Binh Industrial Zone Pho Ten Dist., Thai Nguyen Province, Vietnam	
Applied Standards		47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014	
Test Period		June 7, 2022 ~ June 9, 2022	
Issue date		June 15, 2022	
Test result : Complied The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.)			
Tested by : Seon-Tai Park		Reviewed by : Chang-Eun Park	
The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS center. * Not KOLAS report			
Samsung Electronics Co., Ltd., Global CS Center (Maetan dong) 129, Samsung-ro, Yeongtong-Gu, Suwon-Si, Gyeonggi-Do 16677, Korea			

Table of Contents

1. Report Information	3
1.1 Revision history	3
2. Summary of test results	3
2.1 Emission	3
3. General Information	3
3.1 Test facility	3
4. Test Setup configuration	4
4.1 Test Peripherals	4
4.2 EUT operating mode	5
4.3 Details of Sampling	5
4.4 Used cable description	6
4.5 Test arrangement	7
4.6 EUT Description	10
4.7 EUT Frequencies	10
4.8 Test configuration and condition	11
4.9 Measurement uncertainty	11
5. Results of individual test	12
5.1 Conducted Emission	12
5.2 Radiated Emission	17

1. Report Information

1.1 Revision history

No.	Date of Issue	Revised detailed information
Issue 0	June 10, 2022	There are no revisions and this version is basic test report.
Issue 1	June 15, 2022	Modified FCC ID. (A3LSMG990B → A3LSMG990B2)

※ Remark

Only compliance with Part 15B (Section 15.107 Conducted limits) requirements for the receiver part of the licensed transmitter (equipment code CXX) is covered by this report.

2. Summary of test results

2.1 Emission

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result
■	Conducted Emission (Mains port)	47 CFR Part 15 Subpart B / ANSI C63.4-2014 (Class B)	Complied
■	Radiated Emission		Complied

3. General Information

3.1 Test facility

The Global CS Center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea.

All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms.

And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS Center is an ISO/IEC 17025 accredited testing laboratory by the National Radio Research Agency with designation No. KR0004. for EMC testing.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Description	Model No.	Serial No.	Manufacturer / Trademark	FCC ID
Mobile Phone	SM-G990B2/DS	-	SAMSUNG	
Battery	EB-BG990ABY	-	SDI	-
Headset	AMD-21HS	-	CRESYN	-
Data Cable	EP-DN980	-	RF TECH	-
Laptop Computer	Latitude5580	1WYRYM2	Dell	DoC
Laptop Computer	Latitude5580	D3HRYM2	Dell	DoC
Laptop AC Adapter	LA65NM130	5DEA	Dell	DoC
Laptop AC Adapter	LA65NM130	5B3C	Dell	DoC
Mouse	AA-SM7PCPB	CN57BA5903634AD V8JJCD4371	SAMSUNG	DoC
Mouse	SMH-210UB	TAKGA05788Z	SAMSUNG	DoC
Router	DIR-806A	RF0F1D8018454	D-Link	DoC
Router	DIR-806A	RF0F1D8011504	D-Link	DoC
Travel Adapter	EP-TA800	R37NAVT13L8SE3	SoluM	-

4.2 EUT operating mode

To achieve compliance applied standard specification including CXX, JAB and JBP requirement, the following mode(s) were made during compliance testing:

4.2.1 Conducted Emission

No.	Operating mode
1	Camera (Rear) + Charging (w/TA) + Cellular receiver (LTE B26 Center Frequency)
2	Camera (Front) + Charging (w/TA)
3	Video + Audio playback from internal memory + Charging (w/TA)
4	USB data communication with PC (from internal memory)

4.2.2 Radiated Emission

No.	Operating mode
1	Camera (Rear) + Charging (w/TA)
2	Camera (Front) (w/Headset)
3	Video + Audio playback from internal memory (w/Headset)
4	USB data communication with PC (from internal memory)

4.3 Details of Sampling

Customer selected, single unit.


4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:


Connected cable	Length [m]	Shielded [Y/N]	Note
Data Cable	1.0	Y	From EUT to Laptop Computer or Travel Adapter
Headset	1.2	N	For EUT
Power	1.8	N	From Laptop Computer to AC Adapter
Power	1.5	N	For Laptop AC Adapter
LAN	1.5	N	From Laptop Computer to Router
USB	0.8	Y	From Laptop Computer to Router for DC Power
USB	1.8	Y	From Laptop Computer to Mouse

4.5 Test arrangement

4.5.1 Conducted Emission




[Mode 1 – 3]




[Mode 4]


4.5.2 Radiated Emission



[Mode 1]



[Mode 2 – 3]



[Mode 4]

4.6 EUT Description

The EUT is a bar type mobile phone which can operate on GSM 850/900/1800/1900, WCDMA FDD 1/2/4/5/8, LTE FDD 1/2/3/4/5/7/8/12/17/20/26/28/32/66, LTE TDD 38/40/41, 5G NR n1/3/5/7/8/28/38/40/41/66/78, and incorporates a Wi-Fi (802.11 a/b/g/n/ac/ax), Bluetooth, Camera, GNSS, NFC, Audio and Video.

4.6.1 The variant models

- SM-G990B2

4.7 EUT Frequencies

The highest frequencies (Generated and used)	Frequency [MHz]
Wi-Fi	5 825

4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables.

All the external I/O ports are exercised, as well as internal and the external SD card(if available), by writing and reading arbitrary data or charging with TA.

The EUT was investigated in three orientations and the worst case orientation is reported.

RX mode(850MHz) testing for AC conducted emission test was performed with the LTE B26 RX Test mode at center frequency. All licensed communication (850MHz) RX mode, GSM/WCDMA/LTE, test results are not significantly different.

The video and audio(1 kHz sound) were repetitively played with the earphone connected.

The camera of the EUT was operated continuously.

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus : (According to CISPR 16-4-2 and UKAS M3003)

Test type		Measurement uncertainty (C.L. approximately 95 %, $k = 2$)
Conducted Emission	AC Mains	2.83 dB
Radiated Emission (Below 1 GHz)	Horizontal	4.15 dB
	Vertical	4.51 dB
Radiated Emission (Above 1 GHz)	Horizontal	4.99 dB
	Vertical	4.99 dB

* Remark

- 1) The values for uncertainty of conducted and radiated emissions are less than the Corresponding values of U_{CISPR} given in CISPR 16-4-2. Therefore no adjustment of measurement results is necessary when comparing them with the relevant limits.

5. Results of individual test

5.1 Conducted Emission

The EUT is connected to a LISN via travel adapter. If the EUT is connected to the Laptop Computer USB port, the Laptop AC adapter is connected to a LISN.

Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Limits for Conducted emission at the mains ports of Class B

Frequency range Limits [MHz]	Resolution Bandwidth [kHz]	Limits [dB(μV)]	
		Quasi-peak	Average
0.15 to 0.50	9	66 to 56	56 to 46
0.50 to 5	9	56	46
5 to 30	9	60	50

NOTE 1 The lower limit shall apply at the transition frequency.

NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.1.1 Test instrumentation


EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Next Calibration	
					Date	Interval (Month)
E5I-006	LTE Communicator	CMW500	R&S	132728	2023-04-12	12
E5I-127	Two-Line V-Network	ENV216	R&S	102061	2023-01-17	12
E5I-018	EMI Test Receiver	ESU8	R&S	100484	2023-05-26	12
-	Test software	EMC32	R&S	Ver 10.60.20	-	-

5.1.2 Temperature and humidity condition

Test date	2022-06-09	Test engineer	Seon-Tai Park
Climate condition	Ambient temperature	(23.6 ± 0.5) °C	Limit (15.0 to 35.0) °C
	Humidity	(42.3 ± 0.5) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(100.8 ± 0.5) kPa	Limit (86.0 to 106.0) kPa
Test place	Shield Room (SR8)		

5.1.3 Test Results

□ Operating Mode 1: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.152	52.1	---	65.9	13.8	N	10.0
0.152	---	35.0	55.9	20.9	N	10.0
0.193	47.1	---	63.9	16.8	N	10.1
0.193	---	28.9	53.9	25.0	N	10.1
0.240	41.5	---	62.1	20.6	N	9.9
0.240	---	21.4	52.1	30.7	N	9.9
0.440	36.8	---	57.1	20.2	N	10.1
0.440	---	25.6	47.1	21.5	N	10.1
5.332	---	19.7	50.0	30.3	L1	10.0
5.332	26.7	---	60.0	33.3	L1	10.0
18.267	---	24.8	50.0	25.2	L1	10.5
18.267	31.3	---	60.0	28.7	L1	10.5

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 2: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.159	---	28.4	55.5	27.1	L1	10.1
0.159	49.0	---	65.5	16.5	L1	10.1
0.202	---	27.0	53.5	26.5	L1	10.0
0.202	45.7	---	63.5	17.8	L1	10.0
0.233	---	23.3	52.3	29.1	L1	9.9
0.233	42.2	---	62.3	20.1	L1	9.9
0.449	---	27.4	46.9	19.5	N	10.1
0.449	38.0	---	56.9	18.9	N	10.1
4.868	24.4	---	56.0	31.6	L1	10.0
4.868	---	17.1	46.0	28.9	L1	10.0
17.948	30.2	---	60.0	29.8	L1	10.5
17.948	---	23.8	50.0	26.2	L1	10.5

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 3: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:


Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.161	---	31.1	55.4	24.3	L1	10.1
0.161	50.1	---	65.4	15.3	L1	10.1
0.202	---	27.3	53.5	26.2	L1	10.0
0.202	46.1	---	63.5	17.4	L1	10.0
0.224	43.2	---	62.7	19.5	N	9.9
0.224	---	23.6	52.7	29.0	N	9.9
0.443	---	26.4	47.0	20.7	N	10.1
0.443	37.9	---	57.0	19.1	N	10.1
13.574	---	17.6	50.0	32.4	N	10.4
13.574	24.3	---	60.0	35.7	N	10.4
18.152	30.1	---	60.0	29.9	L1	10.5
18.152	---	23.6	50.0	26.4	L1	10.5

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 4: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.150	---	23.4	56.0	32.6	L1	9.8
0.152	46.5	---	65.9	19.4	N	9.9
0.184	44.9	---	64.3	19.4	N	10.0
0.193	---	20.1	53.9	33.8	L1	10.0
0.497	32.0	---	56.1	24.0	L1	10.0
0.497	---	22.0	46.1	24.1	L1	10.0
3.579	33.8	---	56.0	22.2	N	9.8
3.599	---	24.3	46.0	21.7	N	9.8
3.887	---	24.3	46.0	21.7	N	9.8
3.887	33.9	---	56.0	22.1	N	9.8
9.787	34.9	---	60.0	25.1	L1	9.9
9.859	---	27.4	50.0	22.6	L1	9.9

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

5.2 Radiated Emission

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

Antenna Height [cm]	Antenna Polarization	Resolution Bandwidth [kHz]	Video Bandwidth [kHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	120	300	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position.

Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operates or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

Antenna Height [cm]	Antenna Polarization	Resolution Bandwidth [MHz]	Video Bandwidth [MHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	1	3	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position.

Final measurements were made using peak and CISPR-average detectors.

Limits for Radiated emission of Class B at a measuring distance of 3 m and 10 m

Frequency range Limits [MHz]	Field Strength		
	3 m [$\mu\text{V/m}$]	3 m [$\text{dB}(\mu\text{V/m})$]	10 m [$\text{dB}(\mu\text{V/m})$]
30 to 88	100	40.0	29.5
88 to 216	150	43.5	33.0
216 to 960	200	46.0	35.5
Above 960	500	54.0	43.5

Note) Distance correction formula from D1(3m) to D2(10m)

: Limit at D2 = Limit at D1 + $20\log(D1/D2)$

Results checked manually; and points close to the limit line were re-measured.

5.2.1 Test instrumentation

EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Next Calibration	
					Date	Interval (Month)
E5I-021	EMI Test Receiver	ESU40	R&S	100376	2023-01-28	12
E5I-020	EMI Test Receiver	ESU40	R&S	100375	2022-09-23	12
E5I-069	BiLog Antenna	CBL6112D	TESEQ	35382	2023-08-09	24
E5I-138	6 dB Fixed Attenuator	8491A	Keysight	MY52462285	2023-08-09	24
E5I-071	BiLog Antenna	CBL6112D	TESEQ	35384	2023-08-09	24
E5I-136	6 dB Fixed Attenuator	8491A	Keysight	MY52462355	2023-08-09	24
E5I-073	Preamplifier	310N	SONOMA	332016	2023-05-02	12
E5I-074	Preamplifier	310N	SONOMA	332017	2023-05-02	12
E5I-035	Horn Antenna	HF907	R&S	100506	2022-09-28	12
E5I-039	Signal Conditioning Unit	SCU-18	R&S	10211	2023-04-18	12
E5I-243	WideBand Horn Antenna	QMS-00880	STEATITE	25187	2022-11-17	12
E5I-042	Signal Conditioning Unit	SCU-40A	R&S	10004	2022-09-10	12
-	Test software	EP7RE	TOYO	Ver 8.0.20	-	-
-	Test software	EMC32	R&S	Ver 9.25.00	-	-


5.2.1 Temperature and humidity condition

Test date	2022-06-07 ~ 2022-06-08	Test engineer	Seon-Tai Park
Climate condition	Ambient temperature	(22.7 ± 0.5) °C	Limit (15.0 to 35.0) °C
	Humidity	(40.5 ± 0.5) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(101.2 ± 0.5) kPa	Limit (86.0 to 106.0) kPa
Test place	Semi-Anechoic Chamber (SAC5)		

5.2.3 Test Results

□ Operating Mode 1

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB (uV)]	c.f [dB (1/m)]	Result QP [dB (uV/m)]	Limit QP [dB (uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	30.121	H	23.0	-7.0	16.0	29.5	13.5	107	180	1
2	43.459	V	22.8	-13.8	9.0	29.5	20.5	140	54	2
3	75.832	V	38.7	-18.1	20.6	29.5	8.9	172	235	2
4	92.808	V	44.8	-15.4	29.4	33.0	3.6	126	241	2
5	171.014	V	36.3	-14.1	22.2	33.0	10.8	113	138	2
6	956.107	H	20.3	0.4	20.7	35.5	14.8	275	164	1

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions.

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 2

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB (uV)]	c.f [dB (1/m)]	Result QP [dB (uV/m)]	Limit QP [dB (uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	30.243	H	23.1	-7.1	16.0	29.5	13.5	100	271	1
2	37.639	H	22.3	-11.0	11.3	29.5	18.2	200	182	1
3	75.469	H	22.5	-18.4	4.1	29.5	25.4	100	285	1
4	265.104	V	20.9	-9.8	11.1	35.5	24.4	100	316	2
5	817.761	V	19.8	-0.8	19.0	35.5	16.5	200	10	2
6	951.985	V	18.7	1.2	19.9	35.5	15.6	300	94	2

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions.

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 3

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB (uV)]	c.f [dB (1/m)]	Result QP [dB (uV/m)]	Limit QP [dB (uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	30.728	H	23.0	-7.3	15.7	29.5	13.8	400	273	1
2	31.819	V	22.3	-7.6	14.7	29.5	14.8	200	216	2
3	81.774	V	21.4	-17.2	4.2	29.5	25.3	400	147	2
4	128.334	H	22.4	-12.5	9.9	33.0	23.1	100	93	1
5	648.981	V	19.9	-2.5	17.4	35.5	18.1	300	116	2
6	812.063	V	19.7	-0.9	18.8	35.5	16.7	300	142	2

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions.

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 4

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB (uV)]	c.f [dB (1/m)]	Result QP [dB (uV/m)]	Limit QP [dB (uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	71.952	V	34.6	-18.5	16.1	29.5	13.4	176	93	2
2	83.229	V	32.0	-17.0	15.0	29.5	14.5	189	39	2
3	151.008	H	34.9	-14.2	20.7	33.0	12.3	400	355	1
4	256.010	H	39.7	-10.4	29.3	35.5	6.2	339	274	1
5	272.379	H	39.9	-10.8	29.1	35.5	6.4	296	281	1
6	864.685	V	19.5	-0.1	19.4	35.5	16.1	190	308	2


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dBµV/m)	CAV (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1859.600	42.15	---	74.00	31.85	102.6	V	138.0	12.16
1859.600	---	36.18	54.00	17.82	103.2	V	138.0	12.16
2127.400	---	45.49	54.00	8.51	101.0	V	31.0	13.82
2127.400	51.95	---	74.00	22.05	101.5	V	31.0	13.82
3184.500	40.73	---	74.00	33.27	105.1	V	0.0	1.81
3186.000	---	32.76	54.00	21.24	106.9	V	1.0	1.81
11430.000	44.85	---	74.00	29.15	108.7	H	217.0	20.64
11488.500	---	36.15	54.00	17.85	107.2	H	281.0	20.87
16788.000	48.53	---	74.00	25.47	101.9	V	228.0	34.37
16803.000	---	41.27	54.00	12.73	102.3	H	0.0	34.69
17799.000	---	45.10	54.00	8.90	104.7	H	171.0	38.42
17805.000	51.98	---	74.00	22.02	104.1	V	224.0	38.29

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions.

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor