



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

09/28/17 - 10/26/17

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M1709270258-01.A3L

FCC ID:

A3LSMJ250F

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model:

SM-J250F/DS

Additional Model:

SM-J250F

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
TNE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.32	0.58	0.69
TNE	UMTS 850	826.40 - 846.60 MHz	0.27	0.36	0.43
TNE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.27	0.36	0.43
TNE	LTE Band 7	2502.5 - 2567.5 MHz	1.06	0.52	0.78
TNE	LTE Band 38	2572.5 - 2617.5 MHz	0.57	0.28	0.58
DTS	2.4 GHz WLAN	2412 - 2462 MHz	1.05	0.10	0.25
DSS/DTS	Bluetooth	2402 - 2480 MHz	0.22	N/A	N/A
Simultaneous SAR per KDB 690783 D01v01r03:			1.51	0.77	1.03

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 1 of 57	

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	8
3	INTRODUCTION	9
4	DOSIMETRIC ASSESSMENT	10
5	DEFINITION OF REFERENCE POINTS	11
6	TEST CONFIGURATION POSITIONS	12
7	RF EXPOSURE LIMITS	16
8	FCC MEASUREMENT PROCEDURES.....	17
9	RF CONDUCTED POWERS.....	22
10	SYSTEM VERIFICATION.....	36
11	SAR DATA SUMMARY	38
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	46
13	SAR MEASUREMENT VARIABILITY	52
14	EQUIPMENT LIST.....	53
15	MEASUREMENT UNCERTAINTIES.....	54
16	CONCLUSION.....	55
17	REFERENCES	56
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 2 of 57

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 7	Data	2502.5 - 2567.5 MHz
LTE Band 38	Data	2572.5 - 2617.5 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
Bluetooth	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device utilizes a single step power reduction mechanism for SAR compliance under portable hotspot conditions for LTE band 7. All hotspot SAR evaluations for this device were performed at the maximum allowed output power when hotspot is enabled. Detailed descriptions of the power reduction mechanism are included in the operational description.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

Maximum TNE Target Powers

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.3	33.3	30.0	28.0	26.5	27.5	25.0	23.0	22.0
	Nominal	32.8	32.8	29.5	27.5	26.0	27.0	24.5	22.5	21.5

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	23.0	22.0	22.0	22.0
	Nominal	22.5	21.5	21.5	21.5

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 3 of 57

Mode / Band		Modulated Average (dBm)
LTE Band 5 (Cell)	Maximum	23.5
	Nominal	23.0
LTE Band 7	Maximum	22.5
	Nominal	22.0
LTE Band 38	Maximum	23.0
	Nominal	22.5

Reduced TNE Target Powers

Mode / Band		Modulated Average (dBm)
LTE Band 7	Maximum	20.5
	Nominal	20.0

WLAN Target Powers

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	17.0
	Nominal	16.5
IEEE 802.11g (2.4 GHz)	Maximum	14.5
	Nominal	14.0
IEEE 802.11n (2.4 GHz)	Maximum	12.5
	Nominal	12.0
Bluetooth BDR	Maximum	11.0
	Nominal	10.5
Bluetooth EDR	Maximum	9.5
	Nominal	9.0
Bluetooth LE	Maximum	1.0
	Nominal	0.5

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 4 of 57

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is ≤160 mm and the diagonal display is ≤150 mm. A diagram showing the location of the device antennas can be found in Appendix F.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 7	Yes	Yes	No	Yes	Yes	Yes
LTE Band 38	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	Yes	No

Note: Particular DUT edges were not required to be evaluated for wireless router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III. The distances between the transmit antennas and the edges of the device are included in the filing.

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



Figure 1-1
Simultaneous Transmission Paths

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 5 of 57

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	
2	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	^ Bluetooth Tethering is considered
3	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
4	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	^ Bluetooth Tethering is considered
5	LTE + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	*-Pre-installed VOIP applications are considered.
6	LTE + 2.4 GHz Bluetooth	Yes*^	Yes*	Yes^	*-Pre-installed VOIP applications are considered. ^ Bluetooth Tethering is considered
7	GPRS/EDGE + 2.4 GHz Wi-Fi	N/A	N/A	Yes	
8	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	N/A	Yes^	^ Bluetooth Tethering is considered

- 2.4 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- This device supports Bluetooth tethering for EDR packet only.

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth BDR (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(13/15) * \sqrt{2.480}] = 1.4 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Based on the maximum conducted power of Bluetooth EDR (rounded to the nearest mW) and the antenna to user separation distance, hotspot Bluetooth SAR was not required; $[(9/10) * \sqrt{2.480}] = 1.4 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 6 of 57

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 7 of 57

2 LTE INFORMATION

LTE Information					
FCC ID	A3LSMJ250F				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 7 (2502.5 - 2567.5 MHz)				
	LTE Band 38 (2572.5 - 2617.5 MHz)				
Channel Bandwidths	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 38: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 7: 5 MHz	2502.5 (20775)		2535 (21100)		2567.5 (21425)
LTE Band 7: 10 MHz	2505 (20800)		2535 (21100)		2565 (21400)
LTE Band 7: 15 MHz	2507.5 (20825)		2535 (21100)		2562.5 (21375)
LTE Band 7: 20 MHz	2510 (20850)		2535 (21100)		2560 (21350)
LTE Band 38: 5 MHz	2572.5 (37775)		2595 (38000)		2617.5 (38225)
LTE Band 38: 10 MHz	2575 (37800)		2595 (38000)		2615 (38200)
LTE Band 38: 15 MHz	2577.5 (37825)		2595 (38000)		2612.5 (38175)
LTE Band 38: 20 MHz	2580 (37850)		2595 (38000)		2610 (38150)
UE Category	4				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Release 10 Additional Information	This device does not support full CA features on 3GPP Release 10. All uplink communications are identical to the Release 8 Specifications. The following LTE Release 10 Features are not supported: Carrier Aggregation, Relay, HetNet, Enhanced MIMO, eICIC, WIFI Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 8 of 57

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 9 of 57

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset			Page 10 of 57

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 11 of 57

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 12 of 57

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 13 of 57

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4
Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 14 of 57

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 15 of 57

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 16 of 57

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 17 of 57

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.4.6 SAR Measurement Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 18 of 57

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 19 of 57

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

8.6.32.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.6.4 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset
		Page 20 of 57

8.6.5 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.4).

8.6.6 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 21 of 57	

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

Table 9-1
Maximum Conducted Power

Maximum Burst-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	31.90	31.88	28.80	27.50	26.07	25.65	24.10	22.25	21.21
	190	32.03	31.86	29.13	27.76	25.93	25.67	24.11	22.27	21.26
	251	31.98	32.00	29.19	27.83	26.12	25.69	24.09	22.28	21.16

Calculated Maximum Frame-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	22.87	22.85	22.78	23.24	23.06	16.62	18.08	17.99	18.20
	190	23.00	22.83	23.11	23.50	22.92	16.64	18.09	18.01	18.25
	251	22.95	22.97	23.17	23.57	23.11	16.66	18.07	18.02	18.15

GSM 850	Frame Avg.Targets:	23.77	23.77	23.48	23.24	22.99	17.97	18.48	18.24	18.49
---------	--------------------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 22 of 57

MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33 (Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A



Figure 9-1
Power Measurement Setup

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 23 of 57

9.2 UMTS Conducted Powers

Table 9-2
Maximum Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	
99	WCDMA	12.2 kbps RMC	22.45	22.52	22.45	-
99		12.2 kbps AMR	22.34	22.43	22.40	-
6	HSDPA	Subtest 1	21.60	21.56	21.43	0
6		Subtest 2	21.48	21.52	21.30	0
6		Subtest 3	21.49	21.49	21.31	0.5
6		Subtest 4	21.48	21.47	21.29	0.5
6	HSUPA	Subtest 1	21.64	21.11	21.44	0
6		Subtest 2	20.60	20.59	20.61	2
6		Subtest 3	20.58	20.20	20.35	1
6		Subtest 4	20.47	20.81	20.48	2
6		Subtest 5	21.55	21.57	21.35	0
8	DC-HSDPA	Subtest 1	21.69	21.66	21.49	0
8		Subtest 2	21.62	21.70	21.41	0
8		Subtest 3	21.47	21.48	21.42	0.5
8		Subtest 4	21.47	21.49	21.48	0.5

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 9-2
Power Measurement Setup

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 24 of 57

9.3 LTE Conducted Powers

9.3.1 LTE Band 5 (Cell)

Table 9-3
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.14	0	0
	1	25	23.01		0
	1	49	23.12		0
	25	0	21.04	0-1	1
	25	12	21.01		1
	25	25	21.09		1
	50	0	21.08		1
16QAM	1	0	21.10	0-1	1
	1	25	21.01		1
	1	49	21.20		1
	25	0	20.01	0-2	2
	25	12	20.02		2
	25	25	20.02		2
	50	0	20.06		2
					2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-4
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.10	23.01	22.97	0	0
	1	12	23.37	23.09	23.14		0
	1	24	22.86	22.91	22.92		0
	12	0	20.79	20.73	20.80	0-1	1
	12	6	20.85	20.75	20.89		1
	12	13	20.80	20.72	20.77		1
	25	0	20.76	20.73	20.70		1
16QAM	1	0	20.58	20.51	20.72	0-1	1
	1	12	20.88	20.68	20.92		1
	1	24	20.50	20.64	20.64		1
	12	0	20.08	19.81	19.74	0-2	2
	12	6	20.08	19.79	19.92		2
	12	13	19.92	20.05	19.87		2
	25	0	20.15	19.90	19.95		2

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 25 of 57

Table 9-5
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.36	23.33	23.14	0	0
	1	7	23.49	23.50	23.25		0
	1	14	23.42	23.39	23.18		0
	8	0	21.30	21.21	21.15	0-1	1
	8	4	21.34	21.32	21.19		1
	8	7	21.37	21.20	21.21		1
	15	0	21.25	21.26	21.28		1
16QAM	1	0	21.47	21.42	21.33	0-1	1
	1	7	21.60	21.64	21.51		1
	1	14	21.61	21.55	21.38		1
	8	0	20.57	20.50	20.54	0-2	2
	8	4	20.59	20.60	20.61		2
	8	7	20.54	20.55	20.62		2
	15	0	20.61	20.56	20.64		2

Table 9-6
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.25	23.04	23.04	0	0
	1	2	23.32	23.13	23.14		0
	1	5	23.19	23.03	23.11		0
	3	0	23.16	23.01	23.15		0
	3	2	23.24	23.05	23.07		0
	3	3	23.19	23.01	23.07		0
	6	0	20.88	20.67	20.77	0-1	1
16QAM	1	0	20.80	20.52	20.89	0-1	1
	1	2	20.65	20.67	20.94		1
	1	5	20.66	20.68	20.96		1
	3	0	21.09	20.73	20.92		1
	3	2	21.06	20.70	21.16		1
	3	3	21.28	20.88	21.20	1	
	6	0	20.20	20.18	20.10	0-2	2

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 26 of 57

9.3.2

LTE Band 7

Table 9-7
Maximum LTE Band 7 Conducted Powers - 20 MHz Bandwidth

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.55	21.86	22.02	0	0
	1	50	21.87	22.18	22.13		0
	1	99	22.00	21.91	21.73		0
	50	0	20.57	20.86	20.79	0-1	1
	50	25	20.60	20.94	20.64		1
	50	50	20.75	20.91	20.74		1
	100	0	20.67	20.86	20.70		1
16QAM	1	0	21.05	20.84	21.38	0-1	1
	1	50	21.41	21.04	21.42		1
	1	99	21.35	20.81	21.03		1
	50	0	19.76	19.67	19.96	0-2	2
	50	25	19.77	19.90	19.85		2
	50	50	19.78	19.86	19.63		2
	100	0	19.62	19.89	19.60		2

Table 9-8
Maximum LTE Band 7 Conducted Powers - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.52	21.84	21.97	0	0
	1	36	21.84	21.50	22.01		0
	1	74	21.84	21.89	21.87		0
	36	0	20.57	20.84	20.74	0-1	1
	36	18	20.57	20.92	20.59		1
	36	37	20.72	20.89	20.69		1
	75	0	20.64	20.84	20.65		1
16QAM	1	0	21.00	20.82	21.33	0-1	1
	1	36	21.38	21.02	21.37		1
	1	74	21.32	20.79	20.98		1
	36	0	19.73	19.65	19.91	0-2	2
	36	18	19.74	19.88	19.80		2
	36	37	19.75	19.84	19.59		2
	75	0	19.59	19.87	19.60		2

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 27 of 57

Table 9-9
Maximum LTE Band 7 Conducted Powers - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.47	21.83	21.98	0	0
	1	25	21.82	22.00	22.02		0
	1	49	21.95	21.88	21.69		0
	25	0	20.64	20.83	20.75	0-1	1
	25	12	20.55	20.91	20.60		1
	25	25	20.69	20.88	20.70		1
	50	0	20.62	20.83	20.66		1
16QAM	1	0	21.03	20.81	21.34	0-1	1
	1	25	21.36	21.00	21.38		1
	1	49	21.30	20.78	21.00		1
	25	0	19.71	19.64	19.92	0-2	2
	25	12	19.72	19.87	19.81		2
	25	25	19.73	19.83	19.59		2
	50	0	19.46	19.86	19.61		2

Table 9-10
Maximum LTE Band 7 Conducted Powers - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.64	21.80	21.99	0	0
	1	12	21.85	22.07	21.98		0
	1	24	21.89	21.85	21.70		0
	12	0	20.60	20.80	20.76	0-1	1
	12	6	20.58	20.88	20.61		1
	12	13	20.73	20.85	20.71		1
	25	0	20.65	20.81	20.67		1
16QAM	1	0	21.03	20.78	21.35	0-1	1
	1	12	21.39	21.00	21.31		1
	1	24	21.33	20.75	21.00		1
	12	0	19.74	19.57	19.93	0-2	2
	12	6	19.75	19.84	19.82		2
	12	13	19.76	19.83	19.60		2
	25	0	19.60	19.83	19.60		2

FCC ID: A3LSMJ250F



SAR EVALUATION REPORT



Approved by:
Quality Manager

Document S/N:

1M1709270258-01.A3L

Test Dates:

09/28/17 - 10/26/17

DUT Type:

Portable Handset

Page 28 of 57

Table 9-11
Reduced LTE Band 7 Conducted Powers - 20 MHz Bandwidth- Hotspot Mode Active

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.46	19.80	19.72	0	0
	1	50	19.93	19.99	20.00		0
	1	99	19.80	19.76	19.51		0
	50	0	19.68	19.93	19.94	0-1	0
	50	25	19.81	19.87	19.72		0
	50	50	19.67	19.72	19.62		0
	100	0	19.63	19.77	19.71		0
16QAM	1	0	19.05	19.58	19.30	0-1	0
	1	50	19.85	20.01	19.58		0
	1	99	19.01	19.15	19.08		0
	50	0	19.48	19.51	19.54	0-2	0
	50	25	19.53	19.58	19.55		0
	50	50	19.36	19.44	19.40		0
	100	0	19.36	19.49	19.65		0

Table 9-12
Reduced LTE Band 7 Conducted Powers - 15 MHz Bandwidth- Hotspot Mode Active

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.43	19.75	19.70	0	0
	1	36	19.91	19.94	19.97		0
	1	74	19.77	19.70	19.49		0
	36	0	19.65	19.88	19.92	0-1	0
	36	18	19.78	19.82	19.70		0
	36	37	19.64	19.67	19.60		0
	75	0	19.60	19.72	19.69		0
16QAM	1	0	19.02	19.53	19.28	0-1	0
	1	36	19.82	19.96	19.56		0
	1	74	19.09	19.35	19.26		0
	36	0	19.45	19.46	19.52	0-2	0
	36	18	19.50	19.53	19.53		0
	36	37	19.33	19.40	19.38		0
	75	0	19.39	19.45	19.63		0

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 29 of 57

Table 9-13
Reduced LTE Band 7 Conducted Powers - 10 MHz Bandwidth- Hotspot Mode Active

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.42	19.78	19.69	0	0
	1	25	19.89	19.97	19.98		0
	1	49	19.76	19.78	19.51		0
	25	0	19.65	19.91	19.91	0-1	0
	25	12	19.77	19.85	19.69		0
	25	25	19.63	19.70	19.59		0
	50	0	19.59	19.75	19.68		0
16QAM	1	0	19.01	19.56	19.27	0-1	0
	1	25	19.81	19.98	19.55		0
	1	49	19.03	19.13	19.24		0
	25	0	19.44	19.49	19.51	0-2	0
	25	12	19.49	19.56	19.52		0
	25	25	19.32	19.42	19.37		0
	50	0	19.35	19.45	19.62		0

Table 9-14
Reduced LTE Band 7 Conducted Powers - 5 MHz Bandwidth- Hotspot Mode Active

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.40	19.76	19.65	0	0
	1	12	19.84	19.95	19.94		0
	1	24	19.74	19.72	19.44		0
	12	0	19.62	19.89	19.87	0-1	0
	12	6	19.75	19.83	19.65		0
	12	13	19.61	19.68	19.55		0
	25	0	19.57	19.73	19.64		0
16QAM	1	0	19.03	19.54	19.23	0-1	0
	1	12	19.79	19.97	19.51		0
	1	24	19.04	19.11	19.14		0
	12	0	19.42	19.47	19.47	0-2	0
	12	6	19.47	19.54	19.48		0
	12	13	19.30	19.40	19.33		0
	25	0	19.30	19.45	19.58		0

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 30 of 57

9.3.3

LTE Band 38

Table 9-15
LTE Band 38 Conducted Powers - 20 MHz Bandwidth

LTE Band 38 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			38000 (2595.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.29	0	0
	1	50	22.75		0
	1	99	22.05		0
	50	0	21.03	0-1	1
	50	25	21.13		1
	50	50	21.05		1
	100	0	21.06		1
16QAM	1	0	20.98	0-1	1
	1	50	21.11		1
	1	99	20.95		1
	50	0	20.04	0-2	2
	50	25	20.23		2
	50	50	20.03		2
	100	0	20.07		2

Note: LTE Band 38 at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-16
LTE Band 38 Conducted Powers - 15 MHz Bandwidth

LTE Band 38 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			37825 (2577.5 MHz)	38000 (2595.0 MHz)	38175 (2612.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.60	22.45	22.30	0	0
	1	36	22.52	22.50	22.22		0
	1	74	22.54	22.36	22.02		0
	36	0	21.02	21.32	20.87	0-1	1
	36	18	20.96	21.22	20.75		1
	36	37	21.03	21.11	20.71		1
	75	0	20.97	21.04	20.96		1
16QAM	1	0	20.96	21.11	20.62	0-1	1
	1	36	20.77	21.00	20.51		1
	1	74	20.82	20.92	20.59		1
	36	0	19.85	20.15	19.83	0-2	2
	36	18	19.84	20.11	19.68		2
	36	37	19.82	20.10	19.51		2
	75	0	19.83	20.05	19.62		2

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 31 of 57

Table 9-17
LTE Band 38 Conducted Powers - 10 MHz Bandwidth

LTE Band 38 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			37800 (2575.0 MHz)	38000 (2595.0 MHz)	38200 (2615.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.51	22.60	22.43	0	0
	1	25	22.56	22.66	22.32		0
	1	49	22.58	22.61	22.28		0
	25	0	20.85	20.84	20.82	0-1	1
	25	12	20.82	20.95	20.67		1
	25	25	21.02	21.09	20.69		1
	50	0	20.79	20.82	20.67		1
16QAM	1	0	20.85	20.88	20.78	0-1	1
	1	25	20.69	21.11	20.73		1
	1	49	20.83	20.92	20.58		1
	25	0	19.78	19.88	19.65	0-2	2
	25	12	19.72	19.78	19.58		2
	25	25	19.77	19.86	19.61		2
	50	0	19.81	19.81	19.55		2

Table 9-18
LTE Band 38 Conducted Powers - 5 MHz Bandwidth

LTE Band 38 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			37775 (2572.5 MHz)	38000 (2595.0 MHz)	38225 (2617.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.58	22.40	22.15	0	0
	1	12	22.58	22.57	22.22		0
	1	24	22.56	22.62	22.04		0
	12	0	20.93	21.04	20.63	0-1	1
	12	6	20.89	21.11	20.56		1
	12	13	20.87	21.05	20.58		1
	25	0	20.89	21.08	20.64		1
16QAM	1	0	21.11	21.04	20.96	0-1	1
	1	12	21.23	21.34	21.08		1
	1	24	21.15	21.03	20.87		1
	12	0	19.85	20.22	19.47	0-2	2
	12	6	19.81	20.25	19.74		2
	12	13	19.79	20.05	19.69		2
	25	0	19.82	20.10	19.50		2

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 32 of 57

9.4 WLAN Conducted Powers

Table 9-19
2.4 GHz WLAN Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	16.30	13.76	11.80
2437	6	16.97	14.45	12.47
2462	11	16.24	13.58	11.63

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.




Figure 9-3
Power Measurement Setup for Bandwidths < 50 MHz

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 33 of 57

9.5 Bluetooth Conducted Powers

Table 9-20
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	10.49	11.200
2441	1.0	39	10.66	11.631
2480	1.0	78	9.69	9.306
2402	2.0	0	8.88	7.727
2441	2.0	39	9.08	8.090
2480	2.0	78	8.21	6.624
2402	3.0	0	8.94	7.840
2441	3.0	39	9.15	8.215
2480	3.0	78	8.24	6.665

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 34 of 57

Figure 9-4
Bluetooth Transmission Plot



Equation 9-1
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{PulseWidth}{Period} * 100\% = \frac{2.927ms}{3.767ms} * 100\% = 77.7\%$$




Figure 9-5
Power Measurement Setup

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 35 of 57

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
10/1/2017	835H	20.3	820	0.886	42.040	0.899	41.578	-1.45%	1.11%
			835	0.901	41.876	0.900	41.500	0.11%	0.91%
			850	0.916	41.696	0.916	41.500	0.00%	0.47%
10/9/2017	835H	21.0	820	0.895	41.928	0.899	41.578	-0.44%	0.84%
			835	0.910	41.742	0.900	41.500	1.11%	0.58%
			850	0.925	41.540	0.916	41.500	0.98%	0.10%
9/28/2017	2450-2600H	21.5	2450	1.794	38.482	1.800	39.200	-0.33%	-1.83%
			2500	1.851	38.304	1.855	39.136	-0.22%	-2.13%
			2550	1.906	38.107	1.909	39.073	-0.16%	-2.47%
			2600	1.960	37.943	1.964	39.009	-0.20%	-2.73%
10/10/2017	2450H	22.9	2400	1.792	38.322	1.756	39.289	2.05%	-2.46%
			2450	1.849	38.156	1.800	39.200	2.72%	-2.66%
			2500	1.904	37.949	1.855	39.136	2.64%	-3.03%
10/17/2017	2450H	21.2	2400	1.828	38.782	1.756	39.289	4.10%	-1.29%
			2450	1.880	38.615	1.800	39.200	4.44%	-1.49%
			2500	1.938	38.406	1.855	39.136	4.47%	-1.87%
10/26/2017	2450H	22.9	2400	1.803	39.669	1.756	39.289	2.68%	0.97%
			2450	1.855	39.496	1.800	39.200	3.06%	0.76%
			2500	1.916	39.283	1.855	39.136	3.29%	0.38%
10/2/2017	835B	20.7	820	0.970	54.106	0.969	55.258	0.10%	-2.08%
			835	0.986	53.975	0.970	55.200	1.65%	-2.22%
			850	1.001	53.831	0.988	55.154	1.32%	-2.40%
10/9/2017	835B	21.2	820	0.983	53.333	0.969	55.258	1.44%	-3.48%
			835	0.999	53.175	0.970	55.200	2.99%	-3.67%
			850	1.013	53.016	0.988	55.154	2.53%	-3.88%
10/11/2017	835B	21.2	820	0.985	52.952	0.969	55.258	1.65%	-4.17%
			835	0.999	52.814	0.970	55.200	2.99%	-4.32%
			850	1.013	52.652	0.988	55.154	2.53%	-4.54%
9/28/2017	2450-2600B	23.5	2400	1.939	52.111	1.902	52.767	1.95%	-1.24%
			2450	2.004	51.938	1.950	52.700	2.77%	-1.45%
			2500	2.072	51.719	2.021	52.636	2.52%	-1.74%
			2550	2.138	51.555	2.092	52.573	2.20%	-1.94%
10/25/2017	2450B	21.6	2600	2.208	51.342	2.163	52.509	2.08%	-2.22%
			2400	1.952	52.222	1.902	52.767	2.63%	-1.03%
			2450	2.020	52.049	1.950	52.700	3.59%	-1.24%
			2500	2.094	51.857	2.021	52.636	3.61%	-1.48%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 36 of 57

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-2
System Verification Results

System Verification												
TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
I	835	HEAD	10/01/2017	20.7	20.3	0.200	4d133	3213	1.820	9.520	9.100	-4.41%
I	835	HEAD	10/09/2017	21.5	21.2	0.200	4d047	3213	1.870	9.130	9.350	2.41%
E	2450	HEAD	09/28/2017	21.8	21.5	0.100	981	3319	5.300	52.800	53.000	0.38%
I	2450	HEAD	10/10/2017	23.5	21.4	0.100	719	3213	5.470	51.900	54.700	5.39%
G	2450	HEAD	10/17/2017	22.6	21.6	0.100	719	3332	5.450	51.900	54.500	5.01%
G	2450	HEAD	10/20/2017	22.0	20.9	0.100	981	3332	5.260	52.800	52.600	-0.38%
E	2600	HEAD	09/28/2017	21.8	21.5	0.100	1126	3319	5.550	56.400	55.500	-1.60%
E	835	BODY	10/02/2017	21.0	20.8	0.200	4d132	3319	2.080	9.800	10.400	6.12%
H	835	BODY	10/09/2017	21.5	21.2	0.200	4d132	7410	2.030	9.800	10.150	3.57%
G	835	BODY	10/11/2017	21.1	21.2	0.200	4d133	3332	1.960	9.410	9.800	4.14%
K	2450	BODY	09/28/2017	22.7	22.1	0.100	719	7406	5.200	50.100	52.000	3.79%
E	2450	BODY	10/25/2017	23.7	21.6	0.100	719	3319	5.100	50.100	51.000	1.80%
K	2600	BODY	09/28/2017	22.7	22.1	0.100	1126	7406	5.500	54.300	55.000	1.29%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 37 of 57

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.3	32.03	-0.05	Right	Cheek	48632	1:8.3	0.232	1.340	0.311	
836.60	190	GSM 850	GSM	33.3	32.03	0.00	Right	Tilt	48632	1:8.3	0.148	1.340	0.198	
836.60	190	GSM 850	GSM	33.3	32.03	-0.02	Left	Cheek	48632	1:8.3	0.236	1.340	0.316	A1
836.60	190	GSM 850	GSM	33.3	32.03	0.06	Left	Tilt	48632	1:8.3	0.156	1.340	0.209	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-2
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.0	22.52	0.04	Right	Cheek	48632	1:1	0.240	1.117	0.268	A2
836.60	4183	UMTS 850	RMC	23.0	22.52	0.01	Right	Tilt	48632	1:1	0.144	1.117	0.161	
836.60	4183	UMTS 850	RMC	23.0	22.52	0.05	Left	Cheek	48632	1:1	0.223	1.117	0.249	
836.60	4183	UMTS 850	RMC	23.0	22.52	0.01	Left	Tilt	48632	1:1	0.143	1.117	0.160	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 38 of 57

Table 11-3
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	0.10	0	Right	Cheek	QPSK	1	0	49176	1:1	0.244	1.086	0.265	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	0.03	1	Right	Cheek	QPSK	25	25	49176	1:1	0.183	1.384	0.253	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	0.01	0	Right	Tilt	QPSK	1	0	49176	1:1	0.156	1.086	0.169	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	0.02	1	Right	Tilt	QPSK	25	25	49176	1:1	0.099	1.384	0.137	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	0.09	0	Left	Cheek	QPSK	1	0	49176	1:1	0.247	1.086	0.268	A3
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	0.04	1	Left	Cheek	QPSK	25	25	49176	1:1	0.154	1.384	0.213	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	0.01	0	Left	Tilt	QPSK	1	0	49176	1:1	0.178	1.086	0.193	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	0.01	1	Left	Tilt	QPSK	25	25	49176	1:1	0.104	1.384	0.144	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-4
LTE Band 7 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																(W/kg)		(W/kg)	
2535.00	21100	Mid	LTE Band 7	20	22.5	22.18	-0.09	0	Right	Cheek	QPSK	1	50	48772	1:1	0.390	1.076	0.420	
2535.00	21100	Mid	LTE Band 7	20	21.5	20.94	0.05	1	Right	Cheek	QPSK	50	25	48772	1:1	0.305	1.138	0.347	
2535.00	21100	Mid	LTE Band 7	20	22.5	22.18	0.13	0	Right	Tilt	QPSK	1	50	48772	1:1	0.424	1.076	0.456	
2535.00	21100	Mid	LTE Band 7	20	21.5	20.94	0.08	1	Right	Tilt	QPSK	50	25	48772	1:1	0.312	1.138	0.355	
2510.00	20850	Low	LTE Band 7	20	22.5	22.00	0.15	0	Left	Cheek	QPSK	1	99	48772	1:1	0.909	1.122	1.020	
2535.00	21100	Mid	LTE Band 7	20	22.5	22.18	-0.02	0	Left	Cheek	QPSK	1	50	48772	1:1	0.989	1.076	1.064	A4
2560.00	21350	High	LTE Band 7	20	22.5	22.13	0.15	0	Left	Cheek	QPSK	1	50	48772	1:1	0.795	1.089	0.866	
2510.00	20850	Low	LTE Band 7	20	21.5	20.75	0.03	1	Left	Cheek	QPSK	50	50	48772	1:1	0.713	1.189	0.848	
2535.00	21100	Mid	LTE Band 7	20	21.5	20.94	0.07	1	Left	Cheek	QPSK	50	25	48772	1:1	0.706	1.138	0.803	
2560.00	21350	High	LTE Band 7	20	21.5	20.79	0.14	1	Left	Cheek	QPSK	50	0	48772	1:1	0.634	1.178	0.747	
2535.00	21100	Mid	LTE Band 7	20	21.5	20.86	0.10	1	Left	Cheek	QPSK	100	0	48772	1:1	0.695	1.159	0.806	
2535.00	21100	Mid	LTE Band 7	20	22.5	22.18	-0.10	0	Left	Tilt	QPSK	1	50	48772	1:1	0.320	1.076	0.344	
2535.00	21100	Mid	LTE Band 7	20	21.5	20.94	0.07	1	Left	Tilt	QPSK	50	25	48772	1:1	0.225	1.138	0.256	
2535.00	21100	Mid	LTE Band 7	20	22.5	22.18	0.09	0	Left	Cheek	QPSK	1	50	48772	1:1	0.986	1.076	1.061	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability data

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 39 of 57

Table 11-5
LTE Band 38 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	0.12	0	Right	Cheek	QPSK	1	50	48772	1:1.58	0.234	1.059	0.248	
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	0.06	1	Right	Cheek	QPSK	50	25	48772	1:1.58	0.167	1.222	0.204	
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	0.05	0	Right	Tilt	QPSK	1	50	48772	1:1.58	0.251	1.059	0.266	
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	0.04	1	Right	Tilt	QPSK	50	25	48772	1:1.58	0.179	1.222	0.219	
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	0.13	0	Left	Cheek	QPSK	1	50	48772	1:1.58	0.537	1.059	0.569	A5
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	0.11	1	Left	Cheek	QPSK	50	25	48772	1:1.58	0.377	1.222	0.461	
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	0.17	0	Left	Tilt	QPSK	1	50	48772	1:1.58	0.179	1.059	0.190	
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	0.11	1	Left	Tilt	QPSK	50	25	48772	1:1.58	0.123	1.222	0.150	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-6
DTS Head SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	17.0	16.97	-0.10	Right	Cheek	49135	1	98.9	0.446	-	1.007	1.011	-	
2437	6	802.11b	DSSS	22	17.0	16.97	-0.13	Right	Tilt	49135	1	98.9	0.427	-	1.007	1.011	-	
2412	1	802.11b	DSSS	22	17.0	16.30	0.00	Left	Cheek	49135	1	98.9	0.845	0.687	1.175	1.011	0.816	
2437	6	802.11b	DSSS	22	17.0	16.97	-0.06	Left	Cheek	49135	1	98.9	1.357	1.030	1.007	1.011	1.049	A6
2462	11	802.11b	DSSS	22	17.0	16.24	-0.03	Left	Cheek	49135	1	98.9	0.844	0.754	1.191	1.011	0.908	
2437	6	802.11b	DSSS	22	17.0	16.97	-0.17	Left	Tilt	49135	1	98.9	0.486	0.396	1.007	1.011	0.403	
2437	6	802.11b	DSSS	22	17.0	16.97	-0.12	Left	Cheek	49135	1	98.9	1.236	1.000	1.007	1.011	1.018	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability data

Table 11-7
DSS Head SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle %	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441.00	39	Bluetooth	FHSS	9.5	9.08	0.05	Right	Cheek	49135	2	77.7	0.096	1.102	1.287	0.136	
2441.00	39	Bluetooth	FHSS	9.5	9.08	0.07	Right	Tilt	49135	2	77.7	0.094	1.102	1.287	0.133	
2441.00	39	Bluetooth	FHSS	9.5	9.08	0.00	Left	Cheek	49135	2	77.7	0.156	1.102	1.287	0.221	A7
2441.00	39	Bluetooth	FHSS	9.5	9.08	0.04	Left	Tilt	49135	2	77.7	0.111	1.102	1.287	0.157	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 40 of 57

11.2 Standalone Body-Worn SAR Data

Table 11-8
GSM/UMTS Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.3	32.03	-0.02	15 mm	48772	1	1:8.3	back	0.436	1.340	0.584	A8
836.60	4183	UMTS 850	RMC	23.0	22.52	-0.02	15 mm	48772	N/A	1:1	back	0.321	1.117	0.359	A10
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-9
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	-0.01	0	48632	QPSK	1	0	15 mm	back	1:1	0.332	1.086	0.361	A12
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	0.02	1	48632	QPSK	25	25	15 mm	back	1:1	0.231	1.384	0.320	
2535.00	21100	Mid	LTE Band 7	20	22.5	22.18	0.02	0	49176	QPSK	1	50	15 mm	back	1:1	0.487	1.076	0.524	A14
2535.00	21100	Mid	LTE Band 7	20	21.5	20.94	0.05	1	49176	QPSK	50	25	15 mm	back	1:1	0.371	1.138	0.422	
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	0.00	0	49176	QPSK	1	50	15 mm	back	1:1.58	0.260	1.059	0.275	A16
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	-0.08	1	49176	QPSK	50	25	15 mm	back	1:1.58	0.184	1.222	0.225	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-10
DTS Body-Worn SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	17.0	16.97	0.02	15 mm	49176	1	back	98.9	0.115	0.097	1.007	1.011	0.099	A18
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 41 of 57

11.3 Standalone Hotspot SAR Data

Table 11-11
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
824.20	128	GSM 850	GPRS	33.3	31.88	0.06	10 mm	48772	1	1:8.3	back	0.475	1.387	0.659	A9
836.60	190	GSM 850	GPRS	33.3	31.86	0.02	10 mm	48772	1	1:8.3	back	0.493	1.393	0.687	
848.80	251	GSM 850	GPRS	33.3	32.00	-0.02	10 mm	48772	1	1:8.3	back	0.457	1.349	0.616	
836.60	190	GSM 850	GPRS	33.3	31.86	-0.04	10 mm	48772	1	1:8.3	front	0.281	1.393	0.391	
836.60	190	GSM 850	GPRS	33.3	31.86	-0.16	10 mm	48772	1	1:8.3	bottom	0.035	1.393	0.049	
836.60	190	GSM 850	GPRS	33.3	31.86	-0.02	10 mm	48772	1	1:8.3	right	0.304	1.393	0.423	
836.60	190	GSM 850	GPRS	33.3	31.86	-0.04	10 mm	48772	1	1:8.3	left	0.216	1.393	0.301	A11
836.60	4183	UMTS 850	RMC	23.0	22.52	-0.03	10 mm	48772	N/A	1:1	back	0.383	1.117	0.428	
836.60	4183	UMTS 850	RMC	23.0	22.52	0.11	10 mm	48772	N/A	1:1	front	0.258	1.117	0.288	
836.60	4183	UMTS 850	RMC	23.0	22.52	0.04	10 mm	48772	N/A	1:1	bottom	0.030	1.117	0.034	
836.60	4183	UMTS 850	RMC	23.0	22.52	-0.01	10 mm	48772	N/A	1:1	right	0.291	1.117	0.325	
836.60	4183	UMTS 850	RMC	23.0	22.52	-0.02	10 mm	48772	N/A	1:1	left	0.221	1.117	0.247	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-12
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	-0.02	0	48632	QPSK	1	0	10 mm	back	1:1	0.396	1.086	0.430	A13
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	0.00	1	48632	QPSK	25	25	10 mm	back	1:1	0.298	1.384	0.412	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	-0.01	0	48632	QPSK	1	0	10 mm	front	1:1	0.260	1.086	0.282	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	0.01	1	48632	QPSK	25	25	10 mm	front	1:1	0.188	1.384	0.260	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	0.05	0	48632	QPSK	1	0	10 mm	bottom	1:1	0.036	1.086	0.039	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	-0.05	1	48632	QPSK	25	25	10 mm	bottom	1:1	0.028	1.384	0.039	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	0.00	0	48632	QPSK	1	0	10 mm	right	1:1	0.343	1.086	0.372	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	-0.01	1	48632	QPSK	25	25	10 mm	right	1:1	0.196	1.384	0.271	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.14	0.04	0	48632	QPSK	1	0	10 mm	left	1:1	0.166	1.086	0.180	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.09	0.06	1	48632	QPSK	25	25	10 mm	left	1:1	0.105	1.384	0.145	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 42 of 57

Table 11-13
LTE Band 7 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2560.00	21350	High	LTE Band 7	20	20.5	20.00	0.04	0	48780	QPSK	1	50	10 mm	back	1:1	0.631	1.122	0.708	
2510.00	20850	Low	LTE Band 7	20	20.5	19.81	-0.09	0	48780	QPSK	50	25	10 mm	back	1:1	0.637	1.172	0.747	
2535.00	21100	Mid	LTE Band 7	20	20.5	19.93	-0.09	0	48780	QPSK	50	0	10 mm	back	1:1	0.682	1.140	0.777	A15
2560.00	21350	High	LTE Band 7	20	20.5	19.94	0.03	0	48780	QPSK	50	0	10 mm	back	1:1	0.651	1.138	0.741	
2560.00	21350	High	LTE Band 7	20	20.5	20.00	-0.19	0	48780	QPSK	1	50	10 mm	front	1:1	0.525	1.122	0.589	
2560.00	21350	High	LTE Band 7	20	20.5	19.94	-0.02	0	48780	QPSK	50	0	10 mm	front	1:1	0.547	1.138	0.622	
2560.00	21350	High	LTE Band 7	20	20.5	20.00	-0.15	0	48780	QPSK	1	50	10 mm	bottom	1:1	0.382	1.122	0.429	
2560.00	21350	High	LTE Band 7	20	20.5	19.94	-0.04	0	48780	QPSK	50	0	10 mm	bottom	1:1	0.408	1.138	0.464	
2560.00	21350	High	LTE Band 7	20	20.5	20.00	0.03	0	48780	QPSK	1	50	10 mm	right	1:1	0.069	1.122	0.077	
2560.00	21350	High	LTE Band 7	20	20.5	19.94	0.13	0	48780	QPSK	50	0	10 mm	right	1:1	0.072	1.138	0.082	
2560.00	21350	High	LTE Band 7	20	20.5	20.00	0.08	0	48780	QPSK	1	50	10 mm	left	1:1	0.335	1.122	0.376	
2560.00	21350	High	LTE Band 7	20	20.5	19.94	0.00	0	48780	QPSK	50	0	10 mm	left	1:1	0.350	1.138	0.398	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak								Body											
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g)											
								averaged over 1 gram											

Table 11-14
LTE Band 38 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (lg)	Scaling Factor	Reported SAR (lg)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	-0.08	0	49176	QPSK	1	50	10 mm	back	1:1.58	0.543	1.059	0.575	A17
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	0.06	1	49176	QPSK	50	25	10 mm	back	1:1.58	0.380	1.222	0.464	
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	0.15	0	49176	QPSK	1	50	10 mm	front	1:1.58	0.496	1.059	0.525	
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	0.15	1	49176	QPSK	50	25	10 mm	front	1:1.58	0.362	1.222	0.442	
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	0.17	0	49176	QPSK	1	50	10 mm	bottom	1:1.58	0.278	1.059	0.294	
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	-0.12	1	49176	QPSK	50	25	10 mm	bottom	1:1.58	0.197	1.222	0.241	
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	0.05	0	49176	QPSK	1	50	10 mm	right	1:1.58	0.037	1.059	0.039	
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	0.11	1	49176	QPSK	50	25	10 mm	right	1:1.58	0.029	1.222	0.035	
2595.00	38000	Mid	LTE Band 38	20	23.0	22.75	-0.13	0	49176	QPSK	1	50	10 mm	left	1:1.58	0.352	1.059	0.373	
2595.00	38000	Mid	LTE Band 38	20	22.0	21.13	0.01	1	49176	QPSK	50	25	10 mm	left	1:1.58	0.253	1.222	0.309	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 43 of 57

Table 11-15
WLAN Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	17.0	16.97	-0.13	10 mm	49176	1	back	98.9	0.262	0.245	1.007	1.011	0.249	A19
2437	6	802.11b	DSSS	22	17.0	16.97	0.16	10 mm	49176	1	front	98.9	0.191	-	1.007	1.011	-	
2437	6	802.11b	DSSS	22	17.0	16.97	0.06	10 mm	49176	1	top	98.9	0.222	-	1.007	1.011	-	
2437	6	802.11b	DSSS	22	17.0	16.97	0.10	10 mm	49176	1	right	98.9	0.123	-	1.007	1.011	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body									
Spatial Peak									1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population									averaged over 1 gram									

11.4 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
- During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

GSM Test Notes:

- Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
- Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
- Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 44 of 57

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.3 for more information. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
3. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9.5 for the time domain plot and calculation for the duty factor of the device.
2. Head Bluetooth SAR was evaluated for BT EDR tethering applications.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 45 of 57

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance	Estimated SAR
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth BDR - Bodyworn	2480	11.00	15	0.182
Bluetooth EDR - Hotspot	2480	9.5	10	0.189

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 46 of 57

12.3 Head SAR Simultaneous Transmission Analysis

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB Publication 248227, the worst case WLAN head SAR result was used for simultaneous transmission analysis.

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	
		1	2	1+2	
Head SAR	GSM 850	0.316	1.049	1.365	
	UMTS 850	0.268	1.049	1.317	
	LTE Band 5 (Cell)	0.268	1.049	1.317	
	LTE Band 7	1.064	1.049	See Table Below	
	LTE Band 38	0.569	1.049	See Table Below	

Simult Tx	Configuration	LTE Band 7 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Head SAR	Right Cheek	0.420	1.049*	1.469	N/A
	Right Tilt	0.456	1.049*	1.505	N/A
	Left Cheek	1.064	1.049	See Note 1	0.04
	Left Tilt	0.344	0.403	0.747	N/A

Simult Tx	Configuration	LTE Band 38 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Head SAR	Right Cheek	0.248	1.049*	1.297	N/A
	Right Tilt	0.266	1.049*	1.315	N/A
	Left Cheek	0.569	1.049	See Note 1	0.04
	Left Tilt	0.190	0.403	0.593	N/A

Table 12-3
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM 850	0.316	0.221	0.537
	UMTS 850	0.268	0.221	0.489
	LTE Band 5 (Cell)	0.268	0.221	0.489
	LTE Band 7	1.064	0.221	1.285
	LTE Band 38	0.569	0.221	0.790

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 47 of 57

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 850	0.584	0.099	0.683
	UMTS 850	0.359	0.099	0.458
	LTE Band 5 (Cell)	0.361	0.099	0.460
	LTE Band 7	0.524	0.099	0.623
	LTE Band 38	0.275	0.099	0.374

Table 12-5
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 850	0.584	0.182	0.766
	UMTS 850	0.359	0.182	0.541
	LTE Band 5 (Cell)	0.361	0.182	0.543
	LTE Band 7	0.524	0.182	0.706
	LTE Band 38	0.275	0.182	0.457

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 48 of 57	

12.5 Hotspot SAR Simultaneous Transmission Analysis

Table 12-6
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.687	0.249	0.936
	UMTS 850	0.428	0.249	0.677
	LTE Band 5 (Cell)	0.430	0.249	0.679
	LTE Band 7	0.777	0.249	1.026
	LTE Band 38	0.575	0.249	0.824

Table 12-7
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.687	0.189	0.876
	UMTS 850	0.428	0.189	0.617
	LTE Band 5 (Cell)	0.430	0.189	0.619
	LTE Band 7	0.777	0.189	0.966
	LTE Band 38	0.575	0.189	0.764

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.6 for detailed SPLS ratio analysis.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 49 of 57

12.6 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 for 1g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

12.6.1 Head SPLSR Evaluation and Analysis

Table 12-4
Peak SAR Locations for Left Cheek



Mode/Band	x (mm)	y (mm)	z (mm)	Reported SAR (W/kg)
2.4 GHz WLAN	22.63	330.81	-172.63	1.049
LTE Band 7	45.30	248.13	-171.29	1.064
LTE Band 38	43.97	251.85	-171.95	0.569

Table 12-5
Left Cheek SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}	
LTE Band 7	2.4 GHz WLAN	1.064	1.049	2.113	85.74	0.04	1
LTE Band 38	2.4 GHz WLAN	0.569	1.049	1.618	81.80	0.03	2

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 50 of 57

Table 12-6
Left Cheek SAR to Peak Location Separation Ratio Plots



12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 51 of 57

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Head SAR Measurement Variability Results

HEAD VARIABILITY RESULTS														
Band	FREQUENCY		Mode/Band	Service	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)
	MHz	Ch.							(W/kg)	(W/kg)		(W/kg)		(W/kg)
2600	2535.00	21100	LTE Band 7, 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	Left	Cheek	48772	N/A	0.989	0.986	1.00	N/A	N/A	N/A
2450	2437.00	6	802.11b, 22 MHz Bandwidth	DSSS	Left	Cheek	49135	1	1.030	1.000	1.03	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Head 1.6 W/kg (mW/g) averaged over 1 gram									

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 52 of 57

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E8257D	(250kHz–20GHz) Signal Generator	3/22/2017	Annual	3/22/2018	MY45470194
Agilent	8594A	(9kHz–2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	E4438C	ESG Vector Signal Generator	3/23/2017	Annual	3/23/2018	MY47270002
Agilent	E4432B	ESG–D Series Signal Generator	3/24/2017	Annual	3/24/2018	US40053896
Agilent	N9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561
Agilent	N5182A	MXG Vector Signal Generator	2/28/2017	Annual	2/28/2018	MY47420800
Agilent	8753ES	S–Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	8753ES	S–Parameter Vector Network Analyzer	8/17/2017	Annual	8/17/2018	MY40003841
Agilent	E5515C	Wireless Communications Test Set	1/8/2015	Triennial	1/8/2018	GB43163447
Agilent	N4010A	Wireless Connectivity Test Set	CBT	N/A	CBT	GB46170464
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433974
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433975
Anritsu	ML2496A	Power Meter	3/28/2017	Annual	3/28/2018	1351001
Anritsu	MA2411B	Pulse Power Sensor	2/10/2017	Annual	2/10/2018	1207364
Anritsu	MA2411B	Pulse Power Sensor	2/10/2017	Annual	2/10/2018	1339018
Anritsu	MT8821C	Radio Communication Analyzer	7/25/2017	Annual	7/25/2018	6201664756
Anritsu	MA24106A	USB Power Sensor	10/27/2016	Annual	10/27/2017	1344545
Anritsu	MA24106A	USB Power Sensor	10/27/2016	Annual	10/27/2017	1344559
COMTECH	AR85729–5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00–1002
Control Company	4040	Therm./Clock/Humidity Monitor	3/31/2017	Biennial	3/31/2019	170232394
Control Company	4352	Ultra Long Stem Thermometer	5/2/2017	Biennial	5/2/2019	170330156
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/1/2017	Annual	6/1/2018	MY53401181
MiniCircuits	SLP–2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini–Circuits	BW–N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini–Circuits	NLP–1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini–Circuits	NLP–2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini–Circuits	BW–N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mitutoyo	CD–6”CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264165
Narda	4772–3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW–S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	PE2209–10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011–1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	4/11/2017	Annual	4/11/2018	836371/0079
Rohde & Schwarz	CMW500	Radio Communication Tester	10/20/2016	Annual	10/20/2017	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	3/29/2017	Annual	3/29/2018	128633
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/10/2017	Annual	2/10/2018	162125
Seekonk	NC–100	Torque Wrench	11/6/2015	Biennial	11/6/2017	N/A
Seekonk	NC–100	Torque Wrench (8” lb)	8/30/2016	Biennial	8/30/2018	N/A
Seekonk	NC–100	Torque Wrench (8” lb)	9/1/2016	Biennial	9/1/2018	21053
Seekonk	NC–100	Torque Wrench 5/16”, 8” lbs	3/2/2016	Biennial	3/2/2018	N/A
SPEAG	D2450V2	2450 MHz SAR Dipole	7/25/2016	Biennial	7/25/2018	981
SPEAG	D2450V2	2450 MHz SAR Dipole	8/17/2017	Annual	8/17/2018	719
SPEAG	D2600V2	2600 MHz SAR Dipole	7/10/2017	Annual	7/10/2018	1126
SPEAG	D835V2	835 MHz SAR Dipole	7/11/2017	Annual	7/11/2018	4d133
SPEAG	D835V2	835 MHz SAR Dipole	7/13/2016	Biennial	7/13/2018	4d047
SPEAG	D835V2	835 MHz SAR Dipole	1/11/2017	Annual	1/11/2018	4d132
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2017	Annual	2/9/2018	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/8/2017	Annual	3/8/2018	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/9/2017	Annual	8/9/2018	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/13/2017	Annual	7/13/2018	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2017	Annual	4/11/2018	1407
SPEAG	DAK–3.5	Dielectric Assessment Kit	5/10/2017	Annual	5/10/2018	1070
SPEAG	DAKS–3.5	Portable Dielectric Assessment Kit	8/8/2017	Annual	8/8/2018	1041
SPEAG	ES3DV3	SAR Probe	2/10/2017	Annual	2/10/2018	3213
SPEAG	ES3DV3	SAR Probe	3/14/2017	Annual	3/14/2018	3319
SPEAG	ES3DV3	SAR Probe	8/14/2017	Annual	8/14/2018	3332
SPEAG	EX3DV4	SAR Probe	7/17/2017	Annual	7/17/2018	7410
SPEAG	EX3DV4	SAR Probe	4/18/2017	Annual	4/18/2018	7406

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 53 of 57

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 54 of 57

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMJ250F	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 55 of 57

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMJ250F	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset	Page 56 of 57

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMJ250F		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1709270258-01.A3L	Test Dates: 09/28/17 - 10/26/17	DUT Type: Portable Handset		Page 57 of 57

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48632

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 41.857$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 10-01-2017; Ambient Temp: 20.7°C; Tissue Temp: 20.3°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 850, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.85 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.288 W/kg

SAR(1 g) = 0.236 W/kg



0 dB = 0.256 W/kg = -5.92 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48632

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 41.857$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 10-01-2017; Ambient Temp: 20.7°C; Tissue Temp: 20.3°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.90 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.300 W/kg

SAR(1 g) = 0.240 W/kg



0 dB = 0.263 W/kg = -5.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 49176

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.911 \text{ S/m}$; $\epsilon_r = 41.722$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 10-09-2017; Ambient Temp: 21.5°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Left Head, Cheek,
Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.71 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.301 W/kg

SAR(1 g) = 0.247 W/kg



0 dB = 0.268 W/kg = -5.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48772

Communication System: UID 0, LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: 2450-2600 Head Medium parameters used (interpolated):

$f = 2535 \text{ MHz}$; $\sigma = 1.89 \text{ S/m}$; $\epsilon_r = 38.166$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 9-28-2017; Ambient Temp: 21.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3319; ConvF(4.41, 4.41, 4.41); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Left Head, Cheek,
Mid.ch, QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.283 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.75 W/kg

SAR(1 g) = 0.989 W/kg



0 dB = 1.21 W/kg = 0.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48772

Communication System: UID 0, _LTE Band 38; Frequency: 2595 MHz; Duty Cycle: 1:1.58

Medium: 2450-2600 Head Medium parameters used (interpolated):

$f = 2595 \text{ MHz}$; $\sigma = 1.955 \text{ S/m}$; $\epsilon_r = 37.959$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 9-28-2017; Ambient Temp: 21.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3319; ConvF(4.41, 4.41, 4.41); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 38, Left Head, Cheek,
Mid.ch, QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset**


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.94 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.980 W/kg

SAR(1 g) = 0.537 W/kg



0 dB = 0.666 W/kg = -1.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 49135

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 MHz Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.866 \text{ S/m}$; $\epsilon_r = 38.658$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 10-17-2017; Ambient Temp: 22.6°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Left Head, Cheek, Ch 6, 1 Mbps


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (13x9x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.25 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 2.21 W/kg

SAR(1 g) = 1.03 W/kg



0 dB = 1.32 W/kg = 1.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 49135

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.287

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.839 \text{ S/m}$; $\epsilon_r = 38.186$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 10-10-2017; Ambient Temp: 23.5°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3213; ConvF(4.7, 4.7, 4.7); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Left Head, Cheek, Ch 39, 2 Mbps


Area Scan (11x19x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.904 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.352 W/kg

SAR(1 g) = 0.156 W/kg



0 dB = 0.204 W/kg = -6.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48772

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.988 \text{ S/m}$; $\epsilon_r = 53.96$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-02-2017; Ambient Temp: 21.0°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.70 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.553 W/kg

SAR(1 g) = 0.436 W/kg



0 dB = 0.477 W/kg = -3.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48772


Communication System: UID 0, GSM GPRS; 1 Tx slot;
Frequency: 836.6 MHz; Duty Cycle: 1:8.3
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.988 \text{ S/m}$; $\epsilon_r = 53.96$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-02-2017; Ambient Temp: 21.0°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1368; Calibrated: 3/8/2017
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 1 Tx Slots

Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 22.99 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.617 W/kg
SAR(1 g) = 0.493 W/kg



0 dB = 0.537 W/kg = -2.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48772

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1 \text{ S/m}$; $\epsilon_r = 52.797$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-11-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(6.47, 6.47, 6.47); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.59 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.398 W/kg

SAR(1 g) = 0.321 W/kg



0 dB = 0.351 W/kg = -4.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48772

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.988 \text{ S/m}$; $\epsilon_r = 53.96$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-02-2017; Ambient Temp: 21.0°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.30 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.482 W/kg

SAR(1 g) = 0.383 W/kg



0 dB = 0.418 W/kg = -3.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48632

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1 \text{ S/m}$; $\epsilon_r = 53.159$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-09-2017; Ambient Temp: 21.5°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7410; ConvF(9.95, 9.95, 9.95); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side,
Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.63 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.423 W/kg

SAR(1 g) = 0.332 W/kg



0 dB = 0.393 W/kg = -4.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48632

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1 \text{ S/m}$; $\epsilon_r = 53.159$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-09-2017; Ambient Temp: 21.5°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7410; ConvF(9.95, 9.95, 9.95); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side,
Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.35 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.501 W/kg

SAR(1 g) = 0.396 W/kg



0 dB = 0.468 W/kg = -3.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 49176

Communication System: UID 0, LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: 2450-2600 Body Medium parameters used (interpolated):

$f = 2535 \text{ MHz}$; $\sigma = 2.118 \text{ S/m}$; $\epsilon_r = 51.604$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 09-28-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Body SAR, Back side,
Mid.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.80 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.961 W/kg

SAR(1 g) = 0.487 W/kg



0 dB = 0.771 W/kg = -1.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 48780

Communication System: UID 0, LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: 2450-2600 Body Medium parameters used (interpolated):

$f = 2535 \text{ MHz}$; $\sigma = 2.118 \text{ S/m}$; $\epsilon_r = 51.604$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-28-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Body SAR, Back side,
Mid.ch, 20 MHz Bandwidth, QPSK, 50 RB, 0 RB Offset**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.03 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.682 W/kg



0 dB = 1.13 W/kg = 0.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 49176

Communication System: UID 0, _LTE Band 38; Frequency: 2595 MHz; Duty Cycle: 1:1.58

Medium: 2450-2600 Body Medium parameters used (interpolated):

$f = 2595 \text{ MHz}$; $\sigma = 2.201 \text{ S/m}$; $\epsilon_r = 51.363$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 09-28-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 38, Body SAR, Back side,
Mid.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (10x16x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.30 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.533 W/kg

SAR(1 g) = 0.260 W/kg



0 dB = 0.425 W/kg = -3.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 49176

Communication System: UID 0, _LTE Band 38; Frequency: 2595 MHz; Duty Cycle: 1:1.58

Medium: 2450-2600 Body Medium parameters used (interpolated):

$f = 2595 \text{ MHz}$; $\sigma = 2.201 \text{ S/m}$; $\epsilon_r = 51.363$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-28-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 38, Body SAR, Back side,
Mid.ch, 20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (10x16x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.50 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.543 W/kg



0 dB = 0.883 W/kg = -0.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 49176

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.002 \text{ S/m}$; $\epsilon_r = 52.094$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth,
Body SAR, Ch 6, 1 Mbps, Back Side**


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.454 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.195 W/kg

SAR(1 g) = 0.097 W/kg



0 dB = 0.124 W/kg = -9.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ250F; Type: Portable Handset; Serial: 49176

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.002 \text{ S/m}$; $\epsilon_r = 52.094$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth,
Body SAR, Ch 6, 1 Mbps, Back Side**


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (15x18x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.120 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.534 W/kg

SAR(1 g) = 0.245 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.901 \text{ S/m}$; $\epsilon_r = 41.876$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-01-2017; Ambient Temp: 20.7°C; Tissue Temp: 20.3°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.67 W/kg

SAR(1 g) = 1.82 W/kg

Deviation(1 g) = -4.41%



0 dB = 2.12 W/kg = 3.26 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.91 \text{ S/m}$; $\epsilon_r = 41.742$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-09-2017; Ambient Temp: 21.5°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.75 W/kg

SAR(1 g) = 1.87 W/kg

Deviation(1 g) = 2.41%



0 dB = 2.18 W/kg = 3.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450$ MHz; $\sigma = 1.794$ S/m; $\epsilon_r = 38.482$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 9-28-2017; Ambient Temp: 21.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3319; ConvF(4.6, 4.6, 4.6); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 08/03/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.2 W/kg

SAR(1 g) = 5.3 W/kg

Deviation(1 g) = 0.38%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.849 \text{ S/m}$; $\epsilon_r = 38.156$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0cm

Test Date: 10-10-2017; Ambient Temp: 23.5°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3213; ConvF(4.7, 4.7, 4.7); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.4 W/kg

SAR(1 g) = 5.47 W/kg

Deviation(1 g) = 5.39%



0 dB = 7.19 W/kg = 8.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 MHz Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.88 \text{ S/m}$; $\epsilon_r = 38.615$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-17-2017; Ambient Temp: 22.6°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.2 W/kg

SAR(1 g) = 5.45 W/kg

Deviation(1 g) = 5.01%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.855 \text{ S/m}$; $\epsilon_r = 39.496$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-26-2017; Ambient Temp: 23.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.1 W/kg

SAR(1 g) = 5.45 W/kg

Deviation(1 g) = 3.22%



0 dB = 6.52 W/kg = 8.14 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Head Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 1.96 \text{ S/m}$; $\epsilon_r = 37.943$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 9-28-2017; Ambient Temp: 21.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3319; ConvF(4.41, 4.41, 4.41); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 08/03/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 12.6 W/kg

SAR(1 g) = 5.55 W/kg

Deviation(1 g) = -1.60%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 53.975$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-02-2017; Ambient Temp: 21.0°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 08/03/2017

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.07 W/kg

SAR(1 g) = 2.08 W/kg

Deviation(1 g) = 6.12%



0 dB = 2.42 W/kg = 3.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.999 \text{ S/m}$; $\epsilon_r = 53.175$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-09-2017; Ambient Temp: 21.5°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7410; ConvF(9.95, 9.95, 9.95); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.01 W/kg

SAR(1 g) = 2.03 W/kg

Deviation(1 g) = 3.57%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.999 \text{ S/m}$; $\epsilon_r = 52.814$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-11-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(6.47, 6.47, 6.47); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.84 W/kg

SAR(1 g) = 1.96 W/kg

Deviation(1 g) = 4.14%



0 dB = 2.28 W/kg = 3.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.004$ S/m; $\epsilon_r = 51.938$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-28-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.0 W/kg

SAR(1 g) = 5.2 W/kg

Deviation(1 g) = 3.79%



0 dB = 8.75 W/kg = 9.42 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.02 \text{ S/m}$; $\epsilon_r = 52.049$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-25-2017; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.42, 4.42, 4.42); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.6 W/kg

SAR(1 g) = 5.10 W/kg

Deviation(1 g) = 1.80%



0 dB = 6.72 W/kg = 8.27 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2600$ MHz; $\sigma = 2.208$ S/m; $\epsilon_r = 51.342$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-28-2017; Ambient Temp: 22.7°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 12.6 W/kg

SAR(1 g) = 5.5 W/kg

Deviation(1 g) = 1.29%



0 dB = 9.80 W/kg = 9.91 dBW/kg