

MEASUREMENT REPORT

GSM / GPRS / EDGE / WCDMA

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

9/27 - 10/12/2017

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M1709270258-02.A3L

FCC ID:

A3LSMJ250F

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-J250F/DS

Additional Model:

SM-J250F

EUT Type:

Portable Handset

FCC Classification:

TNE (Licensed Non-Broadcast Transmitter Held to Ear)

FCC Rule Part(s):

22(H)

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v02r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President




FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 1 of 43

TABLE OF CONTENTS


1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Cellular - Base Frequency Blocks	6
3.3	Cellular - Mobile Frequency Blocks	6
3.4	Radiated Measurements	7
4.0	MEASUREMENT UNCERTAINTY	8
5.0	TEST EQUIPMENT CALIBRATION DATA	9
6.0	SAMPLE CALCULATIONS	10
7.0	TEST RESULTS.....	11
7.1	Summary.....	11
7.2	Occupied Bandwidth	12
7.3	Spurious and Harmonic Emissions at Antenna Terminal	15
7.4	Band Edge Emissions at Antenna Terminal	26
7.5	Radiated Power (ERP/EIRP).....	29
7.6	Radiated Spurious Emissions Measurements.....	32
7.7	Frequency Stability / Temperature Variation	38
8.0	CONCLUSION.....	43

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 2 of 43



MEASUREMENT REPORT

GSM / GPRS / EDGE / WCDMA



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	
GPRS850	22H	824.2 - 848.8	1.177	30.71	1.931	32.86	245KGXW
EDGE850	22H	824.2 - 848.8	0.217	23.37	0.357	25.52	244KG7W
WCDMA850	22H	826.4 - 846.6	0.125	20.97	0.205	23.12	4M18F9W

EUT Overview

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 3 of 43

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 4 of 43

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMJ250F**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

Test Device Serial No.: 48772, 49135

2.2 Device Capabilities

This device contains the following capabilities:

850 GSM/GPRS/EDGE, 850 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE)

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 5 of 43

3.0 DESCRIPTION OF TESTS


3.1 Evaluation Procedure

The measurement procedures described in the "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-E-2016) and "Measurement Guidance for Certification of Licensed Digital Transmitters" (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset	Page 6 of 43	

3.4 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/ITA-603-D-2010.

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 7 of 43

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 8 of 43

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx3	Licensed Transmitter Cable Set	8/10/2017	Annual	8/10/2018	LTx3
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	6/21/2017	Annual	6/21/2018	RE1
Agilent	N9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561
Emco	6502	Active Loop Antenna (10k - 30 MHz)	8/9/2016	Biennial	8/9/2018	2936
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
Espec	ESX-2CA	Environmental Chamber	4/11/2017	Annual	4/11/2018	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128337
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	8/23/2016	Biennial	8/23/2018	135427
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/24/2017	Annual	3/24/2018	11401010036
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
PCTEST	-	EMC Switch System	6/21/2017	Annual	6/21/2018	NM1
PCTEST	-	EMC Switch System	6/21/2017	Annual	6/21/2018	NM2
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/11/2017	Annual	8/11/2018	103200
Rohde & Schwarz	CMU200	Base Station Simulator	5/22/2017	Annual	5/22/2018	109892
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	4/19/2017	Annual	4/19/2018	100342
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/11/2017	Annual	5/11/2018	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/18/2015	Biennial	11/18/2017	91052523RX
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

Notes:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMJ250F			FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset	Page 9 of 43		

6.0 SAMPLE CALCULATIONS

GPRS Emission Designator

Emission Designator = 250KGXW

GPRS BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 10 of 43

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMJ250F
 FCC Classification: TNE (Licensed Non-Broadcast Transmitter Held to Ear)
 Mode(s): GSM / GPRS / EDGE / WCDMA

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	RSS-Gen (4.6.1)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a)	RSS-132(5.5)	Conducted Band Edge / Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
2.1046	RSS-132(5.4)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355	RSS-132(5.3)	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part		PASS	Section 7.7
22.913(a.2)	RSS-132(5.4)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.5
22.917(a)	RSS-132(5.5)	Radiated Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Section 7.6

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 11 of 43

7.2 Occupied Bandwidth

§2.1049 RSS-Gen (4.6.1)

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 12 of 43



Plot 7-1. Occupied Bandwidth Plot (Cellular GPRS Mode)



Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 13 of 43



Plot 7-3. Occupied Bandwidth Plot (Cellular WCDMA Mode)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 14 of 43

7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) RSS-132(5.5)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1MHz, and 100 kHz or greater for Part 22 and RSS-132 measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 15 of 43

Cellular GPRS Mode




Plot 7-4. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)




Plot 7-5. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 16 of 43




Plot 7-6. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)




Plot 7-7. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 17 of 43




Plot 7-8. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)




Plot 7-9. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 18 of 43




Plot 7-10. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)



Plot 7-11. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)


FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 19 of 43




Plot 7-12. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 20 of 43

Cellular WCDMA Mode



Plot 7-13. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-14. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 21 of 43




Plot 7-15. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-16. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 22 of 43




Plot 7-17. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)




Plot 7-18. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 23 of 43



Plot 7-19. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)



Plot 7-20. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 24 of 43



Plot 7-21. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 25 of 43

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) RSS-132(5.5)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq 1\%$ of the emission bandwidth
4. VBW $\geq 3 \times$ RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

Test Notes


Per 22.917(b) and RSS-132(5.5) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 26 of 43



© 2017 PCTEST Engineering Laboratory, Inc. V 7 9/25/2017
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Cellular WCDMA Mode



Plot 7-24. Band Edge Plot (Cellular WCDMA Mode - Low Channel)



Plot 7-25. Band Edge Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 28 of 43

7.5 Radiated Power (ERP/EIRP)

§22.913(a)(2) 24.232(c) RSS-132(5.4)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto". Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 29 of 43

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Radiated Test Setup <1GHz




Figure 7-5. Radiated Test Setup >1GHz

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 30 of 43

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
824.20	GPRS850	H	150	87	31.13	1.50	30.47	1.115	38.45	-7.98	32.62	1.829	40.61	-7.98
836.60	GPRS850	H	150	87	31.36	1.50	30.71	1.177	38.45	-7.74	32.86	1.931	40.61	-7.75
848.80	GPRS850	H	150	340	30.70	1.50	30.05	1.011	38.45	-8.40	32.20	1.659	40.61	-8.41
836.60	GPRS850	V	150	13	25.03	1.50	24.38	0.274	38.45	-14.07	26.53	0.450	40.61	-14.08
836.60	EDGE850	H	150	87	24.02	1.50	23.37	0.217	38.45	-15.08	25.52	0.357	40.61	-15.08

Table 7-2. ERP/EIRP (Cellular GPRS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	150	336	21.62	1.50	20.97	0.125	38.45	-17.48	23.12	0.205	40.61	-17.49
836.60	WCDMA850	H	150	330	21.16	1.50	20.51	0.112	38.45	-17.94	22.66	0.185	40.61	-17.95
846.60	WCDMA850	H	150	346	20.81	1.50	20.16	0.104	38.45	-18.29	22.31	0.170	40.61	-18.30
826.40	WCDMA850	V	150	88	20.12	1.50	19.47	0.089	38.45	-18.98	21.62	0.145	40.61	-18.99

Table 7-3. ERP/EIRP (Cellular WCDMA)

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 31 of 43

7.6 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a)RSS-132(5.5)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 32 of 43

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 5) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 6) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 7) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 33 of 43

Cellular GPRS Mode

OPERATING FREQUENCY: 824.20 MHz
 CHANNEL: 128
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1648.40	H	146	12	-65.83	9.01	-56.82	-43.8
2472.60	H	155	227	-47.65	9.12	-38.53	-25.5
3296.80	H	160	341	-46.47	9.37	-37.10	-24.1
4121.00	H	188	170	-57.84	9.83	-48.00	-35.0
4945.20	H	-	-	-72.23	11.24	-60.99	-48.0

Table 7-4. Radiated Spurious Data (Cellular GPRS Mode – Ch. 128)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	121	7	-58.74	8.85	-49.90	-36.9
2509.80	H	115	156	-57.00	9.17	-47.84	-34.8
3346.40	H	123	352	-52.95	9.36	-43.59	-30.6
4183.00	H	113	177	-65.50	10.19	-55.30	-42.3
5019.60	H	-	-	-71.09	11.09	-59.99	-47.0

Table 7-5. Radiated Spurious Data (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 34 of 43

OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1697.60	H	229	9	-56.37	8.67	-47.70	-34.7
2546.40	H	104	319	-47.64	9.28	-38.36	-25.4
3395.20	H	169	303	-51.22	9.46	-41.76	-28.8
4244.00	H	197	154	-63.86	10.48	-53.38	-40.4
5092.80	H	-	-	-69.87	10.88	-58.99	-46.0

Table 7-6. Radiated Spurious Data (Cellular GPRS Mode – Ch. 251)

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 35 of 43

Cellular WCDMA Mode

OPERATING FREQUENCY: 826.40 MHz
 CHANNEL: 4132
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	143	16	-51.23	8.85	-42.38	-29.4
2479.20	H	100	59	-67.24	9.69	-57.55	-44.5
3305.60	H	-	-	-72.05	9.53	-62.52	-49.5

Table 7-7. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 4183
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	134	18	-47.51	8.85	-38.67	-25.7
2509.80	H	100	67	-65.97	9.78	-56.19	-43.2
3346.40	H	-	-	-70.94	9.67	-61.27	-48.3

Table 7-8. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 36 of 43

OPERATING FREQUENCY: 846.60 MHz
 CHANNEL: 4233
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	132	14	-50.27	8.85	-41.43	-28.4
2539.80	H	100	339	-68.50	9.75	-58.75	-45.7
3386.40	H	100	99	-71.98	9.80	-62.18	-49.2

Table 7-9. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 37 of 43

7.7 Frequency Stability / Temperature Variation

§2.1055 §22.355 RSS-132(5.3)

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22 and RSS-132, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Test Procedure Used

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 38 of 43

Frequency Stability / Temperature Variation

§2.1055 §22.355 RSS-132(5.3)

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 190
 REFERENCE VOLTAGE: 3.80 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,599,988	-12	-0.0000014
100 %		- 30	836,599,903	-97	-0.0000116
100 %		- 20	836,599,882	-118	-0.0000141
100 %		- 10	836,599,966	-34	-0.0000040
100 %		0	836,599,851	-149	-0.0000178
100 %		+ 10	836,599,953	-47	-0.0000056
100 %		+ 20	836,599,953	-47	-0.0000056
100 %		+ 30	836,599,906	-94	-0.0000113
100 %		+ 40	836,599,871	-129	-0.0000155
100 %		+ 50	836,599,814	-186	-0.0000223
BATT. ENDPOINT	3.40	+ 20	836,599,854	-146	-0.0000175

Table 7-10. Frequency Stability Data (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 39 of 43

Frequency Stability / Temperature Variation

§2.1055 §22.355 RSS-132(5.3)




Figure 7-7. Frequency Stability Graph (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 40 of 43

Frequency Stability / Temperature Variation

§2.1055 §22.355 RSS-132(5.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 4183

REFERENCE VOLTAGE: 3.80 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,599,840	-160	-0.0000191
100 %		- 30	836,599,982	-18	-0.0000022
100 %		- 20	836,599,877	-123	-0.0000147
100 %		- 10	836,599,972	-28	-0.0000034
100 %		0	836,599,834	-166	-0.0000198
100 %		+ 10	836,599,932	-68	-0.0000081
100 %		+ 20	836,599,967	-33	-0.0000040
100 %		+ 30	836,599,893	-107	-0.0000128
100 %		+ 40	836,599,855	-145	-0.0000173
100 %		+ 50	836,599,810	-190	-0.0000227
BATT. ENDPOINT	3.40	+ 20	836,599,923	-77	-0.0000092

Table 7-11. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 41 of 43

Frequency Stability / Temperature Variation

§2.1055 §22.355 RSS-132(5.3)



Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ250F	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 TEST REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 42 of 43

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMJ250F** complies with all the requirements of Part 22 of the FCC Rules.

FCC ID: A3LSMJ250F		FCC Pt. 22 TEST REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709270258-02.A3L	Test Dates: 9/27 - 10/12/2017	EUT Type: Portable Handset		Page 43 of 43