



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

01/27/16 - 02/22/16

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

0Y1601280163-R1.A3L

FCC ID:

A3LSMJ320VPP

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SM-J320VPP

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.38	0.62	0.62
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.58	0.51	0.45
PCE	UMTS 850	826.40 - 846.60 MHz	0.29	0.53	0.53
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.89	0.71	1.04
PCE	Cell. CDMA/EVDO	824.70 - 848.31 MHz	0.56	0.62	0.61
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.54	0.88	1.06
PCE	LTE Band 13	779.5 - 784.5 MHz	0.37	0.52	0.52
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.35	0.39	0.39
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.66	0.90	0.90
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.93	0.69	0.74
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.28	0.14	0.17
NII	U-NII-1	5180 - 5240 MHz			
NII	U-NII-2A	5260 - 5320 MHz	0.21	0.29	
NII	U-NII-2C	5500 - 5720 MHz	0.21	0.44	
NII	U-NII-3	5745 - 5825 MHz	0.14	0.22	0.22
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A	<0.1	N/A
Simultaneous SAR per KDB 690783 D01v01r03:			1.20	1.34	1.27

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

"Note: This revised Test Report (S/N: 0Y1601280163-R1.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 1 of 62

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	8
3	INTRODUCTION	9
4	DOSIMETRIC ASSESSMENT	10
5	DEFINITION OF REFERENCE POINTS	11
6	TEST CONFIGURATION POSITIONS	12
7	RF EXPOSURE LIMITS	15
8	FCC MEASUREMENT PROCEDURES.....	16
9	RF CONDUCTED POWERS	23
10	SYSTEM VERIFICATION.....	38
11	SAR DATA SUMMARY	41
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	52
13	SAR MEASUREMENT VARIABILITY	57
14	EQUIPMENT LIST	58
15	MEASUREMENT UNCERTAINTIES.....	59
16	CONCLUSION.....	60
17	REFERENCES	61
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 2 of 62	

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
Cell. CDMA/EVDO	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
U-NII-1	Data	5180 - 5240 MHz
U-NII-2A	Data	5260 - 5320 MHz
U-NII-2C	Data	5500 - 5720 MHz
U-NII-3	Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device uses an independent fixed level power reduction mechanism for PCS CDMA/EVDO and WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Output Powers

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.0	33.0	29.5	27.5	27.5	27.0	27.0	26.5	25.0
	Nominal	32.5	32.5	29.0	27.0	27.0	26.5	26.5	26.0	24.5
GSM/GPRS/EDGE 1900	Maximum	30.0	30.0	27.0	25.0	25.0	27.0	26.5	25.0	23.5
	Nominal	29.5	29.5	26.5	24.5	24.5	26.5	26.0	24.5	23.0

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 3 of 62

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	22.5	22.5	22.5
	Nominal	22.0	22.0	22.0
UMTS Band 2 (1900 MHz)	Maximum	23.0	23.0	23.0
	Nominal	22.5	22.5	22.5
Mode / Band		Modulated Average (dBm)		
Cell. CDMA/EVDO	Maximum	24.7		
	Nominal	24.2		
PCS CDMA/EVDO	Maximum	24.7		
	Nominal	24.2		
Mode / Band		Modulated Average (dBm)		
LTE Band 13	Maximum	23.5		
	Nominal	23.0		
LTE Band 5 (Cell)	Maximum	23.5		
	Nominal	23.0		
LTE Band 4 (AWS)	Maximum	23.0		
	Nominal	22.5		
LTE Band 2 (PCS)	Maximum	23.0		
	Nominal	22.5		
Mode / Band		Modulated Average (dBm)		
IEEE 802.11b (2.4 GHz 22 MHz)	Maximum	16.5		
	Nominal	16.0		
IEEE 802.11g (2.4 GHz 20 MHz)	Maximum	14.0		
	Nominal	13.5		
IEEE 802.11n (2.4 GHz 20 MHz)	Maximum	14.0		
	Nominal	13.5		
Bluetooth	Maximum	13.0		
	Nominal	12.5		
Bluetooth LE	Maximum	3.5		
	Nominal	3.0		
Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	
IEEE 802.11a (5 GHz)	Maximum	14.0		
	Nominal	13.5		
IEEE 802.11n (5 GHz)	Maximum	14.0	12.5	
	Nominal	13.5	12.0	

1.3.2 Reduced Output Powers -Held to Ear

Mode / Band		Modulated Average (dBm)
PCS CDMA/EVDO	Maximum	22.2
	Nominal	21.7

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 4 of 62	

Mode / Band		Modulated Average (dBm)	
IEEE 802.11b (2.4 GHz 22 MHz)	Maximum	12.5	
	Nominal	12.0	
IEEE 802.11g (2.4 GHz 20 MHz)	Maximum	10.0	
	Nominal	9.5	
IEEE 802.11n (2.4 GHz 20 MHz)	Maximum	10.0	
	Nominal	9.5	

Mode / Band		Modulated Average (dBm)	
		20 MHz Bandwidth	40 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	9.0	
	Nominal	8.5	
IEEE 802.11n (5 GHz)	Maximum	9.0	7.5
	Nominal	8.5	7.0

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is ≤160 mm and the diagonal display is ≤150 mm. A diagram showing the location of the device antennas can be found in Appendix F.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
Cell. EVDO	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	Yes	No
5 GHz WLAN	Yes	Yes	Yes	No	Yes	No

Note: Particular DUT edges were not required to be evaluated for wireless router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled. Therefore, U-NII-1, U-NII-2A, U-NII-2C operations are not considered in this section.

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 5 of 62



Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	1x CDMA voice + 2.4 GHz WI-FI	Yes	Yes	N/A	
2	1x CDMA voice + 5 GHz WI-FI	Yes	Yes	N/A	
3	1x CDMA voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
4	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A	
5	GSM voice + 5 GHz WI-FI	Yes	Yes	N/A	
6	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
7	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes	
8	UMTS + 5 GHz WI-FI	Yes	Yes	Yes	
9	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	
10	LTE + 2.4 GHz WI-FI	Yes	Yes	Yes	
11	LTE + 5 GHz WI-FI	Yes	Yes	Yes	
12	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A	
13	CDMA/EVDO data + 2.4 GHz WI-FI	Yes*	Yes*	Yes	*-Pre-installed VOIP applications are considered.
14	CDMA/EVDO data + 5 GHz WI-FI	Yes*	Yes*	Yes	*-Pre-installed VOIP applications are considered.
15	CDMA/EVDO data + 2.4 GHz Bluetooth	N/A	Yes*	N/A	*-Pre-installed VOIP applications are considered.
16	GPRS/EDGE + 2.4 GHz WI-FI	N/A	N/A	Yes	
17	GPRS/EDGE + 5 GHz WI-FI	N/A	N/A	Yes	
18	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	N/A	N/A	

- 2.4 GHz WLAN, 5 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call.
- 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
- This device supports VoLTE

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 6 of 62

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1x Advanced was not more than 0.25 dB higher than the maximum powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg per FCC KDB Publication 941225 D01.

1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
GSM/GPRS/EDGE 850	38596	38414	38414
GSM/GPRS/EDGE 1900	38596	38956	38956
UMTS 850	38414	38414	38414
UMTS 1900	38414	38414	38414
Cell. CDMA/EVDO	38414	41970	41970
PCS CDMA/EVDO	38414	38414	38414
LTE Band 13	41970	41970	41970
LTE Band 5 (Cell)	41970	41970	41970
LTE Band 4 (AWS)	41970	41970	41970
LTE Band 2 (PCS)	41970	41970	41970
2.4 GHz WLAN	38422	41970	41970
5 GHz WLAN	38422	41970	41970
2.4 GHz Bluetooth	-	41970	-

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 7 of 62

2 LTE INFORMATION

LTE Information			
FCC ID	A3LSMJ320VPP		
Form Factor	Portable Handset		
Frequency Range of each LTE transmission band	LTE Band 13 (779.5 - 784.5 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
Channel Bandwidths	LTE Band 13: 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 13: 5 MHz	779.5 (23205)	782 (23230)	784.5 (23255)
LTE Band 13: 10 MHz	N/A	782 (23230)	N/A
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
UE Category	4		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		
LTE Carrier Aggregation Possible Combinations	This device does not support carrier aggregation.		
LTE Release 10 Additional Information	This device does not support full CA features on 3GPP Release 10. The following LTE Release 10 Features are not supported: LTE CA ,Relay, HetNet, Enhanced MIMO, eICI, WIFI Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.		

FCC ID: A3LSMJ320VPP	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 8 of 62

3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 9 of 62

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area
Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 10 of 62

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 11 of 62

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position



2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 12 of 62



metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 14 of 62

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 15 of 62

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 16 of 62

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

Table 8-1
Parameters for Max. Power for RC1

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 8-2
Parameters for Max. Power for RC3

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with "All Up" power control bits.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

8.4.3 Body-worn SAR Measurements

SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with Ev-Do capabilities, the 3G SAR test reduction procedure is applied to Ev-Do Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 17 of 62

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For Ev-Do data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with Ev-Do Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

8.4.6 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers are measured using SO75 with RC8 on the uplink and RC11 on the downlink per FCC KDB Publication 941225 D01v03r01. Smart blanking is disabled for all measurements. The EUT is configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers are measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

The 3G SAR test reduction procedure is applied to the 1x-Advanced transmission mode with 1x RTT RC3 as the primary mode. When SAR measurement is required, the 1x-Advanced power measurement configurations are used. The 1x Advanced SAR procedures are applied separately to head, body-worn accessory and other exposure conditions.

8.5 SAR Measurement Conditions for UMTS

8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1s". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 18 of 62

8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

FCC ID: A3LSMJ320VPP	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 19 of 62

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.7.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 20 of 62

8.7.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.7.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

8.7.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.7.6 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz and 5 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.7.7 Initial Test Configuration Procedure

For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified

FCC ID: A3LSMJ320VPP	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset
		Page 21 of 62

for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.6).

8.7.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 22 of 62

9 RF CONDUCTED POWERS

9.1 CDMA Conducted Powers

9.1.1 Maximum Output Powers

Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	1013	22H	824.7	24.28	24.30	24.22	24.26	24.15	24.25	24.15
	384	22H	836.52	24.24	24.27	24.18	24.19	24.29	24.31	24.22
	777	22H	848.31	24.10	24.12	24.02	24.15	24.11	24.17	24.12
PCS	25	24E	1851.25	24.51	24.38	24.53	24.47	24.47	24.49	24.45
	600	24E	1880	24.33	24.28	24.39	24.35	24.36	24.37	24.36
	1175	24E	1908.75	24.22	24.29	24.32	24.31	24.38	24.32	24.22

9.1.2 Reduced Power – Held to Ear

Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
PCS	25	24E	1851.25	22.08	22.10	22.01	22.10	22.09	22.09	22.12
	600	24E	1880	21.95	21.98	21.95	21.94	21.98	22.04	21.97
	1175	24E	1908.75	21.97	21.96	21.94	21.92	21.99	21.91	22.03

Note: RC1 is only applicable for IS-95 compatibility.



Figure 9-1
Power Measurement Setup

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 23 of 62

9.2 GSM Conducted Powers

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	31.60	31.67	28.88	27.00	26.77	26.55	26.36	25.92	24.49
	190	31.75	31.78	29.09	27.20	26.96	26.57	26.49	25.97	24.60
	251	31.87	31.95	29.27	27.43	27.23	26.88	26.85	26.12	24.90
GSM 1900	512	28.82	28.80	26.22	24.01	23.78	26.24	26.04	24.46	23.02
	661	29.22	29.10	26.50	24.52	24.23	26.46	26.35	24.65	23.29
	810	29.31	29.27	26.61	24.87	24.60	26.69	26.00	24.89	23.50
		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	22.57	22.64	22.86	22.74	23.76	17.52	20.34	21.66	21.48
	190	22.72	22.75	23.07	22.94	23.95	17.54	20.47	21.71	21.59
	251	22.84	22.92	23.25	23.17	24.22	17.85	20.83	21.86	21.89
GSM 1900	512	19.79	19.77	20.20	19.75	20.77	17.21	20.02	20.20	20.01
	661	20.19	20.07	20.48	20.26	21.22	17.43	20.33	20.39	20.28
	810	20.28	20.24	20.59	20.61	21.59	17.66	19.98	20.63	20.49
GSM 850	Frame	23.47	23.47	22.98	22.74	23.99	17.47	20.48	21.74	21.49
GSM 1900	Avg.Targets:	20.47	20.47	20.48	20.24	21.49	17.47	19.98	20.24	19.99

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B

GPRS Multislot class: 33 (Max 4 Tx uplink slots)

EDGE Multislot class: 33 (Max 4 Tx uplink slots)

DTM Multislot Class: N/A



Figure 9-2
Power Measurement Setup

FCC ID: A3LSMJ320VPP	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 24 of 62

9.3 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	21.95	21.97	22.04	22.58	22.47	22.26	-
99		12.2 kbps AMR	21.92	21.95	22.06	22.57	22.43	22.28	-
6	HSDPA	Subtest 1	21.85	21.88	21.92	22.75	22.60	22.35	0
6		Subtest 2	21.89	21.92	22.08	22.82	22.62	22.40	0
6		Subtest 3	20.93	20.97	21.03	21.71	21.57	21.48	0.5
6		Subtest 4	20.90	20.95	21.02	21.70	21.58	21.49	0.5
6	HSUPA	Subtest 1	21.49	21.33	21.24	22.20	22.25	21.85	0
6		Subtest 2	21.88	21.74	21.82	22.63	22.58	22.41	2
6		Subtest 3	19.82	19.57	19.51	20.17	20.20	20.38	1
6		Subtest 4	20.41	20.16	20.11	20.86	20.73	20.84	2
6		Subtest 5	21.83	21.82	21.85	22.70	22.54	22.35	0

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 1 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.



Figure 9-3
Power Measurement Setup

FCC ID: A3LSMJ320VPP	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 25 of 62

9.4 LTE Conducted Powers

9.4.1 LTE Band 13

Table 9-1
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.37	0	0
	1	25	23.24		0
	1	49	23.12		0
	25	0	22.18	0-1	1
	25	12	22.13		1
	25	25	22.11		1
	50	0	22.31		1
16QAM	1	0	22.50	0-1	1
	1	25	22.42		1
	1	49	22.47		1
	25	0	21.29	0-2	2
	25	12	21.22		2
	25	25	21.23		2
	50	0	21.22		2

Table 9-2
LTE Band 13 Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.10	0	0
	1	12	22.92		0
	1	24	22.81		0
	12	0	22.23	0-1	1
	12	6	22.22		1
	12	13	22.11		1
	25	0	22.24		1
16QAM	1	0	21.77	0-1	1
	1	12	21.90		1
	1	24	21.80		1
	12	0	20.99	0-2	2
	12	6	20.86		2
	12	13	21.05		2
	25	0	21.29		2

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 26 of 62

9.4.2

LTE Band 5

Table 9-3
LTE Band 5 Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.31	0	0
	1	25	23.02		0
	1	49	23.46		0
	25	0	21.93	0-1	1
	25	12	21.86		1
	25	25	22.06		1
	50	0	21.92		1
16QAM	1	0	22.43	0-1	1
	1	25	22.24		1
	1	49	22.49		1
	25	0	20.97	0-2	2
	25	12	20.87		2
	25	25	21.21		2
	50	0	20.95		2

Note: LTE Band 5 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-4
LTE Band 5 Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.05	22.93	22.89	0	0
	1	12	23.03	23.03	23.45		0
	1	24	23.10	22.86	22.85		0
	12	0	21.85	21.96	22.02	0-1	1
	12	6	21.82	21.92	22.12		1
	12	13	21.77	22.00	22.05		1
	25	0	21.88	21.95	22.03		1
16QAM	1	0	22.00	21.56	22.21	0-1	1
	1	12	21.78	21.84	22.40		1
	1	24	21.95	21.91	22.16		1
	12	0	20.90	20.74	21.05	0-2	2
	12	6	20.87	20.76	20.85		2
	12	13	20.82	20.87	20.77		2
	25	0	20.84	20.82	21.19		2

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 27 of 62

Table 9-5
LTE Band 5 Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.02	23.35	23.19	0	0
	1	7	23.22	23.23	23.20		0
	1	14	22.93	23.37	23.23		0
	8	0	21.89	21.97	22.04	0-1	1
	8	4	21.86	22.01	22.04		1
	8	7	21.90	21.97	22.06		1
	15	0	21.88	21.88	22.08		1
16QAM	1	0	21.95	21.90	22.15	0-1	1
	1	7	22.36	21.93	21.93		1
	1	14	21.88	21.94	21.66		1
	8	0	20.97	20.62	20.81	0-2	2
	8	4	20.92	20.72	21.18		2
	8	7	20.95	20.91	21.09		2
	15	0	20.72	21.23	21.16		2

Table 9-6
LTE Band 5 Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.90	23.44	23.47	0	0
	1	2	23.30	23.33	23.43		0
	1	5	23.25	23.32	23.30		0
	3	0	22.82	23.08	23.24		0
	3	2	22.99	23.07	23.28		0
	3	3	22.95	23.02	23.10		0
	6	0	21.76	21.97	22.12	0-1	1
16QAM	1	0	21.31	22.14	22.20	0-1	1
	1	2	21.36	22.13	22.23		1
	1	5	21.37	21.78	22.03		1
	3	0	21.37	22.11	22.10		1
	3	2	21.38	22.08	22.09		1
	3	3	21.56	22.05	22.04		1
	6	0	20.74	21.19	21.35	0-2	2

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 28 of 62

9.4.3

LTE Band 4 (AWS)

Table 9-7
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.72	0	0
	1	50	22.64		0
	1	99	22.49		0
	50	0	21.46	0-1	1
	50	25	21.41		1
	50	50	21.37		1
	100	0	21.40		1
16QAM	1	0	21.71	0-1	1
	1	50	21.69		1
	1	99	21.41		1
	50	0	20.52	0-2	2
	50	25	20.57		2
	50	50	20.52		2
	100	0	20.34		2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-8
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 4 (AWS) Configured for 15 MHz Bandwidth							
LTE Band 4 (AWS) 15 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.77	22.84	22.48	0	0
	1	36	22.47	22.74	22.37		0
	1	74	22.61	22.75	22.54		0
	36	0	21.37	21.55	21.60	0-1	1
	36	18	21.29	21.55	21.65		1
	36	37	21.39	21.52	21.53		1
	75	0	21.46	21.50	21.54		1
16QAM	1	0	21.96	22.00	21.99	0-1	1
	1	36	21.63	21.84	21.98		1
	1	74	21.93	21.88	22.00		1
	36	0	20.34	20.58	20.61	0-2	2
	36	18	20.32	20.63	20.55		2
	36	37	20.36	20.62	20.52		2
	75	0	20.29	20.50	20.48		2

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 29 of 62

Table 9-9
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 4 (AWS) 10 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.94	23.00	22.92	0	0
	1	25	22.25	22.59	23.00		0
	1	49	22.89	22.63	22.87		0
	25	0	21.36	21.54	21.55	0-1	1
	25	12	21.33	21.55	21.50		1
	25	25	21.35	21.51	21.52		1
	50	0	21.40	21.52	21.56		1
16QAM	1	0	22.00	21.97	21.92	0-1	1
	1	25	21.91	21.71	21.98		1
	1	49	21.98	21.81	21.90		1
	25	0	20.51	20.67	20.45	0-2	2
	25	12	20.46	20.61	20.56		2
	25	25	20.38	20.62	20.54		2
	50	0	20.36	20.53	20.65		2

Table 9-10
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 4 (AWS) 5 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.72	22.67	23.00	0	0
	1	12	22.55	22.66	22.94		0
	1	24	22.56	22.81	22.89		0
	12	0	21.38	21.49	21.46	0-1	1
	12	6	21.36	21.52	21.55		1
	12	13	21.30	21.47	21.58		1
	25	0	21.36	21.46	21.53		1
16QAM	1	0	21.42	21.75	21.43	0-1	1
	1	12	21.36	21.61	21.50		1
	1	24	20.91	21.73	21.29		1
	12	0	20.35	20.54	20.14	0-2	2
	12	6	20.36	20.49	20.07		2
	12	13	20.30	20.44	20.11		2
	25	0	20.58	20.55	20.18		2

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 30 of 62

Table 9-11
LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 4 (AWS) 3 MHzBandwidth							
Modulation	RB Size	RB Offset	Frequency [MHz]	Frequency [MHz]	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.60	22.57	22.31	0	0
	1	7	22.59	22.60	22.30		0
	1	14	22.50	22.66	22.36		0
	8	0	21.37	21.49	21.51	0-1	1
	8	4	21.29	21.48	21.48		1
	8	7	21.31	21.50	21.47		1
16QAM	15	0	21.32	21.52	21.62	0-1	1
	1	0	21.63	21.78	21.98		1
	1	7	21.54	21.79	21.93		1
	1	14	21.56	21.70	22.00	0-2	1
	8	0	20.34	20.22	20.71		2
	8	4	20.15	20.23	20.67		2
	8	7	20.19	20.53	20.68		2
	15	0	20.29	20.62	20.59		2

Table 9-12
LTE Band 4 (AWS) Conducted Powers - 1.4 MHz Bandwidth

LTE Band 4 (AWS) 1.4 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.71	22.80	22.27	0	0
	1	2	22.74	22.83	22.33		0
	1	5	22.67	22.71	22.26		0
	3	0	22.50	22.60	22.29		0
	3	2	22.61	22.64	22.32		0
	3	3	22.56	22.59	22.30	0	
	6	0	21.28	21.51	21.55	0-1	1
16QAM	1	0	21.53	21.54	21.67	0-1	1
	1	2	21.59	21.70	21.70		1
	1	5	21.44	21.55	21.68		1
	3	0	21.66	21.71	21.56		1
	3	2	21.56	21.83	21.69		1
	3	3	21.53	21.58	21.63	1	
		6	0	20.87	20.83	20.80	0-2

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 31 of 62

9.4.4

LTE Band 2 (PCS)

Table 9-13
LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 2 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18700 (1860.0 MHz)	18900 (1880.0 MHz)	19100 (1900.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.61	22.40	22.24	0	0
	1	50	22.44	22.23	21.82		0
	1	99	22.37	22.25	22.00		0
	50	0	21.51	21.20	21.39	0-1	1
	50	25	21.31	21.21	21.15		1
	50	50	21.41	21.08	21.02		1
	100	0	21.33	21.17	21.24		1
16QAM	1	0	21.35	20.99	21.28	0-1	1
	1	50	21.68	21.01	20.93		1
	1	99	21.78	21.24	20.87		1
	50	0	20.43	20.19	20.12	0-2	2
	50	25	20.38	20.08	20.08		2
	50	50	20.24	20.05	20.04		2
	100	0	20.30	20.07	20.28		2

Table 9-14
LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 2 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			18675 (1857.5 MHz)	18900 (1880.0 MHz)	19125 (1902.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.36	22.38	22.58	0	0
	1	36	22.26	22.21	22.17		0
	1	74	22.38	22.35	22.28		0
	36	0	21.40	21.34	21.35	0-1	1
	36	18	21.37	21.16	21.12		1
	36	37	21.34	21.23	21.13		1
	75	0	21.34	21.22	21.14		1
16QAM	1	0	21.72	21.43	21.54	0-1	1
	1	36	21.55	21.24	20.68		1
	1	74	21.65	21.21	20.80		1
	36	0	20.43	20.20	20.21	0-2	2
	36	18	20.29	20.00	20.12		2
	36	37	20.25	20.22	20.17		2
	75	0	20.28	20.19	20.11		2

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 32 of 62

Table 9-15
LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 2 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Frequency [MHz]	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			18650 (1855.0 MHz)	18900 (1880.0 MHz)	19150 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.42	22.33	22.28	0	0
	1	25	22.29	22.00	22.43		0
	1	49	22.57	22.55	22.16		0
	25	0	21.39	21.21	21.23	0-1	1
	25	12	21.37	21.14	21.13		1
	25	25	21.31	21.29	21.14		1
	50	0	21.34	21.24	21.17		1
16QAM	1	0	21.66	21.24	20.59	0-1	1
	1	25	21.48	21.36	20.51		1
	1	49	21.71	21.25	21.25		1
	25	0	20.33	20.16	20.30	0-2	2
	25	12	20.36	20.19	20.19		2
	25	25	20.39	20.29	20.17		2
	50	0	20.28	20.23	20.15		2

Table 9-16
LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 2 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	Frequency [MHz]	MPR Allowed per 3GPP [dB]	MPR [dB]
			18625 (1852.5 MHz)	18900 (1880.0 MHz)	19175 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.52	21.84	21.87	0	0
	1	12	22.39	21.86	21.96		0
	1	24	22.23	21.80	22.01		0
	12	0	21.27	21.15	21.05	0-1	1
	12	6	21.33	21.18	21.09		1
	12	13	21.33	21.22	21.17		1
	25	0	21.34	21.25	21.07		1
16QAM	1	0	21.42	21.00	21.31	0-1	1
	1	12	21.44	20.90	20.90		1
	1	24	21.26	20.96	21.25		1
	12	0	20.21	20.23	19.98	0-2	2
	12	6	20.20	20.20	19.96		2
	12	13	20.18	20.24	20.16		2
	25	0	20.22	20.26	20.22		2

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 33 of 62	

Table 9-17
LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 2 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18615 (1851.5 MHz)	18900 (1880.0 MHz)	19185 (1908.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.29	22.43	22.10	0	0
	1	7	22.36	22.16	22.13		0
	1	14	22.46	22.35	22.26		0
	8	0	21.28	21.20	21.11	0-1	1
	8	4	21.29	21.15	21.08		1
	8	7	21.30	21.19	21.14		1
	15	0	21.32	21.16	21.08		1
16QAM	1	0	21.50	21.32	20.76	0-1	1
	1	7	21.48	21.53	21.09		1
	1	14	21.46	21.10	20.69		1
	8	0	20.18	19.84	20.10	0-2	2
	8	4	20.19	20.07	20.17		2
	8	7	20.18	20.13	20.24		2
	15	0	19.82	20.27	20.18		2

Table 9-18
LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 2 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18607 (1850.7 MHz)	18900 (1880.0 MHz)	19193 (1909.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.08	22.23	22.08	0	0
	1	2	22.21	22.43	22.42		0
	1	5	22.17	22.35	22.38		0
	3	0	22.29	21.96	22.09		0
	3	2	22.36	22.10	22.11		0
	3	3	22.13	22.05	22.08		0
	6	0	21.22	21.07	21.07	0-1	1
16QAM	1	0	21.41	21.33	20.74	0-1	1
	1	2	21.42	21.29	20.95		1
	1	5	21.42	21.31	20.95		1
	3	0	21.35	21.01	20.59		1
	3	2	21.31	21.08	20.72		1
	3	3	21.24	21.05	20.85		1
	6	0	20.31	20.26	20.03	0-2	2

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 34 of 62

9.5 WLAN Conducted Powers

Table 9-19
2.4 GHz WLAN Maximum Average RF Power

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	15.67	13.69	13.38
2437	6	15.62	13.28	13.64
2462	11	16.15	13.22	13.99

Table 9-20
2.4 GHz WLAN Reduced Maximum Average RF Power – Held to Ear

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	12.06	9.62	9.73
2437	6	11.93	9.41	9.39
2462	11	12.04	9.26	9.54

Table 9-21
5 GHz WLAN Maximum Average RF Power 20 MHz Bandwidth

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11a	802.11n
5180	36	13.66	13.75
5200	40	13.84	13.89
5220	44	13.99	13.99
5240	48	13.98	13.99
5260	52	13.72	13.75
5280	56	13.85	13.91
5300	60	13.58	13.60
5320	64	13.28	13.28
5500	100	13.78	13.85
5600	120	13.67	13.73
5620	124	13.72	13.71
5720	144	13.71	13.78
5745	149	13.77	13.80
5785	157	13.70	13.75
5825	165	13.60	13.62

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 35 of 62

Table 9-22
5 GHz WLAN Reduced Maximum Average RF Power 20 MHz Bandwidth – Held to Ear

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11a	802.11n
5180	36	8.58	7.70
5200	40	8.30	7.92
5220	44	8.47	8.11
5240	48	8.40	8.07
5260	52	8.69	7.87
5280	56	8.72	8.96
5300	60	8.56	8.76
5320	64	8.58	8.62
5500	100	8.14	8.17
5600	120	8.52	7.82
5620	124	8.13	8.29
5720	144	8.86	8.63
5745	149	8.17	8.16
5785	157	8.10	8.22
5825	165	8.78	8.16

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-4
Power Measurement Setup for Bandwidths < 50 MHz

FCC ID: A3LSMJ320VPP	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 36 of 62

9.6 Bluetooth Conducted Powers

Table 9-23
Bluetooth RF Conducted Powers

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	10.75	11.883
2441	1.0	39	12.64	18.362
2480	1.0	78	10.24	10.559
2402	2.0	0	8.63	7.286
2441	2.0	39	10.42	11.018
2480	2.0	78	8.10	6.462
2402	3.0	0	8.64	7.317
2441	3.0	39	10.45	11.098
2480	3.0	78	8.15	6.531

Note: The bolded data rate and channel above was tested for SAR.




Figure 9-5
Power Measurement Setup

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 37 of 62

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Head Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
2/7/2016	750H	20.0	740	0.892	43.180	0.893	41.994	-0.11%	2.82%
			755	0.907	42.981	0.894	41.916	1.45%	2.54%
			770	0.924	42.786	0.895	41.838	3.24%	2.27%
			785	0.940	42.534	0.896	41.760	4.91%	1.85%
1/28/2016	835H	22.5	820	0.872	40.902	0.899	41.578	-3.00%	-1.63%
			835	0.885	40.687	0.900	41.500	-1.67%	-1.96%
			850	0.900	40.465	0.916	41.500	-1.75%	-2.49%
2/8/2016	835H	21.5	820	0.910	42.016	0.899	41.578	1.22%	1.05%
			835	0.925	41.838	0.900	41.500	2.78%	0.81%
			850	0.940	41.614	0.916	41.500	2.62%	0.27%
2/6/2016	1750H	22.5	1710	1.291	39.088	1.348	40.142	-4.23%	-2.63%
			1750	1.329	38.903	1.371	40.079	-3.06%	-2.93%
			1790	1.366	38.724	1.394	40.016	-2.01%	-3.23%
2/3/2016	1900H	23.3	1850	1.347	38.636	1.400	40.000	-3.79%	-3.41%
			1880	1.377	38.524	1.400	40.000	-1.64%	-3.69%
			1910	1.412	38.399	1.400	40.000	0.86%	-4.00%
2/17/2016	2450H	23.5	2400	1.799	39.200	1.756	39.289	2.45%	-0.23%
			2450	1.851	39.013	1.800	39.200	2.83%	-0.48%
			2500	1.906	38.831	1.855	39.136	2.75%	-0.78%
02/17/2016	5200H-5800H	21.8	5240	4.484	36.181	4.696	35.940	-4.51%	0.67%
			5260	4.489	36.115	4.717	35.917	-4.83%	0.55%
			5280	4.512	36.090	4.737	35.894	-4.75%	0.55%
			5600	4.886	35.801	5.065	35.529	-3.53%	0.77%
			5700	4.961	35.630	5.168	35.414	-4.01%	0.61%
			5745	4.972	35.567	5.214	35.363	-4.64%	0.58%
			5765	5.021	35.505	5.234	35.340	-4.07%	0.47%
			5825	5.075	35.422	5.296	35.271	-4.17%	0.43%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 38 of 62

Table 10-2
Measured Body Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
2/1/2016	750B	21.8	740	0.949	54.339	0.963	55.570	-1.45%	-2.22%
			755	0.967	54.219	0.964	55.512	0.31%	-2.33%
			770	0.979	54.021	0.965	55.453	1.45%	-2.58%
			785	0.993	53.804	0.966	55.395	2.80%	-2.87%
1/27/2016	835B	22.5	820	0.973	52.824	0.969	55.258	0.41%	-4.40%
			835	0.987	52.668	0.970	55.200	1.75%	-4.59%
			850	1.002	52.494	0.988	55.154	1.42%	-4.82%
2/8/2016	1750B	22.8	1710	1.450	51.417	1.463	53.537	-0.89%	-3.96%
			1750	1.494	51.287	1.488	53.432	0.40%	-4.01%
			1790	1.539	51.121	1.514	53.326	1.65%	-4.13%
2/1/2016	1900B	21.8	1850	1.520	51.666	1.520	53.300	0.00%	-3.07%
			1880	1.550	51.522	1.520	53.300	1.97%	-3.34%
			1910	1.590	51.453	1.520	53.300	4.61%	-3.47%
2/9/2016	1900B	23.1	1850	1.491	51.974	1.520	53.300	-1.91%	-2.49%
			1880	1.524	51.861	1.520	53.300	0.26%	-2.70%
			1910	1.562	51.782	1.520	53.300	2.76%	-2.85%
2/3/2016	2450B	22.5	2400	1.956	50.545	1.902	52.767	2.84%	-4.21%
			2450	2.024	50.380	1.950	52.700	3.79%	-4.40%
			2500	2.089	50.195	2.021	52.636	3.36%	-4.64%
2/22/2016	2450B	22.1	2400	1.938	51.241	1.902	52.767	1.89%	-2.89%
			2450	2.003	51.054	1.950	52.700	2.72%	-3.12%
			2500	2.072	50.834	2.021	52.636	2.52%	-3.42%
02/01/2016	5200B-5800B	21.8	5240	5.472	46.861	5.346	48.960	2.36%	-4.29%
			5260	5.494	46.817	5.369	48.933	2.33%	-4.32%
			5280	5.523	46.793	5.393	48.906	2.41%	-4.32%
			5500	5.847	46.578	5.650	48.607	3.49%	-4.17%
			5600	5.979	46.471	5.766	48.471	3.69%	-4.13%
			5745	6.126	46.156	5.936	48.275	3.20%	-4.39%
			5765	6.149	46.119	5.959	48.248	3.19%	-4.41%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 39 of 62

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
I	750	HEAD	02/07/2016	20.7	20.4	0.200	1054	3333	1.690	8.280	8.450	2.05%
J	835	HEAD	01/28/2016	21.6	22.5	0.200	4d133	3319	1.910	9.130	9.550	4.60%
C	835	HEAD	02/08/2016	22.1	21.5	0.200	4d132	3288	1.920	9.470	9.600	1.37%
C	1750	HEAD	02/06/2016	22.9	22.5	0.100	1008	3288	3.470	37.700	34.700	-7.96%
C	1900	HEAD	02/03/2016	24.5	23.3	0.100	5d148	3288	3.990	40.600	39.900	-1.72%
E	2450	HEAD	02/17/2016	23.2	22.0	0.100	719	3351	5.440	54.200	54.400	0.37%
A	5250	HEAD	02/17/2016	22.9	21.8	0.050	1057	3589	3.980	77.100	79.600	3.24%
A	5600	HEAD	02/17/2016	22.9	21.8	0.050	1057	3589	4.090	81.600	81.800	0.25%
A	5750	HEAD	02/17/2016	22.9	21.8	0.050	1057	3589	3.770	80.700	75.400	-6.57%
B	750	BODY	02/01/2016	23.3	22.1	0.200	1046	3287	1.580	8.290	7.900	-4.70%
E	835	BODY	01/27/2016	24.0	22.2	0.200	4d119	3351	1.900	9.200	9.500	3.26%
B	1750	BODY	02/08/2016	23.1	22.8	0.100	1008	3287	3.610	38.000	36.100	-5.00%
C	1900	BODY	02/01/2016	23.1	21.8	0.100	5d148	3288	4.070	40.200	40.700	1.24%
B	1900	BODY	02/09/2016	22.5	23.1	0.100	5d141	3287	3.820	40.000	38.200	-4.50%
B	2450	BODY	02/03/2016	23.5	22.5	0.100	882	3287	4.770	50.700	47.700	-5.92%
G	2450	BODY	02/22/2016	23.1	22.6	0.100	719	3334	5.470	51.900	54.700	5.39%
A	5250	BODY	02/01/2016	22.3	21.8	0.050	1057	3589	3.720	73.900	74.400	0.68%
A	5600	BODY	02/01/2016	22.3	21.8	0.050	1057	3589	3.830	79.000	76.600	-3.04%
A	5750	BODY	02/01/2016	23.1	22.7	0.050	1057	3589	3.730	74.100	74.600	0.67%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 40 of 62

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

**Table 11-1
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.0	31.75	-0.03	Right	Cheek	38596	1	1:8.3	0.285	1.334	0.380	A1
836.60	190	GSM 850	GSM	33.0	31.75	0.01	Right	Tilt	38596	1	1:8.3	0.149	1.334	0.199	
836.60	190	GSM 850	GSM	33.0	31.75	0.01	Left	Cheek	38596	1	1:8.3	0.277	1.334	0.370	
836.60	190	GSM 850	GSM	33.0	31.75	0.03	Left	Tilt	38596	1	1:8.3	0.151	1.334	0.201	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-2
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.0	29.22	-0.02	Right	Cheek	38596	1	1:8.3	0.286	1.197	0.342	
1880.00	661	GSM 1900	GSM	30.0	29.22	-0.08	Right	Tilt	38596	1	1:8.3	0.111	1.197	0.133	
1880.00	661	GSM 1900	GSM	30.0	29.22	-0.11	Left	Cheek	38596	1	1:8.3	0.485	1.197	0.581	A2
1880.00	661	GSM 1900	GSM	30.0	29.22	-0.06	Left	Tilt	38596	1	1:8.3	0.133	1.197	0.159	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-3
UMTS 850 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	22.5	21.97	-0.03	Right	Cheek	38414	1:1	0.260	1.130	0.294	A3
836.60	4183	UMTS 850	RMC	22.5	21.97	0.03	Right	Tilt	38414	1:1	0.150	1.130	0.170	
836.60	4183	UMTS 850	RMC	22.5	21.97	-0.05	Left	Cheek	38414	1:1	0.255	1.130	0.288	
836.60	4183	UMTS 850	RMC	22.5	21.97	-0.02	Left	Tilt	38414	1:1	0.144	1.130	0.163	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 41 of 62

Table 11-4
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.07	Right	Cheek	38414	1:1	0.389	1.130	0.440	
1880.00	9400	UMTS 1900	RMC	23.0	22.47	-0.07	Right	Tilt	38414	1:1	0.188	1.130	0.212	
1852.40	9262	UMTS 1900	RMC	23.0	22.58	-0.06	Left	Cheek	38414	1:1	0.783	1.102	0.863	A4
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.04	Left	Cheek	38414	1:1	0.779	1.130	0.880	
1907.60	9538	UMTS 1900	RMC	23.0	22.26	0.03	Left	Cheek	38414	1:1	0.754	1.186	0.894	
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.00	Left	Tilt	38414	1:1	0.182	1.130	0.206	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-5
Cell CDMA Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	Cell. CDMA	RC3 / SO55	24.7	24.27	-0.05	Right	Cheek	38414	1:1	0.503	1.104	0.555	
836.52	384	Cell. CDMA	RC3 / SO55	24.7	24.27	0.01	Right	Tilt	38414	1:1	0.268	1.104	0.296	
836.52	384	Cell. CDMA	RC3 / SO55	24.7	24.27	0.09	Left	Cheek	38414	1:1	0.504	1.104	0.556	A5
836.52	384	Cell. CDMA	RC3 / SO55	24.7	24.27	-0.02	Left	Tilt	38414	1:1	0.286	1.104	0.316	
836.52	384	Cell. CDMA	EVDO Rev. A	24.7	24.22	0.08	Right	Cheek	38414	1:1	0.432	1.117	0.483	
836.52	384	Cell. CDMA	EVDO Rev. A	24.7	24.22	0.01	Right	Tilt	38414	1:1	0.215	1.117	0.240	
836.52	384	Cell. CDMA	EVDO Rev. A	24.7	24.22	-0.03	Left	Cheek	38414	1:1	0.464	1.117	0.518	
836.52	384	Cell. CDMA	EVDO Rev. A	24.7	24.22	0.00	Left	Tilt	38414	1:1	0.239	1.117	0.267	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-6
PCS CDMA Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	22.2	21.98	0.13	Right	Cheek	38414	1:1	0.298	1.052	0.313	
1880.00	600	PCS CDMA	RC3 / SO55	22.2	21.98	-0.04	Right	Tilt	38414	1:1	0.125	1.052	0.132	
1880.00	600	PCS CDMA	RC3 / SO55	22.2	21.98	-0.01	Left	Cheek	38414	1:1	0.511	1.052	0.538	A6
1880.00	600	PCS CDMA	RC3 / SO55	22.2	21.98	0.04	Left	Tilt	38414	1:1	0.114	1.052	0.120	
1880.00	600	PCS CDMA	EVDO Rev. A	22.2	21.97	0.07	Right	Cheek	38414	1:1	0.317	1.054	0.334	
1880.00	600	PCS CDMA	EVDO Rev. A	22.2	21.97	0.13	Right	Tilt	38414	1:1	0.124	1.054	0.131	
1880.00	600	PCS CDMA	EVDO Rev. A	22.2	21.97	-0.10	Left	Cheek	38414	1:1	0.490	1.054	0.516	
1880.00	600	PCS CDMA	EVDO Rev. A	22.2	21.97	0.05	Left	Tilt	38414	1:1	0.122	1.054	0.129	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 42 of 62

Table 11-7
LTE Band 13 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	-0.02	0	Right	Cheek	QPSK	1	0	41970	1:1	0.362	1.030	0.373	A7
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	0.15	1	Right	Cheek	QPSK	25	0	41970	1:1	0.265	1.076	0.285	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	0.07	1	Right	Cheek	QPSK	50	0	41970	1:1	0.271	1.045	0.283	
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	0.14	0	Right	Tilt	QPSK	1	0	41970	1:1	0.204	1.030	0.210	
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	0.04	1	Right	Tilt	QPSK	25	0	41970	1:1	0.152	1.076	0.164	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	0.06	1	Right	Tilt	QPSK	50	0	41970	1:1	0.168	1.045	0.176	
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	0.00	0	Left	Cheek	QPSK	1	0	41970	1:1	0.326	1.030	0.336	
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	0.11	1	Left	Cheek	QPSK	25	0	41970	1:1	0.259	1.076	0.279	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	0.07	1	Left	Cheek	QPSK	50	0	41970	1:1	0.250	1.045	0.261	
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	0.01	0	Left	Tilt	QPSK	1	0	41970	1:1	0.184	1.030	0.190	
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	0.00	1	Left	Tilt	QPSK	25	0	41970	1:1	0.150	1.076	0.161	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	0.07	1	Left	Tilt	QPSK	50	0	41970	1:1	0.151	1.045	0.158	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-8
LTE Band 5 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	0.19	0	Right	Cheek	QPSK	1	49	41970	1:1	0.314	1.009	0.317	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	0.00	1	Right	Cheek	QPSK	25	25	41970	1:1	0.218	1.107	0.241	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	-0.02	0	Right	Tilt	QPSK	1	49	41970	1:1	0.133	1.009	0.134	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	0.09	1	Right	Tilt	QPSK	25	25	41970	1:1	0.092	1.107	0.102	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	-0.04	0	Left	Cheek	QPSK	1	49	41970	1:1	0.350	1.009	0.353	A8
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	-0.13	1	Left	Cheek	QPSK	25	25	41970	1:1	0.246	1.107	0.272	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	0.05	0	Left	Tilt	QPSK	1	49	41970	1:1	0.152	1.009	0.153	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	-0.02	1	Left	Tilt	QPSK	25	25	41970	1:1	0.106	1.107	0.117	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-9
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	0.04	0	Right	Cheek	QPSK	1	0	41970	1:1	0.313	1.067	0.334	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	0.08	1	Right	Cheek	QPSK	50	0	41970	1:1	0.251	1.132	0.284	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	-0.07	0	Right	Tilt	QPSK	1	0	41970	1:1	0.106	1.067	0.113	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	0.02	1	Right	Tilt	QPSK	50	0	41970	1:1	0.086	1.132	0.097	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	-0.13	0	Left	Cheek	QPSK	1	0	41970	1:1	0.616	1.067	0.657	A9
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	-0.02	1	Left	Cheek	QPSK	50	0	41970	1:1	0.499	1.132	0.565	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	0.08	0	Left	Tilt	QPSK	1	0	41970	1:1	0.172	1.067	0.184	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	0.01	1	Left	Tilt	QPSK	50	0	41970	1:1	0.138	1.132	0.156	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 43 of 62

Table 11-10
LTE Band 2 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	-0.11	0	Right	Cheek	QPSK	1	0	41970	1:1	0.353	1.094	0.386	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	0.08	1	Right	Cheek	QPSK	50	0	41970	1:1	0.281	1.119	0.314	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	0.04	0	Right	Tilt	QPSK	1	0	41970	1:1	0.143	1.094	0.156	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	0.05	1	Right	Tilt	QPSK	50	0	41970	1:1	0.111	1.119	0.124	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	0.03	0	Left	Cheek	QPSK	1	0	41970	1:1	0.848	1.094	0.928	A10
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.0	22.40	0.00	0	Left	Cheek	QPSK	1	0	41970	1:1	0.795	1.148	0.913	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.0	22.24	0.07	0	Left	Cheek	QPSK	1	0	41970	1:1	0.776	1.191	0.924	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	0.03	1	Left	Cheek	QPSK	50	0	41970	1:1	0.606	1.119	0.678	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.33	-0.06	1	Left	Cheek	QPSK	100	0	41970	1:1	0.531	1.167	0.620	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	-0.02	0	Left	Tilt	QPSK	1	0	41970	1:1	0.183	1.094	0.200	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	-0.03	1	Left	Tilt	QPSK	50	0	41970	1:1	0.144	1.119	0.161	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-11
DTS Head SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	12.5	12.06	-	Right	Cheek	38422	1	99.8	0.191	-	1.107	1.002	-	
2412	1	802.11b	DSSS	22	12.5	12.06	-	Right	Tilt	38422	1	99.8	0.140	-	1.107	1.002	-	
2412	1	802.11b	DSSS	22	12.5	12.06	0.01	Left	Cheek	38422	1	99.8	0.298	0.248	1.107	1.002	0.276	A11
2412	1	802.11b	DSSS	22	12.5	12.06	-	Left	Tilt	38422	1	99.8	0.202	-	1.107	1.002	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-12
NII Head SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5280	56	802.11a	OFDM	20	9.0	8.72	-	Right	Cheek	38422	6	98.6	0.370	-	1.067	1.014	-	
5280	56	802.11a	OFDM	20	9.0	8.72	-	Right	Tilt	38422	6	98.6	0.328	-	1.067	1.014	-	
5280	56	802.11a	OFDM	20	9.0	8.72	0.05	Left	Cheek	38422	6	98.6	0.423	0.193	1.067	1.014	0.209	
5280	56	802.11a	OFDM	20	9.0	8.72	-	Left	Tilt	38422	6	98.6	0.417	-	1.067	1.014	-	
5720	144	802.11a	OFDM	20	9.0	8.86	-	Right	Cheek	38422	6	98.6	0.354	-	1.033	1.014	-	
5720	144	802.11a	OFDM	20	9.0	8.86	-	Right	Tilt	38422	6	98.6	0.254	-	1.033	1.014	-	
5720	144	802.11a	OFDM	20	9.0	8.86	-0.04	Left	Cheek	38422	6	98.6	0.624	0.199	1.033	1.014	0.209	A12
5720	144	802.11a	OFDM	20	9.0	8.86	-	Left	Tilt	38422	6	98.6	0.373	-	1.033	1.014	-	
5825	165	802.11a	OFDM	20	9.0	8.78	-	Right	Cheek	38422	6	98.6	0.223	-	1.052	1.014	-	
5825	165	802.11a	OFDM	20	9.0	8.78	-	Right	Tilt	38422	6	98.6	0.177	-	1.052	1.014	-	
5825	165	802.11a	OFDM	20	9.0	8.78	0.02	Left	Cheek	38422	6	98.6	0.375	0.127	1.052	1.014	0.136	
5825	165	802.11a	OFDM	20	9.0	8.78	-	Left	Tilt	38422	6	98.6	0.280	-	1.052	1.014	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 44 of 62

11.1 Standalone Body-Worn SAR Data

Table 11-13
GSM/UMTS/CDMA Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maxim um Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.0	31.75	0.02	10 mm	38414	1	1:8.3	back	0.463	1.334	0.618	A13
1880.00	661	GSM 1900	GSM	30.0	29.22	0.06	10 mm	38956	1	1:8.3	back	0.423	1.197	0.506	A15
836.60	4183	UMTS 850	RMC	22.5	21.97	0.03	10 mm	38414	N/A	1:1	back	0.470	1.130	0.531	A17
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.06	10 mm	38414	N/A	1:1	back	0.628	1.130	0.710	A18
836.52	384	Cell. CDMA	TDSO / SO32	24.7	24.29	0.05	10 mm	41970	N/A	1:1	back	0.563	1.099	0.619	A20
1851.25	25	PCS CDMA	TDSO / SO32	24.7	24.47	0.02	10 mm	38414	N/A	1:1	back	0.836	1.054	0.881	A22
1880.00	600	PCS CDMA	TDSO / SO32	24.7	24.36	-0.02	10 mm	38414	N/A	1:1	back	0.753	1.081	0.814	
1908.75	1175	PCS CDMA	TDSO / SO32	24.7	24.38	-0.08	10 mm	38414	N/A	1:1	back	0.702	1.076	0.755	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-14
LTE Body-Worn SAR Data

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	0.07	0	41970	QPSK	1	0	10 mm	back	1:1	0.505	1.030	0.520	A24
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	-0.04	1	41970	QPSK	25	0	10 mm	back	1:1	0.410	1.076	0.441	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	0.02	1	41970	QPSK	50	0	10 mm	back	1:1	0.417	1.045	0.436	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	0.03	0	41970	QPSK	1	49	10 mm	back	1:1	0.387	1.009	0.390	A25
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	-0.03	1	41970	QPSK	25	25	10 mm	back	1:1	0.274	1.107	0.303	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	0.15	0	41970	QPSK	1	0	10 mm	back	1:1	0.846	1.067	0.903	A26
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	0.03	1	41970	QPSK	50	0	10 mm	back	1:1	0.654	1.132	0.740	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.40	0.01	1	41970	QPSK	100	0	10 mm	back	1:1	0.622	1.148	0.714	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	-0.07	0	41970	QPSK	1	0	10 mm	back	1:1	0.838	1.067	0.894	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	0.05	0	41970	QPSK	1	0	10 mm	back	1:1	0.627	1.094	0.686	A27
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	0.00	1	41970	QPSK	50	0	10 mm	back	1:1	0.448	1.119	0.501	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak									Body 1.6 W/kg (mW/g) averaged over 1 gram										
Uncontrolled Exposure/General Population																			

Note: Blue Entry represents variability measurement

Table 11-15
DTS Body-Worn SAR Data

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	16.5	16.15	-0.04	10 mm	41970	1	back	99.8	0.155	0.127	1.084	1.002	0.138	A29
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMJ320VPP			SAR EVALUATION REPORT				Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16		DUT Type: Portable Handset				Page 45 of 62

Table 11-16
NII Body-Worn SAR Data

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5280	56	802.11a	OFDM	20	14.0	13.85	-0.07	10 mm	41970	6	back	98.6	0.666	0.277	1.035	1.014	0.291	
5500	100	802.11a	OFDM	20	14.0	13.78	-0.09	10 mm	41970	6	back	98.6	0.881	0.411	1.052	1.014	0.438	A31
5745	149	802.11a	OFDM	20	14.0	13.77	-0.03	10 mm	41970	6	back	98.6	0.533	0.201	1.054	1.014	0.215	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-17
Bluetooth Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2441	39	Bluetooth	FHSS	13.0	12.64	-0.13	10 mm	41970	1	back	1:1	0.044	1.086	0.048	A33
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 46 of 62

11.2 Standalone Hotspot SAR Data

Table 11-18
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	27.5	26.96	-0.05	10 mm	38414	4	1:2.076	back	0.548	1.132	0.620	A14
836.60	190	GSM 850	GPRS	27.5	26.96	0.03	10 mm	38414	4	1:2.076	front	0.434	1.132	0.491	
836.60	190	GSM 850	GPRS	27.5	26.96	0.08	10 mm	38414	4	1:2.076	bottom	0.043	1.132	0.049	
836.60	190	GSM 850	GPRS	27.5	26.96	0.00	10 mm	38414	4	1:2.076	right	0.320	1.132	0.362	
836.60	190	GSM 850	GPRS	27.5	26.96	-0.04	10 mm	38414	4	1:2.076	left	0.326	1.132	0.369	
1909.80	810	GSM 1900	GPRS	25.0	24.60	0.02	10 mm	38956	4	1:2.076	back	0.400	1.096	0.438	
1909.80	810	GSM 1900	GPRS	25.0	24.60	-0.01	10 mm	38956	4	1:2.076	front	0.406	1.096	0.445	A16
1909.80	810	GSM 1900	GPRS	25.0	24.60	-0.02	10 mm	38956	4	1:2.076	bottom	0.141	1.096	0.155	
1909.80	810	GSM 1900	GPRS	25.0	24.60	-0.14	10 mm	38956	4	1:2.076	right	0.085	1.096	0.093	
1909.80	810	GSM 1900	GPRS	25.0	24.60	-0.06	10 mm	38956	4	1:2.076	left	0.380	1.096	0.416	
836.60	4183	UMTS 850	RMC	22.5	21.97	0.03	10 mm	38414	N/A	1:1	back	0.470	1.130	0.531	A17
836.60	4183	UMTS 850	RMC	22.5	21.97	0.09	10 mm	38414	N/A	1:1	front	0.374	1.130	0.423	
836.60	4183	UMTS 850	RMC	22.5	21.97	-0.02	10 mm	38414	N/A	1:1	bottom	0.041	1.130	0.046	
836.60	4183	UMTS 850	RMC	22.5	21.97	-0.03	10 mm	38414	N/A	1:1	right	0.314	1.130	0.355	
836.60	4183	UMTS 850	RMC	22.5	21.97	0.01	10 mm	38414	N/A	1:1	left	0.306	1.130	0.346	
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.06	10 mm	38414	N/A	1:1	back	0.628	1.130	0.710	
1852.40	9262	UMTS 1900	RMC	23.0	22.58	0.02	10 mm	38414	N/A	1:1	front	0.947	1.102	1.044	A19
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.00	10 mm	38414	N/A	1:1	front	0.862	1.130	0.974	
1907.60	9538	UMTS 1900	RMC	23.0	22.26	0.04	10 mm	38414	N/A	1:1	front	0.847	1.186	1.005	
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.02	10 mm	38414	N/A	1:1	bottom	0.215	1.130	0.243	
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.10	10 mm	38414	N/A	1:1	right	0.151	1.130	0.171	
1880.00	9400	UMTS 1900	RMC	23.0	22.47	0.04	10 mm	38414	N/A	1:1	left	0.699	1.130	0.790	
836.52	384	Cell. CDMA	EVDO Rev. 0	24.7	24.31	0.07	10 mm	41970	N/A	1:1	back	0.554	1.094	0.606	A21
836.52	384	Cell. CDMA	EVDO Rev. 0	24.7	24.31	-0.04	10 mm	41970	N/A	1:1	front	0.457	1.094	0.500	
836.52	384	Cell. CDMA	EVDO Rev. 0	24.7	24.31	0.05	10 mm	41970	N/A	1:1	bottom	0.076	1.094	0.083	
836.52	384	Cell. CDMA	EVDO Rev. 0	24.7	24.31	-0.05	10 mm	41970	N/A	1:1	right	0.389	1.094	0.426	
836.52	384	Cell. CDMA	EVDO Rev. 0	24.7	24.31	-0.02	10 mm	41970	N/A	1:1	left	0.265	1.094	0.290	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.37	0.12	10 mm	38414	N/A	1:1	back	0.704	1.079	0.760	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.7	24.49	-0.13	10 mm	38414	N/A	1:1	front	0.907	1.050	0.952	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.37	0.02	10 mm	38414	N/A	1:1	front	0.837	1.079	0.903	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.32	0.00	10 mm	38414	N/A	1:1	front	0.959	1.091	1.046	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.37	0.09	10 mm	38414	N/A	1:1	bottom	0.230	1.079	0.248	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.37	-0.05	10 mm	38414	N/A	1:1	right	0.161	1.079	0.174	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.37	0.03	10 mm	38414	N/A	1:1	left	0.677	1.079	0.730	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.32	-0.06	10 mm	38414	N/A	1:1	front	0.969	1.091	1.057	A23
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Blue Entry represents variability measurement

FCC ID: A3LSMJ320VPP	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 47 of 62

Table 11-19
LTE Band 13 Hotspot SAR Data

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	0.07	0	41970	QPSK	1	0	10 mm	back	1:1	0.505	1.030	0.520	A24
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	-0.04	1	41970	QPSK	25	0	10 mm	back	1:1	0.410	1.076	0.441	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	0.02	1	41970	QPSK	50	0	10 mm	back	1:1	0.417	1.045	0.436	
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	-0.02	0	41970	QPSK	1	0	10 mm	front	1:1	0.407	1.030	0.419	
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	-0.02	1	41970	QPSK	25	0	10 mm	front	1:1	0.327	1.076	0.352	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	0.02	1	41970	QPSK	50	0	10 mm	front	1:1	0.336	1.045	0.351	
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	-0.16	0	41970	QPSK	1	0	10 mm	bottom	1:1	0.043	1.030	0.044	
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	0.04	1	41970	QPSK	25	0	10 mm	bottom	1:1	0.034	1.076	0.037	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	-0.05	1	41970	QPSK	50	0	10 mm	bottom	1:1	0.034	1.045	0.036	
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	-0.12	0	41970	QPSK	1	0	10 mm	right	1:1	0.252	1.030	0.260	
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	0.07	1	41970	QPSK	25	0	10 mm	right	1:1	0.194	1.076	0.209	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	-0.12	1	41970	QPSK	50	0	10 mm	right	1:1	0.219	1.045	0.229	
782.00	23230	Mid	LTE Band 13	10	23.5	23.37	0.13	0	41970	QPSK	1	0	10 mm	left	1:1	0.189	1.030	0.195	
782.00	23230	Mid	LTE Band 13	10	22.5	22.18	0.03	1	41970	QPSK	25	0	10 mm	left	1:1	0.155	1.076	0.167	
782.00	23230	Mid	LTE Band 13	10	22.5	22.31	0.08	1	41970	QPSK	50	0	10 mm	left	1:1	0.178	1.045	0.186	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-20
LTE Band 5 (Cell) Hotspot SAR Data

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																(W/kg)		(W/kg)	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	0.03	0	41970	QPSK	1	49	10 mm	back	1:1	0.387	1.009	0.390	A25
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	-0.03	1	41970	QPSK	25	25	10 mm	back	1:1	0.274	1.107	0.303	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	-0.02	0	41970	QPSK	1	49	10 mm	front	1:1	0.328	1.009	0.331	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	0.03	1	41970	QPSK	25	25	10 mm	front	1:1	0.234	1.107	0.259	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	-0.08	0	41970	QPSK	1	49	10 mm	bottom	1:1	0.054	1.009	0.054	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	0.10	1	41970	QPSK	25	25	10 mm	bottom	1:1	0.038	1.107	0.042	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	0.12	0	41970	QPSK	1	49	10 mm	right	1:1	0.242	1.009	0.244	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	-0.14	1	41970	QPSK	25	25	10 mm	right	1:1	0.185	1.107	0.205	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.46	0.12	0	41970	QPSK	1	49	10 mm	left	1:1	0.171	1.009	0.173	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.06	-0.03	1	41970	QPSK	25	25	10 mm	left	1:1	0.124	1.107	0.137	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body 1.6 W/kg (mW/g) averaged over 1 gram											
Spatial Peak Uncontrolled Exposure/General Population																			

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 48 of 62

Table 11-21
LTE Band 4 (AWS) Hotspot SAR Data

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	0.15	0	41970	QPSK	1	0	10 mm	back	1:1	0.846	1.067	0.903	A26
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	0.03	1	41970	QPSK	50	0	10 mm	back	1:1	0.654	1.132	0.740	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.40	0.01	1	41970	QPSK	100	0	10 mm	back	1:1	0.622	1.148	0.714	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	-0.03	0	41970	QPSK	1	0	10 mm	front	1:1	0.828	1.067	0.883	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	0.05	1	41970	QPSK	50	0	10 mm	front	1:1	0.615	1.132	0.696	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.40	0.02	1	41970	QPSK	100	0	10 mm	front	1:1	0.583	1.148	0.669	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	0.02	0	41970	QPSK	1	0	10 mm	bottom	1:1	0.157	1.067	0.168	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	-0.07	1	41970	QPSK	50	0	10 mm	bottom	1:1	0.114	1.132	0.129	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	-0.09	0	41970	QPSK	1	0	10 mm	right	1:1	0.106	1.067	0.113	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	-0.09	1	41970	QPSK	50	0	10 mm	right	1:1	0.074	1.132	0.084	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	-0.02	0	41970	QPSK	1	0	10 mm	left	1:1	0.530	1.067	0.566	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.46	-0.08	1	41970	QPSK	50	0	10 mm	left	1:1	0.389	1.132	0.440	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.72	-0.07	0	41970	QPSK	1	0	10 mm	back	1:1	0.838	1.067	0.894	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue Entry represents variability measurement

Table 11-22
LTE Band 2 (PCS) Hotspot SAR Data

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	0.05	0	41970	QPSK	1	0	10 mm	back	1:1	0.627	1.094	0.686	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	0.00	1	41970	QPSK	50	0	10 mm	back	1:1	0.448	1.119	0.501	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	-0.02	0	41970	QPSK	1	0	10 mm	front	1:1	0.678	1.094	0.742	A28
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	0.02	1	41970	QPSK	50	0	10 mm	front	1:1	0.502	1.119	0.562	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	0.03	0	41970	QPSK	1	0	10 mm	bottom	1:1	0.191	1.094	0.209	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	-0.05	1	41970	QPSK	50	0	10 mm	bottom	1:1	0.144	1.119	0.161	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	0.00	0	41970	QPSK	1	0	10 mm	right	1:1	0.142	1.094	0.155	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	-0.04	1	41970	QPSK	50	0	10 mm	right	1:1	0.098	1.119	0.110	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.0	22.61	-0.02	0	41970	QPSK	1	0	10 mm	left	1:1	0.651	1.094	0.712	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.0	21.51	-0.09	1	41970	QPSK	50	0	10 mm	left	1:1	0.480	1.119	0.537	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-23
WLAN Hotspot SAR Data

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	16.5	16.15	-	10 mm	41970	1	back	99.8	0.155	-	1.084	1.002	-	
2462	11	802.11b	DSSS	22	16.5	16.15	-0.11	10 mm	41970	1	front	99.8	0.204	0.154	1.084	1.002	0.167	A30
2462	11	802.11b	DSSS	22	16.5	16.15	-	10 mm	41970	1	top	99.8	0.120	-	1.084	1.002	-	
2462	11	802.11b	DSSS	22	16.5	16.15	-	10 mm	41970	1	right	99.8	0.056	-	1.084	1.002	-	
5745	149	802.11a	OFDM	20	14.0	13.77	-0.03	10 mm	41970	6	back	98.6	0.533	0.201	1.054	1.014	0.215	A32
5745	149	802.11a	OFDM	20	14.0	13.77	-	10 mm	41970	6	front	98.6	0.299	-	1.054	1.014	-	
5745	149	802.11a	OFDM	20	14.0	13.77	-	10 mm	41970	6	top	98.6	0.269	-	1.054	1.014	-	
5745	149	802.11a	OFDM	20	14.0	13.77	-	10 mm	41970	6	right	98.6	0.011	-	1.054	1.014	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																		
Spatial Peak								Body										
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 49 of 62

11.3 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03r01.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO Rev0 and RevA and TDSO / SO32 FCH+SCH SAR tests were not required per the 3G SAR Test Reduction Procedure in FCC KDB Publication 941225 D01v03r01.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 50 of 62

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI)..

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.7.6 for more information.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 51 of 62

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g SAR.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 52 of 62

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.380	0.276	0.656
	GSM 1900	0.581	0.276	0.857
	UMTS 850	0.294	0.276	0.570
	UMTS 1900	0.894	0.276	1.170
	Cell. CDMA/EVDO	0.556	0.276	0.832
	PCS CDMA/EVDO	0.538	0.276	0.814
	LTE Band 13	0.373	0.276	0.649
	LTE Band 5 (Cell)	0.353	0.276	0.629
	LTE Band 4 (AWS)	0.657	0.276	0.933
	LTE Band 2 (PCS)	0.928	0.276	1.204

Table 12-2
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.380	0.209	0.589
	GSM 1900	0.581	0.209	0.790
	UMTS 850	0.294	0.209	0.503
	UMTS 1900	0.894	0.209	1.103
	Cell. CDMA/EVDO	0.556	0.209	0.765
	PCS CDMA/EVDO	0.538	0.209	0.747
	LTE Band 13	0.373	0.209	0.582
	LTE Band 5 (Cell)	0.353	0.209	0.562
	LTE Band 4 (AWS)	0.657	0.209	0.866
	LTE Band 2 (PCS)	0.928	0.209	1.137

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 53 of 62

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-3
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.618	0.138	0.756
	GSM 1900	0.506	0.138	0.644
	UMTS 850	0.531	0.138	0.669
	UMTS 1900	0.710	0.138	0.848
	Cell. CDMA	0.619	0.138	0.757
	PCS CDMA	0.881	0.138	1.019
	LTE Band 13	0.520	0.138	0.658
	LTE Band 5 (Cell)	0.390	0.138	0.528
	LTE Band 4 (AWS)	0.903	0.138	1.041
	LTE Band 2 (PCS)	0.686	0.138	0.824

Table 12-4
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.618	0.438	1.056
	GSM 1900	0.506	0.438	0.944
	UMTS 850	0.531	0.438	0.969
	UMTS 1900	0.710	0.438	1.148
	Cell. CDMA	0.619	0.438	1.057
	PCS CDMA	0.881	0.438	1.319
	LTE Band 13	0.520	0.438	0.958
	LTE Band 5 (Cell)	0.390	0.438	0.828
	LTE Band 4 (AWS)	0.903	0.438	1.341
	LTE Band 2 (PCS)	0.686	0.438	1.124

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 54 of 62

Table 12-5
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.618	0.048	0.666
	GSM 1900	0.506	0.048	0.554
	UMTS 850	0.531	0.048	0.579
	UMTS 1900	0.710	0.048	0.758
	Cell. CDMA	0.619	0.048	0.667
	PCS CDMA	0.881	0.048	0.929
	LTE Band 13	0.520	0.048	0.568
	LTE Band 5 (Cell)	0.390	0.048	0.438
	LTE Band 4 (AWS)	0.903	0.048	0.951
	LTE Band 2 (PCS)	0.686	0.048	0.734

12.5 Hotspot SAR Simultaneous Transmission Analysis

Table 12-6
Simultaneous Transmission Scenario (2.4 GHz Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.620	0.167	0.787
	GPRS 1900	0.445	0.167	0.612
	UMTS 850	0.531	0.167	0.698
	UMTS 1900	1.044	0.167	1.211
	Cell. EVDO	0.606	0.167	0.773
	PCS EVDO	1.057	0.167	1.224
	LTE Band 13	0.520	0.167	0.687
	LTE Band 5 (Cell)	0.390	0.167	0.557
	LTE Band 4 (AWS)	0.903	0.167	1.070
	LTE Band 2 (PCS)	0.742	0.167	0.909

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 55 of 62

Table 12-7
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.620	0.215	0.835
	GPRS 1900	0.445	0.215	0.660
	UMTS 850	0.531	0.215	0.746
	UMTS 1900	1.044	0.215	1.259
	Cell. EVDO	0.606	0.215	0.821
	PCS EVDO	1.057	0.215	1.272
	LTE Band 13	0.520	0.215	0.735
	LTE Band 5 (Cell)	0.390	0.215	0.605
	LTE Band 4 (AWS)	0.903	0.215	1.118
	LTE Band 2 (PCS)	0.742	0.215	0.957

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: A3LSMJ320VPP	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 56 of 62

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1908.75	1175	PCS CDMA	EVDO Rev. 0	front	10 mm	0.959	0.969	1.01	N/A	N/A	N/A	N/A
1750	1732.50	20175	LTE Band 4 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	back	10 mm	0.846	0.838	1.01	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body							
Spatial Peak						1.6 W/kg (mW/g)							
Uncontrolled Exposure/General Population						averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMJ320VPP	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 57 of 62

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
SPEAG	D750V3	750 MHz SAR Dipole	3/11/2015	Annual	3/11/2016	1054
SPEAG	D750V3	750 MHz SAR Dipole	2/19/2015	Annual	2/19/2016	1046
SPEAG	D835V2	835 MHz SAR Dipole	4/13/2015	Annual	4/13/2016	4d119
SPEAG	D835V2	835 MHz SAR Dipole	1/20/2016	Annual	1/20/2017	4d132
SPEAG	D835V2	835 MHz SAR Dipole	7/23/2015	Annual	7/23/2016	4d133
SPEAG	D1765V2	1765 MHz SAR Dipole	5/13/2015	Annual	5/13/2016	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	4/14/2015	Annual	4/14/2016	5d141
SPEAG	D1900V2	1900 MHz SAR Dipole	2/18/2015	Annual	2/18/2016	5d148
SPEAG	D2450V2	2450 MHz SAR Dipole	8/20/2015	Annual	8/20/2016	719
SPEAG	D2450V2	2450 MHz SAR Dipole	2/18/2015	Annual	2/18/2016	882
SPEAG	D5GHzV2	5 GHz SAR Dipole	1/19/2016	Annual	1/19/2017	1057
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/24/2015	Annual	8/24/2016	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/27/2015	Annual	10/27/2016	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/18/2015	Annual	9/18/2016	1364
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/13/2015	Annual	3/13/2016	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/20/2015	Annual	10/20/2016	1408
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/11/2015	Annual	11/11/2016	1415
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/15/2016	Annual	1/15/2017	1466
SPEAG	ES3DV3	SAR Probe	10/29/2015	Annual	10/29/2016	3287
SPEAG	ES3DV3	SAR Probe	9/18/2015	Annual	9/18/2016	3288
SPEAG	ES3DV3	SAR Probe	3/19/2015	Annual	3/19/2016	3319
SPEAG	ES3DV3	SAR Probe	10/29/2015	Annual	10/29/2016	3333
SPEAG	ES3DV3	SAR Probe	11/17/2015	Annual	11/17/2016	3334
SPEAG	ES3DV3	SAR Probe	6/22/2015	Annual	6/22/2016	3351
SPEAG	EX3DV4	SAR Probe	1/20/2016	Annual	1/20/2017	3589
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/12/2015	Annual	5/12/2016	1070
Rohde & Schwarz	CMW500	Radio Communication Tester	5/15/2015	Annual	5/15/2016	112347
Rohde & Schwarz	CMW500	Radio Communication Tester	7/21/2015	Annual	7/21/2016	116743
Pasternack	NC-100	Torque Wrench	5/21/2015	Biennial	5/21/2017	N/A
Pasternack	NC-100	Torque Wrench	5/21/2015	Biennial	5/21/2017	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264165
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Control Company	4040	Digital Thermometer	3/18/2015	Biennial	3/18/2017	150195001
Control Company	4040	Digital Thermometer	3/15/2015	Biennial	3/15/2017	150195005
Control Company	4353	Long Stem Thermometer	1/22/2015	Biennial	1/22/2017	150053029
Control Company	4353	Long Stem Thermometer	1/22/2015	Biennial	1/22/2017	150053036
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Anritsu	MA24106A	USB Power Sensor	3/11/2015	Annual	3/11/2016	1344554
Anritsu	MA24106A	USB Power Sensor	3/2/2015	Annual	3/2/2016	1344555
Anritsu	MA2411B	Pulse Power Sensor	3/13/2015	Annual	3/13/2016	1207470
Anritsu	MA2411B	Pulse Power Sensor	12/7/2015	Annual	12/7/2016	1339018
Anritsu	MA2481A	Power Sensor	3/10/2015	Annual	3/10/2016	5821
Anritsu	ML2438A	Power Meter	3/13/2015	Annual	3/13/2016	1190013
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	1039008
Anritsu	ML2496A	Power Meter	3/13/2015	Annual	3/13/2016	1306009
Anritsu	MT8820C	Radio Communication Analyzer	6/12/2015	Annual	6/12/2016	6201240328
Anritsu	MT8820C	Radio Communication Analyzer	12/4/2015	Annual	12/4/2016	6201300731
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433975
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	CBT	N/A	CBT	3051A00187
Agilent	8648D	(9kHz-4GHz) Signal Generator	3/15/2015	Annual	3/15/2016	3629U00687
Agilent	8753ES	Network Analyzer	3/20/2015	Annual	3/20/2016	MY40001472
Agilent	E4432B	ESG-D Series Signal Generator	3/16/2015	Annual	3/16/2016	US40053896
Agilent	E4438C	ESG Vector Signal Generator	4/1/2014	Biennial	4/1/2016	MY47270002
Agilent	E5515C	Wireless Communications Test Set	4/13/2015	Annual	4/13/2016	GB43460554
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/15/2015	Annual	3/15/2016	MY45470194
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB46170464
Agilent	N5182A	MXG Vector Signal Generator	3/16/2015	Annual	3/16/2016	MY47420651
Agilent	N9020A	MXA Signal Analyzer	11/5/2015	Annual	11/5/2016	US46470561

All Equipment was used solely within its valid calibration period.

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 58 of 62

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)						RSS	11.5	11.3
Expanded Uncertainty (95% CONFIDENCE LEVEL)						k=2	23.0	22.6

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 59 of 62

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMJ320VPP		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset		Page 60 of 62

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMJ320VPP	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 61 of 62

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMJ320VPP	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1601280163-R1.A3L	Test Dates: 01/27/16 - 02/22/16	DUT Type: Portable Handset	Page 62 of 62

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38596

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.927 \text{ S/m}$; $\epsilon_r = 41.814$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-08-2016; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3288; ConvF(6.41, 6.41, 6.41); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.125 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.369 W/kg

SAR(1 g) = 0.285 W/kg



0 dB = 0.316 W/kg = -5.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38596

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.377 \text{ S/m}$; $\epsilon_r = 38.524$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-03-2016; Ambient Temp: 24.5°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3288; ConvF(5.17, 5.17, 5.17); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.655 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.777 W/kg

SAR(1 g) = 0.485 W/kg



0 dB = 0.559 W/kg = -2.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.927 \text{ S/m}$; $\epsilon_r = 41.814$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-08-2016; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3288; ConvF(6.41, 6.41, 6.41); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.576 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.327 W/kg

SAR(1 g) = 0.260 W/kg



0 dB = 0.284 W/kg = -5.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$; $\sigma = 1.349 \text{ S/m}$; $\epsilon_r = 38.627$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-03-2016; Ambient Temp: 24.5°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3288; ConvF(5.17, 5.17, 5.17); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Left Head, Cheek, Low.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.881 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.783 W/kg



0 dB = 0.892 W/kg = -0.50 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.927 \text{ S/m}$; $\epsilon_r = 41.815$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-08-2016; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3288; ConvF(6.41, 6.41, 6.41); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. CDMA, Rule Part 22H, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.704 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.650 W/kg

SAR(1 g) = 0.504 W/kg



0 dB = 0.560 W/kg = -2.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.377 \text{ S/m}$; $\epsilon_r = 38.524$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-03-2016; Ambient Temp: 24.5°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3288; ConvF(5.17, 5.17, 5.17); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: PCS CDMA, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.985 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.824 W/kg

SAR(1 g) = 0.511 W/kg



0 dB = 0.589 W/kg = -2.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.937 \text{ S/m}$; $\epsilon_r = 42.584$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-07-2016; Ambient Temp: 20.7°C; Tissue Temp: 20.4°C

Probe: ES3DV3 - SN3333; ConvF(6.46, 6.46, 6.46); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Right Head, Cheek, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.444 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.463 W/kg

SAR(1 g) = 0.362 W/kg



0 dB = 0.397 W/kg = -4.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.886 \text{ S/m}$; $\epsilon_r = 40.665$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-28-2016; Ambient Temp: 21.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Left Head, Cheek, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.492 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.443 W/kg

SAR(1 g) = 0.350 W/kg



0 dB = 0.384 W/kg = -4.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.312 \text{ S/m}$; $\epsilon_r = 38.984$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-06-2016; Ambient Temp: 22.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3288; ConvF(5.4, 5.4, 5.4); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.891 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.936 W/kg

SAR(1 g) = 0.616 W/kg



0 dB = 0.731 W/kg = -1.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1860$ MHz; $\sigma = 1.357$ S/m; $\epsilon_r = 38.599$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Test Date: 02-03-2016; Ambient Temp: 24.5°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3288; ConvF(5.17, 5.17, 5.17); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Left Head, Cheek, Low.ch

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.476 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.37 W/kg

SAR(1 g) = 0.848 W/kg



0 dB = 0.987 W/kg = -0.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38422

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$; $\sigma = 1.811 \text{ S/m}$; $\epsilon_r = 39.155$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-17-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3351; ConvF(4.46, 4.46, 4.46); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Left Head, Cheek, Ch 01, 1 Mbps


Area Scan (11x15x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.459 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.528 W/kg

SAR(1 g) = 0.248 W/kg



0 dB = 0.337 W/kg = -4.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38422

Communication System: UID 0, IEEE 802.11a; Frequency: 5720 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5720 \text{ MHz}$; $\sigma = 4.966 \text{ S/m}$; $\epsilon_r = 35.602$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-17-2016; Ambient Temp: 22.9°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(4.07, 4.07, 4.07); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub ; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-2C, 20 MHz Bandwidth, Left Head, Cheek, Ch 144, 6 Mbps


Area Scan (13x11x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio = 1.4

Reference Value = 7.026 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.20 W/kg

SAR(1 g) = 0.199 W/kg



0 dB = 0.620 W/kg = -2.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.989 \text{ S/m}$; $\epsilon_r = 52.649$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(6.11, 6.11, 6.11); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.159 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.574 W/kg

SAR(1 g) = 0.463 W/kg



0 dB = 0.507 W/kg = -2.95 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.076

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.989 \text{ S/m}$; $\epsilon_r = 52.649$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(6.11, 6.11, 6.11); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 4 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.154 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.684 W/kg

SAR(1 g) = 0.548 W/kg



0 dB = 0.597 W/kg = -2.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38956

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.55 \text{ S/m}$; $\epsilon_r = 51.522$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(4.81, 4.81, 4.81); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x7x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.643 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.800 W/kg

SAR(1 g) = 0.423 W/kg



0 dB = 0.525 W/kg = -2.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38956

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 1909.8 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body Medium parameters used:

$f = 1910 \text{ MHz}$; $\sigma = 1.59 \text{ S/m}$; $\epsilon_r = 51.453$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(4.81, 4.81, 4.81); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Front side, High.ch, 4 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.079 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.691 W/kg

SAR(1 g) = 0.406 W/kg



0 dB = 0.484 W/kg = -3.15 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.989 \text{ S/m}$; $\epsilon_r = 52.649$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(6.11, 6.11, 6.11); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.528 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.582 W/kg

SAR(1 g) = 0.470 W/kg



0 dB = 0.516 W/kg = -2.87 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.55 \text{ S/m}$; $\epsilon_r = 51.522$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(4.81, 4.81, 4.81); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.984 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.989 W/kg

SAR(1 g) = 0.628 W/kg



0 dB = 0.725 W/kg = -1.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$; $\sigma = 1.522 \text{ S/m}$; $\epsilon_r = 51.654$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(4.81, 4.81, 4.81); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Front side, Low.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.789 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.947 W/kg



0 dB = 1.10 W/kg = 0.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.989 \text{ S/m}$; $\epsilon_r = 52.65$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(6.11, 6.11, 6.11); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. CDMA, Rule Part 22H, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.575 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.689 W/kg

SAR(1 g) = 0.563 W/kg



0 dB = 0.613 W/kg = -2.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.989 \text{ S/m}$; $\epsilon_r = 52.65$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(6.11, 6.11, 6.11); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Cell. EVDO Rev.0, Rule Part 22H, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.080 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.697 W/kg

SAR(1 g) = 0.554 W/kg



0 dB = 0.606 W/kg = -2.18 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, CDMA; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1851.25 \text{ MHz}$; $\sigma = 1.521 \text{ S/m}$; $\epsilon_r = 51.66$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(4.81, 4.81, 4.81); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: PCS CDMA, Body SAR, Back side, Low.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.768 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.836 W/kg



0 dB = 0.973 W/kg = -0.12 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 38414

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1908.75 \text{ MHz}$; $\sigma = 1.56 \text{ S/m}$; $\epsilon_r = 51.785$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-09-2016; Ambient Temp: 22.5°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3287; ConvF(4.72, 4.72, 4.72); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: PCS EVDO Rev. 0, Body SAR, Front side, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.84 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.46 W/kg

SAR(1 g) = 0.969 W/kg



0 dB = 1.13 W/kg = 0.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.99 \text{ S/m}$; $\epsilon_r = 53.847$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.3°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3287; ConvF(6.62, 6.62, 6.62); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Body SAR, Back side, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.045 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.638 W/kg

SAR(1 g) = 0.505 W/kg



0 dB = 0.552 W/kg = -2.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.989 \text{ S/m}$; $\epsilon_r = 52.651$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(6.11, 6.11, 6.11); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.479 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.485 W/kg

SAR(1 g) = 0.387 W/kg



0 dB = 0.421 W/kg = -3.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.475 \text{ S/m}$; $\epsilon_r = 51.344$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-08-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3287; ConvF(4.96, 4.96, 4.96); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.294 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.846 W/kg



0 dB = 0.989 W/kg = -0.05 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.53 \text{ S/m}$; $\epsilon_r = 51.618$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(4.81, 4.81, 4.81); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Body SAR, Back side, Low.ch

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.113 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.939 W/kg

SAR(1 g) = 0.627 W/kg



0 dB = 0.724 W/kg = -1.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.53 \text{ S/m}$; $\epsilon_r = 51.618$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(4.81, 4.81, 4.81); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Body SAR, Front side, Low.ch

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.713 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.678 W/kg



0 dB = 0.803 W/kg = -0.95 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.04 \text{ S/m}$; $\epsilon_r = 50.336$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3287; ConvF(4.2, 4.2, 4.2); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 11, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.296 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.328 W/kg

SAR(1 g) = 0.127 W/kg



0 dB = 0.162 W/kg = -7.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.04 \text{ S/m}$; $\epsilon_r = 50.336$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3287; ConvF(4.2, 4.2, 4.2); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 11, 1 Mbps, Front Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.400 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.350 W/kg

SAR(1 g) = 0.154 W/kg



0 dB = 0.201 W/kg = -6.97 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, IEEE 802.11a; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 5.847 \text{ S/m}$; $\epsilon_r = 46.578$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 22.3°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(3.37, 3.37, 3.37); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub ; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-2C, 20 MHz Bandwidth, Body SAR, Ch 100, 6 Mbps, Back Side


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 8.587 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.85 W/kg

SAR(1 g) = 0.411 W/kg



0 dB = 0.980 W/kg = -0.09 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, IEEE 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 6.126 \text{ S/m}$; $\epsilon_r = 46.156$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3589; ConvF(3.71, 3.71, 3.71); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub ; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Body SAR, Ch 149, 6 Mbps, Back Side


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.073 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.201 W/kg



0 dB = 0.489 W/kg = -3.11 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ320VPP; Type: Portable Handset; Serial: 41970

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.991 \text{ S/m}$; $\epsilon_r = 51.088$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-22-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Back Side


Area Scan (11x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.098 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.0850 W/kg

SAR(1 g) = 0.044 W/kg



0 dB = 0.0540 W/kg = -12.68 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.902 \text{ S/m}$; $\epsilon_r = 43.047$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-07-2016; Ambient Temp: 20.7°C; Tissue Temp: 20.4°C

Probe: ES3DV3 - SN3333; ConvF(6.46, 6.46, 6.46); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.49 W/kg

SAR(1 g) = 1.69 W/kg

Deviation(1 g) = 2.05%



0 dB = 1.98 W/kg = 2.97 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.885 \text{ S/m}$; $\epsilon_r = 40.687$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-28-2016; Ambient Temp: 21.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(6.41, 6.41, 6.41); Calibrated: 3/19/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/13/2015

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.79 W/kg

SAR(1 g) = 1.91 W/kg

Deviation(1 g) = 4.60%



0 dB = 2.23 W/kg = 3.48 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.925 \text{ S/m}$; $\epsilon_r = 41.838$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-08-2016; Ambient Temp: 22.1°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3288; ConvF(6.41, 6.41, 6.41); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.86 W/kg

SAR(1 g) = 1.92 W/kg

Deviation(1 g) = 1.37%



0 dB = 2.24 W/kg = 3.50 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.329 \text{ S/m}$; $\epsilon_r = 38.903$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2016; Ambient Temp: 22.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3288; ConvF(5.4, 5.4, 5.4); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.21 W/kg

SAR(1 g) = 3.47 W/kg

Deviation(1 g) = -7.96%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.4 \text{ S/m}$; $\epsilon_r = 38.441$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2016; Ambient Temp: 24.5°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3288; ConvF(5.17, 5.17, 5.17); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.18 W/kg

SAR(1 g) = 3.99 W/kg

Deviation(1 g) = -1.72%



0 dB = 5.00 W/kg = 6.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.851 \text{ S/m}$; $\epsilon_r = 39.013$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-17-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3351; ConvF(4.46, 4.46, 4.46); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.2 W/kg

SAR(1 g) = 5.44 W/kg

Deviation(1 g) = 0.37%



0 dB = 7.11 W/kg = 8.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.487 \text{ S/m}$; $\epsilon_r = 36.148$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-17-2016; Ambient Temp: 22.9°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(4.28, 4.28, 4.28); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub ; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio = 1.4

Peak SAR (extrapolated) = 15.3 W/kg

SAR(1 g) = 3.98 W/kg

Deviation(1 g) = 3.24%



0 dB = 8.25 W/kg = 9.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.886 \text{ S/m}$; $\epsilon_r = 35.801$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-17-2016; Ambient Temp: 22.9°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(3.9, 3.9, 3.9); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub ; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio = 1.4

Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 4.09 W/kg

Deviation(1 g) = 0.25%



0 dB = 10.2 W/kg = 10.09 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 4.984 \text{ S/m}$; $\epsilon_r = 35.551$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-17-2016; Ambient Temp: 22.9°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(4.07, 4.07, 4.07); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub ; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio = 1.4

Peak SAR (extrapolated) = 15.9 W/kg

SAR(1 g) = 3.77 W/kg

Deviation(1 g) = -6.57%



0 dB = 9.78 W/kg = 9.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1046

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.961 \text{ S/m}$; $\epsilon_r = 54.259$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-01-2016; Ambient Temp: 23.3°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3287; ConvF(6.62, 6.62, 6.62); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.32 W/kg

SAR(1 g) = 1.58 W/kg

Deviation(1 g) = -4.70%



0 dB = 1.84 W/kg = 2.65 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.987 \text{ S/m}$; $\epsilon_r = 52.668$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-27-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3351; ConvF(6.11, 6.11, 6.11); Calibrated: 6/22/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/24/2015

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)

Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 46.32 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 2.76 W/kg

SAR(1 g) = 1.90 W/kg

Deviation(1 g) = 3.26%



0 dB = 2.21 W/kg = 3.44 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.494 \text{ S/m}$; $\epsilon_r = 51.287$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-08-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3287; ConvF(4.96, 4.96, 4.96); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.38 W/kg

SAR(1 g) = 3.61 W/kg

Deviation(1 g) = -5.00%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.577 \text{ S/m}$; $\epsilon_r = 51.476$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3288; ConvF(4.81, 4.81, 4.81); Calibrated: 9/18/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2015

Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.28 W/kg

SAR(1 g) = 4.07 W/kg

Deviation(1 g) = 1.24%



0 dB = 5.19 W/kg = 7.15 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.549 \text{ S/m}$; $\epsilon_r = 51.808$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-09-2016; Ambient Temp: 22.5°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3287; ConvF(4.72, 4.72, 4.72); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1158

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.97 W/kg

SAR(1 g) = 3.82 W/kg

Deviation(1 g) = -4.50%



0 dB = 4.69 W/kg = 6.71 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 882

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.024 \text{ S/m}$; $\epsilon_r = 50.38$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-03-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3287; ConvF(4.2, 4.2, 4.2); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 10/20/2015

Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.1 W/kg

SAR(1 g) = 4.77 W/kg

Deviation(1 g) = -5.92%



0 dB = 6.31 W/kg = 8.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.003 \text{ S/m}$; $\epsilon_r = 51.054$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-22-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.9 W/kg

SAR(1 g) = 5.47 W/kg

Deviation(1 g) = 5.39%



0 dB = 7.29 W/kg = 8.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.483 \text{ S/m}$; $\epsilon_r = 46.839$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 22.3°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(3.8, 3.8, 3.8); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (10x11x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.3 W/kg

SAR(1 g) = 3.72 W/kg

Deviation(1 g) = 0.68%



0 dB = 4.17 W/kg = 6.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.979 \text{ S/m}$; $\epsilon_r = 46.471$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 22.3°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(3.37, 3.37, 3.37); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (10x11x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 3.83 W/kg

Deviation(1 g) = -3.04%



0 dB = 4.82 W/kg = 6.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.132 \text{ S/m}$; $\epsilon_r = 46.147$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-01-2016; Ambient Temp: 23.1°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3589; ConvF(3.71, 3.71, 3.71); Calibrated: 1/20/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/15/2016

Phantom: SAM Sub; Type: QD000P40CC; Serial: TP:1357

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (10x11x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 3.73 W/kg

Deviation(1 g) = 0.67%



0 dB = 4.66 W/kg = 6.68 dBW/kg