

7.4 Band Edge Emissions at Antenna Terminal

\$2.1051 \$22.917(a) \$24.238(a) \$27.53(g) \$27.53(h)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq$ 1% of the emission bandwidth
4. VBW $\geq$ 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq$ 2 x Span/RBW
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup

Test Notes


Per 22.917(b) 24.238(a) 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 51 of 112




Plot 7-73. Lower Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)




Plot 7-74. Upper Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 52 of 112




Plot 7-75. Lower Band Edge Plot (Band 17 – 10.0MHz QPSK – RB Size 50)




Plot 7-76. Upper Band Edge Plot (Band 17 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 53 of 112




Plot 7-77. Lower Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)




Plot 7-78. Upper Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 54 of 112




Plot 7-79. Lower Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)




Plot 7-80. Upper Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 55 of 112




Plot 7-81. Lower Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)




Plot 7-82. Upper Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 56 of 112




Plot 7-83. Lower Band Edge Plot (Band 5 – 10.0MHz QPSK – RB Size 50)




Plot 7-84. Upper Band Edge Plot (Band 5 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 57 of 112




Plot 7-85. Lower Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 7-86. Lower Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 58 of 112




Plot 7-87. Upper Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 7-88. Upper Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 59 of 112




Plot 7-89. Lower Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 7-90. Lower Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 60 of 112




Plot 7-91. Upper Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 7-92. Upper Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 61 of 112




Plot 7-93. Lower Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 7-94. Lower Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 62 of 112




Plot 7-95. Upper Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 7-96. Upper Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 63 of 112




Plot 7-97. Lower Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)




Plot 7-98. Lower Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 64 of 112




Plot 7-99. Upper Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)




Plot 7-100. Upper Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 65 of 112




Plot 7-101. Lower Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 7-102. Lower Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 66 of 112	




Plot 7-103. Upper Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 7-104. Upper Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 67 of 112




Plot 7-105. Lower Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)




Plot 7-106. Lower Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 68 of 112




Plot 7-107. Upper Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)




Plot 7-108. Upper Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 69 of 112




Plot 7-109. Lower Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)




Plot 7-110. Lower Extended Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 70 of 112




Plot 7-111. Upper Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)




Plot 7-112. Upper Extended Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 71 of 112




Plot 7-113. Lower Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)




Plot 7-114. Lower Extended Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMJ510MN	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 72 of 112




Plot 7-115. Upper Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)




Plot 7-116. Upper Extended Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 73 of 112




Plot 7-117. Lower Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)




Plot 7-118. Lower Extended Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMJ510MN	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 74 of 112	




Plot 7-119. Upper Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)




Plot 7-120. Upper Extended Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 75 of 112




Plot 7-121. Lower Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)



Plot 7-122. Lower Extended Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 76 of 112	




Plot 7-123. Upper Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)




Plot 7-124. Upper Extended Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 77 of 112




Plot 7-125. Lower Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)




Plot 7-126. Lower Extended Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 78 of 112




Plot 7-127. Upper Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)




Plot 7-128. Upper Extended Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 79 of 112




Plot 7-129. Lower Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)




Plot 7-130. Lower Extended Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 80 of 112



Plot 7-131. Upper Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)



Plot 7-132. Upper Extended Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 81 of 112

7.5 Peak-Average Ratio

§24.232(d)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMJ510MN		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 82 of 112




Plot 7-133. PAR Plot (Band 2 – 1.4MHz QPSK – RB Size 6)




Plot 7-134. PAR Plot (Band 2 – 1.4MHz 16-QAM – RB Size 6)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 83 of 112




Plot 7-135. PAR Plot (Band 2 – 3.0MHz QPSK – RB Size 15)




Plot 7-136. PAR Plot (Band 2 – 3.0MHz 16-QAM – RB Size 15)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 84 of 112




Plot 7-137. PAR Plot (Band 2 – 5.0MHz QPSK – RB Size 25)




Plot 7-138. PAR Plot (Band 2 – 5.0MHz 16-QAM – RB Size 25)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 85 of 112




Plot 7-139. PAR Plot (Band 2 – 10.0MHz QPSK – RB Size 50)




Plot 7-140. PAR Plot (Band 2 – 10.0MHz 16-QAM – RB Size 50)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 86 of 112




Plot 7-141. PAR Plot (Band 2 – 15.0MHz QPSK – RB Size 75)




Plot 7-142. PAR Plot (Band 2 – 15.0MHz 16-QAM – RB Size 75)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 87 of 112



Plot 7-143. PAR Plot (Band 2 – 20.0MHz QPSK – RB Size 100)



Plot 7-144. PAR Plot (Band 2 – 20.0MHz 16-QAM – RB Size 100)

FCC ID: A3LSMJ510MN	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 88 of 112

7.6 Radiated Power (ERP/EIRP)

§22.913(a.2) §24.232(c.2) §27.50(c.10) §27.50(d.4)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using horizontally and vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMJ510MN		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 89 of 112

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup >1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 90 of 112

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
706.50	5	QPSK	H	199	1	1 / 24	14.73	-0.55	14.18	34.77	-20.59
710.00	5	QPSK	H	200	355	1 / 24	14.27	-0.55	13.72	34.77	-21.05
713.50	5	QPSK	H	200	5	1 / 24	15.21	-0.55	14.66	34.77	-20.11
706.50	5	16-QAM	H	199	1	1 / 24	13.39	-0.55	12.84	34.77	-21.93
710.00	5	16-QAM	H	200	355	1 / 24	13.74	-0.55	13.19	34.77	-21.58
713.50	5	16-QAM	H	200	5	1 / 24	14.36	-0.55	13.81	34.77	-20.96
709.00	10	QPSK	H	200	11	1 / 49	15.91	-0.55	15.36	34.77	-19.41
710.00	10	QPSK	H	290	356	1 / 49	16.77	-0.55	16.22	34.77	-18.55
711.00	10	QPSK	H	200	20	1 / 49	15.32	-0.55	14.77	34.77	-20.00
709.00	10	16-QAM	H	200	11	1 / 49	14.94	-0.55	14.39	34.77	-20.38
710.00	10	16-QAM	H	200	5	1 / 49	15.60	-0.55	15.05	34.77	-19.72
711.00	10	16-QAM	H	200	20	1 / 49	14.49	-0.55	13.94	34.77	-20.83
710.00	10	QPSK	V	270	240	1 / 49	11.95	-0.99	10.96	34.77	-23.81

Table 7-2. ERP Data (Band 17)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 91 of 112

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
824.70	1.4	QPSK	H	100	181	1 / 5	20.06	-0.75	19.31	38.45	-19.14
836.50	1.4	QPSK	H	100	193	1 / 5	22.81	-0.80	22.01	38.45	-16.44
848.30	1.4	QPSK	H	100	189	1 / 5	22.80	-0.84	21.96	38.45	-16.49
824.70	1.4	16-QAM	H	100	181	1 / 5	19.39	-0.75	18.64	38.45	-19.81
836.50	1.4	16-QAM	H	100	193	1 / 5	21.92	-0.80	21.12	38.45	-17.33
848.30	1.4	16-QAM	H	100	189	1 / 5	21.81	-0.84	20.97	38.45	-17.48
825.50	3	QPSK	H	101	180	1 / 14	20.95	-0.75	20.20	38.45	-18.25
836.50	3	QPSK	H	103	189	1 / 14	23.42	-0.80	22.62	38.45	-15.83
847.50	3	QPSK	H	100	191	1 / 14	23.06	-0.84	22.22	38.45	-16.23
825.50	3	16-QAM	H	101	180	1 / 14	20.31	-0.75	19.56	38.45	-18.89
836.50	3	16-QAM	H	103	189	1 / 14	22.25	-0.80	21.45	38.45	-17.00
847.50	3	16-QAM	H	100	191	1 / 14	21.91	-0.84	21.07	38.45	-17.38
826.50	5	QPSK	H	100	281	1 / 24	20.16	-0.76	19.40	38.45	-19.05
836.50	5	QPSK	H	100	285	1 / 24	21.86	-0.80	21.06	38.45	-17.39
846.50	5	QPSK	H	100	279	1 / 24	21.84	-0.84	21.00	38.45	-17.45
826.50	5	16-QAM	H	100	281	1 / 24	18.95	-0.76	18.19	38.45	-20.26
836.50	5	16-QAM	H	100	285	1 / 24	20.94	-0.80	20.14	38.45	-18.31
846.50	5	16-QAM	H	100	279	1 / 24	20.96	-0.84	20.12	38.45	-18.33
829.00	10	QPSK	H	100	104	1 / 49	21.94	-0.77	21.17	38.45	-17.28
836.50	10	QPSK	H	100	102	1 / 49	23.00	-0.80	22.20	38.45	-16.25
844.00	10	QPSK	H	100	79	1 / 49	21.80	-0.83	20.97	38.45	-17.48
829.00	10	16-QAM	H	100	104	1 / 49	21.40	-0.77	20.63	38.45	-17.82
836.50	10	16-QAM	H	100	102	1 / 49	22.19	-0.80	21.39	38.45	-17.06
844.00	10	16-QAM	H	100	79	1 / 49	21.02	-0.83	20.19	38.45	-18.26
836.50	3	QPSK	V	135	245	1 / 14	21.41	-1.74	19.67	38.45	-18.78

Table 7-3. ERP Data (Band 5)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 92 of 112

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1710.70	1.4	QPSK	H	100	56	1 / 5	13.22	8.23	21.45	30.00	-8.55
1732.50	1.4	QPSK	H	100	51	1 / 5	14.14	8.18	22.32	30.00	-7.68
1754.30	1.4	QPSK	H	100	277	1 / 5	13.95	8.12	22.07	30.00	-7.93
1710.70	1.4	16-QAM	H	100	56	1 / 5	12.44	8.23	20.67	30.00	-9.33
1732.50	1.4	16-QAM	H	100	51	1 / 5	13.53	8.18	21.71	30.00	-8.29
1754.30	1.4	16-QAM	H	100	277	1 / 5	13.07	8.12	21.19	30.00	-8.81
1711.50	3	QPSK	H	100	274	1 / 14	14.10	8.23	22.33	30.00	-7.67
1732.50	3	QPSK	H	100	54	1 / 14	14.08	8.18	22.26	30.00	-7.74
1753.50	3	QPSK	H	100	64	1 / 14	13.88	8.12	22.00	30.00	-8.00
1711.50	3	16-QAM	H	100	274	1 / 14	13.66	8.23	21.89	30.00	-8.11
1732.50	3	16-QAM	H	100	54	1 / 14	13.30	8.18	21.48	30.00	-8.52
1753.50	3	16-QAM	H	100	64	1 / 14	12.96	8.12	21.08	30.00	-8.92
1712.50	5	QPSK	H	100	55	1 / 24	13.17	8.23	21.40	30.00	-8.60
1732.50	5	QPSK	H	100	51	1 / 24	13.62	8.18	21.80	30.00	-8.20
1752.50	5	QPSK	H	100	275	1 / 24	13.56	8.13	21.69	30.00	-8.31
1712.50	5	16-QAM	H	100	55	1 / 24	11.98	8.23	20.21	30.00	-9.79
1732.50	5	16-QAM	H	100	51	1 / 24	13.00	8.18	21.18	30.00	-8.82
1752.50	5	16-QAM	H	100	275	1 / 24	12.51	8.13	20.64	30.00	-9.36
1715.00	10	QPSK	H	100	53	1 / 49	12.99	8.22	21.21	30.00	-8.79
1732.50	10	QPSK	H	100	52	1 / 49	14.31	8.18	22.49	30.00	-7.51
1750.00	10	QPSK	H	100	269	1 / 49	13.57	8.13	21.70	30.00	-8.30
1715.00	10	16-QAM	H	100	53	1 / 49	12.26	8.22	20.48	30.00	-9.52
1732.50	10	16-QAM	H	100	52	1 / 49	13.25	8.18	21.43	30.00	-8.57
1750.00	10	16-QAM	H	100	269	1 / 49	12.77	8.13	20.90	30.00	-9.10
1717.50	15	QPSK	H	100	53	1 / 74	13.93	8.22	22.15	30.00	-7.85
1732.50	15	QPSK	H	100	51	1 / 74	13.80	8.18	21.98	30.00	-8.02
1747.50	15	QPSK	H	100	273	1 / 74	13.49	8.14	21.63	30.00	-8.37
1717.50	15	16-QAM	H	100	53	1 / 74	13.38	8.22	21.60	30.00	-8.40
1732.50	15	16-QAM	H	100	51	1 / 74	13.00	8.18	21.18	30.00	-8.82
1747.50	15	16-QAM	H	100	273	1 / 74	12.61	8.14	20.75	30.00	-9.25
1720.00	20	QPSK	H	100	50	1 / 99	14.31	8.21	22.52	30.00	-7.48
1732.50	20	QPSK	H	100	269	1 / 99	14.39	8.18	22.57	30.00	-7.43
1745.00	20	QPSK	H	100	271	1 / 99	13.76	8.15	21.91	30.00	-8.09
1720.00	20	16-QAM	H	100	50	1 / 99	13.08	8.21	21.29	30.00	-8.71
1732.50	20	16-QAM	H	100	269	1 / 99	12.73	8.18	20.91	30.00	-9.09
1745.00	20	16-QAM	H	100	271	1 / 99	12.82	8.15	20.97	30.00	-9.03
1732.50	20	QPSK	V	100	269	1 / 99	13.26	8.12	21.38	30.00	-8.62

Table 7-4. EIRP Data (Band 4)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 93 of 112

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1850.70	1.4	QPSK	H	167	309	1 / 0	14.90	7.99	22.89	33.01	-10.12
1880.00	1.4	QPSK	H	168	308	1 / 0	16.22	7.98	24.20	33.01	-8.82
1909.30	1.4	QPSK	H	160	300	1 / 0	15.42	8.04	23.46	33.01	-9.55
1850.70	1.4	16-QAM	H	167	309	1 / 0	13.86	7.99	21.85	33.01	-11.16
1880.00	1.4	16-QAM	H	168	308	1 / 0	15.76	7.98	23.74	33.01	-9.28
1909.30	1.4	16-QAM	H	160	300	1 / 0	14.52	8.04	22.56	33.01	-10.45
1851.50	3	QPSK	H	160	307	1 / 0	14.77	7.99	22.76	33.01	-10.25
1880.00	3	QPSK	H	162	312	1 / 0	16.58	7.98	24.56	33.01	-8.46
1908.50	3	QPSK	H	159	326	1 / 0	15.32	8.03	23.35	33.01	-9.66
1851.50	3	16-QAM	H	160	307	1 / 0	13.99	7.99	21.98	33.01	-11.03
1880.00	3	16-QAM	H	162	312	1 / 0	16.08	7.98	24.06	33.01	-8.96
1908.50	3	16-QAM	H	159	326	1 / 0	14.52	8.03	22.55	33.01	-10.46
1852.50	5	QPSK	H	100	310	1 / 0	14.69	7.99	22.68	33.01	-10.33
1880.00	5	QPSK	H	166	308	1 / 0	16.26	7.98	24.24	33.01	-8.78
1907.50	5	QPSK	H	160	327	1 / 0	14.68	8.02	22.70	33.01	-10.31
1852.50	5	16-QAM	H	100	310	1 / 0	13.67	7.99	21.66	33.01	-11.35
1880.00	5	16-QAM	H	166	308	1 / 0	15.23	7.98	23.21	33.01	-9.81
1907.50	5	16-QAM	H	160	327	1 / 0	14.10	8.02	22.12	33.01	-10.89
1855.00	10	QPSK	H	100	305	1 / 0	15.41	7.99	23.40	33.01	-9.61
1880.00	10	QPSK	H	172	303	1 / 0	16.75	7.98	24.73	33.01	-8.29
1905.00	10	QPSK	H	164	305	1 / 0	15.91	8.00	23.91	33.01	-9.10
1855.00	10	16-QAM	H	100	305	1 / 0	14.59	7.99	22.58	33.01	-10.43
1880.00	10	16-QAM	H	172	303	1 / 0	16.27	7.98	24.25	33.01	-8.77
1905.00	10	16-QAM	H	164	305	1 / 0	15.08	8.00	23.08	33.01	-9.93
1857.50	15	QPSK	H	100	305	1 / 0	15.66	7.98	23.64	33.01	-9.37
1880.00	15	QPSK	H	175	257	1 / 0	14.77	7.98	22.75	33.01	-10.27
1902.50	15	QPSK	H	163	328	1 / 0	14.88	7.99	22.87	33.01	-10.14
1857.50	15	16-QAM	H	100	305	1 / 0	14.63	7.98	22.61	33.01	-10.40
1880.00	15	16-QAM	H	175	257	1 / 0	14.14	7.98	22.12	33.01	-10.90
1902.50	15	16-QAM	H	163	328	1 / 0	14.44	7.99	22.43	33.01	-10.58
1860.00	20	QPSK	H	171	307	1 / 0	15.41	7.98	23.39	33.01	-9.62
1880.00	20	QPSK	H	172	306	1 / 0	15.62	7.98	23.60	33.01	-9.42
1900.00	20	QPSK	H	172	311	1 / 0	15.51	7.97	23.48	33.01	-9.53
1860.00	20	16-QAM	H	171	307	1 / 0	14.77	7.98	22.75	33.01	-10.26
1880.00	20	16-QAM	H	172	306	1 / 0	15.02	7.98	23.00	33.01	-10.02
1900.00	20	16-QAM	H	172	311	1 / 0	14.65	7.97	22.62	33.01	-10.39
1880.00	10	QPSK	V	140	15	1 / 0	12.00	7.89	19.89	33.01	-13.12

Table 7-5. EIRP Data (Band 2)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 94 of 112

7.7 Radiated Spurious Emissions Measurements

\$2.1053 \$22.917(a) \$24.238(a) \$27.53(g) \$27.53(h)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 95 of 112	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 5) The “-” shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMJ510MN		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 96 of 112

OPERATING FREQUENCY: 709.00 MHz
 CHANNEL: 23780
 MEASURED OUTPUT POWER: 15.36 dBm = 0.034 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 28.36 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1418.00	H	130	325	-63.97	6.24	-57.73	73.1
2127.00	H	-	-	-63.92	6.81	-57.11	72.5

Table 7-6. Radiated Spurious Data (Band 17 – Low Channel)

OPERATING FREQUENCY: 710.00 MHz
 CHANNEL: 23790
 MEASURED OUTPUT POWER: 16.22 dBm = 0.042 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 29.22 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1420.00	H	140	235	-63.46	6.24	-57.22	73.4
2130.00	H	-	-	-63.81	6.81	-56.99	73.2

Table 7-7. Radiated Spurious Data (Band 17 – Mid Channel)

OPERATING FREQUENCY: 711.00 MHz
 CHANNEL: 23800
 MEASURED OUTPUT POWER: 14.77 dBm = 0.030 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 27.77 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1422.00	H	138	262	-62.39	6.25	-56.14	70.9
2133.00	H	-	-	-63.74	6.82	-56.92	71.7

Table 7-8. Radiated Spurious Data (Band 17 – High Channel)

OPERATING FREQUENCY: 825.50 MHz
 CHANNEL: 20415
 MEASURED OUTPUT POWER: 20.20 dBm = 0.105 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.20 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1651.00	H	109	263	-54.66	6.24	-48.42	68.6
2476.50	H	109	266	-54.37	6.61	-47.75	68.0
3302.00	H	-	-	-58.33	7.00	-51.33	71.5

Table 7-9. Radiated Spurious Data (Band 5 – Low Channel)

OPERATING FREQUENCY: 836.50 MHz
 CHANNEL: 20525
 MEASURED OUTPUT POWER: 22.62 dBm = 0.183 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 35.62 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.00	H	102	12	-56.67	6.13	-50.54	73.2
2509.50	H	100	195	-55.28	6.64	-48.65	71.3
3346.00	H	-	-	-57.52	7.14	-50.38	73.0

Table 7-10. Radiated Spurious Data (Band 5 – Mid Channel)

OPERATING FREQUENCY: 847.50 MHz
 CHANNEL: 20635
 MEASURED OUTPUT POWER: 22.22 dBm = 0.167 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 35.22 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1695.00	H	105	35	-48.23	6.02	-42.22	64.4
2542.50	H	170	5	-50.55	6.73	-43.82	66.0
3390.00	H	-	-	-58.95	7.28	-51.66	73.9

Table 7-11. Radiated Spurious Data (Band 5 – High Channel)

OPERATING FREQUENCY: 1720.00 MHz
 CHANNEL: 20050
 MEASURED OUTPUT POWER: 22.52 dBm = 0.179 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 35.52 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3440.00	H	149	153	-37.74	9.57	-28.17	50.7
5160.00	H	140	110	-50.63	11.01	-39.62	62.1
6880.00	H	115	112	-50.10	10.77	-39.33	61.9
8600.00	H	-	-	-50.42	11.34	-39.08	61.6

Table 7-12. Radiated Spurious Data (Band 4 – Low Channel)

OPERATING FREQUENCY: 1732.50 MHz
 CHANNEL: 20175
 MEASURED OUTPUT POWER: 22.57 dBm = 0.181 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 35.57 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3465.00	H	115	115	-36.95	9.64	-27.31	49.9
5197.50	H	114	80	-51.19	10.98	-40.21	62.8
6930.00	H	115	90	-51.32	10.85	-40.47	63.0
8662.50	H	-	-	-51.15	11.53	-39.62	62.2

Table 7-13. Radiated Spurious Data (Band 4 – Mid Channel)

OPERATING FREQUENCY: 1745.00 MHz
 CHANNEL: 20300
 MEASURED OUTPUT POWER: 21.91 dBm = 0.155 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 34.91 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3490.00	H	130	145	-36.32	9.71	-26.61	48.5
5235.00	H	130	262	-48.72	11.03	-37.69	59.6
6980.00	H	129	105	-51.01	10.95	-40.06	62.0
8725.00	H	-	-	-50.90	11.68	-39.23	61.1

Table 7-14. Radiated Spurious Data (Band 4 – High Channel)

OPERATING FREQUENCY: 1855.00 MHz
 CHANNEL: 18650
 MEASURED OUTPUT POWER: 23.40 dBm = 0.219 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 36.40 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3710.00	H	140	120	-45.18	9.87	-35.31	58.7
5565.00	H	113	305	-54.89	11.18	-43.71	67.1
7420.00	H	-	-	-51.57	10.85	-40.73	64.1

Table 7-15. Radiated Spurious Data (Band 2 – Low Channel)

FCC ID: A3LSMJ510MN		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset		Page 101 of 112

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 18900
 MEASURED OUTPUT POWER: 24.73 dBm = 0.297 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.73 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	130	185	-51.66	9.63	-42.03	66.8
5640.00	H	102	112	-54.79	11.29	-43.50	68.2
7520.00	H	-	-	-51.60	11.12	-40.47	65.2

Table 7-16. Radiated Spurious Data (Band 2 – Mid Channel)

OPERATING FREQUENCY: 1905.00 MHz
 CHANNEL: 19150
 MEASURED OUTPUT POWER: 23.91 dBm = 0.246 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 36.91 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3810.00	H	152	156	-50.97	9.41	-41.55	65.5
5715.00	H	126	305	-55.47	11.37	-44.11	68.0
7620.00	H	-	-	-52.32	11.33	-40.99	64.9

Table 7-17. Radiated Spurious Data (Band 2 – High Channel)

7.8 Frequency Stability / Temperature Variation

\$2.1055 \$22.355 \$24.235 \$27.54

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-C-2004

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 103 of 112

Band 17 Frequency Stability Measurements

\$2.1055 \$27.54

OPERATING FREQUENCY: 710,000,000 Hz
 CHANNEL: 23090
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	709,999,832	-168	-0.0000237
100 %		- 30	709,999,880	-120	-0.0000169
100 %		- 20	709,999,811	-189	-0.0000266
100 %		- 10	709,999,870	-130	-0.0000183
100 %		0	709,999,890	-110	-0.0000155
100 %		+ 10	710,000,105	105	0.0000148
100 %		+ 20	709,999,832	-168	-0.0000237
100 %		+ 30	709,999,863	-137	-0.0000193
100 %		+ 40	709,999,841	-159	-0.0000224
100 %		+ 50	709,999,823	-177	-0.0000249
BATT. ENDPOINT	3.45	+ 20	709,999,765	-235	-0.0000331

Table 7-18. Frequency Stability Data (Band 17)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMJ510MN		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset			Page 104 of 112

Band 17 Frequency Stability Measurements

\$2.1055 \$27.54




Figure 7-8. Frequency Stability Graph (Band 17)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 105 of 112

Band 5 Frequency Stability Measurements

§2.1055 §22.355

OPERATING FREQUENCY: 836,500,000 Hz

CHANNEL: 20525

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,499,955	-45	-0.0000054
100 %		- 30	836,500,104	104	0.0000124
100 %		- 20	836,499,828	-172	-0.0000206
100 %		- 10	836,500,101	101	0.0000121
100 %		0	836,500,028	28	0.0000033
100 %		+ 10	836,499,943	-57	-0.0000068
100 %		+ 20	836,500,047	47	0.0000056
100 %		+ 30	836,500,084	84	0.0000100
100 %		+ 40	836,500,105	105	0.0000126
100 %		+ 50	836,499,869	-131	-0.0000157
BATT. ENDPOINT	3.45	+ 20	836,500,293	293	0.0000350

Table 7-19. Frequency Stability Data (Band 5)

Band 5 Frequency Stability Measurements

§2.1055 §22.355




Figure 7-9. Frequency Stability Graph (Band 5)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 107 of 112

Band 4 Frequency Stability Measurements

\$2.1055 \$27.54

OPERATING FREQUENCY: 1,732,500,000 Hz
 CHANNEL: 20175
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,732,499,816	-184	-0.0000106
100 %		- 30	1,732,499,878	-122	-0.0000070
100 %		- 20	1,732,499,883	-117	-0.0000068
100 %		- 10	1,732,499,820	-180	-0.0000104
100 %		0	1,732,499,837	-163	-0.0000094
100 %		+ 10	1,732,499,806	-194	-0.0000112
100 %		+ 20	1,732,499,816	-184	-0.0000106
100 %		+ 30	1,732,499,839	-161	-0.0000093
100 %		+ 40	1,732,499,863	-137	-0.0000079
100 %		+ 50	1,732,499,868	-132	-0.0000076
BATT. ENDPOINT	3.45	+ 20	1,732,499,797	-203	-0.0000117

Table 7-20. Frequency Stability Data (Band 4)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMJ510MN		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 108 of 112	

Band 4 Frequency Stability Measurements

§2.1055 §27.54




Figure 7-10. Frequency Stability Graph (Band 4)

FCC ID: A3LSMJ510MN	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 109 of 112

Band 2 Frequency Stability Measurements

\$2.1055 \$24.235

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 18900
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,879,999,844	-156	-0.0000083
100 %		- 30	1,879,999,825	-175	-0.0000093
100 %		- 20	1,879,999,880	-120	-0.0000064
100 %		- 10	1,879,999,803	-197	-0.0000105
100 %		0	1,879,999,858	-142	-0.0000076
100 %		+ 10	1,879,999,822	-178	-0.0000095
100 %		+ 20	1,879,999,844	-156	-0.0000083
100 %		+ 30	1,879,999,866	-134	-0.0000071
100 %		+ 40	1,879,999,880	-120	-0.0000064
100 %		+ 50	1,879,999,893	-107	-0.0000057
BATT. ENDPOINT	3.45	+ 20	1,879,999,790	-210	-0.0000112

Table 7-21. Frequency Stability Data (Band 2)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMJ510MN		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset			Page 110 of 112

Band 2 Frequency Stability Measurements

§2.1055 §24.235




Figure 7-11. Frequency Stability Graph (Band 2)

FCC ID: A3LSMJ510MN			FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset			Page 111 of 112

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMJ510MN** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules for LTE operation only.

FCC ID: A3LSMJ510MN		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1602290409.A3L	Test Dates: Feb 15 - Mar 08, 2016	EUT Type: Portable Handset	Page 112 of 112	