

EMI TEST REPORT

FCC CERTIFICATION

Applicant:

SAMSUNG Electronics Co., Ltd.
129, Samsung-ro, Yeongtong-gu, Suwon-si,
Gyeonggi-do, 16677, Korea

Date of Issue: September 17, 2018**Test Report No. HCT-EM-1809-FC009-R1****Test Site: HCT CO., LTD.****FCC ID :****A3LSMJ610FN**

Applicable Standards : FCC CFR 47 PART 15 Subpart B Class B
ANSI C63.4-2014

Type of Device : Class B Personal Computers and Peripherals

EUT Type : Mobile Phone

Model Name : SM-J415FN/DS

Additional Model Name : SM-J415FN

Date of Test : September 06, 2018 to September 14, 2018

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Na-Eun Song
Test Engineer
EMC Team
Certification Division

Reviewed By

Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



REVISION HISTORY

The revision history for this document is shown in table.

Report No.	Issue Date	Information About Changes
HCT-EM-1809-FC009	September 14, 2018	Initial Release
HCT-EM-1809-FC009-R1	September 17, 2018	Revised text in Clause 4.2, NOTE



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Equipment Units Tested	4
1.3 Cable Description	5
1.4 Noise Suppression Parts on Cable (I/O Cable)	5
1.5. Test Facility	6
1.6 Calibration of Measuring Instrument	6
1.7 Measurement Uncertainty	6
2. LIST OF TEST EQUIPMENT	7
3. DESCRIPTION OF MEASUREMENTS	8
3.1 Measurement of Conducted Emission	8
3.2 Measurement of Radiated Emission	9
4. PRELIMINARY TEST	11
4.1 Conducted Emission Test	11
4. 2 Radiated Emission Test	11
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
5.1 Conducted Emission Test	12
5.2 Radiated Emission Test	19
6. CONCLUSION	21
7. APPENDIX A. TEST SETUP PHOTOGRAPHS	22



1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	A3LSMJ610FN
Model	SM-J415FN/DS
Additional Model	SM-J415FN
EUT Type	Mobile Phone
Frequency Band	GSM 850/1900, WCDMA 850/1900, LTE B5/B41, Bluetooth 4.2, WLAN 2.4 GHz, NFC
Manufacturer	Samsung India Electronics PVT. Ltd. NOIDA uttar Pradeshe, Indio 201-305

1.2 Equipment Units Tested

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer	FCC ID / DoC
EUT	SM-J415FN/DS	-	SAMSUNG	A3LSMJ610FN
Notebook PC	ProBook6560b	5CB2053MXF	HP	-
Notebook PC Adaptor	Series PPP009L-E	-	LITE-ON TECHNOLOGY (CHANGZHOU)	
Gateway	TL-WR747N	-	TP Link	
Gateway Adaptor	T090060-2H1	-	TP Link	
Serial Mouse	Serial 2 Button mouse	02031069	Radio Shack	
RJ45 cable	-	-	-	
Data Cable	ECB-DU68WE	-	SAMSUNG	
Earphone	EHS61ASFWE	-	SAMSUNG	
Micro SD Card	64 GB	-	SAMSUNG	



1.3 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D) 1.0
	Earphone	N/A	N	(D) 1.2
Notebook PC	RJ 45	N/A	N	(D) 1.6
	Serial(Mouse)	N/A	Y	(D) 1.8
	DC IN	N	N/A	(P) 1.8
Gateway	DC IN	N	N/A	(P) 1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.4 Noise Suppression Parts on Cable (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial(Mouse)	N	N/A	Y	Notebook End



1.5. Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	90661
Radiated Field strength measurement facility 10 m Semi Anechoic chamber	

1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).

1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	1.82 dB ($k = 2$)
Radiated Emissions (30 MHz to 1 GHz)	5.20 dB ($k = 2$)
Radiated Emissions (1 GHz to 18 GHz)	5.24 dB ($k = 2$)
Radiated Emissions (18 GHz to 40 GHz)	5.40 dB ($k = 2$)



2. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.25.2018
☒ LISN	Rohde & Schwarz	ENV216	102245	1 year	12.20.2017
☒ LISN	Rohde & Schwarz	ENV216	100073	1 year	05.03.2018
☒ Software	Rohde & Schwarz	EMC32 VER8.54.0	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	07.27.2018
☒ Trilog Antenna	Schwarzbeck	VULB 9168	760	2 year	04.06.2017
☒ Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒ Antenna master controller	INNCO Systems	CO 3000	CO3000/870/ 35990515/L	N/A	-
☒ Turn Table	INNCO Systems	1060-2M	-	N/A	-
☒ Turn Table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.14.2018
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-
-For measurement above 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	07.27.2018
☒ Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒ Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
☒ Turn Table	INNCO Systems	1060-2M	-	N/A	-
☒ Turn Table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
☒ Low Noise Amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.06.2018
☐ Power Amplifier	TESTEK	TK-PA1840H	170030-L	1 year	12.20.2017
☐ Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170#786	2 year	12.05.2017
☐ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☐ Power Amplifier	CERNEX	CBLU1183540	21691	1 year	06.25.2018
☐ Antenna master	HD GmbH	MA240	240/520	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.14.2018
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-



3. DESCRIPTION OF MEASUREMENTS

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

3.3 Configuration of Tested System



Non-Conductive Table
Power Line: 120 VAC, 60 Hz



4. PRELIMINARY TEST

4.1 Conducted Emission Test

It was tested the following operating mode, after connecting all peripheral devices.

Operation Mode: ☒ Data communication mode (READ)
☒ Data communication mode (WRITE)

NOTE. *The worst-case emissions are reported.*

4.2 Radiated Emission Test

It was tested the following operating mode, after connecting all peripheral devices.

Operation Mode: ☒ Data communication mode (READ)
☒ Data communication mode (WRITE)

NOTE. Three orientations have been investigated and the worst case orientation is reported.



5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY


5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:

Applicable Standards	FCC PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Worst Case of Operation Mode	Data communication mode (READ)
Kind of Test Site	Shielded Room
Temperature	23.6-24.7 °C
Relative Humidity	48.0-50.2 %
Test Date	September 10, 2018- September 14, 2018

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

**Figure 1: Conducted Emission, AC Main Port, Line (L1)**




QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	43.9	9.000	L1	9.6	22.1	66.0
0.156000	43.0	9.000	L1	9.6	22.6	65.7
0.166000	44.9	9.000	L1	9.6	20.2	65.2
0.170000	45.8	9.000	L1	9.6	19.2	65.0
0.174000	44.4	9.000	L1	9.6	20.4	64.8
0.178000	44.6	9.000	L1	9.6	20.0	64.6
1.098000	37.7	9.000	L1	9.7	18.3	56.0
1.114000	39.1	9.000	L1	9.7	16.9	56.0
1.136000	39.6	9.000	L1	9.7	16.4	56.0
1.140000	40.1	9.000	L1	9.7	15.9	56.0
1.150000	39.4	9.000	L1	9.7	16.6	56.0
1.158000	40.0	9.000	L1	9.7	16.0	56.0
9.242000	33.6	9.000	L1	9.9	26.4	60.0
9.272000	33.9	9.000	L1	10.0	26.1	60.0
9.474000	34.6	9.000	L1	10.0	25.4	60.0
9.502000	34.3	9.000	L1	10.0	25.7	60.0
9.524000	34.7	9.000	L1	10.0	25.3	60.0
9.556000	37.9	9.000	L1	10.0	22.1	60.0



CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.0	9.000	L1	9.6	28.0	56.0
0.154000	30.3	9.000	L1	9.6	25.5	55.8
0.174000	33.6	9.000	L1	9.6	21.2	54.8
0.178000	32.8	9.000	L1	9.6	21.8	54.6
0.182000	32.8	9.000	L1	9.6	21.6	54.4
0.192000	28.2	9.000	L1	9.6	25.8	53.9
1.098000	31.8	9.000	L1	9.7	14.2	46.0
1.126000	32.5	9.000	L1	9.7	13.5	46.0
1.138000	32.8	9.000	L1	9.7	13.2	46.0
1.142000	32.6	9.000	L1	9.7	13.4	46.0
1.156000	32.2	9.000	L1	9.7	13.8	46.0
1.160000	32.3	9.000	L1	9.7	13.7	46.0
9.242000	26.8	9.000	L1	9.9	23.2	50.0
9.272000	26.7	9.000	L1	10.0	23.3	50.0
9.474000	27.5	9.000	L1	10.0	22.5	50.0
9.502000	27.6	9.000	L1	10.0	22.4	50.0
9.556000	27.8	9.000	L1	10.0	22.2	50.0
9.768000	26.3	9.000	L1	10.0	23.7	50.0

**Figure 2: Conducted Emission, AC Main Port, Line (N)**



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	44.3	9.000	N	9.6	21.5	65.8
0.164000	43.6	9.000	N	9.6	21.6	65.3
0.174000	44.7	9.000	N	9.6	20.1	64.8
0.180000	43.7	9.000	N	9.6	20.8	64.5
0.190000	42.2	9.000	N	9.7	21.9	64.0
0.194000	39.8	9.000	N	9.7	24.1	63.9
1.120000	35.3	9.000	N	9.7	20.7	56.0
1.136000	36.2	9.000	N	9.8	19.8	56.0
1.140000	36.7	9.000	N	9.8	19.3	56.0
1.146000	35.3	9.000	N	9.8	20.7	56.0
1.150000	35.9	9.000	N	9.8	20.1	56.0
1.158000	35.8	9.000	N	9.8	20.2	56.0
9.184000	34.1	9.000	N	10.0	25.9	60.0
9.294000	34.5	9.000	N	10.0	25.5	60.0
9.310000	35.1	9.000	N	10.0	24.9	60.0
9.322000	34.3	9.000	N	10.0	25.7	60.0
9.362000	35.0	9.000	N	10.0	25.0	60.0
9.398000	34.9	9.000	N	10.0	25.1	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	25.9	9.000	N	9.6	30.1	56.0
0.156000	29.6	9.000	N	9.6	26.0	55.7
0.164000	29.5	9.000	N	9.6	25.7	55.3
0.168000	31.8	9.000	N	9.6	23.3	55.1
0.176000	33.8	9.000	N	9.6	20.9	54.7
0.182000	32.9	9.000	N	9.6	21.5	54.4
1.120000	28.7	9.000	N	9.7	17.3	46.0
1.140000	29.6	9.000	N	9.8	16.4	46.0
1.144000	28.8	9.000	N	9.8	17.2	46.0
1.150000	28.7	9.000	N	9.8	17.3	46.0
1.158000	28.4	9.000	N	9.8	17.6	46.0
1.162000	28.6	9.000	N	9.8	17.4	46.0
9.256000	27.5	9.000	N	10.0	22.5	50.0
9.294000	27.6	9.000	N	10.0	22.4	50.0
9.310000	27.7	9.000	N	10.0	22.3	50.0
9.322000	27.7	9.000	N	10.0	22.3	50.0
9.326000	27.7	9.000	N	10.0	22.3	50.0
9.362000	27.9	9.000	N	10.0	22.1	50.0



5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Applicable Standards	FCC PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Worst Case of Operation Mode	Data communication mode (READ)
Kind of Test Site	3 m semi anechoic chamber
Temperature	24.0-24.6 °C
Relative Humidity	48.3-49.5 %
Test Date	September 06, 2018- September 14, 2018

Frequency (MHz)	Quasi Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
30.388000	25.1	100.0	V	270.0	18.7	14.9	40.0
275.992000	30.9	150.0	H	323.0	19.7	12.6	43.5
600.028800	38.6	100.0	V	345.0	27.5	7.4	46.0
711.108000	34.9	100.0	V	8.0	28.9	11.1	46.0
799.996800	40.7	120.0	H	46.0	30.2	5.3	46.0
960.000000	40.9	100.0	V	190.0	31.7	5.1	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Applicable Standards	FCC PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	2 690 MHz
Tested Frequency Range	1 GHz to 18 GHz
Worst Case of Operation Mode	Data communication mode (READ)
Kind of Test Site	3 m semi anechoic chamber
Temperature	24.0-24.6 °C
Relative Humidity	48.3-49.5 %
Test Date	September 06, 2018- September 14, 2018

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1400.020000	49.2	334.7	V	215.0	-28.5	24.8	74.0
1999.950000	51.9	100.0	V	49.0	-27.0	22.1	74.0
2588.445000	53.7	292.5	V	53.0	-24.1	20.3	74.0
4481.570000	40.4	231.4	V	45.0	-19.7	33.6	74.0
5989.915000	42.8	350.0	V	84.0	-16.6	31.2	74.0
9195.735000	42.9	100.0	V	296.0	-11.1	31.1	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1400.020000	48.0	334.7	V	215.0	-28.5	6.0	54.0
1999.950000	35.2	100.0	V	49.0	-27.0	18.8	54.0
2588.445000	30.8	292.5	V	53.0	-24.1	23.2	54.0
4481.570000	24.9	231.4	V	45.0	-19.7	29.1	54.0
5989.915000	26.6	350.0	V	84.0	-16.6	27.4	54.0
9195.735000	30.0	100.0	V	296.0	-11.1	24.0	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



6. CONCLUSION

The data collected shows that the **EUT Type: Mobile Phone, FCC ID: A3LSMJ610FN, Model: SM-J415FN/DS** complies with §15.107 and §15.109 of the FCC rules.



7. APPENDIX A. TEST SETUP PHOTOGRAPHS

Please refer to Appendix A