



**MEASUREMENT REPORT**  
**FCC Part 22 & 27 LTE**

**Applicant Name:**

Samsung Electronics Co., Ltd.

129, Samsung-ro,

Yeongtong-gu, Suwon-si

Gyeonggi-do, 16677, Korea

**Date of Testing:**

Jan 23 - Apr 07, 2017

**Test Site/Location:**

PCTEST Lab., Columbia, MD, USA

**Test Report Serial No.:**

1M1703150106-03.A3L

**FCC ID :**

**A3LSMJ727S**

**APPLICANT:**

**SAMSUNG ELECTRONICS CO., LTD.**

**Application Type:**

Certification

**FCC Classification:**

PCS Licensed Transmitter Held to Ear (PCE)

**FCC Rule Part(s):**

§2; §22; §27

**Test Procedure(s):**

ANSI/TIA-603-D-2010, KDB 971168 D01 v02r02

**EUT Type:**

Portable Handset

**Model:**

SM-J727S

**Test Device Serial No.:**

*identical prototype* [S/N: 21118, 27MAR-4]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez  
President




|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             |                                                                                       | Page 1 of 53                    |

# TABLE OF CONTENTS


|                                                               |    |
|---------------------------------------------------------------|----|
| FCC PART 22 & 27 MEASUREMENT REPORT .....                     | 3  |
| 1.0 INTRODUCTION .....                                        | 5  |
| 1.1 Scope.....                                                | 5  |
| 1.2 Testing Facility .....                                    | 5  |
| 2.0 PRODUCT INFORMATION.....                                  | 6  |
| 2.1 Equipment Description .....                               | 6  |
| 2.2 Device Capabilities .....                                 | 6  |
| 2.3 Test Configuration.....                                   | 6  |
| 2.4 EMI Suppression Device(s)/Modifications.....              | 6  |
| 3.0 DESCRIPTION OF TESTS .....                                | 7  |
| 3.1 Measurement Procedure.....                                | 7  |
| 3.2 Block A Frequency Range .....                             | 7  |
| 3.3 Cellular - Base Frequency Blocks .....                    | 7  |
| 3.4 Cellular - Mobile Frequency Blocks.....                   | 7  |
| 3.5 Radiated Power and Radiated Spurious Emissions.....       | 8  |
| 4.0 MEASUREMENT UNCERTAINTY .....                             | 9  |
| 5.0 TEST EQUIPMENT CALIBRATION DATA .....                     | 10 |
| 6.0 SAMPLE CALCULATIONS .....                                 | 11 |
| 7.0 TEST RESULTS.....                                         | 12 |
| 7.1 Summary.....                                              | 12 |
| 7.2 Occupied Bandwidth .....                                  | 13 |
| 7.3 Spurious and Harmonic Emissions at Antenna Terminal ..... | 20 |
| 7.4 Band Edge Emissions at Antenna Terminal.....              | 30 |
| 7.5 Radiated Power (ERP).....                                 | 39 |
| 7.6 Radiated Spurious Emissions Measurements.....             | 43 |
| 7.7 Frequency Stability / Temperature Variation .....         | 48 |
| 8.0 CONCLUSION.....                                           | 53 |

|                                                |                                                                                     |                                                                       |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMJ727S                      |  | <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1703150106-03.A3L | <b>Test Dates:</b><br>Jan 23 - Apr 07, 2017                                         | <b>EUT Type:</b><br>Portable Handset                                  | Page 2 of 53                                                                          |                                        |



## MEASUREMENT REPORT

### FCC Part 22 & 27




#### §2.1033 General Information

**APPLICANT:** Samsung Electronics Co., Ltd.  
**APPLICANT ADDRESS:** 129, Samsung-ro,  
 Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §22; §27  
**BASE MODEL:** SM-J727S  
**FCC ID:** A3LSMJ727S  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
**FREQUENCY TOLERANCE:**  $\pm 0.00025\%$  (2.5 ppm)  
**Test Device Serial No.:** 21118, 27MAR-4 ☐ Production ☒ Pre-Production ☐ Engineering  
**DATE(S) OF TEST:** Jan 23 - Apr 07, 2017  
**TEST REPORT S/N:** 1M1703150106-03.A3L


#### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             |                                                                                       | Page 3 of 53                    |



## MEASUREMENT REPORT

### FCC Part 22 & 27



| Mode        | FCC Rule Part | Tx Frequency (MHz) | ERP            |                  | Emission Designator | Modulation |
|-------------|---------------|--------------------|----------------|------------------|---------------------|------------|
|             |               |                    | Max. Power (W) | Max. Power (dBm) |                     |            |
| LTE Band 17 | 27            | 706.5 - 713.5      | 0.029          | 14.61            | 4M52G7D             | QPSK       |
| LTE Band 17 | 27            | 706.5 - 713.5      | 0.021          | 13.31            | 4M51W7D             | 16QAM      |
| LTE Band 17 | 27            | 709 - 711          | 0.029          | 14.59            | 8M98G7D             | QPSK       |
| LTE Band 17 | 27            | 709 - 711          | 0.022          | 13.51            | 8M99W7D             | 16QAM      |
| LTE Band 5  | 22H           | 824.7 - 848.3      | 0.143          | 21.54            | 1M15G7D             | QPSK       |
| LTE Band 5  | 22H           | 824.7 - 848.3      | 0.101          | 20.04            | 1M14W7D             | 16QAM      |
| LTE Band 5  | 22H           | 825.5 - 847.5      | 0.134          | 21.28            | 2M73G7D             | QPSK       |
| LTE Band 5  | 22H           | 825.5 - 847.5      | 0.104          | 20.19            | 2M75W7D             | 16QAM      |
| LTE Band 5  | 22H           | 826.5 - 846.5      | 0.139          | 21.43            | 4M52G7D             | QPSK       |
| LTE Band 5  | 22H           | 826.5 - 846.5      | 0.102          | 20.09            | 4M53W7D             | 16QAM      |
| LTE Band 5  | 22H           | 829 - 844          | 0.138          | 21.41            | 9M00G7D             | QPSK       |
| LTE Band 5  | 22H           | 829 - 844          | 0.102          | 20.07            | 9M02W7D             | 16QAM      |

#### EUT Overview

|                                         |                                      |                                                                                                                                                                                                                                             |  |                                 |
|-----------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------------------------|
| FCC ID: A3LSMJ727S                      |                                      |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT (CERTIFICATION)</b>  |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017 | EUT Type:<br>Portable Handset                                                                                                                                                                                                               |  | Page 4 of 53                    |

## 1.0 INTRODUCTION


### 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.



**Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area**

|                                         |                                                                                                                                                                                                                                                 |                               |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</b>  |                               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                                                                                                                                                                            | EUT Type:<br>Portable Handset | Page 5 of 53                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMJ727S**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

### 2.2 Device Capabilities

This device contains the following capabilities:

1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac  
UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

|                                                |                                             |                                                                                                                                                           |  |                                                                                                                                 |
|------------------------------------------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------------------------------------------------------------------------------------------------------------------------|
| FCC ID: A3LSMJ727S                             |                                             |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |  | <br><b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1703150106-03.A3L | <b>Test Dates:</b><br>Jan 23 - Apr 07, 2017 | <b>EUT Type:</b><br>Portable Handset                                                                                                                      |  | Page 6 of 53                                                                                                                    |

## 3.0 DESCRIPTION OF TESTS

### 3.1 Measurement Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-D-2010) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

### 3.2 Block A Frequency Range


#### §27.5(c)

**698-746 MHz band.** The following frequencies are available for licensing pursuant to this part in the 698-746 MHz band: (1) Three paired channel blocks of 12 megahertz each are available for assignment as follows:

Block A: 698-704 MHz and 728-734 MHz;  
Block B: 704-710 MHz and 734-740 MHz; and  
Block C: 710-716 MHz and 740-746 MHz.

### 3.3 Cellular - Base Frequency Blocks

#### §22.905




BLOCK 1: 869 – 880 MHz (A\* Low + A)  
BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A\* High)  
BLOCK 4: 891.5 – 894 MHz (B\*)

### 3.4 Cellular - Mobile Frequency Blocks

#### §22.905



BLOCK 1: 824 – 835 MHz (A\* Low + A)  
BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A\* High)  
BLOCK 4: 846.5 – 849 MHz (B\*)

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             |                                                                                       | Page 7 of 53                    |

### 3.5 Radiated Power and Radiated Spurious Emissions

\$2.1053 \$22.913(a.2) \$22.917(a) \$27.50(c.10) \$27.53(g)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v02r02.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

The calculated  $P_d$  levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of  $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$ .

|                                         |                                                                                                                                                                                                                                                 |                               |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</b>  |                               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                                                                                                                                                                            | EUT Type:<br>Portable Handset | Page 8 of 53                    |

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution                     | Expanded Uncertainty ( $\pm$ dB) |
|----------------------------------|----------------------------------|
| Conducted Bench Top Measurements | 1.13                             |
| Radiated Disturbance (<1GHz)     | 4.98                             |
| Radiated Disturbance (>1GHz)     | 5.07                             |
| Radiated Disturbance (>18GHz)    | 5.09                             |

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             |                                                                                       | Page 9 of 53                    |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.10-2013.

| Manufacturer    | Model              | Description                            | Cal Date   | Cal Interval | Cal Due    | Serial Number        |
|-----------------|--------------------|----------------------------------------|------------|--------------|------------|----------------------|
| -               | RE1                | Radiated Emissions Cable Set (UHF/EHF) | 7/11/2016  | Annual       | 7/11/2017  | RE1                  |
| -               | LTx1               | Licensed Transmitter Cable Set         | 4/11/2016  | Annual       | 4/11/2017  | LTx1                 |
| Agilent         | N9030A             | PXA Signal Analyzer (44GHz)            | 4/1/2016   | Annual       | 4/1/2017   | MY52350166           |
| Agilent         | N9020A             | MXA Signal Analyzer                    | 10/28/2016 | Annual       | 10/28/2017 | US46470561           |
| Anritsu         | MT8820C            | Radio Communication Analyzer           | 9/15/2016  | Annual       | 9/15/2017  | 6200901190           |
| Com-Power       | PAM-103            | Pre-Amplifier (1-1000MHz)              | 7/6/2016   | Annual       | 7/6/2017   | 441119               |
| Com-Power       | AL-130             | 9kHz - 30MHz Loop Antenna              | 7/30/2015  | Biennial     | 7/30/2017  | 121034               |
| Com-Power       | PAM-118A           | Pre-Amplifier                          | 7/26/2016  | Annual       | 7/26/2017  | 551080               |
| Emco            | 3115               | Horn Antenna (1-18GHz)                 | 3/10/2016  | Biennial     | 3/10/2018  | 9704-5182            |
| EMCO            | 3160-09            | Small Horn (18 - 26.5GHz)              | 8/23/2016  | Biennial     | 8/23/2018  | 135427               |
| Espec           | ESX-2CA            | Environmental Chamber                  | 3/4/2016   | Annual       | 4/4/2017   | 17620                |
| ETS Lindgren    | 3164-08            | Quad Ridge Horn Antenna                | 12/5/2016  | Biennial     | 12/5/2018  | 128338               |
| ETS Lindgren    | 3164-08            | Quad Ridge Horn Antenna                | 4/26/2016  | Biennial     | 4/26/2018  | 128337               |
| ETS Lindgren    | 3117               | 1-18 GHz DRG Horn (Medium)             | 12/1/2016  | Biennial     | 12/1/2018  | 125518               |
| K & L           | 11SH10-3075/U18000 | High Pass Filter                       | 7/11/2016  | Annual       | 7/11/2017  | 11SH10-3075/U18000-2 |
| K & L           | 13SH10-1000/U1000  | N Type High Pass Filter                | 7/6/2016   | Annual       | 7/6/2017   | 13SH10-1000/U1000-1  |
| Mini Circuits   | PWR-SEN-4GHS       | USB Power Sensor                       | 3/4/2016   | Annual       | 4/4/2017   | 11401010036          |
| Mini Circuits   | TVA-11-422         | RF Power Amp                           | N/A        |              |            | QA1317001            |
| Mini-Circuits   | SSG-4000HP         | Synthesized Signal Generator           | N/A        |              |            | 11208010032          |
| Mini-Circuits   | PWR-SENS-4RMS      | USB Power Sensor                       | 3/4/2016   | Annual       | 4/4/2017   | 11210140001          |
| PCTEST          | -                  | EMC Switch System                      | 7/11/2016  | Annual       | 7/11/2017  | NM1                  |
| PCTEST          | -                  | EMC Switch System                      | 7/6/2016   | Annual       | 7/6/2017   | NM2                  |
| Rohde & Schwarz | ESU26              | EMI Test Receiver (26.5GHz)            | 5/16/2016  | Annual       | 5/16/2017  | 100342               |
| Rohde & Schwarz | TS-PR26            | 18-26.5 GHz Pre-Amplifier              | 3/7/2016   | Annual       | 4/7/2017   | 100040               |
| Rohde & Schwarz | CMW500             | Radio Communication Tester             | 10/20/2016 | Annual       | 10/20/2017 | 100976               |
| Rohde & Schwarz | ESU40              | EMI Test Receiver (40GHz)              | 7/15/2016  | Annual       | 7/15/2017  | 100348               |
| Schwarzbeck     | UHA 9105           | Dipole Antenna (400 - 1GHz) Tx         | 3/30/2016  | Biennial     | 3/30/2018  | 9105-2403            |
| Schwarzbeck     | UHA 9105           | Dipole Antenna (400 - 1GHz) Rx         | 3/30/2016  | Biennial     | 3/30/2018  | 9105-2404            |
| Seekonk         | NC-100             | Torque Wrench 5/16", 8" lbs            | 3/2/2016   | Biennial     | 3/2/2018   | N/A                  |
| Sunol           | DRH-118            | Horn Antenna (1-18GHz)                 | 7/30/2015  | Biennial     | 7/30/2017  | A050307              |
| Sunol           | JB5                | Bi-Log Antenna (30M - 5GHz)            | 3/14/2016  | Biennial     | 3/14/2018  | A051107              |

**Table 5-1. Test Equipment**

### Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

|                                         |                                                                                                                                                                                                                                             |                               |                                 |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT (CERTIFICATION)</b>  |                               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                                                                                                                                                                        | EUT Type:<br>Portable Handset | Page 10 of 53                   |

## 6.0 SAMPLE CALCULATIONS

### Emission Designator

#### QPSK Modulation

**Emission Designator = 8M62G7D**

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

#### 16QAM Modulation

**Emission Designator = 8M45W7D**

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

### Spurious Radiated Emission – LTE Band

#### **Example: Middle Channel LTE Mode 2<sup>nd</sup> Harmonic (1564 MHz)**

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm.

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             | Page 11 of 53                                                                         |                                 |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LSMJ727S  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): LTE

| FCC Part Section(s)          | Test Description                   | Test Limit                                                                                       | Test Condition | Result | Reference              |
|------------------------------|------------------------------------|--------------------------------------------------------------------------------------------------|----------------|--------|------------------------|
| 2.1049                       | Occupied Bandwidth                 | N/A                                                                                              | CONDUCTED      | PASS   | Section 7.2            |
| 2.1051 22.917(a)<br>27.53(g) | Out of Band Emissions              | $> 43 + 10\log_{10} (P[\text{Watts}])$ at Band Edge and for all out-of-band emissions            |                | PASS   | Section 7.3, 7.4       |
| 2.1046                       | Transmitter Conducted Output Power | N/A                                                                                              |                | PASS   | See RF Exposure Report |
| 2.1055. 22.355<br>27.54      | Frequency Stability                | $< 2.5$ ppm (Part 22) and fundamental emissions stay within authorized frequency block (Part 27) |                | PASS   | Section 7.7            |
| 22.913(a.2)                  | Effective Radiated Power (Band 5)  | $< 7$ Watts max. ERP                                                                             | RADIATED       | PASS   | Section 7.5            |
| 27.50(c.10)                  | Effective Radiated Power (Band 17) | $< 3$ Watts max. ERP                                                                             |                | PASS   | Section 7.5            |
| 2.1053 22.917(a)<br>27.53(g) | Undesirable Emissions              | $> 43 + 10\log_{10} (P[\text{Watts}])$ for all out-of-band emissions                             |                | PASS   | Section 7.6            |

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots (Sections 7.2, 7.3, 7.4) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 4.5.

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             | Page 12 of 53                                                                         |                                 |

## 7.2 Occupied Bandwidth

\$2.1049

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used


KDB 971168 D01 v02r02 – Section 4.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-1. Test Instrument & Measurement Setup**


### Test Notes

None.

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             | Page 13 of 53  |                                 |




Plot 7-1. Occupied Bandwidth Plot (Band 17 – 5.0MHz QPSK – RB Size 25)



Plot 7-2. Occupied Bandwidth Plot (Band 17 – 5.0MHz 16-QAM – RB Size 25)

|                                         |                                      |                               |                                                           |  |                                 |
|-----------------------------------------|--------------------------------------|-------------------------------|-----------------------------------------------------------|--|---------------------------------|
| FCC ID: A3LSMJ727S                      |                                      |                               | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017 | EUT Type:<br>Portable Handset | Page 14 of 53                                             |  |                                 |




Plot 7-3. Occupied Bandwidth Plot (Band 17 – 10.0MHz QPSK – RB Size 50)




Plot 7-4. Occupied Bandwidth Plot (Band 17 – 10.0MHz 16-QAM – RB Size 50)

|                                         |                                                                   |                               |                                        |
|-----------------------------------------|-------------------------------------------------------------------|-------------------------------|----------------------------------------|
| FCC ID: A3LSMJ727S                      | <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT (CERTIFICATION)</b> |                               | <b>Approved by:</b><br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                              | EUT Type:<br>Portable Handset | Page 15 of 53                          |



Plot 7-5. Occupied Bandwidth Plot (Band 5 – 1.4MHz QPSK – RB Size 6)




Plot 7-6. Occupied Bandwidth Plot (Band 5 – 1.4MHz 16-QAM – RB Size 6)

|                                         |                                               |                               |                                                           |  |                                 |
|-----------------------------------------|-----------------------------------------------|-------------------------------|-----------------------------------------------------------|--|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. |                               | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset |                                                           |  | Page 16 of 53                   |


© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.




Plot 7-7. Occupied Bandwidth Plot (Band 5 – 3.0MHz QPSK – RB Size 15)




Plot 7-8. Occupied Bandwidth Plot (Band 5 – 3.0MHz 16-QAM – RB Size 15)

|                                         |                                      |                               |                                                           |  |                                 |
|-----------------------------------------|--------------------------------------|-------------------------------|-----------------------------------------------------------|--|---------------------------------|
| FCC ID: A3LSMJ727S                      |                                      |                               | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017 | EUT Type:<br>Portable Handset | Page 17 of 53                                             |  |                                 |




Plot 7-9. Occupied Bandwidth Plot (Band 5 - 5.0MHz QPSK - RB Size 25)




Plot 7-10. Occupied Bandwidth Plot (Band 5 - 5.0MHz 16-QAM - RB Size 25)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 18 of 53                   |



Plot 7-11. Occupied Bandwidth Plot (Band 5 – 10.0MHz QPSK – RB Size 50)



Plot 7-12. Occupied Bandwidth Plot (Band 5 – 10.0MHz 16-QAM – RB Size 50)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 19 of 53                   |

### 7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) §27.53(g)

#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

#### Test Procedure Used


KDB 971168 D01 v02r02 – Section 6.0

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to at least 10 \* the fundamental frequency (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**


#### Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             | Page 20 of 53  |                                 |




Plot 7-13. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-14. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

|                                                |                                                                                                                                                           |                                      |                                                                                                                              |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| FCC ID: A3LSMJ727S                             |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                                      |  <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1703150106-03.A3L | <b>Test Dates:</b><br>Jan 23 - Apr 07, 2017                                                                                                               | <b>EUT Type:</b><br>Portable Handset | Page 21 of 53                                                                                                                |




Plot 7-15. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-16. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 22 of 53                   |




Plot 7-17. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 7-18. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 23 of 53                   |




Plot 7-19. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 7-20. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 24 of 53                   |




Plot 7-21. Conducted Spurious Plot (Band 17 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 7-22. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 25 of 53                   |




Plot 7-23. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-24. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 26 of 53                   |




**Plot 7-25. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)**




**Plot 7-26. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)**

|                                                |                                                                                                                                                                                                                                                 |                                      |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| FCC ID: A3LSMJ727S                             |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</b>  |                                      | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1703150106-03.A3L | <b>Test Dates:</b><br>Jan 23 - Apr 07, 2017                                                                                                                                                                                                     | <b>EUT Type:</b><br>Portable Handset | Page 27 of 53                          |




Plot 7-27. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 7-28. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 28 of 53                   |



Plot 7-29. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – High Channel)



Plot 7-30. Conducted Spurious Plot (Band 5 – 1.4MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 29 of 53                   |

## 7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §27.53(g)

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{\text{Watts}})$ , where  $P$  is the transmitter power in Watts.***

### Test Procedure Used


KDB 971168 D01 v02r02 – Section 6.0

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW  $\geq 1\%$  of the emission bandwidth
4. VBW  $\geq 3 \times$  RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times$  Span/RBW
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-3. Test Instrument & Measurement Setup**

### Test Notes


Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             | Page 30 of 53  |                                 |



Plot 7-31. Lower Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)




Plot 7-32. Lower Extended Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 31 of 53                   |



Plot 7-33. Upper Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)



Plot 7-34. Lower Band Edge Plot (Band 17 – 10.0MHz QPSK – RB Size 50)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 32 of 53                   |


© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.





Plot 7-35. Upper Band Edge Plot (Band 17 – 10.0MHz QPSK – RB Size 50)




Plot 7-36. Lower Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)


|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 33 of 53                   |



|                                                |                                                                                                                                                                                                                                                 |                                      |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| FCC ID: A3LSMJ727S                             |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</b>  |                                      | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1703150106-03.A3L | <b>Test Dates:</b><br>Jan 23 - Apr 07, 2017                                                                                                                                                                                                     | <b>EUT Type:</b><br>Portable Handset | Page 34 of 53                          |



Plot 7-39. Upper Extended Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)




Plot 7-40. Lower Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 35 of 53                   |



Plot 7-41. Upper Band Edge Plot (Band 5 - 3.0MHz QPSK - RB Size 15)




Plot 7-42. Lower Band Edge Plot (Band 5 - 5.0MHz QPSK - RB Size 25)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 36 of 53                   |



Plot 7-43. Upper Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)




Plot 7-44. Lower Band Edge Plot (Band 5 – 10.0MHz QPSK – RB Size 50)

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 37 of 53                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.



Plot 7-45. Upper Band Edge Plot (Band 5 – 10.0MHz QPSK – RB Size 50)

|                                         |                                                                       |                               |                                 |
|-----------------------------------------|-----------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                  | EUT Type:<br>Portable Handset | Page 38 of 53                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3

/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

## 7.5 Radiated Power (ERP)

\$22.913(a.2) \$27.50(c.10)

### Test Overview

Effective Radiated Power (ERP) measurement is performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17


### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq 3 \times$  RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq 2 \times$  span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize


|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             | Page 39 of 53                                                                         |                                 |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Radiated Test Setup <1GHz**



**Figure 7-5. Radiated Test Setup >1GHz**

## Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 40 of 53                   |

| Frequency [MHz] | Channel Bandwidth [MHz] | Mod.   | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | RB Size/Offset | Substitute Level [dBm] | Ant. Gain [dBd] | ERP [dBm] | ERP Limit [dBm] | Margin [dB] |
|-----------------|-------------------------|--------|-----------------|---------------------|----------------------------|----------------|------------------------|-----------------|-----------|-----------------|-------------|
| 706.50          | 5                       | QPSK   | H               | 104                 | 81                         | 1 / 0          | 14.89                  | -0.28           | 14.61     | 34.77           | -20.16      |
| 710.00          | 5                       | QPSK   | H               | 105                 | 78                         | 1 / 0          | 14.69                  | -0.29           | 14.40     | 34.77           | -20.37      |
| 713.50          | 5                       | QPSK   | H               | 110                 | 85                         | 1 / 0          | 14.60                  | -0.30           | 14.29     | 34.77           | -20.48      |
| 706.50          | 5                       | 16-QAM | H               | 104                 | 81                         | 1 / 0          | 13.59                  | -0.28           | 13.31     | 34.77           | -21.46      |
| 709.00          | 10                      | QPSK   | H               | 100                 | 91                         | 1 / 0          | 13.82                  | -0.29           | 13.53     | 34.77           | -21.24      |
| 710.00          | 10                      | QPSK   | H               | 103                 | 85                         | 1 / 0          | 14.88                  | -0.29           | 14.59     | 34.77           | -20.18      |
| 711.00          | 10                      | QPSK   | H               | 104                 | 85                         | 1 / 0          | 14.89                  | -0.29           | 14.59     | 34.77           | -20.18      |
| 710.00          | 10                      | 16-QAM | H               | 103                 | 85                         | 1 / 0          | 13.80                  | -0.29           | 13.51     | 34.77           | -21.26      |
| 706.50          | 5                       | QPSK   | V               | 137                 | 61                         | 1 / 0          | 14.83                  | -0.29           | 14.54     | 34.77           | -20.23      |

**Table 7-2. ERP Data (Band 17)**

|                                                |                                                                                     |                                                                   |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMJ727S                      |  | <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT (CERTIFICATION)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1703150106-03.A3L | <b>Test Dates:</b><br>Jan 23 - Apr 07, 2017                                         | <b>EUT Type:</b><br>Portable Handset                              |                                                                                       | Page 41 of 53                          |

| Frequency [MHz] | Channel Bandwidth [MHz] | Mod.   | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | RB Size/Offset | Substitute Level [dBm] | Ant. Gain [dBd] | ERP [dBm] | ERP Limit [dBm] | Margin [dB] |
|-----------------|-------------------------|--------|-----------------|---------------------|----------------------------|----------------|------------------------|-----------------|-----------|-----------------|-------------|
| 824.70          | 1.4                     | QPSK   | H               | 150                 | 73                         | 1 / 0          | 22.19                  | -0.65           | 21.54     | 38.45           | -16.91      |
| 836.50          | 1.4                     | QPSK   | H               | 150                 | 70                         | 1 / 0          | 21.67                  | -0.65           | 21.02     | 38.45           | -17.43      |
| 848.30          | 1.4                     | QPSK   | H               | 150                 | 70                         | 1 / 0          | 21.19                  | -0.65           | 20.54     | 38.45           | -17.91      |
| 824.70          | 1.4                     | 16-QAM | H               | 150                 | 73                         | 1 / 0          | 20.69                  | -0.65           | 20.04     | 38.45           | -18.41      |
| 825.50          | 3                       | QPSK   | H               | 190                 | 62                         | 1 / 0          | 19.99                  | -0.65           | 19.34     | 38.45           | -19.11      |
| 836.50          | 3                       | QPSK   | H               | 150                 | 72                         | 1 / 0          | 21.93                  | -0.65           | 21.28     | 38.45           | -17.17      |
| 847.50          | 3                       | QPSK   | H               | 150                 | 75                         | 1 / 0          | 21.34                  | -0.65           | 20.69     | 38.45           | -17.76      |
| 825.50          | 3                       | 16-QAM | H               | 190                 | 62                         | 1 / 0          | 20.84                  | -0.65           | 20.19     | 38.45           | -18.26      |
| 826.50          | 5                       | QPSK   | H               | 150                 | 73                         | 1 / 0          | 22.08                  | -0.65           | 21.43     | 38.45           | -17.02      |
| 836.50          | 5                       | QPSK   | H               | 150                 | 70                         | 1 / 0          | 21.57                  | -0.65           | 20.92     | 38.45           | -17.53      |
| 846.50          | 5                       | QPSK   | H               | 150                 | 75                         | 1 / 0          | 21.34                  | -0.65           | 20.69     | 38.45           | -17.76      |
| 826.50          | 5                       | 16-QAM | H               | 150                 | 73                         | 1 / 0          | 20.74                  | -0.65           | 20.09     | 38.45           | -18.36      |
| 829.00          | 10                      | QPSK   | H               | 150                 | 70                         | 1 / 0          | 22.06                  | -0.65           | 21.41     | 38.45           | -17.04      |
| 836.50          | 10                      | QPSK   | H               | 150                 | 75                         | 1 / 0          | 21.60                  | -0.65           | 20.95     | 38.45           | -17.50      |
| 844.00          | 10                      | QPSK   | H               | 150                 | 73                         | 1 / 0          | 21.48                  | -0.65           | 20.83     | 38.45           | -17.62      |
| 829.00          | 10                      | 16-QAM | H               | 150                 | 70                         | 1 / 0          | 20.72                  | -0.65           | 20.07     | 38.45           | -18.38      |
| 824.70          | 1.4                     | QPSK   | V               | 150                 | 170                        | 1 / 0          | 18.56                  | -0.65           | 17.91     | 38.45           | -20.54      |

**Table 7-3. ERP Data (Band 5)**

|                                         |                                                                                                                                                                                                                                                                                                                                     |                               |               |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <div><b>PCTEST<sup>®</sup></b><br/>ENGINEERING LABORATORY, INC.</div> <div>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT<br/>(CERTIFICATION)</div> <div></div> |                               |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                                                                                                                                                                                                                                                                | EUT Type:<br>Portable Handset | Page 42 of 53 |                                 |

## 7.6 Radiated Spurious Emissions Measurements

\$2.1053 \$22.917(a) \$27.53(g)

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12


### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq 2 \times$  span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             | Page 43 of 53                                                                         |                                 |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-6. Test Instrument & Measurement Setup**

## Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 5) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

|                                         |                                               |                                                           |                |                                 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMJ727S                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017          | EUT Type:<br>Portable Handset                             |                | Page 44 of 53                   |

OPERATING FREQUENCY: 706.50 MHz  
 CHANNEL: 23755  
 MEASURED OUTPUT POWER: 14.61 dBm = 0.029 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  27.61 dBc

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | [dBc] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------|
| 1413.00         | H               | 100                 | 5                          | -56.30                           | 6.22                          | -50.08                        | 64.7  |
| 2119.50         | H               | 100                 | 201                        | -59.38                           | 6.80                          | -52.58                        | 67.2  |
| 2826.00         | H               | 153                 | 23                         | -59.77                           | 8.06                          | -51.70                        | 66.3  |
| 3532.50         | H               | -                   | -                          | -57.43                           | 7.66                          | -49.76                        | 64.4  |

**Table 7-4. Radiated Spurious Data (Band 17 – Low Channel)**

OPERATING FREQUENCY: 710.00 MHz  
 CHANNEL: 23790  
 MEASURED OUTPUT POWER: 14.40 dBm = 0.028 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  27.40 dBc

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | [dBc] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------|
| 1420.00         | H               | 100                 | 5                          | -59.04                           | 6.24                          | -52.80                        | 67.2  |
| 2130.00         | H               | -                   | -                          | -60.67                           | 6.81                          | -53.85                        | 68.3  |

**Table 7-5. Radiated Spurious Data (Band 17 – Mid Channel)**

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             | Page 45 of 53                                                                         |                                 |

OPERATING FREQUENCY: 713.50 MHz  
 CHANNEL: 23825  
 MEASURED OUTPUT POWER: 14.29 dBm = 0.027 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  27.29 dBc

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | [dBc] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------|
| 1427.00         | H               | -                   | -                          | -64.88                           | 6.27                          | -58.62                        | 72.9  |
| 2140.50         | H               | -                   | -                          | -60.54                           | 6.83                          | -53.70                        | 68.0  |

**Table 7-6. Radiated Spurious Data (Band 17 – High Channel)**

OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 20407  
 MEASURED OUTPUT POWER: 21.54 dBm = 0.143 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 1.4 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.54 dBc

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | [dBc] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------|
| 1649.40         | H               | 122                 | 2                          | -68.53                           | 6.29                          | -62.24                        | 83.8  |
| 2474.10         | H               | 181                 | 284                        | -65.54                           | 6.85                          | -58.69                        | 80.2  |
| 3298.80         | H               | -                   | -                          | -63.97                           | 7.13                          | -56.84                        | 78.4  |

**Table 7-7. Radiated Spurious Data (Band 5 – Low Channel)**

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             |                                                                                       | Page 46 of 53                   |

OPERATING FREQUENCY: 836.50 MHz  
 CHANNEL: 20525  
 MEASURED OUTPUT POWER: 21.02 dBm = 0.126 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 1.4 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  34.02 dBc

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | [dBc] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------|
| 1673.00         | H               | 228                 | 192                        | -68.64                           | 6.21                          | -62.43                        | 83.4  |
| 2509.50         | H               | 100                 | 40                         | -62.75                           | 6.86                          | -55.89                        | 76.9  |
| 3346.00         | H               | 181                 | 46                         | -63.86                           | 7.26                          | -56.59                        | 77.6  |
| 4182.50         | H               | -                   | -                          | -66.86                           | 8.07                          | -58.79                        | 79.8  |

**Table 7-8. Radiated Spurious Data (Band 5 – Mid Channel)**

OPERATING FREQUENCY: 848.30 MHz  
 CHANNEL: 20643  
 MEASURED OUTPUT POWER: 20.54 dBm = 0.113 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 1.4 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  33.54 dBc

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | [dBc] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------|
| 1696.60         | H               | 295                 | 101                        | -67.35                           | 6.13                          | -61.23                        | 81.8  |
| 2544.90         | H               | 385                 | 253                        | -65.54                           | 6.96                          | -58.58                        | 79.1  |
| 3393.20         | H               | 151                 | 316                        | -62.70                           | 7.39                          | -55.31                        | 75.8  |
| 4241.50         | H               | -                   | -                          | -66.92                           | 8.36                          | -58.56                        | 79.1  |

**Table 7-9. Radiated Spurious Data (Band 5 – High Channel)**

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             |                                                                                       | Page 47 of 53                   |

## 7.7 Frequency Stability / Temperature Variation

\$2.1055 \$22.355 \$27.54

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 22, the frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency. For Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.***

### Test Procedure Used

ANSI/TIA-603-D-2010

### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

### Test Notes

None

|                                         |                                                                                     |                                                           |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             | Page 48 of 53                                                                         |                                 |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## Band 17 Frequency Stability Measurements

\$2.1055 \$27.54

OPERATING FREQUENCY: 710,000,000 Hz

CHANNEL: 23090

REFERENCE VOLTAGE: 3.85 VDC


| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 3.85        | + 20 (Ref) | 709,999,865    | -135            | -0.0000190    |
| 100 %          |             | - 30       | 709,999,876    | -124            | -0.0000175    |
| 100 %          |             | - 20       | 710,000,090    | 90              | 0.0000127     |
| 100 %          |             | - 10       | 710,000,016    | 16              | 0.0000023     |
| 100 %          |             | 0          | 709,999,863    | -137            | -0.0000193    |
| 100 %          |             | + 10       | 709,999,830    | -170            | -0.0000239    |
| 100 %          |             | + 20       | 709,999,865    | -135            | -0.0000190    |
| 100 %          |             | + 30       | 709,999,799    | -201            | -0.0000283    |
| 100 %          |             | + 40       | 709,999,897    | -103            | -0.0000145    |
| 100 %          |             | + 50       | 709,999,885    | -115            | -0.0000162    |
| BATT. ENDPOINT | 3.40        | + 20       | 709,999,777    | -223            | -0.0000314    |

**Table 7-10. Frequency Stability Data (Band 17)**

|                                         |                                                                                                                                                                                                                                             |                               |                                 |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT (CERTIFICATION)</b>  |                               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                                                                                                                                                                        | EUT Type:<br>Portable Handset | Page 49 of 53                   |

## Band 17 Frequency Stability Measurements

\$2.1055 \$27.54



**Figure 7-7. Frequency Stability Graph (Band 17)**

|                                         |                                      |                                                           |  |  |                                 |
|-----------------------------------------|--------------------------------------|-----------------------------------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMJ727S                      |                                      | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017 | EUT Type:<br>Portable Handset                             |  |  | Page 50 of 53                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## Band 5 Frequency Stability Measurements

\$2.1055 \$22.355

OPERATING FREQUENCY: 836,500,000 Hz

CHANNEL: 20525

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm


| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 3.85        | + 20 (Ref) | 836,499,994    | -6              | -0.0000007    |
| 100 %          |             | - 30       | 836,499,954    | -46             | -0.0000055    |
| 100 %          |             | - 20       | 836,500,014    | 14              | 0.0000017     |
| 100 %          |             | - 10       | 836,500,205    | 205             | 0.0000245     |
| 100 %          |             | 0          | 836,500,259    | 259             | 0.0000310     |
| 100 %          |             | + 10       | 836,500,178    | 178             | 0.0000213     |
| 100 %          |             | + 20       | 836,499,743    | -257            | -0.0000307    |
| 100 %          |             | + 30       | 836,499,986    | -14             | -0.0000017    |
| 100 %          |             | + 40       | 836,499,910    | -90             | -0.0000108    |
| 100 %          |             | + 50       | 836,500,132    | 132             | 0.0000158     |
| BATT. ENDPOINT | 3.40        | + 20       | 836,500,286    | 286             | 0.0000342     |

**Table 7-11. Frequency Stability Data (Band 5)**

|                                         |                                                                                                                                                                                                                                             |                               |                                 |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  <b>FCC Pt. 22 &amp; 27 LTE MEASUREMENT REPORT (CERTIFICATION)</b>  |                               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                                                                                                                                                                        | EUT Type:<br>Portable Handset | Page 51 of 53                   |

## Band 5 Frequency Stability Measurements

\$2.1055 \$22.355



**Figure 7-8. Frequency Stability Graph (Band 5)**

|                                         |                                      |                               |                                                           |                                     |
|-----------------------------------------|--------------------------------------|-------------------------------|-----------------------------------------------------------|-------------------------------------|
| FCC ID: A3LSMJ727S                      |                                      |                               | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) | <br>Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017 | EUT Type:<br>Portable Handset | Page 52 of 53                                             |                                     |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMJ727S** complies with all the requirements of Parts 22 & 27 of the FCC rules for LTE operation only.

|                                         |                                                                                     |                                                           |  |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|--|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMJ727S                      |  | FCC Pt. 22 & 27 LTE MEASUREMENT REPORT<br>(CERTIFICATION) |  |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1703150106-03.A3L | Test Dates:<br>Jan 23 - Apr 07, 2017                                                | EUT Type:<br>Portable Handset                             |  |                                                                                       | Page 53 of 53                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.3  
/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).