



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

02/19/18 - 04/03/18

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M1802160028-01-R2.A3L

FCC ID:

A3LSMJ737P

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model:

SM-J737P

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1g Head (W/kg)	1g Body-Worn (W/kg)	1g Hotspot (W/kg)	10g Phablet (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.26	0.33	0.55	N/A
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.50	0.23	0.59	N/A
PCE	UMTS 850	826.40 - 846.60 MHz	0.25	0.31	0.36	N/A
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.54	0.31	0.58	2.96
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.71	0.50	0.80	2.65
PCE	CDMA/EVDO BC10 (\$90S)	817.90 - 823.10 MHz	0.31	0.42	0.46	N/A
PCE	CDMA/EVDO BC0 (\$22H)	824.70 - 848.31 MHz	0.40	0.44	0.46	N/A
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.96	0.76	0.96	3.29
PCE	LTE Band 12	699.7 - 715.3 MHz	0.29	0.60	0.73	N/A
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.38	0.51	0.64	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.67	0.40	0.52	2.53
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.69	0.60	0.74	3.13
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.74	0.56	0.80	2.78
PCE	LTE Band 41	2498.5 - 2687.5 MHz	0.51	0.50	1.20	N/A
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.82	< 0.1	0.15	N/A
Nil	U-NII-1	5180 - 5240 MHz	N/A	N/A	N/A	N/A
Nil	U-NII-2A	5260 - 5320 MHz	0.92	0.16	N/A	1.14
Nil	U-NII-2C	5500 - 5720 MHz	0.82	0.17	N/A	1.02
Nil	U-NII-3	5745 - 5825 MHz	0.88	0.21	0.55	N/A
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A			
Simultaneous SAR per KDB 690783 D01v01r03:			1.59	0.97	1.52	3.91

Note: This revised Test Report (S/N: 1M1802160028-01-R2.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortaez
President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 1 of 107	

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	10
3	INTRODUCTION	11
4	DOSIMETRIC ASSESSMENT	12
5	DEFINITION OF REFERENCE POINTS	13
6	TEST CONFIGURATION POSITIONS	14
7	RF EXPOSURE LIMITS	18
8	FCC MEASUREMENT PROCEDURES.....	19
9	RF CONDUCTED POWERS.....	26
10	SYSTEM VERIFICATION.....	60
11	SAR DATA SUMMARY	64
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	85
13	SAR MEASUREMENT VARIABILITY	99
14	ADDITIONAL TESTING PER FCC GUIDANCE	100
15	EQUIPMENT LIST	103
16	MEASUREMENT UNCERTAINTIES.....	104
17	CONCLUSION.....	105
18	REFERENCES	106
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: POWER REDUCTION VERIFICATION		

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 2 of 107

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
CDMA/EVDO BC10 (S90S)	Voice/Data	817.90 - 823.10 MHz
CDMA/EVDO BC0 (S22H)	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 26 (Cell)	Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
ANT+	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device utilizes a power reduction mechanism for some wireless modes and bands for SAR compliance under portable hotspot conditions, under held-to-ear conditions during voice or VOIP scenarios, and under some conditions when the device is being used in close proximity to the user's hand. All hotspot SAR evaluations for this device were performed at the maximum allowed output power when hotspot is enabled. Held-to-ear exposure conditions were evaluated at reduced power for the applicable modes per FCC guidance. Additionally, FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device when being used in phablet use conditions. Detailed descriptions of the power reduction mechanism are included in the operational description.

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 3 of 107

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Output Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.0	33.0	31.0	29.0	27.5	26.5	25.0	24.0	23.0
	Nominal	32.0	32.0	30.0	28.0	26.5	25.5	24.0	23.0	22.0
GSM/GPRS/EDGE 1900	Maximum	30.0	30.0	28.0	26.0	24.0	26.5	24.5	23.0	22.5
	Nominal	29.0	29.0	27.0	25.0	23.0	25.5	23.5	22.0	21.5

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	24.0	23.5	23.5
	Nominal	23.0	22.5	22.5
UMTS Band 4 (1750 MHz)	Maximum	23.0	23.0	22.5
	Nominal	22.0	22.0	21.5
UMTS Band 2 (1900 MHz)	Maximum	23.0	23.0	23.0
	Nominal	22.0	22.0	22.0

Mode / Band		Modulated Average (dBm)		
		1x-RTT	EVDO Rev 0	EVDO Rev A
CDMA/EVDO BC10 (\$90S)	Maximum	25.5	25.5	25.5
	Nominal	24.5	24.5	24.5
CDMA/EVDO BC0 (\$22H)	Maximum	25.5	25.0	25.0
	Nominal	24.5	24.0	24.0
PCS CDMA/EVDO	Maximum	24.5	24.5	24.5
	Nominal	23.5	23.5	23.5

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	25.5
	Nominal	24.5
LTE Band 26 (Cell)	Maximum	25.5
	Nominal	24.5
LTE Band 5 (Cell)	Maximum	25.5
	Nominal	24.5
LTE Band 4 (AWS)	Maximum	24.5
	Nominal	23.5
LTE Band 25 (PCS)	Maximum	24.5
	Nominal	23.5
LTE Band 2 (PCS)	Maximum	24.5
	Nominal	23.5
LTE Band 41 PC3	Maximum	24.0
	Nominal	23.0
LTE Band 41 PC2	Maximum	27.5
	Nominal	26.5

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 4 of 107

Mode / Band		Modulated Average (dBm)		
		Ch 1	Ch 2-10	Ch 11
IEEE 802.11b (2.4 GHz)	Maximum	16.0		
	Nominal	15.0		
IEEE 802.11g (2.4 GHz)	Maximum	14.0	16.0	14.0
	Nominal	13.0	15.0	13.0
IEEE 802.11n (2.4 GHz)	Maximum	14.0	16.0	14.0
	Nominal	13.0	15.0	13.0

Mode / Band		Modulated Average (dBm)									
		20 MHz Bandwidth		40 MHz Bandwidth				80 MHz Bandwidth			
		Ch 36, 64, 100, 165	Ch 40-60, 104-161	Ch 38	Ch 62	Ch 102, 159	Ch 46-54, 110-151	Ch 42	Ch 58	Ch 106	Ch 122-155
IEEE 802.11a (5 GHz)	Maximum	14.0	16.0								
	Nominal	13.0	15.0								
IEEE 802.11n (5 GHz)	Maximum	14.0	16.0	10.0	9.0	12.0	14.0				
	Nominal	13.0	15.0	9.0	8.0	11.0	13.0				
IEEE 802.11ac (5 GHz)	Maximum	14.0	16.0	10.0	9.0	12.0	14.0	9.0	8.0	8.5	11.0
	Nominal	13.0	15.0	9.0	8.0	11.0	13.0	8.0	7.0	7.5	10.0

Mode / Band		Modulated Average (dBm)
Bluetooth	Maximum	9.0
	Nominal	8.0
Bluetooth LE	Maximum	6.0
	Nominal	5.0

1.3.2 Reduced Output Power

Mode / Band		Voice (dBm)
		1 TX Slot
GSM 1900	Maximum	29.0
	Nominal	28.0

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 4 (1750 MHz)	Maximum	22.5	22.5	22.5
	Nominal	21.5	21.5	21.5
UMTS Band 2 (1900 MHz)	Maximum	21.5	21.5	21.5
	Nominal	20.5	20.5	20.5

Mode / Band		Modulated Average (dBm)
PCS CDMA/EVDO	Maximum	22.3
	Nominal	21.3

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 5 of 107

Mode / Band		Modulated Average (dBm)
LTE Band 4 (AWS)	Maximum	22.5
	Nominal	21.5
LTE Band 25 (PCS)	Maximum	22.0
	Nominal	21.0
LTE Band 2 (PCS)	Maximum	22.5
	Nominal	21.5

Mode / Band		Modulated Average (dBm)							
		20 MHz Bandwidth	40 MHz Bandwidth			80 MHz Bandwidth			
		Ch 36-165	Ch 38	Ch 62	Ch 46-54, 102-159	Ch 42	Ch 58	Ch 106	Ch 122-155
IEEE 802.11a (5 GHz)	Maximum	12.0							
	Nominal	11.0							
IEEE 802.11n (5 GHz)	Maximum	12.0	10.0	9.0	12.0				
	Nominal	11.0	9.0	8.0	11.0				
IEEE 802.11ac (5 GHz)	Maximum	12.0	10.0	9.0	12.0	9.0	8.0	8.5	11.0
	Nominal	11.0	9.0	8.0	11.0	8.0	7.0	7.5	10.0

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
EVDO BC10 (§90S)	Yes	Yes	No	Yes	Yes	Yes
EVDO BC0 (§22H)	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	Yes	Yes
5 GHz WLAN	Yes	Yes	Yes	No	Yes	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2 A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 6 of 107

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet	Notes
1	1x CDMA voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	Yes	
2	1x CDMA voice + 5 GHz Wi-Fi	Yes	Yes	N/A	Yes	
3	1x CDMA voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	^Bluetooth Tethering is considered
4	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	Yes	
5	GSM voice + 5 GHz Wi-Fi	Yes	Yes	N/A	Yes	
6	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	^Bluetooth Tethering is considered
7	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	Yes	
8	UMTS + 5 GHz Wi-Fi	Yes	Yes	Yes	Yes	
9	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	^Bluetooth Tethering is considered
10	LTE + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
11	LTE + 5 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
12	LTE + 2.4 GHz Bluetooth	Yes*^	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^Bluetooth Tethering is considered
13	CDMA/EVDO data + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
14	CDMA/EVDO data + 5 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
15	CDMA/EVDO data + 2.4 GHz Bluetooth	Yes*^	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^Bluetooth Tethering is considered
16	GPRS/EDGE + 2.4 GHz Wi-Fi	N/A	N/A	Yes	Yes	
17	GPRS/EDGE + 5 GHz Wi-Fi	N/A	N/A	Yes	Yes	
18	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	N/A	Yes^	Yes	

- 2.4 GHz WLAN, 5 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
- This device supports VoWIFI.

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 7 of 107

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, head Bluetooth SAR was not required; $[(8/5) * \sqrt{2.480}] = 2.5 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(8/15) * \sqrt{2.480}] = 0.8 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, hotspot Bluetooth SAR was not required; $[(8/10) * \sqrt{2.480}] = 1.3 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Per FCC KDB 447498 D01v06, the 10g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 7.5$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, phablet Bluetooth SAR was not required; $[(8/5) * \sqrt{2.480}] = 2.5 < 7.5$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 1 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-1, U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for 2.4 GHz and U-NII-3 WLAN operations since wireless router 1g SAR was < 1.2 W/kg.

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

For LTE Band 12, 4, 25, 2, and 41, LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 8 of 107

than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

For LTE Band 26, since the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is > ½ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration, LTE SAR for Band 26 is required for the equivalent channel configurations for lower bandwidth according to FCC KDB 941225 D05v02r04.

CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1x Advanced was not more than 0.25 dB higher than the maximum powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg per FCC KDB Publication 941225 D01v03r01.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

This device supports both Power Class 2 (PC2) and Power Class 3 (PC3) for LTE Band 41. Per May 2017 TCB Workshop Notes, SAR tests were performed with Power Class 3 (given the specific UL/DL limitations for Power Class 2). Additionally, SAR testing for the power class condition was evaluated for the highest configuration in Power Class 3 for each test configuration to confirm the results were scalable linearly (See Section 14.1).

1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- FCC KDB Publication 616217 D04v01r02 (Proximity Sensor)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- May 2017 TCB Workshop Notes (LTE Band 41 Power Class 2/3)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 9 of 107

2 LTE INFORMATION

LTE Information					
FCC ID	A3LSMJ737P				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)		831.5 (26865)		848.3 (27033)
LTE Band 26 (Cell): 3 MHz	815.5 (26705)		831.5 (26865)		847.5 (27025)
LTE Band 26 (Cell): 5 MHz	816.5 (26715)		831.5 (26865)		846.5 (27015)
LTE Band 26 (Cell): 10 MHz	819 (26740)		831.5 (26865)		844 (26990)
LTE Band 26 (Cell): 15 MHz	821.5 (26765)		831.5 (26865)		841.5 (26965)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)		1914.3 (26683)
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)		1913.5 (26675)
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)		1912.5 (26665)
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)		1910 (26640)
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)		1907.5 (26615)
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)		1905 (26590)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	6				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations				
LTE Additional Information	This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eICIC, WIFI Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 10 of 107

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 11 of 107

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1 point
Sample SAR Area
Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid $\Delta z_{\text{zoom}}(n)$	Graded Grid		
				$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 12 of 107

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 13 of 107

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 14 of 107




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 15 of 107

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1g body and 10g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

6.8 Phablet Configurations

For smart phones with a display diagonal dimension $> 150 \text{ mm}$ or an overall diagonal dimension $> 160 \text{ mm}$ that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna $\leq 25 \text{ mm}$ from that surface or edge, in direct contact with the phantom, for 10g SAR. The UMPC mini-tablet 1g SAR at 5 mm is not required. When hotspot mode applies, 10g SAR is required only for the surfaces and edges with hotspot mode 1g SAR $> 1.2 \text{ W/kg}$.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 16 of 107

6.9 Proximity Sensor Considerations

This device uses a power reduction mechanism to reduce output powers in certain use conditions when the device is used close the user's body.

When the device's antenna is within a certain distance of the user, the sensor activates and reduces the maximum allowed output power. However, the sensor is not active when the device is moved beyond the sensor triggering distance and the maximum output power is no longer limited. Therefore, additional evaluation is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a non-reduced output power level. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional test positions. Sensor triggering distance summary data is included in Appendix G.

The sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the sensor entirely covers the antennas.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 17 of 107

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 18 of 107

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as **reported** SAR. The highest **reported** SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 19 of 107

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

Table 8-1
Parameters for Max. Power for RC1

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 8-2
Parameters for Max. Power for RC3

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at fullrate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

8.4.3 Body-worn SAR Measurements

SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with EVDO capabilities, the 3G SAR test reduction procedure is applied to EVDO Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 20 of 107

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For EVDO data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with EVDO Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

8.4.6 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers are measured using SO75 with RC8 on the uplink and RC11 on the downlink per FCC KDB Publication 941225 D01v03r01. Smart blanking is disabled for all measurements. The EUT is configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers are measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

The 3G SAR test reduction procedure is applied to the 1x-Advanced transmission mode with 1x RTT RC3 as the primary mode. When SAR measurement is required, the 1x-Advanced power measurement configurations are used. The 1x Advanced SAR procedures are applied separately to head, body-worn accessory and other exposure conditions.

8.5 SAR Measurement Conditions for UMTS

8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1s". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 21 of 107

8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 22 of 107

8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.6.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. For every supported combination of downlink only carrier aggregation, additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 23 of 107

8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.7.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.7.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 24 of 107

- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.7.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.6). When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 25 of 107

9 RF CONDUCTED POWERS

9.1 CDMA Conducted Powers

Table 9-1
Maximum Conducted Power

Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	564	90S	820.1	24.48	24.43	24.48	24.37	24.40	23.96	23.93
Cellular	1013	22H	824.7	24.45	24.41	24.48	24.36	24.40	23.93	23.94
	384	22H	836.52	24.33	24.32	24.39	24.28	24.29	23.81	23.84
	777	22H	848.31	24.36	24.32	24.36	24.29	24.31	23.83	23.83
PCS	25	24E	1851.25	23.96	23.83	24.01	23.90	23.84	23.87	23.91
	600	24E	1880	23.83	23.70	23.85	23.73	23.71	23.73	23.78
	1175	24E	1908.75	23.89	23.75	23.88	23.83	23.75	23.78	23.84

Table 9-2
Reduced Conducted Power

Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
PCS	25	24E	1851.25	21.92	21.84	21.77	21.86	21.84	21.88	21.83
	600	24E	1880	21.78	21.71	21.65	21.67	21.70	21.75	21.67
	1175	24E	1908.75	21.82	21.72	21.69	21.72	21.72	21.77	21.73

Note: RC1 is only applicable for IS-95 compatibility. For FCC Rule Part 90S, Per FCC KDB Publication 447498 D01v06 4.1.g), only one channel is required since the device operates within the transmission range of 817.90 – 823.10 MHz.



Figure 9-1
Power Measurement Setup

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 26 of 107

9.2 GSM Conducted Powers

Table 9-3
Maximum Conducted Power

Maximum Burst-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	31.71	31.70	29.69	28.36	26.95	26.17	24.81	23.37	22.16
	190	31.88	31.96	29.73	28.27	27.00	26.17	24.65	23.17	21.91
	251	31.97	31.99	30.08	28.45	26.99	26.25	24.74	23.27	22.23
GSM 1900	512	29.14	29.08	26.80	25.02	23.22	25.85	23.65	22.12	21.27
	661	29.02	28.95	26.73	25.25	23.37	25.66	23.82	22.18	21.35
	810	29.15	29.17	27.05	25.39	23.49	25.95	23.98	22.47	21.76

Calculated Maximum Frame-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	22.68	22.67	23.67	24.10	23.94	17.14	18.79	19.11	19.15
	190	22.85	22.93	23.71	24.01	23.99	17.14	18.63	18.91	18.90
	251	22.94	22.96	24.06	24.19	23.98	17.22	18.72	19.01	19.22
GSM 1900	512	20.11	20.05	20.78	20.76	20.21	16.82	17.63	17.86	18.26
	661	19.99	19.92	20.71	20.99	20.36	16.63	17.80	17.92	18.34
	810	20.12	20.14	21.03	21.13	20.48	16.92	17.96	18.21	18.75

GSM 850	Frame Avg.Targets:	22.97	22.97	23.98	23.74	23.49	16.47	17.98	18.74	18.99
GSM 1900		19.97	19.97	20.98	20.74	19.99	16.47	17.48	17.74	18.49

FCC ID: A3LSMJ737P			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 27 of 107

Table 9-4
Reduced Conducted Power

Maximum Burst-Averaged Output Power		
		Voice
Band	Channel	GSM [dBm] CS (1 Slot)
GSM 1900	512	27.98
	661	27.91
	810	28.09

Calculated Maximum Frame-Averaged Output Power		
		Voice
Band	Channel	GSM [dBm] CS (1 Slot)
GSM 1900	512	18.95
	661	18.88
	810	19.06

GSM 1900	Frame Avg.Targets:	18.97
----------	--------------------	-------

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33(Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A




Figure 9-2
Power Measurement Setup

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 28 of 107

9.3 UMTS Conducted Powers

Table 9-5
Maximum Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.92	22.98	22.67	22.13	22.07	21.70	21.88	22.33	21.93	-
99		12.2 kbps AMR	22.88	22.89	22.71	22.09	21.98	21.69	21.86	22.35	21.91	-
6	HSDPA	Subtest 1	22.86	22.78	22.61	22.11	21.96	21.72	21.77	22.29	21.80	0
6		Subtest 2	22.26	22.19	21.90	22.16	22.02	21.79	21.83	22.39	21.87	0
6		Subtest 3	22.26	22.21	21.95	22.18	22.08	21.80	21.87	22.09	21.93	0.5
6		Subtest 4	21.19	21.13	21.06	22.19	22.06	21.84	21.85	22.09	21.92	0.5
6	HSUPA	Subtest 1	22.04	21.96	21.80	21.30	21.16	20.93	21.00	21.50	21.02	0
6		Subtest 2	20.15	20.02	19.81	19.11	19.11	18.96	19.24	19.48	19.29	2
6		Subtest 3	22.05	21.96	20.65	21.21	21.18	20.63	20.52	20.13	20.62	1
6		Subtest 4	20.14	20.05	19.83	19.10	19.08	18.95	19.25	19.43	19.24	2
6		Subtest 5	22.89	22.77	22.59	22.00	21.94	21.69	21.77	22.34	21.81	0

Table 9-6
Reduced Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	21.53	21.22	21.22	20.15	20.85	20.37	-
99		12.2 kbps AMR	21.52	21.20	21.19	20.11	20.88	20.36	-
6	HSDPA	Subtest 1	21.57	21.32	21.32	20.17	20.89	20.34	0
6		Subtest 2	21.62	21.36	21.33	20.24	20.95	20.38	0
6		Subtest 3	21.67	21.28	21.39	20.23	20.98	20.42	0.5
6		Subtest 4	21.69	21.46	21.38	20.20	20.98	20.37	0.5
6	HSUPA	Subtest 1	20.76	20.53	20.62	19.08	19.90	19.25	0
6		Subtest 2	19.28	19.15	19.27	19.12	19.34	19.20	2
6		Subtest 3	20.49	20.28	20.28	19.12	19.97	19.31	1
6		Subtest 4	19.19	19.12	19.23	19.04	19.49	19.21	2
6		Subtest 5	21.57	21.31	21.26	20.17	20.90	20.33	0

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 9-3
Power Measurement Setup

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 29 of 107

9.4 LTE Conducted Powers

9.4.1

LTE Band 12

Table 9-7
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.36	0	0
	1	25	24.31		0
	1	49	24.35		0
	25	0	22.95	0-1	1
	25	12	22.92		1
	25	25	22.90		1
	50	0	22.89		1
16QAM	1	0	23.39	0-1	1
	1	25	23.24		1
	1	49	23.27		1
	25	0	22.00	0-2	2
	25	12	21.99		2
	25	25	21.96		2
	50	0	22.08		2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-8
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.35	24.24	24.30	0	0
	1	12	24.30	24.21	24.33		0
	1	24	24.24	24.29	24.27		0
	12	0	22.94	22.85	22.91	0-1	1
	12	6	22.87	22.89	22.91		1
	12	13	22.90	22.83	22.90		1
	25	0	22.89	22.85	22.90		1
16QAM	1	0	23.15	23.14	23.20	0-1	1
	1	12	23.13	23.15	23.11		1
	1	24	23.08	23.11	23.09		1
	12	0	22.09	22.04	22.08	0-2	2
	12	6	22.08	22.05	22.09		2
	12	13	22.09	22.02	22.05		2
	25	0	22.11	22.01	22.09		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 30 of 107

Table 9-9
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.25	24.17	24.20	0	0
	1	7	24.24	24.18	24.20		0
	1	14	24.20	24.17	24.24		0
	8	0	22.97	22.83	22.90	0-1	1
	8	4	22.91	22.85	22.82		1
	8	7	22.85	22.84	22.88		1
	15	0	22.95	22.84	22.87		1
16QAM	1	0	23.19	23.09	23.20	0-1	1
	1	7	23.20	23.07	23.18		1
	1	14	23.17	23.09	23.20		1
	8	0	22.12	22.10	22.12	0-2	2
	8	4	22.10	22.07	22.11		2
	8	7	22.14	22.09	22.11		2
	15	0	22.07	22.06	22.06		2

Table 9-10
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.30	24.18	24.22	0	0
	1	2	24.31	24.21	24.23		0
	1	5	24.24	24.19	24.30		0
	3	0	24.32	24.17	24.25		0
	3	2	24.31	24.22	24.26		0
	3	3	24.29	24.20	24.23		0
	6	0	22.93	22.83	22.85	0-1	1
16QAM	1	0	23.12	23.09	23.10	0-1	1
	1	2	23.11	23.03	23.09		1
	1	5	23.15	23.05	23.05		1
	3	0	23.36	23.33	23.35		1
	3	2	23.37	23.30	23.36		1
	3	3	23.34	23.28	23.31		1
	6	0	22.09	21.97	22.04	0-2	2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 				Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 31 of 107

9.4.2

LTE Band 26 (Cell)

Table 9-11
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26865 (831.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.03	0	0
	1	36	23.95		0
	1	74	23.89		0
	36	0	22.64	0-1	1
	36	18	22.57		1
	36	37	22.52		1
	75	0	22.58		1
16QAM	1	0	22.86	0-1	1
	1	36	22.75		1
	1	74	22.74		1
	36	0	21.77	0-2	2
	36	18	21.75		2
	36	37	21.77		2
	75	0	21.76		2

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-12
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.48	24.53	24.40	0	0
	1	25	24.43	24.51	24.38		0
	1	49	24.30	24.49	24.26		0
	25	0	23.16	23.19	23.10	0-1	1
	25	12	23.13	23.15	23.06		1
	25	25	23.08	23.13	23.02		1
	50	0	23.14	23.11	23.08		1
16QAM	1	0	23.46	23.49	23.36	0-1	1
	1	25	23.39	23.45	23.31		1
	1	49	23.31	23.34	23.25		1
	25	0	22.39	22.40	22.27	0-2	2
	25	12	22.34	22.34	22.25		2
	25	25	22.26	22.28	22.20		2
	50	0	22.37	22.42	22.27		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 32 of 107

Table 9-13
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.45	24.51	24.67	0	0
	1	12	24.42	24.49	24.68		0
	1	24	24.41	24.50	24.61		0
	12	0	23.16	23.19	23.25	0-1	1
	12	6	23.13	23.18	23.24		1
	12	13	23.08	23.15	23.22		1
	25	0	23.10	23.15	23.24		1
16QAM	1	0	23.30	23.56	23.55	0-1	1
	1	12	23.21	23.52	23.50		1
	1	24	23.16	23.49	23.51		1
	12	0	22.34	22.43	22.54	0-2	2
	12	6	22.33	22.42	22.53		2
	12	13	22.30	22.35	22.50		2
	25	0	22.37	22.43	22.48		2

Table 9-14
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.48	24.36	24.79	0	0
	1	7	24.43	24.49	24.78		0
	1	14	24.35	24.46	24.74		0
	8	0	23.10	23.12	23.39	0-1	1
	8	4	23.08	23.14	23.37		1
	8	7	23.07	23.11	23.35		1
	15	0	23.11	23.16	23.39		1
16QAM	1	0	23.32	23.28	23.65	0-1	1
	1	7	23.25	23.25	23.63		1
	1	14	23.20	23.28	23.59		1
	8	0	22.31	22.37	22.62	0-2	2
	8	4	22.31	22.37	22.60		2
	8	7	22.30	22.38	22.61		2
	15	0	22.31	22.36	22.57		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 				Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 33 of 107

Table 9-15
LTE Band 26 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.48	24.49	24.81	0	0
	1	2	24.45	24.49	24.82		0
	1	5	24.43	24.46	24.81		0
	3	0	24.39	24.47	24.81		0
	3	2	24.40	24.46	24.77		0
	3	3	24.38	24.43	24.78		0
	6	0	23.12	23.16	23.44	0-1	1
16QAM	1	0	23.23	23.32	23.68	0-1	1
	1	2	23.21	23.33	23.62		1
	1	5	23.20	23.43	23.63		1
	3	0	23.44	23.55	23.82		1
	3	2	23.46	23.56	23.76		1
	3	3	23.50	23.56	23.79		1
	6	0	22.28	22.39	22.65	0-2	2

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 34 of 107

9.4.3

LTE Band 4 (AWS)

Table 9-16
LTE Band 4 (AWS) Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.50	0	0
	1	50	23.43		0
	1	99	23.35		0
	50	0	22.05	0-1	1
	50	25	21.99		1
	50	50	21.98		1
	100	0	22.00		1
16QAM	1	0	22.27	0-1	1
	1	50	22.28		1
	1	99	22.32		1
	50	0	21.27	0-2	2
	50	25	21.23		2
	50	50	21.26		2
	100	0	21.22		2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-17
LTE Band 4 (AWS) Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 4 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.43	23.47	23.43	0	0
	1	36	23.35	23.37	23.36		0
	1	74	23.20	23.31	23.35		0
	36	0	22.13	22.10	22.11	0-1	1
	36	18	22.10	22.07	22.11		1
	36	37	22.06	22.03	22.10		1
	75	0	22.02	22.09	22.12		1
16QAM	1	0	22.52	22.55	22.49	0-1	1
	1	36	22.45	22.36	22.47		1
	1	74	22.38	22.30	22.51		1
	36	0	21.32	21.29	21.39	0-2	2
	36	18	21.30	21.32	21.35		2
	36	37	21.26	21.30	21.33		2
	75	0	21.29	21.29	21.39		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 35 of 107

Table 9-18
LTE Band 4 (AWS) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 4 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.54	23.52	23.58	0	0
	1	25	23.52	23.46	23.57		0
	1	49	23.49	23.42	23.54		0
	25	0	22.14	22.12	22.16	0-1	1
	25	12	22.12	22.09	22.18		1
	25	25	22.09	22.08	22.17		1
	50	0	22.11	22.11	22.17		1
16QAM	1	0	22.52	22.51	22.56	0-1	1
	1	25	22.49	22.47	22.57		1
	1	49	22.43	22.42	22.56		1
	25	0	21.38	21.38	21.37	0-2	2
	25	12	21.37	21.35	21.39		2
	25	25	21.30	21.30	21.38		2
	50	0	21.38	21.36	21.43		2

Table 9-19
LTE Band 4 (AWS) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 4 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.54	23.51	23.69	0	0
	1	12	23.53	23.47	23.66		0
	1	24	23.49	23.43	23.65		0
	12	0	22.17	22.11	22.30	0-1	1
	12	6	22.15	22.09	22.31		1
	12	13	22.14	22.07	22.31		1
	25	0	22.15	22.10	22.30		1
16QAM	1	0	22.49	22.35	22.62	0-1	1
	1	12	22.50	22.34	22.63		1
	1	24	22.48	22.31	22.62		1
	12	0	21.38	21.32	21.45	0-2	2
	12	6	21.37	21.31	21.51		2
	12	13	21.36	21.28	21.53		2
	25	0	21.40	21.26	21.46		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 				Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 36 of 107

Table 9-20
LTE Band 4 (AWS) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 4 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.48	23.40	23.54	0	0
	1	7	23.45	23.38	23.59		0
	1	14	23.47	23.37	23.59		0
	8	0	22.20	22.08	22.23	0-1	1
	8	4	22.19	22.07	22.24		1
	8	7	22.20	22.06	22.22		1
	15	0	22.19	22.09	22.25		1
16QAM	1	0	22.32	22.50	22.47	0-1	1
	1	7	22.31	22.46	22.51		1
	1	14	22.29	22.30	22.50		1
	8	0	21.44	21.34	21.47	0-2	2
	8	4	21.43	21.32	21.49		2
	8	7	21.44	21.30	21.49		2
	15	0	21.41	21.42	21.46		2

Table 9-21
LTE Band 4 (AWS) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 4 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.49	23.37	23.49	0	0
	1	2	23.48	23.38	23.45		0
	1	5	23.48	23.24	23.48		0
	3	0	23.54	23.39	23.50		0
	3	2	23.55	23.38	23.49		0
	3	3	23.53	23.36	23.48		0
	6	0	22.22	22.03	22.16	0-1	1
16QAM	1	0	22.35	22.15	22.33	0-1	1
	1	2	22.39	22.16	22.34		1
	1	5	22.41	22.13	22.30		1
	3	0	22.81	22.55	22.65		1
	3	2	22.85	22.53	22.65		1
	3	3	22.82	22.47	22.64		1
	6	0	21.50	21.30	21.42	0-2	2

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 37 of 107

Table 9-22
LTE Band 4 (AWS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	21.47	0	0
	1	50	21.53		0
	1	99	21.37		0
	50	0	20.05	0-1	1
	50	25	19.97		1
	50	50	19.94		1
	100	0	20.03		1
16QAM	1	0	20.28	0-1	1
	1	50	20.44		1
	1	99	20.35		1
	50	0	19.25	0-2	2
	50	25	19.15		2
	50	50	19.18		2
	100	0	19.18		2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-23
LTE Band 4 (AWS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 4 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.51	21.44	21.51	0	0
	1	36	21.46	21.38	21.46		0
	1	74	21.35	21.29	21.42		0
	36	0	20.14	20.07	20.09	0-1	1
	36	18	20.11	20.04	20.07		1
	36	37	20.07	20.00	20.06		1
	75	0	20.12	20.05	20.06		1
16QAM	1	0	20.50	20.45	20.47	0-1	1
	1	36	20.46	20.37	20.43		1
	1	74	20.38	20.31	20.39		1
	36	0	19.32	19.27	19.30	0-2	2
	36	18	19.26	19.25	19.27		2
	36	37	19.21	19.19	19.23		2
	75	0	19.30	19.19	19.25		2

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 38 of 107

Table 9-24
LTE Band 4 (AWS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 4 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.57	21.45	21.51	0	0
	1	25	21.55	21.40	21.50		0
	1	49	21.47	21.33	21.49		0
	25	0	20.22	20.10	20.16	0-1	1
	25	12	20.20	20.07	20.15		1
	25	25	20.16	20.02	20.13		1
	50	0	20.20	20.06	20.14		1
16QAM	1	0	20.39	20.23	20.29	0-1	1
	1	25	20.33	20.20	20.29		1
	1	49	20.28	20.17	20.37		1
	25	0	19.37	19.24	19.33	0-2	2
	25	12	19.35	19.23	19.32		2
	25	25	19.34	19.18	19.31		2
	50	0	19.37	19.23	19.37		2

Table 9-25
LTE Band 4 (AWS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 4 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.50	21.37	21.44	0	0
	1	12	21.51	21.32	21.47		0
	1	24	21.59	21.32	21.43		0
	12	0	20.21	20.06	20.16	0-1	1
	12	6	20.20	20.08	20.17		1
	12	13	20.18	20.05	20.15		1
	25	0	20.20	20.04	20.14		1
16QAM	1	0	20.53	20.30	20.36	0-1	1
	1	12	20.49	20.29	20.33		1
	1	24	20.47	20.27	20.34		1
	12	0	19.39	19.23	19.37	0-2	2
	12	6	19.39	19.20	19.35		2
	12	13	19.36	19.22	19.36		2
	25	0	19.35	19.19	19.33		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 				Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 39 of 107

Table 9-26
LTE Band 4 (AWS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 4 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.50	21.33	21.46	0	0
	1	7	21.48	21.32	21.47		0
	1	14	21.56	21.34	21.43		0
	8	0	20.21	20.04	20.16	0-1	1
	8	4	20.20	20.03	20.17		1
	8	7	20.19	20.03	20.16		1
	15	0	20.21	20.05	20.14		1
16QAM	1	0	20.43	20.35	20.38	0-1	1
	1	7	20.44	20.26	20.43		1
	1	14	20.43	20.21	20.44		1
	8	0	19.43	19.20	19.35	0-2	2
	8	4	19.41	19.21	19.34		2
	8	7	19.38	19.18	19.33		2
	15	0	19.39	19.20	19.31		2

Table 9-27
LTE Band 4 (AWS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 4 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.57	21.43	21.50	0	0
	1	2	21.61	21.39	21.46		0
	1	5	21.60	21.40	21.46		0
	3	0	21.52	21.31	21.42		0
	3	2	21.54	21.31	21.44		0
	3	3	21.52	21.29	21.44		0
	6	0	20.23	20.03	20.16	0-1	1
16QAM	1	0	20.43	20.18	20.26	0-1	1
	1	2	20.43	20.20	20.21		1
	1	5	20.44	20.17	20.25		1
	3	0	20.66	20.43	20.53		1
	3	2	20.64	20.45	20.52		1
	3	3	20.62	20.45	20.57		1
	6	0	19.38	19.21	19.30	0-2	2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 				Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 40 of 107

9.4.4

LTE Band 25 (PCS)

Table 9-28
LTE Band 25 (PCS) Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.69	23.08	23.83	0	0
	1	50	23.62	23.04	23.94		0
	1	99	23.56	23.16	23.75		0
	50	0	22.32	21.75	22.51	0-1	1
	50	25	22.31	21.70	22.50		1
	50	50	22.26	21.75	22.49		1
	100	0	22.31	21.68	22.48		1
16QAM	1	0	22.48	21.83	22.65	0-1	1
	1	50	22.49	21.85	22.69		1
	1	99	22.42	21.96	22.61		1
	50	0	21.58	20.90	21.80	0-2	2
	50	25	21.55	20.90	21.82		2
	50	50	21.51	20.94	21.77		2
	100	0	21.56	20.91	21.76		2

Table 9-29
LTE Band 25 (PCS) Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.45	22.84	23.74	0	0
	1	36	23.45	22.77	23.77		0
	1	74	23.39	22.82	23.68		0
	36	0	22.16	21.51	22.43	0-1	1
	36	18	22.14	21.50	22.42		1
	36	37	22.13	21.52	22.39		1
	75	0	22.16	21.51	22.41		1
16QAM	1	0	22.38	21.78	22.64	0-1	1
	1	36	22.38	21.82	22.59		1
	1	74	22.38	21.85	22.57		1
	36	0	21.39	20.70	21.70	0-2	2
	36	18	21.40	20.71	21.68		2
	36	37	21.37	20.74	21.65		2
	75	0	21.38	20.73	21.68		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 41 of 107

Table 9-30
LTE Band 25 (PCS) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.48	22.73	23.78	0	0
	1	25	23.57	22.76	23.82		0
	1	49	23.47	22.81	23.72		0
	25	0	22.22	21.52	22.41	0-1	1
	25	12	22.20	21.50	22.43		1
	25	25	22.19	21.49	22.39		1
	50	0	22.20	21.49	22.40		1
16QAM	1	0	22.53	21.80	22.74	0-1	1
	1	25	22.53	21.73	22.59		1
	1	49	22.39	21.83	22.52		1
	25	0	21.42	20.68	21.69	0-2	2
	25	12	21.44	20.69	21.64		2
	25	25	21.42	20.69	21.62		2
	50	0	21.45	20.74	21.71		2

Table 9-31
LTE Band 25 (PCS) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.58	22.72	23.72	0	0
	1	12	23.55	22.74	23.66		0
	1	24	23.56	22.73	23.63		0
	12	0	22.27	21.52	22.40	0-1	1
	12	6	22.27	21.51	22.38		1
	12	13	22.28	21.49	22.33		1
	25	0	22.27	21.47	22.37		1
16QAM	1	0	22.59	21.88	22.75	0-1	1
	1	12	22.62	21.85	22.69		1
	1	24	22.63	21.86	22.64		1
	12	0	21.50	20.70	21.64	0-2	2
	12	6	21.53	20.69	21.62		2
	12	13	21.50	20.71	21.61		2
	25	0	21.52	20.70	21.63		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 			Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 42 of 107

Table 9-32
LTE Band 25 (PCS) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.62	22.62	23.75	0	0
	1	7	23.63	22.64	23.72		0
	1	14	23.65	22.68	23.66		0
	8	0	22.30	21.53	22.36	0-1	1
	8	4	22.31	21.50	22.38		1
	8	7	22.31	21.49	22.36		1
	15	0	22.31	21.51	22.39		1
16QAM	1	0	22.65	21.83	22.72	0-1	1
	1	7	22.61	21.73	22.64		1
	1	14	22.55	21.75	22.56		1
	8	0	21.56	20.73	21.70	0-2	2
	8	4	21.57	20.73	21.66		2
	8	7	21.53	20.71	21.65		2
	15	0	21.58	20.71	21.64		2

Table 9-33
LTE Band 25 (PCS) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.70	22.67	23.75	0	0
	1	2	23.64	22.71	23.75		0
	1	5	23.75	22.81	23.74		0
	3	0	23.68	22.78	23.74		0
	3	2	23.66	22.77	23.73		0
	3	3	23.61	22.77	23.70		0
	6	0	22.34	21.46	22.43	0-1	1
16QAM	1	0	22.55	21.62	22.59	0-1	1
	1	2	22.61	21.64	22.49		1
	1	5	22.57	21.57	22.52		1
	3	0	22.74	21.95	22.81		1
	3	2	22.72	21.92	22.84		1
	3	3	22.73	21.94	22.85		1
	6	0	21.61	20.66	21.65	0-2	2

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 43 of 107

Table 9-34
LTE Band 25 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.05	20.45	21.23	0	0
	1	50	20.96	20.48	21.33		0
	1	99	20.93	20.51	21.24		0
	50	0	19.61	19.11	19.85	0-1	1
	50	25	19.59	19.12	19.87		1
	50	50	19.52	19.22	19.84		1
	100	0	19.55	19.13	19.85		1
16QAM	1	0	19.82	19.32	20.13	0-1	1
	1	50	19.89	19.34	20.15		1
	1	99	19.85	19.30	20.05		1
	50	0	19.08	19.04	19.49	0-2	2
	50	25	19.10	19.08	19.50		2
	50	50	19.08	19.10	19.47		2
	100	0	19.12	19.05	19.48		2

Table 9-35
LTE Band 25 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.12	20.46	21.46	0	0
	1	36	21.08	20.45	21.47		0
	1	74	20.98	20.43	21.34		0
	36	0	19.70	19.00	20.05	0-1	1
	36	18	19.67	19.00	20.07		1
	36	37	19.65	19.01	20.03		1
	75	0	20.19	19.86	20.56		1
16QAM	1	0	20.04	19.24	20.30	0-1	1
	1	36	19.98	19.22	20.29		1
	1	74	19.92	19.27	20.20		1
	36	0	18.79	18.17	19.17	0-2	2
	36	18	18.76	18.17	19.17		2
	36	37	18.74	18.17	19.15		2
	75	0	18.77	18.21	19.15		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 			Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 44 of 107

Table 9-36
LTE Band 25 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.18	20.46	21.46	0	0
	1	25	21.14	20.44	21.41		0
	1	49	21.08	20.44	21.37		0
	25	0	19.76	18.99	20.05	0-1	1
	25	12	19.75	18.99	20.00		1
	25	25	19.73	18.99	19.97		1
	50	0	19.75	18.98	20.02		1
16QAM	1	0	20.06	19.32	20.40	0-1	1
	1	25	20.03	19.30	20.42		1
	1	49	20.01	19.36	20.35		1
	25	0	18.85	18.20	19.16	0-2	2
	25	12	18.85	18.20	19.15		2
	25	25	18.83	18.21	19.11		2
	50	0	18.87	18.26	19.17		2

Table 9-37
LTE Band 25 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.10	20.37	21.43	0	0
	1	12	21.06	20.33	21.37		0
	1	24	21.05	20.36	21.36		0
	12	0	19.77	18.94	20.04	0-1	1
	12	6	19.78	18.96	20.04		1
	12	13	19.77	18.97	20.02		1
	25	0	19.77	18.98	20.04		1
16QAM	1	0	20.13	19.34	20.43	0-1	1
	1	12	20.17	19.33	20.38		1
	1	24	20.17	19.35	20.35		1
	12	0	18.90	18.18	19.20	0-2	2
	12	6	18.89	18.18	19.17		2
	12	13	18.87	18.19	19.16		2
	25	0	18.92	18.22	19.18		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 			Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 45 of 107

Table 9-38
LTE Band 25 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.11	20.30	21.34	0	0
	1	7	21.09	20.29	21.34		0
	1	14	21.03	20.31	21.32		0
	8	0	19.81	18.97	20.06	0-1	1
	8	4	19.81	18.97	20.05		1
	8	7	19.81	18.96	20.04		1
	15	0	19.84	19.02	20.03		1
16QAM	1	0	20.25	19.32	20.51	0-1	1
	1	7	20.20	19.44	20.53		1
	1	14	20.20	19.40	20.50		1
	8	0	18.95	18.19	19.23	0-2	2
	8	4	18.94	18.18	19.21		2
	8	7	18.94	18.15	19.22		2
	15	0	18.96	18.18	19.20		2

Table 9-39
LTE Band 25 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.16	20.31	21.48	0	0
	1	2	21.19	20.37	21.47		0
	1	5	21.18	20.43	21.49		0
	3	0	21.18	20.32	21.46		0
	3	2	21.21	20.34	21.44		0
	3	3	21.19	20.32	21.43		0
	6	0	19.89	18.98	20.09	0-1	1
16QAM	1	0	20.00	19.11	20.22	0-1	1
	1	2	20.00	19.20	20.25		1
	1	5	19.98	19.17	20.23		1
	3	0	20.34	19.35	20.52		1
	3	2	20.33	19.44	20.52		1
	3	3	20.33	19.45	20.51		1
	6	0	18.96	18.18	19.21	0-2	2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 				Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 46 of 107

9.4.5

LTE Band 2 (PCS)

Table 9-40
LTE Band 2 (PCS) Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 2 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18700 (1860.0 MHz)	18900 (1880.0 MHz)	19100 (1900.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.61	23.18	23.73	0	0
	1	50	23.60	23.20	23.77		0
	1	99	23.55	23.21	23.78		0
	50	0	22.26	21.86	22.42	0-1	1
	50	25	22.28	21.83	22.60		1
	50	50	22.22	21.87	22.44		1
	100	0	22.25	21.84	22.40		1
16QAM	1	0	22.48	22.01	22.58	0-1	1
	1	50	22.50	21.98	22.55		1
	1	99	22.39	22.02	22.60		1
	50	0	21.53	21.04	21.66	0-2	2
	50	25	21.54	21.10	21.67		2
	50	50	21.52	21.08	21.69		2
	100	0	21.47	21.02	21.64		2

Table 9-41
LTE Band 2 (PCS) Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 2 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18675 (1857.5 MHz)	18900 (1880.0 MHz)	19125 (1902.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.57	23.22	23.74	0	0
	1	36	23.52	23.16	23.77		0
	1	74	23.48	23.17	23.83		0
	36	0	22.24	21.82	22.42	0-1	1
	36	18	22.22	21.79	22.45		1
	36	37	22.19	21.80	22.44		1
	75	0	22.21	21.78	22.41		1
16QAM	1	0	22.61	21.95	22.63	0-1	1
	1	36	22.59	21.91	22.59		1
	1	74	22.53	21.75	22.69		1
	36	0	21.47	21.02	21.64	0-2	2
	36	18	21.45	21.04	21.65		2
	36	37	21.43	21.05	21.64		2
	75	0	21.42	21.00	21.68		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 47 of 107

Table 9-42
LTE Band 2 (PCS) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 2 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18650 (1855.0 MHz)	18900 (1880.0 MHz)	19150 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.68	23.18	23.82	0	0
	1	25	23.65	23.14	23.87		0
	1	49	23.60	23.16	23.80		0
	25	0	22.26	21.78	22.49	0-1	1
	25	12	22.25	21.79	22.51		1
	25	25	22.23	21.81	22.49		1
	50	0	22.25	21.78	22.50		1
16QAM	1	0	22.65	22.27	22.52	0-1	1
	1	25	22.61	22.24	22.54		1
	1	49	22.57	22.25	22.70		1
	25	0	21.48	20.95	21.68	0-2	2
	25	12	21.46	21.00	21.70		2
	25	25	21.43	21.01	21.72		2
	50	0	21.51	21.00	21.72		2

Table 9-43
LTE Band 2 (PCS) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 2 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18625 (1852.5 MHz)	18900 (1880.0 MHz)	19175 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.57	23.09	23.86	0	0
	1	12	23.55	23.10	23.85		0
	1	24	23.60	23.07	23.80		0
	12	0	22.30	21.76	22.51	0-1	1
	12	6	22.28	21.75	22.50		1
	12	13	22.29	21.74	22.49		1
	25	0	22.29	21.77	22.52		1
16QAM	1	0	22.54	22.11	22.88	0-1	1
	1	12	22.52	22.12	22.85		1
	1	24	22.49	22.13	22.75		1
	12	0	21.47	20.94	21.70	0-2	2
	12	6	21.48	20.96	21.71		2
	12	13	21.46	20.93	21.67		2
	25	0	21.44	20.95	21.77		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 				Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 48 of 107

Table 9-44
LTE Band 2 (PCS) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 2 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18615 (1851.5 MHz)	18900 (1880.0 MHz)	19185 (1908.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.66	23.04	23.81	0	0
	1	7	23.64	23.10	23.90		0
	1	14	23.61	23.09	23.93		0
	8	0	22.32	21.76	22.57	0-1	1
	8	4	22.34	21.77	22.56		1
	8	7	22.33	21.75	22.54		1
	15	0	22.33	21.77	22.55		1
16QAM	1	0	22.72	21.90	22.73	0-1	1
	1	7	22.76	21.93	22.75		1
	1	14	22.73	21.91	22.74		1
	8	0	21.55	21.01	21.82	0-2	2
	8	4	21.53	21.00	21.84		2
	8	7	21.52	20.99	21.83		2
	15	0	21.53	21.02	21.71		2

Table 9-45
LTE Band 2 (PCS) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 2 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18607 (1850.7 MHz)	18900 (1880.0 MHz)	19193 (1909.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.69	23.09	23.98	0	0
	1	2	23.65	23.08	23.94		0
	1	5	23.72	23.08	23.93		0
	3	0	23.71	23.15	23.90		0
	3	2	23.70	23.13	23.88		0
	3	3	23.67	23.12	23.87		0
	6	0	22.36	21.78	22.58	0-1	1
16QAM	1	0	22.58	21.73	22.84	0-1	1
	1	2	22.53	21.77	22.85		1
	1	5	22.54	21.78	22.84		1
	3	0	22.71	22.23	22.96		1
	3	2	22.68	22.19	22.94		1
	3	3	22.70	22.22	22.93		1
	6	0	21.45	21.04	21.78	0-2	2

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 49 of 107

Table 9-46
LTE Band 2 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 2 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18700 (1860.0 MHz)	18900 (1880.0 MHz)	19100 (1900.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.61	21.22	21.68	0	0
	1	50	21.64	21.21	21.76		0
	1	99	21.55	21.41	21.69		0
	50	0	20.16	19.82	20.33	0-1	1
	50	25	20.14	19.81	20.30		1
	50	50	20.17	19.85	20.32		1
	100	0	20.15	19.77	20.30		1
16QAM	1	0	20.53	20.09	20.64	0-1	1
	1	50	20.49	20.08	20.68		1
	1	99	20.48	20.18	20.63		1
	50	0	19.39	19.12	19.48	0-2	2
	50	25	19.34	19.16	19.54		2
	50	50	19.32	19.18	19.55		2
	100	0	19.33	19.08	19.47		2

Table 9-47
LTE Band 2 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 2 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18675 (1857.5 MHz)	18900 (1880.0 MHz)	19125 (1902.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.62	21.24	21.83	0	0
	1	36	21.63	21.21	21.83		0
	1	74	21.51	21.20	21.81		0
	36	0	20.23	19.85	20.45	0-1	1
	36	18	20.20	19.86	20.46		1
	36	37	20.17	19.84	20.45		1
	75	0	20.21	19.87	20.45		1
16QAM	1	0	20.55	20.14	20.74	0-1	1
	1	36	20.48	20.09	20.80		1
	1	74	20.42	20.13	20.77		1
	36	0	19.40	19.09	19.62	0-2	2
	36	18	19.38	19.08	19.63		2
	36	37	19.35	19.08	19.73		2
	75	0	19.38	19.09	19.60		2

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 50 of 107

Table 9-48
LTE Band 2 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 2 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18650 (1855.0 MHz)	18900 (1880.0 MHz)	19150 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.65	21.24	21.89	0	0
	1	25	21.64	21.23	21.89		0
	1	49	21.56	21.22	21.88		0
	25	0	20.25	19.84	20.50	0-1	1
	25	12	20.24	19.84	20.52		1
	25	25	20.22	19.84	20.51		1
	50	0	20.26	19.87	20.53		1
16QAM	1	0	20.60	20.18	20.81	0-1	1
	1	25	20.58	20.15	20.84		1
	1	49	20.59	20.13	20.83		1
	25	0	19.41	19.09	19.68	0-2	2
	25	12	19.39	19.08	19.70		2
	25	25	19.37	19.07	19.67		2
	50	0	19.44	19.11	19.71		2

Table 9-49
LTE Band 2 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 2 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18625 (1852.5 MHz)	18900 (1880.0 MHz)	19175 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.70	21.17	21.95	0	0
	1	12	21.67	21.19	21.96		0
	1	24	21.65	21.16	21.91		0
	12	0	20.34	19.85	20.60	0-1	1
	12	6	20.33	19.85	20.59		1
	12	13	20.32	19.82	20.56		1
	25	0	20.32	19.84	20.57		1
16QAM	1	0	20.62	20.05	20.76	0-1	1
	1	12	20.55	20.03	20.68		1
	1	24	20.52	20.05	20.64		1
	12	0	19.45	19.04	19.68	0-2	2
	12	6	19.47	19.02	19.69		2
	12	13	19.48	19.00	19.70		2
	25	0	19.48	19.04	19.78		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 				Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset			Page 51 of 107

Table 9-50
LTE Band 2 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 2 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18615 (1851.5 MHz)	18900 (1880.0 MHz)	19185 (1908.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.61	21.05	21.87	0	0
	1	7	21.57	21.10	21.82		0
	1	14	21.59	21.05	21.81		0
	8	0	20.35	19.84	20.60	0-1	1
	8	4	20.34	19.84	20.58		1
	8	7	20.35	19.84	20.60		1
	15	0	20.33	19.82	20.58		1
16QAM	1	0	20.63	20.18	20.96	0-1	1
	1	7	20.69	20.17	20.96		1
	1	14	20.66	20.15	20.96		1
	8	0	19.52	19.07	19.81	0-2	2
	8	4	19.54	19.04	19.78		2
	8	7	19.55	19.03	19.76		2
	15	0	19.53	19.05	19.75		2

Table 9-51
LTE Band 2 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 2 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18607 (1850.7 MHz)	18900 (1880.0 MHz)	19193 (1909.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.62	21.04	21.77	0	0
	1	2	21.61	21.04	21.78		0
	1	5	21.61	21.06	21.80		0
	3	0	21.68	21.14	21.85		0
	3	2	21.69	21.14	21.85		0
	3	3	21.68	21.12	21.84		0
	6	0	20.35	19.80	20.52	0-1	1
16QAM	1	0	20.50	19.99	20.71	0-1	1
	1	2	20.51	19.99	20.70		1
	1	5	20.55	19.93	20.71		1
	3	0	20.89	20.31	21.04		1
	3	2	20.86	20.32	21.04		1
	3	3	20.86	20.33	21.04		1
	6	0	19.53	18.98	19.71	0-2	2

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 52 of 107

9.4.6

LTE Band 41

Table 9-52
LTE Band 41 PC3 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.93	22.21	22.03	22.01	22.00	0	0
	1	50	21.98	22.19	22.05	21.81	22.04		0
	1	99	22.06	22.16	22.08	21.79	22.05		0
	50	0	20.86	21.22	21.07	20.71	20.94	0-1	1
	50	25	20.90	21.20	21.06	20.72	20.95		1
	50	50	20.95	21.20	21.08	20.70	20.96		1
	100	0	20.91	21.21	21.07	20.75	20.97		1
16QAM	1	0	20.56	20.96	20.89	20.68	20.84	0-1	1
	1	50	20.62	20.93	20.95	20.70	20.73		1
	1	99	20.69	20.92	20.92	20.65	20.78		1
	50	0	19.90	20.23	20.07	19.66	19.91	0-2	2
	50	25	19.93	20.21	20.08	19.65	19.92		2
	50	50	19.97	20.20	20.07	19.66	19.93		2
	100	0	19.92	20.18	20.06	19.64	19.88		2

Table 9-53
LTE Band 41 PC3 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.96	22.13	22.11	21.84	22.07	0	0
	1	36	22.01	22.16	22.14	21.77	22.02		0
	1	74	22.04	22.23	22.24	21.89	22.08		0
	36	0	20.97	21.12	21.13	20.71	20.95	0-1	1
	36	18	20.98	21.15	21.16	20.73	20.96		1
	36	37	21.01	21.16	21.19	20.76	20.97		1
	75	0	20.96	21.10	21.12	20.69	20.94		1
16QAM	1	0	20.66	20.82	20.71	20.51	20.63	0-1	1
	1	36	20.60	20.79	20.76	20.57	20.64		1
	1	74	20.66	20.89	20.86	20.55	20.69		1
	36	0	19.91	20.05	20.03	19.58	19.83	0-2	2
	36	18	19.93	20.06	20.03	19.60	19.84		2
	36	37	19.94	20.08	20.06	19.61	19.85		2
	75	0	19.93	20.05	20.06	19.57	19.82		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 53 of 107

Table 9-54
LTE Band 41 PC3 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.16	22.34	22.34	21.91	22.21	0	0
	1	25	22.21	22.34	22.35	21.95	22.16		0
	1	49	22.19	22.37	22.40	21.91	22.21		0
	25	0	20.99	21.16	21.15	20.74	20.98	0-1	1
	25	12	21.00	21.16	21.16	20.75	20.97		1
	25	25	21.02	21.17	21.17	20.75	20.98		1
	50	0	20.99	21.17	21.17	20.78	20.99		1
16QAM	1	0	20.60	20.63	20.64	20.52	20.50	0-1	1
	1	25	20.51	20.60	20.80	20.55	20.64		1
	1	49	20.56	20.59	20.77	20.53	20.62		1
	25	0	19.87	20.00	19.99	19.56	19.85	0-2	2
	25	12	19.90	20.04	20.11	19.56	19.83		2
	25	25	19.90	20.05	20.13	19.55	19.86		2
	50	0	20.02	20.15	20.16	19.69	19.96		2

Table 9-55
LTE Band 41 PC3 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.01	22.17	22.14	21.78	22.02	0	0
	1	12	22.02	22.17	22.09	21.80	22.02		0
	1	24	22.02	22.22	22.24	21.83	22.04		0
	12	0	20.99	21.15	21.14	20.74	20.97	0-1	1
	12	6	20.99	21.15	21.15	20.76	20.97		1
	12	13	20.98	21.15	21.15	20.76	20.99		1
	25	0	20.99	21.15	21.16	20.75	20.97		1
16QAM	1	0	20.56	20.62	20.50	20.51	20.52	0-1	1
	1	12	20.50	20.57	20.55	20.55	20.63		1
	1	24	20.54	20.64	20.68	20.50	20.62		1
	12	0	19.85	20.04	20.03	19.60	19.81	0-2	2
	12	6	19.91	20.06	20.09	19.62	19.82		2
	12	13	19.93	20.10	20.07	19.64	19.84		2
	25	0	19.89	20.00	20.05	19.59	19.86		2

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 54 of 107

Table 9-56
LTE Band 41 PC2 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	26.40	26.75	26.76	26.51	26.57	0	0
	1	50	26.46	26.79	26.83	26.37	26.58		0
	1	99	26.48	26.84	26.88	26.43	26.56		0
	50	0	25.26	25.56	25.64	25.22	25.44	0-1	1
	50	25	25.27	25.59	25.67	25.23	25.45		1
	50	50	25.28	25.61	25.69	25.25	25.47		1
16QAM	100	0	25.27	25.55	25.66	25.22	25.44		1
	1	0	25.11	25.30	25.52	24.89	24.98	0-1	1
	1	50	25.07	25.33	25.60	24.95	25.03		1
	1	99	25.08	25.38	25.56	25.00	25.06		1
	50	0	24.44	24.68	24.75	24.33	24.57	0-2	2
	50	25	24.45	24.70	24.77	24.35	24.58		2
	50	50	24.46	24.72	24.87	24.35	24.59		2
	100	0	24.36	24.64	24.74	24.26	24.50		2

Table 9-57
LTE Band 41 PC2 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	26.12	26.41	26.37	25.99	26.05	0	0
	1	36	26.15	26.38	26.34	25.97	26.06		0
	1	74	26.20	26.35	26.36	25.91	26.04		0
	36	0	24.85	25.18	25.10	24.77	24.85	0-1	1
	36	18	24.85	25.16	25.10	24.78	24.86		1
	36	37	24.86	25.15	25.08	24.70	24.88		1
16QAM	75	0	24.87	25.14	25.06	24.76	24.85	0-1	1
	1	0	24.78	24.94	24.80	24.39	24.40		1
	1	36	24.85	24.88	24.84	24.35	24.43		1
	1	74	24.86	24.86	24.92	24.45	24.44	0-2	2
	36	0	23.95	24.25	24.12	23.82	23.92		2
	36	18	23.96	24.23	24.13	23.83	23.94		2
	36	37	23.98	24.20	24.15	23.85	23.93		2
	75	0	23.94	24.20	24.10	23.84	23.90		2

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 55 of 107

Table 9-58
LTE Band 41 PC2 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	26.28	26.65	26.34	26.21	26.41	0	0
	1	25	26.29	26.57	26.30	26.15	26.39		0
	1	49	26.28	26.56	26.29	26.13	26.33		0
	25	0	24.97	25.24	25.08	24.84	25.10	0-1	1
	25	12	24.97	25.22	25.07	24.84	25.09		1
	25	25	25.00	25.20	25.05	24.82	25.08		1
	50	0	24.99	25.23	25.06	24.82	25.09		1
16QAM	1	0	24.99	25.43	24.98	24.80	25.22	0-1	1
	1	25	25.02	25.39	24.95	24.75	25.14		1
	1	49	25.04	25.42	24.99	24.72	25.20		1
	25	0	23.94	24.26	24.19	23.84	24.09	0-2	2
	25	12	23.93	24.25	24.18	23.79	24.06		2
	25	25	23.95	24.23	24.18	23.78	24.07		2
	50	0	24.06	24.28	24.22	23.95	24.19		2

Table 9-59
LTE Band 41 PC2 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	26.11	26.43	26.38	26.07	26.27	0	0
	1	12	26.16	26.44	26.35	26.05	26.26		0
	1	24	26.15	26.41	26.37	26.04	26.25		0
	12	0	24.95	25.18	25.14	24.85	25.07	0-1	1
	12	6	24.95	25.18	25.13	24.84	25.06		1
	12	13	24.94	25.16	25.13	24.82	25.05		1
	25	0	24.93	25.17	25.12	24.83	25.05		1
16QAM	1	0	24.61	25.00	24.95	24.77	24.81	0-1	1
	1	12	24.62	25.07	24.94	24.75	24.78		1
	1	24	24.58	25.10	24.96	24.81	24.77		1
	12	0	24.02	24.34	24.20	23.86	24.08	0-2	2
	12	6	24.02	24.33	24.19	23.84	24.07		2
	12	13	24.03	24.31	24.19	23.86	24.06		2
	25	0	23.95	24.20	24.13	23.83	24.00		2

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 			Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 56 of 107

9.4.7 LTE Carrier Aggregation Conducted Powers

Table 9-60
LTE Carrier Aggregation Conducted Powers

	PCC									SCC				Power	
Combination	PCC Band	PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Ch.	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Ch.	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_41C (1)	LTE B41	10	40620	2593	QPSK	1	49	40620	2593	LTE B41	20	40764	2607.4	22.30	22.40
CA_41C (1)	LTE B41 PC2	20	40620	2593	QPSK	1	99	40620	2593	LTE B41 PC2	20	40818	2612.8	26.87	26.88

Notes:

1. For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.
2. All control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
3. For downlink carrier aggregation combinations, PCC uplink channel was selected based on section C)3)b)ii) of KBD 941225 D05 V01r02. The downlink PCC channel was paired with the selected PCC uplink channel according to normal configurations without carrier aggregation. For inter-band CA, the SCC downlink channels were selected near the middle of their transmission bands. For contiguous intra-band CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing defined in section 5.4.1A of 3GPP TS 36.521. For non-contiguous intra-band CA, the downlink channel spacing between the component carriers was set to be larger than the nominal channel spacing and provided maximum separation between the component carriers. All selected downlink channels remained fully within the downlink transmission band of the respective component carrier.




Figure 9-4
Power Measurement Setup

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 57 of 107

9.5 WLAN Conducted Powers

Table 9-61
2.4 GHz WLAN Maximum Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	15.10	13.51	13.64
2417	2	N/A	15.33	15.37
2437	6	15.58	15.45	15.36
2457	10	N/A	15.37	15.34
2462	11	15.25	12.65	12.71

Table 9-62
5 GHz WLAN Maximum Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
		Average	Average	Average
5180	36	13.41	13.38	13.44
5200	40	15.42	15.34	15.48
5220	44	15.11	15.04	15.28
5240	48	15.17	15.11	15.13
5260	52	14.46	15.49	15.47
5280	56	14.50	15.33	15.46
5300	60	15.49	15.23	15.36
5320	64	13.47	13.13	13.39
5500	100	13.49	13.45	13.44
5600	120	14.63	14.68	14.62
5620	124	14.81	15.49	14.54
5720	144	14.71	15.35	15.41
5745	149	15.24	15.23	15.27
5785	157	15.09	15.13	15.36
5825	165	13.01	13.04	13.11

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 58 of 107

Table 9-63
5 GHz WLAN Reduced Average RF Power

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11n	802.11ac
		Average	Average
5190	38	9.67	9.74
5230	46	11.49	11.56
5270	54	10.60	11.85
5310	62	8.66	8.72
5510	102	11.27	11.14
5590	118	11.00	11.94
5630	126	11.11	11.97
5710	142	10.71	11.99
5755	151	11.24	11.59
5795	159	11.13	11.09

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-5
Power Measurement Setup for Bandwidths < 50 MHz

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 59 of 107

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties – Head

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
03/14/2018	750H	20.3	700	0.860	40.818	0.889	42.201	-3.26%	-3.28%
			710	0.864	40.817	0.890	42.149	-2.92%	-3.16%
			740	0.874	40.715	0.893	41.994	-2.13%	-3.05%
			755	0.879	40.699	0.894	41.916	-1.68%	-2.90%
03/05/2018	835H	22.5	820	0.910	43.517	0.899	41.578	1.22%	4.66%
			835	0.925	43.335	0.900	41.500	2.78%	4.42%
			850	0.939	43.165	0.916	41.500	2.51%	4.01%
02/28/2018	1750H	22.5	1710	1.336	39.309	1.348	40.142	-0.89%	-2.08%
			1750	1.377	39.127	1.371	40.079	0.44%	-2.38%
			1790	1.419	38.920	1.394	40.016	1.79%	-2.74%
03/05/2018	1900H	21.1	1850	1.401	40.343	1.400	40.000	0.07%	0.86%
			1880	1.436	40.210	1.400	40.000	2.57%	0.53%
			1910	1.467	40.067	1.400	40.000	4.79%	0.17%
03/21/2018	1900H	23.0	1850	1.397	38.849	1.400	40.000	-0.21%	-2.88%
			1880	1.428	38.738	1.400	40.000	2.00%	-3.16%
			1910	1.462	38.630	1.400	40.000	4.43%	-3.42%
02/25/2018	2450H	22.0	2400	1.827	38.250	1.756	39.289	4.04%	-2.64%
			2450	1.880	38.071	1.800	39.200	4.44%	-2.88%
03/05/2018	2600H	21.5	2500	1.938	37.838	1.855	39.136	4.47%	-3.32%
			2500	1.924	37.842	1.855	39.136	3.72%	-3.31%
			2550	1.984	37.669	1.909	39.073	3.93%	-3.59%
			2600	2.037	37.459	1.964	39.009	3.72%	-3.97%
02/20/2018	5200H-5800H	22.5	5240	4.501	35.238	4.696	35.940	-4.15%	-1.95%
			5260	4.522	35.218	4.717	35.917	-4.13%	-1.95%
			5280	4.534	35.198	4.737	35.894	-4.29%	-1.94%
			5300	4.551	35.145	4.758	35.871	-4.35%	-2.02%
			5320	4.564	35.142	4.778	35.849	-4.48%	-1.97%
			5500	4.743	34.859	4.963	35.643	-4.43%	-2.20%
			5520	4.769	34.852	4.983	35.620	-4.29%	-2.16%
			5600	4.845	34.777	5.065	35.529	-4.34%	-2.12%
			5620	4.861	34.702	5.086	35.506	-4.42%	-2.26%
			5640	4.890	34.699	5.106	35.483	-4.23%	-2.21%
			5745	5.002	34.557	5.214	35.363	-4.07%	-2.28%
			5765	5.030	34.536	5.234	35.340	-3.90%	-2.28%
			5785	5.048	34.509	5.255	35.317	-3.94%	-2.29%
			5800	5.065	34.502	5.270	35.300	-3.89%	-2.26%

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 60 of 107

Table 10-2
Measured Tissue Properties – Body

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
03/12/2018	750B	21.0	700	0.960	56.208	0.959	55.726	0.10%	0.86%
			710	0.964	56.200	0.960	55.687	0.42%	0.92%
			740	0.975	56.142	0.963	55.570	1.25%	1.03%
			755	0.980	56.089	0.964	55.512	1.66%	1.04%
02/26/2018	835B	21.7	820	0.979	53.494	0.969	55.258	1.03%	-3.19%
			835	0.995	53.337	0.970	55.200	2.58%	-3.38%
			850	1.009	53.178	0.988	55.154	2.13%	-3.58%
03/04/2018	835B	21.1	820	0.983	53.024	0.969	55.258	1.44%	-4.04%
			835	0.998	52.865	0.970	55.200	2.89%	-4.23%
			850	1.012	52.701	0.988	55.154	2.43%	-4.45%
03/07/2018	835B	20.7	820	0.969	53.678	0.969	55.258	0.00%	-2.86%
			835	0.985	53.465	0.970	55.200	1.55%	-3.14%
			850	0.999	53.377	0.988	55.154	1.11%	-3.22%
04/03/2018	835B	21.3	820	0.960	53.680	0.969	55.258	-0.93%	-2.86%
			835	0.974	53.530	0.970	55.200	0.41%	-3.03%
			850	0.989	53.387	0.988	55.154	0.10%	-3.20%
02/26/2018	1750B	22.1	1710	1.430	52.881	1.463	53.537	-2.26%	-1.23%
			1750	1.475	52.733	1.488	53.432	-0.87%	-1.31%
			1790	1.516	52.565	1.514	53.326	0.13%	-1.43%
02/28/2018	1750B	20.6	1710	1.456	53.370	1.463	53.537	-0.48%	-0.31%
			1750	1.499	53.187	1.488	53.432	0.74%	-0.46%
			1790	1.549	53.045	1.514	53.326	2.31%	-0.53%
02/26/2018	1900B	21.6	1850	1.517	52.122	1.520	53.300	-0.20%	-2.21%
			1880	1.551	52.010	1.520	53.300	2.04%	-2.42%
			1910	1.587	51.901	1.520	53.300	4.41%	-2.62%
03/01/2018	1900B	22.2	1850	1.508	52.426	1.520	53.300	-0.79%	-1.64%
			1880	1.545	52.296	1.520	53.300	1.64%	-1.88%
			1910	1.579	52.206	1.520	53.300	3.88%	-2.05%
03/19/2018	1900B	22.3	1850	1.520	52.874	1.520	53.300	0.00%	-0.80%
			1880	1.558	52.748	1.520	53.300	2.50%	-1.04%
			1910	1.592	52.674	1.520	53.300	4.74%	-1.17%
03/21/2018	1900B	21.5	1850	1.520	52.331	1.520	53.300	0.00%	-1.82%
			1880	1.556	52.249	1.520	53.300	2.37%	-1.97%
			1910	1.591	52.168	1.520	53.300	4.67%	-2.12%
02/19/2018	2450B	21.0	2400	1.982	50.925	1.902	52.767	4.21%	-3.49%
			2450	2.039	50.762	1.950	52.700	4.56%	-3.68%
			2500	2.097	50.584	2.021	52.636	3.76%	-3.90%
03/04/2018	2450B-2600B	21.9	2450	2.004	50.846	1.950	52.700	2.77%	-3.52%
			2500	2.063	50.699	2.021	52.636	2.08%	-3.68%
			2550	2.123	50.566	2.092	52.573	1.48%	-3.82%
			2600	2.181	50.405	2.163	52.509	0.83%	-4.01%
			2650	2.240	50.259	2.234	52.445	0.27%	-4.17%
			2700	2.295	50.102	2.305	52.382	-0.43%	-4.35%
03/18/2018	2600B	21.1	2600	2.227	50.553	2.163	52.509	2.96%	-3.73%
			2650	2.289	50.424	2.234	52.445	2.46%	-3.85%
			2700	2.350	50.237	2.305	52.382	1.95%	-4.09%
02/21/2018	5200B-5800B	21.1	5240	5.523	47.324	5.346	48.960	3.31%	-3.34%
			5260	5.550	47.305	5.369	48.933	3.37%	-3.33%
			5300	5.587	47.239	5.416	48.879	3.16%	-3.36%
			5600	5.996	46.725	5.766	48.471	3.99%	-3.60%
			5620	6.019	46.701	5.790	48.444	3.96%	-3.60%
			5745	6.223	46.434	5.936	48.275	4.83%	-3.81%
			5765	6.243	46.422	5.959	48.248	4.77%	-3.78%
03/26/2018	5200B-5800B	21.6	5240	5.482	47.192	5.346	48.960	2.54%	-3.61%
			5260	5.507	47.138	5.369	48.933	2.57%	-3.67%
			5300	5.559	47.048	5.416	48.879	2.64%	-3.75%
			5600	5.953	46.547	5.766	48.471	3.24%	-3.97%
			5620	5.977	46.501	5.790	48.444	3.23%	-4.01%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 61 of 107

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results – 1g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
E	750	HEAD	03/14/2018	23.9	20.7	0.200	1003	3213	1.550	8.280	7.750	-6.40%
E	835	HEAD	03/05/2018	23.9	22.5	0.200	4d133	3213	1.960	9.520	9.800	2.94%
E	1750	HEAD	02/28/2018	24.1	22.5	0.100	1008	3319	3.430	36.400	34.300	-5.77%
G	1900	HEAD	03/05/2018	22.8	21.5	0.100	5d080	3332	3.770	39.300	37.700	-4.07%
G	1900	HEAD	03/21/2018	21.3	21.1	0.100	5d148	3332	3.930	40.100	39.300	-2.00%
G	2450	HEAD	02/25/2018	21.3	20.7	0.100	797	3332	5.640	52.700	56.400	7.02%
H	2600	HEAD	03/05/2018	22.4	21.5	0.100	1126	7410	5.870	56.400	58.700	4.08%
H	5250	HEAD	02/20/2018	22.3	20.6	0.050	1191	3589	3.680	78.900	73.600	-6.72%
H	5600	HEAD	02/20/2018	22.3	20.6	0.050	1191	3589	3.900	83.600	78.000	-6.70%
H	5750	HEAD	02/20/2018	22.3	20.6	0.050	1191	3589	3.690	79.100	73.800	-6.70%
K	750	BODY	03/12/2018	21.9	21.0	0.200	1161	7406	1.800	8.430	9.000	6.76%
K	835	BODY	02/26/2018	22.8	21.7	0.200	4d047	7406	1.980	9.570	9.900	3.45%
J	835	BODY	03/04/2018	22.6	21.1	0.200	4d133	3914	2.010	9.410	10.050	6.80%
J	835	BODY	03/07/2018	21.0	20.7	0.200	4d133	3914	1.830	9.410	9.150	-2.76%
E	835	BODY	04/03/2018	22.0	21.3	0.200	4d132	3213	2.070	9.710	10.350	6.59%
J	1750	BODY	02/26/2018	21.5	22.1	0.100	1150	3209	3.640	36.500	36.400	-0.27%
D	1900	BODY	02/26/2018	22.4	21.5	0.100	5d149	3318	4.190	40.100	41.900	4.49%
J	1900	BODY	03/19/2018	20.7	22.3	0.100	5d080	3914	4.180	39.100	41.800	6.91%
J	1900	BODY	03/21/2018	21.5	21.5	0.100	5d148	3914	4.110	39.600	41.100	3.79%
K	2450	BODY	02/19/2018	22.2	21.0	0.100	981	7406	5.240	50.800	52.400	3.15%
K	2450	BODY	03/04/2018	22.7	21.9	0.100	797	7406	5.110	51.100	51.100	0.00%
K	2600	BODY	03/04/2018	22.7	21.9	0.100	1126	7406	5.370	54.300	53.700	-1.10%
K	2600	BODY	03/18/2018	22.5	21.1	0.100	1126	7406	5.390	54.300	53.900	-0.74%
D	5250	BODY	02/21/2018	21.5	21.0	0.050	1237	7308	3.590	76.900	71.800	-6.63%
D	5600	BODY	02/21/2018	21.5	21.0	0.050	1237	7308	3.840	78.500	76.800	-2.17%
D	5750	BODY	02/21/2018	21.5	21.0	0.050	1237	7308	3.850	77.100	77.000	-0.13%

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 62 of 107

Table 10-4
System Verification Results – 10g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{10g} (W/kg)	1 W Target SAR _{10g} (W/kg)	1 W Normalized SAR _{10g} (W/kg)	Deviation _{10g} (%)
J	1750	BODY	02/28/2018	21.5	20.6	0.100	1148	3914	2.070	19.800	20.700	4.55%
D	1900	BODY	02/26/2018	22.4	21.5	0.100	5d149	3318	2.180	21.300	21.800	2.35%
D	1900	BODY	03/01/2018	22.5	20.6	0.100	5d080	3318	2.120	20.700	21.200	2.42%
J	1900	BODY	03/19/2018	20.7	22.3	0.100	5d080	3914	2.140	20.700	21.400	3.38%
D	5250	BODY	03/26/2018	21.6	20.7	0.050	1237	7308	0.995	21.500	19.900	-7.44%
D	5600	BODY	03/26/2018	21.6	20.7	0.050	1237	7308	1.020	22.100	20.400	-7.69%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 63 of 107

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

**Table 11-1
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.0	31.88	-0.06	Right	Cheek	34937	1	1:8.3	0.202	1.294	0.261	A1
836.60	190	GSM 850	GSM	33.0	31.88	0.05	Right	Tilt	34937	1	1:8.3	0.121	1.294	0.157	
836.60	190	GSM 850	GSM	33.0	31.88	0.08	Left	Cheek	34937	1	1:8.3	0.198	1.294	0.256	
836.60	190	GSM 850	GSM	33.0	31.88	-0.01	Left	Tilt	34937	1	1:8.3	0.118	1.294	0.153	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-2
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	29.0	27.91	0.02	Right	Cheek	34937	1	1:8.3	0.226	1.285	0.290	
1880.00	661	GSM 1900	GSM	29.0	27.91	-0.13	Right	Tilt	34937	1	1:8.3	0.129	1.285	0.166	
1880.00	661	GSM 1900	GSM	29.0	27.91	-0.05	Left	Cheek	34937	1	1:8.3	0.388	1.285	0.499	A2
1880.00	661	GSM 1900	GSM	29.0	27.91	0.01	Left	Tilt	34937	1	1:8.3	0.200	1.285	0.257	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-3
UMTS 850 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	24.0	22.98	0.08	Right	Cheek	34937	1:1	0.179	1.265	0.226	
836.60	4183	UMTS 850	RMC	24.0	22.98	0.08	Right	Tilt	34937	1:1	0.107	1.265	0.135	
836.60	4183	UMTS 850	RMC	24.0	22.98	0.08	Left	Cheek	34937	1:1	0.198	1.265	0.250	A3
836.60	4183	UMTS 850	RMC	24.0	22.98	0.07	Left	Tilt	34937	1:1	0.117	1.265	0.148	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 64 of 107

Table 11-4
UMTS 1750 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	-0.21	Right	Cheek	34945	1:1	0.203	1.343	0.273	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	-0.01	Right	Tilt	34945	1:1	0.222	1.343	0.298	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	0.02	Left	Cheek	34945	1:1	0.399	1.343	0.536	A4
1732.40	1412	UMTS 1750	RMC	22.5	21.22	-0.01	Left	Tilt	34945	1:1	0.214	1.343	0.287	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-5
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	-0.01	Right	Cheek	34960	1:1	0.304	1.161	0.353	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	0.08	Right	Tilt	34960	1:1	0.173	1.161	0.201	
1852.40	9262	UMTS 1900	RMC	21.5	20.15	0.02	Left	Cheek	34960	1:1	0.368	1.365	0.502	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	0.04	Left	Cheek	34960	1:1	0.578	1.161	0.671	A5
1907.60	9538	UMTS 1900	RMC	21.5	20.37	0.00	Left	Cheek	34960	1:1	0.548	1.297	0.711	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	0.00	Left	Tilt	34960	1:1	0.243	1.161	0.282	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-6
CDMA BC10 (§90S) Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.5	24.43	-0.03	Right	Cheek	34978	1:1	0.228	1.279	0.292	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.5	24.43	0.14	Right	Tilt	34978	1:1	0.145	1.279	0.185	
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.5	24.43	0.03	Left	Cheek	34978	1:1	0.245	1.279	0.313	A6
820.10	564	CDMA BC10 (§90S)	RC3 / SO55	25.5	24.43	0.07	Left	Tilt	34978	1:1	0.135	1.279	0.173	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.5	23.93	-0.01	Right	Cheek	34978	1:1	0.169	1.435	0.243	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.5	23.93	0.15	Right	Tilt	34978	1:1	0.114	1.435	0.164	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.5	23.93	0.06	Left	Cheek	34978	1:1	0.193	1.435	0.277	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. A	25.5	23.93	0.05	Left	Tilt	34978	1:1	0.106	1.435	0.152	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 65 of 107

Table 11-7
CDMA BC0 (\$22H) Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.5	24.32	0.05	Right	Cheek	34978	1:1	0.272	1.312	0.357	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.5	24.32	0.03	Right	Tilt	34978	1:1	0.167	1.312	0.219	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.5	24.32	0.00	Left	Cheek	34978	1:1	0.303	1.312	0.398	A7
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.5	24.32	-0.04	Left	Tilt	34978	1:1	0.167	1.312	0.219	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.0	23.84	-0.04	Right	Cheek	34978	1:1	0.248	1.306	0.324	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.0	23.84	-0.07	Right	Tilt	34978	1:1	0.148	1.306	0.193	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.0	23.84	0.03	Left	Cheek	34978	1:1	0.254	1.306	0.332	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.0	23.84	0.03	Left	Tilt	34978	1:1	0.166	1.306	0.217	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-8
PCS CDMA Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	22.3	21.71	0.01	Right	Cheek	34945	1:1	0.401	1.146	0.460	
1880.00	600	PCS CDMA	RC3 / SO55	22.3	21.71	0.03	Right	Tilt	34945	1:1	0.191	1.146	0.219	
1851.25	25	PCS CDMA	RC3 / SO55	22.3	21.84	0.08	Left	Cheek	34945	1:1	0.627	1.112	0.697	
1880.00	600	PCS CDMA	RC3 / SO55	22.3	21.71	0.06	Left	Cheek	34945	1:1	0.674	1.146	0.772	
1908.75	1175	PCS CDMA	RC3 / SO55	22.3	21.72	-0.01	Left	Cheek	34945	1:1	0.733	1.143	0.838	
1880.00	600	PCS CDMA	RC3 / SO55	22.3	21.71	0.03	Left	Tilt	34945	1:1	0.324	1.146	0.371	
1880.00	600	PCS CDMA	EVDO Rev. A	22.3	21.67	0.04	Right	Cheek	34945	1:1	0.435	1.156	0.503	
1880.00	600	PCS CDMA	EVDO Rev. A	22.3	21.67	0.01	Right	Tilt	34945	1:1	0.213	1.156	0.246	
1851.25	25	PCS CDMA	EVDO Rev. A	22.3	21.83	-0.01	Left	Cheek	34945	1:1	0.715	1.114	0.797	
1880.00	600	PCS CDMA	EVDO Rev. A	22.3	21.67	0.16	Left	Cheek	34945	1:1	0.758	1.156	0.876	
1908.75	1175	PCS CDMA	EVDO Rev. A	22.3	21.73	-0.01	Left	Cheek	34945	1:1	0.839	1.140	0.956	A8
1880.00	600	PCS CDMA	EVDO Rev. A	22.3	21.67	0.01	Left	Tilt	34945	1:1	0.345	1.156	0.399	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 66 of 107

Table 11-9
LTE Band 12 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	0.09	0	Right	Cheek	QPSK	1	0	34978	1:1	0.202	1.300	0.263	
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	-0.02	1	Right	Cheek	QPSK	25	0	34978	1:1	0.148	1.429	0.211	
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	-0.04	0	Right	Tilt	QPSK	1	0	34978	1:1	0.115	1.300	0.150	
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	0.04	1	Right	Tilt	QPSK	25	0	34978	1:1	0.089	1.429	0.127	
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	0.14	0	Left	Cheek	QPSK	1	0	34978	1:1	0.224	1.300	0.291	A9
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	-0.08	1	Left	Cheek	QPSK	25	0	34978	1:1	0.155	1.429	0.221	
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	-0.03	0	Left	Tilt	QPSK	1	0	34978	1:1	0.112	1.300	0.146	
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	-0.14	1	Left	Tilt	QPSK	25	0	34978	1:1	0.078	1.429	0.111	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-10
LTE Band 26 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	-0.02	0	Right	Cheek	QPSK	1	0	34937	1:1	0.161	1.403	0.226	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.03	1	Right	Cheek	QPSK	36	0	34937	1:1	0.151	1.535	0.232	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	0.10	0	Right	Tilt	QPSK	1	0	34937	1:1	0.092	1.403	0.129	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.06	1	Right	Tilt	QPSK	36	0	34937	1:1	0.092	1.535	0.141	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	0.17	0	Left	Cheek	QPSK	1	0	34937	1:1	0.153	1.403	0.215	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.17	1	Left	Cheek	QPSK	36	0	34937	1:1	0.152	1.535	0.233	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	-0.09	0	Left	Tilt	QPSK	1	0	34937	1:1	0.091	1.403	0.128	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.12	1	Left	Tilt	QPSK	36	0	34937	1:1	0.090	1.535	0.138	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	-0.07	0	Right	Cheek	QPSK	1	12	34937	1:1	0.311	1.208	0.376	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	0.00	0	Right	Tilt	QPSK	1	12	34937	1:1	0.170	1.208	0.205	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	0.03	0	Left	Cheek	QPSK	1	12	34937	1:1	0.312	1.208	0.377	A10
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	0.00	0	Left	Tilt	QPSK	1	12	34937	1:1	0.165	1.208	0.199	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-11
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	-0.07	0	Right	Cheek	QPSK	1	50	34945	1:1	0.234	1.250	0.293	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.02	1	Right	Cheek	QPSK	50	0	34945	1:1	0.180	1.396	0.251	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	0.11	0	Right	Tilt	QPSK	1	50	34945	1:1	0.284	1.250	0.355	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.04	1	Right	Tilt	QPSK	50	0	34945	1:1	0.216	1.396	0.302	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	0.03	0	Left	Cheek	QPSK	1	50	34945	1:1	0.537	1.250	0.671	A11
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.01	1	Left	Cheek	QPSK	50	0	34945	1:1	0.388	1.396	0.542	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	-0.04	0	Left	Tilt	QPSK	1	50	34945	1:1	0.287	1.250	0.359	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.02	1	Left	Tilt	QPSK	50	0	34945	1:1	0.214	1.396	0.299	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 67 of 107

Table 11-12
LTE Band 25 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	0.02	0	Right	Cheek	QPSK	1	50	34960	1:1	0.297	1.167	0.347	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	0.09	1	Right	Cheek	QPSK	50	25	34960	1:1	0.209	1.297	0.271	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	0.11	0	Right	Tilt	QPSK	1	50	34960	1:1	0.168	1.167	0.196	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	0.06	1	Right	Tilt	QPSK	50	25	34960	1:1	0.116	1.297	0.150	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.0	21.05	0.07	0	Left	Cheek	QPSK	1	0	34960	1:1	0.382	1.245	0.476	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	20.51	-0.01	0	Left	Cheek	QPSK	1	99	34960	1:1	0.491	1.409	0.692	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	-0.01	0	Left	Cheek	QPSK	1	50	34960	1:1	0.558	1.167	0.651	A12
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	0.02	1	Left	Cheek	QPSK	50	25	34960	1:1	0.386	1.297	0.501	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	0.03	0	Left	Tilt	QPSK	1	50	34960	1:1	0.186	1.167	0.217	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	0.04	1	Left	Tilt	QPSK	50	25	34960	1:1	0.152	1.297	0.197	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-13
LTE Band 2 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.12	0	Right	Cheek	QPSK	1	50	34960	1:1	0.352	1.186	0.417	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	0.03	1	Right	Cheek	QPSK	50	0	34960	1:1	0.247	1.309	0.323	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.11	0	Right	Tilt	QPSK	1	50	34960	1:1	0.169	1.186	0.200	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	0.05	1	Right	Tilt	QPSK	50	0	34960	1:1	0.116	1.309	0.152	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	21.64	0.04	0	Left	Cheek	QPSK	1	50	34960	1:1	0.479	1.219	0.584	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.41	-0.02	0	Left	Cheek	QPSK	1	99	34960	1:1	0.573	1.285	0.736	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.16	0	Left	Cheek	QPSK	1	50	34960	1:1	0.626	1.186	0.742	A13
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	-0.01	1	Left	Cheek	QPSK	50	0	34960	1:1	0.450	1.309	0.589	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	-0.01	0	Left	Tilt	QPSK	1	50	34960	1:1	0.220	1.186	0.261	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	0.02	1	Left	Tilt	QPSK	50	0	34960	1:1	0.178	1.309	0.233	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-14
LTE Band 41 Head SAR

MEASUREMENT RESULTS																				
Power Class	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
	MHz	Ch.														(W/kg)		(W/kg)		
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.07	0	Right	Cheek	QPSK	1	0	34978	1:1.58	0.143	1.510	0.216	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.14	1	Right	Cheek	QPSK	50	0	34978	1:1.58	0.111	1.507	0.167	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.10	0	Right	Tilt	QPSK	1	0	34978	1:1.58	0.150	1.510	0.227	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.07	1	Right	Tilt	QPSK	50	0	34978	1:1.58	0.120	1.507	0.181	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.04	0	Left	Cheek	QPSK	1	0	34978	1:1.58	0.228	1.510	0.344	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.08	1	Left	Cheek	QPSK	50	0	34978	1:1.58	0.186	1.507	0.280	
Power Class 2	2549.50	40185	Low-Mid	LTE Band 41	20	27.5	26.75	0.02	0	Left	Cheek	QPSK	1	0	34978	1:2.31	0.430	1.189	0.511	A14
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.15	0	Left	Tilt	QPSK	1	0	34978	1:1.58	0.090	1.510	0.136	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.11	1	Left	Tilt	QPSK	50	0	34978	1:1.58	0.073	1.507	0.110	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 68 of 107

**Table 11-15
DTS Head SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	16.0	15.10	-0.18	Right	Cheek	37039	1	99.6	0.687	0.552	1.230	1.004	0.682	
2437	6	802.11b	DSSS	22	16.0	15.58	0.02	Right	Cheek	37039	1	99.6	0.702	0.589	1.102	1.004	0.652	
2462	11	802.11b	DSSS	22	16.0	15.25	0.11	Right	Cheek	37039	1	99.6	0.736	0.683	1.189	1.004	0.815	A15
2437	6	802.11b	DSSS	22	16.0	15.58	0.02	Right	Tilt	37039	1	99.6	0.588	0.463	1.102	1.004	0.512	
2437	6	802.11b	DSSS	22	16.0	15.58	-0.11	Left	Cheek	37039	1	99.6	0.327	0.279	1.102	1.004	0.309	
2437	6	802.11b	DSSS	22	16.0	15.58	-0.12	Left	Tilt	37039	1	99.6	0.359	-	1.102	1.004	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-16
NII Head SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5270	54	802.11n	OFDM	40	12.0	10.60	-0.11	Right	Cheek	37039	13.5	97.7	1.190	-	1.380	1.024	-	
5270	54	802.11n	OFDM	40	12.0	10.60	0.04	Right	Tilt	37039	13.5	97.7	1.278	0.537	1.380	1.024	0.759	
5310	62	802.11n	OFDM	40	9.0	8.66	0.16	Right	Tilt	37039	13.5	97.7	0.645	0.282	1.081	1.024	0.312	
5270	54	802.11n	OFDM	40	12.0	10.60	0.19	Left	Cheek	37039	13.5	97.7	1.154	0.621	1.380	1.024	0.878	
5310	62	802.11n	OFDM	40	9.0	8.66	-0.20	Left	Cheek	37039	13.5	97.7	0.509	0.277	1.081	1.024	0.307	
5270	54	802.11n	OFDM	40	12.0	10.60	0.13	Left	Tilt	37039	13.5	97.7	1.332	0.652	1.380	1.024	0.921	
5310	62	802.11n	OFDM	40	9.0	8.66	0.16	Left	Tilt	37039	13.5	97.7	0.530	0.292	1.081	1.024	0.323	
5510	102	802.11n	OFDM	40	12.0	11.27	0.12	Right	Cheek	37039	13.5	97.7	1.234	-	1.183	1.024	-	
5510	102	802.11n	OFDM	40	12.0	11.27	0.18	Right	Tilt	37039	13.5	97.7	1.297	0.585	1.183	1.024	0.709	
5510	102	802.11n	OFDM	40	12.0	11.27	-0.12	Left	Cheek	37039	13.5	97.7	1.237	-	1.183	1.024	-	
5510	102	802.11n	OFDM	40	12.0	11.27	0.16	Left	Tilt	37039	13.5	97.7	1.405	0.675	1.183	1.024	0.818	
5630	126	802.11n	OFDM	40	12.0	11.11	0.13	Left	Tilt	37039	13.5	97.7	0.852	0.423	1.227	1.024	0.531	
5755	151	802.11n	OFDM	40	12.0	11.24	0.05	Right	Cheek	37039	13.5	97.7	1.596	0.639	1.191	1.024	0.779	
5755	151	802.11n	OFDM	40	12.0	11.24	0.14	Right	Tilt	37039	13.5	97.7	1.805	0.724	1.191	1.024	0.883	A16
5795	159	802.11n	OFDM	40	12.0	11.13	0.10	Right	Tilt	37039	13.5	97.7	1.033	0.429	1.222	1.024	0.537	
5755	151	802.11n	OFDM	40	12.0	11.24	0.14	Left	Cheek	37039	13.5	97.7	1.359	-	1.191	1.024	-	
5755	151	802.11n	OFDM	40	12.0	11.24	-0.16	Left	Tilt	37039	13.5	97.7	1.438	-	1.191	1.024	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 69 of 107

11.2 Standalone Body-Worn SAR Data

Table 11-17
GSM/UMTS/CDMA Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.0	31.88	0.02	15 mm	34978	1	1:8.3	back	0.257	1.294	0.333	A17
1880.00	661	GSM 1900	GSM	30.0	29.02	-0.03	15 mm	34978	1	1:8.3	back	0.180	1.253	0.226	A19
836.60	4183	UMTS 850	RMC	24.0	22.98	0.01	15 mm	34937	N/A	1:1	back	0.242	1.265	0.306	A21
1732.40	1412	UMTS 1750	RMC	23.0	22.07	0.02	15 mm	34937	N/A	1:1	back	0.248	1.239	0.307	A23
1880.00	9400	UMTS 1900	RMC	23.0	22.33	0.02	15 mm	34978	N/A	1:1	back	0.431	1.167	0.503	A25
820.10	564	CDMA BC10 (S90S)	TDSO / SO32	25.5	24.40	0.13	15 mm	34978	N/A	1:1	back	0.325	1.288	0.419	A27
836.52	384	CDMA BC0 (S22H)	TDSO / SO32	25.5	24.29	-0.03	15 mm	34978	N/A	1:1	back	0.335	1.321	0.443	A29
1851.25	25	PCS CDMA	TDSO / SO32	24.5	23.84	-0.01	15 mm	34937	N/A	1:1	back	0.449	1.164	0.523	
1880.00	600	PCS CDMA	TDSO / SO32	24.5	23.71	0.02	15 mm	34937	N/A	1:1	back	0.553	1.199	0.663	
1908.75	1175	PCS CDMA	TDSO / SO32	24.5	23.75	-0.02	15 mm	34937	N/A	1:1	back	0.635	1.189	0.755	A31
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-18
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	-0.09	0	34937	QPSK	1	0	15 mm	back	1:1	0.464	1.300	0.603	A33
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	-0.03	1	34937	QPSK	25	0	15 mm	back	1:1	0.325	1.429	0.464	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	0.00	0	34978	QPSK	1	0	15 mm	back	1:1	0.294	1.403	0.412	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.02	1	34978	QPSK	36	0	15 mm	back	1:1	0.245	1.535	0.376	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	-0.14	0	82142	QPSK	1	12	15 mm	back	1:1	0.419	1.208	0.506	A35
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	23.50	0.05	0	34978	QPSK	1	0	15 mm	back	1:1	0.314	1.259	0.395	A37
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.05	-0.03	1	34978	QPSK	50	0	15 mm	back	1:1	0.230	1.396	0.321	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.5	23.94	0.03	0	34978	QPSK	1	50	15 mm	back	1:1	0.526	1.138	0.599	A39
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.51	-0.02	1	34978	QPSK	50	0	15 mm	back	1:1	0.381	1.256	0.479	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	23.78	0.01	0	34978	QPSK	1	99	15 mm	back	1:1	0.475	1.180	0.561	A41
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.60	0.03	1	34978	QPSK	50	25	15 mm	back	1:1	0.363	1.230	0.446	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 70 of 107

Table 11-19
LTE Band 41 Body-Worn SAR

MEASUREMENT RESULTS																				
Power Class	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
	MHz	Ch.														(W/kg)		(W/kg)		
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.07	0	34978	QPSK	1	0	15 mm	back	1:1.58	0.239	1.510	0.361	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.04	1	34978	QPSK	50	0	15 mm	back	1:1.58	0.194	1.507	0.292	
Power Class 2	2549.50	40185	Low-Mid	LTE Band 41	20	27.5	26.75	0.13	0	34978	QPSK	1	0	15 mm	back	1:2.31	0.423	1.189	0.503	A43
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body											
Spatial Peak									1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population									averaged over 1 gram											

Table 11-20
DTS Body-Worn SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	16.0	15.58	0.06	15 mm	37039	1	back	99.6	0.108	0.077	1.102	1.004	0.085	A45
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body										
Spatial Peak								1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 1 gram										

Table 11-21
NII Body-Worn SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5300	60	802.11a	OFDM	20	16.0	15.49	-0.13	15 mm	37039	6	back	98.9	0.314	0.141	1.125	1.011	0.160	
5620	124	802.11a	OFDM	20	16.0	14.81	0.01	15 mm	37039	6	back	98.9	0.288	0.131	1.315	1.011	0.174	
5745	149	802.11a	OFDM	20	16.0	15.24	-0.02	15 mm	37039	6	back	98.9	0.430	0.175	1.191	1.011	0.211	A47
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body										
Spatial Peak								1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 1 gram										

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 71 of 107

11.3 Standalone Hotspot SAR Data

Table 11-22
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	29.0	28.27	-0.06	10 mm	34978	3	1:2.76	back	0.463	1.183	0.548	A18
836.60	190	GSM 850	GPRS	29.0	28.27	-0.21	10 mm	34978	3	1:2.76	front	0.354	1.183	0.419	
836.60	190	GSM 850	GPRS	29.0	28.27	0.09	10 mm	34978	3	1:2.76	bottom	0.046	1.183	0.054	
836.60	190	GSM 850	GPRS	29.0	28.27	0.04	10 mm	34978	3	1:2.76	right	0.267	1.183	0.316	
836.60	190	GSM 850	GPRS	29.0	28.27	0.03	10 mm	34978	3	1:2.76	left	0.279	1.183	0.330	
1880.00	661	GSM 1900	GPRS	26.0	25.25	-0.08	10 mm	34978	3	1:2.76	back	0.494	1.189	0.587	A20
1880.00	661	GSM 1900	GPRS	26.0	25.25	0.00	10 mm	34978	3	1:2.76	front	0.492	1.189	0.585	
1880.00	661	GSM 1900	GPRS	26.0	25.25	0.05	10 mm	34978	3	1:2.76	bottom	0.080	1.189	0.095	
1880.00	661	GSM 1900	GPRS	26.0	25.25	-0.06	10 mm	34978	3	1:2.76	right	0.039	1.189	0.046	
1880.00	661	GSM 1900	GPRS	26.0	25.25	0.03	10 mm	34978	3	1:2.76	left	0.409	1.189	0.486	
836.60	4183	UMTS 850	RMC	24.0	22.98	0.00	10 mm	34937	N/A	1:1	back	0.288	1.265	0.364	A22
836.60	4183	UMTS 850	RMC	24.0	22.98	-0.01	10 mm	34937	N/A	1:1	front	0.209	1.265	0.264	
836.60	4183	UMTS 850	RMC	24.0	22.98	-0.04	10 mm	34937	N/A	1:1	bottom	0.027	1.265	0.034	
836.60	4183	UMTS 850	RMC	24.0	22.98	0.00	10 mm	34937	N/A	1:1	right	0.163	1.265	0.206	
836.60	4183	UMTS 850	RMC	24.0	22.98	0.03	10 mm	34937	N/A	1:1	left	0.184	1.265	0.233	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	0.02	10 mm	34960	N/A	1:1	back	0.426	1.343	0.572	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	-0.06	10 mm	34960	N/A	1:1	front	0.435	1.343	0.584	A24
1732.40	1412	UMTS 1750	RMC	22.5	21.22	-0.01	10 mm	34960	N/A	1:1	bottom	0.214	1.343	0.287	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	-0.03	10 mm	34960	N/A	1:1	right	0.054	1.343	0.073	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	-0.07	10 mm	34960	N/A	1:1	left	0.310	1.343	0.416	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	0.08	10 mm	34960	N/A	1:1	back	0.588	1.161	0.683	
1852.40	9262	UMTS 1900	RMC	21.5	20.15	-0.01	10 mm	34960	N/A	1:1	front	0.451	1.365	0.616	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	0.02	10 mm	34960	N/A	1:1	front	0.630	1.161	0.731	A26
1907.60	9538	UMTS 1900	RMC	21.5	20.37	-0.03	10 mm	34960	N/A	1:1	front	0.616	1.297	0.799	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	-0.01	10 mm	34960	N/A	1:1	bottom	0.120	1.161	0.139	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	0.01	10 mm	34960	N/A	1:1	right	0.029	1.161	0.034	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	-0.03	10 mm	34960	N/A	1:1	left	0.448	1.161	0.520	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 72 of 107

Table 11-23
CDMA Hotspot SAR Data

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (S90S)	EVDO Rev. 0	25.5	23.96	0.20	10 mm	34978	1:1	back	0.324	1.426	0.462	A28
820.10	564	CDMA BC10 (S90S)	EVDO Rev. 0	25.5	23.96	0.20	10 mm	34978	1:1	front	0.248	1.426	0.354	
820.10	564	CDMA BC10 (S90S)	EVDO Rev. 0	25.5	23.96	0.11	10 mm	34978	1:1	bottom	0.019	1.426	0.027	
820.10	564	CDMA BC10 (S90S)	EVDO Rev. 0	25.5	23.96	-0.05	10 mm	34978	1:1	right	0.194	1.426	0.277	
820.10	564	CDMA BC10 (S90S)	EVDO Rev. 0	25.5	23.96	-0.19	10 mm	34978	1:1	left	0.209	1.426	0.298	
836.52	384	CDMA BC0 (S22H)	EVDO Rev. 0	25.0	23.81	0.16	10 mm	34978	1:1	back	0.349	1.315	0.459	A30
836.52	384	CDMA BC0 (S22H)	EVDO Rev. 0	25.0	23.81	0.01	10 mm	34978	1:1	front	0.246	1.315	0.323	
836.52	384	CDMA BC0 (S22H)	EVDO Rev. 0	25.0	23.81	0.17	10 mm	34978	1:1	bottom	0.024	1.315	0.032	
836.52	384	CDMA BC0 (S22H)	EVDO Rev. 0	25.0	23.81	-0.16	10 mm	34978	1:1	right	0.190	1.315	0.250	
836.52	384	CDMA BC0 (S22H)	EVDO Rev. 0	25.0	23.81	0.03	10 mm	34978	1:1	left	0.211	1.315	0.277	
1851.25	25	PCS CDMA	EVDO Rev. 0	22.3	21.88	-0.03	10 mm	34945	1:1	back	0.676	1.102	0.745	
1880.00	600	PCS CDMA	EVDO Rev. 0	22.3	21.75	-0.19	10 mm	34945	1:1	back	0.777	1.135	0.882	
1908.75	1175	PCS CDMA	EVDO Rev. 0	22.3	21.77	0.05	10 mm	34945	1:1	back	0.852	1.130	0.963	A32
1851.25	25	PCS CDMA	EVDO Rev. 0	22.3	21.88	0.05	10 mm	34945	1:1	front	0.632	1.102	0.696	
1880.00	600	PCS CDMA	EVDO Rev. 0	22.3	21.75	0.03	10 mm	34945	1:1	front	0.761	1.135	0.864	
1908.75	1175	PCS CDMA	EVDO Rev. 0	22.3	21.77	-0.05	10 mm	34945	1:1	front	0.818	1.130	0.924	
1880.00	600	PCS CDMA	EVDO Rev. 0	22.3	21.75	0.01	10 mm	34945	1:1	bottom	0.161	1.135	0.183	
1880.00	600	PCS CDMA	EVDO Rev. 0	22.3	21.75	0.08	10 mm	34945	1:1	right	0.058	1.135	0.066	
1880.00	600	PCS CDMA	EVDO Rev. 0	22.3	21.75	0.01	10 mm	34945	1:1	left	0.597	1.135	0.678	
1908.75	1175	PCS CDMA	EVDO Rev. 0	22.3	21.77	0.03	10 mm	34945	1:1	back	0.837	1.130	0.946	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body 1.6 W/kg (mW/g) averaged over 1 gram							
Spatial Peak														
Uncontrolled Exposure/General Population														

Note: Blue entry represents variability measurement.

Table 11-24
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	-0.10	0	34937	QPSK	1	0	10 mm	back	1:1	0.561	1.300	0.729	A34
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	0.03	1	34937	QPSK	25	0	10 mm	back	1:1	0.387	1.429	0.553	
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	0.06	0	34937	QPSK	1	0	10 mm	front	1:1	0.367	1.300	0.477	
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	0.09	1	34937	QPSK	25	0	10 mm	front	1:1	0.253	1.429	0.362	
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	0.14	0	34937	QPSK	1	0	10 mm	bottom	1:1	0.031	1.300	0.040	
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	0.18	1	34937	QPSK	25	0	10 mm	bottom	1:1	0.021	1.429	0.030	
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	0.05	0	34937	QPSK	1	0	10 mm	right	1:1	0.336	1.300	0.437	
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	0.04	1	34937	QPSK	25	0	10 mm	right	1:1	0.242	1.429	0.346	
707.50	23095	Mid	LTE Band 12	10	25.5	24.36	0.02	0	34937	QPSK	1	0	10 mm	left	1:1	0.381	1.300	0.495	
707.50	23095	Mid	LTE Band 12	10	24.5	22.95	0.00	1	34937	QPSK	25	0	10 mm	left	1:1	0.275	1.429	0.393	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 73 of 107

Table 11-25
LTE Band 26 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	0.01	0	34978	QPSK	1	0	10 mm	back	1:1	0.335	1.403	0.470	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.05	1	34978	QPSK	36	0	10 mm	back	1:1	0.281	1.535	0.431	
816.50	26715	Low	LTE Band 26 (Cell)	5	25.5	24.45	-0.14	0	82142	QPSK	1	0	10 mm	back	1:1	0.430	1.274	0.548	
831.50	26865	Mid	LTE Band 26 (Cell)	5	25.5	24.51	0.00	0	82142	QPSK	1	0	10 mm	back	1:1	0.457	1.256	0.574	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	-0.19	0	82142	QPSK	1	12	10 mm	back	1:1	0.526	1.208	0.635	A36
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	0.01	0	34978	QPSK	1	0	10 mm	front	1:1	0.244	1.403	0.342	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.00	1	34978	QPSK	36	0	10 mm	front	1:1	0.208	1.535	0.319	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	-0.05	0	82142	QPSK	1	12	10 mm	front	1:1	0.381	1.208	0.460	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	0.16	0	34978	QPSK	1	0	10 mm	bottom	1:1	0.022	1.403	0.031	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.13	1	34978	QPSK	36	0	10 mm	bottom	1:1	0.021	1.535	0.032	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	0.00	0	82142	QPSK	1	12	10 mm	bottom	1:1	0.054	1.208	0.065	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	0.00	0	34978	QPSK	1	0	10 mm	right	1:1	0.208	1.403	0.292	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	-0.01	1	34978	QPSK	36	0	10 mm	right	1:1	0.177	1.535	0.272	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	-0.03	0	82142	QPSK	1	12	10 mm	right	1:1	0.352	1.208	0.425	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	24.03	0.06	0	34978	QPSK	1	0	10 mm	left	1:1	0.246	1.403	0.345	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	22.64	0.03	1	34978	QPSK	36	0	10 mm	left	1:1	0.203	1.535	0.312	
846.50	27015	High	LTE Band 26 (Cell)	5	25.5	24.68	-0.01	0	82142	QPSK	1	12	10 mm	left	1:1	0.394	1.208	0.476	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak								Body											
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g)											
								averaged over 1 gram											

Table 11-26
LTE Band 4 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR[dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	0.00	0	34960	QPSK	1	50	10 mm	back	1:1	0.413	1.250	0.516	A38
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.03	1	34960	QPSK	50	0	10 mm	back	1:1	0.310	1.396	0.433	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	-0.02	0	34960	QPSK	1	50	10 mm	front	1:1	0.413	1.250	0.516	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.01	1	34960	QPSK	50	0	10 mm	front	1:1	0.306	1.396	0.427	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	-0.02	0	34960	QPSK	1	50	10 mm	bottom	1:1	0.215	1.250	0.269	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.09	1	34960	QPSK	50	0	10 mm	bottom	1:1	0.153	1.396	0.214	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	-0.04	0	34960	QPSK	1	50	10 mm	right	1:1	0.048	1.250	0.060	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.14	1	34960	QPSK	50	0	10 mm	right	1:1	0.037	1.396	0.052	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	0.06	0	34960	QPSK	1	50	10 mm	left	1:1	0.284	1.250	0.355	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.03	1	34960	QPSK	50	0	10 mm	left	1:1	0.208	1.396	0.290	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram											
Uncontrolled Exposure/General Population																			

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 74 of 107

Table 11-27
LTE Band 25 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR[dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	0.08	0	34960	QPSK	1	50	10 mm	back	1:1	0.518	1.167	0.605	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	0.02	1	34960	QPSK	50	25	10 mm	back	1:1	0.337	1.297	0.437	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.0	21.05	0.13	0	34960	QPSK	1	0	10 mm	front	1:1	0.408	1.245	0.508	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	20.51	-0.03	0	34960	QPSK	1	99	10 mm	front	1:1	0.524	1.409	0.738	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	0.06	0	34960	QPSK	1	50	10 mm	front	1:1	0.560	1.167	0.654	A40
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	0.01	1	34960	QPSK	50	25	10 mm	front	1:1	0.378	1.297	0.490	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	-0.05	0	34960	QPSK	1	50	10 mm	bottom	1:1	0.117	1.167	0.137	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	-0.03	1	34960	QPSK	50	25	10 mm	bottom	1:1	0.091	1.297	0.118	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	-0.11	0	34960	QPSK	1	50	10 mm	right	1:1	0.022	1.167	0.026	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	-0.01	1	34960	QPSK	50	25	10 mm	right	1:1	0.023	1.297	0.030	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	-0.02	0	34960	QPSK	1	50	10 mm	left	1:1	0.430	1.167	0.502	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	0.03	1	34960	QPSK	50	25	10 mm	left	1:1	0.307	1.297	0.398	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population										averaged over 1 gram									

Table 11-28
LTE Band 2 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	21.64	-0.08	0	34960	QPSK	1	50	10 mm	back	1:1	0.504	1.219	0.614	A42
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.41	0.04	0	34960	QPSK	1	99	10 mm	back	1:1	0.621	1.285	0.798	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.04	0	34960	QPSK	1	50	10 mm	back	1:1	0.577	1.186	0.684	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	-0.05	1	34960	QPSK	50	0	10 mm	back	1:1	0.424	1.309	0.555	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.00	0	34960	QPSK	1	50	10 mm	front	1:1	0.537	1.186	0.637	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	0.01	1	34960	QPSK	50	0	10 mm	front	1:1	0.396	1.309	0.518	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.00	0	34960	QPSK	1	50	10 mm	bottom	1:1	0.129	1.186	0.153	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	-0.02	1	34960	QPSK	50	0	10 mm	bottom	1:1	0.093	1.309	0.122	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.04	0	34960	QPSK	1	50	10 mm	right	1:1	0.032	1.186	0.038	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	0.07	1	34960	QPSK	50	0	10 mm	right	1:1	0.022	1.309	0.029	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.02	0	34960	QPSK	1	50	10 mm	left	1:1	0.484	1.186	0.574	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	0.01	1	34960	QPSK	50	0	10 mm	left	1:1	0.355	1.309	0.465	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 75 of 107

Table 11-29
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																				
Power Class	FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
	MHz	Ch.															(W/kg)		(W/kg)	
Power Class 3	2506.00	39750	Low	LTE Band 41	20	24.0	22.06	0.11	0	34978	QPSK	1	99	10 mm	back	1:1.58	0.463	1.563	0.724	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.05	0	34978	QPSK	1	0	10 mm	back	1:1.58	0.455	1.510	0.687	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.0	22.08	0.11	0	34978	QPSK	1	99	10 mm	back	1:1.58	0.454	1.556	0.706	
Power Class 3	2636.50	41055	Mid-High	LTE Band 41	20	24.0	22.01	0.03	0	34978	QPSK	1	0	10 mm	back	1:1.58	0.505	1.581	0.798	
Power Class 3	2680.00	41490	High	LTE Band 41	20	24.0	22.05	0.04	0	34978	QPSK	1	99	10 mm	back	1:1.58	0.454	1.567	0.711	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.02	1	34978	QPSK	50	0	10 mm	back	1:1.58	0.370	1.507	0.558	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.21	0.03	1	34978	QPSK	100	0	10 mm	back	1:1.58	0.395	1.510	0.596	
Power Class 2	2636.50	41055	Mid-High	LTE Band 41	20	27.5	26.51	0.15	0	34978	QPSK	1	0	10 mm	back	1:2.31	0.955	1.256	1.199	A4
Power Class 3	2506.00	39750	Low	LTE Band 41	20	24.0	22.06	0.07	0	34978	QPSK	1	99	10 mm	front	1:1.58	0.434	1.563	0.678	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.00	0	34978	QPSK	1	0	10 mm	front	1:1.58	0.417	1.510	0.630	
Power Class 3	2593.00	40620	Mid	LTE Band 41	20	24.0	22.08	0.17	0	34978	QPSK	1	99	10 mm	front	1:1.58	0.507	1.556	0.789	
Power Class 3	2636.50	41055	Mid-High	LTE Band 41	20	24.0	22.01	-0.06	0	34978	QPSK	1	0	10 mm	front	1:1.58	0.484	1.581	0.765	
Power Class 3	2680.00	41490	High	LTE Band 41	20	24.0	22.05	0.12	0	34978	QPSK	1	99	10 mm	front	1:1.58	0.487	1.567	0.763	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.01	1	34978	QPSK	50	0	10 mm	front	1:1.58	0.343	1.507	0.517	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.21	0.01	1	34978	QPSK	100	0	10 mm	front	1:1.58	0.412	1.510	0.622	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.07	0	34978	QPSK	1	0	10 mm	bottom	1:1.58	0.193	1.510	0.291	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.02	1	34978	QPSK	50	0	10 mm	bottom	1:1.58	0.160	1.507	0.241	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	-0.05	0	34978	QPSK	1	0	10 mm	right	1:1.58	0.038	1.510	0.057	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.16	1	34978	QPSK	50	0	10 mm	right	1:1.58	0.029	1.507	0.044	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	24.0	22.21	0.07	0	34978	QPSK	1	0	10 mm	left	1:1.58	0.232	1.510	0.350	
Power Class 3	2549.50	40185	Low-Mid	LTE Band 41	20	23.0	21.22	0.02	1	34978	QPSK	50	0	10 mm	left	1:1.58	0.188	1.507	0.283	
Power Class 2	2636.50	41055	Mid-High	LTE Band 41	20	27.5	26.51	0.12	0	34978	QPSK	1	0	10 mm	back	1:2.31	0.895	1.256	1.124	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																				
Spatial Peak										Body										
Uncontrolled Exposure/General Population										1.6 W/kg (mW/g) averaged over 1 gram										

Note: Blue entry represents variability measurement.

Table 11-30
WLAN Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	16.0	15.58	0.14	10 mm	37039	1	back	99.6	0.194	0.139	1.102	1.004	0.154	A46
2437	6	802.11b	DSSS	22	16.0	15.58	0.12	10 mm	37039	1	front	99.6	0.169	-	1.102	1.004	-	
2437	6	802.11b	DSSS	22	16.0	15.58	0.10	10 mm	37039	1	top	99.6	0.108	-	1.102	1.004	-	
2437	6	802.11b	DSSS	22	16.0	15.58	0.11	10 mm	37039	1	right	99.6	0.045	-	1.102	1.004	-	
2437	6	802.11b	DSSS	22	16.0	15.58	0.16	10 mm	37039	1	left	99.6	0.138	-	1.102	1.004	-	
5745	149	802.11a	OFDM	20	16.0	15.24	-0.15	10 mm	37039	6	back	98.9	0.576	0.263	1.191	1.011	0.317	
5745	149	802.11a	OFDM	20	16.0	15.24	-0.10	10 mm	37039	6	front	98.9	0.887	0.409	1.191	1.011	0.492	
5745	149	802.11a	OFDM	20	16.0	15.24	-0.03	10 mm	37039	6	top	98.9	0.993	0.458	1.191	1.011	0.551	A48
5745	149	802.11a	OFDM	20	16.0	15.24	-0.19	10 mm	37039	6	right	98.9	0.563	-	1.191	1.011	-	
5745	149	802.11a	OFDM	20	16.0	15.24	0.10	10 mm	37039	6	left	98.9	0.015	-	1.191	1.011	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body										
Spatial Peak								1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 1 gram										

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 76 of 107

11.4 Standalone Phablet SAR Data

Table 11-31
UMTS Phablet SAR Data

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Duty Cycle	Side	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	23.0	22.07	-0.03	2 mm	34978	1:1	back	1.210	1.239	1.499	
1732.40	1412	UMTS 1750	RMC	23.0	22.07	-0.06	2 mm	34978	1:1	front	1.040	1.239	1.289	
1732.40	1412	UMTS 1750	RMC	23.0	22.07	0.00	2 mm	34978	1:1	bottom	0.193	1.239	0.239	
1732.40	1412	UMTS 1750	RMC	23.0	22.07	0.10	0 mm	34978	1:1	right	0.102	1.239	0.126	
1732.40	1412	UMTS 1750	RMC	23.0	22.07	0.01	0 mm	34978	1:1	left	0.724	1.239	0.897	
1712.40	1312	UMTS 1750	RMC	22.5	21.53	0.01	0 mm	34960	1:1	back	2.300	1.250	2.875	A49
1732.40	1412	UMTS 1750	RMC	22.5	21.22	0.01	0 mm	34960	1:1	back	2.200	1.343	2.955	
1752.60	1513	UMTS 1750	RMC	22.5	21.22	0.02	0 mm	34960	1:1	back	2.170	1.343	2.914	
1712.40	1312	UMTS 1750	RMC	22.5	21.53	0.00	0 mm	34960	1:1	front	1.980	1.250	2.475	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	0.10	0 mm	34960	1:1	front	1.910	1.343	2.565	
1752.60	1513	UMTS 1750	RMC	22.5	21.22	0.02	0 mm	34960	1:1	front	1.930	1.343	2.592	
1732.40	1412	UMTS 1750	RMC	22.5	21.22	-0.11	0 mm	34960	1:1	bottom	0.292	1.343	0.392	
1712.40	1312	UMTS 1750	RMC	22.5	21.53	0.14	0 mm	34960	1:1	back	2.130	1.250	2.663	
1852.40	9262	UMTS 1900	RMC	23.0	21.88	0.01	2 mm	34978	1:1	back	1.670	1.294	2.161	
1880.00	9400	UMTS 1900	RMC	23.0	22.33	0.00	2 mm	34978	1:1	back	2.000	1.167	2.334	
1907.60	9538	UMTS 1900	RMC	23.0	21.93	0.01	2 mm	34978	1:1	back	1.680	1.279	2.149	
1852.40	9262	UMTS 1900	RMC	23.0	21.88	0.12	2 mm	34978	1:1	front	1.850	1.294	2.394	
1880.00	9400	UMTS 1900	RMC	23.0	22.33	0.01	2 mm	34978	1:1	front	1.950	1.167	2.276	
1907.60	9538	UMTS 1900	RMC	23.0	21.93	0.06	2 mm	34978	1:1	front	1.820	1.279	2.328	
1880.00	9400	UMTS 1900	RMC	23.0	22.33	-0.14	2 mm	34978	1:1	bottom	0.198	1.167	0.231	
1880.00	9400	UMTS 1900	RMC	23.0	22.33	-0.03	0 mm	34978	1:1	right	0.031	1.167	0.036	
1880.00	9400	UMTS 1900	RMC	23.0	22.33	-0.05	0 mm	34978	1:1	left	1.320	1.167	1.540	
1852.40	9262	UMTS 1900	RMC	21.5	20.15	-0.03	0 mm	34960	1:1	back	1.610	1.365	2.198	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	-0.12	0 mm	34960	1:1	back	1.770	1.161	2.055	
1907.60	9538	UMTS 1900	RMC	21.5	20.37	-0.02	0 mm	34960	1:1	back	1.940	1.297	2.516	
1852.40	9262	UMTS 1900	RMC	21.5	20.15	0.05	0 mm	34960	1:1	front	1.850	1.365	2.525	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	0.13	0 mm	34960	1:1	front	2.280	1.161	2.647	A50
1907.60	9538	UMTS 1900	RMC	21.5	20.37	0.19	0 mm	34960	1:1	front	2.000	1.297	2.594	
1880.00	9400	UMTS 1900	RMC	21.5	20.85	-0.04	0 mm	34960	1:1	bottom	0.199	1.161	0.231	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams							

Note: Blue entry represents variability measurement.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 77 of 107

Table 11-32
CDMA Phablet SAR Data

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Duty Cycle	Side	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.5	23.87	0.03	2 mm	34937	1:1	back	2.600	1.156	3.006	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.5	23.73	-0.01	2 mm	34937	1:1	back	2.600	1.194	3.104	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.5	23.78	0.05	2 mm	34937	1:1	back	2.670	1.180	3.151	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.5	23.87	0.05	2 mm	34937	1:1	front	2.660	1.156	3.075	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.5	23.73	0.01	2 mm	34937	1:1	front	2.590	1.194	3.092	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.5	23.78	-0.03	2 mm	34937	1:1	front	2.740	1.180	3.233	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.5	23.73	0.02	2 mm	34937	1:1	bottom	0.211	1.194	0.252	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.5	23.73	-0.20	0 mm	34937	1:1	right	0.046	1.194	0.055	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.5	23.87	-0.01	0 mm	34937	1:1	left	1.890	1.156	2.185	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.5	23.73	0.03	0 mm	34937	1:1	left	1.980	1.194	2.364	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.5	23.78	0.03	0 mm	34937	1:1	left	2.010	1.180	2.372	
1851.25	25	PCS CDMA	EVDO Rev. 0	22.3	21.88	0.01	0 mm	34945	1:1	back	2.810	1.102	3.097	
1880.00	600	PCS CDMA	EVDO Rev. 0	22.3	21.75	-0.01	0 mm	34945	1:1	back	2.830	1.135	3.212	
1908.75	1175	PCS CDMA	EVDO Rev. 0	22.3	21.77	0.02	0 mm	34945	1:1	back	2.910	1.130	3.288	A51
1851.25	25	PCS CDMA	EVDO Rev. 0	22.3	21.88	0.10	0 mm	34945	1:1	front	2.430	1.102	2.678	
1880.00	600	PCS CDMA	EVDO Rev. 0	22.3	21.75	0.01	0 mm	34945	1:1	front	2.570	1.135	2.917	
1908.75	1175	PCS CDMA	EVDO Rev. 0	22.3	21.77	-0.02	0 mm	34945	1:1	front	2.740	1.130	3.096	
1880.00	600	PCS CDMA	EVDO Rev. 0	22.3	21.75	-0.17	0 mm	34945	1:1	bottom	0.231	1.135	0.262	
1908.75	1175	PCS CDMA	EVDO Rev. 0	22.3	21.77	0.01	0 mm	34945	1:1	back	2.830	1.130	3.198	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams							

Note: Blue entry represents variability measurement.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 78 of 107

Table 11-33
LTE Band 4 (AWS) Phablet SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #
MHz	Ch.														(W/kg)		(W/kg)	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	23.50	-0.02	0	34978	QPSK	1	0	2 mm	back	1:1	1.390	1.259	1.750
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.05	0.02	1	34978	QPSK	50	0	2 mm	back	1:1	1.010	1.396	1.410
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	23.50	-0.04	0	34978	QPSK	1	0	2 mm	front	1:1	1.130	1.259	1.423
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.05	0.03	1	34978	QPSK	50	0	2 mm	front	1:1	0.814	1.396	1.136
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	23.50	-0.13	0	34978	QPSK	1	0	2 mm	bottom	1:1	0.213	1.259	0.268
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.05	0.11	1	34978	QPSK	50	0	2 mm	bottom	1:1	0.212	1.396	0.296
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	23.50	-0.01	0	34978	QPSK	1	0	0 mm	right	1:1	0.141	1.259	0.178
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.05	0.06	1	34978	QPSK	50	0	0 mm	right	1:1	0.097	1.396	0.135
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	23.50	0.01	0	34978	QPSK	1	0	0 mm	left	1:1	0.846	1.259	1.065
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.05	0.03	1	34978	QPSK	50	0	0 mm	left	1:1	0.620	1.396	0.866
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	0.02	0	34960	QPSK	1	50	0 mm	back	1:1	2.020	1.250	2.525
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	-0.02	1	34960	QPSK	50	0	0 mm	back	1:1	1.510	1.396	2.108
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.03	-0.02	1	34960	QPSK	100	0	0 mm	back	1:1	1.500	1.403	2.105
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	0.03	0	34960	QPSK	1	50	0 mm	front	1:1	1.900	1.250	2.375
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	0.00	1	34960	QPSK	50	0	0 mm	front	1:1	1.460	1.396	2.038
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.03	0.00	1	34960	QPSK	100	0	0 mm	front	1:1	1.440	1.403	2.020
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.53	-0.07	0	34960	QPSK	1	50	0 mm	bottom	1:1	0.280	1.250	0.350
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.5	20.05	-0.06	1	34960	QPSK	50	0	0 mm	bottom	1:1	0.203	1.396	0.283
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Phablet										
Spatial Peak								4.0 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 10 grams										

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 79 of 107

Table 11-34
LTE Band 25 (PCS) Phablet SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.5	23.69	-0.08	0	34978	QPSK	1	0	2 mm	back	1:1	2.450	1.205	2.952	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.5	23.16	-0.11	0	34978	QPSK	1	99	2 mm	back	1:1	2.300	1.361	3.130	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.5	23.94	-0.01	0	34978	QPSK	1	50	2 mm	back	1:1	2.600	1.138	2.959	A53
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.32	-0.01	1	34978	QPSK	50	0	2 mm	back	1:1	1.810	1.312	2.375	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.5	21.75	0.01	1	34978	QPSK	50	50	2 mm	back	1:1	1.770	1.496	2.648	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.51	0.09	1	34978	QPSK	50	0	2 mm	back	1:1	1.840	1.256	2.311	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.48	0.00	1	34978	QPSK	100	0	2 mm	back	1:1	1.890	1.265	2.391	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.5	23.69	0.09	0	34978	QPSK	1	0	2 mm	front	1:1	2.240	1.205	2.699	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.5	23.16	0.19	0	34978	QPSK	1	99	2 mm	front	1:1	2.180	1.361	2.967	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.5	23.94	-0.05	0	34978	QPSK	1	50	2 mm	front	1:1	2.370	1.138	2.697	
1860.00	26140	Low	LTE Band 25 (PCS)	20	23.5	22.32	0.07	1	34978	QPSK	50	0	2 mm	front	1:1	1.720	1.312	2.257	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.5	21.75	0.05	1	34978	QPSK	50	50	2 mm	front	1:1	1.670	1.496	2.498	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.51	0.07	1	34978	QPSK	50	0	2 mm	front	1:1	1.790	1.256	2.248	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.48	0.03	1	34978	QPSK	100	0	2 mm	front	1:1	1.800	1.265	2.277	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.5	23.94	-0.16	0	34978	QPSK	1	50	2 mm	bottom	1:1	0.126	1.138	0.143	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.51	-0.01	1	34978	QPSK	50	0	2 mm	bottom	1:1	0.095	1.256	0.119	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.5	23.94	0.12	0	34978	QPSK	1	50	0 mm	right	1:1	0.031	1.138	0.035	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.51	0.20	1	34978	QPSK	50	0	0 mm	right	1:1	0.021	1.256	0.026	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.5	23.94	-0.16	0	34978	QPSK	1	50	0 mm	left	1:1	1.750	1.138	1.992	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.5	22.51	0.08	1	34978	QPSK	50	0	0 mm	left	1:1	1.270	1.256	1.595	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	0.01	0	34960	QPSK	1	50	0 mm	back	1:1	1.700	1.167	1.984	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	-0.10	1	34960	QPSK	50	25	0 mm	back	1:1	1.220	1.297	1.582	
1860.00	26140	Low	LTE Band 25 (PCS)	20	22.0	21.05	-0.09	0	34960	QPSK	1	0	0 mm	front	1:1	1.870	1.245	2.328	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	22.0	20.51	0.16	0	34960	QPSK	1	99	0 mm	front	1:1	1.860	1.409	2.621	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	0.05	0	34960	QPSK	1	50	0 mm	front	1:1	2.000	1.167	2.334	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	0.17	1	34960	QPSK	50	25	0 mm	front	1:1	1.460	1.297	1.894	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.85	-0.02	1	34960	QPSK	100	0	0 mm	front	1:1	1.440	1.303	1.876	
1905.00	26590	High	LTE Band 25 (PCS)	20	22.0	21.33	-0.13	0	34960	QPSK	1	50	0 mm	bottom	1:1	0.200	1.167	0.233	
1905.00	26590	High	LTE Band 25 (PCS)	20	21.0	19.87	-0.19	1	34960	QPSK	50	25	0 mm	bottom	1:1	0.138	1.297	0.179	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Phablet 4.0 W/kg (mW/g) averaged over 10 grams											

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 80 of 107

Table 11-35
LTE Band 2 (PCS) Phablet SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maxmum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.5	23.61	0.08	0	34937	QPSK	1	0	2 mm	back	1:1	1.920	1.227	2.356	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	24.5	23.21	0.07	0	34937	QPSK	1	99	2 mm	back	1:1	1.930	1.346	2.598	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	23.78	0.01	0	34937	QPSK	1	99	2 mm	back	1:1	2.070	1.180	2.443	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.60	0.03	1	34937	QPSK	50	25	2 mm	back	1:1	1.610	1.230	1.980	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.40	-0.08	1	34937	QPSK	100	0	2 mm	back	1:1	1.520	1.288	1.958	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.5	23.61	0.01	0	34937	QPSK	1	0	2 mm	front	1:1	1.860	1.227	2.282	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	24.5	23.21	0.06	0	34937	QPSK	1	99	2 mm	front	1:1	1.880	1.346	2.530	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	23.78	0.04	0	34937	QPSK	1	99	2 mm	front	1:1	1.900	1.180	2.242	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.60	0.10	1	34937	QPSK	50	25	2 mm	front	1:1	1.480	1.230	1.820	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.40	-0.03	1	34937	QPSK	100	0	2 mm	front	1:1	1.480	1.288	1.906	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	23.78	-0.08	0	34937	QPSK	1	99	2 mm	bottom	1:1	0.208	1.180	0.245	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.60	0.00	1	34937	QPSK	50	25	2 mm	bottom	1:1	0.151	1.230	0.186	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	23.78	0.03	0	34937	QPSK	1	99	0 mm	right	1:1	0.037	1.180	0.044	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.60	-0.02	1	34937	QPSK	50	25	0 mm	right	1:1	0.022	1.230	0.027	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	23.78	-0.14	0	34937	QPSK	1	99	0 mm	left	1:1	1.600	1.180	1.888	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.60	0.10	1	34937	QPSK	50	25	0 mm	left	1:1	1.210	1.230	1.488	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	21.64	-0.02	0	34960	QPSK	1	50	0 mm	back	1:1	1.730	1.219	2.109	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.41	0.07	0	34960	QPSK	1	99	0 mm	back	1:1	1.960	1.285	2.519	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.12	0	34960	QPSK	1	50	0 mm	back	1:1	1.970	1.186	2.336	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	0.03	1	34960	QPSK	50	0	0 mm	back	1:1	1.500	1.309	1.964	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.30	0.00	1	34960	QPSK	100	0	0 mm	back	1:1	1.500	1.318	1.977	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	21.64	0.14	0	34960	QPSK	1	50	0 mm	front	1:1	2.120	1.219	2.584	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.41	0.11	0	34960	QPSK	1	99	0 mm	front	1:1	2.160	1.285	2.776	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.02	0	34960	QPSK	1	50	0 mm	front	1:1	2.190	1.186	2.597	A54
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.5	20.17	0.06	1	34960	QPSK	50	50	0 mm	front	1:1	1.390	1.358	1.888	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.5	19.85	0.06	1	34960	QPSK	50	50	0 mm	front	1:1	1.500	1.462	2.193	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	0.11	1	34960	QPSK	50	0	0 mm	front	1:1	1.710	1.309	2.238	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.30	0.08	1	34960	QPSK	100	0	0 mm	front	1:1	1.630	1.318	2.148	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.76	0.03	0	34960	QPSK	1	50	0 mm	bottom	1:1	0.195	1.186	0.231	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.33	-0.12	1	34960	QPSK	50	0	0 mm	bottom	1:1	0.141	1.309	0.185	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Phablet											
Spatial Peak								4.0 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 10 grams											

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 81 of 107

Table 11-36
WLAN Phablet SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5300	60	802.11a	OFDM	20	16.0	15.49	0.17	0 mm	37039	6	back	98.9	8.479	0.963	1.125	1.011	1.095	
5300	60	802.11a	OFDM	20	16.0	15.49	-0.17	0 mm	37039	6	front	98.9	8.212	1.000	1.125	1.011	1.137	A55
5300	60	802.11a	OFDM	20	16.0	15.49	-0.17	0 mm	37039	6	top	98.9	8.315	0.883	1.125	1.011	1.004	
5300	60	802.11a	OFDM	20	16.0	15.49	0.17	0 mm	37039	6	right	98.9	1.522	-	1.125	1.011	-	
5300	60	802.11a	OFDM	20	16.0	15.49	0.17	0 mm	37039	6	left	98.9	0.270	-	1.125	1.011	-	
5620	124	802.11a	OFDM	20	16.0	14.81	-0.13	0 mm	37039	6	back	98.9	7.499	0.763	1.315	1.011	1.014	
5620	124	802.11a	OFDM	20	16.0	14.81	-0.12	0 mm	37039	6	front	98.9	6.119	0.739	1.315	1.011	0.982	
5620	124	802.11a	OFDM	20	16.0	14.81	-0.11	0 mm	37039	6	top	98.9	7.149	0.767	1.315	1.011	1.020	
5620	124	802.11a	OFDM	20	16.0	14.81	0.06	0 mm	37039	6	right	98.9	1.044	-	1.315	1.011	-	
5620	124	802.11a	OFDM	20	16.0	14.81	0.10	0 mm	37039	6	left	98.9	0.096	-	1.315	1.011	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population												Phablet 4.0 W/kg (mW/g) averaged over 10 grams						

11.5 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
- During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
- Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.
- This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.
- Unless otherwise noted, when 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds below.
- Additional SAR tests for phablet SAR were evaluated per KDB 616217 Section 6 (See Section 6.9 for more information).

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 82 of 107

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
4. There was no power reduction for GPRS/EDGE modes. Therefore, Hotspot SAR Evaluations (and phablet SAR Exclusion analysis) were performed at the maximum allowed output power.

CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03r01.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO Rev0 and RevA and TDSO / SO32 FCH+SCH SAR tests were not required per the 3G SAR Test Reduction Procedure in FCC KDB Publication 941225 D01v03r01.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
6. CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1X Advanced was not more than 0.25 dB higher than the maximum powers for 1X.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 83 of 107

3. A-MPR was disabled for all SAR tests by setting NS=01 and MCC=001 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg for 1g evaluations, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
6. Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.
7. This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per FCC Guidance, all SAR tests were performed using Power Class 3. SAR with power class 2 at the available duty factor was additionally performed for the power class 3 configuration with the highest SAR configuration for each exposure conditions. Please see Section 14 for linearity results.

WLAN Notes:

1. For held-to-ear, hotspot, and phablet operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g evaluations, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 8.7.6 for more information.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
6. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 84 of 107

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 10g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{18.75} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Head)	Estimated SAR (Head)	Separation Distance (Body, Body-Worn)	Estimated SAR (Body, Body-Worn)	Separation Distance (Body, Hotspot)	Estimated SAR (Body, Hotspot)	Separation Distance (Phablet)	Estimated SAR (Phablet)
	[MHz]	[dBm]	[mm]	[W/kg]	[mm]	[W/kg]	[mm]	[W/kg]	[mm]	[W/kg]
Bluetooth	2480	9.00	5	0.336	15	0.112	10	0.168	5	0.134

Note: Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for applicable exposure conditions was used for simultaneous transmission analysis.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 85 of 107

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.261	0.815	1.076
	GSM 1900	0.499	0.815	1.314
	UMTS 850	0.250	0.815	1.065
	UMTS 1750	0.536	0.815	1.351
	UMTS 1900	0.711	0.815	1.526
	CDMA/EVDO BC10 (\$90S)	0.313	0.815	1.128
	CDMA/EVDO BC0 (\$22H)	0.398	0.815	1.213
	PCS CDMA/EVDO	0.956	0.815	See Table Below
	LTE Band 12	0.291	0.815	1.106
	LTE Band 26 (Cell)	0.377	0.815	1.192
	LTE Band 4 (AWS)	0.671	0.815	1.486
	LTE Band 25 (PCS)	0.692	0.815	1.507
	LTE Band 2 (PCS)	0.742	0.815	1.557
	LTE Band 41	0.511	0.815	1.326

Simult Tx	Configuration	PCS CDMA SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	PCS EVDO SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.460	0.815	1.275	Head SAR	Right Cheek	0.503	0.815	1.318
	Right Tilt	0.219	0.512	0.731		Right Tilt	0.246	0.512	0.758
	Left Cheek	0.838	0.309	1.147		Left Cheek	0.956	0.309	1.265
	Left Tilt	0.371	0.815*	1.186		Left Tilt	0.399	0.815*	1.214

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 86 of 107

Table 12-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.261	0.921	1.182
	GSM 1900	0.499	0.921	1.420
	UMTS 850	0.250	0.921	1.171
	UMTS 1750	0.536	0.921	1.457
	UMTS 1900	0.711	0.921	See Table Below
	CDMA/EVDO BC10 (\$90S)	0.313	0.921	1.234
	CDMA/EVDO BC0 (\$22H)	0.398	0.921	1.319
	PCS CDMA/EVDO	0.956	0.921	See Table Below
	LTE Band 12	0.291	0.921	1.212
	LTE Band 26 (Cell)	0.377	0.921	1.298
	LTE Band 4 (AWS)	0.671	0.921	1.592
	LTE Band 25 (PCS)	0.692	0.921	See Table Below
	LTE Band 2 (PCS)	0.742	0.921	See Table Below
	LTE Band 41	0.511	0.921	1.432

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	PCS CDMA SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.353	0.779	1.132	Head SAR	Right Cheek	0.460	0.779	1.239	N/A
	Right Tilt	0.201	0.883	1.084		Right Tilt	0.219	0.883	1.102	N/A
	Left Cheek	0.711	0.878	1.589		Left Cheek	0.838	0.878	See Note 1	0.03
	Left Tilt	0.282	0.921	1.203		Left Tilt	0.371	0.921	1.292	N/A

Simult Tx	Configuration	PCS EVDO SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.503	0.779	1.282	N/A
	Right Tilt	0.246	0.883	1.129	N/A
	Left Cheek	0.956	0.878	See Note 1	0.03
	Left Tilt	0.399	0.921	1.320	N/A

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Head SAR	Right Cheek	0.347	0.779	1.126	Head SAR	Right Cheek	0.417	0.779	1.196	N/A
	Right Tilt	0.196	0.883	1.079		Right Tilt	0.200	0.883	1.083	N/A
	Left Cheek	0.692	0.878	1.570		Left Cheek	0.742	0.878	See Note 1	0.03
	Left Tilt	0.217	0.921	1.138		Left Tilt	0.261	0.921	1.182	N/A

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 			Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 87 of 107

Table 12-4
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.261	0.336	0.597
	GSM 1900	0.499	0.336	0.835
	UMTS 850	0.250	0.336	0.586
	UMTS 1750	0.536	0.336	0.872
	UMTS 1900	0.711	0.336	1.047
	CDMA/EVDO BC10 (\$90S)	0.313	0.336	0.649
	CDMA/EVDO BC0 (\$22H)	0.398	0.336	0.734
	PCS CDMA/EVDO	0.956	0.336	1.292
	LTE Band 12	0.291	0.336	0.627
	LTE Band 26 (Cell)	0.377	0.336	0.713
	LTE Band 4 (AWS)	0.671	0.336	1.007
	LTE Band 25 (PCS)	0.692	0.336	1.028
	LTE Band 2 (PCS)	0.742	0.336	1.078
	LTE Band 41	0.511	0.336	0.847

Notes:

- No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 for 1g and not greater than 0.10 for 10g per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 88 of 107

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.333	0.085	0.418
	GSM 1900	0.226	0.085	0.311
	UMTS 850	0.306	0.085	0.391
	UMTS 1750	0.307	0.085	0.392
	UMTS 1900	0.503	0.085	0.588
	CDMA BC10 (§90S)	0.419	0.085	0.504
	CDMA BC0 (§22H)	0.443	0.085	0.528
	PCS CDMA	0.755	0.085	0.840
	LTE Band 12	0.603	0.085	0.688
	LTE Band 26 (Cell)	0.506	0.085	0.591
	LTE Band 4 (AWS)	0.395	0.085	0.480
	LTE Band 25 (PCS)	0.599	0.085	0.684
	LTE Band 2 (PCS)	0.561	0.085	0.646
	LTE Band 41	0.503	0.085	0.588

Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.333	0.211	0.544
	GSM 1900	0.226	0.211	0.437
	UMTS 850	0.306	0.211	0.517
	UMTS 1750	0.307	0.211	0.518
	UMTS 1900	0.503	0.211	0.714
	CDMA BC10 (§90S)	0.419	0.211	0.630
	CDMA BC0 (§22H)	0.443	0.211	0.654
	PCS CDMA	0.755	0.211	0.966
	LTE Band 12	0.603	0.211	0.814
	LTE Band 26 (Cell)	0.506	0.211	0.717
	LTE Band 4 (AWS)	0.395	0.211	0.606
	LTE Band 25 (PCS)	0.599	0.211	0.810
	LTE Band 2 (PCS)	0.561	0.211	0.772
	LTE Band 41	0.503	0.211	0.714

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 89 of 107

Table 12-7
Simultaneous Transmission Scenario with Bluetooth(Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.333	0.112	0.445
	GSM 1900	0.226	0.112	0.338
	UMTS 850	0.306	0.112	0.418
	UMTS 1750	0.307	0.112	0.419
	UMTS 1900	0.503	0.112	0.615
	CDMA BC10 (§90S)	0.419	0.112	0.531
	CDMA BC0 (§22H)	0.443	0.112	0.555
	PCS CDMA	0.755	0.112	0.867
	LTE Band 12	0.603	0.112	0.715
	LTE Band 26 (Cell)	0.506	0.112	0.618
	LTE Band 4 (AWS)	0.395	0.112	0.507
	LTE Band 25 (PCS)	0.599	0.112	0.711
	LTE Band 2 (PCS)	0.561	0.112	0.673
	LTE Band 41	0.503	0.112	0.615

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 90 of 107

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

Table 12-8
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.548	0.154	0.702
	GPRS 1900	0.587	0.154	0.741
	UMTS 850	0.364	0.154	0.518
	UMTS 1750	0.584	0.154	0.738
	UMTS 1900	0.799	0.154	0.953
	EVDO BC10 (\$90S)	0.462	0.154	0.616
	EVDO BC0 (\$22H)	0.459	0.154	0.613
	PCS EVDO	0.963	0.154	1.117
	LTE Band 12	0.729	0.154	0.883
	LTE Band 26 (Cell)	0.635	0.154	0.789
	LTE Band 4 (AWS)	0.516	0.154	0.670
	LTE Band 25 (PCS)	0.738	0.154	0.892
	LTE Band 2 (PCS)	0.798	0.154	0.952
	LTE Band 41	1.199	0.154	1.353

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 	Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset
		Page 91 of 107

Table 12-9
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.548	0.551	1.099
	GPRS 1900	0.587	0.551	1.138
	UMTS 850	0.364	0.551	0.915
	UMTS 1750	0.584	0.551	1.135
	UMTS 1900	0.799	0.551	1.350
	EVDO BC10 (\$90S)	0.462	0.551	1.013
	EVDO BC0 (\$22H)	0.459	0.551	1.010
	PCS EVDO	0.963	0.551	1.514
	LTE Band 12	0.729	0.551	1.280
	LTE Band 26 (Cell)	0.635	0.551	1.186
	LTE Band 4 (AWS)	0.516	0.551	1.067
	LTE Band 25 (PCS)	0.738	0.551	1.289
	LTE Band 2 (PCS)	0.798	0.551	1.349
	LTE Band 41	1.199	0.551	See Table Below

Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	Back	1.199	0.317	1.516
	Front	0.789	0.492	1.281
	Top	-	0.551	0.551
	Bottom	0.291	-	0.291
	Right	0.057	0.551*	0.608
	Left	0.350	0.551*	0.901

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 92 of 107

Table 12-10
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.548	0.168	0.716
	GPRS 1900	0.587	0.168	0.755
	UMTS 850	0.364	0.168	0.532
	UMTS 1750	0.584	0.168	0.752
	UMTS 1900	0.799	0.168	0.967
	EVDO BC10 (\$90S)	0.462	0.168	0.630
	EVDO BC0 (\$22H)	0.459	0.168	0.627
	PCS EVDO	0.963	0.168	1.131
	LTE Band 12	0.729	0.168	0.897
	LTE Band 26 (Cell)	0.635	0.168	0.803
	LTE Band 4 (AWS)	0.516	0.168	0.684
	LTE Band 25 (PCS)	0.738	0.168	0.906
	LTE Band 2 (PCS)	0.798	0.168	0.966
	LTE Band 41	1.199	0.168	1.367

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 93 of 107

12.6 Phablet Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore, no further analysis beyond the tables included in this section was required to determine that possible simultaneous transmission scenarios would not exceed the SAR limit.

Table 12-11
Simultaneous Transmission Scenario with 5 GHz WLAN (Phablet)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Phablet SAR	UMTS 1750	2.955	1.137	See Table Below
	UMTS 1900	2.647	1.137	3.784
	PCS EVDO	3.288	1.137	See Table Below
	LTE Band 4 (AWS)	2.525	1.137	3.662
	LTE Band 25 (PCS)	3.130	1.137	See Table Below
	LTE Band 2 (PCS)	2.776	1.137	3.913

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	PCS EVDO SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Phablet SAR	Back	2.955	1.095	See Note 1	0.06	Phablet SAR	Back	3.288	1.095	See Note 1	0.07
	Front	2.592	1.137	3.729	N/A		Front	3.233	1.137	See Note 1	0.07
	Top	-	1.020	1.020	N/A		Top	-	1.020	1.020	N/A
	Bottom	0.392	-	0.392	N/A		Bottom	0.262	-	0.262	N/A
	Right	0.126	1.137*	1.263	N/A		Right	0.055	1.137*	1.192	N/A
	Left	0.897	1.137*	2.034	N/A		Left	2.372	1.137*	3.509	N/A

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Phablet SAR	Back	3.130	1.095	See Note 1	0.06
	Front	2.967	1.137	See Note 1	0.06
	Top	-	1.020	1.020	N/A
	Bottom	0.233	-	0.233	N/A
	Right	0.035	1.137*	1.172	N/A
	Left	1.992	1.137*	3.129	N/A

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 94 of 107

Table 12-12
Simultaneous Transmission Scenario with Bluetooth (Phablet)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Phablet SAR	UMTS 1750	2.955	0.134	3.089
	UMTS 1900	2.647	0.134	2.781
	PCS EVDO	3.288	0.134	3.422
	LTE Band 4 (AWS)	2.525	0.134	2.659
	LTE Band 25 (PCS)	3.130	0.134	3.264
	LTE Band 2 (PCS)	2.776	0.134	2.910

Notes:

1. No evaluation was performed to determine the aggregate 10g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 for 1g and not greater than 0.10 for 10g per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.
2. For SAR summation, the highest reported SAR across all test distances was used as the most conservative evaluation for simultaneous transmission analysis for each device edge.

12.7 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g and 4 W/kg for 10g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 for 1g and ≤ 0.10 for 10g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2}$$

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 95 of 107

12.7.1 Left Cheek SPLSR Evaluation and Analysis


Table 12-13
Peak SAR Locations for Left Cheek

Mode/Band	x (mm)	y (mm)	z (mm)	Reported SAR (W/kg)
5 GHz WLAN	-7.51	309.46	-172.93	0.878
PCS CDMA	46.77	257.83	-171.44	0.838
PCS EVDO	43.19	248.02	-170.93	0.956
LTE Band 2 (PCS)	42.89	251.50	-171.23	0.742

Table 12-14
Left Cheek SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	$(a+b)^{1.5}/D_{a-b}$	
5 GHz WLAN	PCS CDMA	0.878	0.838	1.716	74.93	0.03	1
5 GHz WLAN	PCS EVDO	0.878	0.956	1.834	79.68	0.03	2
5 GHz WLAN	LTE Band 2 (PCS)	0.878	0.742	1.620	76.83	0.03	3

Table 12-15
Left Cheek SAR to Peak Location Separation Ratio Plots



FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 96 of 107

12.7.2 Phablet Back Side SPLSR Evaluation and Analysis


Table 12-16
Peak SAR Locations for Phablet Back Side

Mode/Band	x (mm)	y (mm)	Reported SAR (W/kg)
5 GHz WLAN	-12.00	70.00	1.095
UMTS 1750	-2.50	-57.00	2.955
PCS EVDO	-1.00	-68.00	3.288
LTE Band 25	3.90	-62.70	3.130

Table 12-17
Phablet Back Side SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	$(a+b)^{1.5}/D_{a-b}$	
5 GHz WLAN	UMTS 1750	1.095	2.955	4.050	127.35	0.06	1
5 GHz WLAN	PCS EVDO	1.095	3.288	4.383	138.44	0.07	2
5 GHz WLAN	LTE Band 25	1.095	3.130	4.225	133.65	0.06	3

Table 12-18
Phablet Back Side SAR to Peak Location Separation Ratio Plots



FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 97 of 107

12.7.3 Phablet Front Side SPLSR Evaluation and Analysis


Table 12-19
Peak SAR Locations for Phablet Back Side

Mode/Band	x (mm)	y (mm)	Reported SAR (W/kg)
5 GHz WLAN	-19.00	65.00	1.137
PCS EVDO	-50.50	-66.50	3.233
LTE Band 25 (PCS)	-41.00	-67.50	2.967

Table 12-20
Phablet Front Side SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	$(a+b)^{1.5}/D_{a-b}$	
5 GHz WLAN	PCS EVDO	1.137	3.233	4.370	135.22	0.07	1
5 GHz WLAN	LTE Band 25 (PCS)	1.137	2.967	4.104	134.31	0.06	2

Table 12-21
Phablet Front Side SAR to Peak Location Separation Ratio Plots



12.8 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 98 of 107

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1908.75	1175	PCS CDMA	EVDO Rev. 0	back	10 mm	0.852	0.837	1.02	N/A	N/A	N/A	N/A
2600	2636.50	41055	LTE Band 41, Power Class 2, 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	back	10 mm	0.955	0.895	1.07	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

Table 13-2
Phablet SAR Measurement Variability Results

PHABLET VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (10g)	1st Repeated SAR (10g)	Ratio	2nd Repeated SAR (10g)	Ratio	3rd Repeated SAR (10g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1712.40	1312	UMTS 1750	RMC	back	0 mm	2.300	2.130	1.08	N/A	N/A	N/A	N/A
1900	1908.75	1175	PCS CDMA	EVDO Rev. 0	back	0 mm	2.910	2.830	1.03	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams						

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg and < 3.75 W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 99 of 107

14 ADDITIONAL TESTING PER FCC GUIDANCE

14.1 LTE Band 41 Power Class 2 and Power Class 3 Linearity

This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per May 2017 TCB Workshop Notes based on the device behavior, all SAR tests were performed using Power Class 3. SAR with Power Class 2 at the highest power and available duty factor was additionally performed for the Power Class 3 configuration with the highest SAR for each exposure condition. The linearity between the Power Class 2 and Power Class 3 SAR results and the respective frame averaged powers was calculated to determine that the results were linear. Per May 2017 TCB Workshop, no additional SAR measurements were required since the linearity between power classes as < 10% and all reported SAR values were < 1.4 W/kg for 1g and < 3.5 W/kg for 10g.

LTE Band 41 SAR testing with power class 2 at the highest power and available duty factor was additionally performed for the power class 3 configuration with the highest SAR for each exposure condition.

Table 14-1
LTE Band 41 Head Linearity Data

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24	27.5
Measured Output Power (dBm)	22.21	26.75
Measured SAR (W/kg)	0.228	0.43
Measured Power (mW)	166.34	473.15
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	105.29	204.87
% deviation from expected linearity		-3.07%




Figure 14-1
LTE Band 41 Head Linearity

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 100 of 107

Table 14-2
LTE Band 41 Body-Worn Linearity Data

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24	27.5
Measured Output Power (dBm)	22.21	26.75
Measured SAR (W/kg)	0.239	0.423
Measured Power (mW)	166.34	473.15
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	105.29	204.87
% deviation from expected linearity		-9.04%




Figure 14-2
LTE Band 41 Body-Worn Linearity

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 101 of 107

Table 14-3
LTE Band 41 Hotspot Linearity Data

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	24	27.5
Measured Output Power (dBm)	22.01	26.51
Measured SAR (W/kg)	0.505	0.895
Measured Power (mW)	158.85	447.71
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	100.56	193.86
% deviation from expected linearity		-8.07%




Figure 14-3
LTE Band 41 Hotspot Linearity

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 102 of 107

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/22/2017	Annual	3/22/2018	MY45470194
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	E5515C	8960 Series 10 Wireless Communications Test Set	11/15/2017	Annual	11/15/2018	GB42230325
Agilent	E4438C	ESG Vector Signal Generator	3/24/2017	Biennial	3/24/2019	MY42082385
Agilent	E4432B	ESG-D Series Signal Generator	3/24/2017	Annual	3/24/2018	US40053896
Agilent	N9020A	MXA Signal Analyzer	1/24/2018	Annual	1/24/2019	US46470561
Agilent	N5182A	MXG Vector Signal Generator	11/1/2017	Annual	11/1/2018	MY47420603
Agilent	87535	S-Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	87535E	S-Parameter Network Analyzer	2/8/2018	Annual	2/8/2019	US39170122
Agilent	87535E	S-Parameter Vector Network Analyzer	8/17/2017	Annual	8/17/2018	MY40003841
Agilent	E5515C	Wireless Communications Test Set	5/31/2017	Annual	5/31/2018	GB43304278
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433971
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433972
Anritsu	ML2495A	Power Meter	10/22/2017	Annual	10/22/2018	941001
Anritsu	ML2495A	Power Meter	11/28/2017	Annual	11/28/2018	1059008
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1207364
Anritsu	MA2411B	Pulse Power Sensor	10/16/2017	Annual	10/16/2018	1207470
Anritsu	MT8820C	Radio Communication Analyzer	1/5/2018	Annual	1/5/2019	6201144418
Anritsu	MT8820C	Radio Communication Analyzer	5/23/2017	Annual	5/23/2018	6201240328
Anritsu	MA24106A	USB Power Sensor	6/7/2017	Annual	6/7/2018	1231535
Anritsu	MA24106A	USB Power Sensor	6/7/2017	Annual	6/7/2018	1231538
COMTech	AR85729-S	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	4040	Therm./Clock/Humidity Monitor	1/8/2018	Annual	1/8/2019	160473909
Control Company	435Z	Ultra Low Stem Thermometer	5/2/2017	Biennial	5/2/2019	170330171
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/4/2017	Annual	6/4/2018	MY53401181
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Mini Circuits	PWR-4GH5	USB Power Sensor	1/22/2018	Annual	1/22/2019	11710030062
Mini Circuits	PWR-4GH5	USB Power Sensor	1/20/2018	Annual	1/20/2019	11710030063
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mitutoyo	CD-6 CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264162
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	BW-53W2	Attenuator (3dB)	CBT	N/A	CBT	320
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	4/11/2017	Annual	4/11/2018	836371/0079
Rohde & Schwarz	CMW500	Radio Communication Tester	11/3/2017	Annual	11/3/2018	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	5/4/2017	Annual	5/4/2018	101699
Rohde & Schwarz	CMW500	Radio Communication Tester	10/13/2017	Annual	10/13/2018	102060
Seakork	NC-100	Torque Wrench	12/28/2017	Annual	12/28/2018	N/A
SPEAG	D750V3	750 MHz SAR Dipole	1/15/2018	Annual	1/15/2019	1003
SPEAG	D750V3	750 MHz SAR Dipole	7/13/2016	Biennial	7/13/2018	1161
SPEAG	D835V2	835 MHz SAR Dipole	7/13/2016	Biennial	7/13/2018	44047
SPEAG	D835V2	835 MHz SAR Dipole	1/15/2018	Annual	1/15/2019	46132
SPEAG	D835V2	835 MHz SAR Dipole	7/11/2017	Annual	7/11/2018	46133
SPEAG	D1750V2	1750 MHz SAR Dipole	5/9/2017	Annual	5/9/2018	1148
SPEAG	D1750V2	1750 MHz SAR Dipole	7/14/2016	Biennial	7/14/2018	1150
SPEAG	D1765V2	1765 MHz SAR Dipole	5/9/2017	Annual	5/9/2018	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	7/8/2016	Biennial	7/8/2018	54080
SPEAG	D1900V2	1900 MHz SAR Dipole	2/7/2018	Annual	2/7/2019	54148
SPEAG	D1900V2	1900 MHz SAR Dipole	7/11/2017	Annual	7/11/2018	54149
SPEAG	D2450V2	2450 MHz SAR Dipole	9/11/2017	Annual	9/11/2018	757
SPEAG	D2450V2	2450 MHz SAR Dipole	7/25/2016	Biennial	7/25/2018	981
SPEAG	D2600V2	2600 MHz SAR Dipole	7/10/2017	Annual	7/10/2018	1126
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/21/2016	Biennial	9/21/2018	1191
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/15/2017	Annual	8/15/2018	1237
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/15/2018	Annual	2/15/2019	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2018	Annual	2/9/2019	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/13/2017	Annual	7/13/2018	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/9/2017	Annual	8/9/2018	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/14/2017	Annual	6/14/2018	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/8/2017	Annual	3/8/2018	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2017	Annual	4/11/2018	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/13/2017	Annual	3/13/2018	1415
SPEAG	DAK-3.5	Dielectric Assessment Kit	9/12/2017	Annual	9/12/2018	1091
SPEAG	ES30V3	SAR Probe	3/14/2017	Annual	3/14/2018	3209
SPEAG	ES30V3	SAR Probe	2/13/2018	Annual	2/13/2019	3213
SPEAG	ES30V3	SAR Probe	9/22/2017	Annual	9/22/2018	3318
SPEAG	ES30V3	SAR Probe	3/14/2017	Annual	3/14/2018	3319
SPEAG	ES30V3	SAR Probe	8/14/2017	Annual	8/14/2018	3332
SPEAG	EX30V4	SAR Probe	1/16/2018	Annual	1/16/2019	3589
SPEAG	EX30V4	SAR Probe	2/14/2018	Annual	2/14/2019	3914
SPEAG	EX30V4	SAR Probe	8/16/2017	Annual	8/16/2018	7308
SPEAG	EX30V4	SAR Probe	4/18/2017	Annual	4/18/2018	7406
SPEAG	EX30V4	SAR Probe	7/17/2017	Annual	7/17/2018	7410

Note:

- Each equipment was used solely within its calibration period.
- CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMJ737P		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 103 of 107

16 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 104 of 107

17 CONCLUSION

17.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMJ737P	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset		Page 105 of 107

18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 106 of 107

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMJ737P	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1802160028-01-R2.A3L	Test Dates: 02/19/18 - 04/03/18	DUT Type: Portable Handset	Page 107 of 107

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 43.317$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-05-2018; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.23 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.255 W/kg

SAR(1 g) = 0.202 W/kg



0 dB = 0.218 W/kg = -6.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.436 \text{ S/m}$; $\epsilon_r = 40.21$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.37 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.583 W/kg

SAR(1 g) = 0.388 W/kg



0 dB = 0.447 W/kg = -3.50 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 43.317$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.05 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.247 W/kg

SAR(1 g) = 0.198 W/kg



0 dB = 0.213 W/kg = -6.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34945

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1
Medium: 1750 Head; Medium parameters used (interpolated):
 $f = 1732.4 \text{ MHz}$; $\sigma = 1.359 \text{ S/m}$; $\epsilon_r = 39.207$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 02-28-2018; Ambient Temp: 24.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(5.38, 5.38, 5.38); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.06 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.594 W/kg

SAR(1 g) = 0.399 W/kg



0 dB = 0.461 W/kg = -3.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.436 \text{ S/m}$; $\epsilon_r = 40.21$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.03 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.870 W/kg

SAR(1 g) = 0.578 W/kg



0 dB = 0.666 W/kg = -1.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, Cellular CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.91 \text{ S/m}$; $\epsilon_r = 43.516$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. CDMA, Rule Part 90S, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.02 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.307 W/kg

SAR(1 g) = 0.245 W/kg



0 dB = 0.267 W/kg = -5.73 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 43.318$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. CDMA, Rule Part 22H, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.78 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.378 W/kg

SAR(1 g) = 0.303 W/kg



0 dB = 0.328 W/kg = -4.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34945

Communication System: UID 0, PCS CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1908.75 \text{ MHz}$; $\sigma = 1.461 \text{ S/m}$; $\epsilon_r = 38.635$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-21-2018; Ambient Temp: 21.3°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: PCS EVDO Rev A, Left Head, Cheek, High.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.31 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.28 W/kg

SAR(1 g) = 0.839 W/kg



0 dB = 0.976 W/kg = -0.11 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head; Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.863 \text{ S/m}$; $\epsilon_r = 40.817$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-14-2018; Ambient Temp: 23.9°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3213; ConvF(6.75, 6.75, 6.75); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Left Head, Cheek, Mid.ch, QPSK,
10 MHz Bandwidth, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.28 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.277 W/kg

SAR(1 g) = 0.224 W/kg



0 dB = 0.245 W/kg = -6.11 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, LTE Band 26; Frequency: 846.5 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 846.5 \text{ MHz}$; $\sigma = 0.936 \text{ S/m}$; $\epsilon_r = 43.205$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 26 (Cell.), Left Head, Cheek, High.ch,
5 MHz Bandwidth, QPSK, 1 RB, 12 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.58 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.391 W/kg

SAR(1 g) = 0.312 W/kg



0 dB = 0.339 W/kg = -4.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34945

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.359 \text{ S/m}$; $\epsilon_r = 39.207$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-28-2018; Ambient Temp: 24.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(5.38, 5.38, 5.38); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.18 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.805 W/kg

SAR(1 g) = 0.537 W/kg



0 dB = 0.620 W/kg = -2.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, _LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.462 \text{ S/m}$; $\epsilon_r = 40.091$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.32 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.872 W/kg

SAR(1 g) = 0.558 W/kg



0 dB = 0.642 W/kg = -1.92 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.457 \text{ S/m}$; $\epsilon_r = 40.115$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 2 (PCS), Left Head, Cheek, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.81 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.954 W/kg

SAR(1 g) = 0.626 W/kg



0 dB = 0.722 W/kg = -1.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, LTE Band 41 (Class 2); Frequency: 2549.5 MHz; Duty Cycle: 1:2.31

Medium: 2600 Head; Medium parameters used:

$f = 2549.5 \text{ MHz}$; $\sigma = 1.983 \text{ S/m}$; $\epsilon_r = 37.671$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 03-05-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7410; ConvF(7.42, 7.42, 7.42); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 41, Power Class 2, Left Head, Cheek, Low-Mid.ch, QPSK,
20 MHz Bandwidth, 1 RB, 0 RB Offset**


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.68 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.788 W/kg

SAR(1 g) = 0.430 W/kg



0 dB = 0.654 W/kg = -1.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 37039

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.894 \text{ S/m}$; $\epsilon_r = 38.015$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-25-2018; Ambient Temp: 21.3°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Right Head, Cheek, Ch 11, 1 Mbps


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.10 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.60 W/kg

SAR(1 g) = 0.683 W/kg



0 dB = 0.873 W/kg = -0.59 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 37039

Communication System: UID 0, 802.11n 5.2-5.8 GHz Band; Frequency: 5755 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5755 \text{ MHz}$; $\sigma = 5.016 \text{ S/m}$; $\epsilon_r = 34.547$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-20-2018; Ambient Temp: 22.3°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN3589; ConvF(4.42, 4.42, 4.42); Calibrated: 1/16/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

Mode: IEEE 802.11n, U-NII-3, 40 MHz Bandwidth, Right Head, Tilt, Ch 151, 13.5 Mbps


Area Scan (13x11x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 10.48 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 3.12 W/kg

SAR(1 g) = 0.724 W/kg



0 dB = 1.81 W/kg = 2.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.996 \text{ S/m}$; $\epsilon_r = 53.32$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-26-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7406; ConvF(9.77, 9.77, 9.77); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 850, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.44 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.329 W/kg

SAR(1 g) = 0.257 W/kg



0 dB = 0.305 W/kg = -5.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.76

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.996 \text{ S/m}$; $\epsilon_r = 53.32$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7406; ConvF(9.77, 9.77, 9.77); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 850, Body SAR, Back Side, Mid.ch, 3 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.94 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.590 W/kg

SAR(1 g) = 0.463 W/kg



0 dB = 0.549 W/kg = -2.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.551 \text{ S/m}$; $\epsilon_r = 52.01$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 1900, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.27 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.286 W/kg

SAR(1 g) = 0.180 W/kg



0 dB = 0.213 W/kg = -6.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.551 \text{ S/m}$; $\epsilon_r = 52.01$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 1900, Body SAR, Back Side, Mid.ch, 3 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.79 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.823 W/kg

SAR(1 g) = 0.494 W/kg



0 dB = 0.589 W/kg = -2.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.999 \text{ S/m}$; $\epsilon_r = 52.848$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-04-2018; Ambient Temp: 22.6°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.87 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.316 W/kg

SAR(1 g) = 0.242 W/kg



0 dB = 0.292 W/kg = -5.35 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.999 \text{ S/m}$; $\epsilon_r = 52.848$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-04-2018; Ambient Temp: 22.6°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.28 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.372 W/kg

SAR(1 g) = 0.288 W/kg



0 dB = 0.344 W/kg = -4.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.455 \text{ S/m}$; $\epsilon_r = 52.798$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3209; ConvF(5.13, 5.13, 5.13); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.59 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.356 W/kg

SAR(1 g) = 0.248 W/kg



0 dB = 0.283 W/kg = -5.48 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.455 \text{ S/m}$; $\epsilon_r = 52.798$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3209; ConvF(5.13, 5.13, 5.13); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Body SAR, Front Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.00 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.650 W/kg

SAR(1 g) = 0.435 W/kg



0 dB = 0.495 W/kg = -3.05 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.551 \text{ S/m}$; $\epsilon_r = 52.01$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.65 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.690 W/kg

SAR(1 g) = 0.431 W/kg



0 dB = 0.511 W/kg = -2.92 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.551 \text{ S/m}$; $\epsilon_r = 52.01$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Front Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.52 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.630 W/kg



0 dB = 0.758 W/kg = -1.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.969 \text{ S/m}$; $\epsilon_r = 53.677$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-07-2018; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. CDMA BC10, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.33 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.423 W/kg

SAR(1 g) = 0.325 W/kg



0 dB = 0.405 W/kg = -3.93 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.969 \text{ S/m}$; $\epsilon_r = 53.677$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-07-2018; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. EVDO BC10, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.41 V/m; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 0.415 W/kg

SAR(1 g) = 0.324 W/kg



0 dB = 0.381 W/kg = -4.19 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 53.456$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-07-2018; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. CDMA, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.79 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.440 W/kg

SAR(1 g) = 0.335 W/kg.



0 dB = 0.390 W/kg = -4.09 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 53.456$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-07-2018; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. EVDO, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.77 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.455 W/kg

SAR(1 g) = 0.349 W/kg



0 dB = 0.419 W/kg = -3.78 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1908.75 \text{ MHz}$; $\sigma = 1.591 \text{ S/m}$; $\epsilon_r = 52.677$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-19-2018; Ambient Temp: 20.7°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: PCS CDMA, Body SAR, Back Side, High.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.45 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.635 W/kg



0 dB = 0.888 W/kg = -0.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34945

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1908.75$ MHz; $\sigma = 1.591$ S/m; $\epsilon_r = 52.677$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-19-2018; Ambient Temp: 20.7°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: PCS EVDO, Body SAR, Back Side, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.16 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.47 W/kg

SAR(1 g) = 0.852 W/kg



0 dB = 1.23 W/kg = 0.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 56.202$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-12-2018; Ambient Temp: 21.9°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7406; ConvF(9.9, 9.9, 9.9); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Body SAR, Back Side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.49 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.592 W/kg

SAR(1 g) = 0.464 W/kg



0 dB = 0.551 W/kg = -2.59 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34937

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 56.202$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-12-2018; Ambient Temp: 21.9°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7406; ConvF(9.9, 9.9, 9.9); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Body SAR, Back Side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.70 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.712 W/kg

SAR(1 g) = 0.561 W/kg



0 dB = 0.659 W/kg = -1.81 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 82142

Communication System: UID 0, _LTE Band 26; Frequency: 846.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 846.5 \text{ MHz}$; $\sigma = 0.985 \text{ S/m}$; $\epsilon_r = 53.42$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, High.ch,
5 MHz Bandwidth, QPSK, 1 RB, 12 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.74 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.523 W/kg

SAR(1 g) = 0.419 W/kg



0 dB = 0.458 W/kg = -3.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 82142

Communication System: UID 0, _LTE Band 26; Frequency: 846.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 846.5 \text{ MHz}$; $\sigma = 0.985 \text{ S/m}$; $\epsilon_r = 53.42$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, High.ch,
5 MHz Bandwidth, QPSK, 1 RB, 12 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.41 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.658 W/kg

SAR(1 g) = 0.526 W/kg



0 dB = 0.576 W/kg = -2.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.455 \text{ S/m}$; $\epsilon_r = 52.798$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3209; ConvF(5.13, 5.13, 5.13); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 4 (AWS), Body SAR, Back Side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.37 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.448 W/kg

SAR(1 g) = 0.314 W/kg



0 dB = 0.357 W/kg = -4.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.455 \text{ S/m}$; $\epsilon_r = 52.798$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3209; ConvF(5.13, 5.13, 5.13); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 4 (AWS), Body SAR, Back Side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.76 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.649 W/kg

SAR(1 g) = 0.413 W/kg



0 dB = 0.475 W/kg = -3.23 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.581 \text{ S/m}$; $\epsilon_r = 51.919$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Body SAR, Back Side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.40 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.831 W/kg

SAR(1 g) = 0.526 W/kg



0 dB = 0.621 W/kg = -2.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.581 \text{ S/m}$; $\epsilon_r = 51.919$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Body SAR, Front Side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.02 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.914 W/kg

SAR(1 g) = 0.560 W/kg



0 dB = 0.653 W/kg = -1.85 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.575 \text{ S/m}$; $\epsilon_r = 51.937$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 2 (PCS), Body SAR, Back Side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.40 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.745 W/kg

SAR(1 g) = 0.475 W/kg



0 dB = 0.555 W/kg = -2.56 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.551 \text{ S/m}$; $\epsilon_r = 52.01$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 2 (PCS), Body SAR, Back Side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.32 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.621 W/kg



0 dB = 0.755 W/kg = -1.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, LTE Band 41 (Class 2); Frequency: 2549.5 MHz; Duty Cycle: 1:2.31

Medium: 2600 Body; Medium parameters used:

$f = 2549.5 \text{ MHz}$; $\sigma = 2.122 \text{ S/m}$; $\epsilon_r = 50.567$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-04-2018; Ambient Temp: 22.7°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 41, Power Class 2, Body SAR, Back Side, Low-Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.60 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.824 W/kg

SAR(1 g) = 0.423 W/kg



0 dB = 0.665 W/kg = -1.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, LTE Band 41 (Class 2); Frequency: 2636.5 MHz; Duty Cycle: 1:2.31

Medium: 2600 Body; Medium parameters used (interpolated):

$f = 2636.5 \text{ MHz}$; $\sigma = 2.224 \text{ S/m}$; $\epsilon_r = 50.298$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-04-2018; Ambient Temp: 22.7°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 41, Power Class 2, Body SAR, Back Side, Mid-High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.54 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.93 W/kg

SAR(1 g) = 0.955 W/kg



0 dB = 1.53 W/kg = 1.85 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 37039

Communication System: UID 0, _IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.024 \text{ S/m}$; $\epsilon_r = 50.804$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-19-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 6, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.397 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.143 W/kg

SAR(1 g) = 0.077 W/kg



0 dB = 0.117 W/kg = -9.32 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 37039

Communication System: UID 0, _IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.024 \text{ S/m}$; $\epsilon_r = 50.804$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-19-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 6, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.811 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.252 W/kg

SAR(1 g) = 0.139 W/kg



0 dB = 0.207 W/kg = -6.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 37039

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 6.223 \text{ S/m}$; $\epsilon_r = 46.434$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-21-2018; Ambient Temp: 21.5°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: IEEE 802.11a, UNII-3, 20 MHz Bandwidth, Body SAR, Ch 149, 6 Mbps, Back Side


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 5.327 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.753 W/kg

SAR(1 g) = 0.175 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 37039

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 6.223 \text{ S/m}$; $\epsilon_r = 46.434$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-21-2018; Ambient Temp: 21.5°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Body SAR, Ch 149, 6 Mbps, Top Edge


Area Scan (9x17x1): Measurement grid: $dx=5\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 8.170 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.98 W/kg

SAR(1 g) = 0.458 W/kg



0 dB = 1.08 W/kg = 0.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1712.4 \text{ MHz}$; $\sigma = 1.459 \text{ S/m}$; $\epsilon_r = 53.359$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 02-28-2018; Ambient Temp: 21.5°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN3914; ConvF(7.91, 7.91, 7.91); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Phablet SAR, Back Side, Low.ch



Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 57.41 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 10.5 W/kg

SAR(10 g) = 2.3 W/kg



0 dB = 7.16 W/kg = 8.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.551 \text{ S/m}$; $\epsilon_r = 52.01$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Phablet SAR, Front Side, Mid.ch



Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 57.95 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 10.8 W/kg

SAR(10 g) = 2.28 W/kg



0 dB = 5.58 W/kg = 7.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34945

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: 1900 Body, Medium parameters used (interpolated):

$f = 1908.75 \text{ MHz}$; $\sigma = 1.591 \text{ S/m}$; $\epsilon_r = 52.677$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 3-19-2018; Ambient Temp: 20.7°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: PCS EVDO, Phablet SAR, Back side, High.ch


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 63.06 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 16.4 W/kg

SAR(10 g) = 2.91 W/kg



0 dB = 11.0 W/kg = 10.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.48 \text{ S/m}$; $\epsilon_r = 53.267$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 02-28-2018; Ambient Temp: 21.5°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN3914; ConvF(7.91, 7.91, 7.91); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 4 (AWS), Phablet SAR, Back Side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 51.53 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 9.06 W/kg

SAR(10 g) = 2.02 W/kg



0 dB = 6.51 W/kg = 8.14 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34978

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.573 \text{ S/m}$; $\epsilon_r = 52.221$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.2 cm

Test Date: 03-01-2018; Ambient Temp: 22.5°C; Tissue Temp: 20.6°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Phablet SAR, Back Side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 59.65 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 10.9 W/kg

SAR(10 g) = 2.60 W/kg



0 dB = 5.97 W/kg = 7.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 34960

Communication System: UID 0, _LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.575 \text{ S/m}$; $\epsilon_r = 51.937$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 2 (PCS), Phablet SAR, Front Side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 58.31 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 10.8 W/kg

SAR(10 g) = 2.19 W/kg



0 dB = 5.76 W/kg = 7.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737P; Type: Portable Handset; Serial: 37039

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.559 \text{ S/m}$; $\epsilon_r = 47.048$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 03-26-2018; Ambient Temp: 21.6°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.84, 4.84, 4.84); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: IEEE 802.11a, UNII-2A, 20 MHz Bandwidth, Phablet SAR, Ch 60, 6 Mbps, Front Side


Area Scan (13x19x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 27.45 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 16.4 W/kg

SAR(10 g) = 1.00 W/kg



0 dB = 8.97 W/kg = 9.53 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.877 \text{ S/m}$; $\epsilon_r = 40.704$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-14-2018; Ambient Temp: 23.9°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3213; ConvF(6.75, 6.75, 6.75); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.29 W/kg

SAR(1 g) = 1.55 W/kg

Deviation(1 g) = -6.40%



0 dB = 1.81 W/kg = 2.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.925 \text{ S/m}$; $\epsilon_r = 43.335$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-05-2018; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.93 W/kg

SAR(1 g) = 1.96 W/kg

Deviation(1 g) = 2.94%



0 dB = 2.29 W/kg = 3.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.377 \text{ S/m}$; $\epsilon_r = 39.127$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-28-2018; Ambient Temp: 24.1°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(5.38, 5.38, 5.38); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 6.11 W/kg

SAR(1 g) = 3.43 W/kg

Deviation(1 g) = -5.77%



0 dB = 4.28 W/kg = 6.31 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.457 \text{ S/m}$; $\epsilon_r = 40.115$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-05-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 6.90 W/kg

SAR(1 g) = 3.77 W/kg

Deviation(1 g) = -4.07%



0 dB = 4.81 W/kg = 6.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.451 \text{ S/m}$; $\epsilon_r = 38.666$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-21-2018; Ambient Temp: 21.3°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.10 W/kg

SAR(1 g) = 3.93 W/kg

Deviation(1 g) = -2.00%



0 dB = 4.97 W/kg = 6.96 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.88 \text{ S/m}$; $\epsilon_r = 38.071$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-25-2018; Ambient Temp: 21.3°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.7 W/kg

SAR(1 g) = 5.64 W/kg

Deviation(1 g) = 7.02%



0 dB = 7.40 W/kg = 8.69 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Head; Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.037 \text{ S/m}$; $\epsilon_r = 37.459$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-05-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7410; ConvF(7.42, 7.42, 7.42); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 13.6 W/kg

SAR(1 g) = 5.87 W/kg

Deviation(1 g) = 4.08%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.511 \text{ S/m}$; $\epsilon_r = 35.228$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-20-2018; Ambient Temp: 22.3°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN3589; ConvF(4.69, 4.69, 4.69); Calibrated: 1/16/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.2 W/kg

SAR(1 g) = 3.68 W/kg

Deviation(1 g) = -6.72%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.845 \text{ S/m}$; $\epsilon_r = 34.777$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-20-2018; Ambient Temp: 22.3°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN3589; ConvF(4.17, 4.17, 4.17); Calibrated: 1/16/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.6 W/kg

SAR(1 g) = 3.90 W/kg

Deviation(1 g) = -6.70%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 5.009 \text{ S/m}$; $\epsilon_r = 34.552$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-20-2018; Ambient Temp: 22.3°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN3589; ConvF(4.42, 4.42, 4.42); Calibrated: 1/16/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.1 W/kg

SAR(1 g) = 3.69 W/kg

Deviation(1 g) = -6.70%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1161

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.978 \text{ S/m}$; $\epsilon_r = 56.107$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-12-2018; Ambient Temp: 21.9°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7406; ConvF(9.9, 9.9, 9.9); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.69 W/kg

SAR(1 g) = 1.80 W/kg

Deviation(1 g) = 6.76%



0 dB = 2.40 W/kg = 3.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 53.337$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-26-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7406; ConvF(9.77, 9.77, 9.77); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.04 W/kg

SAR(1 g) = 1.98 W/kg

Deviation(1 g) = 3.45%



0 dB = 2.67 W/kg = 4.27 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.998 \text{ S/m}$; $\epsilon_r = 52.865$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-04-2018; Ambient Temp: 22.6°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.00 W/kg

SAR(1 g) = 2.01 W/kg

Deviation(1 g) = 6.80%



0 dB = 2.67 W/kg = 4.27 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.974 \text{ S/m}$; $\epsilon_r = 53.53$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.04 W/kg

SAR(1 g) = 2.07 W/kg

Deviation(1 g) = 6.59%



0 dB = 2.41 W/kg = 3.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1150

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.475 \text{ S/m}$; $\epsilon_r = 52.733$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3209; ConvF(5.13, 5.13, 5.13); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.32 W/kg

SAR(1 g) = 3.64 W/kg

Deviation(1 g) = -0.27%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.499 \text{ S/m}$; $\epsilon_r = 53.187$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-28-2018; Ambient Temp: 21.5°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN3914; ConvF(7.91, 7.91, 7.91); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.05 W/kg

SAR(10 g) = 2.07 W/kg

Deviation(10 g) = 4.55%



0 dB = 5.84 W/kg = 7.66 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.575 \text{ S/m}$; $\epsilon_r = 51.937$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-26-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.58 W/kg

SAR(1 g) = 4.19 W/kg; SAR(10 g) = 2.18 W/kg

Deviation(1 g) = 4.49%; Deviation(10 g) = 2.35%



0 dB = 5.26 W/kg = 7.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.568 \text{ S/m}$; $\epsilon_r = 52.236$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-01-2018; Ambient Temp: 22.5°C; Tissue Temp: 20.6°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 9/22/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.38 W/kg

SAR(10 g) = 2.12 W/kg

Deviation(10 g) = 2.42%



0 dB = 5.19 W/kg = 7.15 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.581 \text{ S/m}$; $\epsilon_r = 52.699$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-19-2018; Ambient Temp: 20.7°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.80 W/kg

SAR(1 g) = 4.18 W/kg; SAR(10 g) = 2.14 W/kg

Deviation(1 g) = 6.91%; Deviation(10 g) = 3.38%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.579 \text{ S/m}$; $\epsilon_r = 52.195$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-21-2018; Ambient Temp: 21.5°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.80 W/kg

SAR(1 g) = 4.11 W/kg

Deviation(1 g) = 3.79%



0 dB = 6.19 W/kg = 7.92 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.039 \text{ S/m}$; $\epsilon_r = 50.762$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-19-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.4 W/kg

SAR(1 g) = 5.24 W/kg

Deviation(1 g) = 3.15%



0 dB = 9.01 W/kg = 9.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.004 \text{ S/m}$; $\epsilon_r = 50.846$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-04-2018; Ambient Temp: 22.7°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.7 W/kg

SAR(1 g) = 5.11 W/kg

Deviation(1 g) = 0.00%



0 dB = 8.51 W/kg = 9.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body; Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.181 \text{ S/m}$; $\epsilon_r = 50.405$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-04-2018; Ambient Temp: 22.7°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)



Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.8 W/kg

SAR(1 g) = 5.37 W/kg

Deviation(1 g) = -1.10%



0 dB = 9.18 W/kg = 9.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.537 \text{ S/m}$; $\epsilon_r = 47.314$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-21-2018; Ambient Temp: 21.5°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(4.84, 4.84, 4.84); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.6 W/kg

SAR(1 g) = 3.59 W/kg

Deviation(1 g) = -6.63%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.996 \text{ S/m}$; $\epsilon_r = 46.725$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-21-2018; Ambient Temp: 21.5°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(4.23, 4.23, 4.23); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.6 W/kg

SAR(1 g) = 3.84 W/kg

Deviation(1 g) = -2.17%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.228 \text{ S/m}$; $\epsilon_r = 46.431$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-21-2018; Ambient Temp: 21.5°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 19.3 W/kg

SAR(1 g) = 3.85 W/kg

Deviation(1 g) = -0.13%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.495 \text{ S/m}$; $\epsilon_r = 47.165$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-26-2018; Ambient Temp: 21.6°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.84, 4.84, 4.84); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.8 W/kg

SAR(10 g) = 0.995 W/kg

Deviation(10 g) = -7.44%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.953 \text{ S/m}$; $\epsilon_r = 46.547$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-26-2018; Ambient Temp: 21.6°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.23, 4.23, 4.23); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.5 W/kg

SAR(10 g) = 1.02 W/kg

Deviation(10 g) = -7.69%



APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D750V3-1003_Jan18**

CALIBRATION CERTIFICATE

Object **D750V3 - SN:1003**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **January 15, 2018**

BN
01-25-2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by: **Leif Klysner** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Technical Manager

Signature

Leif Klysner

Katja Pokovic

Issued: January 15, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5.0 mm	
Frequency	750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.9 $\pm$ 6 %	0.90 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.10 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.28 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.37 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.42 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	55.0 $\pm$ 6 %	0.96 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.15 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.58 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.43 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.71 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	53.8 Ω - 2.1 j Ω
Return Loss	- 27.6 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	49.2 Ω - 6.2 j Ω
Return Loss	- 24.0 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.043 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	January 21, 2009

Appendix (Additional assessments outside the scope of SCS 0108)

Measurement Conditions

DASY system configuration, as far as not given on page 1 and 3.

Phantom	SAM Head Phantom	For usage with cSAR3DV2-R/L
---------	------------------	-----------------------------

SAR result with SAM Head (Top)

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.98 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	7.94 W/kg ± 17.5 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.33 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.32 W/kg ± 16.9 % (k=2)

SAR result with SAM Head (Mouth)

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.05 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.22 W/kg ± 17.5 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.52 W/kg ± 16.9 % (k=2)

SAR result with SAM Head (Neck)

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.01 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.06 W/kg ± 17.5 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.52 W/kg ± 16.9 % (k=2)

SAR result with SAM Head (Ear)

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.67 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.70 W/kg ± 17.5 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.15 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	4.60 W/kg ± 16.9 % (k=2)

DASY5 Validation Report for Head TSL

Date: 12.01.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1003

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 40.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.22, 10.22, 10.22); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.11 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.15 W/kg

SAR(1 g) = 2.1 W/kg; SAR(10 g) = 1.37 W/kg

Maximum value of SAR (measured) = 2.80 W/kg




0 dB = 2.80 W/kg = 4.47 dBW/kg

Impedance Measurement Plot for Head TSL

12 Jan 2018 13:14:07
CH1 S11 1 U FS 1: 53.754 Ω -2.0996 Ω 101.07 pF 750.000 000 MHz


*
De1
CA



Avg
16
H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-27.643 dB 750.000 000 MHz

CA
Avg
16
H1d



DASY5 Validation Report for Body TSL

Date: 12.01.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1003

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.96 \text{ S/m}$; $\epsilon_r = 55$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.19, 10.19, 10.19); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x8x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.31 V/m; Power Drift = -0.01 dB


Peak SAR (extrapolated) = 3.17 W/kg

SAR(1 g) = 2.15 W/kg; SAR(10 g) = 1.43 W/kg

Maximum value of SAR (measured) = 2.83 W/kg



Impedance Measurement Plot for Body TSL



DASY5 Validation Report for SAM Head

Date: 15.01.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1003

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.9 \text{ S/m}$; $\epsilon_r = 44.2$; $\rho = 1000 \text{ kg/m}^3$

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.22, 10.22, 10.22); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: SAM Head
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

SAM Head/Top/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 56.79 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.89 W/kg

SAR(1 g) = 1.98 W/kg; SAR(10 g) = 1.33 W/kg

Maximum value of SAR (measured) = 2.58 W/kg

SAM Head/Mouth/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 56.85 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 2.94 W/kg

SAR(1 g) = 2.05 W/kg; SAR(10 g) = 1.38 W/kg

Maximum value of SAR (measured) = 2.62 W/kg

SAM Head/Neck/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 56.29 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.78 W/kg

SAR(1 g) = 2.01 W/kg; SAR(10 g) = 1.38 W/kg

Maximum value of SAR (measured) = 2.56 W/kg


SAM Head/Ear/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.01 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.31 W/kg

SAR(1 g) = 1.67 W/kg; SAR(10 g) = 1.15 W/kg

Maximum value of SAR (measured) = 2.11 W/kg



0 dB = 2.58 W/kg = 4.12 dBW/kg



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D835V2-4d133_Jul17**

CALIBRATION CERTIFICATE

Object **D835V2 - SN:4d133**

*PN ✓
8/3/2017*

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **July 11, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	31-May-17 (No. EX3-7349_May17)	May-18
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Johannes Kurikka** Function: **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** Technical Manager

[Signatures]

Issued: July 12, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.8 $\pm$ 6 %	0.91 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.41 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.52 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.54 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.10 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.8 $\pm$ 6 %	1.01 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.43 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.41 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.58 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.16 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.0 Ω - 2.9 j Ω
Return Loss	- 30.4 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.7 Ω - 6.8 j Ω
Return Loss	- 22.2 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.196 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 22, 2011

DASY5 Validation Report for Head TSL

Date: 11.07.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d133

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.91 \text{ S/m}$; $\epsilon_r = 40.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.07, 10.07, 10.07); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 62.84 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.74 W/kg

SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.54 W/kg

Maximum value of SAR (measured) = 3.28 W/kg



0 dB = 3.28 W/kg = 5.16 dBW/kg

Impedance Measurement Plot for Head TSL

11 Jul 2017 13:58:45
[CH1] S11 1 U FS 1: 50.998 Ω -2.8750 Ω 66.297 pF 835.000 000 MHz


*

De1

CA

Avg
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1:-30.411 dB 835.000 000 MHz

CA

Avg
16

H1d



DASY5 Validation Report for Body TSL

Date: 11.07.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d133

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 1.01$ S/m; $\epsilon_r = 54.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.2, 10.2, 10.2); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.25 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 3.67 W/kg

SAR(1 g) = 2.43 W/kg; SAR(10 g) = 1.58 W/kg

Maximum value of SAR (measured) = 3.21 W/kg



Impedance Measurement Plot for Body TSL

11 Jul 2017 13:57:15
 [CH1] S11 1 U FS 1: 46.736 Ω -6.7871 Ω 28.083 pF 835.000 000 MHz


*

De1

CA

Avg
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1:-22.199 dB 835.000 000 MHz

CA

Avg
16

H1d





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D1765V2-1008_May17**

CALIBRATION CERTIFICATE

Object **D1765V2 - SN:1008**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **May 09, 2017**

BNV
05-23-2017

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	31-Dec-16 (No. EX3-7349_Dec16)	Dec-17
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Claudio Leubler** Function: **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** Technical Manager

Issued: May 11, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.1	1.37 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.0 $\pm$ 6 %	1.36 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.07 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	36.4 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	4.79 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	19.2 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.4	1.50 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.7 $\pm$ 6 %	1.47 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.24 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	37.5 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	4.95 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.0 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	47.6 Ω - 6.6 j Ω
Return Loss	- 22.8 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	43.9 Ω - 6.7 j Ω
Return Loss	- 20.3 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.212 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	October 06, 2005

DASY5 Validation Report for Head TSL

Date: 09.05.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1765 MHz; Type: D1765V2; Serial: D1765V2 - SN:1008

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.36$ S/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.46, 8.46, 8.46); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.10.0(1444); SEMCAD X 14.6.10(7416)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 105.0 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 16.5 W/kg


SAR(1 g) = 9.07 W/kg; SAR(10 g) = 4.79 W/kg

Maximum value of SAR (measured) = 13.9 W/kg



0 dB = 13.9 W/kg = 11.43 dBW/kg

Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 09.05.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1765 MHz; Type: D1765V2; Serial: D1765V2 - SN:1008

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.47$ S/m; $\epsilon_r = 53.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.25, 8.25, 8.25); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1444); SEMCAD X 14.6.10(7416)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 101.5 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 16.0 W/kg

SAR(1 g) = 9.24 W/kg; SAR(10 g) = 4.95 W/kg

Maximum value of SAR (measured) = 13.6 W/kg



0 dB = 13.6 W/kg = 11.34 dBW/kg

Impedance Measurement Plot for Body TSL

