

Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR24-SRF0022 Page (43) of (73)	
--	---	---

Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT ($D \geq 98\%$) cannot be achieved and the duty cycle is constant (duty cycle variations are less than $\pm 2\%$), then the following procedure shall be used:


1. The EUT shall be configured to operate at the maximum achievable duty cycle.
2. Measure the duty cycle D of the transmitter output signal as described in 11.6.
3. $RBW = 1 \text{ MHz}$ (unless otherwise specified).
4. $VBW \geq [3 \times RBW]$.
5. Detector = RMS (power averaging), if $[\text{span} / (\# \text{ of points in sweep})] \leq (RBW / 2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
6. Averaging type = power (i.e., rms):
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
7. Sweep time = auto.
8. Perform a trace average of at least 100 traces.
9. A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is $[10 \log (1 / D)]$, where D is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $[20 \log (1 / D)]$, where D is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous ($D \geq 98\%$) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Notes:

1. $f < 30 \text{ MHz}$, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
 $f \geq 30 \text{ MHz}$, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$
Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
2. $\text{Factors(dB)} = \text{Antenna factor(dB/m)} + \text{Cable loss(dB)} + \text{or Amp. gain(dB)} + \text{or } F_d(\text{dB})$
3. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
4. Average test would be performed if the peak result were greater than the average limit.
5. ¹⁾ means restricted band.
6. Below 30 MHz frequency range, In order to search for the worst result, all orientations about parallel, perpendicular, and ground-parallel were investigated then reported. when the emission level was higher than 20 dB of the limit, then the following statement shall be made: "No spurious emissions were detected within 20 dB of the limit."
7. Above 1 GHz the worst results between two antenna polarizations (H and V) were documented in the test report.
8. For above 1 GHz pre-scan to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 kHz for peak measurements.


Test results (Below 30 MHz) – Worst case: 802.11a / UNII 2A_5 320 MHz

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data								
No spurious emissions were detected within 20 dB of the limit.								



Test results (Below 1 000 MHz) – Worst case: 802.11a / UNII 2A_5 320 MHz

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data								
118.76 ¹⁾	H	24.00	17.80	-31.47	-	10.33	43.50	33.17
260.01 ¹⁾	V	24.20	19.90	-31.03	-	13.07	46.00	32.93
335.79	H	24.50	19.79	-30.80	-	13.49	46.00	32.51
580.84	V	23.80	24.50	-30.45	-	17.85	46.00	28.15
706.09	V	24.30	24.80	-30.27	-	18.83	46.00	27.17
834.74	V	24.50	25.84	-29.52	-	20.82	46.00	25.18



Test results (Above 1 000 MHz)

UNII 1

802.11a_Lowest Channel (5 180 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 148.33 ¹⁾	H	59.40	32.90	-27.13	-	65.17	74.00	8.83
10 362.08	H	54.00	38.48	-42.28	-	50.20	68.20	18.00
15 463.10 ¹⁾	V	52.70	38.27	-40.34	-	50.63	74.00	23.37
Average Data								
5 148.33 ¹⁾	H	43.31	32.90	-27.13	0.39	49.47	54.00	4.53

802.11a_Middle Channel (5 200 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
10 404.63	H	53.00	38.50	-41.99	-	49.51	68.20	18.69
15 599.95 ¹⁾	H	52.30	38.00	-40.15	-	50.15	74.00	23.85
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11a_Highest Channel (5 240 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
10 481.68	V	53.50	38.50	-42.02	-	49.98	68.20	18.22
15 721.47 ¹⁾	H	51.10	38.10	-39.58	-	49.62	74.00	24.38
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

In order to simplify the report, attached plots were only the lowest margin condition

802.11a_Lowest Channel (5 180 MHz)



802.11n_HT20_Lowest Channel (5 180 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 149.38 ¹⁾	H	63.20	32.90	-27.13	-	68.97	74.00	5.03
10 403.10	H	53.30	38.50	-41.99	-	49.81	68.20	18.39
15 599.95 ¹⁾	V	52.40	38.00	-40.15	-	50.25	74.00	23.75
Average Data								
5 149.38 ¹⁾	H	43.30	32.90	-27.13	0.42	49.49	54.00	4.51

802.11n_HT20_Middle Channel (5 200 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
10 405.78	V	52.80	38.50	-41.99	-	49.31	68.20	18.89
15 599.18 ¹⁾	H	51.60	38.00	-40.15	-	49.45	74.00	24.55
Average Data								
No spurious emissions were detected within 20 dB of the limit								

802.11n_HT20_Highest Channel (5 240 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
10 474.40	V	53.20	38.50	-41.99	-	49.71	68.20	18.49
15 305.93	H	52.70	38.78	-40.06	-	51.42	68.20	16.78
Average Data								
No spurious emissions were detected within 20 dB of the limit								

In order to simplify the report, attached plots were only the lowest margin condition

802.11n_HT20_Lowest Channel (5 180 MHz)




Plot of Harmonics and Spurious Emissions


In order to simplify the report, attached plots were only the lowest margin condition

802.11n HT20_UNII 1_Lowest Channel (5 180 MHz)


Horizontal/Vertical for 1 GHz ~ 6.5 GHz



Horizontal/Vertical for 6.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 40 GHz



UNII 2A

802.11a_Lowest Channel (5 260 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
10 520.02	H	52.90	38.50	-42.13	-	49.27	68.20	18.93
15 791.23 ¹⁾	H	51.90	38.10	-39.21	-	50.79	74.00	23.21
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11a_Middle Channel (5 280 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
10 562.57	H	53.20	38.63	-42.23	-	49.60	68.20	18.60
15 840.30 ¹⁾	V	51.90	38.28	-39.32	-	50.86	74.00	23.14
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11a_Highest Channel (5 320 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 350.33 ¹⁾	H	60.30	32.60	-27.02	-	65.88	74.00	8.12
10 643.45 ¹⁾	H	52.90	38.79	-42.49	-	49.20	74.00	24.80
15 967.95 ¹⁾	H	51.00	38.34	-39.10	-	50.24	74.00	23.76
Average Data								
5 350.33 ¹⁾	H	43.02	32.60	-27.02	0.39	48.99	54.00	5.01

In order to simplify the report, attached plots were only the lowest margin condition

802.11a_Highest Channel (5 320 MHz)



802.11n_HT20_Lowest Channel (5 260 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
10 516.18	H	53.80	38.50	-42.12	-	50.18	68.20	18.02
15 787.40 ¹⁾	V	51.90	38.10	-39.22	-	50.78	74.00	23.22
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11n_HT20_Middle Channel (5 280 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
10 559.12	H	53.10	38.62	-42.22	-	49.50	68.20	18.70
15 840.30 ¹⁾	H	51.90	38.28	-39.32	-	50.86	74.00	23.14
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11n_HT20_Highest Channel (5 320 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 350.08 ¹⁾	H	59.00	32.60	-27.02	-	64.58	74.00	9.42
10 641.15 ¹⁾	H	52.10	38.78	-42.48	-	48.40	74.00	25.60
15 957.98 ¹⁾	V	50.50	38.32	-39.18	-	49.64	74.00	24.36
Average Data								
5 350.08 ¹⁾	H	43.75	32.60	-27.02	0.42	49.75	54.00	4.25

In order to simplify the report, attached plots were only the lowest margin condition

802.11n_HT20_Highest Channel (5 320 MHz)




Plot of Harmonics and Spurious Emissions


In order to simplify the report, attached plots were only the lowest margin condition

802.11n_HT20_UNII 2A_Highest Channel (5 320 MHz)


Horizontal/Vertical for 1 GHz ~ 6.5 GHz



Horizontal/Vertical for 6.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 40 GHz



UNII 2C

802.11a_Lowest Channel (5 500 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 459.88 ¹⁾	H	52.10	32.60	-26.97	-	57.73	74.00	16.27
10 998.80 ¹⁾	V	52.20	38.40	-41.93	-	48.67	74.00	25.33
16 496.95	H	48.90	38.40	-38.59	-	48.71	68.20	19.49
Average Data								
5 459.88 ¹⁾	H	43.18	32.60	-26.97	0.39	49.20	54.00	4.80

802.11a_Middle Channel (5 600 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
11 200.05 ¹⁾	V	51.40	38.40	-41.63	-	48.17	74.00	25.83
16 809.75	V	49.50	38.18	-37.67	-	50.01	68.20	18.19
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11a_Highest Channel (5 700 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 725.80	H	50.90	33.35	-26.57	-	57.68	68.20	10.52
11 401.30 ¹⁾	V	52.70	38.70	-41.82	-	49.58	74.00	24.42
17 100.70	H	49.40	38.00	-37.68	-	49.72	68.20	18.48
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

In order to simplify the report, attached plots were only the lowest margin condition

802.11a_Lowest Channel (5 500 MHz)



Highest Channel (5 700 MHz)



802.11n_HT20_Lowest Channel (5 500 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 459.86 ¹⁾	H	51.00	32.60	-26.97	-	56.63	74.00	17.37
10 999.95 ¹⁾	V	52.30	38.40	-41.94	-	48.76	74.00	25.24
16 494.65	V	50.10	38.40	-38.58	-	49.92	68.20	18.28
Average Data								
5 459.86 ¹⁾	H	39.75	32.60	-26.97	0.42	45.80	54.00	8.20

802.11n_HT20_Middle Channel (5 600 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
11 200.82 ¹⁾	V	50.90	38.40	-41.63	-	47.67	74.00	26.33
16 810.13	H	50.30	38.18	-37.67	-	50.81	68.20	17.39
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11n_HT20_Highest Channel (5 700 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 729.27	H	52.90	33.38	-26.57	-	59.71	68.20	8.49
11 399.38 ¹⁾	V	53.20	38.80	-41.83	-	50.17	74.00	23.83
17 098.40	H	50.10	38.10	-37.69	-	50.51	68.20	17.69
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

In order to simplify the report, attached plots were only the lowest margin condition

802.11n_HT20_Lowest Channel (5 500 MHz)



Highest Channel (5 700 MHz)




Plot of Harmonics and Spurious Emissions


In order to simplify the report, attached plots were only the lowest margin condition

802.11a_UNII 2C_Highest Channel (5 500 MHz)


Horizontal/Vertical for 1 GHz ~ 6.5 GHz



Horizontal/Vertical for 6.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 40 GHz



Straddle Channel

802.11a (5 720 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
11 399.38 ¹⁾	H	52.30	38.80	-41.83	-	49.27	74.00	24.73
17 160.50	H	48.70	37.88	-37.16	-	49.42	68.20	18.78
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11n HT20 (5 720 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
11 400.15 ¹⁾	H	52.00	38.70	-41.83	-	48.87	74.00	25.13
17 159.35	V	49.20	37.88	-37.17	-	49.91	68.20	18.29
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

Plot of Harmonics and Spurious Emissions


In order to simplify the report, attached plots were only the lowest margin condition

802.11n HT20_Straddle Channel (5 720 MHz)


Horizontal/Vertical for 1 GHz ~ 6.5 GHz



Horizontal/Vertical for 6.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 40 GHz



UNII 3

802.11a_Lowest Channel (5 745 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 725.00	H	60.80	33.35	-26.58	-	67.57	122.20	54.63
11 490.62 ¹⁾	V	50.90	38.70	-41.45	-	48.15	74.00	25.85
17 235.63	H	49.00	38.24	-36.82	-	50.42	68.20	17.78
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


802.11a_Middle Channel (5 785 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
11 570.73 ¹⁾	H	53.00	38.46	-41.69	-	49.77	74.00	24.23
17 354.08	H	49.40	38.62	-37.16	-	50.86	68.20	17.34
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


802.11a_Highest Channel (5 825 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 850.85	H	51.60	33.80	-26.48	-	58.92	120.30	61.38
11 649.70 ¹⁾	V	50.20	38.30	-41.60	-	46.90	74.00	27.10
17 494.00	H	46.80	39.36	-36.66	-	49.50	68.20	18.70
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11a_Lowest Channel (5 745 MHz)



802.11a_Highest Channel (5 825 MHz)



802.11n_HT20_Lowest Channel (5 745 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 723.83	H	60.90	33.34	-26.58	-	67.66	119.50	51.84
11 489.85 ¹⁾	V	50.60	38.70	-41.46	-	47.84	74.00	26.16
17 235.25	H	47.90	38.24	-36.82	-	49.32	68.20	18.88
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


802.11n_HT20_Middle Channel (5 785 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
11 571.12 ¹⁾	V	51.30	38.46	-41.69	-	48.07	74.00	25.93
17 355.23	H	49.40	38.63	-37.15	-	50.88	68.20	17.32
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


802.11n_HT20_Highest Channel (5 825 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
5 851.92	H	53.00	33.81	-26.48	-	60.33	117.80	57.47
11 648.55 ¹⁾	H	50.30	38.30	-41.60	-	47.00	74.00	27.00
17 494.00	V	46.70	39.36	-36.66	-	49.40	68.20	18.80
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

802.11n_HT20_Lowest Channel (5 745 MHz)



802.11n_HT20_Highest Channel (5 825 MHz)




Plot of Harmonics and Spurious Emissions


In order to simplify the report, attached plots were only the lowest margin condition

802.11n HT20_UNII 3_Middle Channel (5 785 MHz)


Horizontal/Vertical for 1 GHz ~ 6.5 GHz



Horizontal/Vertical for 6.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 40 GHz



Spurious Emission for Simultaneous Tx Condition


Case	WLAN 5 GHz	Bluetooth
Mode	802.11n HT20	BLE
Channel	36	40
Frequency	5 180 MHz	2 480 MHz
Data Rate	MCS0	2M Bits/s, 37 Packet

Notes.


The lowest margin condition among the channels and modes were selected for test.

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
4 960.30 ¹⁾	V	51.20	32.64	-43.19	-	40.65	74.00	33.35
7 439.93 ¹⁾	V	50.10	36.32	-40.75	-	45.67	74.00	28.33
10 359.78	V	52.70	38.48	-42.30	-	48.88	68.20	19.32
15 540.15 ¹⁾	H	51.40	38.12	-40.20	-	49.32	74.00	24.68
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


Horizontal/Vertical for 1 GHz ~ 3.5 GHz




Horizontal/Vertical for 3.5 GHz ~ 5 GHz




Horizontal/Vertical for 5 GHz ~ 6.5 GHz



Horizontal/Vertical for 6.5 GHz ~ 18 GHz




Horizontal/Vertical for 18 GHz ~ 40 GHz



7.8. AC Conducted emission

Test setup



Limit

According to 15.207(a),

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.


Frequency of Emission (MHz)	Conducted limit (dB μ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

Test results

Worst case: 802.11a / UNII 2A_5 320 MHz



Final Result

--- N_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.16368	26.8	4.5	10.4	37.2	14.9	65.3	55.3	28.1	40.4
2	0.24453	20.2	1.4	10.0	30.2	11.4	61.9	51.9	31.7	40.5
3	1.01721	16.1	5.7	10.0	26.1	15.7	56.0	46.0	29.9	30.3
4	4.4999	22.8	10.4	10.0	32.8	20.4	56.0	46.0	23.2	25.6
5	5.66093	23.4	11.0	10.1	33.5	21.1	60.0	50.0	26.5	28.9
6	12.62601	24.7	12.5	10.8	35.5	23.3	60.0	50.0	24.5	26.7

--- L1_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.16085	26.0	4.3	10.2	36.2	14.5	65.4	55.4	29.2	40.9
2	0.27458	19.3	1.5	10.0	29.3	11.5	61.0	51.0	31.7	39.5
3	1.03199	19.9	7.1	10.0	29.9	17.1	56.0	46.0	26.1	28.9
4	4.78893	26.3	13.2	10.0	36.3	23.2	56.0	46.0	19.7	22.8
5	12.91681	28.0	15.6	10.8	38.8	26.4	60.0	50.0	21.2	23.6
6	29.31289	24.9	1.7	11.6	36.5	13.3	60.0	50.0	23.5	36.7

8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV30	100807	24.07.03
Signal Generator	R&S	SMB100A	176206	25.01.18
DC Power Supply	AGILENT	E3632A	MY40016393	24.07.04
Attenuator	API Inmet	40AH2W-10	10	24.07.04
Spectrum Analyzer	R&S	FSV40	100988	24.07.03
Power Divider	Aeroflex/ Weinschel, Inc	1580-1	PE430	24.07.04
Power Divider	AGILENT	11636B	54456	24.10.13
Step Attenuator	KEYSIGHT	8495D	MY42144300	25.01.19
Step Attenuator	AGILENT	8494B	MY42140941	25.01.19
Vector Signal Generator	R&S	SMBV100A	257566	24.07.04
DC Power Supply	AGILENT	E3632A	KR94907664	24.04.27
PSA Spectrum Analyzer	Agilent	E4440A	MY44303500	24.07.04
EMI TEST RECEIVER	R&S	ESC13	101408	24.08.18
TWO-LINE V - NETWORK	R&S	ENV216	101358	24.09.27
Broadband PreAmplifier	SCHWARZBECK	BBV9718D	53	25.01.19
Low Noise Amplifier	TESTEK	TK-PA18H	220123-L	24.10.12
Low Noise Amplifier	TESTEK	TK-PA1840H	220234-L	24.10.17
Amplifier	SONOMA INSTRUMENT	310N	421910	24.10.12
Bilog Antenna	Teseq GmbH	CBL 6112D	61521	24.11.17
Loop Antenna	R&S	HFH2-Z2	100355	24.08.10
Horn Antenna	SCHWARZBECK	BBHA9120D	2764	24.10.18
Horn Antenna	SCHWARZBECK	BBHA9170	1266	24.10.16
High Pass Filter	Wainwright Instruments GmbH	WHKX8-5655-6500-18000-40SS	SN7	24.10.16
High Pass Filter	Qotana TECHNOLOGIES	DBHF058004000A	23041800061	24.07.10

End of test report