

FCC DTS REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Address:

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Date of Issue:

January 03, 2019

Location:

HCT CO., LTD.,

74, Seoicheon-ro 578beon-gil, Majang-myeon,

Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-RF-1812-FC048-R1

FCC ID:

A3LSMM205F

APPLICANT:

SAMSUNG Electronics Co., Ltd.

Model:

SM-M205F/DS

Additional Model:

SM-M205F, SM-M205G/DS

EUT Type:

Mobile Phone

Average Output Power:

802.11b : 16.112 dBm

802.11g : 15.491 dBm

802.11n(HT20) : 14.992 dBm

Frequency Range:

2412 MHz - 2462 MHz

Modulation type:

CCK/DSSS/OFDM

FCC Classification:

Digital Transmission System(DTS)

FCC Rule Part(s):

Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



Report prepared by : Se Wook Park
Engineer of Telecommunication testing center



Approved by : Kwon Jeong
Manager of Telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1812-FC048	December 28, 2018	- First Approval Report
HCT-RF-1812-FC048-R1	January 03, 2019	- Additional model Update - Revised the Date of Test - Revised the typo on page 26 - Revised the 6dB BW plot on page 28 - Revised the PSD data table on page 36 - Revised the Conducted band edge plot on page 41 - Revised the Radiation result table. (Duty, Axis, Plot Result)

Table of Contents

1. EUT DESCRIPTION	4
2. TEST METHODOLOGY	5
EUT CONFIGURATION	5
EUT EXERCISE	5
GENERAL TEST PROCEDURES	5
DESCRIPTION OF TEST MODES	5
3. INSTRUMENT CALIBRATION.....	6
4. FACILITIES AND ACCREDITATIONS	6
FACILITIES	6
EQUIPMENT	6
5. ANTENNA REQUIREMENTS	6
6. MEASUREMENT UNCERTAINTY	7
7. DESCRIPTION OF TESTS.....	8
8. SUMMARY TEST OF RESULTS	23
9. TEST RESULT	24
9.1 DUTY CYCLE.....	24
9.2 6dB BANDWIDTH.....	27
9.3 OUTPUT POWER	30
9.4 POWER SPECTRAL DENSITY	36
9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS.....	39
9.6 RADIATED SPURIOUS EMISSIONS	50
9.7 RADIATED RESTRICTED BAND EDGES	60
9.8 POWERLINE CONDUCTED EMISSIONS	65
9.9 CONFIRMATION OF GEO-LOCATION MECHANISM	69
10. LIST OF TEST EQUIPMENT	72
11. ANNEX A_ TEST SETUP PHOTO	74

1. EUT DESCRIPTION

Model	SM-M205F/DS
Additional Model	SM-M205F, SM-M205G/DS
EUT Type	Mobile Phone
Power Supply	DC 3.85 V
Battery Information	Model: EB-BG580ABN Type: Li-ion Battery
Travel Adapter Information	Model: EP-TA200 Manufacture: ELENTec
Frequency Range	2412 MHz - 2462 MHz
Max. RF Output Power	<u>Peak Power (For Information Only)</u> 802.11b : 21.46 dBm 802.11g : 23.74 dBm 802.11n(HT20) : 23.72 dBm <u>Average Power</u> 802.11b : 16.11 dBm 802.11g : 15.49 dBm 802.11n(HT20) : 14.99 dBm
Modulation Type	DSSS/CCK : 802.11b OFDM : 802.11g, 802.11n
Number of Channels	11 Channels
Antenna Specification	Antenna type: LDS Peak Gain : -1.52 dBi
Date(s) of Tests	December 05, 2018 ~ January 03, 2018

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05 dated August 24, 2018 entitled “guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2013)

Conducted Antenna Terminal

See Section from 8.3.(KDB 558074 v05)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Republic of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

* The E.U.T Complies with the requirement of §15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.


The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method, 6.0)b) in KDB 558074 v05.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz ($\geq$ RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

7.2. 6dB Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 8.2 in KDB 558074 v05, Procedure 11.8.2 in ANSI 63.10-2013)


- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 8.3.1.3 in KDB 558074 v05, Procedure 11.9.1.3 in ANSI 63.10-2013)
: Measure the peak power of the transmitter.
- Average Power (Procedure 8.3.2.3 in KDB 558074 v05, Procedure 11.9.2.3 in ANSI 63.10-2013)
 - 1) Measure the duty cycle.
 - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 - 3) Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Total Power (Peak) = Reading Value + ATT loss + Cable loss
- Total Power (Average) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure in KDB 558074 v05, Procedure 11.10.3 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Span = 1.5 times the DTS channel bandwidth.
- 3) $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$.
- 4) $VBW \geq 3 \times RBW$.
- 5) Sweep = auto couple
- 6) Detector = power average(rms)
- 7) Ensure that the number of measurement points $\geq 2 \times \text{Span} / RBW$
- 8) Trace Mode = Average mode (a minimum of 100 traces.)
- 9) Allow trace to fully stabilize.
- 10) Measure the duty cycle(D) and Add Duty cycle factor[$10 \log(1/D)$, D=duty cycle], to the measured Average PSD result
- 11) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Sample Calculation

- Power Spectral Density(Avg) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor


7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

Limit

The maximum conducted (average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 30 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 8.5 in KDB 558074 v05, Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points $\geq 2 \times \text{Span} / \text{RBW}$
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

Freq(MHz)	Factor(dB)
30	11.40
100	9.93
200	10.29
300	10.23
400	10.33
500	10.35
600	10.32
700	10.36
800	10.37
900	10.38
1000	10.35
2000	10.38
2400*	10.36
2500*	10.39
3000	10.78
4000	10.99
5000	11.17
6000	11.16
7000	11.45
8000	11.42
9000	11.58
10000	11.66
11000	11.66
12000	11.78
13000	11.93
14000	12.00
15000	12.08
16000	12.14
17000	12.12
18000	12.18
19000	12.17
20000	12.24
21000	12.27
22000	12.41
23000	12.70
24000	12.44
25000	12.63
26000	12.12

Note : 1. '*' is fundamental frequency range.
2. Factor = Attenuator loss + Cable loss


7.6. Radiated Test

Limit


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = $40 \cdot \log(3 \text{ m}/300 \text{ m}) = -80 \text{ dB}$

Measurement Distance : 3 m

7. Distance Correction Factor(0.490 MHz – 30 MHz) = $40 \cdot \log(3 \text{ m}/30 \text{ m}) = -40 \text{ dB}$

Measurement Distance : 3 m

8. Spectrum Setting

- Frequency Range = 9 kHz ~ 30 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 9 kHz
- VBW $\geq 3 \cdot \text{RBW}$

9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

10. The test results for below 30 MHz is correlated to an open site.

The result on OATS is about 2 dB higher than semi-anechoic chamber(10 m chamber)

Test Procedure of Radiated spurious emissions(Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

5. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW $\geq 3 \cdot \text{RBW}$

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

*In general, (1) is used mainly

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
*Distance extrapolation factor = $20 \cdot \log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting (Method 8.6 in KDB 558074 v05, Procedure 11.12 in ANSI 63.10-2013)
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW $\geq 3 \cdot \text{RBW}$
 - (2) Measurement Type(Average): Duty cycle $\geq 98\%$
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = RMS
 - Averaging type = power (i.e., RMS)
 - RBW = 1 MHz
 - VBW $\geq 3 \cdot \text{RBW}$
 - Sweep time = auto.
 - Trace mode = average (at least 100 traces).
 - (3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = RMS
 - Averaging type = power (i.e., RMS)
 - RBW = 1 MHz
 - VBW $\geq 3 \cdot \text{RBW}$
 - Sweep time = auto.

- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle $\geq$ 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle < 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

+ Duty Cycle Factor

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
*Distance extrapolation factor = $20 \cdot \log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting (Integration method 11.13.3 in ANSI 63.10-2013)
 - When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used:
 - (1) Measurement Type(Peak):
 - Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).
 - Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 100 KHz
 - VBW $\geq 3 \cdot \text{RBW}$
 - Sweep time = auto.
 - (2) Measurement Type(Average): Duty cycle $\geq 98\%$,
 - Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).
 - Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
 - Detector = RMS
 - Averaging type = power (i.e., RMS), if $[\text{span} / (\# \text{ of points in sweep})] \leq (\text{RBW} / 2)$.
 - RBW = 100 KHz
 - VBW $\geq 3 \cdot \text{RBW}$
 - Sweep time = auto.
 - Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle < 98%, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (i.e., RMS), if $[\text{span} / (\# \text{ of points in sweep})] \leq (\text{RBW} / 2)$.
- RBW = 1 MHz
- VBW $\geq 3 \times \text{RBW}$
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle $\geq 98\%$)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle < 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)
+ Duty Cycle Factor

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

7.8. Worst case configuration and mode

Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + external accessories(earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Radiated Spurious Emissions : X
 - Radiated Restricted Band Edge : X
3. Duty cycle factor applies only 802.11g/n(Duty cycle < 98%).
4. All datarate of operation were investigated and the worst case datarate results are reported
 - 802.11b : 1 Mbps
 - 802.11g : 6 Mbps
 - 802.11n : MCS 0

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone+Earphone+Travel Adapter, Stand alone+Travel Adapter
 - Worstcase : Stand alone+Travel Adapter

Conducted test

All datarate of operation were investigated and the worst case datarate results are reported.

8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		N/A
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§15.247(d)	Conducted > 30 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 7.6		PASS

9. TEST RESULT

9.1 DUTY CYCLE


Mode	Data Rate (Mbps)	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
802.11b	1	8.608	8.640	0.99629630	0.016
	2	4.400	4.431	0.99300384	0.030
	5.5	1.722	1.754	0.98175599	0.080
	11	0.957	0.989	0.96813354	0.141
802.11g	6	1.428	1.463	0.97599098	0.106
	9	0.960	1.058	0.90724669	0.423
	12	0.724	0.819	0.88389472	0.536
	18	0.492	0.609	0.80856467	0.923
	24	0.372	0.488	0.76198986	1.181
	36	0.256	0.372	0.68764658	1.626
	48	0.196	0.312	0.62777885	2.022
	54	0.180	0.296	0.60810811	2.160
802.11n (HT20)	6.5 (MCS0)	1.336	1.410	0.94715683	0.236
	13 (MCS1)	0.688	0.783	0.87872335	0.561
	19.5 (MCS2)	0.471	0.568	0.83033991	0.807
	26 (MCS3)	0.364	0.480	0.75840909	1.201
	39 (MCS4)	0.256	0.372	0.68836202	1.622
	52 (MCS5)	0.199	0.315	0.63255987	1.989
	58.5 (MCS6)	0.185	0.300	0.61613760	2.103
	65 (MCS7)	0.168	0.284	0.59173009	2.279

■ Test Plots


Duty cycle plot (802.11b(1Mbps))



Duty cycle plot (802.11g(6Mbps))



Duty cycle plot (802.11n(MCS 0))



9.2 6dB BANDWIDTH


802.11b Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	8.101	0.5
2437	6	8.117	0.5
2462	11	8.093	0.5

802.11g Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	15.34	0.5
2437	6	15.49	0.5
2462	11	15.53	0.5


802.11n Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	15.17	0.5
2437	6	15.47	0.5
2462	11	15.59	0.5

■ Test Plots


6dB Bandwidth plot (802.11b-CH 11)



6dB Bandwidth plot (802.11g-CH 1)



6dB Bandwidth plot (802.11n_HT20-CH 1)



Note:

In order to simplify the report, attached plots were only the most narrow 6 dB BW channel.

9.3 OUTPUT POWER

Peak Power

1. Power Meter offset = Attenuator loss + Cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
So, 10.36 dB is offset for 2.4 GHz Band.

802.11b Mode		Power Level Setting	Data Rate [Mbps]	Measured Power[dBm]	Limit [dBm]
Frequency [MHz]	Channel No.				
2412	1	16	1	18.30	30
			2	18.95	30
			5.5	18.70	30
			11	21.46	30
2437	6	15	1	17.48	30
			2	18.14	30
			5.5	19.04	30
			11	20.60	30
2462	11	14	1	18.24	30
			2	18.12	30
			5.5	18.51	30
			11	21.10	30

802.11g Mode		Power Level Setting	Data Rate [Mbps]	Measured Power[dBm]	Limit [dBm]
Frequency[M Hz]	Channel No.				
2412	1	10	6	22.07	30
			9	22.28	30
			12	21.79	30
			18	21.98	30
			24	22.77	30
			36	22.75	30
			48	23.42	30
			54	23.69	30
2437	6	14	6	23.10	30
			9	23.21	30
			12	22.81	30
			18	23.02	30
			24	23.68	30
			36	23.74	30
			48	22.67	30
			54	22.86	30
2462	11	12	6	20.34	30
			9	20.47	30
			12	20.06	30
			18	20.29	30
			24	20.97	30
			36	20.87	30
			48	22.34	30
			54	22.57	30

802.11n Mode		Power Level Setting	MCS Index	Measured Power[dBm]	Limit [dBm]
Frequency[M Hz]	Channel No.				
2412	1	9	0	21.94	30
			1	22.10	30
			2	21.96	30
			3	22.44	30
			4	22.59	30
			5	22.14	30
			6	22.46	30
			7	22.31	30
2437	6	15	0	23.21	30
			1	23.24	30
			2	23.38	30
			3	23.63	30
			4	23.72	30
			5	21.51	30
			6	21.88	30
			7	21.66	30
2462	11	11	0	19.60	30
			1	19.73	30
			2	19.70	30
			3	20.16	30
			4	20.30	30
			5	20.46	30
			6	20.68	30
			7	20.57	30

Average Power

1. Power Meter offset = Attenuator loss + Cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
So, 10.36 dB is offset for 2.4 GHz Band.

802.11b Mode		Power Level Setting	Data Rate [Mbps]	Measured Power[dBm]	Duty Cycle Factor [dB]	Measured Power(dBm) + Duty Cycle Factor[dB]	Limit [dBm]
Frequency [MHz]	Channel No.						
2412	1	16	1	15.81	0.016	15.83	30
			2	16.08	0.030	16.11	30
			5.5	15.78	0.080	15.86	30
			11	15.27	0.141	15.41	30
2437	6	15	1	14.97	0.016	14.99	30
			2	15.30	0.030	15.33	30
			5.5	15.03	0.080	15.11	30
			11	14.64	0.141	14.78	30
2462	11	14	1	15.78	0.016	15.79	30
			2	15.60	0.030	15.63	30
			5.5	15.75	0.080	15.83	30
			11	15.18	0.141	15.32	30

802.11g Mode		Power Level Setting	Data Rate [Mbps]	Measured Power[dBm]	Duty Cycle Factor [dB]	Measured Power(dBm) + Duty Cycle Factor[dB]	Limit [dBm]
Frequency [MHz]	Channel No.						
2412	1	10	6	13.88	0.106	13.99	30
			9	13.84	0.423	14.27	30
			12	13.73	0.536	14.26	30
			18	13.50	0.923	14.43	30
			24	13.25	1.181	14.43	30
			36	12.94	1.626	14.57	30
			48	13.40	2.022	15.42	30
			54	13.33	2.160	15.49	30
2437	6	14	6	14.94	0.106	15.05	30
			9	14.78	0.423	15.20	30
			12	14.63	0.536	15.17	30
			18	14.52	0.923	15.45	30
			24	14.29	1.181	15.47	30
			36	13.85	1.626	15.48	30
			48	12.49	2.022	14.51	30
			54	12.34	2.160	14.50	30
2462	11	12	6	12.18	0.106	12.28	30
			9	12.03	0.423	12.45	30
			12	11.90	0.536	12.43	30
			18	11.70	0.923	12.63	30
			24	11.48	1.181	12.66	30
			36	11.12	1.626	12.74	30
			48	12.23	2.022	14.25	30
			54	12.03	2.160	14.19	30

802.11n Mode		Power Level Setting	MCS Index	Measured Power[dBm]	Duty Cycle Factor [dB]	Measured Power(dBm) + Duty Cycle Factor[dB]	Limit [dBm]
Frequency [MHz]	Channel No.						
2412	1	9	0	13.73	0.236	13.97	30
			1	13.49	0.561	14.05	30
			2	13.24	0.807	14.05	30
			3	13.11	1.201	14.31	30
			4	12.83	1.622	14.45	30
			5	12.25	1.989	14.24	30
			6	12.17	2.103	14.28	30
			7	12.01	2.279	14.29	30
2437	6	15	0	14.74	0.236	14.98	30
			1	14.36	0.561	14.92	30
			2	14.12	0.807	14.93	30
			3	13.76	1.201	14.96	30
			4	13.37	1.622	14.99	30
			5	11.48	1.989	13.47	30
			6	11.49	2.103	13.59	30
			7	11.34	2.279	13.61	30
2462	11	11	0	11.31	0.236	11.54	30
			1	11.25	0.561	11.81	30
			2	10.91	0.807	11.72	30
			3	10.75	1.201	11.95	30
			4	10.28	1.622	11.90	30
			5	9.86	1.989	11.85	30
			6	9.75	2.103	11.85	30
			7	9.71	2.279	11.99	30

9.4 POWER SPECTRAL DENSITY

Mode	Frequency (MHz)	Channel No.	Test Result			
			PSD (dBm)	Duty Factor (dBm)	Result (dBm)	Limit (dBm)
802.11b	2412	1	-9.028	0.030	-8.998	8
	2437	6	-10.720	0.030	-10.690	8
	2462	11	-9.584	0.080	-9.504	8
802.11g	2412	1	-16.298	2.160	-14.138	8
	2437	6	-16.580	1.626	-14.954	8
	2462	11	-17.665	2.022	-15.643	8
802.11n (HT20)	2412	1	-17.611	1.622	-15.989	8
	2437	6	-16.070	1.622	-14.448	8
	2462	11	-20.828	2.279	-18.549	8

Note :

1. Spectrum reading values are not plot data.

The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.

2. Spectrum offset = Attenuator loss + Cable loss

3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.

So, 10.36 dB is offset for 2.4 GHz Band.

4. Worst Datarate

802.11b CH1 → 2 Mbps

802.11b CH6 → 2 Mbps

802.11b CH11 → 5.5 Mbps

802.11g CH1 → 54 Mbps

802.11g CH6 → 36 Mbps

802.11g CH11 → 48 Mbps


802.11n CH1 → 39 Mbps

802.11n CH6 → 39 Mbps


802.11n CH11 → 65 Mbps

■ Test Plots


Power Spectral Density (802.11b-CH 1)



Power Spectral Density (802.11g-CH 1)



Power Spectral Density (802.11n_HT20 -CH 6)



Note :

In order to simplify the report, attached plots were only the worstcase PSD channel.

9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.

In order to simplify the report, attached plots were only the worst case channel and data rate.

■ Test Plots(BandEdge)

Band Edge (802.11b-CH1)



Band Edge (802.11b-CH11)



Band Edge (802.11g-CH1)



Band Edge (802.11g-CH11)



Band Edge (802.11n_HT20-CH1)




Band Edge (802.11n_HT20-CH11)



■ Test Plots(Conducted Spurious Emission)


30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




1 GHz ~ 3 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




3 GHz ~ 5 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




5 GHz ~ 7 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




7 GHz ~ 9 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




9 GHz ~ 11 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




11 GHz ~ 13 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




13 GHz ~ 15 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




15 GHz ~ 17 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




17 GHz ~ 19 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




19 GHz ~ 21 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)




21 GHz ~ 23 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)



23 GHz ~ 25 GHz

Conducted Spurious Emission (802.11b_Ch.1_2 Mbps)



9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40 \cdot \log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. The test results for below 30 MHz is correlated to an open site.
The result on OATS is about 2 dB higher than semi-anechoic chamber(10 m chamber)

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	51.89	-0.67	V	51.23	73.98	22.76	PK
4824	40.02	-0.67	V	39.36	53.98	14.63	AV
7236	52.96	5.28	V	58.24	73.98	15.75	PK
7236	44.48	5.28	V	49.76	53.98	4.23	AV
4824	52.02	-0.67	H	51.36	73.98	22.63	PK
4824	40.05	-0.67	H	39.39	53.98	14.60	AV
7236	53.64	5.28	H	58.92	73.98	15.07	PK
7236	44.58	5.28	H	49.86	53.98	4.13	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	51.92	0.00	-0.67	V	51.26	73.98	22.73	PK
4824	39.98	0.11	-0.67	V	39.42	53.98	14.56	AV
7236	53.84	0.00	5.28	V	59.12	73.98	14.87	PK
7236	40.39	0.11	5.28	V	45.77	53.98	8.21	AV
4824	51.96	0.00	-0.67	H	51.30	73.98	22.69	PK
4824	40.02	0.11	-0.67	H	39.46	53.98	14.52	AV
7236	53.95	0.00	5.28	H	59.23	73.98	14.76	PK
7236	40.52	0.11	5.28	H	45.90	53.98	8.08	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	51.84	0.00	-0.67	V	51.18	73.98	22.81	PK
4824	39.95	0.24	-0.67	V	39.52	53.98	14.46	AV
7236	53.55	0.00	5.28	V	58.83	73.98	15.16	PK
7236	40.29	0.24	5.28	V	45.80	53.98	8.18	AV
4824	51.91	0.00	-0.67	H	51.25	73.98	22.74	PK
4824	40.00	0.24	-0.67	H	39.57	53.98	14.41	AV
7236	53.69	0.00	5.28	H	58.97	73.98	15.02	PK
7236	40.32	0.24	5.28	H	45.83	53.98	8.15	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	51.79	-0.37	V	51.42	73.98	22.56	PK
4874	40.05	-0.37	V	39.68	53.98	14.30	AV
7311	54.04	5.60	V	59.64	73.98	14.34	PK
7311	44.61	5.60	V	50.21	53.98	3.77	AV
4874	51.88	-0.37	H	51.51	73.98	22.47	PK
4874	40.12	-0.37	H	39.75	53.98	14.23	AV
7311	54.23	5.60	H	59.83	73.98	14.15	PK
7311	44.93	5.60	H	50.53	53.98	3.45	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	51.98	0.00	2.62	V	54.60	73.98	19.38	PK
4874	39.74	0.30	2.62	V	42.66	53.98	11.32	AV
7311	54.95	0.00	9.86	V	64.81	73.98	9.17	PK
7311	39.68	0.30	9.86	V	49.84	53.98	4.14	AV
4874	51.76	0.00	-0.37	H	51.39	73.98	22.59	PK
4874	40.10	0.11	-0.37	H	39.84	53.98	14.14	AV
7311	56.23	0.00	5.60	H	61.83	73.98	12.15	PK
7311	42.72	0.11	5.60	H	48.43	53.98	5.55	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	51.56	0.00	-0.37	V	51.19	73.98	22.79	PK
4874	39.76	0.24	-0.37	V	39.63	53.98	14.35	AV
7311	55.90	0.00	5.60	V	61.50	73.98	12.48	PK
7311	41.71	0.24	5.60	V	47.55	53.98	6.43	AV
4874	51.69	0.00	-0.37	H	51.32	73.98	22.66	PK
4874	40.00	0.24	-0.37	H	39.87	53.98	14.11	AV
7311	56.16	0.00	5.60	H	61.76	73.98	12.22	PK
7311	41.84	0.24	5.60	H	47.68	53.98	6.30	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	51.58	-0.60	V	50.99	73.98	23.00	PK
4924	39.59	-0.60	V	39.00	53.98	14.99	AV
7386	53.75	5.67	V	59.42	73.98	14.57	PK
7386	43.76	5.67	V	49.43	53.98	4.56	AV
4924	51.62	-0.60	H	51.03	73.98	22.96	PK
4924	39.66	-0.60	H	39.07	53.98	14.92	AV
7386	53.84	5.67	H	59.51	73.98	14.48	PK
7386	43.89	5.67	H	49.56	53.98	4.43	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2462
Channel No.	11 Ch


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	51.46	0.00	-0.60	V	50.87	73.98	23.12	PK
4924	39.26	0.11	-0.60	V	38.77	53.98	15.21	AV
7386	50.68	0.00	5.67	V	56.35	73.98	17.64	PK
7386	39.16	0.11	5.67	V	44.93	53.98	9.05	AV
4924	51.55	0.00	-0.60	H	50.96	73.98	23.03	PK
4924	39.49	0.11	-0.60	H	39.00	53.98	14.98	AV
7386	50.90	0.00	5.67	H	56.57	73.98	17.42	PK
7386	39.25	0.11	5.67	H	45.02	53.98	8.96	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	51.29	0.00	-0.60	V	50.70	73.98	23.29	PK
4924	39.16	0.24	-0.60	V	38.80	53.98	15.18	AV
7386	51.32	0.00	5.67	V	56.99	73.98	17.00	PK
7386	39.05	0.24	5.67	V	44.95	53.98	9.03	AV
4924	51.39	0.00	-0.60	H	50.80	73.98	23.19	PK
4924	39.29	0.24	-0.60	H	38.93	53.98	15.05	AV
7386	51.43	0.00	5.67	H	57.10	73.98	16.89	PK
7386	39.13	0.24	5.67	H	45.03	53.98	8.95	AV


■ Test Plots (Worst case : X-H)

Radiated Spurious Emissions plot – Average Reading (802.11b, Ch.6 3rd Harmonic)




Date: 26.DEC.2018 06:44:08

Radiated Spurious Emissions plot – Peak Reading (802.11b, Ch.6 3rd Harmonic)




Date: 26.DEC.2018 06:45:18

Radiated Spurious Emissions plot – Average Reading (802.11g, Ch.6 3rd Harmonic)




Date: 26.DEC.2018 06:48:01

Radiated Spurious Emissions plot – Peak Reading (802.11g, Ch.6 3rd Harmonic)




Date: 26.DEC.2018 06:50:32

Radiated Spurious Emissions plot – Average Reading (802.11n, Ch.6 3rd Harmonic)



Date: 26.DEC.2018 12:22:42

Radiated Spurious Emissions plot – Peak Reading (802.11n, Ch.6 3rd Harmonic)



Date: 26.DEC.2018 06:52:53

Note:

Plot of worst case are only reported.

9.7 RADIATED RESTRICTED BAND EDGES

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.73	34.42	H	60.15	73.98	13.83	PK
2390.0	16.06	34.42	H	50.48	53.98	3.50	AV
2390.0	25.69	34.42	V	60.11	73.98	13.87	PK
2390.0	16.02	34.42	V	50.44	53.98	3.54	AV
2483.5	26.43	33.59	H	60.02	73.98	13.96	PK
2483.5	16.22	33.59	H	49.81	53.98	4.17	AV
2483.5	26.28	33.59	V	59.87	73.98	14.11	PK
2483.5	16.16	33.59	V	49.75	53.98	4.23	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	27.97	0.00	34.42	H	62.39	73.98	11.59	PK
2390.0	17.39	0.11	34.42	H	51.92	53.98	2.06	AV
2390.0	27.76	0.00	34.42	V	62.18	73.98	11.80	PK
2390.0	17.26	0.11	34.42	V	51.79	53.98	2.19	AV
2483.5	29.52	0.00	33.59	H	63.11	73.98	10.87	PK
2483.5	18.20	0.11	33.59	H	51.90	53.98	2.08	AV
2483.5	29.26	0.00	33.59	V	62.85	73.98	11.13	PK
2483.5	18.11	0.11	33.59	V	51.81	53.98	2.17	AV

Operation Mode: 802.11n (HT20)
 Transfer MCS Index: 0
 Operating Frequency: 2412 MHz, 2462 MHz
 Channel No. 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	28.26	0.00	34.42	H	62.68	73.98	11.30	PK
2390.0	17.30	0.24	34.42	H	51.96	53.98	2.02	AV
2390.0	28.13	0.00	34.42	V	62.55	73.98	11.43	PK
2390.0	17.24	0.24	34.42	V	51.90	53.98	2.08	AV
2483.5	28.02	0.00	33.59	H	61.61	73.98	12.37	PK
2483.5	17.67	0.24	33.59	H	51.50	53.98	2.48	AV
2483.5	27.66	0.00	33.59	V	61.25	73.98	12.73	PK
2483.5	17.59	0.24	33.59	V	51.42	53.98	2.56	AV


Test Plots (Worst case : X-H)

Radiated Restricted Band Edges plot – Average Reading (802.11b Ch.1)




Date: 26.DEC.2018 03:23:51

Radiated Restricted Band Edges plot – Peak Reading (802.11b Ch.1)




Date: 26.DEC.2018 03:25:10

Radiated Restricted Band Edges plot – Average Reading (802.11g Ch.1)




Date: 26.DEC.2018 03:19:46

Radiated Restricted Band Edges plot – Peak Reading (802.11g Ch.1)




Date: 26.DEC.2018 03:21:12

Radiated Restricted Band Edges plot – Average Reading (802.11n Ch.1)



Date: 26.DEC.2018 03:41:45

Radiated Restricted Band Edges plot – Peak Reading (802.11n Ch.1)



Date: 26.DEC.2018 03:42:34

Note:

Plot of worst case are only reported.

9.8 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions (Line 1)

Test


1 / 2

HCT TEST Report

Common Information

EUT: SM-M205F/DS
Manufacturer: SAMSUNG
Test Site: SHIELD ROOM
Operating Conditions: 2.4 WLAN L1

FCC CLASS B_Exten Cable



— FCC CLASS B_OP — FCC CLASS B_AV — Preview Result 1-PK+
— Preview Result 2-AVG — Final Result 1-OPK — Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	31.9	9.000	Off	L1	9.7	33.9	65.8
0.686000	39.5	9.000	Off	L1	9.8	16.5	56.0
0.690000	40.1	9.000	Off	L1	9.8	15.9	56.0
0.694000	39.6	9.000	Off	L1	9.8	16.4	56.0
0.734000	37.8	9.000	Off	L1	9.8	18.2	56.0
0.738000	37.3	9.000	Off	L1	9.8	18.7	56.0
2.504000	29.5	9.000	Off	L1	9.9	26.5	56.0
2.840000	31.8	9.000	Off	L1	9.9	24.2	56.0
3.276000	32.1	9.000	Off	L1	9.9	23.9	56.0
3.384000	30.1	9.000	Off	L1	9.9	25.9	56.0
3.854000	31.3	9.000	Off	L1	10.0	24.7	56.0
4.016000	28.8	9.000	Off	L1	10.0	27.2	56.0
5.674000	34.0	9.000	Off	L1	10.1	26.0	60.0
5.678000	34.3	9.000	Off	L1	10.1	25.7	60.0
5.724000	34.2	9.000	Off	L1	10.1	25.8	60.0
5.732000	33.7	9.000	Off	L1	10.1	26.3	60.0
5.736000	33.8	9.000	Off	L1	10.1	26.2	60.0
5.746000	32.6	9.000	Off	L1	10.1	27.4	60.0

2018-12-17

오후 9:26:23

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	19.9	9.000	Off	L1	9.7	35.8	55.8
0.158000	21.2	9.000	Off	L1	9.7	34.4	55.6
0.640000	29.2	9.000	Off	L1	9.8	16.8	46.0
0.690000	33.6	9.000	Off	L1	9.8	12.4	46.0
0.742000	27.2	9.000	Off	L1	9.8	18.8	46.0
0.792000	25.6	9.000	Off	L1	9.8	20.4	46.0
2.504000	21.2	9.000	Off	L1	9.9	24.8	46.0
2.840000	23.5	9.000	Off	L1	9.9	22.5	46.0
3.228000	23.0	9.000	Off	L1	9.9	23.0	46.0
3.432000	21.6	9.000	Off	L1	9.9	24.4	46.0
3.562000	22.0	9.000	Off	L1	9.9	24.0	46.0
3.854000	22.4	9.000	Off	L1	10.0	23.6	46.0
5.674000	23.8	9.000	Off	L1	10.1	26.2	50.0
5.678000	24.2	9.000	Off	L1	10.1	25.8	50.0
5.724000	24.2	9.000	Off	L1	10.1	25.8	50.0
5.732000	24.4	9.000	Off	L1	10.1	25.6	50.0
5.746000	23.3	9.000	Off	L1	10.1	26.7	50.0
5.770000	24.0	9.000	Off	L1	10.1	26.0	50.0

2018-12-17

오주 9:26:23

Conducted Emissions (Line 2)

Test


1 / 2

HCT TEST Report

Common Information

EUT: SM-M205F/DS
Manufacturer: SAMSUNG
Test Site: SHIELD ROOM
Operating Conditions: 2.4G WLAN_N

FCC CLASS B_Exten Cable



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	28.2	9.000	Off	N	9.8	37.7	65.9
0.158000	30.1	9.000	Off	N	9.8	35.5	65.6
0.746000	33.1	9.000	Off	N	9.9	22.9	56.0
0.760000	32.0	9.000	Off	N	9.9	24.0	56.0
0.764000	29.9	9.000	Off	N	9.9	26.1	56.0
0.774000	32.1	9.000	Off	N	9.9	23.9	56.0
1.096000	28.4	9.000	Off	N	10.0	27.6	56.0
1.122000	27.9	9.000	Off	N	10.0	28.1	56.0
1.208000	26.4	9.000	Off	N	10.0	29.6	56.0
1.218000	25.0	9.000	Off	N	10.0	31.0	56.0
1.518000	27.9	9.000	Off	N	10.1	28.1	56.0
1.576000	27.4	9.000	Off	N	10.1	28.6	56.0
5.202000	26.2	9.000	Off	N	10.2	33.8	60.0
5.288000	26.9	9.000	Off	N	10.2	33.1	60.0
5.316000	27.3	9.000	Off	N	10.2	32.7	60.0
5.322000	28.0	9.000	Off	N	10.2	32.0	60.0
5.348000	28.2	9.000	Off	N	10.2	31.8	60.0
5.412000	27.7	9.000	Off	N	10.2	32.3	60.0

2018-12-17

오후 9:36:10

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	15.5	9.000	Off	N	9.8	40.4	55.9
0.158000	16.7	9.000	Off	N	9.8	38.9	55.6
0.738000	21.7	9.000	Off	N	9.9	24.3	46.0
0.750000	25.9	9.000	Off	N	9.9	20.1	46.0
0.760000	23.4	9.000	Off	N	9.9	22.6	46.0
0.770000	23.4	9.000	Off	N	9.9	22.6	46.0
1.096000	23.8	9.000	Off	N	10.0	22.2	46.0
1.122000	23.0	9.000	Off	N	10.0	23.0	46.0
1.206000	20.6	9.000	Off	N	10.0	25.4	46.0
1.218000	18.7	9.000	Off	N	10.0	27.3	46.0
1.518000	22.2	9.000	Off	N	10.1	23.8	46.0
2.558000	20.9	9.000	Off	N	10.1	25.1	46.0
5.202000	17.2	9.000	Off	N	10.2	32.8	50.0
5.288000	18.2	9.000	Off	N	10.2	31.8	50.0
5.294000	18.7	9.000	Off	N	10.2	31.3	50.0
5.380000	20.6	9.000	Off	N	10.2	29.4	50.0
5.438000	20.6	9.000	Off	N	10.2	29.4	50.0
5.470000	19.6	9.000	Off	N	10.2	30.4	50.0

2018-12-17

모후 9:36:10

9.9 CONFIRMATION OF GEO-LOCATION MECHANISM

The device uses a geo-location mechanism based on the Country in order to only enable certain WLAN DTS bands when the device is not in the USA.

WLAN	Country code = US	Country code = KR(Korea)
CH 12	Did not connect	Connected
CH 13	Did not connect	Connected

The verification tests confirmed the operational of the geo-location mechanism.

Setting the channel for Access point

- SSID : ap_2g_ht20

- Ch.12 setting

```
Debug:> wl -i radio_1 down
Debug:> wl -i radio_1 chanspec 12
Chanspec set to 0x100c
Debug:> wl -i radio_1 up
```

- Ch.13 setting

```
Debug:> wl -i radio_1 down
Debug:> wl -i radio_1 chanspec 13
Chanspec set to 0x100d
Debug:> wl -i radio_1 up
```

Setting the country for product

Country code = US	Country code = KR(Korea)
오후 9:51 WlanConfiguration MAC ADDRESS 00:12:36:76:85:0A Legacy BackOff : ENABLED Hotspot BackOff : ENABLED ☐ Disable FccChannel TxPower BackOff WLAN RF Test Mode Setting (WLAN RF Test Mode disables PowerSave, Roaming and LPC) ☐ User Mode ☐ RF Test Mode + Enable Proximity Sensor ☐ RF Test Mode MODULE TYPE mx150 CHANGE THE MAC Current Phone's locale : US (Country) us REMOVE COUNTRY SET COUNTRY DOZEMODE ON Country Code Change complete	오후 9:52 WlanConfiguration MAC ADDRESS 00:12:36:76:85:0A Legacy BackOff : ENABLED Hotspot BackOff : ENABLED ☐ Disable FccChannel TxPower BackOff WLAN RF Test Mode Setting (WLAN RF Test Mode disables PowerSave, Roaming and LPC) ☐ User Mode ☐ RF Test Mode + Enable Proximity Sensor ☐ RF Test Mode MODULE TYPE mx150 CHANGE THE MAC Current Phone's locale : KR (Country) kr REMOVE COUNTRY SET COUNTRY DOZEMODE ON Country Code Change complete

Verification test

Did not connect (Country code = US)	Connected (Country code = KR)
	

10. LIST OF TEST EQUIPMENT

Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	12/12/2018	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/27/2018	Annual	100033
ESPAC	SU-642 / Temperature Chamber	03/30/2018	Annual	0093008124
Agilent	N9020A / Signal Analyzer	06/08/2018	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	11/22/2018	Annual	MY49431210
Agilent	N1911A / Power Meter	04/16/2018	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/16/2018	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/20/2018	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	06/07/2018	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/26/2018	Annual	KR75303960
Agilent	8493C / Attenuator(10 dB)	07/10/2018	Annual	07560
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A
Rohde & Schwarz	CBT / Bluetooth Tester	05/17/2018	Annual	100422

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	04/19/2017	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	04/06/2017	Biennial	760
Schwarzbeck	BBHA 9120D / Horn Antenna	05/02/2017	Biennial	9120D-937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	12/04/2017	Biennial	BBHA9170541
Rohde & Schwarz	FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer	09/06/2017	Annual	100688
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/27/2017	Annual	101068-SZ
Wainwright Instruments	WHK3.0/18G-10EF / High Pass Filter	06/07/2018	Annual	8
Wainwright Instruments	WHFX7.0/18G-8SS / High Pass Filter	05/09/2018	Annual	29
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	06/29/2018	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/03/2018	Annual	2
Api tech.	18B-03 / Attenuator (3 dB)	06/07/2018	Annual	1
Agilent	8493C-10 / Attenuator(10 dB)	07/17/2018	Annual	08285
CERNEX	CBLU1183540 / Power Amplifier	07/10/2018	Annual	22964
CERNEX	CBL06185030 / Power Amplifier	07/10/2018	Annual	22965
CERNEX	CBL18265035 / Power Amplifier	01/10/2018	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	06/29/2018	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	03/27/2018	Annual	3000C000276

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-1812-FC046-P
2	HCT-RF-1812-FC047-P
3	HCT-RF-1812-FC048-P