



## MEASUREMENT REPORT FCC Part 22 LTE

**Applicant Name:**

Samsung Electronics, Co. Ltd.  
129, Samsung-ro, Maetan dong,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do 443-742, Korea

**Date of Testing:**

12/2 – 12/3/2014

**Test Site/Location:**

PCTEST Lab., Columbia, MD, USA

**Test Report Serial No.:**

0Y1412012186.A3L

**FCC ID :**

**A3LSMN910P**

**APPLICANT:**

**SAMSUNG ELECTRONICS, CO. LTD.**

**Application Type:**

Class II Permissive Change

**FCC Classification:**

PCS Licensed Transmitter Held to Ear (PCE)

**FCC Rule Part(s):**

§2; §22

**Test Procedure(s):**

ANSI/TIA-603-C-2004, KDB 971168 v02r02

**EUT Type:**

Portable Handset

**Model(s):**

SM-N910P

**Test Device Serial No.:**

*identical prototype* [S/N: F4D31]

**Class II Permissive Change:**

Please see FCC change document

**Original Grant Date:**

9/11/2014

| Mode        | Tx Frequency (MHz) | Emission Designator | Modulation | ERP            |                  |
|-------------|--------------------|---------------------|------------|----------------|------------------|
|             |                    |                     |            | Max. Power (W) | Max. Power (dBm) |
| LTE Band 26 | 831.5 - 841.5      | 13M5G7D             | QPSK       | 0.041          | 16.08            |
| LTE Band 26 | 831.5 - 841.5      | 13M4W7D             | 16QAM      | 0.032          | 14.99            |

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
Randy Ortaez  
President




|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 1 of 25                    |

# TABLE OF CONTENTS


|                                                              |    |
|--------------------------------------------------------------|----|
| FCC PART 22 MEASUREMENT REPORT .....                         | 3  |
| 1.0 INTRODUCTION .....                                       | 4  |
| 1.1 SCOPE .....                                              | 4  |
| 1.2 TESTING FACILITY .....                                   | 4  |
| 2.0 PRODUCT INFORMATION.....                                 | 5  |
| 2.1 EQUIPMENT DESCRIPTION .....                              | 5  |
| 2.2 DEVICE CAPABILITIES.....                                 | 5  |
| 2.3 TEST CONFIGURATION.....                                  | 5  |
| 2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....            | 5  |
| 2.5 LABELING REQUIREMENTS.....                               | 5  |
| 3.0 DESCRIPTION OF TESTS .....                               | 6  |
| 3.1 MEASUREMENT PROCEDURE .....                              | 6  |
| 3.2 CELLULAR - BASE FREQUENCY BLOCKS.....                    | 6  |
| 3.3 CELLULAR - MOBILE FREQUENCY BLOCKS.....                  | 6  |
| 3.4 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS .....     | 6  |
| 4.0 TEST EQUIPMENT CALIBRATION DATA .....                    | 8  |
| 5.0 SAMPLE CALCULATIONS .....                                | 9  |
| 6.0 TEST RESULTS.....                                        | 10 |
| 6.1 SUMMARY.....                                             | 10 |
| 6.2 OCCUPIED BANDWIDTH .....                                 | 11 |
| 6.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL..... | 13 |
| 6.4 BAND EDGE EMISSIONS AT ANTENNA TERMINAL .....            | 17 |
| 6.5 RADIATED POWER (ERP).....                                | 19 |
| 6.6 RADIATED SPURIOUS EMISSIONS MEASUREMENTS .....           | 21 |
| 7.0 CONCLUSION.....                                          | 25 |

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 2 of 25                    |



# MEASUREMENT REPORT

## FCC Part 22





### §2.1033 General Information

**APPLICANT:** Samsung Electronics, Co. Ltd.  
**APPLICANT ADDRESS:** 129, Samsung-ro, Maetan dong,  
 Yeongtong-gu, Suwon-si, Gyeonggi-do 443-742, Korea  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §22  
**BASE MODEL:** SM-N910P  
**FCC ID:** A3LSMN910P  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
**FREQUENCY TOLERANCE:**  $\pm 0.00025\%$  (2.5 ppm)  
**Test Device Serial No.:** F4D31 ☐ Production ☒ Pre-Production ☐ Engineering  
**DATE(S) OF TEST:** 12/2 – 12/3/2014  
**TEST REPORT S/N:** 0Y1412012186.A3L

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 3 of 25                    |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 4 of 25                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMN910P**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, 850/1900 CDMA/EvDO Rev 0/A, 1x Advanced (BC0, BC1, BC10), Multi-band LTE, 802.11a/b/g/n/ac WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

### 2.3 Test Configuration

This device supports a wireless charging cover. Per KDB 648474 D03, spurious emissions measurement data was also investigated with the wireless charging battery cover. The handset was placed on the representative charging pad under normal conditions and in a simulated call configuration. Only worst case emissions are shown in this report and identified as WCC.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.5 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 5 of 25                    |


## 3.0 DESCRIPTION OF TESTS

### 3.1 Measurement Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-C-2004) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168) were used in the measurement of the **Samsung Portable Handset** FCC ID: A3LSMN910P.

### 3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A\* Low + A)


BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A\* High)

BLOCK 4: 891.5 – 894 MHz (B\*)

### 3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A\* Low + A)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A\* High)

BLOCK 4: 846.5 – 849 MHz (B\*)

### 3.4 Radiated Power and Radiated Spurious Emissions

§2.1053 §22.913(a.2) §22.917(a)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     | Page 6 of 25                                                                          |                                 |

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

The calculated  $P_d$  levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of  $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$ .

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 7 of 25                    |

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer    | Model             | Description                            | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|-----------------|-------------------|----------------------------------------|------------|--------------|------------|---------------|
| -               | LTx1              | Licensed Transmitter Cable Set         | 1/29/2014  | Annual       | 1/29/2015  | N/A           |
| -               | RE1               | Radiated Emissions Cable Set (UHF/EHF) | 5/29/2014  | Annual       | 5/29/2015  | N/A           |
| Agilent         | 8447D             | Broadband Amplifier                    | 5/30/2014  | Annual       | 5/30/2015  | 2443A01900    |
| Agilent         | E4448A            | PSA (3Hz-50GHz) Spectrum Analyzer      | 4/16/2014  | Annual       | 4/16/2015  | US42510244    |
| Anritsu         | MT8820C           | Radio Communication Analyzer           | 12/12/2013 | Annual       | 12/12/2014 | 6200901190    |
| Com-Power       | AL-130            | 9kHz - 30MHz Loop Antenna              | 6/26/2013  | Biennial     | 6/26/2015  | 121034        |
| Emco            | 3115              | Horn Antenna (1-18GHz)                 | 1/30/2014  | Biennial     | 1/30/2016  | 9704-5182     |
| Espec           | ESX-2CA           | Environmental Chamber                  | 4/16/2014  | Annual       | 4/16/2015  | 17620         |
| ETS Lindgren    | 3160-09           | 18-26.5 GHz Standard Gain Horn         | 6/17/2014  | Biennial     | 6/17/2016  | 135427        |
| ETS Lindgren    | 3164-08           | Quad Ridge Horn Antenna                | 3/12/2014  | Biennial     | 3/12/2016  | 128337        |
| K & L           | 13SH10-1000/U1000 | N Type High Pass Filter                | 12/1/2014  | Annual       | 12/1/2015  | 1             |
| Mini-Circuits   | SSG-4000HP        | USB Synthesized Signal Generator       | N/A        |              |            | 11208010032   |
| Mini-Circuits   | PWR-SENS-4RMS     | USB Power Sensor                       | 4/17/2014  | Annual       | 4/17/2015  | 11210140001   |
| Mini-Circuits   | TVA-11-422        | RF Power Amp                           | N/A        |              |            | QA1303002     |
| Rhode & Schwarz | TS-PR18           | Pre-Amplifier                          | 6/12/2014  | Annual       | 6/12/2015  | 101622        |
| Rohde & Schwarz | ESU26             | EMI Test Receiver (26.5GHz)            | 1/27/2014  | Annual       | 1/27/2015  | 100342        |
| Rohde & Schwarz | ESU40             | EMI Test Receiver (40GHz)              | 5/21/2014  | Annual       | 5/21/2015  | 100348        |
| Schwarzbeck     | UHA 9105          | Dipole Antenna (400 - 1GHz) Rx         | 11/21/2013 | Biennial     | 11/21/2015 | 9105-2404     |
| Sunol           | JB5               | Bi-Log Antenna (30M - 5GHz)            | 1/28/2014  | Biennial     | 1/28/2016  | A051107       |
| VWR             | 62344-734         | Thermometer with Clock                 | 2/20/2014  | Biennial     | 2/20/2016  | 140140336     |

**Table 4-1. Test Equipment**

### Notes:

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

|                                      |                                                                                                                                                                                                                                                     |                               |  |                                 |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------|
| FCC ID: A3LSMN910P                   |  <b>FCC Pt. 22 LTE MEASUREMENT REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b>  |                               |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                                                                                                                                                                                     | EUT Type:<br>Portable Handset |  | Page 8 of 25                    |

## 5.0 SAMPLE CALCULATIONS

### Emission Designator

#### QPSK Modulation

**Emission Designator = 8M62G7D**

LTE BW = 8.62 MHz  
 G = Phase Modulation  
 7 = Quantized/Digital Info  
 D = Data transmission, telemetry, telecommand

#### 16QAM Modulation

**Emission Designator = 8M45W7D**

LTE BW = 8.45 MHz  
 W = Amplitude/Angle Modulated  
 7 = Quantized/Digital Info  
 D = Data transmission, telemetry, telecommand

### Spurious Radiated Emission – LTE Band

#### **Example: Middle Channel LTE Mode 2<sup>nd</sup> Harmonic (1564 MHz)**

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 9 of 25                    |

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Samsung Electronics, Co. Ltd.  
 FCC ID: A3LSMN910P  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): LTE

| FCC Part Section(s)                 | Test Description                   | Test Limit                                                                           | Test Condition | Result | Reference              |
|-------------------------------------|------------------------------------|--------------------------------------------------------------------------------------|----------------|--------|------------------------|
| <b><u>TRANSMITTER MODE (TX)</u></b> |                                    |                                                                                      |                |        |                        |
| 2.1049                              | Occupied Bandwidth                 | N/A                                                                                  | CONDUCTED      | PASS   | Section 6.2            |
| 2.1051 22.917(a)                    | Out of Band Emissions              | $> 43 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions |                | PASS   | Section 6.3, 6.4       |
| 2.1046                              | Transmitter Conducted Output Power | N/A                                                                                  |                | PASS   | See RF Exposure Report |
| 22.913(a.2)                         | Effective Radiated Power (Band 26) | $< 7$ Watts max. ERP                                                                 | RADIATED       | PASS   | Section 6.5            |
| 2.1053 22.917(a)                    | Undesirable Emissions              | $> 43 + 10\log_{10}(P[\text{Watts}])$ for all out-of-band emissions                  |                | PASS   | Section 6.6            |

**Table 6-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots (Sections 6.2, 6.3, 6.4) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation", Version 2.8.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     | Page 10 of 25                                                                         |                                 |

## 6.2 Occupied Bandwidth

### §2.1049

#### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### Test Procedure Used


KDB 971168 v02r02 – Section 4.2

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 6-1. Test Instrument & Measurement Setup**


#### Test Notes

None.

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 11 of 25                   |



Plot 6-1. Occupied Bandwidth Plot (Band 26 – 15.0MHz QPSK – RB Size 75)



Plot 6-2. Occupied Bandwidth Plot (Band 26 – 15.0MHz 16-QAM – RB Size 75)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 12 of 25                   |

## 6.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a)

### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts.***

### Test Procedure Used


KDB 971168 v02r02 – Section 6.0

### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to at least 10 \* the fundamental frequency (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = max hold
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 6-2. Test Instrument & Measurement Setup**


### Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 13 of 25                   |




Plot 6-3. Conducted Spurious Plot (Band 26 – 15.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 6-4. Conducted Spurious Plot (Band 26 – 15.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 14 of 25                   |




**Plot 6-5. Conducted Spurious Plot (Band 26 – 15.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)**




**Plot 6-6. Conducted Spurious Plot (Band 26 – 15.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)**

|                                             |                                                                                                                                                                                                                                                     |                                      |                                        |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| FCC ID: A3LSMN910P                          |  <b>FCC Pt. 22 LTE MEASUREMENT REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1412012186.A3L | <b>Test Dates:</b><br>12/2 – 12/3/2014                                                                                                                                                                                                              | <b>EUT Type:</b><br>Portable Handset | Page 15 of 25                          |



Plot 6-7. Conducted Spurious Plot (Band 26 – 15.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)



Plot 6-8. Conducted Spurious Plot (Band 26 – 15.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 16 of 25                   |

## 6.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a)

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{\text{Watts}})$ , where  $P$  is the transmitter power in Watts.***

### Test Procedure Used


KDB 971168 v02r02 – Section 6.0

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW  $\geq 1\%$  of the emission bandwidth
4. VBW  $\geq 3 \times$  RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times$  Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 6-3. Test Instrument & Measurement Setup**

### Test Notes

Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 17 of 25                   |



Plot 6-9. Lower Band Edge Plot (Band 26 - 15.0MHz QPSK - RB Size 75)



Plot 6-10. Upper Band Edge Plot (Band 26 - 15.0MHz QPSK - RB Size 75)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 - 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 18 of 25                   |

## 6.5 Radiated Power (ERP)

### §22.913(a.2)

#### Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

#### Test Procedures Used

KDB 971168 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17


#### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq 3 \times$  RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq 2 \times$  span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 19 of 25                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-4. Test Instrument & Measurement Setup**

## Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The “H” positioning is defined with the EUT lying flat on the test surface, the “H2” positioning is defined with the EUT standing up on its side, and the “V” positioning is defined with the EUT standing upright. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) The battery used with this device for testing (Model: EB-BN910BBU) contains an embedded NFC antenna.

| Frequency [MHz] | Channel Bandwidth [MHz] | Mod.   | Battery Cover | RB Size/Offset | Substitute Level [dBm] | Ant. Gain [dBd] | Ant. Pol. [H/V] | ERP [dBm] | ERP [Watts] | Margin [dB] |
|-----------------|-------------------------|--------|---------------|----------------|------------------------|-----------------|-----------------|-----------|-------------|-------------|
| 831.50          | 15                      | QPSK   | Standard      | 1 / 0          | 13.07                  | 3.01            | V               | 16.08     | 38.451      | -22.37      |
| 836.50          | 15                      | QPSK   | Standard      | 1 / 0          | 12.98                  | 3.04            | V               | 16.02     | 38.451      | -22.43      |
| 841.50          | 15                      | QPSK   | Standard      | 1 / 0          | 12.53                  | 3.07            | V               | 15.60     | 38.451      | -22.85      |
| 831.50          | 15                      | 16-QAM | Standard      | 1 / 0          | 11.98                  | 3.01            | V               | 14.99     | 38.451      | -23.46      |
| 836.50          | 15                      | 16-QAM | Standard      | 1 / 0          | 11.83                  | 3.04            | V               | 14.87     | 38.451      | -23.58      |
| 841.50          | 15                      | 16-QAM | Standard      | 1 / 0          | 11.35                  | 3.07            | V               | 14.42     | 38.451      | -24.03      |
| 831.50          | 15                      | QPSK   | WCC           | 1 / 0          | 11.26                  | 3.01            | V               | 14.27     | 38.451      | -24.18      |

**Table 6-2. ERP Data (Band 26)**

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 20 of 25                   |

## 6.6 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a)

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 v02r02 – Section 5.8


ANSI/TIA-603-C-2004 – Section 2.2.12

### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq 2 \times$  span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-5. Test Instrument & Measurement Setup**

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSMN910P                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014               | EUT Type:<br>Portable Handset                                     |                | Page 21 of 25                   |

## Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The “H” positioning is defined with the EUT lying flat on the test surface, the “H2” positioning is defined with the EUT standing up on its side, and the “V” positioning is defined with the EUT standing upright. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) The battery used with this device for testing (Model: EB-BN910BBU) contains an embedded NFC antenna.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

OPERATING FREQUENCY: 831.50 MHz  
 CHANNEL: 26865  
 MEASURED OUTPUT POWER: 16.08 dBm = 0.041 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 15.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  29.08 dBc

| Frequency [MHz] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Ant. Pol. [H/V] | [dBc] |
|-----------------|----------------------------------|-------------------------------|-------------------------------|-----------------|-------|
| 1663.00         | -58.05                           | 6.56                          | -51.49                        | H               | 67.6  |
| 2494.50         | -65.18                           | 7.33                          | -57.85                        | H               | 73.9  |
| 3326.00         | -64.83                           | 7.41                          | -57.42                        | H               | 73.5  |

Table 6-3. Radiated Spurious Data (Band 26 – Low Channel)

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 22 of 25                   |

OPERATING FREQUENCY: 836.50 MHz  
 CHANNEL: 26915  
 MEASURED OUTPUT POWER: 16.02 dBm = 0.040 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 15.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  29.02 dBc

| Frequency [MHz] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | Ant. Pol. [H/V] | [dBc] |
|-----------------|----------------------------------|-------------------------------|-------------------------------|-----------------|-------|
| 1673.00         | -56.70                           | 6.55                          | -50.15                        | H               | 66.2  |
| 2509.50         | -64.36                           | 7.34                          | -57.02                        | H               | 73.0  |
| 3346.00         | -64.19                           | 7.44                          | -56.76                        | H               | 72.8  |

Table 6-4. Radiated Spurious Data (Band 26 – Mid Channel)

OPERATING FREQUENCY: 841.50 MHz  
 CHANNEL: 26965  
 MEASURED OUTPUT POWER: 15.60 dBm = 0.036 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 15.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  28.60 dBc

| Frequency [MHz] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | Ant. Pol. [H/V] | [dBc] |
|-----------------|----------------------------------|-------------------------------|-------------------------------|-----------------|-------|
| 1683.00         | -56.31                           | 6.55                          | -49.76                        | H               | 65.4  |
| 2524.50         | -64.43                           | 7.35                          | -57.08                        | H               | 72.7  |
| 3366.00         | -64.32                           | 7.47                          | -56.85                        | H               | 72.5  |

Table 6-5. Radiated Spurious Data (Band 26 – High Channel)

OPERATING FREQUENCY: 831.50 MHz  
 CHANNEL: 26865  
 MEASURED OUTPUT POWER: 14.27 dBm = 0.027 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 15.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  27.27 dBc

| Frequency [MHz] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBd] | Spurious Emission Level [dBm] | Ant. Pol. [H/V] | [dBc] |
|-----------------|----------------------------------|-------------------------------|-------------------------------|-----------------|-------|
| 1663.00         | -70.22                           | 6.56                          | -63.66                        | H               | 77.9  |
| 2494.50         | -69.59                           | 7.33                          | -62.26                        | H               | 76.5  |
| 3326.00         | -65.89                           | 7.41                          | -58.48                        | H               | 72.8  |

Table 6-6. Radiated Spurious Data with WCC (Band 26 – Low Channel)

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 24 of 25                   |

## 7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMN910P** complies with all the requirements of Parts 22 of the FCC rules for LTE operation only.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN910P                   |  | FCC Pt. 22 LTE MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1412012186.A3L | Test Dates:<br>12/2 – 12/3/2014                                                     | EUT Type:<br>Portable Handset                                     |                                                                                       | Page 25 of 25                   |