



FCC 47 CFR PART 15 SUBPART E

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac, ANT+ and NFC

MODEL NUMBER : SM-N9200

FCC ID: A3LSMN9200

REPORT NUMBER: 15K21157-E4

ISSUE DATE: JUL 10, 2015

Prepared for

**SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 443-742, KOREA**

Prepared by

**UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-823, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433**



Revision History

Rev.	Issue Date	Revisions	Revised By
--	07/07/15	Initial issue	Junwhan Lee
A	07/09/15	Update version of ANSI C63.10	CY Choi
B	07/10/15	Update section 5.2	CY Choi

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	7
2. TEST METHODOLOGY	8
3. FACILITIES AND ACCREDITATION	8
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. SAMPLE CALCULATION	8
4.3. MEASUREMENT UNCERTAINTY	9
5. EQUIPMENT UNDER TEST	10
5.1. DESCRIPTION OF EUT	10
5.2. MAXIMUM OUTPUT POWER.....	11
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	12
5.4. List of test reduction and modes covering other modes:	12
5.5. WORST-CASE CONFIGURATION AND MODE.....	14
5.6. DESCRIPTION OF TEST SETUP.....	15
6. TEST AND MEASUREMENT EQUIPMENT	17
7. SUMMARY TABLE	18
8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	19
8.1. ON TIME AND DUTY CYCLE RESULTS.....	19
8.2. DUTY CYCLE PLOTS	19
9. MEASUREMENT METHOD.....	22
10. ANTENNA PORT TEST RESULTS	23
10.1. 6 dB BANDWIDTH	23
10.1.1. 802.11a MODE IN THE 5.8 GHz BAND	24
10.1.2. 802.11n HT20 MODE IN THE 5.8 GHz BAND	24
10.1.3. 802.11n HT40 MODE IN THE 5.8 GHz BAND	24
10.1.4. 802.11n VHT80 MODE IN THE 5.8 GHz BAND.....	24
10.1.5. 6 dB BANDWIDTH PLOTS	25
10.2. 26 dB BANDWIDTH	31
10.2.1. 802.11a MODE IN THE 5.2 GHz BAND	31
10.2.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND	31
10.2.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND	31
10.2.4. 802.11ac VHT80 MODE IN THE 5.2 GHz BAND	31
10.2.5. 802.11a MODE IN THE 5.3 GHz BAND	32

10.2.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	32
10.2.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	32
10.2.8.	802.11ac VHT80 MODE IN THE 5.3 GHz BAND	32
10.2.9.	802.11a MODE IN THE 5.5 GHz BAND	33
10.2.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	33
10.2.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	33
10.2.12.	802.11ac VHT80 MODE IN THE 5.5 GHz BAND	33
10.2.13.	802.11a MODE IN THE 5.8 GHz BAND	34
10.2.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	34
10.2.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	34
10.2.16.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND	34
10.2.17.	26 dB BANDWIDTH PLOTS	35
10.3.	99% BANDWIDTH	49
10.3.1.	802.11a MODE IN THE 5.2 GHz BAND	49
10.3.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	49
10.3.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	49
10.3.4.	802.11ac VHT80 MODE IN THE 5.2 GHz BAND	49
10.3.5.	802.11a MODE IN THE 5.3 GHz BAND	50
10.3.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	50
10.3.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	50
10.3.8.	802.11ac VHT80 MODE IN THE 5.3 GHz BAND	50
10.3.9.	802.11a MODE IN THE 5.5 GHz BAND	51
10.3.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	51
10.3.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	51
10.3.12.	802.11ac VHT80 MODE IN THE 5.5 GHz BAND	51
10.3.13.	802.11a MODE IN THE 5.8 GHz BAND	52
10.3.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	52
10.3.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	52
10.3.16.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND	52
10.3.17.	99% BANDWIDTH PLOTS	53
10.4.	AVERAGE POWER	67
10.4.1.	802.11a MODE IN THE 5.2 GHz BAND	67
10.4.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	67
10.4.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	67
10.4.4.	802.11ac VHT80 MODE IN THE 5.2 GHz BAND	68
10.4.5.	802.11a MODE IN THE 5.3 GHz BAND	68
10.4.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	68
10.4.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	68
10.4.8.	802.11ac VHT80 MODE IN THE 5.3 GHz BAND	68
10.4.9.	802.11a MODE IN THE 5.5 GHz BAND	69
10.4.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	69
10.4.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	69
10.4.12.	802.11ac VHT80 MODE IN THE 5.5 GHz BAND	69
10.4.13.	802.11a MODE IN THE 5.8 GHz BAND	70
10.4.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	70
10.4.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	70
10.4.16.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND	70
10.5.	OUTPUT POWER AND PPSD	71
10.5.1.	802.11a MODE IN THE 5.2 GHz BAND	72

10.5.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	73
10.5.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	74
10.5.4.	802.11ac HT80 MODE IN THE 5.2 GHz BAND	75
10.5.5.	802.11a MODE IN THE 5.3 GHz BAND.....	76
10.5.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	77
10.5.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	78
10.5.8.	802.11ac HT80 MODE IN THE 5.3 GHz BAND	79
10.5.9.	802.11a MODE IN THE 5.5 GHz BAND.....	80
10.5.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	81
10.5.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	82
10.5.12.	802.11ac HT80 MODE IN THE 5.5 GHz BAND	83
10.5.13.	802.11a MODE IN THE 5.8 GHz BAND.....	84
10.5.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	85
10.5.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	86
10.5.16.	802.11ac HT80 MODE IN THE 5.8 GHz BAND	87
10.5.17.	802.11a MODE AT STRADDLE CHANNEL	88
10.5.18.	802.11n HT20 MODE AT STRADDLE CHANNEL	89
10.5.19.	802.11n HT40 MODE AT STRADDLE CHANNEL	90
10.5.20.	802.11ac VHT80 MODE AT STRADDLE CHANNEL	91
10.5.21.	OUTPUT POWER AND PPSD PLOTS.....	92
11.	TRANSMITTER ABOVE 1 GHz.....	106
11.1.	5.2 GHz.....	107
11.1.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.2 GHz BAND	107
11.1.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.2 GHz BAND.....	115
11.1.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.2 GHz BAND.....	123
11.1.4.	TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.2 GHz BAND	129
11.2.	5.3 GHz.....	133
11.2.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.3 GHz BAND	133
11.2.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.3 GHz BAND.....	141
11.2.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.3 GHz BAND.....	149
11.2.4.	TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.3 GHz BAND.....	155
11.3.	5.5-5.6 GHz.....	159
11.3.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.5 GHz BAND	159
11.3.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.5 GHz BAND.....	169
11.3.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.5 GHz BAND.....	179
11.3.4.	TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.5 GHz BAND	189
11.4.	5.8 GHz.....	196
11.4.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.8 GHz BAND	196
11.4.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.8 GHz BAND.....	208
11.4.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.8 GHz BAND.....	220
11.4.4.	TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.8 GHz BAND.....	230
12.	WORST-CASE BELOW 1 GHz (in the 5.3 GHz Band).....	236
13.	AC POWER LINE CONDUCTED EMISSIONS.....	238
14.	DYNAMIC FREQUENCY SELECTION.....	243

14.1.	OVERVIEW.....	243
14.1.1.	LIMITS.....	243
14.1.1.	TEST AND MEASUREMENT SYSTEM.....	247
14.1.2.	SETUP OF EUT.....	250
14.1.3.	DESCRIPTION OF EUT	251
14.2.	RESULTS FOR 20 MHz BANDWIDTH.....	252
14.2.1.	TEST CHANNEL	252
14.2.2.	RADAR WAVEFORM AND TRAFFIC.....	252
14.2.3.	OVERLAPPING CHANNEL TESTS.....	254
14.2.4.	MOVE AND CLOSING TIME	254
14.3.	RESULTS FOR 40 MHz BANDWIDTH.....	257
14.3.1.	TEST CHANNEL	257
14.3.2.	RADAR WAVEFORM AND TRAFFIC.....	257
14.3.3.	OVERLAPPING CHANNEL TESTS.....	259
14.3.4.	MOVE AND CLOSING TIME	259
14.4.	RESULTS FOR 80 MHz BANDWIDTH.....	262
14.4.1.	TEST CHANNEL	262
14.4.2.	RADAR WAVEFORM AND TRAFFIC.....	262
14.4.3.	OVERLAPPING CHANNEL TESTS.....	264
14.4.4.	MOVE AND CLOSING TIME	264
15.	SETUP PHOTOS.....	267

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac, ANT+ and NFC
MODEL NUMBER: SM-N9200
SERIAL NUMBER: R38G5101T0T (RADIATED); R38G5101SXX (CONDUCTED)
DATE TESTED: JUN 17 - JUL 09, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, FCC 06-96, FCC KDB 789033 D02 v01, ANSI C63.10-2009.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-823, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☒	Chamber 1
☒	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned}\text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m}\end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone+BT/BLE, DTS/UNII a/b/g/n/ac, ANT+ and NFC.
This test report addresses the NII (UNII) operational mode.

WiFi MIMO Condition

Frequency	Mode	Antenna 1	Antenna 2
2.4 GHz	802.11b	TX / RX	TX / RX
	802.11g	TX / RX	TX / RX
	802.11n	TX / RX	TX / RX
	802.11n MIMO	TX / RX	TX / RX
5 GHz	802.11a	TX / RX	TX / RX
	802.11n	TX / RX	TX / RX
	802.11ac	TX / RX	TX / RX
	802.11n/ac MIMO	TX / RX	TX / RX

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted average output power as follows:

Frequency Range [MHz]	Mode	Output Power [dBm]		Output Power [mW]	
		Antenna1	Antenna2	Antenna1	Antenna2
5180 - 5240	802.11a SISO	8.03	7.70	6.35	5.89
	802.11a MIMO	10.88		12.24	
	802.11n HT20 SISO	8.02	7.90	6.34	6.17
	802.11n HT20 MIMO	10.97		12.50	
5190 - 5230	802.11n HT40 SISO	8.14	8.29	6.52	6.75
	802.11n HT40 MIMO	11.23		13.26	
5210	802.11ac VHT80 SISO	7.79	8.12	6.01	6.49
	802.11ac VHT80 MIMO	10.97		12.50	
5260 - 5320	802.11a SISO	8.18	7.59	6.58	5.74
	802.11a MIMO	10.91		12.32	
	802.11n HT20 SISO	7.99	7.73	6.30	5.93
	802.11n HT20 MIMO	10.87		12.22	
5270 - 5310	802.11n HT40 SISO	8.26	7.97	6.70	6.27
	802.11n HT40 MIMO	11.13		12.96	
5290	802.11ac VHT80 SISO	7.87	7.80	6.12	6.03
	802.11ac VHT80 MIMO	10.85		12.15	
5500 - 5720	802.11a SISO	7.43	7.94	5.53	6.22
	802.11a MIMO	10.70		11.76	
	802.11n HT20 SISO	7.43	7.94	5.53	6.22
	802.11n HT20 MIMO	10.70		11.76	
5510 - 5710	802.11n HT40 SISO	7.47	7.93	5.58	6.21
	802.11n HT40 MIMO	10.72		11.79	
5530 - 5690	802.11ac VHT80 SISO	7.04	7.83	5.06	6.07
	802.11ac VHT80 MIMO	10.46		11.13	
5745 - 5825	802.11a SISO	7.71	8.42	5.90	6.95
	802.11a MIMO	11.09		12.85	
	802.11n HT20 SISO	7.75	8.39	5.96	6.90
	802.11n HT20 MIMO	11.09		12.86	
5755 - 5795	802.11n HT40 SISO	7.78	8.46	6.00	7.01
	802.11n HT40 MIMO	11.14		13.01	
5775	802.11ac VHT80 SISO	7.32	8.18	5.40	6.58
	802.11ac VHT80 MIMO	10.78		11.97	

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of:

Frequency Range [MHz]		Antenna Gain [dBi]	
		Antenna 1	Antenna 2
UNII 1 5150 – 5250	5150	-6.69	-6.00
	5250	-5.21	-7.00
UNII 2A 5250 – 5350	5250	-5.21	-7.00
	5350	-5.83	-6.60
UNII 2C 5470 – 5725	5500	-4.65	-7.84
	5725	-5.24	-7.11
UNII 3 5725 – 5825	5725	-5.24	-7.11
	5775	-4.69	-5.12
	5825	-4.60	-6.75

5.4. List of test reduction and modes covering other modes:

The output power on covered modes is equal to or less than one referenced.

UNII 1

5150 - 5250 MHz Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
5180 - 5240	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5180 - 5240	802.11HT20 1TX	802.11n HT20 2TX CDD
5180 - 5240	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5190 - 5230	802.11n HT40 1TX	802.11n HT40 2TX CDD
5190 - 5230	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5210	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5210	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

UNII 2A

5250 - 5350 MHz Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
5260 - 5320	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5260 - 5320	802.11HT20 1TX	802.11n HT20 2TX CDD
5260 - 5320	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5270 - 5310	802.11n HT40 1TX	802.11n HT40 2TX CDD
5270 - 5310	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5290	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5290	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

UNII 2C

5470 - 5725 MHz Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
5500 - 5720	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5500 - 5720	802.11HT20 1TX	802.11n HT20 2TX CDD
5500 - 5720	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5510 - 5710	802.11n HT40 1TX	802.11n HT40 2TX CDD
5510 - 5710	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5530 - 5690	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5530 - 5690	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

UNII 3

5725 - 5850 MHz Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
5745 - 5825	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5745 - 5825	802.11HT20 1TX	802.11n HT20 2TX CDD
5745 - 5825	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5755 - 5795	802.11n HT40 1TX	802.11n HT40 2TX CDD
5755 - 5795	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5775	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5775	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that the Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in the Z orientation.

Based on the baseline scan, the worst-case data rates were:

802.11a mode: 6 Mbps
802.11n HT20mode: MCS0
802.11n HT40mode: MCS0
802.11ac VHT80mode: MCS0

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA20CBC	R37FCPc00R1DK3	N/A
Data Cable	SAMSUNG	EP-DG925UWE	N/A	N/A
Earphone	SAMSUNG	EO-EG920LW	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A
2	Audio	1	Mini-Jack	Unshielded	1.0m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	950	11-17-15
Antenna, Horn, 18 GHz	ETS	3115	00167211	09-20-15
Antenna, Horn, 40 GHz	ETS	3116C	00166255	09-23-15
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	09-29-15
Preamplifier, 1000 MHz	Sonoma	310N	341282	11-17-15
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	11-18-15
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	09-23-15
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	11-17-15
Average Power Sensor	R&S	NRZ-Z91	102681	11-17-15
Average Power Sensor	Agilent / HP	U2000	MY54270007	09-23-15
EMI Test Receive, 40 GHz	R&S	ESU40	100439	11-17-15
EMI Test Receive, 3 GHz	R&S	ESR3	101832	11-17-15
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	009	11-17-15
High Pass Filter 5GHz	Micro-Tronics	HPS17542	009	11-17-15
High Pass Filter 6GHz	Micro-Tronics	HPM17543	010	11-17-15
LISN	R&S	ENV-216	101836	04-09-16
LISN	R&S	ENV-216	101837	04-09-16

7. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.407 (a)	Occupied Band width (26dB)	N/A	Conducted	Pass	81.90 MHz
15.407	6dB Band width (5.8Ghz)	500KHz		Pass	2.65 MHz (Straddle)
15.407 (a)(2)	TX Cond. Power 5.15-2.25, 5.25-5.35 & 5.47-5.725	<24dBm or 11+10Log(OBW)		Pass	11.14 dBm
15.407 (a)(3)	TX Cond. Power 5.725-5.825	< 30dBm or 17+10Log(OBW)		Pass	11.47 dBm
15.407 (a)(5)	PSD (5.2,5.3,5.5GHz)	<11dBm		Pass	-1.62 dBm
15.407 (a)(5)	PSD (5.8GHz)	30dBm per 500kHz		Pass	-1.42 dBm
15.207 (a)	AC Power Line conducted emissions	Section 10	Radiated	Pass	42.72 dBuV (QP)
15.407 (b) & 15.209	Radiated Spurious Emission	< 54dBuV/m		Pass	53.51dBuV/m (AV)
15.407 (h)(2)	Dynamic Frequency Selection	N/A	Radiated / Conducted	Pass	N/A

8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.


PROCEDURE



KDB 789033 Zero-Span Spectrum Analyzer Method.


8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
802.11a	1.428	1.529	0.934	93.4%	0.30	0.700
802.11n HT20	1.335	1.437	0.929	92.9%	0.32	0.749
802.11n HT40	0.664	0.765	0.868	86.8%	0.62	1.506
802.11ac VHT80	0.332	0.433	0.766	76.6%	1.16	3.013

8.2. DUTY CYCLE PLOTS







9. MEASUREMENT METHOD

KDB 789033 D02 General UNII Test Procedures New Rules v01
KDB 905462 D03 Clients Without Radar Detection New Rules v01r01

The Duty Cycle is less than 98% and consistent therefore KDB 789033 Method SA-2 is used for power and PPSD

The Duty Cycle is less than 98% and consistent, KDB 789033 Method AD with Power RMS Averaging and duty cycle correction is used.

MIMO Device: KDB 662911 v02r01

Straddle Channels: KDB 644545 D03 v01

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.407

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

Reference to 789033 D02 General UNII Test Procedures New Rules v01: The transmitter output is connected to a spectrum analyzer with the RBW set to 100 kHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

- Calculation for 6dB Bandwidth of UNII-3 Straddle Channel

ex) 802.11a mode

- o Fundamental frequency : 5720 MHz
- o 6dB BW : 16.350 MHz
- o Starting Frequency of UNII-3 band : 5725 MHz
- o 6dB Bandwidth of UNII-3 band Portion
 $= (5720 + (16.350 / 2) - 5725) = 3.175 \text{ MHz}$

10.1.1. 802.11a MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Primary	Secondary	
Straddle	5720	3.175	3.175	0.5
Low	5745	16.350	16.400	0.5
Mid	5785	16.350	16.350	0.5
High	5825	16.350	16.425	0.5
Worst		3.175		

10.1.2. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Straddle	5720	3.800	3.813	0.5
Low	5745	17.600	17.625	0.5
Mid	5785	17.625	17.650	0.5
High	5825	17.625	17.600	0.5
Worst		3.800		

10.1.3. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Straddle	5710	3.200	3.200	0.5
Low	5765	36.150	36.850	0.5
High	5795	36.400	36.450	0.5
Worst		3.200		


10.1.4. 802.11n VHT80 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Straddle	5690	2.650	2.650	0.5
Middle	5775	75.500	75.300	0.5
Worst		2.650		


10.1.5. 6 dB BANDWIDTH PLOTS

IEEE 802.11a mode


11a Mode Straddle Channel Primary




11a Mode Straddle Channel Secondary







11a Mode Low Channel Primary




11a Mode Low Channel Secondary






IEEE 802.11n HT20 mode


11n HT20 Mode Straddle Channel Chain 0




11n HT20 Mode Straddle Channel Chain 1







11n HT20 Mode Low Channel Chain 0




11n HT20 Mode Low Channel Chain 1






IEEE 802.11n HT40 mode


11n HT40 Mode Straddle Channel Chain 0




11n HT40 Mode Straddle Channel Chain 1




11n HT40 Mode Low Channel Chain 0




11n HT40 Mode Low Channel Chain 1



11n HT40 Mode High Channel Chain 0




11n HT40 Mode High Channel Chain 1




IEEE 802.11ac VHT80 mode


11ac HT80 Mode Middle Channel Chain 0




11ac HT80 Mode Middle Channel Chain 1



11ac HT80 Mode Middle Channel Chain 0



11ac HT80 Mode Middle Channel Chain 1



10.2. 26 dB BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

10.2.1. 802.11a MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Primary	Secondary
Low	5180	21.20	21.20
Mid	5200	21.16	21.16
High	5240	21.08	21.20
Worst		21.20	

10.2.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5180	21.64	21.68
Mid	5200	21.56	21.44
High	5240	21.76	21.52
Worst		21.76	

10.2.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5190	40.20	39.36
High	5230	39.96	39.48
Worst		40.20	

10.2.4. 802.11ac VHT80 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Middle	5210	81.50	81.20
Worst		81.50	

10.2.5. 802.11a MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Primary	Secondary
Low	5260	21.20	21.16
Mid	5300	21.20	21.16
High	5320	21.12	21.12
Worst		21.20	

10.2.6. 802.11n HT20 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5260	21.64	21.40
Mid	5300	21.56	21.32
High	5320	21.56	21.44
Worst		21.64	

10.2.7. 802.11n HT40 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5270	40.02	39.54
High	5310	40.02	39.54
Worst		40.02	

10.2.8. 802.11ac VHT80 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Middle	5290	81.90	81.20
Worst		81.90	

10.2.9. 802.11a MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Primary	Secondary
Low	5500	21.20	21.36
Mid	5580	21.24	21.20
High	5700	21.20	21.28
Straddle	5720	15.58	15.58
Worst		21.36	

10.2.10. 802.11n HT20 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5500	21.64	21.40
Mid	5580	21.64	21.68
High	5700	21.68	21.48
Straddle	5720	15.82	15.78
Worst		21.68	

10.2.11. 802.11n HT40 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5510	39.78	39.60
Mid	5550	39.96	39.48
High	5670	39.90	39.54
Straddle	5710	34.98	34.74
Worst		39.96	

10.2.12. 802.11ac VHT80 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5530	81.70	81.10
High	5610	81.40	81.20
Straddle	5690	75.95	75.55
Worst		81.70	

10.2.13. 802.11a MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Primary	Secondary
Straddle	5720	5.58	5.58
Low	5745	21.16	21.20
Mid	5785	21.20	21.28
High	5825	21.16	21.12
Worst		21.28	

10.2.14. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Straddle	5720	5.82	5.78
Low	5745	21.64	21.56
Mid	5785	21.52	21.56
High	5825	21.60	21.40
Worst		21.64	

10.2.15. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Straddle	5710	4.98	4.74
Low	5755	40.02	39.54
High	5795	40.02	39.48
Worst		40.02	

10.2.16. 802.11ac VHT80 MODE IN THE 5.8 GHz BAND


Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Straddle	5690	5.95	5.55
Middle	5775	81.60	81.00
Worst		81.60	

10.2.17. 26 dB BANDWIDTH PLOTS


UNII 5.2 GHz IEEE 802.11a mode




UNII 5.2 GHz IEEE 802.11n HT20 mode




UNII 5.2 GHz IEEE 802.11n HT40 mode



UNII 5.2 GHz IEEE 802.11ac VHT80 mode




UNII 5.3 GHz IEEE 802.11a mode




UNII 5.3 GHz IEEE 802.11n HT20 mode




UNII 5.3 GHz IEEE 802.11n HT40 mode




UNII 5.3 GHz IEEE 802.11ac VHT80 mode



UNII 5.5 GHz IEEE 802.11a mode



11a Mode Straddle Channel Primary



11a Mode Straddle Channel Secondary




UNII 5.5 GHz IEEE 802.11n HT20 mode

11n HT20 Mode Low Channel Chain 0




11n HT20 Mode Low Channel Chain 1



11n HT20 Mode Middle Channel Chain 0



11n HT20 Mode Middle Channel Chain 1



11n HT20 Mode High Channel Chain 0




11n HT20 Mode High Channel Chain 1



11n HT20 Mode Straddle Channel Chain 0



11n HT20 Mode Straddle Channel Chain 1




UNII 5.5 GHz IEEE 802.11n HT40 mode

11n HT40 Mode Low Channel Chain 0




11n HT40 Mode Low Channel Chain 1



11n HT40 Mode Middle Channel Chain 0




11n HT40 Mode Middle Channel Chain 1



11n HT40 Mode High Channel Chain 0




11n HT40 Mode High Channel Chain 1




11n HT40 Mode Straddle Channel Chain 0



11n HT40 Mode Straddle Channel Chain 1



UNII 5.5 GHz IEEE 802.11ac VHT80 mode




UNII 5.8 GHz IEEE 802.11a mode




UNII 5.8 GHz IEEE 802.11n HT20 mode



UNII 5.8 GHz IEEE 802.11n HT40 mode



UNII 5.8 GHz IEEE 802.11ac VHT80 mode



10.3. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

10.3.1. 802.11a MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Primary	Secondary
Low	5180	16.525	16.607
Mid	5200	16.343	16.400
High	5240	16.603	16.513
Worst		16.607	

10.3.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5180	17.617	17.574
Mid	5200	17.639	17.763
High	5240	17.640	17.721
Worst		17.763	

10.3.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5190	36.103	36.198
High	5230	35.943	36.224
Worst		36.224	

10.3.4. 802.11ac VHT80 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Middle	5210	75.875	74.987
Worst		75.875	

10.3.5. 802.11a MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Primary	Secondary
Low	5260	16.506	16.492
Mid	5300	16.612	16.470
High	5320	16.574	16.472
Worst		16.612	

10.3.6. 802.11n HT20 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5260	17.690	17.766
Mid	5300	17.658	17.717
High	5320	17.690	17.697
Worst		17.766	

10.3.7. 802.11n HT40 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5270	36.153	36.317
High	5310	36.170	36.029
Worst		36.317	

10.3.8. 802.11ac VHT80 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Middle	5290	75.341	75.339
Worst		75.341	

10.3.9. 802.11a MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Primary	Secondary
Low	5500	16.490	16.548
Mid	5580	16.533	16.427
High	5700	16.528	16.504
Straddle	5720	13.171	13.221
Worst		16.548	

10.3.10. 802.11n HT20 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5500	17.696	17.689
Mid	5580	17.708	17.698
High	5700	17.711	17.695
Straddle	5720	13.802	13.829
Worst		17.711	

10.3.11. 802.11n HT40 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5510	36.199	36.126
Mid	5550	36.110	36.282
High	5670	35.945	36.089
Straddle	5710	33.190	33.081
Worst		36.282	

10.3.12. 802.11ac VHT80 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5530	75.492	75.413
High	5610	75.471	75.306
Straddle	5690	72.839	72.653
Worst		75.492	

10.3.13. 802.11a MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Primary	Secondary
Straddle	5720	3.271	3.221
Low	5745	16.487	16.566
Mid	5785	16.653	16.577
High	5825	16.531	16.370
Worst		16.653	

10.3.14. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Straddle	5720	3.801	3.828
Low	5745	17.569	17.667
Mid	5785	17.721	17.693
High	5825	17.637	17.659
Worst		17.721	

10.3.15. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Straddle	5710	3.190	3.081
Low	5755	36.185	36.128
High	5795	36.033	36.182
Worst		36.185	

10.3.16. 802.11ac VHT80 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Straddle	5690	2.838	2.653
Middle	5775	75.795	75.553
Worst		75.795	