

LTE

Band 25

3MHz

QPSK

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Samsung

Project #:

15K21157

Date:

06-24-15

Test Engineer:

Steven.Kim

Configuration:

EUT / X-Position

Mode:

LTE Band 25 QPSK, 3MHz

Test Equipment:

Receiving: 3117[00168724] and Chamber 1 SMA Cables

Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
Low Ch								
1851.50	0.78	V	1.60	9.12	8.30	33.0	-24.7	
1851.50	-0.55	H	1.60	9.12	6.97	33.0	-26.0	
Mid Ch								
1882.50	1.09	V	1.62	8.62	8.09	33.0	-24.9	
1882.50	-3.53	H	1.62	8.62	3.47	33.0	-29.5	
High Ch								
1913.50	-3.98	V	1.63	8.45	2.84	33.0	-30.2	
1913.50	-4.40	H	1.63	8.45	2.42	33.0	-30.6	

Rev. 3.17.11

Note: For Band 4 EIRP limit is 30dBm

LTE

Band 25

3MHz

16QAM

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Samsung

Project #:

15K21157

Date:

06-24-15

Test Engineer:

Steven.Kim

Configuration:

EUT / X-Position

Mode:

LTE Band 25 16QAM, 3MHz

Test Equipment:

Receiving: 3117[00168724] and Chamber 1 SMA Cables

Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
Low Ch								
1851.50	-0.27	V	1.60	9.12	7.25	33.0	-25.8	
1851.50	-1.61	H	1.60	9.12	5.91	33.0	-27.1	
Mid Ch								
1882.50	0.06	V	1.62	8.62	7.06	33.0	-25.9	
1882.50	-4.57	H	1.62	8.62	2.43	33.0	-30.6	
High Ch								
1913.50	-5.04	V	1.63	8.45	1.78	33.0	-31.2	
1913.50	-5.41	H	1.63	8.45	1.41	33.0	-31.6	

Rev. 3.17.11

Note: For Band 4 EIRP limit is 30dBm

LTE Band 25 1.4MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 25 QPSK, 1.4MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1850.70	-1.73	V	1.60	9.12	5.79	33.0	-27.2	
	1850.70	-0.31	H	1.60	9.12	7.21	33.0	-25.8	
	Mid Ch								
	1882.50	-4.01	V	1.62	8.62	2.99	33.0	-30.0	
	1882.50	-3.23	H	1.62	8.62	3.77	33.0	-29.2	
	High Ch								
	1914.30	-7.04	V	1.63	8.44	-0.23	33.0	-33.2	
	1914.30	-7.23	H	1.63	8.44	-0.42	33.0	-33.4	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								
LTE Band 25 1.4MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 25 16QAM, 1.4MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1850.70	-2.70	V	1.60	9.12	4.82	33.0	-28.2	
	1850.70	-1.29	H	1.60	9.12	6.23	33.0	-26.8	
	Mid Ch								
	1882.50	-5.05	V	1.62	8.62	1.95	33.0	-31.0	
	1882.50	-4.26	H	1.62	8.62	2.74	33.0	-30.3	
	High Ch								
	1914.30	-8.10	V	1.63	8.44	-1.29	33.0	-34.3	
	1914.30	-8.26	H	1.63	8.44	-1.45	33.0	-34.4	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								

LTE Band 12

LTE Band 12 10MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: TX, LTE12, 10MHz BW,QPSK Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse. <table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>704.00</td><td>7.15</td><td>V</td><td>1.1</td><td>-1.5</td><td>4.57</td><td>38.5</td><td>-33.9</td></tr><tr><td>704.00</td><td>17.30</td><td>H</td><td>1.1</td><td>-1.5</td><td>14.72</td><td>38.5</td><td>-23.7</td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>707.50</td><td>6.74</td><td>V</td><td>1.1</td><td>-1.4</td><td>4.25</td><td>38.5</td><td>-34.2</td></tr><tr><td>707.50</td><td>17.76</td><td>H</td><td>1.1</td><td>-1.4</td><td>15.27</td><td>38.5</td><td>-23.2</td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>711.00</td><td>6.32</td><td>V</td><td>1.1</td><td>-1.3</td><td>3.93</td><td>38.5</td><td>-34.5</td></tr><tr><td>711.00</td><td>17.31</td><td>H</td><td>1.1</td><td>-1.3</td><td>14.89</td><td>38.5</td><td>-23.6</td></tr></table> Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch								704.00	7.15	V	1.1	-1.5	4.57	38.5	-33.9	704.00	17.30	H	1.1	-1.5	14.72	38.5	-23.7	Mid Ch								707.50	6.74	V	1.1	-1.4	4.25	38.5	-34.2	707.50	17.76	H	1.1	-1.4	15.27	38.5	-23.2	High Ch								711.00	6.32	V	1.1	-1.3	3.93	38.5	-34.5	711.00	17.31	H	1.1	-1.3	14.89	38.5	-23.6
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																	
	Low Ch																																																																																									
	704.00	7.15	V	1.1	-1.5	4.57	38.5	-33.9																																																																																		
	704.00	17.30	H	1.1	-1.5	14.72	38.5	-23.7																																																																																		
	Mid Ch																																																																																									
	707.50	6.74	V	1.1	-1.4	4.25	38.5	-34.2																																																																																		
	707.50	17.76	H	1.1	-1.4	15.27	38.5	-23.2																																																																																		
	High Ch																																																																																									
	711.00	6.32	V	1.1	-1.3	3.93	38.5	-34.5																																																																																		
711.00	17.31	H	1.1	-1.3	14.89	38.5	-23.6																																																																																			
LTE Band 12 10MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: LTE12 10MHz FUND 16QAM Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse. <table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>704.00</td><td>6.11</td><td>V</td><td>1.1</td><td>-1.5</td><td>3.53</td><td>38.5</td><td>-34.9</td></tr><tr><td>704.00</td><td>16.24</td><td>H</td><td>1.1</td><td>-1.5</td><td>13.66</td><td>38.5</td><td>-24.8</td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>707.50</td><td>5.73</td><td>V</td><td>1.1</td><td>-1.4</td><td>3.22</td><td>38.5</td><td>-35.2</td></tr><tr><td>707.50</td><td>16.74</td><td>H</td><td>1.1</td><td>-1.4</td><td>14.23</td><td>38.5</td><td>-24.2</td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>711.00</td><td>5.31</td><td>V</td><td>1.1</td><td>-1.3</td><td>2.89</td><td>38.5</td><td>-35.6</td></tr><tr><td>711.00</td><td>16.31</td><td>H</td><td>1.1</td><td>-1.3</td><td>13.89</td><td>38.5</td><td>-24.6</td></tr></table> Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch								704.00	6.11	V	1.1	-1.5	3.53	38.5	-34.9	704.00	16.24	H	1.1	-1.5	13.66	38.5	-24.8	Mid Ch								707.50	5.73	V	1.1	-1.4	3.22	38.5	-35.2	707.50	16.74	H	1.1	-1.4	14.23	38.5	-24.2	High Ch								711.00	5.31	V	1.1	-1.3	2.89	38.5	-35.6	711.00	16.31	H	1.1	-1.3	13.89	38.5	-24.6
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																	
	Low Ch																																																																																									
	704.00	6.11	V	1.1	-1.5	3.53	38.5	-34.9																																																																																		
	704.00	16.24	H	1.1	-1.5	13.66	38.5	-24.8																																																																																		
	Mid Ch																																																																																									
	707.50	5.73	V	1.1	-1.4	3.22	38.5	-35.2																																																																																		
	707.50	16.74	H	1.1	-1.4	14.23	38.5	-24.2																																																																																		
	High Ch																																																																																									
	711.00	5.31	V	1.1	-1.3	2.89	38.5	-35.6																																																																																		
711.00	16.31	H	1.1	-1.3	13.89	38.5	-24.6																																																																																			

LTE

Band 12

5MHz

QPSK

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Test Equipment:

Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT)

Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
701.50	6.77	V	1.1	-1.5	4.17	38.5	-34.3	
701.50	17.74	H	1.1	-1.5	15.14	38.5	-23.3	
Mid Ch								
707.50	6.40	V	1.1	-1.4	3.91	38.5	-34.5	
707.50	17.44	H	1.1	-1.4	14.95	38.5	-23.5	
High Ch								
713.50	5.41	V	1.6	-1.3	2.53	38.5	-35.9	
713.50	17.16	H	1.6	-1.3	14.28	38.5	-24.2	

Rev. 3.17.11

Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm

LTE

Band 12

5MHz

16QAM

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Test Equipment:

Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT)

Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
701.50	5.86	V	1.1	-1.5	3.26	38.5	-35.2	
701.50	16.71	H	1.1	-1.5	14.11	38.5	-24.3	
Mid Ch								
707.50	5.42	V	1.1	-1.4	2.93	38.5	-35.5	
707.50	16.44	H	1.1	-1.4	13.95	38.5	-24.5	
High Ch								
713.50	4.40	V	1.1	-1.3	2.01	38.5	-36.4	
713.50	16.18	H	1.1	-1.3	13.80	38.5	-24.7	

Rev. 3.17.11

Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm

LTE Band 12 3MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: LTE12 3MHz FUND QPSK								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	700.50	6.81	V	1.1	-1.5	4.21	38.5	-34.2	
	700.50	17.91	H	1.1	-1.5	15.31	38.5	-23.1	
	Mid Ch								
	707.50	6.41	V	1.1	-1.4	3.92	38.5	-34.5	
	707.50	17.54	H	1.1	-1.4	15.05	38.5	-23.4	
	High Ch								
	714.50	5.05	V	1.6	-1.3	2.17	38.5	-36.3	
	714.50	17.11	H	1.6	-1.3	14.23	38.5	-24.2	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									
LTE Band 12 3MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: LTE12 3MHz FUND 16QAM								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	700.50	5.76	V	1.1	-1.5	3.16	38.5	-35.3	
	700.50	16.93	H	1.1	-1.5	14.33	38.5	-24.1	
	Mid Ch								
	707.50	5.42	V	1.1	-1.4	2.93	38.5	-35.5	
	707.50	16.53	H	1.1	-1.4	14.04	38.5	-24.4	
	High Ch								
	714.50	4.00	V	1.1	-1.3	1.62	38.5	-36.8	
	714.50	16.11	H	1.1	-1.3	13.73	38.5	-24.7	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									

LTE Band 12 1.4MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: LTE12 1.4MHz FUND QPSK								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
	Low Ch								
	699.70	4.83	V	1.1	-1.5	2.23	38.5	-36.2	
	699.70	15.75	H	1.1	-1.5	13.15	38.5	-25.3	
	Mid Ch								
	707.50	4.30	V	1.1	-1.4	1.81	38.5	-36.6	
	707.50	15.33	H	1.1	-1.4	12.84	38.5	-25.6	
	High Ch								
	715.30	2.67	V	1.6	-1.3	-0.21	38.5	-38.7	
	715.30	14.94	H	1.6	-1.3	12.06	38.5	-26.4	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									
LTE Band 12 1.4MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: LTE12 1.4MHz FUND 16QAM								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
	Low Ch								
	699.70	3.84	V	1.1	-1.5	1.24	38.5	-37.2	
	699.70	14.71	H	1.1	-1.5	12.11	38.5	-26.3	
	Mid Ch								
	707.50	3.33	V	1.1	-1.4	0.83	38.5	-37.6	
	707.50	14.33	H	1.1	-1.4	11.84	38.5	-26.6	
	High Ch								
	715.30	1.48	V	1.1	-1.3	-0.91	38.5	-39.4	
	715.30	13.95	H	1.1	-1.3	11.57	38.5	-26.9	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									

LTE Band 4

LTE Band 4 20MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, QPSK, 20MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse <table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1720.00</td><td>3.69</td><td>V</td><td>1.54</td><td>9.12</td><td>11.27</td><td>30.0</td><td>-18.7</td></tr><tr><td>1720.00</td><td>12.70</td><td>H</td><td>1.54</td><td>9.12</td><td>20.28</td><td>30.0</td><td>-9.7</td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1732.50</td><td>3.56</td><td>V</td><td>1.55</td><td>9.31</td><td>11.32</td><td>30.0</td><td>-18.7</td></tr><tr><td>1732.50</td><td>12.97</td><td>H</td><td>1.55</td><td>9.31</td><td>20.73</td><td>30.0</td><td>-9.3</td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1745.00</td><td>3.12</td><td>V</td><td>1.56</td><td>9.37</td><td>10.93</td><td>30.0</td><td>-19.1</td></tr><tr><td>1745.00</td><td>11.95</td><td>H</td><td>1.56</td><td>9.37</td><td>19.76</td><td>30.0</td><td>-10.2</td></tr></table> Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch								1720.00	3.69	V	1.54	9.12	11.27	30.0	-18.7	1720.00	12.70	H	1.54	9.12	20.28	30.0	-9.7	Mid Ch								1732.50	3.56	V	1.55	9.31	11.32	30.0	-18.7	1732.50	12.97	H	1.55	9.31	20.73	30.0	-9.3	High Ch								1745.00	3.12	V	1.56	9.37	10.93	30.0	-19.1	1745.00	11.95	H	1.56	9.37	19.76	30.0	-10.2
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																	
	Low Ch																																																																																									
	1720.00	3.69	V	1.54	9.12	11.27	30.0	-18.7																																																																																		
	1720.00	12.70	H	1.54	9.12	20.28	30.0	-9.7																																																																																		
	Mid Ch																																																																																									
	1732.50	3.56	V	1.55	9.31	11.32	30.0	-18.7																																																																																		
	1732.50	12.97	H	1.55	9.31	20.73	30.0	-9.3																																																																																		
	High Ch																																																																																									
	1745.00	3.12	V	1.56	9.37	10.93	30.0	-19.1																																																																																		
1745.00	11.95	H	1.56	9.37	19.76	30.0	-10.2																																																																																			
LTE Band 4 20MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, 16QAM, 20MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse <table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1720.00</td><td>2.67</td><td>V</td><td>1.54</td><td>9.12</td><td>10.25</td><td>30.0</td><td>-19.8</td></tr><tr><td>1720.00</td><td>11.68</td><td>H</td><td>1.54</td><td>9.12</td><td>19.26</td><td>30.0</td><td>-10.7</td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1732.50</td><td>2.57</td><td>V</td><td>1.55</td><td>9.31</td><td>10.33</td><td>30.0</td><td>-19.7</td></tr><tr><td>1732.50</td><td>12.00</td><td>H</td><td>1.55</td><td>9.31</td><td>19.76</td><td>30.0</td><td>-10.2</td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1745.00</td><td>2.11</td><td>V</td><td>1.56</td><td>9.37</td><td>9.92</td><td>30.0</td><td>-20.1</td></tr><tr><td>1745.00</td><td>10.95</td><td>H</td><td>1.56</td><td>9.37</td><td>18.76</td><td>30.0</td><td>-11.2</td></tr></table> Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch								1720.00	2.67	V	1.54	9.12	10.25	30.0	-19.8	1720.00	11.68	H	1.54	9.12	19.26	30.0	-10.7	Mid Ch								1732.50	2.57	V	1.55	9.31	10.33	30.0	-19.7	1732.50	12.00	H	1.55	9.31	19.76	30.0	-10.2	High Ch								1745.00	2.11	V	1.56	9.37	9.92	30.0	-20.1	1745.00	10.95	H	1.56	9.37	18.76	30.0	-11.2
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																	
	Low Ch																																																																																									
	1720.00	2.67	V	1.54	9.12	10.25	30.0	-19.8																																																																																		
	1720.00	11.68	H	1.54	9.12	19.26	30.0	-10.7																																																																																		
	Mid Ch																																																																																									
	1732.50	2.57	V	1.55	9.31	10.33	30.0	-19.7																																																																																		
	1732.50	12.00	H	1.55	9.31	19.76	30.0	-10.2																																																																																		
	High Ch																																																																																									
	1745.00	2.11	V	1.56	9.37	9.92	30.0	-20.1																																																																																		
1745.00	10.95	H	1.56	9.37	18.76	30.0	-11.2																																																																																			

LTE

Band 4

15MHz

QPSK

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Test Equipment:

Receiving: 3117[00168724] and Chamber 1 SMA Cables

Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
1717.50	3.26	V	1.54	9.12	10.84	30.0	-19.2	
1717.50	7.01	H	1.54	9.12	14.59	30.0	-15.4	
Mid Ch								
1732.50	3.26	V	1.55	9.31	11.02	30.0	-19.0	
1732.50	8.91	H	1.55	9.31	16.67	30.0	-13.3	
High Ch								
1747.50	3.21	V	1.56	9.39	11.04	30.0	-19.0	
1747.50	9.11	H	1.56	9.39	16.94	30.0	-13.1	

Rev. 3.17.11

Note: For Band 4 EIRP limit is 30dBm

LTE

Band 4

15MHz

16QAM

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Test Equipment:

Receiving: 3117[00168724] and Chamber 1 SMA Cables

Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
1717.50	2.81	V	1.54	9.12	10.39	30.0	-19.6	
1717.50	5.95	H	1.54	9.12	13.53	30.0	-16.5	
Mid Ch								
1732.50	2.28	V	1.55	9.31	10.04	30.0	-20.0	
1732.50	7.89	H	1.55	9.31	15.65	30.0	-14.4	
High Ch								
1747.50	2.18	V	1.56	9.39	10.01	30.0	-20.0	
1747.50	8.03	H	1.56	9.39	15.86	30.0	-14.1	

Rev. 3.17.11

Note: For Band 4 EIRP limit is 30dBm

LTE Band 4 10MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-23-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, QPSK, 10MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1715.00	5.61	V	1.54	9.12	13.19	30.0	-16.8	
	1715.00	11.69	H	1.54	9.12	19.27	30.0	-10.7	
	Mid Ch								
	1732.50	6.23	V	1.55	9.31	13.99	30.0	-16.0	
	1732.50	12.49	H	1.55	9.31	20.25	30.0	-9.8	
	High Ch								
	1750.00	6.27	V	1.56	9.40	14.11	30.0	-15.9	
	1750.00	11.69	H	1.56	9.40	19.53	30.0	-10.5	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								
LTE Band 4 10MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-23-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4 16QAM, 10MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1715.00	4.60	V	1.54	9.12	12.18	30.0	-17.8	
	1715.00	10.66	H	1.54	9.12	18.24	30.0	-11.8	
	Mid Ch								
	1732.50	5.17	V	1.55	9.31	12.93	30.0	-17.1	
	1732.50	11.83	H	1.55	9.31	19.59	30.0	-10.4	
	High Ch								
	1750.00	5.27	V	1.56	9.40	13.11	30.0	-16.9	
	1750.00	10.62	H	1.56	9.40	18.46	30.0	-11.5	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								

LTE Band 4 5MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-23-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, QPSK , 5MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1712.50	6.89	V	1.54	9.12	14.47	30.0	-15.5	
	1712.50	11.87	H	1.54	9.12	19.45	30.0	-10.6	
	Mid Ch								
	1732.50	6.47	V	1.55	9.31	14.23	30.0	-15.8	
	1732.50	12.59	H	1.55	9.31	20.35	30.0	-9.7	
	High Ch								
	1752.50	5.99	V	1.56	9.39	13.82	30.0	-16.2	
	1752.50	11.89	H	1.56	9.39	19.72	30.0	-10.3	
Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									
LTE Band 4 5MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 15K21157 Date: 06-23-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4 16QAM, 5MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1712.50	5.75	V	1.54	9.12	13.33	30.0	-16.7	
	1712.50	10.81	H	1.54	9.12	18.39	30.0	-11.6	
	Mid Ch								
	1732.50	5.44	V	1.55	9.31	13.20	30.0	-16.8	
	1732.50	11.47	H	1.55	9.31	19.23	30.0	-10.8	
	High Ch								
	1752.50	4.93	V	1.56	9.39	12.76	30.0	-17.2	
	1752.50	10.80	H	1.56	9.39	18.63	30.0	-11.4	
Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									

LTE

Band 4

3MHz

QPSK

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Test Equipment:

Receiving: 3117[00168724] and Chamber 1 SMA Cables

Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
Low Ch								
1711.50	5.73	V	1.54	9.12	13.31	30.0	-16.7	
1711.50	11.88	H	1.54	9.12	19.46	30.0	-10.5	
Mid Ch								
1732.50	8.34	V	1.55	9.31	16.10	30.0	-13.9	
1732.50	12.56	H	1.55	9.31	20.32	30.0	-9.7	
High Ch								
1753.50	5.85	V	1.56	9.38	13.67	30.0	-16.3	
1753.50	12.16	H	1.56	9.38	19.98	30.0	-10.0	

Rev. 3.17.11

Note: For Band 4 EIRP limit is 30dBm

LTE

Band 4

3MHz

16QAM

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Test Equipment:

Receiving: 3117[00168724] and Chamber 1 SMA Cables

Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
Low Ch								
1711.50	4.75	V	1.54	9.12	12.33	30.0	-17.7	
1711.50	10.92	H	1.54	9.12	18.50	30.0	-11.5	
Mid Ch								
1732.50	7.79	V	1.55	9.31	15.55	30.0	-14.5	
1732.50	11.33	H	1.55	9.31	19.09	30.0	-10.9	
High Ch								
1753.50	4.77	V	1.56	9.38	12.59	30.0	-17.4	
1753.50	11.19	H	1.56	9.38	19.01	30.0	-11.0	

Rev. 3.17.11

Note: For Band 4 EIRP limit is 30dBm

LTE Band 4 1.4MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4 QPSK, 1.4MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1710.70	4.39	V	1.54	9.12	11.97	30.0	-18.0	
	1710.70	10.15	H	1.54	9.12	17.73	30.0	-12.3	
	Mid Ch								
	1732.50	5.66	V	1.55	9.31	13.42	30.0	-16.6	
	1732.50	10.57	H	1.55	9.31	18.33	30.0	-11.7	
	High Ch								
	1754.30	4.70	V	1.56	9.37	12.51	30.0	-17.5	
	1754.30	10.48	H	1.56	9.37	18.29	30.0	-11.7	
Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									
LTE Band 4 1.4MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 15K21157 Date: 06-23-15 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4 16QAM, 1.4MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1710.70	3.33	V	1.54	9.12	10.91	30.0	-19.1	
	1710.70	9.08	H	1.54	9.12	16.66	30.0	-13.3	
	Mid Ch								
	1732.50	4.68	V	1.55	9.31	12.44	30.0	-17.6	
	1732.50	9.53	H	1.55	9.31	17.29	30.0	-12.7	
	High Ch								
	1754.30	3.66	V	1.56	9.37	11.47	30.0	-18.5	
	1754.30	9.44	H	1.56	9.37	17.25	30.0	-12.8	
Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									

11.2. FIELD STRENGTH OF SPURIOUS RADIATION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238, §27.53 and §90.691

LIMIT

Part 22.917(a) & Part 24.238(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

Part 27: (m)(4) For mobile station, the attenuation factor shall be not less than $43 + 10 \log (P)$ dB at the channel edge and $(55 + 10 \log (P))$ dB at the 5.5 MHz from the channel edges.

TEST PROCEDURE

For Cellular equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

For PCS equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

RESULTS

LTE Band 17

Due to frequency range and same output power setting, test was carried in LTE Band 12 to cover both LTE Band 12 and LTE Band 17.

LTE Band 5

Due to frequency range and same output power setting, test was carried in LTE Band 26 to cover both LTE Band 26 and LTE Band 5.

LTE Band 2

Due to frequency range and same output power setting, test was carried in LTE Band 25 to cover both LTE Band 25 and LTE Band 2.

LTE Band 41 15MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement																																																																																																																																																																																																																																															
	Company:		Samsung																																																																																																																																																																																																																																													
	Project #:		15K21157																																																																																																																																																																																																																																													
	Date:		06-29-15																																																																																																																																																																																																																																													
	Test Engineer:		Steven.Kim																																																																																																																																																																																																																																													
	Configuration:		EUT / AC Adapter / Ear Phone / X-Position																																																																																																																																																																																																																																													
	Mode:		TX, LTE BAND 41, 15MHz BW,QPSK																																																																																																																																																																																																																																													
	Chamber		Pre-amplifier		Filter		Limit																																																																																																																																																																																																																																									
	Chamber 2		AFS42		Filter 1		FCC Part 27																																																																																																																																																																																																																																									
	<table><tr><th>f</th><th>SG reading</th><th>Ant. Pol.</th><th>Distance</th><th>Preamp</th><th>Filter</th><th>ERP</th><th>Limit</th><th>Delta</th><th>Notes</th></tr><tr><th>GHz</th><th>(dBm)</th><th>(H/V)</th><th>(m)</th><th>(dB)</th><th>(dB)</th><th>(dBm)</th><th>(dBm)</th><th>(dB)</th><th></th></tr><tr><td colspan="10">Low Ch. (2503.5 MHz)</td></tr><tr><td>5.0070</td><td>-30.5</td><td>V</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-70.4</td><td>-25.0</td><td>-45.4</td><td></td></tr><tr><td>7.5100</td><td>-27.0</td><td>V</td><td>3.0</td><td>40.7</td><td>1.0</td><td>-66.7</td><td>-25.0</td><td>-41.7</td><td></td></tr><tr><td>10.0140</td><td>-25.9</td><td>V</td><td>3.0</td><td>39.7</td><td>1.0</td><td>-64.6</td><td>-25.0</td><td>-39.6</td><td></td></tr><tr><td>5.0070</td><td>-30.2</td><td>H</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-70.1</td><td>-25.0</td><td>-45.1</td><td></td></tr><tr><td>7.5100</td><td>-26.8</td><td>H</td><td>3.0</td><td>40.7</td><td>1.0</td><td>-66.5</td><td>-25.0</td><td>-41.5</td><td></td></tr><tr><td>10.0140</td><td>-28.7</td><td>H</td><td>3.0</td><td>39.7</td><td>1.0</td><td>-67.4</td><td>-25.0</td><td>-42.4</td><td></td></tr><tr><td colspan="10">Mid Ch. (2593 MHz)</td></tr><tr><td>5.1860</td><td>-27.7</td><td>V</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-67.6</td><td>-25.0</td><td>-42.6</td><td></td></tr><tr><td>7.7790</td><td>-28.1</td><td>V</td><td>3.0</td><td>40.6</td><td>1.0</td><td>-67.7</td><td>-25.0</td><td>-42.7</td><td></td></tr><tr><td>10.3720</td><td>-25.0</td><td>V</td><td>3.0</td><td>39.4</td><td>1.0</td><td>-63.4</td><td>-25.0</td><td>-38.4</td><td></td></tr><tr><td>5.1860</td><td>-30.3</td><td>H</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-70.2</td><td>-25.0</td><td>-45.2</td><td></td></tr><tr><td>7.7790</td><td>-27.9</td><td>H</td><td>3.0</td><td>40.6</td><td>1.0</td><td>-67.5</td><td>-25.0</td><td>-42.5</td><td></td></tr><tr><td>10.3720</td><td>-27.5</td><td>H</td><td>3.0</td><td>39.4</td><td>1.0</td><td>-65.9</td><td>-25.0</td><td>-40.9</td><td></td></tr><tr><td colspan="10">High Ch. (2682.5 MHz)</td></tr><tr><td>5.3650</td><td>-19.1</td><td>V</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-59.0</td><td>-25.0</td><td>-34.0</td><td></td></tr><tr><td>8.0470</td><td>-22.3</td><td>V</td><td>3.0</td><td>40.4</td><td>1.0</td><td>-61.7</td><td>-25.0</td><td>-36.7</td><td></td></tr><tr><td>10.7300</td><td>-19.5</td><td>V</td><td>3.0</td><td>39.2</td><td>1.0</td><td>-57.7</td><td>-25.0</td><td>-32.7</td><td></td></tr><tr><td>5.3650</td><td>-18.1</td><td>H</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-58.0</td><td>-25.0</td><td>-33.0</td><td></td></tr><tr><td>8.0470</td><td>-20.9</td><td>H</td><td>3.0</td><td>40.4</td><td>1.0</td><td>-60.3</td><td>-25.0</td><td>-35.3</td><td></td></tr><tr><td>10.7300</td><td>-20.8</td><td>H</td><td>3.0</td><td>39.2</td><td>1.0</td><td>-59.0</td><td>-25.0</td><td>-34.0</td><td></td></tr></table>											f	SG reading	Ant. Pol.	Distance	Preamp	Filter	ERP	Limit	Delta	Notes	GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)		Low Ch. (2503.5 MHz)										5.0070	-30.5	V	3.0	40.9	1.0	-70.4	-25.0	-45.4		7.5100	-27.0	V	3.0	40.7	1.0	-66.7	-25.0	-41.7		10.0140	-25.9	V	3.0	39.7	1.0	-64.6	-25.0	-39.6		5.0070	-30.2	H	3.0	40.9	1.0	-70.1	-25.0	-45.1		7.5100	-26.8	H	3.0	40.7	1.0	-66.5	-25.0	-41.5		10.0140	-28.7	H	3.0	39.7	1.0	-67.4	-25.0	-42.4		Mid Ch. (2593 MHz)										5.1860	-27.7	V	3.0	40.9	1.0	-67.6	-25.0	-42.6		7.7790	-28.1	V	3.0	40.6	1.0	-67.7	-25.0	-42.7		10.3720	-25.0	V	3.0	39.4	1.0	-63.4	-25.0	-38.4		5.1860	-30.3	H	3.0	40.9	1.0	-70.2	-25.0	-45.2		7.7790	-27.9	H	3.0	40.6	1.0	-67.5	-25.0	-42.5		10.3720	-27.5	H	3.0	39.4	1.0	-65.9	-25.0	-40.9		High Ch. (2682.5 MHz)										5.3650	-19.1	V	3.0	40.9	1.0	-59.0	-25.0	-34.0		8.0470	-22.3	V	3.0	40.4	1.0	-61.7	-25.0	-36.7		10.7300	-19.5	V	3.0	39.2	1.0	-57.7	-25.0	-32.7		5.3650	-18.1	H	3.0	40.9	1.0	-58.0	-25.0	-33.0		8.0470	-20.9	H	3.0	40.4	1.0	-60.3	-25.0	-35.3		10.7300	-20.8	H	3.0	39.2	1.0	-59.0	-25.0	-34.0
f	SG reading	Ant. Pol.	Distance	Preamp	Filter	ERP	Limit	Delta	Notes																																																																																																																																																																																																																																							
GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)																																																																																																																																																																																																																																								
Low Ch. (2503.5 MHz)																																																																																																																																																																																																																																																
5.0070	-30.5	V	3.0	40.9	1.0	-70.4	-25.0	-45.4																																																																																																																																																																																																																																								
7.5100	-27.0	V	3.0	40.7	1.0	-66.7	-25.0	-41.7																																																																																																																																																																																																																																								
10.0140	-25.9	V	3.0	39.7	1.0	-64.6	-25.0	-39.6																																																																																																																																																																																																																																								
5.0070	-30.2	H	3.0	40.9	1.0	-70.1	-25.0	-45.1																																																																																																																																																																																																																																								
7.5100	-26.8	H	3.0	40.7	1.0	-66.5	-25.0	-41.5																																																																																																																																																																																																																																								
10.0140	-28.7	H	3.0	39.7	1.0	-67.4	-25.0	-42.4																																																																																																																																																																																																																																								
Mid Ch. (2593 MHz)																																																																																																																																																																																																																																																
5.1860	-27.7	V	3.0	40.9	1.0	-67.6	-25.0	-42.6																																																																																																																																																																																																																																								
7.7790	-28.1	V	3.0	40.6	1.0	-67.7	-25.0	-42.7																																																																																																																																																																																																																																								
10.3720	-25.0	V	3.0	39.4	1.0	-63.4	-25.0	-38.4																																																																																																																																																																																																																																								
5.1860	-30.3	H	3.0	40.9	1.0	-70.2	-25.0	-45.2																																																																																																																																																																																																																																								
7.7790	-27.9	H	3.0	40.6	1.0	-67.5	-25.0	-42.5																																																																																																																																																																																																																																								
10.3720	-27.5	H	3.0	39.4	1.0	-65.9	-25.0	-40.9																																																																																																																																																																																																																																								
High Ch. (2682.5 MHz)																																																																																																																																																																																																																																																
5.3650	-19.1	V	3.0	40.9	1.0	-59.0	-25.0	-34.0																																																																																																																																																																																																																																								
8.0470	-22.3	V	3.0	40.4	1.0	-61.7	-25.0	-36.7																																																																																																																																																																																																																																								
10.7300	-19.5	V	3.0	39.2	1.0	-57.7	-25.0	-32.7																																																																																																																																																																																																																																								
5.3650	-18.1	H	3.0	40.9	1.0	-58.0	-25.0	-33.0																																																																																																																																																																																																																																								
8.0470	-20.9	H	3.0	40.4	1.0	-60.3	-25.0	-35.3																																																																																																																																																																																																																																								
10.7300	-20.8	H	3.0	39.2	1.0	-59.0	-25.0	-34.0																																																																																																																																																																																																																																								
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.																																																																																																																																																																																																																																																
LTE Band 41 15MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement																																																																																																																																																																																																																																															
	Company:		Samsung																																																																																																																																																																																																																																													
	Project #:		15K21157																																																																																																																																																																																																																																													
	Date:		06-29-15																																																																																																																																																																																																																																													
	Test Engineer:		Steven.Kim																																																																																																																																																																																																																																													
	Configuration:		EUT / AC Adapter / Ear Phone / X-Position																																																																																																																																																																																																																																													
	Mode:		TX, LTE BAND 41, 15MHz BW,16QAM																																																																																																																																																																																																																																													
	Chamber		Pre-amplifier		Filter		Limit																																																																																																																																																																																																																																									
	Chamber 2		AFS42		Filter 1		FCC Part 27																																																																																																																																																																																																																																									
	<table><tr><th>f</th><th>SG reading</th><th>Ant. Pol.</th><th>Distance</th><th>Preamp</th><th>Filter</th><th>ERP</th><th>Limit</th><th>Delta</th><th>Notes</th></tr><tr><th>GHz</th><th>(dBm)</th><th>(H/V)</th><th>(m)</th><th>(dB)</th><th>(dB)</th><th>(dBm)</th><th>(dBm)</th><th>(dB)</th><th></th></tr><tr><td colspan="10">Low Ch. (2503.5 MHz)</td></tr><tr><td>5.0070</td><td>-31.2</td><td>V</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-71.1</td><td>-25.0</td><td>-46.1</td><td></td></tr><tr><td>7.5100</td><td>-27.3</td><td>V</td><td>3.0</td><td>40.7</td><td>1.0</td><td>-67.0</td><td>-25.0</td><td>-42.0</td><td></td></tr><tr><td>10.0140</td><td>-24.8</td><td>V</td><td>3.0</td><td>39.7</td><td>1.0</td><td>-63.5</td><td>-25.0</td><td>-38.5</td><td></td></tr><tr><td>5.0070</td><td>-30.9</td><td>H</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-70.9</td><td>-25.0</td><td>-45.9</td><td></td></tr><tr><td>7.5100</td><td>-27.1</td><td>H</td><td>3.0</td><td>40.7</td><td>1.0</td><td>-66.8</td><td>-25.0</td><td>-41.8</td><td></td></tr><tr><td>10.0140</td><td>-28.4</td><td>H</td><td>3.0</td><td>39.7</td><td>1.0</td><td>-67.0</td><td>-25.0</td><td>-42.0</td><td></td></tr><tr><td colspan="10">Mid Ch. (2593 MHz)</td></tr><tr><td>5.1860</td><td>-28.5</td><td>V</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-68.4</td><td>-25.0</td><td>-43.4</td><td></td></tr><tr><td>7.7790</td><td>-29.4</td><td>V</td><td>3.0</td><td>40.6</td><td>1.0</td><td>-68.9</td><td>-25.0</td><td>-43.9</td><td></td></tr><tr><td>10.3720</td><td>-25.5</td><td>V</td><td>3.0</td><td>39.4</td><td>1.0</td><td>-63.9</td><td>-25.0</td><td>-38.9</td><td></td></tr><tr><td>5.1860</td><td>-30.6</td><td>H</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-70.5</td><td>-25.0</td><td>-45.5</td><td></td></tr><tr><td>7.7790</td><td>-28.1</td><td>H</td><td>3.0</td><td>40.6</td><td>1.0</td><td>-67.7</td><td>-25.0</td><td>-42.7</td><td></td></tr><tr><td>10.3720</td><td>-27.7</td><td>H</td><td>3.0</td><td>39.4</td><td>1.0</td><td>-66.1</td><td>-25.0</td><td>-41.1</td><td></td></tr><tr><td colspan="10">High Ch. (2682.5 MHz)</td></tr><tr><td>5.3650</td><td>-20.0</td><td>V</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-59.8</td><td>-25.0</td><td>-34.8</td><td></td></tr><tr><td>8.0470</td><td>-23.1</td><td>V</td><td>3.0</td><td>40.4</td><td>1.0</td><td>-62.5</td><td>-25.0</td><td>-37.5</td><td></td></tr><tr><td>10.7300</td><td>-20.6</td><td>V</td><td>3.0</td><td>39.2</td><td>1.0</td><td>-58.8</td><td>-25.0</td><td>-33.8</td><td></td></tr><tr><td>5.3650</td><td>-18.8</td><td>H</td><td>3.0</td><td>40.9</td><td>1.0</td><td>-58.7</td><td>-25.0</td><td>-33.7</td><td></td></tr><tr><td>8.0470</td><td>-22.2</td><td>H</td><td>3.0</td><td>40.4</td><td>1.0</td><td>-61.6</td><td>-25.0</td><td>-36.6</td><td></td></tr><tr><td>10.7300</td><td>-21.7</td><td>H</td><td>3.0</td><td>39.2</td><td>1.0</td><td>-59.8</td><td>-25.0</td><td>-34.8</td><td></td></tr></table>											f	SG reading	Ant. Pol.	Distance	Preamp	Filter	ERP	Limit	Delta	Notes	GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)		Low Ch. (2503.5 MHz)										5.0070	-31.2	V	3.0	40.9	1.0	-71.1	-25.0	-46.1		7.5100	-27.3	V	3.0	40.7	1.0	-67.0	-25.0	-42.0		10.0140	-24.8	V	3.0	39.7	1.0	-63.5	-25.0	-38.5		5.0070	-30.9	H	3.0	40.9	1.0	-70.9	-25.0	-45.9		7.5100	-27.1	H	3.0	40.7	1.0	-66.8	-25.0	-41.8		10.0140	-28.4	H	3.0	39.7	1.0	-67.0	-25.0	-42.0		Mid Ch. (2593 MHz)										5.1860	-28.5	V	3.0	40.9	1.0	-68.4	-25.0	-43.4		7.7790	-29.4	V	3.0	40.6	1.0	-68.9	-25.0	-43.9		10.3720	-25.5	V	3.0	39.4	1.0	-63.9	-25.0	-38.9		5.1860	-30.6	H	3.0	40.9	1.0	-70.5	-25.0	-45.5		7.7790	-28.1	H	3.0	40.6	1.0	-67.7	-25.0	-42.7		10.3720	-27.7	H	3.0	39.4	1.0	-66.1	-25.0	-41.1		High Ch. (2682.5 MHz)										5.3650	-20.0	V	3.0	40.9	1.0	-59.8	-25.0	-34.8		8.0470	-23.1	V	3.0	40.4	1.0	-62.5	-25.0	-37.5		10.7300	-20.6	V	3.0	39.2	1.0	-58.8	-25.0	-33.8		5.3650	-18.8	H	3.0	40.9	1.0	-58.7	-25.0	-33.7		8.0470	-22.2	H	3.0	40.4	1.0	-61.6	-25.0	-36.6		10.7300	-21.7	H	3.0	39.2	1.0	-59.8	-25.0	-34.8
f	SG reading	Ant. Pol.	Distance	Preamp	Filter	ERP	Limit	Delta	Notes																																																																																																																																																																																																																																							
GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)																																																																																																																																																																																																																																								
Low Ch. (2503.5 MHz)																																																																																																																																																																																																																																																
5.0070	-31.2	V	3.0	40.9	1.0	-71.1	-25.0	-46.1																																																																																																																																																																																																																																								
7.5100	-27.3	V	3.0	40.7	1.0	-67.0	-25.0	-42.0																																																																																																																																																																																																																																								
10.0140	-24.8	V	3.0	39.7	1.0	-63.5	-25.0	-38.5																																																																																																																																																																																																																																								
5.0070	-30.9	H	3.0	40.9	1.0	-70.9	-25.0	-45.9																																																																																																																																																																																																																																								
7.5100	-27.1	H	3.0	40.7	1.0	-66.8	-25.0	-41.8																																																																																																																																																																																																																																								
10.0140	-28.4	H	3.0	39.7	1.0	-67.0	-25.0	-42.0																																																																																																																																																																																																																																								
Mid Ch. (2593 MHz)																																																																																																																																																																																																																																																
5.1860	-28.5	V	3.0	40.9	1.0	-68.4	-25.0	-43.4																																																																																																																																																																																																																																								
7.7790	-29.4	V	3.0	40.6	1.0	-68.9	-25.0	-43.9																																																																																																																																																																																																																																								
10.3720	-25.5	V	3.0	39.4	1.0	-63.9	-25.0	-38.9																																																																																																																																																																																																																																								
5.1860	-30.6	H	3.0	40.9	1.0	-70.5	-25.0	-45.5																																																																																																																																																																																																																																								
7.7790	-28.1	H	3.0	40.6	1.0	-67.7	-25.0	-42.7																																																																																																																																																																																																																																								
10.3720	-27.7	H	3.0	39.4	1.0	-66.1	-25.0	-41.1																																																																																																																																																																																																																																								
High Ch. (2682.5 MHz)																																																																																																																																																																																																																																																
5.3650	-20.0	V	3.0	40.9	1.0	-59.8	-25.0	-34.8																																																																																																																																																																																																																																								
8.0470	-23.1	V	3.0	40.4	1.0	-62.5	-25.0	-37.5																																																																																																																																																																																																																																								
10.7300	-20.6	V	3.0	39.2	1.0	-58.8	-25.0	-33.8																																																																																																																																																																																																																																								
5.3650	-18.8	H	3.0	40.9	1.0	-58.7	-25.0	-33.7																																																																																																																																																																																																																																								
8.0470	-22.2	H	3.0	40.4	1.0	-61.6	-25.0	-36.6																																																																																																																																																																																																																																								
10.7300	-21.7	H	3.0	39.2	1.0	-59.8	-25.0	-34.8																																																																																																																																																																																																																																								
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.																																																																																																																																																																																																																																																

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-29-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Ear Phone / X-Position								
Mode:		TX, LTE BAND 41, 10MHz BW, QPSK								
LTE Band 41 10MHz QPSK	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 27			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch. (2501 MHz)									
	5.0020	-28.9	V	3.0	40.9	1.0	-68.9	-25.0	-43.9	
	7.5030	-25.9	V	3.0	40.7	1.0	-65.6	-25.0	-40.6	
	10.0040	-23.5	V	3.0	39.7	1.0	-62.2	-25.0	-37.2	
	5.0020	-28.8	H	3.0	40.9	1.0	-68.8	-25.0	-43.8	
	7.5030	-25.4	H	3.0	40.7	1.0	-65.1	-25.0	-40.1	
	10.0040	-26.9	H	3.0	39.7	1.0	-65.6	-25.0	-40.6	
	Mid Ch. (2593 MHz)									
	5.1860	-30.5	V	3.0	40.9	1.0	-70.4	-25.0	-45.4	
	7.7790	-26.1	V	3.0	40.6	1.0	-65.7	-25.0	-40.7	
	10.3720	-22.7	V	3.0	39.4	1.0	-61.1	-25.0	-36.1	
	5.1860	-26.3	H	3.0	40.9	1.0	-66.2	-25.0	-41.2	
	7.7790	-26.3	H	3.0	40.6	1.0	-65.9	-25.0	-40.9	
	10.3720	-25.0	H	3.0	39.4	1.0	-63.4	-25.0	-38.4	
	High Ch. (2685 MHz)									
	5.3700	-19.2	V	3.0	40.9	1.0	-59.1	-25.0	-34.1	
	8.0550	-22.4	V	3.0	40.4	1.0	-61.8	-25.0	-36.8	
	10.7400	-19.6	V	3.0	39.1	1.0	-57.8	-25.0	-32.8	
	5.3700	-18.5	H	3.0	40.9	1.0	-58.3	-25.0	-33.3	
	8.0550	-20.8	H	3.0	40.4	1.0	-60.2	-25.0	-35.2	
	10.7400	-20.7	H	3.0	39.1	1.0	-58.8	-25.0	-33.8	
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										
UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-29-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Ear Phone / X-Position								
Mode:		TX, LTE BAND 41, 10MHz BW, 16QAM								
LTE Band 41 10MHz 16QAM	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 27			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch. (2501 MHz)									
	5.0020	-30.3	V	3.0	40.9	1.0	-70.2	-25.0	-45.2	
	7.5030	-26.8	V	3.0	40.7	1.0	-66.5	-25.0	-41.5	
	10.0040	-23.7	V	3.0	39.7	1.0	-62.3	-25.0	-37.3	
	5.0020	-29.9	H	3.0	40.9	1.0	-69.9	-25.0	-44.9	
	7.5030	-26.3	H	3.0	40.7	1.0	-66.0	-25.0	-41.0	
	10.0040	-28.1	H	3.0	39.7	1.0	-66.8	-25.0	-41.8	
	Mid Ch. (2593 MHz)									
	5.1860	-31.8	V	3.0	40.9	1.0	-71.7	-25.0	-46.7	
	7.7790	-27.7	V	3.0	40.6	1.0	-67.2	-25.0	-42.2	
	10.3720	-23.8	V	3.0	39.4	1.0	-62.2	-25.0	-37.2	
	5.1860	-27.5	H	3.0	40.9	1.0	-67.4	-25.0	-42.4	
	7.7790	-27.5	H	3.0	40.6	1.0	-67.1	-25.0	-42.1	
	10.3720	-26.0	H	3.0	39.4	1.0	-64.4	-25.0	-39.4	
	High Ch. (2685 MHz)									
	5.3700	-20.1	V	3.0	40.9	1.0	-59.9	-25.0	-34.9	
	8.0550	-23.2	V	3.0	40.4	1.0	-62.6	-25.0	-37.6	
	10.7400	-20.6	V	3.0	39.1	1.0	-58.8	-25.0	-33.8	
	5.3700	-19.3	H	3.0	40.9	1.0	-59.2	-25.0	-34.2	
	8.0550	-22.6	H	3.0	40.4	1.0	-62.0	-25.0	-37.0	
	10.7400	-20.5	H	3.0	39.1	1.0	-58.7	-25.0	-33.7	
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										

		UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 15K21157 Date: 06-29-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 41, 5MHz BW, QPSK									
		Chamber		Pre-amplifier		Filter		Limit			
		Chamber 2		AFS42		Filter 1		FCC Part 27			
LTE		f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Band 41 5 MHz QPSK		Low Ch. (2498.5 MHz)									
		4.9970	-29.5	V	3.0	40.9	1.0	-69.5	-25.0	-44.5	
		7.4955	-25.9	V	3.0	40.7	1.0	-65.6	-25.0	-40.6	
		9.9940	-23.4	V	3.0	39.7	1.0	-62.0	-25.0	-37.0	
		4.9970	-29.4	H	3.0	40.9	1.0	-69.3	-25.0	-44.3	
		7.4955	-25.0	H	3.0	40.7	1.0	-64.8	-25.0	-39.8	
		9.9940	-26.9	H	3.0	39.7	1.0	-65.5	-25.0	-40.5	
		Mid Ch. (2593 MHz)									
		5.1860	-29.5	V	3.0	40.9	1.0	-69.3	-25.0	-44.3	
		7.7790	-26.1	V	3.0	40.6	1.0	-65.7	-25.0	-40.7	
		10.3720	-22.7	V	3.0	39.4	1.0	-61.1	-25.0	-36.1	
		5.1860	-26.3	H	3.0	40.9	1.0	-66.2	-25.0	-41.2	
		7.7790	-26.3	H	3.0	40.6	1.0	-65.9	-25.0	-40.9	
		10.3720	-25.0	H	3.0	39.4	1.0	-63.4	-25.0	-38.4	
		High Ch. (2687.5 MHz)									
		5.3750	-19.1	V	3.0	40.9	1.0	-58.9	-25.0	-33.9	
		8.0625	-22.0	V	3.0	40.4	1.0	-61.4	-25.0	-36.4	
		10.7500	-19.4	V	3.0	39.1	1.0	-57.5	-25.0	-32.5	
		5.3750	-17.8	H	3.0	40.9	1.0	-57.6	-25.0	-32.6	
		8.0625	-21.1	H	3.0	40.4	1.0	-60.5	-25.0	-35.5	
	10.7500	-20.3	H	3.0	39.1	1.0	-58.4	-25.0	-33.4		
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.											
		UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 15K21157 Date: 06-29-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 41, 5MHz BW, 16QAM									
		Chamber		Pre-amplifier		Filter		Limit			
		Chamber 2		AFS42		Filter 1		FCC Part 27			
LTE		f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Band 41 5 MHz 16QAM		Low Ch. (2498.5 MHz)									
		4.9970	-30.0	V	3.0	40.9	1.0	-69.9	-25.0	-44.9	
		7.4955	-26.4	V	3.0	40.7	1.0	-66.1	-25.0	-41.1	
		9.9940	-24.3	V	3.0	39.7	1.0	-63.0	-25.0	-38.0	
		4.9970	-29.7	H	3.0	40.9	1.0	-69.6	-25.0	-44.6	
		7.4955	-26.3	H	3.0	40.7	1.0	-66.0	-25.0	-41.0	
		9.9940	-27.9	H	3.0	39.7	1.0	-66.6	-25.0	-41.6	
		Mid Ch. (2593 MHz)									
		5.1860	-30.5	V	3.0	40.9	1.0	-70.4	-25.0	-45.4	
		7.7790	-27.2	V	3.0	40.6	1.0	-66.7	-25.0	-41.7	
		10.3720	-23.6	V	3.0	39.4	1.0	-62.1	-25.0	-37.1	
		5.1860	-27.7	H	3.0	40.9	1.0	-67.6	-25.0	-42.6	
		7.7790	-27.0	H	3.0	40.6	1.0	-66.6	-25.0	-41.6	
		10.3720	-25.9	H	3.0	39.4	1.0	-64.3	-25.0	-39.3	
		High Ch. (2687.5 MHz)									
		5.3750	-20.0	V	3.0	40.9	1.0	-59.8	-25.0	-34.8	
		8.0625	-23.0	V	3.0	40.4	1.0	-62.4	-25.0	-37.4	
		10.7500	-20.6	V	3.0	39.1	1.0	-58.7	-25.0	-33.7	
		5.3750	-19.0	H	3.0	40.9	1.0	-58.8	-25.0	-33.8	
		8.0625	-21.8	H	3.0	40.4	1.0	-61.2	-25.0	-36.2	
	10.7500	-21.5	H	3.0	39.1	1.0	-59.6	-25.0	-34.6		
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.											

LTE Band 26

		UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung		Project #: 15K21157		Date: 06-24-15		Test Engineer: Steven.Kim		Configuration: EUT / AC Adapter / Earphone, X Position	
LTE Band 26 15MHz QPSK		Chamber		Pre-amplifier		Filter		Limit			
		Chamber 2		AFS42		Filter 1		FCC Part 22			
		f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
		Low Channel (831.5MHz)									
		1.6630	-33.8	V	3.0	39.1	1.0	-71.9	-13.0	-58.9	
		2.4945	-25.5	V	3.0	39.5	1.0	-64.0	-13.0	-51.0	
		3.3260	-35.8	V	3.0	40.1	1.0	-74.9	-13.0	-61.9	
		1.6630	-29.1	H	3.0	39.1	1.0	-67.2	-13.0	-54.2	
		2.4945	-23.7	H	3.0	39.5	1.0	-62.3	-13.0	-49.3	
		3.3260	-35.8	H	3.0	40.1	1.0	-74.9	-13.0	-61.9	
	High Channel (841.5MHz)										
	1.6830	-33.7	V	3.0	39.1	1.0	-71.8	-13.0	-58.8		
	2.5245	-25.6	V	3.0	39.5	1.0	-64.1	-13.0	-51.1		
	3.3660	-35.2	V	3.0	40.2	1.0	-74.4	-13.0	-61.4		
	1.6830	-31.7	H	3.0	39.1	1.0	-69.9	-13.0	-56.9		
	2.5245	-25.0	H	3.0	39.5	1.0	-63.6	-13.0	-50.6		
	3.3660	-35.7	H	3.0	40.2	1.0	-74.9	-13.0	-61.9		
		Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

		UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung		Project #: 15K21157		Date: 06-24-15		Test Engineer: Steven.Kim		Configuration: EUT / AC Adapter / Earphone, X Position	
LTE Band 26 15MHz 16QAM		Chamber		Pre-amplifier		Filter		Limit			
		Chamber 2		AFS42		Filter 1		FCC Part 22			
		f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
		Low Channel (831.5MHz)									
		1.6630	-32.8	V	3.0	39.1	1.0	-70.9	-13.0	-57.9	
		2.4945	-25.0	V	3.0	39.5	1.0	-63.5	-13.0	-50.5	
		3.3260	-35.7	V	3.0	40.1	1.0	-74.9	-13.0	-61.9	
		1.6630	-27.7	H	3.0	39.1	1.0	-65.8	-13.0	-52.8	
		2.4945	-23.2	H	3.0	39.5	1.0	-61.7	-13.0	-48.7	
		3.3260	-35.6	H	3.0	40.1	1.0	-74.8	-13.0	-61.8	
	High Channel (841.5MHz)										
	1.6830	-32.7	V	3.0	39.1	1.0	-70.8	-13.0	-57.8		
	2.5245	-25.3	V	3.0	39.5	1.0	-63.9	-13.0	-50.9		
	3.3660	-35.7	V	3.0	40.2	1.0	-74.8	-13.0	-61.8		
	1.6830	-30.2	H	3.0	39.1	1.0	-68.3	-13.0	-55.3		
	2.5245	-24.5	H	3.0	39.5	1.0	-63.1	-13.0	-50.1		
	3.3660	-35.6	H	3.0	40.2	1.0	-74.8	-13.0	-61.8		
		Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-24-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Earphone, X Position								
Mode:		TX, LTE BAND 26, 10MHz BW,QPSK								

LTE Band 26 5 MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 15K21157									
	Date: 06-24-15									
	Test Engineer: Steven.Kim									
	Configuration: EUT / AC Adapter / Earphone, X Position									
	Mode: TX, LTE BAND 26, 5MHz BW,QPSK									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		Part 22			
	f	SG reading	Ant. Pol.	Distance	Preamp	Filter	EIRP	Limit	Delta	Notes
	GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)	
	Low Channel (816.5MHz)									
	1.6330	-27.2	V	3.0	39.1	1.0	-65.3	-13.0	-52.3	
	2.4495	-27.4	V	3.0	39.5	1.0	-65.9	-13.0	-52.9	
	3.2660	-35.0	V	3.0	40.1	1.0	-74.0	-13.0	-61.0	
	1.6330	-22.5	H	3.0	39.1	1.0	-60.6	-13.0	-47.6	
	2.4495	-25.9	H	3.0	39.5	1.0	-64.4	-13.0	-51.4	
	3.2660	-34.9	H	3.0	40.1	1.0	-73.9	-13.0	-60.9	
	Mid Channel (831.5MHz)									
	1.6630	-32.3	V	3.0	39.1	1.0	-70.4	-13.0	-57.4	
	2.4945	-24.3	V	3.0	39.5	1.0	-62.9	-13.0	-49.9	
	3.3260	-35.6	V	3.0	40.1	1.0	-74.7	-13.0	-61.7	
	1.6630	-30.2	H	3.0	39.1	1.0	-68.3	-13.0	-55.3	
	2.4945	-23.0	H	3.0	39.5	1.0	-61.6	-13.0	-48.6	
	3.3260	-35.4	H	3.0	40.1	1.0	-74.5	-13.0	-61.5	
High Channel (846.5MHz)										
1.6930	-32.7	V	3.0	39.1	1.0	-70.8	-13.0	-57.8		
2.5390	-24.4	V	3.0	39.6	1.0	-63.0	-13.0	-50.0		
3.3860	-35.2	V	3.0	40.2	1.0	-74.4	-13.0	-61.4		
1.6930	-30.7	H	3.0	39.1	1.0	-68.8	-13.0	-55.8		
2.5390	-24.1	H	3.0	39.6	1.0	-62.6	-13.0	-49.6		
3.3860	-35.2	H	3.0	40.2	1.0	-74.4	-13.0	-61.4		
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										
LTE Band 26 5 MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 15K21157									
	Date: 06-24-15									
	Test Engineer: Steven.Kim									
	Configuration: EUT / AC Adapter / Earphone, X Position									
	Mode: TX, LTE BAND 26, 5MHz BW,16QAM									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		Part 22			
	f	SG reading	Ant. Pol.	Distance	Preamp	Filter	EIRP	Limit	Delta	Notes
	GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)	
	Low Channel (816.5MHz)									
	1.6330	-28.9	V	3.0	39.1	1.0	-67.0	-13.0	-54.0	
	2.4495	-30.3	V	3.0	39.5	1.0	-68.8	-13.0	-55.8	
	3.2660	-35.7	V	3.0	40.1	1.0	-74.7	-13.0	-61.7	
	1.6330	-23.5	H	3.0	39.1	1.0	-61.6	-13.0	-48.6	
	2.4495	-27.4	H	3.0	39.5	1.0	-65.9	-13.0	-52.9	
	3.2660	-35.5	H	3.0	40.1	1.0	-74.6	-13.0	-61.6	
	Mid Channel (831.5MHz)									
	1.6630	-33.3	V	3.0	39.1	1.0	-71.4	-13.0	-58.4	
	2.4945	-25.4	V	3.0	39.5	1.0	-64.0	-13.0	-51.0	
	3.3260	-35.4	V	3.0	40.1	1.0	-74.5	-13.0	-61.5	
	1.6630	-31.4	H	3.0	39.1	1.0	-69.5	-13.0	-56.5	
	2.4945	-24.1	H	3.0	39.5	1.0	-62.6	-13.0	-49.6	
	3.3260	-35.4	H	3.0	40.1	1.0	-74.5	-13.0	-61.5	
High Channel (846.5MHz)										
1.6930	-33.7	V	3.0	39.1	1.0	-71.8	-13.0	-58.8		
2.5390	-25.5	V	3.0	39.6	1.0	-64.0	-13.0	-51.0		
3.3860	-35.8	V	3.0	40.2	1.0	-74.9	-13.0	-61.9		
1.6930	-31.8	H	3.0	39.1	1.0	-69.9	-13.0	-56.9		
2.5390	-24.7	H	3.0	39.6	1.0	-63.3	-13.0	-50.3		
3.3860	-35.4	H	3.0	40.2	1.0	-74.6	-13.0	-61.6		
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
LTE Band 26 3MHz QPSK	Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Earphone, X Position Mode: TX, LTE BAND 26, 3MHz BW,QPSK									
	Chamber Chamber 2 Pre-amplifier AFS42 Filter Filter 1 Limit Part 22									
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (815.5MHz)									
	1.6310	-27.9	V	3.0	39.1	1.0	-66.0	-13.0	-53.0	
	2.4465	-27.7	V	3.0	39.5	1.0	-66.2	-13.0	-53.2	
	3.2620	-35.4	V	3.0	40.1	1.0	-74.4	-13.0	-61.4	
	1.6310	-23.2	H	3.0	39.1	1.0	-61.3	-13.0	-48.3	
	2.4465	-26.1	H	3.0	39.5	1.0	-64.6	-13.0	-51.6	
	3.2620	-35.2	H	3.0	40.1	1.0	-74.3	-13.0	-61.3	
	Mid Channel (831.5MHz)									
	1.6630	-32.8	V	3.0	39.1	1.0	-70.9	-13.0	-57.9	
	2.4945	-25.0	V	3.0	39.5	1.0	-63.5	-13.0	-50.5	
	3.3260	-35.4	V	3.0	40.1	1.0	-74.5	-13.0	-61.5	
	1.6630	-30.4	H	3.0	39.1	1.0	-68.5	-13.0	-55.5	
	2.4945	-22.8	H	3.0	39.5	1.0	-61.3	-13.0	-48.3	
	3.3260	-36.1	H	3.0	40.1	1.0	-75.2	-13.0	-62.2	
	High Channel (847.5MHz)									
	1.6950	-32.7	V	3.0	39.1	1.0	-70.8	-13.0	-57.8	
	2.5425	-24.7	V	3.0	39.6	1.0	-63.2	-13.0	-50.2	
	3.3900	-35.6	V	3.0	40.2	1.0	-74.8	-13.0	-61.8	
	1.6950	-30.4	H	3.0	39.1	1.0	-68.5	-13.0	-55.5	
	2.5425	-24.4	H	3.0	39.6	1.0	-63.0	-13.0	-50.0	
	3.3900	-35.7	H	3.0	40.2	1.0	-74.9	-13.0	-61.9	
	Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
LTE Band 26 3MHz 16QAM	Company: Samsung Project #: 15K21157 Date: 06-24-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Earphone, X Position Mode: TX, LTE BAND 26, 3MHz BW,16QAM									
	Chamber Chamber 2 Pre-amplifier AFS42 Filter Filter 1 Limit Part 22									
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (815.5MHz)									
	1.6310	-28.9	V	3.0	39.1	1.0	-67.0	-13.0	-54.0	
	2.4465	-30.6	V	3.0	39.5	1.0	-69.1	-13.0	-56.1	
	3.2620	-34.8	V	3.0	40.1	1.0	-73.9	-13.0	-60.9	
	1.6310	-23.5	H	3.0	39.1	1.0	-61.6	-13.0	-48.6	
	2.4465	-27.4	H	3.0	39.5	1.0	-65.9	-13.0	-52.9	
	3.2620	-34.9	H	3.0	40.1	1.0	-73.9	-13.0	-60.9	
	Mid Channel (831.5MHz)									
	1.6630	-33.1	V	3.0	39.1	1.0	-71.2	-13.0	-58.2	
	2.4945	-25.5	V	3.0	39.5	1.0	-64.0	-13.0	-51.0	
	3.3260	-35.9	V	3.0	40.1	1.0	-75.0	-13.0	-62.0	
	1.6630	-31.4	H	3.0	39.1	1.0	-69.5	-13.0	-56.5	
	2.4945	-23.7	H	3.0	39.5	1.0	-62.3	-13.0	-49.3	
	3.3260	-35.9	H	3.0	40.1	1.0	-75.0	-13.0	-62.0	
	High Channel (847.5MHz)									
	1.6950	-33.0	V	3.0	39.1	1.0	-71.1	-13.0	-58.1	
	2.5425	-25.8	V	3.0	39.6	1.0	-64.4	-13.0	-51.4	
	3.3900	-35.6	V	3.0	40.2	1.0	-74.8	-13.0	-61.8	
	1.6950	-31.3	H	3.0	39.1	1.0	-69.4	-13.0	-56.4	
	2.5425	-24.9	H	3.0	39.6	1.0	-63.5	-13.0	-50.5	
	3.3900	-35.4	H	3.0	40.2	1.0	-74.6	-13.0	-61.6	
	Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-24-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Earphone, X Position								
Mode:		TX, LTE BAND 26, 1.4MHz BW,QPSK								
LTE Band 26 1.4MHz QPSK	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		Part 22			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (814.7MHz)									
	1.6294	-27.3	V	3.0	39.1	1.0	-65.4	-13.0	-52.4	
	2.4441	-27.3	V	3.0	39.5	1.0	-65.8	-13.0	-52.8	
	3.2588	-35.1	V	3.0	40.1	1.0	-74.1	-13.0	-61.1	
	1.6294	-22.6	H	3.0	39.1	1.0	-60.7	-13.0	-47.7	
	2.4441	-25.8	H	3.0	39.5	1.0	-64.3	-13.0	-51.3	
	3.2588	-34.9	H	3.0	40.1	1.0	-74.0	-13.0	-61.0	
	Mid Channel (831.5MHz)									
	1.6630	-32.5	V	3.0	39.1	1.0	-70.6	-13.0	-57.6	
	2.4945	-24.3	V	3.0	39.5	1.0	-62.8	-13.0	-49.8	
	3.3260	-36.1	V	3.0	40.1	1.0	-75.2	-13.0	-62.2	
	1.6630	-31.1	H	3.0	39.1	1.0	-69.2	-13.0	-56.2	
	2.4945	-23.1	H	3.0	39.5	1.0	-61.6	-13.0	-48.6	
	3.3260	-35.3	H	3.0	40.1	1.0	-74.5	-13.0	-61.5	
	High Channel (848.3MHz)									
	1.6966	-32.0	V	3.0	39.1	1.0	-70.1	-13.0	-57.1	
	2.5449	-25.0	V	3.0	39.6	1.0	-63.6	-13.0	-50.6	
	3.3932	-35.6	V	3.0	40.2	1.0	-74.8	-13.0	-61.8	
	1.6966	-30.9	H	3.0	39.1	1.0	-69.0	-13.0	-56.0	
	2.5449	-23.8	H	3.0	39.6	1.0	-62.3	-13.0	-49.3	
	3.3932	-35.6	H	3.0	40.2	1.0	-74.8	-13.0	-61.8	
	Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-24-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Earphone, X Position								
Mode:		TX, LTE BAND 26, 1.4MHz BW,16QAM								
LTE Band 26 1.4MHz 16QAM	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		Part 22			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (814.7MHz)									
	1.6294	-28.4	V	3.0	39.1	1.0	-66.5	-13.0	-53.5	
	2.4441	-28.4	V	3.0	39.5	1.0	-66.9	-13.0	-53.9	
	3.2588	-35.1	V	3.0	40.1	1.0	-74.2	-13.0	-61.2	
	1.6294	-23.5	H	3.0	39.1	1.0	-61.6	-13.0	-48.6	
	2.4441	-27.0	H	3.0	39.5	1.0	-65.5	-13.0	-52.5	
	3.2588	-35.1	H	3.0	40.1	1.0	-74.2	-13.0	-61.2	
	Mid Channel (831.5MHz)									
	1.6630	-33.4	V	3.0	39.1	1.0	-71.5	-13.0	-58.5	
	2.4945	-25.5	V	3.0	39.5	1.0	-64.0	-13.0	-51.0	
	3.3260	-35.5	V	3.0	40.1	1.0	-74.6	-13.0	-61.6	
	1.6630	-32.0	H	3.0	39.1	1.0	-70.1	-13.0	-57.1	
	2.4945	-23.7	H	3.0	39.5	1.0	-62.3	-13.0	-49.3	
	3.3260	-35.6	H	3.0	40.1	1.0	-74.8	-13.0	-61.8	
	High Channel (848.3MHz)									
	1.6966	-33.0	V	3.0	39.1	1.0	-71.1	-13.0	-58.1	
	2.5449	-26.0	V	3.0	39.6	1.0	-64.6	-13.0	-51.6	
	3.3932	-35.6	V	3.0	40.2	1.0	-74.8	-13.0	-61.8	
	1.6966	-31.9	H	3.0	39.1	1.0	-70.0	-13.0	-57.0	
	2.5449	-24.7	H	3.0	39.6	1.0	-63.3	-13.0	-50.3	
	3.3932	-35.6	H	3.0	40.2	1.0	-74.8	-13.0	-61.8	
	Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

LTE Band 26 1.4MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung Project #: 15K21157 Date: 07-09-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Earphone, X Position Mode: TX, LTE BAND 26, 1.4MHz BW,QPSK									
	Chamber Chamber 2		Pre-amplifier AFS42		Filter Filter 1		Limit Part 22			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (819MHz)									
	1.6380	-28.6	V	3.0	39.1	1.0	-66.7	-13.0	-53.7	
	2.4570	-34.0	V	3.0	39.5	1.0	-72.5	-13.0	-59.5	
	3.2760	-33.3	V	3.0	40.1	1.0	-72.4	-13.0	-59.4	
	1.6380	-20.9	H	3.0	39.1	1.0	-59.0	-13.0	-46.0	
	2.4570	-34.6	H	3.0	39.5	1.0	-73.1	-13.0	-60.1	
3.2760	-33.6	H	3.0	40.1	1.0	-72.7	-13.0	-59.7		
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										

LTE Band 26 1.4MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung Project #: 15K21157 Date: 07-09-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Earphone, X Position Mode: TX, LTE BAND 26, 1.4MHz BW,16QAM									
	Chamber Chamber 2		Pre-amplifier AFS42		Filter Filter 1		Limit Part 22			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (819MHz)									
	1.6380	-22.7	V	3.0	39.1	1.0	-60.8	-13.0	-47.8	
	2.4570	-34.0	V	3.0	39.5	1.0	-72.5	-13.0	-59.5	
	3.2760	-33.6	V	3.0	40.1	1.0	-72.7	-13.0	-59.7	
	1.6380	-20.3	H	3.0	39.1	1.0	-58.4	-13.0	-45.4	
	2.4570	-34.2	H	3.0	39.5	1.0	-72.7	-13.0	-59.7	
3.2760	-33.5	H	3.0	40.1	1.0	-72.6	-13.0	-59.6		
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										

LTE Band 25

LTE Band 25 20MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 25, 20MHz BW, QPSK									
	Chamber Pre-amplifier Filter Limit Chamber 2 AFS42 Filter 1 FCC Part 24									
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1860MHz)									
	3.7200	8.4	V	3.0	40.5	1.0	-31.1	-13.0	-18.1	
	5.5800	-2.2	V	3.0	40.8	1.0	-42.1	-13.0	-29.1	
	7.4400	-6.3	V	3.0	40.8	1.0	-46.0	-13.0	-33.0	
	3.7200	-6.9	H	3.0	40.5	1.0	-32.6	-13.0	-19.6	
	5.5800	-3.8	H	3.0	40.8	1.0	-36.0	-13.0	-23.0	
	7.4400	-9.4	H	3.0	40.8	1.0	-49.2	-13.0	-36.2	
	Mid Channel (1882.5MHz)									
	3.7650	8.2	V	3.0	40.5	1.0	-31.3	-13.0	-18.3	
	5.6475	-4.0	V	3.0	40.8	1.0	-43.9	-13.0	-30.9	
	7.5300	-8.6	V	3.0	40.7	1.0	-48.3	-13.0	-35.3	
	3.7650	-6.2	H	3.0	40.5	1.0	-33.3	-13.0	-20.3	
	5.6475	-3.4	H	3.0	40.8	1.0	-36.4	-13.0	-23.4	
	7.5300	-11.0	H	3.0	40.7	1.0	-50.7	-13.0	-37.7	
	High Channel (1905MHz)									
	3.8100	-3.8	V	3.0	40.6	1.0	-35.8	-13.0	-22.8	
	5.7150	-4.2	V	3.0	40.8	1.0	-44.0	-13.0	-31.0	
	7.6200	-11.4	V	3.0	40.7	1.0	-51.1	-13.0	-38.1	
	3.8100	-2.5	H	3.0	40.6	1.0	-37.1	-13.0	-24.1	
	5.7150	-3.1	H	3.0	40.8	1.0	-36.7	-13.0	-23.7	
	7.6200	-13.0	H	3.0	40.7	1.0	-52.7	-13.0	-39.7	
	Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									
LTE Band 25 20MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 25, 20MHz BW, 16QAM									
	Chamber Pre-amplifier Filter Limit Chamber 2 AFS42 Filter 1 FCC Part 24									
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1860MHz)									
	3.7200	-7.4	V	3.0	40.5	1.0	-32.1	-13.0	-19.1	
	5.5800	-3.3	V	3.0	40.8	1.0	-43.1	-13.0	-30.1	
	7.4400	-7.3	V	3.0	40.8	1.0	-47.1	-13.0	-34.1	
	3.7200	-5.8	H	3.0	40.5	1.0	-33.7	-13.0	-20.7	
	5.5800	-2.6	H	3.0	40.8	1.0	-37.2	-13.0	-24.2	
	7.4400	-10.4	H	3.0	40.8	1.0	-50.2	-13.0	-37.2	
	Mid Channel (1882.5MHz)									
	3.7650	-7.2	V	3.0	40.5	1.0	-32.3	-13.0	-19.3	
	5.6475	-5.1	V	3.0	40.8	1.0	-44.9	-13.0	-31.9	
	7.5300	-9.4	V	3.0	40.7	1.0	-49.1	-13.0	-36.1	
	3.7650	-5.2	H	3.0	40.5	1.0	-34.3	-13.0	-21.3	
	5.6475	-2.3	H	3.0	40.8	1.0	-37.5	-13.0	-24.5	
	7.5300	-12.0	H	3.0	40.7	1.0	-51.7	-13.0	-38.7	
	High Channel (1905MHz)									
	3.8100	-2.8	V	3.0	40.6	1.0	-36.8	-13.0	-23.8	
	5.7150	-5.2	V	3.0	40.8	1.0	-45.0	-13.0	-32.0	
	7.6200	-12.5	V	3.0	40.7	1.0	-52.2	-13.0	-39.2	
	3.8100	-1.5	H	3.0	40.6	1.0	-38.1	-13.0	-25.1	
	5.7150	-2.1	H	3.0	40.8	1.0	-37.7	-13.0	-24.7	
	7.6200	-14.1	H	3.0	40.7	1.0	-53.7	-13.0	-40.7	
	Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

LTE Band 25 15MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
	Company: Samsung										
	Project #: 15K21157										
	Date: 06-27-15										
	Test Engineer: Steven.Kim										
	Configuration: EUT / AC Adapter / Ear Phone / X-Position										
	Mode: TX, LTE BAND 25, 15MHz BW, QPSK										
	Chamber		Pre-amplifier		Filter		Limit				
	Chamber 2		AFS42		Filter 1		FCC Part 24				
	f GHz		SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1857.5MHz)										
	3.7150		-1.0	V	3.0	40.5	1.0	-38.5	-13.0	-25.5	
	5.5725		-6.3	V	3.0	40.8	1.0	-46.1	-13.0	-33.1	
	7.4300		-12.5	V	3.0	40.8	1.0	-52.3	-13.0	-39.3	
	3.7150		-5.9	H	3.0	40.5	1.0	-33.6	-13.0	-20.6	
	5.5725		-1.7	H	3.0	40.8	1.0	-38.1	-13.0	-25.1	
	7.4300		-10.3	H	3.0	40.8	1.0	-50.0	-13.0	-37.0	
	Mid Channel (1882.5MHz)										
	3.7650		-3.6	V	3.0	40.5	1.0	-36.0	-13.0	-23.0	
	5.6475		-8.1	V	3.0	40.8	1.0	-47.9	-13.0	-34.9	
	7.5300		-12.2	V	3.0	40.7	1.0	-51.9	-13.0	-38.9	
	3.7650		-0.6	H	3.0	40.5	1.0	-39.0	-13.0	-26.0	
	5.6475		-2.3	H	3.0	40.8	1.0	-37.5	-13.0	-24.5	
	7.5300		-12.0	H	3.0	40.7	1.0	-51.7	-13.0	-38.7	
	High Channel (1907.5MHz)										
3.8150		-3.9	V	3.0	40.6	1.0	-35.7	-13.0	-22.7		
5.7225		-5.9	V	3.0	40.8	1.0	-45.7	-13.0	-32.7		
7.6300		-12.8	V	3.0	40.7	1.0	-52.5	-13.0	-39.5		
3.8150		-4.6	H	3.0	40.6	1.0	-44.2	-13.0	-31.2		
5.7225		-2.1	H	3.0	40.8	1.0	-37.7	-13.0	-24.7		
7.6300		-12.0	H	3.0	40.7	1.0	-51.7	-13.0	-38.7		
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.											
LTE Band 25 15MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
	Company: Samsung										
	Project #: 15K21157										
	Date: 06-27-15										
	Test Engineer: Steven.Kim										
	Configuration: EUT / AC Adapter / Ear Phone / X-Position										
	Mode: TX, LTE BAND 25, 15MHz BW, 16QAM										
	Chamber		Pre-amplifier		Filter		Limit				
	Chamber 2		AFS42		Filter 1		FCC Part 24				
	f GHz		SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1857.5MHz)										
	3.7150		-0.1	V	3.0	40.5	1.0	-39.4	-13.0	-26.4	
	5.5725		-7.2	V	3.0	40.8	1.0	-47.1	-13.0	-34.1	
	7.4300		-12.2	V	3.0	40.8	1.0	-51.9	-13.0	-38.9	
	3.7150		-4.9	H	3.0	40.5	1.0	-34.6	-13.0	-21.6	
	5.5725		-0.3	H	3.0	40.8	1.0	-39.5	-13.0	-26.5	
	7.4300		-11.7	H	3.0	40.8	1.0	-51.5	-13.0	-38.5	
	Mid Channel (1882.5MHz)										
	3.7650		-2.5	V	3.0	40.5	1.0	-37.1	-13.0	-24.1	
	5.6475		-9.1	V	3.0	40.8	1.0	-48.9	-13.0	-35.9	
	7.5300		-13.2	V	3.0	40.7	1.0	-52.9	-13.0	-39.9	
	3.7650		-0.4	H	3.0	40.5	1.0	-40.0	-13.0	-27.0	
	5.6475		-1.3	H	3.0	40.8	1.0	-38.5	-13.0	-25.5	
	7.5300		-13.1	H	3.0	40.7	1.0	-52.8	-13.0	-39.8	
	High Channel (1907.5MHz)										
3.8150		-2.9	V	3.0	40.6	1.0	-36.7	-13.0	-23.7		
5.7225		-6.9	V	3.0	40.8	1.0	-46.7	-13.0	-33.7		
7.6300		-13.7	V	3.0	40.7	1.0	-53.4	-13.0	-40.4		
3.8150		-5.6	H	3.0	40.6	1.0	-45.2	-13.0	-32.2		
5.7225		-1.1	H	3.0	40.8	1.0	-38.7	-13.0	-25.7		
7.6300		-13.0	H	3.0	40.7	1.0	-52.7	-13.0	-39.7		
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.											

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-27-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Ear Phone / X-Position								
Mode:		TX, LTE BAND 25, 10MHz BW,QPSK								
LTE Band 25 10MHz QPSK	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 24			
	f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1855MHz)									
	3.7100	-2.9	V	3.0	40.5	1.0	-36.6	-13.0	-23.6	
	5.5650	-9.3	V	3.0	40.8	1.0	-49.1	-13.0	-36.1	
	7.4450	-12.2	V	3.0	40.8	1.0	-52.0	-13.0	-39.0	
	3.7100	-1.0	H	3.0	40.5	1.0	-38.5	-13.0	-25.5	
	5.5650	-0.8	H	3.0	40.8	1.0	-40.6	-13.0	-27.6	
	7.4450	-14.0	H	3.0	40.8	1.0	-53.8	-13.0	-40.8	
	Mid Channel (1882.5MHz)									
	3.7650	-1.8	V	3.0	40.5	1.0	-37.7	-13.0	-24.7	
	5.6475	-10.1	V	3.0	40.8	1.0	-49.9	-13.0	-36.9	
	7.5300	-12.2	V	3.0	40.7	1.0	-51.9	-13.0	-38.9	
	3.7650	-2.9	H	3.0	40.5	1.0	-42.4	-13.0	-29.4	
	5.6475	-3.3	H	3.0	40.8	1.0	-43.1	-13.0	-30.1	
	7.5300	-12.0	H	3.0	40.7	1.0	-51.7	-13.0	-38.7	
	High Channel (1910MHz)									
	3.8200	-0.8	V	3.0	40.6	1.0	-38.8	-13.0	-25.8	
	5.7300	-8.9	V	3.0	40.8	1.0	-48.7	-13.0	-35.7	
	7.6400	-13.1	V	3.0	40.7	1.0	-52.8	-13.0	-39.8	
	3.8200	-1.5	H	3.0	40.6	1.0	-41.1	-13.0	-28.1	
	5.7300	-1.9	H	3.0	40.8	1.0	-41.7	-13.0	-28.7	
	7.6400	-14.1	H	3.0	40.7	1.0	-53.7	-13.0	-40.7	
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										
UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-27-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Ear Phone / X-Position								
Mode:		TX, LTE BAND 25, 10MHz BW,16QAM								
LTE Band 25 10MHz 16QAM	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 24			
	f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1855MHz)									
	3.7100	-2.3	V	3.0	40.5	1.0	-37.2	-13.0	-24.2	
	5.5650	-10.3	V	3.0	40.8	1.0	-50.1	-13.0	-37.1	
	7.4450	-13.2	V	3.0	40.8	1.0	-53.0	-13.0	-40.0	
	3.7100	-0.0	H	3.0	40.5	1.0	-39.5	-13.0	-26.5	
	5.5650	-1.7	H	3.0	40.8	1.0	-41.6	-13.0	-28.6	
	7.4450	-15.0	H	3.0	40.8	1.0	-54.8	-13.0	-41.8	
	Mid Channel (1882.5MHz)									
	3.7650	-0.8	V	3.0	40.5	1.0	-38.8	-13.0	-25.8	
	5.6475	-11.1	V	3.0	40.8	1.0	-50.9	-13.0	-37.9	
	7.5300	-13.2	V	3.0	40.7	1.0	-52.9	-13.0	-39.9	
	3.7650	-3.8	H	3.0	40.5	1.0	-43.4	-13.0	-30.4	
	5.6475	-4.1	H	3.0	40.8	1.0	-43.9	-13.0	-30.9	
	7.5300	-3.0	H	3.0	40.7	1.0	-42.7	-13.0	-29.7	
	High Channel (1910MHz)									
	3.8200	-0.3	V	3.0	40.6	1.0	-39.9	-13.0	-26.9	
	5.7300	-9.9	V	3.0	40.8	1.0	-49.7	-13.0	-36.7	
	7.6400	-14.1	V	3.0	40.7	1.0	-53.8	-13.0	-40.8	
	3.8200	-2.5	H	3.0	40.6	1.0	-42.1	-13.0	-29.1	
	5.7300	-3.0	H	3.0	40.8	1.0	-42.8	-13.0	-29.8	
	7.6400	-15.1	H	3.0	40.7	1.0	-54.7	-13.0	-41.7	
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										

LTE Band 25 5MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 15K21157									
	Date: 06-27-15									
	Test Engineer: Steven.Kim									
	Configuration: EUT / AC Adapter / Ear Phone / X-Position									
	Mode: TX, LTE BAND 25, 5MHz BW, QPSK									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 24			
	f	SGreading	Ant. Pol.	Distance	Preamp	Filter	ERP	Limit	Delta	Notes
	GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)	
	Low Channel (1852.5MHz)									
	3.7050	-1.9	V	3.0	40.5	1.0	-37.6	-13.0	-24.6	
	5.5575	-7.8	V	3.0	40.8	1.0	-47.6	-13.0	-34.6	
	7.4100	-14.2	V	3.0	40.8	1.0	-54.0	-13.0	-41.0	
	3.7050	0.0	H	3.0	40.5	1.0	-39.5	-13.0	-26.5	
	5.5575	-1.4	H	3.0	40.8	1.0	-41.2	-13.0	-28.2	
	7.4100	-12.0	H	3.0	40.8	1.0	-51.8	-13.0	-38.8	
	Mid Channel (1882.5MHz)									
	3.7650	2.9	V	3.0	40.5	1.0	-36.7	-13.0	-23.7	
	5.6475	-9.5	V	3.0	40.8	1.0	-49.3	-13.0	-36.3	
	7.5300	-12.2	V	3.0	40.7	1.0	-51.9	-13.0	-38.9	
	3.7650	-2.0	H	3.0	40.5	1.0	-41.5	-13.0	-28.5	
	5.6475	-4.1	H	3.0	40.8	1.0	-43.9	-13.0	-30.9	
7.5300	-13.1	H	3.0	40.7	1.0	-52.8	-13.0	-39.8		
High Channel (1912.5MHz)										
3.8250	-1.3	V	3.0	40.6	1.0	-40.9	-13.0	-27.9		
5.7375	-8.0	V	3.0	40.8	1.0	-47.8	-13.0	-34.8		
7.6500	-12.1	V	3.0	40.6	1.0	-51.8	-13.0	-38.8		
3.8250	-2.9	H	3.0	40.6	1.0	-42.5	-13.0	-29.5		
5.7375	-3.0	H	3.0	40.8	1.0	-42.7	-13.0	-29.7		
7.6500	-14.0	H	3.0	40.6	1.0	-53.6	-13.0	-40.6		
Rev.03.03.09										
Note: No other emissions were detected above the system noise floor.										
LTE Band 25 5MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 15K21157									
	Date: 06-27-15									
	Test Engineer: Steven.Kim									
	Configuration: EUT / AC Adapter / Ear Phone / X-Position									
	Mode: TX, LTE BAND 25, 5MHz BW, 16QAM									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 24			
	f	SGreading	Ant. Pol.	Distance	Preamp	Filter	ERP	Limit	Delta	Notes
	GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)	
	Low Channel (1852.5MHz)									
	3.7050	0.9	V	3.0	40.5	1.0	-38.6	-13.0	-25.6	
	5.5575	-8.8	V	3.0	40.8	1.0	-48.6	-13.0	-35.6	
	7.4100	-15.2	V	3.0	40.8	1.0	-55.0	-13.0	-42.0	
	3.7050	-1.0	H	3.0	40.5	1.0	-40.5	-13.0	-27.5	
	5.5575	-2.4	H	3.0	40.8	1.0	-42.2	-13.0	-29.2	
	7.4100	-13.0	H	3.0	40.8	1.0	-52.8	-13.0	-39.8	
	Mid Channel (1882.5MHz)									
	3.7650	2.5	V	3.0	40.5	1.0	-37.0	-13.0	-24.0	
	5.6475	-10.1	V	3.0	40.8	1.0	-49.9	-13.0	-36.9	
	7.5300	-13.2	V	3.0	40.7	1.0	-52.9	-13.0	-39.9	
	3.7650	-3.0	H	3.0	40.5	1.0	-42.5	-13.0	-29.5	
	5.6475	-5.1	H	3.0	40.8	1.0	-44.9	-13.0	-31.9	
7.5300	-14.2	H	3.0	40.7	1.0	-53.9	-13.0	-40.9		
High Channel (1912.5MHz)										
3.8250	-2.3	V	3.0	40.6	1.0	-41.9	-13.0	-28.9		
5.7375	-9.0	V	3.0	40.8	1.0	-48.8	-13.0	-35.8		
7.6500	-13.2	V	3.0	40.6	1.0	-52.9	-13.0	-39.9		
3.8250	-4.0	H	3.0	40.6	1.0	-43.6	-13.0	-30.6		
5.7375	-4.3	H	3.0	40.8	1.0	-44.1	-13.0	-31.1		
7.6500	-15.0	H	3.0	40.6	1.0	-54.7	-13.0	-41.7		
Rev.03.03.09										
Note: No other emissions were detected above the system noise floor.										

		UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
		Company: Samsung										
		Project #: 15K21157										
		Date: 06-27-15										
		Test Engineer: Steven.Kim										
		Configuration: EUT / AC Adapter / Ear Phone / X-Position										
		Mode: TX, LTE BAND 25, 3MHz BW,QPSK										
		Chamber		Pre-amplifier		Filter		Limit				
		Chamber 2		AFS42		Filter 1		FCC Part 24				
LTE Band 25 3MHz QPSK		f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	
	Low Channel (1851.5MHz)											
		3.7030	-1.2	V	3.0	40.5	1.0	-38.3	-13.0	-25.3		
		5.5545	-6.3	V	3.0	40.8	1.0	-46.2	-13.0	-33.2		
		7.4060	-16.2	V	3.0	40.8	1.0	-55.9	-13.0	-42.9		
		3.7030	-4.0	H	3.0	40.5	1.0	-43.5	-13.0	-30.5		
		5.5545	-1.4	H	3.0	40.8	1.0	-41.2	-13.0	-28.2		
		7.4060	-14.0	H	3.0	40.8	1.0	-53.8	-13.0	-40.8		
	Mid Channel (1882.5MHz)											
		3.7650	-1.6	V	3.0	40.5	1.0	-38.0	-13.0	-25.0		
		5.6475	-8.2	V	3.0	40.8	1.0	-48.0	-13.0	-35.0		
		7.5300	-13.2	V	3.0	40.7	1.0	-52.9	-13.0	-39.9		
		3.7650	-1.2	H	3.0	40.5	1.0	-38.3	-13.0	-25.3		
		5.6475	-3.1	H	3.0	40.8	1.0	-42.9	-13.0	-29.9		
		7.5300	-14.0	H	3.0	40.7	1.0	-53.7	-13.0	-40.7		
	High Channel (1913.5MHz)											
		3.8270	-0.6	V	3.0	40.6	1.0	-40.2	-13.0	-27.2		
		5.7405	-12.9	V	3.0	40.8	1.0	-52.7	-13.0	-39.7		
		7.6540	-16.1	V	3.0	40.6	1.0	-55.8	-13.0	-42.8		
		3.8270	-3.7	H	3.0	40.6	1.0	-43.3	-13.0	-30.3		
		5.7405	-1.2	H	3.0	40.8	1.0	-38.6	-13.0	-25.6		
		7.6540	-14.2	H	3.0	40.6	1.0	-53.8	-13.0	-40.8		
		Rev. 03.03.09										
		Note: No other emissions were detected above the system noise floor.										
			UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung										
		Project #: 15K21157										
		Date: 06-27-15										
		Test Engineer: Steven.Kim										
		Configuration: EUT / AC Adapter / Ear Phone / X-Position										
		Mode: TX, LTE BAND 25, 3MHz BW,16QAM										
		Chamber		Pre-amplifier		Filter		Limit				
		Chamber 2		AFS42		Filter 1		FCC Part 24				
LTE Band 25 3MHz 16QAM		f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	
	Low Channel (1851.5MHz)											
		3.7030	-0.8	V	3.0	40.5	1.0	-40.3	-13.0	-27.3		
		5.5545	-8.3	V	3.0	40.8	1.0	-48.1	-13.0	-35.1		
		7.4060	-18.2	V	3.0	40.8	1.0	-58.0	-13.0	-45.0		
		3.7030	-6.0	H	3.0	40.5	1.0	-45.5	-13.0	-32.5		
		5.5545	-3.5	H	3.0	40.8	1.0	-43.3	-13.0	-30.3		
		7.4060	-16.0	H	3.0	40.8	1.0	-55.8	-13.0	-42.8		
	Mid Channel (1882.5MHz)											
		3.7650	-0.6	V	3.0	40.5	1.0	-39.0	-13.0	-26.0		
		5.6475	-9.2	V	3.0	40.8	1.0	-49.0	-13.0	-36.0		
		7.5300	-14.2	V	3.0	40.7	1.0	-53.9	-13.0	-40.9		
		3.7650	-0.0	H	3.0	40.5	1.0	-39.5	-13.0	-26.5		
		5.6475	-4.1	H	3.0	40.8	1.0	-43.9	-13.0	-30.9		
		7.5300	-15.0	H	3.0	40.7	1.0	-54.7	-13.0	-41.7		
	High Channel (1913.5MHz)											
		3.8270	-1.6	V	3.0	40.6	1.0	-41.2	-13.0	-28.2		
		5.7405	-13.8	V	3.0	40.8	1.0	-53.6	-13.0	-40.6		
		7.6540	-17.2	V	3.0	40.6	1.0	-56.8	-13.0	-43.8		
		3.8270	-4.5	H	3.0	40.6	1.0	-44.1	-13.0	-31.1		
		5.7405	-0.2	H	3.0	40.8	1.0	-39.6	-13.0	-26.6		
		7.6540	-15.1	H	3.0	40.6	1.0	-54.7	-13.0	-41.7		
		Rev. 03.03.09										
		Note: No other emissions were detected above the system noise floor.										

UL Korea, Ltd Suwon Laboratory										
Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-29-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Earphone, X Position								
Mode:		TX, LTE BAND 12, 5MHz BW,QPSK								

UL Korea, Ltd Suwon Laboratory										
Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-29-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Earphone, X Position								
Mode:		TX, LTE BAND 12, 3MHz BW,QPSK								
LTE Band 12 3MHz QPSK	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		Part 27			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (700.5MHz)									
	1.4010	-34.3	V	3.0	39.0	1.0	-72.3	-13.0	-59.3	
	2.1015	-33.6	V	3.0	39.3	1.0	-71.9	-13.0	-58.9	
	2.8020	-33.3	V	3.0	39.7	1.0	-72.0	-13.0	-59.0	
	1.4010	-26.4	H	3.0	39.0	1.0	-64.4	-13.0	-51.4	
	2.1015	-26.8	H	3.0	39.3	1.0	-65.1	-13.0	-52.1	
	2.8020	-28.1	H	3.0	39.7	1.0	-66.8	-13.0	-53.8	
	Mid Channel (707.5MHz)									
	1.4150	-32.9	V	3.0	39.0	1.0	-70.9	-13.0	-57.9	
	2.1225	-34.9	V	3.0	39.3	1.0	-73.2	-13.0	-60.2	
	2.8300	-37.4	V	3.0	39.7	1.0	-76.1	-13.0	-63.1	
	1.4150	-23.2	H	3.0	39.0	1.0	-61.2	-13.0	-48.2	
	2.1225	-28.9	H	3.0	39.3	1.0	-67.2	-13.0	-54.2	
	2.8300	-33.2	H	3.0	39.7	1.0	-71.9	-13.0	-58.9	
	High Channel (714.5MHz)									
	1.4290	-33.5	V	3.0	39.0	1.0	-71.5	-13.0	-58.5	
	2.1435	-34.1	V	3.0	39.3	1.0	-72.5	-13.0	-59.5	
	2.8580	-34.7	V	3.0	39.7	1.0	-73.4	-13.0	-60.4	
	1.4290	-24.4	H	3.0	39.0	1.0	-62.5	-13.0	-49.5	
	2.1435	-29.8	H	3.0	39.3	1.0	-68.1	-13.0	-55.1	
	2.8580	-31.3	H	3.0	39.7	1.0	-70.1	-13.0	-57.1	
	Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.										

UL Korea, Ltd Suwon Laboratory										
Above 1GHz High Frequency Substitution Measurement										
Company:		Samsung								
Project #:		15K21157								
Date:		06-29-15								
Test Engineer:		Steven.Kim								
Configuration:		EUT / AC Adapter / Earphone, X Position								
Mode:		TX, LTE BAND 12, 3MHz BW,16QAM								
LTE Band 12 3MHz 16QAM	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		Part 27			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (700.5MHz)									
	1.4010	-35.3	V	3.0	39.0	1.0	-73.3	-13.0	-60.3	
	2.1015	-34.5	V	3.0	39.3	1.0	-72.8	-13.0	-59.8	
	2.8020	-34.3	V	3.0	39.7	1.0	-73.0	-13.0	-60.0	
	1.4010	-26.6	H	3.0	39.0	1.0	-64.6	-13.0	-51.6	
	2.1015	-28.5	H	3.0	39.3	1.0	-66.8	-13.0	-53.8	
	2.8020	-28.7	H	3.0	39.7	1.0	-67.4	-13.0	-54.4	
	Mid Channel (707.5MHz)									
	1.4150	-33.8	V	3.0	39.0	1.0	-71.8	-13.0	-58.8	
	2.1225	-36.0	V	3.0	39.3	1.0	-74.3	-13.0	-61.3	
	2.8300	-37.6	V	3.0	39.7	1.0	-76.4	-13.0	-63.4	
	1.4150	-23.5	H	3.0	39.0	1.0	-61.5	-13.0	-48.5	
	2.1225	-29.8	H	3.0	39.3	1.0	-68.1	-13.0	-55.1	
	2.8300	-34.4	H	3.0	39.7	1.0	-73.1	-13.0	-60.1	
	High Channel (714.5MHz)									
	1.4290	-34.1	V	3.0	39.0	1.0	-72.1	-13.0	-59.1	
	2.1435	-35.3	V	3.0	39.3	1.0	-73.6	-13.0	-60.6	
	2.8580	-35.9	V	3.0	39.7	1.0	-74.6	-13.0	-61.6	
	1.4290	-25.4	H	3.0	39.0	1.0	-63.5	-13.0	-50.5	
	2.1435	-31.5	H	3.0	39.3	1.0	-69.8	-13.0	-56.8	
	2.8580	-31.7	H	3.0	39.7	1.0	-70.4	-13.0	-57.4	
	Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.										

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
LTE Band 12 1.4MHz QPSK	Company: Samsung Project #: 15K21157 Date: 06-29-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Earphone, X Position Mode: TX, LTE BAND 12, 1.4MHz BW,QPSK									
	Chamber: Chamber 2 Pre-amplifier: AFS42 Filter: Filter 1 Limit: Part 27									
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (699.7MHz)									
	1.3994	-34.5	V	3.0	39.0	1.0	-72.5	-13.0	-59.5	
	2.0991	-32.9	V	3.0	39.3	1.0	-71.2	-13.0	-58.2	
	2.7988	-32.6	V	3.0	39.7	1.0	-71.3	-13.0	-58.3	
	1.3994	-25.6	H	3.0	39.0	1.0	-63.6	-13.0	-50.6	
	2.0991	-27.5	H	3.0	39.3	1.0	-65.8	-13.0	-52.8	
	2.7988	-27.7	H	3.0	39.7	1.0	-66.4	-13.0	-53.4	
	Mid Channel (707.5MHz)									
	1.4150	-32.3	V	3.0	39.0	1.0	-70.3	-13.0	-57.3	
	2.1225	-35.1	V	3.0	39.3	1.0	-73.4	-13.0	-60.4	
	2.8300	-36.7	V	3.0	39.7	1.0	-75.4	-13.0	-62.4	
	1.4150	-23.2	H	3.0	39.0	1.0	-61.2	-13.0	-48.2	
	2.1225	-29.5	H	3.0	39.3	1.0	-67.8	-13.0	-54.8	
	2.8300	-32.8	H	3.0	39.7	1.0	-71.5	-13.0	-58.5	
	High Channel (715.3MHz)									
	1.4306	-33.7	V	3.0	39.0	1.0	-71.7	-13.0	-58.7	
	2.1459	-33.9	V	3.0	39.3	1.0	-72.3	-13.0	-59.3	
	2.8612	-35.2	V	3.0	39.7	1.0	-73.9	-13.0	-60.9	
	1.4306	-25.2	H	3.0	39.0	1.0	-63.2	-13.0	-50.2	
	2.1459	-30.5	H	3.0	39.3	1.0	-68.8	-13.0	-55.8	
	2.8612	-31.0	H	3.0	39.7	1.0	-69.7	-13.0	-56.7	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										
UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement										
LTE Band 12 1.4MHz 16QAM	Company: Samsung Project #: 15K21157 Date: 06-29-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Earphone, X Position Mode: TX, LTE BAND 12, 1.4MHz BW,16QAM									
	Chamber: Chamber 2 Pre-amplifier: AFS42 Filter: Filter 1 Limit: Part 27									
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (699.7MHz)									
	1.3994	-35.5	V	3.0	39.0	1.0	-73.5	-13.0	-60.5	
	2.0991	-33.9	V	3.0	39.3	1.0	-72.2	-13.0	-59.2	
	2.7988	-33.6	V	3.0	39.7	1.0	-72.3	-13.0	-59.3	
	1.3994	-26.6	H	3.0	39.0	1.0	-64.6	-13.0	-51.6	
	2.0991	-28.5	H	3.0	39.3	1.0	-66.8	-13.0	-53.8	
	2.7988	-28.7	H	3.0	39.7	1.0	-67.4	-13.0	-54.4	
	Mid Channel (707.5MHz)									
	1.4150	-33.3	V	3.0	39.0	1.0	-71.3	-13.0	-58.3	
	2.1225	-35.9	V	3.0	39.3	1.0	-74.2	-13.0	-61.2	
	2.8300	-36.7	V	3.0	39.7	1.0	-75.4	-13.0	-62.4	
	1.4150	-24.2	H	3.0	39.0	1.0	-62.2	-13.0	-49.2	
	2.1225	-29.8	H	3.0	39.3	1.0	-68.1	-13.0	-55.1	
	2.8300	-33.8	H	3.0	39.7	1.0	-72.5	-13.0	-59.5	
	High Channel (715.3MHz)									
	1.4306	-34.2	V	3.0	39.0	1.0	-72.2	-13.0	-59.2	
	2.1459	-35.0	V	3.0	39.3	1.0	-73.4	-13.0	-60.4	
	2.8612	-35.3	V	3.0	39.7	1.0	-74.0	-13.0	-61.0	
	1.4306	-25.5	H	3.0	39.0	1.0	-63.5	-13.0	-50.5	
	2.1459	-30.9	H	3.0	39.3	1.0	-69.3	-13.0	-56.3	
	2.8612	-31.7	H	3.0	39.7	1.0	-70.4	-13.0	-57.4	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										

LTE Band 4 15MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 15K21157									
	Date: 06-27-15									
	Test Engineer: Steven.Kim									
	Configuration: EUT / AC Adapter / Ear Phone / X-Position									
	Mode: TX, LTE BAND 4, 15MHz BW,QPSK									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 27			
	f	SG reading	Ant. Pol.	Distance	Preamp	Filter	ERP	Limit	Delta	Notes
	GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)	
	Low Channel (1717.5MHz)									
	3.4350	-34.8	V	3.0	40.2	1.0	-74.1	-13.0	-61.1	
	5.1525	-32.2	V	3.0	40.9	1.0	-72.1	-13.0	-59.1	
	6.8700	-29.3	V	3.0	41.0	1.0	-69.3	-13.0	-56.3	
	3.4350	-34.9	H	3.0	40.2	1.0	-74.1	-13.0	-61.1	
	5.1525	-31.2	H	3.0	40.9	1.0	-71.1	-13.0	-58.1	
	6.8700	-29.1	H	3.0	41.0	1.0	-69.1	-13.0	-56.1	
	Mid Channel (1732.5MHz)									
	3.4650	-34.5	V	3.0	40.3	1.0	-73.8	-13.0	-60.8	
	5.1975	-31.7	V	3.0	40.9	1.0	-71.6	-13.0	-58.6	
	6.9300	-28.8	V	3.0	41.0	1.0	-68.8	-13.0	-55.8	
	3.4650	-34.8	H	3.0	40.3	1.0	-74.1	-13.0	-61.1	
	5.1975	-31.4	H	3.0	40.9	1.0	-71.3	-13.0	-58.3	
6.9300	-29.9	H	3.0	41.0	1.0	-69.9	-13.0	-56.9		
High Channel (1747.5MHz)										
3.4950	-33.9	V	3.0	40.3	1.0	-73.1	-13.0	-60.1		
5.2425	-31.8	V	3.0	40.9	1.0	-71.7	-13.0	-58.7		
6.9900	-29.5	V	3.0	41.0	1.0	-69.5	-13.0	-56.5		
3.4950	-34.0	H	3.0	40.3	1.0	-73.3	-13.0	-60.3		
5.2425	-31.4	H	3.0	40.9	1.0	-71.3	-13.0	-58.3		
6.9900	-29.4	H	3.0	41.0	1.0	-69.5	-13.0	-56.5		
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										
LTE Band 4 15MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 15K21157									
	Date: 06-27-15									
	Test Engineer: Steven.Kim									
	Configuration: EUT / AC Adapter / Ear Phone / X-Position									
	Mode: TX, LTE BAND 4, 15MHz BW,16QAM									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 27			
	f	SG reading	Ant. Pol.	Distance	Preamp	Filter	ERP	Limit	Delta	Notes
	GHz	(dBm)	(H/V)	(m)	(dB)	(dB)	(dBm)	(dBm)	(dB)	
	Low Channel (1717.5MHz)									
	3.4350	-34.8	V	3.0	40.2	1.0	-74.0	-13.0	-61.0	
	5.1525	-32.2	V	3.0	40.9	1.0	-72.1	-13.0	-59.1	
	6.8700	-29.3	V	3.0	41.0	1.0	-69.3	-13.0	-56.3	
	3.4350	-34.9	H	3.0	40.2	1.0	-74.1	-13.0	-61.1	
	5.1525	-31.1	H	3.0	40.9	1.0	-71.0	-13.0	-58.0	
	6.8700	-29.1	H	3.0	41.0	1.0	-69.1	-13.0	-56.1	
	Mid Channel (1732.5MHz)									
	3.4650	-35.5	V	3.0	40.3	1.0	-74.7	-13.0	-61.7	
	5.1975	-31.7	V	3.0	40.9	1.0	-71.6	-13.0	-58.6	
	6.9300	-28.7	V	3.0	41.0	1.0	-68.7	-13.0	-55.7	
	3.4650	-34.8	H	3.0	40.3	1.0	-74.1	-13.0	-61.1	
	5.1975	-31.3	H	3.0	40.9	1.0	-71.2	-13.0	-58.2	
6.9300	-29.9	H	3.0	41.0	1.0	-69.9	-13.0	-56.9		
High Channel (1747.5MHz)										
3.4950	-33.9	V	3.0	40.3	1.0	-73.2	-13.0	-60.2		
5.2425	-31.8	V	3.0	40.9	1.0	-71.7	-13.0	-58.7		
6.9900	-30.5	V	3.0	41.0	1.0	-70.5	-13.0	-57.5		
3.4950	-34.6	H	3.0	40.3	1.0	-73.8	-13.0	-60.8		
5.2425	-31.4	H	3.0	40.9	1.0	-71.3	-13.0	-58.3		
6.9900	-29.5	H	3.0	41.0	1.0	-69.5	-13.0	-56.5		
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										

LTE Band 4 10MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 4, 10MHz BW, QPSK									
	Chamber Chamber 2		Pre-amplifier AFS42		Filter Filter 1		Limit FCC Part 27			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1715MHz)									
	3.4300	-34.6	V	3.0	40.2	1.0	-73.9	-13.0	-60.9	
	5.1450	-30.8	V	3.0	40.9	1.0	-70.7	-13.0	-57.7	
	6.8600	-28.6	V	3.0	41.0	1.0	-68.6	-13.0	-55.6	
	3.4300	-35.0	H	3.0	40.2	1.0	-74.3	-13.0	-61.3	
	5.1450	-31.4	H	3.0	40.9	1.0	-71.3	-13.0	-58.3	
	6.8600	-28.8	H	3.0	41.0	1.0	-68.8	-13.0	-55.8	
	Mid Channel (1732.5MHz)									
	3.4650	-34.3	V	3.0	40.3	1.0	-73.6	-13.0	-60.6	
	5.1975	-31.0	V	3.0	40.9	1.0	-70.9	-13.0	-57.9	
	6.9300	-27.8	V	3.0	41.0	1.0	-67.8	-13.0	-54.8	
	3.4650	-34.9	H	3.0	40.3	1.0	-74.1	-13.0	-61.1	
	5.1975	-31.9	H	3.0	40.9	1.0	-71.7	-13.0	-58.7	
	6.9300	-28.7	H	3.0	41.0	1.0	-68.7	-13.0	-55.7	
	High Channel (1750MHz)									
	3.5000	-33.9	V	3.0	40.3	1.0	-73.2	-13.0	-60.2	
	5.2500	-31.2	V	3.0	40.9	1.0	-71.0	-13.0	-58.0	
	7.0000	-28.7	V	3.0	41.0	1.0	-68.7	-13.0	-55.7	
	3.5000	-34.1	H	3.0	40.3	1.0	-73.4	-13.0	-60.4	
	5.2500	-31.2	H	3.0	40.9	1.0	-71.0	-13.0	-58.0	
7.0000	-29.6	H	3.0	41.0	1.0	-69.7	-13.0	-56.7		
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										
LTE Band 4 10MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 4, 10MHz BW, 16QAM									
	Chamber Chamber 2		Pre-amplifier AFS42		Filter Filter 1		Limit FCC Part 27			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1715MHz)									
	3.4300	-34.6	V	3.0	40.2	1.0	-73.9	-13.0	-60.9	
	5.1450	-30.7	V	3.0	40.9	1.0	-70.6	-13.0	-57.6	
	6.8600	-28.7	V	3.0	41.0	1.0	-68.6	-13.0	-55.6	
	3.4300	-35.0	H	3.0	40.2	1.0	-74.3	-13.0	-61.3	
	5.1450	-31.5	H	3.0	40.9	1.0	-71.4	-13.0	-58.4	
	6.8600	-28.8	H	3.0	41.0	1.0	-68.8	-13.0	-55.8	
	Mid Channel (1732.5MHz)									
	3.4650	-34.3	V	3.0	40.3	1.0	-73.6	-13.0	-60.6	
	5.1975	-31.0	V	3.0	40.9	1.0	-70.9	-13.0	-57.9	
	6.9300	-27.8	V	3.0	41.0	1.0	-67.8	-13.0	-54.8	
	3.4650	-34.9	H	3.0	40.3	1.0	-74.1	-13.0	-61.1	
	5.1975	-31.8	H	3.0	40.9	1.0	-71.7	-13.0	-58.7	
	6.9300	-28.6	H	3.0	41.0	1.0	-68.6	-13.0	-55.6	
	High Channel (1750MHz)									
	3.5000	-35.1	V	3.0	40.3	1.0	-74.4	-13.0	-61.4	
	5.2500	-31.1	V	3.0	40.9	1.0	-71.0	-13.0	-58.0	
	7.0000	-28.7	V	3.0	41.0	1.0	-68.8	-13.0	-55.8	
	3.5000	-34.1	H	3.0	40.3	1.0	-73.4	-13.0	-60.4	
	5.2500	-31.1	H	3.0	40.9	1.0	-70.9	-13.0	-57.9	
7.0000	-29.7	H	3.0	41.0	1.0	-69.7	-13.0	-56.7		
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										

LTE Band 4 5MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 4, 5MHz BW, QPSK									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 27			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1712.5MHz)									
	3.4250	-34.7	V	3.0	40.2	1.0	-73.9	-13.0	-60.9	
	5.1375	-31.2	V	3.0	40.9	1.0	-71.1	-13.0	-58.1	
	6.5800	-28.9	V	3.0	40.9	1.0	-68.8	-13.0	-55.8	
	3.4250	-35.0	H	3.0	40.2	1.0	-74.2	-13.0	-61.2	
	5.1375	-30.8	H	3.0	40.9	1.0	-70.7	-13.0	-57.7	
	6.5800	-29.1	H	3.0	40.9	1.0	-69.0	-13.0	-56.0	
	Mid Channel (1732.5MHz)									
	3.4650	-34.3	V	3.0	40.3	1.0	-73.6	-13.0	-60.6	
	5.1975	-31.3	V	3.0	40.9	1.0	-71.2	-13.0	-58.2	
	6.9300	-27.8	V	3.0	41.0	1.0	-67.8	-13.0	-54.8	
	3.4650	-34.7	H	3.0	40.3	1.0	-74.0	-13.0	-61.0	
	5.1975	-31.1	H	3.0	40.9	1.0	-71.0	-13.0	-58.0	
	6.9300	-28.5	H	3.0	41.0	1.0	-68.5	-13.0	-55.5	
	High Channel (1752.5MHz)									
	3.5050	-33.9	V	3.0	40.3	1.0	-73.2	-13.0	-60.2	
	5.2575	-31.3	V	3.0	40.9	1.0	-71.1	-13.0	-58.1	
	7.0100	-29.7	V	3.0	41.0	1.0	-69.7	-13.0	-56.7	
	3.5050	-33.9	H	3.0	40.3	1.0	-73.2	-13.0	-60.2	
5.2575	-31.1	H	3.0	40.9	1.0	-71.0	-13.0	-58.0		
7.0100	-29.6	H	3.0	41.0	1.0	-69.6	-13.0	-56.6		
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										
LTE Band 4 5MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 7, 5MHz BW, 16QAM									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 27			
	f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1712.5MHz)									
	3.4250	-34.7	V	3.0	40.2	1.0	-73.9	-13.0	-60.9	
	5.1375	-31.2	V	3.0	40.9	1.0	-71.1	-13.0	-58.1	
	6.5800	-28.8	V	3.0	40.9	1.0	-68.7	-13.0	-55.7	
	3.4250	-35.0	H	3.0	40.2	1.0	-74.2	-13.0	-61.2	
	5.1375	-30.8	H	3.0	40.9	1.0	-70.7	-13.0	-57.7	
	6.5800	-29.0	H	3.0	40.9	1.0	-68.9	-13.0	-55.9	
	Mid Channel (1732.5MHz)									
	3.4650	-34.0	V	3.0	40.3	1.0	-73.2	-13.0	-60.2	
	5.1975	-31.3	V	3.0	40.9	1.0	-71.2	-13.0	-58.2	
	6.9300	-27.8	V	3.0	41.0	1.0	-67.8	-13.0	-54.8	
	3.4650	-34.7	H	3.0	40.3	1.0	-74.0	-13.0	-61.0	
	5.1975	-32.1	H	3.0	40.9	1.0	-72.0	-13.0	-59.0	
	6.9300	-28.5	H	3.0	41.0	1.0	-68.5	-13.0	-55.5	
	High Channel (1752.5MHz)									
	3.5050	-33.9	V	3.0	40.3	1.0	-73.2	-13.0	-60.2	
	5.2575	-31.3	V	3.0	40.9	1.0	-71.1	-13.0	-58.1	
	7.0100	-29.4	V	3.0	41.0	1.0	-69.4	-13.0	-56.4	
	3.5050	-34.0	H	3.0	40.3	1.0	-73.3	-13.0	-60.3	
5.2575	-31.1	H	3.0	40.9	1.0	-71.0	-13.0	-58.0		
7.0100	-29.5	H	3.0	41.0	1.0	-69.6	-13.0	-56.6		
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										

LTE Band 4 3MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 4, 3MHz BW,QPSK									
	Chamber Pre-amplifier Filter Limit Chamber 2 AFS42 Filter 1 FCC Part 27									
	f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1711.5MHz)									
	3.4230	-34.9	V	3.0	40.2	1.0	-74.1	-13.0	-61.1	
	5.1345	-31.7	V	3.0	40.9	1.0	-71.6	-13.0	-58.6	
	6.8460	-29.0	V	3.0	41.0	1.0	-69.0	-13.0	-56.0	
	3.4230	-35.0	H	3.0	40.2	1.0	-74.2	-13.0	-61.2	
	5.1345	-31.3	H	3.0	40.9	1.0	-71.2	-13.0	-58.2	
	6.8460	-28.8	H	3.0	41.0	1.0	-68.7	-13.0	-55.7	
	Mid Channel (1732.5MHz)									
	3.4650	-34.7	V	3.0	40.3	1.0	-73.9	-13.0	-60.9	
	5.1975	-32.6	V	3.0	40.9	1.0	-72.5	-13.0	-59.5	
	6.9300	-29.3	V	3.0	41.0	1.0	-69.3	-13.0	-56.3	
	3.4650	-34.8	H	3.0	40.3	1.0	-74.1	-13.0	-61.1	
	5.1975	-31.7	H	3.0	40.9	1.0	-71.6	-13.0	-58.6	
	6.9300	-28.5	H	3.0	41.0	1.0	-68.5	-13.0	-55.5	
	High Channel (1753.5MHz)									
	3.5070	-33.9	V	3.0	40.3	1.0	-73.2	-13.0	-60.2	
	5.2605	-31.1	V	3.0	40.9	1.0	-70.9	-13.0	-57.9	
	7.0140	-29.5	V	3.0	41.0	1.0	-69.5	-13.0	-56.5	
	3.5070	-34.1	H	3.0	40.3	1.0	-73.4	-13.0	-60.4	
	5.2605	-31.8	H	3.0	40.9	1.0	-71.7	-13.0	-58.7	
	7.0140	-29.7	H	3.0	41.0	1.0	-69.8	-13.0	-56.8	
	Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									
LTE Band 4 3MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement Company: Samsung Project #: 15K21157 Date: 06-27-15 Test Engineer: Steven.Kim Configuration: EUT / AC Adapter / Ear Phone / X-Position Mode: TX, LTE BAND 4, 3MHz BW,16QAM									
	Chamber Pre-amplifier Filter Limit Chamber 2 AFS42 Filter 1 FCC Part 27									
	f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1711.5MHz)									
	3.4230	-34.8	V	3.0	40.2	1.0	-74.0	-13.0	-61.0	
	5.1345	-31.7	V	3.0	40.9	1.0	-71.6	-13.0	-58.6	
	6.8460	-28.8	V	3.0	41.0	1.0	-68.8	-13.0	-55.8	
	3.4230	-34.9	H	3.0	40.2	1.0	-74.2	-13.0	-61.2	
	5.1345	-31.3	H	3.0	40.9	1.0	-71.2	-13.0	-58.2	
	6.8460	-28.7	H	3.0	41.0	1.0	-68.7	-13.0	-55.7	
	Mid Channel (1732.5MHz)									
	3.4650	-34.6	V	3.0	40.3	1.0	-73.9	-13.0	-60.9	
	5.1975	-32.6	V	3.0	40.9	1.0	-72.5	-13.0	-59.5	
	6.9300	-29.2	V	3.0	41.0	1.0	-69.2	-13.0	-56.2	
	3.4650	-34.8	H	3.0	40.3	1.0	-74.0	-13.0	-61.0	
	5.1975	-31.8	H	3.0	40.9	1.0	-71.6	-13.0	-58.6	
	6.9300	-28.5	H	3.0	41.0	1.0	-68.5	-13.0	-55.5	
	High Channel (1752.5MHz)									
	3.5070	-33.9	V	3.0	40.3	1.0	-73.2	-13.0	-60.2	
	5.2605	-31.1	V	3.0	40.9	1.0	-71.0	-13.0	-58.0	
	7.0140	-29.5	V	3.0	41.0	1.0	-69.5	-13.0	-56.5	
	3.5070	-34.1	H	3.0	40.3	1.0	-73.4	-13.0	-60.4	
	5.2605	-31.8	H	3.0	40.9	1.0	-71.7	-13.0	-58.7	
	7.0140	-29.7	H	3.0	41.0	1.0	-69.7	-13.0	-56.7	
	Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

LTE Band 4 1.4MHz QPSK	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 15K21157									
	Date: 06-27-15									
	Test Engineer: Steven.Kim									
	Configuration: EUT / AC Adapter / Ear Phone / X-Position									
	Mode: TX, LTE BAND 4, 1.4MHz BW, QPSK									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 27			
	f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1710.7MHz)									
	3.4214	-33.3	V	3.0	40.2	1.0	-72.5	-13.0	-59.5	
	5.1321	-32.4	V	3.0	40.9	1.0	-72.3	-13.0	-59.3	
	6.8428	-29.1	V	3.0	41.0	1.0	-69.0	-13.0	-56.0	
	3.4214	-33.3	H	3.0	40.2	1.0	-72.6	-13.0	-59.6	
	5.1321	-31.4	H	3.0	40.9	1.0	-71.3	-13.0	-58.3	
	6.8428	-29.0	H	3.0	41.0	1.0	-69.0	-13.0	-56.0	
	Mid Channel (1732.5MHz)									
	3.4650	-34.3	V	3.0	40.3	1.0	-73.6	-13.0	-60.6	
	5.1975	-30.9	V	3.0	40.9	1.0	-70.8	-13.0	-57.8	
	6.9300	-27.6	V	3.0	41.0	1.0	-67.6	-13.0	-54.6	
	3.4650	-34.7	H	3.0	40.3	1.0	-74.0	-13.0	-61.0	
	5.1975	-32.8	H	3.0	40.9	1.0	-72.7	-13.0	-59.7	
	6.9300	-29.0	H	3.0	41.0	1.0	-69.0	-13.0	-56.0	
High Channel (1754.3MHz)										
3.5086	-34.0	V	3.0	40.3	1.0	-73.3	-13.0	-60.3		
5.2629	-31.5	V	3.0	40.9	1.0	-71.4	-13.0	-58.4		
7.0172	-29.4	V	3.0	41.0	1.0	-69.4	-13.0	-56.4		
3.5086	-34.1	H	3.0	40.3	1.0	-73.4	-13.0	-60.4		
5.2629	-31.5	H	3.0	40.9	1.0	-71.3	-13.0	-58.3		
7.0172	-29.5	H	3.0	41.0	1.0	-69.5	-13.0	-56.5		
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										

LTE Band 4 1.4MHz 16QAM	UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 15K21157									
	Date: 06-27-15									
	Test Engineer: Steven.Kim									
	Configuration: EUT / AC Adapter / Ear Phone / X-Position									
	Mode: TX, LTE BAND 4, 1.4MHz BW, 16QAM									
	Chamber		Pre-amplifier		Filter		Limit			
	Chamber 2		AFS42		Filter 1		FCC Part 27			
	f GHz	SGreading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Channel (1710.7MHz)									
	3.4214	-33.3	V	3.0	40.2	1.0	-72.5	-13.0	-59.5	
	5.1321	-32.4	V	3.0	40.9	1.0	-72.3	-13.0	-59.3	
	6.8428	-28.7	V	3.0	41.0	1.0	-68.6	-13.0	-55.6	
	3.4214	-33.3	H	3.0	40.2	1.0	-72.5	-13.0	-59.5	
	5.1321	-31.6	H	3.0	40.9	1.0	-71.5	-13.0	-58.5	
	6.8428	-29.1	H	3.0	41.0	1.0	-69.1	-13.0	-56.1	
	Mid Channel (1732.5MHz)									
	3.4650	-34.1	V	3.0	40.3	1.0	-73.4	-13.0	-60.4	
	5.1975	-31.0	V	3.0	40.9	1.0	-70.9	-13.0	-57.9	
	6.9300	-27.9	V	3.0	41.0	1.0	-67.9	-13.0	-54.9	
	3.4650	-34.7	H	3.0	40.3	1.0	-73.9	-13.0	-60.9	
	5.1975	-32.7	H	3.0	40.9	1.0	-72.6	-13.0	-59.6	
	6.9300	-28.4	H	3.0	41.0	1.0	-68.4	-13.0	-55.4	
High Channel (1754.3MHz)										
3.5086	-34.5	V	3.0	40.3	1.0	-73.8	-13.0	-60.8		
5.2629	-31.5	V	3.0	40.9	1.0	-71.4	-13.0	-58.4		
7.0172	-29.4	V	3.0	41.0	1.0	-69.4	-13.0	-56.4		
3.5086	-34.0	H	3.0	40.3	1.0	-73.3	-13.0	-60.3		
5.2629	-31.3	H	3.0	40.9	1.0	-71.1	-13.0	-58.1		
7.0172	-29.4	H	3.0	41.0	1.0	-69.5	-13.0	-56.5		
Rev. 03.03.09										
Note: No other emissions were detected above the system noise floor.										