



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. +1.410.290.6652 / Fax +1.410.290.6654

<http://www.pctestlab.com>



## SAR EVALUATION REPORT

**Applicant Name:**

Samsung Electronics Co., Ltd.  
129, Samsung-ro, Maetan dong,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea

**Date of Testing:**

05/26/16 - 06/06/16, 03/27/17 – 04/10/17

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Document Serial No.:**

1M1703270125-01.A3L

**FCC ID:**

**A3LSMN935F**

**APPLICANT:**

**SAMSUNG ELECTRONICS CO., LTD.**

**DUT Type:**

Portable Handset

**Application Type:**

Certification

**FCC Rule Part(s):**

CFR §2.1093

**Model(s):**

SM-N935F

**Additional Model(s):**

SM-N935FD

| Equipment Class                            | Band & Mode        | Tx Frequency          | SAR              |                       |                     |                      |
|--------------------------------------------|--------------------|-----------------------|------------------|-----------------------|---------------------|----------------------|
|                                            |                    |                       | 1 gm Head (W/kg) | 1 gm Body-Worn (W/kg) | 1 gm Hotspot (W/kg) | 10 gm Phablet (W/kg) |
| PCE                                        | GSM/GPRS/EDGE 850  | 824.20 - 848.80 MHz   | 0.23             | 0.49                  | 0.92                | N/A                  |
| PCE                                        | UMTS 850           | 826.40 - 846.60 MHz   | 0.19             | 0.45                  | 0.72                | N/A                  |
| PCE                                        | UMTS 1755          | 1712.4 - 1752.6 MHz   | 0.34             | 0.51                  | 0.67                | 1.69                 |
| PCE                                        | GSM/GPRS/EDGE 1900 | 1850.20 - 1909.80 MHz | 0.12             | 0.52                  | 1.00                | N/A                  |
| PCE                                        | UMTS 1900          | 1852.4 - 1907.6 MHz   | 0.27             | 0.48                  | 0.77                | 1.43                 |
| PCE                                        | LTE Band 12        | 699.7 - 715.3 MHz     | < 0.1            | 0.15                  | 0.30                | N/A                  |
| PCE                                        | LTE Band 17        | 706.5 - 713.5 MHz     |                  |                       | N/A                 |                      |
| PCE                                        | LTE Band 13        | 779.5 - 784.5 MHz     | 0.11             | 0.30                  | 0.51                | N/A                  |
| PCE                                        | LTE Band 5 (Cell)  | 824.7 - 848.3 MHz     | 0.20             | 0.47                  | 0.80                | N/A                  |
| PCE                                        | LTE Band 26 (Cell) | 814.7 - 848.3 MHz     | 0.13             | 0.30                  | 0.45                | N/A                  |
| PCE                                        | LTE Band 4 (AWS)   | 1710.7 - 1754.3 MHz   | 0.39             | 0.57                  | 0.81                | 2.79                 |
| PCE                                        | LTE Band 2 (PCS)   | 1850.7 - 1909.3 MHz   | 0.32             | 0.67                  | 0.79                | 1.39                 |
| PCE                                        | LTE Band 25 (PCS)  | 1850.7 - 1914.3 MHz   | 0.19             | 0.52                  | 0.65                | 1.11                 |
| PCE                                        | LTE Band 41        | 2496.5 - 2687.5 MHz   | < 0.1            | 0.22                  | 1.10                | N/A                  |
| DTS                                        | 2.4 GHz WLAN       | 2412 - 2472 MHz       | 0.55             | 0.28                  | 0.64                | N/A                  |
| Nil                                        | U-NII-1            | 5180 - 5240 MHz       |                  |                       | N/A                 |                      |
| Nil                                        | U-NII-2A           | 5260 - 5320 MHz       | 0.57             | 0.35                  | N/A                 | 1.92                 |
| Nil                                        | U-NII-2C           | 5500 - 5720 MHz       | 0.64             | 0.11                  | N/A                 | 0.98                 |
| Nil                                        | U-NII-3            | 5745 - 5825 MHz       | 0.64             | < 0.1                 | 0.17                | N/A                  |
| DSS/DTS                                    | Bluetooth          | 2402 - 2480 MHz       |                  |                       | N/A                 |                      |
| Simultaneous SAR per KDB 690783 D01v01r03: |                    |                       | 1.58             | 1.24                  | 1.59                | 3.96                 |

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

  
Randy Ortanez  
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: [sartick@mmfai.info](mailto:sartick@mmfai.info).

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                   | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 1 of 95                           |

# T A B L E   O F   C O N T E N T S

|    |                                                  |    |
|----|--------------------------------------------------|----|
| 1  | DEVICE UNDER TEST .....                          | 3  |
| 2  | LTE INFORMATION .....                            | 12 |
| 3  | INTRODUCTION .....                               | 13 |
| 4  | DOSIMETRIC ASSESSMENT .....                      | 14 |
| 5  | DEFINITION OF REFERENCE POINTS .....             | 15 |
| 6  | TEST CONFIGURATION POSITIONS .....               | 16 |
| 7  | RF EXPOSURE LIMITS .....                         | 20 |
| 8  | FCC MEASUREMENT PROCEDURES.....                  | 21 |
| 9  | RF CONDUCTED POWERS.....                         | 27 |
| 10 | SYSTEM VERIFICATION.....                         | 55 |
| 11 | SAR DATA SUMMARY .....                           | 59 |
| 12 | FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS..... | 75 |
| 13 | SAR MEASUREMENT VARIABILITY .....                | 88 |
| 14 | ADDITIONAL TUNER TESTING PER FCC GUIDANCE.....   | 89 |
| 15 | EQUIPMENT LIST.....                              | 90 |
| 16 | MEASUREMENT UNCERTAINTIES.....                   | 92 |
| 17 | CONCLUSION.....                                  | 93 |
| 18 | REFERENCES .....                                 | 94 |

APPENDIX A: SAR TEST PLOTS

APPENDIX B: SAR DIPOLE VERIFICATION PLOTS

APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES

APPENDIX D: SAR TISSUE SPECIFICATIONS

APPENDIX E: SAR SYSTEM VALIDATION

APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS

APPENDIX G: SENSOR TRIGGERING DATA SUMMARY

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
| Page 2 of 95                                |                                                                                                                                                                                                        |                                        |

# 1 DEVICE UNDER TEST

## 1.1 Device Overview

| Band & Mode        | Operating Modes | Tx Frequency          |
|--------------------|-----------------|-----------------------|
| GSM/GPRS/EDGE 850  | Voice/Data      | 824.20 - 848.80 MHz   |
| UMTS 850           | Voice/Data      | 826.40 - 846.60 MHz   |
| UMTS 1750          | Voice/Data      | 1712.4 - 1752.6 MHz   |
| GSM/GPRS/EDGE 1900 | Voice/Data      | 1850.20 - 1909.80 MHz |
| UMTS 1900          | Voice/Data      | 1852.4 - 1907.6 MHz   |
| LTE Band 12        | Data            | 699.7 - 715.3 MHz     |
| LTE Band 17        | Data            | 706.5 - 713.5 MHz     |
| LTE Band 13        | Data            | 779.5 - 784.5 MHz     |
| LTE Band 5 (Cell)  | Data            | 824.7 - 848.3 MHz     |
| LTE Band 26 (Cell) | Data            | 814.7 - 848.3 MHz     |
| LTE Band 4 (AWS)   | Data            | 1710.7 - 1754.3 MHz   |
| LTE Band 2 (PCS)   | Data            | 1850.7 - 1909.3 MHz   |
| LTE Band 25 (PCS)  | Data            | 1850.7 - 1914.3 MHz   |
| LTE Band 41        | Data            | 2498.5 - 2687.5 MHz   |
| 2.4 GHz WLAN       | Data            | 2412 - 2472 MHz       |
| U-NII-1            | Data            | 5180 - 5240 MHz       |
| U-NII-2A           | Data            | 5260 - 5320 MHz       |
| U-NII-2C           | Data            | 5500 - 5720 MHz       |
| U-NII-3            | Data            | 5745 - 5825 MHz       |
| Bluetooth          | Data            | 2402 - 2480 MHz       |
| NFC                | Data            | 13.56 MHz             |
| ANT+               | Data            | 2402 - 2480 MHz       |
| MST                | Data            | 555 Hz - 8.33 kHz     |

## 1.2 Power Reduction for SAR

This device utilizes a power reduction mechanism for some wireless modes and bands for SAR compliance under portable hotspot conditions and under some conditions when the device is being used in close proximity to the user's hand. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device when being used in phablet use conditions. Detailed descriptions of the power reduction mechanism are included in the operational description.

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

The reduced powers for the power reduction mechanisms were confirmed via conducted power measurements at the RF port (See Section 9). Detailed descriptions of the mechanisms are included in the operational description.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 3 of 95                           |

### 1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

#### 1.3.1 Maximum PCE Power

| Mode / Band        |         | Voice<br>(dBm) | Burst Average GMSK (dBm) |            |            |            | Burst Average 8-PSK (dBm) |            |            |            |
|--------------------|---------|----------------|--------------------------|------------|------------|------------|---------------------------|------------|------------|------------|
|                    |         | 1 TX Slot      | 1 TX Slots               | 2 TX Slots | 3 TX Slots | 4 TX Slots | 1 TX Slots                | 2 TX Slots | 3 TX Slots | 4 TX Slots |
| GSM/GPRS/EDGE 850  | Maximum | 34.0           | 34.0                     | 32.0       | 30.8       | 29.6       | 28.0                      | 25.5       | 24.5       | 23.5       |
|                    | Nominal | 33.5           | 33.5                     | 31.5       | 30.3       | 29.1       | 27.5                      | 25.0       | 24.0       | 23.0       |
| GSM/GPRS/EDGE 1900 | Maximum | 30.5           | 30.5                     | 28.0       | 26.5       | 25.0       | 25.0                      | 23.0       | 21.8       | 20.6       |
|                    | Nominal | 30.0           | 30.0                     | 27.5       | 26.0       | 24.5       | 24.5                      | 22.5       | 21.3       | 20.1       |

| Mode / Band            |         | Modulated Average (dBm) |            |            |               |
|------------------------|---------|-------------------------|------------|------------|---------------|
|                        |         | 3GPP WCDMA              | 3GPP HSDPA | 3GPP HSUPA | 3GPP DC-HSDPA |
| UMTS Band 5 (850 MHz)  | Maximum | 25.0                    | 24.0       | 24.0       | 24.0          |
|                        | Nominal | 24.5                    | 23.5       | 23.5       | 23.5          |
| UMTS Band 4 (1750 MHz) | Maximum | 24.5                    | 24.5       | 23.5       | 23.5          |
|                        | Nominal | 24.0                    | 24.0       | 23.0       | 23.0          |
| UMTS Band 2 (1900 MHz) | Maximum | 24.5                    | 24.5       | 23.5       | 24.5          |
|                        | Nominal | 24.0                    | 24.0       | 23.0       | 24.0          |
| Mode / Band            |         | Modulated Average (dBm) |            |            |               |
| LTE Band 12            | Maximum | 23.5                    |            |            |               |
|                        | Nominal | 23.0                    |            |            |               |
| LTE Band 17            | Maximum | 23.5                    |            |            |               |
|                        | Nominal | 23.0                    |            |            |               |
| LTE Band 13            | Maximum | 23.5                    |            |            |               |
|                        | Nominal | 23.0                    |            |            |               |
| LTE Band 5 (Cell)      | Maximum | 25.0                    |            |            |               |
|                        | Nominal | 24.5                    |            |            |               |
| LTE Band 26 (Cell)     | Maximum | 23.5                    |            |            |               |
|                        | Nominal | 23.0                    |            |            |               |
| LTE Band 4 (AWS)       | Maximum | 24.5                    |            |            |               |
|                        | Nominal | 24.0                    |            |            |               |
| LTE Band 2 (PCS)       | Maximum | 24.5                    |            |            |               |
|                        | Nominal | 24.0                    |            |            |               |
| LTE Band 25 (PCS)      | Maximum | 23.5                    |            |            |               |
|                        | Nominal | 23.0                    |            |            |               |
| LTE Band 41            | Maximum | 23.5                    |            |            |               |
|                        | Nominal | 23.0                    |            |            |               |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 4 of 95                    |



### 1.3.2 Reduced PCE Power

| Mode / Band            |         | Modulated Average (dBm) |               |               |                  |
|------------------------|---------|-------------------------|---------------|---------------|------------------|
|                        |         | 3GPP<br>WCDMA           | 3GPP<br>HSDPA | 3GPP<br>HSUPA | 3GPP<br>DC-HSDPA |
| UMTS Band 4 (1750 MHz) | Maximum | 21.5                    | 21.5          | 21.5          | 21.5             |
|                        | Nominal | 21.0                    | 21.0          | 21.0          | 21.0             |
| UMTS Band 2 (1900 MHz) | Maximum | 21.5                    | 21.5          | 21.5          | 21.5             |
|                        | Nominal | 21.0                    | 21.0          | 21.0          | 21.0             |

| Mode / Band       |         | Modulated Average (dBm) |
|-------------------|---------|-------------------------|
| LTE Band 4 (AWS)  | Maximum | 21.5                    |
|                   | Nominal | 21.0                    |
| LTE Band 2 (PCS)  | Maximum | 21.5                    |
|                   | Nominal | 21.0                    |
| LTE Band 25 (PCS) | Maximum | 20.5                    |
|                   | Nominal | 20.0                    |

### 1.3.3 Maximum WLAN/BT Power

#### 2.4 GHz WLAN Antenna 1/ BT

| Mode / Band            |         | Modulated Average - Single Tx Chain (dBm) |       |       |
|------------------------|---------|-------------------------------------------|-------|-------|
| IEEE 802.11b (2.4 GHz) |         | Ch 1-11                                   | Ch 12 | Ch 13 |
|                        | Maximum | 19.5                                      | 17.5  | 11.5  |
|                        | Nominal | 19.0                                      | 17.0  | 11.0  |
| IEEE 802.11g (2.4 GHz) |         | Ch 1-11                                   | Ch 12 | Ch 13 |
|                        | Maximum | 16.5                                      | 14.5  | 8.5   |
|                        | Nominal | 16.0                                      | 14.0  | 8.0   |
| IEEE 802.11n (2.4 GHz) |         | Ch 1-11                                   | Ch 12 | Ch 13 |
|                        | Maximum | 15.5                                      | 13.5  | 7.5   |
|                        | Nominal | 15.0                                      | 13.0  | 7.0   |
| Bluetooth              | Maximum | 11.5                                      |       |       |
|                        | Nominal | 11.0                                      |       |       |
| Bluetooth LE           | Maximum | 7.5                                       |       |       |
|                        | Nominal | 7.0                                       |       |       |

#### 2.4 GHz WLAN Antenna 2

| Mode / Band            |         | Modulated Average - Single Tx Chain (dBm) |           |       |       |
|------------------------|---------|-------------------------------------------|-----------|-------|-------|
| IEEE 802.11b (2.4 GHz) |         | Ch 1-11                                   |           | Ch 12 | Ch 13 |
|                        | Maximum | 19.5                                      |           | 17.5  | 11.5  |
|                        | Nominal | 19.0                                      |           | 17.0  | 11.0  |
| IEEE 802.11g (2.4 GHz) |         | Ch 1                                      | Ch 2 - 11 | Ch 12 | Ch 13 |
|                        | Maximum | 16.0                                      | 16.5      | 14.5  | 8.5   |
|                        | Nominal | 15.5                                      | 16.0      | 14.0  | 8.0   |
| IEEE 802.11n (2.4 GHz) |         | Ch 1                                      | Ch 2 - 11 | Ch 12 | Ch 13 |
|                        | Maximum | 15.0                                      | 15.5      | 13.5  | 7.5   |
|                        | Nominal | 14.5                                      | 15.0      | 13.0  | 7.0   |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 5 of 95                    |

### 5GHz WLAN Antenna 1

| Mode / Band           |         | Modulated Average - Single Tx Chain<br>(dBm) |             |                  |             |                  |             |
|-----------------------|---------|----------------------------------------------|-------------|------------------|-------------|------------------|-------------|
|                       |         | 20 MHz Bandwidth                             |             | 40 MHz Bandwidth |             | 80 MHz Bandwidth |             |
| IEEE 802.11a (5 GHz)  |         | Ch 36                                        | Ch 40 - 165 |                  |             |                  |             |
|                       | Maximum | 15.5                                         | 17.5        |                  |             |                  |             |
|                       | Nominal | 15.0                                         | 17.0        |                  |             |                  |             |
| IEEE 802.11n (5 GHz)  |         | Ch 36 - 165                                  |             | Ch 38            | Ch 46 - 159 |                  |             |
|                       | Maximum | 14.5                                         |             | 12.5             | 15.5        |                  |             |
|                       | Nominal | 14.0                                         |             | 12.0             | 15.0        |                  |             |
| IEEE 802.11ac (5 GHz) |         | Ch 36 - 165                                  |             | Ch 38            | Ch 46 - 159 | Ch 42            | Ch 58 - 155 |
|                       | Maximum | 14.5                                         |             | 12.5             | 15.5        | 11.5             | 13.5        |
|                       | Nominal | 14.0                                         |             | 12.0             | 15.0        | 11.0             | 13.0        |

### 5GHz WLAN Antenna 2

| Mode / Band           |         | Modulated Average - Single Tx Chain<br>(dBm) |             |                  |             |                  |
|-----------------------|---------|----------------------------------------------|-------------|------------------|-------------|------------------|
|                       |         | 20 MHz Bandwidth                             |             | 40 MHz Bandwidth |             | 80 MHz Bandwidth |
| IEEE 802.11a (5 GHz)  |         | Ch 36                                        | Ch 40 - 165 |                  |             |                  |
|                       | Maximum | 17.0                                         | 17.5        |                  |             |                  |
|                       | Nominal | 16.5                                         | 17.0        |                  |             |                  |
| IEEE 802.11n (5 GHz)  |         | Ch 36 - 165                                  |             | Ch 38            | Ch 46 - 159 |                  |
|                       | Maximum | 14.5                                         |             | 14.0             | 15.5        |                  |
|                       | Nominal | 14.0                                         |             | 13.5             | 15.0        |                  |
| IEEE 802.11ac (5 GHz) |         | Ch 36 - 165                                  |             | Ch 38            | Ch 46 - 159 | Ch 42 - 155      |
|                       | Maximum | 14.5                                         |             | 14.0             | 15.5        | 13.5             |
|                       | Nominal | 14.0                                         |             | 13.5             | 15.0        | 13.0             |

### 2.4/5GHz WLAN MIMO

| Mode / Band            |         | Modulated Average - MIMO<br>(dBm) |       |       |                  |  |                  |
|------------------------|---------|-----------------------------------|-------|-------|------------------|--|------------------|
|                        |         | 20 MHz Bandwidth                  |       |       | 40 MHz Bandwidth |  | 80 MHz Bandwidth |
| IEEE 802.11n (2.4 GHz) |         | Ch 1-11                           | Ch 12 | Ch 13 |                  |  |                  |
|                        | Maximum | 17.5                              | 15.5  | 9.5   |                  |  |                  |
|                        | Nominal | 17.0                              | 15.0  | 9.0   |                  |  |                  |
| IEEE 802.11g (2.4 GHz) |         | Ch 1-11                           | Ch 12 | Ch 13 |                  |  |                  |
|                        | Maximum | 17.5                              | 15.5  | 9.5   |                  |  |                  |
|                        | Nominal | 17.0                              | 15.0  | 9.0   |                  |  |                  |
| IEEE 802.11a (5 GHz)   | Maximum | 17.5                              |       |       |                  |  |                  |
|                        | Nominal | 17.0                              |       |       |                  |  |                  |
| IEEE 802.11n (5 GHz)   | Maximum | 17.5                              |       |       | 15.5             |  |                  |
|                        | Nominal | 17.0                              |       |       | 15.0             |  |                  |
| IEEE 802.11ac (5 GHz)  | Maximum | 17.5                              |       |       | 15.5             |  | 13.5             |
|                        | Nominal | 17.0                              |       |       | 15.0             |  | 13.0             |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |                                 |
|                                      |                                                                                                                                                                                                        |                               | Page 6 of 95                    |

### 1.3.4 Reduced WLAN Power

#### 2.4 GHz WLAN Antenna 1

| Mode / Band            |         | Modulated Average - Single Tx Chain (dBm) |       |       |
|------------------------|---------|-------------------------------------------|-------|-------|
| IEEE 802.11b (2.4 GHz) |         | Ch 1-12                                   |       | Ch 13 |
|                        | Maximum | 15.5                                      |       | 11.5  |
|                        | Nominal | 15.0                                      |       | 11.0  |
| IEEE 802.11g (2.4 GHz) |         | Ch 1-11                                   | Ch 12 | Ch 13 |
|                        | Maximum | 15.5                                      | 14.5  | 8.5   |
|                        | Nominal | 15.0                                      | 14.0  | 8.0   |
| IEEE 802.11n (2.4 GHz) |         | Ch 1-11                                   | Ch 12 | Ch 13 |
|                        | Maximum | 15.5                                      | 13.5  | 7.5   |
|                        | Nominal | 15.0                                      | 13.0  | 7.0   |

#### 2.4 GHz WLAN Antenna 2

| Mode / Band            |         | Modulated Average - Single Tx Chain (dBm) |           |       |       |
|------------------------|---------|-------------------------------------------|-----------|-------|-------|
| IEEE 802.11b (2.4 GHz) |         | Ch 1 - 12                                 |           | Ch 13 |       |
|                        | Maximum | 15.5                                      |           | 7.5   |       |
|                        | Nominal | 15.0                                      |           | 7.0   |       |
| IEEE 802.11g (2.4 GHz) |         | Ch 1 - 11                                 |           | Ch 12 | Ch 13 |
|                        | Maximum | 15.5                                      |           | 14.5  | 8.5   |
|                        | Nominal | 15.0                                      |           | 14.0  | 8.0   |
| IEEE 802.11n (2.4 GHz) |         | Ch 1                                      | Ch 2 - 11 | Ch 12 | Ch 13 |
|                        | Maximum | 15.0                                      | 15.5      | 13.5  | 7.5   |
|                        | Nominal | 14.5                                      | 15.0      | 13.0  | 7.0   |

#### 5GHz WLAN Antenna 1

| Mode / Band           |         | Modulated Average - Single Tx Chain (dBm) |                  |             |                  |             |
|-----------------------|---------|-------------------------------------------|------------------|-------------|------------------|-------------|
|                       |         | 20 MHz Bandwidth                          | 40 MHz Bandwidth |             | 80 MHz Bandwidth |             |
| IEEE 802.11a (5 GHz)  |         | Ch 36 - 165                               |                  |             |                  |             |
|                       | Maximum | 13.5                                      |                  |             |                  |             |
|                       | Nominal | 13.0                                      |                  |             |                  |             |
| IEEE 802.11n (5 GHz)  |         | Ch 36 - 165                               | Ch 38            | Ch 46 - 159 |                  |             |
|                       | Maximum | 13.5                                      | 12.5             | 13.5        |                  |             |
|                       | Nominal | 13.0                                      | 12.0             | 13.0        |                  |             |
| IEEE 802.11ac (5 GHz) |         | Ch 36 - 165                               | Ch 38            | Ch 46 - 159 | Ch 42            | Ch 58 - 155 |
|                       | Maximum | 13.5                                      | 12.5             | 13.5        | 11.5             | 13.5        |
|                       | Nominal | 13.0                                      | 12.0             | 13.0        | 11.0             | 13.0        |

#### 5GHz WLAN Antenna 2

| Mode / Band           |         | Modulated Average - Single Tx Chain (dBm) |                  |                  |
|-----------------------|---------|-------------------------------------------|------------------|------------------|
|                       |         | 20 MHz Bandwidth                          | 40 MHz Bandwidth | 80 MHz Bandwidth |
| IEEE 802.11a (5 GHz)  | Maximum | 13.5                                      |                  |                  |
|                       | Nominal | 13.0                                      |                  |                  |
| IEEE 802.11n (5 GHz)  | Maximum | 13.5                                      | 13.5             |                  |
|                       | Nominal | 13.0                                      | 13.0             |                  |
| IEEE 802.11ac (5 GHz) | Maximum | 13.5                                      | 13.5             | 13.5             |
|                       | Nominal | 13.0                                      | 13.0             | 13.0             |

|                                      |                                                                                                                                                                                                 |                               |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  SAR EVALUATION REPORT  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | DUT Type:<br>Portable Handset | Page 7 of 95                    |

## 2.4/5GHz WLAN MIMO

| Mode / Band            |         | Modulated Average - MIMO<br>(dBm) |       |                  |                  |
|------------------------|---------|-----------------------------------|-------|------------------|------------------|
|                        |         | 20 MHz Bandwidth                  |       | 40 MHz Bandwidth | 80 MHz Bandwidth |
| IEEE 802.11n (2.4 GHz) |         | Ch 1-12                           | Ch 13 |                  |                  |
|                        | Maximum | 15.5                              | 9.5   |                  |                  |
|                        | Nominal | 15.0                              | 9.0   |                  |                  |
| IEEE 802.11g (2.4 GHz) |         | Ch 1-12                           | Ch 13 |                  |                  |
|                        | Maximum | 15.5                              | 9.5   |                  |                  |
|                        | Nominal | 15.0                              | 9.0   |                  |                  |
| IEEE 802.11a (5 GHz)   | Maximum | 13.5                              |       |                  |                  |
|                        | Nominal | 13.0                              |       |                  |                  |
| IEEE 802.11n (5 GHz)   | Maximum | 13.5                              | 13.5  |                  |                  |
|                        | Nominal | 13.0                              | 13.0  |                  |                  |
| IEEE 802.11ac (5 GHz)  | Maximum | 13.5                              | 13.5  |                  |                  |
|                        | Nominal | 13.0                              | 13.0  |                  |                  |

## 1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”.

**Table 1-1**  
**Device Edges/Sides for SAR Testing**

| Mode               | Back | Front | Top | Bottom | Right | Left |
|--------------------|------|-------|-----|--------|-------|------|
| GPRS 850           | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| UMTS 850           | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| UMTS 1750          | Yes  | Yes   | No  | Yes    | No    | Yes  |
| GPRS 1900          | Yes  | Yes   | No  | Yes    | No    | Yes  |
| UMTS 1900          | Yes  | Yes   | No  | Yes    | No    | Yes  |
| LTE Band 12        | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| LTE Band 13        | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| LTE Band 5 (Cell)  | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| LTE Band 26 (Cell) | Yes  | Yes   | No  | Yes    | Yes   | Yes  |
| LTE Band 4 (AWS)   | Yes  | Yes   | No  | Yes    | No    | Yes  |
| LTE Band 2 (PCS)   | Yes  | Yes   | No  | Yes    | No    | Yes  |
| LTE Band 25 (PCS)  | Yes  | Yes   | No  | Yes    | No    | Yes  |
| LTE Band 41        | Yes  | Yes   | No  | Yes    | No    | Yes  |
| 2.4 GHz WLAN Ant 1 | Yes  | Yes   | Yes | No     | No    | Yes  |
| 2.4 GHz WLAN Ant 2 | Yes  | Yes   | Yes | No     | No    | Yes  |
| 5 GHz WLAN Ant 1   | Yes  | Yes   | Yes | No     | No    | Yes  |
| 5 GHz WLAN Ant 2   | Yes  | Yes   | Yes | No     | No    | Yes  |

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled.

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 8 of 95                    |

## 1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

## 1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




**Figure 1-1**  
**Simultaneous Transmission Paths**

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

**Table 1-2**  
**Simultaneous Transmission Scenarios**

| No. | Capable Transmit Configuration          | Head | Body-Worn Accessory | Wireless Router | Phablet | Notes                                             |
|-----|-----------------------------------------|------|---------------------|-----------------|---------|---------------------------------------------------|
| 1   | GSM voice + 2.4 GHz Wi-Fi               | Yes  | Yes                 | N/A             | Yes     |                                                   |
| 2   | GSM voice + 5 GHz Wi-Fi                 | Yes  | Yes                 | N/A             | Yes     |                                                   |
| 3   | GSM voice + 2.4 GHz Bluetooth           | N/A  | Yes                 | N/A             | Yes     |                                                   |
| 4   | GSM voice + 2.4 GHz Wi-Fi MIMO          | Yes  | Yes                 | N/A             | Yes     |                                                   |
| 5   | GSM voice + 5 GHz Wi-Fi MIMO            | Yes  | Yes                 | N/A             | Yes     |                                                   |
| 6   | GSM voice + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi | Yes  | Yes                 | N/A             | Yes     |                                                   |
| 7   | UMTS + 2.4 GHz Wi-Fi                    | Yes  | Yes                 | Yes             | Yes     |                                                   |
| 8   | UMTS + 5 GHz Wi-Fi                      | Yes  | Yes                 | Yes             | Yes     |                                                   |
| 9   | UMTS + 2.4 GHz Bluetooth                | N/A  | Yes                 | N/A             | Yes     |                                                   |
| 10  | UMTS + 2.4 GHz Wi-Fi MIMO               | Yes  | Yes                 | Yes             | Yes     |                                                   |
| 11  | UMTS + 5 GHz Wi-Fi MIMO                 | Yes  | Yes                 | Yes             | Yes     |                                                   |
| 12  | UMTS + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi      | Yes  | Yes                 | Yes             | Yes     |                                                   |
| 13  | LTE + 2.4 GHz Wi-Fi                     | Yes* | Yes*                | Yes             | Yes     | *-Pre-installed VOIP applications are considered. |
| 14  | LTE + 5 GHz Wi-Fi                       | Yes* | Yes*                | Yes             | Yes     | *-Pre-installed VOIP applications are considered. |
| 15  | LTE + 2.4 GHz Bluetooth                 | N/A  | Yes*                | N/A             | Yes     | *-Pre-installed VOIP applications are considered. |
| 16  | LTE + 2.4 GHz Wi-Fi MIMO                | Yes* | Yes*                | Yes             | Yes     | *-Pre-installed VOIP applications are considered. |
| 17  | LTE + 5 GHz Wi-Fi MIMO                  | Yes* | Yes*                | Yes             | Yes     | *-Pre-installed VOIP applications are considered. |
| 18  | LTE + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi       | Yes* | Yes*                | Yes             | Yes     | *-Pre-installed VOIP applications are considered. |
| 19  | GPRS/EDGE + 2.4 GHz Wi-Fi               | N/A  | N/A                 | Yes             | Yes     |                                                   |
| 20  | GPRS/EDGE + 5 GHz Wi-Fi                 | N/A  | N/A                 | Yes             | Yes     |                                                   |
| 21  | GPRS/EDGE + 2.4 GHz Bluetooth           | N/A  | N/A                 | N/A             | Yes     |                                                   |
| 22  | GPRS/EDGE + 2.4 GHz Wi-Fi MIMO          | N/A  | N/A                 | Yes             | Yes     |                                                   |
| 23  | GPRS/EDGE + 5 GHz Wi-Fi MIMO            | N/A  | N/A                 | Yes             | Yes     |                                                   |
| 24  | GPRS/EDGE + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi | N/A  | N/A                 | Yes             | Yes     |                                                   |

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                   | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 9 of 95                           |

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
3. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
4. 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
5. This device supports 2x2 MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.

## 1.7 Miscellaneous SAR Test Considerations

### (A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required;  $[(14/15) * \sqrt{2.480}] = 1.5 < 3.0$ . Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Per FCC KDB 447498 D01v06, the 10g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 7.5$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, phablet Bluetooth SAR was not required;  $[(14/5) * \sqrt{2.480}] = 4.4 < 7.5$ . Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
| Page 10 of 95                               |                                                                                                                                                                                                        |                                        |

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-1, U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for 2.4 GHz and U-NII-3 WLAN operations since wireless router 1g SAR was < 1.2 W/kg.

## (B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports both LTE B17 and LTE B12. Since the supported frequency span for LTE B17 falls completely within the supported frequency span for LTE B12, both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B12.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.

## 1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

## 1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

|                    | Head Serial Number | Body-Worn Serial Number | Hotspot Serial Number | Phablet Serial Number |
|--------------------|--------------------|-------------------------|-----------------------|-----------------------|
| GSM/GPRS/EDGE 850  | 87763              | 85F64                   | 85F64                 | -                     |
| UMTS 850           | 8424D              | 8424D                   | 8424D                 | -                     |
| UMTS 1750          | 841E0              | 84162                   | 841E0                 | 84162/841E0           |
| GSM/GPRS/EDGE 1900 | 84250              | 84102                   | 84102                 | -                     |
| UMTS 1900          | 84250              | 84102                   | 841E0                 | 84102/841E0           |
| LTE Band 12        | 84102              | 84102                   | 84102                 | -                     |
| LTE Band 13        | 84102              | 98443                   | 98443                 | -                     |
| LTE Band 5 (Cell)  | 8413C              | 85F64                   | 85F64                 | -                     |
| LTE Band 26 (Cell) | 8413C              | 841C3                   | 841C3                 | -                     |
| LTE Band 4 (AWS)   | 84162              | 84162                   | 841E0                 | 84162/841E0           |
| LTE Band 2 (PCS)   | 84250              | 84102                   | 841E0                 | 84102/841E0           |
| LTE Band 25 (PCS)  | 84250              | 84102                   | 841E0                 | 84102/841E0           |
| LTE Band 41        | 81462              | 84162                   | 84162                 | -                     |
| 2.4 GHz WLAN       | 05C3E              | 85F64                   | 85F64                 | -                     |
| 5 GHz WLAN         | 05C3E/04160        | 05C28                   | 05C28                 | 05C28                 |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 11 of 95                   |



## 2 LTE INFORMATION

| LTE Information                                                                                                   |                                                                                                                                                                                                                                                                                                                                        |                |                |                |              |
|-------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------------|----------------|--------------|
| FCC ID                                                                                                            | A3LSMN935F                                                                                                                                                                                                                                                                                                                             |                |                |                |              |
| Form Factor                                                                                                       | Portable Handset                                                                                                                                                                                                                                                                                                                       |                |                |                |              |
| Frequency Range of each LTE transmission band                                                                     | LTE Band 12 (699.7 - 715.3 MHz)                                                                                                                                                                                                                                                                                                        |                |                |                |              |
|                                                                                                                   | LTE Band 17 (706.5 - 713.5 MHz)                                                                                                                                                                                                                                                                                                        |                |                |                |              |
|                                                                                                                   | LTE Band 13 (779.5 - 784.5 MHz)                                                                                                                                                                                                                                                                                                        |                |                |                |              |
|                                                                                                                   | LTE Band 5 (Cell) (824.7 - 848.3 MHz)                                                                                                                                                                                                                                                                                                  |                |                |                |              |
|                                                                                                                   | LTE Band 26 (Cell) (814.7 - 848.3 MHz)                                                                                                                                                                                                                                                                                                 |                |                |                |              |
|                                                                                                                   | LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)                                                                                                                                                                                                                                                                                                 |                |                |                |              |
|                                                                                                                   | LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)                                                                                                                                                                                                                                                                                                 |                |                |                |              |
|                                                                                                                   | LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)                                                                                                                                                                                                                                                                                                |                |                |                |              |
|                                                                                                                   | LTE Band 41 (2498.5 - 2687.5 MHz)                                                                                                                                                                                                                                                                                                      |                |                |                |              |
|                                                                                                                   | LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz                                                                                                                                                                                                                                                                                             |                |                |                |              |
| Channel Bandwidths                                                                                                | LTE Band 17: 5 MHz, 10 MHz                                                                                                                                                                                                                                                                                                             |                |                |                |              |
|                                                                                                                   | LTE Band 13: 5 MHz, 10 MHz                                                                                                                                                                                                                                                                                                             |                |                |                |              |
|                                                                                                                   | LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz                                                                                                                                                                                                                                                                                       |                |                |                |              |
|                                                                                                                   | LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz                                                                                                                                                                                                                                                                              |                |                |                |              |
|                                                                                                                   | LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz                                                                                                                                                                                                                                                                        |                |                |                |              |
|                                                                                                                   | LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz                                                                                                                                                                                                                                                                        |                |                |                |              |
|                                                                                                                   | LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz                                                                                                                                                                                                                                                                       |                |                |                |              |
|                                                                                                                   | LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz                                                                                                                                                                                                                                                                                             |                |                |                |              |
|                                                                                                                   |                                                                                                                                                                                                                                                                                                                                        |                |                |                |              |
|                                                                                                                   |                                                                                                                                                                                                                                                                                                                                        |                |                |                |              |
| Channel Numbers and Frequencies (MHz)                                                                             | Low                                                                                                                                                                                                                                                                                                                                    | Low-Mid        | Mid            | Mid-High       | High         |
| LTE Band 12: 1.4 MHz                                                                                              | 699.7 (23017)                                                                                                                                                                                                                                                                                                                          |                | 707.5 (23095)  | 715.3 (23173)  |              |
| LTE Band 12: 3 MHz                                                                                                | 700.5 (23025)                                                                                                                                                                                                                                                                                                                          |                | 707.5 (23095)  | 714.5 (23165)  |              |
| LTE Band 12: 5 MHz                                                                                                | 701.5 (23035)                                                                                                                                                                                                                                                                                                                          |                | 707.5 (23095)  | 713.5 (23155)  |              |
| LTE Band 12: 10 MHz                                                                                               | 704 (23060)                                                                                                                                                                                                                                                                                                                            |                | 707.5 (23095)  | 711 (23130)    |              |
| LTE Band 17: 5 MHz                                                                                                | 706.5 (23755)                                                                                                                                                                                                                                                                                                                          |                | 710 (23790)    | 713.5 (23825)  |              |
| LTE Band 17: 10 MHz                                                                                               | 709 (23780)                                                                                                                                                                                                                                                                                                                            |                | 710 (23790)    | 711 (23800)    |              |
| LTE Band 13: 5 MHz                                                                                                | 779.5 (23205)                                                                                                                                                                                                                                                                                                                          |                | 782 (23230)    | 784.5 (23255)  |              |
| LTE Band 13: 10 MHz                                                                                               | N/A                                                                                                                                                                                                                                                                                                                                    |                | 782 (23230)    | N/A            |              |
| LTE Band 5 (Cell): 1.4 MHz                                                                                        | 824.7 (20407)                                                                                                                                                                                                                                                                                                                          |                | 836.5 (20525)  | 848.3 (20643)  |              |
| LTE Band 5 (Cell): 3 MHz                                                                                          | 825.5 (20415)                                                                                                                                                                                                                                                                                                                          |                | 836.5 (20525)  | 847.5 (20635)  |              |
| LTE Band 5 (Cell): 5 MHz                                                                                          | 826.5 (20425)                                                                                                                                                                                                                                                                                                                          |                | 836.5 (20525)  | 846.5 (20625)  |              |
| LTE Band 5 (Cell): 10 MHz                                                                                         | 829 (20450)                                                                                                                                                                                                                                                                                                                            |                | 836.5 (20525)  | 844 (20600)    |              |
| LTE Band 26 (Cell): 1.4 MHz                                                                                       | 814.7 (26697)                                                                                                                                                                                                                                                                                                                          |                | 831.5 (26865)  | 848.3 (27033)  |              |
| LTE Band 26 (Cell): 3 MHz                                                                                         | 815.5 (26705)                                                                                                                                                                                                                                                                                                                          |                | 831.5 (26865)  | 847.5 (27025)  |              |
| LTE Band 26 (Cell): 5 MHz                                                                                         | 816.5 (26715)                                                                                                                                                                                                                                                                                                                          |                | 831.5 (26865)  | 846.5 (27015)  |              |
| LTE Band 26 (Cell): 10 MHz                                                                                        | 819 (26740)                                                                                                                                                                                                                                                                                                                            |                | 831.5 (26865)  | 844 (26990)    |              |
| LTE Band 26 (Cell): 15 MHz                                                                                        | 821.5 (26765)                                                                                                                                                                                                                                                                                                                          |                | 831.5 (26865)  | 841.5 (26965)  |              |
| LTE Band 4 (AWS): 1.4 MHz                                                                                         | 1710.7 (19957)                                                                                                                                                                                                                                                                                                                         |                | 1732.5 (20175) | 1754.3 (20393) |              |
| LTE Band 4 (AWS): 3 MHz                                                                                           | 1711.5 (19965)                                                                                                                                                                                                                                                                                                                         |                | 1732.5 (20175) | 1753.5 (20385) |              |
| LTE Band 4 (AWS): 5 MHz                                                                                           | 1712.5 (19975)                                                                                                                                                                                                                                                                                                                         |                | 1732.5 (20175) | 1752.5 (20375) |              |
| LTE Band 4 (AWS): 10 MHz                                                                                          | 1715 (20000)                                                                                                                                                                                                                                                                                                                           |                | 1732.5 (20175) | 1750 (20350)   |              |
| LTE Band 4 (AWS): 15 MHz                                                                                          | 1717.5 (20025)                                                                                                                                                                                                                                                                                                                         |                | 1732.5 (20175) | 1747.5 (20325) |              |
| LTE Band 4 (AWS): 20 MHz                                                                                          | 1720 (20050)                                                                                                                                                                                                                                                                                                                           |                | 1732.5 (20175) | 1745 (20300)   |              |
| LTE Band 2 (PCS): 1.4 MHz                                                                                         | 1850.7 (18607)                                                                                                                                                                                                                                                                                                                         |                | 1880 (18900)   | 1909.3 (19193) |              |
| LTE Band 2 (PCS): 3 MHz                                                                                           | 1851.5 (18615)                                                                                                                                                                                                                                                                                                                         |                | 1880 (18900)   | 1908.5 (19185) |              |
| LTE Band 2 (PCS): 5 MHz                                                                                           | 1852.5 (18625)                                                                                                                                                                                                                                                                                                                         |                | 1880 (18900)   | 1907.5 (19175) |              |
| LTE Band 2 (PCS): 10 MHz                                                                                          | 1855 (18650)                                                                                                                                                                                                                                                                                                                           |                | 1880 (18900)   | 1905 (19150)   |              |
| LTE Band 2 (PCS): 15 MHz                                                                                          | 1857.5 (18675)                                                                                                                                                                                                                                                                                                                         |                | 1880 (18900)   | 1902.5 (19125) |              |
| LTE Band 2 (PCS): 20 MHz                                                                                          | 1860 (18700)                                                                                                                                                                                                                                                                                                                           |                | 1880 (18900)   | 1900 (19100)   |              |
| LTE Band 25 (PCS): 1.4 MHz                                                                                        | 1850.7 (26047)                                                                                                                                                                                                                                                                                                                         |                | 1882.5 (26365) | 1914.3 (26683) |              |
| LTE Band 25 (PCS): 3 MHz                                                                                          | 1851.5 (26055)                                                                                                                                                                                                                                                                                                                         |                | 1882.5 (26365) | 1913.5 (26675) |              |
| LTE Band 25 (PCS): 5 MHz                                                                                          | 1852.5 (26065)                                                                                                                                                                                                                                                                                                                         |                | 1882.5 (26365) | 1912.5 (26665) |              |
| LTE Band 25 (PCS): 10 MHz                                                                                         | 1855 (26090)                                                                                                                                                                                                                                                                                                                           |                | 1882.5 (26365) | 1910 (26640)   |              |
| LTE Band 25 (PCS): 15 MHz                                                                                         | 1857.5 (26115)                                                                                                                                                                                                                                                                                                                         |                | 1882.5 (26365) | 1907.5 (26615) |              |
| LTE Band 25 (PCS): 20 MHz                                                                                         | 1860 (26140)                                                                                                                                                                                                                                                                                                                           |                | 1882.5 (26365) | 1905 (26590)   |              |
| LTE Band 41: 5 MHz                                                                                                | 2506 (39750)                                                                                                                                                                                                                                                                                                                           | 2549.5 (40185) | 2593 (40620)   | 2636.5 (41055) | 2680 (41490) |
| LTE Band 41: 10 MHz                                                                                               | 2506 (39750)                                                                                                                                                                                                                                                                                                                           | 2549.5 (40185) | 2593 (40620)   | 2636.5 (41055) | 2680 (41490) |
| LTE Band 41: 15 MHz                                                                                               | 2506 (39750)                                                                                                                                                                                                                                                                                                                           | 2549.5 (40185) | 2593 (40620)   | 2636.5 (41055) | 2680 (41490) |
| LTE Band 41: 20 MHz                                                                                               | 2506 (39750)                                                                                                                                                                                                                                                                                                                           | 2549.5 (40185) | 2593 (40620)   | 2636.5 (41055) | 2680 (41490) |
| UE Category                                                                                                       | 9                                                                                                                                                                                                                                                                                                                                      |                |                |                |              |
| Modulations Supported in UL                                                                                       | QPSK, 16QAM                                                                                                                                                                                                                                                                                                                            |                |                |                |              |
| LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided) | YES                                                                                                                                                                                                                                                                                                                                    |                |                |                |              |
| A-MPR (Additional MPR) disabled for SAR Testing?                                                                  | YES                                                                                                                                                                                                                                                                                                                                    |                |                |                |              |
| LTE Release 10 Additional Information                                                                             | This device does not support full CA features on 3GPP Release 10. All uplink communications are identical to the Release 8 Specifications. The following LTE Release 10 Features are not supported: Carrier Aggregation, Relay, HetNet, Enhanced MIMO, eICIC, WiFi Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA. |                |                |                |              |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 12 of 95                   |



### 3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

#### 3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1**  
**SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dv} \right)$$

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- $\sigma$  = conductivity of the tissue-simulating material (S/m)
- $\rho$  = mass density of the tissue-simulating material (kg/m<sup>3</sup>)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                   | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 13 of 95                          |

### 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




**Figure 4-1**  
Sample SAR Area Scan

**Table 4-1**  
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04\*

| Frequency | Maximum Area Scan Resolution (mm)<br>( $\Delta x_{\text{area}}, \Delta y_{\text{area}}$ ) | Maximum Zoom Scan Resolution (mm)<br>( $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$ ) | Maximum Zoom Scan Spatial Resolution (mm) |                             |                                      | Minimum Zoom Scan Volume (mm)<br>(x, y, z) |
|-----------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------|-----------------------------|--------------------------------------|--------------------------------------------|
|           |                                                                                           |                                                                                           | Uniform Grid                              | Graded Grid                 |                                      |                                            |
|           |                                                                                           |                                                                                           |                                           | $\Delta z_{\text{zoom}}(n)$ | $\Delta z_{\text{zoom}}(1)^*$        |                                            |
| ≤ 2 GHz   | ≤ 15                                                                                      | ≤ 8                                                                                       | ≤ 5                                       | ≤ 4                         | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 30                                       |
| 2-3 GHz   | ≤ 12                                                                                      | ≤ 5                                                                                       | ≤ 5                                       | ≤ 4                         | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 30                                       |
| 3-4 GHz   | ≤ 12                                                                                      | ≤ 5                                                                                       | ≤ 4                                       | ≤ 3                         | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 28                                       |
| 4-5 GHz   | ≤ 10                                                                                      | ≤ 4                                                                                       | ≤ 3                                       | ≤ 2.5                       | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 25                                       |
| 5-6 GHz   | ≤ 10                                                                                      | ≤ 4                                                                                       | ≤ 2                                       | ≤ 2                         | ≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$ | ≥ 22                                       |

\*Also compliant to IEEE 1528-2013 Table 6

|                                      |                                                                                                                                                                                                        |                               |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  | Page 14 of 95                   |

### 5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




**Figure 5-1**  
Close-Up Side view  
of ERP

### 5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



**Figure 5-2**  
Front, back and side view of SAM Twin Phantom




**Figure 5-3**  
Handset Vertical Center & Horizontal Line Reference Points

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 15 of 95                   |

## 6 TEST CONFIGURATION POSITIONS

### 6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ .

### 6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.



Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

### 6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

|                                      |                                                                                                                                                                                                 |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  SAR EVALUATION REPORT  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | DUT Type:<br>Portable Handset   |
|                                      |                                                                                                                                                                                                 | Page 16 of 95                   |



**Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position**




**Figure 6-3 Side view w/ relevant markings**

## 6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

## 6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




**Figure 6-4 Sample Body-Worn Diagram**

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                   | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 17 of 95                          |



Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

## 6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

## 6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ( $L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$ ) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 18 of 95                          |

## 6.8 Phablet Configurations

For smart phones with a display diagonal dimension > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna  $\leq 25$  mm from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg.

## 6.9 Additional Test Positions due to Proximity Conditions

This device uses a sensor to reduce voice and data powers in extremity (hand-held) use conditions.

When the sensor detects a user is touching the device on or near to the antenna the device reduces the maximum allowed output power. However, the proximity sensor is not active when the device is moved beyond the sensor triggering distance and the maximum output power is no longer limited. Therefore, an additional exposure condition is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a non-reduced output power level.

FCC KDB 616217 D04 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional test positions. Sensor Triggering distance summary data is included in Appendix G.

The proximity sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the proximity sensor entirely covers the antenna.

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
|                                             |                                                                                                                                                                                                        | Page 19 of 95                          |



## 7 RF EXPOSURE LIMITS

### 7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1**  
**SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

| HUMAN EXPOSURE LIMITS                                               |                                                                           |                                                                   |
|---------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------|
|                                                                     | UNCONTROLLED ENVIRONMENT<br><i>General Population</i><br>(W/kg) or (mW/g) | CONTROLLED ENVIRONMENT<br><i>Occupational</i><br>(W/kg) or (mW/g) |
| <b>Peak Spatial Average SAR</b><br>Head                             | 1.6                                                                       | 8.0                                                               |
| <b>Whole Body SAR</b>                                               | 0.08                                                                      | 0.4                                                               |
| <b>Peak Spatial Average SAR</b><br>Hands, Feet, Ankle, Wrists, etc. | 4.0                                                                       | 20                                                                |

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 20 of 95                          |

## 8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

### 8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

### 8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is

|                                      |                                                                                                                                                                                                 |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  SAR EVALUATION REPORT  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | DUT Type:<br>Portable Handset   |
|                                      |                                                                                                                                                                                                 | Page 21 of 95                   |

## 8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

## 8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH<sub>n</sub> configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH<sub>n</sub>, for the highest reported SAR configuration in 12.2 kbps RMC.

## 8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

## 8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

## 8.4.6 SAR Measurement Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

## 8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
|                                             |                                                                                                                                                                                                        | Page 22 of 95                          |

### 8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

### 8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

### 8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg for LTE FDD bands and  $\leq 0.6$  W/kg for LTE TDD Band 41, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $\leq 0.8$  W/kg for LTE FDD bands and  $\leq 0.6$  W/kg for LTE TDD Band 41.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to  $\frac{1}{2}$  dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.

### 8.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

|                                      |                                                                                                                                                                                                 |                               |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  SAR EVALUATION REPORT  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | DUT Type:<br>Portable Handset | Page 23 of 95                   |

## 8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

### 8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

### 8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is  $> 1.2$  W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is  $> 1.2$  W/kg. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

### 8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

### 8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
|                                             |                                                                                                                                                                                                        | Page 24 of 95                          |

### 8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is  $> 0.8$  W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is  $> 1.2$  W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

### 8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

### 8.6.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is  $\leq 0.8$  W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is  $\leq 1.2$  W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6). When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
|                                             |                                                                                                                                                                                                        | Page 25 of 95                          |



### 8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is  $\leq 1.2$  W/kg, no additional SAR tests for the subsequent test configurations are required. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

### 8.6.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is  $< 1.6$  W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 26 of 95                          |



## 9 RF CONDUCTED POWERS

### 9.1 GSM Conducted Powers

| Maximum Burst-Averaged Output Power            |               |                          |                         |                         |                         |                         |                         |                         |                         |                         |
|------------------------------------------------|---------------|--------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
|                                                |               | Voice                    | GPRS/EDGE Data (GMSK)   |                         |                         |                         | EDGE Data (8-PSK)       |                         |                         |                         |
| Band                                           | Channel       | GSM [dBm]<br>CS (1 Slot) | GPRS [dBm]<br>1 Tx Slot | GPRS [dBm]<br>2 Tx Slot | GPRS [dBm]<br>3 Tx Slot | GPRS [dBm]<br>4 Tx Slot | EDGE [dBm]<br>1 Tx Slot | EDGE [dBm]<br>2 Tx Slot | EDGE [dBm]<br>3 Tx Slot | EDGE [dBm]<br>4 Tx Slot |
| GSM 850                                        | 128           | 33.48                    | 33.49                   | 30.06                   | 29.64                   | <b>28.77</b>            | 26.61                   | 24.12                   | 22.78                   | 21.50                   |
|                                                | 190           | 33.45                    | 33.50                   | 30.11                   | 29.75                   | <b>29.15</b>            | 26.70                   | 24.43                   | 22.96                   | 21.74                   |
|                                                | 251           | 33.46                    | 33.46                   | 30.25                   | 30.03                   | <b>29.19</b>            | 27.01                   | 24.31                   | 22.80                   | 21.85                   |
| GSM 1900                                       | 512           | 29.45                    | 29.44                   | 26.75                   | <b>25.51</b>            | 24.23                   | 23.98                   | 22.10                   | 20.84                   | 19.79                   |
|                                                | 661           | 29.17                    | 29.01                   | 26.41                   | <b>24.92</b>            | 23.66                   | 23.46                   | 21.57                   | 20.55                   | 19.26                   |
|                                                | 810           | 29.39                    | 29.53                   | 26.86                   | <b>25.56</b>            | 24.23                   | 23.77                   | 22.04                   | 20.76                   | 19.75                   |
| Calculated Maximum Frame-Averaged Output Power |               |                          |                         |                         |                         |                         |                         |                         |                         |                         |
|                                                |               | Voice                    | GPRS/EDGE Data (GMSK)   |                         |                         |                         | EDGE Data (8-PSK)       |                         |                         |                         |
| Band                                           | Channel       | GSM [dBm]<br>CS (1 Slot) | GPRS [dBm]<br>1 Tx Slot | GPRS [dBm]<br>2 Tx Slot | GPRS [dBm]<br>3 Tx Slot | GPRS [dBm]<br>4 Tx Slot | EDGE [dBm]<br>1 Tx Slot | EDGE [dBm]<br>2 Tx Slot | EDGE [dBm]<br>3 Tx Slot | EDGE [dBm]<br>4 Tx Slot |
| GSM 850                                        | 128           | 24.45                    | 24.46                   | 24.04                   | 25.38                   | <b>25.76</b>            | 17.58                   | 18.10                   | 18.52                   | 18.49                   |
|                                                | 190           | 24.42                    | 24.47                   | 24.09                   | 25.49                   | <b>26.14</b>            | 17.67                   | 18.41                   | 18.70                   | 18.73                   |
|                                                | 251           | 24.43                    | 24.43                   | 24.23                   | 25.77                   | <b>26.18</b>            | 17.98                   | 18.29                   | 18.54                   | 18.84                   |
| GSM 1900                                       | 512           | 20.42                    | 20.41                   | 20.73                   | <b>21.25</b>            | 21.22                   | 14.95                   | 16.08                   | 16.58                   | 16.78                   |
|                                                | 661           | 20.14                    | 19.98                   | 20.39                   | <b>20.66</b>            | 20.65                   | 14.43                   | 15.55                   | 16.29                   | 16.25                   |
|                                                | 810           | 20.36                    | 20.50                   | 20.84                   | <b>21.30</b>            | 21.22                   | 14.74                   | 16.02                   | 16.50                   | 16.74                   |
| GSM 850                                        | Frame         | 24.47                    | 24.47                   | 25.48                   | 26.04                   | <b>26.09</b>            | 18.47                   | 18.98                   | 19.74                   | 19.99                   |
| GSM 1900                                       | Avg. Targets: | 20.97                    | 20.97                   | 21.48                   | <b>21.74</b>            | 21.49                   | 15.47                   | 16.48                   | 17.04                   | 17.09                   |

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

**GSM Class: B**  
**GPRS Multislot class: 33 (Max 4 Tx uplink slots)**  
**EDGE Multislot class: 33 (Max 4 Tx uplink slots)**  
**DTM Multislot Class: N/A**



**Figure 9-1**  
**Power Measurement Setup**

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 27 of 95                   |

## 9.2 UMTS Conducted Powers

**Maximum Conducted Powers**

| 3GPP Release Version | Mode     | 3GPP 34.121 Subtest | Cellular Band [dBm] |       |       | AWS Band [dBm] |       |       | PCS Band [dBm] |       |       | 3GPP MPR [dB] |
|----------------------|----------|---------------------|---------------------|-------|-------|----------------|-------|-------|----------------|-------|-------|---------------|
|                      |          |                     | 4132                | 4183  | 4233  | 1312           | 1412  | 1513  | 9262           | 9400  | 9538  |               |
| 99                   | WCDMA    | 12.2 kbps RMC       | 24.08               | 24.33 | 24.58 | 23.93          | 24.00 | 23.75 | 23.45          | 23.12 | 23.77 | -             |
| 99                   |          | 12.2 kbps AMR       | 24.12               | 24.30 | 24.63 | 23.93          | 23.94 | 23.83 | 23.42          | 23.09 | 23.74 | -             |
| 6                    | HSDPA    | Subtest 1           | 23.30               | 23.31 | 23.24 | 24.50          | 24.40 | 24.50 | 24.05          | 24.50 | 24.30 | 0             |
| 6                    |          | Subtest 2           | 22.47               | 22.47 | 22.39 | 23.52          | 23.35 | 23.77 | 23.07          | 23.39 | 23.35 | 0             |
| 6                    |          | Subtest 3           | 22.50               | 22.47 | 22.40 | 22.48          | 22.37 | 22.74 | 22.12          | 22.58 | 22.38 | 0.5           |
| 6                    |          | Subtest 4           | 21.52               | 21.50 | 21.53 | 22.50          | 22.36 | 22.74 | 22.11          | 22.52 | 22.34 | 0.5           |
| 6                    | HSUPA    | Subtest 1           | 22.40               | 22.33 | 22.28 | 21.92          | 21.85 | 22.22 | 22.03          | 22.49 | 22.32 | 0             |
| 6                    |          | Subtest 2           | 20.44               | 20.41 | 20.35 | 19.75          | 19.57 | 19.92 | 19.75          | 20.25 | 20.03 | 2             |
| 6                    |          | Subtest 3           | 22.42               | 22.41 | 22.30 | 21.94          | 21.87 | 21.24 | 22.15          | 22.57 | 22.41 | 1             |
| 6                    |          | Subtest 4           | 20.47               | 20.41 | 20.35 | 19.59          | 19.54 | 19.91 | 19.75          | 20.22 | 20.04 | 2             |
| 6                    | DC-HSDPA | Subtest 5           | 23.99               | 23.92 | 23.85 | 21.87          | 21.91 | 22.37 | 22.53          | 23.06 | 22.82 | 0             |
| 8                    |          | Subtest 1           | 23.25               | 23.09 | 22.97 | 22.59          | 22.68 | 22.99 | 23.05          | 23.36 | 23.29 | 0             |
| 8                    |          | Subtest 2           | 22.15               | 22.37 | 22.33 | 23.08          | 23.23 | 23.40 | 23.48          | 23.13 | 23.35 | 0             |
| 8                    |          | Subtest 3           | 22.25               | 22.12 | 22.03 | 22.21          | 22.45 | 22.63 | 22.53          | 22.84 | 22.31 | 0.5           |
| 8                    |          | Subtest 4           | 22.18               | 22.16 | 22.11 | 22.30          | 22.26 | 22.61 | 22.09          | 22.38 | 22.39 | 0.5           |

**Reduced Conducted Powers**

| 3GPP Release Version | Mode     | 3GPP 34.121 Subtest | AWS Band [dBm] |       |       | PCS Band [dBm] |       |       | 3GPP MPR [dB] |
|----------------------|----------|---------------------|----------------|-------|-------|----------------|-------|-------|---------------|
|                      |          |                     | 1312           | 1412  | 1513  | 9262           | 9400  | 9538  |               |
| 99                   | WCDMA    | 12.2 kbps RMC       | 20.87          | 21.17 | 20.81 | 20.63          | 20.25 | 21.02 | -             |
| 99                   |          | 12.2 kbps AMR       | 20.84          | 21.12 | 20.77 | 20.48          | 20.18 | 20.98 | -             |
| 6                    | HSDPA    | Subtest 1           | 20.97          | 21.18 | 20.74 | 20.52          | 20.05 | 20.73 | 0             |
| 6                    |          | Subtest 2           | 20.99          | 21.20 | 20.81 | 20.54          | 20.08 | 20.75 | 0             |
| 6                    |          | Subtest 3           | 20.96          | 21.19 | 20.76 | 20.57          | 20.11 | 20.72 | 0.5           |
| 6                    |          | Subtest 4           | 20.98          | 21.16 | 20.79 | 20.55          | 20.09 | 20.74 | 0.5           |
| 6                    | HSUPA    | Subtest 1           | 20.29          | 20.45 | 20.13 | 19.75          | 19.53 | 19.79 | 0             |
| 6                    |          | Subtest 2           | 19.19          | 19.34 | 19.07 | 19.18          | 18.86 | 19.29 | 2             |
| 6                    |          | Subtest 3           | 20.32          | 20.43 | 20.09 | 19.84          | 19.47 | 19.86 | 1             |
| 6                    |          | Subtest 4           | 19.14          | 19.28 | 18.97 | 19.21          | 18.83 | 19.26 | 2             |
| 6                    | DC-HSDPA | Subtest 5           | 20.93          | 21.21 | 20.84 | 20.47          | 20.06 | 20.71 | 0             |
| 8                    |          | Subtest 1           | 21.09          | 20.98 | 20.81 | 20.00          | 19.88 | 20.46 | 0             |
| 8                    |          | Subtest 2           | 20.99          | 20.96 | 20.72 | 19.98          | 19.87 | 20.47 | 0             |
| 8                    |          | Subtest 3           | 21.00          | 20.92 | 20.77 | 20.02          | 19.88 | 20.46 | 0.5           |
| 8                    |          | Subtest 4           | 20.98          | 20.95 | 20.73 | 20.03          | 19.91 | 20.44 | 0.5           |

### DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




**Figure 9-2  
Power Measurement Setup**

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 28 of 95                   |

## 9.3 LTE Conducted Powers

### 9.3.1

### LTE Band 12

**Table 9-1**  
**LTE Band 12 Conducted Powers - 10 MHz Bandwidth**

| LTE Band 12<br>10 MHz Bandwidth |         |           |                          |                              |          |
|---------------------------------|---------|-----------|--------------------------|------------------------------|----------|
| Modulation                      | RB Size | RB Offset | Mid Channel              | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                 |         |           | 23095<br>(707.5 MHz)     |                              |          |
|                                 |         |           | Conducted Power<br>[dBm] |                              |          |
| QPSK                            | 1       | 0         | 22.63                    | 0                            | 0        |
|                                 | 1       | 25        | 22.53                    |                              | 0        |
|                                 | 1       | 49        | 22.48                    |                              | 0        |
|                                 | 25      | 0         | 21.81                    | 0-1                          | 1        |
|                                 | 25      | 12        | 21.77                    |                              | 1        |
|                                 | 25      | 25        | 21.78                    |                              | 1        |
|                                 | 50      | 0         | 21.79                    |                              | 1        |
| 16QAM                           | 1       | 0         | 21.82                    | 0-1                          | 1        |
|                                 | 1       | 25        | 21.76                    |                              | 1        |
|                                 | 1       | 49        | 21.73                    |                              | 1        |
|                                 | 25      | 0         | 20.81                    | 0-2                          | 2        |
|                                 | 25      | 12        | 20.79                    |                              | 2        |
|                                 | 25      | 25        | 20.69                    |                              | 2        |
|                                 | 50      | 0         | 20.80                    |                              | 2        |

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-2**  
**LTE Band 12 Conducted Powers - 5 MHz Bandwidth**

| LTE Band 12<br>5 MHz Bandwidth |         |           |                          |                          |                          |                              |          |
|--------------------------------|---------|-----------|--------------------------|--------------------------|--------------------------|------------------------------|----------|
| Modulation                     | RB Size | RB Offset | Low Channel              | Mid Channel              | High Channel             | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                |         |           | 23035<br>(701.5 MHz)     | 23095<br>(707.5 MHz)     | 23155<br>(713.5 MHz)     |                              |          |
|                                |         |           | Conducted Power<br>[dBm] | Conducted Power<br>[dBm] | Conducted Power<br>[dBm] |                              |          |
| QPSK                           | 1       | 0         | 22.63                    | 22.59                    | 22.67                    | 0                            | 0        |
|                                | 1       | 12        | 22.59                    | 22.52                    | 22.62                    |                              | 0        |
|                                | 1       | 24        | 22.49                    | 22.51                    | 22.66                    |                              | 0        |
|                                | 12      | 0         | 21.71                    | 21.65                    | 21.66                    | 0-1                          | 1        |
|                                | 12      | 6         | 21.69                    | 21.68                    | 21.65                    |                              | 1        |
|                                | 12      | 13        | 21.69                    | 21.67                    | 21.60                    |                              | 1        |
|                                | 25      | 0         | 21.69                    | 21.70                    | 21.59                    |                              | 1        |
| 16QAM                          | 1       | 0         | 21.68                    | 21.74                    | 21.57                    | 0-1                          | 1        |
|                                | 1       | 12        | 21.52                    | 21.69                    | 21.52                    |                              | 1        |
|                                | 1       | 24        | 21.53                    | 21.70                    | 21.56                    |                              | 1        |
|                                | 12      | 0         | 20.71                    | 20.72                    | 20.62                    | 0-2                          | 2        |
|                                | 12      | 6         | 20.67                    | 20.73                    | 20.66                    |                              | 2        |
|                                | 12      | 13        | 20.66                    | 20.74                    | 20.65                    |                              | 2        |
|                                | 25      | 0         | 20.67                    | 20.76                    | 20.67                    |                              | 2        |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 29 of 95                   |

**Table 9-3**  
**LTE Band 12 Conducted Powers - 3 MHz Bandwidth**

| LTE Band 12<br>3 MHz Bandwidth |         |           |                       |                      |                      |                              |          |
|--------------------------------|---------|-----------|-----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                     | RB Size | RB Offset | Low Channel           | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                |         |           | 23025<br>(700.5 MHz)  | 23095<br>(707.5 MHz) | 23165<br>(714.5 MHz) |                              |          |
|                                |         |           | Conducted Power [dBm] |                      |                      |                              |          |
| QPSK                           | 1       | 0         | 22.56                 | 22.41                | 22.49                | 0                            | 0        |
|                                | 1       | 7         | 22.45                 | 22.39                | 22.46                |                              | 0        |
|                                | 1       | 14        | 22.46                 | 22.35                | 22.43                |                              | 0        |
|                                | 8       | 0         | 21.58                 | 21.60                | 21.63                | 0-1                          | 1        |
|                                | 8       | 4         | 21.59                 | 21.59                | 21.52                |                              | 1        |
|                                | 8       | 7         | 21.57                 | 21.61                | 21.54                |                              | 1        |
|                                | 15      | 0         | 21.66                 | 21.66                | 21.59                |                              | 1        |
| 16QAM                          | 1       | 0         | 21.56                 | 21.75                | 21.65                | 0-1                          | 1        |
|                                | 1       | 7         | 21.53                 | 21.73                | 21.58                |                              | 1        |
|                                | 1       | 14        | 21.45                 | 21.71                | 21.64                |                              | 1        |
|                                | 8       | 0         | 20.53                 | 20.66                | 20.52                | 0-2                          | 2        |
|                                | 8       | 4         | 20.58                 | 20.62                | 20.50                |                              | 2        |
|                                | 8       | 7         | 20.56                 | 20.63                | 20.52                |                              | 2        |
|                                | 15      | 0         | 20.69                 | 20.65                | 20.60                |                              | 2        |

**Table 9-4**  
**LTE Band 12 Conducted Powers – 1.4 MHz Bandwidth**

| LTE Band 12<br>1.4 MHz Bandwidth |         |           |                       |                      |                      |                              |          |
|----------------------------------|---------|-----------|-----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                       | RB Size | RB Offset | Low Channel           | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                  |         |           | 23017<br>(699.7 MHz)  | 23095<br>(707.5 MHz) | 23173<br>(715.3 MHz) |                              |          |
|                                  |         |           | Conducted Power [dBm] |                      |                      |                              |          |
| QPSK                             | 1       | 0         | 22.65                 | 22.65                | 22.57                | 0                            | 0        |
|                                  | 1       | 2         | 22.64                 | 22.55                | 22.55                |                              | 0        |
|                                  | 1       | 5         | 22.64                 | 22.57                | 22.52                |                              | 0        |
|                                  | 3       | 0         | 22.68                 | 22.55                | 22.60                |                              | 0        |
|                                  | 3       | 2         | 22.69                 | 22.54                | 22.60                |                              | 0        |
|                                  | 3       | 3         | 22.67                 | 22.56                | 22.57                |                              | 0        |
|                                  | 6       | 0         | 21.73                 | 21.61                | 21.58                | 0-1                          | 1        |
| 16QAM                            | 1       | 0         | 21.62                 | 21.56                | 21.74                | 0-1                          | 1        |
|                                  | 1       | 2         | 21.59                 | 21.53                | 21.75                |                              | 1        |
|                                  | 1       | 5         | 21.59                 | 21.60                | 21.76                |                              | 1        |
|                                  | 3       | 0         | 21.52                 | 21.56                | 21.56                |                              | 1        |
|                                  | 3       | 2         | 21.50                 | 21.61                | 21.50                |                              | 1        |
|                                  | 3       | 3         | 21.52                 | 21.63                | 21.55                |                              | 1        |
|                                  | 6       | 0         | 20.65                 | 20.61                | 20.53                | 0-2                          | 2        |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 30 of 95                          |

### 9.3.2

### LTE Band 13

**Table 9-5**  
**LTE Band 13 Conducted Powers - 10 MHz Bandwidth**

| LTE Band 13<br>10 MHz Bandwidth |         |           |                          |                              |          |
|---------------------------------|---------|-----------|--------------------------|------------------------------|----------|
| Modulation                      | RB Size | RB Offset | Mid Channel              | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                 |         |           | 23230<br>(782.0 MHz)     |                              |          |
|                                 |         |           | Conducted Power<br>[dBm] |                              |          |
| QPSK                            | 1       | 0         | 22.37                    | 0                            | 0        |
|                                 | 1       | 25        | <b>22.42</b>             |                              | 0        |
|                                 | 1       | 49        | 22.02                    |                              | 0        |
|                                 | 25      | 0         | <b>20.92</b>             | 0-1                          | 1        |
|                                 | 25      | 12        | 20.80                    |                              | 1        |
|                                 | 25      | 25        | 20.68                    |                              | 1        |
| 16QAM                           | 50      | 0         | 20.80                    | 0-1                          | 1        |
|                                 | 1       | 0         | 20.86                    |                              | 1        |
|                                 | 1       | 25        | 20.96                    |                              | 1        |
|                                 | 1       | 49        | 20.50                    | 0-2                          | 1        |
|                                 | 25      | 0         | 20.88                    |                              | 1        |
|                                 | 25      | 12        | 20.80                    |                              | 1        |
|                                 | 25      | 25        | 20.62                    |                              | 1        |
|                                 | 50      | 0         | 20.78                    |                              | 1        |

**Table 9-6**  
**LTE Band 13 Conducted Powers - 5 MHz Bandwidth**

| LTE Band 13<br>5 MHz Bandwidth |         |           |                          |                              |          |
|--------------------------------|---------|-----------|--------------------------|------------------------------|----------|
| Modulation                     | RB Size | RB Offset | Mid Channel              | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                |         |           | 23230<br>(782.0 MHz)     |                              |          |
|                                |         |           | Conducted Power<br>[dBm] |                              |          |
| QPSK                           | 1       | 0         | 22.29                    | 0                            | 0        |
|                                | 1       | 12        | 22.26                    |                              | 0        |
|                                | 1       | 24        | 21.99                    |                              | 0        |
|                                | 12      | 0         | 20.80                    | 0-1                          | 1        |
|                                | 12      | 6         | 20.71                    |                              | 1        |
|                                | 12      | 13        | 20.65                    |                              | 1        |
|                                | 25      | 0         | 20.75                    |                              | 1        |
| 16QAM                          | 1       | 0         | 20.95                    | 0-1                          | 1        |
|                                | 1       | 12        | 20.93                    |                              | 1        |
|                                | 1       | 24        | 20.69                    |                              | 1        |
|                                | 12      | 0         | 20.83                    | 0-2                          | 1        |
|                                | 12      | 6         | 20.73                    |                              | 1        |
|                                | 12      | 13        | 20.65                    |                              | 1        |
|                                | 25      | 0         | 20.70                    |                              | 1        |

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 31 of 95                   |

### 9.3.3

### LTE Band 5 (Cell)

**Table 9-7**  
**LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth**

| LTE Band 5 (Cell)<br>10 MHz Bandwidth |         |           |                          |                              |          |
|---------------------------------------|---------|-----------|--------------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Mid Channel              | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 20525<br>(836.5 MHz)     |                              |          |
|                                       |         |           | Conducted Power<br>[dBm] |                              |          |
| QPSK                                  | 1       | 0         | 24.08                    | 0                            | 0        |
|                                       | 1       | 25        | 24.07                    |                              | 0        |
|                                       | 1       | 49        | 24.03                    |                              | 0        |
|                                       | 25      | 0         | 22.67                    | 0-1                          | 1        |
|                                       | 25      | 12        | 22.57                    |                              | 1        |
|                                       | 25      | 25        | 22.63                    |                              | 1        |
|                                       | 50      | 0         | 22.65                    |                              | 1        |
| 16QAM                                 | 1       | 0         | 22.78                    | 0-1                          | 1        |
|                                       | 1       | 25        | 22.71                    |                              | 1        |
|                                       | 1       | 49        | 22.72                    |                              | 1        |
|                                       | 25      | 0         | 22.62                    | 0-2                          | 1        |
|                                       | 25      | 12        | 22.65                    |                              | 1        |
|                                       | 25      | 25        | 22.64                    |                              | 1        |
|                                       | 50      | 0         | 22.65                    |                              | 1        |

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-8**  
**LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth**

| LTE Band 5 (Cell)<br>5 MHz Bandwidth |         |           |                       |                      |                      |                              |          |
|--------------------------------------|---------|-----------|-----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 20425<br>(826.5 MHz)  | 20525<br>(836.5 MHz) | 20625<br>(846.5 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                      |                      |                              |          |
| QPSK                                 | 1       | 0         | 23.88                 | 23.97                | 24.03                | 0                            | 0        |
|                                      | 1       | 12        | 23.86                 | 23.92                | 24.02                |                              | 0        |
|                                      | 1       | 24        | 23.87                 | 23.85                | 23.95                |                              | 0        |
|                                      | 12      | 0         | 22.44                 | 22.46                | 22.66                | 0-1                          | 1        |
|                                      | 12      | 6         | 22.43                 | 22.42                | 22.58                |                              | 1        |
|                                      | 12      | 13        | 22.42                 | 22.64                | 22.55                |                              | 1        |
|                                      | 25      | 0         | 22.47                 | 22.53                | 22.57                |                              | 1        |
| 16QAM                                | 1       | 0         | 22.65                 | 22.78                | 22.89                | 0-1                          | 1        |
|                                      | 1       | 12        | 22.68                 | 22.68                | 22.91                |                              | 1        |
|                                      | 1       | 24        | 22.55                 | 22.60                | 22.89                |                              | 1        |
|                                      | 12      | 0         | 22.43                 | 22.64                | 22.61                | 0-2                          | 1        |
|                                      | 12      | 6         | 22.46                 | 22.61                | 22.62                |                              | 1        |
|                                      | 12      | 13        | 22.44                 | 22.61                | 22.58                |                              | 1        |
|                                      | 25      | 0         | 22.50                 | 22.59                | 22.60                |                              | 1        |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 32 of 95                   |



**Table 9-9**  
**LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth**

| LTE Band 5 (Cell)<br>3 MHz Bandwidth |         |           |                       |                      |                      |                              |          |
|--------------------------------------|---------|-----------|-----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 20415<br>(825.5 MHz)  | 20525<br>(836.5 MHz) | 20635<br>(847.5 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                      |                      |                              |          |
| QPSK                                 | 1       | 0         | 23.91                 | 23.78                | 23.93                | 0                            | 0        |
|                                      | 1       | 7         | 23.90                 | 23.78                | 23.96                |                              | 0        |
|                                      | 1       | 14        | 23.88                 | 23.79                | 23.95                |                              | 0        |
|                                      | 8       | 0         | 22.43                 | 22.44                | 22.61                | 0-1                          | 1        |
|                                      | 8       | 4         | 22.42                 | 22.45                | 22.58                |                              | 1        |
|                                      | 8       | 7         | 22.42                 | 22.44                | 22.55                |                              | 1        |
|                                      | 15      | 0         | 22.45                 | 22.48                | 22.55                |                              | 1        |
| 16QAM                                | 1       | 0         | 22.63                 | 22.37                | 22.61                | 0-1                          | 1        |
|                                      | 1       | 7         | 22.52                 | 22.34                | 22.69                |                              | 1        |
|                                      | 1       | 14        | 22.57                 | 22.27                | 22.74                |                              | 1        |
|                                      | 8       | 0         | 22.39                 | 22.48                | 22.54                | 0-2                          | 1        |
|                                      | 8       | 4         | 22.34                 | 22.47                | 22.50                |                              | 1        |
|                                      | 8       | 7         | 22.35                 | 22.48                | 22.47                |                              | 1        |
|                                      | 15      | 0         | 22.45                 | 22.47                | 22.56                |                              | 1        |

**Table 9-10**  
**LTE Band 5 (Cell) Conducted Powers - 1.4 MHz Bandwidth**

| LTE Band 5 (Cell)<br>1.4 MHz Bandwidth |         |           |                       |                      |                      |                              |          |
|----------------------------------------|---------|-----------|-----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                             | RB Size | RB Offset | Low Channel           | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                        |         |           | 20407<br>(824.7 MHz)  | 20525<br>(836.5 MHz) | 20643<br>(848.3 MHz) |                              |          |
|                                        |         |           | Conducted Power [dBm] |                      |                      |                              |          |
| QPSK                                   | 1       | 0         | 23.81                 | 23.98                | 24.04                | 0                            | 0        |
|                                        | 1       | 2         | 23.80                 | 23.96                | 23.97                |                              | 0        |
|                                        | 1       | 5         | 23.80                 | 23.94                | 23.91                |                              | 0        |
|                                        | 3       | 0         | 23.99                 | 24.09                | 24.19                |                              | 0        |
|                                        | 3       | 2         | 24.00                 | 24.08                | 24.20                |                              | 0        |
|                                        | 3       | 3         | 23.98                 | 24.07                | 24.16                |                              | 0        |
|                                        | 6       | 0         | 22.51                 | 22.60                | 22.61                | 0-1                          | 1        |
| 16QAM                                  | 1       | 0         | 22.34                 | 22.61                | 22.63                | 0-1                          | 1        |
|                                        | 1       | 2         | 22.36                 | 22.63                | 22.64                |                              | 1        |
|                                        | 1       | 5         | 22.31                 | 22.70                | 22.59                |                              | 1        |
|                                        | 3       | 0         | 22.38                 | 22.46                | 22.58                |                              | 1        |
|                                        | 3       | 2         | 22.34                 | 22.40                | 22.55                |                              | 1        |
|                                        | 3       | 3         | 22.46                 | 22.45                | 22.44                |                              | 1        |
|                                        | 6       | 0         | 22.42                 | 22.55                | 22.65                | 0-2                          | 1        |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 33 of 95                          |

### 9.3.4

### LTE Band 26 (Cell)

**Table 9-11**  
**LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth**

| LTE Band 26 (Cell)<br>15 MHz Bandwidth |         |           |                          |                              |          |
|----------------------------------------|---------|-----------|--------------------------|------------------------------|----------|
| Modulation                             | RB Size | RB Offset | Mid Channel              | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                        |         |           | 26865<br>(831.5 MHz)     |                              |          |
|                                        |         |           | Conducted Power<br>[dBm] |                              |          |
| QPSK                                   | 1       | 0         | 23.46                    | 0                            | 0        |
|                                        | 1       | 36        | 23.31                    |                              | 0        |
|                                        | 1       | 74        | 23.28                    |                              | 0        |
|                                        | 36      | 0         | 22.30                    | 0-1                          | 1        |
|                                        | 36      | 18        | 22.23                    |                              | 1        |
|                                        | 36      | 37        | 22.21                    |                              | 1        |
|                                        | 75      | 0         | 22.29                    |                              | 1        |
| 16QAM                                  | 1       | 0         | 22.50                    | 0-1                          | 1        |
|                                        | 1       | 36        | 22.48                    |                              | 1        |
|                                        | 1       | 74        | 22.42                    |                              | 1        |
|                                        | 36      | 0         | 21.33                    | 0-2                          | 2        |
|                                        | 36      | 18        | 21.28                    |                              | 2        |
|                                        | 36      | 37        | 21.24                    |                              | 2        |
|                                        | 75      | 0         | 21.26                    |                              | 2        |

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-12**  
**LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth**

| LTE Band 26 (Cell)<br>10 MHz Bandwidth |         |           |                      |                      |                      |                              |          |
|----------------------------------------|---------|-----------|----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                             | RB Size | RB Offset | Low Channel          | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                        |         |           | 26740<br>(819.0 MHz) | 26865<br>(831.5 MHz) | 26990<br>(844.0 MHz) |                              |          |
| QPSK                                   | 1       | 0         | 23.01                | 23.27                | 23.45                | 0                            | 0        |
|                                        | 1       | 25        | 23.03                | 23.19                | 23.48                |                              | 0        |
|                                        | 1       | 49        | 22.97                | 23.18                | 23.36                |                              | 0        |
|                                        | 25      | 0         | 22.01                | 22.23                | 22.47                | 0-1                          | 1        |
|                                        | 25      | 12        | 22.03                | 22.21                | 22.48                |                              | 1        |
|                                        | 25      | 25        | 22.00                | 22.18                | 22.45                |                              | 1        |
|                                        | 50      | 0         | 22.02                | 22.20                | 22.45                |                              | 1        |
| 16QAM                                  | 1       | 0         | 22.07                | 22.27                | 22.37                | 0-1                          | 1        |
|                                        | 1       | 25        | 22.05                | 22.17                | 22.36                |                              | 1        |
|                                        | 1       | 49        | 22.09                | 22.24                | 22.31                |                              | 1        |
|                                        | 25      | 0         | 21.11                | 21.24                | 21.48                | 0-2                          | 2        |
|                                        | 25      | 12        | 21.10                | 21.23                | 21.48                |                              | 2        |
|                                        | 25      | 25        | 21.07                | 21.22                | 21.46                |                              | 2        |
|                                        | 50      | 0         | 21.12                | 21.28                | 21.47                |                              | 2        |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 34 of 95                   |

**Table 9-13**  
**LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth**

| LTE Band 26 (Cell)<br>5 MHz Bandwidth |         |           |                       |                      |                      |                              |          |
|---------------------------------------|---------|-----------|-----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 26715<br>(816.5 MHz)  | 26865<br>(831.5 MHz) | 27015<br>(846.5 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                      |                      |                              |          |
| QPSK                                  | 1       | 0         | 23.02                 | 23.24                | 23.45                | 0                            | 0        |
|                                       | 1       | 12        | 22.98                 | 23.10                | 23.43                |                              | 0        |
|                                       | 1       | 24        | 23.01                 | 23.18                | 23.31                |                              | 0        |
|                                       | 12      | 0         | 22.03                 | 22.22                | 22.42                | 0-1                          | 1        |
|                                       | 12      | 6         | 22.04                 | 22.23                | 22.46                |                              | 1        |
|                                       | 12      | 13        | 22.03                 | 22.22                | 22.34                |                              | 1        |
|                                       | 25      | 0         | 22.02                 | 22.21                | 22.42                |                              | 1        |
| 16QAM                                 | 1       | 0         | 22.06                 | 22.23                | 22.48                | 0-1                          | 1        |
|                                       | 1       | 12        | 22.07                 | 22.21                | 22.45                |                              | 1        |
|                                       | 1       | 24        | 22.05                 | 22.30                | 22.39                |                              | 1        |
|                                       | 12      | 0         | 21.06                 | 21.20                | 21.46                | 0-2                          | 2        |
|                                       | 12      | 6         | 21.04                 | 21.27                | 21.50                |                              | 2        |
|                                       | 12      | 13        | 21.04                 | 21.27                | 21.47                |                              | 2        |
|                                       | 25      | 0         | 21.01                 | 21.28                | 21.44                |                              | 2        |

**Table 9-14**  
**LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth**

| LTE Band 26 (Cell)<br>3 MHz Bandwidth |         |           |                       |                      |                      |                              |          |
|---------------------------------------|---------|-----------|-----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 26705<br>(815.5 MHz)  | 26865<br>(831.5 MHz) | 27025<br>(847.5 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                      |                      |                              |          |
| QPSK                                  | 1       | 0         | 23.09                 | 23.23                | 23.45                | 0                            | 0        |
|                                       | 1       | 7         | 23.03                 | 23.17                | 23.38                |                              | 0        |
|                                       | 1       | 14        | 23.02                 | 23.18                | 23.34                |                              | 0        |
|                                       | 8       | 0         | 22.19                 | 22.38                | 22.49                | 0-1                          | 1        |
|                                       | 8       | 4         | 22.21                 | 22.36                | 22.48                |                              | 1        |
|                                       | 8       | 7         | 22.16                 | 22.37                | 22.46                |                              | 1        |
|                                       | 15      | 0         | 22.18                 | 22.39                | 22.50                |                              | 1        |
| 16QAM                                 | 1       | 0         | 22.15                 | 22.33                | 22.39                | 0-1                          | 1        |
|                                       | 1       | 7         | 22.14                 | 22.45                | 22.45                |                              | 1        |
|                                       | 1       | 14        | 22.21                 | 22.38                | 22.48                |                              | 1        |
|                                       | 8       | 0         | 21.09                 | 21.38                | 21.47                | 0-2                          | 2        |
|                                       | 8       | 4         | 21.04                 | 21.37                | 21.43                |                              | 2        |
|                                       | 8       | 7         | 21.07                 | 21.39                | 21.43                |                              | 2        |
|                                       | 15      | 0         | 21.22                 | 21.44                | 21.49                |                              | 2        |

**Table 9-15**  
**LTE Band 26 (Cell) Conducted Powers - 1.4 MHz Bandwidth**

| LTE Band 26 (Cell)<br>1.4 MHz Bandwidth |         |           |                       |                      |                      |                              |          |
|-----------------------------------------|---------|-----------|-----------------------|----------------------|----------------------|------------------------------|----------|
| Modulation                              | RB Size | RB Offset | Low Channel           | Mid Channel          | High Channel         | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                         |         |           | 26697<br>(814.7 MHz)  | 26865<br>(831.5 MHz) | 27033<br>(848.3 MHz) |                              |          |
|                                         |         |           | Conducted Power [dBm] |                      |                      |                              |          |
| QPSK                                    | 1       | 0         | 23.06                 | 23.37                | 23.44                | 0                            | 0        |
|                                         | 1       | 2         | 23.06                 | 23.33                | 23.40                |                              | 0        |
|                                         | 1       | 5         | 23.03                 | 23.40                | 23.37                |                              | 0        |
|                                         | 3       | 0         | 23.08                 | 23.28                | 23.49                |                              | 0        |
|                                         | 3       | 2         | 23.15                 | 23.29                | 23.50                |                              | 0        |
|                                         | 3       | 3         | 23.10                 | 23.31                | 23.40                |                              | 0        |
|                                         | 6       | 0         | 22.11                 | 22.32                | 22.34                |                              | 0-1      |
| 16QAM                                   | 1       | 0         | 21.98                 | 22.10                | 22.44                | 0-1                          | 1        |
|                                         | 1       | 2         | 21.91                 | 22.04                | 22.49                |                              | 1        |
|                                         | 1       | 5         | 21.97                 | 22.10                | 22.38                |                              | 1        |
|                                         | 3       | 0         | 21.99                 | 22.18                | 22.43                |                              | 1        |
|                                         | 3       | 2         | 22.01                 | 22.19                | 22.45                |                              | 1        |
|                                         | 3       | 3         | 22.02                 | 22.22                | 22.44                |                              | 1        |
|                                         | 6       | 0         | 20.98                 | 21.37                | 21.42                |                              | 0-2      |

|                                      |                                                                                                                                                                                                        |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset   |
| Page 35 of 95                        |                                                                                                                                                                                                        |                                 |

### 9.3.5

### LTE Band 4 (AWS)

**Table 9-16**  
**LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth**

| LTE Band 4 (AWS)<br>20 MHz Bandwidth |         |           |                          |                              |          |
|--------------------------------------|---------|-----------|--------------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Mid Channel              | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 20175<br>(1732.5 MHz)    |                              |          |
|                                      |         |           | Conducted Power<br>[dBm] |                              |          |
| QPSK                                 | 1       | 0         | 23.81                    | 0                            | 0        |
|                                      | 1       | 50        | 23.76                    |                              | 0        |
|                                      | 1       | 99        | 23.74                    |                              | 0        |
|                                      | 50      | 0         | 22.85                    | 0-1                          | 1        |
|                                      | 50      | 25        | 22.87                    |                              | 1        |
|                                      | 50      | 50        | 22.84                    |                              | 1        |
|                                      | 100     | 0         | 22.85                    |                              | 1        |
| 16QAM                                | 1       | 0         | 22.81                    | 0-1                          | 1        |
|                                      | 1       | 50        | 22.79                    |                              | 1        |
|                                      | 1       | 99        | 22.76                    |                              | 1        |
|                                      | 50      | 0         | 21.79                    | 0-2                          | 2        |
|                                      | 50      | 25        | 21.72                    |                              | 2        |
|                                      | 50      | 50        | 21.74                    |                              | 2        |
|                                      | 100     | 0         | 21.75                    |                              | 2        |

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-17**  
**LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth**

| LTE Band 4 (AWS)<br>15 MHzBandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 20025<br>(1717.5 MHz) | 20175<br>(1732.5 MHz) | 20325<br>(1747.5 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 24.01                 | 24.14                 | 23.93                 | 0                            | 0        |
|                                     | 1       | 36        | 24.00                 | 24.14                 | 23.95                 |                              | 0        |
|                                     | 1       | 74        | 24.02                 | 24.12                 | 23.92                 |                              | 0        |
|                                     | 36      | 0         | 22.92                 | 23.08                 | 22.84                 | 0-1                          | 1        |
|                                     | 36      | 18        | 22.90                 | 23.07                 | 22.83                 |                              | 1        |
|                                     | 36      | 37        | 22.90                 | 23.04                 | 22.84                 |                              | 1        |
|                                     | 75      | 0         | 22.91                 | 23.06                 | 22.87                 |                              | 1        |
| 16QAM                               | 1       | 0         | 23.19                 | 22.70                 | 23.13                 | 0-1                          | 1        |
|                                     | 1       | 36        | 22.87                 | 23.17                 | 22.93                 |                              | 1        |
|                                     | 1       | 74        | 23.07                 | 23.17                 | 22.97                 |                              | 1        |
|                                     | 36      | 0         | 21.84                 | 21.91                 | 21.73                 | 0-2                          | 2        |
|                                     | 36      | 18        | 21.81                 | 21.97                 | 21.74                 |                              | 2        |
|                                     | 36      | 37        | 21.79                 | 21.97                 | 21.75                 |                              | 2        |
|                                     | 75      | 0         | 21.83                 | 21.93                 | 21.77                 |                              | 2        |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 36 of 95                   |

**Table 9-18**  
**LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth**

| LTE Band 4 (AWS)<br>10 MHzBandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 20000<br>(1715.0 MHz) | 20175<br>(1732.5 MHz) | 20350<br>(1750.0 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 23.81                 | 24.11                 | 23.83                 | 0                            | 0        |
|                                     | 1       | 25        | 23.80                 | 24.04                 | 23.79                 |                              | 0        |
|                                     | 1       | 49        | 23.90                 | 23.99                 | 23.87                 |                              | 0        |
|                                     | 25      | 0         | 22.90                 | 23.06                 | 22.83                 | 0-1                          | 1        |
|                                     | 25      | 12        | 22.90                 | 23.09                 | 22.80                 |                              | 1        |
|                                     | 25      | 25        | 22.89                 | 23.08                 | 22.83                 |                              | 1        |
|                                     | 50      | 0         | 22.89                 | 23.05                 | 22.82                 |                              | 1        |
| 16QAM                               | 1       | 0         | 22.91                 | 23.20                 | 22.79                 | 0-1                          | 1        |
|                                     | 1       | 25        | 23.00                 | 23.10                 | 22.91                 |                              | 1        |
|                                     | 1       | 49        | 22.87                 | 23.17                 | 22.99                 |                              | 1        |
|                                     | 25      | 0         | 21.84                 | 21.91                 | 21.72                 | 0-2                          | 2        |
|                                     | 25      | 12        | 21.79                 | 21.91                 | 21.76                 |                              | 2        |
|                                     | 25      | 25        | 21.81                 | 21.97                 | 21.75                 |                              | 2        |
|                                     | 50      | 0         | 21.83                 | 21.93                 | 21.76                 |                              | 2        |

**Table 9-19**  
**LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth**

| LTE Band 4 (AWS)<br>5 MHzBandwidth |         |           |                       |                       |                       |                              |          |
|------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                         | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                    |         |           | 19975<br>(1712.5 MHz) | 20175<br>(1732.5 MHz) | 20375<br>(1752.5 MHz) |                              |          |
|                                    |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                               | 1       | 0         | 24.18                 | 24.18                 | 23.73                 | 0                            | 0        |
|                                    | 1       | 12        | 24.10                 | 24.17                 | 23.66                 |                              | 0        |
|                                    | 1       | 24        | 24.03                 | 24.17                 | 23.62                 |                              | 0        |
|                                    | 12      | 0         | 22.93                 | 23.08                 | 22.85                 | 0-1                          | 1        |
|                                    | 12      | 6         | 22.96                 | 23.10                 | 22.82                 |                              | 1        |
|                                    | 12      | 13        | 22.94                 | 23.12                 | 22.80                 |                              | 1        |
|                                    | 25      | 0         | 22.92                 | 23.10                 | 22.82                 |                              | 1        |
| 16QAM                              | 1       | 0         | 22.97                 | 23.20                 | 22.85                 | 0-1                          | 1        |
|                                    | 1       | 12        | 23.07                 | 23.17                 | 22.92                 |                              | 1        |
|                                    | 1       | 24        | 23.18                 | 22.97                 | 22.87                 |                              | 1        |
|                                    | 12      | 0         | 21.85                 | 21.98                 | 21.73                 | 0-2                          | 2        |
|                                    | 12      | 6         | 21.82                 | 21.97                 | 21.73                 |                              | 2        |
|                                    | 12      | 13        | 21.85                 | 21.98                 | 21.75                 |                              | 2        |
|                                    | 25      | 0         | 21.88                 | 22.00                 | 21.76                 |                              | 2        |

**Table 9-20**  
**LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth**

| LTE Band 4 (AWS)<br>3 MHzBandwidth |         |           |                       |                       |                       |                              |          |
|------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                         | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                    |         |           | 19965<br>(1711.5 MHz) | 20175<br>(1732.5 MHz) | 20385<br>(1753.5 MHz) |                              |          |
|                                    |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                               | 1       | 0         | 23.95                 | 24.13                 | 23.95                 | 0                            | 0        |
|                                    | 1       | 7         | 23.92                 | 24.11                 | 23.82                 |                              | 0        |
|                                    | 1       | 14        | 23.99                 | 24.03                 | 23.74                 |                              | 0        |
|                                    | 8       | 0         | 22.92                 | 23.05                 | 22.80                 | 0-1                          | 1        |
|                                    | 8       | 4         | 22.92                 | 23.12                 | 22.78                 |                              | 1        |
|                                    | 8       | 7         | 22.89                 | 23.07                 | 22.79                 |                              | 1        |
|                                    | 15      | 0         | 22.92                 | 23.07                 | 22.79                 |                              | 1        |
| 16QAM                              | 1       | 0         | 23.08                 | 23.15                 | 22.98                 | 0-1                          | 1        |
|                                    | 1       | 7         | 22.99                 | 23.20                 | 22.91                 |                              | 1        |
|                                    | 1       | 14        | 22.96                 | 23.11                 | 22.79                 |                              | 1        |
|                                    | 8       | 0         | 21.87                 | 21.95                 | 21.70                 | 0-2                          | 2        |
|                                    | 8       | 4         | 21.88                 | 21.94                 | 21.73                 |                              | 2        |
|                                    | 8       | 7         | 21.81                 | 21.97                 | 21.74                 |                              | 2        |
|                                    | 15      | 0         | 21.85                 | 22.03                 | 21.77                 |                              | 2        |

|                                      |                                                                                     |                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  | SAR EVALUATION REPORT         |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                          | DUT Type:<br>Portable Handset |                                                                                       | Page 37 of 95                   |

**Table 9-21**  
**LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth**

| LTE Band 4 (AWS)<br>1.4 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|---------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 19957<br>(1710.7 MHz) | 20175<br>(1732.5 MHz) | 20393<br>(1754.3 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                  | 1       | 0         | 23.96                 | 24.16                 | 23.84                 | 0                            | 0        |
|                                       | 1       | 2         | 23.90                 | 24.13                 | 23.83                 |                              | 0        |
|                                       | 1       | 5         | 24.01                 | 24.11                 | 23.86                 |                              | 0        |
|                                       | 3       | 0         | 24.01                 | 24.14                 | 23.84                 |                              | 0        |
|                                       | 3       | 2         | 23.97                 | 24.14                 | 23.85                 |                              | 0        |
|                                       | 3       | 3         | 24.00                 | 24.12                 | 23.83                 |                              | 0        |
|                                       | 6       | 0         | 22.94                 | 23.13                 | 22.80                 |                              | 0        |
| 16QAM                                 | 1       | 0         | 22.93                 | 23.11                 | 22.68                 | 0-1                          | 1        |
|                                       | 1       | 2         | 22.91                 | 23.11                 | 22.60                 | 0-1                          | 1        |
|                                       | 1       | 5         | 22.87                 | 23.20                 | 22.55                 |                              | 1        |
|                                       | 3       | 0         | 23.05                 | 23.11                 | 22.89                 |                              | 1        |
|                                       | 3       | 2         | 22.90                 | 23.02                 | 22.81                 |                              | 1        |
|                                       | 3       | 3         | 23.11                 | 23.17                 | 22.74                 |                              | 1        |
|                                       | 6       | 0         | 21.94                 | 21.99                 | 21.76                 | 0-2                          | 2        |

**Table 9-22**  
**LTE Band 4 (AWS) Reduced Conducted Powers - 20 MHz Bandwidth**

| LTE Band 4 (AWS)<br>20 MHz Bandwidth |         |           |                          |                              |          |
|--------------------------------------|---------|-----------|--------------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Mid Channel              | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 20175<br>(1732.5 MHz)    |                              |          |
|                                      |         |           | Conducted Power<br>[dBm] |                              |          |
| QPSK                                 | 1       | 0         | 19.84                    | 0                            | 0        |
|                                      | 1       | 50        | <b>19.85</b>             |                              | 0        |
|                                      | 1       | 99        | 19.79                    |                              | 0        |
|                                      | 50      | 0         | <b>19.86</b>             | 0-1                          | 0        |
|                                      | 50      | 25        | 19.83                    |                              | 0        |
|                                      | 50      | 50        | 19.80                    |                              | 0        |
|                                      | 100     | 0         | 19.84                    |                              | 0        |
| 16QAM                                | 1       | 0         | 19.69                    | 0-1                          | 0        |
|                                      | 1       | 50        | 19.76                    |                              | 0        |
|                                      | 1       | 99        | 19.68                    |                              | 0        |
|                                      | 50      | 0         | 19.89                    | 0-2                          | 0        |
|                                      | 50      | 25        | 19.87                    |                              | 0        |
|                                      | 50      | 50        | 19.85                    |                              | 0        |
|                                      | 100     | 0         | 19.85                    |                              | 0        |

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

|                                             |                                                                                                                                                                                                        |                                      |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  | Page 38 of 95                          |

**Table 9-23**  
**LTE Band 4 (AWS) Reduced Conducted Powers - 15 MHz Bandwidth**

| LTE Band 4 (AWS)<br>15 MHzBandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 20025<br>(1717.5 MHz) | 20175<br>(1732.5 MHz) | 20325<br>(1747.5 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 19.91                 | 20.12                 | 19.86                 | 0                            | 0        |
|                                     | 1       | 36        | 19.87                 | 20.14                 | 19.80                 |                              | 0        |
|                                     | 1       | 74        | 19.69                 | 20.13                 | 19.75                 |                              | 0        |
|                                     | 36      | 0         | 19.81                 | 20.08                 | 19.77                 | 0-1                          | 0        |
|                                     | 36      | 18        | 19.86                 | 20.08                 | 19.78                 |                              | 0        |
|                                     | 36      | 37        | 19.72                 | 20.06                 | 19.74                 |                              | 0        |
|                                     | 75      | 0         | 19.77                 | 20.07                 | 19.80                 |                              | 0        |
| 16QAM                               | 1       | 0         | 19.62                 | 20.08                 | 19.67                 | 0-1                          | 0        |
|                                     | 1       | 36        | 19.61                 | 20.06                 | 19.60                 |                              | 0        |
|                                     | 1       | 74        | 19.66                 | 19.93                 | 19.64                 |                              | 0        |
|                                     | 36      | 0         | 19.81                 | 20.08                 | 19.77                 | 0-2                          | 0        |
|                                     | 36      | 18        | 19.79                 | 20.05                 | 19.74                 |                              | 0        |
|                                     | 36      | 37        | 19.78                 | 20.01                 | 19.76                 |                              | 0        |
|                                     | 75      | 0         | 19.82                 | 20.04                 | 19.75                 |                              | 0        |

**Table 9-24**  
**LTE Band 4 (AWS) Reduced Conducted Powers - 10 MHz Bandwidth**

| LTE Band 4 (AWS)<br>10 MHzBandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 20000<br>(1715.0 MHz) | 20175<br>(1732.5 MHz) | 20350<br>(1750.0 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 19.69                 | 19.91                 | 19.73                 | 0                            | 0        |
|                                     | 1       | 25        | 19.81                 | 19.83                 | 19.81                 |                              | 0        |
|                                     | 1       | 49        | 19.70                 | 19.86                 | 19.64                 |                              | 0        |
|                                     | 25      | 0         | 19.66                 | 20.06                 | 19.86                 | 0-1                          | 0        |
|                                     | 25      | 12        | 19.68                 | 20.06                 | 19.65                 |                              | 0        |
|                                     | 25      | 25        | 19.68                 | 20.05                 | 19.69                 |                              | 0        |
|                                     | 50      | 0         | 19.73                 | 20.06                 | 19.76                 |                              | 0        |
| 16QAM                               | 1       | 0         | 19.89                 | 19.98                 | 19.71                 | 0-1                          | 0        |
|                                     | 1       | 25        | 19.68                 | 19.84                 | 19.67                 |                              | 0        |
|                                     | 1       | 49        | 19.79                 | 19.81                 | 19.67                 |                              | 0        |
|                                     | 25      | 0         | 19.83                 | 20.09                 | 19.80                 | 0-2                          | 0        |
|                                     | 25      | 12        | 19.86                 | 20.11                 | 19.75                 |                              | 0        |
|                                     | 25      | 25        | 19.74                 | 20.06                 | 19.72                 |                              | 0        |
|                                     | 50      | 0         | 19.78                 | 20.11                 | 19.70                 |                              | 0        |

**Table 9-25**  
**LTE Band 4 (AWS) Reduced Conducted Powers - 5 MHz Bandwidth**

| LTE Band 4 (AWS)<br>5 MHzBandwidth |         |           |                       |                       |                       |                              |          |
|------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                         | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                    |         |           | 19975<br>(1712.5 MHz) | 20175<br>(1732.5 MHz) | 20375<br>(1752.5 MHz) |                              |          |
|                                    |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                               | 1       | 0         | 19.73                 | 20.12                 | 19.77                 | 0                            | 0        |
|                                    | 1       | 12        | 19.78                 | 19.90                 | 19.74                 |                              | 0        |
|                                    | 1       | 24        | 19.86                 | 20.12                 | 19.72                 |                              | 0        |
|                                    | 12      | 0         | 19.99                 | 20.14                 | 19.71                 | 0-1                          | 0        |
|                                    | 12      | 6         | 20.01                 | 20.16                 | 19.77                 |                              | 0        |
|                                    | 12      | 13        | 19.98                 | 20.14                 | 19.75                 |                              | 0        |
|                                    | 25      | 0         | 19.96                 | 20.15                 | 19.79                 |                              | 0        |
| 16QAM                              | 1       | 0         | 19.60                 | 19.91                 | 19.73                 | 0-1                          | 0        |
|                                    | 1       | 12        | 19.69                 | 19.82                 | 19.71                 |                              | 0        |
|                                    | 1       | 24        | 19.61                 | 19.73                 | 19.75                 |                              | 0        |
|                                    | 12      | 0         | 19.85                 | 20.15                 | 19.70                 | 0-2                          | 0        |
|                                    | 12      | 6         | 19.75                 | 20.14                 | 19.72                 |                              | 0        |
|                                    | 12      | 13        | 19.80                 | 20.12                 | 19.75                 |                              | 0        |
|                                    | 25      | 0         | 19.97                 | 20.11                 | 19.73                 |                              | 0        |

|                                      |                                                                                                                                                                                                        |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset   |
| Page 39 of 95                        |                                                                                                                                                                                                        |                                 |



**Table 9-26**  
**LTE Band 4 (AWS) Reduced Conducted Powers - 3 MHz Bandwidth**

| LTE Band 4 (AWS)<br>3 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 19965<br>(1711.5 MHz) | 20175<br>(1732.5 MHz) | 20385<br>(1753.5 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 19.83                 | 19.94                 | 19.78                 | 0                            | 0        |
|                                     | 1       | 7         | 19.85                 | 19.98                 | 19.75                 |                              | 0        |
|                                     | 1       | 14        | 19.83                 | 19.93                 | 19.74                 |                              | 0        |
|                                     | 8       | 0         | 19.94                 | 20.06                 | 19.77                 | 0-1                          | 0        |
|                                     | 8       | 4         | 19.92                 | 20.08                 | 19.80                 |                              | 0        |
|                                     | 8       | 7         | 19.94                 | 20.07                 | 19.76                 |                              | 0        |
| 16QAM                               | 15      | 0         | 20.03                 | 20.12                 | 19.83                 |                              | 0        |
|                                     | 1       | 0         | 19.78                 | 20.18                 | 19.83                 | 0-1                          | 0        |
|                                     | 1       | 7         | 19.80                 | 20.22                 | 19.82                 |                              | 0        |
|                                     | 1       | 14        | 19.88                 | 20.23                 | 19.89                 |                              | 0        |
|                                     | 8       | 0         | 19.81                 | 20.05                 | 19.79                 | 0-2                          | 0        |
|                                     | 8       | 4         | 19.89                 | 20.09                 | 19.82                 |                              | 0        |
|                                     | 8       | 7         | 19.86                 | 20.08                 | 19.78                 |                              | 0        |
|                                     | 15      | 0         | 19.97                 | 20.08                 | 19.80                 |                              | 0        |

**Table 9-27**  
**LTE Band 4 (AWS) Reduced Conducted Powers -1.4 MHz Bandwidth**

| LTE Band 4 (AWS)<br>1.4 MHzBandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 19957<br>(1710.7 MHz) | 20175<br>(1732.5 MHz) | 20393<br>(1754.3 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 19.98                 | 20.17                 | 19.75                 | 0                            | 0        |
|                                      | 1       | 2         | 19.91                 | 20.13                 | 19.73                 |                              | 0        |
|                                      | 1       | 5         | 19.93                 | 20.13                 | 19.76                 |                              | 0        |
|                                      | 3       | 0         | 20.02                 | 20.22                 | 19.82                 |                              | 0        |
|                                      | 3       | 2         | 20.06                 | 20.29                 | 19.79                 |                              | 0        |
|                                      | 3       | 3         | 19.99                 | 20.14                 | 19.78                 |                              | 0        |
|                                      | 6       | 0         | 19.97                 | 20.16                 | 19.81                 |                              | 0        |
| 16QAM                                | 1       | 0         | 19.96                 | 19.85                 | 19.66                 | 0-1                          | 0        |
|                                      | 1       | 2         | 19.95                 | 19.83                 | 19.66                 | 0-1                          | 0        |
|                                      | 1       | 5         | 19.96                 | 19.86                 | 19.73                 |                              | 0        |
|                                      | 3       | 0         | 20.02                 | 20.03                 | 19.60                 |                              | 0        |
|                                      | 3       | 2         | 19.99                 | 20.08                 | 19.59                 |                              | 0        |
|                                      | 3       | 3         | 20.04                 | 20.05                 | 19.61                 |                              | 0        |
|                                      | 6       | 0         | 19.99                 | 20.23                 | 19.66                 |                              | 0-2      |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 40 of 95                          |

### 9.3.6

### LTE Band 2 (PCS)

**Table 9-28**  
**LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth**

| LTE Band 2 (PCS)<br>20 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 18700<br>(1860.0 MHz) | 18900<br>(1880.0 MHz) | 19100<br>(1900.0 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 22.84                 | 22.53                 | 23.21                 | 0                            | 0        |
|                                      | 1       | 50        | 22.76                 | 22.58                 | 23.15                 |                              | 0        |
|                                      | 1       | 99        | 22.74                 | 22.59                 | 23.09                 |                              | 0        |
|                                      | 50      | 0         | 21.91                 | 21.67                 | 22.19                 | 0-1                          | 1        |
|                                      | 50      | 25        | 21.90                 | 21.68                 | 22.18                 |                              | 1        |
|                                      | 50      | 50        | 21.92                 | 21.72                 | 22.13                 |                              | 1        |
|                                      | 100     | 0         | 21.97                 | 21.69                 | 22.15                 |                              | 1        |
| 16QAM                                | 1       | 0         | 21.98                 | 21.62                 | 22.50                 | 0-1                          | 1        |
|                                      | 1       | 50        | 21.93                 | 21.64                 | 22.42                 |                              | 1        |
|                                      | 1       | 99        | 21.91                 | 21.68                 | 22.39                 |                              | 1        |
|                                      | 50      | 0         | 21.00                 | 20.74                 | 21.27                 | 0-2                          | 2        |
|                                      | 50      | 25        | 20.96                 | 20.71                 | 21.21                 |                              | 2        |
|                                      | 50      | 50        | 20.95                 | 20.76                 | 21.15                 |                              | 2        |
|                                      | 100     | 0         | 20.96                 | 20.75                 | 21.16                 |                              | 2        |

**Table 9-29**  
**LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth**

| LTE Band 2 (PCS)<br>15 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 18675<br>(1857.5 MHz) | 18900<br>(1880.0 MHz) | 19125<br>(1902.5 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 23.15                 | 22.79                 | 23.39                 | 0                            | 0        |
|                                      | 1       | 36        | 23.09                 | 22.80                 | 23.41                 |                              | 0        |
|                                      | 1       | 74        | 23.02                 | 22.84                 | 23.24                 |                              | 0        |
|                                      | 36      | 0         | 22.06                 | 21.77                 | 22.36                 | 0-1                          | 1        |
|                                      | 36      | 18        | 22.03                 | 21.78                 | 22.32                 |                              | 1        |
|                                      | 36      | 37        | 21.99                 | 21.77                 | 22.31                 |                              | 1        |
|                                      | 75      | 0         | 22.01                 | 21.81                 | 22.30                 |                              | 1        |
| 16QAM                                | 1       | 0         | 22.02                 | 21.79                 | 22.49                 | 0-1                          | 1        |
|                                      | 1       | 36        | 21.95                 | 21.89                 | 22.39                 |                              | 1        |
|                                      | 1       | 74        | 22.05                 | 21.85                 | 22.28                 |                              | 1        |
|                                      | 36      | 0         | 21.06                 | 20.79                 | 21.38                 | 0-2                          | 2        |
|                                      | 36      | 18        | 21.01                 | 20.75                 | 21.34                 |                              | 2        |
|                                      | 36      | 37        | 20.97                 | 20.78                 | 21.23                 |                              | 2        |
|                                      | 75      | 0         | 21.01                 | 20.80                 | 21.32                 |                              | 2        |

**Table 9-30**  
**LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth**

| LTE Band 2 (PCS)<br>10 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 18650<br>(1855.0 MHz) | 18900<br>(1880.0 MHz) | 19150<br>(1905.0 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 22.99                 | 22.71                 | 23.50                 | 0                            | 0        |
|                                      | 1       | 25        | 23.06                 | 22.68                 | 23.41                 |                              | 0        |
|                                      | 1       | 49        | 22.93                 | 22.84                 | 23.24                 |                              | 0        |
|                                      | 25      | 0         | 22.02                 | 21.76                 | 22.36                 | 0-1                          | 1        |
|                                      | 25      | 12        | 22.03                 | 21.77                 | 22.32                 |                              | 1        |
|                                      | 25      | 25        | 21.98                 | 21.80                 | 22.31                 |                              | 1        |
|                                      | 50      | 0         | 22.00                 | 21.76                 | 22.30                 |                              | 1        |
| 16QAM                                | 1       | 0         | 22.25                 | 21.65                 | 22.50                 | 0-1                          | 1        |
|                                      | 1       | 25        | 22.15                 | 21.79                 | 22.25                 |                              | 1        |
|                                      | 1       | 49        | 22.06                 | 21.88                 | 22.14                 |                              | 1        |
|                                      | 25      | 0         | 21.03                 | 20.77                 | 21.38                 | 0-2                          | 2        |
|                                      | 25      | 12        | 21.05                 | 20.75                 | 21.34                 |                              | 2        |
|                                      | 25      | 25        | 20.96                 | 20.80                 | 21.23                 |                              | 2        |
|                                      | 50      | 0         | 21.01                 | 20.76                 | 21.32                 |                              | 2        |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 41 of 95                   |

**Table 9-31**  
**LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth**

| LTE Band 2 (PCS)<br>5 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 18625<br>(1852.5 MHz) | 18900<br>(1880.0 MHz) | 19175<br>(1907.5 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 23.16                 | 23.06                 | 23.22                 | 0                            | 0        |
|                                     | 1       | 12        | 23.24                 | 23.10                 | 23.19                 |                              | 0        |
|                                     | 1       | 24        | 23.23                 | 22.81                 | 23.18                 |                              | 0        |
|                                     | 12      | 0         | 22.01                 | 21.76                 | 22.35                 | 0-1                          | 1        |
|                                     | 12      | 6         | 22.01                 | 21.74                 | 22.33                 |                              | 1        |
|                                     | 12      | 13        | 21.99                 | 21.75                 | 22.31                 |                              | 1        |
| 16QAM                               | 25      | 0         | 22.03                 | 21.73                 | 22.34                 | 0-1                          | 1        |
|                                     | 1       | 0         | 22.25                 | 21.90                 | 22.50                 |                              | 1        |
|                                     | 1       | 12        | 22.01                 | 21.89                 | 22.31                 |                              | 1        |
|                                     | 1       | 24        | 22.09                 | 21.69                 | 22.29                 | 0-2                          | 1        |
|                                     | 12      | 0         | 21.02                 | 20.71                 | 21.33                 |                              | 2        |
|                                     | 12      | 6         | 21.07                 | 20.77                 | 21.35                 |                              | 2        |
|                                     | 12      | 13        | 21.02                 | 20.74                 | 21.33                 | 0-2                          | 2        |
|                                     | 25      | 0         | 21.02                 | 20.76                 | 21.31                 |                              | 2        |

**Table 9-32**  
**LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth**

| LTE Band 2 (PCS)<br>3 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 18615<br>(1851.5 MHz) | 18900<br>(1880.0 MHz) | 19185<br>(1908.5 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 23.03                 | 22.69                 | 23.46                 | 0                            | 0        |
|                                     | 1       | 7         | 23.05                 | 22.69                 | 23.45                 |                              | 0        |
|                                     | 1       | 14        | 22.99                 | 22.68                 | 23.45                 |                              | 0        |
|                                     | 8       | 0         | 22.03                 | 21.78                 | 22.37                 | 0-1                          | 1        |
|                                     | 8       | 4         | 22.04                 | 21.83                 | 22.40                 |                              | 1        |
|                                     | 8       | 7         | 22.07                 | 21.76                 | 22.37                 |                              | 1        |
| 16QAM                               | 15      | 0         | 22.04                 | 21.77                 | 22.36                 | 0-1                          | 1        |
|                                     | 1       | 0         | 22.02                 | 21.80                 | 22.49                 |                              | 1        |
|                                     | 1       | 7         | 22.31                 | 22.00                 | 22.50                 |                              | 1        |
|                                     | 1       | 14        | 22.12                 | 21.95                 | 22.50                 | 0-2                          | 1        |
|                                     | 8       | 0         | 21.03                 | 20.83                 | 21.37                 |                              | 2        |
|                                     | 8       | 4         | 21.04                 | 20.82                 | 21.36                 |                              | 2        |
|                                     | 8       | 7         | 21.11                 | 20.86                 | 21.32                 |                              | 2        |
|                                     | 15      | 0         | 21.08                 | 20.82                 | 21.37                 |                              | 2        |

**Table 9-33**  
**LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth**

| LTE Band 2 (PCS)<br>1.4 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|---------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 18607<br>(1850.7 MHz) | 18900<br>(1880.0 MHz) | 19193<br>(1909.3 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                  | 1       | 0         | 22.97                 | 22.78                 | 23.47                 | 0                            | 0        |
|                                       | 1       | 2         | 23.09                 | 22.77                 | 23.44                 |                              | 0        |
|                                       | 1       | 5         | 23.06                 | 22.81                 | 23.46                 |                              | 0        |
|                                       | 3       | 0         | 23.05                 | 22.79                 | 23.48                 |                              | 0        |
|                                       | 3       | 2         | 23.05                 | 22.80                 | 23.43                 |                              | 0        |
|                                       | 3       | 3         | 23.07                 | 22.74                 | 23.48                 |                              | 0        |
| 16QAM                                 | 6       | 0         | 22.05                 | 21.77                 | 22.39                 | 0-1                          | 1        |
|                                       | 1       | 0         | 22.25                 | 21.78                 | 22.28                 | 0-1                          | 1        |
|                                       | 1       | 2         | 22.02                 | 21.60                 | 22.43                 |                              | 1        |
|                                       | 1       | 5         | 22.10                 | 21.68                 | 22.43                 |                              | 1        |
|                                       | 3       | 0         | 22.07                 | 21.86                 | 22.48                 |                              | 1        |
|                                       | 3       | 2         | 22.12                 | 21.86                 | 22.48                 |                              | 1        |
|                                       | 3       | 3         | 22.10                 | 21.74                 | 22.50                 | 1                            |          |
|                                       | 6       | 0         | 21.02                 | 20.77                 | 21.32                 | 0-2                          | 2        |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 42 of 95                          |

**Table 9-34**  
**LTE Band 2 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth**

| LTE Band 2 (PCS)<br>20 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 18700<br>(1860.0 MHz) | 18900<br>(1880.0 MHz) | 19100<br>(1900.0 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 20.35                 | 20.11                 | 20.51                 | 0                            | 0        |
|                                      | 1       | 50        | 20.19                 | 20.04                 | 20.48                 |                              | 0        |
|                                      | 1       | 99        | 20.14                 | 20.10                 | 20.34                 |                              | 0        |
|                                      | 50      | 0         | 20.21                 | 20.00                 | 20.48                 | 0-1                          | 0        |
|                                      | 50      | 25        | 20.18                 | 20.02                 | 20.46                 |                              | 0        |
|                                      | 50      | 50        | 20.12                 | 20.03                 | 20.41                 |                              | 0        |
| 16QAM                                | 100     | 0         | 20.17                 | 20.03                 | 20.44                 | 0-1                          | 0        |
|                                      | 1       | 0         | 20.26                 | 20.00                 | 20.40                 |                              | 0        |
|                                      | 1       | 50        | 20.17                 | 20.00                 | 20.40                 |                              | 0        |
|                                      | 1       | 99        | 20.03                 | 19.91                 | 20.30                 | 0-1                          | 0        |
|                                      | 50      | 0         | 20.20                 | 20.03                 | 20.49                 |                              | 0        |
|                                      | 50      | 25        | 20.17                 | 20.04                 | 20.46                 |                              | 0        |
|                                      | 50      | 50        | 20.14                 | 20.05                 | 20.41                 | 0-2                          | 0        |
|                                      | 100     | 0         | 20.17                 | 20.01                 | 20.41                 |                              | 0        |

**Table 9-35**  
**LTE Band 2 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth**

| LTE Band 2 (PCS)<br>15 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 18675<br>(1857.5 MHz) | 18900<br>(1880.0 MHz) | 19125<br>(1902.5 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 20.36                 | 20.14                 | 20.54                 | 0                            | 0        |
|                                      | 1       | 36        | 20.35                 | 20.07                 | 20.49                 |                              | 0        |
|                                      | 1       | 74        | 20.26                 | 20.08                 | 20.44                 |                              | 0        |
|                                      | 36      | 0         | 20.29                 | 20.09                 | 20.45                 | 0-1                          | 0        |
|                                      | 36      | 18        | 20.21                 | 20.06                 | 20.39                 |                              | 0        |
|                                      | 36      | 37        | 20.18                 | 20.05                 | 20.40                 |                              | 0        |
| 16QAM                                | 75      | 0         | 20.24                 | 20.02                 | 20.42                 | 0-1                          | 0        |
|                                      | 1       | 0         | 20.33                 | 20.01                 | 20.59                 |                              | 0        |
|                                      | 1       | 36        | 20.26                 | 20.06                 | 20.60                 | 0-1                          | 0        |
|                                      | 1       | 74        | 20.29                 | 20.08                 | 20.53                 |                              | 0        |
|                                      | 36      | 0         | 20.28                 | 19.98                 | 20.48                 |                              | 0        |
|                                      | 36      | 18        | 20.22                 | 20.00                 | 20.42                 | 0-2                          | 0        |
|                                      | 36      | 37        | 20.18                 | 20.01                 | 20.38                 |                              | 0        |
|                                      | 75      | 0         | 20.19                 | 20.02                 | 20.44                 |                              | 0        |

**Table 9-36**  
**LTE Band 2 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth**

| LTE Band 2 (PCS)<br>10 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 18650<br>(1855.0 MHz) | 18900<br>(1880.0 MHz) | 19150<br>(1905.0 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 20.22                 | 19.96                 | 20.52                 | 0                            | 0        |
|                                      | 1       | 25        | 20.16                 | 20.00                 | 20.50                 |                              | 0        |
|                                      | 1       | 49        | 20.10                 | 20.01                 | 20.42                 |                              | 0        |
|                                      | 25      | 0         | 20.23                 | 19.98                 | 20.53                 | 0-1                          | 0        |
|                                      | 25      | 12        | 20.24                 | 19.97                 | 20.51                 |                              | 0        |
|                                      | 25      | 25        | 20.18                 | 19.99                 | 20.47                 |                              | 0        |
| 16QAM                                | 50      | 0         | 20.22                 | 19.98                 | 20.51                 | 0-1                          | 0        |
|                                      | 1       | 0         | 20.33                 | 19.95                 | 20.52                 |                              | 0        |
|                                      | 1       | 25        | 20.22                 | 20.08                 | 20.55                 |                              | 0        |
|                                      | 1       | 49        | 20.21                 | 20.01                 | 20.51                 | 0-2                          | 0        |
|                                      | 25      | 0         | 20.23                 | 19.96                 | 20.51                 |                              | 0        |
|                                      | 25      | 12        | 20.21                 | 19.97                 | 20.49                 |                              | 0        |
|                                      | 25      | 25        | 20.16                 | 20.01                 | 20.46                 | 0                            |          |
|                                      | 50      | 0         | 20.32                 | 19.97                 | 20.46                 | 0                            |          |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 43 of 95                          |

**Table 9-37**  
**LTE Band 2 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth**

| LTE Band 2 (PCS)<br>5 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 18625<br>(1852.5 MHz) | 18900<br>(1880.0 MHz) | 19175<br>(1907.5 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 20.19                 | 19.92                 | 20.52                 | 0                            | 0        |
|                                     | 1       | 12        | 20.13                 | 19.94                 | 20.48                 |                              | 0        |
|                                     | 1       | 24        | 20.12                 | 19.89                 | 20.47                 |                              | 0        |
|                                     | 12      | 0         | 20.26                 | 19.97                 | 20.55                 | 0-1                          | 0        |
|                                     | 12      | 6         | 20.24                 | 19.96                 | 20.54                 |                              | 0        |
|                                     | 12      | 13        | 20.23                 | 19.94                 | 20.49                 |                              | 0        |
| 16QAM                               | 25      | 0         | 20.26                 | 19.96                 | 20.53                 | 0-1                          | 0        |
|                                     | 1       | 0         | 20.21                 | 20.04                 | 20.53                 |                              | 0        |
|                                     | 1       | 12        | 20.21                 | 19.84                 | 20.46                 |                              | 0        |
|                                     | 1       | 24        | 20.15                 | 19.97                 | 20.55                 | 0-2                          | 0        |
|                                     | 12      | 0         | 20.18                 | 19.94                 | 20.51                 |                              | 0        |
|                                     | 12      | 6         | 20.19                 | 19.97                 | 20.49                 |                              | 0        |
|                                     | 12      | 13        | 20.17                 | 19.96                 | 20.50                 |                              | 0        |
|                                     | 25      | 0         | 20.16                 | 19.95                 | 20.48                 |                              | 0        |

**Table 9-38**  
**LTE Band 2 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth**

| LTE Band 2 (PCS)<br>3 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|-------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                          | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                     |         |           | 18615<br>(1851.5 MHz) | 18900<br>(1880.0 MHz) | 19185<br>(1908.5 MHz) |                              |          |
|                                     |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                | 1       | 0         | 20.19                 | 19.91                 | 20.59                 | 0                            | 0        |
|                                     | 1       | 7         | 20.18                 | 19.90                 | 20.55                 |                              | 0        |
|                                     | 1       | 14        | 20.20                 | 19.88                 | 20.57                 |                              | 0        |
|                                     | 8       | 0         | 20.32                 | 20.08                 | 20.58                 | 0-1                          | 0        |
|                                     | 8       | 4         | 20.31                 | 20.08                 | 20.60                 |                              | 0        |
|                                     | 8       | 7         | 20.28                 | 20.11                 | 20.56                 |                              | 0        |
| 16QAM                               | 15      | 0         | 20.35                 | 20.07                 | 20.62                 | 0-1                          | 0        |
|                                     | 1       | 0         | 20.16                 | 20.21                 | 20.74                 |                              | 0        |
|                                     | 1       | 7         | 20.07                 | 20.21                 | 20.68                 | 0-1                          | 0        |
|                                     | 1       | 14        | 20.16                 | 20.18                 | 20.70                 |                              | 0        |
|                                     | 8       | 0         | 20.27                 | 20.14                 | 20.56                 |                              | 0-2      |
|                                     | 8       | 4         | 20.24                 | 20.15                 | 20.57                 | 0                            |          |
|                                     | 8       | 7         | 20.23                 | 20.16                 | 20.53                 | 0                            |          |
|                                     |         | 15        | 0                     | 20.36                 | 20.12                 | 20.72                        |          |

**Table 9-39**  
**LTE Band 2 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth**

| LTE Band 2 (PCS)  |         |           |                       |                       |                       |                              |          |
|-------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| 1.4 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
| Modulation        | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                   |         |           | 18607<br>(1850.7 MHz) | 18900<br>(1880.0 MHz) | 19193<br>(1909.3 MHz) |                              |          |
|                   |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK              | 1       | 0         | 20.32                 | 20.12                 | 20.51                 | 0                            | 0        |
|                   | 1       | 2         | 20.33                 | 20.06                 | 20.67                 |                              | 0        |
|                   | 1       | 5         | 20.40                 | 20.12                 | 20.53                 |                              | 0        |
|                   | 3       | 0         | 20.47                 | 20.06                 | 20.61                 |                              | 0        |
|                   | 3       | 2         | 20.51                 | 20.04                 | 20.63                 |                              | 0        |
|                   | 3       | 3         | 20.45                 | 20.09                 | 20.63                 |                              | 0        |
| 16QAM             | 6       | 0         | 20.47                 | 20.13                 | 20.65                 | 0-1                          | 0        |
|                   | 1       | 0         | 20.27                 | 20.08                 | 20.21                 | 0-1                          | 0        |
|                   | 1       | 2         | 20.21                 | 20.05                 | 20.27                 |                              | 0        |
|                   | 1       | 5         | 20.22                 | 20.04                 | 20.29                 |                              | 0        |
|                   | 3       | 0         | 20.26                 | 20.08                 | 20.42                 |                              | 0        |
|                   | 3       | 2         | 20.19                 | 20.07                 | 20.41                 |                              | 0        |
|                   | 3       | 3         | 20.24                 | 20.05                 | 20.43                 | 0                            |          |
|                   | 6       | 0         | 20.37                 | 20.13                 | 20.58                 | 0-2                          | 0        |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 44 of 95                          |

### 9.3.7

### LTE Band 25 (PCS)

**Table 9-40**  
**LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth**

| LTE Band 25 (PCS)<br>20 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|---------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 26140<br>(1860.0 MHz) | 26365<br>(1882.5 MHz) | 26590<br>(1905.0 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                  | 1       | 0         | 21.98                 | 21.63                 | 22.30                 | 0                            | 0        |
|                                       | 1       | 50        | 21.90                 | 21.59                 | 22.21                 |                              | 0        |
|                                       | 1       | 99        | 21.87                 | 21.67                 | 22.09                 |                              | 0        |
|                                       | 50      | 0         | 20.98                 | 20.82                 | 21.22                 | 0-1                          | 1        |
|                                       | 50      | 25        | 20.93                 | 20.81                 | 21.20                 |                              | 1        |
|                                       | 50      | 50        | 20.90                 | 20.86                 | 21.13                 |                              | 1        |
|                                       | 100     | 0         | 20.94                 | 20.84                 | 21.19                 |                              | 1        |
| 16QAM                                 | 1       | 0         | 21.23                 | 20.68                 | 21.43                 | 0-1                          | 1        |
|                                       | 1       | 50        | 21.07                 | 20.65                 | 21.32                 |                              | 1        |
|                                       | 1       | 99        | 21.11                 | 20.67                 | 21.26                 |                              | 1        |
|                                       | 50      | 0         | 19.92                 | 19.74                 | 20.31                 | 0-2                          | 2        |
|                                       | 50      | 25        | 19.88                 | 19.77                 | 20.17                 |                              | 2        |
|                                       | 50      | 50        | 19.88                 | 19.83                 | 20.21                 |                              | 2        |
|                                       | 100     | 0         | 19.87                 | 19.82                 | 20.30                 |                              | 2        |

**Table 9-41**  
**LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth**

| LTE Band 25 (PCS)<br>15 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|---------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 26115<br>(1857.5 MHz) | 26365<br>(1882.5 MHz) | 26615<br>(1907.5 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                  | 1       | 0         | 21.89                 | 21.72                 | 22.50                 | 0                            | 0        |
|                                       | 1       | 36        | 21.90                 | 21.74                 | 22.47                 |                              | 0        |
|                                       | 1       | 74        | 21.86                 | 21.70                 | 22.41                 |                              | 0        |
|                                       | 36      | 0         | 21.10                 | 20.92                 | 21.39                 | 0-1                          | 1        |
|                                       | 36      | 18        | 21.06                 | 20.95                 | 21.33                 |                              | 1        |
|                                       | 36      | 37        | 21.03                 | 20.98                 | 21.30                 |                              | 1        |
|                                       | 75      | 0         | 21.06                 | 20.95                 | 21.32                 |                              | 1        |
| 16QAM                                 | 1       | 0         | 21.07                 | 21.05                 | 21.50                 | 0-1                          | 1        |
|                                       | 1       | 36        | 20.96                 | 21.09                 | 21.47                 |                              | 1        |
|                                       | 1       | 74        | 20.89                 | 21.03                 | 21.45                 |                              | 1        |
|                                       | 36      | 0         | 20.07                 | 19.90                 | 20.35                 | 0-2                          | 2        |
|                                       | 36      | 18        | 20.00                 | 19.88                 | 20.32                 |                              | 2        |
|                                       | 36      | 37        | 19.97                 | 19.90                 | 20.30                 |                              | 2        |
|                                       | 75      | 0         | 20.00                 | 19.91                 | 20.30                 |                              | 2        |

**Table 9-42**  
**LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth**

| LTE Band 25 (PCS)<br>10 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|---------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 26090<br>(1855.0 MHz) | 26365<br>(1882.5 MHz) | 26640<br>(1910.0 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                  | 1       | 0         | 22.12                 | 21.74                 | 22.46                 | 0                            | 0        |
|                                       | 1       | 25        | 22.09                 | 21.74                 | 22.40                 |                              | 0        |
|                                       | 1       | 49        | 22.01                 | 21.75                 | 22.39                 |                              | 0        |
|                                       | 25      | 0         | 21.06                 | 20.97                 | 21.34                 | 0-1                          | 1        |
|                                       | 25      | 12        | 21.03                 | 20.94                 | 21.32                 |                              | 1        |
|                                       | 25      | 25        | 21.02                 | 20.98                 | 21.30                 |                              | 1        |
|                                       | 50      | 0         | 21.01                 | 20.96                 | 21.30                 |                              | 1        |
| 16QAM                                 | 1       | 0         | 21.16                 | 20.79                 | 21.50                 | 0-1                          | 1        |
|                                       | 1       | 25        | 21.10                 | 20.79                 | 21.47                 |                              | 1        |
|                                       | 1       | 49        | 21.06                 | 20.78                 | 21.48                 |                              | 1        |
|                                       | 25      | 0         | 20.00                 | 19.86                 | 20.32                 | 0-2                          | 2        |
|                                       | 25      | 12        | 20.00                 | 19.87                 | 20.31                 |                              | 2        |
|                                       | 25      | 25        | 19.97                 | 19.87                 | 20.25                 |                              | 2        |
|                                       | 50      | 0         | 19.93                 | 19.87                 | 20.30                 |                              | 2        |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 45 of 95                   |

**Table 9-43**  
**LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth**

| LTE Band 25 (PCS)<br>5 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 26065<br>(1852.5 MHz) | 26365<br>(1882.5 MHz) | 26665<br>(1912.5 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 21.86                 | 21.74                 | 22.35                 | 0                            | 0        |
|                                      | 1       | 12        | 21.87                 | 21.75                 | 22.28                 |                              | 0        |
|                                      | 1       | 24        | 21.86                 | 21.80                 | 22.27                 |                              | 0        |
|                                      | 12      | 0         | 21.01                 | 20.91                 | 21.24                 | 0-1                          | 1        |
|                                      | 12      | 6         | 21.02                 | 20.91                 | 21.23                 |                              | 1        |
|                                      | 12      | 13        | 21.01                 | 20.94                 | 21.25                 |                              | 1        |
| 16QAM                                | 25      | 0         | 21.03                 | 20.96                 | 21.26                 | 0-1                          | 1        |
|                                      | 1       | 0         | 21.05                 | 20.87                 | 21.28                 |                              | 1        |
|                                      | 1       | 12        | 20.96                 | 20.84                 | 21.23                 |                              | 1        |
|                                      | 1       | 24        | 20.98                 | 20.87                 | 21.29                 | 0-2                          | 1        |
|                                      | 12      | 0         | 19.99                 | 19.84                 | 20.37                 |                              | 2        |
|                                      | 12      | 6         | 19.96                 | 19.91                 | 20.25                 |                              | 2        |
|                                      | 12      | 13        | 19.97                 | 19.96                 | 20.26                 |                              | 2        |
|                                      | 25      | 0         | 19.93                 | 19.89                 | 20.33                 |                              | 2        |

**Table 9-44**  
**LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth**

| LTE Band 25 (PCS)<br>3 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 26055<br>(1851.5 MHz) | 26365<br>(1882.5 MHz) | 26675<br>(1913.5 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 21.79                 | 21.67                 | 22.07                 | 0                            | 0        |
|                                      | 1       | 7         | 21.79                 | 21.72                 | 22.09                 |                              | 0        |
|                                      | 1       | 14        | 21.84                 | 21.69                 | 22.09                 |                              | 0        |
|                                      | 8       | 0         | 20.86                 | 20.87                 | 21.16                 | 0-1                          | 1        |
|                                      | 8       | 4         | 20.85                 | 20.86                 | 21.14                 |                              | 1        |
|                                      | 8       | 7         | 20.85                 | 20.86                 | 21.14                 |                              | 1        |
| 16QAM                                | 15      | 0         | 20.92                 | 20.84                 | 21.13                 | 0-1                          | 1        |
|                                      | 1       | 0         | 20.89                 | 21.02                 | 20.85                 |                              | 1        |
|                                      | 1       | 7         | 20.89                 | 21.13                 | 20.96                 |                              | 1        |
|                                      | 1       | 14        | 20.90                 | 21.05                 | 21.03                 | 0-2                          | 1        |
|                                      | 8       | 0         | 19.71                 | 19.71                 | 20.14                 |                              | 2        |
|                                      | 8       | 4         | 19.75                 | 19.72                 | 20.12                 |                              | 2        |
|                                      | 8       | 7         | 19.71                 | 19.71                 | 20.12                 |                              | 2        |
|                                      | 15      | 0         | 19.82                 | 19.76                 | 20.10                 |                              | 2        |

**Table 9-45**  
**LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth**

| LTE Band 25 (PCS)<br>1.4 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|----------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                             | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                        |         |           | 26047<br>(1850.7 MHz) | 26365<br>(1882.5 MHz) | 26683<br>(1914.3 MHz) |                              |          |
|                                        |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                   | 1       | 0         | 21.83                 | 21.84                 | 22.12                 | 0                            | 0        |
|                                        | 1       | 2         | 21.76                 | 21.80                 | 22.05                 |                              | 0        |
|                                        | 1       | 5         | 21.81                 | 21.82                 | 22.14                 |                              | 0        |
|                                        | 3       | 0         | 21.81                 | 21.79                 | 22.15                 |                              | 0        |
|                                        | 3       | 2         | 21.83                 | 21.78                 | 22.16                 |                              | 0        |
|                                        | 3       | 3         | 21.81                 | 21.80                 | 22.19                 |                              | 0        |
| 6                                      | 0       | 20.87     | 20.82                 | 21.16                 | 0-1                   | 1                            |          |
| 16QAM                                  | 1       | 0         | 20.75                 | 20.99                 | 21.18                 | 0-1                          | 1        |
|                                        | 1       | 2         | 20.70                 | 20.92                 | 21.20                 |                              | 1        |
|                                        | 1       | 5         | 20.71                 | 20.79                 | 21.15                 |                              | 1        |
|                                        | 3       | 0         | 20.69                 | 20.66                 | 21.06                 |                              | 1        |
|                                        | 3       | 2         | 20.73                 | 20.75                 | 21.05                 |                              | 1        |
|                                        | 3       | 3         | 20.67                 | 20.69                 | 21.10                 |                              | 1        |
| 6                                      | 0       | 19.68     | 19.65                 | 20.10                 | 0-2                   | 2                            |          |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 46 of 95                          |



**Table 9-46**  
**LTE Band 25 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth**

| LTE Band 25 (PCS)<br>20 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|---------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 26140<br>(1860.0 MHz) | 26365<br>(1882.5 MHz) | 26590<br>(1905.0 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                  | 1       | 0         | 19.47                 | 19.33                 | 19.73                 | 0                            | 0        |
|                                       | 1       | 50        | 19.40                 | 19.31                 | 19.63                 |                              | 0        |
|                                       | 1       | 99        | 19.36                 | 19.28                 | 19.55                 |                              | 0        |
|                                       | 50      | 0         | 19.33                 | 19.24                 | 19.65                 | 0-1                          | 0        |
|                                       | 50      | 25        | 19.29                 | 19.22                 | 19.62                 |                              | 0        |
|                                       | 50      | 50        | 19.25                 | 19.22                 | 19.58                 |                              | 0        |
|                                       | 100     | 0         | 19.26                 | 19.21                 | 19.61                 |                              | 0        |
| 16QAM                                 | 1       | 0         | 19.42                 | 19.27                 | 19.72                 | 0-1                          | 0        |
|                                       | 1       | 50        | 19.35                 | 19.21                 | 19.62                 |                              | 0        |
|                                       | 1       | 99        | 19.33                 | 19.31                 | 19.58                 |                              | 0        |
|                                       | 50      | 0         | 19.34                 | 19.18                 | 19.65                 | 0-2                          | 0        |
|                                       | 50      | 25        | 19.30                 | 19.20                 | 19.60                 |                              | 0        |
|                                       | 50      | 50        | 19.29                 | 19.21                 | 19.57                 |                              | 0        |
|                                       | 100     | 0         | 19.28                 | 19.18                 | 19.61                 |                              | 0        |

**Table 9-47**  
**LTE Band 25 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth**

| LTE Band 25 (PCS)<br>15 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|---------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 26115<br>(1857.5 MHz) | 26365<br>(1882.5 MHz) | 26615<br>(1907.5 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                  | 1       | 0         | 19.32                 | 19.15                 | 19.55                 | 0                            | 0        |
|                                       | 1       | 36        | 19.21                 | 19.12                 | 19.46                 |                              | 0        |
|                                       | 1       | 74        | 19.15                 | 19.22                 | 19.41                 |                              | 0        |
|                                       | 36      | 0         | 19.24                 | 19.07                 | 19.47                 | 0-1                          | 0        |
|                                       | 36      | 18        | 19.19                 | 19.08                 | 19.46                 |                              | 0        |
|                                       | 36      | 37        | 19.17                 | 19.08                 | 19.42                 |                              | 0        |
|                                       | 75      | 0         | 19.20                 | 19.08                 | 19.46                 |                              | 0        |
| 16QAM                                 | 1       | 0         | 19.18                 | 19.01                 | 19.21                 | 0-1                          | 0        |
|                                       | 1       | 36        | 19.00                 | 19.00                 | 19.16                 |                              | 0        |
|                                       | 1       | 74        | 19.01                 | 19.08                 | 19.30                 |                              | 0        |
|                                       | 36      | 0         | 19.23                 | 18.99                 | 19.49                 | 0-2                          | 0        |
|                                       | 36      | 18        | 19.19                 | 19.04                 | 19.47                 |                              | 0        |
|                                       | 36      | 37        | 19.18                 | 19.09                 | 19.45                 |                              | 0        |
|                                       | 75      | 0         | 19.20                 | 19.06                 | 19.44                 |                              | 0        |

**Table 9-48**  
**LTE Band 25 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth**

| LTE Band 25 (PCS)<br>10 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|---------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                            | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                       |         |           | 26090<br>(1855.0 MHz) | 26365<br>(1882.5 MHz) | 26640<br>(1910.0 MHz) |                              |          |
|                                       |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                  | 1       | 0         | 19.25                 | 19.06                 | 19.51                 | 0                            | 0        |
|                                       | 1       | 25        | 19.17                 | 19.06                 | 19.49                 |                              | 0        |
|                                       | 1       | 49        | 19.15                 | 19.08                 | 19.45                 |                              | 0        |
|                                       | 25      | 0         | 19.23                 | 19.06                 | 19.51                 | 0-1                          | 0        |
|                                       | 25      | 12        | 19.22                 | 19.07                 | 19.47                 |                              | 0        |
|                                       | 25      | 25        | 19.19                 | 19.08                 | 19.46                 |                              | 0        |
|                                       | 50      | 0         | 19.23                 | 19.01                 | 19.50                 |                              | 0        |
| 16QAM                                 | 1       | 0         | 19.12                 | 19.00                 | 19.19                 | 0-1                          | 0        |
|                                       | 1       | 25        | 19.02                 | 19.04                 | 19.26                 |                              | 0        |
|                                       | 1       | 49        | 19.28                 | 19.02                 | 19.24                 |                              | 0        |
|                                       | 25      | 0         | 19.22                 | 19.02                 | 19.51                 | 0-2                          | 0        |
|                                       | 25      | 12        | 19.20                 | 19.05                 | 19.52                 |                              | 0        |
|                                       | 25      | 25        | 19.21                 | 19.07                 | 19.50                 |                              | 0        |
|                                       | 50      | 0         | 19.26                 | 19.08                 | 19.53                 |                              | 0        |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 47 of 95                          |

**Table 9-49**  
**LTE Band 25 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth**

| LTE Band 25 (PCS)<br>5 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 26065<br>(1852.5 MHz) | 26365<br>(1882.5 MHz) | 26665<br>(1912.5 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 19.16                 | 19.02                 | 19.43                 | 0                            | 0        |
|                                      | 1       | 12        | 19.19                 | 19.08                 | 19.38                 |                              | 0        |
|                                      | 1       | 24        | 19.16                 | 19.02                 | 19.41                 |                              | 0        |
|                                      | 12      | 0         | 19.24                 | 19.04                 | 19.46                 | 0-1                          | 0        |
|                                      | 12      | 6         | 19.21                 | 19.06                 | 19.48                 |                              | 0        |
|                                      | 12      | 13        | 19.20                 | 19.05                 | 19.46                 |                              | 0        |
| 16QAM                                | 25      | 0         | 19.22                 | 19.06                 | 19.50                 | 0-1                          | 0        |
|                                      | 1       | 0         | 19.13                 | 19.13                 | 19.39                 |                              | 0        |
|                                      | 1       | 12        | 19.23                 | 19.03                 | 19.24                 |                              | 0        |
|                                      | 1       | 24        | 19.02                 | 19.00                 | 19.45                 | 0-2                          | 0        |
|                                      | 12      | 0         | 19.26                 | 19.01                 | 19.53                 |                              | 0        |
|                                      | 12      | 6         | 19.25                 | 19.19                 | 19.55                 |                              | 0        |
|                                      | 12      | 13        | 19.22                 | 19.24                 | 19.54                 |                              | 0        |
|                                      | 25      | 0         | 19.21                 | 19.16                 | 19.50                 |                              | 0        |

**Table 9-50**  
**LTE Band 25 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth**

| LTE Band 25 (PCS)<br>3 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|--------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                           | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                      |         |           | 26055<br>(1851.5 MHz) | 26365<br>(1882.5 MHz) | 26675<br>(1913.5 MHz) |                              |          |
|                                      |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                 | 1       | 0         | 19.43                 | 19.08                 | 19.51                 | 0                            | 0        |
|                                      | 1       | 7         | 19.37                 | 19.09                 | 19.48                 |                              | 0        |
|                                      | 1       | 14        | 19.38                 | 19.07                 | 19.48                 |                              | 0        |
|                                      | 8       | 0         | 19.42                 | 19.26                 | 19.61                 | 0-1                          | 0        |
|                                      | 8       | 4         | 19.38                 | 19.23                 | 19.58                 |                              | 0        |
|                                      | 8       | 7         | 19.39                 | 19.18                 | 19.59                 |                              | 0        |
|                                      | 15      | 0         | 19.42                 | 19.19                 | 19.62                 |                              | 0        |
| 16QAM                                | 1       | 0         | 19.72                 | 19.24                 | 19.48                 | 0-1                          | 0        |
|                                      | 1       | 7         | 19.62                 | 19.26                 | 19.51                 |                              | 0        |
|                                      | 1       | 14        | 19.62                 | 19.21                 | 19.47                 |                              | 0        |
|                                      | 8       | 0         | 19.36                 | 19.21                 | 19.57                 | 0-2                          | 0        |
|                                      | 8       | 4         | 19.38                 | 19.19                 | 19.53                 |                              | 0        |
|                                      | 8       | 7         | 19.35                 | 19.17                 | 19.52                 |                              | 0        |
|                                      | 15      | 0         | 19.45                 | 19.20                 | 19.62                 |                              | 0        |

**Table 9-51**  
**LTE Band 25 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth**

| LTE Band 25 (PCS)<br>1.4 MHz Bandwidth |         |           |                       |                       |                       |                              |          |
|----------------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                             | RB Size | RB Offset | Low Channel           | Mid Channel           | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                        |         |           | 26047<br>(1850.7 MHz) | 26365<br>(1882.5 MHz) | 26683<br>(1914.3 MHz) |                              |          |
|                                        |         |           | Conducted Power [dBm] |                       |                       |                              |          |
| QPSK                                   | 1       | 0         | 19.35                 | 19.20                 | 19.52                 | 0                            | 0        |
|                                        | 1       | 2         | 19.37                 | 19.19                 | 19.53                 |                              | 0        |
|                                        | 1       | 5         | 19.36                 | 19.27                 | 19.56                 |                              | 0        |
|                                        | 3       | 0         | 19.38                 | 19.12                 | 19.51                 |                              | 0        |
|                                        | 3       | 2         | 19.39                 | 19.09                 | 19.54                 |                              | 0        |
|                                        | 3       | 3         | 19.38                 | 19.10                 | 19.54                 |                              | 0        |
|                                        | 6       | 0         | 19.33                 | 19.19                 | 19.60                 |                              | 0-1      |
| 16QAM                                  | 1       | 0         | 19.39                 | 18.99                 | 19.36                 | 0-1                          | 0        |
|                                        | 1       | 2         | 19.35                 | 18.98                 | 19.37                 |                              | 0        |
|                                        | 1       | 5         | 19.38                 | 19.01                 | 19.34                 |                              | 0        |
|                                        | 3       | 0         | 19.29                 | 18.98                 | 19.32                 |                              | 0        |
|                                        | 3       | 2         | 19.33                 | 18.98                 | 19.31                 |                              | 0        |
|                                        | 3       | 3         | 19.28                 | 19.00                 | 19.30                 |                              | 0        |
|                                        | 6       | 0         | 19.32                 | 19.28                 | 19.48                 |                              | 0-2      |

|                                             |                                                                                                                                                                                                        |                                      |  |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|--|----------------------------------------|
| FCC ID: A3LSMN935F                          |  <b>SAR EVALUATION REPORT</b>  |                                      |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  |  | Page 48 of 95                          |

## 9.3.8

## LTE Band 41

**Table 9-52**  
**LTE Band 41 Conducted Powers - 20 MHz Bandwidth**

| LTE Band 41<br>20 MHz Bandwidth |         |           |                       |                       |                       |                       |                       |                              |          |
|---------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                      | RB Size | RB Offset | Low Channel           | Low-Mid Channel       | Mid Channel           | Mid-High Channel      | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                 |         |           | 39750<br>(2506.0 MHz) | 40185<br>(2549.5 MHz) | 40620<br>(2593.0 MHz) | 41055<br>(2636.5 MHz) | 41490<br>(2680.0 MHz) |                              |          |
|                                 |         |           | Conducted Power [dBm] |                       |                       |                       |                       |                              |          |
| QPSK                            | 1       | 0         | 22.86                 | 23.43                 | 22.50                 | 22.39                 | 22.90                 | 0                            | 0        |
|                                 | 1       | 50        | 22.77                 | 23.40                 | 22.45                 | 22.38                 | 22.70                 |                              | 0        |
|                                 | 1       | 99        | 22.72                 | 23.36                 | 22.44                 | 22.39                 | 22.66                 |                              | 0        |
|                                 | 50      | 0         | 21.71                 | 22.33                 | 21.54                 | 21.32                 | 21.65                 | 0-1                          | 1        |
|                                 | 50      | 25        | 21.66                 | 22.30                 | 21.49                 | 21.30                 | 21.64                 |                              | 1        |
|                                 | 50      | 50        | 21.63                 | 22.28                 | 21.47                 | 21.29                 | 21.61                 |                              | 1        |
|                                 | 100     | 0         | 21.67                 | 22.30                 | 21.48                 | 21.29                 | 21.63                 |                              | 1        |
| 16QAM                           | 1       | 0         | 21.84                 | 22.45                 | 21.47                 | 21.13                 | 21.32                 | 0-1                          | 1        |
|                                 | 1       | 50        | 21.80                 | 22.40                 | 21.44                 | 21.16                 | 21.30                 |                              | 1        |
|                                 | 1       | 99        | 21.76                 | 22.38                 | 21.43                 | 21.18                 | 21.28                 |                              | 1        |
|                                 | 50      | 0         | 20.78                 | 21.39                 | 20.57                 | 20.41                 | 20.68                 | 0-2                          | 2        |
|                                 | 50      | 25        | 20.77                 | 21.34                 | 20.50                 | 20.33                 | 20.66                 |                              | 2        |
|                                 | 50      | 50        | 20.74                 | 21.33                 | 20.45                 | 20.34                 | 20.67                 |                              | 2        |
|                                 | 100     | 0         | 20.72                 | 21.34                 | 20.51                 | 20.28                 | 20.67                 |                              | 2        |

**Table 9-53**  
**LTE Band 41 Conducted Powers - 15 MHz Bandwidth**

| LTE Band 41<br>15 MHz Bandwidth |         |           |                       |                       |                       |                       |                       |                              |          |
|---------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                      | RB Size | RB Offset | Low Channel           | Low-Mid Channel       | Mid Channel           | Mid-High Channel      | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                 |         |           | 39750<br>(2506.0 MHz) | 40185<br>(2549.5 MHz) | 40620<br>(2593.0 MHz) | 41055<br>(2636.5 MHz) | 41490<br>(2680.0 MHz) |                              |          |
|                                 |         |           | Conducted Power [dBm] |                       |                       |                       |                       |                              |          |
| QPSK                            | 1       | 0         | 23.31                 | 22.87                 | 22.90                 | 22.86                 | 23.10                 | 0                            | 0        |
|                                 | 1       | 36        | 23.22                 | 22.82                 | 22.89                 | 22.83                 | 23.08                 |                              | 0        |
|                                 | 1       | 74        | 23.10                 | 22.77                 | 22.82                 | 22.80                 | 23.00                 |                              | 0        |
|                                 | 36      | 0         | 22.27                 | 21.87                 | 22.04                 | 21.91                 | 22.22                 | 0-1                          | 1        |
|                                 | 36      | 18        | 22.24                 | 21.88                 | 22.00                 | 21.89                 | 22.20                 |                              | 1        |
|                                 | 36      | 37        | 22.21                 | 21.90                 | 21.99                 | 21.87                 | 22.16                 |                              | 1        |
|                                 | 75      | 0         | 22.24                 | 21.89                 | 22.04                 | 21.88                 | 22.19                 |                              | 1        |
| 16QAM                           | 1       | 0         | 22.29                 | 22.50                 | 21.85                 | 21.89                 | 21.92                 | 0-1                          | 1        |
|                                 | 1       | 36        | 22.19                 | 22.49                 | 21.83                 | 21.90                 | 21.89                 |                              | 1        |
|                                 | 1       | 74        | 22.05                 | 22.47                 | 21.74                 | 21.85                 | 21.88                 |                              | 1        |
|                                 | 36      | 0         | 21.24                 | 21.50                 | 21.03                 | 20.86                 | 21.30                 | 0-2                          | 2        |
|                                 | 36      | 18        | 21.20                 | 21.49                 | 20.99                 | 20.85                 | 21.27                 |                              | 2        |
|                                 | 36      | 37        | 21.18                 | 21.45                 | 21.00                 | 20.87                 | 21.26                 |                              | 2        |
|                                 | 75      | 0         | 21.21                 | 21.50                 | 21.02                 | 20.92                 | 21.23                 | 2                            |          |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 49 of 95                   |

**Table 9-54**  
**LTE Band 41 Conducted Powers - 10 MHz Bandwidth**

| LTE Band 41<br>10 MHz Bandwidth |         |           |                       |                       |                       |                       |                       |                              |          |
|---------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                      | RB Size | RB Offset | Low Channel           | Low-Mid Channel       | Mid Channel           | Mid-High Channel      | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                 |         |           | 39750<br>(2506.0 MHz) | 40185<br>(2549.5 MHz) | 40620<br>(2593.0 MHz) | 41055<br>(2636.5 MHz) | 41490<br>(2680.0 MHz) |                              |          |
|                                 |         |           | Conducted Power [dBm] |                       |                       |                       |                       |                              |          |
| QPSK                            | 1       | 0         | 23.35                 | 23.03                 | 23.01                 | 22.82                 | 23.24                 | 0                            | 0        |
|                                 | 1       | 25        | 23.30                 | 23.01                 | 22.95                 | 22.81                 | 23.26                 |                              | 0        |
|                                 | 1       | 49        | 23.24                 | 23.00                 | 22.89                 | 22.79                 | 23.20                 |                              | 0        |
|                                 | 25      | 0         | 22.21                 | 22.07                 | 22.00                 | 21.77                 | 22.16                 | 0-1                          | 1        |
|                                 | 25      | 12        | 22.19                 | 22.00                 | 21.99                 | 21.85                 | 22.17                 |                              | 1        |
|                                 | 25      | 25        | 22.18                 | 22.03                 | 22.00                 | 21.80                 | 22.15                 |                              | 1        |
|                                 | 50      | 0         | 22.17                 | 22.02                 | 21.97                 | 21.78                 | 22.12                 |                              | 1        |
| 16QAM                           | 1       | 0         | 22.01                 | 21.98                 | 21.95                 | 21.81                 | 21.99                 | 0-1                          | 1        |
|                                 | 1       | 25        | 21.98                 | 21.89                 | 21.92                 | 21.79                 | 21.88                 |                              | 1        |
|                                 | 1       | 49        | 21.90                 | 21.87                 | 21.90                 | 21.84                 | 21.86                 |                              | 1        |
|                                 | 25      | 0         | 21.23                 | 21.16                 | 21.09                 | 20.80                 | 21.20                 | 0-2                          | 2        |
|                                 | 25      | 12        | 21.21                 | 21.10                 | 21.08                 | 20.81                 | 21.21                 |                              | 2        |
|                                 | 25      | 25        | 21.18                 | 21.11                 | 21.06                 | 20.79                 | 21.19                 |                              | 2        |
|                                 | 50      | 0         | 21.20                 | 21.02                 | 21.05                 | 20.84                 | 21.18                 |                              | 2        |

**Table 9-55**  
**LTE Band 41 Conducted Powers - 5 MHz Bandwidth**

| LTE Band 41<br>5 MHz Bandwidth |         |           |                       |                       |                       |                       |                       |                              |          |
|--------------------------------|---------|-----------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|------------------------------|----------|
| Modulation                     | RB Size | RB Offset | Low Channel           | Low-Mid Channel       | Mid Channel           | Mid-High Channel      | High Channel          | MPR Allowed per<br>3GPP [dB] | MPR [dB] |
|                                |         |           | 39750<br>(2506.0 MHz) | 40185<br>(2549.5 MHz) | 40620<br>(2593.0 MHz) | 41055<br>(2636.5 MHz) | 41490<br>(2680.0 MHz) |                              |          |
|                                |         |           | Conducted Power [dBm] |                       |                       |                       |                       |                              |          |
| QPSK                           | 1       | 0         | 23.08                 | 22.97                 | 22.98                 | 22.64                 | 23.10                 | 0                            | 0        |
|                                | 1       | 12        | 23.00                 | 22.93                 | 22.96                 | 22.65                 | 23.04                 |                              | 0        |
|                                | 1       | 24        | 23.05                 | 22.95                 | 22.97                 | 22.66                 | 23.09                 |                              | 0        |
|                                | 12      | 0         | 22.22                 | 22.07                 | 21.98                 | 21.81                 | 22.15                 | 0-1                          | 1        |
|                                | 12      | 6         | 22.20                 | 22.04                 | 21.95                 | 21.83                 | 22.14                 |                              | 1        |
|                                | 12      | 13        | 22.21                 | 22.07                 | 22.00                 | 21.82                 | 22.15                 |                              | 1        |
|                                | 25      | 0         | 22.19                 | 22.05                 | 21.98                 | 21.83                 | 22.15                 |                              | 1        |
| 16QAM                          | 1       | 0         | 22.07                 | 21.83                 | 21.86                 | 21.67                 | 21.92                 | 0-1                          | 1        |
|                                | 1       | 12        | 22.03                 | 21.88                 | 21.84                 | 21.70                 | 21.89                 |                              | 1        |
|                                | 1       | 24        | 22.06                 | 21.85                 | 21.88                 | 21.66                 | 21.95                 |                              | 1        |
|                                | 12      | 0         | 21.21                 | 21.04                 | 21.02                 | 20.85                 | 21.14                 | 0-2                          | 2        |
|                                | 12      | 6         | 21.16                 | 21.02                 | 20.99                 | 20.82                 | 21.12                 |                              | 2        |
|                                | 12      | 13        | 21.15                 | 21.05                 | 21.01                 | 20.84                 | 21.16                 |                              | 2        |
|                                | 25      | 0         | 21.19                 | 21.03                 | 21.00                 | 20.86                 | 21.15                 |                              | 2        |

|                                      |                                                                                                                                                                                                        |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset   |
| Page 50 of 95                        |                                                                                                                                                                                                        |                                 |

## 9.4 WLAN Conducted Powers

**Table 9-56**  
**2.4 GHz WLAN Maximum Average RF Power – Antenna 1**

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |         |
|------------|---------|------------------------------|---------|
|            |         | IEEE Transmission Mode       |         |
|            |         | 802.11b                      | 802.11g |
| 2412       | 1       | 18.45                        | 16.27   |
| 2437       | 6       | 18.55                        | 16.09   |
| 2462       | 11      | 18.44                        | 16.01   |
| 2467       | 12      | 17.08                        | 14.42   |
| 2472       | 13      | 11.36                        | 8.33    |

**Table 9-57**  
**2.4 GHz WLAN Maximum Average RF Power – Antenna 2**

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |         |
|------------|---------|------------------------------|---------|
|            |         | IEEE Transmission Mode       |         |
|            |         | 802.11b                      | 802.11g |
| 2412       | 1       | 18.33                        | 14.98   |
| 2437       | 6       | 19.15                        | 16.39   |
| 2462       | 11      | 19.21                        | 16.26   |
| 2467       | 12      | 16.95                        | 13.55   |
| 2472       | 13      | 10.76                        | 7.78    |

**Table 9-58**  
**2.4 GHz WLAN Maximum Average RF Power – MIMO**

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |
|------------|---------|------------------------------|
|            |         | 802.11n MIMO                 |
| 2412       | 1       | 16.77                        |
| 2437       | 6       | 16.83                        |
| 2462       | 11      | 16.73                        |
| 2467       | 12      | 15.31                        |
| 2472       | 13      | 9.23                         |

**Table 9-59**  
**2.4 GHz WLAN Reduced Average RF Power – Antenna 1**

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |         |         |
|------------|---------|------------------------------|---------|---------|
|            |         | IEEE Transmission Mode       |         |         |
|            |         | 802.11b                      | 802.11g | 802.11n |
| 2412       | 1       | 14.98                        | 14.70   | 15.20   |
| 2437       | 6       | 14.96                        | 14.53   | 15.33   |
| 2462       | 11      | 14.72                        | 15.16   | 15.06   |

**Table 9-60**  
**2.4 GHz WLAN Reduced Average RF Power – Antenna 2**

| Freq [MHz] | Channel | 2.4GHz Conducted Power [dBm] |         |         |
|------------|---------|------------------------------|---------|---------|
|            |         | IEEE Transmission Mode       |         |         |
|            |         | 802.11b                      | 802.11g | 802.11n |
| 2412       | 1       | 15.22                        | 14.89   | 14.62   |
| 2437       | 6       | 14.90                        | 14.75   | 15.19   |
| 2462       | 11      | 14.76                        | 14.53   | 15.22   |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 51 of 95                   |

**Table 9-61**  
**5 GHz WLAN Maximum Average RF Power – Antenna 1**

| Freq [MHz] | Channel | 5GHz (20MHz) Conducted Power [dBm] |         |          |
|------------|---------|------------------------------------|---------|----------|
|            |         | IEEE Transmission Mode             |         |          |
|            |         | 802.11a                            | 802.11n | 802.11ac |
| 5180       | 36      | 14.58                              | 13.51   | 13.42    |
| 5200       | 40      | 17.07                              | 13.55   | 13.50    |
| 5220       | 44      | 17.05                              | 13.52   | 13.55    |
| 5240       | 48      | 17.17                              | 13.55   | 13.64    |
| 5260       | 52      | 16.90                              | 13.50   | 13.54    |
| 5280       | 56      | 16.96                              | 13.66   | 13.64    |
| 5300       | 60      | 16.87                              | 13.70   | 13.63    |
| 5320       | 64      | 16.91                              | 13.64   | 13.74    |
| 5500       | 100     | 17.07                              | 13.42   | 14.46    |
| 5600       | 120     | 16.76                              | 14.28   | 14.27    |
| 5620       | 124     | 17.11                              | 14.07   | 14.05    |
| 5720       | 144     | 17.30                              | 13.87   | 13.74    |
| 5745       | 149     | 17.12                              | 13.94   | 14.04    |
| 5785       | 157     | 16.93                              | 13.83   | 13.71    |
| 5825       | 165     | 17.13                              | 13.73   | 13.71    |

**Table 9-62**  
**5 GHz WLAN Maximum Average RF Power – Antenna 2**

| Freq [MHz] | Channel | 5GHz (20MHz) Conducted Power [dBm] |         |          |
|------------|---------|------------------------------------|---------|----------|
|            |         | IEEE Transmission Mode             |         |          |
|            |         | 802.11a                            | 802.11n | 802.11ac |
| 5180       | 36      | 16.34                              | 14.49   | 14.44    |
| 5200       | 40      | 17.39                              | 14.46   | 14.45    |
| 5220       | 44      | 17.42                              | 14.49   | 14.43    |
| 5240       | 48      | 17.43                              | 14.45   | 14.49    |
| 5260       | 52      | 17.27                              | 14.14   | 14.32    |
| 5280       | 56      | 17.19                              | 14.02   | 14.31    |
| 5300       | 60      | 17.26                              | 13.99   | 14.08    |
| 5320       | 64      | 17.25                              | 13.88   | 14.22    |
| 5500       | 100     | 17.20                              | 13.64   | 13.94    |
| 5600       | 120     | 17.00                              | 14.22   | 13.51    |
| 5620       | 124     | 17.12                              | 14.30   | 14.26    |
| 5720       | 144     | 16.82                              | 14.15   | 14.13    |
| 5745       | 149     | 16.66                              | 13.71   | 13.54    |
| 5785       | 157     | 16.67                              | 13.54   | 13.49    |
| 5825       | 165     | 16.75                              | 13.55   | 13.55    |

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
| Page 52 of 95                               |                                                                                                                                                                                                        |                                        |

**Table 9-63**  
**5 GHz WLAN Maximum Average RF Power – 802.11a/n/ac MIMO**

| Freq [MHz] | Channel | Detector | 5GHz (20MHz) Conducted Power [dBm] |         |          |
|------------|---------|----------|------------------------------------|---------|----------|
|            |         |          | 802.11a                            | 802.11n | 802.11ac |
| 5180       | 36      | AVG      | 16.85                              | 17.04   | 16.97    |
| 5200       | 40      | AVG      | 16.92                              | 17.04   | 17.01    |
| 5220       | 44      | AVG      | 16.87                              | 17.04   | 17.02    |
| 5240       | 48      | AVG      | 16.66                              | 17.03   | 17.10    |
| 5260       | 52      | AVG      | 16.47                              | 16.84   | 16.96    |
| 5280       | 56      | AVG      | 17.11                              | 16.85   | 17.00    |
| 5300       | 60      | AVG      | 17.46                              | 16.86   | 16.87    |
| 5320       | 64      | AVG      | 17.30                              | 16.77   | 17.00    |
| 5500       | 100     | AVG      | 16.30                              | 16.54   | 17.22    |
| 5600       | 120     | AVG      | 16.31                              | 17.26   | 16.92    |
| 5620       | 124     | AVG      | 16.23                              | 17.20   | 17.17    |
| 5720       | 144     | AVG      | 16.67                              | 17.02   | 16.95    |
| 5745       | 149     | AVG      | 16.45                              | 16.84   | 16.81    |
| 5785       | 157     | AVG      | 16.41                              | 16.70   | 16.61    |
| 5825       | 165     | AVG      | 17.11                              | 16.65   | 16.64    |

1. This device supports MIMO operations for IEEE 802.11a/g using Cyclic Delay Diversity (CDD) only. Antenna 1 and Antenna 2 will never transmit at the same time while operating in CDD mode (switched transmission only). Since IEEE 802.11n/ac MIMO modes additionally support Spatial Diversity Multiplexing, only IEEE 802.11n/ac modes were considered for MIMO SAR.

**Table 9-64**  
**5 GHz WLAN Reduced Average RF Power – Antenna 1**

| 5GHz (80MHz) Conducted Power [dBm] |         |                        |
|------------------------------------|---------|------------------------|
| Freq [MHz]                         | Channel | IEEE Transmission Mode |
|                                    |         | 802.11ac               |
| 5210                               | 42      | 11.09                  |
| 5290                               | 58      | 13.14                  |
| 5530                               | 106     | 12.61                  |
| 5610                               | 122     | 12.98                  |
| 5690                               | 138     | 13.27                  |
| 5775                               | 155     | 13.25                  |

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
| Page 53 of 95                               |                                                                                                                                                                                                        |                                        |

**Table 9-65**  
**5 GHz WLAN Reduced Average RF Power – Antenna 2**

| 5GHz (80MHz) Conducted Power [dBm] |         |                        |
|------------------------------------|---------|------------------------|
| Freq [MHz]                         | Channel | IEEE Transmission Mode |
|                                    |         | 802.11ac               |
| 5210                               | 42      | 12.72                  |
| 5290                               | 58      | <b>13.26</b>           |
| 5530                               | 106     | 12.65                  |
| 5610                               | 122     | <b>13.50</b>           |
| 5690                               | 138     | 13.40                  |
| 5775                               | 155     | <b>12.87</b>           |

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




**Figure 9-3**  
**Power Measurement Setup for Bandwidths < 50 MHz**




**Figure 9-4**  
**Power Measurement Setup for Bandwidths > 50 MHz**

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
| Page 54 of 95                               |                                                                                                                                                                                                        |                                        |



# 10 SYSTEM VERIFICATION

## 10.1 Tissue Verification

**Table 10-1**  
**Measured Head Tissue Properties**

| Calibrated for Tests Performed on: | Tissue Type | Tissue Temp During Calibration (°C) | Measured Frequency (MHz) | Measured Conductivity, $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon$ | TARGET Conductivity, $\sigma$ (S/m) | TARGET Dielectric Constant, $\epsilon$ | % dev $\sigma$ | % dev $\epsilon$ |
|------------------------------------|-------------|-------------------------------------|--------------------------|---------------------------------------|------------------------------------------|-------------------------------------|----------------------------------------|----------------|------------------|
| 5/31/2016                          | 750H        | 21.9                                | 700                      | 0.851                                 | 41.995                                   | 0.889                               | 42.201                                 | -4.27%         | -0.49%           |
|                                    |             |                                     | 710                      | 0.859                                 | 41.886                                   | 0.890                               | 42.149                                 | -3.48%         | -0.62%           |
|                                    |             |                                     | 740                      | 0.884                                 | 41.506                                   | 0.893                               | 41.994                                 | -1.01%         | -1.16%           |
|                                    |             |                                     | 755                      | 0.898                                 | 41.278                                   | 0.894                               | 41.916                                 | 0.45%          | -1.52%           |
|                                    |             |                                     | 770                      | 0.912                                 | 41.057                                   | 0.895                               | 41.838                                 | 1.90%          | -1.87%           |
|                                    |             |                                     | 785                      | 0.925                                 | 40.855                                   | 0.896                               | 41.760                                 | 3.24%          | -2.17%           |
| 6/1/2016                           | 835H        | 22.8                                | 820                      | 0.886                                 | 41.285                                   | 0.899                               | 41.578                                 | -1.45%         | -0.70%           |
|                                    |             |                                     | 835                      | 0.900                                 | 41.083                                   | 0.900                               | 41.500                                 | 0.00%          | -1.00%           |
|                                    |             |                                     | 850                      | 0.915                                 | 40.862                                   | 0.916                               | 41.500                                 | -0.11%         | -1.54%           |
| 3/27/2017                          | 835H        | 20.6                                | 820                      | 0.870                                 | 40.343                                   | 0.899                               | 41.578                                 | -3.23%         | -2.97%           |
|                                    |             |                                     | 835                      | 0.884                                 | 40.108                                   | 0.900                               | 41.500                                 | -1.78%         | -3.35%           |
|                                    |             |                                     | 850                      | 0.898                                 | 39.965                                   | 0.916                               | 41.500                                 | -1.97%         | -3.70%           |
| 6/1/2016                           | 1750H       | 22.2                                | 1710                     | 1.327                                 | 39.409                                   | 1.348                               | 40.142                                 | -1.56%         | -1.83%           |
|                                    |             |                                     | 1750                     | 1.366                                 | 39.201                                   | 1.371                               | 40.079                                 | -0.36%         | -2.19%           |
|                                    |             |                                     | 1790                     | 1.402                                 | 39.078                                   | 1.394                               | 40.016                                 | 0.57%          | -2.34%           |
| 6/3/2016                           | 1900H       | 22.2                                | 1850                     | 1.368                                 | 39.219                                   | 1.400                               | 40.000                                 | -2.29%         | -1.95%           |
|                                    |             |                                     | 1880                     | 1.398                                 | 39.087                                   | 1.400                               | 40.000                                 | -0.14%         | -2.28%           |
|                                    |             |                                     | 1910                     | 1.435                                 | 39.002                                   | 1.400                               | 40.000                                 | 2.50%          | -2.49%           |
| 5/31/2016                          | 2450H-2600H | 24.6                                | 2400                     | 1.776                                 | 41.040                                   | 1.756                               | 39.289                                 | 1.14%          | 4.46%            |
|                                    |             |                                     | 2450                     | 1.829                                 | 40.801                                   | 1.800                               | 39.200                                 | 1.61%          | 4.08%            |
|                                    |             |                                     | 2500                     | 1.888                                 | 40.633                                   | 1.855                               | 39.136                                 | 1.78%          | 3.83%            |
|                                    |             |                                     | 2550                     | 1.946                                 | 40.452                                   | 1.909                               | 39.073                                 | 1.94%          | 3.53%            |
|                                    |             |                                     | 2600                     | 2.001                                 | 40.227                                   | 1.964                               | 39.009                                 | 1.88%          | 3.12%            |
|                                    |             |                                     | 2650                     | 2.064                                 | 40.046                                   | 2.018                               | 38.945                                 | 2.28%          | 2.83%            |
|                                    |             |                                     | 2700                     | 2.127                                 | 39.855                                   | 2.073                               | 38.882                                 | 2.60%          | 2.50%            |
| 06/06/2016                         | 5250H-5800H | 21.0                                | 5240                     | 4.623                                 | 35.114                                   | 4.696                               | 35.940                                 | -1.55%         | -2.30%           |
|                                    |             |                                     | 5260                     | 4.642                                 | 35.063                                   | 4.717                               | 35.917                                 | -1.59%         | -2.38%           |
|                                    |             |                                     | 5280                     | 4.662                                 | 35.027                                   | 4.737                               | 35.894                                 | -1.58%         | -2.42%           |
|                                    |             |                                     | 5300                     | 4.682                                 | 35.004                                   | 4.758                               | 35.871                                 | -1.60%         | -2.42%           |
|                                    |             |                                     | 5600                     | 4.989                                 | 34.615                                   | 5.065                               | 35.529                                 | -1.50%         | -2.57%           |
|                                    |             |                                     | 5680                     | 5.070                                 | 34.484                                   | 5.147                               | 35.437                                 | -1.50%         | -2.69%           |
|                                    |             |                                     | 5700                     | 5.097                                 | 34.485                                   | 5.168                               | 35.414                                 | -1.37%         | -2.62%           |
|                                    |             |                                     | 5745                     | 5.141                                 | 34.401                                   | 5.214                               | 35.363                                 | -1.40%         | -2.72%           |
|                                    |             |                                     | 5765                     | 5.162                                 | 34.365                                   | 5.234                               | 35.340                                 | -1.38%         | -2.76%           |
|                                    |             |                                     | 5785                     | 5.194                                 | 34.315                                   | 5.255                               | 35.317                                 | -1.16%         | -2.84%           |
| 04/06/2017                         | 5250H-5800H | 22.1                                | 5240                     | 4.582                                 | 35.522                                   | 4.696                               | 35.940                                 | -2.43%         | -1.16%           |
|                                    |             |                                     | 5260                     | 4.602                                 | 35.445                                   | 4.717                               | 35.917                                 | -2.44%         | -1.31%           |
|                                    |             |                                     | 5280                     | 4.615                                 | 35.374                                   | 4.737                               | 35.894                                 | -2.58%         | -1.45%           |
|                                    |             |                                     | 5300                     | 4.616                                 | 35.343                                   | 4.758                               | 35.871                                 | -2.98%         | -1.47%           |
|                                    |             |                                     | 5600                     | 4.915                                 | 34.990                                   | 5.065                               | 35.529                                 | -2.96%         | -1.52%           |
|                                    |             |                                     | 5620                     | 4.957                                 | 34.989                                   | 5.086                               | 35.506                                 | -2.54%         | -1.46%           |
|                                    |             |                                     | 5745                     | 5.061                                 | 34.842                                   | 5.214                               | 35.363                                 | -2.93%         | -1.47%           |
|                                    |             |                                     | 5765                     | 5.077                                 | 34.839                                   | 5.234                               | 35.340                                 | -3.00%         | -1.42%           |
|                                    |             |                                     | 5785                     | 5.102                                 | 34.740                                   | 5.255                               | 35.317                                 | -2.91%         | -1.63%           |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 55 of 95                   |

**Table 10-2**  
**Measured Body Tissue Properties**

| Calibrated for Tests Performed on: | Tissue Type | Tissue Temp During Calibration (°C) | Measured Frequency (MHz) | Measured Conductivity, $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon$ | TARGET Conductivity, $\sigma$ (S/m) | TARGET Dielectric Constant, $\epsilon$ | % dev $\sigma$ | % dev $\epsilon$ |
|------------------------------------|-------------|-------------------------------------|--------------------------|---------------------------------------|------------------------------------------|-------------------------------------|----------------------------------------|----------------|------------------|
| 6/6/2016                           | 750B        | 21.6                                | 700                      | 0.928                                 | 55.191                                   | 0.959                               | 55.726                                 | -3.23%         | -0.96%           |
|                                    |             |                                     | 710                      | 0.937                                 | 55.076                                   | 0.960                               | 55.687                                 | -2.40%         | -1.10%           |
|                                    |             |                                     | 740                      | 0.965                                 | 54.772                                   | 0.963                               | 55.570                                 | 0.21%          | -1.44%           |
|                                    |             |                                     | 755                      | 0.980                                 | 54.630                                   | 0.964                               | 55.512                                 | 1.66%          | -1.59%           |
|                                    |             |                                     | 770                      | 0.995                                 | 54.477                                   | 0.965                               | 55.453                                 | 3.11%          | -1.76%           |
|                                    |             |                                     | 785                      | 1.010                                 | 54.308                                   | 0.966                               | 55.395                                 | 4.55%          | -1.96%           |
| 4/3/2017                           | 750B        | 24.5                                | 740                      | 0.943                                 | 54.286                                   | 0.963                               | 55.570                                 | -2.08%         | -2.31%           |
|                                    |             |                                     | 755                      | 0.956                                 | 54.145                                   | 0.964                               | 55.512                                 | -0.83%         | -2.46%           |
|                                    |             |                                     | 770                      | 0.972                                 | 54.034                                   | 0.965                               | 55.453                                 | 0.73%          | -2.56%           |
|                                    |             |                                     | 785                      | 0.989                                 | 53.935                                   | 0.966                               | 55.395                                 | 2.38%          | -2.64%           |
| 6/2/2016                           | 835B        | 20.7                                | 820                      | 0.985                                 | 53.642                                   | 0.969                               | 55.258                                 | 1.65%          | -2.92%           |
|                                    |             |                                     | 835                      | 1.000                                 | 53.494                                   | 0.970                               | 55.200                                 | 3.09%          | -3.09%           |
|                                    |             |                                     | 850                      | 1.014                                 | 53.331                                   | 0.988                               | 55.154                                 | 2.63%          | -3.31%           |
| 4/3/2017                           | 835B        | 21.2                                | 820                      | 0.983                                 | 55.305                                   | 0.969                               | 55.258                                 | 1.44%          | 0.09%            |
|                                    |             |                                     | 835                      | 0.994                                 | 55.071                                   | 0.970                               | 55.200                                 | 2.47%          | -0.23%           |
|                                    |             |                                     | 850                      | 1.012                                 | 54.977                                   | 0.988                               | 55.154                                 | 2.43%          | -0.32%           |
| 4/10/2017                          | 835B        | 21.5                                | 820                      | 0.969                                 | 53.199                                   | 0.969                               | 55.258                                 | 0.00%          | -3.73%           |
|                                    |             |                                     | 835                      | 0.987                                 | 53.127                                   | 0.970                               | 55.200                                 | 1.75%          | -3.76%           |
|                                    |             |                                     | 850                      | 1.000                                 | 52.985                                   | 0.988                               | 55.154                                 | 1.21%          | -3.93%           |
| 6/1/2016                           | 1750B       | 21.2                                | 1710                     | 1.459                                 | 51.806                                   | 1.463                               | 53.537                                 | -0.27%         | -3.23%           |
|                                    |             |                                     | 1750                     | 1.502                                 | 51.718                                   | 1.488                               | 53.432                                 | 0.94%          | -3.21%           |
|                                    |             |                                     | 1790                     | 1.544                                 | 51.447                                   | 1.514                               | 53.326                                 | 1.98%          | -3.52%           |
| 6/2/2016                           | 1900B       | 22.8                                | 1850                     | 1.508                                 | 52.099                                   | 1.520                               | 53.300                                 | -0.79%         | -2.25%           |
|                                    |             |                                     | 1880                     | 1.543                                 | 52.019                                   | 1.520                               | 53.300                                 | 1.51%          | -2.40%           |
|                                    |             |                                     | 1910                     | 1.576                                 | 51.924                                   | 1.520                               | 53.300                                 | 3.68%          | -2.58%           |
| 5/31/2016                          | 2450B-2600B | 22.2                                | 2400                     | 1.946                                 | 51.651                                   | 1.902                               | 52.767                                 | 2.31%          | -2.11%           |
|                                    |             |                                     | 2450                     | 2.012                                 | 51.444                                   | 1.950                               | 52.700                                 | 3.18%          | -2.38%           |
|                                    |             |                                     | 2500                     | 2.082                                 | 51.240                                   | 2.021                               | 52.636                                 | 3.02%          | -2.65%           |
|                                    |             |                                     | 2550                     | 2.151                                 | 51.063                                   | 2.092                               | 52.573                                 | 2.82%          | -2.87%           |
|                                    |             |                                     | 2600                     | 2.216                                 | 50.857                                   | 2.163                               | 52.509                                 | 2.45%          | -3.15%           |
|                                    |             |                                     | 2650                     | 2.284                                 | 50.644                                   | 2.234                               | 52.445                                 | 2.24%          | -3.43%           |
|                                    |             |                                     | 2700                     | 2.353                                 | 50.452                                   | 2.305                               | 52.382                                 | 2.08%          | -3.68%           |
| 3/29/2017                          | 2450B       | 22.1                                | 2400                     | 1.948                                 | 51.178                                   | 1.902                               | 52.767                                 | 2.42%          | -3.01%           |
|                                    |             |                                     | 2450                     | 2.011                                 | 50.977                                   | 1.950                               | 52.700                                 | 3.13%          | -3.27%           |
|                                    |             |                                     | 2500                     | 2.081                                 | 50.801                                   | 2.021                               | 52.636                                 | 2.97%          | -3.49%           |
| 05/30/2016                         | 5200B-5800B | 21.6                                | 5240                     | 5.503                                 | 47.084                                   | 5.346                               | 48.960                                 | 2.94%          | -3.83%           |
|                                    |             |                                     | 5260                     | 5.535                                 | 47.087                                   | 5.369                               | 48.933                                 | 3.09%          | -3.77%           |
|                                    |             |                                     | 5280                     | 5.555                                 | 47.102                                   | 5.393                               | 48.906                                 | 3.00%          | -3.69%           |
|                                    |             |                                     | 5500                     | 5.776                                 | 46.800                                   | 5.650                               | 48.607                                 | 2.23%          | -3.72%           |
|                                    |             |                                     | 5600                     | 5.962                                 | 46.533                                   | 5.766                               | 48.471                                 | 3.40%          | -4.00%           |
|                                    |             |                                     | 5700                     | 6.104                                 | 46.353                                   | 5.883                               | 48.336                                 | 3.76%          | -4.10%           |
|                                    |             |                                     | 5745                     | 6.134                                 | 46.295                                   | 5.936                               | 48.275                                 | 3.34%          | -4.10%           |
|                                    |             |                                     | 5765                     | 6.199                                 | 46.254                                   | 5.959                               | 48.248                                 | 4.03%          | -4.13%           |
|                                    |             |                                     | 5825                     | 6.296                                 | 46.120                                   | 6.029                               | 48.166                                 | 4.43%          | -4.25%           |

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

|                                      |                                                                                                                                                                                                        |                               |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  | Page 56 of 95                   |

## 10.2 Test System Verification

Prior to SAR assessment, the system is verified to  $\pm 10\%$  of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

**Table 10-3**  
**1g System Verification Results**

| System Verification<br>TARGET & MEASURED |                        |             |            |                |                  |                 |           |          |                                   |                                     |                                         |                             |
|------------------------------------------|------------------------|-------------|------------|----------------|------------------|-----------------|-----------|----------|-----------------------------------|-------------------------------------|-----------------------------------------|-----------------------------|
| SAR System #                             | Tissue Frequency (MHz) | Tissue Type | Date:      | Amb. Temp (°C) | Liquid Temp (°C) | Input Power (W) | Dipole SN | Probe SN | Measured SAR <sub>1g</sub> (W/kg) | 1 W Target SAR <sub>1g</sub> (W/kg) | 1 W Normalized SAR <sub>1g</sub> (W/kg) | Deviation <sub>1g</sub> (%) |
| K                                        | 750                    | HEAD        | 05/31/2016 | 22.0           | 21.9             | 0.200           | 1046      | 3022     | 1.620                             | 8.200                               | 8.100                                   | -1.22%                      |
| I                                        | 835                    | HEAD        | 06/01/2016 | 24.0           | 22.5             | 0.200           | 4d119     | 3333     | 1.860                             | 9.140                               | 9.300                                   | 1.75%                       |
| E                                        | 835                    | HEAD        | 03/27/2017 | 22.0           | 20.6             | 0.200           | 4d133     | 7406     | 1.840                             | 9.320                               | 9.200                                   | -1.29%                      |
| E                                        | 1750                   | HEAD        | 06/01/2016 | 23.2           | 22.2             | 0.100           | 1051      | 7406     | 3.440                             | 36.100                              | 34.400                                  | -4.71%                      |
| I                                        | 1900                   | HEAD        | 06/03/2016 | 23.0           | 22.2             | 0.100           | 5d141     | 3333     | 4.150                             | 38.500                              | 41.500                                  | 7.79%                       |
| K                                        | 2450                   | HEAD        | 05/31/2016 | 23.8           | 22.8             | 0.100           | 882       | 3022     | 5.340                             | 50.500                              | 53.400                                  | 5.74%                       |
| K                                        | 2600                   | HEAD        | 05/31/2016 | 23.8           | 22.8             | 0.100           | 1071      | 3022     | 5.810                             | 55.900                              | 58.100                                  | 3.94%                       |
| J                                        | 5250                   | HEAD        | 06/06/2016 | 20.5           | 20.8             | 0.050           | 1120      | 7357     | 3.840                             | 78.700                              | 76.800                                  | -2.41%                      |
| K                                        | 5250                   | HEAD        | 04/06/2017 | 23.7           | 22.0             | 0.050           | 1237      | 7308     | 3.670                             | 79.200                              | 73.400                                  | -7.32%                      |
| J                                        | 5600                   | HEAD        | 06/06/2016 | 20.5           | 20.8             | 0.050           | 1120      | 7357     | 4.250                             | 82.300                              | 85.000                                  | 3.28%                       |
| K                                        | 5600                   | HEAD        | 04/06/2017 | 23.7           | 22.0             | 0.050           | 1237      | 7308     | 3.900                             | 83.300                              | 78.000                                  | -6.36%                      |
| J                                        | 5750                   | HEAD        | 06/06/2016 | 20.5           | 20.8             | 0.050           | 1120      | 7357     | 3.880                             | 79.100                              | 77.600                                  | -1.90%                      |
| K                                        | 5750                   | HEAD        | 04/06/2017 | 23.7           | 22.0             | 0.050           | 1237      | 7308     | 3.680                             | 81.500                              | 73.600                                  | -9.69%                      |
| G                                        | 750                    | BODY        | 06/06/2016 | 22.8           | 21.6             | 0.200           | 1054      | 3334     | 1.710                             | 8.560                               | 8.550                                   | -0.12%                      |
| I                                        | 750                    | BODY        | 04/03/2017 | 24.5           | 23.1             | 0.200           | 1161      | 3213     | 1.590                             | 8.430                               | 7.950                                   | -5.69%                      |
| J                                        | 835                    | BODY        | 06/02/2016 | 21.0           | 20.7             | 0.200           | 4d119     | 3318     | 1.980                             | 9.140                               | 9.900                                   | 8.32%                       |
| H                                        | 835                    | BODY        | 04/03/2017 | 21.6           | 21.2             | 0.200           | 4d133     | 3318     | 2.030                             | 9.500                               | 10.150                                  | 6.84%                       |
| H                                        | 835                    | BODY        | 04/10/2017 | 22.9           | 21.5             | 0.200           | 4d047     | 3318     | 1.940                             | 9.570                               | 9.700                                   | 1.36%                       |
| E                                        | 1750                   | BODY        | 06/01/2016 | 23.2           | 21.2             | 0.100           | 1051      | 7406     | 3.920                             | 36.500                              | 39.200                                  | 7.40%                       |
| H                                        | 1900                   | BODY        | 06/02/2016 | 22.0           | 22.5             | 0.100           | 5d141     | 3319     | 4.160                             | 39.600                              | 41.600                                  | 5.05%                       |
| G                                        | 2450                   | BODY        | 05/31/2016 | 22.0           | 22.0             | 0.100           | 882       | 3334     | 5.200                             | 49.400                              | 52.000                                  | 5.26%                       |
| E                                        | 2450                   | BODY        | 03/29/2017 | 23.5           | 22.1             | 0.100           | 981       | 7406     | 4.770                             | 50.800                              | 47.700                                  | -6.10%                      |
| G                                        | 2600                   | BODY        | 05/31/2016 | 22.0           | 22.0             | 0.100           | 1071      | 3334     | 5.770                             | 54.900                              | 57.700                                  | 5.10%                       |
| D                                        | 5250                   | BODY        | 05/30/2016 | 22.8           | 21.6             | 0.050           | 1120      | 3914     | 3.780                             | 75.600                              | 75.600                                  | 0.00%                       |
| D                                        | 5600                   | BODY        | 05/30/2016 | 22.8           | 21.6             | 0.050           | 1120      | 3914     | 3.900                             | 80.800                              | 78.000                                  | -3.47%                      |
| D                                        | 5750                   | BODY        | 05/30/2016 | 22.8           | 21.6             | 0.050           | 1120      | 3914     | 3.700                             | 76.500                              | 74.000                                  | -3.27%                      |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 57 of 95                   |

**Table 10-4**  
**10g System Verification Results**

| System Verification<br>TARGET & MEASURED |                        |             |            |                |                  |                 |           |          |                                    |                                      |                                          |                              |
|------------------------------------------|------------------------|-------------|------------|----------------|------------------|-----------------|-----------|----------|------------------------------------|--------------------------------------|------------------------------------------|------------------------------|
| SAR System #                             | Tissue Frequency (MHz) | Tissue Type | Date:      | Amb. Temp (°C) | Liquid Temp (°C) | Input Power (W) | Dipole SN | Probe SN | Measured SAR <sub>10g</sub> (W/kg) | 1 W Target SAR <sub>10g</sub> (W/kg) | 1 W Normalized SAR <sub>10g</sub> (W/kg) | Deviation <sub>10g</sub> (%) |
| E                                        | 1750                   | BODY        | 06/01/2016 | 23.2           | 21.2             | 0.100           | 1051      | 7406     | 2.080                              | 19.500                               | 20.800                                   | 6.67%                        |
| H                                        | 1900                   | BODY        | 06/02/2016 | 22.0           | 22.5             | 0.100           | 5d141     | 3319     | 2.160                              | 20.900                               | 21.600                                   | 3.35%                        |
| D                                        | 5250                   | BODY        | 05/30/2016 | 22.8           | 21.6             | 0.050           | 1120      | 3914     | 1.070                              | 21.200                               | 21.400                                   | 0.94%                        |
| D                                        | 5600                   | BODY        | 05/30/2016 | 22.8           | 21.6             | 0.050           | 1120      | 3914     | 1.100                              | 22.600                               | 22.000                                   | -2.65%                       |
| D                                        | 5750                   | BODY        | 05/30/2016 | 22.8           | 21.6             | 0.050           | 1120      | 3914     | 1.050                              | 21.300                               | 21.000                                   | -1.41%                       |




**Figure 10-1**  
**System Verification Setup Diagram**



**Figure 10-2**  
**System Verification Setup Photo**

|                                      |                                                                                                                                                                                                        |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset   |
| Page 58 of 95                        |                                                                                                                                                                                                        |                                 |

# 11 SAR DATA SUMMARY

## 11.1 Standalone Head SAR Data

**Table 11-1  
GSM 850 Head SAR**

| MEASUREMENT RESULTS                                                                               |     |           |         |                             |                       |                  |                                                 |               |                      |            |          |                |                   |        |
|---------------------------------------------------------------------------------------------------|-----|-----------|---------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------------|----------------------|------------|----------|----------------|-------------------|--------|
| FREQUENCY                                                                                         |     | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side                                            | Test Position | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |           |         |                             |                       |                  |                                                 |               |                      |            | (W/kg)   |                | (W/kg)            |        |
| 836.60                                                                                            | 190 | GSM 850   | GSM     | 34.0                        | 33.45                 | -0.01            | Right                                           | Cheek         | 87763                | 1:8.3      | 0.202    | 1.135          | 0.229             | A1     |
| 836.60                                                                                            | 190 | GSM 850   | GSM     | 34.0                        | 33.45                 | 0.05             | Right                                           | Tilt          | 87763                | 1:8.3      | 0.098    | 1.135          | 0.111             |        |
| 836.60                                                                                            | 190 | GSM 850   | GSM     | 34.0                        | 33.45                 | -0.08            | Left                                            | Cheek         | 87763                | 1:8.3      | 0.108    | 1.135          | 0.123             |        |
| 836.60                                                                                            | 190 | GSM 850   | GSM     | 34.0                        | 33.45                 | 0.01             | Left                                            | Tilt          | 87763                | 1:8.3      | 0.082    | 1.135          | 0.093             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |           |         |                             |                       |                  | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |               |                      |            |          |                |                   |        |

**Table 11-2  
UMTS 850 Head SAR**

| MEASUREMENT RESULTS                                                                               |      |           |         |                             |                       |                  |       |                                                 |            |                      |            |          |                |                   |        |
|---------------------------------------------------------------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|------------|----------------------|------------|----------|----------------|-------------------|--------|
| FREQUENCY                                                                                         |      | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Ant. State | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch.  |           |         |                             |                       |                  |       |                                                 |            |                      |            | (W/kg)   |                | (W/kg)            |        |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | -0.02            | Right | Cheek                                           | 1          | 8424D                | 1:1        | 0.164    | 1.167          | 0.191             | A2     |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | 0.04             | Right | Tilt                                            | 1          | 8424D                | 1:1        | 0.064    | 1.167          | 0.075             |        |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | 0.05             | Left  | Cheek                                           | 1          | 8424D                | 1:1        | 0.111    | 1.167          | 0.130             |        |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | 0.00             | Left  | Tilt                                            | 1          | 8424D                | 1:1        | 0.078    | 1.167          | 0.091             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |                      |            |          |                |                   |        |

**Table 11-3  
UMTS 1750 Head SAR**

| MEASUREMENT RESULTS                                                                               |      |           |         |                             |                       |                  |                                                 |               |                      |            |          |                |                   |        |
|---------------------------------------------------------------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------------|----------------------|------------|----------|----------------|-------------------|--------|
| FREQUENCY                                                                                         |      | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side                                            | Test Position | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch.  |           |         |                             |                       |                  |                                                 |               |                      |            | (W/kg)   |                | (W/kg)            |        |
| 1732.40                                                                                           | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | 0.03             | Right                                           | Cheek         | 841E0                | 1:1        | 0.168    | 1.122          | 0.188             |        |
| 1732.40                                                                                           | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | 0.02             | Right                                           | Tilt          | 841E0                | 1:1        | 0.129    | 1.122          | 0.145             |        |
| 1732.40                                                                                           | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | 0.03             | Left                                            | Cheek         | 841E0                | 1:1        | 0.303    | 1.122          | 0.340             | A3     |
| 1732.40                                                                                           | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | -0.01            | Left                                            | Tilt          | 841E0                | 1:1        | 0.118    | 1.122          | 0.132             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |               |                      |            |          |                |                   |        |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 59 of 95                   |

**Table 11-4**  
**GSM 1900 Head SAR**

| MEASUREMENT RESULTS                                                                               |     |           |         |                             |                       |                  |                                                 |               |                      |            |          |                |                   |        |
|---------------------------------------------------------------------------------------------------|-----|-----------|---------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------------|----------------------|------------|----------|----------------|-------------------|--------|
| FREQUENCY                                                                                         |     | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side                                            | Test Position | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |           |         |                             |                       |                  |                                                 |               |                      |            | (W/kg)   |                | (W/kg)            |        |
| 1880.00                                                                                           | 661 | GSM 1900  | GSM     | 30.5                        | 29.17                 | 0.11             | Right                                           | Cheek         | 84250                | 1:8.3      | 0.059    | 1.358          | 0.080             |        |
| 1880.00                                                                                           | 661 | GSM 1900  | GSM     | 30.5                        | 29.17                 | -0.01            | Right                                           | Tilt          | 84250                | 1:8.3      | 0.049    | 1.358          | 0.067             |        |
| 1880.00                                                                                           | 661 | GSM 1900  | GSM     | 30.5                        | 29.17                 | 0.06             | Left                                            | Cheek         | 84250                | 1:8.3      | 0.090    | 1.358          | 0.122             | A4     |
| 1880.00                                                                                           | 661 | GSM 1900  | GSM     | 30.5                        | 29.17                 | 0.00             | Left                                            | Tilt          | 84250                | 1:8.3      | 0.035    | 1.358          | 0.048             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |           |         |                             |                       |                  | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |               |                      |            |          |                |                   |        |

**Table 11-5**  
**UMTS 1900 Head SAR**

| MEASUREMENT RESULTS                                                                               |      |           |         |                             |                       |                  |       |                                                 |                      |            |          |                |                   |        |
|---------------------------------------------------------------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|----------------------|------------|----------|----------------|-------------------|--------|
| FREQUENCY                                                                                         |      | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch.  |           |         |                             |                       |                  |       |                                                 |                      |            | (W/kg)   |                | (W/kg)            |        |
| 1907.60                                                                                           | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | 0.13             | Right | Cheek                                           | 84250                | 1:1        | 0.159    | 1.183          | 0.188             |        |
| 1907.60                                                                                           | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | -0.01            | Right | Tilt                                            | 84250                | 1:1        | 0.113    | 1.183          | 0.134             |        |
| 1907.60                                                                                           | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | 0.02             | Left  | Cheek                                           | 84250                | 1:1        | 0.228    | 1.183          | 0.270             | A5     |
| 1907.60                                                                                           | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | 0.02             | Left  | Tilt                                            | 84250                | 1:1        | 0.083    | 1.183          | 0.098             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                      |            |          |                |                   |        |

**Table 11-6**  
**LTE Band 12 Head SAR**

| MEASUREMENT RESULTS                      |       |     |             |                 |                             |                       |                  |          |       |                                         |            |         |           |                      |            |          |                |                   |        |
|------------------------------------------|-------|-----|-------------|-----------------|-----------------------------|-----------------------|------------------|----------|-------|-----------------------------------------|------------|---------|-----------|----------------------|------------|----------|----------------|-------------------|--------|
| FREQUENCY                                |       |     | Mode        | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side  | Test Position                           | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                      | Ch.   |     |             |                 |                             |                       |                  |          |       |                                         |            |         |           |                      |            | (W/kg)   |                | (W/kg)            |        |
| 707.50                                   | 23095 | Mid | LTE Band 12 | 10              | 23.5                        | 22.63                 | -0.01            | 0        | Right | Cheek                                   | QPSK       | 1       | 0         | 84102                | 1:1        | 0.064    | 1.222          | 0.078             | A6     |
| 707.50                                   | 23095 | Mid | LTE Band 12 | 10              | 22.5                        | 21.81                 | 0.16             | 1        | Right | Cheek                                   | QPSK       | 25      | 0         | 84102                | 1:1        | 0.050    | 1.172          | 0.059             |        |
| 707.50                                   | 23095 | Mid | LTE Band 12 | 10              | 23.5                        | 22.63                 | 0.10             | 0        | Right | Tilt                                    | QPSK       | 1       | 0         | 84102                | 1:1        | 0.033    | 1.222          | 0.040             |        |
| 707.50                                   | 23095 | Mid | LTE Band 12 | 10              | 22.5                        | 21.81                 | -0.14            | 1        | Right | Tilt                                    | QPSK       | 25      | 0         | 84102                | 1:1        | 0.026    | 1.172          | 0.030             |        |
| 707.50                                   | 23095 | Mid | LTE Band 12 | 10              | 23.5                        | 22.63                 | 0.03             | 0        | Left  | Cheek                                   | QPSK       | 1       | 0         | 84102                | 1:1        | 0.052    | 1.222          | 0.064             |        |
| 707.50                                   | 23095 | Mid | LTE Band 12 | 10              | 22.5                        | 21.81                 | 0.12             | 1        | Left  | Cheek                                   | QPSK       | 25      | 0         | 84102                | 1:1        | 0.041    | 1.172          | 0.048             |        |
| 707.50                                   | 23095 | Mid | LTE Band 12 | 10              | 23.5                        | 22.63                 | 0.20             | 0        | Left  | Tilt                                    | QPSK       | 1       | 0         | 84102                | 1:1        | 0.030    | 1.222          | 0.037             |        |
| 707.50                                   | 23095 | Mid | LTE Band 12 | 10              | 22.5                        | 21.81                 | 0.13             | 1        | Left  | Tilt                                    | QPSK       | 25      | 0         | 84102                | 1:1        | 0.020    | 1.172          | 0.023             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |       |     |             |                 |                             |                       |                  |          |       |                                         |            |         |           |                      |            |          |                |                   |        |
| Spatial Peak                             |       |     |             |                 |                             |                       |                  |          |       | Head                                    |            |         |           |                      |            |          |                |                   |        |
| Uncontrolled Exposure/General Population |       |     |             |                 |                             |                       |                  |          |       | 1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |                      |            |          |                |                   |        |

|                                      |                                                                                                                                                                                                        |                               |  |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  |  | Page 60 of 95                   |

**Table 11-7**  
**LTE Band 13 Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                 |                             |                       |                  |          |      |                                                 |            |         |           |                      |            |          |                |                   |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|-----------------|-----------------------------|-----------------------|------------------|----------|------|-------------------------------------------------|------------|---------|-----------|----------------------|------------|----------|----------------|-------------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position                                   | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                 |                             |                       |                  |          |      |                                                 |            |         |           |                      |            | (W/kg)   |                | (W/kg)            |        |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 23.5                  | 22.42            | 0.03     | 0    | Right                                           | Cheek      | QPSK    | 1         | 25                   | 84102      | 1:1      | 0.089          | 1.282             | 0.114  | A7 |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 22.5                  | 20.92            | 0.08     | 1    | Right                                           | Cheek      | QPSK    | 25        | 0                    | 84102      | 1:1      | 0.072          | 1.439             | 0.104  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 23.5                  | 22.42            | 0.07     | 0    | Right                                           | Tilt       | QPSK    | 1         | 25                   | 84102      | 1:1      | 0.040          | 1.282             | 0.051  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 22.5                  | 20.92            | 0.15     | 1    | Right                                           | Tilt       | QPSK    | 25        | 0                    | 84102      | 1:1      | 0.033          | 1.439             | 0.047  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 23.5                  | 22.42            | 0.04     | 0    | Left                                            | Cheek      | QPSK    | 1         | 25                   | 84102      | 1:1      | 0.051          | 1.282             | 0.065  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 22.5                  | 20.92            | 0.13     | 1    | Left                                            | Cheek      | QPSK    | 25        | 0                    | 84102      | 1:1      | 0.041          | 1.439             | 0.059  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 23.5                  | 22.42            | 0.08     | 0    | Left                                            | Tilt       | QPSK    | 1         | 25                   | 84102      | 1:1      | 0.046          | 1.282             | 0.059  |    |
| 782.00                                                                                            | 23230 | Mid  | LTE Band 13     | 10                          | 22.5                  | 20.92            | 0.18     | 1    | Left                                            | Tilt       | QPSK    | 25        | 0                    | 84102      | 1:1      | 0.039          | 1.439             | 0.056  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                 |                             |                       |                  |          |      | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |                      |            |          |                |                   |        |    |

**Table 11-8**  
**LTE Band 5 (Cell) Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                   |                             |                       |                  |          |      |                                                 |            |            |         |           |                      |            |          |                |                   |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|-------------------|-----------------------------|-----------------------|------------------|----------|------|-------------------------------------------------|------------|------------|---------|-----------|----------------------|------------|----------|----------------|-------------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]   | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position                                   | Ant. State | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                   |                             |                       |                  |          |      |                                                 |            |            |         |           |                      |            | (W/kg)   |                | (W/kg)            |        |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | 0.14     | 0    | Right                                           | Cheek      | 1          | QPSK    | 1         | 0                    | 8413C      | 1:1      | 0.164          | 1.236             | 0.203  | A8 |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | 0.06     | 1    | Right                                           | Cheek      | 1          | QPSK    | 25        | 0                    | 8413C      | 1:1      | 0.137          | 1.358             | 0.186  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | 0.13     | 0    | Right                                           | Tilt       | 1          | QPSK    | 1         | 0                    | 8413C      | 1:1      | 0.054          | 1.236             | 0.067  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | 0.07     | 1    | Right                                           | Tilt       | 1          | QPSK    | 25        | 0                    | 8413C      | 1:1      | 0.047          | 1.358             | 0.064  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | -0.04    | 0    | Left                                            | Cheek      | 1          | QPSK    | 1         | 0                    | 8413C      | 1:1      | 0.109          | 1.236             | 0.135  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | 0.10     | 1    | Left                                            | Cheek      | 1          | QPSK    | 25        | 0                    | 8413C      | 1:1      | 0.085          | 1.358             | 0.115  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | 0.09     | 0    | Left                                            | Tilt       | 1          | QPSK    | 1         | 0                    | 8413C      | 1:1      | 0.090          | 1.236             | 0.111  |    |
| 836.50                                                                                            | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | 0.07     | 1    | Left                                            | Tilt       | 1          | QPSK    | 25        | 0                    | 8413C      | 1:1      | 0.075          | 1.358             | 0.102  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                   |                             |                       |                  |          |      | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |            |         |           |                      |            |          |                |                   |        |    |

**Table 11-9**  
**LTE Band 26 (Cell) Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                    |                             |                       |                  |          |      |                                                 |            |         |           |                      |            |          |                |                   |        |    |
|---------------------------------------------------------------------------------------------------|-------|------|--------------------|-----------------------------|-----------------------|------------------|----------|------|-------------------------------------------------|------------|---------|-----------|----------------------|------------|----------|----------------|-------------------|--------|----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]    | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position                                   | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |    |
| MHz                                                                                               | Ch.   |      |                    |                             |                       |                  |          |      |                                                 |            |         |           |                      |            | (W/kg)   |                | (W/kg)            |        |    |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                          | 23.5                  | 23.46            | 0.01     | 0    | Right                                           | Cheek      | QPSK    | 1         | 0                    | 8413C      | 1:1      | 0.127          | 1.009             | 0.128  | A9 |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                          | 22.5                  | 22.30            | 0.02     | 1    | Right                                           | Cheek      | QPSK    | 36        | 0                    | 8413C      | 1:1      | 0.099          | 1.047             | 0.104  |    |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                          | 23.5                  | 23.46            | -0.07    | 0    | Right                                           | Tilt       | QPSK    | 1         | 0                    | 8413C      | 1:1      | 0.044          | 1.009             | 0.044  |    |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                          | 22.5                  | 22.30            | 0.17     | 1    | Right                                           | Tilt       | QPSK    | 36        | 0                    | 8413C      | 1:1      | 0.036          | 1.047             | 0.038  |    |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                          | 23.5                  | 23.46            | 0.09     | 0    | Left                                            | Cheek      | QPSK    | 1         | 0                    | 8413C      | 1:1      | 0.075          | 1.009             | 0.076  |    |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                          | 22.5                  | 22.30            | 0.01     | 1    | Left                                            | Cheek      | QPSK    | 36        | 0                    | 8413C      | 1:1      | 0.057          | 1.047             | 0.060  |    |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                          | 23.5                  | 23.46            | 0.05     | 0    | Left                                            | Tilt       | QPSK    | 1         | 0                    | 8413C      | 1:1      | 0.065          | 1.009             | 0.066  |    |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                          | 22.5                  | 22.30            | 0.01     | 1    | Left                                            | Tilt       | QPSK    | 36        | 0                    | 8413C      | 1:1      | 0.051          | 1.047             | 0.053  |    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                    |                             |                       |                  |          |      | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |                      |            |          |                |                   |        |    |

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMN935F                          |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                   | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 61 of 95                          |

**Table 11-10**  
**LTE Band 4 (AWS) Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                  |                             |                       |                  |          |      |                                                 |            |         |           |                      |            |          |                |                   |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|------|-------------------------------------------------|------------|---------|-----------|----------------------|------------|----------|----------------|-------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position                                   | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| Mhz                                                                                               | Ch.   |      |                  |                             |                       |                  |          |      |                                                 |            |         |           |                      |            | (W/kg)   |                | (W/kg)            |        |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 23.81            | 0.06     | 0    | Right                                           | Cheek      | QPSK    | 1         | 0                    | 84162      | 1:1      | 0.212          | 1.172             | 0.248  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 22.87            | 0.05     | 1    | Right                                           | Cheek      | QPSK    | 50        | 25                   | 84162      | 1:1      | 0.142          | 1.156             | 0.164  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 23.81            | 0.10     | 0    | Right                                           | Tilt       | QPSK    | 1         | 0                    | 84162      | 1:1      | 0.213          | 1.172             | 0.250  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 22.87            | 0.06     | 1    | Right                                           | Tilt       | QPSK    | 50        | 25                   | 84162      | 1:1      | 0.143          | 1.156             | 0.165  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 23.81            | 0.06     | 0    | Left                                            | Cheek      | QPSK    | 1         | 0                    | 84162      | 1:1      | 0.335          | 1.172             | 0.393  | A10 |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 22.87            | 0.02     | 1    | Left                                            | Cheek      | QPSK    | 50        | 25                   | 84162      | 1:1      | 0.254          | 1.156             | 0.294  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 24.5                  | 23.81            | 0.07     | 0    | Left                                            | Tilt       | QPSK    | 1         | 0                    | 84162      | 1:1      | 0.151          | 1.172             | 0.177  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 23.5                  | 22.87            | 0.03     | 1    | Left                                            | Tilt       | QPSK    | 50        | 25                   | 84162      | 1:1      | 0.114          | 1.156             | 0.132  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          |      | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |                      |            |          |                |                   |        |     |

**Table 11-11**  
**LTE Band 2 (PCS) Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                  |                             |                       |                  |          |      |                                                 |            |         |           |                      |            |          |                |                   |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|------|-------------------------------------------------|------------|---------|-----------|----------------------|------------|----------|----------------|-------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position                                   | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                  |                             |                       |                  |          |      |                                                 |            |         |           |                      |            | (W/kg)   |                | (W/kg)            |        |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.21            | -0.05    | 0    | Right                                           | Cheek      | QPSK    | 1         | 0                    | 84250      | 1:1      | 0.167          | 1.346             | 0.225  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.19            | 0.04     | 1    | Right                                           | Cheek      | QPSK    | 50        | 0                    | 84250      | 1:1      | 0.115          | 1.352             | 0.155  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.21            | 0.05     | 0    | Right                                           | Tilt       | QPSK    | 1         | 0                    | 84250      | 1:1      | 0.118          | 1.346             | 0.159  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.19            | 0.02     | 1    | Right                                           | Tilt       | QPSK    | 50        | 0                    | 84250      | 1:1      | 0.090          | 1.352             | 0.122  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.21            | -0.04    | 0    | Left                                            | Cheek      | QPSK    | 1         | 0                    | 84250      | 1:1      | 0.234          | 1.346             | 0.315  | A11 |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.19            | 0.05     | 1    | Left                                            | Cheek      | QPSK    | 50        | 0                    | 84250      | 1:1      | 0.176          | 1.352             | 0.238  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 24.5                  | 23.21            | 0.05     | 0    | Left                                            | Tilt       | QPSK    | 1         | 0                    | 84250      | 1:1      | 0.072          | 1.346             | 0.097  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 23.5                  | 22.19            | 0.11     | 1    | Left                                            | Tilt       | QPSK    | 50        | 0                    | 84250      | 1:1      | 0.056          | 1.352             | 0.076  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          |      | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |                      |            |          |                |                   |        |     |

**Table 11-12**  
**LTE Band 25 (PCS) Head SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                   |                             |                       |                  |          |      |                                                 |            |         |           |                      |            |          |                |                   |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|-------------------|-----------------------------|-----------------------|------------------|----------|------|-------------------------------------------------|------------|---------|-----------|----------------------|------------|----------|----------------|-------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]   | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position                                   | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                   |                             |                       |                  |          |      |                                                 |            |         |           |                      |            | (W/kg)   |                | (W/kg)            |        |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 23.5                  | 22.30            | -0.01    | 0    | Right                                           | Cheek      | QPSK    | 1         | 0                    | 84250      | 1:1      | 0.098          | 1.318             | 0.129  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 22.5                  | 21.22            | 0.03     | 1    | Right                                           | Cheek      | QPSK    | 50        | 0                    | 84250      | 1:1      | 0.084          | 1.343             | 0.113  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 23.5                  | 22.30            | -0.06    | 0    | Right                                           | Tilt       | QPSK    | 1         | 0                    | 84250      | 1:1      | 0.080          | 1.318             | 0.105  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 22.5                  | 21.22            | 0.05     | 1    | Right                                           | Tilt       | QPSK    | 50        | 0                    | 84250      | 1:1      | 0.066          | 1.343             | 0.089  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 23.5                  | 22.30            | 0.03     | 0    | Left                                            | Cheek      | QPSK    | 1         | 0                    | 84250      | 1:1      | 0.146          | 1.318             | 0.192  | A12 |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 22.5                  | 21.22            | 0.02     | 1    | Left                                            | Cheek      | QPSK    | 50        | 0                    | 84250      | 1:1      | 0.119          | 1.343             | 0.160  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 23.5                  | 22.30            | 0.13     | 0    | Left                                            | Tilt       | QPSK    | 1         | 0                    | 84250      | 1:1      | 0.049          | 1.318             | 0.065  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 22.5                  | 21.22            | -0.01    | 1    | Left                                            | Tilt       | QPSK    | 50        | 0                    | 84250      | 1:1      | 0.041          | 1.343             | 0.055  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                   |                             |                       |                  |          |      | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |                      |            |          |                |                   |        |     |

|                                      |                                                                                                                                                                                                        |                               |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  | Page 62 of 95                   |



**Table 11-13**  
**LTE Band 41 Head SAR**

| MEASUREMENT RESULTS                                                                               |       |         |                 |                             |                       |                  |          |      |                                                 |            |         |           |                      |            |          |                |                   |        |     |
|---------------------------------------------------------------------------------------------------|-------|---------|-----------------|-----------------------------|-----------------------|------------------|----------|------|-------------------------------------------------|------------|---------|-----------|----------------------|------------|----------|----------------|-------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode    | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position                                   | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |         |                 |                             |                       |                  |          |      |                                                 |            |         |           |                      |            | (W/kg)   |                | (W/kg)            |        |     |
| 2549.50                                                                                           | 40185 | Low-Mid | LTE Band 41     | 20                          | 23.5                  | 23.43            | 0.05     | 0    | Right                                           | Cheek      | QPSK    | 1         | 0                    | 84162      | 1:1.58   | 0.062          | 1.016             | 0.063  |     |
| 2549.50                                                                                           | 40185 | Low-Mid | LTE Band 41     | 20                          | 22.5                  | 22.33            | -0.08    | 1    | Right                                           | Cheek      | QPSK    | 50        | 0                    | 84162      | 1:1.58   | 0.048          | 1.040             | 0.050  |     |
| 2549.50                                                                                           | 40185 | Low-Mid | LTE Band 41     | 20                          | 23.5                  | 23.43            | 0.13     | 0    | Right                                           | Tilt       | QPSK    | 1         | 0                    | 84162      | 1:1.58   | 0.055          | 1.016             | 0.056  |     |
| 2549.50                                                                                           | 40185 | Low-Mid | LTE Band 41     | 20                          | 22.5                  | 22.33            | -0.02    | 1    | Right                                           | Tilt       | QPSK    | 50        | 0                    | 84162      | 1:1.58   | 0.042          | 1.040             | 0.044  |     |
| 2549.50                                                                                           | 40185 | Low-Mid | LTE Band 41     | 20                          | 23.5                  | 23.43            | -0.13    | 0    | Left                                            | Cheek      | QPSK    | 1         | 0                    | 84162      | 1:1.58   | 0.079          | 1.016             | 0.080  | A13 |
| 2549.50                                                                                           | 40185 | Low-Mid | LTE Band 41     | 20                          | 22.5                  | 22.33            | 0.02     | 1    | Left                                            | Cheek      | QPSK    | 50        | 0                    | 84162      | 1:1.58   | 0.062          | 1.040             | 0.064  |     |
| 2549.50                                                                                           | 40185 | Low-Mid | LTE Band 41     | 20                          | 23.5                  | 23.43            | -0.01    | 0    | Left                                            | Tilt       | QPSK    | 1         | 0                    | 84162      | 1:1.58   | 0.021          | 1.016             | 0.021  |     |
| 2549.50                                                                                           | 40185 | Low-Mid | LTE Band 41     | 20                          | 22.5                  | 22.33            | 0.13     | 1    | Left                                            | Tilt       | QPSK    | 50        | 0                    | 84162      | 1:1.58   | 0.017          | 1.040             | 0.018  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |         |                 |                             |                       |                  |          |      | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |                      |            |          |                |                   |        |     |

**Table 11-14**  
**DTS Head SAR**

| MEASUREMENT RESULTS                                                                               |     |         |         |                 |                             |                       |                  |       |                                                 |                 |                      |                  |                |                       |          |                        |                             |                   |        |
|---------------------------------------------------------------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|-------|-------------------------------------------------|-----------------|----------------------|------------------|----------------|-----------------------|----------|------------------------|-----------------------------|-------------------|--------|
| FREQUENCY                                                                                         |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side  | Test Position                                   | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |         |         |                 |                             |                       |                  |       |                                                 |                 |                      |                  |                | (W/kg)                | (W/kg)   |                        |                             | (W/kg)            |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 14.98                 | 0.06             | Right | Cheek                                           | 1               | 05C3E                | 1                | 98.9           | 0.638                 | 0.482    | 1.127                  | 1.011                       | 0.549             | A14    |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 14.98                 | 0.13             | Right | Tilt                                            | 1               | 05C3E                | 1                | 98.9           | 0.491                 | 0.354    | 1.127                  | 1.011                       | 0.403             |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 14.98                 | -0.17            | Left  | Cheek                                           | 1               | 05C3E                | 1                | 98.9           | 0.270                 | -        | 1.127                  | 1.011                       | -                 |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 14.98                 | 0.01             | Left  | Tilt                                            | 1               | 05C3E                | 1                | 98.9           | 0.181                 | -        | 1.127                  | 1.011                       | -                 |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 15.22                 | -0.15            | Right | Cheek                                           | 2               | 05C3E                | 1                | 99.9           | 0.523                 | 0.473    | 1.067                  | 1.001                       | 0.505             |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 15.22                 | 0.06             | Right | Tilt                                            | 2               | 05C3E                | 1                | 99.9           | 0.457                 | 0.344    | 1.067                  | 1.001                       | 0.367             |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 15.22                 | 0.13             | Left  | Cheek                                           | 2               | 05C3E                | 1                | 99.9           | 0.159                 | -        | 1.067                  | 1.001                       | -                 |        |
| 2412                                                                                              | 1   | 802.11b | DSSS    | 22              | 15.5                        | 15.22                 | 0.15             | Left  | Tilt                                            | 2               | 05C3E                | 1                | 99.9           | 0.184                 | -        | 1.067                  | 1.001                       | -                 |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  |       | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                 |                      |                  |                |                       |          |                        |                             |                   |        |

|                                      |                                                                                                                                                                                                        |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset   |
| Page 63 of 95                        |                                                                                                                                                                                                        |                                 |

**Table 11-15  
NII Head SAR**

| MEASUREMENT RESULTS                                                                               |     |          |         |                 |                             |                       |                  |                                                 |               |                 |                      |                  |                |                       |          |                        |                             |                   |        |
|---------------------------------------------------------------------------------------------------|-----|----------|---------|-----------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|---------------|-----------------|----------------------|------------------|----------------|-----------------------|----------|------------------------|-----------------------------|-------------------|--------|
| FREQUENCY                                                                                         |     | Mode     | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side                                            | Test Position | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |          |         |                 |                             |                       |                  |                                                 |               |                 |                      |                  |                | W/kg                  | (W/kg)   |                        |                             | (W/kg)            |        |
| 5290                                                                                              | 58  | 802.11ac | OFDM    | 80              | 13.5                        | 13.14                 | 0.20             | Right                                           | Cheek         | 1               | 05C3E                | 29.3             | 94.0           | 0.319                 | -        | 1.086                  | 1.063                       | -                 |        |
| 5290                                                                                              | 58  | 802.11ac | OFDM    | 80              | 13.5                        | 13.14                 | 0.16             | Right                                           | Tilt          | 1               | 05C3E                | 29.3             | 94.0           | 0.281                 | -        | 1.086                  | 1.063                       | -                 |        |
| 5290                                                                                              | 58  | 802.11ac | OFDM    | 80              | 13.5                        | 13.14                 | 0.15             | Left                                            | Cheek         | 1               | 05C3E                | 29.3             | 94.0           | 0.594                 | 0.171    | 1.086                  | 1.063                       | 0.197             |        |
| 5290                                                                                              | 58  | 802.11ac | OFDM    | 80              | 13.5                        | 13.14                 | 0.16             | Left                                            | Tilt          | 1               | 05C3E                | 29.3             | 94.0           | 0.305                 | -        | 1.086                  | 1.063                       | -                 |        |
| 5290                                                                                              | 58  | 802.11ac | OFDM    | 80              | 13.5                        | 13.26                 | 0.12             | Right                                           | Cheek         | 2               | 04160                | 29.3             | 94.1           | 0.956                 | 0.504    | 1.057                  | 1.063                       | 0.566             |        |
| 5290                                                                                              | 58  | 802.11ac | OFDM    | 80              | 13.5                        | 13.26                 | 0.12             | Right                                           | Tilt          | 2               | 04160                | 29.3             | 94.1           | 0.718                 | 0.454    | 1.057                  | 1.063                       | 0.510             |        |
| 5290                                                                                              | 58  | 802.11ac | OFDM    | 80              | 13.5                        | 13.26                 | 0.12             | Left                                            | Cheek         | 2               | 04160                | 29.3             | 94.1           | 0.695                 | -        | 1.057                  | 1.063                       | -                 |        |
| 5290                                                                                              | 58  | 802.11ac | OFDM    | 80              | 13.5                        | 13.26                 | 0.15             | Left                                            | Tilt          | 2               | 04160                | 29.3             | 94.1           | 0.445                 | -        | 1.057                  | 1.063                       | -                 |        |
| 5690                                                                                              | 138 | 802.11ac | OFDM    | 80              | 13.5                        | 13.27                 | 0.15             | Right                                           | Cheek         | 1               | 05C3E                | 29.3             | 94.0           | 0.296                 | -        | 1.054                  | 1.063                       | -                 |        |
| 5690                                                                                              | 138 | 802.11ac | OFDM    | 80              | 13.5                        | 13.27                 | 0.13             | Right                                           | Tilt          | 1               | 05C3E                | 29.3             | 94.0           | 0.284                 | -        | 1.054                  | 1.063                       | -                 |        |
| 5690                                                                                              | 138 | 802.11ac | OFDM    | 80              | 13.5                        | 13.27                 | 0.12             | Left                                            | Cheek         | 1               | 05C3E                | 29.3             | 94.0           | 1.085                 | 0.290    | 1.054                  | 1.063                       | 0.325             |        |
| 5690                                                                                              | 138 | 802.11ac | OFDM    | 80              | 13.5                        | 13.27                 | 0.18             | Left                                            | Tilt          | 1               | 05C3E                | 29.3             | 94.0           | 0.680                 | -        | 1.054                  | 1.063                       | -                 |        |
| 5610                                                                                              | 122 | 802.11ac | OFDM    | 80              | 13.5                        | 13.50                 | 0.15             | Right                                           | Cheek         | 2               | 04160                | 29.3             | 94.1           | 1.152                 | 0.600    | 1.000                  | 1.063                       | 0.638             | A15    |
| 5610                                                                                              | 122 | 802.11ac | OFDM    | 80              | 13.5                        | 13.50                 | 0.04             | Right                                           | Tilt          | 2               | 04160                | 29.3             | 94.1           | 0.904                 | -        | 1.000                  | 1.063                       | -                 |        |
| 5610                                                                                              | 122 | 802.11ac | OFDM    | 80              | 13.5                        | 13.50                 | 0.13             | Left                                            | Cheek         | 2               | 04160                | 29.3             | 94.1           | 0.963                 | 0.593    | 1.000                  | 1.063                       | 0.630             |        |
| 5610                                                                                              | 122 | 802.11ac | OFDM    | 80              | 13.5                        | 13.50                 | 0.12             | Left                                            | Tilt          | 2               | 04160                | 29.3             | 94.1           | 0.622                 | -        | 1.000                  | 1.063                       | -                 |        |
| 5775                                                                                              | 155 | 802.11ac | OFDM    | 80              | 13.5                        | 13.25                 | 0.17             | Right                                           | Cheek         | 1               | 05C3E                | 29.3             | 94.0           | 0.273                 | -        | 1.059                  | 1.063                       | -                 |        |
| 5775                                                                                              | 155 | 802.11ac | OFDM    | 80              | 13.5                        | 13.25                 | 0.17             | Right                                           | Tilt          | 1               | 05C3E                | 29.3             | 94.0           | 0.211                 | -        | 1.059                  | 1.063                       | -                 |        |
| 5775                                                                                              | 155 | 802.11ac | OFDM    | 80              | 13.5                        | 13.25                 | 0.15             | Left                                            | Cheek         | 1               | 05C3E                | 29.3             | 94.0           | 0.836                 | 0.216    | 1.059                  | 1.063                       | 0.243             |        |
| 5775                                                                                              | 155 | 802.11ac | OFDM    | 80              | 13.5                        | 13.25                 | 0.17             | Left                                            | Tilt          | 1               | 05C3E                | 29.3             | 94.0           | 0.566                 | -        | 1.059                  | 1.063                       | -                 |        |
| 5775                                                                                              | 155 | 802.11ac | OFDM    | 80              | 13.5                        | 12.87                 | 0.15             | Right                                           | Cheek         | 2               | 04160                | 29.3             | 94.1           | 0.762                 | -        | 1.156                  | 1.063                       | -                 |        |
| 5775                                                                                              | 155 | 802.11ac | OFDM    | 80              | 13.5                        | 12.87                 | 0.11             | Right                                           | Tilt          | 2               | 04160                | 29.3             | 94.1           | 0.811                 | 0.521    | 1.156                  | 1.063                       | 0.640             |        |
| 5775                                                                                              | 155 | 802.11ac | OFDM    | 80              | 13.5                        | 12.87                 | 0.18             | Left                                            | Cheek         | 2               | 04160                | 29.3             | 94.1           | 0.803                 | 0.507    | 1.156                  | 1.063                       | 0.623             |        |
| 5775                                                                                              | 155 | 802.11ac | OFDM    | 80              | 13.5                        | 12.87                 | 0.11             | Left                                            | Tilt          | 2               | 04160                | 29.3             | 94.1           | 0.721                 | -        | 1.156                  | 1.063                       | -                 |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |          |         |                 |                             |                       |                  | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |               |                 |                      |                  |                |                       |          |                        |                             |                   |        |

## 11.2 Standalone Body-Worn SAR Data

**Table 11-16  
GSM/UMTS Body-Worn SAR Data**

| MEASUREMENT RESULTS                                                                               |      |           |         |                             |                       |                  |         |                                                 |                      |            |      |          |                |                   |        |
|---------------------------------------------------------------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|---------|-------------------------------------------------|----------------------|------------|------|----------|----------------|-------------------|--------|
| FREQUENCY                                                                                         |      | Mode      | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing | Ant. State                                      | Device Serial Number | Duty Cycle | Side | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch.  |           |         |                             |                       |                  |         |                                                 |                      |            |      | (W/kg)   |                | (W/kg)            |        |
| 836.60                                                                                            | 190  | GSM 850   | GSM     | 34.0                        | 33.45                 | -0.03            | 15 mm   | N/A                                             | 85F64                | 1:8.3      | back | 0.433    | 1.135          | 0.491             | A16    |
| 836.60                                                                                            | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | 0.01             | 15 mm   | 1                                               | 8424D                | 1:1        | back | 0.385    | 1.167          | 0.449             | A18    |
| 1732.40                                                                                           | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | -0.01            | 15 mm   | N/A                                             | 84162                | 1:1        | back | 0.452    | 1.122          | 0.507             | A20    |
| 1880.00                                                                                           | 661  | GSM 1900  | GSM     | 30.5                        | 29.17                 | -0.03            | 15 mm   | N/A                                             | 84102                | 1:8.3      | back | 0.383    | 1.358          | 0.520             | A22    |
| 1907.60                                                                                           | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | -0.01            | 15 mm   | N/A                                             | 84102                | 1:1        | back | 0.403    | 1.183          | 0.477             | A24    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  |         | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                      |            |      |          |                |                   |        |

|                                      |                                                                                     |                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                          | DUT Type:<br>Portable Handset |                                                                                       | Page 64 of 95                   |

**Table 11-17**  
**LTE Body-Worn SAR**

| MEASUREMENT RESULTS                      |       |         |                    |                             |                       |                  |          |            |                      |            |         |           |         |       |            |          |                |                   |        |     |
|------------------------------------------|-------|---------|--------------------|-----------------------------|-----------------------|------------------|----------|------------|----------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|-------------------|--------|-----|
| FREQUENCY                                |       | Mode    | Bandwidth [MHz]    | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Ant. State | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| MHz                                      | Ch.   |         |                    |                             |                       |                  |          |            |                      |            |         |           |         |       |            | (W/kg)   |                | (W/kg)            |        |     |
| 707.50                                   | 23095 | Mid     | LTE Band 12        | 10                          | 23.5                  | 22.63            | 0.00     | 0          | N/A                  | 84102      | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.124          | 1.222             | 0.152  | A26 |
| 707.50                                   | 23095 | Mid     | LTE Band 12        | 10                          | 22.5                  | 21.81            | 0.00     | 1          | N/A                  | 84102      | QPSK    | 25        | 0       | 15 mm | back       | 1:1      | 0.101          | 1.172             | 0.118  |     |
| 782.00                                   | 23230 | Mid     | LTE Band 13        | 10                          | 23.5                  | 22.42            | 0.01     | 0          | N/A                  | 98443      | QPSK    | 1         | 25      | 15 mm | back       | 1:1      | 0.236          | 1.282             | 0.303  | A28 |
| 782.00                                   | 23230 | Mid     | LTE Band 13        | 10                          | 22.5                  | 20.92            | -0.02    | 1          | N/A                  | 98443      | QPSK    | 25        | 0       | 15 mm | back       | 1:1      | 0.169          | 1.439             | 0.243  |     |
| 836.50                                   | 20525 | Mid     | LTE Band 5 (Cell)  | 10                          | 25.0                  | 24.08            | -0.03    | 0          | 1                    | 85F64      | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.381          | 1.236             | 0.471  | A30 |
| 836.50                                   | 20525 | Mid     | LTE Band 5 (Cell)  | 10                          | 24.0                  | 22.67            | 0.05     | 1          | 1                    | 85F64      | QPSK    | 25        | 0       | 15 mm | back       | 1:1      | 0.246          | 1.358             | 0.334  |     |
| 831.50                                   | 26865 | Mid     | LTE Band 26 (Cell) | 15                          | 23.5                  | 23.46            | 0.00     | 0          | N/A                  | 841C3      | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.292          | 1.009             | 0.295  | A32 |
| 831.50                                   | 26865 | Mid     | LTE Band 26 (Cell) | 15                          | 22.5                  | 22.30            | -0.12    | 1          | N/A                  | 841C3      | QPSK    | 36        | 0       | 15 mm | back       | 1:1      | 0.224          | 1.047             | 0.235  |     |
| 1732.50                                  | 20175 | Mid     | LTE Band 4 (AWS)   | 20                          | 24.5                  | 23.81            | 0.01     | 0          | N/A                  | 84162      | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.490          | 1.172             | 0.574  | A34 |
| 1732.50                                  | 20175 | Mid     | LTE Band 4 (AWS)   | 20                          | 23.5                  | 22.87            | -0.03    | 1          | N/A                  | 84162      | QPSK    | 50        | 25      | 15 mm | back       | 1:1      | 0.393          | 1.156             | 0.454  |     |
| 1900.00                                  | 19100 | High    | LTE Band 2 (PCS)   | 20                          | 24.5                  | 23.21            | -0.02    | 0          | N/A                  | 84102      | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.499          | 1.346             | 0.672  | A36 |
| 1900.00                                  | 19100 | High    | LTE Band 2 (PCS)   | 20                          | 23.5                  | 22.19            | 0.00     | 1          | N/A                  | 84102      | QPSK    | 50        | 0       | 15 mm | back       | 1:1      | 0.388          | 1.352             | 0.525  |     |
| 1905.00                                  | 26590 | High    | LTE Band 25 (PCS)  | 20                          | 23.5                  | 22.30            | -0.04    | 0          | N/A                  | 84102      | QPSK    | 1         | 0       | 15 mm | back       | 1:1      | 0.392          | 1.318             | 0.517  | A38 |
| 1905.00                                  | 26590 | High    | LTE Band 25 (PCS)  | 20                          | 22.5                  | 21.22            | -0.04    | 1          | N/A                  | 84102      | QPSK    | 50        | 0       | 15 mm | back       | 1:1      | 0.303          | 1.343             | 0.407  |     |
| 2549.50                                  | 40185 | Low-Mid | LTE Band 41        | 20                          | 23.5                  | 23.43            | 0.09     | 0          | N/A                  | 84162      | QPSK    | 1         | 0       | 15 mm | back       | 1:1.58   | 0.220          | 1.016             | 0.224  | A40 |
| 2549.50                                  | 40185 | Low-Mid | LTE Band 41        | 20                          | 22.5                  | 22.33            | 0.05     | 1          | N/A                  | 84162      | QPSK    | 50        | 0       | 15 mm | back       | 1:1.58   | 0.172          | 1.040             | 0.179  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |       |         |                    |                             |                       |                  |          |            | Body                 |            |         |           |         |       |            |          |                |                   |        |     |
| Spatial Peak                             |       |         |                    |                             |                       |                  |          |            | 1.6 W/kg (mW/g)      |            |         |           |         |       |            |          |                |                   |        |     |
| Uncontrolled Exposure/General Population |       |         |                    |                             |                       |                  |          |            | averaged over 1 gram |            |         |           |         |       |            |          |                |                   |        |     |

**Table 11-18**  
**DTS Body-Worn SAR**

| MEASUREMENT RESULTS                                                                               |     |         |         |                 |                             |                       |                  |                                                 |                 |                      |                  |      |                |                       |          |                        |                             |                   |        |
|---------------------------------------------------------------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|-----------------|----------------------|------------------|------|----------------|-----------------------|----------|------------------------|-----------------------------|-------------------|--------|
| FREQUENCY                                                                                         |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Side | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Reported SAR (1g) | Plot # |
| MHz                                                                                               | Ch. |         |         |                 |                             |                       |                  |                                                 |                 |                      |                  |      |                | W/kg                  | (W/kg)   |                        |                             | (W/kg)            |        |
| 2437                                                                                              | 6   | 802.11b | DSSS    | 22              | 19.5                        | 18.55                 | 0.02             | 15 mm                                           | 1               | 85F64                | 1                | back | 98.9           | 0.305                 | 0.223    | 1.245                  | 1.011                       | 0.281             | A42    |
| 2462                                                                                              | 11  | 802.11b | DSSS    | 22              | 19.5                        | 19.21                 | 0.10             | 15 mm                                           | 2               | 85F64                | 1                | back | 99.9           | 0.294                 | 0.204    | 1.069                  | 1.001                       | 0.218             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                 |                      |                  |      |                |                       |          |                        |                             |                   |        |

**Table 11-19**  
**NII Body-Worn SAR**

| MEASUREMENT RESULTS                                      |     |         |         |                 |                             |                       |                  |                                                 |                 |                      |                  |      |                |                       |          |                        |                             |                   |        |
|----------------------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|-------------------------------------------------|-----------------|----------------------|------------------|------|----------------|-----------------------|----------|------------------------|-----------------------------|-------------------|--------|
| FREQUENCY                                                |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                                         | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Side | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Reported SAR (1g) | Plot # |
| MHz                                                      | Ch. |         |         |                 |                             |                       |                  |                                                 |                 |                      |                  |      |                | W/kg                  | (W/kg)   |                        |                             | (W/kg)            |        |
| 5280                                                     | 56  | 802.11a | OFDM    | 20              | 17.5                        | 16.96                 | 0.12             | 15 mm                                           | 1               | 05C28                | 6                | back | 98.6           | 0.627                 | 0.308    | 1.132                  | 1.014                       | 0.354             | A44    |
| 5260                                                     | 52  | 802.11a | OFDM    | 20              | 17.5                        | 17.27                 | 0.17             | 15 mm                                           | 2               | 05C28                | 6                | back | 98.6           | 0.151                 | 0.075    | 1.054                  | 1.014                       | 0.080             |        |
| 5720                                                     | 144 | 802.11a | OFDM    | 20              | 17.5                        | 17.30                 | 0.07             | 15 mm                                           | 1               | 05C28                | 6                | back | 98.6           | 0.183                 | 0.102    | 1.047                  | 1.014                       | 0.108             |        |
| 5500                                                     | 100 | 802.11a | OFDM    | 20              | 17.5                        | 17.20                 | 0.07             | 15 mm                                           | 2               | 05C28                | 6                | back | 98.6           | 0.096                 | 0.055    | 1.072                  | 1.014                       | 0.060             |        |
| 5825                                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 17.13                 | 0.13             | 15 mm                                           | 1               | 05C28                | 6                | back | 98.6           | 0.145                 | 0.080    | 1.089                  | 1.014                       | 0.088             |        |
| 5825                                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 16.75                 | -0.12            | 15 mm                                           | 2               | 05C28                | 6                | back | 98.6           | 0.108                 | 0.059    | 1.189                  | 1.014                       | 0.071             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT                    |     |         |         |                 |                             |                       |                  | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |                 |                      |                  |      |                |                       |          |                        |                             |                   |        |
| Spatial Peak<br>Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  |                                                 |                 |                      |                  |      |                |                       |          |                        |                             |                   |        |

|                                      |                                                                                                                                                                                                 |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  SAR EVALUATION REPORT  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | DUT Type:<br>Portable Handset   |
| Page 65 of 95                        |                                                                                                                                                                                                 |                                 |

## 11.3 Standalone Hotspot SAR Data

**Table 11-20**  
**GPRS/UMTS Hotspot SAR Data**

| MEASUREMENT RESULTS                      |      |           |         |                             |                       |                  |                      |            |                      |                 |            |        |          |                |                   |        |
|------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|----------------------|------------|----------------------|-----------------|------------|--------|----------|----------------|-------------------|--------|
| FREQUENCY                                |      | Mode      | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing              | Ant. State | Device Serial Number | # of GPRS Slots | Duty Cycle | Side   | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                      | Ch.  |           |         |                             |                       |                  |                      |            |                      |                 |            |        | (W/kg)   |                | (W/kg)            |        |
| 824.20                                   | 128  | GSM 850   | GPRS    | 29.6                        | 28.77                 | -0.02            | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | back   | 0.579    | 1.211          | 0.701             |        |
| 836.60                                   | 190  | GSM 850   | GPRS    | 29.6                        | 29.15                 | -0.01            | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | back   | 0.768    | 1.109          | 0.852             |        |
| 848.80                                   | 251  | GSM 850   | GPRS    | 29.6                        | 29.19                 | -0.02            | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | back   | 0.774    | 1.099          | 0.851             |        |
| 824.20                                   | 128  | GSM 850   | GPRS    | 29.6                        | 28.77                 | 0.03             | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | front  | 0.656    | 1.211          | 0.794             |        |
| 836.60                                   | 190  | GSM 850   | GPRS    | 29.6                        | 29.15                 | -0.04            | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | front  | 0.753    | 1.109          | 0.835             |        |
| 848.80                                   | 251  | GSM 850   | GPRS    | 29.6                        | 29.19                 | -0.06            | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | front  | 0.836    | 1.099          | 0.919             |        |
| 836.60                                   | 190  | GSM 850   | GPRS    | 29.6                        | 29.15                 | -0.04            | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | bottom | 0.418    | 1.109          | 0.464             |        |
| 836.60                                   | 190  | GSM 850   | GPRS    | 29.6                        | 29.15                 | 0.15             | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | right  | 0.328    | 1.109          | 0.364             |        |
| 836.60                                   | 190  | GSM 850   | GPRS    | 29.6                        | 29.15                 | 0.03             | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | left   | 0.079    | 1.109          | 0.088             |        |
| 848.80                                   | 251  | GSM 850   | GPRS    | 29.6                        | 29.19                 | -0.09            | 10 mm                | N/A        | 85F64                | 4               | 1:2.076    | front  | 0.841    | 1.099          | 0.924             | A17    |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | -0.01            | 10 mm                | 1          | 8424D                | N/A             | 1:1        | back   | 0.575    | 1.167          | 0.671             |        |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | -0.02            | 10 mm                | 1          | 8424D                | N/A             | 1:1        | front  | 0.617    | 1.167          | 0.720             | A19    |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | -0.05            | 10 mm                | 1          | 8424D                | N/A             | 1:1        | bottom | 0.257    | 1.167          | 0.300             |        |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | 0.02             | 10 mm                | 1          | 8424D                | N/A             | 1:1        | right  | 0.300    | 1.167          | 0.350             |        |
| 836.60                                   | 4183 | UMTS 850  | RMC     | 25.0                        | 24.33                 | -0.10            | 10 mm                | 1          | 8424D                | N/A             | 1:1        | left   | 0.043    | 1.167          | 0.050             |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 21.5                        | 21.17                 | 0.02             | 10 mm                | N/A        | 841E0                | N/A             | 1:1        | back   | 0.495    | 1.079          | 0.534             |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 21.5                        | 21.17                 | 0.01             | 10 mm                | N/A        | 841E0                | N/A             | 1:1        | front  | 0.475    | 1.079          | 0.513             |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 21.5                        | 21.17                 | 0.01             | 10 mm                | N/A        | 841E0                | N/A             | 1:1        | bottom | 0.618    | 1.079          | 0.667             | A21    |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 21.5                        | 21.17                 | -0.01            | 10 mm                | N/A        | 841E0                | N/A             | 1:1        | left   | 0.335    | 1.079          | 0.361             |        |
| 1909.80                                  | 810  | GSM 1900  | GPRS    | 26.5                        | 25.56                 | -0.03            | 10 mm                | N/A        | 84102                | 3               | 1:2.76     | back   | 0.463    | 1.242          | 0.575             |        |
| 1909.80                                  | 810  | GSM 1900  | GPRS    | 26.5                        | 25.56                 | 0.03             | 10 mm                | N/A        | 84102                | 3               | 1:2.76     | front  | 0.428    | 1.242          | 0.532             |        |
| 1850.20                                  | 512  | GSM 1900  | GPRS    | 26.5                        | 25.51                 | -0.06            | 10 mm                | N/A        | 84102                | 3               | 1:2.76     | bottom | 0.685    | 1.256          | 0.860             |        |
| 1880.00                                  | 661  | GSM 1900  | GPRS    | 26.5                        | 24.92                 | 0.02             | 10 mm                | N/A        | 84102                | 3               | 1:2.76     | bottom | 0.696    | 1.439          | 1.002             | A23    |
| 1909.80                                  | 810  | GSM 1900  | GPRS    | 26.5                        | 25.56                 | -0.01            | 10 mm                | N/A        | 84102                | 3               | 1:2.76     | bottom | 0.659    | 1.242          | 0.818             |        |
| 1909.80                                  | 810  | GSM 1900  | GPRS    | 26.5                        | 25.56                 | -0.07            | 10 mm                | N/A        | 84102                | 3               | 1:2.76     | left   | 0.099    | 1.242          | 0.123             |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 21.5                        | 21.02                 | 0.01             | 10 mm                | N/A        | 841E0                | N/A             | 1:1        | back   | 0.472    | 1.117          | 0.527             |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 21.5                        | 21.02                 | 0.02             | 10 mm                | N/A        | 841E0                | N/A             | 1:1        | front  | 0.417    | 1.117          | 0.466             |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 21.5                        | 21.02                 | -0.02            | 10 mm                | N/A        | 841E0                | N/A             | 1:1        | bottom | 0.693    | 1.117          | 0.774             | A25    |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 21.5                        | 21.02                 | -0.03            | 10 mm                | N/A        | 841E0                | N/A             | 1:1        | left   | 0.108    | 1.117          | 0.121             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |      |           |         |                             |                       |                  | Body                 |            |                      |                 |            |        |          |                |                   |        |
| Spatial Peak                             |      |           |         |                             |                       |                  | 1.6 W/kg (mW/g)      |            |                      |                 |            |        |          |                |                   |        |
| Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  | averaged over 1 gram |            |                      |                 |            |        |          |                |                   |        |

Blue entry represents variability measurement

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 66 of 95                   |

**Table 11-21**  
**LTE Band 12 Hotspot SAR**

| MEASUREMENT RESULTS                                   |       |      |                    |                                   |                          |                     |          |                                                 |            |         |           |         |       |            |          |                |                      |        |     |
|-------------------------------------------------------|-------|------|--------------------|-----------------------------------|--------------------------|---------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|----------------------|--------|-----|
| FREQUENCY                                             |       | Mode | Bandwidth<br>[MHz] | Maximum<br>Allowed<br>Power [dBm] | Conducted<br>Power [dBm] | Power<br>Drift [dB] | MPR [dB] | Device Serial<br>Number                         | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR<br>(1g) | Plot # |     |
| MHz                                                   | Ch.   |      |                    |                                   |                          |                     |          |                                                 |            |         |           |         |       |            | (W/kg)   |                | (W/kg)               |        |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 23.5                     | 22.63               | 0.00     | 0                                               | 84102      | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.189          | 1.222                | 0.231  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 22.5                     | 21.81               | -0.01    | 1                                               | 84102      | QPSK    | 25        | 0       | 10 mm | back       | 1:1      | 0.149          | 1.172                | 0.175  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 23.5                     | 22.63               | -0.06    | 0                                               | 84102      | QPSK    | 1         | 0       | 10 mm | front      | 1:1      | 0.241          | 1.222                | 0.295  | A27 |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 22.5                     | 21.81               | -0.02    | 1                                               | 84102      | QPSK    | 25        | 0       | 10 mm | front      | 1:1      | 0.192          | 1.172                | 0.225  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 23.5                     | 22.63               | 0.02     | 0                                               | 84102      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.130          | 1.222                | 0.159  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 22.5                     | 21.81               | 0.07     | 1                                               | 84102      | QPSK    | 25        | 0       | 10 mm | bottom     | 1:1      | 0.105          | 1.172                | 0.123  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 23.5                     | 22.63               | -0.08    | 0                                               | 84102      | QPSK    | 1         | 0       | 10 mm | right      | 1:1      | 0.121          | 1.222                | 0.148  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 22.5                     | 21.81               | -0.08    | 1                                               | 84102      | QPSK    | 25        | 0       | 10 mm | right      | 1:1      | 0.096          | 1.172                | 0.113  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 23.5                     | 22.63               | 0.20     | 0                                               | 84102      | QPSK    | 1         | 0       | 10 mm | left       | 1:1      | 0.037          | 1.222                | 0.045  |     |
| 707.50                                                | 23095 | Mid  | LTE Band 12        | 10                                | 22.5                     | 21.81               | -0.03    | 1                                               | 84102      | QPSK    | 25        | 0       | 10 mm | left       | 1:1      | 0.027          | 1.172                | 0.032  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak |       |      |                    |                                   |                          |                     |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |          |                |                      |        |     |
| Uncontrolled Exposure/General Population              |       |      |                    |                                   |                          |                     |          |                                                 |            |         |           |         |       |            |          |                |                      |        |     |

**Table 11-22**  
**LTE Band 13 Hotspot SAR**

| MEASUREMENT RESULTS                      |       |        |             |                 |                             |                       |                  |                      |                      |            |         |           |         |        |            |          |                |                   |        |
|------------------------------------------|-------|--------|-------------|-----------------|-----------------------------|-----------------------|------------------|----------------------|----------------------|------------|---------|-----------|---------|--------|------------|----------|----------------|-------------------|--------|
| FREQUENCY                                |       |        | Mode        | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB]             | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side   | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                      | Ch.   | (W/kg) |             |                 |                             |                       |                  |                      |                      |            |         |           |         |        |            | (W/kg)   |                |                   |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 23.5                        | 22.42                 | 0.01             | 0                    | 98443                | QPSK       | 1       | 25        | 10 mm   | back   | 1:1        | 0.345    | 1.282          | 0.442             |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 22.5                        | 20.92                 | -0.01            | 1                    | 98443                | QPSK       | 25      | 0         | 10 mm   | back   | 1:1        | 0.248    | 1.439          | 0.357             |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 23.5                        | 22.42                 | 0.04             | 0                    | 98443                | QPSK       | 1       | 25        | 10 mm   | front  | 1:1        | 0.401    | 1.282          | 0.514             | A29    |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 22.5                        | 20.92                 | 0.06             | 1                    | 98443                | QPSK       | 25      | 0         | 10 mm   | front  | 1:1        | 0.281    | 1.439          | 0.404             |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 23.5                        | 22.42                 | -0.02            | 0                    | 98443                | QPSK       | 1       | 25        | 10 mm   | bottom | 1:1        | 0.200    | 1.282          | 0.256             |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 22.5                        | 20.92                 | -0.02            | 1                    | 98443                | QPSK       | 25      | 0         | 10 mm   | bottom | 1:1        | 0.136    | 1.439          | 0.196             |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 23.5                        | 22.42                 | -0.01            | 0                    | 98443                | QPSK       | 1       | 25        | 10 mm   | right  | 1:1        | 0.156    | 1.282          | 0.200             |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 22.5                        | 20.92                 | 0.00             | 1                    | 98443                | QPSK       | 25      | 0         | 10 mm   | right  | 1:1        | 0.112    | 1.439          | 0.161             |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 23.5                        | 22.42                 | 0.15             | 0                    | 98443                | QPSK       | 1       | 25        | 10 mm   | left   | 1:1        | 0.060    | 1.282          | 0.077             |        |
| 782.00                                   | 23230 | Mid    | LTE Band 13 | 10              | 22.5                        | 20.92                 | -0.05            | 1                    | 98443                | QPSK       | 25      | 0         | 10 mm   | left   | 1:1        | 0.039    | 1.439          | 0.056             |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |       |        |             |                 |                             |                       |                  | Body                 |                      |            |         |           |         |        |            |          |                |                   |        |
| Spatial Peak                             |       |        |             |                 |                             |                       |                  | 1.6 W/kg (mW/g)      |                      |            |         |           |         |        |            |          |                |                   |        |
| Uncontrolled Exposure/General Population |       |        |             |                 |                             |                       |                  | averaged over 1 gram |                      |            |         |           |         |        |            |          |                |                   |        |

**Table 11-23**  
**LTE Band 5 (Cell) Hotspot SAR**

| MEASUREMENT RESULTS                      |       |      |                   |                             |                       |                  |          |                      |                      |            |         |           |         |       |            |          |                |                   |        |     |
|------------------------------------------|-------|------|-------------------|-----------------------------|-----------------------|------------------|----------|----------------------|----------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|-------------------|--------|-----|
| FREQUENCY                                |       | Mode | Bandwidth [MHz]   | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Ant. State           | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| MHz                                      | Ch.   |      |                   |                             |                       |                  |          |                      |                      |            |         |           |         |       |            | (W/kg)   |                | (W/kg)            |        |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | -0.04    | 0                    | 1                    | 85F64      | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.530          | 1.236             | 0.655  |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | -0.03    | 1                    | 1                    | 85F64      | QPSK    | 25        | 0       | 10 mm | back       | 1:1      | 0.391          | 1.358             | 0.531  |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | -0.05    | 0                    | 1                    | 85F64      | QPSK    | 1         | 0       | 10 mm | front      | 1:1      | 0.646          | 1.236             | 0.798  | A31 |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | -0.08    | 1                    | 1                    | 85F64      | QPSK    | 25        | 0       | 10 mm | front      | 1:1      | 0.440          | 1.358             | 0.598  |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | -0.02    | 0                    | 1                    | 85F64      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.259          | 1.236             | 0.320  |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | 0.01     | 1                    | 1                    | 85F64      | QPSK    | 25        | 0       | 10 mm | bottom     | 1:1      | 0.254          | 1.358             | 0.345  |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | -0.06    | 0                    | 1                    | 85F64      | QPSK    | 1         | 0       | 10 mm | right      | 1:1      | 0.291          | 1.236             | 0.360  |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | 0.00     | 1                    | 1                    | 85F64      | QPSK    | 25        | 0       | 10 mm | right      | 1:1      | 0.211          | 1.358             | 0.287  |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 25.0                  | 24.08            | -0.15    | 0                    | 1                    | 85F64      | QPSK    | 1         | 0       | 10 mm | left       | 1:1      | 0.072          | 1.236             | 0.089  |     |
| 836.50                                   | 20525 | Mid  | LTE Band 5 (Cell) | 10                          | 24.0                  | 22.67            | 0.13     | 1                    | 1                    | 85F64      | QPSK    | 25        | 0       | 10 mm | left       | 1:1      | 0.052          | 1.358             | 0.071  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |       |      |                   |                             |                       |                  |          | Body                 |                      |            |         |           |         |       |            |          |                |                   |        |     |
| Spatial Peak                             |       |      |                   |                             |                       |                  |          | 1.6 W/kg (mW/g)      |                      |            |         |           |         |       |            |          |                |                   |        |     |
| Uncontrolled Exposure/General Population |       |      |                   |                             |                       |                  |          | averaged over 1 gram |                      |            |         |           |         |       |            |          |                |                   |        |     |

|                                      |                                                                                     |                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  | <b>SAR EVALUATION REPORT</b>  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                          | DUT Type:<br>Portable Handset |                                                                                       | Page 67 of 95                   |

**Table 11-24**  
**LTE Band 26 (Cell) Hotspot SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                    |                                   |                          |                     |          |                                                 |            |         |           |         |       |            |          |                |                      |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|--------------------|-----------------------------------|--------------------------|---------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|----------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth<br>[MHz] | Maximum<br>Allowed<br>Power [dBm] | Conducted<br>Power [dBm] | Power<br>Drift [dB] | MPR [dB] | Device Serial<br>Number                         | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR<br>(1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                    |                                   |                          |                     |          |                                                 |            |         |           |         |       |            | (W/kg)   |                | (W/kg)               |        |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 23.5                     | 23.46               | 0.13     | 0                                               | 841C3      | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.418          | 1.009                | 0.422  | A33 |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 22.5                     | 22.30               | 0.03     | 1                                               | 841C3      | QPSK    | 36        | 0       | 10 mm | back       | 1:1      | 0.349          | 1.047                | 0.365  |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 23.5                     | 23.46               | 0.02     | 0                                               | 841C3      | QPSK    | 1         | 0       | 10 mm | front      | 1:1      | 0.443          | 1.009                | 0.447  |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 22.5                     | 22.30               | 0.09     | 1                                               | 841C3      | QPSK    | 36        | 0       | 10 mm | front      | 1:1      | 0.362          | 1.047                | 0.379  |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 23.5                     | 23.46               | 0.04     | 0                                               | 841C3      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.211          | 1.009                | 0.213  |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 22.5                     | 22.30               | -0.03    | 1                                               | 841C3      | QPSK    | 36        | 0       | 10 mm | bottom     | 1:1      | 0.161          | 1.047                | 0.169  |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 23.5                     | 23.46               | 0.07     | 0                                               | 841C3      | QPSK    | 1         | 0       | 10 mm | right      | 1:1      | 0.229          | 1.009                | 0.231  |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 22.5                     | 22.30               | -0.04    | 1                                               | 841C3      | QPSK    | 36        | 0       | 10 mm | right      | 1:1      | 0.184          | 1.047                | 0.193  |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 23.5                     | 23.46               | 0.17     | 0                                               | 841C3      | QPSK    | 1         | 0       | 10 mm | left       | 1:1      | 0.049          | 1.009                | 0.049  |     |
| 831.50                                                                                            | 26865 | Mid  | LTE Band 26 (Cell) | 15                                | 22.5                     | 22.30               | 0.09     | 1                                               | 841C3      | QPSK    | 36        | 0       | 10 mm | left       | 1:1      | 0.037          | 1.047                | 0.039  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                    |                                   |                          |                     |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |          |                |                      |        |     |

**Table 11-25**  
**LTE Band 4 (AWS) Hotspot SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                  |                             |                       |                  |          |                                                 |            |         |           |         |       |            |          |                |                   |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|-------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                            | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                  |                             |                       |                  |          |                                                 |            |         |           |         |       |            | (W/kg)   |                | (W/kg)            |        |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.85            | -0.05    | 0                                               | 841E0      | QPSK    | 1         | 50      | 10 mm | back       | 1:1      | 0.556          | 1.462             | 0.813  | A35 |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.86            | -0.03    | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | back       | 1:1      | 0.555          | 1.459             | 0.810  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.84            | 0.02     | 0                                               | 841E0      | QPSK    | 100       | 0       | 10 mm | back       | 1:1      | 0.531          | 1.466             | 0.778  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.85            | 0.03     | 0                                               | 841E0      | QPSK    | 1         | 50      | 10 mm | front      | 1:1      | 0.348          | 1.462             | 0.509  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.86            | 0.00     | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | front      | 1:1      | 0.338          | 1.459             | 0.493  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.85            | -0.06    | 0                                               | 841E0      | QPSK    | 1         | 50      | 10 mm | bottom     | 1:1      | 0.471          | 1.462             | 0.689  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.86            | -0.07    | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | bottom     | 1:1      | 0.459          | 1.459             | 0.670  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.85            | -0.04    | 0                                               | 841E0      | QPSK    | 1         | 50      | 10 mm | left       | 1:1      | 0.355          | 1.462             | 0.519  |     |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS) | 20                          | 21.5                  | 19.86            | 0.01     | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | left       | 1:1      | 0.349          | 1.459             | 0.509  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |          |                |                   |        |     |

**Table 11-26**  
**LTE Band 2 (PCS) Hotspot SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                  |                             |                       |                  |          |                                                 |            |         |           |         |       |            |          |                |                   |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|------------------|-----------------------------|-----------------------|------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|----------|----------------|-------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]  | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                            | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR (1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                  |                             |                       |                  |          |                                                 |            |         |           |         |       |            | (W/kg)   |                | (W/kg)            |        |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.5                  | 20.51            | -0.02    | 0                                               | 841E0      | QPSK    | 1         | 0       | 10 mm | back       | 1:1      | 0.436          | 1.256             | 0.548  | A37 |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.5                  | 20.48            | -0.02    | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | back       | 1:1      | 0.425          | 1.265             | 0.538  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.5                  | 20.51            | -0.04    | 0                                               | 841E0      | QPSK    | 1         | 0       | 10 mm | front      | 1:1      | 0.456          | 1.256             | 0.573  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.5                  | 20.48            | 0.06     | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | front      | 1:1      | 0.455          | 1.265             | 0.576  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.5                  | 20.51            | 0.02     | 0                                               | 841E0      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1      | 0.630          | 1.256             | 0.791  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.5                  | 20.48            | 0.03     | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | bottom     | 1:1      | 0.610          | 1.265             | 0.772  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.5                  | 20.51            | 0.00     | 0                                               | 841E0      | QPSK    | 1         | 0       | 10 mm | left       | 1:1      | 0.116          | 1.256             | 0.146  |     |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS) | 20                          | 21.5                  | 20.48            | 0.00     | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | left       | 1:1      | 0.108          | 1.265             | 0.137  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                  |                             |                       |                  |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |          |                |                   |        |     |

|                                      |                                                                                                                                                                                                        |                               |  |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  |  | Page 68 of 95                   |

**Table 11-27**  
**LTE Band 25 (PCS) Hotspot SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                   |                             |                       |                  |          |                                                 |            |         |           |         |       |            |         |                |                   |        |     |
|---------------------------------------------------------------------------------------------------|-------|------|-------------------|-----------------------------|-----------------------|------------------|----------|-------------------------------------------------|------------|---------|-----------|---------|-------|------------|---------|----------------|-------------------|--------|-----|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]   | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                            | Modulation | RB Size | RB Offset | Spacing | Side  | Duty Cycle | SAR(1g) | Scaling Factor | Reported SAR (1g) | Plot # |     |
| MHz                                                                                               | Ch.   |      |                   |                             |                       |                  |          |                                                 |            |         |           |         |       |            | (W/kg)  |                | (W/kg)            |        |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.73            | 0.06     | 0                                               | 841E0      | QPSK    | 1         | 0       | 10 mm | back       | 1:1     | 0.357          | 1.194             | 0.426  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.65            | -0.07    | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | back       | 1:1     | 0.356          | 1.216             | 0.433  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.73            | 0.01     | 0                                               | 841E0      | QPSK    | 1         | 0       | 10 mm | front      | 1:1     | 0.380          | 1.194             | 0.454  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.65            | 0.08     | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | front      | 1:1     | 0.379          | 1.216             | 0.461  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.73            | -0.05    | 0                                               | 841E0      | QPSK    | 1         | 0       | 10 mm | bottom     | 1:1     | 0.548          | 1.194             | 0.654  | A39 |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.65            | -0.03    | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | bottom     | 1:1     | 0.536          | 1.216             | 0.652  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.73            | 0.01     | 0                                               | 841E0      | QPSK    | 1         | 0       | 10 mm | left       | 1:1     | 0.096          | 1.194             | 0.115  |     |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.65            | 0.04     | 0                                               | 841E0      | QPSK    | 50        | 0       | 10 mm | left       | 1:1     | 0.087          | 1.216             | 0.106  |     |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                   |                             |                       |                  |          | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |            |         |           |         |       |            |         |                |                   |        |     |

**Table 11-28**  
**LTE Band 41 Hotspot SAR**

| MEASUREMENT RESULTS                      |       |          |             |                 |                             |                       |                  |                      |                      |            |         |           |         |        |            |         |                |                   |        |
|------------------------------------------|-------|----------|-------------|-----------------|-----------------------------|-----------------------|------------------|----------------------|----------------------|------------|---------|-----------|---------|--------|------------|---------|----------------|-------------------|--------|
| FREQUENCY                                |       |          | Mode        | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB]             | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side   | Duty Cycle | SAR(1g) | Scaling Factor | Reported SAR (1g) | Plot # |
| MHz                                      | Ch.   | (W/kg)   |             |                 |                             |                       |                  |                      |                      |            |         |           |         |        |            | (W/kg)  |                |                   |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 23.5                        | 23.43                 | 0.01             | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | back   | 1:1.58     | 0.440   | 1.016          | 0.447             |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 22.5                        | 22.33                 | 0.04             | 1                    | 84162                | QPSK       | 50      | 0         | 10 mm   | back   | 1:1.58     | 0.340   | 1.040          | 0.354             |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 23.5                        | 23.43                 | 0.13             | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | front  | 1:1.58     | 0.369   | 1.016          | 0.375             |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 22.5                        | 22.33                 | 0.07             | 1                    | 84162                | QPSK       | 50      | 0         | 10 mm   | front  | 1:1.58     | 0.291   | 1.040          | 0.303             |        |
| 2506.00                                  | 39750 | Low      | LTE Band 41 | 20              | 23.5                        | 22.86                 | -0.20            | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | bottom | 1:1.58     | 0.553   | 1.159          | 0.641             |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 23.5                        | 23.43                 | -0.07            | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | bottom | 1:1.58     | 0.775   | 1.016          | 0.787             |        |
| 2593.00                                  | 40620 | Mid      | LTE Band 41 | 20              | 23.5                        | 22.50                 | -0.02            | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | bottom | 1:1.58     | 0.871   | 1.259          | 1.097             |        |
| 2636.50                                  | 41055 | Mid-High | LTE Band 41 | 20              | 23.5                        | 22.39                 | -0.10            | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | bottom | 1:1.58     | 0.834   | 1.291          | 1.077             |        |
| 2680.00                                  | 41490 | High     | LTE Band 41 | 20              | 23.5                        | 22.90                 | -0.05            | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | bottom | 1:1.58     | 0.921   | 1.148          | 1.057             |        |
| 2506.00                                  | 39750 | Low      | LTE Band 41 | 20              | 22.5                        | 21.71                 | -0.03            | 1                    | 84162                | QPSK       | 50      | 0         | 10 mm   | bottom | 1:1.58     | 0.443   | 1.199          | 0.531             |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 22.5                        | 22.33                 | -0.01            | 1                    | 84162                | QPSK       | 50      | 0         | 10 mm   | bottom | 1:1.58     | 0.626   | 1.040          | 0.651             |        |
| 2593.00                                  | 40620 | Mid      | LTE Band 41 | 20              | 22.5                        | 21.54                 | -0.07            | 1                    | 84162                | QPSK       | 50      | 0         | 10 mm   | bottom | 1:1.58     | 0.704   | 1.247          | 0.878             |        |
| 2636.50                                  | 41055 | Mid-High | LTE Band 41 | 20              | 22.5                        | 21.32                 | -0.05            | 1                    | 84162                | QPSK       | 50      | 0         | 10 mm   | bottom | 1:1.58     | 0.670   | 1.312          | 0.879             |        |
| 2680.00                                  | 41490 | High     | LTE Band 41 | 20              | 22.5                        | 21.65                 | 0.01             | 1                    | 84162                | QPSK       | 50      | 0         | 10 mm   | bottom | 1:1.58     | 0.705   | 1.216          | 0.857             |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 22.5                        | 22.30                 | -0.01            | 1                    | 84162                | QPSK       | 100     | 0         | 10 mm   | bottom | 1:1.58     | 0.441   | 1.047          | 0.462             |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 23.5                        | 23.43                 | 0.17             | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | left   | 1:1.58     | 0.215   | 1.016          | 0.218             |        |
| 2549.50                                  | 40185 | Low-Md   | LTE Band 41 | 20              | 22.5                        | 22.33                 | 0.04             | 1                    | 84162                | QPSK       | 50      | 0         | 10 mm   | left   | 1:1.58     | 0.169   | 1.040          | 0.176             |        |
| 2680.00                                  | 41490 | High     | LTE Band 41 | 20              | 23.5                        | 22.90                 | -0.03            | 0                    | 84162                | QPSK       | 1       | 0         | 10 mm   | bottom | 1:1.58     | 0.936   | 1.148          | 1.075             | A41    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |       |          |             |                 |                             |                       |                  | Body                 |                      |            |         |           |         |        |            |         |                |                   |        |
| Spatial Peak                             |       |          |             |                 |                             |                       |                  | 1.6 W/kg (mW/g)      |                      |            |         |           |         |        |            |         |                |                   |        |
| Uncontrolled Exposure/General Population |       |          |             |                 |                             |                       |                  | averaged over 1 gram |                      |            |         |           |         |        |            |         |                |                   |        |

Blue entry represents variability measurement

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMN935F                          |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                   | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 69 of 95                          |

**Table 11-29  
WLAN Hotspot SAR**

| MEASUREMENT RESULTS                      |     |         |         |                 |                             |                       |                  |                      |                 |                      |                  |       |                |                       |          |                        |                             |                   |        |
|------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|----------------------|-----------------|----------------------|------------------|-------|----------------|-----------------------|----------|------------------------|-----------------------------|-------------------|--------|
| FREQUENCY                                |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing              | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Side  | Duty Cycle (%) | Peak SAR of Area Scan | SAR (1g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Reported SAR (1g) | Plot # |
| MHz                                      | Ch. |         |         |                 |                             |                       |                  |                      |                 |                      |                  |       |                | W/kg                  | (W/kg)   |                        |                             | (W/kg)            |        |
| 2437                                     | 6   | 802.11b | DSSS    | 22              | 19.5                        | 18.55                 | 0.14             | 10 mm                | 1               | 85F64                | 1                | back  | 98.9           | 0.853                 | 0.505    | 1.245                  | 1.011                       | 0.636             |        |
| 2437                                     | 6   | 802.11b | DSSS    | 22              | 19.5                        | 18.55                 | 0.10             | 10 mm                | 1               | 85F64                | 1                | front | 98.9           | 0.610                 | 0.428    | 1.245                  | 1.011                       | 0.539             |        |
| 2437                                     | 6   | 802.11b | DSSS    | 22              | 19.5                        | 18.55                 | 0.02             | 10 mm                | 1               | 85F64                | 1                | top   | 98.9           | 0.460                 | -        | 1.245                  | 1.011                       | -                 |        |
| 2437                                     | 6   | 802.11b | DSSS    | 22              | 19.5                        | 18.55                 | 0.11             | 10 mm                | 1               | 85F64                | 1                | left  | 98.9           | 0.385                 | -        | 1.245                  | 1.011                       | -                 |        |
| 2462                                     | 11  | 802.11b | DSSS    | 22              | 19.5                        | 19.21                 | -0.05            | 10 mm                | 2               | 85F64                | 1                | back  | 99.9           | 0.744                 | 0.511    | 1.069                  | 1.001                       | 0.547             | A43    |
| 2462                                     | 11  | 802.11b | DSSS    | 22              | 19.5                        | 19.21                 | 0.17             | 10 mm                | 2               | 85F64                | 1                | front | 99.9           | 0.290                 | 0.222    | 1.069                  | 1.001                       | 0.238             |        |
| 2462                                     | 11  | 802.11b | DSSS    | 22              | 19.5                        | 19.21                 | 0.08             | 10 mm                | 2               | 85F64                | 1                | top   | 99.9           | 0.294                 | 0.239    | 1.069                  | 1.001                       | 0.256             |        |
| 2462                                     | 11  | 802.11b | DSSS    | 22              | 19.5                        | 19.21                 | 0.10             | 10 mm                | 2               | 85F64                | 1                | left  | 99.9           | 0.272                 | -        | 1.069                  | 1.001                       | -                 |        |
| 2437                                     | 6   | 802.11n | OFDM    | 20              | 17.5                        | 16.83                 | 0.15             | 10 mm                | MIMO            | 85F64                | 13               | back  | 98.5           | 0.131                 | 0.102    | 1.178                  | 1.015                       | 0.122             |        |
| 2437                                     | 6   | 802.11n | OFDM    | 20              | 17.5                        | 16.83                 | -0.15            | 10 mm                | MIMO            | 85F64                | 13               | front | 98.5           | 0.080                 | -        | 1.178                  | 1.015                       | -                 |        |
| 2437                                     | 6   | 802.11n | OFDM    | 20              | 17.5                        | 16.83                 | 0.13             | 10 mm                | MIMO            | 85F64                | 13               | top   | 98.5           | 0.061                 | -        | 1.178                  | 1.015                       | -                 |        |
| 2437                                     | 6   | 802.11n | OFDM    | 20              | 17.5                        | 16.83                 | 0.00             | 10 mm                | MIMO            | 85F64                | 13               | left  | 98.5           | 0.001                 | -        | 1.178                  | 1.015                       | -                 |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 17.13                 | 0.13             | 10 mm                | 1               | 05C28                | 6                | back  | 98.6           | 0.255                 | -        | 1.089                  | 1.014                       | -                 |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 17.13                 | -0.14            | 10 mm                | 1               | 05C28                | 6                | front | 98.6           | 0.259                 | 0.158    | 1.089                  | 1.014                       | 0.174             | A45    |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 17.13                 | 0.18             | 10 mm                | 1               | 05C28                | 6                | top   | 98.6           | 0.171                 | -        | 1.089                  | 1.014                       | -                 |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 17.13                 | 0.13             | 10 mm                | 1               | 05C28                | 6                | left  | 98.6           | 0.075                 | -        | 1.089                  | 1.014                       | -                 |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 16.75                 | 0.18             | 10 mm                | 2               | 05C28                | 6                | back  | 98.6           | 0.184                 | 0.088    | 1.189                  | 1.014                       | 0.106             |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 16.75                 | 0.15             | 10 mm                | 2               | 05C28                | 6                | front | 98.6           | 0.159                 | -        | 1.189                  | 1.014                       | -                 |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 16.75                 | 0.14             | 10 mm                | 2               | 05C28                | 6                | top   | 98.6           | 0.106                 | -        | 1.189                  | 1.014                       | -                 |        |
| 5825                                     | 165 | 802.11a | OFDM    | 20              | 17.5                        | 16.75                 | 0.18             | 10 mm                | 2               | 05C28                | 6                | left  | 98.6           | 0.049                 | -        | 1.189                  | 1.014                       | -                 |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |     |         |         |                 |                             |                       |                  | Body                 |                 |                      |                  |       |                |                       |          |                        |                             |                   |        |
| Spatial Peak                             |     |         |         |                 |                             |                       |                  | 1.6 W/kg (mW/g)      |                 |                      |                  |       |                |                       |          |                        |                             |                   |        |
| Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  | averaged over 1 gram |                 |                      |                  |       |                |                       |          |                        |                             |                   |        |

## 11.4 Standalone Phablet SAR Data

**Table 11-30  
UMTS Phablet SAR Data**

| MEASUREMENT RESULTS                      |      |           |         |                             |                       |                  |                        |                      |            |        |           |                |                    |        |
|------------------------------------------|------|-----------|---------|-----------------------------|-----------------------|------------------|------------------------|----------------------|------------|--------|-----------|----------------|--------------------|--------|
| FREQUENCY                                |      | Mode      | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                | Device Serial Number | Duty Cycle | Side   | SAR (10g) | Scaling Factor | Reported SAR (10g) | Plot # |
| MHz                                      | Ch.  |           |         |                             |                       |                  |                        |                      |            |        | (W/kg)    |                | (W/kg)             |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | -0.06            | 7 mm                   | 84162                | 1:1        | back   | 0.662     | 1.122          | 0.743              |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | -0.09            | 5 mm                   | 84162                | 1:1        | front  | 0.898     | 1.122          | 1.008              |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | -0.03            | 9 mm                   | 84162                | 1:1        | bottom | 0.701     | 1.122          | 0.787              |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 24.5                        | 24.00                 | -0.01            | 0 mm                   | 84162                | 1:1        | left   | 1.020     | 1.122          | 1.144              |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 21.5                        | 21.17                 | 0.00             | 0 mm                   | 841E0                | 1:1        | back   | 1.540     | 1.079          | 1.662              |        |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 21.5                        | 21.17                 | 0.00             | 0 mm                   | 841E0                | 1:1        | front  | 1.570     | 1.079          | 1.694              | A46    |
| 1732.40                                  | 1412 | UMTS 1750 | RMC     | 21.5                        | 21.17                 | -0.04            | 0 mm                   | 841E0                | 1:1        | bottom | 1.480     | 1.079          | 1.597              |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | 0.02             | 7 mm                   | 84102                | 1:1        | back   | 0.629     | 1.183          | 0.744              |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | -0.07            | 5 mm                   | 84102                | 1:1        | front  | 0.942     | 1.183          | 1.114              |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | 0.00             | 9 mm                   | 84102                | 1:1        | bottom | 0.747     | 1.183          | 0.884              |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 24.5                        | 23.77                 | -0.01            | 0 mm                   | 84102                | 1:1        | left   | 0.728     | 1.183          | 0.861              |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 21.5                        | 21.02                 | -0.07            | 0 mm                   | 841E0                | 1:1        | back   | 1.150     | 1.117          | 1.285              |        |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 21.5                        | 21.02                 | 0.03             | 0 mm                   | 841E0                | 1:1        | front  | 1.280     | 1.117          | 1.430              | A47    |
| 1907.60                                  | 9538 | UMTS 1900 | RMC     | 21.5                        | 21.02                 | -0.11            | 0 mm                   | 841E0                | 1:1        | bottom | 0.974     | 1.117          | 1.088              |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |      |           |         |                             |                       |                  | Phablet                |                      |            |        |           |                |                    |        |
| Spatial Peak                             |      |           |         |                             |                       |                  | 4.0 W/kg (mW/g)        |                      |            |        |           |                |                    |        |
| Uncontrolled Exposure/General Population |      |           |         |                             |                       |                  | averaged over 10 grams |                      |            |        |           |                |                    |        |

|                                      |                                                                                                                                                                                                        |                               |  |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  |  | Page 70 of 95                   |



**Table 11-31  
LTE Phablet SAR**

| MEASUREMENT RESULTS                                                                               |       |      |                   |                             |                       |                  |          |                                                      |            |         |           |         |      |            |                 |                |                           |        |
|---------------------------------------------------------------------------------------------------|-------|------|-------------------|-----------------------------|-----------------------|------------------|----------|------------------------------------------------------|------------|---------|-----------|---------|------|------------|-----------------|----------------|---------------------------|--------|
| FREQUENCY                                                                                         |       | Mode | Bandwidth [MHz]   | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number                                 | Modulation | RB Size | RB Offset | Spacing | Side | Duty Cycle | SAR(10g) (W/kg) | Scaling Factor | Reported SAR (10g) (W/kg) | Plot # |
| MHz                                                                                               | Ch.   |      |                   |                             |                       |                  |          |                                                      |            |         |           |         |      |            |                 |                |                           |        |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 24.5                  | 23.81            | -0.03    | 0                                                    | 84162      | QPSK    | 1         | 0       | 7 mm | back       | 1:1             | 0.698          | 1.172                     | 0.818  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 23.5                  | 22.87            | -0.01    | 1                                                    | 84162      | QPSK    | 50        | 25      | 7 mm | back       | 1:1             | 0.554          | 1.156                     | 0.640  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 24.5                  | 23.81            | -0.08    | 0                                                    | 84162      | QPSK    | 1         | 0       | 5 mm | front      | 1:1             | 0.910          | 1.172                     | 1.067  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 23.5                  | 22.87            | -0.06    | 1                                                    | 84162      | QPSK    | 50        | 25      | 5 mm | front      | 1:1             | 0.716          | 1.156                     | 0.828  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 24.5                  | 23.81            | 0.00     | 0                                                    | 84162      | QPSK    | 1         | 0       | 9 mm | bottom     | 1:1             | 0.744          | 1.172                     | 0.872  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 23.5                  | 22.87            | 0.00     | 1                                                    | 84162      | QPSK    | 50        | 25      | 9 mm | bottom     | 1:1             | 0.600          | 1.156                     | 0.694  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 24.5                  | 23.81            | -0.01    | 0                                                    | 84162      | QPSK    | 1         | 0       | 0 mm | left       | 1:1             | 1.080          | 1.172                     | 1.266  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 23.5                  | 22.87            | -0.02    | 1                                                    | 84162      | QPSK    | 50        | 25      | 0 mm | left       | 1:1             | 0.867          | 1.156                     | 1.002  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.85            | -0.04    | 0                                                    | 841E0      | QPSK    | 1         | 50      | 0 mm | back       | 1:1             | 1.700          | 1.462                     | 2.485  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.86            | -0.12    | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | back       | 1:1             | 1.770          | 1.459                     | 2.582  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.84            | 0.05     | 0                                                    | 841E0      | QPSK    | 100       | 0       | 0 mm | back       | 1:1             | 1.760          | 1.466                     | 2.580  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.85            | 0.00     | 0                                                    | 841E0      | QPSK    | 1         | 50      | 0 mm | front      | 1:1             | 1.910          | 1.462                     | 2.792  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.86            | 0.08     | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | front      | 1:1             | 1.770          | 1.459                     | 2.582  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.84            | -0.03    | 0                                                    | 841E0      | QPSK    | 100       | 0       | 0 mm | front      | 1:1             | 1.750          | 1.466                     | 2.566  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.85            | -0.14    | 0                                                    | 841E0      | QPSK    | 1         | 50      | 0 mm | bottom     | 1:1             | 1.760          | 1.462                     | 2.573  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.86            | -0.09    | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | bottom     | 1:1             | 1.800          | 1.459                     | 2.626  |
| 1732.50                                                                                           | 20175 | Mid  | LTE Band 4 (AWS)  | 20                          | 21.5                  | 19.84            | -0.04    | 0                                                    | 841E0      | QPSK    | 100       | 0       | 0 mm | bottom     | 1:1             | 1.770          | 1.466                     | 2.595  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 24.5                  | 23.21            | -0.02    | 0                                                    | 84102      | QPSK    | 1         | 0       | 7 mm | back       | 1:1             | 0.715          | 1.346                     | 0.962  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 23.5                  | 22.19            | -0.04    | 1                                                    | 84102      | QPSK    | 50        | 0       | 7 mm | back       | 1:1             | 0.554          | 1.352                     | 0.749  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 24.5                  | 23.21            | -0.07    | 0                                                    | 84102      | QPSK    | 1         | 0       | 5 mm | front      | 1:1             | 0.886          | 1.346                     | 1.193  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 23.5                  | 22.19            | 0.01     | 1                                                    | 84102      | QPSK    | 50        | 0       | 5 mm | front      | 1:1             | 0.689          | 1.352                     | 0.932  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 24.5                  | 23.21            | -0.03    | 0                                                    | 84102      | QPSK    | 1         | 0       | 9 mm | bottom     | 1:1             | 0.732          | 1.346                     | 0.985  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 23.5                  | 22.19            | -0.04    | 1                                                    | 84102      | QPSK    | 50        | 0       | 9 mm | bottom     | 1:1             | 0.578          | 1.352                     | 0.781  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 24.5                  | 23.21            | -0.01    | 0                                                    | 84102      | QPSK    | 1         | 0       | 0 mm | left       | 1:1             | 0.790          | 1.346                     | 1.063  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 23.5                  | 22.19            | -0.04    | 1                                                    | 84102      | QPSK    | 50        | 0       | 0 mm | left       | 1:1             | 0.590          | 1.352                     | 0.798  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 21.5                  | 20.51            | 0.05     | 0                                                    | 841E0      | QPSK    | 1         | 0       | 0 mm | back       | 1:1             | 1.100          | 1.256                     | 1.382  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 21.5                  | 20.48            | 0.08     | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | back       | 1:1             | 1.090          | 1.265                     | 1.379  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 21.5                  | 20.51            | 0.09     | 0                                                    | 841E0      | QPSK    | 1         | 0       | 0 mm | front      | 1:1             | 1.110          | 1.256                     | 1.394  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 21.5                  | 20.48            | 0.09     | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | front      | 1:1             | 1.080          | 1.265                     | 1.366  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 21.5                  | 20.51            | -0.02    | 0                                                    | 841E0      | QPSK    | 1         | 0       | 0 mm | bottom     | 1:1             | 0.903          | 1.256                     | 1.134  |
| 1900.00                                                                                           | 19100 | High | LTE Band 2 (PCS)  | 20                          | 21.5                  | 20.48            | -0.07    | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | bottom     | 1:1             | 0.901          | 1.265                     | 1.140  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 23.5                  | 22.30            | -0.04    | 0                                                    | 84102      | QPSK    | 1         | 0       | 7 mm | back       | 1:1             | 0.559          | 1.318                     | 0.737  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 22.5                  | 21.22            | -0.01    | 1                                                    | 84102      | QPSK    | 50        | 0       | 7 mm | back       | 1:1             | 0.439          | 1.343                     | 0.590  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 23.5                  | 22.30            | -0.02    | 0                                                    | 84102      | QPSK    | 1         | 0       | 5 mm | front      | 1:1             | 0.743          | 1.318                     | 0.979  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 22.5                  | 21.22            | 0.01     | 1                                                    | 84102      | QPSK    | 50        | 0       | 5 mm | front      | 1:1             | 0.576          | 1.343                     | 0.774  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 23.5                  | 22.30            | 0.00     | 0                                                    | 84102      | QPSK    | 1         | 0       | 9 mm | bottom     | 1:1             | 0.633          | 1.318                     | 0.834  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 22.5                  | 21.22            | -0.03    | 1                                                    | 84102      | QPSK    | 50        | 0       | 9 mm | bottom     | 1:1             | 0.475          | 1.343                     | 0.638  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 23.5                  | 22.30            | 0.06     | 0                                                    | 84102      | QPSK    | 1         | 0       | 0 mm | left       | 1:1             | 0.565          | 1.318                     | 0.745  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 22.5                  | 21.22            | -0.06    | 1                                                    | 84102      | QPSK    | 50        | 0       | 0 mm | left       | 1:1             | 0.445          | 1.343                     | 0.598  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.73            | 0.08     | 0                                                    | 841E0      | QPSK    | 1         | 0       | 0 mm | back       | 1:1             | 0.928          | 1.194                     | 1.108  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.65            | -0.02    | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | back       | 1:1             | 0.909          | 1.216                     | 1.105  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.73            | -0.04    | 0                                                    | 841E0      | QPSK    | 1         | 0       | 0 mm | front      | 1:1             | 0.929          | 1.194                     | 1.109  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.65            | 0.08     | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | front      | 1:1             | 0.915          | 1.216                     | 1.113  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.73            | 0.03     | 0                                                    | 841E0      | QPSK    | 1         | 0       | 0 mm | bottom     | 1:1             | 0.760          | 1.194                     | 0.907  |
| 1905.00                                                                                           | 26590 | High | LTE Band 25 (PCS) | 20                          | 20.5                  | 19.65            | -0.06    | 0                                                    | 841E0      | QPSK    | 50        | 0       | 0 mm | bottom     | 1:1             | 0.737          | 1.216                     | 0.896  |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |       |      |                   |                             |                       |                  |          | Phablet<br>4.0 W/kg (mW/g)<br>averaged over 10 grams |            |         |           |         |      |            |                 |                |                           |        |

|                                      |                                                                                                                                                                                                        |                               |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  | Page 71 of 95                   |

**Table 11-32  
WLAN Phablet SAR**

| MEASUREMENT RESULTS                      |     |         |         |                 |                             |                       |                  |                        |                 |                      |                  |       |                |                       |           |                        |                             |                    |        |
|------------------------------------------|-----|---------|---------|-----------------|-----------------------------|-----------------------|------------------|------------------------|-----------------|----------------------|------------------|-------|----------------|-----------------------|-----------|------------------------|-----------------------------|--------------------|--------|
| FREQUENCY                                |     | Mode    | Service | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing                | Antenna Config. | Device Serial Number | Data Rate (Mbps) | Side  | Duty Cycle (%) | Peak SAR of Area Scan | SAR (10g) | Scaling Factor (Power) | Scaling Factor (Duty Cycle) | Reported SAR (10g) | Plot # |
| MHz                                      | Ch. |         |         |                 |                             |                       |                  |                        |                 |                      |                  |       |                | W/kg                  | (W/kg)    |                        |                             | (W/kg)             |        |
| 5280                                     | 56  | 802.11a | OFDM    | 20              | 17.5                        | 16.96                 | 0.03             | 0 mm                   | 1               | 05C28                | 6                | back  | 98.6           | 29.092                | 1.670     | 1.132                  | 1.014                       | 1.917              | A51    |
| 5280                                     | 56  | 802.11a | OFDM    | 20              | 17.5                        | 16.96                 | -0.12            | 0 mm                   | 1               | 05C28                | 6                | front | 98.6           | 2.128                 | 0.349     | 1.132                  | 1.014                       | 0.401              |        |
| 5280                                     | 56  | 802.11a | OFDM    | 20              | 17.5                        | 16.96                 | 0.19             | 0 mm                   | 1               | 05C28                | 6                | top   | 98.6           | 1.582                 | -         | 1.132                  | 1.014                       | -                  |        |
| 5280                                     | 56  | 802.11a | OFDM    | 20              | 17.5                        | 16.96                 | 0.15             | 0 mm                   | 1               | 05C28                | 6                | left  | 98.6           | 2.063                 | -         | 1.132                  | 1.014                       | -                  |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 17.5                        | 17.27                 | 0.06             | 0 mm                   | 2               | 05C28                | 6                | back  | 98.6           | 4.888                 | 0.686     | 1.054                  | 1.014                       | 0.733              |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 17.5                        | 17.27                 | -0.11            | 0 mm                   | 2               | 05C28                | 6                | front | 98.6           | 2.771                 | -         | 1.054                  | 1.014                       | -                  |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 17.5                        | 17.27                 | 0.13             | 0 mm                   | 2               | 05C28                | 6                | top   | 98.6           | 1.541                 | -         | 1.054                  | 1.014                       | -                  |        |
| 5260                                     | 52  | 802.11a | OFDM    | 20              | 17.5                        | 17.27                 | 0.14             | 0 mm                   | 2               | 05C28                | 6                | left  | 98.6           | 0.896                 | -         | 1.054                  | 1.014                       | -                  |        |
| 5300                                     | 60  | 802.11n | OFDM    | 20              | 17.5                        | 16.86                 | 0.06             | 0 mm                   | MIMO            | 05C28                | 13               | back  | 98.6           | 18.466                | 0.957     | 1.202                  | 1.014                       | 1.166              |        |
| 5300                                     | 60  | 802.11n | OFDM    | 20              | 17.5                        | 16.86                 | 0.11             | 0 mm                   | MIMO            | 05C28                | 13               | front | 98.6           | 2.142                 | 0.262     | 1.202                  | 1.014                       | 0.319              |        |
| 5300                                     | 60  | 802.11n | OFDM    | 20              | 17.5                        | 16.86                 | 0.13             | 0 mm                   | MIMO            | 05C28                | 13               | top   | 98.6           | 0.645                 | -         | 1.202                  | 1.014                       | -                  |        |
| 5300                                     | 60  | 802.11n | OFDM    | 20              | 17.5                        | 16.86                 | 0.13             | 0 mm                   | MIMO            | 05C28                | 13               | left  | 98.6           | 0.857                 | -         | 1.202                  | 1.014                       | -                  |        |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 17.5                        | 17.30                 | -0.02            | 0 mm                   | 1               | 05C28                | 6                | back  | 98.6           | 15.955                | 0.922     | 1.047                  | 1.014                       | 0.979              |        |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 17.5                        | 17.30                 | -0.06            | 0 mm                   | 1               | 05C28                | 6                | front | 98.6           | 3.554                 | -         | 1.047                  | 1.014                       | -                  |        |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 17.5                        | 17.30                 | 0.15             | 0 mm                   | 1               | 05C28                | 6                | top   | 98.6           | 2.265                 | -         | 1.047                  | 1.014                       | -                  |        |
| 5720                                     | 144 | 802.11a | OFDM    | 20              | 17.5                        | 17.30                 | 0.13             | 0 mm                   | 1               | 05C28                | 6                | left  | 98.6           | 0.827                 | -         | 1.047                  | 1.014                       | -                  |        |
| 5500                                     | 100 | 802.11a | OFDM    | 20              | 17.5                        | 17.20                 | 0.12             | 0 mm                   | 2               | 05C28                | 6                | back  | 98.6           | 5.165                 | 0.805     | 1.072                  | 1.014                       | 0.875              |        |
| 5500                                     | 100 | 802.11a | OFDM    | 20              | 17.5                        | 17.20                 | 0.13             | 0 mm                   | 2               | 05C28                | 6                | front | 98.6           | 3.127                 | -         | 1.072                  | 1.014                       | -                  |        |
| 5500                                     | 100 | 802.11a | OFDM    | 20              | 17.5                        | 17.20                 | 0.14             | 0 mm                   | 2               | 05C28                | 6                | top   | 98.6           | 1.244                 | -         | 1.072                  | 1.014                       | -                  |        |
| 5500                                     | 100 | 802.11a | OFDM    | 20              | 17.5                        | 17.20                 | 0.14             | 0 mm                   | 2               | 05C28                | 6                | left  | 98.6           | 0.243                 | -         | 1.072                  | 1.014                       | -                  |        |
| 5600                                     | 120 | 802.11n | OFDM    | 20              | 17.5                        | 17.26                 | 0.03             | 0 mm                   | MIMO            | 05C28                | 13               | back  | 98.6           | 5.792                 | 0.491     | 1.067                  | 1.014                       | 0.531              |        |
| 5600                                     | 120 | 802.11n | OFDM    | 20              | 17.5                        | 17.26                 | 0.12             | 0 mm                   | MIMO            | 05C28                | 13               | front | 98.6           | 1.943                 | -         | 1.067                  | 1.014                       | -                  |        |
| 5600                                     | 120 | 802.11n | OFDM    | 20              | 17.5                        | 17.26                 | 0.16             | 0 mm                   | MIMO            | 05C28                | 13               | top   | 98.6           | 0.747                 | -         | 1.067                  | 1.014                       | -                  |        |
| 5600                                     | 120 | 802.11n | OFDM    | 20              | 17.5                        | 17.26                 | -0.20            | 0 mm                   | MIMO            | 05C28                | 13               | left  | 98.6           | 0.482                 | -         | 1.067                  | 1.014                       | -                  |        |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |     |         |         |                 |                             |                       |                  | Phablet                |                 |                      |                  |       |                |                       |           |                        |                             |                    |        |
| Spatial Peak                             |     |         |         |                 |                             |                       |                  | 4.0 W/kg (mW/g)        |                 |                      |                  |       |                |                       |           |                        |                             |                    |        |
| Uncontrolled Exposure/General Population |     |         |         |                 |                             |                       |                  | averaged over 10 grams |                 |                      |                  |       |                |                       |           |                        |                             |                    |        |

## 11.5 SAR Test Notes

### General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was  $\leq 1.2$  W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg for 1g SAR and 2.0 W/kg for 10g SAR. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMN935F                          |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                   | <b>DUT Type:</b><br>Portable Handset | Page 72 of 95                                                                         |                                        |

9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.
11. This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.
12. This device supports dynamic antenna tuning for some bands. Per FCC Guidance, SAR was measured according to the normally required SAR measurement configurations with the tuner active. The auto-tune state determined by the device was verified before and after each SAR measurement and is listed in the tables above. Please see Section 14 for supplemental data.

#### GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

#### UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 73 of 95                          |

#### LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported (scaled) for LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.

#### WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.6.6 for more information.
4. Per KDB Publication 248227 D01v02r02, MIMO SAR for 2.4 GHz Hotspot and 5 GHz Phablet exposure conditions were measured with both antennas transmitting simultaneously at the specified maximum output power in MIMO mode following the initial test configuration procedures. MIMO SAR for other bands/exposure conditions was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06. Please see Section 12 for complete analysis.
5. When the maximum reported 1g averaged SAR is  $\leq 0.8$  W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was  $\leq 1.20$  W/kg or all test channels were measured.
6. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.
7. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
8. This device supports MIMO operations for IEEE 802.11a/g using Cyclic Delay Diversity (CDD) only. Antenna 1 and Antenna 2 will never transmit at the same time while operating in CDD mode (switched transmission only). Since IEEE 802.11n/ac MIMO modes additionally support Spatial Diversity Multiplexing, only IEEE 802.11n/ac modes were considered for MIMO SAR.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 74 of 95                          |

## 12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

### 12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

### 12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is  $\leq 1.6$  W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equations must be used to estimate the standalone 1g and 10g SAR, respectively, for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{18.75} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1**  
**Estimated SAR**

| Mode      | Frequency | Maximum Allowed Power | Separation Distance (Body) | Estimated SAR (Body) | Separation Distance (Phablet) | Estimated SAR (Phablet) |
|-----------|-----------|-----------------------|----------------------------|----------------------|-------------------------------|-------------------------|
|           | [MHz]     | [dBm]                 | [mm]                       | [W/kg]               | [mm]                          | [W/kg]                  |
| Bluetooth | 2480      | 11.50                 | 15                         | 0.196                | 5                             | 0.235                   |

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

(\*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB Publication 248227, the worst case WLAN SAR result for the exposure was used for simultaneous transmission analysis.

Per FCC KDB Publication 648474 D04 Handset SAR v01r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-“)

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMN935F                          |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                   | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 75 of 95                          |

## 12.3 Head SAR Simultaneous Transmission Analysis

**Table 12-2**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |       |              |
|--------------------|--------------------|---------------------|-------------------------------|-------------------------------|---------------------|-------|--------------|
|                    |                    | 1                   | 2                             | 3                             | 1+2                 | 1+3   | 1+2+3        |
| Head SAR           | GSM 850            | 0.229               | 0.549                         | 0.505                         | 0.778               | 0.734 | 1.283        |
|                    | UMTS 850           | 0.191               | 0.549                         | 0.505                         | 0.740               | 0.696 | 1.245        |
|                    | UMTS 1750          | 0.340               | 0.549                         | 0.505                         | 0.889               | 0.845 | 1.394        |
|                    | GSM 1900           | 0.122               | 0.549                         | 0.505                         | 0.671               | 0.627 | 1.176        |
|                    | UMTS 1900          | 0.270               | 0.549                         | 0.505                         | 0.819               | 0.775 | 1.324        |
|                    | LTE Band 12        | 0.078               | 0.549                         | 0.505                         | 0.627               | 0.583 | 1.132        |
|                    | LTE Band 13        | 0.114               | 0.549                         | 0.505                         | 0.663               | 0.619 | 1.168        |
|                    | LTE Band 5 (Cell)  | 0.203               | 0.549                         | 0.505                         | 0.752               | 0.708 | 1.257        |
|                    | LTE Band 26 (Cell) | 0.128               | 0.549                         | 0.505                         | 0.677               | 0.633 | 1.182        |
|                    | LTE Band 4 (AWS)   | 0.393               | 0.549                         | 0.505                         | 0.942               | 0.898 | <b>1.447</b> |
|                    | LTE Band 2 (PCS)   | 0.315               | 0.549                         | 0.505                         | 0.864               | 0.820 | 1.369        |
|                    | LTE Band 25 (PCS)  | 0.192               | 0.549                         | 0.505                         | 0.741               | 0.697 | 1.246        |
|                    | LTE Band 41        | 0.080               | 0.549                         | 0.505                         | 0.629               | 0.585 | 1.134        |

**Table 12-3**  
**Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |       |              |
|--------------------|--------------------|---------------------|-----------------------------|-----------------------------|---------------------|-------|--------------|
|                    |                    | 1                   | 2                           | 3                           | 1+2                 | 1+3   | 1+2+3        |
| Head SAR           | GSM 850            | 0.229               | 0.325                       | 0.640                       | 0.554               | 0.869 | 1.194        |
|                    | UMTS 850           | 0.191               | 0.325                       | 0.640                       | 0.516               | 0.831 | 1.156        |
|                    | UMTS 1750          | 0.340               | 0.325                       | 0.640                       | 0.665               | 0.980 | 1.305        |
|                    | GSM 1900           | 0.122               | 0.325                       | 0.640                       | 0.447               | 0.762 | 1.087        |
|                    | UMTS 1900          | 0.270               | 0.325                       | 0.640                       | 0.595               | 0.910 | 1.235        |
|                    | LTE Band 12        | 0.078               | 0.325                       | 0.640                       | 0.403               | 0.718 | 1.043        |
|                    | LTE Band 13        | 0.114               | 0.325                       | 0.640                       | 0.439               | 0.754 | 1.079        |
|                    | LTE Band 5 (Cell)  | 0.203               | 0.325                       | 0.640                       | 0.528               | 0.843 | 1.168        |
|                    | LTE Band 26 (Cell) | 0.128               | 0.325                       | 0.640                       | 0.453               | 0.768 | 1.093        |
|                    | LTE Band 4 (AWS)   | 0.393               | 0.325                       | 0.640                       | 0.718               | 1.033 | <b>1.358</b> |
|                    | LTE Band 2 (PCS)   | 0.315               | 0.325                       | 0.640                       | 0.640               | 0.955 | 1.280        |
|                    | LTE Band 25 (PCS)  | 0.192               | 0.325                       | 0.640                       | 0.517               | 0.832 | 1.157        |
|                    | LTE Band 41        | 0.080               | 0.325                       | 0.640                       | 0.405               | 0.720 | 1.045        |

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 76 of 95                          |



**Table 12-4**  
**Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Held to Ear)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|--------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                    | 1                   | 2                             | 3                           | 1+2+3        |
| Head SAR           | GSM 850            | 0.229               | 0.549                         | 0.640                       | 1.418        |
|                    | UMTS 850           | 0.191               | 0.549                         | 0.640                       | 1.380        |
|                    | UMTS 1750          | 0.340               | 0.549                         | 0.640                       | 1.529        |
|                    | GSM 1900           | 0.122               | 0.549                         | 0.640                       | 1.311        |
|                    | UMTS 1900          | 0.270               | 0.549                         | 0.640                       | 1.459        |
|                    | LTE Band 12        | 0.078               | 0.549                         | 0.640                       | 1.267        |
|                    | LTE Band 13        | 0.114               | 0.549                         | 0.640                       | 1.303        |
|                    | LTE Band 5 (Cell)  | 0.203               | 0.549                         | 0.640                       | 1.392        |
|                    | LTE Band 26 (Cell) | 0.128               | 0.549                         | 0.640                       | 1.317        |
|                    | LTE Band 4 (AWS)   | 0.393               | 0.549                         | 0.640                       | <b>1.582</b> |
|                    | LTE Band 2 (PCS)   | 0.315               | 0.549                         | 0.640                       | 1.504        |
|                    | LTE Band 25 (PCS)  | 0.192               | 0.549                         | 0.640                       | 1.381        |
|                    | LTE Band 41        | 0.080               | 0.549                         | 0.640                       | 1.269        |

**Table 12-5**  
**Simultaneous Transmission Scenario with 2.4 GHz Ant 2 and 5 GHz Ant 1 WLAN (Held to Ear)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|--------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                    | 1                   | 2                             | 3                           | 1+2+3        |
| Head SAR           | GSM 850            | 0.229               | 0.505                         | 0.325                       | 1.059        |
|                    | UMTS 850           | 0.191               | 0.505                         | 0.325                       | 1.021        |
|                    | UMTS 1750          | 0.340               | 0.505                         | 0.325                       | 1.170        |
|                    | GSM 1900           | 0.122               | 0.505                         | 0.325                       | 0.952        |
|                    | UMTS 1900          | 0.270               | 0.505                         | 0.325                       | 1.100        |
|                    | LTE Band 12        | 0.078               | 0.505                         | 0.325                       | 0.908        |
|                    | LTE Band 13        | 0.114               | 0.505                         | 0.325                       | 0.944        |
|                    | LTE Band 5 (Cell)  | 0.203               | 0.505                         | 0.325                       | 1.033        |
|                    | LTE Band 26 (Cell) | 0.128               | 0.505                         | 0.325                       | 0.958        |
|                    | LTE Band 4 (AWS)   | 0.393               | 0.505                         | 0.325                       | <b>1.223</b> |
|                    | LTE Band 2 (PCS)   | 0.315               | 0.505                         | 0.325                       | 1.145        |
|                    | LTE Band 25 (PCS)  | 0.192               | 0.505                         | 0.325                       | 1.022        |
|                    | LTE Band 41        | 0.080               | 0.505                         | 0.325                       | 0.910        |

|                                             |                                                                                                                                                                                                        |                                      |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  | Page 77 of 95                          |

## 12.4 Body-Worn Simultaneous Transmission Analysis

**Table 12-6**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |       |              |
|--------------------|--------------------|---------------------|-------------------------------|-------------------------------|---------------------|-------|--------------|
|                    |                    | 1                   | 2                             | 3                             | 1+2                 | 1+3   | 1+2+3        |
| Body-Worn          | GSM 850            | 0.491               | 0.281                         | 0.218                         | 0.772               | 0.709 | 0.990        |
|                    | UMTS 850           | 0.449               | 0.281                         | 0.218                         | 0.730               | 0.667 | 0.948        |
|                    | UMTS 1750          | 0.507               | 0.281                         | 0.218                         | 0.788               | 0.725 | 1.006        |
|                    | GSM 1900           | 0.520               | 0.281                         | 0.218                         | 0.801               | 0.738 | 1.019        |
|                    | UMTS 1900          | 0.477               | 0.281                         | 0.218                         | 0.758               | 0.695 | 0.976        |
|                    | LTE Band 12        | 0.152               | 0.281                         | 0.218                         | 0.433               | 0.370 | 0.651        |
|                    | LTE Band 13        | 0.303               | 0.281                         | 0.218                         | 0.584               | 0.521 | 0.802        |
|                    | LTE Band 5 (Cell)  | 0.471               | 0.281                         | 0.218                         | 0.752               | 0.689 | 0.970        |
|                    | LTE Band 26 (Cell) | 0.295               | 0.281                         | 0.218                         | 0.576               | 0.513 | 0.794        |
|                    | LTE Band 4 (AWS)   | 0.574               | 0.281                         | 0.218                         | 0.855               | 0.792 | 1.073        |
|                    | LTE Band 2 (PCS)   | 0.672               | 0.281                         | 0.218                         | 0.953               | 0.890 | <b>1.171</b> |
|                    | LTE Band 25 (PCS)  | 0.517               | 0.281                         | 0.218                         | 0.798               | 0.735 | 1.016        |
|                    | LTE Band 41        | 0.224               | 0.281                         | 0.218                         | 0.505               | 0.442 | 0.723        |

**Table 12-7**  
**Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.5 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |       |              |
|--------------------|--------------------|---------------------|-----------------------------|-----------------------------|---------------------|-------|--------------|
|                    |                    | 1                   | 2                           | 3                           | 1+2                 | 1+3   | 1+2+3        |
| Body-Worn          | GSM 850            | 0.491               | 0.354                       | 0.080                       | 0.845               | 0.571 | 0.925        |
|                    | UMTS 850           | 0.449               | 0.354                       | 0.080                       | 0.803               | 0.529 | 0.883        |
|                    | UMTS 1750          | 0.507               | 0.354                       | 0.080                       | 0.861               | 0.587 | 0.941        |
|                    | GSM 1900           | 0.520               | 0.354                       | 0.080                       | 0.874               | 0.600 | 0.954        |
|                    | UMTS 1900          | 0.477               | 0.354                       | 0.080                       | 0.831               | 0.557 | 0.911        |
|                    | LTE Band 12        | 0.152               | 0.354                       | 0.080                       | 0.506               | 0.232 | 0.586        |
|                    | LTE Band 13        | 0.303               | 0.354                       | 0.080                       | 0.657               | 0.383 | 0.737        |
|                    | LTE Band 5 (Cell)  | 0.471               | 0.354                       | 0.080                       | 0.825               | 0.551 | 0.905        |
|                    | LTE Band 26 (Cell) | 0.295               | 0.354                       | 0.080                       | 0.649               | 0.375 | 0.729        |
|                    | LTE Band 4 (AWS)   | 0.574               | 0.354                       | 0.080                       | 0.928               | 0.654 | 1.008        |
|                    | LTE Band 2 (PCS)   | 0.672               | 0.354                       | 0.080                       | 1.026               | 0.752 | <b>1.106</b> |
|                    | LTE Band 25 (PCS)  | 0.517               | 0.354                       | 0.080                       | 0.871               | 0.597 | 0.951        |
|                    | LTE Band 41        | 0.224               | 0.354                       | 0.080                       | 0.578               | 0.304 | 0.658        |

|                                             |                                                                                                                                                                                                        |                                      |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  | Page 78 of 95                          |



**Table 12-8**  
**Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Body-Worn at 1.5 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|--------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                    | 1                   | 2                             | 3                           | 1+2+3        |
| Body-Worn          | GSM 850            | 0.491               | 0.281                         | 0.080                       | 0.852        |
|                    | UMTS 850           | 0.449               | 0.281                         | 0.080                       | 0.810        |
|                    | UMTS 1750          | 0.507               | 0.281                         | 0.080                       | 0.868        |
|                    | GSM 1900           | 0.520               | 0.281                         | 0.080                       | 0.881        |
|                    | UMTS 1900          | 0.477               | 0.281                         | 0.080                       | 0.838        |
|                    | LTE Band 12        | 0.152               | 0.281                         | 0.080                       | 0.513        |
|                    | LTE Band 13        | 0.303               | 0.281                         | 0.080                       | 0.664        |
|                    | LTE Band 5 (Cell)  | 0.471               | 0.281                         | 0.080                       | 0.832        |
|                    | LTE Band 26 (Cell) | 0.295               | 0.281                         | 0.080                       | 0.656        |
|                    | LTE Band 4 (AWS)   | 0.574               | 0.281                         | 0.080                       | 0.935        |
|                    | LTE Band 2 (PCS)   | 0.672               | 0.281                         | 0.080                       | <b>1.033</b> |
|                    | LTE Band 25 (PCS)  | 0.517               | 0.281                         | 0.080                       | 0.878        |
|                    | LTE Band 41        | 0.224               | 0.281                         | 0.080                       | 0.585        |

**Table 12-9**  
**Simultaneous Transmission Scenario with 2.4 GHz Ant 2 and 5 GHz Ant 1 WLAN (Body-Worn at 1.5 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|--------------------|---------------------|-------------------------------|-----------------------------|--------------|
|                    |                    | 1                   | 2                             | 3                           | 1+2+3        |
| Body-Worn          | GSM 850            | 0.491               | 0.218                         | 0.354                       | 1.063        |
|                    | UMTS 850           | 0.449               | 0.218                         | 0.354                       | 1.021        |
|                    | UMTS 1750          | 0.507               | 0.218                         | 0.354                       | 1.079        |
|                    | GSM 1900           | 0.520               | 0.218                         | 0.354                       | 1.092        |
|                    | UMTS 1900          | 0.477               | 0.218                         | 0.354                       | 1.049        |
|                    | LTE Band 12        | 0.152               | 0.218                         | 0.354                       | 0.724        |
|                    | LTE Band 13        | 0.303               | 0.218                         | 0.354                       | 0.875        |
|                    | LTE Band 5 (Cell)  | 0.471               | 0.218                         | 0.354                       | 1.043        |
|                    | LTE Band 26 (Cell) | 0.295               | 0.218                         | 0.354                       | 0.867        |
|                    | LTE Band 4 (AWS)   | 0.574               | 0.218                         | 0.354                       | 1.146        |
|                    | LTE Band 2 (PCS)   | 0.672               | 0.218                         | 0.354                       | <b>1.244</b> |
|                    | LTE Band 25 (PCS)  | 0.517               | 0.218                         | 0.354                       | 1.089        |
|                    | LTE Band 41        | 0.224               | 0.218                         | 0.354                       | 0.796        |

|                                             |                                                                                                                                                                                                        |                                      |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  | Page 79 of 95                          |

**Table 12-10**  
**Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|--------------------|---------------------|----------------------|--------------|
|                    |                    | 1                   | 2                    | 1+2          |
| Body-Worn          | GSM 850            | 0.491               | 0.196                | 0.687        |
|                    | UMTS 850           | 0.449               | 0.196                | 0.645        |
|                    | UMTS 1750          | 0.507               | 0.196                | 0.703        |
|                    | GSM 1900           | 0.520               | 0.196                | 0.716        |
|                    | UMTS 1900          | 0.477               | 0.196                | 0.673        |
|                    | LTE Band 12        | 0.152               | 0.196                | 0.348        |
|                    | LTE Band 13        | 0.303               | 0.196                | 0.499        |
|                    | LTE Band 5 (Cell)  | 0.471               | 0.196                | 0.667        |
|                    | LTE Band 26 (Cell) | 0.295               | 0.196                | 0.491        |
|                    | LTE Band 4 (AWS)   | 0.574               | 0.196                | 0.770        |
|                    | LTE Band 2 (PCS)   | 0.672               | 0.196                | <b>0.868</b> |
|                    | LTE Band 25 (PCS)  | 0.517               | 0.196                | 0.713        |
|                    | LTE Band 41        | 0.224               | 0.196                | 0.420        |

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 80 of 95                          |

## 12.5 Hotspot SAR Simultaneous Transmission Analysis

**Table 12-11**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | $\Sigma$ SAR (W/kg) |                 |
|--------------------|--------------------|---------------------|-------------------------------|-------------------------------|---------------------|-----------------|
|                    |                    | 1                   | 2                             | 3                             | 1+2                 | 1+3             |
| Hotspot SAR        | GPRS 850           | 0.924               | 0.636                         | 0.547                         | <b>1.560</b>        | 1.471           |
|                    | UMTS 850           | 0.720               | 0.636                         | 0.547                         | 1.356               | 1.267           |
|                    | UMTS 1750          | 0.667               | 0.636                         | 0.547                         | 1.303               | 1.214           |
|                    | GPRS 1900          | 1.002               | 0.636                         | 0.547                         | See Table 12-12     | 1.549           |
|                    | UMTS 1900          | 0.774               | 0.636                         | 0.547                         | 1.410               | 1.321           |
|                    | LTE Band 12        | 0.295               | 0.636                         | 0.547                         | 0.931               | 0.842           |
|                    | LTE Band 13        | 0.514               | 0.636                         | 0.547                         | 1.150               | 1.061           |
|                    | LTE Band 5 (Cell)  | 0.798               | 0.636                         | 0.547                         | 1.434               | 1.345           |
|                    | LTE Band 26 (Cell) | 0.447               | 0.636                         | 0.547                         | 1.083               | 0.994           |
|                    | LTE Band 4 (AWS)   | 0.813               | 0.636                         | 0.547                         | 1.449               | 1.360           |
|                    | LTE Band 2 (PCS)   | 0.791               | 0.636                         | 0.547                         | 1.427               | 1.338           |
|                    | LTE Band 25 (PCS)  | 0.654               | 0.636                         | 0.547                         | 1.290               | 1.201           |
|                    | LTE Band 41        | 1.097               | 0.636                         | 0.547                         | See Table 12-12     | See Table 12-12 |

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN MIMO SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|--------------------|--------------------|---------------------|------------------------------|---------------------|
|                    |                    | 1                   | 2                            | 1+2                 |
| Hotspot SAR        | GPRS 850           | 0.924               | 0.122                        | 1.046               |
|                    | UMTS 850           | 0.720               | 0.122                        | 0.842               |
|                    | UMTS 1750          | 0.667               | 0.122                        | 0.789               |
|                    | GPRS 1900          | 1.002               | 0.122                        | 1.124               |
|                    | UMTS 1900          | 0.774               | 0.122                        | 0.896               |
|                    | LTE Band 12        | 0.295               | 0.122                        | 0.417               |
|                    | LTE Band 13        | 0.514               | 0.122                        | 0.636               |
|                    | LTE Band 5 (Cell)  | 0.798               | 0.122                        | 0.920               |
|                    | LTE Band 26 (Cell) | 0.447               | 0.122                        | 0.569               |
|                    | LTE Band 4 (AWS)   | 0.813               | 0.122                        | 0.935               |
|                    | LTE Band 2 (PCS)   | 0.791               | 0.122                        | 0.913               |
|                    | LTE Band 25 (PCS)  | 0.654               | 0.122                        | 0.776               |
|                    | LTE Band 41        | 1.097               | 0.122                        | <b>1.219</b>        |

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
| Page 81 of 95                               |                                                                                                                                                                                                        |                                        |

**Table 12-12**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)**

| Simult Tx   | Configuration | GPRS 1900 SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|-------------|---------------|----------------------|-------------------------------|--------------|
|             |               | 1                    | 2                             | 1+2          |
| Hotspot SAR | Back          | 0.575                | 0.636                         | 1.211        |
|             | Front         | 0.532                | 0.539                         | 1.071        |
|             | Top           | -                    | 0.636*                        | 0.636        |
|             | Bottom        | 1.002                | -                             | 1.002        |
|             | Left          | 0.123                | 0.636*                        | 0.759        |

| Simult Tx   | Configuration | LTE Band 41 SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |       |
|-------------|---------------|------------------------|-------------------------------|-------------------------------|--------------|-------|
|             |               | 1                      | 2                             | 3                             | 1+2          | 1+3   |
| Hotspot SAR | Back          | 0.447                  | 0.636                         | 0.547                         | 1.083        | 0.994 |
|             | Front         | 0.375                  | 0.539                         | 0.238                         | 0.914        | 0.613 |
|             | Top           | -                      | 0.636*                        | 0.256                         | 0.636        | 0.256 |
|             | Bottom        | 1.097                  | -                             | -                             | 1.097        | 1.097 |
|             | Left          | 0.218                  | 0.636*                        | 0.547*                        | 0.854        | 0.765 |

**Table 12-13**  
**Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |       |              |
|--------------------|--------------------|---------------------|-----------------------------|-----------------------------|--------------|-------|--------------|
|                    |                    | 1                   | 2                           | 3                           | 1+2          | 1+3   | 1+2+3        |
| Hotspot SAR        | GPRS 850           | 0.924               | 0.174                       | 0.106                       | 1.098        | 1.030 | 1.204        |
|                    | UMTS 850           | 0.720               | 0.174                       | 0.106                       | 0.894        | 0.826 | 1.000        |
|                    | UMTS 1750          | 0.667               | 0.174                       | 0.106                       | 0.841        | 0.773 | 0.947        |
|                    | GPRS 1900          | 1.002               | 0.174                       | 0.106                       | 1.176        | 1.108 | 1.282        |
|                    | UMTS 1900          | 0.774               | 0.174                       | 0.106                       | 0.948        | 0.880 | 1.054        |
|                    | LTE Band 12        | 0.295               | 0.174                       | 0.106                       | 0.469        | 0.401 | 0.575        |
|                    | LTE Band 13        | 0.514               | 0.174                       | 0.106                       | 0.688        | 0.620 | 0.794        |
|                    | LTE Band 5 (Cell)  | 0.798               | 0.174                       | 0.106                       | 0.972        | 0.904 | 1.078        |
|                    | LTE Band 26 (Cell) | 0.447               | 0.174                       | 0.106                       | 0.621        | 0.553 | 0.727        |
|                    | LTE Band 4 (AWS)   | 0.813               | 0.174                       | 0.106                       | 0.987        | 0.919 | 1.093        |
|                    | LTE Band 2 (PCS)   | 0.791               | 0.174                       | 0.106                       | 0.965        | 0.897 | 1.071        |
|                    | LTE Band 25 (PCS)  | 0.654               | 0.174                       | 0.106                       | 0.828        | 0.760 | 0.934        |
|                    | LTE Band 41        | 1.097               | 0.174                       | 0.106                       | 1.271        | 1.203 | <b>1.377</b> |

|                                      |                                                                                                                                                                                                        |                               |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  | Page 82 of 95                   |

**Table 12-14**  
**Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Hotspot at 1.0 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg)    |
|--------------------|--------------------|---------------------|-------------------------------|-----------------------------|-----------------|
|                    |                    | 1                   | 2                             | 3                           | 1+2+3           |
| Hotspot SAR        | GPRS 850           | 0.924               | 0.636                         | 0.106                       | See Table 12-15 |
|                    | UMTS 850           | 0.720               | 0.636                         | 0.106                       | 1.462           |
|                    | UMTS 1750          | 0.667               | 0.636                         | 0.106                       | 1.409           |
|                    | GPRS 1900          | 1.002               | 0.636                         | 0.106                       | See Table 12-15 |
|                    | UMTS 1900          | 0.774               | 0.636                         | 0.106                       | 1.516           |
|                    | LTE Band 12        | 0.295               | 0.636                         | 0.106                       | 1.037           |
|                    | LTE Band 13        | 0.514               | 0.636                         | 0.106                       | 1.256           |
|                    | LTE Band 5 (Cell)  | 0.798               | 0.636                         | 0.106                       | 1.540           |
|                    | LTE Band 26 (Cell) | 0.447               | 0.636                         | 0.106                       | 1.189           |
|                    | LTE Band 4 (AWS)   | 0.813               | 0.636                         | 0.106                       | <b>1.555</b>    |
|                    | LTE Band 2 (PCS)   | 0.791               | 0.636                         | 0.106                       | 1.533           |
|                    | LTE Band 25 (PCS)  | 0.654               | 0.636                         | 0.106                       | 1.396           |
|                    | LTE Band 41        | 1.097               | 0.636                         | 0.106                       | See Table 12-15 |

**Table 12-15**  
**Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Hotspot at 1.0 cm)**

| Simult Tx   | Configuration | GPRS 850 SAR (W/kg)    | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|-------------|---------------|------------------------|-------------------------------|-----------------------------|--------------|
|             |               | 1                      | 2                             | 3                           | 1+2+3        |
| Hotspot SAR | Back          | 0.852                  | 0.636                         | 0.106                       | <b>1.594</b> |
|             | Front         | 0.924                  | 0.539                         | 0.106*                      | 1.569        |
|             | Top           | -                      | 0.636*                        | 0.106*                      | 0.742        |
|             | Bottom        | 0.464                  | -                             | -                           | 0.464        |
|             | Right         | 0.364                  | -                             | -                           | 0.364        |
|             | Left          | 0.088                  | 0.636*                        | 0.106*                      | 0.830        |
| Simult Tx   | Configuration | GPRS 1900 SAR (W/kg)   | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|             |               | 1                      | 2                             | 3                           | 1+2+3        |
| Hotspot SAR | Back          | 0.575                  | 0.636                         | 0.106                       | <b>1.317</b> |
|             | Front         | 0.532                  | 0.539                         | 0.106*                      | 1.177        |
|             | Top           | -                      | 0.636*                        | 0.106*                      | 0.742        |
|             | Bottom        | 1.002                  | -                             | -                           | 1.002        |
|             | Right         | -                      | -                             | -                           | -            |
|             | Left          | 0.123                  | 0.636*                        | 0.106*                      | 0.865        |
| Simult Tx   | Configuration | LTE Band 41 SAR (W/kg) | 2.4 GHz WLAN Ant 1 SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|             |               | 1                      | 2                             | 3                           | 1+2+3        |
| Hotspot SAR | Back          | 0.447                  | 0.636                         | 0.106                       | <b>1.189</b> |
|             | Front         | 0.375                  | 0.539                         | 0.106*                      | 1.020        |
|             | Top           | -                      | 0.636*                        | 0.106*                      | 0.742        |
|             | Bottom        | 1.097                  | -                             | -                           | 1.097        |
|             | Right         | -                      | -                             | -                           | -            |
|             | Left          | 0.218                  | 0.636*                        | 0.106*                      | 0.960        |

|                                      |                                                                                                                                                                                                        |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset   |
| Page 83 of 95                        |                                                                                                                                                                                                        |                                 |

**Table 12-16**  
**Simultaneous Transmission Scenario with 2.4 GHz Ant 2 and 5 GHz Ant 1 WLAN (Hotspot at 1.0 cm)**

| Exposure Condition | Mode               | 2G/3G/4G SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg)    |
|--------------------|--------------------|---------------------|-------------------------------|-----------------------------|-----------------|
|                    |                    | 1                   | 2                             | 3                           | 1+2+3           |
| Hotspot SAR        | GPRS 850           | 0.924               | 0.547                         | 0.174                       | See Table 12-17 |
|                    | UMTS 850           | 0.720               | 0.547                         | 0.174                       | 1.441           |
|                    | UMTS 1750          | 0.667               | 0.547                         | 0.174                       | 1.388           |
|                    | GPRS 1900          | 1.002               | 0.547                         | 0.174                       | See Table 12-17 |
|                    | UMTS 1900          | 0.774               | 0.547                         | 0.174                       | 1.495           |
|                    | LTE Band 12        | 0.295               | 0.547                         | 0.174                       | 1.016           |
|                    | LTE Band 13        | 0.514               | 0.547                         | 0.174                       | 1.235           |
|                    | LTE Band 5 (Cell)  | 0.798               | 0.547                         | 0.174                       | 1.519           |
|                    | LTE Band 26 (Cell) | 0.447               | 0.547                         | 0.174                       | 1.168           |
|                    | LTE Band 4 (AWS)   | 0.813               | 0.547                         | 0.174                       | <b>1.534</b>    |
|                    | LTE Band 2 (PCS)   | 0.791               | 0.547                         | 0.174                       | 1.512           |
|                    | LTE Band 25 (PCS)  | 0.654               | 0.547                         | 0.174                       | 1.375           |
|                    | LTE Band 41        | 1.097               | 0.547                         | 0.174                       | See Table 12-17 |

**Table 12-17**  
**Simultaneous Transmission Scenario with 2.4 GHz Ant 2 and 5 GHz Ant 1 WLAN (Hotspot at 1.0 cm)**

| Simult Tx   | Configuration | GPRS 850 SAR (W/kg)    | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|-------------|---------------|------------------------|-------------------------------|-----------------------------|--------------|
|             |               | 1                      | 2                             | 3                           | 1+2+3        |
| Hotspot SAR | Back          | 0.852                  | 0.547                         | 0.174*                      | <b>1.573</b> |
|             | Front         | 0.924                  | 0.238                         | 0.174                       | 1.336        |
|             | Top           | -                      | 0.256                         | 0.174*                      | 0.430        |
|             | Bottom        | 0.464                  | -                             | -                           | 0.464        |
|             | Right         | 0.364                  | -                             | -                           | 0.364        |
|             | Left          | 0.088                  | 0.547*                        | 0.174*                      | 0.809        |
| Simult Tx   | Configuration | GPRS 1900 SAR (W/kg)   | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|             |               | 1                      | 2                             | 3                           | 1+2+3        |
| Hotspot SAR | Back          | 0.575                  | 0.547                         | 0.174*                      | <b>1.296</b> |
|             | Front         | 0.532                  | 0.238                         | 0.174                       | 0.944        |
|             | Top           | -                      | 0.256                         | 0.174*                      | 0.430        |
|             | Bottom        | 1.002                  | -                             | -                           | 1.002        |
|             | Right         | 0.123                  | 0.547*                        | 0.174*                      | 0.844        |
|             | Left          | 0.123                  | 0.547*                        | 0.174*                      | 0.844        |
| Simult Tx   | Configuration | LTE Band 41 SAR (W/kg) | 2.4 GHz WLAN Ant 2 SAR (W/kg) | 5 GHz WLAN Ant 1 SAR (W/kg) | Σ SAR (W/kg) |
|             |               | 1                      | 2                             | 3                           | 1+2+3        |
| Hotspot SAR | Back          | 0.447                  | 0.547                         | 0.174*                      | <b>1.168</b> |
|             | Front         | 0.375                  | 0.238                         | 0.174                       | 0.787        |
|             | Top           | -                      | 0.256                         | 0.174*                      | 0.430        |
|             | Bottom        | 1.097                  | -                             | -                           | 1.097        |
|             | Right         | 0.218                  | 0.547*                        | 0.174*                      | 0.939        |
|             | Left          | 0.218                  | 0.547*                        | 0.174*                      | 0.939        |

|                                      |                                                                                                                                                                                                        |                               |  |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               |  | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset |  | Page 84 of 95                   |

## 12.6 Phablet SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore no further analysis was required to for 2.4Ghz WLAN Phablet Simultaneous Transmission Analysis.

**Table 12-18**  
**Simultaneous Transmission Scenario - 5 GHz WLAN Ant 1**

| Simult Tx   | Configuration | UMTS<br>1750 SAR<br>(W/kg) | 5 GHz<br>WLAN Ant<br>1 SAR<br>(W/kg) | Σ SAR<br>(W/kg) | Simult Tx   | Configuration | UMTS<br>1900 SAR<br>(W/kg) | 5 GHz<br>WLAN Ant<br>1 SAR<br>(W/kg) | Σ SAR<br>(W/kg) |
|-------------|---------------|----------------------------|--------------------------------------|-----------------|-------------|---------------|----------------------------|--------------------------------------|-----------------|
|             |               | 1                          | 2                                    | 1+2             |             |               | 1                          | 2                                    | 1+2             |
| Phablet SAR | Back          | 1.662                      | 1.917                                | <b>3.579</b>    | Phablet SAR | Back          | 1.285                      | 1.917                                | <b>3.202</b>    |
|             | Front         | 1.694                      | 0.401                                | 2.095           |             | Front         | 1.430                      | 0.401                                | 1.831           |
|             | Top           | -                          | 1.917*                               | 1.917           |             | Top           | -                          | 1.917*                               | 1.917           |
|             | Bottom        | 1.597                      | -                                    | 1.597           |             | Bottom        | 1.088                      | -                                    | 1.088           |
|             | Left          | 1.144                      | 1.917*                               | 3.061           |             | Left          | 0.861                      | 1.917*                               | 2.778           |

| Simult Tx   | Configuration | LTE Band<br>4 (AWS)<br>SAR<br>(W/kg) | 5 GHz<br>WLAN Ant<br>1 SAR<br>(W/kg) | Σ SAR<br>(W/kg) | SPLSR |
|-------------|---------------|--------------------------------------|--------------------------------------|-----------------|-------|
|             |               | 1                                    | 2                                    | 1+2             | 1+2   |
| Phablet SAR | Back          | 2.582                                | 1.917                                | See Note 1      | 0.07  |
|             | Front         | 2.792                                | 0.401                                | <b>3.193</b>    | N/A   |
|             | Top           | -                                    | 1.917*                               | 1.917           | N/A   |
|             | Bottom        | 2.626                                | -                                    | 2.626           | N/A   |
|             | Left          | 1.266                                | 1.917*                               | 3.183           | N/A   |

| Simult Tx   | Configuration | LTE Band<br>2 (PCS)<br>SAR<br>(W/kg) | 5 GHz<br>WLAN Ant<br>1 SAR<br>(W/kg) | Σ SAR<br>(W/kg) |
|-------------|---------------|--------------------------------------|--------------------------------------|-----------------|
|             |               | 1                                    | 2                                    | 1+2             |
| Phablet SAR | Back          | 1.382                                | 1.917                                | <b>3.299</b>    |
|             | Front         | 1.394                                | 0.401                                | 1.795           |
|             | Top           | -                                    | 1.917*                               | 1.917           |
|             | Bottom        | 1.140                                | -                                    | 1.140           |
|             | Left          | 1.063                                | 1.917*                               | 2.980           |

| Simult Tx   | Configuration | LTE Band<br>25 (PCS)<br>SAR<br>(W/kg) | 5 GHz<br>WLAN Ant<br>1 SAR<br>(W/kg) | Σ SAR<br>(W/kg) |
|-------------|---------------|---------------------------------------|--------------------------------------|-----------------|
|             |               | 1                                     | 2                                    | 1+2             |
| Phablet SAR | Back          | 1.108                                 | 1.917                                | <b>3.025</b>    |
|             | Front         | 1.113                                 | 0.401                                | 1.514           |
|             | Top           | -                                     | 1.917*                               | 1.917           |
|             | Bottom        | 0.907                                 | -                                    | 0.907           |
|             | Left          | 0.745                                 | 1.917*                               | 2.662           |

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
| Page 85 of 95                               |                                                                                                                                                                                                        |                                        |

**Table 12-19**  
**Simultaneous Transmission Scenario - 5 GHz WLAN Ant 2**

| Exposure Condition | Mode              | 3G/4G SAR (W/kg) | 5 GHz WLAN Ant 2 SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|------------------|-----------------------------|--------------|
|                    |                   | 1                | 2                           | 1+2          |
| Phablet SAR        | UMTS 1750         | 1.694            | 0.875                       | 2.569        |
|                    | UMTS 1900         | 1.430            | 0.875                       | 2.305        |
|                    | LTE Band 4 (AWS)  | 2.792            | 0.875                       | <b>3.667</b> |
|                    | LTE Band 2 (PCS)  | 1.394            | 0.875                       | 2.269        |
|                    | LTE Band 25 (PCS) | 1.113            | 0.875                       | 1.988        |

**Table 12-20**  
**Simultaneous Transmission Scenario - 5 GHz WLAN MIMO**

| Exposure Condition | Mode              | 3G/4G SAR (W/kg) | 5 GHz WLAN MIMO SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|------------------|----------------------------|--------------|
|                    |                   | 1                | 2                          | 1+2          |
| Phablet SAR        | UMTS 1750         | 1.694            | 1.166                      | 2.860        |
|                    | UMTS 1900         | 1.430            | 1.166                      | 2.596        |
|                    | LTE Band 4 (AWS)  | 2.792            | 1.166                      | <b>3.958</b> |
|                    | LTE Band 2 (PCS)  | 1.394            | 1.166                      | 2.560        |
|                    | LTE Band 25 (PCS) | 1.113            | 1.166                      | 2.279        |

**Table 12-21**  
**Simultaneous Transmission Scenario - Bluetooth**

| Exposure Condition | Mode              | 3G/4G SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |
|--------------------|-------------------|------------------|----------------------|--------------|
|                    |                   | 1                | 2                    | 1+2          |
| Phablet SAR        | UMTS 1750         | 1.694            | 0.235                | 1.929        |
|                    | UMTS 1900         | 1.430            | 0.235                | 1.665        |
|                    | LTE Band 4 (AWS)  | 2.792            | 0.235                | <b>3.027</b> |
|                    | LTE Band 2 (PCS)  | 1.394            | 0.235                | 1.629        |
|                    | LTE Band 25 (PCS) | 1.113            | 0.235                | 1.348        |

**Notes:**

1. No evaluation was performed to determine the aggregate 10g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.10 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.
2. For SAR summation, the highest reported SAR across all test distances was used as the most conservative evaluation for simultaneous transmission analysis for each device edge.

|                                             |                                                                                                                                                                                                        |                                      |  |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset |  | Page 86 of 95                          |



## 12.7 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 4 W/kg for 10g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 87 of 95                          |

## 13 SAR MEASUREMENT VARIABILITY

### 13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is  $\geq 0.80$  W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was  $> 1.20$  or when the original or repeated measurement was  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .
- 4) Repeated measurements are not required when the original highest measured SAR is  $< 0.80$  W/kg
- 5) When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

**Table 13-1**  
**Body SAR Measurement Variability Results**

| BODY VARIABILITY RESULTS                 |           |       |                               |                         |                 |        |                      |                   |                       |       |                       |       |                       |
|------------------------------------------|-----------|-------|-------------------------------|-------------------------|-----------------|--------|----------------------|-------------------|-----------------------|-------|-----------------------|-------|-----------------------|
| Band                                     | FREQUENCY |       | Mode                          | Service                 | # of Time Slots | Side   | Spacing              | Measured SAR (1g) | 1st Repeated SAR (1g) | Ratio | 2nd Repeated SAR (1g) | Ratio | 3rd Repeated SAR (1g) |
|                                          | MHz       | Ch.   |                               |                         |                 |        |                      | (W/kg)            | (W/kg)                |       | (W/kg)                |       | (W/kg)                |
| 835                                      | 848.80    | 251   | GSM850                        | GPRS                    | 4               | front  | 10 mm                | 0.836             | 0.841                 | 1.01  | N/A                   | N/A   | N/A                   |
| 2600                                     | 2680.00   | 41490 | LTE Band 41, 20 MHz Bandwidth | QPSK, 1 RB, 0 RB Offset | N/A             | bottom | 10 mm                | 0.921             | 0.936                 | 1.02  | N/A                   | N/A   | N/A                   |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |           |       |                               |                         |                 |        | Body                 |                   |                       |       |                       |       |                       |
| Spatial Peak                             |           |       |                               |                         |                 |        | 1.6 W/kg (mW/g)      |                   |                       |       |                       |       |                       |
| Uncontrolled Exposure/General Population |           |       |                               |                         |                 |        | averaged over 1 gram |                   |                       |       |                       |       |                       |

### 13.2 Measurement Uncertainty

The measured SAR was  $< 1.5$  W/kg for 1g and  $< 3.75$  W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 88 of 95                   |

## 14 ADDITIONAL TUNER TESTING PER FCC GUIDANCE

The following test procedures were followed to demonstrate that the SAR results in Section 11 represented the appropriate SAR test conditions. For bands with dynamic tuning implemented, SAR was measured according to the required FCC SAR test procedures with the dynamic tuner active to allow the device to automatically tune to the antenna state for the respective RF exposure test configurations. Additional single point SAR time-sweep measurements were evaluated for other tuner states to determine that the other tuner configurations would result in equivalent or lower SAR values. The additional tuner hardware has no influence to the antenna characteristics, other than impedance matching.

To evaluate all of the tuner states, the 25 tuner states were divided evenly among band, mode and exposure combinations so that at least one single point SAR measurement was measured among the configurations. Single point time-sweep measurements were performed at the peak SAR location determined by the zoom scan of the configuration with the highest reported SAR for each combination. While inserting and removing the USB cable between single point SAR measurements, the device was ensured to capture the same physical point SAR that generated the highest SAR. The SAR probe remained stationary at the same position throughout the entire series of single point measurements for each combination.

The operational description contains more information about the design and implementation of the dynamic antenna tuning.

**Table 14-1  
Supplemental SAR Data**

| Supplemental Head SAR Data                  |             |                                    |             | Supplemental Body SAR Data                  |            |                                    |            |
|---------------------------------------------|-------------|------------------------------------|-------------|---------------------------------------------|------------|------------------------------------|------------|
| LTE Band 5                                  |             | UMTS 850                           |             | LTE Band 5                                  |            | UMTS 850                           |            |
| QPSK, 10MHz Bandwidth,<br>1 RB, 0 RB Offset |             | RMC                                |             | QPSK, 10MHz Bandwidth,<br>1 RB, 0 RB Offset |            | RMC                                |            |
| Test Position                               | Right Cheek | Test Position                      | Right Cheek | Test Position                               | Front Side | Test Position                      | Front Side |
|                                             |             |                                    |             | Spacing                                     | 10 mm      | Spacing                            | 10 mm      |
| Frequency (MHz)                             | 836.5       | Frequency (MHz)                    | 836.6       | Frequency (MHz)                             | 836.5      | Frequency (MHz)                    | 836.6      |
| Channel                                     | 20525       | Channel                            | 4183        | Channel                                     | 20525      | Channel                            | 4183       |
| Measured 1g SAR (W/kg)                      | 0.164       | Measured 1g SAR (W/kg)             | 0.164       | Measured 1g SAR (W/kg)                      | 0.646      | Measured 1g SAR (W/kg)             | 0.617      |
| Average Value of Time Sweep (W/kg)          |             | Average Value of Time Sweep (W/kg) |             | Average Value of Time Sweep (W/kg)          |            | Average Value of Time Sweep (W/kg) |            |
| Auto-tune (State 1)                         | 0.223       | Auto-tune (State 1)                | 0.250       | Auto-tune (State 1)                         | 0.896      | Auto-tune (State 1)                | 0.810      |
| Default (State 1)                           | 0.223       | Default (State 1)                  | 0.245       | Default (State 1)                           | 0.896      | Default (State 1)                  | 0.792      |
| State 1                                     | 0.223       | State 2                            | 0.246       | State 2                                     | 0.895      | State 3                            | 0.792      |
| State 5                                     | 0.135       | State 6                            | 0.156       | State 4                                     | 0.865      | State 7                            | 0.642      |
| State 9                                     | 0.220       | State 10                           | 0.254       | State 8                                     | 0.862      | State 11                           | 0.682      |
| State 13                                    | 0.085       | State 12                           | 0.158       | State 12                                    | 0.882      | State 15                           | 0.794      |
| State 19                                    | 0.151       | State 14                           | 0.094       | State 16                                    | 0.900      | State 17                           | 0.793      |
| State 21                                    | 0.156       | State 18                           | 0.245       | State 20                                    | 0.887      | State 21                           | 0.656      |
| State 25                                    | 0.221       | State 22                           | 0.094       | State 24                                    | 0.883      | State 23                           | 0.581      |

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 89 of 95                          |

# 15 EQUIPMENT LIST

## Equipment List for Test Period 05/26/16 – 06/06/16

| Manufacturer       | Model     | Description                                   | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|--------------------|-----------|-----------------------------------------------|------------|--------------|------------|---------------|
| Agilent            | 8594A     | (9kHz-2.9GHz) Spectrum Analyzer               | N/A        | N/A          | N/A        | 3051A00187    |
| Agilent            | 8753E     | (30kHz-6GHz) Network Analyzer                 | 3/2/2016   | Annual       | 3/2/2017   | JP38020182    |
| Agilent            | 8753ES    | S-Parameter Network Analyzer                  | 11/4/2015  | Annual       | 11/4/2016  | US39170118    |
| Agilent            | E4432B    | ESG-D Series Signal Generator                 | 3/5/2016   | Annual       | 3/5/2017   | US40053896    |
| Agilent            | E4438C    | ESG Vector Signal Generator                   | 3/13/2015  | Biennial     | 3/13/2017  | MY42082659    |
| Agilent            | E5515C    | Wireless Communications Test Set              | 11/4/2014  | Biennial     | 11/4/2016  | GB43193563    |
| Agilent            | F8257D    | (250kHz-20GHz) Signal Generator               | 3/2/2016   | Annual       | 3/2/2017   | MY45470194    |
| Agilent            | N5182A    | MXG Vector Signal Generator                   | 3/5/2016   | Annual       | 3/5/2017   | MY47420800    |
| Agilent            | N9020A    | MXA Signal Analyzer                           | 11/5/2015  | Annual       | 11/5/2016  | US46470561    |
| Amplifier Research | 1551G6    | Amplifier                                     | CBT        | N/A          | CBT        | 433978        |
| Anritsu            | MA24106A  | USB Power Sensor                              | 3/4/2016   | Annual       | 3/4/2017   | 1344557       |
| Anritsu            | MA24106A  | USB Power Sensor                              | 3/28/2016  | Annual       | 3/28/2017  | 1344554       |
| Anritsu            | MA2411B   | Pulse Power Sensor                            | 12/7/2015  | Annual       | 12/7/2016  | 1339018       |
| Anritsu            | MA2411B   | Pulse Power Sensor                            | 2/28/2016  | Annual       | 2/28/2017  | 1207470       |
| Anritsu            | MA2481A   | Power Sensor                                  | 3/3/2016   | Annual       | 3/3/2017   | 5318          |
| Anritsu            | MA2481A   | Power Sensor                                  | 3/3/2016   | Annual       | 3/3/2017   | 2400          |
| Anritsu            | ML2438A   | Power Meter                                   | 3/3/2016   | Annual       | 3/3/2017   | 1070030       |
| Anritsu            | ML2495A   | Power Meter                                   | 10/16/2015 | Biennial     | 10/16/2017 | 941001        |
| Anritsu            | ML2495A   | Power Meter                                   | 10/16/2015 | Biennial     | 10/16/2017 | 1090908       |
| Anritsu            | ML2496A   | Power Meter                                   | 2/28/2016  | Annual       | 2/28/2017  | 1306009       |
| Anritsu            | ML2496A   | Power Meter                                   | 3/5/2016   | Annual       | 3/5/2017   | 1351001       |
| Anritsu            | MT8820C   | Radio Communication Analyzer                  | 7/24/2015  | Annual       | 7/24/2016  | 6200901190    |
| Anritsu            | MT8820C   | Radio Communication Analyzer                  | 9/1/2015   | Annual       | 9/1/2016   | 620144419     |
| COMTech            | AR85729-5 | Solid State Amplifier                         | CBT        | N/A          | CBT        | M155A00-009   |
| Control Company    | 4040      | Digital Thermometer                           | 3/18/2015  | Biennial     | 3/18/2017  | 150194896     |
| Control Company    | 4352      | Ultra Long Stem Thermometer                   | 3/8/2016   | Biennial     | 3/8/2018   | 160261701     |
| Control Company    | 4353      | Long Stem Thermometer                         | 3/5/2015   | Biennial     | 3/5/2017   | 150149565     |
| Gigatronics        | 80701A    | (0.05-18GHz) Power Sensor                     | 11/4/2015  | Annual       | 11/4/2016  | 1833460       |
| Gigatronics        | 8651A     | Universal Power Meter                         | 11/4/2015  | Annual       | 11/4/2016  | 8650319       |
| Keysight           | 772D      | Dual Directional Coupler                      | CBT        | N/A          | CBT        | MY52180215    |
| MCL                | BW-N6W5+  | 6dB Attenuator                                | CBT        | N/A          | CBT        | 1139          |
| MiniCircuits       | SLP-2400+ | Low Pass Filter                               | CBT        | N/A          | CBT        | R897950903    |
| MiniCircuits       | VLF-6000+ | Low Pass Filter                               | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | BW-N20W5  | Power Attenuator                              | CBT        | N/A          | CBT        | 1226          |
| Mini-Circuits      | BW-N20W5+ | DC to 18 GHz Precision Fixed 20 dB Attenuator | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | NLP-1200+ | Low Pass Filter DC to 1000 MHz                | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | NLP-2950+ | Low Pass Filter DC to 2700 MHz                | CBT        | N/A          | CBT        | N/A           |
| Mitutoyo           | CD-6°CSX  | Digital Caliper                               | 3/2/2016   | Biennial     | 3/2/2018   | 13264162      |
| Narda              | 4014C-6   | 4 - 8 GHz SMA 6 dB Directional Coupler        | CBT        | N/A          | CBT        | N/A           |
| Narda              | 4772-3    | Attenuator (3dB)                              | CBT        | N/A          | CBT        | 9406          |
| Pasternack         | NC-100    | Torque Wrench                                 | 11/6/2015  | Biennial     | 11/6/2017  | N/A           |
| Pasternack         | PE2208-6  | Bidirectional Coupler                         | CBT        | N/A          | CBT        | N/A           |
| Pasternack         | PE2209-10 | Bidirectional Coupler                         | CBT        | N/A          | CBT        | N/A           |
| Rohde & Schwarz    | CMU200    | Base Station Simulator                        | 3/29/2016  | Annual       | 3/29/2017  | 836371/0079   |
| Rohde & Schwarz    | CMW500    | Radio Communication Tester                    | 4/27/2016  | Annual       | 4/27/2017  | 101699        |
| Seekonk            | NC-100    | Torque Wrench 5/16", 8" lbs                   | 3/2/2016   | Biennial     | 3/2/2018   | N/A           |
| SPEAG              | D750V3    | 750 MHz SAR Dipole                            | 2/16/2016  | Annual       | 2/16/2017  | 1046          |
| SPEAG              | D835V2    | 835 MHz SAR Dipole                            | 4/14/2016  | Annual       | 4/14/2017  | 4d119         |
| SPEAG              | D1750V2   | 1750 MHz SAR Dipole                           | 4/13/2016  | Annual       | 4/13/2017  | 1051          |
| SPEAG              | D1900V2   | 1900 MHz SAR Dipole                           | 4/12/2016  | Annual       | 4/12/2017  | 5d141         |
| SPEAG              | D2450V2   | 2450 MHz SAR Dipole                           | 2/18/2016  | Annual       | 2/18/2017  | 882           |
| SPEAG              | D2600V2   | 2600 MHz SAR Dipole                           | 10/21/2015 | Annual       | 10/21/2016 | 1071          |
| SPEAG              | D5GHzV2   | 5 GHz SAR Dipole                              | 2/25/2016  | Annual       | 2/25/2017  | 1120          |
| SPEAG              | D750V3    | 750 MHz Dipole                                | 3/16/2016  | Annual       | 3/16/2017  | 1054          |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics             | 9/16/2015  | Annual       | 9/16/2016  | 1323          |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics             | 10/27/2015 | Annual       | 10/27/2016 | 1333          |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics             | 4/14/2016  | Annual       | 4/14/2017  | 1407          |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics             | 2/19/2016  | Annual       | 2/19/2017  | 665           |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics             | 11/11/2015 | Annual       | 11/11/2016 | 1415          |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics             | 3/14/2016  | Annual       | 3/14/2017  | 1368          |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics             | 2/18/2016  | Annual       | 2/18/2017  | 1272          |
| SPEAG              | DAK-12    | Dielectric Assessment Kit (10MHz - 3GHz)      | 3/1/2016   | Annual       | 3/1/2017   | 1102          |
| SPEAG              | DAK-3.5   | Dielectric Assessment Kit                     | 10/20/2015 | Annual       | 10/20/2016 | 1091          |
| SPEAG              | ES3DV2    | SAR Probe                                     | 8/26/2015  | Annual       | 8/26/2016  | 3022          |
| SPEAG              | ES3DV3    | SAR Probe                                     | 10/29/2015 | Annual       | 10/29/2016 | 3333          |
| SPEAG              | EX3DV4    | SAR Probe                                     | 4/19/2016  | Annual       | 4/19/2017  | 7406          |
| SPEAG              | EX3DV4    | SAR Probe                                     | 4/19/2016  | Annual       | 4/19/2017  | 7357          |
| SPEAG              | ES3DV3    | SAR Probe                                     | 11/17/2015 | Annual       | 11/17/2016 | 3334          |
| SPEAG              | ES3DV3    | SAR Probe                                     | 2/19/2016  | Annual       | 2/19/2017  | 3318          |
| SPEAG              | ES3DV3    | SAR Probe                                     | 3/18/2016  | Annual       | 3/18/2017  | 3319          |
| SPEAG              | EX3DV4    | SAR Probe                                     | 2/22/2016  | Annual       | 2/22/2017  | 3914          |

|                                             |                                                                                     |                                      |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| FCC ID: A3LSMN935F                          |  | <b>SAR EVALUATION REPORT</b>         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                   | <b>DUT Type:</b><br>Portable Handset |                                                                                       | Page 90 of 95                          |

### Equipment List for Test Period 03/27/17 – 04/10/17

| Manufacturer       | Model     | Description                                     | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|--------------------|-----------|-------------------------------------------------|------------|--------------|------------|---------------|
| SPEAG              | D750V3    | 750 MHz SAR Dipole                              | 7/13/2016  | Annual       | 7/13/2017  | 1161          |
| SPEAG              | D835V2    | 835 MHz SAR Dipole                              | 7/14/2016  | Annual       | 7/14/2017  | 4d133         |
| SPEAG              | D835V2    | 835 MHz SAR Dipole                              | 7/13/2016  | Annual       | 7/13/2017  | 4d047         |
| SPEAG              | D2450V2   | 2450 MHz SAR Dipole                             | 7/25/2016  | Annual       | 7/25/2017  | 981           |
| SPEAG              | D5GHzV2   | 5 GHz SAR Dipole                                | 8/2/2016   | Annual       | 8/2/2017   | 1237          |
| SPEAG              | EX3DV4    | SAR Probe                                       | 7/21/2016  | Annual       | 7/21/2017  | 7308          |
| SPEAG              | ES3DV3    | SAR Probe                                       | 2/10/2017  | Annual       | 2/10/2018  | 3213          |
| SPEAG              | ES3DV3    | SAR Probe                                       | 2/10/2017  | Annual       | 2/10/2018  | 3318          |
| SPEAG              | EX3DV4    | SAR Probe                                       | 4/19/2016  | Annual       | 4/19/2017  | 7406          |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics               | 5/11/2016  | Annual       | 5/11/2017  | 859           |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics               | 2/9/2017   | Annual       | 2/9/2018   | 1272          |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics               | 2/9/2017   | Annual       | 2/9/2018   | 665           |
| SPEAG              | DAE4      | Dasy Data Acquisition Electronics               | 4/14/2016  | Annual       | 4/14/2017  | 1407          |
| Agilent            | 8753ES    | S-Parameter Network Analyzer                    | 10/26/2016 | Annual       | 10/26/2017 | US39170118    |
| Agilent            | E5515C    | 8960 Series 10 Wireless Communications Test Set | 10/5/2016  | Annual       | 10/5/2017  | GB42230325    |
| SPEAG              | DAK-3.5   | Dielectric Assessment Kit                       | 5/10/2016  | Annual       | 5/10/2017  | 1070          |
| Agilent            | N9020A    | MXA Signal Analyzer                             | 10/28/2016 | Annual       | 10/28/2017 | US46470561    |
| Agilent            | N5182A    | MXG Vector Signal Generator                     | 2/28/2017  | Annual       | 2/28/2018  | MY47420800    |
| Anritsu            | ML2495A   | Power Meter                                     | 10/16/2015 | Biennial     | 10/16/2017 | 941001        |
| Anritsu            | ML2495A   | Power Meter                                     | 10/16/2015 | Biennial     | 10/16/2017 | 1039008       |
| Anritsu            | MA2411B   | Pulse Power Sensor                              | 8/18/2016  | Annual       | 8/18/2017  | 1207470       |
| Anritsu            | MA2411B   | Pulse Power Sensor                              | 2/10/2017  | Annual       | 2/10/2018  | 1339018       |
| Anritsu            | MT8820C   | Radio Communication Analyzer                    | 9/15/2016  | Annual       | 9/15/2017  | 6200901190    |
| Rohde & Schwarz    | CMW500    | Radio Communication tester                      | 5/27/2016  | Annual       | 5/27/2017  | 140144        |
| Seekonk            | NC-100    | Torque Wrench (8" lb)                           | 8/30/2016  | Biennial     | 8/30/2018  | N/A           |
| Seekonk            | NC-100    | Torque Wrench 5/16", 8" lbs                     | 3/2/2016   | Biennial     | 3/2/2018   | N/A           |
| Anritsu            | MA24106A  | USB Power Sensor                                | 6/2/2016   | Annual       | 6/2/2017   | 1231538       |
| Anritsu            | MA24106A  | USB Power Sensor                                | 6/2/2016   | Annual       | 6/2/2017   | 1231535       |
| Agilent            | E5515C    | Wireless Communications Test Set                | 5/22/2015  | Biennial     | 5/22/2017  | GB43304278    |
| Agilent            | 8594A     | (9kHz-2.9GHz) Spectrum Analyzer                 | N/A        | N/A          | N/A        | 3051A00187    |
| Narda              | 4772-3    | Attenuator (3dB)                                | CBT        | N/A          | CBT        | 9406          |
| Narda              | BW-S3W2   | Attenuator (3dB)                                | CBT        | N/A          | CBT        | 120           |
| MCL                | BW-N6W5+  | 6dB Attenuator                                  | CBT        | N/A          | CBT        | 1139          |
| Mini-Circuits      | BW-N20W5+ | DC to 18 GHz Precision Fixed 20 dB Attenuator   | CBT        | N/A          | CBT        | N/A           |
| Amplifier Research | 15S1G6    | Amplifier                                       | CBT        | N/A          | CBT        | 433971        |
| Amplifier Research | 15S1G6    | Amplifier                                       | CBT        | N/A          | CBT        | 433972        |
| Pasternack         | PE2208-6  | Bidirectional Coupler                           | CBT        | N/A          | CBT        | N/A           |
| Pasternack         | PE2209-10 | Bidirectional Coupler                           | CBT        | N/A          | CBT        | N/A           |
| Narda              | 4014C-6   | 4 - 8 GHz SMA 6 dB Directional Coupler          | CBT        | N/A          | CBT        | N/A           |
| MiniCircuits       | VLF-6000+ | Low Pass Filter                                 | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | NLP-1200+ | Low Pass Filter DC to 1000 MHz                  | CBT        | N/A          | CBT        | N/A           |
| Mini-Circuits      | NLP-2950+ | Low Pass Filter DC to 2700 MHz                  | CBT        | N/A          | CBT        | N/A           |

**Note:**

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment item was used solely within its respective calibration period.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 91 of 95                          |

## 16 MEASUREMENT UNCERTAINTIES

| a                                                                             | c             | d              | e=<br>f(d,k) | f                     | g                        | h =<br>c x f/e                 | i =<br>c x g/e                   | k              |
|-------------------------------------------------------------------------------|---------------|----------------|--------------|-----------------------|--------------------------|--------------------------------|----------------------------------|----------------|
| Uncertainty Component                                                         | Tol.<br>(± %) | Prob.<br>Dist. | Div.         | c <sub>i</sub><br>1gm | c <sub>i</sub><br>10 gms | 1gm<br>u <sub>i</sub><br>(± %) | 10gms<br>u <sub>i</sub><br>(± %) | v <sub>i</sub> |
| <b>Measurement System</b>                                                     |               |                |              |                       |                          |                                |                                  |                |
| Probe Calibration                                                             | 6.55          | N              | 1            | 1.0                   | 1.0                      | 6.6                            | 6.6                              | ∞              |
| Axial Isotropy                                                                | 0.25          | N              | 1            | 0.7                   | 0.7                      | 0.2                            | 0.2                              | ∞              |
| Hemishperical Isotropy                                                        | 1.3           | N              | 1            | 0.7                   | 0.7                      | 0.9                            | 0.9                              | ∞              |
| Boundary Effect                                                               | 2.0           | R              | 1.73         | 1.0                   | 1.0                      | 1.2                            | 1.2                              | ∞              |
| Linearity                                                                     | 0.3           | N              | 1            | 1.0                   | 1.0                      | 0.3                            | 0.3                              | ∞              |
| System Detection Limits                                                       | 0.25          | R              | 1.73         | 1.0                   | 1.0                      | 0.1                            | 0.1                              | ∞              |
| Readout Electronics                                                           | 0.3           | N              | 1            | 1.0                   | 1.0                      | 0.3                            | 0.3                              | ∞              |
| Response Time                                                                 | 0.8           | R              | 1.73         | 1.0                   | 1.0                      | 0.5                            | 0.5                              | ∞              |
| Integration Time                                                              | 2.6           | R              | 1.73         | 1.0                   | 1.0                      | 1.5                            | 1.5                              | ∞              |
| RF Ambient Conditions - Noise                                                 | 3.0           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| RF Ambient Conditions - Reflections                                           | 3.0           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Probe Positioner Mechanical Tolerance                                         | 0.4           | R              | 1.73         | 1.0                   | 1.0                      | 0.2                            | 0.2                              | ∞              |
| Probe Positioning w/ respect to Phantom                                       | 6.7           | R              | 1.73         | 1.0                   | 1.0                      | 3.9                            | 3.9                              | ∞              |
| Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation | 4.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.3                            | 2.3                              | ∞              |
| <b>Test Sample Related</b>                                                    |               |                |              |                       |                          |                                |                                  |                |
| Test Sample Positioning                                                       | 2.7           | N              | 1            | 1.0                   | 1.0                      | 2.7                            | 2.7                              | 35             |
| Device Holder Uncertainty                                                     | 1.67          | N              | 1            | 1.0                   | 1.0                      | 1.7                            | 1.7                              | 5              |
| Output Power Variation - SAR drift measurement                                | 5.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.9                            | 2.9                              | ∞              |
| SAR Scaling                                                                   | 0.0           | R              | 1.73         | 1.0                   | 1.0                      | 0.0                            | 0.0                              | ∞              |
| <b>Phantom &amp; Tissue Parameters</b>                                        |               |                |              |                       |                          |                                |                                  |                |
| Phantom Uncertainty (Shape & Thickness tolerances)                            | 7.6           | R              | 1.73         | 1.0                   | 1.0                      | 4.4                            | 4.4                              | ∞              |
| Liquid Conductivity - measurement uncertainty                                 | 4.2           | N              | 1            | 0.78                  | 0.71                     | 3.3                            | 3.0                              | 10             |
| Liquid Permittivity - measurement uncertainty                                 | 4.1           | N              | 1            | 0.23                  | 0.26                     | 1.0                            | 1.1                              | 10             |
| Liquid Conductivity - Temperature Uncertainty                                 | 3.4           | R              | 1.73         | 0.78                  | 0.71                     | 1.5                            | 1.4                              | ∞              |
| Liquid Permittivity - Temperature Uncertainty                                 | 0.6           | R              | 1.73         | 0.23                  | 0.26                     | 0.1                            | 0.1                              | ∞              |
| Liquid Conductivity - deviation from target values                            | 5.0           | R              | 1.73         | 0.64                  | 0.43                     | 1.8                            | 1.2                              | ∞              |
| Liquid Permittivity - deviation from target values                            | 5.0           | R              | 1.73         | 0.60                  | 0.49                     | 1.7                            | 1.4                              | ∞              |
| <b>Combined Standard Uncertainty (k=1)</b>                                    | RSS           |                |              |                       |                          | 11.5                           | 11.3                             | 60             |
| <b>Expanded Uncertainty</b><br>(95% CONFIDENCE LEVEL)                         | k=2           |                |              |                       |                          | 23.0                           | 22.6                             |                |

|                                      |                                                                                                                                                                                                        |                               |                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------|
| FCC ID: A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                               | Reviewed by:<br>Quality Manager |
| Document S/N:<br>1M1703270125-01.A3L | Test Dates:<br>05/26/16 - 06/06/16,<br>03/27/17 - 04/10/17                                                                                                                                             | DUT Type:<br>Portable Handset | Page 92 of 95                   |

## 17 CONCLUSION

### 17.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

|                                             |                                                                                                                                                                                                        |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset   |
|                                             |                                                                                                                                                                                                        | Page 93 of 95                          |

## 18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 94 of 95                          |



- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

|                                             |                                                                                                                                                                                                        |                                      |                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LSMN935F                   |  <b>SAR EVALUATION REPORT</b>  |                                      | <b>Reviewed by:</b><br>Quality Manager |
| <b>Document S/N:</b><br>1M1703270125-01.A3L | <b>Test Dates:</b><br>05/26/16 - 06/06/16,<br>03/27/17 – 04/10/17                                                                                                                                      | <b>DUT Type:</b><br>Portable Handset | Page 95 of 95                          |

## APPENDIX A: SAR TEST DATA

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 87763**

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.885 \text{ S/m}$ ;  $\epsilon_r = 40.093$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 03-27-2017; Ambient Temp: 22.0°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 04/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 04/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 850, Right Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 15.45 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.244 W/kg

**SAR(1 g) = 0.202 W/kg**



0 dB = 0.231 W/kg = -6.36 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 8424D**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.902 \text{ S/m}$ ;  $\epsilon_r = 41.059$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-01-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(6.16, 6.16, 6.16); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Right Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 13.96 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.203 W/kg

**SAR(1 g) = 0.164 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$ ;  $\sigma = 1.349 \text{ S/m}$ ;  $\epsilon_r = 39.293$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7406; ConvF(8.85, 8.85, 8.85); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1750, Left Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 15.56 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.451 W/kg

**SAR(1 g) = 0.303 W/kg**



0 dB = 0.386 W/kg = -4.13 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84250**

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.398 \text{ S/m}$ ;  $\epsilon_r = 39.087$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-03-2016; Ambient Temp: 23.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 1900, Left Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 8.401 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.136 W/kg

**SAR(1 g) = 0.090 W/kg**



0 dB = 0.103 W/kg = -9.87 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84250**

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$ ;  $\sigma = 1.432 \text{ S/m}$ ;  $\epsilon_r = 39.009$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-03-2016; Ambient Temp: 23.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Left Head, Cheek, High.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 13.32 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.345 W/kg

**SAR(1 g) = 0.228 W/kg**



0 dB = 0.265 W/kg = -5.77 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$ ;  $\sigma = 0.857 \text{ S/m}$ ;  $\epsilon_r = 41.913$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-31-2016; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(6.33, 6.33, 6.33); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/16/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (8x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 9.208 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.0790 W/kg

**SAR(1 g) = 0.064 W/kg**





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$ ;  $\sigma = 0.922 \text{ S/m}$ ;  $\epsilon_r = 40.895$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-31-2016; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(6.33, 6.33, 6.33); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/16/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Right Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


**Area Scan (8x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 10.58 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.113 W/kg

**SAR(1 g) = 0.089 W/kg**



0 dB = 0.0974 W/kg = -10.11 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 8413C**

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$ ;  $\sigma = 0.902 \text{ S/m}$ ;  $\epsilon_r = 41.061$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-01-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(6.16, 6.16, 6.16); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.43 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.199 W/kg

**SAR(1 g) = 0.164 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 8413C**

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$ ;  $\sigma = 0.897 \text{ S/m}$ ;  $\epsilon_r = 41.13$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-01-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(6.16, 6.16, 6.16); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Right Head, Cheek, Mid.ch,  
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 12.72 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.155 W/kg

**SAR(1 g) = 0.127 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84162**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.349 \text{ S/m}$ ;  $\epsilon_r = 39.292$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7406; ConvF(8.85, 8.85, 8.85); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.96 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.493 W/kg

**SAR(1 g) = 0.335 W/kg**



0 dB = 0.429 W/kg = -3.68 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84250**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.423 \text{ S/m}$ ;  $\epsilon_r = 39.03$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-03-2016; Ambient Temp: 23.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Left Head, Cheek, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.39 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.353 W/kg

**SAR(1 g) = 0.234 W/kg**



0 dB = 0.274 W/kg = -5.62 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84250**

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$ ;  $\sigma = 1.429 \text{ S/m}$ ;  $\epsilon_r = 39.016$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-03-2016; Ambient Temp: 23.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.45 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.226 W/kg

**SAR(1 g) = 0.146 W/kg**



0 dB = 0.175 W/kg = -7.57 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84162**

Communication System: UID 0, LTE Band 41; Frequency: 2549.5 MHz; Duty Cycle: 1:1.58

Medium: 2450 Head Medium parameters used:

$f = 2549.5$  MHz;  $\sigma = 1.946$  S/m;  $\epsilon_r = 40.452$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Test Date: 05-31-2016; Ambient Temp: 23.8°C; Tissue Temp: 22.8°C

Probe: ES3DV2 - SN3022; ConvF(4.12, 4.12, 4.12); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/16/2015

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Left Head, Cheek, Low-Mid.ch, QPSK,  
20 MHz Bandwidth, 1 RB, 0 RB Offset**


**Area Scan (10x17x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.677 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.143 W/kg

**SAR(1 g) = 0.079 W/kg**





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 05C3E**

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$ ;  $\sigma = 1.789 \text{ S/m}$ ;  $\epsilon_r = 40.983$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-31-2016; Ambient Temp: 23.8°C; Tissue Temp: 22.8°C

Probe: ES3DV2 - SN3022; ConvF(4.3, 4.3, 4.3); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/16/2015

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Right Head, Cheek, Ch 01, 1 Mbps, Antenna 1**


**Area Scan (11x18x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$

**Zoom Scan (8x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 16.59 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.06 W/kg

**SAR(1 g) = 0.482 W/kg**



0 dB = 0.652 W/kg = -1.86 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 04160**

Communication System: UID 0, IEEE 802.11ac; Frequency: 5610 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5610 \text{ MHz}$ ;  $\sigma = 4.936 \text{ S/m}$ ;  $\epsilon_r = 34.99$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 04-06-2017; Ambient Temp: 23.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7308; ConvF(4.63, 4.63, 4.63); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11ac, U-NII-2C, 80 MHz Bandwidth**

**Right Head, Cheek, Ch 122, 29.3 Mbps, Antenna 2**


**Area Scan (11x20x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Reference Value = 10.56 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 2.81 W/kg

**SAR(1 g) = 0.600 W/kg**



0 dB = 1.57 W/kg = 1.96 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 85F64**

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.996 \text{ S/m}$ ;  $\epsilon_r = 55.061$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2017; Ambient Temp: 21.6°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 850, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 21.90 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.595 W/kg

**SAR(1 g) = 0.433 W/kg**



0 dB = 0.494 W/kg = -3.06 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 85F64**

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 848.8 MHz; Duty Cycle: 1:2.076

Medium: 835 Body Medium parameters used (interpolated):

$f = 848.8 \text{ MHz}$ ;  $\sigma = 0.999 \text{ S/m}$ ;  $\epsilon_r = 52.996$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-10-2017; Ambient Temp: 22.9°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 850, Body SAR, Front side, High.ch, 4 Tx Slots**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 30.76 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.39 W/kg

**SAR(1 g) = 0.841 W/kg**



0 dB = 1.02 W/kg = 0.09 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 8424D**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 1.001 \text{ S/m}$ ;  $\epsilon_r = 53.477$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-02-2016; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3318; ConvF(6.11, 6.11, 6.11); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 20.45 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.518 W/kg

**SAR(1 g) = 0.385 W/kg**



0 dB = 0.430 W/kg = -3.67 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 8424D**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 1.001 \text{ S/m}$ ;  $\epsilon_r = 53.477$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-02-2016; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3318; ConvF(6.11, 6.11, 6.11); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Body SAR, Front side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 26.00 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.04 W/kg

**SAR(1 g) = 0.617 W/kg**



0 dB = 0.721 W/kg = -1.42 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84162**

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1  
Medium: 1750 Body Medium parameters used (interpolated):  
 $f = 1732.4 \text{ MHz}$ ;  $\sigma = 1.483 \text{ S/m}$ ;  $\epsilon_r = 51.757$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;  
Sensor-Surface: 1.4mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016  
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648  
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1750, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 18.03 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.706 W/kg

**SAR(1 g) = 0.452 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$ ;  $\sigma = 1.483 \text{ S/m}$ ;  $\epsilon_r = 51.757$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1750, Body SAR, Bottom Edge, Mid.ch**


**Area Scan (11x9x1):** Measurement grid:  $dx=5\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 21.43 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.04 W/kg

**SAR(1 g) = 0.618 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880$  MHz;  $\sigma = 1.543$  S/m;  $\epsilon_r = 52.019$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 1900, Body SAR, Back side, Mid.ch**


**Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.66 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.618 W/kg

**SAR(1 g) = 0.383 W/kg**





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body, Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.543 \text{ S/m}$ ;  $\epsilon_r = 52.019$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 3 Tx Slots**


**Area Scan (10x9x1):** Measurement grid:  $dx=5\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 22.67 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.16 W/kg

**SAR(1 g) = 0.696 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$ ;  $\sigma = 1.573 \text{ S/m}$ ;  $\epsilon_r = 51.932$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Body SAR, Back side, High.ch**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 16.97 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.618 W/kg

**SAR(1 g) = 0.403 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$ ;  $\sigma = 1.573 \text{ S/m}$ ;  $\epsilon_r = 51.932$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Body SAR, Bottom Edge, High.ch**


**Area Scan (10x7x1):** Measurement grid:  $dx=5\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 22.55 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.16 W/kg

**SAR(1 g) = 0.693 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$ ;  $\sigma = 0.935 \text{ S/m}$ ;  $\epsilon_r = 55.105$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-06-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 11.99 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.168 W/kg

**SAR(1 g) = 0.124 W/kg**



0 dB = 0.139 W/kg = -8.57 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$ ;  $\sigma = 0.935 \text{ S/m}$ ;  $\epsilon_r = 55.105$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-06-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Front side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 16.75 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.417 W/kg

**SAR(1 g) = 0.241 W/kg**



0 dB = 0.283 W/kg = -5.48 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 98443**

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$ ;  $\sigma = 0.986 \text{ S/m}$ ;  $\epsilon_r = 53.955$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2017; Ambient Temp: 24.5°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch**  
**10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


**Area Scan (9x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 16.13 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.323 W/kg

**SAR(1 g) = 0.236 W/kg**



0 dB = 0.263 W/kg = -5.80 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 98443**

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$ ;  $\sigma = 0.986 \text{ S/m}$ ;  $\epsilon_r = 53.955$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2017; Ambient Temp: 24.5°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 13, Body SAR, Front side, Mid.ch**  
**10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


**Area Scan (9x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 21.50 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.678 W/kg

**SAR(1 g) = 0.401 W/kg**



0 dB = 0.494 W/kg = -3.06 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 85F64**

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$ ;  $\sigma = 0.996 \text{ S/m}$ ;  $\epsilon_r = 55.062$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2017; Ambient Temp: 21.6°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch**  
**10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 20.54 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.511 W/kg

**SAR(1 g) = 0.381 W/kg**



0 dB = 0.430 W/kg = -3.67 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 85F64**

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$ ;  $\sigma = 0.996 \text{ S/m}$ ;  $\epsilon_r = 55.062$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2017; Ambient Temp: 21.6°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Front side, Mid.ch**  
**10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 28.85 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.07 W/kg

**SAR(1 g) = 0.646 W/kg**



0 dB = 0.799 W/kg = -0.97 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841C3**

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$ ;  $\sigma = 0.996 \text{ S/m}$ ;  $\epsilon_r = 53.529$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-02-2016; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3318; ConvF(6.11, 6.11, 6.11); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch,  
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 17.51 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.395 W/kg

**SAR(1 g) = 0.292 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841C3**

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$ ;  $\sigma = 0.996 \text{ S/m}$ ;  $\epsilon_r = 53.529$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-02-2016; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3318; ConvF(6.11, 6.11, 6.11); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 26 (Cell.), Body SAR, Front side, Mid.ch,  
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 21.36 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.746 W/kg

**SAR(1 g) = 0.443 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84162**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5$  MHz;  $\sigma = 1.483$  S/m;  $\epsilon_r = 51.756$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.82 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.758 W/kg

**SAR(1 g) = 0.490 W/kg**



0 dB = 0.665 W/kg = -1.77 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.483 \text{ S/m}$ ;  $\epsilon_r = 51.756$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.00 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.902 W/kg

**SAR(1 g) = 0.556 W/kg**



0 dB = 0.758 W/kg = -1.20 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900$  MHz;  $\sigma = 1.565$  S/m;  $\epsilon_r = 51.956$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.95 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.775 W/kg

**SAR(1 g) = 0.499 W/kg**



0 dB = 0.590 W/kg = -2.29 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900$  MHz;  $\sigma = 1.565$  S/m;  $\epsilon_r = 51.956$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Bottom Edge, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (10x9x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.94 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.04 W/kg

**SAR(1 g) = 0.630 W/kg**



0 dB = 0.764 W/kg = -1.17 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84102**

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905$  MHz;  $\sigma = 1.57$  S/m;  $\epsilon_r = 51.94$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.87 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.612 W/kg

**SAR(1 g) = 0.392 W/kg**



0 dB = 0.464 W/kg = -3.33 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$ ;  $\sigma = 1.57 \text{ S/m}$ ;  $\epsilon_r = 51.94$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Body SAR, Bottom Edge, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x9x1):** Measurement grid:  $dx=5\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 20.19 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.909 W/kg

**SAR(1 g) = 0.548 W/kg**



0 dB = 0.675 W/kg = -1.71 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84162**

Communication System: UID 0, LTE Band 41; Frequency: 2549.5 MHz; Duty Cycle: 1:1.58

Medium: 2600 Body Medium parameters used:

$f = 2549.5$  MHz;  $\sigma = 2.151$  S/m;  $\epsilon_r = 51.063$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date:05-31-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(4.29, 4.29, 4.29); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Back side, Low-Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (11x17x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.66 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.417 W/kg

**SAR(1 g) = 0.220 W/kg**



0 dB = 0.275 W/kg = -5.61 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 84162**

Communication System: UID 0, LTE Band 41; Frequency: 2680 MHz; Duty Cycle: 1:1.58

Medium: 2600 Body, Medium parameters used (interpolated):

$f = 2680 \text{ MHz}$ ;  $\sigma = 2.325 \text{ S/m}$ ;  $\epsilon_r = 50.529$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-31-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(4.29, 4.29, 4.29); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 41, Body SAR, Bottom Edge, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (10x11x1):** Measurement grid: dx=5mm, dy=12mm

**Zoom Scan (7x9x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.72 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.98 W/kg

**SAR(1 g) = 0.936 W/kg**



0 dB = 1.22 W/kg = 0.86 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 85F64**

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437$  MHz;  $\sigma = 1.995$  S/m;  $\epsilon_r = 51.029$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-29-2017; Ambient Temp: 23.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 04/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 04/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR  
Ch 06, 1 Mbps, Back Side, Antenna 1**


**Area Scan (10x17x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.21 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.423 W/kg

**SAR(1 g) = 0.223 W/kg**



0 dB = 0.347 W/kg = -4.60 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 85F64**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462$  MHz;  $\sigma = 2.028$  S/m;  $\epsilon_r = 50.935$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-29-2017; Ambient Temp: 23.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 04/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 04/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR  
Ch 11, 1 Mbps, Back Side, Antenna 2**


**Area Scan (11x17x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.075 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.13 W/kg

**SAR(1 g) = 0.511 W/kg**



0 dB = 0.888 W/kg = -0.52 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 05C28**

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5280 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5280 \text{ MHz}$ ;  $\sigma = 5.555 \text{ S/m}$ ;  $\epsilon_r = 47.102$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-30-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3914; ConvF(4.32, 4.32, 4.32); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, UNII-2A, 20 MHz Bandwidth,  
Body SAR, Ch 56, 6 Mbps, Back Side, Antenna 1**


**Area Scan (13x22x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 7.580 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.09 W/kg

**SAR(1 g) = 0.308 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 05C28**

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5825 \text{ MHz}$ ;  $\sigma = 6.296 \text{ S/m}$ ;  $\epsilon_r = 46.12$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-30-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, UNII-3, 20 MHz Bandwidth,  
Body SAR, Ch 165, 6 Mbps, Front Side, Antenna 1**


**Area Scan (11x19x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$ ; Graded Ratio: 1.4

Reference Value = 5.709 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.663 W/kg

**SAR(1 g) = 0.158 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$ ;  $\sigma = 1.483 \text{ S/m}$ ;  $\epsilon_r = 51.757$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1750, Phablet SAR, Front side, Mid.ch**


**Area Scan (9x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 51.68 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 9.34 W/kg

**SAR(10 g) = 1.57 W/kg**



0 dB = 6.90 W/kg = 8.39 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$ ;  $\sigma = 1.573 \text{ S/m}$ ;  $\epsilon_r = 51.932$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Phablet SAR, Front side, High.ch**


**Area Scan (9x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 41.75 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 6.27 W/kg

**SAR(10 g) = 1.28 W/kg**



0 dB = 3.41 W/kg = 5.33 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.483 \text{ S/m}$ ;  $\epsilon_r = 51.756$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Phablet SAR, Front side, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 56.87 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 11.7 W/kg

**SAR(10 g) = 1.91 W/kg**



0 dB = 7.98 W/kg = 9.02 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.565 \text{ S/m}$ ;  $\epsilon_r = 51.956$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Phablet SAR, Front side, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 37.82 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 4.81 W/kg

**SAR(10 g) = 1.11 W/kg**



0 dB = 2.62 W/kg = 4.18 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 841E0**

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$ ;  $\sigma = 1.57 \text{ S/m}$ ;  $\epsilon_r = 51.94$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 25 (PCS), Phablet SAR, Front side, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 34.85 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.98 W/kg

**SAR(10 g) = 0.929 W/kg**



0 dB = 2.16 W/kg = 3.34 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMN935F; Type: Portable Handset; Serial: 05C28**

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5280 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5280 \text{ MHz}$ ;  $\sigma = 5.555 \text{ S/m}$ ;  $\epsilon_r = 47.102$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-30-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3914; ConvF(4.32, 4.32, 4.32); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, UNII-2A, 20 MHz Bandwidth,  
Phablet SAR, Ch 56, 6 Mbps, Back Side, Antenna 1**


**Area Scan (11x19x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 45.30 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 90.7 W/kg

**SAR(10 g) = 1.67 W/kg**



0 dB = 35.9 W/kg = 15.55 dBW/kg

## APPENDIX B: SYSTEM VERIFICATION

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1046**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.893 \text{ S/m}$ ;  $\epsilon_r = 41.354$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-31-2016; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(6.33, 6.33, 6.33); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/16/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **750 MHz System Verification at 23.0 dBm (200 mW)**


**Area Scan (7x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.41 W/kg

**SAR(1 g) = 1.62 W/kg**

Deviation(1 g) = -1.22%



0 dB = 1.90 W/kg = 2.79 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.9 \text{ S/m}$ ;  $\epsilon_r = 41.083$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-01-2016; Ambient Temp: 24.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(6.16, 6.16, 6.16); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **835 MHz System Verification at 23.0 dBm (200 mW)**


**Area Scan (7x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.76 W/kg

**SAR(1 g) = 1.86 W/kg**

Deviation(1 g) = 1.75%



0 dB = 2.18 W/kg = 3.38 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.884 \text{ S/m}$ ;  $\epsilon_r = 40.108$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-27-2017; Ambient Temp: 22.0°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7406; ConvF(9.83, 9.83, 9.83); Calibrated: 04/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 04/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **835 MHz System Verification at 23.0 dBm (200 mW)**


**Area Scan (7x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.79 W/kg

**SAR(1 g) = 1.84 W/kg**

Deviation(1 g) = -1.29%



0 dB = 2.48 W/kg = 3.94 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.366 \text{ S/m}$ ;  $\epsilon_r = 39.201$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7406; ConvF(8.85, 8.85, 8.85); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **1750 MHz System Verification at 20.0 dBm (100 mW)**


**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.32 W/kg

**SAR(1 g) = 3.44 W/kg**

Deviation(1 g) = -4.71%



0 dB = 5.22 W/kg = 7.18 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.423 \text{ S/m}$ ;  $\epsilon_r = 39.03$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-03-2016; Ambient Temp: 23.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Right; Type: QD000P40CD; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **1900 MHz System Verification at 20.0 dBm (100 mW)**


**Area Scan (7x10x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.53 W/kg

**SAR(1 g) = 4.15 W/kg**

Deviation(1 g) = 7.79%



0 dB = 5.26 W/kg = 7.21 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 882**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 1.829 \text{ S/m}$ ;  $\epsilon_r = 40.801$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-31-2016; Ambient Temp: 23.8°C; Tissue Temp: 22.8°C

Probe: ES3DV2 - SN3022; ConvF(4.3, 4.3, 4.3); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/16/2015

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.4 W/kg

**SAR(1 g) = 5.34 W/kg**

Deviation(1 g) = 5.74%



0 dB = 7.15 W/kg = 8.54 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071**

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2600 \text{ MHz}$ ;  $\sigma = 2.001 \text{ S/m}$ ;  $\epsilon_r = 40.227$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-31-2016; Ambient Temp: 23.8°C; Tissue Temp: 22.8°C

Probe: ES3DV2 - SN3022; ConvF(4.12, 4.12, 4.12); Calibrated: 8/26/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/16/2015

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **2600 MHz System Verification at 20.0 dBm (100 mW)**


**Area Scan (8x9x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 12.9 W/kg

**SAR(1 g) = 5.81 W/kg**

Deviation(1 g) = 3.94%



0 dB = 7.84 W/kg = 8.94 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$ ;  $\sigma = 4.633 \text{ S/m}$ ;  $\epsilon_r = 35.088$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-06-2016; Ambient Temp: 20.5°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN7357; ConvF(5.1, 5.1, 5.1); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 5250 MHz System Verification at 17.0 dBm (50 mW)


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.9 W/kg

**SAR(1 g) = 3.84 W/kg**

Deviation(1 g) = -2.41%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237**

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$ ;  $\sigma = 4.592 \text{ S/m}$ ;  $\epsilon_r = 35.483$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-06-2017; Ambient Temp: 23.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7308; ConvF(5.21, 5.21, 5.21); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **5250 MHz System Verification at 17.0 dBm (50 mW)**


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.9 W/kg

**SAR(1 g) = 3.67 W/kg**

Deviation(1 g) = -7.32%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$ ;  $\sigma = 4.989 \text{ S/m}$ ;  $\epsilon_r = 34.615$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-06-2016; Ambient Temp: 20.5°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN7357; ConvF(4.41, 4.41, 4.41); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **5600 MHz System Verification at 17.0 dBm (50 mW)**


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.6 W/kg

**SAR(1 g) = 4.25 W/kg**

Deviation(1 g) = 3.28%





# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237**

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$ ;  $\sigma = 4.915 \text{ S/m}$ ;  $\epsilon_r = 34.99$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-06-2017; Ambient Temp: 23.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7308; ConvF(4.63, 4.63, 4.63); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **5600 MHz System Verification at 17.0 dBm (50 mW)**


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.8 W/kg

**SAR(1 g) = 3.9 W/kg**

Deviation(1 g) = -6.36%



0 dB = 9.51 W/kg = 9.78 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$ ;  $\sigma = 5.146 \text{ S/m}$ ;  $\epsilon_r = 34.392$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-06-2016; Ambient Temp: 20.5°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN7357; ConvF(4.65, 4.65, 4.65); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **5750 MHz System Verification at 17.0 dBm (50 mW)**


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.4 W/kg

**SAR(1 g) = 3.88 W/kg**

Deviation(1 g) = -1.90%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237**

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$ ;  $\sigma = 5.065 \text{ S/m}$ ;  $\epsilon_r = 34.841$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-06-2017; Ambient Temp: 23.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7308; ConvF(4.86, 4.86, 4.86); Calibrated: 7/21/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **5750 MHz System Verification at 17.0 dBm (50 mW)**


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.0 W/kg

**SAR(1 g) = 3.68 W/kg**

Deviation(1 g) = -9.69%



0 dB = 9.52 W/kg = 9.79 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.975 \text{ S/m}$ ;  $\epsilon_r = 54.677$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-06-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.52 W/kg

**SAR(1 g) = 1.71 W/kg**

Deviation(1 g) = -0.12%



0 dB = 2.01 W/kg = 3.03 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 750 MHz; Type: D750V3; Serial: 1161**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.952 \text{ S/m}$ ;  $\epsilon_r = 54.192$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2017; Ambient Temp: 24.5°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3213; ConvF(6.38, 6.38, 6.38); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification at 23.0 dBm (200 mW)


**Area Scan (7x15x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.34 W/kg

**SAR(1 g) = 1.59 W/kg**

Deviation(1 g) = -5.69%



0 dB = 1.85 W/kg = 2.67 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 1 \text{ S/m}$ ;  $\epsilon_r = 53.494$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-02-2016; Ambient Temp: 21.0°C; Tissue Temp: 20.7°C

Probe: ES3DV3 - SN3318; ConvF(6.11, 6.11, 6.11); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **835 MHz System Verification at 23.0 dBm (200 mW)**


**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.88 W/kg

**SAR(1 g) = 1.98 W/kg**

Deviation(1 g) = 8.32%



0 dB = 2.30 W/kg = 3.62 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.994 \text{ S/m}$ ;  $\epsilon_r = 55.071$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2017; Ambient Temp: 21.6°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **835 MHz System Verification at 23.0 dBm (200 mW)**


**Area Scan (7x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.96 W/kg

**SAR(1 g) = 2.03 W/kg**

Deviation(1 g) = 6.84%



0 dB = 2.38 W/kg = 3.77 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.987 \text{ S/m}$ ;  $\epsilon_r = 53.127$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-10-2017; Ambient Temp: 22.9°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **835 MHz System Verification at 23.0 dBm (200 mW)**


**Area Scan (7x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.81 W/kg

**SAR(1 g) = 1.94 W/kg**

Deviation(1 g) = 1.36%



0 dB = 2.26 W/kg = 3.54 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.502 \text{ S/m}$ ;  $\epsilon_r = 51.718$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-01-2016; Ambient Temp: 23.2°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.93 W/kg

**SAR(1 g) = 3.92 W/kg; SAR(10 g) = 2.08 W/kg**

Deviation(1 g) = 7.40%; Deviation(10 g) = 6.67%



0 dB = 4.89 W/kg = 6.89 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.565 \text{ S/m}$ ;  $\epsilon_r = 51.956$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-02-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (7x10x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.51 W/kg

**SAR(1 g) = 4.16 W/kg; SAR(10 g) = 2.16 W/kg**

Deviation(1 g) = 5.05%; Deviation(10 g) = 3.35%



0 dB = 5.26 W/kg = 7.21 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 882**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$  MHz;  $\sigma = 2.012$  S/m;  $\epsilon_r = 51.444$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-31-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(4.45, 4.45, 4.45); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **2450 MHz System Verification at 20.0 dBm (100 mW)**


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.0 W/kg

**SAR(1 g) = 5.2 W/kg**

Deviation(1 g) = 5.26%



0 dB = 7.03 W/kg = 8.47 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$  MHz;  $\sigma = 2.011$  S/m;  $\epsilon_r = 50.977$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-29-2017; Ambient Temp: 23.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 04/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 04/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 9.77 W/kg

**SAR(1 g) = 4.77 W/kg**

Deviation(1 g) = -6.10%



0 dB = 7.95 W/kg = 9.00 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071**

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body Medium parameters used:

$f = 2600 \text{ MHz}$ ;  $\sigma = 2.216 \text{ S/m}$ ;  $\epsilon_r = 50.857$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-31-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(4.29, 4.29, 4.29); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2600 MHz System Verification at 20.0 dBm (100 mW)


**Area Scan (8x9x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Peak SAR (extrapolated) = 12.4 W/kg

**SAR(1 g) = 5.77 W/kg**

Deviation(1 g) = 5.10%



0 dB = 7.80 W/kg = 8.92 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$ ;  $\sigma = 5.519 \text{ S/m}$ ;  $\epsilon_r = 47.086$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-30-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3914; ConvF(4.32, 4.32, 4.32); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **5250 MHz System Verification at 17.0 dBm (50 mW)**


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.3 W/kg

**SAR(1 g) = 3.78 W/kg; SAR(10 g) = 1.07 W/kg**

Deviation(1 g) = 0.00%; Deviation(10 g) = 0.94%



0 dB = 8.67 W/kg = 9.38 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$ ;  $\sigma = 5.962 \text{ S/m}$ ;  $\epsilon_r = 46.533$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-30-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3914; ConvF(3.63, 3.63, 3.63); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **5600 MHz System Verification at 17.0 dBm (50 mW)**


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.1 W/kg

**SAR(1 g) = 3.90 W/kg; SAR(10 g) = 1.10 W/kg**

Deviation(1 g) = -3.47%; Deviation(10 g) = -2.65%



0 dB = 9.13 W/kg = 9.60 dBW/kg



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120**

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$ ;  $\sigma = 6.15 \text{ S/m}$ ;  $\epsilon_r = 46.285$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-30-2016; Ambient Temp: 22.8°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## **5750 MHz System Verification at 17.0 dBm (50 mW)**


**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.9 W/kg

**SAR(1 g) = 3.70 W/kg; SAR(10 g) = 1.05 W/kg**

Deviation(1 g) = -3.27%; Deviation(10 g) = -1.41%



0 dB = 8.80 W/kg = 9.44 dBW/kg



## APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D750V3-1046\_Feb16**

## CALIBRATION CERTIFICATE

Object **D750V3 - SN:1046**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **February 16, 2016**

BN ✓  
 3/1/2016

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | US37292783         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | MY41092317         | 07-Oct-15 (No. 217-02223)         | Oct-16                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 01-Apr-15 (No. 217-02131)         | Mar-16                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 01-Apr-15 (No. 217-02134)         | Mar-16                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)    | Dec-16                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| RF generator R&S SMT-06     | 100972             | 15-Jun-15 (in house check Jun-15) | In house check: Jun-18 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Name** Michael Weber **Function** Laboratory Technician

Signature

*M. Weber*

Approved by: **Name** Katja Pokovic **Technical Manager**

*K. Pokovic*

Issued: February 17, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 750 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.9           | 0.89 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 41.8 $\pm$ 6 % | 0.90 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.07 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 8.20 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.35 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 5.36 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.5           | 0.96 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 55.1 $\pm$ 6 % | 0.98 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.23 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 8.77 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.47 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 5.80 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 56.7 $\Omega$ + 2.3 j $\Omega$ |
| Return Loss                          | - 23.6 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.7 $\Omega$ - 0.8 j $\Omega$ |
| Return Loss                          | - 34.5 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.037 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                    |
|-----------------|--------------------|
| Manufactured by | SPEAG              |
| Manufactured on | September 02, 2011 |

## DASY5 Validation Report for Head TSL

Date: 16.02.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1046**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.9 \text{ S/m}$ ;  $\epsilon_r = 41.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.28, 10.28, 10.28); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Head Tissue/Pin=250 mW,  $d=15\text{mm}$ /Zoom Scan (7x7x7)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 58.40 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.11 W/kg

**SAR(1 g) = 2.07 W/kg; SAR(10 g) = 1.35 W/kg**

Maximum value of SAR (measured) = 2.75 W/kg



## Impedance Measurement Plot for Head TSL

16 Feb 2016 12:19:20  
[CH1] S11 1 U FS 1: 56.666  $\Omega$  2.3223  $\Omega$  492.80 pF 750.000 000 MHz


\*

De1

CA

Avg  
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1: -23.586 dB 750.000 000 MHz

De1

CA

Avg  
16

H1d



## DASY5 Validation Report for Body TSL

Date: 16.02.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1046**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 55.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.99, 9.99, 9.99); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/ $P_{in}=250$ mW, $d=15$ mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 57.48 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.31 W/kg

**SAR(1 g) = 2.23 W/kg; SAR(10 g) = 1.47 W/kg**


Maximum value of SAR (measured) = 2.94 W/kg



0 dB = 2.94 W/kg = 4.68 dBW/kg



Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D835V2-4d119\_Apr16**

## CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d119**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **April 14, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289) | Apr-17                |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)       | Apr-17                |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)       | Apr-17                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)       | Apr-17                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)       | Apr-17                |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)  | Dec-16                |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)  | Dec-16                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Michael Weber**      Name: **Michael Weber**      Function: **Laboratory Technician**

Approved by: **Katja Pokovic**      Technical Manager

Signature

*M. Weber*

*Katja Pokovic*

Issued: April 15, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                        |             |
|-------------------------------------|------------------------|-------------|
| <b>DASY Version</b>                 | DASY5                  | V52.8.8     |
| <b>Extrapolation</b>                | Advanced Extrapolation |             |
| <b>Phantom</b>                      | Modular Flat Phantom   |             |
| <b>Distance Dipole Center - TSL</b> | 15 mm                  | with Spacer |
| <b>Zoom Scan Resolution</b>         | dx, dy, dz = 5 mm      |             |
| <b>Frequency</b>                    | 835 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 41.5           | 0.90 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 41.7 $\pm$ 6 % | 0.93 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.34 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>9.14 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.52 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>5.97 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Body TSL parameters</b>             | 22.0 °C             | 55.2           | 0.97 mho/m           |
| <b>Measured Body TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 54.4 $\pm$ 6 % | 1.02 mho/m $\pm$ 6 % |
| <b>Body TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.38 W/kg                                      |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>9.14 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.56 W/kg                                      |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>6.04 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.8 $\Omega$ - 4.1 j $\Omega$ |
| Return Loss                          | - 27.8 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 46.9 $\Omega$ - 6.1 j $\Omega$ |
| Return Loss                          | - 23.0 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.385 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |               |
|-----------------|---------------|
| Manufactured by | SPEAG         |
| Manufactured on | June 29, 2010 |

## DASY5 Validation Report for Head TSL

Date: 14.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.93$  S/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.83, 9.83, 9.83); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 60.95 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.48 W/kg

**SAR(1 g) = 2.34 W/kg; SAR(10 g) = 1.52 W/kg**

Maximum value of SAR (measured) = 3.11 W/kg




0 dB = 3.11 W/kg = 4.93 dBW/kg

Impedance Measurement Plot for Head TSL

14 Apr 2016 12:40:53  
CH1 S11 1 U FS 1: 50.793  $\Omega$  -4.0527  $\Omega$  47.031 pF 835.000 000 MHz


\*  
De1  
CA



Avg  
16  
H1d

CH2 S11 LOG 5 dB/ REF -20 dB 1:-27.758 dB 835.000 000 MHz

De1  
CA  
Avg  
16  
H1d



## DASY5 Validation Report for Body TSL

Date: 14.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 1.02 \text{ S/m}$ ;  $\epsilon_r = 54.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.73, 9.73, 9.73); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**



Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 58.35 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.46 W/kg

**SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.56 W/kg**

Maximum value of SAR (measured) = 3.11 W/kg




0 dB = 3.11 W/kg = 4.93 dBW/kg



Impedance Measurement Plot for Body TSL

14 Apr 2016 12:11:18  
[CH1] S11 1 U FS 1: 46.922  $\Omega$  -6.1035  $\Omega$  31.229 pF 835.000 000 MHz

\*  
De1  
Ca




Avg  
16  
H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-23.046 dB 835.000 000 MHz

De1  
Ca

Avg  
16  
H1d





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D1750V2-1051\_Apr16**

## CALIBRATION CERTIFICATE

Object **D1750V2 - SN: 1051**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **April 13, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289) | Apr-17                |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)       | Apr-17                |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)       | Apr-17                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)       | Apr-17                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)       | Apr-17                |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)  | Dec-16                |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)  | Dec-16                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Michael Weber** Function: **Laboratory Technician**

Signature

*M. Weber*

Approved by: **Katja Pokovic** Technical Manager

*K. Pokovic*

Issued: April 15, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- e) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 1750 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 40.1           | 1.37 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 39.9 $\pm$ 6 % | 1.35 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 8.94 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 36.1 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 4.75 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 19.1 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 53.4           | 1.49 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 52.8 $\pm$ 6 % | 1.48 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 9.12 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 36.5 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 4.87 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 19.5 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $51.6 \Omega + 0.9 j\Omega$ |
| Return Loss                          | - 35.0 dB                   |

### Antenna Parameters with Body TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $47.9 \Omega + 1.0 j\Omega$ |
| Return Loss                          | - 32.6 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.221 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | February 19, 2010 |

## DASY5 Validation Report for Head TSL

Date: 13.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1051**

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.35$  S/m;  $\epsilon_r = 39.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.54, 8.54, 8.54); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.0 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 16.2 W/kg

**SAR(1 g) = 8.94 W/kg; SAR(10 g) = 4.75 W/kg**


Maximum value of SAR (measured) = 13.5 W/kg



Impedance Measurement Plot for Head TSL


13 Apr 2016 10:37:39  
CH1 S11 1 U FS 1: 51.594  $\Omega$  0.8633  $\Omega$  78.512 pF 1 750.000 000 MHz

\*  
De1  
Ca  
Avg  
16  
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1:-34.971 dB 1 750.000 000 MHz

De1  
Ca  
Avg  
16  
H1d



## DASY5 Validation Report for Body TSL

Date: 13.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1051**

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.48$  S/m;  $\epsilon_r = 52.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.25, 8.25, 8.25); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 100.6 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 16.0 W/kg

**SAR(1 g) = 9.12 W/kg; SAR(10 g) = 4.87 W/kg**

Maximum value of SAR (measured) = 13.8 W/kg




0 dB = 13.8 W/kg = 11.40 dBW/kg



Impedance Measurement Plot for Body TSL

13 Apr 2016 10:37:13  
CH1 S11 1 U FS 1: 47.918  $\Omega$  0.9922  $\Omega$  90.235  $\mu$ H 1 750.000 000 MHz

\*  
De1  
CA




Avg  
16  
H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-32.564 dB 1 750.000 000 MHz

De1  
CA

Avg  
16  
H1d





Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D1900V2-5d141\_Apr16**

## CALIBRATION CERTIFICATE

Object **D1900V2 - SN:5d141**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **April 12, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289) | Apr-17                |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)       | Apr-17                |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)       | Apr-17                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)       | Apr-17                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)       | Apr-17                |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)  | Dec-16                |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)  | Dec-16                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Claudio Leubler**      Name: **Claudio Leubler**      Function: **Laboratory Technician**

Approved by: **Katja Pokovic**      Technical Manager

Signature

Issued: April 15, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 1900 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 40.0           | 1.40 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.0 $\pm$ 6 % | 1.37 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 9.50 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 38.5 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 4.97 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 20.0 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 53.3           | 1.52 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 52.9 $\pm$ 6 % | 1.49 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 9.80 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 39.6 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.20 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 20.9 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $53.0 \Omega + 6.3 j\Omega$ |
| Return Loss                          | - 23.4 dB                   |

### Antenna Parameters with Body TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $48.9 \Omega + 7.5 j\Omega$ |
| Return Loss                          | - 22.3 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.198 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                |
|-----------------|----------------|
| Manufactured by | SPEAG          |
| Manufactured on | March 11, 2011 |

## DASY5 Validation Report for Head TSL

Date: 12.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d141**

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.37$  S/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.2, 8.2, 8.2); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.9 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 17.2 W/kg

**SAR(1 g) = 9.5 W/kg; SAR(10 g) = 4.97 W/kg**


Maximum value of SAR (measured) = 14.2 W/kg



Impedance Measurement Plot for Head TSL

12 Apr 2016 13:21:16  
CH1 S11 1 U FS 1: 52.961  $\Omega$  6.3418  $\Omega$  531.23  $\mu\text{H}$  1 900.000 000 MHz


\*  
De1  
CA



Avg  
16  
H1d

CH2 S11 LOG 5 dB/ REF -20 dB 1:-23.372 dB 1 900.000 000 MHz

CA  
Avg  
16  
H1d



## DASY5 Validation Report for Body TSL

Date: 12.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d141**

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.03, 8.03, 8.03); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.2 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 17.1 W/kg

**SAR(1 g) = 9.8 W/kg; SAR(10 g) = 5.2 W/kg**



Maximum value of SAR (measured) = 14.8 W/kg



0 dB = 14.8 W/kg = 11.70 dBW/kg



Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D2450V2-882\_Feb16**

## CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 882**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **February 18, 2016**

*BN ✓*  
*03/01/2016*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | US37292783         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | MY41092317         | 07-Oct-15 (No. 217-02223)         | Oct-16                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 01-Apr-15 (No. 217-02131)         | Mar-16                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 01-Apr-15 (No. 217-02134)         | Mar-16                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)    | Dec-16                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| RF generator R&S SMT-06     | 100972             | 15-Jun-15 (in house check Jun-15) | In house check: Jun-18 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Claudio Leubler** **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** **Technical Manager**

Issued: February 19, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2450 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.2           | 1.80 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 38.7 $\pm$ 6 % | 1.84 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 12.8 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 50.5 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.92 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.5 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.7           | 1.95 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 52.9 $\pm$ 6 % | 2.00 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 12.5 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 49.4 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.81 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 23.1 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.5 $\Omega$ + 1.0 j $\Omega$ |
| Return Loss                          | - 31.5 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 48.7 $\Omega$ + 3.5 j $\Omega$ |
| Return Loss                          | - 28.6 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.157 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                  |
|-----------------|------------------|
| Manufactured by | SPEAG            |
| Manufactured on | October 06, 2011 |

## DASY5 Validation Report for Head TSL

Date: 18.02.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 882**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.84$  S/m;  $\epsilon_r = 38.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.76, 7.76, 7.76); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 109.8 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 25.7 W/kg

**SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.92 W/kg**

Maximum value of SAR (measured) = 20.1 W/kg




0 dB = 20.1 W/kg = 13.03 dBW/kg

Impedance Measurement Plot for Head TSL


18 Feb 2016 17:46:49  
CH1 S11 1 U FS 1: 52.516  $\Omega$  1.0352  $\Omega$  67.245  $\mu\text{H}$  2 450.000 000 MHz

\*  
De1  
CA  
Avg  
16  
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1:-31.516 dB 2 450.000 000 MHz

CA  
Avg  
16  
H1d



## DASY5 Validation Report for Body TSL

Date: 18.02.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 882**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2$  S/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.79, 7.79, 7.79); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### **Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.8 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 24.8 W/kg

**SAR(1 g) = 12.5 W/kg; SAR(10 g) = 5.81 W/kg**

Maximum value of SAR (measured) = 20.0 W/kg





# Impedance Measurement Plot for Body TSL

18 Feb 2016 17:47:21  
CH1 S11 1 U FS 1: 48.740  $\Omega$  3.4629  $\Omega$  224.95 pH 2 450.000 000 MHz


\*

De1

CA

Avg  
10

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1: -28.562 dB 2 450.000 000 MHz

CA

Avg  
10

H1d





Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D2600V2-1071\_Oct15**

## CALIBRATION CERTIFICATE

Object **D2600V2 - SN: 1071**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **October 21, 2015**

BN ✓  
u/03/15

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&E critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | US37292783         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | MY41092317         | 07-Oct-15 (No. 217-02223)         | Oct-16                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 01-Apr-15 (No. 217-02131)         | Mar-16                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 01-Apr-15 (No. 217-02134)         | Mar-16                 |
| Reference Probe EX3DV4      | SN: 7349           | 30-Dec-14 (No. EX3-7349_Dec14)    | Dec-15                 |
| DAE4                        | SN: 601            | 17-Aug-15 (No. DAE4-601_Aug15)    | Aug-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| RF generator R&S SMT-06     | 100972             | 15-Jun-15 (in house check Jun-15) | In house check: Jun-18 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Leif Klyster** Name: **Leif Klyster** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Name: **Katja Pokovic** Function: **Technical Manager**

Signature

*Leif Klyster*

*Katja Pokovic*

Issued: October 22, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2600 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.0           | 1.98 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 37.4 $\pm$ 6 % | 2.02 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 14.3 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 55.9 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 6.33 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 25.0 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.5           | 2.16 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 52.4 $\pm$ 6 % | 2.16 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 13.8 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 54.9 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 6.14 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 24.5 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.4 $\Omega$ - 5.4 j $\Omega$ |
| Return Loss                          | - 25.2 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 45.7 $\Omega$ - 4.6 j $\Omega$ |
| Return Loss                          | - 23.7 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.153 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |               |
|-----------------|---------------|
| Manufactured by | SPEAG         |
| Manufactured on | July 17, 2013 |

## DASY5 Validation Report for Head TSL

Date: 21.10.2015

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1071**

Communication System: UID 0 - CW; Frequency: 2600 MHz

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.02$  S/m;  $\epsilon_r = 37.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.4, 7.4, 7.4); Calibrated: 30.12.2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 17.08.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Dipole Calibration for Head Tissue/ $P_{in}=250$  mW,  $d=10$ mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 115.2 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 30.8 W/kg

**SAR(1 g) = 14.3 W/kg; SAR(10 g) = 6.33 W/kg**

Maximum value of SAR (measured) = 24.2 W/kg




# Impedance Measurement Plot for Head TSL

21 Oct 2015 09:53:21  
 CH1 S11 1 U F8 1: 49.434  $\Omega$  -5.4141  $\Omega$  11.306 pF 2 600.000 000 MHz

#  
 Del  
 CA

Avg  
 16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1: -25.246 dB 2 600.000 000 MHz

Del

CA

Avg  
 16

H1d



## DASY5 Validation Report for Body TSL

Date: 21.10.2015

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1071**

Communication System: UID 0 - CW; Frequency: 2600 MHz

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.18$  S/m;  $\epsilon_r = 52.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.52, 7.52, 7.52); Calibrated: 30.12.2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 17.08.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 108.6 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 28.8 W/kg

**SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.14 W/kg**


Maximum value of SAR (measured) = 23.3 W/kg



0 dB = 23.3 W/kg = 13.67 dBW/kg



# Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D5GHzV2-1120\_Feb16**

## CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN: 1120**

Calibration procedure(s) **QA CAL-22.v2**  
**Calibration procedure for dipole validation kits between 3-6 GHz**

Calibration date: **February 25, 2016**

*BN ✓*  
*03/01/2016*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | US37292783         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | MY41092317         | 07-Oct-15 (No. 217-02223)         | Oct-16                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 01-Apr-15 (No. 217-02131)         | Mar-16                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 01-Apr-15 (No. 217-02134)         | Mar-16                 |
| Reference Probe EX3DV4      | SN: 3503           | 31-Dec-15 (No. EX3-3503_Dec15)    | Dec-16                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| RF generator R&S SMT-06     | 100972             | 15-Jun-15 (in house check Jun-15) | In house check: Jun-18 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

|                |                |                       |           |
|----------------|----------------|-----------------------|-----------|
|                | Name           | Function              | Signature |
| Calibrated by: | Jeton Kastrati | Laboratory Technician |           |
| Approved by:   | Katja Pokovic  | Technical Manager     |           |

Issued: February 25, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                                                                      |                                  |
|------------------------------|----------------------------------------------------------------------|----------------------------------|
| DASY Version                 | DASY5                                                                | V52.8.8                          |
| Extrapolation                | Advanced Extrapolation                                               |                                  |
| Phantom                      | Modular Flat Phantom V5.0                                            |                                  |
| Distance Dipole Center - TSL | 10 mm                                                                | with Spacer                      |
| Zoom Scan Resolution         | dx, dy = 4.0 mm, dz = 1.4 mm                                         | Graded Ratio = 1.4 (Z direction) |
| Frequency                    | 5250 MHz $\pm$ 1 MHz<br>5600 MHz $\pm$ 1 MHz<br>5750 MHz $\pm$ 1 MHz |                                  |

## Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 35.9           | 4.71 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 34.8 $\pm$ 6 % | 4.56 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL at 5250 MHz

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 100 mW input power | 7.93 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 78.7 W/kg $\pm$ 19.9 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 100 mW input power | 2.28 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 22.6 W/kg $\pm$ 19.5 % (k=2) |

## Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.5         | 5.07 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.3 ± 6 %   | 4.91 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

## SAR result with Head TSL at 5600 MHz

|                                                             |                    |                                   |
|-------------------------------------------------------------|--------------------|-----------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                   |
| SAR measured                                                | 100 mW input power | 8.30 W/kg                         |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>82.3 W / kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.40 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>23.8 W/kg ± 19.5 % (k=2)</b> |

## Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.4         | 5.22 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.1 ± 6 %   | 5.07 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

## SAR result with Head TSL at 5750 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.98 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>79.1 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.28 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>22.6 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5250 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.9         | 5.36 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.1 ± 6 %   | 5.46 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5250 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.61 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>75.6 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.14 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>21.2 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.5         | 5.77 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.4 ± 6 %   | 5.94 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5600 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.14 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>80.8 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.28 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>22.6 W/kg ± 19.5 % (k=2)</b> |

## Body TSL parameters at 5750 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.3         | 5.94 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.2 ± 6 %   | 6.15 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

## SAR result with Body TSL at 5750 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 7.71 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 76.5 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.15 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.3 W/kg ± 19.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL at 5250 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.8 $\Omega$ - 1.3 j $\Omega$ |
| Return Loss                          | - 30.5 dB                      |

### Antenna Parameters with Head TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 56.8 $\Omega$ - 1.0 j $\Omega$ |
| Return Loss                          | - 23.8 dB                      |

### Antenna Parameters with Head TSL at 5750 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 53.5 $\Omega$ + 4.2 j $\Omega$ |
| Return Loss                          | - 25.6 dB                      |

### Antenna Parameters with Body TSL at 5250 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.7 $\Omega$ - 0.6 j $\Omega$ |
| Return Loss                          | - 34.9 dB                      |

### Antenna Parameters with Body TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 58.8 $\Omega$ + 2.2 j $\Omega$ |
| Return Loss                          | - 21.5 dB                      |

### Antenna Parameters with Body TSL at 5750 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 53.9 $\Omega$ + 6.1 j $\Omega$ |
| Return Loss                          | - 23.1 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.205 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                    |
|-----------------|--------------------|
| Manufactured by | SPEAG              |
| Manufactured on | September 08, 2011 |



## DASY5 Validation Report for Head TSL

Date: 25.02.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1120**

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz  
Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.56$  S/m;  $\epsilon_r = 34.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.91$  S/m;  $\epsilon_r = 34.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.07$  S/m;  $\epsilon_r = 34.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.53, 5.53, 5.53); Calibrated: 31.12.2015, ConvF(4.99, 4.99, 4.99); Calibrated: 31.12.2015, ConvF(4.95, 4.95, 4.95); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom Type: QD000P50AA
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 73.31 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 29.0 W/kg

**SAR(1 g) = 7.93 W/kg; SAR(10 g) = 2.28 W/kg**

Maximum value of SAR (measured) = 18.4 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 73.36 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 32.5 W/kg

**SAR(1 g) = 8.3 W/kg; SAR(10 g) = 2.4 W/kg**

Maximum value of SAR (measured) = 19.9 W/kg


**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.09 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 32.5 W/kg

**SAR(1 g) = 7.98 W/kg; SAR(10 g) = 2.28 W/kg**

Maximum value of SAR (measured) = 19.3 W/kg




0 dB = 18.4 W/kg = 12.65 dBW/kg

Impedance Measurement Plot for Head TSL

23 Feb 2016 14:32:25  
CH1 S11 1 U FS 1: 52.766  $\Omega$  -1.2852  $\Omega$  23.589 pF 5 250.000 000 MHz


\*  
Del  
Cor  
Avg  
16  
H1d



CH1 Markers  
2: 56.799  $\Omega$   
-1.0039  $\Omega$   
5.60000 GHz  
3: 53.527  $\Omega$   
4.1504  $\Omega$   
5.75000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -30.546 dB 5 250.000 000 MHz

Cor  
Avg  
0  
H1d



CH2 Markers  
2: -23.825 dB  
5.60000 GHz  
3: -25.580 dB  
5.75000 GHz

## DASY5 Validation Report for Body TSL

Date: 17.02.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1120**

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz  
Medium parameters used:  $f = 5250$  MHz;  $\sigma = 5.46$  S/m;  $\epsilon_r = 47.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.94$  S/m;  $\epsilon_r = 46.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5750$  MHz;  $\sigma = 6.15$  S/m;  $\epsilon_r = 46.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(4.85, 4.85, 4.85); Calibrated: 31.12.2015, ConvF(4.35, 4.35, 4.35); Calibrated: 31.12.2015, ConvF(4.3, 4.3, 4.3); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.97 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 28.5 W/kg

**SAR(1 g) = 7.61 W/kg; SAR(10 g) = 2.14 W/kg**

Maximum value of SAR (measured) = 18.3 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 67.65 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 33.6 W/kg

**SAR(1 g) = 8.14 W/kg; SAR(10 g) = 2.28 W/kg**

Maximum value of SAR (measured) = 20.4 W/kg



**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.41 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 33.1 W/kg

**SAR(1 g) = 7.71 W/kg; SAR(10 g) = 2.15 W/kg**

Maximum value of SAR (measured) = 19.6 W/kg




0 dB = 18.3 W/kg = 12.62 dBW/kg

# Impedance Measurement Plot for Body TSL

17 Feb 2016 16:45:23  
 [CH1] S11 1 U FS 1: 51.736  $\Omega$  -552.73 m $\Omega$  54.846 pF 5 250.000 000 MHz


\*  
 Del  
 Cor  
 Avg  
 16  
 H1d



CH1 Markers  
 2: 58.842  $\Omega$   
 2.2363  $\Omega$   
 5.60000 GHz  
 3: 53.906  $\Omega$   
 6.1094  $\Omega$   
 5.75000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -34.932 dB 5 250.000 000 MHz

Del  
 Cor  
 Avg  
 16  
 H1d



CH2 Markers  
 2: -21.538 dB  
 5.60000 GHz  
 3: -23.135 dB  
 5.75000 GHz



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D750V3-1054\_Mar16**

## CALIBRATION CERTIFICATE

Object **D750V3 - SN:1054**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **March 16, 2016**

*BN*  
*03/30/2016*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | US37292783         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | MY41092317         | 07-Oct-15 (No. 217-02223)         | Oct-16                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 01-Apr-15 (No. 217-02131)         | Mar-16                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 01-Apr-15 (No. 217-02134)         | Mar-16                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)    | Dec-16                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| RF generator R&S SMT-06     | 100972             | 15-Jun-15 (in house check Jun-15) | In house check: Jun-18 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

|                |                |                       |           |
|----------------|----------------|-----------------------|-----------|
|                | Name           | Function              | Signature |
| Calibrated by: | Jeton Kastrati | Laboratory Technician |           |
| Approved by:   | Katja Pokovic  | Technical Manager     |           |

Issued: March 16, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.



## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                        |             |
|-------------------------------------|------------------------|-------------|
| <b>DASY Version</b>                 | DASY5                  | V52.8.8     |
| <b>Extrapolation</b>                | Advanced Extrapolation |             |
| <b>Phantom</b>                      | Modular Flat Phantom   |             |
| <b>Distance Dipole Center - TSL</b> | 15 mm                  | with Spacer |
| <b>Zoom Scan Resolution</b>         | dx, dy, dz = 5 mm      |             |
| <b>Frequency</b>                    | 750 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 41.9           | 0.89 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 41.9 $\pm$ 6 % | 0.91 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.09 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>8.22 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.37 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>5.41 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Body TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Body TSL parameters</b>             | 22.0 °C             | 55.5           | 0.96 mho/m           |
| <b>Measured Body TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 54.7 $\pm$ 6 % | 0.98 mho/m $\pm$ 6 % |
| <b>Body TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 2.18 W/kg                                      |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>8.56 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 1.44 W/kg                                      |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>5.68 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 54.2 $\Omega$ - 0.9 j $\Omega$ |
| Return Loss                          | - 27.7 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.1 $\Omega$ - 2.3 j $\Omega$ |
| Return Loss                          | - 32.9 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.035 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | November 08, 2011 |

## DASY5 Validation Report for Head TSL

Date: 16.03.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1054**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.91 \text{ S/m}$ ;  $\epsilon_r = 41.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.28, 10.28, 10.28); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom Type: QD000P49AA
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue EX-Probe/Pin=250 mW, $d=15\text{mm}$ /Zoom Scan


(7x7x7)/Cube 0: Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 58.13 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.14 W/kg

**SAR(1 g) = 2.09 W/kg; SAR(10 g) = 1.37 W/kg**


Maximum value of SAR (measured) = 2.78 W/kg



# Impedance Measurement Plot for Head TSL

CH1 S11 1 U FS 15 Mar 2016 13:55:57  
1: 54.217  $\Omega$  -931.64  $m\Omega$  227.78 pF 750.000 000 MHz

\*  
De1  
CA



Avg  
16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-27.652 dB 750.000 000 MHz

CA

Avg  
16

H1d



# DASY5 Validation Report for Body TSL

Date: 16.03.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1054**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.98 \text{ S/m}$ ;  $\epsilon_r = 54.7$ ;  $\rho = 1000 \text{ kg/m}^3$

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.99, 9.99, 9.99); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom Type: QD000P49AA
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

## Dipole Calibration for Body Tissue EX-Probe/Pin=250 mW, d=15mm/Zoom Scan



(7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.90 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.24 W/kg

**SAR(1 g) = 2.18 W/kg; SAR(10 g) = 1.44 W/kg**

Maximum value of SAR (measured) = 2.89 W/kg



0 dB = 2.89 W/kg = 4.61 dBW/kg

# Impedance Measurement Plot for Body TSL


CH1 S11 1 U FS 1: 50.104  $\Omega$  -2.2773  $\Omega$  93.182 pF 16 Mar 2016 11:38:16 750.000 000 MHz

\*  
De1

CA

Avg  
16

H1d




CH2 S11 L06 5 dB/REF -20 dB 1:-32.854 dB 750.000 000 MHz

CA

Avg  
16

H1d





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D2450V2-981\_Jul16**

## CALIBRATION CERTIFICATE

Object **D2450V2 - SN:981**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **July 25, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289) | Apr-17                |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)       | Apr-17                |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)       | Apr-17                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)       | Apr-17                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)       | Apr-17                |
| Reference Probe EX3DV4      | SN: 7349           | 15-Jun-16 (No. EX3-7349_Jun16)  | Jun-17                |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)  | Dec-16                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Michael Weber**      Name: **Michael Weber**      Function: **Laboratory Technician**

Approved by: **Katja Pokovic**      Name: **Katja Pokovic**      Technical Manager

Signature

*M. Weber*  
*K. Pokovic*

Issued: July 27, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.



## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2450 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.2           | 1.80 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 38.0 $\pm$ 6 % | 1.86 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 13.5 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 52.8 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 6.26 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 24.7 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.7           | 1.95 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 51.8 $\pm$ 6 % | 2.03 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 13.0 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 50.8 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 6.04 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 23.8 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                               |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | $53.2\ \Omega + 3.4\ j\Omega$ |
| Return Loss                          | - 26.9 dB                     |

### Antenna Parameters with Body TSL

|                                      |                               |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | $50.2\ \Omega + 4.5\ j\Omega$ |
| Return Loss                          | - 27.0 dB                     |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.162 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | December 30, 2014 |

## DASY5 Validation Report for Head TSL

Date: 13.07.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN:981**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.86$  S/m;  $\epsilon_r = 38$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.72, 7.72, 7.72); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 115.8 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 27.4 W/kg

**SAR(1 g) = 13.5 W/kg; SAR(10 g) = 6.26 W/kg**

Maximum value of SAR (measured) = 22.5 W/kg




0 dB = 22.5 W/kg = 13.52 dBW/kg

Impedance Measurement Plot for Head TSL


13 Jul 2016 12:53:29  
CH1 S11 1 U FS 3: 53.234  $\Omega$  3.3633  $\Omega$  218.48  $\mu\text{H}$  2 450.000 000 MHz

\*  
De1  
CA  
Avg  
16  
H1d



CH2 S11 LOG 5 dB/REF -20 dB 3:-26.900 dB 2 450.000 000 MHz

CA  
Avg  
16  
H1d



## DASY5 Validation Report for Body TSL

Date: 25.07.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN:981**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.03$  S/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.79, 7.79, 7.79); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 107.1 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 26.0 W/kg

**SAR(1 g) = 13 W/kg; SAR(10 g) = 6.04 W/kg**

Maximum value of SAR (measured) = 21.4 W/kg




0 dB = 21.4 W/kg = 13.30 dBW/kg

# Impedance Measurement Plot for Body TSL

25 Jul 2016 10:03:11  
 CH1 S11 1 U FS 1: 50.184  $\Omega$  4.4980  $\Omega$  292.20 pH 2 450.000 000 MHz

\*  
 De1  
 CA




Avg  
 16

H1 d

CH2 S11 LOG 5 dB/ REF -20 dB 1: -26.957 dB 2 450.000 000 MHz

CA

H1 d





Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D750V3-1161\_Jul16**

## CALIBRATION CERTIFICATE

Object **D750V3 - SN:1161**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **July 13, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&T'E critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289) | Apr-17                |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)       | Apr-17                |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)       | Apr-17                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)       | Apr-17                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)       | Apr-17                |
| Reference Probe EX3DV4      | SN: 7349           | 15-Jun-16 (No. EX3-7349_Jun16)  | Jun-17                |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)  | Dec-16                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Claudio Leubler**      Name: **Claudio Leubler**      Function: **Laboratory Technician**

Approved by: **Katja Pokovic**      Technical Manager

Signature

Issued: July 13, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.



## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 750 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.9           | 0.89 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.9 $\pm$ 6 % | 0.91 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.09 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 8.17 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.37 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 5.39 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.5           | 0.96 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 55.1 $\pm$ 6 % | 0.99 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.16 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 8.43 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.41 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 5.53 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 55.6 $\Omega$ - 0.9 j $\Omega$ |
| Return Loss                          | - 25.4 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.2 $\Omega$ - 4.0 j $\Omega$ |
| Return Loss                          | - 28.0 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.033 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | November 19, 2015 |

## DASY5 Validation Report for Head TSL

Date: 13.07.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1161**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.91 \text{ S/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.07, 10.07, 10.07); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 58.07 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.13 W/kg

**SAR(1 g) = 2.09 W/kg; SAR(10 g) = 1.37 W/kg**

Maximum value of SAR (measured) = 2.80 W/kg




0 dB = 2.80 W/kg = 4.47 dBW/kg

# Impedance Measurement Plot for Head TSL

13 Jul 2016 09:55:53  
 [CH1] S11 1 U FS 1: 55.615  $\Omega$  -949.22 m $\Omega$  223.56 pF 750.000 000 MHz

\*  
 Del  
 CA



Avg  
 16


H1 d

CH2 S11 LOG 5 dB/REF -20 dB 1:-25.361 dB 750.000 000 MHz

CA

Avg  
 16

H1 d



## DASY5 Validation Report for Body TSL

Date: 13.07.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1161**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.99 \text{ S/m}$ ;  $\epsilon_r = 55.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.99, 9.99, 9.99); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/ $P_{in}=250 \text{ mW}$ , $d=15\text{mm}$ /Zoom Scan (7x7x7)/Cube 0:

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $56.33 \text{ V/m}$ ; Power Drift =  $-0.00 \text{ dB}$

Peak SAR (extrapolated) =  $3.22 \text{ W/kg}$

**SAR(1 g) =  $2.16 \text{ W/kg}$ ; SAR(10 g) =  $1.41 \text{ W/kg}$**

Maximum value of SAR (measured) =  $2.87 \text{ W/kg}$




0 dB =  $2.87 \text{ W/kg}$  =  $4.58 \text{ dBW/kg}$

# Impedance Measurement Plot for Body TSL

13 Jul 2016 13:16:34  
 [CH1] S11 1 U FS 1: 50.244  $\Omega$  -3.9707  $\Omega$  53.443 pF 750.000 000 MHz

\*  
 Del  
 CA




Avg  
 16

H1d

CH2 S11 L06 5 dB/REF -20 dB 1:-27.995 dB 750.000 000 MHz

CA



H1d



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D5GHzV2-1237\_Aug16**

## CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1237**

Calibration procedure(s) **QA CAL-22.v2**  
**Calibration procedure for dipole validation kits between 3-6 GHz**

✓PN  
8/9/16

Calibration date: **August 02, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289) | Apr-17                |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)       | Apr-17                |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)       | Apr-17                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)       | Apr-17                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)       | Apr-17                |
| Reference Probe EX3DV4      | SN: 3503           | 30-Jun-16 (No. EX3-3503_Jun16)  | Jun-17                |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)  | Dec-16                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Claudio Leubler**      Name: **Claudio Leubler**      Function: **Laboratory Technician**

Approved by: **Katja Pokovic**      Name: **Katja Pokovic**      Function: **Technical Manager**

Signature

Issued: August 4, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.



## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                                                                      |                                  |
|------------------------------|----------------------------------------------------------------------|----------------------------------|
| DASY Version                 | DASY5                                                                | V52.8.8                          |
| Extrapolation                | Advanced Extrapolation                                               |                                  |
| Phantom                      | Modular Flat Phantom V5.0                                            |                                  |
| Distance Dipole Center - TSL | 10 mm                                                                | with Spacer                      |
| Zoom Scan Resolution         | dx, dy = 4.0 mm, dz = 1.4 mm                                         | Graded Ratio = 1.4 (Z direction) |
| Frequency                    | 5250 MHz $\pm$ 1 MHz<br>5600 MHz $\pm$ 1 MHz<br>5750 MHz $\pm$ 1 MHz |                                  |

## Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 35.9           | 4.71 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 34.4 $\pm$ 6 % | 4.52 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL at 5250 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 100 mW input power | 8.00 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 79.2 W/kg $\pm$ 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 100 mW input power | 2.30 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 22.7 W/kg $\pm$ 19.5 % (k=2) |

### Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.5         | 5.07 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 33.9 ± 6 %   | 4.86 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5600 MHz

|                                                       |                    |                            |
|-------------------------------------------------------|--------------------|----------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                            |
| SAR measured                                          | 100 mW input power | 8.43 W/kg                  |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 83.3 W / kg ± 19.9 % (k=2) |

|                                                         |                    |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
| SAR measured                                            | 100 mW input power | 2.42 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.9 W/kg ± 19.5 % (k=2) |

### Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.4         | 5.22 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 33.7 ± 6 %   | 5.02 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5750 MHz

|                                                       |                    |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                          |
| SAR measured                                          | 100 mW input power | 8.25 W/kg                |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 81.5 W/kg ± 19.9 % (k=2) |

|                                                         |                    |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
| SAR measured                                            | 100 mW input power | 2.35 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.2 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5250 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.9         | 5.36 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.1 ± 6 %   | 5.42 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5250 MHz

|                                                       |                    |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
| SAR measured                                          | 100 mW input power | 7.54 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 74.8 W/kg ± 19.9 % (k=2) |

|                                                         |                    |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
| SAR measured                                            | 100 mW input power | 2.12 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.0 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.5         | 5.77 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.5 ± 6 %   | 5.88 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5600 MHz

|                                                       |                    |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
| SAR measured                                          | 100 mW input power | 7.76 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 77.0 W/kg ± 19.9 % (k=2) |

|                                                         |                    |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
| SAR measured                                            | 100 mW input power | 2.17 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.5 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5750 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.3         | 5.94 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.2 ± 6 %   | 6.11 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5750 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.60 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>75.4 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.11 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>20.9 W/kg ± 19.5 % (k=2)</b> |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL at 5250 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 48.6 $\Omega$ - 2.5 j $\Omega$ |
| Return Loss                          | - 30.7 dB                      |

### Antenna Parameters with Head TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.9 $\Omega$ + 1.5 j $\Omega$ |
| Return Loss                          | - 35.3 dB                      |

### Antenna Parameters with Head TSL at 5750 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 53.8 $\Omega$ + 5.8 j $\Omega$ |
| Return Loss                          | - 23.5 dB                      |

### Antenna Parameters with Body TSL at 5250 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 47.0 $\Omega$ - 3.9 j $\Omega$ |
| Return Loss                          | - 25.9 dB                      |

### Antenna Parameters with Body TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.5 $\Omega$ + 3.9 j $\Omega$ |
| Return Loss                          | - 27.7 dB                      |

### Antenna Parameters with Body TSL at 5750 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 53.8 $\Omega$ + 0.3 j $\Omega$ |
| Return Loss                          | - 28.6 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.193 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |              |
|-----------------|--------------|
| Manufactured by | SPEAG        |
| Manufactured on | May 04, 2015 |

## DASY5 Validation Report for Head TSL

Date: 02.08.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1237**

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz

Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.52$  S/m;  $\epsilon_r = 34.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.86$  S/m;  $\epsilon_r = 33.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.02$  S/m;  $\epsilon_r = 33.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.42, 5.42, 5.42); Calibrated: 30.06.2016; ConvF(4.89, 4.89, 4.89); Calibrated: 30.06.2016, ConvF(4.85, 4.85, 4.85); Calibrated: 30.06.2016,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 74.10 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 29.5 W/kg

**SAR(1 g) = 8 W/kg; SAR(10 g) = 2.3 W/kg**

Maximum value of SAR (measured) = 18.3 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 73.55 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 32.9 W/kg

**SAR(1 g) = 8.43 W/kg; SAR(10 g) = 2.42 W/kg**

Maximum value of SAR (measured) = 19.7 W/kg


**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 72.23 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 33.6 W/kg

**SAR(1 g) = 8.25 W/kg; SAR(10 g) = 2.35 W/kg**

Maximum value of SAR (measured) = 18.3 W/kg




0 dB = 18.3 W/kg = 12.62 dBW/kg

# Impedance Measurement Plot for Head TSL

2 Aug 2016 08:52:20  
 [CH1] S11 1 U FS 1: 48.623  $\Omega$  -2.5332  $\Omega$  11.967 pF 5 250.000 000 MHz


\*  
 Del  
 Cor  
 Avg  
 16  
 H1d



CH1 Markers  
 2: 50.867  $\Omega$   
 1.4961  $\Omega$   
 5.60000 GHz  
 3: 53.785  $\Omega$   
 5.8164  $\Omega$   
 5.75000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -30.691 dB 5 250.000 000 MHz

Cor  
 Avg  
 16  
 H1d



CH2 Markers  
 2: -35.297 dB  
 5.60000 GHz  
 3: -23.501 dB  
 5.75000 GHz



## DASY5 Validation Report for Body TSL

Date: 02.08.2016

Test Laboratory: SPEAG, Zurich, Switzerland

### DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1237

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz

Medium parameters used:  $f = 5250$  MHz;  $\sigma = 5.42$  S/m;  $\epsilon_r = 47.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.88$  S/m;  $\epsilon_r = 46.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Medium parameters used:  $f = 5750$  MHz;  $\sigma = 6.11$  S/m;  $\epsilon_r = 46.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(4.85, 4.85, 4.85); Calibrated: 30.06.2016, ConvF(4.35, 4.35, 4.35); Calibrated: 30.06.2016, ConvF(4.3, 4.3, 4.3); Calibrated: 30.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAB4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7372)

#### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 67.19 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 28.4 W/kg

**SAR(1 g) = 7.54 W/kg; SAR(10 g) = 2.12 W/kg**

Maximum value of SAR (measured) = 17.3 W/kg

#### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.80 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 31.9 W/kg

**SAR(1 g) = 7.76 W/kg; SAR(10 g) = 2.17 W/kg**

Maximum value of SAR (measured) = 18.3 W/kg



#### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.31 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 32.6 W/kg

**SAR(1 g) = 7.6 W/kg; SAR(10 g) = 2.11 W/kg**

Maximum value of SAR (measured) = 18.4 W/kg




0 dB = 17.3 W/kg = 12.38 dBW/kg

# Impedance Measurement Plot for Body TSL

2 Aug 2016 08:49:13  
 CH1 S11 1 U FS 1: 46.998  $\Omega$  -3.8984  $\Omega$  7.7763 pF 5 250.000 000 MHz


\*  
 Del  
 Cor  
 Avg  
 16  
 H1d



CH1 Markers  
 2: 51.525  $\Omega$   
 3.8945  $\Omega$   
 5.60000 GHz  
 3: 53.848  $\Omega$   
 0.2930  $\Omega$   
 5.75000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -25.900 dB 5 250.000 000 MHz

Cor  
 Avg  
 16  
 H1d



CH2 Markers  
 2: -27.699 dB  
 5.60000 GHz  
 3: -28.596 dB  
 5.75000 GHz



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D835V2-4d133\_Jul16**

## CALIBRATION CERTIFICATE

Object **D835V2 - SN:4d133**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **July 14, 2016**

BN ✓  
07/27/2016

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)         | Apr-17                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 15-Jun-16 (No. EX3-7349_Jun16)    | Jun-17                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: GB37480704     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: US37292783     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: MY41092317     | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06     | SN: 100972         | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E   | SN: US37390585     | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Jeton Kastrati**

Function  
**Laboratory Technician**

Signature

Approved by: **Kalja Pokovic**

Technical Manager

Issued: July 14, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 835 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.5           | 0.90 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.6 $\pm$ 6 % | 0.94 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.42 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 9.32 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.57 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 6.10 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.2           | 0.97 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 54.9 $\pm$ 6 % | 1.01 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.45 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 9.50 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.59 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 6.20 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.5 $\Omega$ - 5.1 j $\Omega$ |
| Return Loss                          | - 25.7 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 46.4 $\Omega$ - 7.5 j $\Omega$ |
| Return Loss                          | - 21.3 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.395 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |               |
|-----------------|---------------|
| Manufactured by | SPEAG         |
| Manufactured on | July 22, 2011 |

## DASY5 Validation Report for Head TSL

Date: 14.07.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d133**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.94$  S/m;  $\epsilon_r = 40.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.72, 9.72, 9.72); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 61.36 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.64 W/kg

**SAR(1 g) = 2.42 W/kg; SAR(10 g) = 1.57 W/kg**

Maximum value of SAR (measured) = 3.23 W/kg



0 dB = 3.23 W/kg = 5.09 dBW/kg




# Impedance Measurement Plot for Head TSL

14 Jul 2016 11:38:16  
 CH1 S11 1 U FS 1: 50.514  $\Omega$  -5.1445  $\Omega$  37.050 pF 835.000 000 MHz

\*  
 Del  
 CA

Avg  
 16


H1d



CH2 S11 LOG 5 dB/REF -20 dB 1:-25.729 dB 835.000 000 MHz

CA

H1d



## DASY5 Validation Report for Body TSL

Date: 13.07.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d133**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 1.01 \text{ S/m}$ ;  $\epsilon_r = 54.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.73, 9.73, 9.73); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 59.93 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.62 W/kg

**SAR(1 g) = 2.45 W/kg; SAR(10 g) = 1.59 W/kg**

Maximum value of SAR (measured) = 3.24 W/kg




0 dB = 3.24 W/kg = 5.11 dBW/kg

Impedance Measurement Plot for Body TSL


13 Jul 2016 09:27:58  
[CH1] S11 1 U FS 1: 46.404  $\Omega$  -7.4727  $\Omega$  25.505 pF 835.000 000 MHz

\*  
De1  
CA  
Avg  
16  
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1:-21.336 dB 835.000 000 MHz

CA  
Avg  
16  
H1d





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D835V2-4d047\_Jul16**

## CALIBRATION CERTIFICATE

Object **D835V2 - SN:4d047**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **July 13, 2016**

BNV  
 7/16/2016

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)         | Apr-17                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 15-Jun-16 (No. EX3-7349_Jun16)    | Jun-17                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: GB37480704     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: US37292783     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: MY41092317     | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06     | SN: 100972         | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E   | SN: US37390585     | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Jeton Kastrati** Name  
 Function  
**Laboratory Technician**

Approved by: **Katja Pokovic** Name  
 Function  
**Technical Manager**

Signature

Issued: July 13, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- e) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 835 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.5           | 0.90 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.6 $\pm$ 6 % | 0.94 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.37 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 9.13 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.53 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 5.95 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.2           | 0.97 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 54.9 $\pm$ 6 % | 1.01 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.47 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 9.57 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.60 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 6.24 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.8 $\Omega$ - 5.9 j $\Omega$ |
| Return Loss                          | - 24.5 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 45.8 $\Omega$ - 8.2 j $\Omega$ |
| Return Loss                          | - 20.3 dB                      |

### General Antenna Parameters and Design

|                                  |         |
|----------------------------------|---------|
| Electrical Delay (one direction) | None ns |
|----------------------------------|---------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                 |
|-----------------|-----------------|
| Manufactured by | SPEAG           |
| Manufactured on | August 16, 2006 |

## DASY5 Validation Report for Head TSL

Date: 13.07.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:4d047**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.94 \text{ S/m}$ ;  $\epsilon_r = 40.6$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.72, 9.72, 9.72); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 60.98 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.56 W/kg

**SAR(1 g) = 2.37 W/kg; SAR(10 g) = 1.53 W/kg**

Maximum value of SAR (measured) = 3.17 W/kg




0 dB = 3.17 W/kg = 5.01 dBW/kg



# Impedance Measurement Plot for Head TSL

13 Jul 2016 12:00:27  
 CH1 S11 1 U FS 1: 49.820  $\Omega$  -5.9316  $\Omega$  32.134 pF 835.000 000 MHz

\*  
 Del  
 CA



Avg  
 16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-24.525 dB 835.000 000 MHz

CA

Avg  
 16

H1d



## DASY5 Validation Report for Body TSL

Date: 13.07.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:4d047**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 1.01 \text{ S/m}$ ;  $\epsilon_r = 54.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.73, 9.73, 9.73); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 59.88 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.67 W/kg


**SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.6 W/kg**

Maximum value of SAR (measured) = 3.27 W/kg



0 dB = 3.27 W/kg = 5.15 dBW/kg

Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **ES3-3022\_Aug15**

## CALIBRATION CERTIFICATE

Object **ES3DV2 - SN:3022**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **August 26, 2015**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 01-Apr-15 (No. 217-02128)         | Mar-16                 |
| Power sensor E4412A        | MY41498087      | 01-Apr-15 (No. 217-02128)         | Mar-16                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 01-Apr-15 (No. 217-02129)         | Mar-16                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 01-Apr-15 (No. 217-02132)         | Mar-16                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 01-Apr-15 (No. 217-02133)         | Mar-16                 |
| Reference Probe ES3DV2     | SN: 3013        | 30-Dec-14 (No. ES3-3013_Dec14)    | Dec-15                 |
| DAE4                       | SN: 660         | 14-Jan-15 (No. DAE4-660_Jan15)    | Jan-16                 |
|                            |                 |                                   |                        |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-16 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-14) | In house check: Oct-15 |

|                                                                                                                                                       |                              |                                          |                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|------------------------------------------|----------------------------------------------------------------------------------------------------|
| Calibrated by:                                                                                                                                        | Name<br><b>Michael Weber</b> | Function<br><b>Laboratory Technician</b> | Signature<br> |
| Approved by:                                                                                                                                          | <b>Katja Pokovic</b>         | <b>Technical Manager</b>                 |               |
| <p>Issued: August 27, 2015</p> <p>This calibration certificate shall not be reproduced except in full without written approval of the laboratory.</p> |                              |                                          |                                                                                                    |



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                       |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |
| Connector Angle          | information used in DASY system to align probe sensor X to the robot coordinate system                                                                  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below **ConvF**).
- NORM( $f$ )<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of **ConvF**.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for **ConvF**. A frequency dependent **ConvF** is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

# Probe ES3DV2

## SN:3022

Manufactured: April 15, 2003  
Calibrated: August 26, 2015

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

# DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

## Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 1.00     | 1.03     | 0.95     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 99.9     | 99.7     | 100.9    |               |

## Modulation Calibration Parameters

| UID           | Communication System Name                     |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C    | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|---------------|-----------------------------------------------|---|---------|------------------------------|------|---------|----------|---------------------------|
| 0             | CW                                            | X | 0.0     | 0.0                          | 1.0  | 0.00    | 179.6    | $\pm 3.3 \%$              |
|               |                                               | Y | 0.0     | 0.0                          | 1.0  |         | 183.9    |                           |
|               |                                               | Z | 0.0     | 0.0                          | 1.0  |         | 179.0    |                           |
| 10010-<br>CAA | SAR Validation (Square, 100ms, 10ms)          | X | 3.60    | 65.9                         | 14.2 | 10.00   | 43.5     | $\pm 2.2 \%$              |
|               |                                               | Y | 2.84    | 63.5                         | 13.0 |         | 43.3     |                           |
|               |                                               | Z | 2.76    | 63.7                         | 12.7 |         | 41.7     |                           |
| 10011-<br>CAB | UMTS-FDD (WCDMA)                              | X | 3.32    | 67.0                         | 18.7 | 2.91    | 144.4    | $\pm 0.7 \%$              |
|               |                                               | Y | 3.24    | 66.3                         | 18.0 |         | 147.3    |                           |
|               |                                               | Z | 3.19    | 66.3                         | 18.0 |         | 143.5    |                           |
| 10012-<br>CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)      | X | 3.15    | 69.9                         | 19.5 | 1.87    | 146.1    | $\pm 0.7 \%$              |
|               |                                               | Y | 2.88    | 67.7                         | 18.0 |         | 147.9    |                           |
|               |                                               | Z | 2.78    | 67.4                         | 17.8 |         | 145.6    |                           |
| 10013-<br>CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps) | X | 11.40   | 71.3                         | 23.8 | 9.46    | 144.9    | $\pm 3.3 \%$              |
|               |                                               | Y | 11.15   | 70.5                         | 23.1 |         | 146.9    |                           |
|               |                                               | Z | 10.95   | 70.5                         | 23.3 |         | 140.3    |                           |
| 10021-<br>DAB | GSM-FDD (TDMA, GMSK)                          | X | 20.66   | 99.8                         | 29.2 | 9.39    | 132.6    | $\pm 2.2 \%$              |
|               |                                               | Y | 14.36   | 93.3                         | 26.6 |         | 145.3    |                           |
|               |                                               | Z | 17.17   | 97.2                         | 27.8 |         | 145.4    |                           |
| 10023-<br>DAB | GPRS-FDD (TDMA, GMSK, TN 0)                   | X | 17.22   | 96.5                         | 28.2 | 9.57    | 125.4    | $\pm 1.9 \%$              |
|               |                                               | Y | 11.06   | 88.6                         | 25.0 |         | 136.0    |                           |
|               |                                               | Z | 8.71    | 84.6                         | 23.4 |         | 130.7    |                           |
| 10024-<br>DAB | GPRS-FDD (TDMA, GMSK, TN 0-1)                 | X | 31.05   | 99.5                         | 25.9 | 6.56    | 135.2    | $\pm 2.2 \%$              |
|               |                                               | Y | 25.28   | 97.4                         | 25.0 |         | 132.5    |                           |
|               |                                               | Z | 21.58   | 95.7                         | 24.5 |         | 144.4    |                           |
| 10027-<br>DAB | GPRS-FDD (TDMA, GMSK, TN 0-1-2)               | X | 42.88   | 99.9                         | 24.0 | 4.80    | 129.5    | $\pm 1.9 \%$              |
|               |                                               | Y | 40.80   | 99.6                         | 23.7 |         | 124.9    |                           |
|               |                                               | Z | 38.42   | 99.7                         | 23.7 |         | 137.8    |                           |
| 10028-<br>DAB | GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)             | X | 44.48   | 100.0                        | 23.2 | 3.55    | 138.2    | $\pm 1.9 \%$              |
|               |                                               | Y | 44.03   | 99.7                         | 22.8 |         | 133.0    |                           |
|               |                                               | Z | 41.36   | 99.8                         | 22.8 |         | 147.5    |                           |
| 10032-<br>CAA | IEEE 802.15.1 Bluetooth (GFSK, DH5)           | X | 16.08   | 99.5                         | 23.3 | 1.16    | 127.5    | $\pm 1.4 \%$              |
|               |                                               | Y | 79.69   | 99.6                         | 19.3 |         | 146.2    |                           |
|               |                                               | Z | 45.81   | 99.9                         | 20.4 |         | 138.2    |                           |
| 10100-<br>CAB | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)      | X | 6.43    | 67.4                         | 19.8 | 5.67    | 138.7    | $\pm 1.4 \%$              |
|               |                                               | Y | 6.27    | 66.8                         | 19.2 |         | 134.9    |                           |
|               |                                               | Z | 6.16    | 66.6                         | 19.2 |         | 127.6    |                           |

|           |                                          |   |       |      |      |      |       |        |
|-----------|------------------------------------------|---|-------|------|------|------|-------|--------|
| 10103-CAB | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK) | X | 10.13 | 75.0 | 25.9 | 9.29 | 129.4 | ±3.3 % |
|           |                                          | Y | 9.46  | 73.0 | 24.5 |      | 131.8 |        |
|           |                                          | Z | 9.52  | 74.0 | 25.4 |      | 137.0 |        |
| 10108-CAC | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK) | X | 6.27  | 66.9 | 19.7 | 5.80 | 137.0 | ±1.7 % |
|           |                                          | Y | 6.24  | 66.7 | 19.3 |      | 140.0 |        |
|           |                                          | Z | 6.06  | 66.3 | 19.2 |      | 127.1 |        |
| 10117-CAB | IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK) | X | 10.16 | 68.7 | 21.3 | 8.07 | 127.7 | ±2.2 % |
|           |                                          | Y | 9.99  | 68.2 | 20.9 |      | 131.5 |        |
|           |                                          | Z | 10.22 | 69.1 | 21.4 |      | 141.6 |        |
| 10151-CAB | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)  | X | 9.34  | 73.4 | 25.2 | 9.28 | 125.0 | ±3.3 % |
|           |                                          | Y | 8.92  | 72.2 | 24.3 |      | 127.2 |        |
|           |                                          | Z | 8.95  | 73.1 | 25.1 |      | 131.9 |        |
| 10154-CAC | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)  | X | 5.95  | 66.4 | 19.4 | 5.75 | 134.4 | ±1.4 % |
|           |                                          | Y | 5.92  | 66.2 | 19.1 |      | 137.0 |        |
|           |                                          | Z | 5.98  | 66.7 | 19.5 |      | 146.8 |        |
| 10160-CAB | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)  | X | 6.39  | 66.9 | 19.6 | 5.82 | 139.9 | ±1.7 % |
|           |                                          | Y | 6.35  | 66.7 | 19.3 |      | 141.9 |        |
|           |                                          | Z | 6.15  | 66.2 | 19.2 |      | 128.4 |        |
| 10169-CAB | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)    | X | 4.96  | 66.6 | 19.8 | 5.73 | 137.3 | ±1.4 % |
|           |                                          | Y | 4.85  | 66.1 | 19.3 |      | 139.8 |        |
|           |                                          | Z | 4.85  | 66.6 | 19.7 |      | 146.7 |        |
| 10172-CAB | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)    | X | 8.75  | 78.7 | 28.3 | 9.21 | 138.9 | ±3.0 % |
|           |                                          | Y | 7.69  | 75.1 | 26.1 |      | 140.1 |        |
|           |                                          | Z | 7.80  | 76.6 | 27.2 |      | 144.0 |        |
| 10175-CAC | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)    | X | 4.88  | 66.2 | 19.6 | 5.72 | 132.0 | ±1.4 % |
|           |                                          | Y | 4.77  | 65.8 | 19.1 |      | 132.6 |        |
|           |                                          | Z | 4.83  | 66.5 | 19.6 |      | 146.0 |        |
| 10181-CAB | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)    | X | 4.91  | 66.3 | 19.7 | 5.72 | 131.7 | ±1.4 % |
|           |                                          | Y | 4.82  | 66.0 | 19.2 |      | 138.4 |        |
|           |                                          | Z | 4.86  | 66.7 | 19.7 |      | 145.7 |        |
| 10196-CAB | IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)  | X | 10.04 | 69.1 | 21.7 | 8.10 | 140.9 | ±2.2 % |
|           |                                          | Y | 9.62  | 67.9 | 20.8 |      | 125.2 |        |
|           |                                          | Z | 9.74  | 68.6 | 21.3 |      | 133.3 |        |
| 10225-CAB | UMTS-FDD (HSPA+)                         | X | 7.01  | 67.1 | 19.6 | 5.97 | 143.7 | ±1.4 % |
|           |                                          | Y | 6.78  | 66.2 | 19.0 |      | 129.3 |        |
|           |                                          | Z | 6.80  | 66.7 | 19.3 |      | 136.5 |        |
| 10237-CAB | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)    | X | 8.55  | 78.0 | 27.9 | 9.21 | 134.6 | ±3.0 % |
|           |                                          | Y | 7.79  | 75.6 | 26.3 |      | 141.6 |        |
|           |                                          | Z | 7.89  | 76.9 | 27.4 |      | 145.2 |        |
| 10252-CAB | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)  | X | 9.30  | 74.8 | 26.1 | 9.24 | 134.8 | ±3.3 % |
|           |                                          | Y | 8.65  | 72.5 | 24.5 |      | 136.4 |        |
|           |                                          | Z | 8.33  | 72.3 | 24.8 |      | 126.6 |        |
| 10267-CAB | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK) | X | 10.20 | 76.2 | 26.8 | 9.30 | 144.8 | ±3.3 % |
|           |                                          | Y | 9.41  | 73.7 | 25.1 |      | 145.9 |        |
|           |                                          | Z | 9.18  | 73.9 | 25.6 |      | 138.6 |        |



|           |                                                               |   |       |      |      |      |       |        |
|-----------|---------------------------------------------------------------|---|-------|------|------|------|-------|--------|
| 10275-CAB | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)                      | X | 4.45  | 66.7 | 18.9 | 3.96 | 147.0 | ±0.9 % |
|           |                                                               | Y | 4.21  | 65.5 | 17.9 |      | 126.5 |        |
|           |                                                               | Z | 4.36  | 66.5 | 18.5 |      | 148.0 |        |
| 10291-AAB | CDMA2000, RC3, SO55, Full Rate                                | X | 3.57  | 66.3 | 18.5 | 3.46 | 134.3 | ±0.7 % |
|           |                                                               | Y | 3.48  | 65.6 | 17.8 |      | 136.8 |        |
|           |                                                               | Z | 3.51  | 66.2 | 18.3 |      | 136.4 |        |
| 10292-AAB | CDMA2000, RC3, SO32, Full Rate                                | X | 3.53  | 66.4 | 18.6 | 3.39 | 135.8 | ±0.7 % |
|           |                                                               | Y | 3.45  | 65.8 | 17.9 |      | 140.4 |        |
|           |                                                               | Z | 3.50  | 66.5 | 18.5 |      | 137.0 |        |
| 10297-AAA | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)                       | X | 6.18  | 66.5 | 19.5 | 5.81 | 129.4 | ±1.4 % |
|           |                                                               | Y | 6.15  | 66.3 | 19.1 |      | 133.6 |        |
|           |                                                               | Z | 6.13  | 66.5 | 19.3 |      | 131.2 |        |
| 10311-AAA | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                      | X | 6.77  | 67.2 | 19.9 | 6.06 | 134.8 | ±1.7 % |
|           |                                                               | Y | 6.81  | 67.3 | 19.7 |      | 144.8 |        |
|           |                                                               | Z | 6.68  | 67.1 | 19.7 |      | 136.7 |        |
| 10400-AAC | IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)           | X | 10.30 | 69.4 | 22.0 | 8.37 | 142.0 | ±2.5 % |
|           |                                                               | Y | 9.90  | 68.2 | 21.1 |      | 126.8 |        |
|           |                                                               | Z | 10.15 | 69.3 | 21.9 |      | 142.6 |        |
| 10403-AAB | CDMA2000 (1xEV-DO, Rev. 0)                                    | X | 4.72  | 68.1 | 18.9 | 3.76 | 147.8 | ±0.7 % |
|           |                                                               | Y | 4.56  | 67.5 | 18.2 |      | 133.6 |        |
|           |                                                               | Z | 4.61  | 68.2 | 18.7 |      | 147.4 |        |
| 10404-AAB | CDMA2000 (1xEV-DO, Rev. A)                                    | X | 4.57  | 67.8 | 18.8 | 3.77 | 144.3 | ±0.7 % |
|           |                                                               | Y | 4.43  | 67.3 | 18.1 |      | 131.3 |        |
|           |                                                               | Z | 4.57  | 68.3 | 18.8 |      | 145.0 |        |
| 10415-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)     | X | 2.64  | 67.9 | 18.7 | 1.54 | 142.1 | ±0.5 % |
|           |                                                               | Y | 2.36  | 65.4 | 16.8 |      | 130.3 |        |
|           |                                                               | Z | 2.50  | 66.7 | 17.7 |      | 145.0 |        |
| 10416-AAA | IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle) | X | 10.04 | 69.0 | 21.7 | 8.23 | 138.8 | ±2.2 % |
|           |                                                               | Y | 9.71  | 68.0 | 20.9 |      | 125.6 |        |
|           |                                                               | Z | 9.94  | 69.0 | 21.6 |      | 140.4 |        |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 7 and 8).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 750                  | 41.9                               | 0.89                            | 6.33    | 6.33    | 6.33    | 0.46               | 1.43                    | ± 12.0 %  |
| 835                  | 41.5                               | 0.90                            | 6.11    | 6.11    | 6.11    | 0.24               | 2.08                    | ± 12.0 %  |
| 1750                 | 40.1                               | 1.37                            | 5.08    | 5.08    | 5.08    | 0.45               | 1.47                    | ± 12.0 %  |
| 1900                 | 40.0                               | 1.40                            | 4.93    | 4.93    | 4.93    | 0.59               | 1.25                    | ± 12.0 %  |
| 2300                 | 39.5                               | 1.67                            | 4.63    | 4.63    | 4.63    | 0.55               | 1.39                    | ± 12.0 %  |
| 2450                 | 39.2                               | 1.80                            | 4.30    | 4.30    | 4.30    | 0.51               | 1.47                    | ± 12.0 %  |
| 2600                 | 39.0                               | 1.96                            | 4.12    | 4.12    | 4.12    | 0.57               | 1.46                    | ± 12.0 %  |

<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 750                  | 55.5                               | 0.96                            | 6.16    | 6.16    | 6.16    | 0.50               | 1.34                    | ± 12.0 %  |
| 835                  | 55.2                               | 0.97                            | 6.13    | 6.13    | 6.13    | 0.25               | 2.16                    | ± 12.0 %  |
| 1750                 | 53.4                               | 1.49                            | 4.79    | 4.79    | 4.79    | 0.61               | 1.33                    | ± 12.0 %  |
| 1900                 | 53.3                               | 1.52                            | 4.56    | 4.56    | 4.56    | 0.31               | 2.02                    | ± 12.0 %  |
| 2300                 | 52.9                               | 1.81                            | 4.32    | 4.32    | 4.32    | 0.79               | 1.19                    | ± 12.0 %  |
| 2450                 | 52.7                               | 1.95                            | 4.08    | 4.08    | 4.08    | 0.80               | 1.12                    | ± 12.0 %  |
| 2600                 | 52.5                               | 2.16                            | 3.96    | 3.96    | 3.96    | 0.80               | 1.10                    | ± 12.0 %  |


<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## Frequency Response of E-Field


(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

Receiving Pattern ( $\phi$ ),  $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

**Dynamic Range  $f(\text{SAR}_{\text{head}})$**   
(TEM cell ,  $f_{\text{eval}}= 1900 \text{ MHz}$ )





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$



## DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | 98.5       |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 10 mm      |
| Tip Diameter                                  | 4 mm       |
| Probe Tip to Sensor X Calibration Point       | 2 mm       |
| Probe Tip to Sensor Y Calibration Point       | 2 mm       |
| Probe Tip to Sensor Z Calibration Point       | 2 mm       |
| Recommended Measurement Distance from Surface | 3 mm       |