

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h) §27.53(m)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level for Band 41 is as noted in the Test Notes on the following page.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq 1\%$ of the emission bandwidth
4. VBW $\geq 3 \times$ RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup


Test Notes

Per 22.917(b) 24.238(a) 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 64 of 148


Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

Per 27.53(m) for operations in the BRS/EBS bands, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.



Plot 7-96. Lower Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 65 of 148



Plot 7-97. Lower Extended Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)




Plot 7-98. Upper Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 66 of 148




Plot 7-99. Upper Extended Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)




Plot 7-100. Lower Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 67 of 148



Plot 7-101. Lower Extended Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)




Plot 7-102. Upper Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 68 of 148




Plot 7-103. Upper Extended Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)




Plot 7-104. Lower Band Edge Plot (Band 12/17 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 69 of 148




Plot 7-105. Lower Extended Band Edge Plot (Band 12/17 - 5.0MHz QPSK - RB Size 25)




Plot 7-106. Upper Band Edge Plot (Band 12/17 - 5.0MHz QPSK - RB Size 25)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 70 of 148




Plot 7-107. Upper Extended Band Edge Plot (Band 12/17 – 5.0MHz QPSK – RB Size 25)




Plot 7-108. Lower Band Edge Plot (Band 12/17 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 71 of 148




Plot 7-109. Lower Extended Band Edge Plot (Band 12/17 – 10.0MHz QPSK – RB Size 50)




Plot 7-110. Upper Band Edge Plot (Band 12/17 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 72 of 148



Plot 7-111. Upper Extended Band Edge Plot (Band 12/17 - 10.0MHz QPSK - RB Size 50)




Plot 7-112. Lower Band Edge Plot (Band 5/26 - 1.4MHz QPSK - RB Size 6)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 73 of 148




Plot 7-113. Upper Band Edge Plot (Band 5/26 – 1.4MHz QPSK – RB Size 6)




Plot 7-114. Lower Band Edge Plot (Band 5/26 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 74 of 148




Plot 7-115. Upper Band Edge Plot (Band 5/26 – 3.0MHz QPSK – RB Size 15)




Plot 7-116. Lower Band Edge Plot (Band 5/26 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 75 of 148




Plot 7-117. Upper Band Edge Plot (Band 5/26 – 5.0MHz QPSK – RB Size 25)




Plot 7-118. Lower Band Edge Plot (Band 5/26 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 76 of 148




Plot 7-119. Upper Band Edge Plot (Band 5/26 – 10.0MHz QPSK – RB Size 50)




Plot 7-120. Lower Band Edge Plot (Band 26 – 15.0MHz QPSK – RB Size 50)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 77 of 148	




Plot 7-121. Upper Band Edge Plot (Band 26 – 15.0MHz QPSK – RB Size 50)



Plot 7-122. Lower Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 78 of 148




Plot 7-123. Lower Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 7-124. Upper Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 79 of 148




Plot 7-125. Upper Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 7-126. Lower Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 80 of 148




Plot 7-127. Lower Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 7-128. Upper Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 81 of 148




Plot 7-129. Upper Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 7-130. Lower Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 82 of 148




Plot 7-131. Lower Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 7-132. Upper Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 83 of 148




Plot 7-133. Upper Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 7-134. Lower Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 84 of 148




Plot 7-135. Lower Extended Band Edge Plot (Band 4 - 10.0MHz QPSK - RB Size 50)




Plot 7-136. Upper Band Edge Plot (Band 4 - 10.0MHz QPSK - RB Size 50)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 85 of 148




Plot 7-137. Upper Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)




Plot 7-138. Lower Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 86 of 148




Plot 7-139. Lower Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 7-140. Upper Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 87 of 148




Plot 7-141. Upper Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 7-142. Lower Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 88 of 148




Plot 7-143. Lower Extended Band Edge Plot (Band 4 - 20.0MHz QPSK - RB Size 100)




Plot 7-144. Upper Band Edge Plot (Band 4 - 20.0MHz QPSK - RB Size 100)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 89 of 148



Plot 7-145. Upper Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)




Plot 7-146. Lower Band Edge Plot (Band 25 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 90 of 148




Plot 7-147. Lower Extended Band Edge Plot (Band 25 – 1.4MHz QPSK – RB Size 6)




Plot 7-148. Upper Band Edge Plot (Band 25 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 91 of 148




Plot 7-149. Upper Extended Band Edge Plot (Band 25 – 1.4MHz QPSK – RB Size 6)




Plot 7-150. Lower Band Edge Plot (Band 25 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 92 of 148




Plot 7-151. Lower Extended Band Edge Plot (Band 25 – 3.0MHz QPSK – RB Size 15)




Plot 7-152. Upper Band Edge Plot (Band 25 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 93 of 148




Plot 7-153. Upper Extended Band Edge Plot (Band 25 – 3.0MHz QPSK – RB Size 15)




Plot 7-154. Lower Band Edge Plot (Band 25 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 94 of 148




Plot 7-155. Lower Extended Band Edge Plot (Band 25 – 5.0MHz QPSK – RB Size 25)




Plot 7-156. Upper Band Edge Plot (Band 25 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 95 of 148




Plot 7-157. Upper Extended Band Edge Plot (Band 25 – 5.0MHz QPSK – RB Size 25)



Plot 7-158. Lower Band Edge Plot (Band 25 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 96 of 148




Plot 7-159. Lower Extended Band Edge Plot (Band 25 – 10.0MHz QPSK – RB Size 50)




Plot 7-160. Upper Band Edge Plot (Band 25 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 97 of 148




Plot 7-161. Upper Extended Band Edge Plot (Band 25 – 10.0MHz QPSK – RB Size 50)




Plot 7-162. Lower Band Edge Plot (Band 25 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 98 of 148




Plot 7-163. Lower Extended Band Edge Plot (Band 25 – 15.0MHz QPSK – RB Size 75)




Plot 7-164. Upper Band Edge Plot (Band 25 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 99 of 148




Plot 7-165. Upper Extended Band Edge Plot (Band 25 – 15.0MHz QPSK – RB Size 75)



Plot 7-166. Lower Band Edge Plot (Band 25 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 100 of 148



Plot 7-167. Lower Extended Band Edge Plot (Band 25 – 20.0MHz QPSK – RB Size 100)




Plot 7-168. Upper Band Edge Plot (Band 25 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 101 of 148




Plot 7-169. Upper Extended Band Edge Plot (Band 25 – 20.0MHz QPSK – RB Size 100)




Plot 7-170. Lower ACP Plot (Band 41 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 102 of 148	




Plot 7-171. Upper ACP Plot (Band 41 – 5.0MHz QPSK – RB Size 25)




Plot 7-172. Lower ACP Plot (Band 41 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMN935KOR	 PCTEST ENGINEERING LABORATORY, INC.		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 103 of 148		




Plot 7-173. Upper ACP Plot (Band 41 – 10.0MHz QPSK – RB Size 50)




Plot 7-174. Lower ACP Plot (Band 41 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 104 of 148




Plot 7-175. Upper ACP Plot (Band 41 – 15.0MHz QPSK – RB Size 75)



Plot 7-176. Lower ACP Plot (Band 41 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 105 of 148	



Plot 7-177. Upper ACP Plot (Band 41 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 106 of 148

7.5 Peak-Average Ratio

§24.232(d)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 107 of 148	




Plot 7-178. PAR Plot (Band 2/25 – 1.4MHz QPSK – RB Size 6)




Plot 7-179. PAR Plot (Band 2/25 – 1.4MHz 16-QAM – RB Size 6)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 108 of 148




Plot 7-180. PAR Plot (Band 2/25 – 3.0MHz QPSK – RB Size 15)




Plot 7-181. PAR Plot (Band 2/25 – 3.0MHz 16-QAM – RB Size 15)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 109 of 148




Plot 7-182. PAR Plot (Band 2/25 – 5.0MHz QPSK – RB Size 25)




Plot 7-183. PAR Plot (Band 2/25 – 5.0MHz 16-QAM – RB Size 25)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 110 of 148




Plot 7-184. PAR Plot (Band 2/25 – 10.0MHz QPSK – RB Size 50)




Plot 7-185. PAR Plot (Band 2/25 – 10.0MHz 16-QAM – RB Size 50)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 111 of 148




Plot 7-186. PAR Plot (Band 2/25 – 15.0MHz QPSK – RB Size 75)




Plot 7-187. PAR Plot (Band 2/25 – 15.0MHz 16-QAM – RB Size 75)

FCC ID: A3LSMN935KOR	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 112 of 148



Plot 7-188. PAR Plot (Band 2/25 – 20.0MHz QPSK – RB Size 100)



Plot 7-189. PAR Plot (Band 2/25 – 20.0MHz 16-QAM – RB Size 100)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 113 of 148

7.6 Radiated Power (ERP/EIRP)

§22.913(a.2) §24.232(c.2) §27.50(h.2) §27.50(c.10) §27.50(d.4)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq$ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 114 of 148

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup >1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 115 of 148

7.6.1 Antenna A Radiated Power (ERP/EIRP)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
699.70	1.4	QPSK	H	291	11	1 / 5	12.95	2.12	15.07	34.77	-19.70
707.50	1.4	QPSK	H	267	10	1 / 5	12.73	2.31	15.04	34.77	-19.73
715.30	1.4	QPSK	H	297	32	1 / 5	12.10	2.50	14.60	34.77	-20.17
699.70	1.4	16-QAM	H	291	11	1 / 5	11.61	2.12	13.73	34.77	-21.04
707.50	1.4	16-QAM	H	267	10	1 / 5	11.65	2.31	13.96	34.77	-20.81
715.30	1.4	16-QAM	H	297	32	1 / 5	11.13	2.50	13.63	34.77	-21.14
700.50	3	QPSK	H	265	19	1 / 0	13.36	2.12	15.48	34.77	-19.29
707.50	3	QPSK	H	266	22	1 / 14	13.63	2.31	15.94	34.77	-18.83
714.50	3	QPSK	H	275	26	1 / 0	12.49	2.50	14.99	34.77	-19.78
700.50	3	16-QAM	H	265	19	1 / 0	12.15	2.12	14.27	34.77	-20.50
707.50	3	16-QAM	H	266	22	1 / 14	12.02	2.31	14.33	34.77	-20.44
714.50	3	16-QAM	H	275	26	1 / 0	11.48	2.50	13.98	34.77	-20.79
707.50	3	QPSK	V	266	22	1 / 74	11.63	2.31	13.94	34.77	-20.83
707.50	3 (WCP)	QPSK	H	266	22	1 / 74	11.37	2.31	13.68	34.77	-21.09

Table 7-2. ERP Data (Band 12)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 116 of 148

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
701.50	5	QPSK	H	265	195	1 / 0	11.67	2.15	13.82	34.77	-20.95
707.50	5	QPSK	H	273	202	1 / 24	12.22	2.31	14.53	34.77	-20.24
713.50	5	QPSK	H	271	216	1 / 0	11.98	2.48	14.46	34.77	-20.31
701.50	5	16-QAM	H	265	195	1 / 0	10.49	2.15	12.64	34.77	-22.13
707.50	5	16-QAM	H	273	202	1 / 24	10.98	2.31	13.29	34.77	-21.48
713.50	5	16-QAM	H	271	216	1 / 0	11.03	2.48	13.51	34.77	-21.26
704.00	10	QPSK	H	267	25	1 / 0	12.96	2.22	15.18	34.77	-19.59
707.50	10	QPSK	H	272	37	1 / 49	12.43	2.31	14.74	34.77	-20.03
711.00	10	QPSK	H	273	0	1 / 0	12.54	2.41	14.95	34.77	-19.82
704.00	10	16-QAM	H	267	25	1 / 0	12.09	2.22	14.31	34.77	-20.46
707.50	10	16-QAM	H	272	37	1 / 49	11.62	2.31	13.93	34.77	-20.84
711.00	10	16-QAM	H	273	0	1 / 0	11.49	2.41	13.90	34.77	-20.87

Table 7-3. ERP Data (Band 12/17)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 117 of 148

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
824.70	1.4	QPSK	H	187	194	3 / 2	13.69	5.01	18.70	38.45	-19.75
836.50	1.4	QPSK	H	187	194	3 / 2	13.90	5.16	19.06	38.45	-19.39
848.30	1.4	QPSK	H	187	194	1 / 0	12.04	5.30	17.34	38.45	-21.11
824.70	1.4	16-QAM	H	187	194	3 / 2	13.42	5.01	18.43	38.45	-20.02
836.50	1.4	16-QAM	H	187	194	1 / 0	12.95	5.16	18.11	38.45	-20.34
848.30	1.4	16-QAM	H	187	194	1 / 0	10.79	5.30	16.09	38.45	-22.36
825.50	3	QPSK	H	208	267	1 / 0	12.74	5.02	17.76	38.45	-20.69
836.50	3	QPSK	H	208	267	1 / 0	12.66	5.16	17.82	38.45	-20.63
847.50	3	QPSK	H	208	267	1 / 0	12.45	5.29	17.74	38.45	-20.71
825.50	3	16-QAM	H	208	267	1 / 14	11.61	5.02	16.63	38.45	-21.82
836.50	3	16-QAM	H	208	267	1 / 0	11.90	5.16	17.06	38.45	-21.39
847.50	3	16-QAM	H	208	267	1 / 0	11.32	5.29	16.61	38.45	-21.84
826.50	5	QPSK	H	222	276	1 / 0	13.16	5.03	18.19	38.45	-20.26
836.50	5	QPSK	H	222	276	1 / 0	12.51	5.16	17.67	38.45	-20.78
846.50	5	QPSK	H	222	276	1 / 0	12.80	5.28	18.08	38.45	-20.37
826.50	5	16-QAM	H	222	276	1 / 0	13.27	5.03	18.30	38.45	-20.15
836.50	5	16-QAM	H	222	276	1 / 0	11.99	5.16	17.15	38.45	-21.30
846.50	5	16-QAM	H	222	276	1 / 0	11.80	5.28	17.08	38.45	-21.37
829.00	10	QPSK	H	208	260	1 / 49	13.80	5.06	18.86	38.45	-19.59
836.50	10	QPSK	H	208	260	1 / 0	13.45	5.16	18.61	38.45	-19.84
844.00	10	QPSK	H	208	260	1 / 49	13.02	5.25	18.27	38.45	-20.18
829.00	10	16-QAM	H	208	260	1 / 49	12.53	5.06	17.59	38.45	-20.86
836.50	10	16-QAM	H	208	260	1 / 0	12.72	5.16	17.88	38.45	-20.57
844.00	10	16-QAM	H	208	260	1 / 0	11.87	5.25	17.12	38.45	-21.33
831.50	15	QPSK	H	191	110	1 / 74	12.81	5.16	17.97	38.45	-20.48
836.50	15	QPSK	H	191	110	1 / 74	12.97	5.16	18.13	38.45	-20.32
841.50	15	QPSK	H	191	110	1 / 0	12.74	4.97	17.71	38.45	-20.74
831.50	15	16-QAM	H	191	110	1 / 74	11.69	4.97	16.66	38.45	-21.79
836.50	15	16-QAM	H	191	110	1 / 74	12.09	5.16	17.25	38.45	-21.20
841.50	15	16-QAM	H	191	110	1 / 0	11.75	5.22	16.97	38.45	-21.48
836.50	1.4	QPSK	V	187	194	36 / 18	12.63	5.16	17.79	38.45	-20.66
836.50	1.4 (WCP)	QPSK	H	187	194	1 / 0	12.59	5.16	17.75	38.45	-20.70

Table 7-4. ERP Data (Band 5/26)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 118 of 148

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1710.70	1.4	QPSK	V	163	10	1 / 5	9.81	9.66	19.47	30.00	-10.53
1732.50	1.4	QPSK	V	168	11	1 / 0	10.30	9.61	19.91	30.00	-10.09
1754.30	1.4	QPSK	V	159	10	1 / 0	10.33	9.57	19.90	30.00	-10.10
1710.70	1.4	16-QAM	V	163	10	1 / 5	8.62	9.66	18.28	30.00	-11.72
1732.50	1.4	16-QAM	V	168	11	1 / 0	9.27	9.61	18.88	30.00	-11.12
1754.30	1.4	16-QAM	V	159	10	1 / 0	9.02	9.57	18.59	30.00	-11.41
1711.50	3	QPSK	V	163	10	1 / 7	9.86	9.65	19.51	30.00	-10.49
1732.50	3	QPSK	V	171	11	1 / 0	10.19	9.61	19.80	30.00	-10.20
1753.50	3	QPSK	V	157	7	1 / 7	10.63	9.57	20.20	30.00	-9.80
1711.50	3	16-QAM	V	163	10	1 / 7	8.96	9.65	18.61	30.00	-11.39
1732.50	3	16-QAM	V	171	11	1 / 0	9.28	9.61	18.89	30.00	-11.11
1753.50	3	16-QAM	V	157	7	1 / 7	9.67	9.57	19.24	30.00	-10.76
1712.50	5	QPSK	V	163	10	1 / 0	9.92	9.65	19.57	30.00	-10.43
1732.50	5	QPSK	V	170	11	1 / 0	10.23	9.61	19.84	30.00	-10.16
1752.50	5	QPSK	V	162	10	1 / 0	10.68	9.57	20.25	30.00	-9.75
1712.50	5	16-QAM	V	163	10	1 / 0	8.90	9.65	18.55	30.00	-11.45
1732.50	5	16-QAM	V	170	11	1 / 0	9.35	9.61	18.96	30.00	-11.04
1752.50	5	16-QAM	V	162	10	1 / 0	9.79	9.57	19.36	30.00	-10.64
1715.00	10	QPSK	V	165	12	1 / 25	10.07	9.65	19.72	30.00	-10.28
1732.50	10	QPSK	V	169	10	1 / 0	10.01	9.61	19.62	30.00	-10.38
1750.00	10	QPSK	V	157	10	1 / 49	10.33	9.58	19.91	30.00	-10.09
1715.00	10	16-QAM	V	165	12	1 / 25	9.15	9.65	18.80	30.00	-11.20
1732.50	10	16-QAM	V	169	10	1 / 0	9.09	9.61	18.70	30.00	-11.30
1750.00	10	16-QAM	V	157	10	1 / 49	9.41	9.58	18.99	30.00	-11.01
1717.50	15	QPSK	V	174	11	1 / 0	9.96	9.64	19.60	30.00	-10.40
1732.50	15	QPSK	V	159	7	1 / 0	9.89	9.61	19.50	30.00	-10.50
1747.50	15	QPSK	V	165	10	1 / 74	10.26	9.58	19.84	30.00	-10.16
1717.50	15	16-QAM	V	174	11	1 / 0	9.07	9.64	18.71	30.00	-11.29
1732.50	15	16-QAM	V	159	7	1 / 0	9.13	9.61	18.74	30.00	-11.26
1747.50	15	16-QAM	V	165	10	1 / 74	9.38	9.58	18.96	30.00	-11.04
1720.00	20	QPSK	V	168	14	1 / 0	9.83	9.64	19.47	30.00	-10.53
1732.50	20	QPSK	V	160	10	1 / 0	9.86	9.61	19.47	30.00	-10.53
1745.00	20	QPSK	V	160	10	1 / 99	10.21	9.59	19.80	30.00	-10.20
1720.00	20	16-QAM	V	168	14	1 / 0	9.04	9.64	18.68	30.00	-11.32
1732.50	20	16-QAM	V	160	10	1 / 0	9.05	9.61	18.66	30.00	-11.34
1745.00	20	16-QAM	V	160	10	1 / 99	9.23	9.59	18.82	30.00	-11.18
1752.50	5	QPSK	H	102	271	1 / 99	8.92	9.57	18.49	30.00	-11.51
1752.50	5 (WCP)	QPSK	V	162	10	1 / 99	8.37	9.57	17.94	30.00	-12.06

Table 7-5. EIRP Data (Band 4)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC. FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 119 of 148	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1850.70	1.4	QPSK	H	100	305	3 / 2	10.41	9.35	19.76	33.01	-13.25
1882.50	1.4	QPSK	H	100	314	3 / 2	10.18	9.27	19.45	33.01	-13.56
1914.30	1.4	QPSK	H	100	310	3 / 2	9.36	9.26	18.62	33.01	-14.39
1850.70	1.4	16-QAM	H	100	305	3 / 2	9.54	9.35	18.89	33.01	-14.12
1882.50	1.4	16-QAM	H	100	314	3 / 2	9.54	9.27	18.81	33.01	-14.20
1914.30	1.4	16-QAM	H	100	310	3 / 2	8.49	9.26	17.75	33.01	-15.26
1851.50	3	QPSK	H	100	309	1 / 14	11.54	9.35	20.89	33.01	-12.12
1882.50	3	QPSK	H	100	318	1 / 14	10.97	9.27	20.24	33.01	-12.77
1913.50	3	QPSK	H	100	315	1 / 14	9.76	9.26	19.02	33.01	-13.99
1851.50	3	16-QAM	H	100	309	1 / 14	10.60	9.35	19.95	33.01	-13.06
1882.50	3	16-QAM	H	100	318	1 / 14	9.95	9.27	19.22	33.01	-13.79
1913.50	3	16-QAM	H	100	315	1 / 14	9.00	9.26	18.26	33.01	-14.75
1852.50	5	QPSK	H	100	313	1 / 24	11.72	9.34	21.06	33.01	-11.95
1882.50	5	QPSK	H	100	315	1 / 24	11.13	9.27	20.40	33.01	-12.61
1912.50	5	QPSK	H	100	313	1 / 24	10.03	9.26	19.29	33.01	-13.72
1852.50	5	16-QAM	H	100	313	1 / 24	10.62	9.34	19.96	33.01	-13.05
1882.50	5	16-QAM	H	100	315	1 / 24	10.17	9.27	19.44	33.01	-13.57
1912.50	5	16-QAM	H	100	313	1 / 24	8.99	9.26	18.25	33.01	-14.76
1855.00	10	QPSK	H	100	311	1 / 49	11.23	9.34	20.57	33.01	-12.44
1882.50	10	QPSK	H	100	313	1 / 0	10.32	9.27	19.59	33.01	-13.42
1910.00	10	QPSK	H	100	313	1 / 0	9.98	9.25	19.23	33.01	-13.78
1855.00	10	16-QAM	H	100	311	1 / 49	10.01	9.34	19.35	33.01	-13.66
1882.50	10	16-QAM	H	100	313	1 / 0	9.34	9.27	18.61	33.01	-14.40
1910.00	10	16-QAM	H	100	313	1 / 0	9.21	9.25	18.46	33.01	-14.55
1857.50	15	QPSK	H	154	1	1 / 0	10.26	9.33	19.59	33.01	-13.42
1882.50	15	QPSK	H	148	2	1 / 0	9.73	9.27	19.00	33.01	-14.01
1907.50	15	QPSK	H	145	359	1 / 0	9.70	9.24	18.94	33.01	-14.07
1857.50	15	16-QAM	H	154	1	1 / 0	9.26	9.33	18.59	33.01	-14.42
1882.50	15	16-QAM	H	148	2	1 / 0	8.76	9.27	18.03	33.01	-14.98
1907.50	15	16-QAM	H	145	359	1 / 0	8.81	9.24	18.05	33.01	-14.96
1860.00	20	QPSK	H	153	2	1 / 0	9.59	9.32	18.91	33.01	-14.10
1882.50	20	QPSK	H	147	2	1 / 0	9.24	9.27	18.51	33.01	-14.50
1905.00	20	QPSK	H	144	358	1 / 99	9.53	9.24	18.77	33.01	-14.24
1860.00	20	16-QAM	H	153	2	1 / 0	8.69	9.32	18.01	33.01	-15.00
1882.50	20	16-QAM	H	147	2	1 / 0	8.38	9.27	17.65	33.01	-15.36
1905.00	20	16-QAM	H	144	358	1 / 99	8.53	9.24	17.77	33.01	-15.24
1852.50	5	QPSK	V	131	276	1 / 99	8.01	9.34	17.35	33.01	-15.66
1852.50	5 (WCP)	QPSK	H	139	0	1 / 99	8.85	9.34	18.19	33.01	-14.82

Table 7-6. EIRP Data (Band 2/25)

FCC ID: A3LSMN935KOR	PCTEST ENGINEERING LABORATORY, INC. FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 120 of 148

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
2498.50	5	QPSK	H	245	338	1 / 0	14.39	8.60	22.99	33.01	-10.02
2593.00	5	QPSK	H	224	335	1 / 24	15.90	8.53	24.43	33.01	-8.58
2687.50	5	QPSK	H	245	338	1 / 24	14.49	8.79	23.28	33.01	-9.73
2498.50	5	16-QAM	H	245	338	1 / 0	12.59	8.60	21.19	33.01	-11.82
2593.00	5	16-QAM	H	224	335	1 / 24	12.72	8.53	21.25	33.01	-11.76
2687.50	5	16-QAM	H	245	338	1 / 24	12.15	8.79	20.94	33.01	-12.07
2501.00	10	QPSK	H	239	356	1 / 49	14.52	8.60	23.12	33.01	-9.89
2593.00	10	QPSK	H	224	335	1 / 49	14.21	8.53	22.74	33.01	-10.27
2685.00	10	QPSK	H	218	332	1 / 49	13.99	8.78	22.77	33.01	-10.24
2501.00	10	16-QAM	H	239	356	1 / 49	12.20	8.60	20.80	33.01	-12.21
2593.00	10	16-QAM	H	224	335	1 / 49	12.61	8.53	21.14	33.01	-11.87
2685.00	10	16-QAM	H	218	332	1 / 49	11.81	8.78	20.59	33.01	-12.42
2503.50	15	QPSK	H	246	335	1 / 0	14.42	8.59	23.01	33.01	-10.00
2593.00	15	QPSK	H	224	335	1 / 74	15.73	8.53	24.26	33.01	-8.75
2682.50	15	QPSK	H	217	336	1 / 74	12.70	8.77	21.47	33.01	-11.54
2503.50	15	16-QAM	H	246	335	1 / 0	12.31	8.59	20.90	33.01	-12.11
2593.00	15	16-QAM	H	224	335	1 / 74	14.28	8.53	22.81	33.01	-10.20
2682.50	15	16-QAM	H	217	336	1 / 0	11.76	8.77	20.53	33.01	-12.48
2506.00	20	QPSK	H	246	335	1 / 0	14.20	8.59	22.79	33.01	-10.22
2593.00	20	QPSK	H	224	335	50 / 25	14.91	8.53	23.44	33.01	-9.57
2680.00	20	QPSK	H	217	336	1 / 99	14.72	8.77	23.49	33.01	-9.52
2506.00	20	16-QAM	H	246	335	50 / 25	13.29	8.59	21.88	33.01	-11.13
2593.00	20	16-QAM	H	224	335	50 / 25	14.27	8.53	22.80	33.01	-10.21
2680.00	20	16-QAM	H	217	336	1 / 99	10.64	8.77	19.41	33.01	-13.60
2593.00	5	QPSK	V	224	335	1 / 99	10.83	8.53	19.36	33.01	-13.65
2593.00	5 (WCP)	QPSK	H	335	335	1 / 0	11.36	8.53	19.89	33.01	-13.12

Table 7-7. EIRP Data (Band 41)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 121 of 148

7.6.2 Antenna B Radiated Power (ERP/EIRP)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
824.70	1.4	QPSK	V	140	237	3 / 2	9.10	5.01	14.12	38.45	-24.34
836.50	1.4	QPSK	V	140	282	3 / 2	8.99	5.16	14.15	38.45	-24.30
848.30	1.4	QPSK	V	143	284	3 / 2	7.58	5.30	12.89	38.45	-25.56
824.70	1.4	16-QAM	V	140	237	3 / 2	9.19	5.01	14.20	38.45	-24.25
836.50	1.4	16-QAM	V	140	282	3 / 2	8.87	5.16	14.02	38.45	-24.43
848.30	1.4	16-QAM	V	143	284	1 / 0	7.22	5.30	12.52	38.45	-25.93
825.50	3	QPSK	V	140	237	1 / 14	9.00	5.02	14.02	38.45	-24.43
836.50	3	QPSK	V	140	282	1 / 0	9.23	5.16	14.39	38.45	-24.06
847.50	3	QPSK	V	143	284	1 / 0	8.68	5.29	13.97	38.45	-24.48
825.50	3	16-QAM	V	140	237	1 / 14	8.61	5.02	13.63	38.45	-24.82
836.50	3	16-QAM	V	140	282	1 / 0	8.63	5.16	13.79	38.45	-24.66
847.50	3	16-QAM	V	143	284	1 / 0	7.28	5.29	12.57	38.45	-25.88
826.50	5	QPSK	V	140	237	1 / 24	10.27	5.03	15.31	38.45	-23.15
836.50	5	QPSK	V	140	282	1 / 0	9.80	5.16	14.96	38.45	-23.49
846.50	5	QPSK	V	143	284	1 / 0	8.57	5.28	13.85	38.45	-24.60
826.50	5	16-QAM	V	140	237	1 / 24	9.80	5.03	14.84	38.45	-23.61
836.50	5	16-QAM	V	140	282	1 / 0	9.45	5.16	14.61	38.45	-23.84
846.50	5	16-QAM	V	143	284	1 / 0	8.62	5.28	13.90	38.45	-24.55
829.00	10	QPSK	V	140	237	1 / 49	9.55	5.06	14.62	38.45	-23.83
836.50	10	QPSK	V	140	282	1 / 0	9.40	5.16	14.55	38.45	-23.90
844.00	10	QPSK	V	143	284	1 / 0	9.16	5.25	14.41	38.45	-24.04
829.00	10	16-QAM	V	140	237	1 / 49	9.12	5.06	14.19	38.45	-24.26
836.50	10	16-QAM	V	140	282	1 / 0	9.15	5.16	14.30	38.45	-24.15
844.00	10	16-QAM	V	143	284	1 / 0	8.84	5.25	14.09	38.45	-24.36
826.50	5	QPSK	H	140	237	1 / 74	8.95	5.03	13.98	38.45	-24.47
826.50	5 (WCP)	QPSK	H	140	237	1 / 99	5.81	5.03	10.84	38.45	-27.61

Table 7-8. ERP Data (Band 5)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 122 of 148

7.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h) §27.53(m)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 123 of 148

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 5) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 124 of 148

7.7.1 Antenna A Radiated Spurious Emissions Measurements

OPERATING FREQUENCY: 701.50 MHz
 CHANNEL: 23035
 MEASURED OUTPUT POWER: 13.82 dBm = 0.024 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) = 26.82$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1403.00	H	217	213	-57.01	2.36	-54.65	68.5
2104.50	H	219	11	-55.84	3.46	-52.38	66.2
2806.00	H	-	-	-58.27	4.74	-53.52	67.3

Table 7-9. Radiated Spurious Data (Band 12/17 – Low Channel)

OPERATING FREQUENCY: 707.50 MHz
 CHANNEL: 23095
 MEASURED OUTPUT POWER: 14.53 dBm = 0.028 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) = 27.53$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1415.00	H	309	290	-58.51	2.54	-55.96	70.5
2122.50	H	316	156	-57.21	3.42	-53.80	68.3
2830.00	H	316	302	-57.30	4.85	-52.45	67.0
3537.50	H	-	-	-57.56	6.26	-51.29	65.8

Table 7-10. Radiated Spurious Data (Band 12/17 – Mid Channel)

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 125 of 148

OPERATING FREQUENCY: 713.50 MHz
 CHANNEL: 23155
 MEASURED OUTPUT POWER: 14.46 dBm = 0.028 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 27.46 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1427.00	H	130	182	-53.86	2.72	-51.13	65.6
2140.50	H	261	4	-54.16	3.37	-50.79	65.2
2854.00	H	183	190	-57.87	4.96	-52.90	67.4
3567.50	H	-	-	-57.84	6.31	-51.52	66.0

Table 7-11. Radiated Spurious Data (Band 12/17 – High Channel)

OPERATING FREQUENCY: 707.50 MHz
 CHANNEL: 23095
 MEASURED OUTPUT POWER: 13.68 dBm = 0.023 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 26.68 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1415.00	H	222	101	-59.61	2.54	-57.06	70.7
2122.50	H	213	107	-58.94	3.42	-55.53	69.2
2830.00	H	-	-	-60.52	4.85	-55.67	69.3

Table 7-12. Radiated Spurious Data with WCP (Band 12/17 – Mid Channel)

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 26797
 MEASURED OUTPUT POWER: 18.70 dBm = 0.074 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 31.70 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
1649.40	H	344	112	-58.39	3.64	-54.74	73.4
2474.10	H	277	65	-53.42	3.57	-49.86	68.6

Table 7-13. Radiated Spurious Data (Band 5/26 – Low Channel)

OPERATING FREQUENCY: 836.50 MHz
 CHANNEL: 26915
 MEASURED OUTPUT POWER: 19.06 dBm = 0.081 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 32.06 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.00	H	102	181	-54.48	3.52	-50.96	70.0
2509.50	H	301	215	-55.43	3.59	-51.84	70.9

Table 7-14. Radiated Spurious Data (Band 5/26 – Mid Channel)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 127 of 148

OPERATING FREQUENCY: 848.30 MHz
 CHANNEL: 27033
 MEASURED OUTPUT POWER: 17.34 dBm = 0.054 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 30.34 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1696.60	H	134	138	-56.27	3.40	-52.88	70.2
2544.90	H	100	137	-52.31	3.74	-48.57	65.9

Table 7-15. Radiated Spurious Data (Band 5/26 – High Channel)

OPERATING FREQUENCY: 836.50 MHz
 CHANNEL: 26915
 MEASURED OUTPUT POWER: 17.75 dBm = 0.060 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 30.75 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.00	H	159	126	-56.29	3.52	-52.77	70.5
2509.50	H	220	359	-52.97	3.59	-49.38	67.1

Table 7-16. Radiated Spurious Data with WCP (Band 5/26 – Mid Channel)

FCC ID: A3LSMN935KOR	PCTEST[®] ENGINEERING LABORATORY, INC. FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 128 of 148	

OPERATING FREQUENCY: 1712.50 MHz
 CHANNEL: 19975
 MEASURED OUTPUT POWER: 19.57 dBm = 0.091 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 32.57 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3425.00	H	-	-	-61.59	9.87	-51.72	71.3
5137.50	H	100	0	-57.15	10.76	-46.39	66.0
6850.00	H	-	-	-58.56	11.67	-46.89	66.5

Table 7-17. Radiated Spurious Data (Band 4 – Low Channel)

OPERATING FREQUENCY: 1732.50 MHz
 CHANNEL: 20175
 MEASURED OUTPUT POWER: 19.84 dBm = 0.096 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 32.84 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3465.00	H	-	-	-61.18	9.91	-51.27	71.1
5197.50	H	100	346	-57.02	10.75	-46.28	66.1
6930.00	H	-	-	-58.60	11.76	-46.84	66.7

Table 7-18. Radiated Spurious Data (Band 4 – Mid Channel)

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 129 of 148

OPERATING FREQUENCY: 1752.50 MHz
 CHANNEL: 20375
 MEASURED OUTPUT POWER: 20.25 dBm = 0.106 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.25 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3505.00	H	-	-	-61.48	9.95	-51.53	71.8
5257.50	H	100	350	-56.52	10.71	-45.81	66.1
7010.00	H	-	-	-59.30	11.83	-47.47	67.7

Table 7-19. Radiated Spurious Data (Band 4 – High Channel)

OPERATING FREQUENCY: 1752.50 MHz
 CHANNEL: 20375
 MEASURED OUTPUT POWER: 17.94 dBm = 0.062 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 30.94 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3505.00	H	-	-	-61.62	9.95	-51.67	69.6
5257.50	H	-	-	-56.12	10.71	-45.41	63.4
7010.00	H	-	-	-58.93	11.83	-47.10	65.0

Table 7-20. Radiated Spurious Data with WCP (Band 4 – High Channel)

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 130 of 148

OPERATING FREQUENCY: 1852.50 MHz
 CHANNEL: 26065
 MEASURED OUTPUT POWER: 21.06 dBm = 0.128 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 34.06 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3705.00	H	-	-	-58.17	9.52	-48.65	69.7
5557.50	H	100	0	-56.54	11.03	-45.51	66.6
7410.00	H	-	-	-55.84	10.95	-44.89	65.9

Table 7-21. Radiated Spurious Data (Band 2/25 – Low Channel)

OPERATING FREQUENCY: 1882.50 MHz
 CHANNEL: 26365
 MEASURED OUTPUT POWER: 20.40 dBm = 0.110 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.40 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3765.00	H	-	-	-55.71	9.37	-46.34	66.7
5647.50	H	100	0	-56.42	11.23	-45.19	65.6
7530.00	H	-	-	-59.13	11.13	-48.00	68.4

Table 7-22. Radiated Spurious Data (Band 2/25 – Mid Channel)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	

OPERATING FREQUENCY: 1912.50 MHz
 CHANNEL: 26665
 MEASURED OUTPUT POWER: 19.29 dBm = 0.085 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 32.29 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3825.00	H	100	0	-55.24	9.33	-45.90	65.2
5737.50	H	100	0	-56.35	11.39	-44.96	64.3
7650.00	H	-	-	-58.34	11.34	-47.00	66.3

Table 7-23. Radiated Spurious Data (Band 2/25 – High Channel)

OPERATING FREQUENCY: 1852.50 MHz
 CHANNEL: 26065
 MEASURED OUTPUT POWER: 18.19 dBm = 0.066 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 31.19 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3705.00	H	-	-	-58.06	9.52	-48.54	66.7
5557.50	H	-	-	-56.51	11.03	-45.48	63.7
7410.00	H	-	-	-57.54	10.95	-46.59	64.8

Table 7-24. Radiated Spurious Data with WCP (Band 2/25 – High Channel)

FCC ID: A3LSMN935KOR	PCTEST[®] ENGINEERING LABORATORY, INC. FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 132 of 148	

OPERATING FREQUENCY: 2498.50 MHz
 CHANNEL: 39675
 MEASURED OUTPUT POWER: 22.99 dBm = 0.199 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W)$ 47.99 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
4997.00	H	-	-	-56.18	10.14	-46.04	69.0

Table 7-25. Radiated Spurious Data (Band 41 – Low Channel)

OPERATING FREQUENCY: 2593.00 MHz
 CHANNEL: 40620
 MEASURED OUTPUT POWER: 24.43 dBm = 0.278 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W)$ 49.43 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
5186.00	H	136	0	-54.20	10.40	-43.80	68.2
7779.00	H	-	-	-55.52	12.24	-43.28	67.7

Table 7-26. Radiated Spurious Data (Band 41 – Mid Channel)

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 133 of 148

OPERATING FREQUENCY: 2687.50 MHz
 CHANNEL: 41565
 MEASURED OUTPUT POWER: 23.28 dBm = 0.213 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W)$ 48.28 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
5375.00	H	-	-	-55.03	10.38	-44.65	67.9

Table 7-27. Radiated Spurious Data (Band 41 – High Channel)

OPERATING FREQUENCY: 2593.00 MHz
 CHANNEL: 40620
 MEASURED OUTPUT POWER: 19.89 dBm = 0.097 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W)$ 44.89 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
5186.00	H	100	326	-47.82	10.40	-37.41	57.3
7779.00	H	100	171	-53.47	12.24	-41.23	61.1
10372.00	H	-	-	-53.75	13.13	-40.62	60.5

Table 7-28. Radiated Spurious Data with WCP (Band 41 – Mid Channel)

7.7.2 Antenna B Radiated Spurious Emissions Measurements

OPERATING FREQUENCY: 826.50 MHz
 CHANNEL: 20425
 MEASURED OUTPUT POWER: 15.31 dBm = 0.034 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 28.31 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1653.00	H	-	-	-59.87	3.62	-56.25	71.6
2479.50	H	-	-	-55.79	3.56	-52.23	67.5
3306.00	H	-	-	-56.47	5.83	-50.64	65.9

Table 7-29. Radiated Spurious Data (Band 5 – Low Channel)

OPERATING FREQUENCY: 836.50 MHz
 CHANNEL: 20525
 MEASURED OUTPUT POWER: 14.96 dBm = 0.031 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 27.96 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.00	H	-	-	-59.28	3.52	-55.76	70.7
2509.50	H	-	-	-53.91	3.59	-50.32	65.3
3346.00	H	-	-	-57.21	5.87	-51.34	66.3

Table 7-30. Radiated Spurious Data (Band 5 – Mid Channel)

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 135 of 148

OPERATING FREQUENCY: 846.50 MHz
 CHANNEL: 20625
 MEASURED OUTPUT POWER: 13.85 dBm = 0.024 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 26.85 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1693.00	H	-	-	-58.65	3.42	-55.23	69.1
2539.50	H	-	-	-56.55	3.72	-52.83	66.7
3386.00	H	-	-	-56.48	5.91	-50.57	64.4

Table 7-31. Radiated Spurious Data (Band 5 – High Channel)

OPERATING FREQUENCY: 836.50 MHz
 CHANNEL: 20425
 MEASURED OUTPUT POWER: 10.84 dBm = 0.012 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 23.84 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.00	H	258	331	-56.57	3.52	-53.05	63.9
2509.50	H	322	330	-56.16	3.59	-52.57	63.4
3346.00	H	-	-	-56.65	5.87	-50.78	61.6

Table 7-32. Radiated Spurious Data with WCP (Band 5 – Mid Channel)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset		Page 136 of 148

7.8 Frequency Stability / Temperature Variation

\$2.1055 \$22.355 \$24.235 \$27.54

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-D-2010

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 137 of 148

Band 12 Frequency Stability Measurements

§2.1055 §27.54

OPERATING FREQUENCY: 707,500,000 Hz

CHANNEL: 23790

REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	707,500,158	158	0.0000223
100 %		- 30	707,500,118	118	0.0000167
100 %		- 20	707,500,004	4	0.0000006
100 %		- 10	707,500,419	419	0.0000592
100 %		0	707,499,890	-110	-0.0000155
100 %		+ 10	707,499,896	-104	-0.0000147
100 %		+ 20	707,500,386	386	0.0000546
100 %		+ 30	707,499,914	-86	-0.0000122
100 %		+ 40	707,499,874	-126	-0.0000178
100 %		+ 50	707,499,880	-120	-0.0000170
BATT. ENDPOINT	3.40	+ 20	707,500,140	140	0.0000198

Table 7-33. Frequency Stability Data (Band 12)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 138 of 148

Band 12 Frequency Stability Measurements

§2.1055 §27.54




Figure 7-8. Frequency Stability Graph (Band 12)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 139 of 148

Band 26 Frequency Stability Measurements

§2.1055 §22.355

OPERATING FREQUENCY: 831,500,000 Hz

CHANNEL: 26865

REFERENCE VOLTAGE: 3.80 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	831,500,073	73	0.0000088
100 %		- 30	831,500,361	361	0.0000434
100 %		- 20	831,499,742	-258	-0.0000310
100 %		- 10	831,499,901	-99	-0.0000119
100 %		0	831,500,090	90	0.0000108
100 %		+ 10	831,499,869	-131	-0.0000158
100 %		+ 20	831,500,378	378	0.0000455
100 %		+ 30	831,499,923	-77	-0.0000093
100 %		+ 40	831,499,942	-58	-0.0000070
100 %		+ 50	831,499,900	-100	-0.0000120
BATT. ENDPOINT	3.40	+ 20	831,499,987	-13	-0.0000016

Table 7-34. Frequency Stability Data (Band 26)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 140 of 148

Band 26 Frequency Stability Measurements

§2.1055 §22.355




Figure 7-9. Frequency Stability Graph (Band 26)

FCC ID: A3LSMN935KOR			FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset			Page 141 of 148

Band 4 Frequency Stability Measurements

§2.1055 §§27.54

OPERATING FREQUENCY: 1,732,500,000 Hz
 CHANNEL: 20175
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,732,499,894	-106	-0.0000061
100 %		- 30	1,732,500,103	103	0.0000059
100 %		- 20	1,732,499,879	-121	-0.0000070
100 %		- 10	1,732,499,836	-164	-0.0000095
100 %		0	1,732,500,111	111	0.0000064
100 %		+ 10	1,732,499,820	-180	-0.0000104
100 %		+ 20	1,732,499,890	-110	-0.0000063
100 %		+ 30	1,732,499,870	-130	-0.0000075
100 %		+ 40	1,732,500,046	46	0.0000027
100 %		+ 50	1,732,500,002	2	0.0000001
BATT. ENDPOINT	3.40	+ 20	1,732,500,212	212	0.0000122

Table 7-35. Frequency Stability Data (Band 4)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	

Band 4 Frequency Stability Measurements

§2.1055 §§27.54




Figure 7-10. Frequency Stability Graph (Band 4)

FCC ID: A3LSMN935KOR			FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset			Page 143 of 148

Band 25 Frequency Stability Measurements

§2.1055 §24.235

OPERATING FREQUENCY: 1,882,500,000 Hz

CHANNEL: 26365

REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,882,500,006	6	0.0000003
100 %		- 30	1,882,499,852	-148	-0.0000079
100 %		- 20	1,882,500,370	370	0.0000197
100 %		- 10	1,882,499,739	-261	-0.0000139
100 %		0	1,882,499,682	-318	-0.0000169
100 %		+ 10	1,882,500,280	280	0.0000149
100 %		+ 20	1,882,500,008	8	0.0000004
100 %		+ 30	1,882,499,968	-32	-0.0000017
100 %		+ 40	1,882,499,811	-189	-0.0000100
100 %		+ 50	1,882,500,278	278	0.0000148
BATT. ENDPOINT	3.40	+ 20	1,882,499,897	-103	-0.0000055

Table 7-36. Frequency Stability Data (Band 25)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 144 of 148

Band 25 Frequency Stability Measurements

§2.1055 §24.235




Figure 7-11. Frequency Stability Graph (Band 25)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 145 of 148

Band 41 Frequency Stability Measurements

§2.1055 §27.54

OPERATING FREQUENCY: 2,593,000,000 Hz

CHANNEL: 40620

REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	2,593,000,184	184	0.0000071
100 %		- 30	2,593,000,174	174	0.0000067
100 %		- 20	2,593,000,159	159	0.0000061
100 %		- 10	2,592,999,862	-138	-0.0000053
100 %		0	2,592,999,905	-95	-0.0000037
100 %		+ 10	2,593,000,230	230	0.0000089
100 %		+ 20	2,592,999,979	-21	-0.0000008
100 %		+ 30	2,593,000,153	153	0.0000059
100 %		+ 40	2,593,000,141	141	0.0000054
100 %		+ 50	2,593,000,208	208	0.0000080
BATT. ENDPOINT	3.40	+ 20	2,593,000,096	96	0.0000037

Table 7-37. Frequency Stability Data (Band 41)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 146 of 148

Band 41 Frequency Stability Measurements

§2.1055 §27.54




Figure 7-12. Frequency Stability Graph (Band 41)

FCC ID: A3LSMN935KOR	 FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 147 of 148

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMN935KOR** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules for LTE operation only.

FCC ID: A3LSMN935KOR		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 1M1703230122-03.A3L	Test Dates: 6/1 - 6/28/2016	EUT Type: Portable Handset	Page 148 of 148	