

**MEASUREMENT REPORT**
LTE**Applicant Name:**

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

4/4-5/18/2018

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M1804040063-03.A3L

FCC ID:

A3LSMN960F

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-N960F

Additional Model(s):

SM-N960F/DS, SM-N960X

EUT Type:

Portable Handset

Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):

22, 24, & 27

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03,
KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 1 of 224

TABLE OF CONTENTS


1.0	INTRODUCTION	5
1.1	Scope	5
1.2	PCTEST Test Location.....	5
1.3	Test Facility / Accreditations.....	5
2.0	PRODUCT INFORMATION.....	6
2.1	Equipment Description	6
2.2	Device Capabilities.....	6
2.3	Test Configuration	6
2.4	EMI Suppression Device(s)/Modifications	7
3.0	DESCRIPTION OF TESTS	8
3.1	Measurement Procedure.....	8
3.2	Block C Frequency Range	8
3.3	Block A Frequency Range.....	8
3.4	Cellular - Base Frequency Blocks	8
3.5	Cellular - Mobile Frequency Blocks	8
3.6	PCS - Base Frequency Blocks	9
3.7	PCS - Mobile Frequency Blocks.....	9
3.8	AWS - Base Frequency Blocks	9
3.9	AWS - Mobile Frequency Blocks.....	10
3.10	BRS/EBS Frequency Block	10
3.11	Radiated Power and Radiated Spurious Emissions	11
4.0	MEASUREMENT UNCERTAINTY	12
5.0	TEST EQUIPMENT CALIBRATION DATA	13
6.0	SAMPLE CALCULATIONS	14
7.0	TEST RESULTS	15
7.1	Summary.....	15
7.2	Occupied Bandwidth	17
7.3	Spurious and Harmonic Emissions at Antenna Terminal	65
7.4	Band Edge Emissions at Antenna Terminal	101
7.5	Peak-Average Ratio	163
7.6	Radiated Power (ERP/EIRP).....	173
7.7	Radiated Spurious Emissions Measurements	183
7.8	Frequency Stability / Temperature Variation	209
8.0	CONCLUSION.....	224

FCC ID: A3LSMN960F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 2 of 224



MEASUREMENT REPORT

Part 22, 24, & 27



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)		
LTE Band 12	27	699.7 - 715.3	0.030	14.74	0.049	16.89	1M10G7D	QPSK
LTE Band 12	27	699.7 - 715.3	0.021	13.30	0.035	15.45	1M11W7D	16QAM
LTE Band 12	27	699.7 - 715.3	0.017	12.19	0.027	14.34	1M10W7D	64QAM
LTE Band 12	27	700.5 - 714.5	0.030	14.75	0.049	16.90	2M73G7D	QPSK
LTE Band 12	27	700.5 - 714.5	0.022	13.34	0.035	15.49	2M73W7D	16QAM
LTE Band 12	27	700.5 - 714.5	0.017	12.26	0.028	14.41	2M74W7D	64QAM
LTE Band 12/17	27	701.5 - 713.5	0.029	14.63	0.048	16.78	4M56G7D	QPSK
LTE Band 12/17	27	701.5 - 713.5	0.022	13.39	0.036	15.54	4M56W7D	16QAM
LTE Band 12/17	27	701.5 - 713.5	0.017	12.33	0.028	14.48	4M55W7D	64QAM
LTE Band 12/17	27	704 - 711	0.029	14.64	0.048	16.79	9M02G7D	QPSK
LTE Band 12/17	27	704 - 711	0.022	13.52	0.037	15.67	9M04W7D	16QAM
LTE Band 12/17	27	704 - 711	0.017	12.28	0.028	14.43	9M02W7D	64QAM
LTE Band 13	27	779.5 - 784.5	0.048	16.81	0.079	18.96	4M57G7D	QPSK
LTE Band 13	27	779.5 - 784.5	0.034	15.33	0.056	17.48	4M57W7D	16QAM
LTE Band 13	27	779.5 - 784.5	0.028	14.43	0.045	16.58	4M55W7D	64QAM
LTE Band 13	27	782	0.047	16.74	0.077	18.89	9M00G7D	QPSK
LTE Band 13	27	782	0.036	15.52	0.058	17.67	9M02W7D	16QAM
LTE Band 13	27	782	0.028	14.45	0.046	16.60	9M02W7D	64QAM
LTE Band 26/5	22H	824.7 - 848.3	0.118	20.71	0.193	22.86	1M10G7D	QPSK
LTE Band 26/5	22H	824.7 - 848.3	0.100	19.98	0.163	22.13	1M11W7D	16QAM
LTE Band 26/5	22H	824.7 - 848.3	0.077	18.88	0.127	21.03	1M10W7D	64QAM
LTE Band 26/5	22H	825.5 - 847.5	0.121	20.81	0.198	22.96	2M74G7D	QPSK
LTE Band 26/5	22H	825.5 - 847.5	0.100	19.98	0.163	22.13	2M73W7D	16QAM
LTE Band 26/5	22H	825.5 - 847.5	0.075	18.76	0.123	20.91	2M71W7D	64QAM
LTE Band 26/5	22H	826.5 - 846.5	0.108	20.34	0.177	22.49	4M54G7D	QPSK
LTE Band 26/5	22H	826.5 - 846.5	0.090	19.56	0.148	21.71	4M55W7D	16QAM
LTE Band 26/5	22H	826.5 - 846.5	0.072	18.55	0.117	20.70	4M55W7D	64QAM
LTE Band 26/5	22H	829 - 844	0.105	20.22	0.173	22.37	9M01G7D	QPSK
LTE Band 26/5	22H	829 - 844	0.093	19.68	0.152	21.83	9M02W7D	16QAM
LTE Band 26/5	22H	829 - 844	0.070	18.44	0.115	20.59	9M03W7D	64QAM
LTE Band 26	22H	831.5 - 841.5	0.100	20.00	0.164	22.15	13M5G7D	QPSK
LTE Band 26	22H	831.5 - 841.5	0.083	19.20	0.136	21.35	13M5W7D	16QAM
LTE Band 26	22H	831.5 - 841.5	0.066	18.20	0.108	20.35	13M5W7D	64QAM

EUT Overview (<1GHz)

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03-A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 3 of 224

Mode	FCC Rule Part	Tx Frequency (MHz)	EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)		
LTE Band 66/4	27	1710.7 - 1779.3	0.237	23.75	1M11G7D	QPSK
LTE Band 66/4	27	1710.7 - 1779.3	0.199	22.98	1M11W7D	16QAM
LTE Band 66/4	27	1710.7 - 1779.3	0.148	21.69	1M11W7D	64QAM
LTE Band 66/4	27	1711.5 - 1778.5	0.226	23.55	2M73G7D	QPSK
LTE Band 66/4	27	1711.5 - 1778.5	0.196	22.93	2M74W7D	16QAM
LTE Band 66/4	27	1711.5 - 1778.5	0.151	21.78	2M74W7D	64QAM
LTE Band 66/4	27	1712.5 - 1777.5	0.234	23.69	4M57G7D	QPSK
LTE Band 66/4	27	1712.5 - 1777.5	0.199	22.98	4M56W7D	16QAM
LTE Band 66/4	27	1712.5 - 1777.5	0.154	21.87	4M57W7D	64QAM
LTE Band 66/4	27	1715 - 1775	0.252	24.01	9M06G7D	QPSK
LTE Band 66/4	27	1715 - 1775	0.201	23.04	9M07W7D	16QAM
LTE Band 66/4	27	1715 - 1775	0.166	22.19	9M04W7D	64QAM
LTE Band 66/4	27	1717.5 - 1772.5	0.232	23.66	13M5G7D	QPSK
LTE Band 66/4	27	1717.5 - 1772.5	0.195	22.91	13M5W7D	16QAM
LTE Band 66/4	27	1717.5 - 1772.5	0.156	21.93	13M5W7D	64QAM
LTE Band 66/4	27	1720 - 1770	0.253	24.03	18M1G7D	QPSK
LTE Band 66/4	27	1720 - 1770	0.166	22.19	18M1W7D	16QAM
LTE Band 66/4	27	1720 - 1770	0.126	21.00	18M1W7D	64QAM
LTE Band 25/2	24E	1850.7 - 1914.3	0.235	23.72	1M10G7D	QPSK
LTE Band 25/2	24E	1850.7 - 1914.3	0.191	22.82	1M11W7D	16QAM
LTE Band 25/2	24E	1850.7 - 1914.3	0.155	21.90	1M11W7D	64QAM
LTE Band 25/2	24E	1851.5 - 1913.5	0.257	24.11	2M73G7D	QPSK
LTE Band 25/2	24E	1851.5 - 1913.5	0.219	23.41	2M72W7D	16QAM
LTE Band 25/2	24E	1851.5 - 1913.5	0.158	21.99	2M74W7D	64QAM
LTE Band 25/2	24E	1852.5 - 1912.5	0.226	23.53	4M58G7D	QPSK
LTE Band 25/2	24E	1852.5 - 1912.5	0.188	22.75	4M57W7D	16QAM
LTE Band 25/2	24E	1852.5 - 1912.5	0.137	21.38	4M56W7D	64QAM
LTE Band 25/2	24E	1855 - 1910	0.282	24.50	9M04G7D	QPSK
LTE Band 25/2	24E	1855 - 1910	0.233	23.67	9M09W7D	16QAM
LTE Band 25/2	24E	1855 - 1910	0.185	22.67	9M09W7D	64QAM
LTE Band 25/2	24E	1857.5 - 1907.5	0.277	24.42	13M6G7D	QPSK
LTE Band 25/2	24E	1857.5 - 1907.5	0.229	23.60	13M5W7D	16QAM
LTE Band 25/2	24E	1857.5 - 1907.5	0.180	22.55	13M5W7D	64QAM
LTE Band 25/2	24E	1860 - 1905	0.260	24.15	18M0G7D	QPSK
LTE Band 25/2	24E	1860 - 1905	0.223	23.48	18M0W7D	16QAM
LTE Band 25/2	24E	1860 - 1905	0.169	22.28	18M0W7D	64QAM
LTE Band 7	27	2502.5 - 2567.5	0.234	23.70	4M55G7D	QPSK
LTE Band 7	27	2502.5 - 2567.5	0.176	22.45	4M57W7D	16QAM
LTE Band 7	27	2502.5 - 2567.5	0.141	21.50	4M57W7D	64QAM
LTE Band 7	27	2505 - 2565	0.242	23.84	9M04G7D	QPSK
LTE Band 7	27	2505 - 2565	0.177	22.49	9M08W7D	16QAM
LTE Band 7	27	2505 - 2565	0.144	21.58	9M06W7D	64QAM
LTE Band 7	27	2507.5 - 2562.5	0.240	23.81	13M5G7D	QPSK
LTE Band 7	27	2507.5 - 2562.5	0.176	22.45	13M5W7D	16QAM
LTE Band 7	27	2507.5 - 2562.5	0.150	21.76	13M5W7D	64QAM
LTE Band 7	27	2510 - 2560	0.255	24.07	18M1G7D	QPSK
LTE Band 7	27	2510 - 2560	0.184	22.64	18M1W7D	16QAM
LTE Band 7	27	2510 - 2560	0.147	21.68	18M1W7D	64QAM
LTE Band 41/38	27	2498.5 - 2687.5	0.269	24.30	4M55G7D	QPSK
LTE Band 41/38	27	2498.5 - 2687.5	0.214	23.31	4M54W7D	16QAM
LTE Band 41/38	27	2498.5 - 2687.5	0.193	22.85	4M55W7D	64QAM
LTE Band 41/38	27	2501 - 2685	0.290	24.62	9M08G7D	QPSK
LTE Band 41/38	27	2501 - 2685	0.229	23.59	9M05W7D	16QAM
LTE Band 41/38	27	2501 - 2685	0.184	22.65	9M01W7D	64QAM
LTE Band 41/38	27	2503.5 - 2682.5	0.287	24.57	13M5G7D	QPSK
LTE Band 41/38	27	2503.5 - 2682.5	0.222	23.46	13M5W7D	16QAM
LTE Band 41/38	27	2503.5 - 2682.5	0.172	22.35	13M5W7D	64QAM
LTE Band 41/38	27	2506 - 2680	0.250	23.98	18M1G7D	QPSK
LTE Band 41/38	27	2506 - 2680	0.196	22.91	18M0W7D	16QAM
LTE Band 41/38	27	2506 - 2680	0.136	21.33	18M0W7D	64QAM

EUT Overview (>1GHz)

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 4 of 224

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMN960F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 5 of 224

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMN960F**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

Test Device Serial No.: 05848, 42950, 42828, 05855

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

LTE Band 12 (698 - 716 MHz) overlaps the entire frequency range of LTE Band 17 (704 - 716 MHz). Therefore, test data provided in this report covers Band 17 as well as Band 12.

LTE Band 26 (814.7 – 849 MHz) overlaps the entire frequency range of LTE Band 5 (824 – 849 MHz). Therefore, test data provided in this report covers Band 5 and the portion of Band 26 subject to Part 22.

LTE Band 66 (1710 - 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz). Therefore, test data provided in this report covers Band 4 as well as Band 66.

LTE Band 25 (1850 - 1915 MHz) overlaps the entire frequency range of LTE Band 2 (1850 - 1910 MHz). Therefore, test data provided in this report covers Band 2 as well as Band 25.

LTE Band 41 (2496 – 2690 MHz) overlaps the entire frequency range of LTE Band 38 (2570 - 2620 MHz). Therefore, test data provided in this report covers Band 38 as well as Band 41.

For UMTS 850 and LTE Band 5 operation, this device uses a tuner circuit that dynamically updates the antenna impedance parameters to optimize antenna performance. The tuner for this device was set to simulate a "free space" condition where the transmit antenna is matched to the medium into which it is transmitting and, thus, the power is at its maximum level.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT placed on an authorized wireless charging pad (WCP) Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

This device uses a stylus pen for several functions. The EUT can operate with the stylus pen inserted or removed and the emissions measurements for the EUT were performed with and without the stylus pen inserted into the EUT. There was no degradation found without the stylus pen removed so all emission measurements were performed with the pen inserted into the EUT.

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION)		 Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 6 of 224

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 7 of 224

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-E-2016) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v03) were used in the measurement of the EUT.

3.2 Block C Frequency Range


Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.

3.3 Block A Frequency Range

698-746 MHz band. The following frequencies are available for licensing pursuant to this part in the 698-746 MHz band: (1) Three paired channel blocks of 12 megahertz each are available for assignment as follows:

Block A: 698-704 MHz and 728-734 MHz;
Block B: 704-710 MHz and 734-740 MHz; and
Block C: 710-716 MHz and 740-746 MHz.


3.4 Cellular - Base Frequency Blocks



BLOCK 1: 869 – 880 MHz (A* Low + A)
BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A* High)
BLOCK 4: 891.5 – 894 MHz (B*)

3.5 Cellular - Mobile Frequency Blocks




BLOCK 1: 824 – 835 MHz (A* Low + A)
BLOCK 2: 835 – 845 MHz (B)


BLOCK 3: 845 – 846.5 MHz (A* High)
BLOCK 4: 846.5 – 849 MHz (B*)

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 8 of 224


3.6 PCS - Base Frequency Blocks



3.7 PCS - Mobile Frequency Blocks




3.8 AWS - Base Frequency Blocks



FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 9 of 224	


3.9 AWS - Mobile Frequency Blocks



BLOCK 1: 1710 – 1720 MHz (A)
BLOCK 2: 1720 – 1730 MHz (B)
BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 4: 1735 – 1740 MHz (D)
BLOCK 5: 1740 – 1745 MHz (E)
BLOCK 6: 1745 – 1755 MHz (F)

3.10 BRS/EBS Frequency Block



FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 10 of 224

3.11 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$. For Band 7 and 41, the calculated P_d levels are compared to the absolute spurious emission limit of -25dBm which is equivalent to the required minimum attenuation of $55 + 10\log_{10}(\text{Power [Watts]})$.

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 11 of 224

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMN960F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 12 of 224

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX2	Licensed Transmitter Cable Set	8/10/2017	Annual	8/10/2018	LTX2
Agilent	N9020A	MXA Signal Analyzer	1/24/2018	Annual	1/24/2019	US46470561
Agilent	N9030A	PXA Signal Analyzer (26.5GHz)	8/28/2017	Annual	8/28/2018	MY49432391
COM-Power	AL-130R	Active Loop Antenna	6/5/2017	Annual	6/5/2018	121085
Emco	3115	Horn Antenna (1-18GHz)	3/28/2018	Biennial	3/28/2020	9704-5182
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/23/2016	Biennial	8/23/2018	135427
Espec	ESX-2CA	Environmental Chamber	3/28/2018	Annual	3/28/2019	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	12/1/2016	Biennial	12/1/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	3/28/2018	Biennial	3/28/2020	128337
Huber+Suhner	Sucoflex 102A	40GHz Radiated Cable	5/19/2017	Annual	5/19/2018	251425001
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/30/2018	Annual	3/30/2019	11401010036
Mini Circuits	TVA-11-422	RF Power Amp	N/A		N/A	QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A		N/A	11208010032
Rohde & Schwarz	CMW500	Radio Communication Tester	10/13/2017	Annual	10/13/2018	102060
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	5/19/2017	Annual	5/19/2018	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/31/2017	Annual	7/31/2018	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/11/2017	Annual	8/11/2018	103200
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102133
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102135
Anritsu	MT8820C	Radio Communication Analyzer	10/25/2017	Annual	10/25/2018	6201144419
Rohde & Schwarz	TC-TA18	Cross-Pol Antenna 400MHz-18GHz	10/30/2017	Annual	10/30/2018	101058
Schwarzbeck	UHA 9105	Dipole Antenna	8/26/2016	Biennial	8/26/2018	2696
Rohde & Schwarz	TS-PR8	Preamplifier-Antenna SYS; 30MHz-8GHz	10/19/2017	Annual	10/19/2018	102324
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	1/24/2018	Annual	1/24/2019	100040
Seekonk	NC-100	Torque Wrench	12/28/2017	Annual	12/28/2018	N/A
Sunol	DRH-118	Horn Antenna (1-18GHz)	8/11/2017	Biennial	8/11/2019	A050307
Sunol Sciences	JB6	JB6 Antenna	9/27/2016	Biennial	9/27/2018	A082816

Table 5-1. Test Equipment

Notes:

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 13 of 224

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (–24.80).

FCC ID: A3LSMN960F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 14 of 224

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMN960F
 Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 2.917(a) 24.238(a) 27.53(c) 27.53(g) 27.53(h)	Out of Band Emissions	> 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.3, 7.4
27.53(m)	Out of Band Emissions	Undesirable emissions must meet the limits detailed in 27.53(m)		PASS	Section 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		PASS	See RF Exposure Report
2.1055 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) and fundamental emissions stay within authorized frequency block (Part 24, 27)		PASS	Section 7.8

Table 7-1. Summary of Conducted Test Results

FCC ID: A3LSMN960F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 15 of 224	

Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
22.913(a)(5)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 26/5)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
27.50(b)(10) 27.50(c)(10)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 12/17, 13)	< 3 Watts max. ERP		PASS	Section 7.6
24.232(c) 27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 25/2, 7, 41/38)	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 66/4)	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(c) 27.53(g) 27.53(h)	Undesirable Emissions (Band 12/17, 26/5, 66/4, 25/2)	> 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 7.7
27.53(f)	Undesirable Emissions (Band 13)	< -70 dBW/MHz (for wideband signals) < -80 dBW (for discrete emissions less than 700Hz BW) For all emissions in the band 1559 – 1610 MHz		PASS	Section 7.7
27.53(m)	Undesirable Emissions (Band 7, 38/41)	Undesirable emissions must meet the limits detailed in 27.53(m)		PASS	Section 7.7

Table 7-2. Summary of Radiated Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots (Sections 7.2, 7.3, 7.4, 7.5) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 4.12.
- 5) For operation <1GHz, the EIRP limits in the table above are referenced to the specifications written in the relevant Radio Standards Specifications for Innovation, Science, and Economic Development Canada.

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 16 of 224

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: A3LSMN960F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 17 of 224

Band 12/17




Plot 7-1. Occupied Bandwidth Plot (Band 12 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-2. Occupied Bandwidth Plot (Band 12 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 18 of 224	




Plot 7-3. Occupied Bandwidth Plot (Band 12 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (Band 12 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 19 of 224




Plot 7-5. Occupied Bandwidth Plot (Band 12 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (Band 12 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 20 of 224




Plot 7-7. Occupied Bandwidth Plot (Band 12/17 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (Band 12/17 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 21 of 224	




Plot 7-9. Occupied Bandwidth Plot (Band 12/17 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (Band 12/17 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 22 of 224	




Plot 7-11. Occupied Bandwidth Plot (Band 12/17 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-12. Occupied Bandwidth Plot (Band 12/17 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 23 of 224

Band 13




Plot 7-13. Occupied Bandwidth Plot (Band 13 - 5.0MHz QPSK - Full RB Configuration)



Plot 7-14. Occupied Bandwidth Plot (Band 13 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 24 of 224	



Plot 7-15. Occupied Bandwidth Plot (Band 13 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-16. Occupied Bandwidth Plot (Band 13 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 25 of 224




Plot 7-17. Occupied Bandwidth Plot (Band 13 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-18. Occupied Bandwidth Plot (Band 13 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 26 of 224	

Band 26/5




Plot 7-19. Occupied Bandwidth Plot (Band 26/5 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-20. Occupied Bandwidth Plot (Band 26/5 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 27 of 224




Plot 7-21. Occupied Bandwidth Plot (Band 26/5 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-22. Occupied Bandwidth Plot (Band 26/5 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 28 of 224



Plot 7-23. Occupied Bandwidth Plot (Band 26/5 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-24. Occupied Bandwidth Plot (Band 26/5 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 29 of 224




Plot 7-25. Occupied Bandwidth Plot (Band 26/5 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-26. Occupied Bandwidth Plot (Band 26/5 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 30 of 224



Plot 7-27. Occupied Bandwidth Plot (Band 26/5 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-28. Occupied Bandwidth Plot (Band 26/5 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 31 of 224	




Plot 7-29. Occupied Bandwidth Plot (Band 26/5 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-30. Occupied Bandwidth Plot (Band 26/5 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 32 of 224




Plot 7-31. Occupied Bandwidth Plot (Band 26 - 15.0MHz QPSK - Full RB Configuration)



Plot 7-32. Occupied Bandwidth Plot (Band 26 - 15.0MHz 16-QAM - Full RB Configuration)


FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 33 of 224




Plot 7-33. Occupied Bandwidth Plot (Band 26 - 15.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 34 of 224

Band 66/4




Plot 7-34. Occupied Bandwidth Plot (Band 66/4 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-35. Occupied Bandwidth Plot (Band 66/4 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 35 of 224	




Plot 7-36. Occupied Bandwidth Plot (Band 66/4 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-37. Occupied Bandwidth Plot (Band 66/4 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 36 of 224




Plot 7-38. Occupied Bandwidth Plot (Band 66/4 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-39. Occupied Bandwidth Plot (Band 66/4 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 37 of 224




Plot 7-40. Occupied Bandwidth Plot (Band 66/4 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-41. Occupied Bandwidth Plot (Band 66/4 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 38 of 224




Plot 7-42. Occupied Bandwidth Plot (Band 66/4 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-43. Occupied Bandwidth Plot (Band 66/4 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 39 of 224	




Plot 7-44. Occupied Bandwidth Plot (Band 66/4 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-45. Occupied Bandwidth Plot (Band 66/4 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 40 of 224




Plot 7-46. Occupied Bandwidth Plot (Band 66/4 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-47. Occupied Bandwidth Plot (Band 66/4 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 41 of 224




Plot 7-48. Occupied Bandwidth Plot (Band 66/4 - 15.0MHz 64-QAM - Full RB Configuration)




Plot 7-49. Occupied Bandwidth Plot (Band 66/4 - 20.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 42 of 224




Plot 7-50. Occupied Bandwidth Plot (Band 66/4 - 20.0MHz 16-QAM - Full RB Configuration)




Plot 7-51. Occupied Bandwidth Plot (Band 66/4 - 20.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 43 of 224

Band 25/2




Plot 7-52. Occupied Bandwidth Plot (Band 25/2 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-53. Occupied Bandwidth Plot (Band 25/2 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 44 of 224	




Plot 7-54. Occupied Bandwidth Plot (Band 25/2 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-55. Occupied Bandwidth Plot (Band 25/2 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 45 of 224



Plot 7-56. Occupied Bandwidth Plot (Band 25/2 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-57. Occupied Bandwidth Plot (Band 25/2 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 46 of 224



Plot 7-58. Occupied Bandwidth Plot (Band 25/2 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-59. Occupied Bandwidth Plot (Band 25/2 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 47 of 224




Plot 7-60. Occupied Bandwidth Plot (Band 25/2 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-61. Occupied Bandwidth Plot (Band 25/2 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 48 of 224




Plot 7-62. Occupied Bandwidth Plot (Band 25/2 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-63. Occupied Bandwidth Plot (Band 25/2 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 49 of 224




Plot 7-64. Occupied Bandwidth Plot (Band 25/2 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-65. Occupied Bandwidth Plot (Band 25/2 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 50 of 224




Plot 7-66. Occupied Bandwidth Plot (Band 25/2 - 15.0MHz 64-QAM - Full RB Configuration)




Plot 7-67. Occupied Bandwidth Plot (Band 25/2 - 20.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 51 of 224	




Plot 7-68. Occupied Bandwidth Plot (Band 25/2 - 20.0MHz 16-QAM - Full RB Configuration)




Plot 7-69. Occupied Bandwidth Plot (Band 25/2 - 20.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 52 of 224

Band 7




Plot 7-70. Occupied Bandwidth Plot (Band 7 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-71. Occupied Bandwidth Plot (Band 7 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 53 of 224	




Plot 7-72. Occupied Bandwidth Plot (Band 7 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-73. Occupied Bandwidth Plot (Band 7 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 54 of 224	




Plot 7-74. Occupied Bandwidth Plot (Band 7 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-75. Occupied Bandwidth Plot (Band 7 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 55 of 224




Plot 7-76. Occupied Bandwidth Plot (Band 7 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-77. Occupied Bandwidth Plot (Band 7 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 56 of 224




Plot 7-78. Occupied Bandwidth Plot (Band 7 - 15.0MHz 64-QAM - Full RB Configuration)




Plot 7-79. Occupied Bandwidth Plot (Band 7 - 20.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 57 of 224




Plot 7-80. Occupied Bandwidth Plot (Band 7 - 20.0MHz 16-QAM - Full RB Configuration)




Plot 7-81. Occupied Bandwidth Plot (Band 7 - 20.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 58 of 224	

Band 41/38




Plot 7-82. Occupied Bandwidth Plot (Band 41/38 - 5.0MHz QPSK - Full RB Configuration)



Plot 7-83. Occupied Bandwidth Plot (Band 41/38 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 59 of 224	




Plot 7-84. Occupied Bandwidth Plot (Band 41/38 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-85. Occupied Bandwidth Plot (Band 41/38 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 60 of 224




Plot 7-86. Occupied Bandwidth Plot (Band 41/38 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-87. Occupied Bandwidth Plot (Band 41/38 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 61 of 224




Plot 7-88. Occupied Bandwidth Plot (Band 41/38 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-89. Occupied Bandwidth Plot (Band 41/38 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 62 of 224




Plot 7-90. Occupied Bandwidth Plot (Band 41/38 - 15.0MHz 64-QAM - Full RB Configuration)




Plot 7-91. Occupied Bandwidth Plot (Band 41/38 - 20.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMN960F	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset		Page 63 of 224



Plot 7-92. Occupied Bandwidth Plot (Band 41/38 - 20.0MHz 16-QAM - Full RB Configuration)



Plot 7-93. Occupied Bandwidth Plot (Band 41/38 - 20.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMN960F	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1804040063-03.A3L	Test Dates: 4/4-5/18/2018	EUT Type: Portable Handset	Page 64 of 224	