



74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea  
TEL: +82-31-645-6300 FAX: +82-31-645-6401

## RF Exposure Report

**Applicant Name:****SAMSUNG Electronics Co., Ltd.**

129, Samsung-ro, Yeongtong-gu, Suwon-Si, Gyeonggi-do, 16677 Rep. of Korea

**Date of Issue:** Nov.11, 2021**Test Report No.:** HCT-SR-2110-FC013-R1**Test Site:** HCT CO., LTD.**FCC ID:****A3LSMN980F1**

Equipment Type:

Mobile Phone

Application Type

Certification

FCC Rule Part(s):

KDB 680106 D01

Model Name:

**SM-N980F/DS**

Additional Model Name:

**SM-N980F**

Date of Test:

10/27/2021

This device has been shown to be capable of compliance for the above standards for uncontrolled environment/general population exposure limits specified in FCC KDB procedures and had been tested in accordance with the measurement procedures specified in FCC KDB procedures.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Tested By**

**Jung Hun, Park**  
Test Engineer  
SAR Team  
Certification Division

**Reviewed By**

**Yun-jeang, Heo**  
Technical Manager  
SAR Team  
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## **DOCUMENT HISTORY**

| Rev. | DATE          | DESCRIPTION           |
|------|---------------|-----------------------|
| 0    | Oct. 29, 2021 | First Approval Report |
| 1    | Nov.11,2021   | Revised sec.6         |

## Table of Contents

|                                          |   |
|------------------------------------------|---|
| 1. Test Methodology .....                | 4 |
| 2. Test Location.....                    | 4 |
| 3. DEVICE UNDER TEST DESCRIPTION.....    | 5 |
| 4. TEST AND MEASUREMENT EQUIPMENT .....  | 6 |
| 5. MAXIMUM PERMISSIBLE RE EXPOSURE ..... | 6 |
| 6. TEST RESULTS .....                    | 7 |

## 1. Test Methodology

Per FCC Guidance, SPEN WPT Function was evaluated for portable exposure condition.

## 2. Test Location.

### 2.1 Test Laboratory.

|                      |                                                                                          |
|----------------------|------------------------------------------------------------------------------------------|
| <b>Company Name:</b> | HCT Co., LTD                                                                             |
| <b>Address:</b>      | 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of Korea |
| <b>Telephone:</b>    | +82 31 645 6300                                                                          |
| <b>Fax.:</b>         | +82 31 645 6401                                                                          |

### 2.2 Test Facilities

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

|               |                                                         |
|---------------|---------------------------------------------------------|
| <b>Korea:</b> | National Radio Research Agency (Designation No. KR0032) |
|               | KOLAS (Testing No. KT197)                               |

### 3. DEVICE UNDER TEST DESCRIPTION

|                        |                               |
|------------------------|-------------------------------|
| Applicant Name:        | SAMSUNG Electronics Co., Ltd. |
| Model:                 | SM-N980F/DS                   |
| Additional Model Name: | SM-N980F                      |
| EUT Type:              | Mobile Phone                  |
| Application Type:      | Certification                 |

The device uses only magnetic induction which is a technology that charges a battery by generating a magnetic field by flowing a current through the transmitter coil, and then entering a magnetic field into the receiver coil to generate an induced current again.

Therefore, RF exposure through measurement and calculation of H-field were investigated.

- Test mode: power is transferred from "Phone coil" to "S-pen coil"

|                          |                                   |
|--------------------------|-----------------------------------|
| Operating Frequency(MHz) | 590 kHz ~ 625 kHz                 |
| Maximum output Power(mW) | 50                                |
| Charging Type            | Inductive wireless Power transfer |
| Operating duty factor    | 0.3333                            |

#### Description of S-PEN:( EJ-PN980: FCC ID: A3LEJPN980)

S-Pen (EJ-PN980) is specifically designed for SM-N981B/DS and SM-N981B

Battery in the EJ-PN980 will be charged wirelessly from mobile phone via 590 kHz ~ 625 kHz frequency

More detail description, Please refer to Operational description document.

All Position of S-Pen were investigated and the worst position results are reported.

For S-Pen, both fully charged and non-fully charged condition were investigated. Test wer performed non-fully charged condition as worst case.

## 4. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was used for the tests documented in this report :

| Manufacturer | Model namr | Description                       | S/N        | Calib. Date | Calib.Due  |
|--------------|------------|-----------------------------------|------------|-------------|------------|
| Narda        | EHP-200AC  | Electric and Magnetic Field Probe | 170WX91009 | 11/22/2019  | 11/22/2021 |

The Narda EHP-200AC has physical dimensions of 92 x 92 x 109mm. So the center of the probe would be at 46 x 46 x 54mm. When the probe measures the H-field of the device,, the long axis of the probe (109mm) is perpendicular to the rear surface of the DUT. So when the probe is in direct contact with the rear of the device, the center of the probe would be 54mm away.

## 5. MAXIMUM PERMISSIBLE RE EXPOSURE

### 5.1 FCC RULES

1.13010 The criteria listed in Table 1 shall be used to evaluate the envirimental impact of human exposure to radio-frequency(RF) ragiation as specified in 1.1307(b), except in the case of portable devices which shall ge evaluated according th the provisions of 2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz)                                   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                               |                               |                                     |                          |
| 0.3–3.0 .....                                           | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0–30 .....                                            | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30–300 .....                                            | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300–1500 .....                                          | .....                         | .....                         | f/300                               | 6                        |
| 1500–100,000 .....                                      | .....                         | .....                         | 5                                   | 6                        |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3–1.34 .....                                          | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30 .....                                           | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| 30–300 .....          | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500 .....        | .....                         | .....                         | f/1500                              | 30                       |
| 1500–100,000 .....    | .....                         | .....                         | 1.0                                 | 30                       |

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## 6. TEST RESULTS

### 6.1 H-Field measurement results of DUT's 6 sides

| H-Field Measurement (A/m)                                                             |        |        |        |        |       |        |
|---------------------------------------------------------------------------------------|--------|--------|--------|--------|-------|--------|
| The Direct contact from the edge of the Device to the center of the measurement Probe | Rear   | Front  | Left   | Right  | Top   | Bottom |
| 5.4 cm                                                                                | 0.3378 | 0.0771 | 0.1409 | 0.0107 | 0.234 | 0.0082 |

Note: All measurement sides are taken into account with respect to the front side of the DUT.  
The contact distance between the device and the probe is 5.4 cm from the center of the probe.

### 6.2 H-field measurement results

| H-Field Results Measurement (A/m) :Rear Side                                         |                     |                                         |                         |
|--------------------------------------------------------------------------------------|---------------------|-----------------------------------------|-------------------------|
| The Distance from the Rear of the device to the center of the measurement probe (cm) | H-Field Meas. (A/m) | H-Field meas data * (Duty Factor) (A/m) | FCC H-Field Limit (A/m) |
| 5.4                                                                                  | 0.3378              | 0.1126                                  | 1.63                    |
| 6.4                                                                                  | 0.1836              | 0.0612                                  |                         |
| 7.4                                                                                  | 0.0931              | 0.0310                                  |                         |
| 8.4                                                                                  | 0.0605              | 0.0202                                  |                         |
| 9.4                                                                                  | 0.0323              | 0.0108                                  |                         |
| 10.4                                                                                 | 0.0183              | 0.0061                                  |                         |
| 11.4                                                                                 | 0.0139              | 0.0046                                  |                         |
| 12.4                                                                                 | 0.0059              | 0.0020                                  |                         |
| 13.4                                                                                 | 0.009               | 0.0030                                  |                         |
| 14.4                                                                                 | 0.0057              | 0.0019                                  |                         |
| 15.4                                                                                 | 0.0026              | 0.0009                                  |                         |

Corrected H-Field measurement

•  $0.33781 \text{ A/m} * 0.333 = 0.1126 \text{ A/m}$

#### Operational Correction Factor

The EUT charges for 10 minutes at maximum illumination to full charge. Therefore the operational correction factor is:

Correction Factor (applied over 30 minutes) =  $10/30 = 0.333$ .

#### Description of Test Setup

Testing was performed with a calibrated field probe.

Measurement was performed on each side of the EUT as described per Sec 6.1

### 6.3 FCC SUMMARY OF RESULTS

Measurement procedure was performed per FCC Guidance.

All Position of S-Pen were investigated and the worst position results a reported

| FCC RF Exposure H-Field Limit [A/m] | Maximum meas data (A/m) | Percentage(%) |
|-------------------------------------|-------------------------|---------------|
| 1.63                                | 0.1126                  | 6.91          |

H-Field test result was less than 50% of MPE limit