



ELEMENT MATERIALS TECHNOLOGY,

Columbia MD

(formerly PCTEST)

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>

MEASUREMENT REPORT

FCC Part 15.247 Bluetooth

Applicant Name:

Samsung Electronics Co., Ltd.

129, Samsung-ro,

Yeongtong-gu, Suwon-si

Gyeonggi-do, 16677, Korea

Date of Testing:

1/29/2026 - 7/10/2026

Test Report Issue Date:

7/22/2026

Test Site/Location:

Element Lab., Columbia, MD, USA

Element Lab., Yongin-Si, Gyeonggi-do, South Korea

Test Report Serial No.:

1M2601220004-02-R1.A3L

FCC ID:

A3LSMO200J

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-O200J

Additional Model(s):

SM-O201J, SM-O202J, SM-O203J, SM-O204J, SM-O205J

EUT Type:

Extended Reality Glasses

Max. RF Output Power:

17.262 mW (12.37 dBm) Peak Conducted

Frequency Range:

2402 – 2480MHz

Type of Modulation:

GFSK, $\pi/4$ -DQPSK, 8DPSK

FCC Classification:

FCC Part 15 Spread Spectrum Transmitter (DSS)

FCC Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10:2020. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N:1M2601220004-02-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2601220004-02.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 1 of 64

TEST REPORT REVISION HISTORY

Rev. No.	Description	Issue Date	Revised By
-	Initial Release	7/16/2026	WKR0000005883
1	Addressed comments made by TCB reviewer	7/22/2026	WKR0000005883

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 2 of 64

TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Element Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description	6
2.4	Test Configuration	6
2.5	Software and Firmware	6
2.6	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure	7
3.2	AC Line Conducted Emissions	7
3.3	Radiated Emissions	8
3.4	Environmental Conditions	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	11
7.0	TEST RESULTS	14
7.1	Summary	14
7.2	20dB Bandwidth Measurement	15
7.3	Output Power Measurement	21
7.4	Band Edge Compliance	32
7.5	Carrier Frequency Separation	35
7.6	Time of Occupancy	37
7.7	Number of Hopping Channels	39
7.8	Conducted Spurious Emissions	41
7.9	Radiated Spurious Emission Measurements – Above 1GHz	45
7.10	Radiated Restricted Band Edge Measurements	52
7.11	Radiated Spurious Emissions Measurements – Below 1GHz	55
7.12	Line Conducted Measurement Data	59
8.0	CONCLUSION	62
9.0	APPENDIX A – Data referencing spot-checks	63

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 3 of 64

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

Measurements were conducted at the Element laboratory(ies) indicated in Section 1.3 below. All measurement facilities are compliant with the test site requirements specified in ANSI C63.4:2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A. ("MD")

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered test laboratory with the site description on file with ISED (Wireless Test Lab number 2451B) and FCC (Designation Number US1113).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

Measurements were performed at Element Materials Technology Suwon, Ltd. located in Yongin-si, Gyeonggi-do, 16954, South Korea. ("KR")

- Element Materials Technology Suwon, Ltd. is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation(A2LA) with Certificate number 2041.04 for Specific Absorption Rate (SAR), and Electromagnetic Compatibility (EMC) & Telecommunications testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Materials Technology Suwon, Ltd. facility is accredited, designated, and recognized in accordance with the provision of Radio Wave Act and International Standard ISO/IEC 17025:2017 under the National Radio Research Agency.
 - Designation Number / CABID: KR0169
 - Test Firm Registration Number of FCC: 417945
 - Test Firm Registration Number of ISED: 26168

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 4 of 64

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Extended Reality Glasses FCC ID: A3LSMO200J**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
 - A) The hopping sequence is pseudorandom
 - B) All channels are used equally on average
 - C) The receiver input bandwidth equals the transmit bandwidth
 - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

This device is a variant device that applies Data Referencing from a parent model approved under FCC ID: A3LSMO200P. A summary of the referenced data can be found in Section 7.0 and the corresponding data referencing spot-check data can be found in Section 9.0 of this test report.

Test Device Serial No.: 260302MD10, 260302MD11, 260302MD12, 260302MD13, 260302MD14, 260302MD15, 260302MD16, 260302MD17, 260608MD04, 260609MD03, 260518MD15, 260518MD16, 260518MD17, 260609MD01, 260609MD02, 260518MD18, 260612MD01, 260612MD02, 260624MD02, 260624MD03, 260624MD04, 260624MD05

2.2 Device Capabilities

This device contains the following capabilities:

BT (LE, BDR, EDR), 2.4GHz WLAN (802.11b/g/n/ac/ax), 5 and 6GHz UNII (a/n/ac/ax)

Ch.	Frequency (MHz)
00	2402
:	:
39	2441
:	:
78	2480

Table 2-1. Frequency/ Channel Operations

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 5 of 64

2.3 Antenna Description

The manufacturer provided the antenna gains which can affect the validity of test results used for determination of compliance. The following antenna gains are used in this device per the "Unlicensed Band Antenna Gain" document provided by the client. This document is also included in the filing as a public exhibit.

Frequency [GHz]	Antenna-1 Gain (dBi)
2.4	-4.07

Table 2-2. Antenna Peak Gain

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

2.4 Test Configuration

The EUT was tested per the guidance of ANSI C63.10:2020. ANSI C63.10:2020 was also used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, and 7.8 for antenna port conducted emissions test setups. The worst case radiated emissions data is shown in this report.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst-case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report. The worst orientation was found to be Y-orientation (landscape).

The EUT has four configurations: one is with both ear arm fully open, one is with left ear arm closed/right ear arm open, one is with left ear arm open/right ear arm closed, and one is with both ear arm closed. All configurations are tested, and the worst case radiated emissions data is shown in this report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor (Model: EP-TA12JWE) via USB cable with wire charger

$\pi/4$ -DQPSK has been investigated and confirmed as not the worst case.

2.5 Software and Firmware

The test was conducted with software/firmware version 020XXUEU0AZE3 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 6 of 64

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2020) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1-meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that the cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst-case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.12. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 7 of 64

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3-meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4:2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst-case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4:2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 8 of 64

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 9 of 64

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10:2020. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

Table 5-1. Measurement Uncertainty Budget – MD

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.95
Radiated Disturbance (<1GHz)	4.10
Radiated Disturbance (>1GHz)	4.82
Radiated Disturbance (>18GHz)	4.96

Table 5-2. Measurement Uncertainty Budget – KR

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 10 of 64

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurement antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	MD 1M 40	EMC Cable and Switch System	2/3/2026	Annual	2/3/2027	MD 1M 40
-	AP1-002	EMC Cable and Switch System	2/3/2026	Annual	2/3/2027	AP1-002
-	AP2-001	EMC Cable and Switch System	1/30/2026	Annual	1/30/2027	AP2-001
-	AP2-002	EMC Cable and Switch System	1/30/2026	Annual	1/30/2027	AP2-002
-	ETS-001	EMC Cable and Switch System	1/29/2026	Annual	1/29/2027	ETS-001
-	ETS-002	EMC Cable and Switch System	1/29/2026	Annual	1/29/2027	ETS-002
-	WL25-1	Conducted Cable Set (25GHz)	1/30/2026	Annual	1/30/2027	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	1/30/2026	Annual	1/30/2027	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	1/30/2026	Annual	1/30/2027	WL40-1
-	WL40-2	Conducted Cable Set (40GHz)	1/30/2026	Annual	1/30/2027	WL40-2
Agilent	N4010A	Wireless Connectivity Test Set	N/A			GB46170464
EMCO	3115	Horn Antenna (1-18GHz)	9/6/2024	Biennial	9/6/2026	9704-5182
EMCO	3116	Horn Antenna (18-40GHz)	1/26/2026	Biennial	1/26/2028	9203-2178
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	6/4/2025	Biennial	6/4/2027	125518
ETS-Lindgren	3116C	DRG Horn Antenna	4/22/2025	Biennial	4/22/2027	218893
Keysight Technologies	N9030A	PXA Signal Analyzer	11/3/2025	Annual	11/3/2026	MY54490576
Keysight Technologies	N9038A	MXE EMI Receiver	11/10/2025	Annual	11/10/2026	MY51210133
Keysight Technologies	N9030A	PXA Signal Analyzer	11/3/2025	Annual	11/3/2026	MY54490576
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	1/30/2026	Annual	1/30/2027	NMLC-2
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	12/19/2025	Annual	12/19/2026	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	1/16/2026	Annual	1/16/2027	100348
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	3/11/2026	Annual	3/11/2027	101716
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	12/19/2025	Annual	12/19/2026	100342
Rohde & Schwarz	ENV216	Two-Line V-Network	2/4/2026	Biennial	2/4/2028	101379
Rohde & Schwarz	180-422-KF	Horn (18 - 40GHz)	10/9/2024	Biennial	10/9/2026	U157403-01
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	9/11/2024	Biennial	9/11/2026	A051107
Sunol	JB6	Bi-Log Antenna (30M - 5GHz)	3/24/2025	Biennial	3/24/2027	A082816

Table 6-1. Test Equipment Calibration Table – MD

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Rohde & Schwarz	CMW500	Radio Communication Tester	10/24/2025	Annual	10/23/2026	171075
Rohde & Schwarz	ESW	EMI Test Receiver	09/15/2025	Annual	09/14/2026	101955
schwarzbeck	VULB9162	Broadband TRILOG Antenna	06/05/2025	Biennial	06/04/2027	9162-217
Sunol Sciences	DRH-118	Horn Antenna	05/14/2026	Annual	05/13/2027	A102416-1
-	UEK1	EMC Cable and Switch System	01/28/2026	Annual	01/27/2027	UEK1

Table 6-2. Test Equipment Calibration Table – KR

Note:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment listed with "N/A" under calibration information was not used to make calibrated measurements.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 11 of 64

Component	Serial Number
MegaPhase (CAGE 1GVT4) Cable TM40-K1K1-30	20233002 004
Uniflex Micro Coax UFB 142A-Q-0984-200200	64639 232063 001
R&S TS-PR1840	9037.7670.02

Table 6-3. MD 1M 18-40 EMC Cable and Switch System Components

Component	Serial Number
Sucoflex 106A Cable	501992
MegaPhase Cable N29-N1N1-324	20335606 001
Rohde & Schwarz SF Unit	102133
MiniCircuits Cable CBL-2FT-SMSM+	77745
MegaPhase Cable 10511-1	15034701 001
MiniCircuits Switch RC 2SPDT-A18	11703270 041
Sucoflex 104 Cable	320259/4
Sucoflex 104 Cable	321999/4
Sucoflex 104 Cable	321995/4

Table 6-4. AP2-001 EMC Cable and Switch System Components

Component	Serial Number
Flex Cable	P2A-0001
Micro-Coax Utilfex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Chamber Passthrough	CP4/X12
Micro-Coax Utilfex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Micro-Coax Utilfex Cable UFB142A-0-0629-5GU200 MFR 6463	232069-001
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181

Table 6-5. AP2-001 EMC Cable and Switch System Components

Component	Serial Number
MiniCircuits Cable CBL-0.5M-SMNM+	47261
Micro-Coax Utilfex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-001
Micro-Coax Utilfex Cable UFB311A-1-0629-50U50U MFR 64639	231986-002
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	19046401 001
Megaphase (CAGE 1GVT4) Flex Cable 10511-1	15044701-006
Micro-Coax Utilfex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-002
Micro-Coax Utilfex Cable UFB311A-1-0629-50U50U MFR 64639	231986-004
Micro-Coax Utilfex Cable UFB142A-0-0629-5GU200 MFR 64639	232069-001
Rohde & Schwarz SF Unit	102138
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181
Micro-Coax Utilfex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Micro-Coax Utilfex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335

Table 6-6. AP2-002 EMC Cable and Switch System Components

Component	Serial Number
Pasternack Cable RG214/U	111815
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001

Table 6-7. ETS-001 EMC Cable and Switch System Components

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 12 of 64

Component	Serial Number
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	20502201 001
Rohde & Schwarz SF Unit	102134
Minicircuits Cable CBL=0.5M-NMNM+	15440

Table 6-8. ETS-002 EMC Cable and Switch System Components

Component	Serial Number
MegaPhase Cable, Model: TM26-S1S1-30	20929201 004
Pasternack 6dB Attenuator, Model: PE7005-6	N/A

Table 6-9. WL25-1 Conducted Cable Set Components

Component	Serial Number
Mini-Circuits Cable, Model: CBL-2FT-SMSM+	77743
MCL 6dB Attenuator, Model: BW-S6W2+	1314

Table 6-10. WL25-2 Conducted Cable Set Components

Component	Serial Number
MegaPhase Cable, Model: TM40-K1K1-36	18160102 001
MCL 10dB Attenuator, Model: BW-K10 2W44+	1902

Table 6-11. WL40-1 Conducted Cable Set Components

Component	Serial Number
MegaPhase Cable, Model: TM40-K1K1-30	18165902 001
MCL 10dB Attenuator, Model: BW-K10 2W44+	2108

Table 6-12. WL40-2 Conducted Cable Set Components

Component	Serial Number
Rohde & Schwarz SF Unit	102151
ALPHA WIRE H1	6340
HUBER+SUHNER, Inc. SUCOFLEX_104_PE Cable	305916
HUBER+SUHNER, Inc. SUCOFLEX_100	803242-6

Table 6-13. UEK1 EMC Cable and Switch System Components

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 13 of 64

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMO200J
 Method/System: Frequency Hopping Spread Spectrum (FHSS)
 Number of Channels: 79

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference	Test Lab Location	Data Referencing
15.247(a)(1)(iii)	20dB Bandwidth	N/A	CONDUCTED	PASS	Section 7.2	MD	Yes
15.247(b)(1)	Peak Transmitter Output Power	< 1 Watt if ≥ 75 non-overlapping channels used		PASS	Section 7.3	MD	Yes
15.247(a)(1)	Channel Separation	> 2/3 of 20 dB BW for systems with Output Power < 125mW		PASS	Section 7.5	MD	Yes
15.247(a)(1)(iii)	Number of Channels	> 15 Channels		PASS	Section 7.7	MD	Yes
15.247(a)(1)(iii)	Time of Occupancy	< 0.4 sec in 31.6 sec period		PASS	Section 7.6	MD	Yes
15.247(d)	Band Edge / Out-of-Band Emissions	Conducted > 20dBc		PASS	Section 7.4, Section 7.8	MD	Yes
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-247 limits)	RADIATED	PASS	Section 7.9, Section 7.10, Section 7.11	MD & KR	No
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen [8.8] limits)	LINE CONDUCTED	PASS	Section 7.12	MD	No

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "BT Auto," Version 3.5.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 1.7.7.
- 6) Data was referenced from model SM-O200P for the certification of SM-O200J. See Section 9.0 for spotcheck results.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 14 of 64

7.2 20dB Bandwidth Measurement

Test Overview and Limit

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

Test Procedure Used

ANSI C63.10:2020 – Section 6.9.2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 20dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 20$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% OBW
3. VBW $\geq 3 \times$ RBW
4. Reference level set to keep signal from exceeding maximum input mixer level for linear operation.
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 15 of 64


Frequency [MHz]	Data Rate [Mbps]	Channel No.	20dB Bandwidth Test Results [kHz]
2402	1.0	0	934.60
2441	1.0	39	916.70
2480	1.0	78	887.80
2402	2.0	0	1347.00
2441	2.0	39	1307.00
2480	2.0	78	1327.00
2402	3.0	0	1319.00
2441	3.0	39	1275.00
2480	3.0	78	1342.00

Table 7-2. Conducted 20dB Bandwidth Measurements – SISO ANT 1




Plot 7-1. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 0) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 16 of 64




Plot 7-2. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 39) – SISO ANT 1




Plot 7-3. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 78) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 17 of 64




Plot 7-4. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 0) – SISO ANT 1




Plot 7-5. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 39) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 18 of 64




Plot 7-6. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 78) – SISO ANT 1




Plot 7-7. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 0) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 19 of 64



Plot 7-8. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 39) – SISO ANT 1



Plot 7-9. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 78) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 20 of 64

7.3 Output Power Measurement

Test Overview and Limits

Measurement is made while the EUT is operating in non-hopping transmission mode. The powers shown below were measured using a spectrum analyzer with a Bluetooth signaling test set (Agilent Model: N4010A) used only to maintain a Bluetooth link with the EUT. Average power measurements are performed using the analyzer's "burst power" function with RBW = 3MHz. The burst power function triggers on a single set burst set to maximum power and measures the maximum average power on the on-time.

The maximum permissible output power is 1 Watt.

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.5

Test Settings

Peak Power Measurement

1. Span = approximately 5x 20dB bandwidth, centered on hopping channel
2. RBW > 20dB bandwidth of emission being measured
3. VBW $\geq$ RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 21 of 64


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Peak Conducted Power		Avg Conducted Power	
			[dBm]	[mW]	[dBm]	[mW]
2402	1.0	0	12.08	16.129	11.89	15.457
2441	1.0	39	12.37	17.262	12.34	17.157
2480	1.0	78	11.77	15.028	11.46	14.002
2402	2.0	0	11.15	13.038	8.33	6.813
2441	2.0	39	11.48	14.057	8.59	7.224
2480	2.0	78	10.24	10.563	8.06	6.402
2402	3.0	0	11.58	14.375	8.37	6.864
2441	3.0	39	12.17	16.489	8.47	7.032
2480	3.0	78	10.77	11.934	8.13	6.498

Table 7-3. Conducted Output Power Measurements – SISO ANT 1




Plot 7-10. Peak Conducted Power (1Mbps – Ch. 0) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 22 of 64




Plot 7-11. Peak Conducted Power (1Mbps – Ch. 39) – SISO ANT 1




Plot 7-12. Peak Conducted Power (1Mbps – Ch. 78) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 23 of 64




Plot 7-13. Peak Conducted Power (2Mbps – Ch. 0) – SISO ANT 1




Plot 7-14. Peak Conducted Power (2Mbps – Ch. 39) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 24 of 64




Plot 7-15. Peak Conducted Power (2Mbps – Ch. 78) – SISO ANT 1




Plot 7-16. Peak Conducted Power (3Mbps – Ch. 0) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 25 of 64




Plot 7-17. Peak Conducted Power (3Mbps – Ch. 39) – SISO ANT 1




Plot 7-18. Peak Conducted Power (3Mbps – Ch. 78) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 26 of 64




Plot 7-19. Average Conducted Power (1Mbps - Ch. 0) - SISO ANT 1




Plot 7-20. Average Conducted Power (1Mbps - Ch. 39) - SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 27 of 64




Plot 7-21. Average Conducted Power (1Mbps - Ch. 78) - SISO ANT 1




Plot 7-22. Average Conducted Power (2Mbps - Ch. 0) - SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 28 of 64




Plot 7-23. Average Conducted Power (2Mbps - Ch. 39) - SISO ANT 1




Plot 7-24. Average Conducted Power (2Mbps - Ch. 78) - SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 29 of 64




Plot 7-25. Average Conducted Power (3Mbps - Ch. 0) - SISO ANT 1



Plot 7-26. Average Conducted Power (3Mbps - Ch. 39) - SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 30 of 64



Plot 7-27. Average Conducted Power (3Mbps – Ch. 78) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 31 of 64

7.4 Band Edge Compliance

Test Overview and Limits

EUT operates in hopping and non-hopping transmission mode. Measurement is taken at the highest point located outside of the emission bandwidth. **The maximum permissible out-of-band emission level is 20 dBc.**

Test Procedure Used

ANSI C63.10:2020 – Section 6.10.4

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup


Test Notes

Out of band conducted spurious emissions at the band edge were investigated for all data rates in hopping and non-hopping modes. The worst case emissions were found with the EUT transmitting at 3 Mbps. Band edge emissions were also investigated with the EUT transmitting in all data rates. Plots of the worst case emissions are shown below.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 32 of 64




Plot 7-28. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 0) – SISO ANT 1




Plot 7-29. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 78) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 33 of 64



Plot 7-30. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – SISO ANT 1



Plot 7-31. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 34 of 64

7.5 Carrier Frequency Separation

Test Overview and Limit

Measurement is made with EUT operating in hopping mode. ***The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.***

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.2

Test Settings

1. Span = Wide enough to capture peaks of two adjacent channels
2. RBW = 30% of channel spacing. Adjust as necessary to best identify center of each individual channel
3. VBW $\geq$ RBW
4. Sweep = Auto
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize.
8. Marker-delta function used to determine separation between peaks of the adjacent channels

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup


Test Notes

The EUT complies with the minimum channel separation requirement when it is operating in 1x/EDR mode using 79 channels and when operating in AFH mode using 20 channels.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 35 of 64

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Min. Channel Separation [MHz]
2402	1.0	0	0.623
2441	1.0	39	0.611
2480	1.0	78	0.592
2402	2.0	0	0.899
2441	2.0	39	0.871
2480	2.0	78	0.895
2402	3.0	0	0.897
2441	3.0	39	0.850
2480	3.0	78	0.895

Table 7-4. Minimum Channel Separation – SISO Ant 1



Plot 7-32. Channel Spacing Plot (Bluetooth) – SISO Ant 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 36 of 64

7.6 Time of Occupancy

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. ***The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.***

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.4

Test Settings

1. Span = zero span, centered on a hopping channel
2. RBW $\leq$ channel spacing and $\gg 1/T$, where T is expected dwell time per channel
3. Sweep = as necessary to capture entire dwell time. Second plot may be required to demonstrate two successive hops on a channel
4. Trigger is set with appropriate trigger delay to place pulse near the center of the plot
5. Detector = peak
6. Trace mode = Clear Write
7. Marker-delta function used to determine transmit time per hop

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 37 of 64



Plot 7-33. Time of Occupancy Plot (Bluetooth) – SISO Ant 1

Bluetooth Time of Occupancy Calculation

Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of $1600 / 6 = 266.67$ hops/s/slot

- $400\text{ms} \times 79$ hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second}$ (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops}$ (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.875 \text{ ms/channel} = 306.667 \text{ ms}$ (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of $800 / 6 = 133.3$ hops/s/slot

- $400\text{ms} \times 20$ hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second}$ (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops}$ (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.875 \text{ ms/channel} = 153.333 \text{ ms}$ (worst case dwell time for one channel in AFH mode)

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 38 of 64

7.7 Number of Hopping Channels

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode. ***This frequency hopping system must employ a minimum of 15 hopping channels.***

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.3

Test Settings

1. Span = frequency of band of operation (divided into two plots)
2. RBW < 30% of channel spacing or 20dB bandwidth, whichever is smaller
3. VBW ≥ RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup


Test Notes

The frequency spectrum was broken up into two sub-ranges to clearly show all the hopping frequencies. In AFH mode, this device operates using 20 channels so the requirement for minimum number of hopping channels is satisfied.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 39 of 64



Plot 7-34. Low End Spectrum Channel Hopping Plot (Bluetooth) – SISO Ant 1



Plot 7-35. High End Spectrum Channel Hopping Plot (Bluetooth) – SISO Ant 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 40 of 64

7.8 Conducted Spurious Emissions

Test Overview and Limit

Conducted out-of-band spurious emissions were investigated from 30MHz up to 25GHz to include the 10th harmonic of the fundamental transmit frequency. **The maximum permissible out-of-band emission level is 20 dBc.**

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.7

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz* (See note below)
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup


Test Notes

Out-of-band conducted spurious emissions were investigated for all data rates and the worst-case emissions were found with the EUT transmitting at N/AMbps. The display line shown in the following plots is the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, the traces in the following plots are measured with a 1MHz RBW to reduce test time, so the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 41 of 64




Plot 7-36. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – SISO ANT 1




Plot 7-37. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 42 of 64




Plot 7-38. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – SISO ANT 1




Plot 7-39. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 43 of 64



Plot 7-40. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – SISO ANT 1



Plot 7-41. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – SISO ANT 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 44 of 64

7.9 Radiated Spurious Emission Measurements – Above 1GHz

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-5. Radiated Limits

Test Procedure Used

ANSI C63.10:2020 – Section 6.6.4.3

Test Settings

Average Field Strength Measurements per Section 4.1.5.2.3 of ANSI C63.10:2020

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 1kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to stabilize

Peak Field Strength Measurements per Section 4.1.5.2.2 of ANSI C63.10:2020

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-6 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 45 of 64

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-6. RBW as a Function of Frequency

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-8. Radiated Test Setup >1GHz

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in §15.209.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery and emissions were investigated with the unit powered by an extended battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
6. The duty cycle correction factor was not applied to noise floor measurements.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables is used to denote a noise floor measurement.
9. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 46 of 64

Sample Calculation

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]} + \text{Duty Cycle Correction }_{[dB]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$


Duty Cycle Correction Factor Calculation

- Channel hop rate = 800 hops/second (AFHMode)
- Adjusted channel hop rate for DH5 mode = 133.33 hops/second
- Time per channel hop = $1 / 133.33 \text{ hops/second} = 7.50 \text{ ms}$
- Time to cycle through all channels = $7.50 \times 20 \text{ channels} = 150 \text{ ms}$
- Number of times transmitter hits on one channel = $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$
- Worst case dwell time = 7.5 ms
- Duty cycle correction factor = $20\log_{10}(7.5\text{ms}/100\text{ms}) = -22.5 \text{ dB}$


FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 47 of 64

Radiated Spurious Emission Measurements


§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]



Plot 7-42. Radiated Spurious Plot above 1GHz (BT – Ch. 0) – Ant 1



Plot 7-43. Radiated Spurious Plot above 1GHz (BT – Ch. 39) – Ant 1




Plot 7-44. Radiated Spurious Plot above 1GHz (BT – Ch. 78) – Ant 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 48 of 64

Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209; RSS-Gen [8.9]



Plot 7-45. Radiated Spurious Plot above 18GHz – Ant 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 49 of 64

Radiated Spurious Emission Measurements

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	Avg	V	-	-	-78.11	1.37	30.26	53.98	-23.72
4804.00	Peak	V	-	-	-66.18	1.37	42.19	73.98	-31.79
12010.00	Avg	V	-	-	-79.84	13.03	40.19	53.98	-13.78
12010.00	Peak	V	-	-	-67.93	13.03	52.10	73.98	-21.87

Table 7-7. Radiated Measurements – Ant 1

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4880.00	Avg	V	-	-	-77.85	2.10	31.25	53.98	-22.73
4880.00	Peak	V	-	-	-66.48	2.10	42.62	73.98	-31.36
7320.00	Avg	V	-	-	-79.26	6.79	34.53	53.98	-19.45
7320.00	Peak	V	-	-	-67.18	6.79	46.61	73.98	-27.37
12200.00	Avg	V	-	-	-80.16	12.60	39.44	53.98	-14.54
12200.00	Peak	V	-	-	-67.78	12.60	51.82	73.98	-22.16

Table 7-8. Radiated Measurements– Ant 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 50 of 64

Worst Case Mode: Bluetooth

Worst Case Data Rate: 1 Mbps

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Channel: 78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	V	-	-	-77.93	2.53	31.60	53.98	-22.38
4960.00	Peak	V	-	-	-65.89	2.53	43.64	73.98	-30.34
7440.00	Avg	V	-	-	-79.32	7.45	35.13	53.98	-18.85
7440.00	Peak	V	-	-	-66.34	7.45	48.11	73.98	-25.87
12400.00	Avg	V	-	-	-80.19	12.98	39.79	53.98	-14.19
12400.00	Peak	V	-	-	-68.04	12.98	51.94	73.98	-22.04

Table 7-9. Radiated Measurements – Ant 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 51 of 64

7.10 Radiated Restricted Band Edge Measurements

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated emissions at the band edge are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power, at the appropriate frequencies, and with hopping disabled. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-10. Radiated Limits

Test Procedure Used

ANSI C63.10:2020 – Section 6.10.5.2

Test Settings

- Span is set large enough to capture the peak level of the emission operating on the channel closest to the band edge
- Reference level offset is set with the appropriate corrections for the frequencies shown in the plots
- Reference level is set to provide the appropriate amount of “head room” above the signal as specified in ANSI C63.10:2020 Section 4.1.6.2
- Attenuation is set to a low enough level to maintain enough dynamic range between the noise floor and the radiated limit
- Sweep time = Auto coupled
- RBW = 1MHz
- VBW = 3 x RBW for peak measurements and 1kHz for RMS measurements
- Detector = RMS and peak
- Trace = Max Hold
- Trace was allowed to stabilize

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 52 of 64

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-9. Radiated Test Setup >1GHz

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limits shown in §15.209.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery and emissions were investigated with the unit powered by an extended battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
6. Two different amplitude offsets were used depending on whether peak or average measurements were measured. The average measurements use a duty cycle correction factor (DCCF).

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain} + \text{DCCF}$$


7. The "-" shown in the following RSE tables is used to denote a noise floor measurement.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 53 of 64


Radiated Restricted Band Edge Measurements – Ant 1

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	3 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



Plot 7-46. Radiated Restricted Upper Band Edge Measurement (Average)



Plot 7-47. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 54 of 64

7.11 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-11. Radiated Limits

Test Procedures Used

ANSI C63.10:2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 55 of 64

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-10. Radiated Test Setup < 30Mhz




Figure 7-11. Radiated Test Setup < 1GHz

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 56 of 64


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limits shown in §15.209.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery and emissions were investigated with the unit powered by an extended battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 57 of 64

Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-48. Radiated Spurious Plot below 1GHz – Ant 1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
739.00	Quasi-Peak	V	-	-	-106.21	30.05	30.84	46.02	-15.18
821.00	Quasi-Peak	V	-	-	-107.38	31.99	31.61	46.02	-14.41

Table 7-12. Radiated Spurious Emissions Below 1GHz – Ant 1

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 58 of 64

7.12 Line Conducted Measurement Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-13. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 59 of 64

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-12. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 60 of 64



Plot 7-49. Line-Conducted Test Plot (L1)



Plot 7-50. Line-Conducted Test Plot (N)

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 61 of 64

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Extended Reality Glasses FCC ID: A3LSMO200J** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules. The data referenced from **FCC ID: A3LSMO200P** (Model: **SM-O200P**) included in this report have been reviewed and are deemed acceptable to support the compliance of **FCC ID: A3LSMO200J**.

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 62 of 64

9.0 APPENDIX A – DATA REFERENCING SPOT-CHECKS

The spot-check data presented in this section was measured on the variant model following the guidance of the FCC's Data Referencing guidance in KDB 484596 D01 v03. Each spot-check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device.

All test cases were performed to verify the variant EUT is still in compliance with the spot-checked results to the reference device and was performed using the guidance of ANSI C63.10-2020.

Notes


- Each spot check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device.

Conducted Spot-Checks – SM-O200J



Plot 9-1. 20dB Bandwidth Plot (Spot-check)

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 63 of 64



Plot 9-2. Average Conducted Power(Spot-check)

Results

FCC Rules	Test Item	Test Case	Units	Limit	Reference Model: SM-O200P	Variant Model: SM-O200J	Deviation (dB)	Max Deviation (dB)	Pass/Fail
15.247(b)(1)	Conducted Output Power	1Mbps - Ch39 - avg	dBm	30	12.34	12.23	-0.11	1	PASS
2.1049, 15.247(a)(2)	6dB Bandwidth	3Mbps - CH39	MHz	0.5	1.275	1.329	0.054MHz	N/A	PASS

Table 9-1. Summary of Spot-checks

- END OF TEST REPORT -

FCC ID: A3LSMO200J	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 7/10/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2601220004-02-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 64 of 64