



ELEMENT MATERIALS TECHNOLOGY,

Columbia MD

(formerly PCTEST)

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>

MEASUREMENT REPORT

FCC Part 15.247 Bluetooth (Low Energy)

Applicant Name:

Samsung Electronics Co., Ltd.

129, Samsung-ro,

Yeongtong-gu, Suwon-si

Gyeonggi-do, 16677, Korea

Date of Testing:

1/29/2026 - 6/30/2026

Test Report Issue Date:

7/21/2026

Test Site/Location:

Element Lab., Columbia, MD, USA

Test Report Serial No.:

1M2602260016-03-R1.A3L

FCC ID:

A3LSMO200P

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-O200P

Additional Model(s):

SM-O201P, SM-O202P, SM-O203P, SM-O204P

EUT Type:

Extended Reality Glasses

Max. RF Output Power:

8.228 mW (9.15 dBm) Peak Conducted

Frequency Range:

2402 – 2480MHz

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

FCC Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10:2020. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N:1M2602260016-03-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2602260016-03.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 1 of 73

© 2026 ELEMENT

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

V11.3 5/14/2025

TEST REPORT REVISION HISTORY

Rev. No.	Description	Issue Date	Revised By
-	Initial Release	7/17/2026	WKR0000005883
1	Addressed comments made by TCB reviewer	7/21/2026	WKR0000005883

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 2 of 73

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Element Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description	5
2.4	Test Configuration	6
2.5	Software and Firmware	6
2.6	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure	7
3.2	AC Line Conducted Emissions	7
3.3	Radiated Emissions	8
3.4	Environmental Conditions	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	10
7.0	TEST RESULTS	14
7.1	Summary	14
7.2	6dB Bandwidth & Occupied Bandwidth Measurement – Bluetooth (LE)	15
7.3	Output Power Measurement – Bluetooth (LE)	31
7.4	Power Spectral Density – Bluetooth (LE)	39
7.5	Conducted Emissions at the Band Edge	47
7.6	Conducted Spurious Emissions	52
7.7	Radiated Spurious Emission Measurements	57
7.8	Radiated Restricted Band Edge Measurements	65
7.9	Radiated Spurious Emissions Measurements – Below 1GHz	65
7.10	Line-Conducted Test Data	70
8.0	CONCLUSION	73

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 3 of 73

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

Measurements were conducted at the Element laboratory(ies) indicated in Section 1.3 below. All measurement facilities are compliant with the test site requirements specified in ANSI C63.4:2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A. ("MD")

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISCED Standards (RSS).
- Element Washington DC LLC facility is a registered test laboratory with the site description on file with ISCED (Wireless Test Lab number 2451B) and FCC (Designation Number US1113).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISCED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

Measurements were performed at Element Materials Technology Suwon, Ltd. located in Yongin-si, Gyeonggi-do, 16954, South Korea. ("KR")

- Element Materials Technology Suwon, Ltd. is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation(A2LA) with Certificate number 2041.04 for Specific Absorption Rate (SAR), and Electromagnetic Compatibility (EMC) & Telecommunications testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Materials Technology Suwon, Ltd. facility is accredited, designated, and recognized in accordance with the provision of Radio Wave Act and International Standard ISO/IEC 17025:2017 under the National Radio Research Agency.
 - Designation Number / CABID: KR0169
 - Test Firm Registration Number of FCC: 417945
 - Test Firm Registration Number of ISCED: 26168

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 4 of 73

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Extended Reality Glasses FCC ID: A3LSMO200P**. The data found in this test report was taken with the EUT operating in Bluetooth low energy mode. While in low energy mode, the Bluetooth transmitter hops pseudo-randomly between 40 channels, three of which are “advertising channels”. When the transmitter is hopping only between the three advertising channels, the EUT does not fall under the category of a “hopper” as defined in 15.247(a)(iii) which states that a “frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.” As operation on only the advertising channels does not qualify the EUT as a hopper, the EUT is certified as a DTS device in this mode. The data found in this report is representative of the device when it transmits on its advertising channels. Typical Bluetooth operation is covered under the DSS report found with this application.

Test Device Serial No.: 260302MD20, 260302MD21, 260302MD22, 260302MD23, 260302MD24, 260302MD25, 260310MD15, 260310MD16, 260601MD01, 260608MD02, 260608MD03, 260609MD08, 260609MD04, 260609MD05, 260609MD06, 260609MD07, 260518MD10, 260518MD11, 260518MD12, 260518MD13

2.2 Device Capabilities

This device contains the following capabilities:

BT (LE, BDR, EDR), 2.4GHz WLAN (802.11b/g/n/ac/ax), 5 and 6GHz UNII (a/n/ac/ax)

Ch.	Frequency (MHz)
37	2402
:	:
17	2440
:	:
39	2480

Table 2-1. Frequency / Channel Operations – 125/500kbps & 1Mbps

Ch.	Frequency (MHz)
0	2404
:	:
17	2440
:	:
36	2478

Table 2-2. Frequency / Channel Operations – 2Mbps

2.3 Antenna Description

The manufacturer provided the antenna gains which can affect the validity of test results used for determination of compliance. The following antenna gains are used in this device per the "Unlicensed Band Antenna Gain" document provided by the client. This document is also included in the filing as a public exhibit.

Frequency [GHz]	Antenna-1 Gain (dBi)
2.4	-4.99

Table 2-3. Antenna Peak Gain

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 5 of 73

2.4 Test Configuration

The EUT was tested per the guidance of ANSI C63.10:2020. ANSI C63.10:2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report. The worst orientation was found to be Y-orientation (landscape).

The EUT has four configurations: one is with both ear arm fully open, one is with left ear arm closed/right ear arm open, one is with left ear arm open/right ear arm closed, and one is with both ear arm closed. All configurations are tested, and the worst case radiated emissions data is shown in this report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor (Model: EP-TA12JWE) via USB cable with wire charger

2.5 Software and Firmware

The test was conducted with software/firmware version 020XXUEU0AZE3 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 6 of 73

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2020) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that those cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 7 of 73

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4:2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4:2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 8 of 73

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 9 of 73

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10:2020. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

Table 5-1. Measurement Uncertainty Budget – MD

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.95
Radiated Disturbance (<1GHz)	4.10
Radiated Disturbance (>1GHz)	4.82
Radiated Disturbance (>18GHz)	4.96

Table 5-2. Measurement Uncertainty Budget – KR

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 10 of 73

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurement antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	MD 1M 40	EMC Cable and Switch System	2/3/2026	Annual	2/3/2027	MD 1M 40
-	AP1-002	EMC Cable and Switch System	2/3/2026	Annual	2/3/2027	AP1-002
-	AP2-001	EMC Cable and Switch System	1/30/2026	Annual	1/30/2027	AP2-001
-	AP2-002	EMC Cable and Switch System	1/30/2026	Annual	1/30/2027	AP2-002
-	ETS-001	EMC Cable and Switch System	1/29/2026	Annual	1/29/2027	ETS-001
-	ETS-002	EMC Cable and Switch System	1/29/2026	Annual	1/29/2027	ETS-002
-	WL25-1	Conducted Cable Set (25GHz)	1/30/2026	Annual	1/30/2027	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	1/30/2026	Annual	1/30/2027	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	1/30/2026	Annual	1/30/2027	WL40-1
-	WL40-2	Conducted Cable Set (40GHz)	1/30/2026	Annual	1/30/2027	WL40-2
EMCO	3115	Horn Antenna (1-18GHz)	9/6/2024	Biennial	9/6/2026	9704-5182
EMCO	3116	Horn Antenna (18-40GHz)	1/26/2026	Biennial	1/26/2028	9203-2178
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	6/4/2025	Biennial	6/4/2027	125518
ETS-Lindgren	3116C	DRG Horn Antenna	4/22/2025	Biennial	4/22/2027	218893
Keysight Technologies	N9030A	PXA Signal Analyzer	11/3/2025	Annual	11/3/2026	MY54490576
Keysight Technologies	N9038A	MXE EMI Receiver	11/10/2025	Annual	11/10/2026	MY51210133
Keysight Technologies	N9030A	PXA Signal Analyzer	11/3/2025	Annual	11/3/2026	MY54490576
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	1/30/2026	Annual	1/30/2027	NMLC-2
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	12/19/2025	Annual	12/19/2026	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	1/16/2026	Annual	1/16/2027	100348
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	3/11/2026	Annual	3/11/2027	101716
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	12/19/2025	Annual	12/19/2026	100342
Rohde & Schwarz	ENV216	Two-Line V-Network	2/4/2026	Biennial	2/4/2028	101379
Rohde & Schwarz	180-422-KF	Horn (18 - 40GHz)	10/9/2024	Biennial	10/9/2026	U157403-01
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	9/11/2024	Biennial	9/11/2026	A051107
Sunol	JB6	Bi-Log Antenna (30M - 5GHz)	3/24/2025	Biennial	3/24/2027	A082816

Table 6-1. Test Equipment Calibration Table - MD

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Rohde & Schwarz	ESW	EMI Test Receiver	09/15/2025	Annual	09/14/2026	101955
schwarzbeck	VULB9162	Broadband TRILOG Antenna	06/05/2025	Biennial	06/04/2027	9162-217
Sunol Sciences	DRH-118	Horn Antenna	05/14/2026	Annual	05/13/2027	A102416-1
-	UEK1	EMC Cable and Switch System	01/28/2026	Annual	01/27/2027	UEK1

Table 6-2. Test Equipment Calibration Table -KR

Note:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment listed with "N/A under calibration information was not used to make calibrated measurements.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 11 of 73

Component	Serial Number
MegaPhase (CAGE 1GVT4) Cable TM40-K1K1-30	20233002 004
Uniflex Micro Coax UFB 142A-Q-0984-200200	64639 232063 001
R&S TS-PR1840	9037.7670.02

Table 6-3. MD 1M 18-40 EMC Cable and Switch System Components

Component	Serial Number
Sucoflex 106A Cable	501992
MegaPhase Cable N29-N1N1-324	20335606 001
Rohde & Schwarz SF Unit	102133
MiniCircuits Cable CBL-2FT-SMSM+	77745
MegaPhase Cable 10511-1	15034701 001
MiniCircuits Switch RC 2SPDT-A18	11703270 041
Sucoflex 104 Cable	320259/4
Sucoflex 104 Cable	321999/4
Sucoflex 104 Cable	321995/4

Table 6-4. AP2-001 EMC Cable and Switch System Components

Component	Serial Number
Flex Cable	P2A-0001
Micro-Coax Utilflex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Chamber Passthrough	CP4/X12
Micro-Coax Utilflex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Micro-Coax Utilflex Cable UFB142A-0-0629-5GU200 MFR 6463	232069-001
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181

Table 6-5. AP2-001 EMC Cable and Switch System Components

Component	Serial Number
MiniCircuits Cable CBL-0.5M-SMNM+	47261
Micro-Coax Utilflex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-001
Micro-Coax Utilflex Cable UFB311A-1-0629-50U50U MFR 64639	231986-002
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	19046401 001
Megaphase (CAGE 1GVT4) Flex Cable 10511-1	15044701-006
Micro-Coax Utilflex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-002
Micro-Coax Utilflex Cable UFB311A-1-0629-50U50U MFR 64639	231986-004
Micro-Coax Utilflex Cable UFB142A-0-0629-5GU200 MFR 64639	232069-001
Rohde & Schwarz SF Unit	102138
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181
Micro-Coax Utilflex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Micro-Coax Utilflex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335

Table 6-6. AP2-002 EMC Cable and Switch System Components

Component	Serial Number
Pasternack Cable RG214/U	111815
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001

Table 6-7. ETS-001 EMC Cable and Switch System Components

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 12 of 73

Component	Serial Number
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	20502201 001
Rohde & Schwarz SF Unit	102134
Minicircuits Cable CBL=0.5M-NMNM+	15440

Table 6-8. ETS-002 EMC Cable and Switch System Components

Component	Serial Number
MegaPhase Cable, Model: TM26-S1S1-30	20929201 004
Pasternack 6dB Attenuator, Model: PE7005-6	N/A

Table 6-9. WL25-1 Conducted Cable Set Components

Component	Serial Number
Mini-Circuits Cable, Model: CBL-2FT-SMSM+	77743
MCL 6dB Attenuator, Model: BW-S6W2+	1314

Table 6-10. WL25-2 Conducted Cable Set Components

Component	Serial Number
MegaPhase Cable, Model: TM40-K1K1-36	18160102 001
MCL 10dB Attenuator, Model: BW-K10 2W44+	1902

Table 6-11. WL40-1 Conducted Cable Set Components

Component	Serial Number
MegaPhase Cable, Model: TM40-K1K1-30	18165902 001
MCL 10dB Attenuator, Model: BW-K10 2W44+	2108

Table 6-12. WL40-2 Conducted Cable Set Components

Component	Serial Number
Rohde & Schwarz SF Unit	102151
ALPHA WIRE H1	6340
HUBER+SUHNER, Inc. SUCOFLEX_104 PE Cable	305916
HUBER+SUHNER, Inc. SUCOFLEX_100	803242-6

Table 6-13. UEK1 EMC Cable and Switch System Components

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 13 of 73

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMO200P
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 40

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference	Test Lab Location
15.247(a)(2)	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2	MD
15.247(b)(3)	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3	MD
15.247(e)	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4	MD
15.247(d)	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6	MD
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, 7.8, 7.9	MD & KR
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	LINE CONDUCTED	PASS	Section 7.10	MD

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Bluetooth LE Automation,” Version 3.6.
5. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Chamber Automation,” Version 1.7.7.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 14 of 73

7.2 6dB Bandwidth & Occupied Bandwidth Measurement – Bluetooth (LE)

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10:2020 – Section 11.8.2 Option 2 (6dB BW)

ANSI C63.10:2020 – Section 6.9.3 (OBW)

Test Settings - 6dB Bandwidth

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Settings - Occupied Bandwidth

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 15 of 73

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 16 of 73		


Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	125 kbps	37	LE	606.3	500	Pass
2440	125 kbps	17	LE	606.5	500	Pass
2480	125 kbps	39	LE	607.6	500	Pass
2402	500 kbps	37	LE	660.6	500	Pass
2440	500 kbps	17	LE	657.8	500	Pass
2480	500 kbps	39	LE	658.6	500	Pass
2402	1 Mbps	37	LE	689.6	500	Pass
2440	1 Mbps	17	LE	686.8	500	Pass
2480	1 Mbps	39	LE	683.7	500	Pass
2404	2 Mbps	0	LE	1140.9	500	Pass
2440	2 Mbps	17	LE	1146.7	500	Pass
2478	2 Mbps	36	LE	1142.3	500	Pass

Table 7-2. Conducted 6dB Bandwidth Measurements – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 17 of 73




Plot 7-1. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 37) – Ant 1




Plot 7-2. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 17) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 18 of 73



Plot 7-3. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 39) – Ant 1



Plot 7-4. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 37) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 19 of 73




Plot 7-5. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 17) – Ant 1




Plot 7-6. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 39) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 20 of 73



Plot 7-7. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps - Ch. 37) - Ant 1



Plot 7-8. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps - Ch. 17) - Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 21 of 73		




Plot 7-9. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps - Ch. 39) - Ant 1



Plot 7-10. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps - Ch. 0) - Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 22 of 73		



Plot 7-11. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 1



Plot 7-12. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 23 of 73		

Frequency [MHz]	Data Rate [Mbps]	Bluetooth Mode	Antenna-1 OBW [MHz]
2402	125 kbps	LE	1.045
2440	125 kbps	LE	1.044
2480	125 kbps	LE	1.041
2402	500 kbps	LE	1.018
2440	500 kbps	LE	1.016
2480	500 kbps	LE	1.014
2402	1 Mbps	LE	1.026
2440	1 Mbps	LE	1.020
2480	1 Mbps	LE	1.024
2404	2 Mbps	LE	2.044
2440	2 Mbps	LE	2.045
2478	2 Mbps	LE	2.043

Table 7-3. OBW Measurements - SISO

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 24 of 73




Plot 7-13. OBW Plot (Bluetooth (LE), 125kbps – Ch. 37) – SISO ANT1




Plot 7-14. OBW Plot (Bluetooth (LE), 125kbps – Ch. 17) – SISO ANT1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 25 of 73




Plot 7-15. OBW Plot (Bluetooth (LE), 125kbps – Ch. 39) – SISO ANT1




Plot 7-16. OBW Plot (Bluetooth (LE), 500kbps – Ch. 37) – SISO ANT1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 26 of 73



Plot 7-17. OBW Plot (Bluetooth (LE), 500kbps – Ch. 17) – SISO ANT1



Plot 7-18. OBW Plot (Bluetooth (LE), 500kbps – Ch. 39) – SISO ANT1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 27 of 73



Plot 7-19. OBW Plot (Bluetooth (LE), 1Mbps - Ch. 37) - SISO ANT1



Plot 7-20. OBW Plot (Bluetooth (LE), 1Mbps - Ch. 17) - SISO ANT1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 28 of 73		



Plot 7-21. OBW Plot (Bluetooth (LE), 1Mbps – Ch. 39) – SISO ANT1



Plot 7-22. OBW Plot (Bluetooth (LE), 2Mbps – Ch. 0) – SISO ANT1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 29 of 73



Plot 7-23. OBW Plot (Bluetooth (LE), 2Mbps – Ch. 17) – SISO ANT1



Plot 7-24. OBW Plot (Bluetooth (LE), 2Mbps – Ch. 36) – SISO ANT1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 30 of 73

7.3 Output Power Measurement – Bluetooth (LE)

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

Test Procedure Used

ANSI C63.10:2020 – Section 11.9.1.1

Test Settings

1. RBW = 3MHz
2. VBW = 50MHz
3. Span $\geq 3 \times$ RBW
4. Sweep = auto couple
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 31 of 73		


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Peak Conducted Power	
				[dBm]	[mW]
2402	125 kbps	37	LE	9.10	8.128
2440	125 kbps	17	LE	8.97	7.889
2480	125 kbps	39	LE	8.60	7.238
2402	500 kbps	37	LE	9.15	8.228
2440	500 kbps	17	LE	8.98	7.905
2480	500 kbps	39	LE	8.64	7.315
2402	1 Mbps	37	LE	9.12	8.168
2440	1 Mbps	17	LE	8.98	7.907
2480	1 Mbps	39	LE	8.75	7.492
2404	2 Mbps	0	LE	9.13	8.187
2440	2 Mbps	17	LE	9.06	8.046
2478	2 Mbps	36	LE	8.91	7.775

Table 7-4. Conducted Output Power Measurements (Bluetooth (LE)) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 32 of 73




Plot 7-25. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 37) – Ant 1




Plot 7-26. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 17) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 33 of 73		




Plot 7-27. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 39) – Ant 1




Plot 7-28. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 37) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 34 of 73		




Plot 7-29. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 17) – Ant 1




Plot 7-30. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 39) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 35 of 73		




Plot 7-31. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 1




Plot 7-32. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 36 of 73		




Plot 7-33. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 1




Plot 7-34. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 37 of 73		



Plot 7-35. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 1



Plot 7-36. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 38 of 73		

7.4 Power Spectral Density – Bluetooth (LE)

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10:2020 – Section 11.10.2 Method PKPSD

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 39 of 73		


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	125 kbps	37	LE	2.15	8.0	-5.85
2440	125 kbps	17	LE	1.19	8.0	-6.81
2480	125 kbps	39	LE	1.60	8.0	-6.40
2402	500 kbps	37	LE	1.98	8.0	-6.02
2440	500 kbps	17	LE	0.78	8.0	-7.23
2480	500 kbps	39	LE	1.17	8.0	-6.83
2402	1 Mbps	37	LE	1.84	8.0	-6.16
2440	1 Mbps	17	LE	1.80	8.0	-6.20
2480	1 Mbps	39	LE	1.21	8.0	-6.79
2404	2 Mbps	0	LE	-0.10	8.0	-8.10
2440	2 Mbps	17	LE	-0.48	8.0	-8.48
2478	2 Mbps	36	LE	-0.70	8.0	-8.70

Table 7-5. Conducted Power Density Measurements – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 40 of 73




Plot 7-37. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 37) – Ant 1




Plot 7-38. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 17) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 41 of 73		




Plot 7-39. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 39) – Ant 1




Plot 7-40. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 37) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 42 of 73		




Plot 7-41. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 17) – Ant 1




Plot 7-42. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 39) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 43 of 73		




Plot 7-43. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 1




Plot 7-44. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 44 of 73		




Plot 7-45. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 1




Plot 7-46. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 45 of 73



Plot 7-47. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 1



Plot 7-48. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 46 of 73		

7.5 Conducted Emissions at the Band Edge

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10:2020 – Section 11.11.3

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 47 of 73




Plot 7-49. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 37) – Ant 1




Plot 7-50. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 39) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 48 of 73		




Plot 7-51. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 37) – Ant 1




Plot 7-52. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 39) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 49 of 73		




Plot 7-53. Band Edge Plot (Bluetooth (LE), 1Mbps - Ch. 37) - Ant 1




Plot 7-54. Band Edge Plot (Bluetooth (LE), 1Mbps - Ch. 39) - Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 50 of 73		



Plot 7-55. Band Edge Plot (Bluetooth (LE), 2Mbps - Ch. 0) - Ant 1



Plot 7-56. Band Edge Plot (Bluetooth (LE), 2Mbps - Ch. 36) - Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 51 of 73		

7.6 Conducted Spurious Emissions

Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 8.5 of KDB 558074 D01 v05r02 and Section 11.11.3 of ANSI C63.10:2020.

Test Procedure Used

ANSI C63.10:2020 – Section 11.11.3

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup


FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 52 of 73		

Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 53 of 73






Plot 7-59. Conducted Spurious Plot (Bluetooth (LE), 1Mbps - Ch. 17) - Ant 1




Plot 7-60. Conducted Spurious Plot (Bluetooth (LE), 1Mbps - Ch. 17) - Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 55 of 73		



Plot 7-61. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 1



Plot 7-62. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 56 of 73		

7.7 Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-6 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-6. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 – Section 6.6.4.3

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3kHz > 1/T
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times (1/duty cycle) traces

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 57 of 73

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-7 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-7. RBW as a Function of Frequency

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 58 of 73

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of ANSI C63.10:2020 Section 11.12.2 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-6.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery and emissions were investigated with the unit powered by an extended battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Average measurements were recorded using a VBW of 3kHz, per Section 4.1.4.2.3 of ANSI C63.10:2020, since 1/T is equal to just under 3kHz. This method was used because the EUT could not be configured to operate with a duty cycle > 98%. Both average and peak measurements were made using a peak detector
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
8. No significant radiated band edge emissions were found in the 2310 – 2390MHz restricted band.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
10. In this section, plots showing measurements shown as "channel power" are recorded using the integration methods described in Section 11.12.3.2 of ANSI C63.10:2020 for average and peak measurements as allowed per Section 12.7.4.4.1. Also, the average measurements include the duty cycle correction factor shown in Section 2.2 of this report.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 59 of 73

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset


- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$


FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 60 of 73

Radiated Spurious Emission Measurements – Ant 1


§15.205 §15.209 §15.247(d)



Plot 7-63. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 37) – Ant 1




Plot 7-64. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 17) – Ant 1



Plot 7-65. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 39) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 61 of 73



Plot 7-66. Radiated Spurious Plot above 18GHz (Bluetooth (LE)) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 62 of 73

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 37

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	H	-	-	-77.97	1.37	30.40	53.98	-23.58
4804.00	Peak	H	-	-	-65.55	1.37	42.82	73.98	-31.16
12010.00	Avg	H	-	-	-79.86	13.03	40.17	53.98	-13.80
12010.00	Peak	H	-	-	-67.85	13.03	52.18	73.98	-21.79

Table 7-8. Radiated Measurements @ 3 meters – Ant 1

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2440MHz
 Channel: 17

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4880.00	Avg	H	-	-	-77.87	2.10	31.23	53.98	-22.75
4880.00	Peak	H	-	-	-65.15	2.10	43.95	73.98	-30.03
7320.00	Avg	H	-	-	-79.28	6.79	34.51	53.98	-19.47
7320.00	Peak	H	-	-	-66.49	6.79	47.30	73.98	-26.68
12200.00	Avg	H	-	-	-80.11	12.60	39.49	53.98	-14.49
12200.00	Peak	H	-	-	-67.64	12.60	51.96	73.98	-22.02

Table 7-9. Radiated Measurements @ 3 meters – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	H	-	-	-77.91	2.53	31.62	53.98	-22.36
4960.00	Peak	H	-	-	-65.98	2.53	43.55	73.98	-30.43
7440.00	Avg	H	-	-	-79.42	7.45	35.03	53.98	-18.95
7440.00	Peak	H	-	-	-67.26	7.45	47.19	73.98	-26.79
12400.00	Avg	H	-	-	-79.54	12.98	40.44	53.98	-13.54
12400.00	Peak	H	-	-	-66.76	12.98	53.22	73.98	-20.76

Table 7-10. Radiated Measurements @ 3 meters – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 64 of 73

7.8 Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Bluetooth Mode:	LE
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	39



Plot 7-67. Radiated Restricted Upper Band Edge Measurement (Average) – Ant 1



Plot 7-68. Radiated Restricted Upper Band Edge Measurement (Peak) – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 65 of 73		

7.9 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-11 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-11. Radiated Limits

Test Procedures Used

ANSI C63.10:2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 66 of 73

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 67 of 73		


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-11.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery and emissions were investigated with the unit powered by an extended battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 68 of 73

Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-69. Radiated Spurious Plot below 1GHz – Ant 1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
698.00	Quasi-Peak	H	-	-	-105.83	29.13	30.30	46.02	-15.72
794.00	Quasi-Peak	H	-	-	-106.65	30.22	30.57	46.02	-15.45

Table 7-12. Radiated Spurious Emissions Below 1GHz – Ant 1

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 69 of 73

7.10 Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-13. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 70 of 73

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 71 of 73



Plot 7-70. Line-Conducted Test Plot (L1)



Plot 7-71. Line-Conducted Test Plot (N)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 72 of 73

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Extended Reality Glasses FCC ID: A3LSMO200P** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

- END OF TEST REPORT -

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-03-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 73 of 73