

MEASUREMENT REPORT**FCC Part 15.407 802.11ax WiFi 6E (OFDMA)****Applicant Name:**

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

1/29/2026 - 6/30/2026

Test Report Issue Date:

7/22/2026

Test Site/Location:

Element Lab., Columbia, MD, USA

Element Lab., Yongin-Si, Gyeonggi-do, South Korea

Test Report Serial No.:

1M2602260016-09-R1.A3L

FCC ID:

A3LSMO200P

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-O200P

Additional Model(s):

SM-O201P, SM-O202P, SM-O203P, SM-O204P

EUT Type:

Extended Reality Glasses

Frequency Range:

5935 – 7115MHz

Modulation Type:

OFDMA

FCC Classification:

15E 6GHz Low Power Indoor Client (6XD)

FCC Rule Part(s):

Part 15 Subpart E (15.407)

FCC Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023, KDB 987594 D02 v03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10:2020. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N:1M2602260016-09-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2602260016-09.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



RJ Ortanez
Executive Vice President



FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 1 of 63

TEST REPORT REVISION HISTORY

Rev. No.	Description	Issue Date	Revised By
-	Initial Release	7/17/2026	WKR0000005883
1	Addressed comments made by TCB reviewer	7/22/2026	WKR0000005883

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 2 of 63

T A B L E O F C O N T E N T S

1	INTRODUCTION	5
1.1	Scope.....	5
1.2	Element Test Location.....	5
1.3	Test Facility / Accreditations.....	5
2	PRODUCT INFORMATION	6
2.1	Equipment Description	6
2.2	Device Capabilities.....	6
2.3	Antenna Description.....	8
2.4	Test Configuration.....	9
2.5	Software and Firmware	9
2.6	EMI Suppression Device(s) / Modifications.....	9
3	DESCRIPTION OF TESTS	10
3.1	Evaluation Procedure	10
3.2	AC Line Conducted Emissions	10
3.3	Radiated Emissions.....	11
3.4	Environmental Conditions.....	11
4	ANTENNA REQUIREMENTS	12
5	MEASUREMENT UNCERTAINTY	13
6	TEST EQUIPMENT CALIBRATION DATA.....	14
7	TEST RESULTS	17
7.1	Summary.....	17
7.2	26dB Bandwidth Measurement.....	19
7.2.1	Antenna-1 Bandwidth Measurements - (Partial Tones).....	22
7.2.2	Antenna-1 Bandwidth Measurements - (Full Tones).....	24
7.3	UNII Output Power Measurement.....	26
7.4	Maximum Power Spectral Density	30
7.4.1	Antenna-1 Power Spectral Density Measurements.....	33
7.5	In-Band Emissions	38
7.5.1	Antenna-1 In-Band Emission Measurements.....	42
7.6	Radiated Emission Measurements	46
7.6.1	Radiated Spurious Emission Measurements (26 Tones)	50
7.6.2	Radiated Spurious Emission Measurements (242 Tones)	54
7.6.3	Radiated Band Edge Measurements (20MHz BW – Partial Tone – 106T)	58
7.6.4	Radiated Band Edge Measurements (20MHz BW – Full Tone – 242T)	59
7.6.5	Radiated Band Edge Measurements (40MHz BW – Full Tone – 484T)	60
7.6.6	Radiated Band Edge Measurements (80MHz BW – Full Tone – 996T)	61
7.6.7	Radiated Band Edge Measurements (160MHz BW – Full Tone – 2x996T).....	62
8	CONCLUSION.....	63

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 3 of 63

MEASUREMENT REPORT

Channel Bandwidth [MHz]	UNII Band	Tx Frequency [MHz]	Antenna-1	
			Max. Power [mW]	Max. Power [dBm]
20	5	5935 - 6415	1.74	2.41
	6	6435 - 6515	1.88	2.74
	7	6535 - 6875	2.05	3.12
	8	6895 - 7115	1.39	1.42
40	5	5965 - 6405	3.48	5.41
	6	6445 - 6525	3.72	5.71
	7	6565 - 6845	3.90	5.91
	8	6885 - 7085	2.67	4.26
80	5	5985 - 6385	3.50	5.44
	6	6465	3.81	5.81
	7	6545 - 6865	3.88	5.89
	8	6945 - 7025	2.51	3.99
160	5	6025 - 6345	3.45	5.38
	6	6505	3.85	5.85
	7	6665 - 6825	3.72	5.71
	8	6985	2.45	3.89

EUT Overview - EIRP

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 4 of 63

1 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4:2014.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A. ("MD")

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- Element Washington DC LLC facility is a registered test laboratory with the site description on file with ISSED (Wireless Test Lab number 2451B) and FCC (Designation Number US1113).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISSED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

Measurements were performed at Element Materials Technology Suwon, Ltd. located in Yongin-si, Gyeonggi-do, 16954, South Korea. ("KR")

- Element Materials Technology Suwon, Ltd. is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.04 for Specific Absorption Rate (SAR), and Electromagnetic Compatibility (EMC) & Telecommunications testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Materials Technology Suwon, Ltd. facility is accredited, designated, and recognized in accordance with the provision of Radio Wave Act and International Standard ISO/IEC 17025:2017 under the National Radio Research Agency.
 - Designation Number / CABID: KR0169
 - Test Firm Registration Number of FCC: 417945
 - Test Firm Registration Number of ISSED: 26168

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 5 of 63

2 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Electronics Co., Ltd. Extended Reality Glasses FCC ID: A3LSMO200P**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter while operating in the 6GHz band.

Test Device Serial No.: 260302MD20, 260302MD21, 260302MD22, 260302MD23, 260302MD24, 260302MD25, 260310MD15, 260310MD16, 260601MD01, 260608MD02, 260608MD03, 260609MD08, 260609MD04, 260609MD05, 260609MD06, 260609MD07, 260518MD10, 260518MD11, 260518MD12, 260518MD13

2.2 Device Capabilities

This device contains the following capabilities:

BT (LE, BDR, EDR), 2.4GHz WLAN (802.11b/g/n/ac/ax), 5 and 6GHz UNII (a/n/ac/ax)

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
2	5935	97	6435	117	6535	189	6895
:	:	:	:	:	:	:	:
45	6175	105	6475	149	6695	209	6995
:	:	:	:	:	:	:	:
93	6415	113	6515	185	6875	233	7115

Table 2-1. 802.11ax (20MHz) Frequency / Channel Operations

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
3	5965	99	6445	123	6565	187	6885
:	:	:	:	:	:	:	:
43	6165	107	6485	155	6725	211	7005
:	:	:	:	:	:	:	:
91	6405	115	6525	179	6845	227	7085

Table 2-2. 802.11ax (40MHz BW) Frequency / Channel Operations

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
7	5985	103	6465	119	6545	199	6945
:	:			:	:	:	:
39	6145			151	6705	215	7025
:	:			:	:		
87	6385			183	6865		

Table 2-3. 802.11ax (80MHz BW) Frequency / Channel Operations

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 6 of 63

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
15	6025	111	6505	143	6665	207	6985
:	:			:	:		
47	6185			175	6825		
:	:						
79	6345						

Table 2-4. 802.11ax (160MHz BW) Frequency / Channel Operations

Notes:

- 6GHz NII operation is possible in 20MHz, 40MHz, 80MHz, and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10:2020. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Band	Bandwidth	Tone Type	Tone Size	ANT1	
				Duty Cycle [%]	Radiated DCCF [dB]
6GHz	20MHz	RU	26T	99.63	N/A
			52T	99.67	N/A
			106T	99.62	N/A
			242T	98.99	N/A
	40MHz	RU	26T	99.69	N/A
			52T	99.71	N/A
			106T	99.60	N/A
			242T	99.10	N/A
			484T	98.26	N/A
	80MHz	RU	26T	99.69	N/A
			52T	99.69	N/A
			106T	99.60	N/A
			242T	99.05	N/A
			484T	98.19	N/A
			996T	97.58	0.11
	160MHz	RU	26T	99.71	N/A
			52T	99.71	N/A
			106T	99.55	N/A
			242T	99.05	N/A
			484T	98.21	N/A
			996T	97.43	0.11
			2x996T	97.48	0.11

Table 2-5. Measured Duty Cycles

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 7 of 63

2. The device supports the following data rates (shown in Mbps):

MCS Index	Spatial Stream	OFDMA (802.11ax)																				
		26T			52T			106T			242T			484T			996T			2x996T		
		0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI
0	1	0.9	0.8	0.8	1.8	1.7	1.5	3.8	3.5	3.2	8.6	8.1	7.3	17.2	16.3	14.6	36	34	30.6	72.1	68.1	61.3
1	1	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5
2	1	2.6	2.5	2.3	5.3	5	4.5	11.3	10.6	9.6	25.8	24.4	21.9	51.6	48.8	43.9	108.1	102.1	91.9	216.2	204.2	183.8
3	1	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245
4	1	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5
5	1	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490
6	1	7.9	7.5	6.8	15.9	15	13.5	33.8	31.9	28.7	77.4	73.1	65.8	154.9	146.3	131.6	324.3	306.3	275.6	648.5	612.5	551.3
7	1	8.8	8.3	7.5	17.6	16.7	15	37.5	35.4	31.9	86	81.3	73.1	172.1	162.5	146.3	360.3	340.3	306.3	720.6	680.6	612.5
8	1	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735
9	1	11.8	11.1	10	23.5	22.2	20	50	47.2	42.5	114.7	108.3	97.5	229.4	216.7	195	480.4	453.7	408.3	960.8	907.4	816.7
10	1	13.2	12.5	11.3	26.5	25	22.5	56.3	53.1	47.8	129	121.9	109.7	258.1	243.8	219.4	540.4	510.4	459.4	1080.9	1020.8	918.8
11	1	14.7	13.9	12.5	29.4	27.8	25	62.5	59	53.1	143.4	135.4	121.9	286.8	270.8	243.8	600.5	567.1	510.4	1201	1134.3	1020.8
	1	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3	1297.1	1225	1102.5
	1	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5	1441.2	1361.1	1225

Table 2-6. Supported Data Rates

3. The device supports either Low Power Indoor (LPI) and or Very Low Power (VLP) operation in the following UNII bands:

UNII Band	Low Power Indoor (LPI)	Very Low Power (VLP)
UNII 5	✓	✓
UNII 6	✓	✓
UNII 7	✓	✓
UNII 8	✓	✓

Table 2-7. Power Operation

✓ = Support; ✗ = NOT Support

2.3 Antenna Description

The manufacturer provided the antenna gains which can affect the validity of test results used for determination of compliance. The following antenna gains are used in this device per the "Unlicensed Band Antenna Gain" document provided by the client. This document is also included in the filing as a public exhibit.

Frequency	Peak Gain [dBi]
5925 MHz	-8.55
6025 MHz	-8.6
6125 MHz	-8.89
6225 MHz	-8.88
6325 MHz	-7.01
6425 MHz	-6.44
6525 MHz	-6.11
6625MHz	-5.8
6725MHz	-5.59
6825MHz	-6.24
6925MHz	-7.33
7025MHz	-8.38
7125MHz	-8.85

Table 2-8 Antenna Peak Gain per Frequency

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 8 of 63

Frequency	Peak Gain [dBi]
5925 – 6425 MHz	-6.44
6425 – 6525 MHz	-6.11
6525 – 6875 MHz	-5.59
6875 – 7125 MHz	-7.33

Table 2-9. Antenna Peak Gain – Highest

Frequency	Peak Gain [dBi]
5925 – 6425 MHz	-8.89
6425 – 6525 MHz	-6.44
6525 – 6875 MHz	-7.33
6875 – 7125 MHz	-8.85

Table 2-10. Antenna Peak Gain – Lowest

2.4 Test Configuration

ANSI C63.10:2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5 and 7.6 for antenna port conducted emissions test setups.

This device operates in the 5.925-7.125 GHz band when under control of an indoor access point or very low power access point.

The EUT has four configurations: one is with both ear arm fully open, one is with left ear arm closed/right ear arm open, one is with left ear arm open/right ear arm closed, and one is with both ear arm closed. All configurations are tested, and the worst case radiated emissions data is shown in this report.

2.5 Software and Firmware

The test was conducted with firmware version 020XXUEU0AZE3 installed on the EUT.

2.6 EMI Suppression Device(s) / Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 9 of 63

3 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2020) and the guidance provided in KDB 987594 D02 v03 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1-meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst-case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 10 of 63

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3-meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4:2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4:2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 11 of 63

4 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 12 of 63

5 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10:2020. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Contention Based Protocol Conducted Measurements	0.86
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

Table 5-1. Measurement Uncertainty Budget – MD

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.95
Radiated Disturbance (<1GHz)	4.10
Radiated Disturbance (>1GHz)	4.82
Radiated Disturbance (>18GHz)	4.96

Table 5-2. Measurement Uncertainty Budget – KR

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 13 of 63

6 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurement antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	MD 1M 40	EMC Cable and Switch System	2/3/2026	Annual	2/3/2027	MD 1M 40
-	AP1-002	EMC Cable and Switch System	2/3/2026	Annual	2/3/2027	AP1-002
-	AP2-001	EMC Cable and Switch System	1/30/2026	Annual	1/30/2027	AP2-001
-	AP2-002	EMC Cable and Switch System	1/30/2026	Annual	1/30/2027	AP2-002
-	ETS-001	EMC Cable and Switch System	1/29/2026	Annual	1/29/2027	ETS-001
-	ETS-002	EMC Cable and Switch System	1/29/2026	Annual	1/29/2027	ETS-002
-	WL25-1	Conducted Cable Set (25GHz)	1/30/2026	Annual	1/30/2027	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	1/30/2026	Annual	1/30/2027	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	1/30/2026	Annual	1/30/2027	WL40-1
-	WL40-2	Conducted Cable Set (40GHz)	1/30/2026	Annual	1/30/2027	WL40-2
Anritsu	MA24408A	POWER SENSOR	1/27/2026	Annual	1/27/2027	11676
Anritsu	MA24408A	POWER SENSOR	3/4/2026	Annual	3/4/2027	11675
Anritsu	MA24408A	POWER SENSOR	1/27/2026	Annual	1/27/2027	12798
Anritsu	MA24408A	POWER SENSOR	3/4/2026	Annual	3/4/2027	12776
EMCO	3115	Horn Antenna (1-18GHz)	9/6/2024	Biennial	9/6/2026	9704-5182
EMCO	3116	Horn Antenna (18-40GHz)	1/26/2026	Biennial	1/26/2028	9203-2178
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	6/4/2025	Biennial	6/4/2027	125518
ETS-Lindgren	3116C	DRG Horn Antenna	4/22/2025	Biennial	4/22/2027	218893
Keysight Technologies	N9030A	PXA Signal Analyzer	11/3/2025	Annual	11/3/2026	MY54490576
Keysight Technologies	N9038A	MXE EMI Receiver	11/10/2025	Annual	11/10/2026	MY51210133
Keysight Technologies	N9030A	PXA Signal Analyzer	11/3/2025	Annual	11/3/2026	MY54490576
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	1/30/2026	Annual	1/30/2027	NMLC-2
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	12/19/2025	Annual	12/19/2026	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	1/16/2026	Annual	1/16/2027	100348
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	3/11/2026	Annual	3/11/2027	101716
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	12/19/2025	Annual	12/19/2026	100342
Rohde & Schwarz	ENV216	Two-Line V-Network	2/4/2026	Biennial	2/4/2028	101379
Rohde & Schwarz	180-422-KF	Horn (18 - 40GHz)	10/9/2024	Biennial	10/9/2026	U157403-01
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	9/11/2024	Biennial	9/11/2026	A051107
Sunol	JB6	Bi-Log Antenna (30M - 5GHz)	3/24/2025	Biennial	3/24/2027	A082816

Table 6-1. Test Equipment Calibration Table - MD

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Rohde & Schwarz	ESW	EMI Test Receiver	09/15/2025	Annual	09/14/2026	101955
schwarzbeck	VULB9162	Broadband TRILOG Antenna	06/05/2025	Biennial	06/04/2027	9162-217
Sunol Sciences	DRH-118	Horn Antenna	05/14/2026	Annual	05/13/2027	A102416-1
-	UEK1	EMC Cable and Switch System	01/28/2026	Annual	01/27/2027	UEK1

Table 6-2. Test Equipment Calibration Table - KR

Note:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment listed with "N/A" under calibration information was not used to make calibrated measurements.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 14 of 63

Component	Serial Number
MegaPhase (CAGE 1GVT4) Cable TM40-K1K1-30	20233002 004
Uniflex Micro Coax UFB 142A-Q-0984-200200	64639 232063 001
R&S TS-PR1840	9037.7670.02

Table 6-3. MD 1M 18-40 EMC Cable and Switch System Components

Component	Serial Number
Sucoflex 106A Cable	501992
MegaPhase Cable N29-N1N1-324	20335606 001
Rohde & Schwarz SF Unit	102133
MiniCircuits Cable CBL-2FT-SMSM+	77745
MegaPhase Cable 10511-1	15034701 001
MiniCircuits Switch RC 2SPDT-A18	11703270 041
Sucoflex 104 Cable	320259/4
Sucoflex 104 Cable	321999/4
Sucoflex 104 Cable	321995/4

Table 6-4. AP2-001 EMC Cable and Switch System Components

Component	Serial Number
Flex Cable	P2A-0001
Micro-Coax Utilfex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Chamber Passthrough	CP4/X12
Micro-Coax Utilfex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Micro-Coax Utilfex Cable UFB142A-0-0629-5GU200 MFR 6463	232069-001
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181

Table 6-5. AP2-001 EMC Cable and Switch System Components

Component	Serial Number
MiniCircuits Cable CBL-0.5M-SMNM+	47261
Micro-Coax Utilfex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-001
Micro-Coax Utilfex Cable UFB311A-1-0629-50U50U MFR 64639	231986-002
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	19046401 001
Megaphase (CAGE 1GVT4) Flex Cable 10511-1	15044701-006
Micro-Coax Utilfex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-002
Micro-Coax Utilfex Cable UFB311A-1-0629-50U50U MFR 64639	231986-004
Micro-Coax Utilfex Cable UFB142A-0-0629-5GU200 MFR 64639	232069-001
Rohde & Schwarz SF Unit	102138
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181
Micro-Coax Utilfex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Micro-Coax Utilfex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335

Table 6-6. AP2-002 EMC Cable and Switch System Components

Component	Serial Number
Pasternack Cable RG214/U	111815
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001

Table 6-7. ETS-001 EMC Cable and Switch System Components

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 15 of 63

Component	Serial Number
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	20502201 001
Rohde & Schwarz SF Unit	102134
Minicircuits Cable CBL=0.5M-NMNM+	15440

Table 6-8. ETS-002 EMC Cable and Switch System Components

Component	Serial Number
MegaPhase Cable, Model: TM26-S1S1-30	20929201 004
Pasternack 6dB Attenuator, Model: PE7005-6	N/A

Table 6-9. WL25-1 Conducted Cable Set Components

Component	Serial Number
Mini-Circuits Cable, Model: CBL-2FT-SMSM+	77743
MCL 6dB Attenuator, Model: BW-S6W2+	1314

Table 6-10. WL25-2 Conducted Cable Set Components

Component	Serial Number
MegaPhase Cable, Model: TM40-K1K1-36	18160102 001
MCL 10dB Attenuator, Model: BW-K10 2W44+	1902

Table 6-11. WL40-1 Conducted Cable Set Components

Component	Serial Number
MegaPhase Cable, Model: TM40-K1K1-30	18165902 001
MCL 10dB Attenuator, Model: BW-K10 2W44+	2108

Table 6-12. WL40-2 Conducted Cable Set Components

Component	Serial Number
Rohde & Schwarz SF Unit	102151
ALPHA WIRE H1	6340
HUBER+SUHNER, Inc. SUCOFLEX_104_PE Cable	305916
HUBER+SUHNER, Inc. SUCOFLEX_100	803242-6

Table 6-13. UEK1 EMC Cable and Switch System Components

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 16 of 63

7 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMO200P
 FCC Classification: 15E 6GHz Low Power Indoor Client (6XD)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference	Test Lab Location
2.1046, 15.407(a)(12)	Maximum Conducted Output Power	N/A	CONDUCTED	PASS	Section 7.3	MD
15.407(a)(8), 15.407(a)(7)	Maximum Radiated Output Power	< 24dBm over the frequency band of operation		PASS	Section 7.3	MD
2.1049, 15.407(a)(11)	Occupied Bandwidth/ 26dB Bandwidth	99% of the occupied bandwidth of any channel must be contained within each of its respective U-NII sub bands The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 megahertz.		PASS	Section 7.2	MD
15.407(a)(8), 15.407(a)(7)	Maximum Power Spectral Density	< -1dBm/MHz e.i.r.p.		PASS	Section 7.4	MD
15.407(b)(7)	In-Band Emissions	EUT must meet the limits detailed in 15.407(b)(6)		PASS	Section 7.5	MD
15.407(d)(6)	Contention Based Protocol	EUT must detect AWGN signal with 90% (or better) certainty	RADIATED	PASS	Please see 6XD OFDM report	MD
15.407(b)(6)	Undesirable Emissions	< -27dBm/MHz e.i.r.p. outside of the 5.925 – 7.125GHz band		PASS	Section 7.6	MD & KR
15.205, 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		PASS	Section 7.6	MD & KR
15.407	AC Conducted Emissions 150kHz – 30MHz	<FCC 15.207 limits	LINE CONDUCTED	PASS	Please see 6XD OFDM report	MD

Table 7-1. Summary of Test Results

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 17 of 63

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "EMC Software Tool" Version 2.3.0.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 1.7.7.
- 6) 802.11ax OFDMA testing was performed for all signal tone configurations as specified by the 802.11ax standard. Worst case results are determined and reported per the guidance provided at the October 2018 TCB Workshop.
- 7) Only one RU index could be selected at a time, so no contiguous or non-contiguous RUs were considered for testing.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 18 of 63

7.2 26dB Bandwidth Measurement

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

Test Procedure Used

ANSI C63.10:2020 – Section 12.5

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = in the range of 1% to 5% of the emission bandwidth
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. All cases were investigated; a subset of the taken plots were included to represent relevant settings and measurements.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 19 of 63		

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 26dB Bandwidth [MHz]	Antenna-1 Occupied Bandwidth [MHz]
Band 5	5935	2	ax (20MHz)	19.02	17.19
	6175	45	ax (20MHz)	18.84	17.10
	6415	93	ax (20MHz)	18.71	17.15
	5965	3	ax (40MHz)	23.32	21.45
	6165	43	ax (40MHz)	23.96	21.85
	6405	91	ax (40MHz)	24.17	21.63
	5985	7	ax (80MHz)	28.74	25.26
	6145	39	ax (80MHz)	28.88	25.43
	6385	87	ax (80MHz)	29.26	26.78
	6025	15	ax (160MHz)	32.88	33.35
	6185	47	ax (160MHz)	39.71	35.09
	6345	79	ax (160MHz)	39.48	32.72
Band 6	6435	97	ax (20MHz)	18.88	17.00
	6475	105	ax (20MHz)	18.55	17.04
	6515	113	ax (20MHz)	18.62	17.12
	6445	99	ax (40MHz)	23.82	21.60
	6485	107	ax (40MHz)	23.54	21.49
	6525	115	ax (40MHz)	23.48	21.59
	6465	103	ax (80MHz)	27.76	26.03
	6505	111	ax (160MHz)	40.99	32.52
Band 7	6535	117	ax (20MHz)	18.72	17.07
	6695	149	ax (20MHz)	18.72	17.07
	6875	185	ax (20MHz)	18.97	17.10
	6565	123	ax (40MHz)	23.56	21.45
	6725	155	ax (40MHz)	23.77	21.77
	6845	179	ax (40MHz)	24.02	21.69
	6545	119	ax (80MHz)	27.99	25.68
	6705	151	ax (80MHz)	28.92	26.02
	6865	183	ax (80MHz)	28.33	25.64
	6665	143	ax (160MHz)	35.81	32.55
	6825	175	ax (160MHz)	33.46	33.42
Band 8	6895	189	ax (20MHz)	18.84	17.13
	6995	209	ax (20MHz)	18.49	16.95
	7115	233	ax (20MHz)	18.82	17.02
	6885	187	ax (40MHz)	23.91	21.56
	7005	211	ax (40MHz)	23.64	21.55
	7085	227	ax (40MHz)	23.91	21.95
	6945	199	ax (80MHz)	28.46	25.46
	7025	215	ax (80MHz)	28.67	24.89
	6985	207	ax (160MHz)	34.52	32.56

Table 7-2. 26dB Bandwidth Results – 26 Tones – LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 20 of 63

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 26dB Bandwidth [MHz]	Antenna-1 Occupied Bandwidth [MHz]
Band 5	5935	2	ax (20MHz)	21.93	19.19
	6175	45	ax (20MHz)	21.87	19.17
	6415	93	ax (20MHz)	21.42	19.17
	5965	3	ax (40MHz)	43.01	38.24
	6165	43	ax (40MHz)	42.87	38.15
	6405	91	ax (40MHz)	42.98	38.21
	5985	7	ax (80MHz)	87.12	78.00
	6145	39	ax (80MHz)	87.49	78.13
	6385	87	ax (80MHz)	86.87	78.11
	6025	15	ax (160MHz)	174.06	157.60
	6185	47	ax (160MHz)	176.05	157.57
	6345	79	ax (160MHz)	174.34	157.65
Band 6	6435	97	ax (20MHz)	21.83	19.20
	6475	105	ax (20MHz)	21.78	19.18
	6515	113	ax (20MHz)	21.63	19.19
	6445	99	ax (40MHz)	42.79	38.12
	6485	107	ax (40MHz)	42.63	38.20
	6525	115	ax (40MHz)	42.63	38.11
	6465	103	ax (80MHz)	87.46	78.05
	6505	111	ax (160MHz)	174.75	157.64
Band 7	6535	117	ax (20MHz)	21.61	19.18
	6695	149	ax (20MHz)	21.46	19.20
	6875	185	ax (20MHz)	21.53	19.20
	6565	123	ax (40MHz)	42.91	38.21
	6725	155	ax (40MHz)	42.80	38.18
	6845	179	ax (40MHz)	42.58	38.18
	6545	119	ax (80MHz)	87.80	78.08
	6705	151	ax (80MHz)	87.75	78.09
	6865	183	ax (80MHz)	86.92	78.11
	6665	143	ax (160MHz)	172.07	157.77
	6825	175	ax (160MHz)	175.66	157.80
	6895	189	ax (20MHz)	21.47	19.18
Band 8	6995	209	ax (20MHz)	21.66	19.18
	7115	233	ax (20MHz)	21.64	19.24
	6885	187	ax (40MHz)	42.63	38.09
	7005	211	ax (40MHz)	42.06	38.16
	7085	227	ax (40MHz)	42.92	38.16
	6945	199	ax (80MHz)	87.32	78.12
	7025	215	ax (80MHz)	87.22	78.03
	6985	207	ax (160MHz)	173.53	157.78


Table 7-3. 26dB Bandwidth Results – Full Tones – LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 21 of 63

7.2.1 Antenna-1 Bandwidth Measurements - (Partial Tones)




Plot 7-1. 26dB Bandwidth Plot SISO ANT1 (20MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 45) - LPI




Plot 7-2. 26dB Bandwidth Plot SISO ANT1 (40MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 43) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 22 of 63




Plot 7-3. 26dB Bandwidth Plot SISO ANT1 (80MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 39) - LPI




Plot 7-4. 26dB Bandwidth Plot SISO ANT1 (160MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 47) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 23 of 63

7.2.2 Antenna-1 Bandwidth Measurements - (Full Tones)




Plot 7-5. 26dB Bandwidth Plot SISO ANT1 (20MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 45) – LPI




Plot 7-6. 26dB Bandwidth Plot SISO ANT1 (40MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 43) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 24 of 63



Plot 7-7. 26dB Bandwidth Plot SISO ANT1 (80MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 39) - LPI



Plot 7-8. 26dB Bandwidth Plot SISO ANT1 (160MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 47) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 25 of 63

7.3 UNII Output Power Measurement

Test Overview and Limits

A transmitter antenna terminal of the EUT is connected to the input of an RF pulse power sensor. Measurement is made using a broadband average power meter while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020, and at the appropriate frequencies.

For client devices operating under the control of an indoor access point in the 5.925-7.125 GHz bands, the maximum e.i.r.p. over the frequency band of operation must not exceed 24 dBm.

Test Procedure Used

ANSI C63.10:2020 – Section 12.4.3.2 Method PM-G

Test Settings

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 26 of 63

Maximum Output Power Measurements

Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				RU Index						
				0	4	8				
5	5935	2	26T	-1.79	-1.99	-1.90	-6.44	-8.23	24.00	-32.23
	6175	45	26T	-1.80	-1.93	-1.55	-6.44	-7.99	24.00	-31.99
	6415	93	26T	-1.14	-1.77	-1.35	-6.44	-7.58	24.00	-31.58
6	6435	97	26T	-1.38	-1.82	-1.50	-6.11	-7.49	24.00	-31.49
	6475	105	26T	-1.25	-1.10	-1.28	-6.11	-7.21	24.00	-31.21
	6515	113	26T	-1.20	-1.55	-1.22	-6.11	-7.31	24.00	-31.31
7	6535	117	26T	-1.55	-1.99	-1.62	-5.59	-7.14	24.00	-31.14
	6695	149	26T	-2.00	-1.94	-1.96	-5.59	-7.53	24.00	-31.53
	6875	185	26T	-1.98	-1.89	-1.50	-5.59	-7.09	24.00	-31.09
8	6895	189	26T	-1.99	-1.85	-1.54	-7.33	-8.87	24.00	-32.87
	6995	209	26T	-1.69	-1.93	-1.46	-7.33	-8.79	24.00	-32.79
	7115	233	26T	-1.92	-1.92	-1.59	-7.33	-8.92	24.00	-32.92

Table 7-4. SISO 20MHz BW 802.11ax (UNII) Maximum Output Power – 26T

Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				RU Index						
				37	39	40				
5	5935	2	52T	1.53	1.40	1.57	-6.44	-4.87	24.00	-28.87
	6175	45	52T	1.57	1.35	1.52	-6.44	-4.87	24.00	-28.87
	6415	93	52T	1.86	1.48	1.72	-6.44	-4.58	24.00	-28.58
6	6435	97	52T	1.68	1.50	1.65	-6.11	-4.43	24.00	-28.43
	6475	105	52T	1.68	1.55	1.60	-6.11	-4.43	24.00	-28.43
	6515	113	52T	1.85	1.65	1.82	-6.11	-4.26	24.00	-28.26
7	6535	117	52T	1.83	1.57	1.75	-5.59	-3.76	24.00	-27.76
	6695	149	52T	1.10	1.33	1.50	-5.59	-4.09	24.00	-28.09
	6875	185	52T	1.45	1.25	1.50	-5.59	-4.09	24.00	-28.09
8	6895	189	52T	1.50	1.32	1.45	-7.33	-5.83	24.00	-29.83
	6995	209	52T	1.24	1.05	1.22	-7.33	-6.09	24.00	-30.09
	7115	233	52T	1.80	1.58	1.75	-7.33	-5.53	24.00	-29.53

Table 7-5. SISO 20MHz BW 802.11ax (UNII) Maximum Output Power – 52T

Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				RU Index					
				53	54				
5	5935	2	106T	4.52	4.47	-6.44	-1.92	24.00	-25.92
	6175	45	106T	4.56	4.65	-6.44	-1.79	24.00	-25.79
	6415	93	106T	4.25	4.25	-6.44	-2.19	24.00	-26.19
6	6435	97	106T	4.09	4.05	-6.11	-2.02	24.00	-26.02
	6475	105	106T	4.60	4.55	-6.11	-1.51	24.00	-25.51
	6515	113	106T	4.36	4.25	-6.11	-1.75	24.00	-25.75
7	6535	117	106T	4.28	4.25	-5.59	-1.31	24.00	-25.31
	6695	149	106T	4.39	4.33	-5.59	-1.20	24.00	-25.20
	6875	185	106T	4.30	4.28	-5.59	-1.29	24.00	-25.29
8	6895	189	106T	4.02	4.01	-7.33	-3.31	24.00	-27.31
	6995	209	106T	4.55	4.53	-7.33	-2.78	24.00	-26.78
	7115	233	106T	4.55	4.48	-7.33	-2.78	24.00	-26.78

Table 7-6. SISO 20MHz BW 802.11ax (UNII) Maximum Output Power – 106T

Band	Freq [MHz]	Channel	Tones	Avg Conducted Power	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				(dBm)				
				RU Index				
				61				
5	5935	2	242T	8.85	-6.44	2.41	24.00	-21.59
	6175	45	242T	8.82	-6.44	2.38	24.00	-21.62
	6415	93	242T	8.75	-6.44	2.31	24.00	-21.69
6	6435	97	242T	8.65	-6.11	2.54	24.00	-21.46
	6475	105	242T	8.75	-6.11	2.64	24.00	-21.36
	6515	113	242T	8.85	-6.11	2.74	24.00	-21.26
7	6535	117	242T	8.71	-5.59	3.12	24.00	-20.88
	6695	149	242T	8.10	-5.59	2.51	24.00	-21.49
	6875	185	242T	8.65	-5.59	3.06	24.00	-20.94
8	6895	189	242T	8.60	-7.33	1.27	24.00	-22.73
	6995	209	242T	8.24	-7.33	0.91	24.00	-23.09
	7115	233	242T	8.75	-7.33	1.42	24.00	-22.58

Table 7-7. SISO 20MHz BW 802.11ax (UNII) Maximum Output Power – 242T

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)		Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 27 of 63		

Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				RU Index				
				65				
5	5965	3	484T	11.65	-6.44	5.21	24.00	-18.79
	6005	11	484T	11.85	-6.44	5.41	24.00	-18.59
	6165	43	484T	11.65	-6.44	5.21	24.00	-18.79
	6405	91	484T	11.32	-6.44	4.88	24.00	-19.12
6	6445	99	484T	11.75	-6.11	5.64	24.00	-18.36
	6485	107	484T	11.82	-6.11	5.71	24.00	-18.29
	6525	115	484T	11.80	-6.11	5.69	24.00	-18.31
7	6565	123	484T	11.47	-5.59	5.88	24.00	-18.12
	6685	147	484T	11.02	-5.59	5.43	24.00	-18.57
	6845	179	484T	11.50	-5.59	5.91	24.00	-18.09
8	6885	187	484T	11.59	-7.33	4.26	24.00	-19.74
	7005	211	484T	11.53	-7.33	4.20	24.00	-19.80
	7085	227	484T	11.35	-7.33	4.02	24.00	-19.98

Table 7-8. SISO 40MHz BW 802.11ax (UNII) Maximum Output Power – 484T

Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				RU Index				
				67				
5	5985	7	996T	11.88	-6.44	5.44	24.00	-18.56
	6145	39	996T	11.60	-6.44	5.16	24.00	-18.84
	6385	87	996T	11.10	-6.44	4.66	24.00	-19.34
6	6465	103	996T	11.92	-6.11	5.81	24.00	-18.19
7	6545	119	996T	11.42	-5.59	5.83	24.00	-18.17
	6705	151	996T	11.48	-5.59	5.89	24.00	-18.11
	6865	183	996T	11.32	-5.59	5.73	24.00	-18.27
8	6945	199	996T	11.32	-7.33	3.99	24.00	-20.01
	7025	215	996T	11.25	-7.33	3.92	24.00	-20.08

Table 7-9. SISO 80MHz BW 802.11ax (UNII) Maximum Output Power – 996T

Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				RU Index				
				68				
5	6025	15	2x996T	11.82	-6.44	5.38	24.00	-18.62
	6185	47	2x996T	11.65	-6.44	5.21	24.00	-18.79
	6345	79	2x996T	11.52	-6.44	5.08	24.00	-18.92
6	6505	111	2x996T	11.96	-6.11	5.85	24.00	-18.15
7	6665	143	2x996T	11.19	-5.59	5.60	24.00	-18.40
	6825	175	2x996T	11.30	-5.59	5.71	24.00	-18.29
8	6985	207	2x996T	11.22	-7.33	3.89	24.00	-20.11

Table 7-10. SISO 160MHz BW 802.11ax (UNII) Maximum Output Power – 2*996T

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 28 of 63

Sample e.i.r.p. Calculation:

At 5935MHz in 802.11ax (20MHz BW – 26 Tones) mode, the average conducted power was measured to be -1.79 dBm with directional gain of -6.44 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$-1.79 \text{ dBm} + -6.44 \text{ dBi} = -8.23 \text{ dBm}$$

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 29 of 63

7.4 Maximum Power Spectral Density

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020, and at the appropriate frequencies. Method SA-1, as defined in ANSI C63.10:2020, was used to measure the power spectral density.

In the 5.925-7.125 GHz bands, the maximum power spectral density must not exceed -1 dBm e.i.r.p. in any 1-megahertz band.

Test Procedure Used

ANSI C63.10:2020 – Section 12.4.2.2

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 99% OBW of the signal.
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times (\text{span}/\text{RBW})$
6. Sweep time = auto
7. Detector = power averaging (RMS)
8. Trigger was set to free run for all modes
9. Trace was averaged over 100 sweeps
10. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes

All cases were investigated; a subset of the plots taken were included to represent relevant settings and measurements.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 30 of 63

SISO Power Spectral Density Measurements

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 Power Density [dBm/MHz]	Antenna-1 Gain [dBi]	DCCF	EIRP Density [dBm/MHz]	EIRP Density Limit [dBm/MHz]	Margin [dB]
Band 5	5935	2	ax (20MHz)	-5.75	-6.44	0.00	-12.19	-1	-11.19
	6175	45	ax (20MHz)	-6.88	-6.44	0.00	-13.32	-1	-12.32
	6415	93	ax (20MHz)	-5.78	-6.44	0.00	-12.22	-1	-11.22
	5965	3	ax (40MHz)	-4.75	-6.44	0.00	-11.19	-1	-10.19
	6165	43	ax (40MHz)	-5.74	-6.44	0.00	-12.18	-1	-11.18
	6405	91	ax (40MHz)	-4.54	-6.44	0.00	-10.98	-1	-9.98
	5985	7	ax (80MHz)	-4.87	-6.44	0.00	-11.31	-1	-10.31
	6145	39	ax (80MHz)	-4.77	-6.44	0.00	-11.21	-1	-10.21
	6385	87	ax (80MHz)	-4.37	-6.44	0.00	-10.81	-1	-9.81
	6025	15	ax (160MHz)	-5.36	-6.44	0.00	-11.80	-1	-10.80
Band 6	6185	47	ax (160MHz)	-6.12	-6.44	0.00	-12.56	-1	-11.56
	6345	79	ax (160MHz)	-5.06	-6.44	0.00	-11.50	-1	-10.50
	6435	97	ax (20MHz)	-5.34	-6.11	0.00	-11.45	-1	-10.45
	6475	105	ax (20MHz)	-4.82	-6.11	0.00	-10.93	-1	-9.93
	6515	113	ax (20MHz)	-5.15	-6.11	0.00	-11.26	-1	-10.26
	6445	99	ax (40MHz)	-4.38	-6.11	0.00	-10.49	-1	-9.49
	6485	107	ax (40MHz)	-4.03	-6.11	0.00	-10.14	-1	-9.14
Band 7	6525	115	ax (40MHz)	-4.11	-6.11	0.00	-10.22	-1	-9.22
	6465	103	ax (80MHz)	-4.87	-6.11	0.00	-10.98	-1	-9.98
	6505	111	ax (160MHz)	-4.13	-6.11	0.00	-10.24	-1	-9.24
	6535	117	ax (20MHz)	-5.16	-5.59	0.00	-10.75	-1	-9.75
	6695	149	ax (20MHz)	-7.41	-5.59	0.00	-13.00	-1	-12.00
	6875	185	ax (20MHz)	-6.11	-5.59	0.00	-11.70	-1	-10.70
	6565	123	ax (40MHz)	-4.51	-5.59	0.00	-10.10	-1	-9.10
	6725	155	ax (40MHz)	-5.59	-5.59	0.00	-11.18	-1	-10.18
	6845	179	ax (40MHz)	-5.57	-5.59	0.00	-11.16	-1	-10.16
	6545	119	ax (80MHz)	-4.30	-5.59	0.00	-9.89	-1	-8.89
Band 8	6705	151	ax (80MHz)	-4.99	-5.59	0.00	-10.58	-1	-9.58
	6865	183	ax (80MHz)	-5.34	-5.59	0.00	-10.93	-1	-9.93
	6665	143	ax (160MHz)	-5.02	-5.59	0.00	-10.61	-1	-9.61
	6825	175	ax (160MHz)	-5.79	-5.59	0.00	-11.38	-1	-10.38
	6895	189	ax (20MHz)	-5.86	-7.33	0.00	-13.19	-1	-12.19
	6995	209	ax (20MHz)	-6.59	-7.33	0.00	-13.92	-1	-12.92
	7115	233	ax (20MHz)	-6.67	-7.33	0.00	-14.00	-1	-13.00
	6885	187	ax (40MHz)	-5.03	-7.33	0.00	-12.36	-1	-11.36
	7005	211	ax (40MHz)	-5.05	-7.33	0.00	-12.38	-1	-11.38
	7085	227	ax (40MHz)	-5.57	-7.33	0.00	-12.90	-1	-11.90
	6945	199	ax (80MHz)	-4.96	-7.33	0.00	-12.29	-1	-11.29
	7025	215	ax (80MHz)	-4.96	-7.33	0.00	-12.29	-1	-11.29
	6985	207	ax (160MHz)	-6.06	-7.33	0.00	-13.39	-1	-12.39

Table 7-11. SISO e.i.r.p. Conducted Power Spectral Density Measurements (26 Tones) – LPI


FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 31 of 63

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 Power Density [dBm/MHz]	Antenna-1 Gain [dBi]	DCCF	EIRP Density [dBm/MHz]	EIRP Density Limit [dBm/MHz]	Margin [dB]
Band 5	5935	2	ax (20MHz)	-3.51	-6.44	0.00	-9.95	-1	-8.95
	6175	45	ax (20MHz)	-3.71	-6.44	0.00	-10.15	-1	-9.15
	6415	93	ax (20MHz)	-3.32	-6.44	0.00	-9.76	-1	-8.76
	5965	3	ax (40MHz)	-2.49	-6.44	0.00	-8.93	-1	-7.93
	6165	43	ax (40MHz)	-3.46	-6.44	0.00	-9.90	-1	-8.90
	6405	91	ax (40MHz)	-3.64	-6.44	0.00	-10.08	-1	-9.08
	5985	7	ax (80MHz)	-5.94	-6.44	0.11	-12.27	-1	-11.27
	6145	39	ax (80MHz)	-6.19	-6.44	0.11	-12.52	-1	-11.52
	6385	87	ax (80MHz)	-6.27	-6.44	0.11	-12.60	-1	-11.60
	6025	15	ax (160MHz)	-8.42	-6.44	0.11	-14.75	-1	-13.75
	6185	47	ax (160MHz)	-8.96	-6.44	0.11	-15.29	-1	-14.29
Band 6	6345	79	ax (160MHz)	-8.69	-6.44	0.11	-15.02	-1	-14.02
	6435	97	ax (20MHz)	-3.18	-6.11	0.00	-9.29	-1	-8.29
	6475	105	ax (20MHz)	-2.95	-6.11	0.00	-9.06	-1	-8.06
	6515	113	ax (20MHz)	-2.97	-6.11	0.00	-9.08	-1	-8.08
	6445	99	ax (40MHz)	-2.77	-6.11	0.00	-8.88	-1	-7.88
	6485	107	ax (40MHz)	-2.93	-6.11	0.00	-9.04	-1	-8.04
	6525	115	ax (40MHz)	-2.59	-6.11	0.00	-8.70	-1	-7.70
Band 7	6465	103	ax (80MHz)	-6.04	-6.11	0.11	-12.04	-1	-11.04
	6505	111	ax (160MHz)	-8.59	-6.11	0.11	-14.59	-1	-13.59
	6535	117	ax (20MHz)	-3.18	-5.59	0.00	-8.77	-1	-7.77
	6695	149	ax (20MHz)	-3.53	-5.59	0.00	-9.12	-1	-8.12
	6875	185	ax (20MHz)	-3.47	-5.59	0.00	-9.06	-1	-8.06
	6565	123	ax (40MHz)	-2.97	-5.59	0.00	-8.56	-1	-7.56
	6725	155	ax (40MHz)	-3.24	-5.59	0.00	-8.83	-1	-7.83
	6845	179	ax (40MHz)	-3.35	-5.59	0.00	-8.94	-1	-7.94
	6545	119	ax (80MHz)	-5.60	-5.59	0.11	-11.08	-1	-10.08
	6705	151	ax (80MHz)	-6.39	-5.59	0.11	-11.87	-1	-10.87
	6865	183	ax (80MHz)	-6.02	-5.59	0.11	-11.50	-1	-10.50
Band 8	6665	143	ax (160MHz)	-9.44	-5.59	0.11	-14.92	-1	-13.92
	6825	175	ax (160MHz)	-8.96	-5.59	0.11	-14.44	-1	-13.44
	6895	189	ax (20MHz)	0.13	-7.33	0.00	-7.20	-1	-6.20
	6995	209	ax (20MHz)	-0.28	-7.33	0.00	-7.61	-1	-6.61
	7115	233	ax (20MHz)	-0.31	-7.33	0.00	-7.64	-1	-6.64
	6885	187	ax (40MHz)	-3.24	-7.33	0.00	-10.57	-1	-9.57
	7005	211	ax (40MHz)	-3.48	-7.33	0.00	-10.81	-1	-9.81
	7085	227	ax (40MHz)	-3.06	-7.33	0.00	-10.39	-1	-9.39
	6945	199	ax (80MHz)	-6.06	-7.33	0.11	-13.28	-1	-12.28
	7025	215	ax (80MHz)	-6.21	-7.33	0.11	-13.43	-1	-12.43
	6985	207	ax (160MHz)	-9.37	-7.33	0.11	-16.59	-1	-15.59


Table 7-12. SISO e.i.r.p. Conducted Power Spectral Density Measurements (Full Tones) – LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 32 of 63		

7.4.1 Antenna-1 Power Spectral Density Measurements




Plot 7-9. Power Spectral Density Plot SISO ANT1 (20MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 45) - LPI




Plot 7-10. Power Spectral Density Plot SISO ANT1 (40MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 43) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 33 of 63




Plot 7-11. Power Spectral Density Plot SISO ANT1 (80MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 39) - LPI




Plot 7-12. Power Spectral Density Plot SISO ANT1 (160MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 47) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 34 of 63




Plot 7-13. Power Spectral Density Plot SISO ANT1 (20MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 45) - LPI




Plot 7-14. Power Spectral Density Plot SISO ANT1 (40MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 43) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 35 of 63



Plot 7-15. Power Spectral Density Plot SISO ANT1 (80MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 39) - LPI



Plot 7-16. Power Spectral Density Plot SISO ANT1 (160MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 47) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 36 of 63

Sample e.i.r.p Power Spectral Density Calculation:

At 5935 MHz in 802.11ax (20MHz BW) mode, the average SISO power density was calculated to be -5.75 dBm with directional gain of -6.44 dBi.

$$\text{e.i.r.p. Power Spectral Density(dBm)} = \text{Power Spectral Density (dBm)} + \text{Ant gain (dBi)}$$

$$-5.75 \text{ dBm} + -6.44 \text{ dBi} = -12.19 \text{ dBm}$$

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 37 of 63

7.5 In-Band Emissions

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020, and at the appropriate frequencies.

For transmitters operating within the 5.925-7.125 GHz bands: Power spectral density must be suppressed by 20 dB at 1 MHz outside of channel edge, by 28 dB at one channel bandwidth from the channel center, and by 40 dB at one- and one-half times the channel bandwidth away from channel center. At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression, and at frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression. Emissions removed from the channel center by more than one- and one-half times the channel bandwidth must be suppressed by at least 40 dB.

Test Procedure Used

KDB 987594 D02 v03

Test Settings

1. Connect output of the antenna port to a spectrum analyzer or EMI receiver, with appropriate attenuation, as to not damage the instrumentation.
2. Set the reference level of the measuring equipment in accordance with procedure 4.1.6.2 of ANSI C63.10:2020.
3. Measure the 26 dB EBW using the test procedure 12.5.2 of ANSI C63.10:2020. (This will be used to determine the channel edge.)
4. Measure the power spectral density (which will be used for emissions mask reference) using the following procedure:
 - a) Set the span to encompass the entire 26 dB EBW of the signal.
 - b) Set RBW = same RBW used for 26 dB EBW measurement.
 - c) Set VBW $\geq 3 \times$ RBW
 - d) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$.
 - e) Sweep time = auto.
 - f) Detector = RMS (i.e., power averaging)
 - g) Trace average at least 100 traces in power averaging (rms) mode.
 - h) Use the peak search function on the instrument to find the peak of the spectrum.
5. For the purposes of developing the emission mask, the channel bandwidth is defined as the 26 dB EBW.
6. Using the measuring equipment limit line function, develop the emissions mask based on the following requirements. The emissions power spectral density must be reduced below the peak power spectral density (in dB) as follows:
 - a) Suppressed by 20 dB at 1 MHz outside of the channel edge. (The channel edge is defined as the 26-dB point on either side of the carrier center frequency.)
 - b) Suppressed by 28 dB at one channel bandwidth from the channel center.
 - c) Suppressed by 40 dB at one- and one-half times the channel bandwidth from the channel center.
7. Adjust the span to encompass the entire mask as necessary.
8. Clear trace.
9. Trace average at least 100 traces in power averaging (rms) mode.
10. Adjust the reference level as necessary so that the crest of the channel touches the top of the emission mask.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 38 of 63

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes

All cases were investigated; a subset of the plots taken were included to represent relevant settings and measurements.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 39 of 63

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 In-Band Emission
Band 5	5935	2	ax (20MHz)	PASS
	6175	45	ax (20MHz)	PASS
	6415	93	ax (20MHz)	PASS
	5965	3	ax (40MHz)	PASS
	6165	43	ax (40MHz)	PASS
	6405	91	ax (40MHz)	PASS
	5985	7	ax (80MHz)	PASS
	6145	39	ax (80MHz)	PASS
	6385	87	ax (80MHz)	PASS
	6025	15	ax (160MHz)	PASS
	6185	47	ax (160MHz)	PASS
	6345	79	ax (160MHz)	PASS
Band 6	6435	97	ax (20MHz)	PASS
	6475	105	ax (20MHz)	PASS
	6515	113	ax (20MHz)	PASS
	6445	99	ax (40MHz)	PASS
	6485	107	ax (40MHz)	PASS
	6525	115	ax (40MHz)	PASS
	6465	103	ax (80MHz)	PASS
	6505	111	ax (160MHz)	PASS
Band 7	6535	117	ax (20MHz)	PASS
	6695	149	ax (20MHz)	PASS
	6875	185	ax (20MHz)	PASS
	6565	123	ax (40MHz)	PASS
	6725	155	ax (40MHz)	PASS
	6845	179	ax (40MHz)	PASS
	6545	119	ax (80MHz)	PASS
	6705	151	ax (80MHz)	PASS
	6865	183	ax (80MHz)	PASS
	6665	143	ax (160MHz)	PASS
	6825	175	ax (160MHz)	PASS
	6895	189	ax (20MHz)	PASS
Band 8	6995	209	ax (20MHz)	PASS
	7115	233	ax (20MHz)	PASS
	6885	187	ax (40MHz)	PASS
	7005	211	ax (40MHz)	PASS
	7085	227	ax (40MHz)	PASS
	6945	199	ax (80MHz)	PASS
	7025	215	ax (80MHz)	PASS
	6985	207	ax (160MHz)	PASS

Table 7-13. In Band Emissions Results Measurements (26 Tones) – LPI


FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 40 of 63

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 In-Band Emission
Band 5	5935	2	ax (20MHz)	PASS
	6175	45	ax (20MHz)	PASS
	6415	93	ax (20MHz)	PASS
	5965	3	ax (40MHz)	PASS
	6165	43	ax (40MHz)	PASS
	6405	91	ax (40MHz)	PASS
	5985	7	ax (80MHz)	PASS
	6145	39	ax (80MHz)	PASS
	6385	87	ax (80MHz)	PASS
	6025	15	ax (160MHz)	PASS
	6185	47	ax (160MHz)	PASS
	6345	79	ax (160MHz)	PASS
Band 6	6435	97	ax (20MHz)	PASS
	6475	105	ax (20MHz)	PASS
	6515	113	ax (20MHz)	PASS
	6445	99	ax (40MHz)	PASS
	6485	107	ax (40MHz)	PASS
	6525	115	ax (40MHz)	PASS
	6465	103	ax (80MHz)	PASS
	6505	111	ax (160MHz)	PASS
Band 7	6535	117	ax (20MHz)	PASS
	6695	149	ax (20MHz)	PASS
	6875	185	ax (20MHz)	PASS
	6565	123	ax (40MHz)	PASS
	6725	155	ax (40MHz)	PASS
	6845	179	ax (40MHz)	PASS
	6545	119	ax (80MHz)	PASS
	6705	151	ax (80MHz)	PASS
	6865	183	ax (80MHz)	PASS
	6665	143	ax (160MHz)	PASS
	6825	175	ax (160MHz)	PASS
	6895	189	ax (20MHz)	PASS
Band 8	6995	209	ax (20MHz)	PASS
	7115	233	ax (20MHz)	PASS
	6885	187	ax (40MHz)	PASS
	7005	211	ax (40MHz)	PASS
	7085	227	ax (40MHz)	PASS
	6945	199	ax (80MHz)	PASS
	7025	215	ax (80MHz)	PASS
	6985	207	ax (160MHz)	PASS


Table 7-14. In Band Emissions Results Measurements (Full Tones) – LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 41 of 63

7.5.1 Antenna-1 In-Band Emission Measurements




Plot 7-17. In Band Emissions Plot SISO ANT1 (20MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 45) - LPI




Plot 7-18. In Band Emissions Plot SISO ANT1 (40MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 43) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 42 of 63




Plot 7-19. In Band Emissions Plot SISO ANT1 (80MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 39) - LPI




Plot 7-20. In Band Emissions Plot SISO ANT1 (160MHz 802.11ax (26 Tones) (UNII Band 5) – Ch. 47) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 43 of 63




Plot 7-21. In Band Emissions Plot SISO ANT1 (20MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 45) - LPI




Plot 7-22. In Band Emissions Plot SISO ANT1 (40MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 43) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 44 of 63



Plot 7-23. In Band Emissions Plot SISO ANT1 (80MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 39) - LPI



Plot 7-24. In Band Emissions Plot SISO ANT1 (160MHz 802.11ax (Full Tones) (UNII Band 5) – Ch. 47) - LPI

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 45 of 63

7.6 Radiated Emission Measurements

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020, and at the appropriate frequencies. All channels, modes (e.g. 802.11ax (20/40/80/160MHz), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating within the 5.925-7.125 GHz band: Any emissions outside of the 5.925-7.125 GHz band must not exceed an e.i.r.p. of -27 dBm/MHz. Emissions found in a restricted band are subject to the limits of 15.209 as shown in the table below.

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-15. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 – Sections 12.7.7.2, 12.7.6, 12.7.5

Test Settings – Above 1GHz

Average Field Strength Measurements (Method AD – Average Detection)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 46 of 63

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize.

Test Settings – Below 1GHz

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup < 30MHz

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 47 of 63




Figure 7-6. Radiated Test Setup < 1GHz




Figure 7-7. Radiated Test Setup > 1GHz

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 48 of 63

Test Notes

1. All spurious emissions lying in restricted bands specified in §15.205 are below the limit shown in §15.209. All spurious emissions that do not lie in a restricted band are subject to an average limit of -27dBm/MHz. At 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
2. All spurious emissions that do not lie in a restricted band are subject to a peak limit not to exceed 20dB of the average limit [68.2dB μ V/m]. If a peak measurement passes the average limit, it was determined no further investigation is necessary.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery and emissions were investigated with the unit powered by an extended battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported, however emissions whose levels were not within 20dB of the respective limits were not reported.
6. The worst case emissions below 1 GHz were identified in OFDM mode and are included in the test report.
7. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
8. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
9. The “-” shown in the following RSE tables are used to denote a noise floor measurement.
10. For radiated measurements, emissions were investigated for the fully-loaded RU configuration and for all of the partially-loaded RU configurations. Among all of the available partially-loaded RU configurations, only the configuration with the worst case emissions is reported.

Sample Calculations

Determining Spurious Emissions Levels


- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]

Radiated Band Edge Measurement Offset


- The amplitude offset shown in the radiated restricted band edge plots was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 49 of 63


7.6.1 Radiated Spurious Emission Measurements (26 Tones)



Plot 7-25. Radiated Spurious Plot 1GHz – 18GHz (802.11ax – UNII Band 5 Ch. 45)




Plot 7-26. Radiated Spurious Plot 1GHz – 18GHz (802.11ax – UNII Band 6 Ch. 105)




Plot 7-27. Radiated Spurious Plot 1GHz – 18GHz (802.11ax – UNII Band 7 Ch. 149)


FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 50 of 63



Plot 7-28. Radiated Spurious Plot 1GHz – 18GHz (802.11ax – U Band 8 Ch. 209)



Plot 7-29. Radiated Spurious Plot 18GHz - 26.5GHz (802.11ax)



Plot 7-30. Radiated Spurious Plot 26.5GHz - 40GHz (802.11ax)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 51 of 63

7.6.1.1 Radiated Spurious Emission Measurements (26 Tones) – UNII Band 5

Mode	UNII Band	Channel	Test Channel Freq. [MHz]	RU Index	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11ax	5	2	5935	4	*	11870.00	Average	V	-	-	-80.19	11.53	0.00	38.34	53.98	-15.64
					*	11870.00	Peak	V	-	-	-67.52	11.53	0.00	51.01	73.98	-22.97
					*	17805.00	Average	V	-	-	-80.65	23.46	0.00	49.81	53.98	-4.17
					*	17805.00	Peak	V	-	-	-68.85	23.46	0.00	61.61	73.98	-12.37
					*	23740.00	Average	V	-	-	-62.86	3.52	-9.54	38.12	53.98	-15.86
					*	23740.00	Peak	V	-	-	-52.28	3.52	-9.54	48.70	73.98	-25.28
		45	6175	4		29675.00	Peak	V	-	-	-52.24	5.49	-9.54	50.71	68.20	-17.49
					*	12350.00	Average	V	-	-	-80.34	12.00	0.00	38.66	53.98	-15.32
					*	12350.00	Peak	V	-	-	-68.15	12.00	0.00	50.85	73.98	-23.13
					*	18525.00	Average	V	-	-	-61.69	1.22	-9.54	36.99	53.98	-16.99
					*	18525.00	Peak	V	-	-	-49.83	1.22	-9.54	48.85	73.98	-25.13
						24700.00	Peak	V	-	-	-51.22	3.70	-9.54	49.94	68.20	-18.26
		93	6415	4		30875.00	Peak	V	-	-	-52.45	6.39	-9.54	51.40	68.20	-16.80
						12830.00	Peak	V	-	-	-67.65	14.34	0.00	53.69	68.20	-14.51
					*	19245.00	Average	V	-	-	-61.34	2.06	-9.54	38.19	53.98	-15.79
					*	19245.00	Peak	V	-	-	-50.43	1.95	-9.54	48.98	73.98	-25.00
						25660.00	Peak	V	-	-	-50.81	3.65	-9.54	50.30	68.20	-17.90
						32075.00	Peak	V	-	-	-52.55	7.33	-9.54	52.24	68.20	-15.96

Table 7-16. Radiated Measurements (26 Tones)

7.6.1.2 Radiated Spurious Emission Measurements (26 Tones) – UNII Band 6

Mode	UNII Band	Channel	Test Channel Freq. [MHz]	RU Index	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11ax	6	97	6435	4		12870.00	Peak	V	-	-	-68.11	13.69	0.00	52.58	68.20	-15.62
					*	19305.00	Average	V	-	-	-61.30	1.78	-9.54	37.93	53.98	-16.04
					*	19305.00	Peak	V	-	-	-49.87	1.78	-9.54	49.37	73.98	-24.61
						25740.00	Peak	V	-	-	-50.55	3.63	-9.54	50.54	68.20	-17.66
						32175.00	Peak	V	-	-	-51.55	7.35	-9.54	53.25	68.20	-14.95
		105	6475	4		12950.00	Peak	V	-	-	-67.56	13.81	0.00	53.25	68.20	-14.95
					*	19425.00	Average	V	-	-	-61.29	1.96	-9.54	38.13	53.98	-15.85
					*	19425.00	Peak	V	-	-	-50.31	1.96	-9.54	49.12	73.98	-24.86
						25900.00	Peak	V	-	-	-51.14	3.93	-9.54	50.25	68.20	-17.95
						32375.00	Peak	V	-	-	-51.93	6.87	-9.54	52.40	68.20	-15.80
		113	6515	4		13030.00	Peak	V	-	-	-67.68	13.92	0.00	53.24	68.20	-14.96
					*	19545.00	Average	V	-	-	-61.78	2.06	-9.54	37.74	53.98	-16.24
					*	19545.00	Peak	V	-	-	-50.37	2.06	-9.54	49.15	73.98	-24.83
						26060.00	Peak	V	-	-	-50.74	3.93	-9.54	50.66	68.20	-17.54
						32575.00	Peak	V	-	-	-52.59	6.73	-9.54	51.60	68.20	-16.60

Table 7-17. Radiated Measurements (26 Tones)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 52 of 63

7.6.1.3 Radiated Spurious Emission Measurements (26 Tones) – UNII Band 7

Mode	UNII Band	Channel	Test Channel Freq. [MHz]	RU Index	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11ax	7	117	6535	4		13070.00	Peak	V	-	-	-67.25	14.45	0.00	54.20	68.20	-14.00
					*	19605.00	Average	V	-	-	-61.88	2.36	-9.54	37.93	53.98	-16.04
					*	19605.00	Peak	V	-	-	-50.73	2.36	-9.54	49.09	73.98	-24.89
						26140.00	Peak	V	-	-	-51.67	4.01	-9.54	49.81	68.20	-18.39
						32675.00	Peak	V	-	-	-51.90	6.84	-9.54	52.40	68.20	-15.80
		149	6695	4	*	13390.00	Average	V	-	-	-80.18	14.24	0.00	41.06	53.98	-12.92
					*	13390.00	Peak	V	-	-	-67.81	14.24	0.00	53.43	73.98	-20.55
					*	20085.00	Average	V	-	-	-62.05	2.60	-9.54	38.01	53.98	-15.97
					*	20085.00	Peak	V	-	-	-50.80	2.60	-9.54	49.26	73.98	-24.72
						26780.00	Peak	V	-	-	-50.94	4.13	-9.54	50.65	68.20	-17.55
		185	6875	4		33475.00	Peak	V	-	-	-51.34	7.38	-9.54	53.50	68.20	-14.70
						13750.00	Peak	V	-	-	-67.93	15.59	0.00	54.66	68.20	-13.54
					*	20625.00	Average	V	-	-	-62.27	3.15	-9.54	38.35	53.98	-15.63
					*	20625.00	Peak	V	-	-	-51.16	3.10	-9.54	49.40	73.98	-24.58
						27500.00	Peak	V	-	-	-51.45	3.96	-9.54	49.98	68.20	-18.22
						34375.00	Peak	V	-	-	-52.06	7.56	-9.54	52.96	68.20	-15.24

Table 7-18. Radiated Measurements (26 Tones)


7.6.1.4 Radiated Spurious Emission Measurements (26 Tones) – UNII Band 8

Mode	UNII Band	Channel	Test Channel Freq. [MHz]	RU Index	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11ax	8	189	6895	4		13790.00	Peak	V	-	-	-68.22	16.02	0.00	54.80	68.20	-13.40
					*	20685.00	Average	V	-	-	-62.42	3.16	-9.54	38.21	53.98	-15.77
					*	20685.00	Peak	V	-	-	-50.95	3.16	-9.54	49.67	73.98	-24.31
						27580.00	Peak	V	-	-	-51.61	4.05	-9.54	49.90	68.20	-18.30
						34475.00	Peak	V	-	-	-52.18	7.56	-9.54	52.85	68.20	-15.35
		209	6995	4		13990.00	Peak	V	-	-	-68.10	16.10	0.00	55.00	68.20	-13.20
					*	20985.00	Average	V	-	-	-63.02	3.48	-9.54	37.93	53.98	-16.05
					*	20985.00	Peak	V	-	-	-51.85	3.48	-9.54	49.09	73.98	-24.89
						27980.00	Peak	V	-	-	-51.23	4.31	-9.54	50.54	68.20	-17.66
						34975.00	Peak	V	-	-	-52.64	7.83	-9.54	52.65	68.20	-15.55
		233	7115	4		14230.00	Peak	V	-	-	-67.76	16.93	0.00	56.17	68.20	-12.03
					*	21345.00	Average	V	-	-	-62.52	3.69	-9.54	38.63	53.98	-15.35
					*	21345.00	Peak	V	-	-	-51.70	3.69	-9.54	49.46	73.98	-24.52
						28460.00	Peak	V	-	-	-51.34	4.65	-9.54	50.78	68.20	-17.42
						35575.00	Peak	V	-	-	-51.96	7.99	-9.54	53.49	68.20	-14.71


Table 7-19. Radiated Measurements (26 Tones)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 53 of 63


7.6.2 Radiated Spurious Emission Measurements (242 Tones)



Plot 7-31. Radiated Spurious Plot 1GHz – 18GHz (802.11ax – UNII Band 5 Ch. 45)




Plot 7-32. Radiated Spurious Plot 1GHz – 18GHz (802.11ax – UNII Band 6 Ch. 105)




Plot 7-33. Radiated Spurious Plot 1GHz – 18GHz (802.11ax – UNII Band 7 Ch. 149)


FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 54 of 63



Plot 7-34. Radiated Spurious Plot 1GHz – 18GHz (802.11ax – U Band 8 Ch. 209)



Plot 7-35. Radiated Spurious Plot 18GHz - 26.5GHz (802.11ax)



Plot 7-36. Radiated Spurious Plot 26.5GHz - 40GHz (802.11ax)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 55 of 63

7.6.2.1 Radiated Spurious Emission Measurements (242 Tones) – UNII Band 5

Mode	UNII Band	Channel	Test Channel Freq. [MHz]	RU Index	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11ax	5	2	5935	61	*	11870.00	Average	V	100	184	-77.25	11.53	0.00	41.28	53.98	-12.70
					*	11870.00	Peak	V	100	184	-66.50	11.53	0.00	52.03	73.98	-21.95
					*	17805.00	Average	V	-	-	-80.39	23.46	0.00	50.07	53.98	-3.91
					*	17805.00	Peak	V	-	-	-68.55	23.46	0.00	61.91	73.98	-12.07
					*	23740.00	Average	V	-	-	-62.81	3.52	-9.54	38.17	53.98	-15.81
					*	23740.00	Peak	V	-	-	-51.38	3.52	-9.54	49.60	73.98	-24.38
		45	6175	61		29675.00	Peak	V	-	-	-52.21	5.49	-9.54	50.74	68.20	-17.46
					*	12350.00	Average	V	104	178	-78.62	12.00	0.00	40.38	53.98	-13.60
					*	12350.00	Peak	V	104	178	-67.15	12.00	0.00	51.85	73.98	-22.13
					*	18525.00	Average	V	-	-	-61.53	1.22	-9.54	37.15	53.98	-16.83
					*	18525.00	Peak	V	-	-	-50.11	1.22	-9.54	48.57	73.98	-25.41
						24700.00	Peak	V	-	-	-49.94	3.70	-9.54	51.22	68.20	-16.98
		93	6415	61		30875.00	Peak	V	-	-	-52.43	6.39	-9.54	51.42	68.20	-16.78
						12830.00	Peak	V	-	-	-68.81	14.34	0.00	52.53	68.20	-15.67
					*	19245.00	Average	V	-	-	-61.28	1.95	-9.54	38.13	53.98	-15.85
					*	19245.00	Peak	V	-	-	-50.30	1.95	-9.54	49.11	73.98	-24.87
						25660.00	Peak	V	-	-	-50.45	3.70	-9.54	50.71	68.20	-17.49
						32075.00	Peak	V	-	-	-51.98	7.33	-9.54	52.81	68.20	-15.39

Table 7-20. Radiated Measurements (242 Tones)

7.6.2.2 Radiated Spurious Emission Measurements (242 Tones) – UNII Band 6

Mode	UNII Band	Channel	Test Channel Freq. [MHz]	RU Index	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11ax	6	97	6435	61		12870.00	Peak	V	-	-	-68.03	13.69	0.00	52.66	68.20	-15.54
					*	19305.00	Average	V	-	-	-61.31	1.78	-9.54	37.93	53.98	-16.05
					*	19305.00	Peak	V	-	-	-49.60	1.78	-9.54	49.64	73.98	-24.34
						25740.00	Peak	V	-	-	-50.30	3.63	-9.54	50.80	68.20	-17.40
						32175.00	Peak	V	-	-	-52.21	7.35	-9.54	52.60	68.20	-15.60
		105	6475	61		12950.00	Peak	V	-	-	-68.11	13.81	0.00	52.70	68.20	-15.50
					*	19425.00	Average	V	-	-	-61.75	1.96	-9.54	37.67	53.98	-16.31
					*	19425.00	Peak	V	-	-	-50.54	1.96	-9.54	48.89	73.98	-25.09
						25900.00	Peak	V	-	-	-51.08	3.93	-9.54	50.31	68.20	-17.89
						32375.00	Peak	V	-	-	-52.10	6.82	-9.54	52.18	68.20	-16.02
		113	6515	61		13030.00	Peak	V	-	-	-68.75	13.92	0.00	52.17	68.20	-16.03
					*	19545.00	Average	V	-	-	-61.91	2.06	-9.54	37.61	53.98	-16.37
					*	19545.00	Peak	V	-	-	-50.29	2.06	-9.54	49.23	73.98	-24.75
						26060.00	Peak	V	-	-	-50.79	3.93	-9.54	50.61	68.20	-17.59
						32575.00	Peak	V	-	-	-51.77	6.73	-9.54	52.43	68.20	-15.77

Table 7-21. Radiated Measurements (242 Tones)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 56 of 63

7.6.2.3 Radiated Spurious Emission Measurements (242 Tones) – UNII Band 7

Mode	UNII Band	Channel	Test Channel Freq. [MHz]	RU Index	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11ax	7	117	6535	61		13070.00	Peak	V	-	-	-68.32	14.45	0.00	53.13	68.20	-15.07
					*	19605.00	Average	V	-	-	-61.82	2.36	-9.54	38.00	53.98	-15.98
					*	19605.00	Peak	V	-	-	-51.05	2.36	-9.54	48.77	73.98	-25.21
						26140.00	Peak	V	-	-	-51.56	4.01	-9.54	49.91	68.20	-18.29
						32675.00	Peak	V	-	-	-52.33	6.84	-9.54	51.97	68.20	-16.23
		149	6695	61	*	13390.00	Average	V	-	-	-80.46	14.24	0.00	40.78	53.98	-13.20
					*	13390.00	Peak	V	-	-	-68.83	14.24	0.00	52.41	73.98	-21.57
					*	20085.00	Average	V	-	-	-62.20	2.60	-9.54	37.86	53.98	-16.11
					*	20085.00	Peak	V	-	-	-51.07	2.60	-9.54	48.99	73.98	-24.99
						26780.00	Peak	V	-	-	-50.72	4.13	-9.54	50.87	68.20	-17.33
		185	6875	61		33475.00	Peak	V	-	-	-51.13	7.38	-9.54	53.71	68.20	-14.49
						13750.00	Peak	V	-	-	-69.11	15.59	0.00	53.48	68.20	-14.72
					*	20625.00	Average	V	-	-	-62.37	3.08	-9.54	38.16	53.98	-15.82
					*	20625.00	Peak	V	-	-	-51.05	3.08	-9.54	49.49	73.98	-24.49
						27500.00	Peak	V	-	-	-51.56	4.02	-9.54	49.92	68.20	-18.28
						34375.00	Peak	V	-	-	-52.47	7.66	-9.54	52.65	68.20	-15.55

Table 7-22. Radiated Measurements (242 Tones)

7.6.2.4 Radiated Spurious Emission Measurements (242 Tones) – UNII Band 8


Mode	UNII Band	Channel	Test Channel Freq. [MHz]	RU Index	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11ax	8	189	6895	61		13790.00	Peak	V	-	-	-68.23	16.02	0.00	54.79	68.20	-13.41
					*	20685.00	Average	V	-	-	-62.40	3.16	-9.54	38.22	53.98	-15.76
					*	20685.00	Peak	V	-	-	-50.87	3.16	-9.54	49.75	73.98	-24.23
						27580.00	Peak	V	-	-	-51.65	4.05	-9.54	49.86	68.20	-18.34
						34475.00	Peak	V	-	-	-52.29	7.56	-9.54	52.73	68.20	-15.47
		209	6995	61		13990.00	Peak	V	-	-	-68.33	16.10	0.00	54.77	68.20	-13.43
					*	20985.00	Average	V	-	-	-62.93	3.48	-9.54	38.02	53.98	-15.96
					*	20985.00	Peak	V	-	-	-50.99	3.48	-9.54	49.95	73.98	-24.03
						27980.00	Peak	V	-	-	-51.33	4.31	-9.54	50.44	68.20	-17.76
						34975.00	Peak	V	-	-	-52.43	7.83	-9.54	52.85	68.20	-15.35
		233	7115	61		14230.00	Peak	V	-	-	-68.65	16.93	0.00	55.28	68.20	-12.92
					*	21345.00	Average	V	-	-	-62.76	3.69	-9.54	38.40	53.98	-15.58
					*	21345.00	Peak	V	-	-	-51.52	3.69	-9.54	49.63	73.98	-24.35
						28460.00	Peak	V	-	-	-51.62	4.65	-9.54	50.50	68.20	-17.70
						35575.00	Peak	V	-	-	-52.11	7.99	-9.54	53.33	68.20	-14.87

Table 7-23. Radiated Measurements (242 Tones)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 57 of 63


7.6.3 Radiated Band Edge Measurements (20MHz BW – Partial Tone – 106T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	53
Distance of Measurements:	3 Meters
Operating Frequency:	5935MHz
Channel:	2



Plot 7-37. Radiated Lower Band Edge Plot SISO (Average & Peak – UNII Band 5 – 106T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	54
Distance of Measurements:	3 Meters
Operating Frequency:	7115MHz
Channel:	233




Plot 7-38. Radiated Upper Band Edge Plot SISO (Average & Peak – UNII Band 8 – 106T)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 58 of 63


7.6.4 Radiated Band Edge Measurements (20MHz BW – Full Tone – 242T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	5935MHz
Channel:	2



Plot 7-39. Radiated Lower Band Edge Plot SISO (Average & Peak – UNII Band 5 – 242T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	61
Distance of Measurements:	3 Meters
Operating Frequency:	7115MHz
Channel:	233




Plot 7-40. Radiated Upper Band Edge Plot SISO (Average & Peak – UNII Band 8 – 242T)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 59 of 63


7.6.5 Radiated Band Edge Measurements (40MHz BW – Full Tone – 484T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	5965MHz
Channel:	3



Plot 7-41. Radiated Lower Band Edge Plot SISO (Average & Peak – UNII Band 5 – 484T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	65
Distance of Measurements:	3 Meters
Operating Frequency:	7085MHz
Channel:	227




Plot 7-42. Radiated Upper Band Edge Plot SISO (Average & Peak – UNII Band 8 – 484T)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 60 of 63


7.6.6 Radiated Band Edge Measurements (80MHz BW – Full Tone – 996T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	5985MHz
Channel:	7



Plot 7-43. Radiated Lower Band Edge Plot SISO (Average & Peak – UNII Band 5 – 996T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	67
Distance of Measurements:	3 Meters
Operating Frequency:	7025MHz
Channel:	215




Plot 7-44. Radiated Upper Band Edge Plot SISO (Average & Peak – UNII Band 8 – 996T)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 61 of 63


7.6.7 Radiated Band Edge Measurements (160MHz BW – Full Tone – 2x996T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	68
Distance of Measurements:	3 Meters
Operating Frequency:	6025MHz
Channel:	15



Plot 7-45. Radiated Lower Band Edge Plot SISO (Average & Peak – UNII Band 5 – 2x996T)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index	68
Distance of Measurements:	3 Meters
Operating Frequency:	6985MHz
Channel:	207



Plot 7-46. Radiated Upper Band Edge Plot SISO (Average & Peak – UNII Band 8 – 2x996T)

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 62 of 63

8 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Extended Reality Glasses FCC ID: A3LSMO200P** is in compliance with FCC Part Subpart E (15.407) of the FCC rules for operation as a Low Power Client Device.

- END OF TEST REPORT -

FCC ID: A3LSMO200P	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 1/29/2026 - 6/30/2026	EUT Type: Extended Reality Glasses	Approved by: Technical Manager
Test Report S/N: 1M2602260016-09-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 63 of 63