



SAR EVALUATION REPORT

**FCC 47 CFR § 2.1093
IEEE Std 1528-2013**

For

The model FCC ID: A3LSMP355 shares the same enclosure and circuit board as model FCC ID: A3LSMP355C. The WLAN/Bluetooth circuitry and layout, including antenna, are almost identical between the two units. The WLAN/Bluetooth antenna and surrounding circuitry is the same between these two units, and tune up power targets are identical for WLAN and Bluetooth operations. For these reasons, the SAR data for the WLAN, and Bluetooth operations for FCC ID: A3LSMP355 is considered representative for FCC ID: A3LSMP355C.

**FCC ID: A3LSMP355C
Model Name: SM-P355C, SM-T355C, SM-P355Y**

**Report Number: 15I20358-S1B
Issue Date: 4/30/2015**

Prepared for
**SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI
GYEONGGI-DO 443-742, SOUTH KOREA**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History


Rev.	Date	Revisions	Revised By
--	4/2/2015	Initial Issue	--
A	4/13/2015	Report revised based on Reviewer's comments: 1. Section 4.3., 8.2.: Corrected typo	Kenneth Mak
B	4/30/2015	Report revised to correct typo: 1. Section 1: Corrected typo to FCC ID	Ray Su

Table of Contents

1.	Attestation of Test Results.....	5
2.	Test Specification, Methods and Procedures.....	6
3.	Facilities and Accreditation.....	6
4.	SAR Measurement System & Test Equipment	7
4.1.	<i>SAR Measurement System</i>	<i>7</i>
4.2.	<i>SAR Scan Procedures.....</i>	<i>8</i>
4.3.	<i>Test Equipment</i>	<i>10</i>
5.	Measurement Uncertainty	11
6.	Device Under Test (DUT) Information	12
6.1.	<i>DUT Description</i>	<i>12</i>
6.2.	<i>Wireless Technologies</i>	<i>12</i>
6.3.	<i>Nominal and Maximum Output Power</i>	<i>13</i>
6.4.	<i>General LTE SAR Test and Reporting Considerations</i>	<i>14</i>
6.5.	<i>Power Reduction by Proximity Sensing.....</i>	<i>15</i>
6.5.1.	<i>Proximity Sensor Triggering Distance (KDB 616217 §6.2)</i>	<i>15</i>
6.5.2.	<i>Proximity Sensor Triggering Distance Measurement Results</i>	<i>17</i>
6.5.3.	<i>Proximity Sensor Coverage (KDB 616217 §6.3)</i>	<i>31</i>
6.5.4.	<i>Proximity Sensor Tilt Angle Assessment (KDB 616217 §6.4)</i>	<i>31</i>
6.5.1.	<i>Resulting test positions for SAR measurements</i>	<i>32</i>
7.	RF Exposure Conditions (Test Configurations)	33
7.1.	<i>Standalone SAR Test Exclusion Considerations.....</i>	<i>33</i>
7.2.	<i>Required Test Configurations.....</i>	<i>35</i>
8.	Dielectric Property Measurements & System Check.....	36
8.1.	<i>Dielectric Property Measurements.....</i>	<i>36</i>
8.2.	<i>System Check.....</i>	<i>39</i>
9.	Conducted Output Power Measurements.....	43
9.1.	<i>GSM</i>	<i>43</i>
9.2.	<i>W-CDMA</i>	<i>45</i>
9.3.	<i>LTE</i>	<i>49</i>
9.4.	<i>Wi-Fi 2.4GHz</i>	<i>52</i>
9.5.	<i>Wi-Fi 5GHz</i>	<i>53</i>
9.6.	<i>Bluetooth</i>	<i>54</i>
10.	Measured and Reported (Scaled) SAR Results.....	55

10.1.	GSM850	57
10.2.	GSM1900	57
10.3.	W-CDMA Band II	58
10.4.	W-CDMA Band V	58
10.5.	LTE Band 41 (20MHz Bandwidth).....	58
10.6.	Wi-Fi (DTS Band).....	59
10.7.	Wi-Fi (U-NII Band).....	59
10.8.	Bluetooth.....	60
11.	SAR Measurement Variability	61
12.	Simultaneous Transmission SAR Analysis	62
12.1.	Sum of the SAR for GSM850 & Wi-Fi & BT	64
12.2.	Sum of the SAR for GSM1900 & Wi-Fi & BT	64
12.3.	Sum of the SAR for WCDMA Band II & Wi-Fi & BT	65
12.4.	Sum of the SAR for WCDMA Band V & Wi-Fi & BT.....	65
12.5.	Sum of the SAR for LTE Band 41 & Wi-Fi & BT	66
Appendixes.....		67
A_15I20358v0	SAR Photos & Ant. Locations	67
B_15I20358v0	SAR System Check Plots.....	67
C_15I20358v0	SAR Highest Test Plots	67
D_15I20358v0	SAR Tissue Ingredients	67
E_15I20358v0	SAR Probe Cal. Certificates.....	67
F_15I20358v0	SAR Dipole Cal. Certificates	67

1. Attestation of Test Results

Applicant Name	SAMSUNG ELECTRONICS CO., LTD.				
FCC ID	A3LSMP355C				
Model Name	SM-P355C, SM-T355C, SM-P355Y				
Applicable Standards	FCC 47 CFR § 2.1093 Published RF exposure KDB procedures IEEE Std 1528-2013				
SAR Limits (W/Kg)					
Exposure Category	Peak spatial-average(1g of tissue)				
General population / Uncontrolled exposure	1.6				
The Highest Reported SAR (W/kg)					
RF Exposure Conditions		Equipment Class			
		Licensed	DTS	U-NII	DSS (BT)
Head		0.141	0.525	0.824	N/A
Body		1.070	0.367	0.489	0.426
Simultaneous Tx	Head	0.917	0.606	0.917	N/A
	Body	1.496	1.437	1.480	1.496
Date Tested	Wi-Fi: 2/16/2015 to 2/25/2015, WWAN: 3/24/2015 to 4/1/2015				
Test Results	Pass				
UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report. Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government (NIST Handbook 150, Annex A). This report is written to support regulatory compliance of the applicable standards stated above.					
Approved & Released By:		Prepared By:			
					
Bobby Bayani Senior Engineer UL Verification Services Inc.		Ray Su Laboratory Engineer UL Verification Services Inc.			

2. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528-2013, the following FCC Published RF exposure [KDB](#) procedures:

- o 248227 D01 802.11 Wi-Fi SAR v02
- o 447498 D01 General RF Exposure Guidance v05r02
- o 447498 D03 Supplement C Cross-Reference
- o 616217 D04 SAR for laptop and tablets v01r01
- o 690783 D01 SAR Listings on Grants v01r03
- o 865664 D01 SAR measurement 100 MHz to 6 GHz v01r03
- o 865664 D02 RF Exposure Reporting v01r01
- o 941225 D01 3G SAR Procedures v03
- o 941225 D05 SAR for LTE Devices v02r03
- o 941225 D06 Hotspot Mode v02

3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at


47173 Benicia Street	47266 Benicia Street
SAR Lab A	SAR Lab 1
SAR Lab B	SAR Lab 2
SAR Lab C	SAR Lab 3
SAR Lab D	SAR Lab 4
SAR Lab E	SAR Lab 5
SAR Lab F	
SAR Lab G	
SAR Lab H	

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0.

4. SAR Measurement System & Test Equipment

4.1. SAR Measurement System

The DASY5 system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

4.2. SAR Scan Procedures

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the area scan based <i>1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan (FCC only)

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation the extrapolated distance should not be larger than the step size in Z-direction.

4.3. Test Equipment

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Dielectric Property Measurements

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Network Analyzer	Agilent	E753ES	MY40000980	4/7/2015
Dielectric Probe kit	SPEAG	DAK-3.5	1082	9/16/2015
Dielectric Probe kit	SPEAG	DAK-3.5 Short	SM DAK 200 BA	N/A
Thermometer	Control Company	Traceable	122529163	10/8/2015

System Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Synthesized Signal Generator	HP	8665B	3744A01084	5/20/2015
Power Meter	Agilent	N1912A	MY53040016	5/5/2015
Power Sensor	Agilent	E9323A	MY53070005	5/1/2015
Power Sensor	Agilent	E9323A	MY53070009	5/28/2015
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1795093	N/A
Directional coupler	Werlatone	C8060-102	2149	N/A
DC Power Supply	AMETEK	XT 15-4	1319A02778	N/A
E-Field Probe (SAR Lab A)	SPEAG	EX3DV4	3901	1/27/2016
E-Field Probe (SAR Lab B)	SPEAG	EX3DV4	3751	11/14/2015
E-Field Probe (SAR Lab F)	SPEAG	EX3DV4	3936	7/24/2015
E-Field Probe (SAR Lab G)	SPEAG	EX3DV4	3990	4/15/2015
Data Acquisition Electronics (SAR Lab A)	SPEAG	DAE4	1357	2/20/2016
Data Acquisition Electronics (SAR Lab B)	SPEAG	DAE3	500	5/15/2015
Data Acquisition Electronics (SAR Lab F)	SPEAG	DAE4	1239	4/15/2015
Data Acquisition Electronics (SAR Lab G)	SPEAG	DAE4	1434	4/14/2015
System Validation Dipole	SPEAG	D835V2	4d117	5/16/2015
System Validation Dipole	SPEAG	D1900V2	5d140	4/23/2015
System Validation Dipole	SPEAG	D2450V2	706	5/20/2015
System Validation Dipole	SPEAG	D2600V2	1006	9/10/2015
System Validation Dipole	SPEAG	D5GHzV2	1168	12/4/2015

Other

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Power Sensor	Agilent	N1921A	MY52200012	9/26/2015
Power Meter	Agilent	N1911A	MY53060009	5/5/2015
Power Sensor	Agilent	E9323A	MY53070003	5/1/2015
Base Station Simulator	R & S	CMW500	134855-bw	7/15/2015
Base Station Simulator	R & S	CMW500	134853-ud	7/17/2015
Base Station Simulator	R & S	CMU200	838114/032	7/30/2015

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

6. Device Under Test (DUT) Information

6.1. DUT Description

Device Dimension	Overall (Length x Width): 209 mm x 139 mm Overall Diagonal: 242 mm Display Diagonal: 205 mm
Battery Back Cover	☒ The rechargeable battery is not user accessible.
Battery Options	☒ The rechargeable battery is not user accessible.
Wireless Router (Hotspot)	Wi-Fi Hotspot mode permits the device to share its cellular data connection with other Wi-Fi-enabled devices. ☒ Mobile Hotspot (Wi-Fi 2.4 GHz) ☐ Mobile Hotspot (Wi-Fi 5 GHz)
Wi-Fi Direct	Wi-Fi Direct enabled devices transfer data directly between each other ☒ Wi-Fi Direct (Wi-Fi 2.4 GHz) ☒ Wi-Fi Direct (Wi-Fi 5 GHz)

6.2. Wireless Technologies

Wireless technologies	Frequency bands	Operating mode		Duty Cycle used for SAR testing
GSM	850 1900	Voice (GMSK) GPRS (GMSK) EGPRS (8PSK)	GPRS Multi-Slot Class: ☐ Class 8 - One Up ☐ Class 10 - Two Up ☐ Class 12 - Four Up ☒ Class 33 - Four Up	GSM Voice: 12.5% (E)GPRS: 1 Slot: 12.5% 2 Slots: 25% 3 Slots: 37.5% 4 Slots: 50%
	Does this device support DTM (Dual Transfer Mode)? ☒ Yes ☐ No			
W-CDMA (UMTS)	Band II Band V	UMTS Rel. 99 (Voice & Data) HSDPA (Rel. 5) HSUPA (Rel. 6)		100%
LTE (TDD)	Band 41	QPSK 16QAM ☒ Does not support Carrier Aggregation (CA).		63.3%
	Does this device support SV-LTE (1xRTT-LTE)? ☐ Yes ☒ No			
Wi-Fi	2.4 GHz	802.11b 802.11g 802.11n (HT20)		100%
	5 GHz	802.11a 802.11n (HT20) 802.11n (HT40)		100%
	Does this device support bands 5.60 ~ 5.65 GHz? ☐ Yes ☒ No			
	Does this device support Band gap channel? ☐ Yes ☒ No			
Bluetooth	2.4 GHz	Version 4.1 LE		77.5% (DH5)

6.3. Nominal and Maximum Output Power

KDB 447498 sec.4.1.(3) at the maximum rated output power and within the tune-up tolerance range specified for the product, but not more than 2 dB lower than the maximum tune-up tolerance limit

Upper limit (dB): -1.5 ~ 0.5		Max. RF Output Power (dBm)		Reduced RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit	Target	Max. tune-up tolerance limit
GSM850	Voice	32.5	33.0	6.1	6.6
	GPRS 1 slot	32.5	33.0	6.1	6.6
	GPRS 2 slots	29.5	30.0	6.1	6.6
	GPRS 3 slots	28.5	29.0	6.1	6.6
	GPRS 4 slots	26.5	27.0	6.1	6.6
	EGPRS 1 slot	30.0	30.5	6.1	6.6
	EGPRS 2 slots	30.0	30.5	6.1	6.6
	EGPRS 3 slots	28.0	28.5	6.1	6.6
GSM1900	Voice	30.5	31.0	7.1	7.6
	GPRS 1 slot	30.5	31.0	7.1	7.6
	GPRS 2 slots	28.0	28.5	7.1	7.6
	GPRS 3 slots	25.5	26.0	7.1	7.6
	GPRS 4 slots	24.5	25.0	7.1	7.6
	EGPRS 1 slot	30.0	30.5	7.1	7.6
	EGPRS 2 slots	27.0	27.5	7.1	7.6
	EGPRS 3 slots	25.0	25.5	7.1	7.6
W-CDMA Band II	EGPRS 4 slots	24.0	24.5	7.1	7.6
	R99	23.0	23.5	9.7	10.2
	HSDPA	23.0	23.5	9.7	10.2
W-CDMA Band V	HSUPA	23.0	23.5	9.7	10.2
	R99	23.0	23.5	5.0	5.5
	HSDPA	23.0	23.5	5.0	5.5
W-CDMA Band V	HSUPA	23.0	23.5	5.0	5.5
	HSUPA	23.0	23.5	5.0	5.5
LTE Band 41	QPSK	23.5	24.0	10.5	11.0
Upper limit (dB): 0.5		Max. RF Output Power (dBm)		Reduced RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit	Target	Max. tune-up tolerance limit
WiFi 2.4 GHz	802.11b	16.0	16.5	11.0	11.5
	802.11g	13.0	13.5	11.0	11.5
	802.11n HT20	12.0	12.5	11.0	11.5
WiFi 5 GHz	802.11a	11.0	11.5	6.0	6.5
	802.11n HT20	11.0	11.5	6.0	6.5
	802.11n HT40	9.0	9.5	6.0	6.5
Bluetooth		10.0	10.5	N/A	
Bluetooth LE		0.5	1.0	N/A	

6.4. General LTE SAR Test and Reporting Considerations

Item	Description																																												
Frequency range, Channel Bandwidth, Numbers and Frequencies	Band 41	Frequency range: 2555 – 2655 MHz																																											
		Channel Bandwidth																																											
		20 MHz	15 MHz	10 MHz	5 MHz	3 MHz	1.4 MHz																																						
	Low	40340 /2565	40315/ 2562.5	40290/ 2560	40215/ 2552.5																																								
	Mid	40620/ 2593	40620/ 2593	40620/ 2593	40620/ 2593																																								
	High	41140/ 2645	41165/ 2647.5	41190/ 2650	41215/ 2652.5																																								
LTE transmitter and antenna implementation	LTE has one (1) TX/RX antennas and one (1) RX antennas Refer to Appendix A.																																												
Maximum power reduction (MPR)	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3 <table> <tr> <th rowspan="2">Modulation</th><th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th><th rowspan="2">MPR (dB)</th></tr> <tr> <th>1.4 MHz</th><th>3.0 MHz</th><th>5 MHz</th><th>10 MHz</th><th>15 MHz</th><th>20 MHz</th></tr> <tr> <td>QPSK</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 1</td></tr> <tr> <td>16 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 1</td></tr> <tr> <td>64 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 2</td></tr> </table> MPR Built-in by design A-MPR (additional MPR) was disabled during SAR testing							Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)																																						
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																							
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																						
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																						
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																						
Power reduction	Yes																																												
Spectrum plots for RB configurations	A properly configured base station simulator was used for the SAR and power measurements; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																												

6.5. Power Reduction by Proximity Sensing


6.5.1. Proximity Sensor Triggering Distance (KDB 616217 §6.2)

Edge 1 of the DUT was placed directly below the flat phantom. The DUT was moved toward the phantom in accordance with the steps outlined in KDB 616217 §6.2 to determine the trigger distance for enabling power reduction. The DUT was moved away from the phantom to determine the trigger distance for resuming full power.

The measurement was then repeated for the Rear, Edge 2, and Edge 3 surface.

The DUT featured a visual indicator on its display that showed the status of the proximity sensor (Triggered or not triggered). This was used to determine the status of the sensor during the proximity sensor assessment as monitoring the output power directly was not practical without affecting the measurement.

It was confirmed separately that the output power was altered according to the proximity sensor status indication. This was achieved by observing the proximity sensor status at the same time as monitoring the conducted power. Section 9 contains both the full and reduced conducted power measurements.



LEGEND

- Direction of DUT travel for determination of power reduction triggering point
- Direction of DUT travel for determination of full power resumption triggering point

Summary of Trigger Distances for WWAN

Tissue simulating liquid	Trigger distance - Rear		Trigger distance – Edge 2		Trigger distance – Edge 3	
	Moving toward phantom	Moving from phantom	Moving from phantom	Moving toward phantom	Moving from phantom	Moving toward phantom
850 muscle	20 mm	20 mm	8 mm	8 mm	18 mm	18 mm
1900 muscle	20 mm	20 mm	8 mm	8 mm	18 mm	18 mm
2600 muscle	20 mm	20 mm	8 mm	8 mm	18 mm	18 mm

Summary of Trigger Distances for Wi-Fi


Tissue simulating liquid	Trigger distance - Rear		Trigger distance – Edge 1	
	Moving toward phantom	Moving from phantom	Moving from phantom	Moving toward phantom
2450 muscle	13mm	13mm	11mm	11mm
5000 muscle	13mm	13mm	11mm	11mm

6.5.2. Proximity Sensor Triggering Distance Measurement Results

GSM850

Rear, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: GSM 850			Position: Rear				Trigger Distance: 20 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	16	17	18	19	20	21	22	23	24	25
GSM 850 (Voice)	6.6	6.6	6.6	6.6	6.6	33.0	33.0	33.0	33.0	33.0
GSM850 GPRS 1 Slot	6.6	6.6	6.6	6.6	6.6	33.0	33.0	33.0	33.0	33.0
GSM850 GPRS 2 Slots	6.6	6.6	6.6	6.6	6.6	30.0	30.0	30.0	30.0	30.0
GSM850 GPRS 3 Slots	6.6	6.6	6.6	6.6	6.6	29.0	29.0	29.0	29.0	29.0
GSM850 GPRS 4 Slots	6.6	6.6	6.6	6.6	6.6	27.0	27.0	27.0	27.0	27.0



GSM850

Edge 2, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: GSM 850			Position: Edge 2				Trigger Distance: 8 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	4	5	6	7	8	9	10	11	12	13
GSM 850 (Voice)	6.6	6.6	6.6	6.6	6.6	33.0	33.0	33.0	33.0	33.0
GSM850 GPRS 1 Slot	6.6	6.6	6.6	6.6	6.6	33.0	33.0	33.0	33.0	33.0
GSM850 GPRS 2 Slots	6.6	6.6	6.6	6.6	6.6	30.0	30.0	30.0	30.0	30.0
GSM850 GPRS 3 Slots	6.6	6.6	6.6	6.6	6.6	29.0	29.0	29.0	29.0	29.0
GSM850 GPRS 4 Slots	6.6	6.6	6.6	6.6	6.6	27.0	27.0	27.0	27.0	27.0



GSM850

Edge 3, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: GSM 850			Position: Edge 3				Trigger Distance: 15 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	14	15	16	17	18	19	20	21	22	23
GSM 850 (Voice)	6.6	6.6	6.6	6.6	6.6	33.0	33.0	33.0	33.0	33.0
GSM850 GPRS 1 Slot	6.6	6.6	6.6	6.6	6.6	33.0	33.0	33.0	33.0	33.0
GSM850 GPRS 2 Slots	6.6	6.6	6.6	6.6	6.6	30.0	30.0	30.0	30.0	30.0
GSM850 GPRS 3 Slots	6.6	6.6	6.6	6.6	6.6	29.0	29.0	29.0	29.0	29.0
GSM850 GPRS 4 Slots	6.6	6.6	6.6	6.6	6.6	27.0	27.0	27.0	27.0	27.0



GSM1900

Rear, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: GSM 1900			Position: Rear				Trigger Distance: 20 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	16	17	18	19	20	21	22	23	24	25
GSM1900 (Voice)	7.6	7.6	7.6	7.6	7.6	31.0	31.0	31.0	31.0	31.0
GSM1900 GPRS 1 Slot	7.6	7.6	7.6	7.6	7.6	31.0	31.0	31.0	31.0	31.0
GSM1900 GPRS 2 Slots	7.6	7.6	7.6	7.6	7.6	28.5	28.5	28.5	28.5	28.5
GSM1900 GPRS 3 Slots	7.6	7.6	7.6	7.6	7.6	26.0	26.0	26.0	26.0	26.0
GSM1900 GPRS 4 Slots	7.6	7.6	7.6	7.6	7.6	25.0	25.0	25.0	25.0	25.0



GSM1900

Edge 2, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: GSM 1900			Position: Edge 2				Trigger Distance: 8 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	4	5	6	7	8	9	10	11	12	13
GSM1900 (Voice)	7.6	7.6	7.6	7.6	7.6	31.0	31.0	31.0	31.0	31.0
GSM1900 GPRS 1 Slot	7.6	7.6	7.6	7.6	7.6	31.0	31.0	31.0	31.0	31.0
GSM1900 GPRS 2 Slots	7.6	7.6	7.6	7.6	7.6	28.5	28.5	28.5	28.5	28.5
GSM1900 GPRS 3 Slots	7.6	7.6	7.6	7.6	7.6	26.0	26.0	26.0	26.0	26.0
GSM1900 GPRS 4 Slots	7.6	7.6	7.6	7.6	7.6	25.0	25.0	25.0	25.0	25.0



GSM1900

Edge 3, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: GSM 1900			Position: Edge 3				Trigger Distance: 15 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	14	15	16	17	18	19	20	21	22	23
GSM1900 (Voice)	7.6	7.6	7.6	7.6	7.6	31.0	31.0	31.0	31.0	31.0
GSM1900 GPRS 1 Slot	7.6	7.6	7.6	7.6	7.6	31.0	31.0	31.0	31.0	31.0
GSM1900 GPRS 2 Slots	7.6	7.6	7.6	7.6	7.6	28.5	28.5	28.5	28.5	28.5
GSM1900 GPRS 3 Slots	7.6	7.6	7.6	7.6	7.6	26.0	26.0	26.0	26.0	26.0
GSM1900 GPRS 4 Slots	7.6	7.6	7.6	7.6	7.6	25.0	25.0	25.0	25.0	25.0



WCDMA Bands II and V

Rear, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: W-CDMA			Position: Rear				Trigger Distance: 20 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	16	17	18	19	20	21	22	23	24	25
W-CDMA Band II	10.2	10.2	10.2	10.2	10.2	23.5	23.5	23.5	23.5	23.5
W-CDMA Band V	5.5	5.5	5.5	5.5	5.5	23.5	23.5	23.5	23.5	23.5



WCDMA Bands II and V

Edge 2, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: W-CDMA			Position: Edge 2				Trigger Distance: 8 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	3	4	5	6	8	9	10	11	12	13
W-CDMA Band II	10.2	10.2	10.2	10.2	10.2	23.5	23.5	23.5	23.5	23.5
W-CDMA Band V	5.5	5.5	5.5	5.5	5.5	23.5	23.5	23.5	23.5	23.5



WCDMA Bands II and V

Edge 3, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: W-CDMA			Position: Edge 3				Trigger Distance: 18 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	14	15	16	17	18	19	20	21	22	23
W-CDMA Band II	10.2	10.2	10.2	10.2	10.2	23.5	23.5	23.5	23.5	23.5
W-CDMA Band V	5.5	5.5	5.5	5.5	5.5	23.5	23.5	23.5	23.5	23.5



LTE Band 41

Rear, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: LTE Band 41			Position: Rear				Trigger Distance: 20 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	16	17	18	19	20	21	22	23	24	25
LTE Band 41	11.0	11.0	11.0	11.0	11.0	24.0	24.0	24.0	24.0	24.0



LTE Band 41

Edge 2, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: LTE Band 41			Position: Edge 2				Trigger Distance: 8 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	4	5	6	7	8	9	10	11	12	13
LTE Band 41	11.0	11.0	11.0	11.0	11.0	24.0	24.0	24.0	24.0	24.0



LTE Band 41

Edge 3, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Technology: LTE Band 41			Position: Edge 3				Trigger Distance: 15 mm			
Distance to DUT vs. Output Power in dBm										
Distance (mm)	14	15	16	17	18	19	20	21	22	23
LTE Band 41	11.0	11.0	11.0	11.0	11.0	24.0	24.0	24.0	24.0	24.0



Wi-Fi 2.4GHz and 5GHz

Rear, DUT Moving Toward (Trigger) and Away (Release) from the Phantom


Distance to DUT vs. Output Power in dBm										
Distance	9	10	11	12	13	14	15	16	17	18
2.4 GHz 802.11b	11.20	11.20	11.20	11.20	11.20	16.40	16.40	16.40	16.40	16.40
5 GHz 802.11a	6.50	6.50	6.50	6.50	6.50	11.50	11.50	11.50	11.50	11.50
5 GHz 802.11n HT20	6.50	6.50	6.50	6.50	6.50	11.50	11.50	11.50	11.50	11.50
5 GHz 802.11n HT40	6.40	6.40	6.40	6.40	6.40	9.50	9.50	9.50	9.50	9.50



Wi-Fi 2.4GHz and 5GHz

Edge 1, DUT Moving Toward (Trigger) and Away (Release) from the Phantom

Distance to DUT vs. Output Power in dBm										
Distance	7	8	9	10	11	12	13	14	15	16
2.4 GHz 802.11b	11.20	11.20	11.20	11.20	11.20	16.40	16.40	16.40	16.40	16.40
5 GHz 802.11a	6.50	6.50	6.50	6.50	6.50	11.50	11.50	11.50	11.50	11.50
5 GHz 802.11n HT20	6.50	6.50	6.50	6.50	6.50	11.50	11.50	11.50	11.50	11.50
5 GHz 802.11n HT40	6.40	6.40	6.40	6.40	6.40	9.50	9.50	9.50	9.50	9.50




6.5.3. Proximity Sensor Coverage (KDB 616217 §6.3)

As there is no spatial offset between the antenna and the proximity sensor element, proximity sensor coverage did not need to be assessed.

6.5.4. Proximity Sensor Tilt Angle Assessment (KDB 616217 §6.4)

The DUT was positioned directly below the flat phantom at the minimum measured trigger distance with Edge 3 parallel to the base of the flat phantom for each band.

The EUT was rotated about Edge 3 for angles up to $\pm 45^\circ$. If the output power increased during the rotation the DUT was moved 1mm toward the phantom and the rotation repeated. This procedure was repeated until the power remained reduced for all angles up to $\pm 45^\circ$.



Proximity sensor tilt angle assessment (Edge 3) KDB 616217 §6.4

Summary of Tablet Tilt Angle Influence to Proximity Sensor Triggering for Edge 3

Band (MHz)	Minimum trigger distance measured according to KDB 616217 §6.2	Minimum distance at which power reduction was maintained over $\pm 45^\circ$	Power reduction status										
			-45°	-40°	-30°	-20°	-10°	0°	10°	20°	30°	40°	45°
850	5 mm	5 mm	On	On	On	On	On	On	On	On	On	On	On
1900	5 mm	5 mm	On	On	On	On	On	On	On	On	On	On	On
2600	5 mm	5 mm	On	On	On	On	On	On	On	On	On	On	On
2400	5 mm	5 mm	On	On	On	On	On	On	On	On	On	On	On
5000	5 mm	5 mm	On	On	On	On	On	On	On	On	On	On	On

6.5.1. Resulting test positions for SAR measurements

Wireless technologies	Position	§6.2 Triggering Distance	§6.3 Coverage	§6.4 Tilt Angle
WWAN	Rear	20 mm	N/A	N/A
	Edge 2	8 mm	N/A	8 mm
	Edge 3	17 mm	N/A	17 mm
WLAN	Rear	13 mm	N/A	N/A
	Edge 1	11 mm	N/A	11 mm
	Edge 2	0 mm	N/A	0 mm

7. RF Exposure Conditions (Test Configurations)

Refer to “SAR Photos and Ant locations” Appendix for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

7.1. Standalone SAR Test Exclusion Considerations

Since the *Dedicated Host Approach* is applied, the standalone SAR test exclusion procedure in KDB 447498 § 4.3.1 is applied in conjunction with KDB 616217 § 4.3 to determine the minimum test separation distance:

- o When the separation distance from the antenna to an adjacent edge is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
- o When the separation distance from the antenna to an adjacent edge is > 5 mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.

SAR Test Exclusion Calculations for WWAN

Antennas < 50mm to adjacent edges

Antenna	Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)						Calculated Threshold Value					
			dBm	mW	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front
Full Power																
Cellular	GPRS 3 Slots	848.8	29.00	298	19	195	7	17	93		MEASURE-14.4	> 50 mm	MEASURE-39.2	MEASURE-16.1	> 50 mm	
Cellular	GPRS 3 Slots	1909.8	26.00	149	19	195	7	17	93		MEASURE-10.8	> 50 mm	MEASURE-29.4	MEASURE-12.1	> 50 mm	
Cellular	W-CDMA 5	846.6	23.50	224	19	195	7	17	93		MEASURE-10.8	> 50 mm	MEASURE-29.4	MEASURE-12.1	> 50 mm	
Cellular	W-CDMA 2	1907.6	23.50	224	19	195	7	17	93		MEASURE-16.3	> 50 mm	MEASURE-44.2	MEASURE-18.2	> 50 mm	
Cellular	LTE Band 41	2680	24.00	251	19	195	7	17	93		MEASURE-21.6	> 50 mm	MEASURE-58.7	MEASURE-24.2	> 50 mm	
Power Back Off																
Cellular	GPRS 4 Slots	848.8	6.60	2	5	195	5	5	91		EXEMPT-0	> 50 mm	EXEMPT-0	EXEMPT-0	> 50 mm	
Cellular	GPRS 4 Slots	1909.8	7.60	3	5	195	5	5	91		EXEMPT-1	> 50 mm	EXEMPT-1	EXEMPT-1	> 50 mm	
Cellular	W-CDMA 5	846.6	5.50	4	5	195	5	5	91		EXEMPT-1	> 50 mm	EXEMPT-1	EXEMPT-1	> 50 mm	
Cellular	W-CDMA 2	1907.6	10.20	10	5	195	5	5	91		EXEMPT-3	> 50 mm	EXEMPT-3	EXEMPT-3	> 50 mm	
Cellular	LTE Band 41	2680	11.00	13	5	195	5	5	91		MEASURE-4.3	> 50 mm	MEASURE-4.3	MEASURE-4.3	> 50 mm	

Note(s):

1. According to KDB 447498, if the calculated threshold value is > 3 then SAR testing is required.

Antennas > 50mm to adjacent edges

Antenna	Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)						Calculated Threshold Value					
			dBm	mW	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front
Full Power																
Cellular	GPRS 3 Slots	848.8	29.00	298	19	195	7	17	93		< 50 mm	983.3 mW -EXEMPT.	< 50 mm	< 50 mm	406.1 mW -EXEMPT.	
Cellular	GPRS 3 Slots	1909.8	26.00	149	19	195	7	17	93		< 50 mm	1558.5 mW -EXEMPT.	< 50 mm	< 50 mm	538.5 mW -EXEMPT.	
Cellular	W-CDMA 5	846.6	23.50	224	19	195	7	17	93		< 50 mm	981.4 mW -EXEMPT.	< 50 mm	< 50 mm	405.7 mW -EXEMPT.	
Cellular	W-CDMA 2	1907.6	23.50	224	19	195	7	17	93		< 50 mm	1558.6 mW -EXEMPT.	< 50 mm	< 50 mm	538.6 mW -EXEMPT.	
Cellular	LTE Band 41	2680	24.00	251	19	195	7	17	93		< 50 mm	1541.6 mW -EXEMPT.	< 50 mm	< 50 mm	521.6 mW -EXEMPT.	
Power Back Off																
Cellular	GPRS 4 Slots	848.8	6.60	2	5	195	5	5	91		< 50 mm	983.3 mW -EXEMPT.	< 50 mm	< 50 mm	394.8 mW -EXEMPT.	
Cellular	GPRS 4 Slots	1909.8	7.60	3	5	195	5	5	91		< 50 mm	1558.5 mW -EXEMPT.	< 50 mm	< 50 mm	518.5 mW -EXEMPT.	
Cellular	W-CDMA 5	846.6	5.50	4	5	195	5	5	91		< 50 mm	981.4 mW -EXEMPT.	< 50 mm	< 50 mm	394.4 mW -EXEMPT.	
Cellular	W-CDMA 2	1907.6	10.20	10	5	195	5	5	91		< 50 mm	1558.6 mW -EXEMPT.	< 50 mm	< 50 mm	518.6 mW -EXEMPT.	
Cellular	LTE Band 41	2680	11.00	13	5	195	5	5	91		< 50 mm	1541.6 mW -EXEMPT.	< 50 mm	< 50 mm	501.6 mW -EXEMPT.	

Note(s):

1. According to KDB 447498, if the calculated Power threshold is less than the output power then SAR testing is required.

SAR Test Exclusion Calculations for WLAN**Antennas < 50mm to adjacent edges**

Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)						Calculated Threshold Value					
		dBm	mW	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front
Full Power															
Wi-Fi 2.4 GHz	2462	16.50	45	13	23	14.5	190	98		5.4 -MEASURE-	3.1 -MEASURE-	4.7 -MEASURE-	> 50 mm	> 50 mm	
Wi-Fi 5.2 GHz	5180	11.50	14	13	23	14.5	190	98		2.5 -EXEMPT-	1.4 -EXEMPT-	2.1 -EXEMPT-	> 50 mm	> 50 mm	
Wi-Fi 5.3 GHz	5260	11.50	14	13	23	14.5	190	98		2.5 -EXEMPT-	1.4 -EXEMPT-	2.1 -EXEMPT-	> 50 mm	> 50 mm	
Wi-Fi 5.5 GHz	5580	11.50	14	13	23	14.5	190	98		2.5 -EXEMPT-	1.4 -EXEMPT-	2.2 -EXEMPT-	> 50 mm	> 50 mm	
Wi-Fi 5.8 GHz	5825	11.50	14	13	23	14.5	190	98		2.6 -EXEMPT-	1.5 -EXEMPT-	2.3 -EXEMPT-	> 50 mm	> 50 mm	
Bluetooth	2480	10.50	11	0	12	14.5	190	98		3.5 -MEASURE-	1.4 -EXEMPT-	1.2 -EXEMPT-	> 50 mm	> 50 mm	
Power Back Off															
Wi-Fi 2.4 GHz	2462	11.50	14	5	12					4.4 -MEASURE-	1.8 -EXEMPT-				
Wi-Fi 5.2 GHz	5180	6.50	4	5	12					1.8 -EXEMPT-	0.8 -EXEMPT-				
Wi-Fi 5.3 GHz	5260	6.50	4	5	12					1.8 -EXEMPT-	0.8 -EXEMPT-				
Wi-Fi 5.5 GHz	5580	6.50	4	5	12					1.9 -EXEMPT-	0.8 -EXEMPT-				
Wi-Fi 5.8 GHz	5825	6.50	4	5	12					1.9 -EXEMPT-	0.8 -EXEMPT-				

Note(s):

- According to KDB 447498, if the calculated threshold value is >3 then SAR testing is required.

Antennas > 50mm to adjacent edges

Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)						Calculated Threshold Value					
		dBm	mW	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front
Full Power															
Wi-Fi 2.4 GHz	2462	16.50	45	13	23	14.5	190	98		< 50 mm	< 50 mm	< 50 mm	1495.6 mW -EXEMPT-	575.6 mW -EXEMPT-	
Wi-Fi 5.2 GHz	5180	11.50	14	13	23	14.5	190	98		< 50 mm	< 50 mm	< 50 mm	1465.9 mW -EXEMPT-	545.9 mW -EXEMPT-	
Wi-Fi 5.3 GHz	5260	11.50	14	13	23	14.5	190	98		< 50 mm	< 50 mm	< 50 mm	1465.4 mW -EXEMPT-	545.4 mW -EXEMPT-	
Wi-Fi 5.5 GHz	5580	11.50	14	13	23	14.5	190	98		< 50 mm	< 50 mm	< 50 mm	1463.5 mW -EXEMPT-	543.5 mW -EXEMPT-	
Wi-Fi 5.8 GHz	5825	11.50	14	13	23	14.5	190	98		< 50 mm	< 50 mm	< 50 mm	1462.2 mW -EXEMPT-	542.2 mW -EXEMPT-	
Bluetooth	2480	10.50	11	13	23	14.5	190	98		< 50 mm	< 50 mm	< 50 mm	1495.3 mW -EXEMPT-	575.3 mW -EXEMPT-	
Power Back Off															
Wi-Fi 2.4 GHz	2462	11.50	14	5	12					< 50 mm	< 50 mm				
Wi-Fi 5.2 GHz	5180	6.50	4	5	12					< 50 mm	< 50 mm				
Wi-Fi 5.3 GHz	5260	6.50	4	5	12					< 50 mm	< 50 mm				
Wi-Fi 5.5 GHz	5580	6.50	4	5	12					< 50 mm	< 50 mm				
Wi-Fi 5.8 GHz	5825	6.50	4	5	12					< 50 mm	< 50 mm				

Note(s):

- According to KDB 447498, if the calculated Power threshold is less than the output power then SAR testing is required.

7.2. Required Test Configurations

The table below identifies the standalone test configurations required for this device according to the findings in Section 7.1:

Test Configurations	Rear	Edge 1	Edge 2	Edge 3	Edge 4
		(Top Edge)	(Right Edge)	(Bottom Edge)	(Left Edge)
GSM850 Full Pow er	Yes	No	Yes	Yes	No
GSM850 w / Pow er Reduction	No	No	No	No	No
GSM1900 Full Pow er	Yes	No	Yes	Yes	No
GSM1900 w / Pow er Reduction	No	No	No	No	No
W-CDMA Band 2 Full Pow er	Yes	No	Yes	Yes	No
W-CDMA Band 2 w / Pow er Reduction	No	No	No	No	No
W-CDMA Band 5 Full Pow er	Yes	No	Yes	Yes	No
W-CDMA Band 5 w / Pow er Reduction	No	No	No	No	No
LTE Band 41 Full Pow er	Yes	No	Yes	Yes	No
LTE Band 41 w / Pow er Reduction	Yes	No	Yes	Yes	No
Wi-Fi 2.4 GHz Full Pow er	Yes	Yes	Yes	No	No
Wi-Fi 2.4 GHz Reduced Pow er	Yes	No	No	No	No
Wi-Fi 5 GHz Full Pow er	No	No	No	No	No
Wi-Fi 5 GHz Reduced Pow er	No	No	No	No	No
Bluetooth	Yes	No	No	No	No

Note(s):

1. Yes = Testing is required.
2. No = Testing is not required.

8. Dielectric Property Measurements & System Check

8.1. Dielectric Property Measurements

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

Dielectric Property Measurements Results:**SAR Lab A**

Date	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
3/26/2015	Head 2600	e'	39.0700	Relative Permittivity (ϵ_r):	39.07	39.01	0.15	5
		e''	13.4000	Conductivity (σ):	1.94	1.96	-1.27	5
	Head 2500	e'	39.4100	Relative Permittivity (ϵ_r):	39.41	39.14	0.70	5
		e''	13.1700	Conductivity (σ):	1.83	1.85	-1.26	5
	Head 2700	e'	38.7500	Relative Permittivity (ϵ_r):	38.75	38.88	-0.35	5
		e''	13.7400	Conductivity (σ):	2.06	2.07	-0.36	5
3/26/2015	Body 2600	e'	51.5400	Relative Permittivity (ϵ_r):	51.54	52.51	-1.85	5
		e''	15.2600	Conductivity (σ):	2.21	2.16	2.10	5
	Body 2500	e'	51.8100	Relative Permittivity (ϵ_r):	51.81	52.64	-1.57	5
		e''	14.9600	Conductivity (σ):	2.08	2.02	2.93	5
	Body 2700	e'	51.2600	Relative Permittivity (ϵ_r):	51.26	52.38	-2.15	5
		e''	15.5200	Conductivity (σ):	2.33	2.30	1.24	5

SAR Lab B

Date	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
3/24/2015	Body 835	e'	55.9800	Relative Permittivity (ϵ_r):	55.98	55.20	1.41	5
		e''	21.7200	Conductivity (σ):	1.01	0.97	3.96	5
	Body 820	e'	56.0700	Relative Permittivity (ϵ_r):	56.07	55.28	1.43	5
		e''	21.7800	Conductivity (σ):	0.99	0.97	2.54	5
	Body 850	e'	55.7600	Relative Permittivity (ϵ_r):	55.76	55.16	1.09	5
		e''	21.8200	Conductivity (σ):	1.03	0.99	4.47	5
3/25/2015	Head 835	e'	40.6900	Relative Permittivity (ϵ_r):	40.69	41.50	-1.95	5
		e''	19.4200	Conductivity (σ):	0.90	0.90	0.18	5
	Head 820	e'	40.8400	Relative Permittivity (ϵ_r):	40.84	41.60	-1.83	5
		e''	19.4100	Conductivity (σ):	0.88	0.90	-1.50	5
	Head 850	e'	40.4000	Relative Permittivity (ϵ_r):	40.40	41.50	-2.65	5
		e''	19.4200	Conductivity (σ):	0.92	0.92	0.31	5
3/26/2015	Head 1900	e'	39.4600	Relative Permittivity (ϵ_r):	39.46	40.00	-1.35	5
		e''	13.5800	Conductivity (σ):	1.43	1.40	2.48	5
	Head 1850	e'	39.6800	Relative Permittivity (ϵ_r):	39.68	40.00	-0.80	5
		e''	13.5900	Conductivity (σ):	1.40	1.40	-0.15	5
	Head 1910	e'	39.4600	Relative Permittivity (ϵ_r):	39.46	40.00	-1.35	5
		e''	13.5900	Conductivity (σ):	1.44	1.40	3.09	5
3/26/2015	Body 1900	e'	52.6800	Relative Permittivity (ϵ_r):	52.68	53.30	-1.16	5
		e''	15.0300	Conductivity (σ):	1.59	1.52	4.46	5
	Body 1850	e'	52.7500	Relative Permittivity (ϵ_r):	52.75	53.30	-1.03	5
		e''	15.0500	Conductivity (σ):	1.55	1.52	1.85	5
	Body 1910	e'	52.6300	Relative Permittivity (ϵ_r):	52.63	53.30	-1.26	5
		e''	14.9200	Conductivity (σ):	1.58	1.52	4.25	5
4/1/2015	Body 2600	e'	52.1700	Relative Permittivity (ϵ_r):	52.17	52.51	-0.65	5
		e''	15.1400	Conductivity (σ):	2.19	2.16	1.29	5
	Body 2500	e'	52.2800	Relative Permittivity (ϵ_r):	52.28	52.64	-0.68	5
		e''	14.8600	Conductivity (σ):	2.07	2.02	2.25	5
	Body 2700	e'	51.8500	Relative Permittivity (ϵ_r):	51.85	52.38	-1.02	5
		e''	15.2700	Conductivity (σ):	2.29	2.30	-0.39	5

SAR Lab F

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit ±(%)	
2/18/2015	Head 5180	e'	35.8000	Relative Permittivity (ϵ_r)	35.80	36.01	-0.59	5
		e''	15.5700	Conductivity (σ)	4.48	4.63	-3.15	5
	Head 5200	e'	35.7600	Relative Permittivity (ϵ_r)	35.76	35.99	-0.64	5
		e''	15.5900	Conductivity (σ)	4.51	4.65	-3.08	5
	Head 5600	e'	35.4500	Relative Permittivity (ϵ_r)	35.45	35.53	-0.24	5
		e''	15.7300	Conductivity (σ)	4.90	5.06	-3.21	5
	Head 5800	e'	35.3200	Relative Permittivity (ϵ_r)	35.32	35.30	0.06	5
		e''	15.5500	Conductivity (σ)	5.01	5.27	-4.84	5
	Head 5825	e'	35.2900	Relative Permittivity (ϵ_r)	35.29	35.30	-0.03	5
		e''	15.5500	Conductivity (σ)	5.04	5.27	-4.43	5
2/18/2015	Body 5180	e'	49.0500	Relative Permittivity (ϵ_r)	49.05	49.05	0.01	5
		e''	17.6200	Conductivity (σ)	5.07	5.27	-3.73	5
	Body 5200	e'	49.0700	Relative Permittivity (ϵ_r)	49.07	49.02	0.10	5
		e''	17.6200	Conductivity (σ)	5.09	5.29	-3.78	5
	Body 5600	e'	48.4600	Relative Permittivity (ϵ_r)	48.46	48.48	-0.04	5
		e''	18.0000	Conductivity (σ)	5.60	5.76	-2.71	5
	Body 5800	e'	48.3100	Relative Permittivity (ϵ_r)	48.31	48.20	0.23	5
		e''	18.1100	Conductivity (σ)	5.84	6.00	-2.66	5
	Body 5825	e'	48.2700	Relative Permittivity (ϵ_r)	48.27	48.20	0.15	5
		e''	18.2000	Conductivity (σ)	5.89	6.00	-1.75	5
2/25/2015	Body 5180	e'	47.6800	Relative Permittivity (ϵ_r)	47.68	49.05	-2.79	5
		e''	18.3400	Conductivity (σ)	5.28	5.27	0.21	5
	Body 5200	e'	47.6700	Relative Permittivity (ϵ_r)	47.67	49.02	-2.75	5
		e''	18.3600	Conductivity (σ)	5.31	5.29	0.26	5
	Body 5600	e'	47.0300	Relative Permittivity (ϵ_r)	47.03	48.48	-2.99	5
		e''	18.6800	Conductivity (σ)	5.82	5.76	0.96	5
	Body 5800	e'	46.7300	Relative Permittivity (ϵ_r)	46.73	48.20	-3.05	5
		e''	18.8400	Conductivity (σ)	6.08	6.00	1.26	5
	Body 5825	e'	46.7200	Relative Permittivity (ϵ_r)	46.72	48.20	-3.07	5
		e''	18.8600	Conductivity (σ)	6.11	6.00	1.81	5

SAR Lab G

Date	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
2/16/2015	Head 2450	e'	40.5100	Relative Permittivity (ϵ_r)	40.51	39.20	3.34	5
		e''	13.7500	Conductivity (σ)	1.87	1.80	4.06	5
	Head 2410	e'	40.6600	Relative Permittivity (ϵ_r)	40.66	39.28	3.52	5
		e''	13.6200	Conductivity (σ)	1.83	1.76	3.67	5
	Head 2475	e'	40.4100	Relative Permittivity (ϵ_r)	40.41	39.17	3.17	5
		e''	13.7700	Conductivity (σ)	1.89	1.83	3.72	5
2/16/2015	Body 2450	e'	51.6700	Relative Permittivity (ϵ_r)	51.67	52.70	-1.95	5
		e''	14.8300	Conductivity (σ)	2.02	1.95	3.60	5
	Body 2410	e'	51.8100	Relative Permittivity (ϵ_r)	51.81	52.76	-1.80	5
		e''	14.6800	Conductivity (σ)	1.97	1.91	3.13	5
	Body 2475	e'	51.5500	Relative Permittivity (ϵ_r)	51.55	52.67	-2.12	5
		e''	14.9100	Conductivity (σ)	2.05	1.99	3.36	5

8.2. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions:

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ± 0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- Distance between probe sensors and phantom surface was set to 3 mm.
For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.5 mm
- The dipole input power (forward power) was 100 mW.
- The results are normalized to 1 W input power.

Reference Target SAR Values

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D835V2	4d117	5/16/2014	835	1g	9.23	9.61
				10g	5.98	6.31
D1900V2	5d140	4/23/2014	1900	1g	40.1	40.2
				10g	21.0	21.3
D2450V2	706	5/20/2014	2450	1g	53.0	50.2
				10g	24.5	23.4
D2600V2	1006	9/10/2014	2600	1g	58.6	56.3
				10g	26.1	25.1
D5GHzV2	1168	12/4/2014	5200	1g	79.3	76.0
				10g	22.5	21.1
			5600	1g	81.7	82.0
				10g	23.2	22.7
			5800	1g	78.0	76.2
				10g	22.1	21.0

System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within 10% of the manufacturer calibrated dipole SAR target.

SAR Lab A

Date Tested	System Dipole		T.S. Liquid	Measured Results		Target (Ref. Value)	Delta $\pm 10\%$	Plot No.
	Type	Serial #		Zoom Scan to 100 mW	Normalize to 1 W			
4/1/2015	D2600V2	1006	Body	1g	5.710	57.10	56.3	1.42
				10g	2.410	24.10	25.1	-3.98

SAR Lab B

Date Tested	System Dipole		T.S. Liquid	Measured Results		Target (Ref. Value)	Delta $\pm 10\%$	Plot No.
	Type	Serial #		Zoom Scan to 100 mW	Normalize to 1 W			
3/24/2015	D835V2	4d117	Body	1g	0.975	9.75	9.61	1.46
				10g	0.639	6.39	6.31	1.27
3/25/2015	D835V2	4d117	Head	1g	0.936	9.36	9.23	1.41
				10g	0.611	6.11	5.98	2.17
3/26/2015	D1900V2	5d140	Head	1g	4.010	40.10	40.1	0.00
				10g	2.080	20.80	21.0	-0.95
3/26/2015	D1900V2	5d140	Body	1g	4.180	41.80	40.2	3.98
				10g	2.160	21.60	21.3	1.41
3/26/2015	D2600V3	1006	Head	1g	5.500	55.00	58.6	-6.14
				10g	2.420	24.20	26.1	-7.28
3/26/2015	D2600V3	1006	Body	1g	5.910	59.10	56.3	4.97
				10g	2.570	25.70	25.1	2.39

SAR Lab F

Date Tested	System Dipole		T.S. Liquid	Measured Results		Target (Ref. Value)	Delta $\pm 10\%$	Plot No.
	Type	Serial #		Zoom Scan to 100 mW	Normalize to 1 W			
2/18/2015	D5GHzV2 (5200)	1168	Body	1g	7.14	71.4	76	-6.05
				10g	2.06	20.6	21.1	-2.37
2/18/2015	D5GHzV2 (5600)	1168	Body	1g	7.90	79.0	82.0	-3.66
				10g	2.23	22.3	22.7	-1.76
2/18/2015	D5GHzV2 (5800)	1168	Body	1g	7.67	76.7	76.2	0.66
				10g	2.18	21.8	21	3.81
2/18/2015	D5GHzV2 (5200)	1168	Head	1g	7.53	75.3	79.3	-5.04
				10g	2.18	21.8	22.5	-3.11
2/18/2015	D5GHzV2 (5600)	1168	Head	1g	8.14	81.4	81.7	-0.37
				10g	2.32	23.2	23.2	0.00
2/18/2015	D5GHzV2 (5800)	1168	Head	1g	7.36	73.6	78	-5.64
				10g	2.10	21.0	22.1	-4.98
2/26/2015	D5GHzV2 (5200)	1168	Body	1g	7.54	75.4	76.0	-0.79
				10g	2.15	21.5	21.1	1.90
2/26/2015	D5GHzV2 (5600)	1168	Body	1g	8.41	84.1	82.0	2.56
				10g	2.36	23.6	22.7	3.96
2/26/2015	D5GHzV2 (5800)	1168	Body	1g	7.29	72.9	76.2	-4.33
				10g	2.05	20.5	21.0	-2.38

SAR Lab G

Date Tested	System Dipole		T.S. Liquid	Measured Results		Target (Ref. Value)	Delta ±10 %	Plot No.
	Type	Serial #		Zoom Scan to 100 mW	Normalize to 1 W			
2/16/2015	D2450V2	706	Head	1g	5.42	54.2	53	2.26
				10g	2.47	24.7	24.5	0.82
2/16/2015	D2450V2	706	Body	1g	4.85	48.5	50.2	-3.39
				10g	2.24	22.4	23.4	-4.27

9. Conducted Output Power Measurements

9.1. GSM

GSM850 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Max. Power		with Pwr Back-off	
						Burst Pwr (dBm)	Frame Pwr (dBm)	Burst Pwr (dBm)	Frame Pwr (dBm)
850	GSM (Voice)	CS1	1	128	824.2	31.4	22.4	6.0	-3.0
				190	836.6	31.1	22.1	6.1	-2.9
				251	848.8	31.1	22.1	5.9	-3.1
	GPRS (GMSK)	CS1	1	128	824.2	31.4	22.4	6.0	-3.0
				190	836.6	31.1	22.1	6.1	-2.9
				251	848.8	31.1	22.1	5.9	-3.1
			2	128	824.2	28.4	22.4	5.9	-0.1
				190	836.6	28.2	22.2	5.9	-0.1
				251	848.8	28.1	22.1	6.0	0.0
			3	128	824.2	27.3	23.0	6.1	1.8
				190	836.6	27.1	22.8	6.0	1.7
				251	848.8	27.1	22.8	6.0	1.7
			4	128	824.2	26.0	23.0	5.9	2.9
				190	836.6	26.0	23.0	6.1	3.1
				251	848.8	25.7	22.7	6.1	3.1
	EGPRS (8PSK)	MCS5	1	128	824.2	29.4	20.4	5.8	-3.2
				190	836.6	29.4	20.4	5.9	-3.1
				251	848.8	29.3	20.3	5.8	-3.2
			2	128	824.2	29.2	23.2	5.8	-0.2
				190	836.6	29.3	23.3	5.9	-0.1
				251	848.8	29.3	23.3	5.7	-0.3
			3	128	824.2	27.9	23.6	6.0	1.7
				190	836.6	28.1	23.8	6.1	1.8
				251	848.8	28.0	23.7	5.9	1.6
			4	128	824.2	27.0	24.0	6.0	3.0
				190	836.6	27.1	24.1	6.1	3.1
				251	848.8	27.0	24.0	6.1	3.1

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 3 time slots for Max power; Reduced Power modes qualify for SAR test exclusion due to their low specified output power.
- SAR is not required for EGPRS (8PSK) mode because its output power is no greater than that of GPRS Mode

GSM1900 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Max. Power		with Pwr Back-off	
						Burst Pwr (dBm)	Frame Pwr (dBm)	Burst Pwr (dBm)	Frame Pwr (dBm)
1900	GSM (Voice)	CS1	1	512	1850.2	30.5	21.5	6.9	-2.1
				661	1880.0	30.6	21.6	6.8	-2.2
				810	1909.8	30.8	21.8	6.8	-2.2
	GPRS (GMSK)	CS1	1	512	1850.2	30.5	21.5	6.9	-2.1
				661	1880.0	30.6	21.6	6.8	-2.2
				810	1909.8	30.8	21.8	6.8	-2.2
			2	512	1850.2	27.1	21.1	7.0	1.0
				661	1880.0	27.3	21.3	6.9	0.9
				810	1909.8	27.3	21.3	6.8	0.8
			3	512	1850.2	24.4	20.1	7.0	2.7
				661	1880.0	24.5	20.2	7.1	2.8
				810	1909.8	24.3	20.0	7.0	2.7
			4	512	1850.2	23.2	20.2	6.9	3.9
				661	1880.0	23.2	20.2	7.0	4.0
				810	1909.8	23.1	20.1	7.0	4.0
	EGPRS (8PSK)	MCS5	1	512	1850.2	29.7	20.7	6.7	-2.3
				661	1880.0	29.8	20.8	6.7	-2.3
				810	1909.8	29.9	20.9	6.8	-2.2
			2	512	1850.2	27.1	21.1	6.9	0.9
				661	1880.0	27.1	21.1	7.0	1.0
				810	1909.8	27.2	21.2	7.1	1.1
			3	512	1850.2	25.0	20.7	7.1	2.8
				661	1880.0	25.0	20.7	7.0	2.7
				810	1909.8	25.1	20.8	7.0	2.7
			4	512	1850.2	24.1	21.1	7.1	4.1
				661	1880.0	24.0	21.0	7.0	4.0
				810	1909.8	24.0	21.0	7.0	4.0

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 2 time slots for Max power; Reduced Power modes qualify for SAR test exclusion due to their low specified output power.
- SAR is not required for EGPRS (8PSK) mode because its output power is no greater than that of GPRS Mode

9.2. W-CDMA

Release 99 Setup Procedures used to establish the test signals

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 2
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA Setup Procedures used to establish the test signals

The following 4 Sub-tests were completed according to Release 7 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	11/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
HSDPA Specific Settings	MPR (dB)	0	0	0.5	0.5
	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

HSPA (HSDPA & HSUPA) Setup Procedures used to establish the test signals

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA				
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2 kbps RMC				
	HSDPA FRC	H-Set 1				
	HSUPA Test	HSPA				
	Power Control Algorithm	Algorithm 2				Algorithm 1
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	15/1
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	β_{ed}	1309/225	94/75	47/15	56/75	47/15
HSDPA Specific Settings	CM (dB)	1	3	2	3	1
	MPR (dB)	0	2	1	2	0
	DACK	8				0
	DNAK	8				0
	DCQI	8				0
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
HSUPA Specific Settings	CQI Repetition Factor (Table 5.2B.4)	2				
	$A_{hs} = \beta_{hs}/\beta_c$	30/15				
	E-DPDCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E-TFCIs	5	5	2	5	1
	Reference E-TFCI	11	11	11	11	67
	Reference E-TFCI PO	4	4	4	4	18
	Reference E-TFCI	67	67	92	67	67
	Reference E-TFCI PO	18	18	18	18	18
	Reference E-TFCI	71	71	71	71	71
	Reference E-TFCI PO	23	23	23	23	23
	Reference E-TFCI	75	75	75	75	75
	Reference E-TFCI PO	26	26	26	26	26
	Reference E-TFCI	81	81	81	81	81
	Reference E-TFCI PO	27	27	27	27	27
	Maximum Channelization Codes	2xSF2				SF4

W-CDMA Band II Measured Results

Band	Mode		UL Ch No.	Freq. (MHz)	Avg Pwr (dBm)	
					Max	Pwr Back-off
W-CDMA Band II	Rel 99	RMC, 12.2 kbps	9262	1852.4	23.1	10.0
			9400	1880.0	23.2	10.1
			9538	1907.6	23.0	10.1
	HSDPA	Subtest 1	9262	1852.4	22.9	9.9
			9400	1880.0	23.0	10.0
			9538	1907.6	22.9	10.0
		Subtest 2	9262	1852.4	22.9	10.0
			9400	1880.0	22.9	10.1
			9538	1907.6	22.8	10.1
		Subtest 3	9262	1852.4	22.4	9.4
			9400	1880.0	22.5	9.4
			9538	1907.6	22.4	9.4
		Subtest 4	9262	1852.4	22.4	9.5
			9400	1880.0	22.4	9.3
			9538	1907.6	22.3	9.4
	HSUPA	Subtest 1	9262	1852.4	22.7	10.0
			9400	1880.0	22.8	9.9
			9538	1907.6	22.8	9.9
		Subtest 2	9262	1852.4	20.6	8.0
			9400	1880.0	20.6	8.1
			9538	1907.6	20.7	8.1
		Subtest 3	9262	1852.4	21.8	9.1
			9400	1880.0	21.7	8.9
			9538	1907.6	21.7	9.0
		Subtest 4	9262	1852.4	20.5	8.0
			9400	1880.0	20.6	8.0
			9538	1907.6	20.6	8.1
		Subtest 5	9262	1852.4	22.9	10.0
			9400	1880.0	23.0	10.0
			9538	1907.6	22.8	10.1

W-CDMA Band V Measured Results

Band	Mode		UL Ch No.	Freq. (MHz)	Avg Pwr (dBm)	
					Max	Pwr Back-off
W-CDMA Band V	Rel 99	RMC, 12.2 kbps	4132	826.4	23.4	5.3
			4183	836.6	23.5	5.4
			4233	846.6	23.4	5.4
	HSDPA	Subtest 1	4132	826.4	23.2	5.3
			4183	836.6	23.3	5.3
			4233	846.6	23.3	5.4
		Subtest 2	4132	826.4	23.2	5.2
			4183	836.6	23.3	5.4
			4233	846.6	23.2	5.3
		Subtest 3	4132	826.4	22.9	5.0
			4183	836.6	22.7	5.1
			4233	846.6	22.8	5.0
		Subtest 4	4132	826.4	22.8	5.1
			4183	836.6	22.8	5.0
			4233	846.6	22.7	5.0
	HSUPA	Subtest 1	4132	826.4	23.2	5.2
			4183	836.6	23.2	5.2
			4233	846.6	23.3	5.1
		Subtest 2	4132	826.4	21.4	3.3
			4183	836.6	21.5	3.3
			4233	846.6	21.3	3.2
		Subtest 3	4132	826.4	22.4	4.1
			4183	836.6	22.4	4.3
			4233	846.6	22.3	4.2
		Subtest 4	4132	826.4	21.3	3.4
			4183	836.6	21.4	3.3
			4233	846.6	21.3	3.2
		Subtest 5	4132	826.4	23.2	5.2
			4183	836.6	23.3	5.3
			4233	846.6	23.3	5.1

9.3. LTE

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE Band 41 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Max. Avg Pwr (dBm)			Target MPR	Pwr Back-off Avg Pwr (dBm)		
						2565 MHz	2593 MHz	2645 MHz		2565 MHz	2593 MHz	2645 MHz
LTE Band 41	20	QPSK	1	0	0	24.0	24.0	24.0	0	11.0	11.0	11.0
			1	49	0	24.0	24.0	23.7	0	10.9	10.9	10.9
			1	99	0	23.8	23.7	23.9	0	10.8	10.9	10.8
			50	0	1	22.4	22.5	22.5	1	10.0	10.0	10.0
			50	24	1	22.3	22.5	22.4	1	9.8	9.9	9.9
			50	50	1	22.4	22.5	22.3	1	9.8	9.8	9.9
			100	0	1	22.5	22.6	22.5	1	9.9	10.0	10.0
		16QAM	1	0	1	22.9	23.0	22.9	1	9.9	10.0	10.0
			1	49	1	23.0	23.0	22.9	1	10.0	10.0	10.0
			1	99	1	23.0	22.9	22.8	1	9.9	10.0	9.9
			50	0	2	21.9	22.0	22.0	2	8.8	8.9	8.7
			50	24	2	21.8	21.7	22.0	2	8.9	9.0	8.7
			50	50	2	21.8	21.8	21.9	2	8.8	8.8	8.9
			100	0	2	21.8	21.6	21.8	2	8.7	8.9	8.8
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Max. Avg Pwr (dBm)			Target MPR	Pwr Back-off Avg Pwr (dBm)		
						2562.5 MHz	2593 MHz	2647.5 MHz		2562.5 MHz	2593 MHz	2647.5 MHz
LTE Band 41	15	QPSK	1	0	0	23.8	23.9	23.8	0	10.8	10.9	10.8
			1	37	0	23.9	24.0	23.7	0	10.7	10.7	10.8
			1	74	0	23.8	23.7	23.9	0	10.8	10.8	10.7
			36	0	1	22.3	22.5	22.4	1	9.9	10.0	10.0
			36	20	1	22.3	22.5	22.4	1	9.7	9.8	9.9
			36	39	1	22.4	22.4	22.4	1	9.7	9.8	9.9
			75	0	1	22.5	22.5	22.4	1	9.7	9.8	9.8
		16QAM	1	0	1	22.9	22.9	22.9	1	9.7	9.8	9.7
			1	37	1	22.8	22.9	22.8	1	9.7	9.8	9.9
			1	74	1	22.8	22.7	22.8	1	9.9	10.0	9.9
			36	0	2	21.9	22.0	21.8	2	8.8	9.0	8.8
			36	20	2	21.8	21.8	21.7	2	8.8	8.8	8.9
			36	39	2	21.9	21.8	21.7	2	8.9	8.9	8.9
			75	0	2	21.8	21.6	21.7	2	8.8	8.8	8.7
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Max. Avg Pwr (dBm)			Target MPR	Pwr Back-off Avg Pwr (dBm)		
						2560 MHz	2593 MHz	2650 MHz		2560 MHz	2593 MHz	2650 MHz
LTE Band 41	10	QPSK	1	0	0	23.7	23.9	23.8	0	10.8	10.9	10.8
			1	25	0	23.8	23.9	23.8	0	10.7	10.7	10.8
			1	49	0	23.9	23.8	23.9	0	10.8	10.8	10.7
			25	0	1	22.3	22.5	22.5	1	9.9	10.0	10.0
			25	12	1	22.4	22.5	22.3	1	9.7	9.8	9.9
			25	25	1	22.3	22.3	22.2	1	9.7	9.8	9.9
			50	0	1	22.4	22.4	22.4	1	9.7	9.8	9.8
		16QAM	1	0	1	22.6	22.8	22.7	1	9.7	9.8	9.7
			1	25	1	22.6	22.8	22.7	1	9.7	9.8	9.9
			1	49	1	22.6	22.6	22.7	1	9.9	10.0	9.9
			25	0	2	21.8	21.7	21.8	2	8.8	9.0	8.8
			25	12	2	21.7	21.7	21.6	2	8.8	8.8	8.9
			25	25	2	21.6	21.8	21.7	2	8.9	8.9	8.9
			50	0	2	21.6	21.6	21.7	2	8.8	8.8	8.7

LTE Band 41 Measured Results continued

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Max. Avg Pwr (dBm)			Target MPR	Pwr Back-off Avg Pwr (dBm)		
						2552.5 MHz	2593 MHz	2652.5 MHz		2552.5 MHz	2593 MHz	2652.5 MHz
LTE Band 41	5	QPSK	1	0	0	23.9	24.0	23.8	0	10.9	11.0	10.9
			1	12	0	23.8	23.9	23.9	0	10.9	10.8	10.8
			1	24	0	23.8	23.9	23.9	0	10.7	10.9	10.8
			12	0	1	22.4	22.5	22.5	1	10.0	10.0	9.9
			12	7	1	22.3	22.4	22.3	1	9.8	9.8	9.9
			12	13	1	22.4	22.4	22.2	1	9.9	9.9	9.8
			25	0	1	22.3	22.4	22.3	1	9.8	9.8	9.7
		16QAM	1	0	1	22.7	22.9	22.7	1	9.7	9.9	9.7
			1	12	1	22.7	22.9	22.8	1	9.8	9.8	9.9
			1	24	1	22.8	22.7	22.7	1	9.7	9.9	9.9
			12	0	2	21.8	21.8	21.8	2	8.7	8.9	8.8
			12	7	2	21.6	21.7	21.7	2	8.8	8.9	8.9
			12	13	2	21.5	21.7	21.6	2	8.7	8.8	8.8
			25	0	2	21.6	21.6	21.7	2	8.7	8.8	8.7

9.4. Wi-Fi 2.4GHz

Max Power

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	Max Output Power (dBm)	SAR Test (Yes/No)	Note(s)
2.4	802.11b	1 Mbps	1	2412	16.4	16.5	Yes	
			6	2437	16.1			
			11	2462	16.2			
	802.11g	6 Mbps	1	2412	Not Required	13.5	No	1
			6	2437				
			11	2462				
	802.11n (HT20)	6.5 Mbps	1	2412		12.5	No	1
			6	2437				
			11	2462				

With Power Back-Off

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	Max Output Power (dBm)	SAR Test (Yes/No)	Note(s)
2.4	802.11b	1 Mbps	1	2412	11.2	11.5	Yes	
			6	2437	11.0			
			11	2462	11.0			
	802.11g	6 Mbps	1	2412	Not Required	11.5	No	1
			6	2437				
			11	2462				
	802.11n (HT20)	6.5 Mbps	1	2412		11.5	No	1
			6	2437				
			11	2462				

Note(s):

- Output Power and SAR is not required for 802.11g/n HT20 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

9.5. Wi-Fi 5GHz

Max Power

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	Max Output Power (dBm)	SAR Test (Yes/No)	Note(s)
5.2 (U-NII 1)	802.11a	6 Mbps	36	5180	11.2	11.5	No	3
			40	5200	11.3			
			44	5220	11.4			
			48	5240	10.9			
	802.11n (HT20)	6.5 Mbps	36	5180	11.2	11.5	No	3
			40	5200	11.3			
			44	5220	11.3			
			48	5240	10.9			
	802.11n (HT40)	13.5 Mbps	38-46	5190 - 5230	Not Required	9.5	No	1
5.3 (U-NII 2A)	802.11a	6 Mbps	52	5260	11.1	11.5	Yes	
			56	5280	11.5			
			60	5300	10.8			
			64	5320	10.7			
	802.11n (HT20)	6.5 Mbps	52	5260	11.2	11.5	No	2
			56	5280	11.4			
			60	5300	10.8			
			64	5320	10.9			
	802.11n (HT40)	13.5 Mbps	54-62	5270 - 5310	Not Required	9.5	No	1
5.5 (U-NII 2C)	802.11a	6 Mbps	100	5500	11.3	11.5	Yes	
			116	5580	11.3			
			140	5700	10.7			
	802.11n (HT20)	6.5 Mbps	100	5500	11.0	11.5	No	2
			116	5580	11.0			
	802.11n (HT40)	13.5 Mbps	102-134	5510-5670	Not Required	9.5	No	1
5.8 (U-NII 3)	802.11a	6 Mbps	149	5745	11.1	11.5	Yes	
			157	5785	11.2			
			165	5825	11.5			
	802.11n (HT20)	6.5 Mbps	149	5745	11.5	11.5	No	2
			157	5785	11.1			
			165	5825	11.2			
	802.11n (HT40)	13.5 Mbps	151-159	5755-5795	Not Required	9.5	No	1

Note(s):

- Output Power and SAR is not required for 802.11n HT20/HT40 channels when the specified tune-up tolerances for 802.11n HT20/HT40 are lower than 802.11a by more than ½ dB and the measured SAR is ≤ 1.2 W/Kg.
- When the same transmission mode configurations have the same maximum output power on the same channel for the 802.11 a/g/n/ac modes, the channel in the lower order/sequence 802.11 mode (i.e. a, g, n then ac) is selected.
- When the specified maximum output power is the same for both UNII band I and UNII band 2A, begin SAR measurement in UNII band 2A; and if the highest reported SAR for UNII band 2A is
 - ≤ 1.2 W/kg, SAR is not required for UNII band I
 - > 1.2 W/kg, both bands should be tested independently for SAR.

With Power Back-Off

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	Max Output Power (dBm)	SAR Test (Yes/No)	Note(s)
5.2 (U-NII 1)	802.11a	6 Mbps	36-48	5180-5240	Not Required	6.5	No	2
	802.11n (HT20)	6.5 Mbps	36-48	5180 - 5240		6.5	No	2
	802.11n (HT40)	13.5 Mbps	38	5190		6.5	No	2
			46	5230				
5.3 (U-NII 2A)	802.11a	6 Mbps	52-64	5260-5320	Not Required	6.5	No	1
	802.11n (HT20)	6.5 Mbps	52-64	5260 - 5320		6.5	No	1
	802.11n (HT40)	13.5 Mbps	54	5270	6.4	6.5	Yes	
			62	5310	6.3			
5.5 (U-NII 2C)	802.11a	6 Mbps	100-140	5500-5700	Not Required	6.5	No	1
	802.11n (HT20)	6.5 Mbps	100-140	5500-5700		6.5	No	1
	802.11n (HT40)	13.5 Mbps	102	5510	6.4	6.5	Yes	
			110	5550	6.4			
5.8 (U-NII 3)	802.11a	6 Mbps	149-165	5745-5825	Not Required	6.5	No	1
	802.11n (HT20)	6.5 Mbps	149-165	5745-5825		6.5	No	1
	802.11n (HT40)	13.5 Mbps	151	5755	6.4	6.5	Yes	
			159	5795	6.3			

Note(s):

- Output Power and SAR is not required for 802.11a and 802.11n HT20 channels because the specified tune-up tolerances for 802.11a and 802.11n HT20 are lower than or equal to 802.11n HT40 and the measured SAR is ≤ 1.2 W/Kg.
- When the specified maximum output power is the same for both UNII band I and UNII band 2A, begin SAR measurement in UNII band 2A; and if the highest reported SAR for UNII band 2A is
 - ≤ 1.2 W/kg, SAR is not required for UNII band I
 - > 1.2 W/kg, both bands should be tested independently for SAR.

9.6. Bluetooth

Band (GHz)	Mode	Ch #	Freq. (MHz)	Avg Pwr (dBm)
2.4	V3.0 + EDR, GFSK	0	2402	9.5
		39	2441	9.5
		78	2480	9.8
	V3.0 + EDR, $\pi/4$ DQPSK	0	2402	6.0
		39	2441	6.3
		78	2480	6.8
	V3.0 + EDR, 8-DPSK	0	2402	6.2
		39	2441	6.3
		78	2480	6.9
	V4.0 LE, GFSK	0	2402	0.9
		19	2440	0.9
		39	2480	0.8

10. Measured and Reported (Scaled) SAR Results

SAR Test Reduction criteria are as follows:

KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 941225 D01 SAR test for 3G devices:

When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode

KDB 941225 D05 SAR for LTE Devices:

SAR test reduction is applied using the following criteria:

- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB, and 50% RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel.
- When the reported SAR is > 0.8 W/kg, testing for other Channels is performed at the highest output power level for 1RB, and 50% RB configuration for that channel.
- Testing for 100% RB configuration is performed at the highest output power level for 100% RB configuration across the Low, Mid and High Channel when the highest reported SAR for 1 RB and 50% RB are > 0.8 W/kg. Testing for the remaining required channels is not needed because the reported SAR for 100% RB Allocation < 1.45 W/kg.
- Testing for 16-QAM modulation is not required because the reported SAR for QPSK is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of QPSK.
- Testing for the other channel bandwidths is not required because the reported SAR for the highest channel bandwidth is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of the highest channel bandwidth.

KDB 248227 D01 SAR meas for 802.11 v02:

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the initial test position(s) by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The initial test position(s) is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the reported SAR for the initial test position is:

- ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- > 0.4 W/kg, SAR is repeated using the same wireless mode test configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions are tested.
 - o For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
 - o When it is unclear, all equivalent conditions must be tested.

- For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required test channels are considered.
 - o The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.
- When the specified maximum output power is the same for both UNII 1 and UNII 2A, begin SAR measurements in UNII 2A with the channel with the highest measured output power. If the reported SAR for UNII 2A is ≤ 1.2 W/kg, SAR is not required for UNII 1; otherwise treat the remaining bands separately and test them independently for SAR.
- When the specified maximum output power is different between UNII 1 and UNII 2A, begin SAR with the band that has the higher specified maximum output. If the highest reported SAR for the band with the highest specified power is ≤ 1.2 W/kg, testing for the band with the lower specified output power is not required; otherwise test the remaining bands independently for SAR.

To determine the initial test position, Area Scans were performed to determine the position with the *Maximum Value of SAR (measured)*. The position that produced the highest *Maximum Value of SAR* is considered the worst case position; thus used as the initial test position.

10.1. GSM850

RF Exposure Conditions	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	Voice	Off	0	Left Touch	190	836.6	33.0	31.1	0.049	0.076	0.039	0.060	
				Left Tilt	190	836.6	33.0	31.1	0.085	0.132	0.060	0.093	
				Right Touch	190	836.6	33.0	31.1	0.042	0.065	0.034	0.053	
				Right Tilt	190	836.6	33.0	31.1	0.081	0.125	0.060	0.093	
Head VoIP	GPRS 3 Slots	Off	0	Left Touch	190	836.6	29.0	27.1	0.052	0.081	0.041	0.064	
				Left Tilt	190	836.6	29.0	27.1	0.091	0.141	0.065	0.101	1
				Right Touch	190	836.6	29.0	27.1	0.049	0.076	0.039	0.060	
				Right Tilt	190	836.6	29.0	27.1	0.086	0.133	0.063	0.098	
Body	Voice	Off	19	Rear	190	836.6	33.0	31.1	0.178	0.276	0.121	0.187	
	GPRS 3 Slots		19	Rear	190	836.6	29.0	27.1	0.077	0.119	0.050	0.077	
			7	Edge 2	190	836.6	29.0	27.1	0.234	0.362	0.145	0.225	2
			17	Edge 3	190	836.6	29.0	27.1	0.064	0.099	0.044	0.068	

10.2. GSM1900

RF Exposure Conditions	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	Voice	Off	0	Left Touch	661	1880.0	31.0	30.6	0.022	0.024	0.015	0.017	
				Left Tilt	661	1880.0	31.0	30.6	0.023	0.025	0.014	0.015	
				Right Touch	661	1880.0	31.0	30.6	0.046	0.051	0.031	0.033	3
				Right Tilt	661	1880.0	31.0	30.6	0.023	0.025	0.014	0.016	
Head VoIP	GPRS 2 Slots	Off	0	Left Touch	661	1880.0	28.5	27.3	0.018	0.023	0.012	0.016	
				Left Tilt	661	1880.0	28.5	27.3	0.020	0.027	0.013	0.017	
				Right Touch	661	1880.0	28.5	27.3	0.039	0.051	0.025	0.033	
				Right Tilt	661	1880.0	28.5	27.3	0.019	0.025	0.010	0.013	
Body	Voice	Off	19	Rear	661	1880.0	31.0	30.6	0.468	0.513	0.256	0.281	4
	GPRS 2 Slots		19	Rear	661	1880.0	28.5	27.3	0.089	0.117	0.049	0.065	
			7	Edge 2	661	1880.0	28.5	27.3	0.037	0.048	0.020	0.027	
			17	Edge 3	661	1880.0	28.5	27.3	0.110	0.145	0.060	0.078	

10.3.W-CDMA Band II

RF Exposure Conditions	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	Rel.99 RMC	Off	0	Left Touch	9400	1880.0	23.5	23.2	0.048	0.052	0.032	0.034	5
				Left Tilt	9400	1880.0	23.5	23.2	0.046	0.049	0.029	0.031	
				Right Touch	9400	1880.0	23.5	23.2	0.075	0.080	0.049	0.053	
				Right Tilt	9400	1880.0	23.5	23.2	0.037	0.040	0.023	0.025	
Body	Rel.99 RMC	Off	19	Rear	9400	1880.0	23.5	23.2	0.072	0.077	0.039	0.042	
			7	Edge 2	9400	1880.0	23.5	23.2	0.039	0.041	0.021	0.023	
			17	Edge 3	9400	1880.0	23.5	23.2	0.144	0.154	0.076	0.082	6

10.4.W-CDMA Band V

RF Exposure Conditions	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	Rel.99 RMC	Off	0	Left Touch	4183	836.6	23.5	23.5	0.016	0.016	0.012	0.012	7
				Left Tilt	4183	836.6	23.5	23.5	0.028	0.028	0.019	0.019	
				Right Touch	4183	836.6	23.5	23.5	0.014	0.014	0.011	0.011	
				Right Tilt	4183	836.6	23.5	23.5	0.024	0.024	0.018	0.018	
Body	Rel.99 RMC	Off	19	Rear	4183	836.6	23.5	23.5	0.083	0.083	0.058	0.058	8
			7	Edge 2	4183	836.6	23.5	23.5	0.073	0.073	0.045	0.045	
			17	Edge 3	4183	836.6	23.5	23.5	0.051	0.051	0.036	0.036	

10.5.LTE Band 41 (20MHz Bandwidth)

RF Exposure Conditions	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	RB Allocation	RB offset	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
									Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	QPSK	Off	0	Left Touch	40620	2593.0	1	0	24.0	24.0	0.012	0.012	0.004	0.004	9
							50	0	23.0	23.0	0.003	0.003	0.000	0.000	
				Left Tilt	40620	2593.0	1	0	24.0	24.0	0.003	0.003	0.001	0.001	
							50	0	23.0	23.0	0.004	0.004	0.001	0.001	
				Right Touch	40620	2593.0	1	0	24.0	24.0	0.020	0.020	0.009	0.009	
							50	0	23.0	23.0	0.013	0.013	0.005	0.005	
				Right Tilt	40620	2593.0	1	0	24.0	24.0	0.004	0.004	0.001	0.001	
							50	0	23.0	23.0	0.006	0.006	0.002	0.002	
Body	QPSK	Off	0	19	Rear	2593.0	1	0	24.0	24.0	0.035	0.035	0.016	0.016	
							50	0	23.0	23.0	0.034	0.034	0.015	0.015	
				7	Edge 2	2593.0	1	0	24.0	24.0	0.207	0.207	0.106	0.106	
							50	0	23.0	23.0	0.162	0.162	0.081	0.081	
				17	Edge 3	2593.0	1	0	24.0	24.0	0.510	0.510	0.262	0.262	
							50	0	23.0	23.0	0.400	0.400	0.203	0.203	
		On	0	Rear	40340	2565.0	1	0	11.0	11.0	1.070	1.070	0.325	0.325	10
							50	0	10.0	10.0	0.925	0.925	0.301	0.301	
					40620	2593.0	1	0	11.0	11.0	0.964	0.964	0.343	0.343	
							50	0	10.0	10.0	0.975	0.975	0.306	0.306	
				Edge 2	41140	2645.0	1	0	11.0	11.0	0.918	0.918	0.296	0.296	
							50	0	10.0	10.0	0.880	0.880	0.281	0.281	
					20620	2593.0	1	0	11.0	11.0	0.057	0.057	0.026	0.026	
							50	0	10.0	10.0	0.054	0.054	0.025	0.025	
				Edge 3	40340	2565.0	1	0	11.0	11.0	0.901	0.901	0.304	0.304	
							50	0	10.0	10.0	0.859	0.859	0.288	0.288	
					40620	2593.0	1	0	11.0	11.0	0.916	0.916	0.305	0.305	
							50	0	10.0	10.0	0.886	0.886	0.293	0.293	
					41140	2645.0	1	0	11.0	11.0	0.750	0.750	0.249	0.249	
							50	0	10.0	10.0	0.739	0.739	0.243	0.243	

10.6.Wi-Fi (DTS Band)

RF Exposure Conditions	Frequency Band	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Area Scan Max. SAR (W/kg)	Power (dBm)		1-g SAR (W/kg)		Notes	Plot No.
									Tune-up limit	Meas.	Meas.	Scaled		
Head	2.4GHz	802.11b 1 Mbps	Off	0	Left Touch	1	2412	0.601	16.5	16.4	0.513	0.525	2	11
					Left Tilt	1	2412	0.484	16.5	16.4	0.394	0.403		
					Right Touch	1	2412	0.137	16.5	16.4				
					Right Tilt	1	2412	0.116	16.5	16.4				
Body			Off	13	Rear	1	2412	0.440	16.5	16.4	0.359	0.367	1	12
				11	Edge 1	1	2412	0.062	16.5	16.4				
				0	Edge 2	1	2412	0.382	16.5	16.4				
			On	0	Rear	1	2412	0.531	11.5	11.2	0.340	0.364	1	
					Edge 1	1	2412	0.054	11.5	11.2				

Note(s):

1. Highest reported SAR is ≤ 0.4 W/kg. Therefore, further SAR measurements within this exposure condition are not required.
2. Highest reported SAR is > 0.4 W/kg. Due to the highest reported SAR for this test position, other test positions in this exposure condition were evaluated until a SAR ≤ 0.8 W/kg was reported.
3. Testing for a second channel was required because the reported SAR for this test position was > 0.8 W/kg.
4. Additional testing required in order satisfying FCC simultaneous transmission limit criteria.

10.7.Wi-Fi (U-NII Band)

RF Exposure Conditions	Frequency Band	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Area Scan Max. SAR (W/kg)	Power (dBm)		1-g SAR (W/kg)		Notes	Plot No.	
									Tune-up limit	Meas.	Meas.	Scaled			
Head	5.3 GHz U-NII 2A	802.11a 6 Mbps	Off	0	Left Touch	56	5280	0.680	11.5	11.5	0.419	0.419			
					Left Tilt	56	5280	0.716	11.5	11.5	0.420	0.420	2	13	
					Right Touch	56	5280	0.279	11.5	11.5					
					Right Tilt	56	5280	0.328	11.5	11.5					
Body		Off	13	Rear	56	5280	0.279	11.5	11.4						
			11	Edge 1	56	5280	0.411	11.5	11.4	0.245	0.251	1			
			0	Edge 2	56	5280	0.100	11.5	11.4						
			802.11n (HT40)	On	0	Rear	54	5270	0.826	6.5	6.4	0.384	0.393	1	14
Edge 1	54	5270				0.238	6.5	6.4							
RF Exposure Conditions	Frequency Band	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Area Scan Max. SAR (W/kg)	Power (dBm)		1-g SAR (W/kg)		Notes	Plot No.	
									Tune-up limit	Meas.	Meas.	Scaled			
Head	5.5 GHz U-NII 2C	802.11a 6 Mbps	Off	0	Left Touch	100	5500	1.010	11.5	11.3	0.605	0.634			
						116	5580	1.360	11.5	11.3	0.787	0.824	3	15	
					Left Tilt	116	5580	1.270	11.5	11.3	0.741	0.776	2		
					Right Touch	116	5580	0.451	11.5	11.3					
			Right Tilt	116	5580	0.545	11.5	11.3							
Body			Off	13	Rear	116	5580	0.670	11.5	11.3	0.392	0.410			
				11	Edge 1	116	5580	0.844	11.5	11.3	0.467	0.489	2	16	
				0	Edge 2	116	5580	0.391	11.5	11.3					
		802.11n (HT40)		On	0	Rear	110	5550	0.676	6.5	6.4	0.362	0.370	1	
Edge 1			110			5550	0.233	6.5	6.4						
RF Exposure Conditions	Frequency Band	Mode	Pwr Back Off	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Area Scan Max. SAR (W/kg)	Power (dBm)		1-g SAR (W/kg)		Notes	Plot No.	
									Tune-up limit	Meas.	Meas.	Scaled			
Head	5.8 GHz U-NII 3	802.11a 6 Mbps	Off	0	Left Touch	165	5825	0.898	11.5	11.5	0.473	0.473			
						Left Tilt	165	5825	0.926	11.5	11.5	0.505	0.505	2	17
						Right Touch	165	5825	0.461	11.5	11.5				
						Right Tilt	165	5825	0.651	11.5	11.5				
Body			Off	13	Rear	165	5825	0.260	11.5	11.5					
				11	Edge 1	165	5825	0.596	11.5	11.5	0.346	0.346	1		
				0	Edge 2	165	5825	0.343	11.5	11.5					
		802.11n (HT40)		On	0	Rear	151	5755	0.807	6.5	6.4	0.351	0.359	1	18
Edge 1	151		5755			0.259	6.5	6.4							

Note(s):

1. Highest reported SAR is ≤ 0.4 W/kg. Therefore, further SAR measurements within this exposure condition are not required.
2. Highest reported SAR is > 0.4 W/kg. Due to the highest reported SAR for this test position, other test positions in this exposure condition were evaluated until a SAR ≤ 0.8 W/kg was reported.
3. Testing for a second channel was required because the reported SAR for this test position was > 0.8 W/kg.
4. Additional testing required in order satisfying FCC simultaneous transmission limit criteria.

10.8. Bluetooth

Frequency Band	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
2.4 GHz	GFSK	0	Rear	39	2441.0	10.5	9.5	0.338	0.426	0.130	0.164	19

11. SAR Measurement Variability

In accordance with published RF Exposure KDB 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the **ratio of largest to smallest SAR** for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Frequency Band (MHz)	Air Interface	RF Exposure Conditions	Test Position	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	Repeated Measured SAR (W/kg)	Largest to Smallest SAR Ratio
850	GSM 850	Standalone	Edge 2	No	0.234	N/A	N/A
	WCDMA Band V	Standalone	Rear	No	0.123	N/A	N/A
1900	GSM 1900	Standalone	Rear	No	0.468	N/A	N/A
	WCDMA Band II	Standalone	Rear	No	0.144	0.986	N/A
2400	Wi-Fi 802.11b/g/n	Standalone	Left Touch	No	0.513	N/A	N/A
	Bluetooth	Standalone	Rear	No	0.338	N/A	N/A
2600	LTE Band 41	Standalone	Rear	Yes	1.07	1.02	1.05
5300	Wi-Fi 802.11a/n/ac	Standalone	Left Tilt	No	0.420	N/A	N/A
5600	Wi-Fi 802.11a/n/ac	Standalone	Left Touch	No	0.787	N/A	N/A
5800	Wi-Fi 802.11a/n/ac	Standalone	Rear	No	0.505	N/A	N/A

Note(s):

Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20 .

12. Simultaneous Transmission SAR Analysis

KDB 447498 D01 General RF Exposure Guidance introduces a new formula for calculating the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$SPLSR = (SAR_1 + SAR_2)^{1.5} / Ri$$

Where:

SAR₁ is the highest measured or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

SAR₂ is the highest measured or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

Ri is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$

In order for a pair of simultaneous transmitting antennas with the sum of 1-g SAR > 1.6 W/kg to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(SAR_1 + SAR_2)^{1.5} / Ri < 0.04$$

Simultaneous Transmission Condition

RF Exposure Condition	Item	Capable Transmit Configurations			
Standalone	1	GSM(GPRS/EDGE)	+	DTS	
	2	GSM(GPRS/EDGE)	+	U-NII	
	3	GSM(GPRS/EDGE)	+	BT	
	4	GSM(GPRS/EDGE)	+	U-NII	+ BT
	5	W-CDMA	+	DTS	
	6	W-CDMA	+	U-NII	
	7	W-CDMA	+	BT	
	8	W-CDMA	+	U-NII	+ BT
	9	LTE	+	DTS	
	10	LTE	+	U-NII	
	11	LTE	+	BT	
	12	LTE	+	U-NII	+ BT
Notes:					
1. Only DTS supports Hotspot.					
2. GPRS/EDGE, W-CDMA, CDMA and LTE support Hotspot.					
3. VoIP is supported in GPRS/EDGE, W-CDMA, CDMA and LTE.					
4. DTS Radio cannot transmit simultaneously w ith Bluetooth Radio.					
5. U-NII Radio can transmit simultaneously w ith Bluetooth Radio.					

Estimated SAR for Simultaneous Transmission SAR Analysis

Considerations for SAR estimation

- When standalone SAR test exclusion applies, standalone SAR must also be estimated to determine simultaneous transmission SAR test exclusion.
- Dedicated Host Approach criteria for SAR test exclusion is likewise applied to SAR estimation, with certain distinctions between test exclusion and SAR estimation:
 - When the separation distance from the antenna to an adjacent edge is ≤ 5 mm, a distance of 5 mm is applied for SAR estimation; this is the same between test exclusion and SAR estimation calculations.
 - When the separation distance from the antenna to an adjacent edge is > 5 mm but ≤ 50 mm, the actual antenna-to-edge separation distance is applied for SAR estimation.
 - When the minimum test separation distance is > 50 mm, the estimated SAR value is 0.4 W/kg
- Please refer to Estimated SAR Tables to see which test positions are inherently compliant as they consist of only estimated SAR values for all applicable transmitters and consequently will always have sum of SAR values < 1.2 W/kg. Simultaneous transmission SAR analysis was therefore not performed for these test positions.

Estimated SAR for WWAN

Antenna	Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)						Estimated 1-g SAR Value (W/kg)					
			dBm	mW	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front
Full Power																
Cellular	GPRS 3 Slots	848.8	29.00	298	19	195	7	17	93		-MEA SURE-	0.400	-MEA SURE-	-MEA SURE-	0.400	
Cellular	GPRS 3 Slots	1909.8	26.00	149	19	195	7	17	93		-MEA SURE-	0.400	-MEA SURE-	-MEA SURE-	0.400	
Cellular	W-CDMA 5	846.6	23.50	224	19	195	7	17	93		-MEA SURE-	0.400	-MEA SURE-	-MEA SURE-	0.400	
Cellular	W-CDMA 2	1907.6	23.50	224	19	195	7	17	93		-MEA SURE-	0.400	-MEA SURE-	-MEA SURE-	0.400	
Cellular	LTE Band 41	2680	24.00	251	19	195	7	17	93		-MEA SURE-	0.400	-MEA SURE-	-MEA SURE-	0.400	
Power Back Off																
Cellular	GPRS 4 Slots	848.8	6.60	2	5	195	5	5	91		0.049	0.400	0.049	0.049	0.400	
Cellular	GPRS 4 Slots	1909.8	7.60	3	5	195	5	5	91		0.111	0.400	0.111	0.111	0.400	
Cellular	W-CDMA 5	846.6	5.50	4	5	195	5	5	91		0.098	0.400	0.098	0.098	0.400	
Cellular	W-CDMA 2	1907.6	10.20	10	5	195	5	5	91		0.368	0.400	0.368	0.368	0.400	
Cellular	LTE Band 41	2680	11.00	13	5	195	5	5	91		-MEA SURE-	0.400	-MEA SURE-	-MEA SURE-	0.400	

Estimated SAR for WLAN

Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)					Estimated 1-g SAR Value (W/kg)				
		dBm	mW	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Rear	Edge 1	Edge 2	Edge 3	Edge 4
Full Power													
Wi-Fi 2.4 GHz	2462	16.50	45	13	23	14.5	190	98	-MEASURE-	-MEASURE-	-MEASURE-	0.400	0.400
Wi-Fi 5.2 GHz	5180	11.50	14	13	23	14.5	190	98	0.327	0.185	0.283	0.400	0.400
Wi-Fi 5.3 GHz	5260	11.50	14	13	23	14.5	190	98	0.329	0.186	0.285	0.400	0.400
Wi-Fi 5.5 GHz	5580	11.50	14	13	23	14.5	190	98	0.339	0.192	0.294	0.400	0.400
Wi-Fi 5.8 GHz	5825	11.50	14	13	23	14.5	190	98	0.347	0.196	0.300	0.400	0.400
Bluetooth	2480	10.50	11	13	23	14.5	190	98	0.178	0.100	0.154	0.400	0.400
Power Back Off													
Wi-Fi 2.4 GHz	2462	11.50	14	5	12				-MEASURE-	0.244			
Wi-Fi 5.2 GHz	5180	6.50	4	5	12				0.243	0.101			
Wi-Fi 5.3 GHz	5260	6.50	4	5	12				0.245	0.102			
Wi-Fi 5.5 GHz	5580	6.50	4	5	12				0.252	0.105			
Wi-Fi 5.8 GHz	5825	6.50	4	5	12				0.257	0.107			

12.1. Sum of the SAR for GSM850 & Wi-Fi & BT

RF Exposure conditions	① WWAN	② DSSS	③ U-NII	④ BT	① + ② WWAN + DSSS		① + ③ WWAN + U-NII		① + ④ WWAN + BT	
					Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
Left Touch	0.081	0.525	0.824		0.606	No	0.905	No		
Left Tilt	0.141	0.403	0.776		0.544	No	0.917	No		
Right Touch	0.065	0.525	0.824		0.590	No	0.889	No		
Right Tilt	0.133	0.525	0.824		0.658	No	0.957	No		
Rear	0.276	0.367	0.410	0.426	0.643	No	0.686	No	0.702	No
Edge 1	0.400	0.367	0.489		0.767	No	0.889	No		
Edge 2	0.362	0.367	0.489		0.729	No	0.851	No		
Edge 3	0.099	0.367	0.489		0.466	No	0.588	No		
Edge 4	0.400	0.367	0.489		0.767	No	0.889	No		

12.2. Sum of the SAR for GSM1900 & Wi-Fi & BT

RF Exposure conditions	① WWAN	② DSSS	③ U-NII	④ BT	① + ② WWAN + DSSS		① + ③ WWAN + U-NII		① + ④ WWAN + BT	
					Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
Left Touch	0.024	0.525	0.824		0.549	No	0.848	No		
Left Tilt	0.027	0.403	0.776		0.430	No	0.803	No		
Right Touch	0.051	0.525	0.824		0.576	No	0.875	No		
Right Tilt	0.025	0.525	0.824		0.550	No	0.849	No		
Rear	0.513	0.367	0.410	0.426	0.880	No	0.923	No	0.939	No
Edge 1	0.400	0.367	0.489		0.767	No	0.889	No		
Edge 2	0.048	0.367	0.489		0.415	No	0.537	No		
Edge 3	0.145	0.367	0.489		0.512	No	0.634	No		
Edge 4	0.400	0.367	0.489		0.767	No	0.889	No		

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because the either sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

12.3. Sum of the SAR for WCDMA Band II & Wi-Fi & BT

RF Exposure conditions	① WWAN	② DSSS	③ U-NII	④ BT	① + ② WWAN + DSSS		① + ③ WWAN + U-NII		① + ④ WWAN + BT	
					Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
Left Touch	0.052	0.525	0.824		0.577	No	0.876	No		
Left Tilt	0.049	0.403	0.776		0.452	No	0.825	No		
Right Touch	0.080	0.525	0.824		0.605	No	0.904	No		
Right Tilt	0.040	0.525	0.824		0.565	No	0.864	No		
Rear	0.077	0.367	0.410	0.426	0.444	No	0.487	No	0.503	No
Edge 1	0.400	0.367	0.489		0.767	No	0.889	No		
Edge 2	0.041	0.367	0.489		0.408	No	0.530	No		
Edge 3	0.154	0.367	0.489		0.521	No	0.643	No		
Edge 4	0.400	0.367	0.489		0.767	No	0.889	No		

12.4. Sum of the SAR for WCDMA Band V & Wi-Fi & BT

RF Exposure conditions	① WWAN	② DSSS	③ U-NII	④ BT	① + ② WWAN + DSSS		① + ③ WWAN + U-NII		① + ④ WWAN + BT	
					Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
Left Touch	0.016	0.525	0.824		0.541	No	0.840	No		
Left Tilt	0.028	0.403	0.776		0.431	No	0.804	No		
Right Touch	0.014	0.525	0.824		0.539	No	0.838	No		
Right Tilt	0.024	0.525	0.824		0.549	No	0.848	No		
Rear	0.083	0.367	0.410	0.426	0.450	No	0.493	No	0.509	No
Edge 1	0.400	0.367	0.489		0.767	No	0.889	No		
Edge 2	0.083	0.367	0.489		0.450	No	0.572	No		
Edge 3	0.051	0.367	0.489		0.418	No	0.540	No		
Edge 4	0.400	0.367	0.489		0.767	No	0.889	No		

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because either the sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

12.5. Sum of the SAR for LTE Band 41 & Wi-Fi & BT

RF Exposure conditions	① WWAN	② DSSS	③ U-NII	④ BT	① + ② WWAN + DSSS		① + ③ WWAN + U-NII		① + ④ WWAN + BT	
					Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)	Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
Left Touch	0.012	0.525	0.824		0.537	No	0.836	No		
Left Tilt	0.004	0.403	0.776		0.407	No	0.780	No		
Right Touch	0.020	0.525	0.824		0.545	No	0.844	No		
Right Tilt	0.006	0.525	0.824		0.531	No	0.830	No		
Rear	1.070	0.367	0.410	0.426	1.437	No	1.480	No	1.496	No
Edge 1	0.400	0.367	0.489		0.767	No	0.889	No		
Edge 2	0.207	0.367	0.489		0.574	No	0.696	No		
Edge 3	0.916	0.367	0.489		1.283	No	1.405	No		
Edge 4	0.400	0.367	0.489		0.767	No	0.889	No		

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because either the sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

Appendixes

Refer to separated files for the following appendixes.

A_15I20358v0 SAR Photos & Ant. Locations

B_15I20358v0 SAR System Check Plots

C_15I20358v0 SAR Highest Test Plots

D_15I20358v0 SAR Tissue Ingredients

E_15I20358v0 SAR Probe Cal. Certificates

F_15I20358v0 SAR Dipole Cal. Certificates

END OF REPORT