



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:

08/21/13 - 09/24/13

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

OY1309031750.A3L

FCC ID:

A3LSMP605M

APPLICANT:

SAMSUNG ELECTRONICS, CO. LTD.

DUT Type:

Portable Tablet

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SM-P605M

Equipment Class	Band & Mode	Tx Frequency	Measured Conducted Power [dBm]	SAR
				1 gm Body (W/kg)
PCB	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	28.06	0.58
PCB	UMTS 850	826.40 - 846.60 MHz	21.98	0.79
PCB	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	25.97	1.07
PCB	UMTS 1900	1852.4 - 1907.6 MHz	22.85	0.76
PCB	LTE Band 17	706.5 - 713.5 MHz	23.48	0.59
PCB	LTE Band 5 (Cell)	824.7 - 848.3 MHz	22.86	0.69
PCB	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	23.03	0.79
PCB	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	23.50	0.74
DTS	2.4 GHz WLAN	2412 - 2462 MHz	11.74	1.08
DTS	5.8 GHz WLAN	5745 - 5825 MHz	7.76	0.84
NII	5.2 GHz WLAN	5180 - 5240 MHz	8.03	0.60
NII	5.3 GHz WLAN	5260 - 5320 MHz	8.06	0.85
NII	5.5 GHz WLAN	5500 - 5700 MHz	7.99	1.06
DSS/DTS	Bluetooth	2402 - 2480 MHz	8.13	N/A
Simultaneous SAR per KDB 690783 D01v01r02:				1.55

Note: Powers in the above table represent output powers for the SAR test configurations and may not represent the highest output powers for all configurations for each mode.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 1 of 75

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	9
3	INTRODUCTION	10
4	DOSIMETRIC ASSESSMENT	11
5	SAR TESTING PROCEDURES	12
6	RF EXPOSURE LIMITS	13
7	FCC MEASUREMENT PROCEDURES.....	14
8	RF CONDUCTED POWERS.....	18
9	SYSTEM VERIFICATION.....	43
10	SAR DATA SUMMARY	45
11	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	50
12	SAR MEASUREMENT VARIABILITY	69
13	EQUIPMENT LIST	70
14	MEASUREMENT UNCERTAINTIES	71
15	CONCLUSION.....	73
16	REFERENCES	74
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet	Page 2 of 75	

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 17	Data	706.5 - 713.5 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
5.8 GHz WLAN	Data	5745 - 5825 MHz
5.2 GHz WLAN	Data	5180 - 5240 MHz
5.3 GHz WLAN	Data	5260 - 5320 MHz
5.5 GHz WLAN	Data	5500 - 5700 MHz
Bluetooth	Data	2402 - 2480 MHz
ANT+	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device uses a proximity sensor for SAR compliance. The capacitive proximity sensor is activated when used in close proximity to the user's body. The capacitive proximity sensor triggers power reduction for data modes and is only applicable for tablet operations.

Since the device is a full tablet size, the Body SAR was evaluated per FCC KDB Publication 616217 D04 for full sized tablets.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

Maximum Power: capacitive sensor not active:

Maximum Power Capacitive Sensor Not Active.

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)					Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	
GSM/GPRS/EDGE 850	Maximum	32.0	32.0	31.0	29.0	28.5	26.5	25.0	23.0	22.0	
	Nominal	31.5	31.5	30.5	28.5	28.0	26.0	24.5	22.5	21.5	
GSM/GPRS/EDGE 1900	Maximum	30.0	30.0	29.0	27.0	26.5	26.0	25.0	23.5	22.5	
	Nominal	29.5	29.5	28.5	26.5	26.0	25.5	24.5	23.0	22.0	

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT				Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet				Page 3 of 75

Mode / Band		Modulated Average (dBm)			
		3GPP Rel 99 WCDMA	3GPP Rel 5 HSDPA	3GPP Rel 6 HSUPA	3GPP Rel 8 DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	23.0	22.0	22.0	22.0
	Nominal	22.5	21.5	21.5	21.5
UMTS Band 2 (1900 MHz)	Maximum	23.0	22.0	22.0	22.0
	Nominal	22.5	21.5	21.5	21.5

Mode / Band		Modulated Average (dBm)
LTE Band 17	Maximum	23.5
	Nominal	23.0
LTE Band 5 (Cell)	Maximum	23.5
	Nominal	23.0
LTE Band 4 (AWS)	Maximum	23.5
	Nominal	23.0
LTE Band 2 (PCS)	Maximum	23.5
	Nominal	23.0

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	12.0
	Nominal	11.5
IEEE 802.11g (2.4 GHz)	Maximum	11.5
	Nominal	11.0
IEEE 802.11n (2.4 GHz)	Maximum	10.5
	Nominal	10.0
IEEE 802.11a (5 GHz)	Maximum	8.5
	Nominal	8.0
IEEE 802.11n (5 GHz) 20 MHz BW	Maximum	8.5
	Nominal	8.0
IEEE 802.11n (5 GHz) 40 MHz BW	Maximum	8.5
	Nominal	8.0
IEEE 802.11ac (5 GHz) 80 MHz BW	Maximum	7.9
	Nominal	7.4
Bluetooth	Maximum	8.5
	Nominal	8.0
Bluetooth LE	Maximum	6.0
	Nominal	5.5

With power backoff, capacitive proximity sensor activated:


Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	26.5	26.5	25.0	24.0	22.5	25.0	23.5	22.5	21.0
	Nominal	26.0	26.0	24.5	23.5	22.0	24.5	23.0	22.0	20.5
GSM/GPRS/EDGE 1900	Maximum	22.5	22.5	21.5	20.0	18.5	22.0	20.5	18.5	17.0
	Nominal	22.0	22.0	21.0	19.5	18.0	21.5	20.0	18.0	16.5

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 4 of 75

Mode / Band		Modulated Average (dBm)			
		3GPP Rel 99 WCDMA	3GPP Rel 5 HSDPA	3GPP Rel 6 HSUPA	3GPP Rel 8 DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	20.5	19.5	19.5	19.5
	Nominal	20.0	19.0	19.0	19.0
UMTS Band 2 (1900 MHz)	Maximum	15.5	14.5	14.5	14.5
	Nominal	15.0	14.0	14.0	14.0

Mode / Band		Modulated Average (dBm)
LTE Band 17	Maximum	19.5
	Nominal	19.0
LTE Band 5 (Cell)	Maximum	19.0
	Nominal	18.5
LTE Band 4 (AWS)	Maximum	15.5
	Nominal	15.0
LTE Band 2 (PCS)	Maximum	15.5
	Nominal	15.0

1.4 DUT Antenna Locations



Note: Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC Filing.

Figure 1-1
DUT Antenna Locations

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 5 of 75

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-2 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




Figure 1-2
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

Table 1-1
Simultaneous Transmission Scenarios

No.	Capable Transmit Configurations	Body	Note
		FCC KDB 616217	
1	GSM/GPRS/EDGE 850/1900 Voice/Data + WIFI 2.4 GHz	Yes	2.4 GHz WIFI Direct
2	UMTS 850/1900 Voice/Data + WIFI 2.4 GHz	Yes	2.4 GHz WIFI Direct
3	LTE B2/B4/B5/B17 Data + WIFI 2.4 GHz	Yes	2.4 GHz WIFI Direct
4	GSM/GPRS/EDGE 850/1900 Voice/Data + 2.4 GHz Bluetooth	Yes	
5	UMTS 850/1900 Voice/Data + 2.4 GHz Bluetooth	Yes	
6	LTE B2/B4/B5/B17 Data + 2.4 GHz Bluetooth	Yes	
7	GSM 850/1900 Voice + WIFI 5 GHz	Yes	
8	UMTS 850/1900 Voice + WIFI 5 GHz	Yes	
9	GSM/GPRS/EDGE 850/1900 Data + WIFI 5.8 GHz	Yes	5 GHz WIFI Direct
10	UMTS 850/1900 Data + WIFI 5.8 GHz	Yes	5 GHz WIFI Direct
11	LTE B2/B4/B5/B17 Data + WIFI 5.8 GHz	Yes	5 GHz WIFI Direct

Notes:

1. Per FCC KDB 616217 D04 4.3, when voice mode is limited to speaker mode or headset operations only, additional SAR testing for tablet voice use is not required. Therefore, voice standalone and simultaneous combinations are not evaluated for body configurations. Corresponding data modes are used for summation with Bluetooth when applicable.
2. 2.4 GHz WLAN, 2.4 GHz Bluetooth, and 5 GHz WLAN share the same antenna path and cannot transmit simultaneously.
3. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 6 of 75

1.6 SAR Test Exclusions Applied

(A) WIFI/BT

Per FCC KDB 447498 D01v05, the SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, Bluetooth SAR was not required; $[(7/5) * \sqrt{2.441}] = 2.2 < 3.0$. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

Based on the maximum conducted power of IEEE 802.11ac (rounded to the nearest mW) and the antenna to user separation distance, IEEE 802.11ac SAR was not required; $[(6/5) * \sqrt{5.775}] = 2.9 < 3.0$. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports 20 MHz and 40 MHz Bandwidths for IEEE 802.11n for 5 GHz WIFI only. IEEE 802.11n was not evaluated for SAR since the average output power of 20 MHz and 40 MHz bandwidths was not more than 0.25 dB higher than the average output power of IEEE 802.11a.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 1 Tx antenna output
- d) 256 QAM is supported
- e) No new 5 GHz channels

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v02.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 7 of 75

1.7 Guidance Applied

- FCC KDB Publication 941225 D01-D06 (2G/3G/4G)
- FCC KDB Publication 248227 D01v01r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05 (General SAR Guidance)
- FCC KDB Publication 865664 D01-D02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 616217 D04 (Tablet SAR Considerations)
- April 2013 TCB Workshop Notes (IEEE 802.11ac)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Maximum Power Body Serial Number	Reduced Power Body Serial Number
GSM/GPRS/EDGE 850	005	021
UMTS 850	005	021
GSM/GPRS/EDGE 1900	005	021
UMTS 1900	005	021
LTE Band 17	011	001
LTE Band 5 (Cell)	002	001
LTE Band 4 (AWS)	010	006
LTE Band 2 (PCS)	011	001
2.4 GHz WLAN	159	-
5 GHz WLAN	158	-

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 8 of 75

2

LTE INFORMATION

LTE Information			
FCC ID	A3LSMP605M		
Form Factor	Portable Tablet		
Frequency Range of each LTE transmission band	LTE Band 17 (706.5 - 713.5 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
Channel Bandwidths	LTE Band 17: 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
UE Category	3		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 9 of 75

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [24]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 10 of 75

4

DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1).
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1). On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. The data was extrapolated to the surface of the outer-shell of the phantom. The combined distance extrapolated was the combined distance from the center of the dipoles 2.7mm away from the tip of the probe housing plus the 1.2 mm distance between the surface and the lowest measuring point. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n-1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

FCC ID: A3LSMP605M		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 11 of 75

5 SAR TESTING PROCEDURES

5.1 SAR Testing for Tablet per KDB Publication 616217 D04

This device is used in full sized tablet exposure conditions due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR Exclusion Threshold in KDB 447498 D01v05 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

5.2 Additional Test Positions due to Proximity Sensor Considerations

This device uses a proximity sensor to reduce voice/data powers in tablet-device use conditions.

While the device is touching the user on the antenna, the capacitive proximity sensor activates and thus reduces the maximum output power allowed. However, when the device is moved beyond the sensor triggering distance, the sensor will no longer be active and thus maximum output power is no longer limited. Therefore, an additional exposure condition is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a non-reduced output power level.

FCC KDB 616217 D04 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional exposure conditions. Since the capacitive proximity sensor activation distance for the back side of the device is 13 mm, a conservative distance of 12 mm was tested for SAR on the back side at maximum power. Since the capacitive proximity sensor activation distance for the left edge of the device is 16 mm, a conservative distance of 15 mm was tested for SAR on the left edge, at maximum power. Sensor triggering distance summary data is included in Appendix G. The capacitive proximity sensor does not trigger power reduction from the front side, bottom edge, top edge, or right edge of the device.

The sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the sensor entirely covers the antenna.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 12 of 75

6 RF EXPOSURE LIMITS

6.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 6-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 13 of 75

7 FCC MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

7.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

7.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

7.3 SAR Measurement Conditions for UMTS

7.3.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s".

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

7.3.2 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s".

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 14 of 75

7.3.3 SAR Measurements for Devices with Rel 5 HSDPA

Body SAR for HSDPA is not required for devices with HSDPA capabilities when the maximum average output power of each RF channel with HSDPA active is less than 0.25 dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit. Otherwise, SAR is measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration measured in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that resulted in the highest SAR in 12.2 kbps RMC mode for that RF channel.

The H-set used in FRC for HSDPA should be configured according to the UE category of a test device. The number of HS-DSCH/HSPDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the applicable H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the FRC for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 2 ms to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors of $\beta_c=9$ and $\beta_d=15$, and power offset parameters of $\Delta_{ACK}=\Delta_{NACK}=5$ and $\Delta_{CQI}=2$ is used. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the FRC.

Sub-Test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Rightarrow A_{HS} = \beta_{HS}/\beta_c = 30/15 \Rightarrow \beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 8$ ($A_{HS} = 30/15$) with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 7$ ($A_{HS} = 24/15$) with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Figure 7-1
Table C.10.1.4 of TS 234.121-1

7.3.4 SAR Measurements for Devices with Rel 6 HSUPA

Body SAR for HSUPA is not required when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25 dB higher than as measured without HSUPA/HSDPA using 12.2 kbps RMC and maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit. Otherwise SAR is measured on the maximum output channel for the body exposure configuration produced highest SAR in 12.2 kbps RMC for that RF channel, using the additional procedures under "Release 6 HSPA data devices"

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{HS}^{(1)}$	β_{EC}	β_{ol}	β_{ol} (SF)	β_{ol} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AC ⁽³⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ol} = 47/15$ $\beta_{ol} = 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Rightarrow A_{HS} = \beta_{HS}/\beta_c = 30/15 \Rightarrow \beta_{HS} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPCCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPCCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ol} can not be set directly; it is set by Absolute Grant Value.

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 15 of 75

7.3.5 SAR Measurement Conditions for DC-HSDPA

SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion. DC-HSDPA uplink maximum output power measurements using the four Rel. 5 HSDPA subtests in Table C.10.1.4 of TS 234.121-1 is required.

When the maximum average output power of each RF channel with DC-HSDPA active is $\leq \frac{1}{4}$ dB higher than that measured using 12.2 kbps RMC, or the maximum reported SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit, SAR evaluation for DC-HSDPA is not required.

7.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing.

7.4.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

7.4.2 MPR

MPR is implemented by the manufacturer for the device operating at maximum power with the capacitive sensor inactive. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

7.4.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

7.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r01:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 16 of 75

power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.

- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to ½ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is <1.45 W/kg.

7.5 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g/n/ac transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v01r02 for more details.

7.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

7.5.2 Frequency Channel Configurations [27]

For 2.4 GHz, the highest average RF output power channel between the low, mid and high channel at the lowest data rate was selected for SAR evaluation in 802.11b mode. 802.11g/n modes and higher data rates for 802.11b were additionally evaluated for SAR if the output power of the respective mode was 0.25 dB or higher than the powers of the SAR configurations tested in the 802.11b mode.

For 5 GHz, the highest average RF output power channel across the default test channels at the lowest data rate was selected for SAR evaluation in 802.11a. When the adjacent channels are higher in power than the default channels, these “required channels” were considered instead of the default channels for SAR testing. 802.11n modes and higher data rates for 802.11a/n were evaluated only if the respective mode was 0.25 dB or higher than the 802.11a mode. 802.11ac SAR was not evaluated for highest 802.11a configuration in each 5 GHz band and each exposure condition based on the maximum conducted power of IEEE 802.11ac and the antenna to user separation distance.

If the maximum extrapolated peak SAR of the zoom scan for the highest output channel was less than 1.6 W/kg and if the 1g averaged SAR was less than 0.8 W/kg, SAR testing was not required for the other test channels in the band.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 17 of 75

8 RF CONDUCTED POWERS

8.1 GSM Conducted Powers

Table 8-1
Maximum GSM/GPRS/EDGE Average RF Conducted Powers
Representing Capacitive Sensor Not Active

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	31.84	31.91	30.87	28.77	28.06	26.43	24.74	22.82	21.70
	190	31.73	31.93	30.60	28.59	27.61	25.98	24.45	22.41	21.55
	251	31.00	31.05	30.29	28.12	27.30	25.59	24.03	22.07	21.22
GSM 1900	512	29.82	29.92	28.79	26.77	26.30	25.77	24.67	22.76	21.38
	661	29.81	29.84	28.60	26.56	25.97	25.49	24.43	22.56	21.11
	810	29.62	29.70	28.58	26.45	25.91	25.30	24.22	22.40	21.00

		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	22.81	22.88	24.85	24.51	25.05	17.40	18.72	18.56	18.69
	190	22.70	22.90	24.58	24.33	24.60	16.95	18.43	18.15	18.54
	251	21.97	22.02	24.27	23.86	24.29	16.56	18.01	17.81	18.21
GSM 1900	512	20.79	20.89	22.77	22.51	23.29	16.74	18.65	18.50	18.37
	661	20.78	20.81	22.58	22.30	22.96	16.46	18.41	18.30	18.10
	810	20.59	20.67	22.56	22.19	22.90	16.27	18.20	18.14	17.99

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 18 of 75

Table 8-2
Reduced GSM/GPRS/EDGE Average RF Conducted Powers
Representing Capacitive Sensor Active

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)					EDGE Data (8-PSK)		
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	26.03	26.02	24.98	23.86	22.24	24.74	22.50	21.90	20.10
	190	25.73	25.72	24.66	23.61	22.00	24.25	22.17	21.55	19.75
	251	25.41	25.42	24.00	23.00	21.51	23.91	21.80	21.14	19.31
GSM 1900	512	22.31	22.37	21.35	19.65	18.24	20.74	19.66	18.18	16.75
	661	21.96	22.06	21.04	19.52	17.89	20.50	19.49	17.98	16.54
	810	21.89	21.92	20.80	19.31	17.59	20.26	19.33	17.79	16.36
		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)					EDGE Data (8-PSK)		
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	17.00	16.99	18.96	19.60	19.23	15.71	16.48	17.64	17.09
	190	16.70	16.69	18.64	19.35	18.99	15.22	16.15	17.29	16.74
	251	16.38	16.39	17.98	18.74	18.50	14.88	15.78	16.88	16.30
GSM 1900	512	13.28	13.34	15.33	15.39	15.23	11.71	13.64	13.92	13.74
	661	12.93	13.03	15.02	15.26	14.88	11.47	13.47	13.72	13.53
	810	12.86	12.89	14.78	15.05	14.58	11.23	13.31	13.53	13.35

Notes:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- The bolded GPRS modes were selected for SAR testing according to the highest frame-averaged output power table according to KDB 941225 D03v01.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33 (Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A



Figure 8-1
Power Measurement Setup

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 19 of 75

8.2 UMTS Conducted Powers

Table 8-3
Maximum UMTS Average RF Conducted Powers
Representing Capacitive Sensor Not Active

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.29	21.98	21.89	22.85	22.81	22.23	-
99		12.2 kbps AMR	22.11	21.92	21.87	22.75	22.70	22.30	-
6	HSDPA	Subtest 1	20.95	20.72	20.70	21.84	21.68	21.23	0
6		Subtest 2	20.67	20.35	20.32	21.56	21.34	20.86	0
6		Subtest 3	21.11	20.73	20.80	21.16	21.07	20.53	0.5
6		Subtest 4	21.07	20.82	20.78	21.10	21.11	20.65	0.5
6	HSUPA	Subtest 1	20.45	20.80	20.66	21.46	21.53	21.17	0
6		Subtest 2	19.93	19.30	19.23	20.74	20.31	20.02	2
6		Subtest 3	19.64	19.54	19.50	20.65	20.04	20.31	1
6		Subtest 4	20.22	19.76	20.25	21.27	21.26	20.28	2
6		Subtest 5	20.85	20.21	20.17	21.11	21.17	20.70	0
8	DC-HSDPA	Subtest 1	20.83	20.54	20.51	21.49	21.41	21.11	0
8		Subtest 2	20.77	20.53	20.35	21.52	21.39	20.97	0
8		Subtest 3	20.34	20.07	19.97	20.96	20.94	20.57	0.5
8		Subtest 4	20.38	20.05	19.97	21.07	20.92	20.49	0.5

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 20 of 75

Table 8-4
Reduced UMTS Average RF Conducted Powers
Representing Capacitive Sensor Active

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	20.01	19.99	19.73	15.29	14.84	13.55	-
99		12.2 kbps AMR	20.18	19.93	19.74	15.33	14.80	13.52	-
6	HSDPA	Subtest 1	19.30	19.00	18.84	14.39	14.02	12.65	0
6		Subtest 2	19.27	19.09	19.13	14.35	14.00	12.56	0
6		Subtest 3	18.81	18.64	18.54	13.87	13.52	12.12	0.5
6		Subtest 4	18.79	18.45	18.41	13.89	13.56	12.17	0.5
6	HSUPA	Subtest 1	19.13	18.51	18.32	14.17	13.83	12.53	0
6		Subtest 2	18.01	17.78	17.48	13.35	13.06	11.67	2
6		Subtest 3	17.43	17.97	17.46	13.39	13.08	11.59	1
6		Subtest 4	18.71	18.84	18.19	13.87	13.57	12.08	2
6		Subtest 5	18.93	18.32	18.96	14.05	13.81	12.63	0
8	DC-HSDPA	Subtest 1	18.75	18.48	18.37	14.38	13.74	12.58	0
8		Subtest 2	18.55	18.55	18.22	14.33	13.71	12.51	0
8		Subtest 3	18.34	18.07	17.88	13.87	13.21	12.10	0.5
8		Subtest 4	18.37	18.08	17.90	13.88	13.20	12.01	0.5

UMTS SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- Measured maximum output powers for DC-HSDPA were not greater than 1/4 dB higher than the WCDMA 12.2 kbps RMC maximum output, as a result, SAR is not required for DC-HSDPA
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSUPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 8-2
Power Measurement Setup

FCC ID: A3LSMP605M	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet
Page 21 of 75		

8.3 LTE Conducted Powers

8.3.1 LTE Band 17

Table 8-5
Maximum LTE Band 17 Conducted Powers - 10 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Mid	710.0	23790	10	QPSK	1	0	23.41	0	0
	710.0	23790	10	QPSK	1	25	23.48	0	0
	710.0	23790	10	QPSK	1	49	23.45	0	0
	710.0	23790	10	QPSK	25	0	22.40	1	0-1
	710.0	23790	10	QPSK	25	12	22.44	1	0-1
	710.0	23790	10	QPSK	25	25	22.43	1	0-1
	710.0	23790	10	QPSK	50	0	22.34	1	0-1
	710.0	23790	10	16QAM	1	0	22.40	1	0-1
	710.0	23790	10	16QAM	1	25	22.46	1	0-1
	710.0	23790	10	16QAM	1	49	22.45	1	0-1
	710.0	23790	10	16QAM	25	0	21.35	2	0-2
	710.0	23790	10	16QAM	25	12	21.40	2	0-2
	710.0	23790	10	16QAM	25	25	21.46	2	0-2
	710.0	23790	10	16QAM	50	0	21.31	2	0-2

Note: LTE Band 17 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-6
Maximum LTE Band 17 Conducted Powers - 5 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Mid	710.0	23790	5	QPSK	1	0	23.47	0	0
	710.0	23790	5	QPSK	1	12	23.49	0	0
	710.0	23790	5	QPSK	1	24	23.46	0	0
	710.0	23790	5	QPSK	12	0	22.38	1	0-1
	710.0	23790	5	QPSK	12	6	22.42	1	0-1
	710.0	23790	5	QPSK	12	13	22.47	1	0-1
	710.0	23790	5	QPSK	25	0	22.36	1	0-1
	710.0	23790	5	16-QAM	1	0	22.44	1	0-1
	710.0	23790	5	16-QAM	1	12	22.48	1	0-1
	710.0	23790	5	16-QAM	1	24	22.47	1	0-1
	710.0	23790	5	16-QAM	12	0	21.34	2	0-2
	710.0	23790	5	16-QAM	12	6	21.42	2	0-2
	710.0	23790	5	16-QAM	12	13	21.45	2	0-2
	710.0	23790	5	16-QAM	25	0	21.35	2	0-2

Note: LTE Band 17 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 22 of 75

Table 8-7
Reduced LTE Band 17 Conducted Powers - 10 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Mid	710.0	23790	10	QPSK	1	0	19.33	0	0
	710.0	23790	10	QPSK	1	25	19.43	0	0
	710.0	23790	10	QPSK	1	49	19.40	0	0
	710.0	23790	10	QPSK	25	0	19.28	0	0-1
	710.0	23790	10	QPSK	25	12	19.24	0	0-1
	710.0	23790	10	QPSK	25	25	19.27	0	0-1
	710.0	23790	10	QPSK	50	0	19.25	0	0-1
	710.0	23790	10	16QAM	1	0	19.03	0	0-1
	710.0	23790	10	16QAM	1	25	19.03	0	0-1
	710.0	23790	10	16QAM	1	49	19.12	0	0-1
	710.0	23790	10	16QAM	25	0	19.28	0	0-2
	710.0	23790	10	16QAM	25	12	19.18	0	0-2
	710.0	23790	10	16QAM	25	25	19.16	0	0-2
	710.0	23790	10	16QAM	50	0	19.11	0	0-2

Note: LTE Band 17 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-8
Reduced LTE Band 17 Conducted Powers - 5 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Mid	710.0	23790	5	QPSK	1	0	19.37	0	0
	710.0	23790	5	QPSK	1	12	19.41	0	0
	710.0	23790	5	QPSK	1	24	19.44	0	0
	710.0	23790	5	QPSK	12	0	19.29	0	0-1
	710.0	23790	5	QPSK	12	6	19.32	0	0-1
	710.0	23790	5	QPSK	12	13	19.29	0	0-1
	710.0	23790	5	QPSK	25	0	19.27	0	0-1
	710.0	23790	5	16-QAM	1	0	19.17	0	0-1
	710.0	23790	5	16-QAM	1	12	19.15	0	0-1
	710.0	23790	5	16-QAM	1	24	19.17	0	0-1
	710.0	23790	5	16-QAM	12	0	19.18	0	0-2
	710.0	23790	5	16-QAM	12	6	19.21	0	0-2
	710.0	23790	5	16-QAM	12	13	19.23	0	0-2
	710.0	23790	5	16-QAM	25	0	19.03	0	0-2

Note: LTE Band 17 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 23 of 75

8.3.2

LTE Band 5 (Cell)

Table 8-9
Maximum LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Mid	836.5	20525	10	QPSK	1	0	22.86	0	0
	836.5	20525	10	QPSK	1	25	22.67	0	0
	836.5	20525	10	QPSK	1	49	22.66	0	0
	836.5	20525	10	QPSK	25	0	21.71	1	0-1
	836.5	20525	10	QPSK	25	12	21.61	1	0-1
	836.5	20525	10	QPSK	25	25	21.56	1	0-1
	836.5	20525	10	QPSK	50	0	21.53	1	0-1
	836.5	20525	10	16QAM	1	0	21.81	1	0-1
	836.5	20525	10	16QAM	1	25	21.69	1	0-1
	836.5	20525	10	16QAM	1	49	21.72	1	0-1
	836.5	20525	10	16QAM	25	0	20.66	2	0-2
	836.5	20525	10	16QAM	25	12	20.57	2	0-2
	836.5	20525	10	16QAM	25	25	20.54	2	0-2
	836.5	20525	10	16QAM	50	0	20.51	2	0-2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-10
Maximum LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	826.5	20425	5	QPSK	1	0	23.09	0	0
	826.5	20425	5	QPSK	1	12	23.13	0	0
	826.5	20425	5	QPSK	1	24	23.07	0	0
	826.5	20425	5	QPSK	12	0	22.10	1	0-1
	826.5	20425	5	QPSK	12	6	22.03	1	0-1
	826.5	20425	5	QPSK	12	13	22.08	1	0-1
	826.5	20425	5	QPSK	25	0	22.02	1	0-1
	826.5	20425	5	16-QAM	1	0	22.13	1	0-1
	826.5	20425	5	16-QAM	1	12	22.15	1	0-1
	826.5	20425	5	16-QAM	1	24	22.08	1	0-1
	826.5	20425	5	16-QAM	12	0	21.16	2	0-2
	826.5	20425	5	16-QAM	12	6	21.11	2	0-2
	826.5	20425	5	16-QAM	12	13	21.15	2	0-2
	826.5	20425	5	16-QAM	25	0	21.00	2	0-2
Mid	836.5	20525	5	QPSK	1	0	22.68	0	0
	836.5	20525	5	QPSK	1	12	22.59	0	0
	836.5	20525	5	QPSK	1	24	22.56	0	0
	836.5	20525	5	QPSK	12	0	21.60	1	0-1
	836.5	20525	5	QPSK	12	6	21.57	1	0-1
	836.5	20525	5	QPSK	12	13	21.58	1	0-1
	836.5	20525	5	QPSK	25	0	21.56	1	0-1
	836.5	20525	5	16-QAM	1	0	21.71	1	0-1
	836.5	20525	5	16-QAM	1	12	21.68	1	0-1
	836.5	20525	5	16-QAM	1	24	21.61	1	0-1
	836.5	20525	5	16-QAM	12	0	20.66	2	0-2
	836.5	20525	5	16-QAM	12	6	20.65	2	0-2
	836.5	20525	5	16-QAM	12	13	20.62	2	0-2
	836.5	20525	5	16-QAM	25	0	20.57	2	0-2
High	846.5	20625	5	QPSK	1	0	22.53	0	0
	846.5	20625	5	QPSK	1	12	22.58	0	0
	846.5	20625	5	QPSK	1	24	22.66	0	0
	846.5	20625	5	QPSK	12	0	21.50	1	0-1
	846.5	20625	5	QPSK	12	6	21.53	1	0-1
	846.5	20625	5	QPSK	12	13	21.54	1	0-1
	846.5	20625	5	QPSK	25	0	21.51	1	0-1
	846.5	20625	5	16-QAM	1	0	21.52	1	0-1
	846.5	20625	5	16-QAM	1	12	21.55	1	0-1
	846.5	20625	5	16-QAM	1	24	21.68	1	0-1
	846.5	20625	5	16-QAM	12	0	20.52	2	0-2
	846.5	20625	5	16-QAM	12	6	20.58	2	0-2
	846.5	20625	5	16-QAM	12	13	20.64	2	0-2
	846.5	20625	5	16-QAM	25	0	20.53	2	0-2

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 24 of 75

Table 8-11
Maximum LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	825.5	20415	3	QPSK	1	0	23.12	0	0
	825.5	20415	3	QPSK	1	7	23.05	0	0
	825.5	20415	3	QPSK	1	14	23.13	0	0
	825.5	20415	3	QPSK	8	0	22.11	1	0-1
	825.5	20415	3	QPSK	8	4	22.14	1	0-1
	825.5	20415	3	QPSK	8	7	22.09	1	0-1
	825.5	20415	3	QPSK	15	0	22.10	1	0-1
	825.5	20415	3	16-QAM	1	0	22.16	1	0-1
	825.5	20415	3	16-QAM	1	7	22.11	1	0-1
	825.5	20415	3	16-QAM	1	14	22.15	1	0-1
	825.5	20415	3	16-QAM	8	0	20.96	2	0-2
	825.5	20415	3	16-QAM	8	4	21.02	2	0-2
	825.5	20415	3	16-QAM	8	7	20.99	2	0-2
	825.5	20415	3	16-QAM	15	0	21.05	2	0-2
	836.5	20525	3	QPSK	1	0	22.68	0	0
Mid	836.5	20525	3	QPSK	1	7	22.60	0	0
	836.5	20525	3	QPSK	1	14	22.62	0	0
	836.5	20525	3	QPSK	8	0	21.55	1	0-1
	836.5	20525	3	QPSK	8	4	21.56	1	0-1
	836.5	20525	3	QPSK	8	7	21.54	1	0-1
	836.5	20525	3	QPSK	15	0	21.52	1	0-1
	836.5	20525	3	16-QAM	1	0	21.64	1	0-1
	836.5	20525	3	16-QAM	1	7	21.62	1	0-1
	836.5	20525	3	16-QAM	1	14	21.61	1	0-1
	836.5	20525	3	16-QAM	8	0	20.51	2	0-2
	836.5	20525	3	16-QAM	8	4	20.50	2	0-2
	836.5	20525	3	16-QAM	8	7	20.52	2	0-2
	836.5	20525	3	16-QAM	15	0	20.55	2	0-2
	847.5	20635	3	QPSK	1	0	22.55	0	0
	847.5	20635	3	QPSK	1	7	22.58	0	0
High	847.5	20635	3	QPSK	1	14	22.67	0	0
	847.5	20635	3	QPSK	8	0	21.57	1	0-1
	847.5	20635	3	QPSK	8	4	21.58	1	0-1
	847.5	20635	3	QPSK	8	7	21.59	1	0-1
	847.5	20635	3	QPSK	15	0	21.56	1	0-1
	847.5	20635	3	16-QAM	1	0	21.57	1	0-1
	847.5	20635	3	16-QAM	1	7	21.64	1	0-1
	847.5	20635	3	16-QAM	1	14	21.73	1	0-1
	847.5	20635	3	16-QAM	8	0	20.51	2	0-2
	847.5	20635	3	16-QAM	8	4	20.52	2	0-2
	847.5	20635	3	16-QAM	8	7	20.57	2	0-2
	847.5	20635	3	16-QAM	15	0	20.54	2	0-2

Table 8-12
Maximum LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	824.7	20407	1.4	QPSK	1	0	23.11	0	0
	824.7	20407	1.4	QPSK	1	2	23.13	0	0
	824.7	20407	1.4	QPSK	1	5	23.09	0	0
	824.7	20407	1.4	QPSK	3	0	23.12	0	0
	824.7	20407	1.4	QPSK	3	2	23.07	0	0
	824.7	20407	1.4	QPSK	3	3	23.09	0	0
	824.7	20407	1.4	QPSK	6	0	22.15	1	0-1
	824.7	20407	1.4	16-QAM	1	0	22.18	1	0-1
	824.7	20407	1.4	16-QAM	1	2	22.14	1	0-1
	824.7	20407	1.4	16-QAM	1	5	22.20	1	0-1
	824.7	20407	1.4	16-QAM	3	0	22.10	1	0-1
	824.7	20407	1.4	16-QAM	3	2	22.09	1	0-1
	824.7	20407	1.4	16-QAM	3	3	22.11	1	0-1
	824.7	20407	1.4	16-QAM	6	0	21.08	2	0-2
	836.5	20525	1.4	QPSK	1	0	22.62	0	0
Mid	836.5	20525	1.4	QPSK	1	2	22.60	0	0
	836.5	20525	1.4	QPSK	1	5	22.57	0	0
	836.5	20525	1.4	QPSK	3	0	22.58	0	0
	836.5	20525	1.4	QPSK	3	2	22.56	0	0
	836.5	20525	1.4	QPSK	3	3	22.55	0	0
	836.5	20525	1.4	QPSK	6	0	21.52	1	0-1
	836.5	20525	1.4	16-QAM	1	0	21.64	1	0-1
	836.5	20525	1.4	16-QAM	1	2	21.65	1	0-1
	836.5	20525	1.4	16-QAM	1	5	21.62	1	0-1
	836.5	20525	1.4	16-QAM	3	0	21.67	1	0-1
	836.5	20525	1.4	16-QAM	3	2	21.64	1	0-1
	836.5	20525	1.4	16-QAM	3	3	21.56	1	0-1
	836.5	20525	1.4	16-QAM	6	0	20.51	2	0-2
	848.3	20643	1.4	QPSK	1	0	22.61	0	0
	848.3	20643	1.4	QPSK	1	2	22.62	0	0
High	848.3	20643	1.4	QPSK	1	5	22.64	0	0
	848.3	20643	1.4	QPSK	3	0	22.55	0	0
	848.3	20643	1.4	QPSK	3	2	22.56	0	0
	848.3	20643	1.4	QPSK	3	3	22.54	0	0
	848.3	20643	1.4	QPSK	6	0	21.66	1	0-1
	848.3	20643	1.4	16-QAM	1	0	21.65	1	0-1
	848.3	20643	1.4	16-QAM	1	2	21.71	1	0-1
	848.3	20643	1.4	16-QAM	1	5	21.73	1	0-1
	848.3	20643	1.4	16-QAM	3	0	21.65	1	0-1
	848.3	20643	1.4	16-QAM	3	2	21.63	1	0-1
	848.3	20643	1.4	16-QAM	3	3	21.65	1	0-1
	848.3	20643	1.4	16-QAM	6	0	20.53	2	0-2

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 25 of 75

Table 8-13
Reduced LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Mid	836.5	20525	10	QPSK	1	0	18.68	0	0
	836.5	20525	10	QPSK	1	25	18.59	0	0
	836.5	20525	10	QPSK	1	49	18.53	0	0
	836.5	20525	10	QPSK	25	0	18.52	0	0-1
	836.5	20525	10	QPSK	25	12	18.38	0	0-1
	836.5	20525	10	QPSK	25	25	18.44	0	0-1
	836.5	20525	10	QPSK	50	0	18.43	0	0-1
	836.5	20525	10	16QAM	1	0	18.50	0	0-1
	836.5	20525	10	16QAM	1	25	18.36	0	0-1
	836.5	20525	10	16QAM	1	49	18.31	0	0-1
	836.5	20525	10	16QAM	25	0	18.55	0	0-2
	836.5	20525	10	16QAM	25	12	18.37	0	0-2
	836.5	20525	10	16QAM	25	25	18.34	0	0-2
	836.5	20525	10	16QAM	50	0	18.52	0	0-2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-14
Reduced LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	826.5	20425	5	QPSK	1	0	18.72	0	0
	826.5	20425	5	QPSK	1	12	18.75	0	0
	826.5	20425	5	QPSK	1	24	18.67	0	0
	826.5	20425	5	QPSK	12	0	18.73	0	0-1
	826.5	20425	5	QPSK	12	6	18.71	0	0-1
	826.5	20425	5	QPSK	12	13	18.76	0	0-1
	826.5	20425	5	QPSK	25	0	18.60	0	0-1
	826.5	20425	5	16-QAM	1	0	18.78	0	0-1
	826.5	20425	5	16-QAM	1	12	18.79	0	0-1
	826.5	20425	5	16-QAM	1	24	18.65	0	0-1
	826.5	20425	5	16-QAM	12	0	18.72	0	0-2
	826.5	20425	5	16-QAM	12	6	18.77	0	0-2
	826.5	20425	5	16-QAM	12	13	18.75	0	0-2
	826.5	20425	5	16-QAM	25	0	18.59	0	0-2
Mid	836.5	20525	5	QPSK	1	0	18.53	0	0
	836.5	20525	5	QPSK	1	12	18.50	0	0
	836.5	20525	5	QPSK	1	24	18.31	0	0
	836.5	20525	5	QPSK	12	0	18.59	0	0-1
	836.5	20525	5	QPSK	12	6	18.44	0	0-1
	836.5	20525	5	QPSK	12	13	18.46	0	0-1
	836.5	20525	5	QPSK	25	0	18.44	0	0-1
	836.5	20525	5	16-QAM	1	0	18.52	0	0-1
	836.5	20525	5	16-QAM	1	12	18.44	0	0-1
	836.5	20525	5	16-QAM	1	24	18.33	0	0-1
	836.5	20525	5	16-QAM	12	0	18.49	0	0-2
	836.5	20525	5	16-QAM	12	6	18.43	0	0-2
	836.5	20525	5	16-QAM	12	13	18.35	0	0-2
	836.5	20525	5	16-QAM	25	0	18.38	0	0-2
High	846.5	20625	5	QPSK	1	0	18.31	0	0
	846.5	20625	5	QPSK	1	12	18.41	0	0
	846.5	20625	5	QPSK	1	24	18.38	0	0
	846.5	20625	5	QPSK	12	0	18.43	0	0-1
	846.5	20625	5	QPSK	12	6	18.40	0	0-1
	846.5	20625	5	QPSK	12	13	18.38	0	0-1
	846.5	20625	5	QPSK	25	0	18.40	0	0-1
	846.5	20625	5	16-QAM	1	0	18.49	0	0-1
	846.5	20625	5	16-QAM	1	12	18.45	0	0-1
	846.5	20625	5	16-QAM	1	24	18.41	0	0-1
	846.5	20625	5	16-QAM	12	0	18.49	0	0-2
	846.5	20625	5	16-QAM	12	6	18.41	0	0-2
	846.5	20625	5	16-QAM	12	13	18.33	0	0-2
	846.5	20625	5	16-QAM	25	0	18.38	0	0-2

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 26 of 75

Table 8-15
Reduced LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	825.5	20415	3	QPSK	1	0	18.78	0	0
	825.5	20415	3	QPSK	1	7	18.77	0	0
	825.5	20415	3	QPSK	1	14	18.79	0	0
	825.5	20415	3	QPSK	8	0	18.71	0	0-1
	825.5	20415	3	QPSK	8	4	18.73	0	0-1
	825.5	20415	3	QPSK	8	7	18.72	0	0-1
	825.5	20415	3	QPSK	15	0	18.69	0	0-1
	825.5	20415	3	16-QAM	1	0	18.76	0	0-1
	825.5	20415	3	16-QAM	1	7	18.78	0	0-1
	825.5	20415	3	16-QAM	1	14	18.77	0	0-1
	825.5	20415	3	16-QAM	8	0	18.65	0	0-2
	825.5	20415	3	16-QAM	8	4	18.69	0	0-2
	825.5	20415	3	16-QAM	8	7	18.62	0	0-2
	825.5	20415	3	16-QAM	15	0	18.66	0	0-2
	836.5	20525	3	QPSK	1	0	18.58	0	0
Mid	836.5	20525	3	QPSK	1	7	18.55	0	0
	836.5	20525	3	QPSK	1	14	18.46	0	0
	836.5	20525	3	QPSK	8	0	18.53	0	0-1
	836.5	20525	3	QPSK	8	4	18.47	0	0-1
	836.5	20525	3	QPSK	8	7	18.49	0	0-1
	836.5	20525	3	QPSK	15	0	18.53	0	0-1
	836.5	20525	3	16-QAM	1	0	18.39	0	0-1
	836.5	20525	3	16-QAM	1	7	18.51	0	0-1
	836.5	20525	3	16-QAM	1	14	18.39	0	0-1
	836.5	20525	3	16-QAM	8	0	18.33	0	0-2
	836.5	20525	3	16-QAM	8	4	18.35	0	0-2
	836.5	20525	3	16-QAM	8	7	18.32	0	0-2
	836.5	20525	3	16-QAM	15	0	18.40	0	0-2
	847.5	20635	3	QPSK	1	0	18.48	0	0
	847.5	20635	3	QPSK	1	7	18.40	0	0
High	847.5	20635	3	QPSK	1	14	18.42	0	0
	847.5	20635	3	QPSK	8	0	18.46	0	0-1
	847.5	20635	3	QPSK	8	4	18.35	0	0-1
	847.5	20635	3	QPSK	8	7	18.38	0	0-1
	847.5	20635	3	QPSK	15	0	18.32	0	0-1
	847.5	20635	3	16-QAM	1	0	18.38	0	0-1
	847.5	20635	3	16-QAM	1	7	18.40	0	0-1
	847.5	20635	3	16-QAM	1	14	18.42	0	0-1
	847.5	20635	3	16-QAM	8	0	18.32	0	0-2
	847.5	20635	3	16-QAM	8	4	18.30	0	0-2
	847.5	20635	3	16-QAM	8	7	18.31	0	0-2
	847.5	20635	3	16-QAM	15	0	18.35	0	0-2

Table 8-16
Reduced LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	824.7	20407	1.4	QPSK	1	0	18.63	0	0
	824.7	20407	1.4	QPSK	1	2	18.60	0	0
	824.7	20407	1.4	QPSK	1	5	18.56	0	0
	824.7	20407	1.4	QPSK	3	0	18.56	0	0
	824.7	20407	1.4	QPSK	3	2	18.58	0	0
	824.7	20407	1.4	QPSK	3	3	18.54	0	0
	824.7	20407	1.4	QPSK	6	0	18.58	0	0-1
	824.7	20407	1.4	16-QAM	1	0	18.64	0	0-1
	824.7	20407	1.4	16-QAM	1	2	18.67	0	0-1
	824.7	20407	1.4	16-QAM	1	5	18.60	0	0-1
	824.7	20407	1.4	16-QAM	3	0	18.56	0	0-1
	824.7	20407	1.4	16-QAM	3	2	18.54	0	0-1
	824.7	20407	1.4	16-QAM	3	3	18.51	0	0-1
	824.7	20407	1.4	16-QAM	6	0	18.47	0	0-2
Mid	836.5	20525	1.4	QPSK	1	0	18.35	0	0
	836.5	20525	1.4	QPSK	1	2	18.35	0	0
	836.5	20525	1.4	QPSK	1	5	18.36	0	0
	836.5	20525	1.4	QPSK	3	0	18.32	0	0
	836.5	20525	1.4	QPSK	3	2	18.38	0	0
	836.5	20525	1.4	QPSK	3	3	18.42	0	0
	836.5	20525	1.4	QPSK	6	0	18.32	0	0-1
	836.5	20525	1.4	16-QAM	1	0	18.23	0	0-1
	836.5	20525	1.4	16-QAM	1	2	18.27	0	0-1
	836.5	20525	1.4	16-QAM	1	5	18.17	0	0-1
	836.5	20525	1.4	16-QAM	3	0	18.24	0	0-1
	836.5	20525	1.4	16-QAM	3	2	18.20	0	0-1
	836.5	20525	1.4	16-QAM	3	3	18.19	0	0-1
	836.5	20525	1.4	16-QAM	6	0	18.11	0	0-2
High	848.3	20643	1.4	QPSK	1	0	18.23	0	0
	848.3	20643	1.4	QPSK	1	2	18.14	0	0
	848.3	20643	1.4	QPSK	1	5	18.22	0	0
	848.3	20643	1.4	QPSK	3	0	18.19	0	0
	848.3	20643	1.4	QPSK	3	2	18.09	0	0
	848.3	20643	1.4	QPSK	3	3	18.16	0	0
	848.3	20643	1.4	QPSK	6	0	18.17	0	0-1
	848.3	20643	1.4	16-QAM	1	0	18.18	0	0-1
	848.3	20643	1.4	16-QAM	1	2	18.19	0	0-1
	848.3	20643	1.4	16-QAM	1	5	18.26	0	0-1
	848.3	20643	1.4	16-QAM	3	0	18.14	0	0-1
	848.3	20643	1.4	16-QAM	3	2	18.11	0	0-1
	848.3	20643	1.4	16-QAM	3	3	18.16	0	0-1
	848.3	20643	1.4	16-QAM	6	0	18.09	0	0-2

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 27 of 75

8.3.3

LTE Band 4 (AWS)

Table 8-17
Maximum LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Mid	1732.5	20175	20	QPSK	1	0	23.03	0	0
	1732.5	20175	20	QPSK	1	50	22.93	0	0
	1732.5	20175	20	QPSK	1	99	22.78	0	0
	1732.5	20175	20	QPSK	50	0	21.93	1	0-1
	1732.5	20175	20	QPSK	50	25	21.79	1	0-1
	1732.5	20175	20	QPSK	50	50	21.78	1	0-1
	1732.5	20175	20	QPSK	100	0	21.78	1	0-1
	1732.5	20175	20	16QAM	1	0	21.96	1	0-1
	1732.5	20175	20	16QAM	1	50	21.93	1	0-1
	1732.5	20175	20	16QAM	1	99	21.81	1	0-1
	1732.5	20175	20	16QAM	50	0	20.85	2	0-2
	1732.5	20175	20	16QAM	50	25	20.82	2	0-2
	1732.5	20175	20	16QAM	50	50	20.79	2	0-2
	1732.5	20175	20	16QAM	100	0	20.75	2	0-2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-18
Maximum LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1717.5	20025	15	QPSK	1	0	22.61	0	0
	1717.5	20025	15	QPSK	1	36	22.75	0	0
	1717.5	20025	15	QPSK	1	74	22.90	0	0
	1717.5	20025	15	QPSK	36	0	21.70	1	0-1
	1717.5	20025	15	QPSK	36	18	21.78	1	0-1
	1717.5	20025	15	QPSK	36	37	21.76	1	0-1
	1717.5	20025	15	QPSK	75	0	21.75	1	0-1
	1717.5	20025	15	16QAM	1	0	21.89	1	0-1
	1717.5	20025	15	16QAM	1	36	22.03	1	0-1
	1717.5	20025	15	16QAM	1	74	22.14	1	0-1
	1717.5	20025	15	16QAM	36	0	20.80	2	0-2
	1717.5	20025	15	16QAM	36	18	20.89	2	0-2
	1717.5	20025	15	16QAM	36	37	20.85	2	0-2
	1717.5	20025	15	16QAM	75	0	20.74	2	0-2
Mid	1732.5	20175	15	QPSK	1	0	23.01	0	0
	1732.5	20175	15	QPSK	1	36	22.98	0	0
	1732.5	20175	15	QPSK	1	74	22.91	0	0
	1732.5	20175	15	QPSK	36	0	21.87	1	0-1
	1732.5	20175	15	QPSK	36	18	21.84	1	0-1
	1732.5	20175	15	QPSK	36	37	21.78	1	0-1
	1732.5	20175	15	QPSK	75	0	21.76	1	0-1
	1732.5	20175	15	16QAM	1	0	21.81	1	0-1
	1732.5	20175	15	16QAM	1	36	21.82	1	0-1
	1732.5	20175	15	16QAM	1	74	21.68	1	0-1
	1732.5	20175	15	16QAM	36	0	20.84	2	0-2
	1732.5	20175	15	16QAM	36	18	20.80	2	0-2
	1732.5	20175	15	16QAM	36	37	20.75	2	0-2
	1732.5	20175	15	16QAM	75	0	20.76	2	0-2
High	1747.5	20325	15	QPSK	1	0	22.84	0	0
	1747.5	20325	15	QPSK	1	36	22.88	0	0
	1747.5	20325	15	QPSK	1	74	22.78	0	0
	1747.5	20325	15	QPSK	36	0	21.66	1	0-1
	1747.5	20325	15	QPSK	36	18	21.68	1	0-1
	1747.5	20325	15	QPSK	36	37	21.66	1	0-1
	1747.5	20325	15	QPSK	75	0	21.59	1	0-1
	1747.5	20325	15	16QAM	1	0	21.65	1	0-1
	1747.5	20325	15	16QAM	1	36	21.69	1	0-1
	1747.5	20325	15	16QAM	1	74	21.63	1	0-1
	1747.5	20325	15	16QAM	36	0	20.74	2	0-2
	1747.5	20325	15	16QAM	36	18	20.80	2	0-2
	1747.5	20325	15	16QAM	36	37	20.79	2	0-2
	1747.5	20325	15	16QAM	75	0	20.58	2	0-2

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 28 of 75

Table 8-19
Maximum LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1715	20000	10	QPSK	1	0	22.68	0	0
	1715	20000	10	QPSK	1	25	22.69	0	0
	1715	20000	10	QPSK	1	49	22.83	0	0
	1715	20000	10	QPSK	25	0	21.79	1	0-1
	1715	20000	10	QPSK	25	12	21.78	1	0-1
	1715	20000	10	QPSK	25	25	21.89	1	0-1
	1715	20000	10	QPSK	50	0	21.79	1	0-1
	1715	20000	10	16QAM	1	0	21.94	1	0-1
	1715	20000	10	16QAM	1	25	22.01	1	0-1
	1715	20000	10	16QAM	1	49	22.12	1	0-1
	1715	20000	10	16QAM	25	0	20.84	2	0-2
	1715	20000	10	16QAM	25	12	20.83	2	0-2
	1715	20000	10	16QAM	25	25	20.86	2	0-2
	1715	20000	10	16QAM	50	0	20.77	2	0-2
	1732.5	20175	10	QPSK	1	0	22.81	0	0
	1732.5	20175	10	QPSK	1	25	22.66	0	0
	1732.5	20175	10	QPSK	1	49	22.64	0	0
Mid	1732.5	20175	10	QPSK	25	0	21.93	1	0-1
	1732.5	20175	10	QPSK	25	12	21.86	1	0-1
	1732.5	20175	10	QPSK	25	25	21.85	1	0-1
	1732.5	20175	10	QPSK	50	0	21.82	1	0-1
	1732.5	20175	10	16QAM	1	0	22.11	1	0-1
	1732.5	20175	10	16QAM	1	25	22.08	1	0-1
	1732.5	20175	10	16QAM	1	49	22.05	1	0-1
	1732.5	20175	10	16QAM	25	0	20.85	2	0-2
	1732.5	20175	10	16QAM	25	12	20.87	2	0-2
	1732.5	20175	10	16QAM	25	25	20.80	2	0-2
	1732.5	20175	10	16QAM	50	0	20.77	2	0-2
High	1750	20350	10	QPSK	1	0	22.84	0	0
	1750	20350	10	QPSK	1	25	22.79	0	0
	1750	20350	10	QPSK	1	49	22.78	0	0
	1750	20350	10	QPSK	25	0	21.68	1	0-1
	1750	20350	10	QPSK	25	12	21.67	1	0-1
	1750	20350	10	QPSK	25	25	21.77	1	0-1
	1750	20350	10	QPSK	50	0	21.66	1	0-1
	1750	20350	10	16QAM	1	0	21.59	1	0-1
	1750	20350	10	16QAM	1	25	21.55	1	0-1
	1750	20350	10	16QAM	1	49	21.52	1	0-1
	1750	20350	10	16QAM	25	0	20.84	2	0-2
	1750	20350	10	16QAM	25	12	20.75	2	0-2
	1750	20350	10	16QAM	25	25	20.82	2	0-2
	1750	20350	10	16QAM	50	0	20.72	2	0-2

Table 8-20
Maximum LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1712.5	19975	5	QPSK	1	0	22.55	0	0
	1712.5	19975	5	QPSK	1	12	22.57	0	0
	1712.5	19975	5	QPSK	1	24	22.59	0	0
	1712.5	19975	5	QPSK	12	0	21.67	1	0-1
	1712.5	19975	5	QPSK	12	6	21.70	1	0-1
	1712.5	19975	5	QPSK	12	13	21.65	1	0-1
	1712.5	19975	5	QPSK	25	0	21.72	1	0-1
	1712.5	19975	5	16-QAM	1	0	22.06	1	0-1
	1712.5	19975	5	16-QAM	1	12	21.87	1	0-1
	1712.5	19975	5	16-QAM	1	24	21.88	1	0-1
	1712.5	19975	5	16-QAM	12	0	20.74	2	0-2
	1712.5	19975	5	16-QAM	12	6	20.78	2	0-2
	1712.5	19975	5	16-QAM	12	13	20.77	2	0-2
	1712.5	19975	5	16-QAM	25	0	20.70	2	0-2
Mid	1732.5	20175	5	QPSK	1	0	22.60	0	0
	1732.5	20175	5	QPSK	1	12	22.57	0	0
	1732.5	20175	5	QPSK	1	24	22.60	0	0
	1732.5	20175	5	QPSK	12	0	21.77	1	0-1
	1732.5	20175	5	QPSK	12	6	21.82	1	0-1
	1732.5	20175	5	QPSK	12	13	21.70	1	0-1
	1732.5	20175	5	QPSK	25	0	21.75	1	0-1
	1732.5	20175	5	16-QAM	1	0	21.51	1	0-1
	1732.5	20175	5	16-QAM	1	12	21.53	1	0-1
	1732.5	20175	5	16-QAM	1	24	21.55	1	0-1
	1732.5	20175	5	16-QAM	12	0	20.80	2	0-2
	1732.5	20175	5	16-QAM	12	6	20.84	2	0-2
	1732.5	20175	5	16-QAM	12	13	20.84	2	0-2
	1732.5	20175	5	16-QAM	25	0	20.73	2	0-2
High	1752.5	20375	5	QPSK	1	0	22.72	0	0
	1752.5	20375	5	QPSK	1	12	22.75	0	0
	1752.5	20375	5	QPSK	1	24	22.73	0	0
	1752.5	20375	5	QPSK	12	0	21.84	1	0-1
	1752.5	20375	5	QPSK	12	6	21.83	1	0-1
	1752.5	20375	5	QPSK	12	13	21.76	1	0-1
	1752.5	20375	5	QPSK	25	0	21.84	1	0-1
	1752.5	20375	5	16-QAM	1	0	21.52	1	0-1
	1752.5	20375	5	16-QAM	1	12	21.50	1	0-1
	1752.5	20375	5	16-QAM	1	24	21.51	1	0-1
	1752.5	20375	5	16-QAM	12	0	20.99	2	0-2
	1752.5	20375	5	16-QAM	12	6	20.98	2	0-2
	1752.5	20375	5	16-QAM	12	13	20.91	2	0-2
	1752.5	20375	5	16-QAM	25	0	20.86	2	0-2

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 29 of 75

Table 8-21
Maximum LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth
Representing Capacitive Sensor Not Active

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1711.5	19965	3	QPSK	1	0	22.93	0
	1711.5	19965	3	QPSK	1	7	22.91	0
	1711.5	19965	3	QPSK	1	14	22.90	0
	1711.5	19965	3	QPSK	8	0	21.93	0-1
	1711.5	19965	3	QPSK	8	4	22.03	1
	1711.5	19965	3	QPSK	8	7	22.05	1
	1711.5	19965	3	QPSK	15	0	22.06	1
	1711.5	19965	3	16-QAM	1	0	21.69	0-1
	1711.5	19965	3	16-QAM	1	7	21.71	1
	1711.5	19965	3	16-QAM	1	14	21.67	0-1
	1711.5	19965	3	16-QAM	8	0	21.01	0-2
	1711.5	19965	3	16-QAM	8	4	21.06	2
	1711.5	19965	3	16-QAM	8	7	21.05	2
	1711.5	19965	3	16-QAM	15	0	21.04	2
	1711.5	19965	3	16-QAM	15	0	21.04	2
Mid	1732.5	20175	3	QPSK	1	0	23.05	0
	1732.5	20175	3	QPSK	1	7	22.93	0
	1732.5	20175	3	QPSK	1	14	23.03	0
	1732.5	20175	3	QPSK	8	0	22.04	0-1
	1732.5	20175	3	QPSK	8	4	22.08	1
	1732.5	20175	3	QPSK	8	7	21.99	1
	1732.5	20175	3	QPSK	15	0	22.06	1
	1732.5	20175	3	16-QAM	1	0	21.82	0-1
	1732.5	20175	3	16-QAM	1	7	21.75	1
	1732.5	20175	3	16-QAM	1	14	21.80	1
	1732.5	20175	3	16-QAM	8	0	20.81	0-2
	1732.5	20175	3	16-QAM	8	4	20.86	2
	1732.5	20175	3	16-QAM	8	7	20.76	2
	1732.5	20175	3	16-QAM	15	0	21.05	2
	1732.5	20175	3	16-QAM	15	0	21.05	2
	1732.5	20175	3	16-QAM	15	0	21.05	2
High	1753.5	20385	3	QPSK	1	0	22.83	0
	1753.5	20385	3	QPSK	1	7	22.67	0
	1753.5	20385	3	QPSK	1	14	22.72	0
	1753.5	20385	3	QPSK	8	0	21.89	0-1
	1753.5	20385	3	QPSK	8	4	21.80	1
	1753.5	20385	3	QPSK	8	7	21.79	1
	1753.5	20385	3	QPSK	15	0	21.78	1
	1753.5	20385	3	16-QAM	1	0	22.09	1
	1753.5	20385	3	16-QAM	1	7	21.99	1
	1753.5	20385	3	16-QAM	1	14	21.96	1
	1753.5	20385	3	16-QAM	8	0	20.83	0-2
	1753.5	20385	3	16-QAM	8	4	20.66	2
	1753.5	20385	3	16-QAM	8	7	20.70	2
	1753.5	20385	3	16-QAM	15	0	20.85	2
	1753.5	20385	3	16-QAM	15	0	20.85	2
	1753.5	20385	3	16-QAM	15	0	20.85	2

Table 8-22
Maximum LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth
Representing Capacitive Sensor Not Active

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1710.7	19957	1.4	QPSK	1	0	22.90	0
	1710.7	19957	1.4	QPSK	1	2	22.82	0
	1710.7	19957	1.4	QPSK	1	5	22.84	0
	1710.7	19957	1.4	QPSK	3	0	22.94	0
	1710.7	19957	1.4	QPSK	3	2	22.96	0
	1710.7	19957	1.4	QPSK	3	3	22.95	0
	1710.7	19957	1.4	QPSK	6	0	21.93	0-1
	1710.7	19957	1.4	16-QAM	1	0	21.65	1
	1710.7	19957	1.4	16-QAM	1	2	21.66	1
	1710.7	19957	1.4	16-QAM	1	5	21.63	1
	1710.7	19957	1.4	16-QAM	3	0	21.93	1
	1710.7	19957	1.4	16-QAM	3	2	21.93	1
	1710.7	19957	1.4	16-QAM	3	3	21.95	1
	1710.7	19957	1.4	16-QAM	6	0	20.83	2
	1710.7	19957	1.4	16-QAM	6	0	20.83	2
	1710.7	19957	1.4	16-QAM	6	0	20.83	2
Mid	1732.5	20175	1.4	QPSK	1	0	22.98	0
	1732.5	20175	1.4	QPSK	1	2	22.92	0
	1732.5	20175	1.4	QPSK	1	5	22.83	0
	1732.5	20175	1.4	QPSK	3	0	22.89	0
	1732.5	20175	1.4	QPSK	3	2	22.83	0
	1732.5	20175	1.4	QPSK	3	3	22.86	0
	1732.5	20175	1.4	QPSK	6	0	21.91	1
	1732.5	20175	1.4	16-QAM	1	0	21.73	1
	1732.5	20175	1.4	16-QAM	1	2	21.72	1
	1732.5	20175	1.4	16-QAM	1	5	21.61	1
	1732.5	20175	1.4	16-QAM	3	0	21.93	1
	1732.5	20175	1.4	16-QAM	3	2	21.82	1
	1732.5	20175	1.4	16-QAM	3	3	21.81	1
	1732.5	20175	1.4	16-QAM	6	0	20.82	2
	1732.5	20175	1.4	16-QAM	6	0	20.82	2
	1732.5	20175	1.4	16-QAM	6	0	20.82	2
High	1754.3	20393	1.4	QPSK	1	0	22.92	0
	1754.3	20393	1.4	QPSK	1	2	22.85	0
	1754.3	20393	1.4	QPSK	1	5	22.96	0
	1754.3	20393	1.4	QPSK	3	0	22.82	0
	1754.3	20393	1.4	QPSK	3	2	22.78	0
	1754.3	20393	1.4	QPSK	3	3	22.80	0
	1754.3	20393	1.4	QPSK	6	0	21.81	1
	1754.3	20393	1.4	16-QAM	1	0	21.51	1
	1754.3	20393	1.4	16-QAM	1	2	21.52	1
	1754.3	20393	1.4	16-QAM	1	5	21.50	1
	1754.3	20393	1.4	16-QAM	3	0	21.73	1
	1754.3	20393	1.4	16-QAM	3	2	21.71	1
	1754.3	20393	1.4	16-QAM	3	3	21.74	1
	1754.3	20393	1.4	16-QAM	6	0	20.83	2
	1754.3	20393	1.4	16-QAM	6	0	20.83	2
	1754.3	20393	1.4	16-QAM	6	0	20.83	2

Table 8-23
Reduced LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Mid	1732.5	20175	20	QPSK	1	0	15.05	0	0
	1732.5	20175	20	QPSK	1	50	15.06	0	0
	1732.5	20175	20	QPSK	1	99	14.90	0	0
	1732.5	20175	20	QPSK	50	0	14.98	0	0-1
	1732.5	20175	20	QPSK	50	25	14.92	0	0-1
	1732.5	20175	20	QPSK	50	50	14.87	0	0-1
	1732.5	20175	20	QPSK	100	0	14.97	0	0-1
	1732.5	20175	20	16QAM	1	0	15.02	0	0-1
	1732.5	20175	20	16QAM	1	50	15.01	0	0-1
	1732.5	20175	20	16QAM	1	99	14.89	0	0-1
	1732.5	20175	20	16QAM	50	0	14.98	0	0-2
	1732.5	20175	20	16QAM	50	25	14.97	0	0-2
	1732.5	20175	20	16QAM	50	50	14.85	0	0-2
	1732.5	20175	20	16QAM	100	0	14.90	0	0-2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-24
Reduced LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1717.5	20025	15	QPSK	1	0	14.99	0	0
	1717.5	20025	15	QPSK	1	36	14.96	0	0
	1717.5	20025	15	QPSK	1	74	15.05	0	0
	1717.5	20025	15	QPSK	36	0	14.95	0	0-1
	1717.5	20025	15	QPSK	36	18	15.01	0	0-1
	1717.5	20025	15	QPSK	36	37	14.93	0	0-1
	1717.5	20025	15	QPSK	75	0	14.97	0	0-1
	1717.5	20025	15	16QAM	1	0	14.64	0	0-1
	1717.5	20025	15	16QAM	1	36	14.78	0	0-1
	1717.5	20025	15	16QAM	1	74	14.85	0	0-1
	1717.5	20025	15	16QAM	36	0	14.90	0	0-2
	1717.5	20025	15	16QAM	36	18	14.85	0	0-2
	1717.5	20025	15	16QAM	36	37	14.89	0	0-2
	1717.5	20025	15	16QAM	75	0	15.02	0	0-2
Mid	1732.5	20175	15	QPSK	1	0	14.86	0	0
	1732.5	20175	15	QPSK	1	36	14.82	0	0
	1732.5	20175	15	QPSK	1	74	14.79	0	0
	1732.5	20175	15	QPSK	36	0	14.94	0	0-1
	1732.5	20175	15	QPSK	36	18	14.96	0	0-1
	1732.5	20175	15	QPSK	36	37	14.91	0	0-1
	1732.5	20175	15	QPSK	75	0	14.90	0	0-1
	1732.5	20175	15	16QAM	1	0	15.11	0	0-1
	1732.5	20175	15	16QAM	1	36	15.15	0	0-1
	1732.5	20175	15	16QAM	1	74	15.03	0	0-1
	1732.5	20175	15	16QAM	36	0	14.95	0	0-2
	1732.5	20175	15	16QAM	36	18	14.86	0	0-2
	1732.5	20175	15	16QAM	36	37	14.88	0	0-2
	1732.5	20175	15	16QAM	75	0	14.94	0	0-2
High	1747.5	20325	15	QPSK	1	0	15.03	0	0
	1747.5	20325	15	QPSK	1	36	15.04	0	0
	1747.5	20325	15	QPSK	1	74	14.94	0	0
	1747.5	20325	15	QPSK	36	0	14.82	0	0-1
	1747.5	20325	15	QPSK	36	18	14.87	0	0-1
	1747.5	20325	15	QPSK	36	37	14.84	0	0-1
	1747.5	20325	15	QPSK	75	0	14.88	0	0-1
	1747.5	20325	15	16QAM	1	0	14.74	0	0-1
	1747.5	20325	15	16QAM	1	36	15.04	0	0-1
	1747.5	20325	15	16QAM	1	74	14.76	0	0-1
	1747.5	20325	15	16QAM	36	0	14.96	0	0-2
	1747.5	20325	15	16QAM	36	18	14.98	0	0-2
	1747.5	20325	15	16QAM	36	37	14.91	0	0-2
	1747.5	20325	15	16QAM	75	0	14.93	0	0-2

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 31 of 75

Table 8-25
Reduced LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1715	20000	10	QPSK	1	0	14.81	0	0
	1715	20000	10	QPSK	1	25	14.79	0	0
	1715	20000	10	QPSK	1	49	14.84	0	0
	1715	20000	10	QPSK	25	0	14.92	0	0-1
	1715	20000	10	QPSK	25	12	14.79	0	0-1
	1715	20000	10	QPSK	25	25	14.87	0	0-1
	1715	20000	10	QPSK	50	0	14.96	0	0-1
	1715	20000	10	16QAM	1	0	14.66	0	0-1
	1715	20000	10	16QAM	1	25	14.56	0	0-1
	1715	20000	10	16QAM	1	49	14.58	0	0-1
	1715	20000	10	16QAM	25	0	14.83	0	0-2
	1715	20000	10	16QAM	25	12	14.88	0	0-2
	1715	20000	10	16QAM	25	25	14.82	0	0-2
	1715	20000	10	16QAM	50	0	14.92	0	0-2
	1732.5	20175	10	QPSK	1	0	14.89	0	0
	1732.5	20175	10	QPSK	1	25	14.87	0	0
	1732.5	20175	10	QPSK	1	49	14.73	0	0
Mid	1732.5	20175	10	QPSK	25	0	15.02	0	0-1
	1732.5	20175	10	QPSK	25	12	14.96	0	0-1
	1732.5	20175	10	QPSK	25	25	14.93	0	0-1
	1732.5	20175	10	QPSK	50	0	14.88	0	0-1
	1732.5	20175	10	16QAM	1	0	15.21	0	0-1
	1732.5	20175	10	16QAM	1	25	15.20	0	0-1
	1732.5	20175	10	16QAM	1	49	15.12	0	0-1
	1732.5	20175	10	16QAM	25	0	14.97	0	0-2
	1732.5	20175	10	16QAM	25	12	14.91	0	0-2
	1732.5	20175	10	16QAM	25	25	14.88	0	0-2
	1732.5	20175	10	16QAM	50	0	14.93	0	0-2
High	1750	20350	10	QPSK	1	0	14.87	0	0
	1750	20350	10	QPSK	1	25	14.82	0	0
	1750	20350	10	QPSK	1	49	14.92	0	0
	1750	20350	10	QPSK	25	0	14.76	0	0-1
	1750	20350	10	QPSK	25	12	14.91	0	0-1
	1750	20350	10	QPSK	25	25	14.94	0	0-1
	1750	20350	10	QPSK	50	0	14.86	0	0-1
	1750	20350	10	16QAM	1	0	14.62	0	0-1
	1750	20350	10	16QAM	1	25	14.62	0	0-1
	1750	20350	10	16QAM	1	49	14.65	0	0-1
	1750	20350	10	16QAM	25	0	14.92	0	0-2
	1750	20350	10	16QAM	25	12	14.81	0	0-2
	1750	20350	10	16QAM	25	25	14.91	0	0-2
	1750	20350	10	16QAM	50	0	14.87	0	0-2

Table 8-26
Reduced LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1712.5	19975	5	QPSK	1	0	15.04	0	0
	1712.5	19975	5	QPSK	1	12	14.97	0	0
	1712.5	19975	5	QPSK	1	24	15.06	0	0
	1712.5	19975	5	QPSK	12	0	14.89	0	0-1
	1712.5	19975	5	QPSK	12	6	14.92	0	0-1
	1712.5	19975	5	QPSK	12	13	14.95	0	0-1
	1712.5	19975	5	QPSK	25	0	14.88	0	0-1
	1712.5	19975	5	16-QAM	1	0	14.88	0	0-1
	1712.5	19975	5	16-QAM	1	12	14.89	0	0-1
	1712.5	19975	5	16-QAM	1	24	14.91	0	0-1
	1712.5	19975	5	16-QAM	12	0	14.86	0	0-2
	1712.5	19975	5	16-QAM	12	6	14.89	0	0-2
	1712.5	19975	5	16-QAM	12	13	14.84	0	0-2
	1712.5	19975	5	16-QAM	25	0	14.74	0	0-2
Mid	1732.5	20175	5	QPSK	1	0	14.97	0	0
	1732.5	20175	5	QPSK	1	12	15.07	0	0
	1732.5	20175	5	QPSK	1	24	15.06	0	0
	1732.5	20175	5	QPSK	12	0	14.93	0	0-1
	1732.5	20175	5	QPSK	12	6	15.02	0	0-1
	1732.5	20175	5	QPSK	12	13	15.01	0	0-1
	1732.5	20175	5	QPSK	25	0	14.94	0	0-1
	1732.5	20175	5	16-QAM	1	0	14.87	0	0-1
	1732.5	20175	5	16-QAM	1	12	14.87	0	0-1
	1732.5	20175	5	16-QAM	1	24	14.88	0	0-1
	1732.5	20175	5	16-QAM	12	0	15.03	0	0-2
	1732.5	20175	5	16-QAM	12	6	14.99	0	0-2
	1732.5	20175	5	16-QAM	12	13	15.07	0	0-2
	1732.5	20175	5	16-QAM	25	0	14.97	0	0-2
High	1752.5	20375	5	QPSK	1	0	14.71	0	0
	1752.5	20375	5	QPSK	1	12	14.89	0	0
	1752.5	20375	5	QPSK	1	24	14.78	0	0
	1752.5	20375	5	QPSK	12	0	15.01	0	0-1
	1752.5	20375	5	QPSK	12	6	14.95	0	0-1
	1752.5	20375	5	QPSK	12	13	14.89	0	0-1
	1752.5	20375	5	QPSK	25	0	14.97	0	0-1
	1752.5	20375	5	16-QAM	1	0	14.56	0	0-1
	1752.5	20375	5	16-QAM	1	12	14.63	0	0-1
	1752.5	20375	5	16-QAM	1	24	14.66	0	0-1
	1752.5	20375	5	16-QAM	12	0	15.03	0	0-2
	1752.5	20375	5	16-QAM	12	6	15.05	0	0-2
	1752.5	20375	5	16-QAM	12	13	14.94	0	0-2
	1752.5	20375	5	16-QAM	25	0	14.89	0	0-2

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 32 of 75

Table 8-27
Reduced LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth
Representing Capacitive Sensor Active

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1711.5	19965	3	QPSK	1	0	15.26	0
	1711.5	19965	3	QPSK	1	7	15.29	0
	1711.5	19965	3	QPSK	1	14	15.28	0
	1711.5	19965	3	QPSK	8	0	15.19	0
	1711.5	19965	3	QPSK	8	4	15.22	0
	1711.5	19965	3	QPSK	8	7	15.20	0
	1711.5	19965	3	QPSK	15	0	15.24	0
	1711.5	19965	3	16-QAM	1	0	14.91	0
	1711.5	19965	3	16-QAM	1	7	14.88	0
	1711.5	19965	3	16-QAM	1	14	14.92	0
	1711.5	19965	3	16-QAM	8	0	14.59	0
	1711.5	19965	3	16-QAM	8	4	15.08	0
	1711.5	19965	3	16-QAM	8	7	14.61	0
	1711.5	19965	3	16-QAM	15	0	14.61	0
	1711.5	19965	3	16-QAM	15	0	14.61	0
	1711.5	19965	3	16-QAM	15	0	14.61	0
Mid	1732.5	20175	3	QPSK	1	0	15.20	0
	1732.5	20175	3	QPSK	1	7	15.26	0
	1732.5	20175	3	QPSK	1	14	15.21	0
	1732.5	20175	3	QPSK	8	0	15.36	0
	1732.5	20175	3	QPSK	8	4	15.23	0
	1732.5	20175	3	QPSK	8	7	15.31	0
	1732.5	20175	3	QPSK	15	0	15.28	0
	1732.5	20175	3	16-QAM	1	0	14.52	0
	1732.5	20175	3	16-QAM	1	7	14.73	0
	1732.5	20175	3	16-QAM	1	14	14.83	0
	1732.5	20175	3	16-QAM	8	0	14.55	0
	1732.5	20175	3	16-QAM	8	4	15.29	0
	1732.5	20175	3	16-QAM	8	7	14.73	0
	1732.5	20175	3	16-QAM	15	0	14.52	0
	1732.5	20175	3	16-QAM	15	0	14.52	0
	1732.5	20175	3	16-QAM	15	0	14.52	0
High	1753.5	20385	3	QPSK	1	0	14.98	0
	1753.5	20385	3	QPSK	1	7	14.88	0
	1753.5	20385	3	QPSK	1	14	14.99	0
	1753.5	20385	3	QPSK	8	0	15.15	0
	1753.5	20385	3	QPSK	8	4	14.96	0
	1753.5	20385	3	QPSK	8	7	15.04	0
	1753.5	20385	3	QPSK	15	0	14.99	0
	1753.5	20385	3	16-QAM	1	0	14.60	0
	1753.5	20385	3	16-QAM	1	7	14.57	0
	1753.5	20385	3	16-QAM	1	14	14.55	0
	1753.5	20385	3	16-QAM	8	0	15.03	0
	1753.5	20385	3	16-QAM	8	4	14.94	0
	1753.5	20385	3	16-QAM	8	7	14.92	0
	1753.5	20385	3	16-QAM	15	0	14.90	0
	1753.5	20385	3	16-QAM	15	0	14.90	0
	1753.5	20385	3	16-QAM	15	0	14.90	0

Table 8-28
Reduced LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth
Representing Capacitive Sensor Active

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1710.7	19957	1.4	QPSK	1	0	15.08	0
	1710.7	19957	1.4	QPSK	1	2	15.05	0
	1710.7	19957	1.4	QPSK	1	5	15.13	0
	1710.7	19957	1.4	QPSK	3	0	15.14	0
	1710.7	19957	1.4	QPSK	3	2	15.20	0
	1710.7	19957	1.4	QPSK	3	3	15.12	0
	1710.7	19957	1.4	QPSK	6	0	15.13	0
	1710.7	19957	1.4	16-QAM	1	0	15.10	0
	1710.7	19957	1.4	16-QAM	1	2	15.29	0
	1710.7	19957	1.4	16-QAM	1	5	15.33	0
	1710.7	19957	1.4	16-QAM	3	0	15.28	0
	1710.7	19957	1.4	16-QAM	3	2	15.30	0
	1710.7	19957	1.4	16-QAM	3	3	15.25	0
	1710.7	19957	1.4	16-QAM	6	0	15.17	0
	1710.7	19957	1.4	16-QAM	6	0	15.17	0
	1710.7	19957	1.4	16-QAM	6	0	15.17	0
Mid	1732.5	20175	1.4	QPSK	1	0	15.15	0
	1732.5	20175	1.4	QPSK	1	2	15.10	0
	1732.5	20175	1.4	QPSK	1	5	15.07	0
	1732.5	20175	1.4	QPSK	3	0	15.14	0
	1732.5	20175	1.4	QPSK	3	2	15.04	0
	1732.5	20175	1.4	QPSK	3	3	14.98	0
	1732.5	20175	1.4	QPSK	6	0	14.96	0
	1732.5	20175	1.4	16-QAM	1	0	15.04	0
	1732.5	20175	1.4	16-QAM	1	2	15.08	0
	1732.5	20175	1.4	16-QAM	1	5	14.89	0
	1732.5	20175	1.4	16-QAM	3	0	15.16	0
	1732.5	20175	1.4	16-QAM	3	2	15.10	0
	1732.5	20175	1.4	16-QAM	3	3	15.07	0
	1732.5	20175	1.4	16-QAM	6	0	15.02	0
	1732.5	20175	1.4	16-QAM	6	0	15.02	0
	1732.5	20175	1.4	16-QAM	6	0	15.02	0
High	1754.3	20393	1.4	QPSK	1	0	14.91	0
	1754.3	20393	1.4	QPSK	1	2	14.94	0
	1754.3	20393	1.4	QPSK	1	5	14.93	0
	1754.3	20393	1.4	QPSK	3	0	14.99	0
	1754.3	20393	1.4	QPSK	3	2	14.99	0
	1754.3	20393	1.4	QPSK	3	3	15.00	0
	1754.3	20393	1.4	QPSK	6	0	15.02	0
	1754.3	20393	1.4	16-QAM	1	0	15.43	0
	1754.3	20393	1.4	16-QAM	1	2	15.30	0
	1754.3	20393	1.4	16-QAM	1	5	15.43	0
	1754.3	20393	1.4	16-QAM	3	0	15.34	0
	1754.3	20393	1.4	16-QAM	3	2	15.21	0
	1754.3	20393	1.4	16-QAM	3	3	15.16	0
	1754.3	20393	1.4	16-QAM	6	0	14.81	0
	1754.3	20393	1.4	16-QAM	6	0	14.81	0
	1754.3	20393	1.4	16-QAM	6	0	14.81	0

8.3.4 LTE Band 2 (PCS)

Table 8-29
Maximum LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1860	18700	20	QPSK	1	0	23.47	0	0
	1860	18700	20	QPSK	1	50	23.50	0	0
	1860	18700	20	QPSK	1	99	23.48	0	0
	1860	18700	20	QPSK	50	0	22.23	1	0-1
	1860	18700	20	QPSK	50	25	22.16	1	0-1
	1860	18700	20	QPSK	50	50	22.18	1	0-1
	1860	18700	20	QPSK	100	0	22.17	1	0-1
	1860	18700	20	16QAM	1	0	22.47	1	0-1
	1860	18700	20	16QAM	1	50	22.48	1	0-1
	1860	18700	20	16QAM	1	99	22.45	1	0-1
	1860	18700	20	16QAM	50	0	21.22	2	0-2
	1860	18700	20	16QAM	50	25	21.13	2	0-2
	1860	18700	20	16QAM	50	50	21.25	2	0-2
	1860	18700	20	16QAM	100	0	21.21	2	0-2
	1880.0	18900	20	QPSK	1	0	23.49	0	0
	1880.0	18900	20	QPSK	1	50	23.44	0	0
	1880.0	18900	20	QPSK	1	99	23.24	0	0
Mid	1880.0	18900	20	QPSK	50	0	22.21	1	0-1
	1880.0	18900	20	QPSK	50	25	22.22	1	0-1
	1880.0	18900	20	QPSK	50	50	22.12	1	0-1
	1880.0	18900	20	QPSK	100	0	22.21	1	0-1
	1880.0	18900	20	16QAM	1	0	22.46	1	0-1
	1880.0	18900	20	16QAM	1	50	22.43	1	0-1
	1880.0	18900	20	16QAM	1	99	22.24	1	0-1
	1880.0	18900	20	16QAM	50	0	21.14	2	0-2
	1880.0	18900	20	16QAM	50	25	21.21	2	0-2
	1880.0	18900	20	16QAM	50	50	21.09	2	0-2
	1880.0	18900	20	16QAM	100	0	21.23	2	0-2
High	1900	19100	20	QPSK	1	0	23.08	0	0
	1900	19100	20	QPSK	1	50	22.89	0	0
	1900	19100	20	QPSK	1	99	22.78	0	0
	1900	19100	20	QPSK	50	0	21.78	1	0-1
	1900	19100	20	QPSK	50	25	21.71	1	0-1
	1900	19100	20	QPSK	50	50	21.69	1	0-1
	1900	19100	20	QPSK	100	0	21.73	1	0-1
	1900	19100	20	16QAM	1	0	22.02	1	0-1
	1900	19100	20	16QAM	1	50	21.78	1	0-1
	1900	19100	20	16QAM	1	99	21.81	1	0-1
	1900	19100	20	16QAM	50	0	20.85	2	0-2
	1900	19100	20	16QAM	50	25	20.72	2	0-2
	1900	19100	20	16QAM	50	50	20.67	2	0-2
	1900	19100	20	16QAM	100	0	20.73	2	0-2

Table 8-30
Maximum LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1857.5	18675	15	QPSK	1	0	23.49	0	0
	1857.5	18675	15	QPSK	1	36	23.48	0	0
	1857.5	18675	15	QPSK	1	74	23.47	0	0
	1857.5	18675	15	QPSK	36	0	22.21	1	0-1
	1857.5	18675	15	QPSK	36	18	22.20	1	0-1
	1857.5	18675	15	QPSK	36	37	22.19	1	0-1
	1857.5	18675	15	QPSK	75	0	22.21	1	0-1
	1857.5	18675	15	16QAM	1	0	22.47	1	0-1
	1857.5	18675	15	16QAM	1	36	22.48	1	0-1
	1857.5	18675	15	16QAM	1	74	22.42	1	0-1
	1857.5	18675	15	16QAM	36	0	21.34	2	0-2
	1857.5	18675	15	16QAM	36	18	21.31	2	0-2
	1857.5	18675	15	16QAM	36	37	21.28	2	0-2
	1857.5	18675	15	16QAM	75	0	21.23	2	0-2
Mid	1880.0	18900	15	QPSK	1	0	23.43	0	0
	1880.0	18900	15	QPSK	1	36	23.38	0	0
	1880.0	18900	15	QPSK	1	74	23.23	0	0
	1880.0	18900	15	QPSK	36	0	22.33	1	0-1
	1880.0	18900	15	QPSK	36	18	22.25	1	0-1
	1880.0	18900	15	QPSK	36	37	22.10	1	0-1
	1880.0	18900	15	QPSK	75	0	22.22	1	0-1
	1880.0	18900	15	16QAM	1	0	22.48	1	0-1
	1880.0	18900	15	16QAM	1	36	22.45	1	0-1
	1880.0	18900	15	16QAM	1	74	22.23	1	0-1
	1880.0	18900	15	16QAM	36	0	21.28	2	0-2
	1880.0	18900	15	16QAM	36	18	21.23	2	0-2
	1880.0	18900	15	16QAM	36	37	21.12	2	0-2
	1880.0	18900	15	16QAM	75	0	21.18	2	0-2
High	1902.5	19125	15	QPSK	1	0	22.95	0	0
	1902.5	19125	15	QPSK	1	36	22.84	0	0
	1902.5	19125	15	QPSK	1	74	22.60	0	0
	1902.5	19125	15	QPSK	36	0	21.80	1	0-1
	1902.5	19125	15	QPSK	36	18	21.71	1	0-1
	1902.5	19125	15	QPSK	36	37	21.67	1	0-1
	1902.5	19125	15	QPSK	75	0	21.63	1	0-1
	1902.5	19125	15	16QAM	1	0	21.93	1	0-1
	1902.5	19125	15	16QAM	1	36	21.84	1	0-1
	1902.5	19125	15	16QAM	1	74	21.68	1	0-1
	1902.5	19125	15	16QAM	36	0	20.79	2	0-2
	1902.5	19125	15	16QAM	36	18	20.73	2	0-2
	1902.5	19125	15	16QAM	36	37	20.67	2	0-2
	1902.5	19125	15	16QAM	75	0	20.63	2	0-2

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 34 of 75

Table 8-31
Maximum LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1855	18650	10	QPSK	1	0	23.49	0	0
	1855	18650	10	QPSK	1	25	23.40	0	0
	1855	18650	10	QPSK	1	49	23.47	0	0
	1855	18650	10	QPSK	25	0	22.30	1	0-1
	1855	18650	10	QPSK	25	12	22.27	1	0-1
	1855	18650	10	QPSK	25	25	22.32	1	0-1
	1855	18650	10	QPSK	50	0	22.18	1	0-1
	1855	18650	10	16QAM	1	0	22.47	1	0-1
	1855	18650	10	16QAM	1	25	22.43	1	0-1
	1855	18650	10	16QAM	1	49	22.49	1	0-1
	1855	18650	10	16QAM	25	0	21.34	2	0-2
	1855	18650	10	16QAM	25	12	21.37	2	0-2
	1855	18650	10	16QAM	25	25	21.38	2	0-2
	1855	18650	10	16QAM	50	0	21.26	2	0-2
	1880.0	18900	10	QPSK	1	0	23.44	0	0
Mid	1880.0	18900	10	QPSK	1	25	23.40	0	0
	1880.0	18900	10	QPSK	1	49	23.29	0	0
	1880.0	18900	10	QPSK	25	0	22.41	1	0-1
	1880.0	18900	10	QPSK	25	12	22.33	1	0-1
	1880.0	18900	10	QPSK	25	25	22.22	1	0-1
	1880.0	18900	10	QPSK	50	0	22.25	1	0-1
	1880.0	18900	10	16QAM	1	0	22.45	1	0-1
	1880.0	18900	10	16QAM	1	25	22.44	1	0-1
	1880.0	18900	10	16QAM	1	49	22.37	1	0-1
	1880.0	18900	10	16QAM	25	0	21.39	2	0-2
	1880.0	18900	10	16QAM	25	12	21.28	2	0-2
	1880.0	18900	10	16QAM	25	25	21.25	2	0-2
	1880.0	18900	10	16QAM	50	0	21.17	2	0-2
	1905	19150	10	QPSK	1	0	22.73	0	0
	1905	19150	10	QPSK	1	25	22.81	0	0
High	1905	19150	10	QPSK	1	49	22.64	0	0
	1905	19150	10	QPSK	25	0	21.75	1	0-1
	1905	19150	10	QPSK	25	12	21.63	1	0-1
	1905	19150	10	QPSK	25	25	21.69	1	0-1
	1905	19150	10	QPSK	50	0	21.63	1	0-1
	1905	19150	10	16QAM	1	0	21.84	1	0-1
	1905	19150	10	16QAM	1	25	21.81	1	0-1
	1905	19150	10	16QAM	1	49	21.71	1	0-1
	1905	19150	10	16QAM	25	0	20.79	2	0-2
	1905	19150	10	16QAM	25	12	20.62	2	0-2
	1905	19150	10	16QAM	25	25	20.75	2	0-2
	1905	19150	10	16QAM	50	0	20.63	2	0-2

Table 8-32
Maximum LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1852.5	18625	5	QPSK	1	0	23.48	0	0
	1852.5	18625	5	QPSK	1	12	23.44	0	0
	1852.5	18625	5	QPSK	1	24	23.45	0	0
	1852.5	18625	5	QPSK	12	0	22.37	1	0-1
	1852.5	18625	5	QPSK	12	6	22.36	1	0-1
	1852.5	18625	5	QPSK	12	13	22.34	1	0-1
	1852.5	18625	5	QPSK	25	0	22.27	1	0-1
	1852.5	18625	5	16-QAM	1	0	22.47	1	0-1
	1852.5	18625	5	16-QAM	1	12	22.46	1	0-1
	1852.5	18625	5	16-QAM	1	24	22.43	1	0-1
	1852.5	18625	5	16-QAM	12	0	21.47	2	0-2
	1852.5	18625	5	16-QAM	12	6	21.48	2	0-2
	1852.5	18625	5	16-QAM	12	13	21.47	2	0-2
	1852.5	18625	5	16-QAM	25	0	21.37	2	0-2
Mid	1880.0	18900	5	QPSK	1	0	23.40	0	0
	1880.0	18900	5	QPSK	1	12	23.41	0	0
	1880.0	18900	5	QPSK	1	24	23.30	0	0
	1880.0	18900	5	QPSK	12	0	22.44	1	0-1
	1880.0	18900	5	QPSK	12	6	22.33	1	0-1
	1880.0	18900	5	QPSK	12	13	22.32	1	0-1
	1880.0	18900	5	QPSK	25	0	22.32	1	0-1
	1880.0	18900	5	16-QAM	1	0	22.45	1	0-1
	1880.0	18900	5	16-QAM	1	12	22.41	1	0-1
	1880.0	18900	5	16-QAM	1	24	22.32	1	0-1
	1880.0	18900	5	16-QAM	12	0	21.41	2	0-2
	1880.0	18900	5	16-QAM	12	6	21.39	2	0-2
	1880.0	18900	5	16-QAM	12	13	21.38	2	0-2
	1880.0	18900	5	16-QAM	25	0	21.28	2	0-2
High	1907.5	19175	5	QPSK	1	0	22.79	0	0
	1907.5	19175	5	QPSK	1	12	22.72	0	0
	1907.5	19175	5	QPSK	1	24	22.61	0	0
	1907.5	19175	5	QPSK	12	0	21.70	1	0-1
	1907.5	19175	5	QPSK	12	6	21.72	1	0-1
	1907.5	19175	5	QPSK	12	13	21.57	1	0-1
	1907.5	19175	5	QPSK	25	0	21.65	1	0-1
	1907.5	19175	5	16-QAM	1	0	21.83	1	0-1
	1907.5	19175	5	16-QAM	1	12	21.78	1	0-1
	1907.5	19175	5	16-QAM	1	24	21.71	1	0-1
	1907.5	19175	5	16-QAM	12	0	20.82	2	0-2
	1907.5	19175	5	16-QAM	12	6	20.81	2	0-2
	1907.5	19175	5	16-QAM	12	13	20.84	2	0-2
	1907.5	19175	5	16-QAM	25	0	20.71	2	0-2

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 35 of 75

Table 8-33
Maximum LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1851.5	18615	3	QPSK	1	0	23.45	0	0
	1851.5	18615	3	QPSK	1	7	23.46	0	0
	1851.5	18615	3	QPSK	1	14	23.48	0	0
	1851.5	18615	3	QPSK	8	0	22.38	1	0-1
	1851.5	18615	3	QPSK	8	4	22.34	1	0-1
	1851.5	18615	3	QPSK	8	7	22.38	1	0-1
	1851.5	18615	3	QPSK	15	0	22.36	1	0-1
	1851.5	18615	3	16-QAM	1	0	22.45	1	0-1
	1851.5	18615	3	16-QAM	1	7	22.47	1	0-1
	1851.5	18615	3	16-QAM	1	14	22.41	1	0-1
	1851.5	18615	3	16-QAM	8	0	21.35	2	0-2
	1851.5	18615	3	16-QAM	8	4	21.34	2	0-2
	1851.5	18615	3	16-QAM	8	7	21.36	2	0-2
	1851.5	18615	3	16-QAM	15	0	21.41	2	0-2
	1880.0	18900	3	QPSK	1	0	23.44	0	0
Mid	1880.0	18900	3	QPSK	1	7	23.41	0	0
	1880.0	18900	3	QPSK	1	14	23.43	0	0
	1880.0	18900	3	QPSK	8	0	22.35	1	0-1
	1880.0	18900	3	QPSK	8	4	22.39	1	0-1
	1880.0	18900	3	QPSK	8	7	22.41	1	0-1
	1880.0	18900	3	QPSK	15	0	22.36	1	0-1
	1880.0	18900	3	16-QAM	1	0	22.42	1	0-1
	1880.0	18900	3	16-QAM	1	7	22.44	1	0-1
	1880.0	18900	3	16-QAM	1	14	22.37	1	0-1
	1880.0	18900	3	16-QAM	8	0	21.22	2	0-2
	1880.0	18900	3	16-QAM	8	4	21.28	2	0-2
	1880.0	18900	3	16-QAM	8	7	21.30	2	0-2
	1880.0	18900	3	16-QAM	15	0	21.36	2	0-2
	1908.5	19185	3	QPSK	1	0	22.73	0	0
	1908.5	19185	3	QPSK	1	7	22.67	0	0
High	1908.5	19185	3	QPSK	1	14	22.62	0	0
	1908.5	19185	3	QPSK	8	0	21.65	1	0-1
	1908.5	19185	3	QPSK	8	4	21.61	1	0-1
	1908.5	19185	3	QPSK	8	7	21.59	1	0-1
	1908.5	19185	3	QPSK	15	0	21.60	1	0-1
	1908.5	19185	3	16-QAM	1	0	21.78	1	0-1
	1908.5	19185	3	16-QAM	1	7	21.66	1	0-1
	1908.5	19185	3	16-QAM	1	14	21.59	1	0-1
	1908.5	19185	3	16-QAM	8	0	20.65	2	0-2
	1908.5	19185	3	16-QAM	8	4	20.63	2	0-2
	1908.5	19185	3	16-QAM	8	7	20.61	2	0-2
	1908.5	19185	3	16-QAM	15	0	20.68	2	0-2

Table 8-34
Maximum LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth
Representing Capacitive Sensor Not Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1850.7	18607	1.4	QPSK	1	0	23.49	0	0
	1850.7	18607	1.4	QPSK	1	2	23.48	0	0
	1850.7	18607	1.4	QPSK	1	5	23.47	0	0
	1850.7	18607	1.4	QPSK	3	0	23.43	0	0
	1850.7	18607	1.4	QPSK	3	2	23.42	0	0
	1850.7	18607	1.4	QPSK	3	3	23.44	0	0
	1850.7	18607	1.4	QPSK	6	0	22.41	1	0-1
	1850.7	18607	1.4	16-QAM	1	0	22.43	1	0-1
	1850.7	18607	1.4	16-QAM	1	2	22.48	1	0-1
	1850.7	18607	1.4	16-QAM	1	5	22.42	1	0-1
	1850.7	18607	1.4	16-QAM	3	0	22.42	1	0-1
	1850.7	18607	1.4	16-QAM	3	2	22.46	1	0-1
	1850.7	18607	1.4	16-QAM	3	3	22.42	1	0-1
	1850.7	18607	1.4	16-QAM	6	0	21.39	2	0-2
Mid	1880.0	18900	1.4	QPSK	1	0	23.32	0	0
	1880.0	18900	1.4	QPSK	1	2	23.41	0	0
	1880.0	18900	1.4	QPSK	1	5	23.37	0	0
	1880.0	18900	1.4	QPSK	3	0	23.32	0	0
	1880.0	18900	1.4	QPSK	3	2	23.35	0	0
	1880.0	18900	1.4	QPSK	3	3	23.30	0	0
	1880.0	18900	1.4	QPSK	6	0	22.42	1	0-1
	1880.0	18900	1.4	16-QAM	1	0	22.46	1	0-1
	1880.0	18900	1.4	16-QAM	1	2	22.45	1	0-1
	1880.0	18900	1.4	16-QAM	1	5	22.40	1	0-1
	1880.0	18900	1.4	16-QAM	3	0	22.41	1	0-1
	1880.0	18900	1.4	16-QAM	3	2	22.37	1	0-1
	1880.0	18900	1.4	16-QAM	3	3	22.41	1	0-1
	1880.0	18900	1.4	16-QAM	6	0	21.33	2	0-2
High	1909.3	19193	1.4	QPSK	1	0	22.64	0	0
	1909.3	19193	1.4	QPSK	1	2	22.60	0	0
	1909.3	19193	1.4	QPSK	1	5	22.62	0	0
	1909.3	19193	1.4	QPSK	3	0	22.58	0	0
	1909.3	19193	1.4	QPSK	3	2	22.57	0	0
	1909.3	19193	1.4	QPSK	3	3	22.58	0	0
	1909.3	19193	1.4	QPSK	6	0	21.61	1	0-1
	1909.3	19193	1.4	16-QAM	1	0	21.69	1	0-1
	1909.3	19193	1.4	16-QAM	1	2	21.66	1	0-1
	1909.3	19193	1.4	16-QAM	1	5	21.57	1	0-1
	1909.3	19193	1.4	16-QAM	3	0	21.64	1	0-1
	1909.3	19193	1.4	16-QAM	3	2	21.62	1	0-1
	1909.3	19193	1.4	16-QAM	3	3	21.57	1	0-1
	1909.3	19193	1.4	16-QAM	6	0	20.60	2	0-2

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 36 of 75

Table 8-35
Reduced LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1860	18700	20	QPSK	1	0	15.44	0	0
	1860	18700	20	QPSK	1	50	15.00	0	0
	1860	18700	20	QPSK	1	99	15.48	0	0
	1860	18700	20	QPSK	50	0	15.42	0	0-1
	1860	18700	20	QPSK	50	25	15.39	0	0-1
	1860	18700	20	QPSK	50	50	15.38	0	0-1
	1860	18700	20	QPSK	100	0	15.37	0	0-1
	1860	18700	20	16QAM	1	0	15.36	0	0-1
	1860	18700	20	16QAM	1	50	15.48	0	0-1
	1860	18700	20	16QAM	1	99	15.29	0	0-1
	1860	18700	20	16QAM	50	0	15.31	0	0-2
	1860	18700	20	16QAM	50	25	15.18	0	0-2
	1860	18700	20	16QAM	50	50	15.31	0	0-2
	1860	18700	20	16QAM	100	0	15.26	0	0-2
	1880.0	18900	20	QPSK	1	0	15.50	0	0
	1880.0	18900	20	QPSK	1	50	15.46	0	0
Mid	1880.0	18900	20	QPSK	1	99	15.15	0	0
	1880.0	18900	20	QPSK	50	0	15.32	0	0-1
	1880.0	18900	20	QPSK	50	25	15.25	0	0-1
	1880.0	18900	20	QPSK	50	50	15.09	0	0-1
	1880.0	18900	20	QPSK	100	0	15.21	0	0-1
	1880.0	18900	20	16QAM	1	0	15.34	0	0-1
	1880.0	18900	20	16QAM	1	50	15.36	0	0-1
	1880.0	18900	20	16QAM	1	99	15.02	0	0-1
	1880.0	18900	20	16QAM	50	0	15.20	0	0-2
	1880.0	18900	20	16QAM	50	25	15.06	0	0-2
	1880.0	18900	20	16QAM	50	50	15.03	0	0-2
	1880.0	18900	20	16QAM	100	0	15.12	0	0-2
	1900	19100	20	QPSK	1	0	15.06	0	0
	1900	19100	20	QPSK	1	50	14.65	0	0
	1900	19100	20	QPSK	1	99	14.77	0	0
	1900	19100	20	QPSK	50	0	14.86	0	0-1
High	1900	19100	20	QPSK	50	25	14.56	0	0-1
	1900	19100	20	QPSK	50	50	14.58	0	0-1
	1900	19100	20	QPSK	100	0	14.62	0	0-1
	1900	19100	20	16QAM	1	0	14.88	0	0-1
	1900	19100	20	16QAM	1	50	14.61	0	0-1
	1900	19100	20	16QAM	1	99	14.62	0	0-1
	1900	19100	20	16QAM	50	0	14.64	0	0-2
	1900	19100	20	16QAM	50	25	14.54	0	0-2
	1900	19100	20	16QAM	50	50	14.52	0	0-2
	1900	19100	20	16QAM	100	0	14.57	0	0-2

Table 8-36
Reduced LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1857.5	18675	15	QPSK	1	0	15.32	0	0
	1857.5	18675	15	QPSK	1	36	15.49	0	0
	1857.5	18675	15	QPSK	1	74	15.46	0	0
	1857.5	18675	15	QPSK	36	0	15.43	0	0-1
	1857.5	18675	15	QPSK	36	18	15.41	0	0-1
	1857.5	18675	15	QPSK	36	37	15.44	0	0-1
	1857.5	18675	15	QPSK	75	0	15.38	0	0-1
	1857.5	18675	15	16QAM	1	0	15.32	0	0-1
	1857.5	18675	15	16QAM	1	36	15.37	0	0-1
	1857.5	18675	15	16QAM	1	74	15.15	0	0-1
	1857.5	18675	15	16QAM	36	0	15.11	0	0-2
	1857.5	18675	15	16QAM	36	18	15.08	0	0-2
	1857.5	18675	15	16QAM	36	37	15.12	0	0-2
	1857.5	18675	15	16QAM	75	0	15.05	0	0-2
	1880.0	18900	15	QPSK	1	0	15.40	0	0
	1880.0	18900	15	QPSK	1	36	15.39	0	0
Mid	1880.0	18900	15	QPSK	1	74	15.09	0	0
	1880.0	18900	15	QPSK	36	0	15.39	0	0-1
	1880.0	18900	15	QPSK	36	18	15.25	0	0-1
	1880.0	18900	15	QPSK	36	37	15.19	0	0-1
	1880.0	18900	15	QPSK	75	0	15.27	0	0-1
	1880.0	18900	15	16QAM	1	0	15.26	0	0-1
	1880.0	18900	15	16QAM	1	36	15.34	0	0-1
	1880.0	18900	15	16QAM	1	74	15.22	0	0-1
	1880.0	18900	15	16QAM	36	0	15.38	0	0-2
	1880.0	18900	15	16QAM	36	18	15.34	0	0-2
	1880.0	18900	15	16QAM	36	37	15.16	0	0-2
	1880.0	18900	15	16QAM	75	0	15.29	0	0-2
	1902.5	19125	15	QPSK	1	0	14.74	0	0
	1902.5	19125	15	QPSK	1	36	14.71	0	0
	1902.5	19125	15	QPSK	1	74	14.60	0	0
	1902.5	19125	15	QPSK	36	0	14.66	0	0-1
High	1902.5	19125	15	QPSK	36	18	14.70	0	0-1
	1902.5	19125	15	QPSK	36	37	14.61	0	0-1
	1902.5	19125	15	QPSK	75	0	14.66	0	0-1
	1902.5	19125	15	16QAM	1	0	14.64	0	0-1
	1902.5	19125	15	16QAM	1	36	14.59	0	0-1
	1902.5	19125	15	16QAM	1	74	14.66	0	0-1
	1902.5	19125	15	16QAM	36	0	14.72	0	0-2
	1902.5	19125	15	16QAM	36	18	14.61	0	0-2
	1902.5	19125	15	16QAM	36	37	14.70	0	0-2
	1902.5	19125	15	16QAM	75	0	14.86	0	0-2

Table 8-37
Reduced LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1855	18650	10	QPSK	1	0	15.26	0	0
	1855	18650	10	QPSK	1	25	15.49	0	0
	1855	18650	10	QPSK	1	49	15.22	0	0
	1855	18650	10	QPSK	25	0	15.45	0	0-1
	1855	18650	10	QPSK	25	12	15.31	0	0-1
	1855	18650	10	QPSK	25	25	15.46	0	0-1
	1855	18650	10	QPSK	50	0	15.40	0	0-1
	1855	18650	10	16QAM	1	0	15.29	0	0-1
	1855	18650	10	16QAM	1	25	15.37	0	0-1
	1855	18650	10	16QAM	1	49	15.11	0	0-1
	1855	18650	10	16QAM	25	0	15.13	0	0-2
	1855	18650	10	16QAM	25	12	15.13	0	0-2
	1855	18650	10	16QAM	25	25	15.16	0	0-2
	1855	18650	10	16QAM	50	0	15.08	0	0-2
	1880.0	18900	10	QPSK	1	0	15.42	0	0
	1880.0	18900	10	QPSK	1	25	15.32	0	0
Mid	1880.0	18900	10	QPSK	1	49	15.15	0	0
	1880.0	18900	10	QPSK	25	0	15.43	0	0-1
	1880.0	18900	10	QPSK	25	12	15.37	0	0-1
	1880.0	18900	10	QPSK	25	25	15.14	0	0-1
	1880.0	18900	10	QPSK	50	0	15.29	0	0-1
	1880.0	18900	10	16QAM	1	0	15.29	0	0-1
	1880.0	18900	10	16QAM	1	25	15.37	0	0-1
	1880.0	18900	10	16QAM	1	49	15.27	0	0-1
	1880.0	18900	10	16QAM	25	0	15.42	0	0-2
	1880.0	18900	10	16QAM	25	12	15.32	0	0-2
	1880.0	18900	10	16QAM	25	25	15.14	0	0-2
	1880.0	18900	10	16QAM	50	0	15.19	0	0-2
	1905	19150	10	QPSK	1	0	14.70	0	0
	1905	19150	10	QPSK	1	25	14.64	0	0
	1905	19150	10	QPSK	1	49	14.65	0	0
High	1905	19150	10	QPSK	25	0	14.76	0	0-1
	1905	19150	10	QPSK	25	12	14.69	0	0-1
	1905	19150	10	QPSK	25	25	14.72	0	0-1
	1905	19150	10	QPSK	50	0	14.76	0	0-1
	1905	19150	10	16QAM	1	0	14.90	0	0-1
	1905	19150	10	16QAM	1	25	14.84	0	0-1
	1905	19150	10	16QAM	1	49	14.72	0	0-1
	1905	19150	10	16QAM	25	0	14.86	0	0-2
	1905	19150	10	16QAM	25	12	14.69	0	0-2
	1905	19150	10	16QAM	25	25	14.83	0	0-2
	1905	19150	10	16QAM	50	0	14.92	0	0-2

Table 8-38
Reduced LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1852.5	18625	5	QPSK	1	0	15.46	0	0
	1852.5	18625	5	QPSK	1	12	15.45	0	0
	1852.5	18625	5	QPSK	1	24	15.47	0	0
	1852.5	18625	5	QPSK	12	0	15.46	0	0-1
	1852.5	18625	5	QPSK	12	6	15.43	0	0-1
	1852.5	18625	5	QPSK	12	13	15.46	0	0-1
	1852.5	18625	5	QPSK	25	0	15.40	0	0-1
	1852.5	18625	5	16-QAM	1	0	15.34	0	0-1
	1852.5	18625	5	16-QAM	1	12	15.30	0	0-1
	1852.5	18625	5	16-QAM	1	24	15.27	0	0-1
	1852.5	18625	5	16-QAM	12	0	15.18	0	0-2
	1852.5	18625	5	16-QAM	12	6	15.27	0	0-2
	1852.5	18625	5	16-QAM	12	13	15.19	0	0-2
	1852.5	18625	5	16-QAM	25	0	15.23	0	0-2
	1880.0	18900	5	QPSK	1	0	15.40	0	0
	1880.0	18900	5	QPSK	1	12	15.34	0	0
Mid	1880.0	18900	5	QPSK	1	24	15.21	0	0
	1880.0	18900	5	QPSK	12	0	15.40	0	0-1
	1880.0	18900	5	QPSK	12	6	15.30	0	0-1
	1880.0	18900	5	QPSK	12	13	15.25	0	0-1
	1880.0	18900	5	QPSK	25	0	15.24	0	0-1
	1880.0	18900	5	16-QAM	1	0	15.45	0	0-1
	1880.0	18900	5	16-QAM	1	12	15.43	0	0-1
	1880.0	18900	5	16-QAM	1	24	15.23	0	0-1
	1880.0	18900	5	16-QAM	12	0	15.40	0	0-2
	1880.0	18900	5	16-QAM	12	6	15.42	0	0-2
	1880.0	18900	5	16-QAM	12	13	15.25	0	0-2
	1880.0	18900	5	16-QAM	25	0	15.28	0	0-2
	1907.5	19175	5	QPSK	1	0	14.78	0	0
	1907.5	19175	5	QPSK	1	12	14.63	0	0
	1907.5	19175	5	QPSK	1	24	14.72	0	0
High	1907.5	19175	5	QPSK	12	0	14.62	0	0-1
	1907.5	19175	5	QPSK	12	6	14.72	0	0-1
	1907.5	19175	5	QPSK	12	13	14.66	0	0-1
	1907.5	19175	5	QPSK	25	0	14.73	0	0-1
	1907.5	19175	5	16-QAM	1	0	14.93	0	0-1
	1907.5	19175	5	16-QAM	1	12	14.72	0	0-1
	1907.5	19175	5	16-QAM	1	24	14.69	0	0-1
	1907.5	19175	5	16-QAM	12	0	15.07	0	0-2
	1907.5	19175	5	16-QAM	12	6	14.98	0	0-2
	1907.5	19175	5	16-QAM	12	13	14.85	0	0-2
	1907.5	19175	5	16-QAM	25	0	14.87	0	0-2

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 38 of 75

Table 8-39
Reduced LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1851.5	18615	3	QPSK	1	0	15.47	0	0
	1851.5	18615	3	QPSK	1	7	15.49	0	0
	1851.5	18615	3	QPSK	1	14	15.46	0	0
	1851.5	18615	3	QPSK	8	0	15.41	0	0-1
	1851.5	18615	3	QPSK	8	4	15.47	0	0-1
	1851.5	18615	3	QPSK	8	7	15.44	0	0-1
	1851.5	18615	3	QPSK	15	0	15.47	0	0-1
	1851.5	18615	3	16-QAM	1	0	15.37	0	0-1
	1851.5	18615	3	16-QAM	1	7	15.40	0	0-1
	1851.5	18615	3	16-QAM	1	14	15.22	0	0-1
	1851.5	18615	3	16-QAM	8	0	15.20	0	0-2
	1851.5	18615	3	16-QAM	8	4	15.12	0	0-2
	1851.5	18615	3	16-QAM	8	7	15.19	0	0-2
	1851.5	18615	3	16-QAM	15	0	15.27	0	0-2
	1880.0	18900	3	QPSK	1	0	15.38	0	0
	1880.0	18900	3	QPSK	1	7	15.33	0	0
	1880.0	18900	3	QPSK	1	14	15.30	0	0
Mid	1880.0	18900	3	QPSK	8	0	15.24	0	0-1
	1880.0	18900	3	QPSK	8	4	15.33	0	0-1
	1880.0	18900	3	QPSK	8	7	15.38	0	0-1
	1880.0	18900	3	QPSK	15	0	15.25	0	0-1
	1880.0	18900	3	16-QAM	1	0	15.46	0	0-1
	1880.0	18900	3	16-QAM	1	7	15.41	0	0-1
	1880.0	18900	3	16-QAM	1	14	15.35	0	0-1
	1880.0	18900	3	16-QAM	8	0	15.22	0	0-2
	1880.0	18900	3	16-QAM	8	4	15.34	0	0-2
	1880.0	18900	3	16-QAM	8	7	15.29	0	0-2
	1880.0	18900	3	16-QAM	15	0	15.39	0	0-2
	1908.5	19185	3	QPSK	1	0	14.80	0	0
	1908.5	19185	3	QPSK	1	7	14.64	0	0
	1908.5	19185	3	QPSK	1	14	14.62	0	0
	1908.5	19185	3	QPSK	8	0	14.82	0	0-1
	1908.5	19185	3	QPSK	8	4	14.67	0	0-1
	1908.5	19185	3	QPSK	8	7	14.59	0	0-1
	1908.5	19185	3	QPSK	15	0	14.63	0	0-1
	1908.5	19185	3	16-QAM	1	0	14.85	0	0-1
High	1908.5	19185	3	16-QAM	1	7	14.74	0	0-1
	1908.5	19185	3	16-QAM	1	14	14.69	0	0-1
	1908.5	19185	3	16-QAM	8	0	14.76	0	0-2
	1908.5	19185	3	16-QAM	8	4	14.71	0	0-2
	1908.5	19185	3	16-QAM	8	7	14.62	0	0-2
	1908.5	19185	3	16-QAM	15	0	14.75	0	0-2

Table 8-40
Reduced LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth
Representing Capacitive Sensor Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	Target MPR [dB]	MPR Allowed per 3GPP [dB]
Low	1850.7	18607	1.4	QPSK	1	0	15.48	0	0
	1850.7	18607	1.4	QPSK	1	2	15.49	0	0
	1850.7	18607	1.4	QPSK	1	5	15.46	0	0
	1850.7	18607	1.4	QPSK	3	0	15.48	0	0
	1850.7	18607	1.4	QPSK	3	2	15.50	0	0
	1850.7	18607	1.4	QPSK	3	3	15.49	0	0
	1850.7	18607	1.4	QPSK	6	0	15.47	0	0-1
	1850.7	18607	1.4	16-QAM	1	0	15.41	0	0-1
	1850.7	18607	1.4	16-QAM	1	2	15.43	0	0-1
	1850.7	18607	1.4	16-QAM	1	5	15.37	0	0-1
	1850.7	18607	1.4	16-QAM	3	0	15.31	0	0-1
	1850.7	18607	1.4	16-QAM	3	2	15.23	0	0-1
	1850.7	18607	1.4	16-QAM	3	3	15.28	0	0-1
	1850.7	18607	1.4	16-QAM	6	0	15.20	0	0-2
	1880.0	18900	1.4	QPSK	1	0	15.41	0	0
	1880.0	18900	1.4	QPSK	1	2	15.30	0	0
	1880.0	18900	1.4	QPSK	1	5	15.29	0	0
Mid	1880.0	18900	1.4	QPSK	3	0	15.37	0	0
	1880.0	18900	1.4	QPSK	3	2	15.39	0	0
	1880.0	18900	1.4	QPSK	3	3	15.42	0	0
	1880.0	18900	1.4	QPSK	6	0	15.35	0	0-1
	1880.0	18900	1.4	16-QAM	1	0	15.42	0	0-1
	1880.0	18900	1.4	16-QAM	1	2	15.41	0	0-1
	1880.0	18900	1.4	16-QAM	1	5	15.39	0	0-1
	1880.0	18900	1.4	16-QAM	3	0	15.32	0	0-1
	1880.0	18900	1.4	16-QAM	3	2	15.29	0	0-1
	1880.0	18900	1.4	16-QAM	3	3	15.28	0	0-1
	1880.0	18900	1.4	16-QAM	6	0	15.25	0	0-2
	1909.3	19193	1.4	QPSK	1	0	14.65	0	0
	1909.3	19193	1.4	QPSK	1	2	14.73	0	0
	1909.3	19193	1.4	QPSK	1	5	14.70	0	0
	1909.3	19193	1.4	QPSK	3	0	14.73	0	0
	1909.3	19193	1.4	QPSK	3	2	14.79	0	0
	1909.3	19193	1.4	QPSK	3	3	14.76	0	0
	1909.3	19193	1.4	QPSK	6	0	14.68	0	0-1
High	1909.3	19193	1.4	16-QAM	1	0	14.66	0	0-1
	1909.3	19193	1.4	16-QAM	1	2	14.74	0	0-1
	1909.3	19193	1.4	16-QAM	1	5	14.72	0	0-1
	1909.3	19193	1.4	16-QAM	3	0	14.70	0	0-1
	1909.3	19193	1.4	16-QAM	3	2	14.55	0	0-1
	1909.3	19193	1.4	16-QAM	3	3	14.64	0	0-1
	1909.3	19193	1.4	16-QAM	6	0	14.56	0	0-2

8.4 WLAN Conducted Powers

Table 8-41
IEEE 802.11b Average RF Power

Mode	Freq	Channel	802.11b (2.4 GHz) Conducted Power [dBm]			
			Data Rate [Mbps]			
	[MHz]		1	2	5.5	11
802.11b	2412	1*	11.18	11.32	11.12	11.16
802.11b	2437	6*	11.74	11.72	11.71	11.83
802.11b	2462	11*	11.29	11.23	11.25	11.37

Table 8-42
IEEE 802.11g Average RF Power

Mode	Freq	Channel	802.11g (2.4 GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
	[MHz]		6	9	12	18	24	36	48	54
802.11g	2412	1	10.13	9.98	10.21	10.12	10.20	10.04	10.22	9.88
802.11g	2437	6	10.77	10.69	10.80	10.85	10.79	10.64	10.92	10.62
802.11g	2462	11	10.21	10.13	10.24	10.07	10.20	10.16	10.38	10.10

Table 8-43
IEEE 802.11n Average RF Power

Mode	Freq	Channel	802.11n (2.4 GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
	[MHz]		6.5	13	20	26	39	52	58	65
802.11n	2412	1	9.02	8.97	8.91	9.09	8.90	9.16	8.91	9.01
802.11n	2437	6	9.74	9.72	9.81	9.75	9.66	9.72	9.72	9.72
802.11n	2462	11	9.24	9.24	9.14	9.33	9.14	9.35	9.22	9.19

Table 8-44
IEEE 802.11a Average RF Power

Mode	Freq	Channel	802.11a (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
	[MHz]		6	9	12	18	24	36	48	54
802.11a	5180	36*	7.97	7.92	7.90	8.04	8.13	7.84	8.17	7.62
802.11a	5200	40	8.03	7.90	7.91	8.25	8.17	7.85	8.13	7.81
802.11a	5220	44	7.79	7.97	7.57	8.01	7.93	7.57	8.10	7.41
802.11a	5240	48*	7.81	7.92	7.67	8.04	7.89	7.63	7.99	7.64
802.11a	5260	52*	8.06	7.99	7.91	8.23	8.06	7.98	8.29	7.69
802.11a	5280	56	8.02	7.99	7.88	8.24	7.89	7.98	8.25	7.80
802.11a	5300	60	7.99	8.01	7.75	8.24	8.02	7.92	8.15	7.60
802.11a	5320	64*	7.94	8.05	7.63	8.29	7.82	7.88	8.25	7.54
802.11a	5500	100	7.89	7.97	7.91	7.84	7.97	7.79	8.16	7.36
802.11a	5520	104*	7.90	8.01	7.80	7.91	8.05	7.74	8.12	7.50
802.11a	5540	108	7.99	7.97	7.93	8.07	8.07	7.81	8.02	7.48
802.11a	5560	112	7.76	7.87	8.01	7.55	7.90	7.68	7.91	7.37
802.11a	5580	116*	7.81	7.95	7.87	7.68	8.00	7.61	7.86	7.56
802.11a	5600	120	N/A	NA	NA	NA	NA	NA	NA	NA
802.11a	5620	124	N/A	NA	NA	NA	NA	NA	NA	NA
802.11a	5640	128	N/A	NA	NA	NA	NA	NA	NA	NA
802.11a	5660	132	7.88	7.87	8.01	7.97	7.55	7.98	7.47	8.07
802.11a	5680	136*	7.79	8.04	7.63	7.89	7.78	7.78	7.74	7.49
802.11a	5700	140	7.68	7.96	7.77	7.60	7.66	7.58	7.69	7.48
802.11a	5745	149*	7.76	7.77	7.82	7.80	7.74	7.74	7.87	7.46
802.11a	5765	153	7.65	7.70	7.73	7.64	7.61	7.64	7.76	7.31
802.11a	5785	157*	7.64	7.69	7.63	7.70	7.62	7.69	7.62	7.42
802.11a	5805	161*	7.62	7.64	7.65	7.74	7.54	7.54	7.80	7.29
802.11a	5825	165	7.41	7.42	7.50	7.46	7.43	7.32	7.50	7.16

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power then the default channels, these “required channels” are considered for SAR testing instead of the default channels.

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 40 of 75

Table 8-45
IEEE 802.11n Average RF Power – 20 MHz Bandwidth

Mode	Freq	Channel	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
	[MHz]		6.5	13	19.5	26	39	52	58.5	65
802.11n	5180	36	7.81	7.80	7.75	7.87	7.87	7.74	7.86	7.81
802.11n	5200	40	7.84	7.89	7.70	7.86	7.97	7.77	7.87	7.81
802.11n	5220	44	7.89	7.90	7.81	7.96	7.93	7.84	7.90	7.88
802.11n	5240	48	7.73	7.71	7.59	7.90	7.84	7.59	7.79	7.80
802.11n	5260	52	7.59	7.61	7.58	7.70	7.45	7.67	7.53	7.51
802.11n	5280	56	7.85	7.86	7.77	8.04	7.71	7.93	7.81	7.76
802.11n	5300	60	7.82	7.82	7.79	7.99	7.72	7.88	7.76	7.69
802.11n	5320	64	7.81	7.76	7.81	8.02	7.66	7.90	7.71	7.77
802.11n	5500	100	7.76	7.80	7.64	7.78	7.79	7.71	7.75	7.81
802.11n	5520	104	7.79	7.77	7.67	7.88	7.75	7.86	7.71	7.80
802.11n	5540	108	7.67	7.75	7.49	7.71	7.63	7.74	7.60	7.72
802.11n	5560	112	7.65	7.68	7.51	7.71	7.73	7.60	7.65	7.72
802.11n	5580	116	7.66	7.76	7.52	7.62	7.66	7.70	7.69	7.67
802.11n	5600	120	N/A	NA	NA	NA	NA	NA	NA	NA
802.11n	5620	124	N/A	NA	NA	NA	NA	NA	NA	NA
802.11n	5640	128	N/A	NA	NA	NA	NA	NA	NA	NA
802.11n	5660	132	7.47	7.42	7.59	7.41	7.59	7.39	7.48	7.47
802.11n	5680	136	7.58	7.59	7.48	7.62	7.64	7.47	7.66	7.56
802.11n	5700	140	7.51	7.57	7.42	7.48	7.51	7.54	7.51	7.53
802.11n	5745	149	7.63	7.58	7.63	7.62	7.74	7.52	7.67	7.57
802.11n	5765	153	7.56	7.43	7.62	7.61	7.62	7.50	7.60	7.47
802.11n	5785	157	7.48	7.46	7.48	7.42	7.62	7.33	7.51	7.49
802.11n	5805	161	7.41	7.35	7.40	7.40	7.59	7.26	7.41	7.36
802.11n	5825	165	7.35	7.26	7.37	7.37	7.52	7.10	7.50	7.28

Table 8-46
IEEE 802.11n Average RF Power – 40 MHz Bandwidth

Mode	Freq	Channel	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
	[MHz]		13.5	27	40.5	54	81	108	121.5	135
802.11n	5190	38	7.56	7.49	7.59	7.58	7.60	7.54	7.60	7.53
802.11n	5230	46	7.58	7.62	7.75	7.34	7.71	7.50	7.69	7.56
802.11n	5270	54	7.76	7.72	7.81	7.68	7.76	7.83	7.71	7.79
802.11n	5310	62	7.74	7.79	7.69	7.79	7.78	7.57	7.97	7.69
802.11n	5510	102	7.69	7.62	7.76	7.60	7.69	7.68	7.78	7.73
802.11n	5550	110	7.64	7.51	7.62	7.67	7.67	7.66	7.62	7.74
802.11n	5590	118	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5630	126	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5670	134	7.56	7.65	7.40	7.60	7.64	7.62	7.52	7.58
802.11n	5755	151	7.52	7.63	7.45	7.52	7.45	7.64	7.57	7.38
802.11n	5795	159	7.48	7.42	7.62	7.49	7.43	7.52	7.48	7.54

Table 8-47
IEEE 802.11ac Average RF Power – 80 MHz Bandwidth


Mode	Freq [MHz]	Channel	80MHz BW 802.11ac (5GHz) Conducted Power [dBm]								
			Data Rate [Mbps]								
			29.3	58.5	87.8	117	175.5	234	263.3	292.5	351
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
802.11ac	5210	42	7.40	7.43	7.48	7.36	7.47	7.47	7.41	7.47	7.43
802.11ac	5290	58	7.50	7.47	7.47	7.35	7.51	7.48	7.53	7.37	7.49
802.11ac	5530	106	7.73	7.89	7.78	7.57	7.70	7.69	7.70	7.75	7.63
802.11ac	5775	155	7.53	7.59	7.41	7.46	7.45	7.59	7.44	7.42	7.38

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 41 of 75

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- For 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- For 5 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11a were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
- For 5 GHz IEEE 802.11ac, SAR was not required based on the maximum conducted power of 5 GHz 802.11ac WLAN and the antenna to user separation distance. See section 1.5.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.

Power measurement for signal < 50 MHz Bandwidth



Power measurement for signal > 50 MHz Bandwidth




Figure 8-3
Power Measurement Setup

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 42 of 75

9 SYSTEM VERIFICATION

9.1 Tissue Verification

Table 9-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
9/9/2013	750B	22.9	710	0.938	57.456	0.960	55.687	-2.29%	3.18%
			725	0.964	57.118	0.961	55.629	0.31%	2.68%
			740	0.976	56.828	0.963	55.570	1.35%	2.26%
			755	0.978	56.729	0.964	55.512	1.45%	2.19%
9/9/2013	835B	22.8	820	0.969	56.262	0.969	55.258	0.00%	1.82%
			835	0.992	56.205	0.970	55.200	2.27%	1.82%
			850	1.015	55.919	0.988	55.154	2.73%	1.39%
9/24/2013	1750B	23.1	1710	1.480	51.632	1.460	53.540	1.37%	-3.56%
			1750	1.525	51.493	1.490	53.430	2.35%	-3.63%
			1790	1.572	51.430	1.510	53.330	4.11%	-3.56%
9/7/2013	1900B	22.8	1850	1.474	53.479	1.520	53.300	-3.03%	0.34%
			1880	1.508	53.392	1.520	53.300	-0.79%	0.17%
			1910	1.543	53.323	1.520	53.300	1.51%	0.04%
9/10/2013	1900B	23.1	1850	1.458	52.637	1.520	53.300	-4.08%	-1.24%
			1880	1.495	52.555	1.520	53.300	-1.64%	-1.40%
			1910	1.526	52.463	1.520	53.300	0.39%	-1.57%
8/28/2013	2450B	22.1	2401	1.944	51.000	1.903	52.765	2.15%	-3.35%
			2450	2.005	50.840	1.950	52.700	2.82%	-3.53%
			2499	2.083	50.675	2.019	52.638	3.17%	-3.73%
8/21/2013	5200B-5800B	23.5	5200	5.331	48.955	5.299	49.014	0.60%	-0.12%
			5240	5.374	48.736	5.346	48.933	0.52%	-0.40%
			5260	5.407	48.653	5.369	48.906	0.71%	-0.52%
			5300	5.470	48.631	5.416	48.851	1.00%	-0.45%
			5500	5.726	48.128	5.650	48.580	1.35%	-0.93%
			5540	5.792	48.048	5.696	48.526	1.69%	-0.99%
			5580	5.840	47.969	5.743	48.471	1.69%	-1.04%
			5600	5.872	47.932	5.766	48.444	1.84%	-1.06%
			5660	5.953	47.861	5.837	48.363	1.99%	-1.04%
			5745	6.077	47.761	5.936	48.248	2.38%	-1.01%
			5765	6.114	47.746	5.959	48.220	2.60%	-0.98%
			5800	6.147	47.802	6.000	48.200	2.45%	-0.83%
			5805	6.164	47.764	6.005	48.166	2.65%	-0.83%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per IEEE 1528 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 43 of 75

9.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 9-2
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
E	750	BODY	09/09/2013	23.9	22.7	0.100	1003	3920	0.885	8.830	8.850	0.23%
G	835	BODY	09/09/2013	24.0	22.8	0.100	4d119	3209	0.945	9.540	9.450	-0.94%
B	1750	BODY	09/24/2013	23.7	23.1	0.100	1008	3287	3.760	38.200	37.600	-1.57%
D	1900	BODY	09/07/2013	24.0	22.8	0.100	5d148	3288	4.000	40.800	40.000	-1.96%
D	1900	BODY	09/10/2013	24.5	23.1	0.100	5d148	3022	4.180	40.800	41.800	2.45%
H	2450	BODY	08/28/2013	22.6	22.4	0.100	797	3318	4.990	49.600	49.900	0.60%
A	5200	BODY	08/21/2013	24.2	23.7	0.100	1057	3589	7.420	75.500	74.200	-1.72%
A	5300	BODY	08/21/2013	24.2	23.7	0.100	1057	3589	7.880	75.300	78.800	4.65%
A	5500	BODY	08/21/2013	24.2	23.7	0.100	1057	3589	8.090	80.800	80.900	0.12%
A	5600	BODY	08/21/2013	24.3	23.8	0.100	1057	3589	8.440	80.300	84.400	5.11%
A	5800	BODY	08/21/2013	24.3	23.8	0.100	1057	3589	7.940	75.100	79.400	5.73%




Figure 9-1
System Verification Setup Diagram



Figure 9-2
System Verification Setup Photo

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 44 of 75

10 SAR DATA SUMMARY

10.1 Standalone Body SAR Data

Table 10-1
GPRS/UMTS Body SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
824.20	128	GSM 850	GPRS	28.5	28.06	0.17	12 mm	005	4	1:2.076	back	0.058	1.107	0.064	
824.20	128	GSM 850	GPRS	28.5	28.06	0.03	0 mm	005	4	1:2.076	bottom	0.128	1.107	0.142	
824.20	128	GSM 850	GPRS	28.5	28.06	0.09	15 mm	005	4	1:2.076	left	0.079	1.107	0.087	
824.20	128	GSM 850	GPRS	24.0	23.86	-0.01	0 mm	021	3	1:2.76	back	0.453	1.033	0.468	
824.20	128	GSM 850	GPRS	24.0	23.86	-0.12	0 mm	021	3	1:2.76	left	0.562	1.033	0.581	A1
836.60	4183	UMTS 850	RMC	23.0	21.98	0.03	12 mm	005	N/A	1:1	back	0.076	1.265	0.096	
836.60	4183	UMTS 850	RMC	23.0	21.98	-0.06	0 mm	005	N/A	1:1	bottom	0.074	1.265	0.094	
836.60	4183	UMTS 850	RMC	23.0	21.98	-0.05	15 mm	005	N/A	1:1	left	0.103	1.265	0.130	
836.60	4183	UMTS 850	RMC	20.5	19.99	0.01	0 mm	021	N/A	1:1	back	0.642	1.125	0.722	
836.60	4183	UMTS 850	RMC	20.5	19.99	-0.07	0 mm	021	N/A	1:1	left	0.698	1.125	0.785	A2
1880.00	661	GSM 1900	GPRS	26.5	25.97	-0.04	12 mm	005	4	1:2.076	back	0.346	1.130	0.391	
1880.00	661	GSM 1900	GPRS	26.5	25.97	0.17	0 mm	005	4	1:2.076	bottom	0.035	1.130	0.040	
1880.00	661	GSM 1900	GPRS	26.5	25.97	0.03	15 mm	005	4	1:2.076	left	0.230	1.130	0.260	
1850.20	512	GSM 1900	GPRS	20.0	19.65	-0.16	0 mm	021	3	1:2.76	back	0.804	1.084	0.872	
1880.00	661	GSM 1900	GPRS	20.0	19.52	-0.08	0 mm	021	3	1:2.76	back	0.896	1.117	1.001	
1909.80	810	GSM 1900	GPRS	20.0	19.31	-0.13	0 mm	021	3	1:2.76	back	0.916	1.172	1.074	A3
1880.00	661	GSM 1900	GPRS	20.0	19.52	-0.04	0 mm	021	3	1:2.76	left	0.316	1.117	0.353	
1909.80	810	GSM 1900	GPRS	20.0	19.31	0.00	0 mm	021	3	1:2.76	back	0.872	1.172	1.022	
1852.40	9262	UMTS 1900	RMC	23.0	22.85	0.00	12 mm	005	N/A	1:1	back	0.332	1.035	0.344	
1852.40	9262	UMTS 1900	RMC	23.0	22.85	-0.03	0 mm	005	N/A	1:1	bottom	0.035	1.035	0.036	
1852.40	9262	UMTS 1900	RMC	23.0	22.85	0.00	15 mm	005	N/A	1:1	left	0.183	1.035	0.189	
1852.40	9262	UMTS 1900	RMC	15.5	15.29	0.05	0 mm	021	N/A	1:1	back	0.725	1.050	0.761	A4
1852.40	9262	UMTS 1900	RMC	15.5	15.29	0.09	0 mm	021	N/A	1:1	left	0.275	1.050	0.289	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Blue entry represents variability measurement.

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 45 of 75

Table 10-2
LTE Band 17 Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
710.00	23790	Mid	LTE Band 17	10	23.5	23.48	0.03	0	011	QPSK	1	25	12 mm	back	1:1	0.081	1.005	0.081	A5
710.00	23790	Mid	LTE Band 17	10	22.5	22.44	0.01	1	011	QPSK	25	12	12 mm	back	1:1	0.066	1.014	0.067	
710.00	23790	Mid	LTE Band 17	10	23.5	23.48	0.20	0	011	QPSK	1	25	0 mm	bottom	1:1	0.013	1.005	0.013	
710.00	23790	Mid	LTE Band 17	10	22.5	22.44	0.16	1	011	QPSK	25	12	0 mm	bottom	1:1	0.010	1.014	0.010	
710.00	23790	Mid	LTE Band 17	10	23.5	23.48	0.04	0	011	QPSK	1	25	15 mm	left	1:1	0.075	1.005	0.075	
710.00	23790	Mid	LTE Band 17	10	22.5	22.44	0.06	1	011	QPSK	25	12	15 mm	left	1:1	0.060	1.014	0.061	
710.00	23790	Mid	LTE Band 17	10	19.5	19.43	0.00	0	001	QPSK	1	25	0 mm	back	1:1	0.556	1.016	0.565	
710.00	23790	Mid	LTE Band 17	10	19.5	19.28	0.03	0	001	QPSK	25	0	0 mm	back	1:1	0.565	1.052	0.594	
710.00	23790	Mid	LTE Band 17	10	19.5	19.43	0.03	0	001	QPSK	1	25	0 mm	left	1:1	0.433	1.016	0.440	
710.00	23790	Mid	LTE Band 17	10	19.5	19.28	-0.08	0	001	QPSK	25	0	0 mm	left	1:1	0.410	1.052	0.431	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 10-3
LTE Band 5 (Cell) Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.86	0.02	0	002	QPSK	1	0	12 mm	back	1:1	0.080	1.159	0.093	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.71	0.06	1	002	QPSK	25	0	12 mm	back	1:1	0.059	1.199	0.071	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.86	-0.02	0	002	QPSK	1	0	0 mm	bottom	1:1	0.115	1.159	0.133	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.71	0.04	1	002	QPSK	25	0	0 mm	bottom	1:1	0.096	1.199	0.115	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	22.86	0.02	0	002	QPSK	1	0	15 mm	left	1:1	0.137	1.159	0.159	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	21.71	-0.10	1	002	QPSK	25	0	15 mm	left	1:1	0.104	1.199	0.125	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.0	18.68	-0.02	0	001	QPSK	1	0	0 mm	back	1:1	0.644	1.076	0.693	A6
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.0	18.52	0.02	0	001	QPSK	25	0	0 mm	back	1:1	0.589	1.117	0.658	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.0	18.68	0.04	0	001	QPSK	1	0	0 mm	left	1:1	0.490	1.076	0.527	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.0	18.52	-0.08	0	001	QPSK	25	0	0 mm	left	1:1	0.507	1.117	0.566	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 10-4
LTE Band 4 (AWS) Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	23.03	0.02	0	010	QPSK	1	0	12 mm	back	1:1	0.348	1.114	0.388	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.93	-0.09	1	010	QPSK	50	0	12 mm	back	1:1	0.271	1.140	0.309	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	23.03	-0.12	0	010	QPSK	1	0	0 mm	bottom	1:1	0.112	1.114	0.125	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.93	0.12	1	010	QPSK	50	0	0 mm	bottom	1:1	0.092	1.140	0.105	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	23.03	-0.05	0	010	QPSK	1	0	15 mm	left	1:1	0.399	1.114	0.444	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.5	21.93	0.00	1	010	QPSK	50	0	15 mm	left	1:1	0.310	1.140	0.353	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	15.5	15.06	0.21	0	006	QPSK	1	50	0 mm	back	1:1	0.716	1.107	0.793	A7
1732.50	20175	Mid	LTE Band 4 (AWS)	20	15.5	14.98	0.20	0	006	QPSK	50	0	0 mm	back	1:1	0.484	1.127	0.545	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	15.5	15.06	-0.02	0	006	QPSK	1	50	0 mm	left	1:1	0.363	1.107	0.402	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	15.5	14.98	-0.01	0	006	QPSK	50	0	0 mm	left	1:1	0.249	1.127	0.281	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g) averaged over 1 gram									
Uncontrolled Exposure/General Population																			

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 46 of 75

Table 10-5
LTE Band 2 (PCS) Body SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #		
MHz	Ch.														(W/kg)		(W/kg)			
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	23.50	0.17	0	011	QPSK	1	50	12 mm	back	1:1	0.304	1.000	0.304		
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	22.23	-0.08	1	011	QPSK	50	0	12 mm	back	1:1	0.238	1.064	0.253		
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	23.50	0.05	0	011	QPSK	1	50	0 mm	bottom	1:1	0.036	1.000	0.036		
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	22.23	-0.07	1	011	QPSK	50	0	0 mm	bottom	1:1	0.025	1.064	0.027		
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	23.50	-0.01	0	011	QPSK	1	50	15 mm	left	1:1	0.229	1.000	0.229		
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	22.23	0.01	1	011	QPSK	50	0	15 mm	left	1:1	0.170	1.064	0.181		
1880.00	18900	Mid	LTE Band 2 (PCS)	20	15.5	15.50	0.07	0	001	QPSK	1	0	0 mm	back	1:1	0.738	1.000	0.738		A8
1860.00	18700	Low	LTE Band 2 (PCS)	20	15.5	15.42	0.11	0	001	QPSK	50	0	0 mm	back	1:1	0.718	1.019	0.732		
1880.00	18900	Mid	LTE Band 2 (PCS)	20	15.5	15.50	0.01	0	001	QPSK	1	0	0 mm	left	1:1	0.316	1.000	0.316		
1860.00	18700	Low	LTE Band 2 (PCS)	20	15.5	15.42	-0.05	0	001	QPSK	50	0	0 mm	left	1:1	0.323	1.019	0.329		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram												

Table 10-6
DTS Body SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #
MHz	Ch.											(W/kg)			
2412	1	IEEE 802.11b	DSSS	12.0	11.18	0.04	0 mm	159	1	back	1:1	0.674	1.208	0.814	
2437	6	IEEE 802.11b	DSSS	12.0	11.74	-0.01	0 mm	159	1	back	1:1	0.855	1.062	0.908	
2462	11	IEEE 802.11b	DSSS	12.0	11.29	-0.06	0 mm	159	1	back	1:1	0.915	1.178	1.078	
2437	6	IEEE 802.11b	DSSS	12.0	11.74	0.02	0 mm	159	1	right	1:1	0.474	1.062	0.503	
2462	11	IEEE 802.11b	DSSS	12.0	11.29	-0.02	0 mm	159	1	back	1:1	0.916	1.178	1.079	A9
5745	149	IEEE 802.11a	OFDM	8.5	7.76	0.07	0 mm	158	6	back	1:1	0.600	1.186	0.712	
5765	153	IEEE 802.11a	OFDM	8.5	7.65	0.10	0 mm	158	6	back	1:1	0.615	1.216	0.748	
5805	161	IEEE 802.11a	OFDM	8.5	7.62	0.05	0 mm	158	6	back	1:1	0.689	1.225	0.844	A10
5745	149	IEEE 802.11a	OFDM	8.5	7.76	0.13	0 mm	158	6	right	1:1	0.387	1.186	0.459	
5765	153	IEEE 802.11a	OFDM	8.5	7.65	0.01	0 mm	158	6	right	1:1	0.400	1.216	0.486	
5805	161	IEEE 802.11a	OFDM	8.5	7.62	-0.07	0 mm	158	6	right	1:1	0.395	1.225	0.484	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Note: Blue entry represents variability measurement.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 47 of 75

Table 10-7
NII Body SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
5200	40	IEEE 802.11a	OFDM	8.5	8.03	0.03	0 mm	158	6	back	1:1	0.403	1.114	0.449	
5240	48	IEEE 802.11a	OFDM	8.5	7.81	0.03	0 mm	158	6	back	1:1	0.508	1.172	0.595	
5200	40	IEEE 802.11a	OFDM	8.5	8.03	0.17	0 mm	158	6	right	1:1	0.401	1.114	0.447	
5240	48	IEEE 802.11a	OFDM	8.5	7.81	-0.04	0 mm	158	6	right	1:1	0.502	1.172	0.588	
5260	52	IEEE 802.11a	OFDM	8.5	8.06	0.04	0 mm	158	6	back	1:1	0.482	1.107	0.534	
5300	60	IEEE 802.11a	OFDM	8.5	7.99	0.03	0 mm	158	6	back	1:1	0.756	1.125	0.851	
5260	52	IEEE 802.11a	OFDM	8.5	8.06	0.01	0 mm	158	6	right	1:1	0.549	1.107	0.608	
5300	60	IEEE 802.11a	OFDM	8.5	7.99	-0.05	0 mm	158	6	right	1:1	0.581	1.125	0.654	
5540	108	IEEE 802.11a	OFDM	8.5	7.99	0.02	0 mm	158	6	back	1:1	0.904	1.125	1.017	
5580	116	IEEE 802.11a	OFDM	8.5	7.81	0.02	0 mm	158	6	back	1:1	0.883	1.172	1.035	
5660	132	IEEE 802.11a	OFDM	8.5	7.88	0.02	0 mm	158	6	back	1:1	0.921	1.153	1.062	A11
5540	108	IEEE 802.11a	OFDM	8.5	7.99	0.04	0 mm	158	6	right	1:1	0.579	1.125	0.651	
5580	116	IEEE 802.11a	OFDM	8.5	7.81	0.01	0 mm	158	6	right	1:1	0.515	1.172	0.604	
5660	132	IEEE 802.11a	OFDM	8.5	7.88	0.02	0 mm	158	6	right	1:1	0.449	1.153	0.518	
5540	108	IEEE 802.11a	OFDM	8.5	7.99	0.03	0 mm	158	6	back	1:1	0.857	1.125	0.964	
5660	132	IEEE 802.11a	OFDM	8.5	7.88	0.12	0 mm	158	6	back	1:1	0.893	1.153	1.030	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Blue entries represent variability measurements.

10.2 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in FCC KDB Publication 616217 and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 12 for variability analysis.
7. Per FCC KDB 616217 D04 Section 4.3, SAR tests are required for the back surface and edges of the tablet with the tablet touching the phantom. The SAR Exclusion Threshold in FCC KDB 447498 D01v05 was applied to determine SAR test exclusion for adjacent edge configurations. SAR tests were required for bottom and left edges for the main antenna. SAR tests were required for right edge for the WLAN/BT antenna.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 48 of 75

GSM Test Notes:

1. Justification for reduced test configurations per KDB Publication 941225 D03v01: The source-based time-averaged output power was evaluated for all multi-slot operations. The multi-slot configuration with the highest frame averaged output power was evaluated for SAR for hotspot SAR.
2. Per FCC KDB Publication 447498 D01v05, when the reported (scaled) SAR measured at the middle channel or highest output power channel for a test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in Body SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v05, when the reported (scaled) SAR measured at the middle channel or highest output power channel for a test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r01. The general test procedures used for testing can be found in Section 7.4.4.
2. MPR is implemented by the manufacturer for the device operating at maximum power with the capacitive sensor inactive. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator.

WLAN Notes:

1. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
2. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 5 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11a. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz Bandwidths) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
3. For 5 GHz IEEE 802.11ac, SAR was not required based on the maximum conducted power of 5 GHz 802.11ac WLAN and the antenna to user separation distance. See section 1.5.
4. WIFI transmission was verified using an uncalibrated spectrum analyzer.
5. When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is >1.6 W/kg or the reported 1g averaged SAR is >0.8 W/kg, SAR testing on other default channels was required.
6. There is no proximity sensor power reduction mechanism applied for WLAN or Bluetooth.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 49 of 75

11 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

11.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g/n/ac and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

11.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 11-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Configuration	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]		[mm]	[W/kg]
2.4 GHz WLAN	2437	12.00	Top	45	0.074
5 GHz WLAN	5785	8.50	Top	45	0.050
Bluetooth	2441	8.50	Touching* (Back, Left)	5	0.292
Bluetooth	2441	8.50	Back	12	0.122
Bluetooth	2441	8.50	Top	45	0.032

Notes:

- Per FCC KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.
- (*)Per FCC KDB Publication 447298, when the test separation distance is < 5mm, a distance of 5mm is applied to determine estimated SAR.
- Per FCC KDB Publication 447498 D01v05, an estimated SAR of 0.400 W/kg was used to determine simultaneous transmission SAR exclusion when the test separation distance was >50mm.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 50 of 75

11.3 Body SAR Simultaneous Transmission Analysis

Table 11-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body SAR at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.468	1.079	1.547	N/A	Body SAR	Back	0.722	1.079	See Note 1	0.01
	Top	0.400	0.074	0.474	N/A		Top	0.400	0.074	0.474	N/A
	Bottom	0.142	0.400	0.542	N/A		Bottom	0.094	0.400	0.494	N/A
	Right	0.400	0.503	0.903	N/A		Right	0.400	0.503	0.903	N/A
	Left	0.581	0.400	0.981	N/A		Left	0.785	0.400	1.185	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	1.074	1.079	See Note 1	0.02	Body SAR	Back	0.761	1.079	See Note 1	0.01
	Top	0.400	0.074	0.474	N/A		Top	0.400	0.074	0.474	N/A
	Bottom	0.040	0.400	0.440	N/A		Bottom	0.036	0.400	0.436	N/A
	Right	0.400	0.503	0.903	N/A		Right	0.400	0.503	0.903	N/A
	Left	0.353	0.400	0.753	N/A		Left	0.289	0.400	0.689	N/A
Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.594	1.079	See Note 1	0.01	Body SAR	Back	0.693	1.079	See Note 1	0.01
	Top	0.400	0.074	0.474	N/A		Top	0.400	0.074	0.474	N/A
	Bottom	0.123	0.400	0.413	N/A		Bottom	0.133	0.400	0.533	N/A
	Right	0.400	0.503	0.903	N/A		Right	0.400	0.503	0.903	N/A
	Left	0.440	0.400	0.840	N/A		Left	0.566	0.400	0.966	N/A
Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.793	1.079	See Note 1	0.01	Body SAR	Back	0.738	1.079	See Note 1	0.01
	Top	0.400	0.074	0.474	N/A		Top	0.400	0.074	0.474	N/A
	Bottom	0.125	0.400	0.525	N/A		Bottom	0.036	0.400	0.436	N/A
	Right	0.400	0.503	0.903	N/A		Right	0.400	0.503	0.903	N/A
	Left	0.402	0.400	0.802	N/A		Left	0.329	0.400	0.729	N/A

Table 11-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Body SAR at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.468	1.062	1.530	N/A	Body SAR	Back	0.722	1.062	See Note 1	0.01
	Top	0.400	0.050	0.450	N/A		Top	0.400	0.050	0.450	N/A
	Bottom	0.142	0.400	0.542	N/A		Bottom	0.094	0.400	0.494	N/A
	Right	0.400	0.654	1.054	N/A		Right	0.400	0.654	1.054	N/A
	Left	0.581	0.400	0.981	N/A		Left	0.785	0.400	1.185	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	1.074	1.062	See Note 1	0.02	Body SAR	Back	0.761	1.062	See Note 1	0.01
	Top	0.400	0.050	0.450	N/A		Top	0.400	0.050	0.450	N/A
	Bottom	0.040	0.400	0.440	N/A		Bottom	0.036	0.400	0.436	N/A
	Right	0.400	0.654	1.054	N/A		Right	0.400	0.654	1.054	N/A
	Left	0.353	0.400	0.753	N/A		Left	0.289	0.400	0.689	N/A

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 51 of 75

Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.594	1.062	See Note 1	0.01	Body SAR	Back	0.693	1.062	See Note 1	0.01
	Top	0.400	0.050	0.450	N/A		Top	0.400	0.050	0.450	N/A
	Bottom	0.013	0.400	0.413	N/A		Bottom	0.133	0.400	0.533	N/A
	Right	0.400	0.654	1.054	N/A		Right	0.400	0.654	1.054	N/A
	Left	0.440	0.400	0.840	N/A		Left	0.566	0.400	0.966	N/A
Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.793	1.062	See Note 1	0.01	Body SAR	Back	0.738	1.062	See Note 1	0.01
	Top	0.400	0.050	0.450	N/A		Top	0.400	0.050	0.450	N/A
	Bottom	0.125	0.400	0.525	N/A		Bottom	0.036	0.400	0.436	N/A
	Right	0.400	0.654	1.054	N/A		Right	0.400	0.654	1.054	N/A
	Left	0.402	0.400	0.802	N/A		Left	0.329	0.400	0.729	N/A

Table 11-4
Simultaneous Transmission Scenario with Bluetooth (Body SAR at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.468	0.292	0.760	Body SAR	Back	0.722	0.292	1.014
	Top	0.400	0.032	0.432		Top	0.400	0.032	0.432
	Bottom	0.142	0.400	0.542		Bottom	0.094	0.400	0.494
	Right	0.400	0.292	0.692		Right	0.400	0.292	0.692
	Left	0.581	0.400	0.981		Left	0.785	0.400	1.185
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	1.074	0.292	1.366	Body SAR	Back	0.761	0.292	1.053
	Top	0.400	0.032	0.432		Top	0.400	0.032	0.432
	Bottom	0.040	0.400	0.440		Bottom	0.036	0.400	0.436
	Right	0.400	0.292	0.692		Right	0.400	0.292	0.692
	Left	0.353	0.400	0.753		Left	0.289	0.400	0.689
Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.594	0.292	0.886	Body SAR	Back	0.693	0.292	0.985
	Top	0.400	0.032	0.432		Top	0.400	0.032	0.432
	Bottom	0.013	0.400	0.413		Bottom	0.133	0.400	0.533
	Right	0.400	0.292	0.692		Right	0.400	0.292	0.692
	Left	0.440	0.400	0.840		Left	0.566	0.400	0.966
Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.793	0.292	1.085	Body SAR	Back	0.738	0.292	1.030
	Top	0.400	0.032	0.432		Top	0.400	0.032	0.432
	Bottom	0.125	0.400	0.525		Bottom	0.036	0.400	0.436
	Right	0.400	0.292	0.692		Right	0.400	0.292	0.692
	Left	0.402	0.400	0.802		Left	0.329	0.400	0.729

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 52 of 75

Table 11-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Back Side at 1.2 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Back Side	GPRS 850	0.064	< 1.079	< 1.143
Back Side	UMTS 850	0.096	< 1.079	< 1.175
Back Side	GPRS 1900	0.391	< 1.079	< 1.470
Back Side	UMTS 1900	0.344	< 1.079	< 1.423
Back Side	LTE Band 17	0.081	< 1.079	< 1.160
Back Side	LTE Band 5 (Cell)	0.093	< 1.079	< 1.172
Back Side	LTE Band 4 (AWS)	0.388	< 1.079	< 1.467
Back Side	LTE Band 2 (PCS)	0.304	< 1.079	< 1.383

Table 11-6
Simultaneous Transmission Scenario with 5 GHz WLAN (Back Side at 1.2 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Back Side	GPRS 850	0.064	< 1.062	< 1.126
Back Side	UMTS 850	0.096	< 1.062	< 1.158
Back Side	GPRS 1900	0.391	< 1.062	< 1.453
Back Side	UMTS 1900	0.344	< 1.062	< 1.406
Back Side	LTE Band 17	0.081	< 1.062	< 1.143
Back Side	LTE Band 5 (Cell)	0.093	< 1.062	< 1.155
Back Side	LTE Band 4 (AWS)	0.388	< 1.062	< 1.450
Back Side	LTE Band 2 (PCS)	0.304	< 1.062	< 1.366

Table 11-7
Simultaneous Transmission Scenario with Bluetooth (Back Side at 1.2 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Back Side	GPRS 850	0.064	0.122	0.186
Back Side	UMTS 850	0.096	0.122	0.218
Back Side	GPRS 1900	0.391	0.122	0.513
Back Side	UMTS 1900	0.344	0.122	0.466
Back Side	LTE Band 17	0.081	0.122	0.203
Back Side	LTE Band 5 (Cell)	0.093	0.122	0.215
Back Side	LTE Band 4 (AWS)	0.388	0.122	0.510
Back Side	LTE Band 2 (PCS)	0.304	0.122	0.426

Table 11-8
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Left Edge at 1.5 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Left Edge	GPRS 850	0.087	0.400	0.487
Left Edge	UMTS 850	0.130	0.400	0.530
Left Edge	GPRS 1900	0.260	0.400	0.660
Left Edge	UMTS 1900	0.189	0.400	0.589
Left Edge	LTE Band 17	0.075	0.400	0.475
Left Edge	LTE Band 5 (Cell)	0.159	0.400	0.559
Left Edge	LTE Band 4 (AWS)	0.444	0.400	0.844
Left Edge	LTE Band 2 (PCS)	0.229	0.400	0.629

Table 11-9
Simultaneous Transmission Scenario with 5 GHz WLAN (Left Edge at 1.5 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Left Edge	GPRS 850	0.087	0.400	0.487
Left Edge	UMTS 850	0.130	0.400	0.530
Left Edge	GPRS 1900	0.260	0.400	0.660
Left Edge	UMTS 1900	0.189	0.400	0.589
Left Edge	LTE Band 17	0.075	0.400	0.475
Left Edge	LTE Band 5 (Cell)	0.159	0.400	0.559
Left Edge	LTE Band 4 (AWS)	0.444	0.400	0.844
Left Edge	LTE Band 2 (PCS)	0.229	0.400	0.629

Table 11-10
Simultaneous Transmission Scenario with Bluetooth (Left Edge at 1.5 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Left Edge	GPRS 850	0.087	0.400	0.487
Left Edge	UMTS 850	0.130	0.400	0.530
Left Edge	GPRS 1900	0.260	0.400	0.660
Left Edge	UMTS 1900	0.189	0.400	0.589
Left Edge	LTE Band 17	0.075	0.400	0.475
Left Edge	LTE Band 5 (Cell)	0.159	0.400	0.559
Left Edge	LTE Band 4 (AWS)	0.444	0.400	0.844
Left Edge	LTE Band 2 (PCS)	0.229	0.400	0.629

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not higher than 0.04 per FCC KDB Publication 447498 D01v05r01. See Section 11.4 for SPLS ratio analysis.
2. For SAR summations for body back side at 12 mm, WLAN SAR values for 0.0 cm were used since the 0.0 cm test distance for WLAN was more conservative. "<" denotes that the 0.0 cm WLAN SAR values were used for summation purposes.
3. For SAR summations for body left edge at 15 mm, estimated WLAN/BT SAR values of 0.400 W/kg were used per FCC KDB Publication 447498 D01v05r01 since the test separation distance was > 50mm.
4. The worst case 5 GHz WLAN reported SAR for each configuration was used for SAR summation, regardless of whether the WLAN channel has WIFI Direct / WIFI Display capability. Therefore, the summations above represent the absolute worst cases for simultaneous transmission with 5 GHz WLAN.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 54 of 75

11.4 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v05, when the sum of the standalone transmitters is more than 1.6 W/kg, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 , simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with UMTS 850 MHz antenna operating at limited output power with 2.4 GHz WIFI.




Figure 11-1
Peak SAR Location Plot of UMTS 850 MHz and 2.4 GHz WLAN

Table 11-11
Peak SAR Locations for Body Back Side at 0 cm UMTS 850 MHz and 2.4 GHz WLAN

Mode/Band	x (mm)	y (mm)
UMTS 850 MHz	-10.00	-121.50
IEEE 802.11b	22.60	110.60

Table 11-12
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}
UMTS 850 MHz	IEEE 802.11b	0.722	1.079	1.801	234.38	0.01

FCC ID: A3LSMP605M	 PCTEST INDEPENDENT LABORATORY	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 55 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with GPRS 1900 MHz antenna operating at limited output power with 2.4 GHz WIFI.




Figure 11-2
Peak SAR Location Plot of GPRS 1900 MHz and 2.4 GHz WLAN

Table 11-13
Peak SAR Locations for Body Back Side at 0 cm GPRS 1900 MHz and 2.4 GHz WLAN

Mode/Band	x (mm)	y (mm)
GPRS 1900 MHz	-29.00	-83.00
IEEE 802.11b	22.60	110.60

Table 11-14
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
GPRS 1900 MHz	IEEE 802.11b	1.074	1.079	2.153	200.36	0.02

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with UMTS 1900 MHz antenna operating at limited output power with 2.4 GHz WIFI.




Figure 11-3
Peak SAR Location Plot of UMTS 1900 MHz and 2.4 GHz WLAN

Table 11-15
Peak SAR Locations for Body Back Side at 0 cm UMTS 1900 MHz and 2.4 GHz WLAN

Mode/Band	x (mm)	y (mm)
UMTS 1900 MHz	-18.50	-97.50
IEEE 802.11b	22.60	110.60

Table 11-16
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
UMTS 1900 MHz	IEEE 802.11b	0.761	1.079	1.840	212.12	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 57 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE Band 17 antenna operating at limited output power with 2.4 GHz WIFI.




Figure 11-4
Peak SAR Location Plot of LTE Band 17 and 2.4 GHz WLAN

Table 11-17
Peak SAR Locations for Body Back Side at 0 cm LTE Band 17 and 2.4 GHz WLAN

Mode/Band	x (mm)	y (mm)
LTE Band 17	-30.00	-110.00
IEEE 802.11b	22.60	110.60

Table 11-18
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
LTE Band 17	IEEE 802.11b	0.594	1.079	1.673	226.78	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 58 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE Band 5 antenna operating at limited output power with 2.4 GHz WIFI.




Figure 11-5
Peak SAR Location Plot of LTE Band 5 and 2.4 GHz WLAN

Table 11-19
Peak SAR Locations for Body Back Side at 0 cm LTE Band 5 and 2.4 GHz WLAN

Mode/Band	x (mm)	y (mm)
LTE Band 5	6.00	-128.00
IEEE 802.11b	22.60	110.60

Table 11-20
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
LTE Band 5	IEEE 802.11b	0.693	1.079	1.772	239.18	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 59 of 75	

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE Band 4 antenna operating at limited output power with 2.4 GHz WIFI.




Figure 11-6
Peak SAR Location Plot of LTE Band 4 and 2.4 GHz WLAN

Table 11-21
Peak SAR Locations for Body Back Side at 0 cm LTE Band 4 and 2.4 GHz WLAN

Mode/Band	x (mm)	y (mm)
LTE Band 4	-16.52	-112.99
IEEE 802.11b	22.60	110.60

Table 11-22
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5} / D_{a-b}$
LTE Band 4	IEEE 802.11b	0.793	1.079	1.872	226.99	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 60 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE Band 2 antenna operating at limited output power with 2.4 GHz WIFI.




Figure 11-7
Peak SAR Location Plot of LTE Band 2 and 2.4 GHz WLAN

Table 11-23
Peak SAR Locations for Body Back Side at 0 cm LTE Band 2 and 2.4 GHz WLAN

Mode/Band	x (mm)	y (mm)
LTE Band 2	-30.50	-87.00
IEEE 802.11b	22.60	110.60

Table 11-24
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
LTE Band 2	IEEE 802.11b	0.738	1.079	1.817	204.61	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 61 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with UMTS 850 MHz antenna operating at limited output power with 5 GHz WIFI.




Figure 11-8
Peak SAR Location Plot of UMTS 850 MHz and 5 GHz WLAN

Table 11-25
Peak SAR Locations for Body Back Side at 0 cm UMTS 850 MHz and 5 GHz WLAN

Mode/Band	x (mm)	y (mm)
UMTS 850 MHz	-10.00	-121.50
IEEE 802.11a	10.60	105.60

Table 11-26
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
UMTS 850 MHz	IEEE 802.11a	0.722	1.062	1.784	228.03	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 62 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with GPRS 1900 MHz antenna operating at limited output power with 5 GHz WIFI.




Figure 11-9
Peak SAR Location Plot of GPRS 1900 MHz and 5 GHz WLAN

Table 11-27
Peak SAR Locations for Body Back Side at 0 cm GPRS 1900 MHz and 5 GHz WLAN

Mode/Band	x (mm)	y (mm)
GPRS 1900 MHz	-29.00	-83.00
IEEE 802.11a	10.60	105.60

Table 11-28
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
GPRS 1900 MHz	IEEE 802.11a	1.074	1.062	2.136	192.71	0.02

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 63 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with UMTS 1900 MHz antenna operating at limited output power with 5 GHz WIFI.




Figure 11-10
Peak SAR Location Plot of UMTS 1900 MHz and 5 GHz WLAN

Table 11-29
Peak SAR Locations for Body Back Side at 0 cm UMTS 1900 MHz and 5 GHz WLAN

Mode/Band	x (mm)	y (mm)
UMTS 1900 MHz	-18.50	-97.50
IEEE 802.11a	10.60	105.60

Table 11-30
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
UMTS 1900 MHz	IEEE 802.11a	0.761	1.062	1.823	205.17	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 64 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE Band 17 antenna operating at limited output power with 5 GHz WIFI.




Figure 11-11
Peak SAR Location Plot of LTE Band 17 and 5 GHz WLAN

Table 11-31
Peak SAR Locations for Body Back Side at 0 cm LTE Band 17 and 5 GHz WLAN

Mode/Band	x (mm)	y (mm)
LTE Band 17	-30.00	-110.00
IEEE 802.11a	10.60	105.60

Table 11-32
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
LTE Band 17	IEEE 802.11a	0.594	1.062	1.656	219.39	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 65 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE Band 5 antenna operating at limited output power with 5 GHz WIFI.




Figure 11-12
Peak SAR Location Plot of LTE Band 5 and 5 GHz WLAN

Table 11-33
Peak SAR Locations for Body Back Side at 0 cm LTE Band 5 and 5 GHz WLAN

Mode/Band	x (mm)	y (mm)
LTE Band 5	6.00	-128.00
IEEE 802.11a	10.60	105.60

Table 11-34
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
LTE Band 5	IEEE 802.11a	0.693	1.062	1.755	233.65	0.01

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE Band 4 antenna operating at limited output power with 5 GHz WIFI.




Figure 11-13
Peak SAR Location Plot of LTE Band 4 and 5 GHz WLAN

Table 11-35
Peak SAR Locations for Body Back Side at 0 cm LTE Band 4 and 5 GHz WLAN

Mode/Band	x (mm)	y (mm)
LTE Band 4	-16.52	-112.99
IEEE 802.11a	10.60	105.60

Table 11-36
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
LTE Band 4	IEEE 802.11a	0.793	1.062	1.855	220.27	0.01

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			Page 67 of 75

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE Band 2 antenna operating at limited output power with 5 GHz WIFI.




Figure 11-14
Peak SAR Location Plot of LTE Band 2 and 5 GHz WLAN

Table 11-37
Peak SAR Locations for Body Back Side at 0 mm LTE Band 2 and 5 GHz WLAN

Mode/Band	x (mm)	y (mm)
LTE Band 2	-30.50	-87.00
IEEE 802.11a	10.60	105.60

Table 11-38
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
LTE Band 2	IEEE 802.11a	0.738	1.062	1.800	196.94	0.01

11.1 Simultaneous Transmission Conclusion

The above numerical summed SAR and SPLSR analysis results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 68 of 75	

12 SAR MEASUREMENT VARIABILITY

12.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 12-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS															
Band	FREQUENCY		Mode	Service	# of Time Slots	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.							(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1909.80	810	GSM 1900	GPRS	3	N/A	back	0 mm	0.916	0.872	1.05	N/A	N/A	N/A	N/A
2450	2462.00	11	IEEE 802.11b	DSSS	N/A	1	back	0 mm	0.915	0.916	1.00	N/A	N/A	N/A	N/A
5500	5540.00	108	IEEE 802.11a	OFDM	N/A	6	back	0 mm	0.904	0.857	1.05	N/A	N/A	N/A	N/A
5600	5660.00	132	IEEE 802.11a	OFDM	N/A	6	back	0 mm	0.921	0.893	1.03	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body						
Spatial Peak									1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population									averaged over 1 gram						

12.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 69 of 75

13 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	85047A	S-Parameter Test Set	N/A	N/A	N/A	2904A00579
Agilent	N9020A	MXA Signal Analyzer	10/9/2012	Annual	10/9/2013	US46470561
Agilent	85070C	Dielectric Probe Kit	2/14/2013	Annual	2/14/2014	MY44300633
Agilent	8753E	(30kHz-6GHz) Network Analyzer	4/16/2013	Annual	4/16/2014	JP38020182
Agilent	8648D	(9kHz-4GHz) Signal Generator	4/17/2013	Annual	4/17/2014	3629U00687
Amplifier Research	551G4	5W, 800MHz-4.2GHz	CBT	N/A	CBT	21910
Anritsu	ML2495A	Power Meter	10/11/2012	Annual	10/11/2013	1039008
Anritsu	MA2481A	Power Sensor	2/14/2013	Annual	2/14/2014	5821
Anritsu	ML2438A	Power Meter	12/4/2012	Annual	12/4/2013	1070030
Anritsu	MA2481A	Power Sensor	2/14/2013	Annual	2/14/2014	2400
Anritsu	ML2438A	Power Meter	2/14/2013	Annual	2/14/2014	98150041
Anritsu	MA2411B	Pulse Power Sensor	12/4/2012	Annual	12/4/2013	1207364
Anritsu	MA2411B	Pulse Power Sensor	12/5/2012	Annual	12/5/2013	1126066
Anritsu	MA2481D	Universal Sensor	12/17/2012	Annual	12/17/2013	1204343
Anritsu	MT8820C	Radio Communication Tester	11/6/2012	Annual	11/6/2013	6200901190
Anritsu	MA24106A	USB Power Sensor	12/7/2012	Annual	12/7/2013	1244512
Anritsu	MA24106A	USB Power Sensor	12/7/2012	Annual	12/7/2013	1244524
Anritsu	MA24106A	USB Power Sensor	12/7/2012	Annual	12/7/2013	1244515
Anritsu	MA24106A	USB Power Sensor	12/6/2012	Annual	12/6/2013	1248508
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Control Company	36934-158	Wall-Mounted Thermometer	1/4/2012	Biennial	1/4/2014	122014488
Control Company	36934-158	Wall-Mounted Thermometer	1/4/2012	Biennial	1/4/2014	122014497
Control Company	4353	Long Stem Thermometer	9/25/2012	Biennial	9/25/2014	122541139
Control Company	4353	Long Stem Thermometer	9/25/2012	Biennial	9/25/2014	122539615
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	10/7/2011	Biennial	10/7/2013	103962
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	9/26/2012	Annual	9/26/2013	108798
Rohde & Schwarz	CMU200	Base Station Simulator	5/3/2013	Annual	5/3/2014	836371/0079
Rohde & Schwarz	NRVD	Dual Channel Power Meter	10/12/2012	Biennial	10/12/2014	101695
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2012	Triennial	3/5/2015	N/A
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2012	Triennial	3/5/2015	N/A
SPEAG	DAK-3.5	Dielectric Assessment Kit	12/11/2012	Annual	12/11/2013	1091
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/14/2013	Annual	5/14/2014	1070
SPEAG	D750V3	750 MHz Dipole	1/7/2013	Annual	1/7/2014	1003
SPEAG	D835V2	835 MHz SAR Dipole	4/25/2013	Annual	4/25/2014	40119
SPEAG	D1765V2	1765 MHz SAR Dipole	5/14/2013	Annual	5/14/2014	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	2/6/2013	Annual	2/6/2014	5d148
SPEAG	D2450V2	2450 MHz SAR Dipole	1/8/2013	Annual	1/8/2014	797
SPEAG	D5GHZV2	5 GHz SAR Dipole	1/11/2013	Annual	1/11/2014	1057
SPEAG	ES3DV2	SAR Probe	8/22/2013	Annual	8/22/2014	3022
SPEAG	EX3DV4	SAR Probe	1/17/2013	Annual	1/17/2014	3589
SPEAG	ES3DV3	SAR Probe	4/29/2013	Annual	4/29/2014	3318
SPEAG	EX3DV4	SAR Probe	2/27/2013	Annual	2/27/2014	3920
SPEAG	ES3DV3	SAR Probe	3/15/2013	Annual	3/15/2014	3209
SPEAG	ES3DV3	SAR Probe	11/15/2012	Annual	11/15/2013	3287
SPEAG	ES3DV3	SAR Probe	9/20/2012	Annual	9/20/2013	3288
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/8/2013	Annual	3/8/2014	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/6/2013	Annual	2/6/2014	649
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/17/2013	Annual	1/17/2014	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/21/2013	Annual	8/21/2014	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/22/2013	Annual	4/22/2014	1364
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/13/2012	Annual	11/13/2013	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/19/2012	Annual	9/19/2013	1323
Tektronix	RSA6114A	Real Time Spectrum Analyzer	4/17/2013	Annual	4/17/2014	8010177
VWR	36934-158	Wall-Mounted Thermometer	9/30/2011	Biennial	9/30/2013	111859332
VWR	23226-658	Long Stem Thermometer	7/11/2012	Biennial	7/11/2014	122389334

Note:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment item was used solely within its respective calibration period.

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 70 of 75

14 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.1	11.7
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.2	23.5
									299

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 71 of 75

Applicable for frequencies up to 6 GHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.4	12.0
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.7	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 72 of 75

15 CONCLUSION

15.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 73 of 75

16 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, June 2001.
- [6] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [7] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [8] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [9] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.
- [10] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [11] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [12] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [13] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [14] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [15] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [16] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [17] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

FCC ID: A3LSMP605M	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 74 of 75

- [18] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [19] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [20] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [21] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [22] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [23] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [24] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [25] FCC Public Notice DA-02-1438. Office of Engineering and Technology Announces a Transition Period for the Phantom Requirements of Supplement C to OET Bulletin 65, June 19, 2002
- [26] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [27] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v01r02
- [28] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D02-D04
- [29] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [30] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [31] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [32] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [33] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1309031750.A3L	Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet		Page 75 of 75

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 021

Communication System: GSM GPRS; 3 Tx slots; Frequency: 824.2 MHz; Duty Cycle: 1:2.76

Medium: 835 Body Medium parameters used (interpolated):

$f = 824.2 \text{ MHz}$; $\sigma = 0.975 \text{ S/m}$; $\epsilon_r = 56.246$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 09-09-2013; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3209; ConvF(6.28, 6.28, 6.28); Calibrated: 3/15/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/8/2013

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Mode: GPRS 850, Body SAR, Left Edge, Low.ch, 3 Tx Slots


Area Scan (9x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.007 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.32 W/kg

SAR(1 g) = 0.562 W/kg



0 dB = 0.694 W/kg = -1.59 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 021

Communication System: UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.994 \text{ S/m}$; $\epsilon_r = 56.174$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 09-09-2013; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3209; ConvF(6.28, 6.28, 6.28); Calibrated: 3/15/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/8/2013

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 850, Body SAR, Left Edge, Mid.ch


Area Scan (9x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.586 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.698 W/kg



0 dB = 0.870 W/kg = -0.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 021

Communication System: GSM GPRS; 3 Tx slots; Frequency: 1909.8 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body Medium parameters used:

$f = 1910 \text{ MHz}$; $\sigma = 1.526 \text{ S/m}$; $\epsilon_r = 52.463$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 09-10-2013; Ambient Temp: 24.5°C; Tissue Temp: 23.1°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/22/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/21/2013

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: GPRS 1900, Body SAR, Back side, High.ch, 3 Tx Slots


Area Scan (12x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.769 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 2.16 W/kg

SAR(1 g) = 0.916 W/kg



0 dB = 1.06 W/kg = 0.25 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 021

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$; $\sigma = 1.477 \text{ S/m}$; $\epsilon_r = 53.472$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 09-07-2013; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3288; ConvF(4.89, 4.89, 4.89); Calibrated: 9/20/2012;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/19/2012

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 1900, Body SAR, Back side, Low.ch


Area Scan (11x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.425 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.71 W/kg

SAR(1 g) = 0.725 W/kg



0 dB = 0.888 W/kg = -0.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 001

Communication System: LTE Band 17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used:

$f = 710 \text{ MHz}$; $\sigma = 0.938 \text{ S/m}$; $\epsilon_r = 57.456$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 09-09-2013; Ambient Temp: 23.9°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3920; ConvF(9.57, 9.57, 9.57); Calibrated: 2/27/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/6/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 17, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 25 RB, 0 RB Offset**


Area Scan (14x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.852 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.16 W/kg

SAR(1 g) = 0.565 W/kg



0 dB = 0.652 W/kg = -1.86 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 001

Communication System: LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.994 \text{ S/m}$; $\epsilon_r = 56.176$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 09-09-2013; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3209; ConvF(6.28, 6.28, 6.28); Calibrated: 3/15/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/8/2013

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x19x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.152 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.644 W/kg



0 dB = 0.711 W/kg = -1.48 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 006

Communication System: LTE RF; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.505 \text{ S/m}$; $\epsilon_r = 51.554$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 09-24-2013; Ambient Temp: 23.7°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3287; ConvF(4.86, 4.86, 4.86); Calibrated: 11/15/2012;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/13/2012

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (12x19x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.658 V/m; Power Drift = 0.21 dB

Peak SAR (extrapolated) = 1.71 W/kg

SAR(1 g) = 0.716 W/kg



0 dB = 0.853 W/kg = -0.69 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 001

Communication System: LTE Band 2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.495 \text{ S/m}$; $\epsilon_r = 52.555$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 09-10-2013; Ambient Temp: 24.5°C; Tissue Temp: 23.1°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/22/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/21/2013

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (13x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.590 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.68 W/kg

SAR(1 g) = 0.738 W/kg



0 dB = 0.738 W/kg = -1.32 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 159

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.024 \text{ S/m}$; $\epsilon_r = 50.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-28-2013; Ambient Temp: 22.6°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3318; ConvF(4.31, 4.31, 4.31); Calibrated: 4/29/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 4/22/2013

Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Back Side


Area Scan (13x23x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.909 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 2.83 W/kg

SAR(1 g) = 0.916 W/kg



0 dB = 1.33 W/kg = 1.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 158

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5805 \text{ MHz}$; $\sigma = 6.164 \text{ S/m}$; $\epsilon_r = 47.764$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-21-2013; Ambient Temp: 24.3°C; Tissue Temp: 23.8°C

Probe: EX3DV4 - SN3589; ConvF(3.66, 3.66, 3.66); Calibrated: 1/17/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/17/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11a, 5.8 GHz, Body SAR, Ch 161, 6 Mbps, Back Side


Area Scan (13x19x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio = 1.4

Reference Value = 12.095 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 4.33 W/kg

SAR(1 g) = 0.689 W/kg



0 dB = 1.44 W/kg = 1.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMP605M; Type: Portable Tablet; Serial: 158

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5660 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5660 \text{ MHz}$; $\sigma = 5.953 \text{ S/m}$; $\epsilon_r = 47.861$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-21-2013; Ambient Temp: 24.3°C; Tissue Temp: 23.8°C

Probe: EX3DV4 - SN3589; ConvF(3.32, 3.32, 3.32); Calibrated: 1/17/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/17/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11a, 5.5-5.7 GHz, Body SAR, Ch 132, 6 Mbps, Back Side


Area Scan (13x19x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio=1.4

Reference Value = 9.612 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 6.61 W/kg

SAR(1 g) = 0.921 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.977 \text{ S/m}$; $\epsilon_r = 56.762$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 09-09-2013; Ambient Temp: 23.9°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3920; ConvF(9.57, 9.57, 9.57); Calibrated: 2/27/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/6/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.885 W/kg

Deviation = 0.23 %



0 dB = 0.952 W/kg = -0.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.992 \text{ S/m}$; $\epsilon_r = 56.205$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 09-09-2013; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3209; ConvF(6.28, 6.28, 6.28); Calibrated: 3/15/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/8/2013

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.37 W/kg

SAR(1 g) = 0.945 W/kg

Deviation = -0.94%



0 dB = 1.02 W/kg = 0.09 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.525 \text{ S/m}$; $\epsilon_r = 51.493$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-24-2013; Ambient Temp: 23.7°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3287; ConvF(4.86, 4.86, 4.86); Calibrated: 11/15/2012;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/13/2012

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

1750 MHz System Verification

Area Scan (6x8x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.82 W/kg

SAR(1 g) = 3.76 W/kg

Deviation = -1.57%



0 dB = 4.19 W/kg = 6.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.531 \text{ S/m}$; $\epsilon_r = 53.346$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-07-2013; Ambient Temp: 24.0°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3288; ConvF(4.89, 4.89, 4.89); Calibrated: 9/20/2012;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/19/2012

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.07 W/kg

SAR(1 g) = 4 W/kg

Deviation = -1.96%



0 dB = 4.49 W/kg = 6.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.516 \text{ S/m}$; $\epsilon_r = 52.494$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-10-2013; Ambient Temp: 24.5°C; Tissue Temp: 23.1°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/22/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/21/2013

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

1900 MHz System Verification

Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.39 W/kg

SAR(1 g) = 4.18 W/kg

Deviation = 2.45 %



0 dB = 4.59 W/kg = 6.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.005 \text{ S/m}$; $\epsilon_r = 50.84$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-28-2013; Ambient Temp: 22.6°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3318; ConvF(4.31, 4.31, 4.31); Calibrated: 4/29/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 4/22/2013

Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 10.6 W/kg

SAR(1 g) = 4.99 W/kg

Deviation = 0.60 %



0 dB = 6.60 W/kg = 8.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5200 \text{ MHz}$; $\sigma = 5.331 \text{ S/m}$; $\epsilon_r = 48.955$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-21-2013; Ambient Temp: 24.2°C; Tissue Temp: 23.7°C

Probe: EX3DV4 - SN3589; ConvF(3.99, 3.99, 3.99); Calibrated: 1/17/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/17/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

5200 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio=1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 30.6 W/kg

SAR(1 g) = 7.42 W/kg

Deviation = -1.72 %



0 dB = 18.5 W/kg = 12.67 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.47 \text{ S/m}$; $\epsilon_r = 48.631$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-21-2013; Ambient Temp: 24.2°C; Tissue Temp: 23.7°C

Probe: EX3DV4 - SN3589; ConvF(3.81, 3.81, 3.81); Calibrated: 1/17/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/17/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

5300 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio=1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 33.4 W/kg

SAR(1 g) = 7.88 W/kg

Deviation = 4.65 %



0 dB = 20.1 W/kg = 13.03 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 5.726 \text{ S/m}$; $\epsilon_r = 48.128$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-21-2013; Ambient Temp: 24.2°C; Tissue Temp: 23.7°C

Probe: EX3DV4 - SN3589; ConvF(3.52, 3.52, 3.52); Calibrated: 1/17/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/17/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

5500 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio=1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 35.5 W/kg

SAR(1 g) = 8.09 W/kg

Deviation = 0.12 %



0 dB = 20.9 W/kg = 13.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5600 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.872 \text{ S/m}$; $\epsilon_r = 47.932$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-21-2013; Ambient Temp: 24.3°C; Tissue Temp: 23.8°C

Probe: EX3DV4 - SN3589; ConvF(3.32, 3.32, 3.32); Calibrated: 1/17/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/17/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

5600 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio=1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 37.8 W/kg

SAR(1 g) = 8.44 W/kg

Deviation = 5.11 %



0 dB = 22.2 W/kg = 13.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 6.147 \text{ S/m}$; $\epsilon_r = 47.802$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-21-2013; Ambient Temp: 24.3°C; Tissue Temp: 23.8°C

Probe: EX3DV4 - SN3589; ConvF(3.66, 3.66, 3.66); Calibrated: 1/17/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/17/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

5800 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio=1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 33.5 W/kg

SAR(1 g) = 7.94 W/kg

Deviation = 5.73 %



0 dB = 19.5 W/kg = 12.90 dBW/kg

APPENDIX C: PROBE CALIBRATION

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3288_Sep12**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3288**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-23.v4, QA CAL-25.v4
Calibration procedure for dosimetric E-field probes**


Calibration date: **September 20, 2012**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-12 (No. 217-01508)	Apr-13
Power sensor E4412A	MY41498087	29-Mar-12 (No. 217-01508)	Apr-13
Reference 3 dB Attenuator	SN: S5054 (3c)	27-Mar-12 (No. 217-01531)	Apr-13
Reference 20 dB Attenuator	SN: S5086 (20b)	27-Mar-12 (No. 217-01529)	Apr-13
Reference 30 dB Attenuator	SN: S5129 (30b)	27-Mar-12 (No. 217-01532)	Apr-13
Reference Probe ES3DV2	SN: 3013	29-Dec-11 (No. ES3-3013_Dec11)	Dec-12
DAE4	SN: 660	20-Jun-12 (No. DAE4-660_Jun12)	Jun-13
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-11)	In house check: Apr-13
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-11)	In house check: Oct-12

Calibrated by:	Name Jeton Kastrati	Function Laboratory Technician	Signature 
Approved by:	Name Katja Pokovic	Technical Manager	
			Issued: September 20, 2012
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}; A, B, C** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ES3DV3

SN:3288

Manufactured: July 6, 2010
Calibrated: September 20, 2012

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.87	0.97	0.75	$\pm 10.1 \%$
DCP (mV) ^B	101.3	102.4	103.9	

Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dB	C dB	VR mV	Unc ^E (k=2)
0	CW	0.00	X	0.00	0.00	1.00	168.6	$\pm 3.3 \%$
			Y	0.00	0.00	1.00	132.2	
			Z	0.00	0.00	1.00	156.8	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	41.9	0.89	6.67	6.67	6.67	0.80	1.14	± 12.0 %
835	41.5	0.90	6.41	6.41	6.41	0.76	1.18	± 12.0 %
1750	40.1	1.37	5.51	5.51	5.51	0.70	1.28	± 12.0 %
1900	40.0	1.40	5.28	5.28	5.28	0.80	1.22	± 12.0 %
2450	39.2	1.80	4.61	4.61	4.61	0.80	1.26	± 12.0 %
2600	39.0	1.96	4.45	4.45	4.45	0.80	1.31	± 12.0 %

^c Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	55.5	0.96	6.44	6.44	6.44	0.62	1.31	± 12.0 %
835	55.2	0.97	6.31	6.31	6.31	0.38	1.78	± 12.0 %
1750	53.4	1.49	5.18	5.18	5.18	0.64	1.43	± 12.0 %
1900	53.3	1.52	4.89	4.89	4.89	0.50	1.64	± 12.0 %
2450	52.7	1.95	4.35	4.35	4.35	0.74	1.23	± 12.0 %
2600	52.5	2.16	4.09	4.09	4.09	0.80	1.07	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	54.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3022_Aug13**

CALIBRATION CERTIFICATE

Object **ES3DV2 - SN:3022**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **August 22, 2013**

UTC
9/13/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	31-Jan-13 (No. DAE4-660_Jan13)	Jan-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by:	Name Jeton Kastrati	Function Laboratory Technician	Signature
Approved by:	Katja Pokovic	Technical Manager	

Issued: August 23, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ES3DV2

SN:3022

Manufactured: April 15, 2003
Calibrated: August 22, 2013

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.00	1.04	0.99	± 10.1 %
DCP (mV) ^B	100.7	97.4	99.7	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	178.6	±3.0 %
		Y	0.0	0.0	1.0		141.9	
		Z	0.0	0.0	1.0		134.7	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	41.9	0.89	6.21	6.21	6.21	0.19	2.37	± 12.0 %
835	41.5	0.90	6.09	6.09	6.09	0.30	1.70	± 12.0 %
1750	40.1	1.37	5.19	5.19	5.19	0.65	1.23	± 12.0 %
1900	40.0	1.40	5.03	5.03	5.03	0.51	1.43	± 12.0 %
2450	39.2	1.80	4.36	4.36	4.36	0.51	1.51	± 12.0 %
2600	39.0	1.96	4.16	4.16	4.16	0.74	1.29	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	55.5	0.96	5.92	5.92	5.92	0.24	1.99	± 12.0 %
835	55.2	0.97	5.91	5.91	5.91	0.29	1.85	± 12.0 %
1750	53.4	1.49	4.75	4.75	4.75	0.52	1.52	± 12.0 %
1900	53.3	1.52	4.49	4.49	4.49	0.49	1.56	± 12.0 %
2450	52.7	1.95	4.01	4.01	4.01	0.70	1.02	± 12.0 %
2600	52.5	2.16	3.85	3.85	3.85	0.58	0.90	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{head}) (TEM cell , f = 900 MHz)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV2 - SN:3022

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-83.1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **EX3-3589 Jan13**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3589**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-14.v3, QA CAL-23.v4, QA CAL-25.v4**
Calibration procedure for dosimetric E-field probes

Calibration date: **January 17, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-12 (No. 217-01508)	Apr-13
Power sensor E4412A	MY41498087	29-Mar-12 (No. 217-01508)	Apr-13
Reference 3 dB Attenuator	SN: S5054 (3c)	27-Mar-12 (No. 217-01531)	Apr-13
Reference 20 dB Attenuator	SN: S5086 (20b)	27-Mar-12 (No. 217-01529)	Apr-13
Reference 30 dB Attenuator	SN: S5129 (30b)	27-Mar-12 (No. 217-01532)	Apr-13
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	20-Jun-12 (No. DAE4-660_Jun12)	Jun-13
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-11)	In house check: Apr-13
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: January 17, 2013			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe EX3DV4

SN:3589

Manufactured: March 30, 2006
Calibrated: January 17, 2013

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3589

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.46	0.40	0.40	$\pm 10.1 \%$
DCP (mV) ^B	100.5	103.8	99.6	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	165.8	$\pm 3.3 \%$
		Y	0.0	0.0	1.0		134.3	
		Z	0.0	0.0	1.0		140.5	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3589

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	41.9	0.89	8.70	8.70	8.70	0.39	0.96	± 12.0 %
835	41.5	0.90	8.40	8.40	8.40	0.52	0.74	± 12.0 %
1750	40.1	1.37	7.34	7.34	7.34	0.45	0.93	± 12.0 %
1900	40.0	1.40	7.09	7.09	7.09	0.80	0.65	± 12.0 %
2450	39.2	1.80	6.37	6.37	6.37	0.39	0.97	± 12.0 %
2600	39.0	1.96	6.19	6.19	6.19	0.30	1.12	± 12.0 %
5200	36.0	4.66	4.48	4.48	4.48	0.45	1.80	± 13.1 %
5300	35.9	4.76	4.27	4.27	4.27	0.45	1.80	± 13.1 %
5500	35.6	4.96	4.14	4.14	4.14	0.50	1.80	± 13.1 %
5600	35.5	5.07	3.81	3.81	3.81	0.55	1.80	± 13.1 %
5800	35.3	5.27	3.85	3.85	3.85	0.55	1.80	± 13.1 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3589

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	55.5	0.96	8.59	8.59	8.59	0.49	0.86	± 12.0 %
835	55.2	0.97	8.43	8.43	8.43	0.38	1.05	± 12.0 %
1750	53.4	1.49	7.87	7.87	7.87	0.44	0.89	± 12.0 %
1900	53.3	1.52	7.46	7.46	7.46	0.58	0.75	± 12.0 %
2450	52.7	1.95	7.07	7.07	7.07	0.80	0.50	± 12.0 %
2600	52.5	2.16	6.68	6.68	6.68	0.80	0.50	± 12.0 %
5200	49.0	5.30	3.99	3.99	3.99	0.50	1.90	± 13.1 %
5300	48.9	5.42	3.81	3.81	3.81	0.50	1.90	± 13.1 %
5500	48.6	5.65	3.52	3.52	3.52	0.55	1.90	± 13.1 %
5600	48.5	5.77	3.32	3.32	3.32	0.60	1.90	± 13.1 %
5800	48.2	6.00	3.66	3.66	3.66	0.60	1.90	± 13.1 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22



Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)


Dynamic Range f(SAR_{head})

(TEM cell , f = 900 MHz)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: EX3DV4 - SN:3589**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	-26.4
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	2 mm



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **ES3-3318_Apr13**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3318**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-23.v4, QA CAL-25.v4**
Calibration procedure for dosimetric E-field probes

Calibration date: **April 29, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	31-Jan-13 (No. DAE4-660_Jan13)	Jan-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Dimce Iliev	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: April 29, 2013			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ES3DV3

SN:3318

Manufactured: January 10, 2012
Calibrated: April 29, 2013

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.15	0.92	1.29	± 10.1 %
DCP (mV) ^B	102.6	105.4	100.8	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB/ μV	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	153.6	±3.5 %
		Y	0.0	0.0	1.0		133.8	
		Z	0.0	0.0	1.0		154.8	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	41.9	0.89	6.59	6.59	6.59	0.25	2.12	± 12.0 %
850	41.5	0.92	6.33	6.33	6.33	0.57	1.25	± 12.0 %
1900	40.0	1.40	5.22	5.22	5.22	0.79	1.25	± 12.0 %
2450	39.2	1.80	4.59	4.59	4.59	0.80	1.30	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	55.5	0.96	6.35	6.35	6.35	0.53	1.42	± 12.0 %
850	55.2	0.99	6.21	6.21	6.21	0.57	1.38	± 12.0 %
1900	53.3	1.52	4.79	4.79	4.79	0.46	1.77	± 12.0 %
2450	52.7	1.95	4.31	4.31	4.31	0.80	1.09	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-103.8
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

Additional Conversion Factors

for Dosimetric E-Field Probe

Type:

ES3DV3

Serial Number:

3318

Place of Assessment:

Zurich

Date of Assessment:

June 19, 2013


Probe Calibration Date:

April 29, 2013

✓
Kox
6/25/13

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. The evaluation is coupled with measured conversion factors (probe calibration date indicated above). The uncertainty of the numerical assessment is based on the extrapolation from measured value at 835 MHz or at 1900 MHz.

Assessed by:



Dosimetric E-Field Probe ES3DV3 SN:3318

Conversion factor ($\pm$ standard deviation)

1750 $\pm$ 50 MHz *ConvF* 5.59 $\pm$ 7%

$\epsilon_r = 40.1 \pm 5\%$
 $\sigma = 1.37 \pm 5\%$ mho/m
(head tissue)

1750 $\pm$ 50 MHz *ConvF* 5.22 $\pm$ 7%

$\epsilon_r = 53.4 \pm 5\%$
 $\sigma = 1.49 \pm 5\%$ mho/m
(body tissue)

Important Note:

For numerically assessed probe conversion factors, parameters Alpha and Delta in the DASY software must have the following entries: Alpha = 0 and Delta = 1.

Please see also DASY Manual.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **EX3-3920_Feb13/2**

CALIBRATION CERTIFICATE (Replacement of No: EX3-3920_Feb13)

Object **EX3DV4 - SN:3920**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-14.v3, QA CAL-23.v4, QA CAL-25.v4**
Calibration procedure for dosimetric E-field probes

Calibration date: **February 27, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

✓
KOK
3/24/13

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-12 (No. 217-01508)	Apr-13
Power sensor E4412A	MY41498087	29-Mar-12 (No. 217-01508)	Apr-13
Reference 3 dB Attenuator	SN: S5054 (3c)	27-Mar-12 (No. 217-01531)	Apr-13
Reference 20 dB Attenuator	SN: S5086 (20b)	27-Mar-12 (No. 217-01529)	Apr-13
Reference 30 dB Attenuator	SN: S5129 (30b)	27-Mar-12 (No. 217-01532)	Apr-13
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	31-Jan-13 (No. DAE4-660_Jan13)	Jan-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-11)	In house check: Apr-13
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by:	Name Claudio Leubler	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature
			Issued: March 5, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe EX3DV4

SN:3920

Manufactured: December 18, 2012
Calibrated: February 27, 2013

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3920

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.34	0.50	0.50	$\pm 10.1 \%$
DCP (mV) ^B	101.2	101.0	99.1	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	134.3	$\pm 3.3 \%$
		Y	0.0	0.0	1.0		164.7	
		Z	0.0	0.0	1.0		161.4	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3920

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	41.9	0.89	9.86	9.86	9.86	0.19	1.39	± 12.0 %
835	41.5	0.90	9.58	9.58	9.58	0.77	0.54	± 12.0 %
1750	40.1	1.37	7.97	7.97	7.97	0.57	0.69	± 12.0 %
1900	40.0	1.40	7.73	7.73	7.73	0.54	0.73	± 12.0 %
2450	39.2	1.80	7.04	7.04	7.04	0.40	0.82	± 12.0 %
2600	39.0	1.96	6.80	6.80	6.80	0.49	0.76	± 12.0 %
5200	36.0	4.66	4.87	4.87	4.87	0.35	1.80	± 13.1 %
5300	35.9	4.76	4.73	4.73	4.73	0.37	1.80	± 13.1 %
5500	35.6	4.96	4.52	4.52	4.52	0.39	1.80	± 13.1 %
5600	35.5	5.07	4.17	4.17	4.17	0.50	1.80	± 13.1 %
5800	35.3	5.27	4.02	4.02	4.02	0.45	1.80	± 13.1 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3920

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	55.5	0.96	9.57	9.57	9.57	0.43	0.83	± 12.0 %
835	55.2	0.97	9.42	9.42	9.42	0.36	0.98	± 12.0 %
1750	53.4	1.49	7.59	7.59	7.59	0.43	0.78	± 12.0 %
1900	53.3	1.52	7.38	7.38	7.38	0.33	0.91	± 12.0 %
2450	52.7	1.95	7.07	7.07	7.07	0.80	0.55	± 12.0 %
2600	52.5	2.16	6.73	6.73	6.73	0.80	0.56	± 12.0 %
5200	49.0	5.30	4.23	4.23	4.23	0.51	1.90	± 13.1 %
5300	48.9	5.42	4.13	4.13	4.13	0.49	1.90	± 13.1 %
5500	48.6	5.65	3.63	3.63	3.63	0.52	1.90	± 13.1 %
5600	48.5	5.77	3.62	3.62	3.62	0.49	1.90	± 13.1 %
5800	48.2	6.00	3.91	3.91	3.91	0.54	1.90	± 13.1 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ , θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: EX3DV4 - SN:3920

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-21.6
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	2 mm



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3209_Mar13**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3209**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-23.v4, QA CAL-25.v4**
Calibration procedure for dosimetric E-field probes

Calibration date: **March 15, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

✓ KOK
3/24/13

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-12 (No. 217-01508)	Apr-13
Power sensor E4412A	MY41498087	29-Mar-12 (No. 217-01508)	Apr-13
Reference 3 dB Attenuator	SN: S5054 (3c)	27-Mar-12 (No. 217-01531)	Apr-13
Reference 20 dB Attenuator	SN: S5086 (20b)	27-Mar-12 (No. 217-01529)	Apr-13
Reference 30 dB Attenuator	SN: S5129 (30b)	27-Mar-12 (No. 217-01532)	Apr-13
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	31-Jan-13 (No. DAE4-660_Jan13)	Jan-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-11)	In house check: Apr-13
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by:	Name Israe El-Naouq	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature
			Issued: March 15, 2013
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ES3DV3

SN:3209

Manufactured: October 14, 2008
Calibrated: March 15, 2013

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3209

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.35	1.33	1.14	$\pm 10.1 \%$
DCP (mV) ^B	99.2	97.8	98.3	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	163.6	$\pm 3.5 \%$
		Y	0.0	0.0	1.0		170.3	
		Z	0.0	0.0	1.0		158.7	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3209

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	41.9	0.89	6.74	6.74	6.74	0.76	1.18	± 12.0 %
835	41.5	0.90	6.46	6.46	6.46	0.31	1.81	± 12.0 %
1750	40.1	1.37	5.39	5.39	5.39	0.80	1.21	± 12.0 %
1900	40.0	1.40	5.21	5.21	5.21	0.78	1.26	± 12.0 %
2450	39.2	1.80	4.57	4.57	4.57	0.65	1.43	± 12.0 %
2600	39.0	1.96	4.43	4.43	4.43	0.75	1.36	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3209

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	55.5	0.96	6.38	6.38	6.38	0.80	1.16	± 12.0 %
835	55.2	0.97	6.28	6.28	6.28	0.52	1.45	± 12.0 %
1750	53.4	1.49	5.03	5.03	5.03	0.58	1.45	± 12.0 %
1900	53.3	1.52	4.77	4.77	4.77	0.70	1.36	± 12.0 %
2450	52.7	1.95	4.34	4.34	4.34	0.80	1.15	± 12.0 %
2600	52.5	2.16	4.11	4.11	4.11	0.80	1.00	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3209

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-40.6
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **ES3-3287_Nov12**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3287**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-23.v4, QA CAL-25.v4**
Calibration procedure for dosimetric E-field probes

Calibration date: **November 15, 2012**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-12 (No. 217-01508)	Apr-13
Power sensor E4412A	MY41498087	29-Mar-12 (No. 217-01508)	Apr-13
Reference 3 dB Attenuator	SN: S5054 (3c)	27-Mar-12 (No. 217-01531)	Apr-13
Reference 20 dB Attenuator	SN: S5086 (20b)	27-Mar-12 (No. 217-01529)	Apr-13
Reference 30 dB Attenuator	SN: S5129 (30b)	27-Mar-12 (No. 217-01532)	Apr-13
Reference Probe ES3DV2	SN: 3013	29-Dec-11 (No. ES3-3013_Dec11)	Dec-12
DAE4	SN: 660	20-Jun-12 (No. DAE4-660_Jun12)	Jun-13
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-11)	In house check: Apr-13
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by:	Name Claudio Leubler	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature
			Issued: November 16, 2012

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}**: A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ES3DV3

SN:3287

Manufactured: June 7, 2010
Calibrated: November 15, 2012

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.31	1.25	1.25	$\pm 10.1 \%$
DCP (mV) ^B	102.9	103.6	101.6	

Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dB	C dB	VR mV	Unc ^E (k=2)
0	CW	0.00	X	0.0	0.0	1.0	116.8	$\pm 3.5 \%$
			Y	0.0	0.0	1.0	118.5	
			Z	0.0	0.0	1.0	154.1	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	41.9	0.89	6.40	6.40	6.40	0.20	2.54	± 12.0 %
835	41.5	0.90	6.17	6.17	6.17	0.34	1.68	± 12.0 %
1750	40.1	1.37	5.16	5.16	5.16	0.63	1.30	± 12.0 %
1900	40.0	1.40	4.96	4.96	4.96	0.48	1.55	± 12.0 %
2450	39.2	1.80	4.30	4.30	4.30	0.79	1.31	± 12.0 %
2600	39.0	1.96	4.19	4.19	4.19	0.80	1.31	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	55.5	0.96	6.14	6.14	6.14	0.28	2.06	± 12.0 %
835	55.2	0.97	6.06	6.06	6.06	0.42	1.63	± 12.0 %
1750	53.4	1.49	4.86	4.86	4.86	0.43	1.64	± 12.0 %
1900	53.3	1.52	4.69	4.69	4.69	0.56	1.54	± 12.0 %
2450	52.7	1.95	4.29	4.29	4.29	0.80	1.02	± 12.0 %
2600	52.5	2.16	4.12	4.12	4.12	0.64	0.92	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz, TEM





f=1800 MHz, R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f = 900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-15.9
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D750V3-1003_Jan13**

CALIBRATION CERTIFICATE

Object **D750V3 - SN: 1003**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **January 07, 2013**

✓ KOK
1/28/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.3 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 601	27-Jun-12 (No. DAE4-601_Jun12)	Jun-13
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: January 8, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.4
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.4 $\pm$ 6 %	0.89 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.12 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.46 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.51 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.8 $\pm$ 6 %	0.97 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.23 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.83 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.48 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.87 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	56.1 Ω - 0.2 j Ω
Return Loss	- 24.8 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	49.6 Ω - 3.5 j Ω
Return Loss	- 29.1 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.043 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	January 21, 2009

DASY5 Validation Report for Head TSL

Date: 07.01.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1003

Communication System: CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.89 \text{ S/m}$; $\epsilon_r = 41.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.28, 6.28, 6.28); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.4(1052); SEMCAD X 14.6.8(7028)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.114 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.24 W/kg

SAR(1 g) = 2.12 W/kg; SAR(10 g) = 1.38 W/kg

Maximum value of SAR (measured) = 2.47 W/kg




0 dB = 2.47 W/kg = 3.93 dBW/kg

Impedance Measurement Plot for Head TSL


7 Jan 2013 12:55:14
 [CH1] S11 1 U FS 1: 56.100 Ω -179.69 m Ω 1.1810 nF 750.000 000 MHz

*
 De1
 Ca
 Avg
 16
 H1d



CH2 S11 LOG 5 dB/REF -20 dB 1: -24.803 dB 750.000 000 MHz

Ca
 Avg
 16
 H1d



DASY5 Validation Report for Body TSL

Date: 07.01.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1003

Communication System: CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.97 \text{ S/m}$; $\epsilon_r = 54.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.11, 6.11, 6.11); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.4(1052); SEMCAD X 14.6.8(7028)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 53.114 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.25 W/kg

SAR(1 g) = 2.23 W/kg; SAR(10 g) = 1.48 W/kg

Maximum value of SAR (measured) = 2.57 W/kg



Impedance Measurement Plot for Body TSL

7 Jan 2013 09:57:48
CH1 S11 1 U FS 1: 49.564 Ω -3.4629 Ω 61.280 pF 750.000 000 MHz


*

De1

Ca

Avg
16

H1 d




CH2 S11 LOG 5 dB/REF -20 dB 1:-29.119 dB 750.000 000 MHz

Ca

Avg
16

H1 d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D835V2-4d119_Apr13**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d119**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **April 25, 2013**

✓
KOK
5/8/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 909	11-Sep-12 (No. DAE4-909_Sep12)	Sep-13
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by: **Claudio Leubler** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Technical Manager

Signature

Issued: April 26, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.6
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.8 $\pm$ 6 %	0.94 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.51 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.68 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.62 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.30 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.0 $\pm$ 6 %	1.01 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.47 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.54 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.62 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.31 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	50.1 Ω - 4.7 j Ω
Return Loss	- 26.6 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	45.8 Ω - 6.3 j Ω
Return Loss	- 22.1 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.385 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	June 29, 2010

DASY5 Validation Report for Head TSL

Date: 25.04.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 40.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.05, 6.05, 6.05); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 11.09.2012
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.387 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.86 W/kg

SAR(1 g) = 2.51 W/kg; SAR(10 g) = 1.62 W/kg

Maximum value of SAR (measured) = 2.93 W/kg




0 dB = 2.93 W/kg = 4.67 dBW/kg

Impedance Measurement Plot for Head TSL


25 Apr 2013 09:11:06
 CH1 S11 1 U FS 1: 50.061 Ω -4.6621 Ω 40.884 pF 835.000 000 MHz

*
 Del
 CA
 Avg
 16
 H1 d



CH2 S11 LOG 5 dB/REF -20 dB 1:-26.641 dB 835.000 000 MHz

CA
 Avg
 16
 H1 d



DASY5 Validation Report for Body TSL

Date: 24.04.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1.01 \text{ S/m}$; $\epsilon_r = 54$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.04, 6.04, 6.04); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 11.09.2012
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 55.178 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.68 W/kg


SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.62 W/kg

Maximum value of SAR (measured) = 2.89 W/kg



0 dB = 2.89 W/kg = 4.61 dBW/kg

Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D1765V2-1008_May13**

CALIBRATION CERTIFICATE

Object **D1765V2 - SN: 1008**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **May 14, 2013**

*✓ 100K
5/23/13*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by: **Jeton Kastrat** Function: **Laboratory Technician** Signature: *[Signature]*

Approved by: **Katja Pokovic** Technical Manager *[Signature]*

Issued: May 15, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.6
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.1	1.37 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.1 $\pm$ 6 %	1.33 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.09 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	36.8 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	4.85 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	19.6 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.4	1.49 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	51.7 $\pm$ 6 %	1.47 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.53 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	38.2 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.10 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.4 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	48.3 Ω - 6.4 j Ω
Return Loss	- 23.5 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	43.8 Ω - 6.1 j Ω
Return Loss	- 20.6 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.211 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	October 06, 2005

DASY5 Validation Report for Head TSL

Date: 14.05.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1765 MHz; Type: D1765V2; Serial: D1765V2 - SN: 1008

Communication System: UID 0 - CW ; Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.33$ S/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.18, 5.18, 5.18); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.430 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 16.3 W/kg

SAR(1 g) = 9.09 W/kg; SAR(10 g) = 4.85 W/kg



Maximum value of SAR (measured) = 11.3 W/kg



Impedance Measurement Plot for Head TSL

14 May 2013 15:57:39
[CH1] S11 1 U FS 1: 48.322 Ω -6.3848 Ω 14.244 pF 1 750.000 000 MHz

*
De1
CA
Avg
16
H1 d



DASY5 Validation Report for Body TSL

Date: 13.05.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1765 MHz; Type: D1765V2; Serial: D1765V2 - SN: 1008

Communication System: UID 0 - CW ; Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.47$ S/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.83, 4.83, 4.83); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.430 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 16.4 W/kg

SAR(1 g) = 9.53 W/kg; SAR(10 g) = 5.1 W/kg

Maximum value of SAR (measured) = 12.0 W/kg




0 dB = 12.0 W/kg = 10.79 dBW/kg

Impedance Measurement Plot for Body TSL


13 May 2013 15:25:53
[CH1] S11 1 U FS 1: 43.775 Ω -6.1426 Ω 14.806 pF 1 750.000 000 MHz

*
De1
Cor



Avg
16

H1d





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D1900V2-5d148_Feb13**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d148**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **February 06, 2013**

✓
KOK
2/21/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.3 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 601	27-Jun-12 (No. DAE4-601_Jun12)	Jun-13
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by: **Leif Klysner** Name: **Leif Klysner** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Name: **Katja Pokovic** Technical Manager

Signature

Issued: February 6, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.5
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.4 $\pm$ 6 %	1.38 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.87 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	39.7 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.18 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	20.8 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	51.9 $\pm$ 6 %	1.53 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	10.3 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	40.8 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.45 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.7 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.1 Ω + 5.9 j Ω
Return Loss	- 24.3 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.3 Ω + 6.3 j Ω
Return Loss	- 23.6 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.199 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 11, 2011

DASY5 Validation Report for Head TSL

Date: 06.02.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d148

Communication System: CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.98, 4.98, 4.98); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.534 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.87 W/kg; SAR(10 g) = 5.18 W/kg

Maximum value of SAR (measured) = 12.1 W/kg




0 dB = 12.1 W/kg = 10.83 dBW/kg

Impedance Measurement Plot for Head TSL


6 Feb 2013 09:25:10
 CH1 S11 1 U FS 1: 52.125 $\angle$ 5.8711 $\angle$ 491.80 μ H 1 900.000 000 MHz

*
 Del
 CA
 Avg
 16
 H1d



CH2 S11 LOG 5 dB/REF -20 dB 1: -24.287 dB 1 900.000 000 MHz

CA
 Avg
 16
 H1d



DASY5 Validation Report for Body TSL

Date: 06.02.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d148

Communication System: CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.53$ S/m; $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.6, 4.6, 4.6); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.534 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 17.9 W/kg

SAR(1 g) = 10.3 W/kg; SAR(10 g) = 5.45 W/kg

Maximum value of SAR (measured) = 13.1 W/kg




0 dB = 13.1 W/kg = 11.17 dBW/kg

Impedance Measurement Plot for Body TSL

6 Feb 2013 09:24:17
CH1 S11 1 U FS 1: 48.344 Ω 6.2715 Ω 525.34 μ H 1 900.000 000 MHz


*
De1
CA



Avg
16
H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-23.628 dB 1 900.000 000 MHz

CA
Avg
16
H1d





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D2450V2-797_Jan13**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 797**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **January 08, 2013**

✓
KOK
1/28/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.3 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 601	27-Jun-12 (No. DAE4-601_Jun12)	Jun-13
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Israe El-Naouq	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: January 8, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.4
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	37.9 $\pm$ 6 %	1.85 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.4 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	52.5 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.20 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.5 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	50.5 $\pm$ 6 %	2.01 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.7 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	49.6 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.88 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.2 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$53.3 \Omega + 3.1 j\Omega$
Return Loss	- 27.1 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$49.1 \Omega + 4.9 j\Omega$
Return Loss	- 26.0 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.152 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	January 24, 2006

DASY5 Validation Report for Head TSL

Date: 08.01.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 797

Communication System: CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.85$ S/m; $\epsilon_r = 37.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.52, 4.52, 4.52); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.4(1052); SEMCAD X 14.6.8(7028)

Dipole Calibration for Head Tissue/ $P_{in}=250$ mW, $d=10$ mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 99.154 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 27.8 W/kg

SAR(1 g) = 13.4 W/kg; SAR(10 g) = 6.2 W/kg

Maximum value of SAR (measured) = 17.0 W/kg




0 dB = 17.0 W/kg = 12.30 dBW/kg

Impedance Measurement Plot for Head TSL


8 Jan 2013 12:37:14
CH1 S11 1 U FS 1: 53.346 $\angle$ 3.0762 $\angle$ 199.83 pH 2 450.000 000 MHz

*
De1
Cor
Avg
16
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1: -27.136 dB 2 450.000 000 MHz

Cor
Avg
16
H1d



DASY5 Validation Report for Body TSL

Date: 08.01.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 797

Communication System: CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.01$ S/m; $\epsilon_r = 50.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.42, 4.42, 4.42); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.4(1052); SEMCAD X 14.6.8(7028)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.935 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 26.7 W/kg


SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.88 W/kg

Maximum value of SAR (measured) = 16.7 W/kg



0 dB = 16.7 W/kg = 12.23 dBW/kg

Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D5GHzV2-1057_Jan13**

CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN: 1057**

Calibration procedure(s) **QA CAL-22.v2**
Calibration procedure for dipole validation kits between 3-6 GHz

Calibration date: **January 11, 2013**

✓
KOK
1/29/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.3 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe EX3DV4	SN: 3503	28-Dec-12 (No. EX3-3503_Dec12)	Dec-13
DAE4	SN: 601	27-Jun-12 (No. DAE4-601_Jun12)	Jun-13
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by: **Israe El-Naouq** Name: **Israe El-Naouq** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Name: **Katja Pokovic** Function: **Technical Manager**

Signature
Israe El-Naouq
Katja Pokovic

Issued: January 11, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEC 62209-2, "Evaluation of Human Exposure to Radio Frequency Fields from Handheld and Body-Mounted Wireless Communication Devices in the Frequency Range of 30 MHz to 6 GHz: Human models, Instrumentation, and Procedures"; Part 2: "Procedure to determine the Specific Absorption Rate (SAR) for including accessories and multiple transmitters", March 2010
- b) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- c) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.5
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy = 4.0 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	5200 MHz $\pm$ 1 MHz 5300 MHz $\pm$ 1 MHz 5500 MHz $\pm$ 1 MHz 5600 MHz $\pm$ 1 MHz 5800 MHz $\pm$ 1 MHz	

Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	36.0	4.66 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	34.6 $\pm$ 6 %	4.50 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5200 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	7.66 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	75.9 W/kg $\pm$ 19.9 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.17 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	21.4 W/kg $\pm$ 19.5 % (k=2)

Head TSL parameters at 5300 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.76 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.5 ± 6 %	4.60 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5300 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	7.76 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	76.9 W / kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.22 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	21.9 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.6	4.96 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.2 ± 6 %	4.79 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5500 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.09 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.1 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.28 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.5 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.1 ± 6 %	4.88 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.12 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.4 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.30 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.7 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.3	5.27 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	33.8 ± 6 %	5.09 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5800 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	7.69 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	76.1 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.17 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	21.4 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5200 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	49.0	5.30 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.0 ± 6 %	5.42 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5200 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.61 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.5 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.13 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.1 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5300 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.9	5.42 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.8 ± 6 %	5.55 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5300 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.59 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.13 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.1 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.6	5.65 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.5 ± 6 %	5.81 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5500 MHz

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	8.14 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	80.8 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.26 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.4 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.5	5.77 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.3 ± 6 %	5.94 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5600 MHz

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	8.10 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	80.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.25 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.3 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5800 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.2	6.00 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.0 ± 6 %	6.21 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5800 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.57 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.1 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.09 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.7 W/kg ± 19.5 % (k=2)

Appendix

Antenna Parameters with Head TSL at 5200 MHz

Impedance, transformed to feed point	50.5 Ω - 9.8 j Ω
Return Loss	- 20.3 dB

Antenna Parameters with Head TSL at 5300 MHz

Impedance, transformed to feed point	48.5 Ω - 4.5 j Ω
Return Loss	- 26.4 dB

Antenna Parameters with Head TSL at 5500 MHz

Impedance, transformed to feed point	50.6 Ω - 5.8 j Ω
Return Loss	- 24.8 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	53.9 Ω - 3.8 j Ω
Return Loss	- 25.6 dB

Antenna Parameters with Head TSL at 5800 MHz

Impedance, transformed to feed point	52.5 Ω - 4.4 j Ω
Return Loss	- 26.1 dB

Antenna Parameters with Body TSL at 5200 MHz

Impedance, transformed to feed point	49.3 Ω - 7.9 j Ω
Return Loss	- 22.0 dB

Antenna Parameters with Body TSL at 5300 MHz

Impedance, transformed to feed point	48.7 Ω - 3.2 j Ω
Return Loss	- 29.2 dB

Antenna Parameters with Body TSL at 5500 MHz

Impedance, transformed to feed point	51.2 Ω - 4.8 j Ω
Return Loss	- 26.2 dB

Antenna Parameters with Body TSL at 5600 MHz

Impedance, transformed to feed point	53.6 Ω - 2.1 j Ω
Return Loss	- 27.9 dB

Antenna Parameters with Body TSL at 5800 MHz

Impedance, transformed to feed point	53.3 Ω - 2.9 j Ω
Return Loss	- 27.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.202 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	November 27, 2006

DASY5 Validation Report for Head TSL

Date: 11.01.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1057

Communication System: CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.5$ S/m; $\epsilon_r = 34.6$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5300$ MHz; $\sigma = 4.6$ S/m; $\epsilon_r = 34.5$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5500$ MHz; $\sigma = 4.79$ S/m; $\epsilon_r = 34.2$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5600$ MHz; $\sigma = 4.88$ S/m; $\epsilon_r = 34.1$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5800$ MHz; $\sigma = 5.09$ S/m; $\epsilon_r = 33.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.41, 5.41, 5.41); Calibrated: 28.12.2012, ConvF(5.1, 5.1, 5.1); Calibrated: 28.12.2012, ConvF(4.91, 4.91, 4.91); Calibrated: 28.12.2012, ConvF(4.76, 4.76, 4.76); Calibrated: 28.12.2012, ConvF(4.81, 4.81, 4.81); Calibrated: 28.12.2012;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.671 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 29.4 W/kg

SAR(1 g) = 7.66 W/kg; SAR(10 g) = 2.17 W/kg

Maximum value of SAR (measured) = 18.5 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.473 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 30.3 W/kg

SAR(1 g) = 7.76 W/kg; SAR(10 g) = 2.22 W/kg

Maximum value of SAR (measured) = 18.8 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.735 V/m; Power Drift = 0.08 dB


Peak SAR (extrapolated) = 33.2 W/kg

SAR(1 g) = 8.09 W/kg; SAR(10 g) = 2.28 W/kg

Maximum value of SAR (measured) = 20.1 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 63.848 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 33.5 W/kg
SAR(1 g) = 8.12 W/kg; SAR(10 g) = 2.3 W/kg
Maximum value of SAR (measured) = 20.2 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 60.467 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 33.3 W/kg
SAR(1 g) = 7.69 W/kg; SAR(10 g) = 2.17 W/kg
Maximum value of SAR (measured) = 19.4 W/kg



0 dB = 19.4 W/kg = 12.88 dBW/kg


Impedance Measurement Plot for Head TSL

11 Jan 2013 09:26:56
 [CH1] S11 1 U FS 1: 50.543 Ω -9.7754 Ω 3.1310 pF 5 200.000 000 MHz

*
 Del
 CA

Avg
 16

H1 d



CH1 Markers


2: 48.508 Ω
 -4.4805 Ω
 5.30000 GHz
 3: 50.617 Ω
 -5.7559 Ω
 5.50000 GHz
 4: 53.891 Ω
 -3.8418 Ω
 5.60000 GHz
 5: 52.500 Ω
 -4.4160 Ω
 5.80000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -20.273 dB 5 200.000 000 MHz

CA

Avg
 16

H1 d



CH2 Markers

2: -25.396 dB
 5.30000 GHz
 3: -24.818 dB
 5.50000 GHz
 4: -25.573 dB
 5.60000 GHz
 5: -26.115 dB
 5.80000 GHz

START 5 000.000 000 MHz

STOP 6 000.000 000 MHz

DASY5 Validation Report for Body TSL

Date: 10.01.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1057

Communication System: CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.42$ S/m; $\epsilon_r = 47$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5300$ MHz; $\sigma = 5.55$ S/m; $\epsilon_r = 46.8$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5500$ MHz; $\sigma = 5.81$ S/m; $\epsilon_r = 46.5$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5600$ MHz; $\sigma = 5.94$ S/m; $\epsilon_r = 46.3$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5800$ MHz; $\sigma = 6.21$ S/m; $\epsilon_r = 46$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(4.91, 4.91, 4.91); Calibrated: 28.12.2012, ConvF(4.67, 4.67, 4.67); Calibrated: 28.12.2012, ConvF(4.43, 4.43, 4.43); Calibrated: 28.12.2012, ConvF(4.22, 4.22, 4.22); Calibrated: 28.12.2012, ConvF(4.38, 4.38, 4.38); Calibrated: 28.12.2012;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 27.06.2012
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 59.074 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 30.4 W/kg

SAR(1 g) = 7.61 W/kg; SAR(10 g) = 2.13 W/kg

Maximum value of SAR (measured) = 18.0 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.924 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 30.9 W/kg

SAR(1 g) = 7.59 W/kg; SAR(10 g) = 2.13 W/kg

Maximum value of SAR (measured) = 17.9 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 59.561 V/m; Power Drift = -0.01 dB


Peak SAR (extrapolated) = 35.3 W/kg

SAR(1 g) = 8.14 W/kg; SAR(10 g) = 2.26 W/kg


Maximum value of SAR (measured) = 19.7 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 58.884 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 36.3 W/kg
SAR(1 g) = 8.1 W/kg; SAR(10 g) = 2.25 W/kg
Maximum value of SAR (measured) = 20.0 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 55.753 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 35.6 W/kg
SAR(1 g) = 7.57 W/kg; SAR(10 g) = 2.09 W/kg
Maximum value of SAR (measured) = 18.9 W/kg



Impedance Measurement Plot for Body TSL



APPENDIX D: SAR TISSUE SPECIFICATIONS

Measurement Procedure for Tissue verification:

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the tissue. The tissue was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity ϵ can be calculated from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

Table D-I
Composition of the Tissue Equivalent Matter

Frequency (MHz)	750	835	1750	1900	2450	5200-5800
Tissue	Body	Body	Body	Body	Body	Body
Ingredients (% by weight)						
Bactericide	See Next Page	0.1				
DGBE			31	29.44	26.7	
HEC		1				
NaCl		0.94	0.2	0.39	0.1	
Sucrose		44.9				
Polysorbate (Tween) 80						20
Water		53.06	68.8	70.17	73.2	80

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			APPENDIX D: Page 1 of 2

2 Composition / Information on ingredients

The Item is composed of the following ingredients:

H ₂ O	Water, 35 – 58%
Sucrose	Sugar, white, refined, 40 – 60%
NaCl	Sodium Chloride, 0 – 6%
Hydroxyethyl-cellulose	Medium Viscosity (CAS# 9004-62-0), <0.3%
Preventol-D7	Preservative: aqueous preparation, (CAS# 55965-84-9), containing 5-chloro-2-methyl-3(2H)-isothiazolone and 2-methyl-3(2H)-isothiazolone, 0.1 – 0.7%
Relevant for safety; Refer to the respective Safety Data Sheet*.	

Figure D-1
Composition of 750 MHz Body Tissue Equivalent Matter

Note: 750MHz liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

Measurement Certificate / Material Test

Item Name	Body Tissue Simulating Liquid (MSL750)
Product No.	SL AAM 075 AA (Charge: 111130-3)
Manufacturer	SPEAG

Measurement Method
TSL dielectric parameters measured using calibrated OCP probe (type DAK).

Target Parameters
Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

Test Condition
Ambient Condition 22°C ; 30% humidity
TSL Temperature 22°C
Test Date 7-Dec-11

Additional Information
TSL Density 1.212 g/cm ³
TSL Heat-capacity 3.006 kJ/(kg*K)

Results

f [MHz]	Measured			Target			Diff.to Target (%)	
	HP-e'	HP-e''	sigma	eps	sigma		Δ-eps	Δ-sigma
600	57.9	25.01	0.83	56.1	0.95	3.1	-12.3	
625	57.6	24.66	0.86	56.0	0.95	2.9	-10.1	
650	57.4	24.31	0.88	55.9	0.96	2.6	-8.0	
675	57.1	24.02	0.90	55.8	0.96	2.3	-5.8	
700	56.8	23.74	0.92	55.7	0.96	2.0	-3.7	
725	56.6	23.50	0.95	55.6	0.96	1.7	-1.5	
750	56.4	23.26	0.97	55.5	0.96	1.5	0.8	
775	56.1	23.06	0.99	55.4	0.97	1.2	3.0	
800	55.8	22.86	1.02	55.3	0.97	0.9	5.2	
825	55.6	22.72	1.04	55.2	0.98	0.6	6.6	
850	55.5	22.64	1.05	55.2	0.98	0.5	7.3	
875	55.4	22.57	1.07	55.2	0.99	0.4	8.0	
900	55.1	22.44	1.09	55.1	1.02	0.1	7.2	
925	54.9	22.31	1.12	55.0	1.05	-0.2	6.4	
950	54.7	22.20	1.14	55.0	1.08	-0.5	7.5	
975	54.5	22.09	1.17	54.9	1.08	-0.9	8.5	
1000	54.3	21.99	1.19	54.9	1.09	-1.2	9.7	
1000	54.1	21.89	1.22	54.8	1.10	-1.4	10.9	




Figure D-2
750MHz Body Tissue Equivalent Matter

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet	APPENDIX D: Page 2 of 2		

APPENDIX E: SAR SYSTEM VALIDATION

Per FCC KDB 865664 D02v01, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in IEEE 1528-2003 and FCC KDB 865664 D01 v01. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table E-I
SAR System Validation Summary

SAR SYSTEM #	FREQ. [MHz]	DATE	PROBE SN	PROBE TYPE	PROBE CAL. POINT		COND.	PERM.	CW VALIDATION			MOD. VALIDATION		
							(σ)	(ϵ_r)	SENSI- TIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
E	750	3/28/2013	3920	EX3DV4	750	Body	0.974	55.21	PASS	PASS	PASS	N/A	N/A	N/A
G	835	3/26/2013	3209	ES3DV3	835	Body	1.006	54.42	PASS	PASS	PASS	GMSK	PASS	N/A
B	1750	1/28/2013	3287	ES3DV3	1750	Body	1.524	52.77	PASS	PASS	PASS	N/A	N/A	N/A
D	1900	10/17/2012	3288	ES3DV3	1900	Body	1.562	52.56	PASS	PASS	PASS	GMSK	PASS	N/A
D	1900	9/10/2013	3022	ES3DV3	1900	Body	1.516	52.49	PASS	PASS	PASS	GMSK	PASS	N/A
H	2450	6/21/2013	3318	ES3DV3	2450	Body	2.006	51.66	PASS	PASS	PASS	OFDM	N/A	PASS
A	5200	1/23/2013	3589	EX3DV4	5200	Body	5.292	47.85	PASS	PASS	PASS	OFDM	N/A	PASS
A	5300	1/23/2013	3589	EX3DV4	5300	Body	5.477	47.47	PASS	PASS	PASS	OFDM	N/A	PASS
A	5500	1/23/2013	3589	EX3DV4	5500	Body	5.729	47.03	PASS	PASS	PASS	OFDM	N/A	PASS
A	5600	1/23/2013	3589	EX3DV4	5600	Body	5.916	46.70	PASS	PASS	PASS	OFDM	N/A	PASS
A	5800	1/23/2013	3589	EX3DV4	5800	Body	6.233	46.20	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: All measurements were performed using probes calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to KDB 865664.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/13 - 09/24/13	DUT Type: Portable Tablet			APPENDIX E: Page 1 of 1

APPENDIX G: SENSOR TRIGGERING DATA SUMMARY

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/13 – 09/24/13	DUT Type: Portable Tablet			APPENDIX G: Page 1 of 5

A3LSMP605 Sensor Triggering Data Summary

Per FCC KDB Publication 616217 D04, this device was tested by the manufacturer to determine the proximity sensor triggering distances for the back side and left edge of the device. The measured output power within ± 5 mm of the triggering points (or until touching the phantom) is included for back side and each applicable edge. The output power data in the tables below was measured and provided by the applicant.

To ensure all production units are compliant it is necessary to test SAR at a distance 1mm less than the smallest distance from the device and SAR phantom (determined from these triggering tests according to the KDB 616217 D04) with the device at maximum output power without power reduction. These additional SAR Tests are included additionally to the SAR tests for the device touching the SAR phantom, with reduced power.

The operational description contains information explaining how this device remains compliant in the event of a sensor malfunction.

Back Side

Moving device toward the phantom:

KDB 616217 Measured Power [dBm]											
Distance[mm]	18	17	16	15	14	13	12	11	10	9	8
LTE B2	22.68	22.83	22.76	22.69	22.76	14.96	14.86	14.99	15.10	15.14	14.97
LTE B4	22.91	22.71	22.65	22.93	22.79	15.24	15.21	15.03	14.87	14.79	14.85
LTE B5	22.74	22.97	22.86	22.71	22.68	18.56	18.74	18.98	18.62	18.54	18.64
LTE B17	22.77	22.84	22.90	22.78	22.95	19.21	19.06	19.14	19.32	19.21	19.41
GSM850	31.74	31.64	31.70	31.61	31.47	26.17	26.18	26.02	25.98	26.31	26.11
GSM1900	29.71	29.51	29.54	29.64	29.87	22.34	22.47	22.41	22.35	22.21	22.16
GPRS850 1Tx	31.32	31.55	31.73	31.68	31.62	26.21	26.24	26.12	26.32	26.34	26.47
GPRS850 2Tx	30.18	30.28	30.08	30.36	30.33	24.63	24.62	24.57	24.85	24.87	24.71
GPRS850 3Tx	28.36	28.56	28.67	28.45	28.69	23.28	23.21	23.10	23.42	23.28	23.17
GPRS850 4Tx	27.07	27.14	27.41	27.13	27.26	21.74	21.68	21.71	21.68	21.82	21.90
GPRS1900 1Tx	29.30	29.47	29.39	29.31	29.12	22.44	22.04	22.28	22.40	22.33	22.07
GPRS1900 2Tx	28.62	28.79	28.33	28.54	28.69	21.01	21.18	21.37	21.12	21.24	20.98
GPRS1900 3Tx	26.45	26.64	26.70	26.57	26.92	19.89	19.64	19.74	19.51	19.38	19.87
GPRS1900 4Tx	25.39	25.48	25.33	25.51	25.37	18.36	18.32	18.28	18.12	18.31	18.04
WCDMA850	22.05	22.42	22.30	22.18	22.39	20.03	20.41	20.32	20.17	20.24	20.37
WCDMA1900	22.32	22.43	22.08	22.32	22.41	15.27	15.28	15.21	15.34	15.38	15.36
EDGE850 1Tx	26.38	26.43	26.36	26.39	26.40	24.25	24.82	24.38	24.36	24.37	24.73
EDGE850 2Tx	24.37	24.51	24.89	24.60	24.54	23.37	23.37	23.44	23.22	23.31	23.26
EDGE850 3Tx	22.36	22.15	22.84	22.46	22.39	22.28	22.39	22.05	22.43	22.38	22.08
EDGE850 4Tx	21.53	21.30	21.31	21.49	21.33	20.34	20.19	20.28	20.12	19.98	19.89
EDGE1900 1Tx	25.38	25.58	25.39	25.54	25.70	21.44	21.62	21.69	21.80	21.87	21.91
EDGE1900 2Tx	24.40	24.28	24.33	24.38	24.34	20.41	20.35	20.31	20.25	20.30	20.31
EDGE1900 3Tx	23.37	23.40	23.11	23.35	23.08	18.39	17.76	18.18	17.81	18.07	18.19
EDGE1900 4Tx	22.29	22.24	22.33	22.29	22.17	16.56	16.66	16.39	16.45	16.71	16.84

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/13 – 09/24/13	DUT Type: Portable Tablet			APPENDIX G: Page 2 of 5

Moving device away from the phantom:

KDB 616217															
Measured Power [dBm]															
Distance[mm]	24	21	18	17	16	15	14	13	12	11	10	9	6	3	0
LTE B2	22.73	22.70	22.68	22.83	22.76	22.69	22.76	14.96	14.86	14.99	15.10	15.14	15.19	15.10	15.14
LTE B4	22.54	22.74	22.91	22.71	22.65	22.93	22.79	15.24	15.21	15.03	14.87	14.79	15.05	15.21	15.11
LTE B5	22.63	22.79	22.74	22.97	22.86	22.71	22.68	18.56	18.74	18.98	18.62	18.54	18.55	18.72	18.63
LTE B17	22.64	22.71	22.77	22.84	22.90	22.78	22.95	19.21	19.06	19.14	19.32	19.21	19.21	19.28	19.11
GSM850	31.58	31.33	31.74	31.64	31.70	31.61	31.47	26.17	26.18	26.02	25.98	26.31	26.31	26.42	26.08
GSM1900	29.57	29.41	29.71	29.51	29.54	29.64	29.87	22.34	22.47	22.41	22.35	22.21	22.31	22.47	22.02
GPRS850 1Tx	31.74	31.58	31.32	31.55	31.73	31.68	31.62	26.21	26.24	26.12	26.32	26.34	26.32	26.27	26.15
GPRS850 2Tx	30.43	30.31	30.18	30.28	30.08	30.36	30.33	24.63	24.62	24.57	24.85	24.87	24.82	24.72	24.55
GPRS850 3Tx	28.56	28.64	28.36	28.56	28.67	28.45	28.69	23.28	23.21	23.10	23.42	23.28	23.32	23.34	23.41
GPRS850 4Tx	26.92	27.22	27.07	27.14	27.41	27.13	27.26	21.74	21.68	21.71	21.68	21.82	21.51	21.68	21.72
GPRS1900 1Tx	29.55	29.26	29.30	29.47	29.39	29.31	29.12	22.44	22.04	22.28	22.40	22.33	22.08	22.24	22.34
GPRS1900 2Tx	28.20	28.62	28.62	28.79	28.33	28.54	28.69	21.01	21.18	21.37	21.12	21.24	21.18	21.07	21.22
GPRS1900 3Tx	26.53	26.31	26.45	26.64	26.70	26.57	26.92	19.89	19.64	19.74	19.51	19.38	19.72	19.62	19.58
GPRS1900 4Tx	25.21	25.23	25.39	25.48	25.33	25.51	25.37	18.36	18.32	18.28	18.12	18.31	18.22	18.31	18.13
WCDMA850	22.34	22.48	22.05	22.42	22.30	22.18	22.39	20.03	20.41	20.32	20.17	20.24	20.35	20.24	20.16
WCDMA1900	22.36	22.25	22.32	22.43	22.08	22.32	22.41	15.27	15.28	15.21	15.34	15.38	15.27	15.13	15.11
EDGE850 1Tx	26.07	26.39	26.38	26.43	26.36	26.39	26.40	24.25	24.82	24.38	24.36	24.37	24.38	24.16	24.37
EDGE850 2Tx	24.52	24.24	24.37	24.51	24.89	24.60	24.54	23.37	23.37	23.44	23.22	23.31	23.44	23.34	23.12
EDGE850 3Tx	22.12	22.27	22.36	22.15	22.84	22.46	22.39	22.28	22.39	22.05	22.43	22.38	22.05	22.31	22.68
EDGE850 4Tx	21.51	21.43	21.53	21.30	21.31	21.49	21.33	20.34	20.19	20.28	20.12	19.98	20.28	20.12	20.67
EDGE1900 1Tx	25.75	25.36	25.38	25.58	25.39	25.54	25.70	21.44	21.62	21.69	21.80	21.87	21.89	21.80	21.77
EDGE1900 2Tx	24.33	24.62	24.40	24.28	24.33	24.38	24.34	20.41	20.35	20.31	20.25	20.30	20.23	20.21	20.30
EDGE1900 3Tx	23.19	23.31	23.37	23.40	23.11	23.35	23.08	18.39	17.76	18.18	17.81	18.07	18.18	18.41	18.07
EDGE1900 4Tx	22.38	22.33	22.29	22.24	22.33	22.29	22.17	16.56	16.66	16.39	16.45	16.71	16.79	16.55	16.61

Based on the most conservative measured triggering distance of 13 mm, additional SAR measurements were required at 12 mm from the back side.

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/13 – 09/24/13	DUT Type: Portable Tablet	APPENDIX G: Page 3 of 5		

Left Edge

Moving device toward the phantom:

KDB 616217 Measured Power [dBm]											
Distance[mm]	21	20	19	18	17	16	15	14	13	12	11
LTE B2	22.72	22.81	22.72	22.67	22.76	14.99	15.22	14.84	14.86	14.79	15.10
LTE B4	22.64	22.70	22.61	22.83	22.79	15.03	15.42	15.31	15.21	15.24	14.87
LTE B5	22.59	22.87	22.84	22.61	22.68	18.98	18.75	18.67	18.74	18.72	18.62
LTE B17	22.61	22.74	22.70	22.79	22.95	19.14	19.21	19.37	19.06	19.10	19.32
GSM850	31.43	31.52	31.62	31.65	31.47	26.02	26.32	26.22	26.18	26.23	25.98
GSM1900	29.43	29.56	29.64	29.68	29.87	22.41	22.11	22.37	22.47	22.34	22.35
GPRS850 1Tx	31.59	31.67	31.63	31.71	31.62	26.12	26.32	26.37	26.24	26.29	26.32
GPRS850 2Tx	30.35	30.32	30.18	30.46	30.33	24.57	24.68	24.52	24.62	24.77	24.85
GPRS850 3Tx	28.69	28.76	28.57	28.35	28.69	23.10	23.39	23.17	23.21	23.50	23.42
GPRS850 4Tx	27.27	27.32	27.43	27.43	27.26	21.71	21.57	21.63	21.68	21.82	21.68
GPRS1900 1Tx	29.26	29.41	29.22	29.61	29.12	22.28	22.41	22.34	22.04	22.37	22.40
GPRS1900 2Tx	28.64	28.78	28.44	28.64	28.69	21.37	21.34	21.09	21.18	21.42	21.12
GPRS1900 3Tx	26.33	26.60	26.61	26.53	26.92	19.74	19.76	19.79	19.64	19.61	19.51
GPRS1900 4Tx	25.33	25.41	25.34	25.54	25.37	18.28	18.18	18.45	18.32	18.56	18.12
WCDMA850	22.27	22.42	22.38	22.28	22.39	20.32	20.23	20.13	20.41	20.42	20.17
WCDMA1900	22.22	22.43	22.17	22.42	22.41	15.21	15.24	15.38	15.28	15.12	15.34
EDGE850 1Tx	26.33	26.43	26.39	26.19	26.40	24.38	24.34	24.25	24.82	24.11	24.36
EDGE850 2Tx	24.27	24.51	24.80	24.71	24.54	23.34	23.45	23.37	23.37	23.29	23.15
EDGE850 3Tx	22.21	22.15	22.31	22.26	22.39	22.25	22.26	22.14	22.39	22.37	22.43
EDGE850 4Tx	21.40	21.30	21.38	21.68	21.33	20.28	20.39	20.41	20.89	20.57	20.63
EDGE1900 1Tx	25.32	25.58	25.39	25.44	25.70	21.89	21.41	21.39	21.52	21.53	21.73
EDGE1900 2Tx	24.61	24.28	24.62	24.39	24.34	20.31	20.36	20.42	20.16	20.41	20.25
EDGE1900 3Tx	23.40	23.40	23.31	23.34	23.08	18.18	18.15	18.17	17.76	18.03	17.81
EDGE1900 4Tx	22.44	22.24	22.48	22.42	22.17	16.39	16.53	16.38	16.66	16.59	16.45

FCC ID: A3LSMP605M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/13 – 09/24/13	DUT Type: Portable Tablet	APPENDIX G: Page 4 of 5		

Moving device away from the phantom:

KDB 616217 Measured Power [dBm]															
Distance[mm]	27	24	21	20	19	18	17	16	15	14	13	12	9	6	3
LTE B2	22.79	22.77	22.72	22.81	22.72	22.67	22.76	14.99	15.22	14.84	14.86	14.79	15.11	14.93	15.18
LTE B4	22.81	22.68	22.64	22.70	22.61	22.83	22.79	15.03	15.42	15.31	15.21	15.24	14.85	15.21	15.21
LTE B5	22.69	22.71	22.59	22.87	22.84	22.61	22.68	18.98	18.75	18.67	18.74	18.72	18.63	18.88	18.63
LTE B17	22.92	22.93	22.61	22.74	22.70	22.79	22.95	19.14	19.21	19.37	19.06	19.10	19.31	19.21	18.58
GSM850	31.56	31.75	31.43	31.52	31.62	31.65	31.47	26.02	26.32	26.22	26.18	26.23	25.92	26.21	26.14
GSM1900	29.69	29.48	29.43	29.56	29.64	29.68	29.87	22.41	22.11	22.37	22.47	22.34	22.34	22.06	22.30
GPRS850 1Tx	31.62	31.43	31.59	31.67	31.63	31.71	31.62	26.12	26.32	26.37	26.24	26.29	26.33	26.42	26.45
GPRS850 2Tx	30.26	30.33	30.35	30.32	30.18	30.46	30.33	24.57	24.68	24.52	24.62	24.77	24.84	24.61	24.89
GPRS850 3Tx	28.74	28.79	28.69	28.76	28.57	28.35	28.69	23.10	23.39	23.17	23.21	23.50	23.41	23.38	23.18
GPRS850 4Tx	27.33	27.42	27.27	27.32	27.43	27.43	27.26	21.71	21.57	21.63	21.68	21.82	21.67	21.62	21.73
GPRS1900 1Tx	29.56	29.42	29.26	29.41	29.22	29.61	29.12	22.28	22.41	22.34	22.04	22.37	22.41	22.40	22.33
GPRS1900 2Tx	28.53	28.67	28.64	28.78	28.44	28.64	28.69	21.37	21.34	21.09	21.18	21.42	21.11	21.35	21.12
GPRS1900 3Tx	26.46	26.72	26.33	26.60	26.61	26.53	26.92	19.74	19.76	19.79	19.64	19.61	19.53	19.41	19.52
GPRS1900 4Tx	25.75	25.63	25.33	25.41	25.34	25.54	25.37	18.28	18.18	18.45	18.32	18.56	18.13	18.31	18.25
WCDMA850	22.39	22.41	22.27	22.42	22.38	22.28	22.39	20.32	20.23	20.13	20.41	20.42	20.15	20.40	20.37
WCDMA1900	22.19	22.32	22.22	22.43	22.17	22.42	22.41	15.21	15.24	15.38	15.28	15.12	15.35	15.38	15.33
EDGE850 1Tx	26.26	26.17	26.33	26.43	26.39	26.19	26.40	24.38	24.34	24.25	24.82	24.11	24.31	24.40	24.38
EDGE850 2Tx	24.67	24.30	24.27	24.51	24.80	24.71	24.54	23.34	23.45	23.37	23.37	23.29	23.14	23.41	23.38
EDGE850 3Tx	22.36	22.30	22.21	22.15	22.31	22.26	22.39	22.25	22.26	22.14	22.39	22.37	22.44	22.16	22.42
EDGE850 4Tx	21.58	21.45	21.40	21.30	21.38	21.68	21.33	20.28	20.39	20.41	20.89	20.57	20.64	20.53	20.14
EDGE1900 1Tx	25.27	25.69	25.32	25.58	25.39	25.44	25.70	21.89	21.41	21.39	21.52	21.53	21.76	21.24	21.31
EDGE1900 2Tx	24.62	24.27	24.61	24.28	24.62	24.39	24.34	20.31	20.36	20.42	20.16	20.41	20.26	20.25	20.39
EDGE1900 3Tx	23.34	23.48	23.40	23.40	23.31	23.34	23.08	18.18	18.15	18.17	17.76	18.03	17.85	18.23	18.15
EDGE1900 4Tx	22.39	22.28	22.44	22.24	22.48	22.42	22.17	16.39	16.53	16.38	16.66	16.59	16.41	16.41	16.39

Based on the most conservative measured triggering distance of 16 mm, additional SAR measurements were required at 15 mm from the left edge.

FCC ID: A3LSMP605M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/13 – 09/24/13	DUT Type: Portable Tablet	APPENDIX G: Page 5 of 5		