



**FCC CFR47 PART 15 SUBPART C**

**Bluetooth**

**CERTIFICATION TEST REPORT**

**FOR**

**WCDMA/LTE Watch + Bluetooth/BLE and DTS b/g/n**

**MODEL NUMBER : SM-R765T, SM-R765A**

**FCC ID: A3LSMR765U**

**REPORT NUMBER: 16K23793-E3V2**

**ISSUE DATE: SEP 02, 2016**

*Prepared for*  
**SAMSUNG ELECTRONICS CO., LTD.**  
**129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,**  
**GYEONGGI-DO, 16677, KOREA**

*Prepared by*  
**UL Korea, Ltd. Suwon Laboratory**  
**218 Maeyeong-ro, Yeongtong-gu,**  
**Suwon-si, Gyeonggi-do, 16675, Korea**  
**TEL: (031) 337-9902**  
**FAX: (031) 213-5433**



Revision History

| Rev. | Issue Date | Revisions                   | Revised By  |
|------|------------|-----------------------------|-------------|
| V1   | 08/29/16   | Initial issue               | Junwhan Lee |
| V2   | 09/02/16   | Revised section 5.4, 6, 9.1 | Junwhan Lee |

## TABLE OF CONTENTS

|                                                 |           |
|-------------------------------------------------|-----------|
| <b>1. ATTESTATION OF TEST RESULTS</b>           | <b>5</b>  |
| <b>2. TEST METHODOLOGY</b>                      | <b>6</b>  |
| <b>3. FACILITIES AND ACCREDITATION</b>          | <b>6</b>  |
| <b>4. CALIBRATION AND UNCERTAINTY</b>           | <b>6</b>  |
| 4.1. MEASURING INSTRUMENT CALIBRATION           | 6         |
| 4.2. SAMPLE CALCULATION                         | 6         |
| 4.3. MEASUREMENT UNCERTAINTY                    | 6         |
| <b>5. EQUIPMENT UNDER TEST</b>                  | <b>7</b>  |
| 5.1. DESCRIPTION OF EUT                         | 7         |
| 5.2. MAXIMUM OUTPUT POWER                       | 7         |
| 5.3. DESCRIPTION OF AVAILABLE ANTENNAS          | 7         |
| 5.4. WORST-CASE CONFIGURATION AND MODE          | 7         |
| 5.5. DESCRIPTION OF TEST SETUP                  | 8         |
| <b>6. TEST AND MEASUREMENT EQUIPMENT</b>        | <b>10</b> |
| <b>7. SUMMARY TABLE</b>                         | <b>11</b> |
| <b>8. ANTENNA PORT TEST RESULTS</b>             | <b>12</b> |
| 8.1. 20 dB AND 99% BANDWIDTH                    | 12        |
| 8.1.1. BASIC DATA RATE GFSK MODULATION          | 12        |
| 8.1.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION | 12        |
| 8.1.3. ENHANCED DATA RATE 8PSK MODULATION       | 12        |
| 8.1.4. 20 dB AND 99% BANDWIDTH PLOTS            | 13        |
| 8.2. HOPPING FREQUENCY SEPARATION               | 16        |
| 8.3. NUMBER OF HOPPING CHANNELS                 | 17        |
| 8.4. AVERAGE TIME OF OCCUPANCY                  | 19        |
| 8.5. OUTPUT POWER                               | 23        |
| 8.5.1. BASIC DATA RATE GFSK MODULATION          | 23        |
| 8.5.2. ENHANCED DATA RATE PI/4-DPSK MODULATION  | 23        |
| 8.5.3. ENHANCED DATA RATE 8PSK MODULATION       | 23        |
| 8.5.4. OUTPUT POWER PLOTS                       | 24        |
| 8.6. AVERAGE POWER                              | 27        |
| 8.6.1. BASIC DATA RATE GFSK MODULATION          | 27        |
| 8.6.2. DATA RATE PI/4-DQPSK MODULATION          | 27        |
| 8.6.3. ENHANCED DATA RATE 8PSK MODULATION       | 27        |
| 8.7. CONDUCTED SPURIOUS EMISSIONS               | 28        |
| 8.7.1. BASIC DATA RATE GFSK MODULATION          | 29        |

|                                                    |           |
|----------------------------------------------------|-----------|
| <b>9. RADIATED TEST RESULTS.....</b>               | <b>41</b> |
| 9.1. LIMITS AND PROCEDURE.....                     | 41        |
| 9.2. TRANSMITTER ABOVE 1 GHz.....                  | 43        |
| 9.2.1. BASIC DATA RATE GFSK MODULATION .....       | 43        |
| 9.2.2. ENHANCED DATA RATE 8PSK MODULATION .....    | 53        |
| 9.3. WORST-CASE BELOW 1 GHz .....                  | 63        |
| <b>10. AC POWER LINE CONDUCTED EMISSIONS .....</b> | <b>65</b> |
| <b>11. SETUP PHOTOS.....</b>                       | <b>70</b> |

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** SAMSUNG ELECTRONICS CO., LTD.

**EUT DESCRIPTION:** WCDMA/LTE Watch + Bluetooth/BLE and DTS b/g/n

**MODEL NUMBER:** SM-R765T, SM-R765A

**SERIAL NUMBER:** R3AH700KEKX, R3AH700KEPA (RADIATED);  
R3AH700KEQN (CONDUCTED)

**DATE TESTED:** AUG 17, 2016 - AUG 26, 2016

| APPLICABLE STANDARDS     |              |
|--------------------------|--------------|
| STANDARD                 | TEST RESULTS |
| CFR 47 Part 15 Subpart C | Pass         |

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Korea, Ltd. By:



CY Choi  
Suwon Lab Engineer  
UL Korea, Ltd.

Tested By:



Junwhan Lee  
Suwon Lab Engineer  
UL Korea, Ltd.

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

| 218 Maeyeong-ro                     |           |
|-------------------------------------|-----------|
| <input checked="" type="checkbox"/> | Chamber 1 |
| <input type="checkbox"/>            | Chamber 2 |

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| PARAMETER                             | UNCERTAINTY |
|---------------------------------------|-------------|
| Conducted Disturbance, 0.15 to 30 MHz | 2.32 dB     |
| Radiated Disturbance, Below 1GHz      | 4.14 dB     |
| Radiated Disturbance, Above 1 GHz     | 5.97 dB     |

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a WCDMA/LTE Watch + Bluetooth/BLE and DTS b/g/n.  
This test report addresses the DSS (BT) operational mode.

SM-R765T and SM-R765A are same H/W and only difference is supported band.  
Band 4 (LTE and WCDMA) of SM-R765A are disabled by S/W.  
SM-R765T was used for the test.

### 5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

| Frequency Range<br>[MHz] | Mode               | Power<br>Mode | Output Power<br>[dBm] | Output Power<br>[mW] |
|--------------------------|--------------------|---------------|-----------------------|----------------------|
| 2402 - 2480              | Basic GFSK         | Average       | 14.476                | 28.029               |
|                          |                    | Peak          | 15.007                | 31.674               |
|                          | Enhanced Pi/4-DPSK | Average       | 12.076                | 16.129               |
|                          |                    | Peak          | 14.219                | 26.418               |
|                          | Enhanced 8PSK      | Average       | 12.078                | 16.136               |
|                          |                    | Peak          | 14.648                | 29.161               |

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -4.5 dBi.

### 5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance. For average power data please refer to section 8.6.

## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

| Support Equipment List |              |            |               |            |
|------------------------|--------------|------------|---------------|------------|
| Description            | Manufacturer | Model      | Serial Number | FCC ID     |
| Adapter                | SAMSUNG      | ETA0U60JBE | DK1G826HS17-E | N/A        |
| Data Cable             | SAMSUNG      | ECB-DU2EBE | N/A           | N/A        |
| Wireless Charger       | SAMSUNG      | EP-YO760   | N/A           | A3LEPYO760 |


### I/O CABLES

| I/O Cable List |          |                      |                |            |                  |         |
|----------------|----------|----------------------|----------------|------------|------------------|---------|
| Cable No       | Port     | # of identical ports | Connector Type | Cable Type | Cable Length (m) | Remarks |
| 1              | DC Power | 1                    | Mini-USB       | Shielded   | 0.8m             | N/A     |

### TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.  
EUT was set in the Hidden menu mode to enable BT communications.

**SETUP DIAGRAM FOR TESTS**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

| Test Equipment List        |               |                        |             |          |
|----------------------------|---------------|------------------------|-------------|----------|
| Description                | Manufacturer  | Model                  | S/N         | Cal Due  |
| Antenna, Bilog, 30MHz-1GHz | SCHWARZBECK   | VULB9163               | 750         | 11-17-16 |
| Antenna, Bilog, 30MHz-1GHz | SCHWARZBECK   | VULB9163               | 749         | 04-25-17 |
| Antenna, Horn, 18 GHz      | ETS           | 3115                   | 00167211    | 09-20-16 |
| Antenna, Horn, 18 GHz      | ETS           | 3115                   | 00161451    | 05-17-17 |
| Antenna, Horn, 18 GHz      | ETS           | 3117                   | 00168724    | 06-17-17 |
| Antenna, Horn, 18 GHz      | ETS           | 3117                   | 00168717    | 06-17-17 |
| Antenna, Horn, 40 GHz      | ETS           | 3116C                  | 00166155    | 11-30-17 |
| Antenna, Horn, 40 GHz      | ETS           | 3116C-PA               | 00168841    | 12-15-17 |
| Antenna, Loop, 9kHz-30MHz  | R&S           | HFH2-Z2                | 100418      | 11-25-17 |
| Preamplifier, 1000 MHz     | Sonoma        | 310N                   | 341282      | 08-17-17 |
| Preamplifier, 1000 MHz     | Sonoma        | 310N                   | 351741      | 08-16-17 |
| Preamplifier               | ETS           | 3115-PA                | 00167475    | 08-17-17 |
| Preamplifier, 18 GHz       | Miteq         | AFS42-00101800-25-S-42 | 1896138     | 08-16-17 |
| Spectrum Analyzer, 44 GHz  | Agilent / HP  | N9030A                 | MY54170614  | 08-17-17 |
| Spectrum Analyzer, 44 GHz  | Agilent / HP  | N9030A                 | MY54490312  | 08-16-17 |
| Bluetooth Tester           | TESCOM        | TC-3000C               | 3000C000546 | 08-18-17 |
| Average Power Sensor       | R&S           | NRZ-Z91                | 102681      | 08-16-17 |
| Average Power Sensor       | Agilent / HP  | U2000                  | MY54270007  | 08-17-17 |
| EMI Test Receive, 40 GHz   | R&S           | ESU40                  | 100439      | 08-17-17 |
| EMI Test Receive, 40 GHz   | R&S           | ESU40                  | 100457      | 08-16-17 |
| EMI Test Receive, 3 GHz    | R&S           | ESR3                   | 101832      | 08-16-17 |
| Attenuator / Switch driver | HP            | 11713A                 | 3748A04272  | N/A      |
| Low Pass Filter 5GHz       | Micro-Tronics | LPS17541               | 009         | 08-17-17 |
| Low Pass Filter 5GHz       | Micro-Tronics | LPS17541               | 015         | 08-16-17 |
| High Pass Filter 3GHz      | Micro-Tronics | HPM17543               | 010         | 08-17-17 |
| High Pass Filter 3GHz      | Micro-Tronics | HPM17543               | 015         | 08-16-17 |
| High Pass Filter 6GHz      | Micro-Tronics | HPM17542               | 009         | 08-17-17 |
| High Pass Filter 6GHz      | Micro-Tronics | HPM17542               | 016         | 08-16-17 |
| LISN                       | R&S           | ENV-216                | 101836      | 08-16-17 |
| LISN                       | R&S           | ENV-216                | 101837      | 08-16-17 |
| Attenuator                 | PASTERNAK     | PE7087-10              | A009        | 08-16-17 |

## 7. SUMMARY TABLE

| FCC Part Section   | Test Description                        | Test Limit                            | Test Condition       | Test Result | Worst Case        |
|--------------------|-----------------------------------------|---------------------------------------|----------------------|-------------|-------------------|
| 2.1049             | Occupied Band width (99%)               | N/A                                   | Conducted            | Pass        | 1.196 MHz         |
| 2.1051, 15.247 (d) | Band Edge / Conducted Spurious Emission | -20dBc                                |                      | Pass        | -38.961 dBm       |
| 15.247 (b)(1)      | TX conducted output power               | <21dBm                                |                      | Pass        | 15.007 dBm (Peak) |
| 15.247 (a)(1)      | Hopping frequency separation            | > 25KHz                               |                      | Pass        | 1 MHz             |
| 15.247 (a)(1)(iii) | Number of Hopping channels              | More than 15 non-overlapping channels |                      | Pass        | 79                |
| 15.247 (a)(1)(iii) | Avg Time of Occupancy                   | < 0.4sec                              |                      | Pass        | 0.34548 sec       |
| 15.207 (a)         | AC Power Line conducted emissions       | Section 10                            | Power Line conducted | Pass        | 44.95 dBuV (Pk)   |
| 15.205, 15.209     | Radiated Spurious Emission              | < 40dBuV/m                            | Radiated             | Pass        | 34.7 dBuV/m (Pk)  |

## 8. ANTENNA PORT TEST RESULTS

### 8.1. 20 dB AND 99% BANDWIDTH

#### LIMITS

None; for reporting purposes only.

#### TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to  $\geq 1\%$  of the 20 dB bandwidth. The VBW is set to  $\geq$  RBW. The sweep time is coupled.

#### RESULTS

##### 8.1.1. BASIC DATA RATE GFSK MODULATION

| Channel | Frequency<br>[MHz] | 20 dB Bandwidth<br>[MHz] | 99% Bandwidth<br>[KHz] |
|---------|--------------------|--------------------------|------------------------|
| Low     | 2402               | 1.047                    | 897.470                |
| Mid     | 2441               | 1.046                    | 898.460                |
| High    | 2480               | 1.046                    | 901.360                |
| Worst   |                    | 1.047                    | 901.360                |

##### 8.1.2. ENHANCED DATA RATE $\pi/4$ -DQPSK MODULATION


| Channel | Frequency<br>[MHz] | 20 dB Bandwidth<br>[MHz] | 99% Bandwidth<br>[MHz] |
|---------|--------------------|--------------------------|------------------------|
| Low     | 2402               | 1.290                    | 1.193                  |
| Mid     | 2441               | 1.347                    | 1.165                  |
| High    | 2480               | 1.348                    | 1.196                  |
| Worst   |                    | 1.348                    | 1.196                  |

##### 8.1.3. ENHANCED DATA RATE 8PSK MODULATION


| Channel | Frequency<br>[MHz] | 20 dB Bandwidth<br>[MHz] | 99% Bandwidth<br>[MHz] |
|---------|--------------------|--------------------------|------------------------|
| Low     | 2402               | 1.297                    | 1.164                  |
| Mid     | 2441               | 1.300                    | 1.165                  |
| High    | 2480               | 1.299                    | 1.195                  |
| Worst   |                    | 1.300                    | 1.195                  |

## 8.1.4. 20 dB AND 99% BANDWIDTH PLOTS


### GFSK BANDWIDTH



## Pi/4-DQPSK BANDWIDTH



## 8PSK BANDWIDTH



## 8.2. HOPPING FREQUENCY SEPARATION

### LIMIT

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

### RESULTS

#### HOPPING FREQUENCY SEPARATION PLOT



### 8.3. NUMBER OF HOPPING CHANNELS

#### LIMIT

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

#### TEST PROCEDURE


DA 00-705: The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


#### RESULTS

Normal Mode: 79 Channels observed.

#### NUMBER OF HOPPING CHANNELS PLOTS

##### NUMBER OF HOPPING CHANNELS (100 MHZ SPAN)





## 8.4. AVERAGE TIME OF OCCUPANCY

### LIMIT

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels \* 0.4 s) is equal to  $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{pulse width}$ .

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels \* 0.4 seconds) is equal to  $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{pulse width}$ .


### RESULTS

| DH Packet   | Pulse Width [msec] | Number of Pulses in 3.16 seconds | Average Time of Occupancy [sec] | Limit [sec] | Margin [sec] |
|-------------|--------------------|----------------------------------|---------------------------------|-------------|--------------|
| GFSK Normal |                    |                                  |                                 |             |              |
| DH1         | 0.380              | 32                               | 0.121632                        | 0.4         | -0.2784      |
| DH3         | 1.634              | 17                               | 0.277780                        | 0.4         | -0.1222      |
| DH5         | 2.879              | 12                               | 0.345480                        | 0.4         | -0.0545      |
|             |                    |                                  |                                 |             |              |
| DH Packet   | Pulse Width [msec] | Number of Pulses in 0.8 seconds  | Average Time of Occupancy [sec] | Limit [sec] | Margin [sec] |
| GFSK AFH    |                    |                                  |                                 |             |              |
| DH1         | 0.380              | 8                                | 0.030408                        | 0.4         | -0.36959     |
| DH3         | 1.634              | 4.25                             | 0.069445                        | 0.4         | -0.33056     |
| DH5         | 2.879              | 3                                | 0.086370                        | 0.4         | -0.31363     |


# DH1



### DH3



## DH5



## 8.5. OUTPUT POWER

### LIMIT

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

### TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

### RESULTS

#### 8.5.1. BASIC DATA RATE GFSK MODULATION

| Channel | Frequency [MHz] | Output Power [dBm] | Limit [dBm] | Margin [dB] |
|---------|-----------------|--------------------|-------------|-------------|
| Low     | 2402            | 15.007             | 21          | -5.993      |
| Middle  | 2441            | 14.912             | 21          | -6.088      |
| High    | 2480            | 14.739             | 21          | -6.261      |
| Worst   |                 | 15.007             | 21          | -5.993      |

#### 8.5.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION



| Channel | Frequency [MHz] | Output Power [dBm] | Limit [dBm] | Margin [dB] |
|---------|-----------------|--------------------|-------------|-------------|
| Low     | 2402            | 13.369             | 21          | -7.631      |
| Middle  | 2441            | 13.978             | 21          | -7.022      |
| High    | 2480            | 14.219             | 21          | -6.781      |
| Worst   |                 | 14.219             | 21          | -6.781      |

#### 8.5.3. ENHANCED DATA RATE 8PSK MODULATION



| Channel | Frequency [MHz] | Output Power [dBm] | Limit [dBm] | Margin [dB] |
|---------|-----------------|--------------------|-------------|-------------|
| Low     | 2402            | 13.904             | 21          | -7.096      |
| Middle  | 2441            | 14.518             | 21          | -6.482      |
| High    | 2480            | 14.648             | 21          | -6.352      |
| Worst   |                 | 14.648             | 21          | -6.352      |

## 8.5.4. OUTPUT POWER PLOTS



### GFSK OUTPUT POWER

|                           |                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>GFSK<br/>Low CH</p>    |  <p>Key parameters from the plot:</p> <ul style="list-style-type: none"> <li>Center: 2.402000 GHz</li> <li>Res BW: 3.0 MHz</li> <li>Span: 10.00 MHz</li> <li>Sweep: 1.333 ms (20001 pts)</li> <li>VBW: 50 MHz</li> <li>Ref: 30.00 dBm</li> <li>Mkr1: 2.402 228 0 GHz, 15.007 dBm</li> </ul>   |
| <p>GFSK<br/>Middle CH</p> |  <p>Key parameters from the plot:</p> <ul style="list-style-type: none"> <li>Center: 2.441000 GHz</li> <li>Res BW: 3.0 MHz</li> <li>Span: 10.00 MHz</li> <li>Sweep: 1.333 ms (20001 pts)</li> <li>VBW: 50 MHz</li> <li>Ref: 30.00 dBm</li> <li>Mkr1: 2.441 058 0 GHz, 14.912 dBm</li> </ul>  |
| <p>GFSK<br/>High CH</p>   |  <p>Key parameters from the plot:</p> <ul style="list-style-type: none"> <li>Center: 2.479000 GHz</li> <li>Res BW: 3.0 MHz</li> <li>Span: 10.00 MHz</li> <li>Sweep: 1.333 ms (20001 pts)</li> <li>VBW: 50 MHz</li> <li>Ref: 30.00 dBm</li> <li>Mkr1: 2.479 888 0 GHz, 14.739 dBm</li> </ul> |

# **Pi/4-DPSK OUTPUT POWER**

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Pi/4-DPSK<br/>Low CH</p>    |  <p>KeySight Spectrum Analyzer - Sweep SA<br/>RL RF 50 Ω CORREC SENSE INT ALIGN AUTO 04:55:12 PM Aug 26, 2016<br/>PNO: Fast IF Gain: Low Trig: Free Run Atten: 40 dB #Avg Type: RMS AvgHold: 100/100<br/>Mkr1 2.4021745 GHz 13.369 dBm<br/>10 dB/div Log Ref 30.00 dBm<br/>Center 2.402000 GHz #Res BW 3.0 MHz #VBW 50 MHz Span 10.00 MHz Sweep 1.333 ms (20001 pts)</p>   |
| <p>Pi/4-DPSK<br/>Middle CH</p> |  <p>KeySight Spectrum Analyzer - Sweep SA<br/>RL RF 50 Ω CORREC SENSE INT ALIGN AUTO 04:55:33 PM Aug 26, 2016<br/>PNO: Fast IF Gain: Low Trig: Free Run Atten: 40 dB #Avg Type: RMS AvgHold: 100/100<br/>Mkr1 2.4411025 GHz 13.978 dBm<br/>10 dB/div Log Ref 30.00 dBm<br/>Center 2.441000 GHz #Res BW 3.0 MHz #VBW 50 MHz Span 10.00 MHz Sweep 1.333 ms (20001 pts)</p>  |
| <p>Pi/4-DPSK<br/>High CH</p>   |  <p>KeySight Spectrum Analyzer - Sweep SA<br/>RL RF 50 Ω CORREC SENSE INT ALIGN AUTO 04:55:33 PM Aug 26, 2016<br/>PNO: Fast IF Gain: Low Trig: Free Run Atten: 40 dB #Avg Type: RMS AvgHold: 100/100<br/>Mkr1 2.4802150 GHz 14.219 dBm<br/>10 dB/div Log Ref 30.00 dBm<br/>Center 2.480000 GHz #Res BW 3.0 MHz #VBW 50 MHz Span 10.00 MHz Sweep 1.333 ms (20001 pts)</p> |

## 8PSK OUTPUT POWER

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>8PSK<br/>Low CH</p>    |  <p>Key: Keysight Spectrum Analyzer - Sweep SA<br/>RL RF 50 Ω CORREC SENSE:INT1 ALIGN: AUTO 04:55:47 PM Aug 26, 2016<br/>PNO: Fast IF Gain: Low Trig: Free Run Atten: 40 dB #Avg Type: RMS AvgHold: 100/100<br/>Mkr1 2.402 141.5 GHz 13.904 dBm<br/>10 dB/div Log Ref 30.00 dBm<br/>Center 2.402000 GHz #Res BW 3.0 MHz #VBW 50 MHz Span 10.00 MHz Sweep 1.333 ms (20001 pts)</p>   |
| <p>8PSK<br/>Middle CH</p> |  <p>Key: Keysight Spectrum Analyzer - Sweep SA<br/>RL RF 50 Ω CORREC SENSE:INT1 ALIGN: AUTO 04:56:03 PM Aug 26, 2016<br/>PNO: Fast IF Gain: Low Trig: Free Run Atten: 40 dB #Avg Type: RMS AvgHold: 100/100<br/>Mkr1 2.441 033.0 GHz 14.518 dBm<br/>10 dB/div Log Ref 30.00 dBm<br/>Center 2.441000 GHz #Res BW 3.0 MHz #VBW 50 MHz Span 10.00 MHz Sweep 1.333 ms (20001 pts)</p>  |
| <p>8PSK<br/>High CH</p>   |  <p>Key: Keysight Spectrum Analyzer - Sweep SA<br/>RL RF 50 Ω CORREC SENSE:INT1 ALIGN: AUTO 04:56:14 PM Aug 26, 2016<br/>PNO: Fast IF Gain: Low Trig: Free Run Atten: 40 dB #Avg Type: RMS AvgHold: 100/100<br/>Mkr1 2.480 151.0 GHz 14.648 dBm<br/>10 dB/div Log Ref 30.00 dBm<br/>Center 2.480000 GHz #Res BW 3.0 MHz #VBW 50 MHz Span 10.00 MHz Sweep 1.333 ms (20001 pts)</p> |

## 8.6. AVERAGE POWER

### LIMIT

None; for reporting purposes only.

### TEST PROCEDURE

DA 00-705: The transmitter output is connected to a power meter.

### RESULTS

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

#### 8.6.1. BASIC DATA RATE GFSK MODULATION

| Channel | Frequency [MHz] | AV power [dBm] | AV power [mW] |
|---------|-----------------|----------------|---------------|
| Low     | 2402            | 14.476         | 28.03         |
| Middle  | 2441            | 14.383         | 27.43         |
| High    | 2480            | 14.321         | 27.05         |

#### 8.6.2. DATA RATE PI/4-DQPSK MODULATION

| Channel | Frequency [MHz] | AV power [dBm] | AV power [mW] |
|---------|-----------------|----------------|---------------|
| Low     | 2402            | 10.779         | 11.96         |
| Middle  | 2441            | 11.604         | 14.47         |
| High    | 2480            | 12.076         | 16.13         |

#### 8.6.3. ENHANCED DATA RATE 8PSK MODULATION

| Channel | Frequency [MHz] | AV power [dBm] | AV power [mW] |
|---------|-----------------|----------------|---------------|
| Low     | 2402            | 10.795         | 12.01         |
| Middle  | 2441            | 11.613         | 14.50         |
| High    | 2480            | 12.078         | 16.14         |

## **8.7. CONDUCTED SPURIOUS EMISSIONS**

### **LIMITS**

FCC §15.247 (d)

Limit = -20 dBc

### **TEST PROCEDURE**

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.

### **RESULTS**


## 8.7.1. BASIC DATA RATE GFSK MODULATION

### GFSK Mode


#### [GFSK] Low Channel BandEdge




#### [GFSK] Low Channel Spurious




### [GFSK] Mid Channel BandEdge



### [GFSK] Mid Channel Spurious





### BandEdge Emission at GFSK Hopping Mode


#### [GFSK Hopping Mode] Low Channel BandEdge



#### [GFSK Hopping Mode] High Channel BandEdge



### PI/4-DQPSK Mode




### [PI/4-DQPSK] Mid Channel BandEdge




### [PI/4-DQPSK] Mid Channel Spurious



### [PI/4-DQPSK] High Channel BandEdge




### [PI/4-DQPSK] High Channel Spurious



### BandEdge Emission at PI/4-DQPSK Hopping Mode

#### [PI/4-DQPSK Hopping Mode] Low Channel BandEdge




#### [PI/4-DQPSK Hopping Mode] High Channel BandEdge



## 8PSK Mode


### [8PSK] Low Channel BandEdge



### [8PSK] Low Channel Spurious




### [8PSK] Mid Channel BandEdge



### [8PSK] Mid Channel Spurious





### BandEdge Emission at 8PSK Hopping Mode

#### [8PSK Hopping Mode] Low Channel BandEdge



#### [8PSK Hopping Mode] High Channel BandEdge



## 9. RADIATED TEST RESULTS

### 9.1. LIMITS AND PROCEDURE

#### LIMITS

FCC §15.205 and §15.209

| Limits for radiated disturbance of an intentional radiator |                 |                          |
|------------------------------------------------------------|-----------------|--------------------------|
| Frequency range (MHz)                                      | Limits (μV/m)   | Measurement Distance (m) |
| 0.009 – 0.490                                              | 2400 / F (kHz)  | 300                      |
| 0.490 – 1.705                                              | 24000 / F (kHz) | 30                       |
| 1.705 – 30.0                                               | 30              | 30                       |
| 30 – 88                                                    | 100**           | 3                        |
| 88 - 216                                                   | 150**           | 3                        |
| 216 – 960                                                  | 200**           | 3                        |
| Above 960                                                  | 500             | 3                        |

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

## **TEST PROCEDURE**

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements. (Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.)

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 1/T (on time) for average measurement.

$GFSK = 1/T = 1 / 0.0029S = 350Hz.$

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).  
Per FCC part 15.31(o), test results were not reported.


Formula for converting the field strength from  $\mu V/m$  to  $dB\mu V/m$  is:  
 $Limit (dB\mu V/m) = 20 \log limit (\mu V/m)$

## 9.2. TRANSMITTER ABOVE 1 GHz

### 9.2.1. BASIC DATA RATE GFSK MODULATION

#### RESTRICTED BANDEDGE (LOW CHANNEL)

#### HORIZONTAL PEAK AND AVERAGE PLOT



#### HORIZONTAL DATA

##### Trace Markers


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det  | 3117(0016 8717)_150 619 | Path_2 | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|------|-------------------------|--------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 46.38                | Pk   | 31.8                    | -29    | 49.18                      | -                      | -           | 74                  | -24.82         | 14             | 100         | H        |
| 2      | * 2.337         | 49.05                | Pk   | 31.7                    | -29    | 51.75                      | -                      | -           | 74                  | -22.25         | 14             | 100         | H        |
| 3      | * 2.39          | 35.5                 | VA1T | 31.8                    | -29    | 38.3                       | 54                     | -15.7       | -                   | -              | 14             | 100         | H        |
| 4      | * 2.337         | 36.28                | VA1T | 31.7                    | -29    | 38.98                      | 54                     | -15.02      | -                   | -              | 14             | 100         | H        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average  $V_B = 1/T_{on}$  where:  $T_{on}$  is transmit duration

## VERTICAL PEAK AND AVERAGE PLOT



## VERTICAL DATA

### Trace Markers

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det  | 3117(0016 8717)_150 619 | Path_2 | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|------|-------------------------|--------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 44.55                | Pk   | 31.8                    | -29    | 47.35                      | -                      | -           | 74                  | -26.65         | 194            | 158         | V        |
| 2      | * 2.339         | 49.04                | Pk   | 31.7                    | -29    | 51.74                      | -                      | -           | 74                  | -22.26         | 194            | 158         | V        |
| 3      | * 2.39          | 35.56                | VA1T | 31.8                    | -29    | 38.36                      | 54                     | -15.64      | -                   | -              | 194            | 158         | V        |
| 4      | * 2.353         | 36.42                | VA1T | 31.7                    | -29    | 39.12                      | 54                     | -14.88      | -                   | -              | 194            | 158         | V        |


\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

## AUTHORIZED BANDEDGE (HIGH CHANNEL)

### HORIZONTAL PEAK AND AVERAGE PLOT



### HORIZONTAL DATA

#### Trace Markers


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det  | 3117(0016 8717)_150 619 | Path_2 | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|------|-------------------------|--------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 43.71                | Pk   | 32                      | -28.9  | 46.81                      | -                      | -           | 74                  | -27.19         | 43             | 304         | H        |
| 2      | 2.549           | 48.23                | Pk   | 32                      | -28.8  | 51.43                      | -                      | -           | 74                  | -22.57         | 43             | 304         | H        |
| 3      | * 2.484         | 35.64                | VA1T | 32                      | -28.9  | 38.74                      | 54                     | -15.26      | -                   | -              | 43             | 304         | H        |
| 4      | 2.526           | 36.14                | VA1T | 32                      | -28.8  | 39.34                      | 54                     | -14.66      | -                   | -              | 43             | 304         | H        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average  $V_B = 1/T_{on}$  where:  $T_{on}$  is transmit duration

## VERTICAL PEAK AND AVERAGE PLOT



## VERTICAL DATA

### Trace Markers

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det  | 3117(0016 8717)_150 619 | Path_2 | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|------|-------------------------|--------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 44.01                | Pk   | 32                      | -28.9  | 47.11                      | -                      | -           | 74                  | -26.89         | 194            | 100         | V        |
| 2      | 2.556           | 47.99                | Pk   | 32                      | -28.8  | 51.19                      | -                      | -           | 74                  | -22.81         | 194            | 100         | V        |
| 3      | * 2.484         | 35.55                | VA1T | 32                      | -28.9  | 38.65                      | 54                     | -15.35      | -                   | -              | 194            | 100         | V        |
| 4      | 2.555           | 35.78                | VA1T | 32                      | -28.8  | 38.98                      | 54                     | -15.02      | -                   | -              | 194            | 100         | V        |


\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


VA1T - FHSS: Linear Voltage Average  $V_B = 1/T_{on}$  where:  $T_{on}$  is transmit duration

## HARMONICS AND SPURIOUS EMISSIONS

### LOW CHANNEL HORIZONTAL



### LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## LOW CHANNEL DATA

### Trace Markers


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | 3117(0016 8717)_150 619 | Path_3 | Corrected Reading (dBuV/m) | Avg Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-------------------------|--------|----------------------------|--------------------|-------------|---------------------|-------------|----------------|-------------|----------|
| 1      | * 4.804         | 36.84                | PK  | 34                      | -33.8  | 37.04                      | -                  | -           | 74                  | -36.96      | 0-360          | 150         | H        |
| 4      | 7.206           | 34.07                | PK  | 35.7                    | -30.8  | 38.97                      | -                  | -           | 74                  | -35.03      | 0-360          | 250         | H        |
| 5      | 9.597           | 31.3                 | PK  | 37                      | -27.3  | 41                         | -                  | -           | 74                  | -33         | 0-360          | 150         | H        |
| 2      | * 4.803         | 35.75                | PK  | 34                      | -33.8  | 35.95                      | -                  | -           | 74                  | -38.05      | 0-360          | 150         | V        |
| 3      | 7.206           | 35.04                | PK  | 35.7                    | -30.8  | 39.94                      | -                  | -           | 74                  | -34.06      | 0-360          | 150         | V        |
| 6      | 9.61            | 30.31                | PK  | 37                      | -27.3  | 40.01                      | -                  | -           | 74                  | -33.99      | 0-360          | 150         | V        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

### MID CHANNEL HORIZONTAL



### MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## MID CHANNEL DATA

### Trace Markers


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | 3117(0016 8717)_150 619 | Path_3 | Corrected Reading (dBuV/m) | Avg Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-------------------------|--------|----------------------------|--------------------|-------------|---------------------|-------------|----------------|-------------|----------|
| 1      | * 4.877         | 35.57                | PK  | 34                      | -34    | 35.57                      | -                  | -           | 74                  | -38.43      | 0-360          | 150         | H        |
| 4      | * 7.321         | 33.64                | PK  | 35.8                    | -30.9  | 38.54                      | -                  | -           | 74                  | -35.46      | 0-360          | 150         | H        |
| 5      | 9.763           | 31.21                | PK  | 37.2                    | -26.6  | 41.81                      | -                  | -           | 74                  | -32.19      | 0-360          | 150         | H        |
| 2      | * 4.881         | 35.74                | PK  | 34                      | -34    | 35.74                      | -                  | -           | 74                  | -38.26      | 0-360          | 150         | V        |
| 3      | * 7.334         | 32.93                | PK  | 35.8                    | -30.8  | 37.93                      | -                  | -           | 74                  | -36.07      | 0-360          | 250         | V        |
| 6      | 9.767           | 30.77                | PK  | 37.2                    | -26.5  | 41.47                      | -                  | -           | 74                  | -32.53      | 0-360          | 150         | V        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

### HIGH CHANNEL HORIZONTAL



### HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## HIGH CHANNEL DATA

### Trace Markers

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | 3117(0016 8717)_150 619 | Path_3 | Corrected Reading (dBuV/m) | Avg Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-------------------------|--------|----------------------------|--------------------|-------------|---------------------|-------------|----------------|-------------|----------|
| 1      | * 4.959         | 36.87                | PK  | 34                      | -34    | 36.87                      | -                  | -           | 74                  | -37.13      | 0-360          | 150         | H        |
| 4      | * 7.443         | 33.46                | PK  | 35.8                    | -30.7  | 38.56                      | -                  | -           | 74                  | -35.44      | 0-360          | 150         | H        |
| 5      | 9.923           | 29.43                | PK  | 37.4                    | -27.1  | 39.73                      | -                  | -           | 74                  | -34.27      | 0-360          | 150         | H        |
| 2      | * 4.96          | 37.52                | PK  | 34                      | -34    | 37.52                      | -                  | -           | 74                  | -36.48      | 0-360          | 250         | V        |
| 3      | * 7.446         | 33.42                | PK  | 35.8                    | -30.6  | 38.62                      | -                  | -           | 74                  | -35.38      | 0-360          | 250         | V        |
| 6      | 9.928           | 29.82                | PK  | 37.4                    | -27    | 40.22                      | -                  | -           | 74                  | -33.78      | 0-360          | 150         | V        |


\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

## 9.2.2. ENHANCED DATA RATE 8PSK MODULATION RESTRICTED BANDEDGE (LOW CHANNEL)

### HORIZONTAL PEAK AND AVERAGE PLOT



### HORIZONTAL DATA

#### Trace Markers


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det  | 3117(0016 8717)_150 619 | Path_2 | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|------|-------------------------|--------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 45.05                | Pk   | 31.8                    | -29    | 47.85                      | -                      | -           | 74                  | -26.15         | 14             | 100         | H        |
| 2      | * 2.39          | 49.03                | Pk   | 31.8                    | -29    | 51.83                      | -                      | -           | 74                  | -22.17         | 14             | 100         | H        |
| 3      | * 2.39          | 35.67                | VA1T | 31.8                    | -29    | 38.47                      | 54                     | -15.53      | -                   | -              | 14             | 100         | H        |
| 4      | * 2.328         | 36.43                | VA1T | 31.7                    | -29    | 39.13                      | 54                     | -14.87      | -                   | -              | 14             | 100         | H        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average  $V_B = 1/T_{on}$  where:  $T_{on}$  is transmit duration

## VERTICAL PEAK AND AVERAGE PLOT



## VERTICAL DATA

### Trace Markers

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det  | 3117(0016 8717)_150 619 | Path_2 | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|------|-------------------------|--------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 45.92                | Pk   |                         | -29    | 48.72                      | -                      | -           | 74                  | -25.28         | 194            | 158         | V        |
| 2      | * 2.326         | 48.73                | Pk   |                         | -29    | 51.43                      | -                      | -           | 74                  | -22.57         | 194            | 158         | V        |
| 3      | * 2.39          | 35.75                | VA1T |                         | -29    | 38.55                      | 54                     | -15.45      | -                   | -              | 194            | 158         | V        |
| 4      | * 2.385         | 36.27                | VA1T |                         | -29    | 39.07                      | 54                     | -14.93      | -                   | -              | 194            | 158         | V        |


\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

## AUTHORIZED BANDEDGE (HIGH CHANNEL)

### HORIZONTAL PEAK AND AVERAGE PLOT



### HORIZONTAL DATA

#### Trace Markers


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det  | 3117(0016 8717)_150 619 | Path_2 | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|------|-------------------------|--------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 46.2                 | Pk   | 32                      | -28.9  | 49.3                       | -                      | -           | 74                  | -24.7          | 43             | 304         | H        |
| 2      | 2.522           | 49.2                 | Pk   | 32                      | -28.9  | 52.3                       | -                      | -           | 74                  | -21.7          | 43             | 304         | H        |
| 3      | * 2.484         | 35.94                | VA1T | 32                      | -28.9  | 39.04                      | 54                     | -14.96      | -                   | -              | 43             | 304         | H        |
| 4      | 2.517           | 36.44                | VA1T | 32                      | -28.9  | 39.54                      | 54                     | -14.46      | -                   | -              | 43             | 304         | H        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average  $V_B = 1/T_{on}$  where:  $T_{on}$  is transmit duration

## VERTICAL PEAK AND AVERAGE PLOT



## VERTICAL DATA

### Trace Markers

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det  | 3117(0016 8717)_150 619 | Path_2 | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|------|-------------------------|--------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 45.39                | Pk   | 32                      | -28.9  | 48.49                      | -                      | -           | 74                  | -25.51         | 194            | 100         | V        |
| 2      | 2.517           | 48.85                | Pk   | 32                      | -28.9  | 51.95                      | -                      | -           | 74                  | -22.05         | 194            | 100         | V        |
| 3      | * 2.484         | 35.38                | VA1T | 32                      | -28.9  | 38.48                      | 54                     | -15.52      | -                   | -              | 194            | 100         | V        |
| 4      | 2.557           | 36.19                | VA1T | 32                      | -28.8  | 39.39                      | 54                     | -14.61      | -                   | -              | 194            | 100         | V        |


\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


VA1T - FHSS: Linear Voltage Average  $V_B = 1/T_{on}$  where:  $T_{on}$  is transmit duration

## HARMONICS AND SPURIOUS EMISSIONS

### LOW CHANNEL HORIZONTAL



### LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## LOW CHANNEL DATA

### Trace Markers


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | 3117(0016 8717)_150 619 | Path_3 | Corrected Reading (dBuV/m) | Avg Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-------------------------|--------|----------------------------|--------------------|-------------|---------------------|-------------|----------------|-------------|----------|
| 1      | * 4.812         | 35.63                | PK  | 34                      | -33.8  | 35.83                      | -                  | -           | 74                  | -38.17      | 0-360          | 250         | H        |
| 3      | 7.21            | 32.83                | PK  | 35.7                    | -30.8  | 37.73                      | -                  | -           | 74                  | -36.27      | 0-360          | 250         | H        |
| 5      | 9.594           | 30.96                | PK  | 37                      | -27.3  | 40.66                      | -                  | -           | 74                  | -33.34      | 0-360          | 250         | H        |
| 2      | * 4.814         | 35.29                | PK  | 34                      | -33.8  | 35.49                      | -                  | -           | 74                  | -38.51      | 0-360          | 150         | V        |
| 4      | 7.207           | 33.38                | PK  | 35.7                    | -30.8  | 38.28                      | -                  | -           | 74                  | -35.72      | 0-360          | 250         | V        |
| 6      | 9.599           | 30.49                | PK  | 37                      | -27.3  | 40.19                      | -                  | -           | 74                  | -33.81      | 0-360          | 250         | V        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

### MID CHANNEL HORIZONTAL



### MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## MID CHANNEL DATA

### Trace Markers


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | 3117(0016 8717)_150 619 | Path_3 | Corrected Reading (dBuV/m) | Avg Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-------------------------|--------|----------------------------|--------------------|-------------|---------------------|-------------|----------------|-------------|----------|
| 1      | * 4.886         | 35.37                | PK  | 34                      | -34    | 35.37                      | -                  | -           | 74                  | -38.63      | 0-360          | 250         | H        |
| 3      | * 7.326         | 32.4                 | PK  | 35.8                    | -30.8  | 37.4                       | -                  | -           | 74                  | -36.6       | 0-360          | 250         | H        |
| 5      | 9.765           | 30.35                | PK  | 37.2                    | -26.6  | 40.95                      | -                  | -           | 74                  | -33.05      | 0-360          | 250         | H        |
| 2      | * 4.89          | 35.37                | PK  | 34                      | -34    | 35.37                      | -                  | -           | 74                  | -38.63      | 0-360          | 150         | V        |
| 4      | * 7.328         | 32.92                | PK  | 35.8                    | -30.8  | 37.92                      | -                  | -           | 74                  | -36.08      | 0-360          | 250         | V        |
| 6      | 9.762           | 30.54                | PK  | 37.2                    | -26.6  | 41.14                      | -                  | -           | 74                  | -32.86      | 0-360          | 250         | V        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

### HIGH CHANNEL HORIZONTAL



### HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## HIGH CHANNEL DATA

### Trace Markers

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | 3117(0016 8717)_150 619 | Path_3 | Corrected Reading (dBuV/m) | Avg Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-------------------------|--------|----------------------------|--------------------|-------------|---------------------|-------------|----------------|-------------|----------|
| 1      | * 4.965         | 35.54                | PK  | 34.1                    | -34    | 35.64                      | -                  | -           | 74                  | -38.36      | 0-360          | 250         | H        |
| 5      | 9.922           | 30.22                | PK  | 37.4                    | -27.2  | 40.42                      | -                  | -           | 74                  | -33.58      | 0-360          | 150         | H        |
| 2      | * 4.969         | 35.19                | PK  | 34.1                    | -34    | 35.29                      | -                  | -           | 74                  | -38.71      | 0-360          | 250         | V        |
| 3      | * 7.445         | 33.39                | PK  | 35.8                    | -30.6  | 38.59                      | -                  | -           | 74                  | -35.41      | 0-360          | 150         | V        |
| 4      | * 7.445         | 33.39                | PK  | 35.8                    | -30.6  | 38.59                      | -                  | -           | 74                  | -35.41      | 0-360          | 150         | V        |
| 6      | 9.927           | 30.21                | PK  | 37.4                    | -27.1  | 40.51                      | -                  | -           | 74                  | -33.49      | 0-360          | 250         | V        |

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).


### 9.3. WORST-CASE BELOW 1 GHz

#### GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

##### HORIZONTAL PLOT



##### VERTICAL PLOT



## BELOW 1 GHz TABLE

### Trace Markers

| Marker | Frequency (MHz) | Meter Reading (dBuV) | Det | VULB9163-750 | Bi-Log | Corrected Reading (dBuV/m) | QPk Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|--------------|--------|----------------------------|--------------------|-------------|----------------|-------------|----------|
| 1      | 71.6925         | 48.7                 | Pk  | 9.2          | -29.7  | 28.2                       | 40                 | -11.8       | 0-360          | 300         | H        |
| 2      | 179.345         | 43.61                | Pk  | 9.4          | -28.3  | 24.71                      | 43.52              | -18.81      | 0-360          | 100         | H        |
| 3      | 30.0425         | 58.91                | Pk  | 10.3         | -30.5  | 38.71                      | 40                 | -1.29       | 0-360          | 100         | V        |
| 4      | 32.975          | 54.24                | Pk  | 10.4         | -30.5  | 34.14                      | 40                 | -5.86       | 0-360          | 100         | V        |
| 5      | 38.925          | 47.02                | Pk  | 12           | -30.3  | 28.72                      | 40                 | -11.28      | 0-360          | 100         | V        |
| 6      | 64.8925         | 47.7                 | Pk  | 11.2         | -29.9  | 29                         | 40                 | -11         | 0-360          | 300         | V        |

Pk - Peak detector

### Radiated Emissions

| Frequency (MHz) | Meter Reading (dBuV) | Det | VULB9163-750 | Bi-Log | Corrected Reading (dBuV/m) | QPk Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|-----------------|----------------------|-----|--------------|--------|----------------------------|--------------------|-------------|----------------|-------------|----------|
| 30.0378         | 54.9                 | Qp  | 10.3         | -30.5  | 34.7                       | 40                 | -5.3        | 324            | 111         | V        |

Qp - Quasi-Peak detector

## 10. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

| Frequency of Emission (MHz) | Conducted Limit (dBuV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15-0.5                    | 66 to 56*              | 56 to 46* |
| 0.5-5                       | 56                     | 46        |
| 5-30                        | 60                     | 50        |

\* Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

### RESULTS

**6 WORST EMISSIONS**

**LINE 1 PLOT**



## LINE 1 RESULTS

### Trace Markers


Phase L1 .15 - 30MHz

| Marker | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Det | 101837_w<br>ith ex-<br>cord_L1 | CE Shield<br>Room | Corrected<br>Reading<br>(dB(uVolts<br>) | CISPR 22<br>Class B ITE<br>QP | Margin<br>(dB) | CISPR 22<br>Class B ITE<br>AV | Margin<br>(dB) |
|--------|--------------------|----------------------------|-----|--------------------------------|-------------------|-----------------------------------------|-------------------------------|----------------|-------------------------------|----------------|
| 1      | .177               | 31.99                      | Pk  | 10.2                           | 0                 | 42.19                                   | 64.63                         | -22.44         | -                             | -              |
| 2      | .186               | 15.66                      | Av  | 10.1                           | 0                 | 25.76                                   | -                             | -              | 54.21                         | -28.45         |
| 3      | .555               | 32.56                      | Pk  | 10.1                           | 0                 | 42.66                                   | 56                            | -13.34         | -                             | -              |
| 4      | .555               | 21.74                      | Av  | 10.1                           | 0                 | 31.84                                   | -                             | -              | 46                            | -14.16         |
| 5      | .636               | 29.74                      | Pk  | 10.1                           | 0                 | 39.84                                   | 56                            | -16.16         | -                             | -              |
| 6      | .645               | 18.6                       | Av  | 10.1                           | 0                 | 28.7                                    | -                             | -              | 46                            | -17.3          |
| 7      | 3.048              | 33.01                      | Pk  | 9.8                            | .1                | 42.91                                   | 56                            | -13.09         | -                             | -              |
| 8      | 3.084              | 19.11                      | Av  | 9.8                            | .1                | 29.01                                   | -                             | -              | 46                            | -16.99         |
| 9      | 4.92               | 35.05                      | Pk  | 9.8                            | .1                | 44.95                                   | 56                            | -11.05         | -                             | -              |
| 10     | 4.848              | 19.8                       | Av  | 9.8                            | .1                | 29.7                                    | -                             | -              | 46                            | -16.3          |
| 11     | 22.713             | 30.63                      | Pk  | 10.5                           | .2                | 41.33                                   | 60                            | -18.67         | -                             | -              |
| 12     | 22.65              | 13.83                      | Av  | 10.5                           | .2                | 24.53                                   | -                             | -              | 50                            | -25.47         |

Pk - Peak detector

Av - Average detection

## LINE 2 PLOT



## LINE 2 RESULTS

### Trace Markers

Phase N .15 - 30MHz

| Marker | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Det | 101837_w<br>ith ex-<br>cord_N | CE Shield<br>Room | Corrected<br>Reading<br>(dB(uVolts<br>) | CISPR 22<br>Class B ITE<br>QP | Margin<br>(dB) | CISPR 22<br>Class B ITE<br>AV | Margin<br>(dB) |
|--------|--------------------|----------------------------|-----|-------------------------------|-------------------|-----------------------------------------|-------------------------------|----------------|-------------------------------|----------------|
| 13     | .177               | 29.66                      | Pk  | 10.1                          | 0                 | 39.76                                   | 64.63                         | -24.87         | -                             | -              |
| 14     | .186               | 13.9                       | Av  | 10                            | 0                 | 23.9                                    | -                             | -              | 54.21                         | -30.31         |
| 15     | .555               | 29.65                      | Pk  | 10.1                          | 0                 | 39.75                                   | 56                            | -16.25         | -                             | -              |
| 16     | .555               | 20.56                      | Av  | 10.1                          | 0                 | 30.66                                   | -                             | -              | 46                            | -15.34         |
| 17     | .636               | 27.41                      | Pk  | 10.1                          | 0                 | 37.51                                   | 56                            | -18.49         | -                             | -              |
| 18     | .645               | 17.32                      | Av  | 10                            | 0                 | 27.32                                   | -                             | -              | 46                            | -18.68         |
| 19     | 1.446              | 29.85                      | Pk  | 9.8                           | .1                | 39.75                                   | 56                            | -16.25         | -                             | -              |
| 20     | 1.473              | 16.22                      | Av  | 9.8                           | .1                | 26.12                                   | -                             | -              | 46                            | -19.88         |
| 21     | 4.074              | 34.1                       | Pk  | 9.8                           | .1                | 44                                      | 56                            | -12            | -                             | -              |
| 22     | 4.065              | 19.03                      | Av  | 9.8                           | .1                | 28.93                                   | -                             | -              | 46                            | -17.07         |
| 23     | 18.258             | 31                         | Pk  | 10.5                          | .2                | 41.7                                    | 60                            | -18.3          | -                             | -              |
| 24     | 18.15              | 14.31                      | Av  | 10.5                          | .2                | 25.01                                   | -                             | -              | 50                            | -24.99         |

Pk - Peak detector

Av - Average detection