



**FCC CFR47 PART 27 SUBPART F
FCC CFR47 PART 27 SUBPART L**

WWAN

CERTIFICATION TEST REPORT

FOR

LTE Watch + BT/BLE and DTS b/g/n

MODEL NUMBER : SM-R765V

FCC ID: A3LSMR765V

REPORT NUMBER: 4787821625-E4V1

ISSUE DATE: FEB 03, 2017

Prepared for
**SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA**

Prepared by
**UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433**



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	02/03/17	Initial issue	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION.....	6
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT.....	7
5.2. MAXIMUM OUTPUT POWER (LTE).....	7
5.3. DESCRIPTION OF TEST SETUP.....	9
6. TEST AND MEASUREMENT EQUIPMENT	11
7. Summary Table	12
8. RF POWER OUTPUT VERIFICATION	13
8.1. LTE OUTPUT VERIFICATION	13
8.1.1. LTE OUTPUT POWER RESULT	14
9. PEAK TO AVERAGE RATIO.....	17
9.1. CONDUCTED PEAK TO AVERAGE RESULT	17
9.2. CONDUCTED PEAK TO AVERAGE PLOTS.....	18
10. LIMITS AND CONDUCTED RESULTS.....	21
10.1. OCCUPIED BANDWIDTH	21
10.1.1. OCCUPIED BANDWIDTH PLOTS	24
10.2. BAND EDGE EMISSIONS.....	32
10.2.1. BAND EDGE PLOTS	35
10.3. OUT OF BAND EMISSIONS	45
10.3.1. OUT OF BAND EMISSIONS RESULT	46
10.3.2. OUT OF BAND EMISSIONS PLOTS.....	48
10.4. FREQUENCY STABILITY	56
10.4.1. FREQUENCY STABILITY RESULTS.....	57
11. RADIATED TEST RESULTS.....	59
11.1. RADIATED POWER (ERP & EIRP).....	59
11.1.1. ERP/EIRP Results	60
11.1.2. ERP/EIRP DATA	60

11.2.	FIELD STRENGTH OF SPURIOUS RADIATION.....	68
11.2.1.	SPURIOUS RADIATION PLOTS.....	69
12.	SETUP PHOTOS	77

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: LTE Watch + BT/BLE and DTS b/g/n

MODEL NUMBER: SM-R765V

SERIAL NUMBER: R3AH8008D4T, R3AH8008L9F, R3AH8008H6J,
R3AH8008GVV, R3AH8008H2R (RADIATED);
R3AH8008H8M (CONDUCTED)

DATE TESTED: JAN 11, 2017 - JAN 31, 2017

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 27F and 27L	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:

Tested By:



SungGil Park
Suwon Lab Engineer
UL Korea, Ltd.



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with TIA-603-D, FCC CFR 47 Part 2 and Part 27.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☐	Chamber 1
☒	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\text{EIRP} = \text{PSA reading with EUT worst orientation (dBm)} + \text{Path loss (dB)} - \text{cable loss (between the SG and substitution antenna)} + \text{Substitution Antenna Factor (dBi)}$$

$$\text{ERP} = \text{PSA reading with EUT worst orientation (dBm)} + \text{Path loss (dB)} - \text{cable loss (between the SG and substitution antenna)}$$

(Path loss = Signal generator output – PSA reading with substitution antenna)

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a LTE Watch + Bluetooth/BLE and DTS b/g/n.

5.2. MAXIMUM OUTPUT POWER (LTE)

The transmitter has a maximum peak conducted and radiated ERP / EIRP output powers as follows:

LTE Band 4

FCC Part 27							
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Conducted		Radiated	
				Avg [dBm]	Avg [mW]	Avg [dBm]	Avg [mW]
Band 4	1710 ~ 1755	20	QPSK	22.70	186.21	17.85	60.95
			16QAM	21.64	145.88	16.89	48.87
		15	QPSK	22.62	182.81	17.57	57.15
			16QAM	21.48	140.60	16.61	45.81
		10	QPSK	22.78	189.67	18.13	65.01
			16QAM	21.61	144.88	17.22	52.72
		5	QPSK	22.74	187.93	17.94	62.23
			16QAM	21.71	148.25	16.97	49.77
		3	QPSK	22.72	187.07	18.25	66.83
			16QAM	21.72	148.59	17.18	52.24
		1.4	QPSK	22.75	188.36	16.63	46.03
			16QAM	21.69	147.57	15.47	35.24

LTE Band 13

FCC Part 27							
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Conducted		Radiated	
				Avg [dBm]	Avg [mW]	Avg [dBm]	Avg [mW]
Band 13	777 ~ 787	10	QPSK	23.21	209.41	-1.43	0.72
			16QAM	21.58	143.88	-2.45	0.57
		5	QPSK	23.15	206.54	-1.53	0.70
			16QAM	21.77	150.31	-2.07	0.62

DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a Metal antenna for the [List the bands supported with a maximum peak gain as follow:

Frequency (MHz)	Peak Gain (dBi)
LTE Band 4 1710 ~ 1755 MHz	-2.6
LTE Band 13 777 ~ 787 MHz	-14.8

5.3. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Adapter	SAMSUNG	ETA0U60JBE	DK2H202VS/7 -E	N/A
Data Cable	SAMSUNG	ECB-DU2EBE	N/A	N/A
Wireless Charger	SAMSUNG	EP-YO760	RF7HC1KGZSVCIS	A3LEPYO760


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A


TEST SETUP

The EUT is continuously communicated to the call box during the tests.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Tuned Dipole 400~1000 MHz	ETS	3121D DB4	00164753	07-28-17
Antenna, Horn, 40 GHz	ETS	3116C	00166155	11-30-17
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	12-15-17
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	10-14-18
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-17
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-17
Antenna, Horn, 18 GHz	ETS	3115	00167211	10-14-18
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-17
Combiner	WEINSCHTEL	1575	2150	08-16-17
Communications Test Set	R&S	CMW500	150312	08-17-17
Communications Test Set	R&S	CMW500	115331	08-17-17
DC Power Supply	Agilent / HP	E3640A	MY54226395	08-16-17
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-17-17
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-16-17
Preamplifier	ETS	3115-PA	00167475	08-17-17
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-16-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-17-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-16-17
Average Power Sensor	R&S	NRZ-Z91	102681	08-16-17
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-16-17
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-16-17
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
High Pass Filter 1.2GHz	Micro-Tronics	HPM50108-02	G005	08-17-17
High Pass Filter 1.2GHz	Micro-Tronics	HPM50108-02	G006	08-17-17
High Pass Filter 2.8GHz	Micro-Tronics	HPM50111-02	010	08-17-17
High Pass Filter 2.8GHz	Micro-Tronics	HPM50111-02	011	08-17-17
High Pass Filter 4GHz	Micro-Tronics	HPM50118-02	G001	08-17-17
High Pass Filter 4GHz	Micro-Tronics	HPM50118-02	G002	08-17-17
Attenuator	PASTERNAK	PE7087-10	A009	08-16-17
Temperature Chamber	ESPEC	SH-642	93001109	08-17-17
UL Software				
Description	Manufacturer	Model	Version	
Antenna port test software	UL	CLT	Ver 1.6	

7. Summary Table

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Note
2.1049	Occupied Band width (99%)	N/A	Conducted	Pass	17.922 MHz
27.53	Band Edge / Conducted Spurious Emission	-13dBm		Pass	-16.637dBm
2.1046	Conducted output power	N/A		Pass	23.21 dBm
27.54	Frequency Stability	2.5PPM		Pass	-0.018PPM
27.50(d)	Equivalent Isotropic Radiated Power	30 dBm	Radiated	Pass	18.25 dBm
27.50(b)	Effective Radiated Power	34.77 dBm		Pass	-1.43 dBm
27.53(c),(h)	Radiated Spurious Emission	-13dBm		Pass	-51.2 dBm
27.53(f)		-40dBm		Pass	-52.9 dBm

FCC Rule Part	Frequency Range [MHz]	Output Power [W]	Frequency Tolerance	Emission Designator	Emission Bandwidth	Communication Type
LTE Band 4						
27L	1720.0 - 1745.0.	0.06095	2.5 ppm	17M9G7W	20	QPSK
27L	1720.0 - 1745.0.	0.04887	2.5 ppm	17M9D7W	20	16QAM
27L	1715.0 - 1750.0	0.05272	2.5 ppm	8M96D7W	10	16QAM
27L	1711.5 - 1753.5	0.06683	2.5 ppm	2M70G7W	3	QPSK
LTE Band 13						
27F	782	0.00072	2.5 ppm	8M97G7W	10	QPSK
27F	782	0.00057	2.5 ppm	8M96D7W	10	16QAM
27F	779.5 - 784.5	0.00062	2.5 ppm	4M51D7W	5	16QAM

8. RF POWER OUTPUT VERIFICATION

8.1. LTE OUTPUT VERIFICATION

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signalling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	Table 6.2.4-2
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

8.1.1. LTE OUTPUT POWER RESULT

LTE Band 4 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Avg Pwr (dBm)		
						20050	20175	20300
						1720 MHz	1732.5 MHz	1745 MHz
LTE Band 4	20	QPSK	1	0	0	22.70	22.31	22.24
			1	49	0	22.60	22.30	22.23
			1	99	0	22.41	22.37	22.38
			50	0	1	21.65	21.31	21.18
			50	24	1	21.56	21.30	21.21
			50	50	1	21.55	21.29	21.27
			100	0	1	21.59	21.30	21.23
		16QAM	1	0	1	21.64	21.15	21.22
			1	49	1	21.56	21.16	21.15
			1	99	1	21.45	21.18	21.30
			50	0	2	20.61	20.22	20.10
			50	24	2	20.53	20.20	20.12
			50	50	2	20.48	20.17	20.16
			100	0	2	20.60	20.30	20.20
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Avg Pwr (dBm)		
						20025	20175	20325
						1717.5 MHz	1732.5 MHz	1747.5 MHz
LTE Band 4	15	QPSK	1	0	0	22.58	22.35	22.29
			1	37	0	22.62	22.22	22.44
			1	74	0	22.31	22.32	22.44
			36	0	1	21.59	21.30	21.25
			36	20	1	21.56	21.27	21.27
			36	39	1	21.55	21.27	21.32
			75	0	1	21.57	21.30	21.28
		16QAM	1	0	1	21.00	21.28	21.36
			1	37	1	21.05	21.18	21.47
			1	74	1	20.72	21.29	21.48
			36	0	2	20.55	20.31	20.14
			36	20	2	20.52	20.27	20.18
			36	39	2	20.48	20.25	20.22
			75	0	2	20.53	20.23	20.21
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Avg Pwr (dBm)		
						20000	20175	20350
						1715 MHz	1732.5 MHz	1750 MHz
LTE Band 4	10	QPSK	1	0	0	22.78	22.39	22.16
			1	25	0	22.63	22.26	22.13
			1	49	0	22.35	22.38	22.18
			25	0	1	21.58	21.30	21.16
			25	12	1	21.54	21.26	21.15
			25	25	1	21.55	21.25	21.19
			50	0	1	21.55	21.29	21.19
		16QAM	1	0	1	21.61	21.18	21.09
			1	25	1	21.57	21.04	21.07
			1	49	1	21.27	21.17	21.14
			25	0	2	20.58	20.29	20.14
			25	12	2	20.53	20.23	20.15
			25	25	2	20.54	20.22	20.18
			50	0	2	20.55	20.23	20.13

LTE Band 4 Measured Results (continued)

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Avg Pwr (dBm)		
						19975	20175	20375
						1712.5 MHz	1732.5 MHz	1752.5 MHz
LTE Band 4	5	QPSK	1	0	0	22.65	22.34	22.23
			1	12	0	22.74	22.41	22.35
			1	24	0	22.46	22.33	22.28
			12	0	1	21.60	21.20	21.24
			12	7	1	21.57	21.22	21.30
			12	13	1	21.55	21.19	21.27
			25	0	1	21.52	21.18	21.24
		16QAM	1	0	1	21.71	21.37	21.10
			1	12	1	21.67	21.44	21.22
			1	24	1	21.63	21.35	21.16
			12	0	2	20.49	20.18	20.15
			12	7	2	20.49	20.18	20.21
			12	13	2	20.43	20.17	20.19
			25	0	2	20.58	20.12	20.18
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Avg Pwr (dBm)		
						19965	20175	20385
						1711.5 MHz	1732.5 MHz	1753.5 MHz
LTE Band 4	3	QPSK	1	0	0	22.68	22.33	22.41
			1	8	0	22.50	22.43	22.43
			1	14	0	22.72	22.28	22.35
			8	0	1	21.75	21.22	21.28
			8	4	1	21.66	21.25	21.29
			8	7	1	21.54	21.30	21.27
			15	0	1	21.65	21.25	21.26
		16QAM	1	0	1	21.72	21.32	21.30
			1	8	1	21.47	21.41	21.28
			1	14	1	21.70	21.25	21.21
			8	0	2	20.76	20.05	20.24
			8	4	2	20.60	20.11	20.23
			8	7	2	20.56	20.14	20.20
			15	0	2	20.57	20.18	20.17
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Avg Pwr (dBm)		
						19957	20175	20393
						1710.7 MHz	1732.5 MHz	1754.3 MHz
LTE Band 4	1.4	QPSK	1	0	0	22.65	22.21	22.26
			1	3	0	22.74	22.27	22.19
			1	5	0	22.75	22.26	22.23
			3	0	0	22.68	22.25	22.20
			3	1	0	22.73	22.28	22.20
			3	3	0	22.73	22.27	22.24
			6	0	1	21.76	21.28	21.19
		16QAM	1	0	1	21.50	21.23	21.04
			1	3	1	21.53	21.29	20.98
			1	5	1	21.25	21.28	21.02
			3	0	1	21.69	21.26	21.17
			3	1	1	21.64	21.25	21.21
			3	3	1	21.60	21.26	21.20
			6	0	2	20.73	20.08	20.13

LTE Band 13 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Avg Pwr (dBm)
						23230
						782 MHz
LTE Band 13	10	QPSK	1	0	0	23.21
			1	25	0	23.08
			1	49	0	23.14
			25	0	1	21.58
			25	12	1	21.56
			25	25	1	21.57
			50	0	1	21.58
		16QAM	1	0	1	21.58
			1	25	1	21.44
			1	49	1	21.52
			25	0	2	20.56
			25	12	2	20.53
			25	25	2	20.55
			50	0	2	20.57
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Avg Pwr (dBm)
						23230
						782 MHz
LTE Band 13	5	QPSK	1	0	0	23.12
			1	12	0	23.11
			1	24	0	23.15
			12	0	1	21.56
			12	7	1	21.53
			12	13	1	21.55
			25	0	1	21.55
		16QAM	1	0	1	21.73
			1	12	1	21.71
			1	24	1	21.77
			12	0	2	20.50
			12	7	2	20.46
			12	13	2	20.45
			25	0	2	20.62

9. PEAK TO AVERAGE RATIO

Test Procedure

Per KDB 971168 D01 Power Meas License Digital Systems v02r02;

The transmitter output was connected to a CMW500 Test Set and configured to operate at maximum power. The PAR were measured on the Spectrum Analyzer.

Test Spec

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13 dB.

9.1. CONDUCTED PEAK TO AVERAGE RESULT

LTE B4


Band	BW [MHz]	Channel	f [MHz]	Mode	Ratio [dB]	Limit [dB]
Band 4	20	20174	1732.5	QPSK	4.04	13.00
				16QAM	5.19	
	15			QPSK	4.15	
				16QAM	5.48	
	10			QPSK	4.37	
				16QAM	5.55	
	5			QPSK	4.35	
				16QAM	5.42	
	3			QPSK	4.40	
				16QAM	5.59	
1.4	QPSK	4.41				
	16QAM	5.52				







LTE B13

Band	BW [MHz]	Channel	f [MHz]	Mode	Ratio [dB]	Limit [dB]
Band 13	10	23230	782	QPSK	3.91	13.00
				16QAM	5.36	
	5			QPSK	4.12	
				16QAM	5.39	


9.2. CONDUCTED PEAK TO AVERAGE PLOTS

LTE Band 4



LTE Band 4 5 MHz	 LTE B4 5MHz QPSK Mid channel	 LTE B4 5MHz 16QAM Mid channel
LTE Band 4 3 MHz	 LTE B4 3MHz QPSK Mid channel	 LTE B4 3MHz 16QAM Mid channel
LTE Band 4 1.4 MHz	 LTE B4 1.4MHz QPSK Mid channel	 LTE B4 1.4MHz 16QAM Mid channel

LTE Band 13



10. LIMITS AND CONDUCTED RESULTS

10.1. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049

LIMITS

For reporting purposes only

TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.

(KDB 971168 D01 Power Meas License Digital Systems v02r02)

LTE Band 4


Band	BW [MHz]	Channel	f [MHz]	Mode	99% BW [MHz]	26dB BW [MHz]
Band 4	20	20050	1720.0	QPSK	17.847	19.45
				16QAM	17.865	19.70
		20174	1732.5	QPSK	17.853	19.44
				16QAM	17.871	19.52
		20299	1745.0	QPSK	17.922	19.62
				16QAM	17.909	19.58
	15	20025	1717.5	QPSK	13.452	15.25
				16QAM	13.434	15.05
		20174	1732.5	QPSK	13.427	14.99
				16QAM	13.431	14.82
		20324	1747.5	QPSK	13.445	15.22
				16QAM	13.445	15.13
	10	20000	1715.0	QPSK	8.9717	10.26
				16QAM	8.9626	10.15
		20174	1732.5	QPSK	8.9493	10.27
				16QAM	8.9523	10.16
		20349	1750.0	QPSK	8.9624	10.24
				16QAM	8.9642	10.17
	5	19975	1712.5	QPSK	4.5125	5.312
				16QAM	4.5081	5.338
		20174	1732.5	QPSK	4.5115	5.336
				16QAM	4.5017	5.220
		20374	1752.5	QPSK	4.5113	5.319
				16QAM	4.5015	5.303
	3	19965	1711.5	QPSK	2.7007	3.090
				16QAM	2.6926	3.040
		20174	1732.5	QPSK	2.6994	3.094
				16QAM	2.6966	3.083
		20384	1753.5	QPSK	2.6958	3.067
				16QAM	2.6955	3.047
	1.4	19957	1710.7	QPSK	1.0901	1.369
				16QAM	1.0955	1.414
		20174	1732.5	QPSK	1.0889	1.362
				16QAM	1.0959	1.417
		20392	1754.3	QPSK	1.0888	1.386
				16QAM	1.0944	1.418


LTE Band 13


Band	BW [MHz]	Channel	f [MHz]	Mode	99% BW [MHz]	26dB BW [MHz]
Band 13	10	23230	782.0	QPSK	8.9741	10.25
				16QAM	8.9600	9.987
	5	23207	779.5	QPSK	4.4968	5.255
				16QAM	4.5002	5.133
		23230	782.0	QPSK	4.4830	5.211
				16QAM	4.4890	5.149
		23255	784.5	QPSK	4.5110	5.378
				16QAM	4.5092	5.316


10.1.1. OCCUPIED BANDWIDTH PLOTS

LTE Band 4
















LTE Band 13





10.2. BAND EDGE EMISSIONS

RULE PART(S)

FCC: §27.53(c) (2), (4), (h)

LIMITS

(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(h) The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v02r02

The transmitter output was connected to a CMW500 Test Set and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

LTE

- a) Set the RBW = $1 \sim 1.5$ % of OBW(Typically limited to a minimum RBW of 1% of the OBW)
- b) Set VBW $\geq 3 \times$ RBW;
- c) Set span ≥ 1.5 times the OBW;
- d) Sweep time = Auto ;
- e) Detector = RMS;
- f) Ensure that the number of measurement points $\geq 2 \times \text{Span/RBW}$;
- g) Trace mode = Average(100);

Note: For frequency range of 763-775 MHz and 793-805 MHz,

- a) Set the RBW = 6.2kHz
- b) Set VBW $\geq 3 \times$ RBW;
- c) Sweep time = 1 second ;
- d) Detector = RMS;
- e) Ensure that the number of measurement points $\geq 2 \times \text{Span/RBW}$;
- f) Trace mode = Maxhold;

RESULTS

LTE 4

Bandwidth	Mode	Side	RB Status	f [MHz]	Level [dBm]	Limit [dBm]
20 MHz	QPSK	Lower	1RB	1710.000	-29.871	-13.00
			FRB	1710.000	-28.085	
		Upper	1RB	1755.000	-29.130	
			FRB	1755.000	-26.375	
	16QAM	Lower	1RB	1710.000	-31.822	
			FRB	1710.000	-30.226	
		Upper	1RB	1755.000	-32.770	
			FRB	1755.000	-27.640	
15 MHz	QPSK	Lower	1RB	1710.000	-23.041	
			FRB	1710.000	-28.823	
		Upper	1RB	1755.000	-20.792	
			FRB	1755.000	-25.804	
	16QAM	Lower	1RB	1710.000	-23.971	
			FRB	1710.000	-27.627	
		Upper	1RB	1755.000	-20.098	
			FRB	1755.000	-26.195	
10 MHz	QPSK	Lower	1RB	1710.000	-30.681	
			FRB	1710.000	-25.171	
		Upper	1RB	1755.000	-26.791	
			FRB	1755.000	-25.840	
	16QAM	Lower	1RB	1710.000	-29.432	
			FRB	1710.000	-27.999	
		Upper	1RB	1755.000	-28.197	
			FRB	1755.000	-25.343	
5 MHz	QPSK	Lower	1RB	1710.000	-21.113	
			FRB	1710.000	-23.075	
		Upper	1RB	1755.000	-18.865	
			FRB	1755.000	-21.372	
	16QAM	Lower	1RB	1710.000	-20.927	
			FRB	1710.000	-23.503	
		Upper	1RB	1755.000	-23.107	
			FRB	1755.000	-23.872	

Bandwidth	Mode	Side	RB Status	f [MHz]	Level [dBm]	Limit [dBm]
3 MHz	QPSK	Lower	1RB	1710.000	-16.855	-13.00
			FRB	1710.000	-22.606	
		Upper	1RB	1755.000	-16.637	
			FRB	1755.000	-23.949	
	16QAM	Lower	1RB	1710.000	-21.008	
			FRB	1710.000	-24.217	
		Upper	1RB	1755.000	-19.109	
			FRB	1755.000	-23.226	
1.4 MHz	QPSK	Lower	1RB	1710.000	-21.219	-13.00
			FRB	1710.000	-21.726	
		Upper	1RB	1755.000	-21.840	
			FRB	1755.000	-22.027	
	16QAM	Lower	1RB	1710.000	-22.345	
			FRB	1710.000	-23.209	
		Upper	1RB	1755.000	-23.131	
			FRB	1755.000	-24.660	

LTE 13

Bandwidth	Mode	Side	RB Status	f [MHz]	Level [dBm]	Limit [dBm]
10 MHz	QPSK	Lower	1RB	777.000	-27.981	-13.00
			FRB	777.000	-26.033	
		Upper	1RB	787.000	-29.357	
			FRB	787.000	-23.700	
	16QAM	Lower	1RB	777.000	-30.301	
			FRB	777.000	-27.276	
		Upper	1RB	787.000	-29.173	
			FRB	787.000	-26.103	
5 MHz	QPSK	Lower	1RB	777.000	-20.060	-13.00
			FRB	777.000	-24.211	
		Upper	1RB	787.000	-17.500	
			FRB	787.000	-20.596	
	16QAM	Lower	1RB	777.000	-22.753	
			FRB	777.000	-24.820	
		Upper	1RB	787.000	-20.954	
			FRB	787.000	-23.132	

10.2.1. BAND EDGE PLOTS

LTE Band 4

