verify No.759491271410

위변조방지/진위확인
www.docugr.com

TEST REPORT

KCTL Inc.
65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SRF0128-B

KCTL

1. Client

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
- Date of Receipt : 2020-04-03

2. Use of Report : Certification

3. Name of Product / Model : Smart Wearable / SM-R845U

4. Manufacturer / Country of Origin : Samsung Electronics Co., Ltd. / Vietnam

5. FCC ID : A3LSMR845

6. IC Certificate No. : 649E-SMR845

7. Date of Test : 2020-04-13 to 2020-05-20

8. Location of Test : ■ Permanent Testing Lab ☐ On Site Testing (Address: Address of testing location)

9. Test method used : FCC Part 15 Subpart C, 15.247
RSS-247 Issue 2 February 2017
RSS-Gen Issue 5 March 2019

10. Test Result : Refer to the test result in the test report

Affirmation	Tested by Name : Kwonse Kim (Signature)	Technical Manager Name : Seungyong Kim (Signature)

2020-05-25

KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

REPORT REVISION HISTORY

Date	Revision	Page No
2020-05-22	Originally issued	-
2020-05-24	Updated	5
2020-05-25	Updated	5,30

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

Note. The report No. KR20-SRF0128-A is superseded by the report No. KR20-SRF0128-B.

General remarks for test reports

Nothing significant to report.

CONTENTS

1. General information 4
2. Device information 4
2.1. Accessory information 5
2.2. Model Information 5
2.3. Frequency/channel operations 6
3. Antenna requirement 7
4. Summary of tests 8
5. Measurement uncertainty 9
6. Measurement results explanation example 10
7 Test results 11
7.1. Maximum peak output power 11
7.2. Carrier frequency separation 13
7.3. 20dB channel bandwidth(Occupied bandwidth) 16
7.4. Number of hopping channels 20
7.5. Time of occupancy(Dwell time) 22
7.6. Radiated spurious emissions & band edge 26
7.7. Conducted Spurious Emission 46
7.8. AC Conducted emission 50
8. Measurement equipment 52

This test report shall not be reproduced, except in full, without the written approval

1. General information

Client	:	Samsung Electronics Co., Ltd.
Address	:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Manufacturer	:	Samsung Electronics Co., Ltd.
Address	:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Laboratory	:	KCTL Inc.
Address	:	65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations	:	FCC Site Designation No: KR0040, FCC Site Registration No: 687132
		VCCI Registration No. : R-20080, G-20078, C-20059, T-20056
		Industry Canada Registration No. : 8035A
		KOLAS No.: KT231

2. Device information

Equipment under test	:	Smart Wearable
Model	:	SM-R845U
Derivative model	:	SM-R845F
Modulation technique	:	Bluetooth(BDR/EDR)_ GFSK, π/4DQPSK, 8DPSK
		Bluetooth(BLE)_GFSK
		WIFI(802.11b/g/n20)_DSSS, OFDM
		LTE_QPSK, 16QAM
Number of channels	:	Bluetooth(BDR/EDR)_79 ch
		Bluetooth(BLE)_40 ch
		WIFI(802.11b/g/n20)_13 ch
Power source	:	DC 3.85 V
Antenna specification	:	LTE/WCDMA_PIFA (Housing metal) Antenna
		WIFI/Bluetooth(BDR/EDR/BLE)_LDS Antenna
Antenna gain	:	WIFI/Bluetooth(BDR/EDR/BLE) : -8.31 dBi

This test report shall not be reproduced, except in full, without the written approval

Frequency range	:	Bluetooth(BDR/EDR/BLE)_2 402 ㎒ ~ 2 480 ㎒
		WIFI(802.11b/g/n20)_2 412 ㎒ ~ 2 472 ㎒
		LTE Band 2_1 850.7 ㎒ ~ 1 909.3 ㎒
		LTE Band 4_1 710.7 ㎒ ~ 1 754.3 ㎒
		LTE Band 5_824.7 ㎒ ~ 848.3 ㎒
		LTE Band 12_699.7 ㎒ ~ 715.3 ㎒
		LTE Band 13_779.5 ㎒ ~ 784.5 ㎒
		LTE Band 25_1 850.7 ㎒ ~ 1 914.3 ㎒
		LTE Band 26_824.7 ㎒ ~ 848.3 ㎒, 814.7 ㎒ ~ 823.3 ㎒
		LTE Band 66_1 710.7 ㎒ ~ 1 779.3 ㎒
		LTE Band 71_665.5 ㎒ ~ 688.0 ㎒
		WCDMA 850_826.4 ㎒ ~ 846.6 ㎒
		WCDMA 1700_1 712.4 ㎒ ~ 1 752.6 ㎒
		WCDMA 1900_1 852.4 ㎒ ~ 1 907.6 ㎒
Software version	:	SM-R845U_R845U.001, SM-R845F_R845F.001
Hardware version	:	REV1.0
Test device serial No.	:	Conducted(R3AN3003ZWM)
		Radiated(R3AN400CXFL, R3AN400CWVZ, R3AN400CTXA)
Operation temperature	:	-30 ℃ ~ 50 ℃

2.1. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source	FCC ID & IC
Wireless charger	Samsung Electronics Co., Ltd.	EP-OR825	-	DC 5.0 V, 1.0 A	A3LEPOR825 / 649E-EPOR825

2.2. Model Information

The difference between basic model (SM-R845U) and derivative model (SM-R845F) is:

a. RF Supported Band is Different.
(R845U: 3G (B2, B4, B5), 4G (B2, B4, B5, B12, B13, B25, B26, B66, B71))
(R845F: 3G (B1, B2, B4, B5, B8), 4G (B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B28, B66))
- In EUR R845F : 3G (B1, B5, B8), 4G (B1, B3, B5, B7, B8, B20, B28)
b. All other protocol part is same.
c. All other features of Volte, SUPL is same.
d. In USA & Canada, 4G (B7) disabled by MCC code.
Because device doesn't support B7 roaming in USA & Canada.

2.3. Frequency/channel operations

This device contains the following capabilities:
2.4㎓ WIFI(802.11b/g/n(HT20)), Bluetooth(BDR/EDR/BLE), LTE Band 2, LTE Band 4, LTE Band 5, LTE Band 12, LTE Band 13, LTE Band 25, LTE Band 26, LTE Band 66, LTE Band 71, WCDMA 850, WCDMA 1700, WCDMA 1900

Ch.	Frequency (㎒)
00	2 402
. .	. .
39	2 441
. .	. .
78	2 480

Table 2.3.1. Bluetooth(BDR/EDR) mode

15.247 Requirements for Bluetooth transmitter:

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  1) This system is hopping pseudo-randomly.
  2) Each frequency is used equally on the average by each transmitter.
  3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
  4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Requirement of RSS-Gen Section 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

- The transmitter has permanently attached LDS Antenna (internal antenna) on board.
- The E.U.T Complies with the requirement of §15.203, §15.247.

4. Summary of tests

FCC Part section(s)	IC Rule Referance	Parameter	Test results
15.247(b)(1), (4)	RSS-247, (5.4)(b)	Maximum peak output power	Pass
15.247(a)(1)	RSS-247, (5.1)(b)	Carrier frequency separation	Pass
15.247(a)(1)	RSS-247, (5.1)(a)	20dB channel bandwidth	Pass
-	RSS-Gen (6.7)	Occupied bandwidth	Pass
15.247(a)(iii) 15.247(b)(1)	RSS-247, (5.1)(d)	Number of hopping channel	Pass
15.247(a) (iii)	RSS-247, (5.1)(d)	Time of occupancy(dwell time)	Pass
15.205(a), 15.209(a) 15.247(d)	RSS-Gen (8.9), (8.10) RSS-247(5.5)	Spurious emission	Pass
		Band-edge, restricted band	Pass
15.207(a)	RSS-Gen(8.8)	Conducted Emissions	Pass

Notes:

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. According to exploratory test no any obvious emission were detected from 9 ㎑ to 30 ㎒. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
3. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that **X** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **X** orientation
4. All the radiated tests have been performed two modes (with charger and without charger) and the with charger is the worst case mode.
5. The test procedure(s) in this report were performed in accordance as following.
   - ANSI C63.10-2013
   - KDB 558074 D01 v05r02

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of *k*=2 to indicated a 95 % level of confidence. The measurement data shown herein meets of exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty (±)	
Conducted RF power	1.3 dB	
Conducted spurious emissions	1.3 dB	
Radiated spurious emissions	9 kHz ~ 30 MHz:	2.3 dB
	30 MHz ~ 300 MHz	5.4 dB
	300 MHz ~ 1 000 MHz	5.5 dB
	Above 1 GHz	6.7 dB
Conducted emissions	9 kHz ~ 150 kHz	3.7 dB
	150 kHz ~ 30 MHz	3.3 dB

KCTL

6. Measurement results explanation example

Frequency (㎒)	Factor(㏈)	Frequency (㎒)	Factor(㏈)
30	16.01	9 000	18.38
50	16.26	10 000	18.42
100	16.35	11 000	18.44
200	16.43	12 000	18.83
300	16.50	13 000	19.04
400	16.56	14 000	19.57
500	16.61	15 000	19.64
600	16.64	16 000	19.68
700	16.69	17 000	19.66
800	16.73	18 000	19.82
900	16.75	19 000	20.03
1 000	16.77	20 000	20.11
2 000	17.07	21 000	20.44
3 000	17.24	22 000	20.65
4 000	17.47	23 000	20.78
5 000	17.70	24 000	20.85
6 000	18.00	25 000	20.95
7 000	18.31	26 000	21.09
8 000	18.36	26 500	21.10

Note.
Offset(㏈) = RF cable loss(㏈) + Power Divider(㏈) + Attenuator (㏈)

7 Test results

7.1. Maximum peak output power

Test setup



Limit

FCC

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 ㎑ or the 20 ㏈ bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 ㎒ band may have hopping channel carrier frequencies that are separated by 25 ㎑ or two-thirds of the 20 ㏈ bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽.

According to §15.247(b)(1), for frequency hopping systems operating in the 2 400-2 483.5 ㎒ band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725-5 850 ㎒ band: 1 watt. For all other frequency hopping systems in the 2 400-2 483.5 ㎒ band: 0.125 watts.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 ㏈i. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 ㏈i are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in ㏈ that the directional gain of the antenna exceeds 6 ㏈i.

IC

According to RSS-247(5.4)(b), for FHSs operating in the band 2400-2483.5 ㎒, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels.
The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

Test procedure

ANSI C63.10-2013 - Section 7.8.5

Test settings

The test follows ANSI C63.10-2013 – Section 7.8.5. Using the power sensor instead of a spectrum analyzer.

Notes:

A peak responding power sensor is used, where the power sensor system video bandwidth is greater than the occupied bandwidth of the EUT.

Test results

Frequency (MHz)	Data rate (Mbps)	Conducted output power(dBm)		Conducted power Limit (dBm)	Ant. Gain (dBi)	Max. e.i.r.p (dBm)		Max. e.i.r.p. Limit (dBm)
		Peak	Average			Peak	Average	
2 402	1	15.25	14.84	20.97	-8.31	6.94	6.53	36.02
2 441	1	14.91	14.35			6.60	6.04	
2 480	1	16.29	15.81			7.98	7.50	
2 402	2	11.51	8.48	20.97	-8.31	3.20	0.17	36.02
2 441	2	10.15	7.08			1.84	-1.23	
2 480	2	11.47	8.57			3.16	0.26	
2 402	3	11.98	8.59	20.97	-8.31	3.67	0.28	36.02
2 441	3	10.58	7.04			2.27	-1.27	
2 480	3	11.91	8.49			3.60	0.18	

Notes:

1. e.i.r.p. Calculation: e.i.r.p. (dB m) = Conducted output power (dB m) + Antenna gain (dB i)

7.2. Carrier frequency separation

Test setup



Limit

According to §15.247(a)(1) and RSS-247(5.1)(b), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 ㎑ or the 20 ㏈ bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 ㎒ band may have hopping channel carrier frequencies that are separated by 25 ㎑ or two-thirds of the 20 ㏈ bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽.

Test procedure

ANSI C63.10-2013 - Section 7.8.2

Test settings

a) Span: Wide enough to capture the peaks of two adjacent channels.
b) RBW: Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c) Video (or average) bandwidth (VBW) ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.
Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

Test results

Frequency(㎒)	Data rate(Mbps)	Carrier frequency separation(㎒)	Limit(㎒)
2 402	1	1.002	0.693
2 441	1	1.002	0.693
2 480	1	1.002	0.693
2 402	3	1.002	0.895
2 441	3	1.002	0.895
2 480	3	1.008	0.895

This test report shall not be reproduced, except in full, without the written approval

GFSK / Low ch.



8DPSK / Low ch.



GFSK / Mid ch.



8DPSK / Mid ch.



GFSK / High ch.



8DPSK / High ch.



7.3. 20dB channel bandwidth(Occupied bandwidth)

Test setup



Limit

According to §15.247(a)(1) and RSS-247(5.1)(a), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 ㎑ or the 20 ㏈ bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 ㎒ band may have hopping channel carrier frequencies that are separated by 25 ㎑ or two-thirds of the 20 ㏈ bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽.

Test procedure

ANSI C63.10-2013 - Section 6.9.2

Test settings

20dB channel bandwidth and Occupied bandwidth

The occupied bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of ㏈ down from the reference value). Typical ratios, expressed in dB, are −6 ㏈, −20 ㏈, and −26 ㏈, corresponding to 6 ㏈ BW, 20 ㏈ BW, and 26 ㏈ BW, respectively. In this subclause, the ratio is designated by "−xx ㏈." The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the "−xx ㏈" bandwidth; other requirements might specify that the "−xx ㏈" bandwidth be entirely contained within the authorized or designated frequency band.

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
b) Span: Two times and five times the OBW.
c) RBW = 1 % to 5 % of the OBW and VBW ≥ 3 x RBW
d) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation.
e) The dynamic range of the instrument at the selected RBW shall be more than 10 ㏈ below the target "−xx ㏈ down" requirement; that is, if the requirement calls for measuring the −20 ㏈ OBW, the instrument noise floor at the selected RBW shall be at least 30 ㏈ below the reference value.
f) Detector: peak
g) Trace mode: max hold.
h) Allow the trace to stabilize.
i) Determine the "−xx ㏈ down amplitude" using ((reference value) − xx). Alternatively, this calculation may be made by using the marker-delta function of the instrument.
j) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
k) Place two markers, one at the lowest frequency and the other at the highest frequency of the

envelope of the spectral display, such that each marker is at or slightly below the "−xx dB down amplitude" determined in step h). If a marker is below this "−xx dB down amplitude" value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the "−xx dB down amplitude" determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

Test results

Frequency(MHz)	Data rate (Mbps)	20 dB Bandwidth (MHz)	99% bandwidth (MHz)
2 402	1	1.04	0.92
2 441	1	1.04	0.92
2 480	1	1.04	0.92
2 402	3	1.34	1.20
2 441	3	1.34	1.19
2 480	3	1.34	1.20

This test report shall not be reproduced, except in full, without the written approval

20 dB bandwidth

GFSK / Low ch.



8DPSK / Low ch.



GFSK / Mid ch.



8DPSK / Mid ch.



GFSK / High ch.



8DPSK / High ch.



99 % bandwidth

GFSK / Low ch.



8DPSK / Low ch.



GFSK / Mid ch.



8DPSK / Mid ch.



GFSK / High ch.



8DPSK / High ch.



7.4. Number of hopping channels

Test setup



Limit

According to §15.247(a)(1)(iii) and RSS-247(5.1)(d), frequency hopping systems in the 2 400-2 483.5 ㎒ band shall use at least 15 channels.

Test procedure

ANSI C63.10-2013 - Section 7.8.3

Test settings

a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
b) RBW: To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 ㏈ bandwidth, whichever is smaller.
c) VBW ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Test results

Mode	Number of hopping channel	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15

Notes:

In case of AFH mode, minimum number of hopping channels is 20.

GFSK	π/4DQPSK
	
8DPSK	
	Blank

7.5. Time of occupancy(Dwell time)

Test setup



Limit

According to §15.247(a)(1)(iii) and RSS-247(5.1)(d), frequency hopping systems in the 2 400-2 483.5 ㎒ band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test procedure

ANSI C63.10-2013 - Section 7.8.4

Test settings

a) Span: Zero span, centered on a hopping channel.
b) RBW ≤ channel spacing and >> 1 / T, where T is the expected dwell time per channel.
c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
d) Detector function: Peak.
e) Trace: Max hold.
f) Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Test results

- Non-AFH

Modulation	Frequency (㎒)	Pulse Width (㎳)	Hopping rate (hop/s)	Number of Channels	Result (s)	Limit (s)
DH1	2 441	0.382	800.000	79	0.122	0.400
DH3	2 441	1.636	400.000	79	0.262	0.400
DH5	2 441	2.884	266.667	79	0.308	0.400
2-DH1	2 441	0.384	800.000	79	0.123	0.400
2-DH3	2 441	1.634	400.000	79	0.261	0.400
2-DH5	2 441	2.881	266.667	79	0.307	0.400
3-DH1	2 441	0.377	800.000	79	0.120	0.400
3-DH3	2 441	1.626	400.000	79	0.260	0.400
3-DH5	2 441	2.881	266.667	79	0.307	0.400

- AFH

Modulation	Frequency (㎒)	Pulse Width (㎳)	Hopping rate (hop/s)	Number of Channels	Result (s)	Limit (s)
DH1	2 441	0.382	400.000	20	0.061	0.400
DH3	2 441	1.636	200.000	20	0.131	0.400
DH5	2 441	2.884	133.333	20	0.154	0.400
2-DH1	2 441	0.384	400.000	20	0.061	0.400
2-DH3	2 441	1.634	200.000	20	0.131	0.400
2-DH5	2 441	2.881	133.333	20	0.154	0.400
3-DH1	2 441	0.377	400.000	20	0.060	0.400
3-DH3	2 441	1.626	200.000	20	0.130	0.400
3-DH5	2 441	2.881	133.333	20	0.154	0.400

Notes:

1. Non-AFH
   - Period Time: 0.4 sec x 79 channels = 31.6 sec
   - Result (s)= (Hopping rate (hop/s/slot) / 79 channels) x 31.6 sec x Pulse width (ms)
2. AFH
   - Period Time: 0.4 sec x 20 channels = 8 sec
   - Result (s)= (Hopping rate (hop/s/slot) / 20 channels) x 8 sec x Pulse width (ms)

GFSK / DH1



π/4DQPSK / 2-DH1



GFSK / DH3



π/4DQPSK / 2-DH3



GFSK / DH5



π/4DQPSK / 2-DH5



8DPSK / 3-DH1	8DPSK / 3-DH3
	
8DPSK / 3-DH5	
	Blank

7.6. Radiated spurious emissions & band edge

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 ㎑ to 30 ㎒ Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 ㎓ to the tenth harmonic of the highest fundamental frequency or to 40 ㎓ emissions, whichever is lower.



Limit

FCC

According to section 15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section15.231 and 15.241.

According to section 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 – 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 – 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 – 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 – 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 – 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 – 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 – 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 – 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 – 2 500	17.7 - 21.4
8.376 25 - 8.386 75		2 690 – 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 – 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 – 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 – 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 – 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

IC

According to RSS-247(5.5), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen(8.9), Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5- General field strength limits at frequencies above 30 MHz

Frequency(㎒)	Field strength (μV/m at 3 m)
30 to 88	100
88 to 216	150
216 to 960	200
Above 960	500

Table 6- General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (㎛A/m)	Measurement distance(m)
9 – 490 ㎑ 1)	6.37/F (F in ㎑)	300
490 – 1705 ㎑	63.7/F (F in ㎑)	30
1.705 - 30 ㎒	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

According to RSS-Gen(8.10), Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

(a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD).
(b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.
(c) Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

Table 7- Restricted frequency bands*

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138	--	

* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.