



# TEST REPORT

|                                                                                                                                                                                                         |                                                       |                                                                   |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|-------------------------------------------------------------------|
| <b>Eurofins KCTL Co.,Ltd.</b><br>65, Sinwon-ro, Yeongtong-gu,<br>Suwon-si, Gyeonggi-do, 16677, Korea<br>TEL: 82-70-5008-1021 FAX: 82-505-299-8311<br><a href="http://www.kctl.co.kr">www.kctl.co.kr</a> | Report No.:<br><b>KR24-SRF0083</b><br>Page(1) of (73) | <div style="float: right; text-align: right;"> <b>KCTL</b> </div> |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|-------------------------------------------------------------------|

**1. Client**

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
- Date of Receipt : 2024-05-02

**2. Use of Report** : Certification

**3. Name of Product / Model** : Smart Wearable / SM-R866U

**4. Manufacturer / Country of Origin** : Samsung Electronics Co., Ltd. / Vietnam

**5. FCC ID** : A3LSMR866

**6. Date of Test** : 2024-05-03 to 2024-05-14

**7. Location of Test** : ☒ Permanent Testing Lab ☐ On Site Testing  
 (Address: 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)

**8. Test method used** : FCC Part 15 Subpart E, 15.407

**9. Test Result** : Refer to the test result in the test report

|             |                                                |                                                           |
|-------------|------------------------------------------------|-----------------------------------------------------------|
| Affirmation | Tested by<br><br>Name : Kwonse Kim (Signature) | Technical Manager<br><br>Name : Seungyong Kim (Signature) |
|-------------|------------------------------------------------|-----------------------------------------------------------|

2024-05-17

**Eurofins KCTL Co.,Ltd.**

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by Eurofins KCTL Co.,Ltd.

|                                                                                                                                                                                                         |                                                 |                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Eurofins KCTL Co.,Ltd.</b><br>65, Sinwon-ro, Yeongtong-gu,<br>Suwon-si, Gyeonggi-do, 16677, Korea<br>TEL: 82-70-5008-1021 FAX: 82-505-299-8311<br><a href="http://www.kctl.co.kr">www.kctl.co.kr</a> | Report No.:<br>KR24-SRF0083<br>Page (2) of (73) |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------------------------------------------------------------------------|

## REPORT REVISION HISTORY

| Date       | Revision          | Page No |
|------------|-------------------|---------|
| 2024-05-17 | Originally issued | -       |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |

*This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.*

## General remarks for test reports

### Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

☐ Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

### Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

☒ Statement not required by the standard or client used for type testing

## CONTENTS

|      |                                                         |    |
|------|---------------------------------------------------------|----|
| 1.   | General information.....                                | 4  |
| 2.   | Device information.....                                 | 4  |
| 2.1. | Accessory information .....                             | 4  |
| 2.2. | Frequency/channel operations .....                      | 5  |
| 2.3. | Duty Cycle Factor .....                                 | 5  |
| 3.   | Antenna requirement.....                                | 6  |
| 4.   | Summary of tests .....                                  | 7  |
| 5.   | Measurement uncertainty.....                            | 8  |
| 6.   | Measurement results explanation example.....            | 9  |
| 7.   | Test results .....                                      | 10 |
| 7.1. | Maximum conducted output power.....                     | 10 |
| 7.2. | Maximum Power Spectral Density.....                     | 14 |
| 7.3. | 26 dB Bandwidth.....                                    | 18 |
| 7.4. | 6 dB Bandwidth.....                                     | 22 |
| 7.5. | Straddle channel.....                                   | 25 |
| 7.6. | DFS (Dynamic Frequency Selection) .....                 | 29 |
| 7.7. | Spurious Emission, Band Edge and Restricted bands ..... | 38 |
| 7.8. | AC Conducted emission .....                             | 71 |
| 8.   | Measurement equipment.....                              | 73 |

## 1. General information

Client : Samsung Electronics Co., Ltd.  
 Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea  
 Manufacturer : Samsung Electronics Co., Ltd.  
 Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea  
 Factory 1 : AG TECH CO.,LTD  
 Address 1 : Lot G3, Que Vo Industrial Park(Expanded Area), Nam son Ward, Bac Ninh Province, Vietnam  
 Factory 2 : ALMUS VINA  
 Address 2 : Lot CN07A, Phu Ha Industrial Park, Ha Thach Commune, Phu Tho Town, Phu Tho Province, Vietnam  
 Laboratory : Eurofins KCTL Co.,Ltd.  
 Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
 Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
 VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
 CAB Identifier: KR0040  
 ISED Number: 8035A  
 KOLAS No.: KT231

## 2. Device information

Equipment under test : Smart Wearable  
 Model : SM-R866U  
 Modulation technique : WIFI(802.11a/n) : OFDM  
 Number of channels : UNII 1 : 4 ch (20 MHz)  
 UNII 2A : 4 ch (20 MHz)  
 UNII 2C : 12 ch (20 MHz)  
 UNII 3 : 5 ch (20 MHz)  
 Power source : DC 3.88 V  
 Antenna specification : LDS Antenna  
 Antenna gain : UNII 1 : -5.4 dBi  
 UNII 2A : -6.5 dBi  
 UNII 2C : -8.9 dBi  
 UNII 3 : -8.4 dBi  
 Frequency range : UNII-1 : 5 180 MHz ~ 5 240 MHz (802.11a/n\_HT20)  
 UNII-2A : 5 260 MHz ~ 5 320 MHz (802.11a/n\_HT20)  
 UNII-2C : 5 500 MHz ~ 5 720 MHz (802.11a/n\_HT20)  
 UNII-3 : 5 745 MHz ~ 5 825 MHz (802.11a/n\_HT20)  
 Software version : R866U.001  
 Hardware version : REV1.0  
 Test device serial No. : Conducted : R3AX400M34N  
 Radiated : R3AX400M3JZ, R3AX400LZ6V  
 Operation temperature : -30 °C ~ 50 °C

### 2.1. Accessory information

| Equipment        | Manufacturer | Model    | Serial No. | Power source | FCC ID     |
|------------------|--------------|----------|------------|--------------|------------|
| Wireless charger | SAMSUNG      | EP-OR825 | -          | 5.0 V, 1.0 A | A3LEPOR825 |

## 2.2. Frequency/channel operations

This device contains the following capabilities:  
WLAN (11a/n)

| UNII 1 |                 | UNII 2A |                 | UNII 2C |                 | UNII 3 |                 |
|--------|-----------------|---------|-----------------|---------|-----------------|--------|-----------------|
| Ch.    | Frequency (MHz) | Ch.     | Frequency (MHz) | Ch.     | Frequency (MHz) | Ch.    | Frequency (MHz) |
| 36     | 5 180           | 52      | 5 260           | 100     | 5 500           | 149    | 5 745           |
| 40     | 5 200           | 56      | 5 280           | 120     | 5 600           | 157    | 5 785           |
| 48     | 5 240           | 64      | 5 320           | 140     | 5 700           | 165    | 5 825           |
|        |                 |         |                 | 144     | 5 720           |        |                 |

Table 2.2-1. 802.11a/n HT20 mode

### Notes:


1. The device supports DFS bands between UNII 2A and UNII 2C and operates as a slave device controlled by master

## 2.3. Duty Cycle Factor

| Test mode    | Period (ms) | T <sub>on</sub> time (ms) | Duty cycle |       | Duty cycle factor (dB) |
|--------------|-------------|---------------------------|------------|-------|------------------------|
|              |             |                           | (Linear)   | (%)   |                        |
| 802.11a      | 1.527       | 1.421                     | 0.930 6    | 93.06 | 0.31                   |
| 802.11n_HT20 | 1.438       | 1.331                     | 0.925 6    | 92.56 | 0.34                   |

### Notes:

1. Duty cycle (Linear) = T<sub>on</sub> time / Period
2. DCF(Duty cycle factor) = 10log(1/duty cycle)
3. DCF is not compensated to average result if duty cycle is more than 98%



|                                                                                                                                                                                                         |                                                 |                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Eurofins KCTL Co.,Ltd.</b><br>65, Sinwon-ro, Yeongtong-gu,<br>Suwon-si, Gyeonggi-do, 16677, Korea<br>TEL: 82-70-5008-1021 FAX: 82-505-299-8311<br><a href="http://www.kctl.co.kr">www.kctl.co.kr</a> | Report No.:<br>KR24-SRF0083<br>Page (6) of (73) |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------------------------------------------------------------------------|

### 3. Antenna requirement

#### Requirement of FCC part section 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The transmitter has permanently attached LDS Antenna (Internal antenna) on board.
- The E.U.T Complies with the requirement of §15.203, §15.407.



#### 4. Summary of tests

| FCC Part section(s)                 | Parameter                                                                               | Test Condition | Test results |
|-------------------------------------|-----------------------------------------------------------------------------------------|----------------|--------------|
| 15.407(a)                           | Maximum conducted output power                                                          | Conducted      | Pass         |
| 15.407(a)                           | Maximum power spectral density                                                          |                | Pass         |
| 15.407(a)                           | 26 dB Channel Bandwidth                                                                 |                | Pass         |
| 15.407(e)                           | 6 dB Channel Bandwidth                                                                  |                | Pass         |
| 15.207(a)                           | AC Conducted Emissions                                                                  |                | Pass         |
| 15.407(h)                           | DFS<br>-Channel closing transmission time<br>-Channel move time<br>-Non occupied period |                | Pass         |
| 15.407(b)<br>15.205(a)<br>15.209(a) | Spurious emission                                                                       | Radiated       | Pass         |
|                                     | Band-edge, restricted band                                                              |                | Pass         |

##### Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z and all of the radiated tests have been performed with the accessories as below. It was determined that below orientation was worst case orientation for each band.
- All configurations have been performed (Stand-alone, Stand-alone with TA and Strap).

| Band    | Strap         | With charger | Without charger |        |        |
|---------|---------------|--------------|-----------------|--------|--------|
|         |               | X-axis       | X-axis          | Y-axis | Z-axis |
| UNII-1  | With strap    | O            | -               | -      | -      |
|         | Without strap | -            | -               | -      | -      |
| UNII-2A | With strap    | O            | -               | -      | -      |
|         | Without strap | -            | -               | -      | -      |
| UNII-2C | With strap    | O            | -               | -      | -      |
|         | Without strap | -            | -               | -      | -      |
| UNII-3  | With strap    | O            | -               | -      | -      |
|         | Without strap | -            | -               | -      | -      |

- The device does not support radar detection feature.
- The test procedure(s) in this report were performed in accordance as following.
  - ANSI C63.10-2013
  - KDB 789033 D02 v02r01
  - KDB 905462 D02 UNII DFS compliance procedure new rules.
  - KDB 905462 D03 UNII client without radar detection new rules.
- Based on the baseline scan, the worst-case data rates were:
  - 802.11a mode: 6Mbps, 802.11n HT20 mode: MCS0

## 5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

| Parameter                    | Expanded uncertainty ( $\pm$ ) |        |
|------------------------------|--------------------------------|--------|
| Conducted RF power           | 0.9 dB                         |        |
| Conducted spurious emissions | 1.9 dB                         |        |
| Radiated spurious emissions  | 9 kHz ~ 30 MHz:                | 2.3 dB |
|                              | 30 MHz ~ 1 000 MHz             | 2.5 dB |
|                              | 1 000 MHz ~ 18 000 MHz         | 4.7 dB |
|                              | Above 18 000 MHz               | 4.8 dB |
| Conducted emissions          | 9 kHz ~ 150 kHz                | 2.8 dB |
|                              | 150 kHz ~ 30 MHz               | 2.8 dB |

## 6. Measurement results explanation example

The offset level is set in the spectrum analyzer to compensate the RF cable loss factor between EUT conducted output port and spectrum analyzer.

With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

| Frequency (MHz) | Factor(dB) | Frequency (MHz) | Factor(dB) |
|-----------------|------------|-----------------|------------|
| 30              | 9.74       | 9 000           | 12.81      |
| 50              | 10.14      | 10 000          | 12.69      |
| 100             | 10.19      | 11 000          | 13.21      |
| 200             | 10.23      | 12 000          | 12.34      |
| 300             | 10.40      | 13 000          | 13.31      |
| 400             | 10.41      | 14 000          | 13.71      |
| 500             | 10.47      | 15 000          | 12.91      |
| 600             | 10.43      | 16 000          | 14.63      |
| 700             | 10.50      | 17 000          | 12.93      |
| 800             | 10.49      | 18 000          | 13.78      |
| 900             | 10.65      | 19 000          | 14.55      |
| 1 000           | 10.68      | 20 000          | 14.46      |
| 2 000           | 11.12      | 21 000          | 14.59      |
| 3 000           | 11.44      | 22 000          | 14.57      |
| 4 000           | 11.69      | 23 000          | 15.06      |
| 5 000           | 12.03      | 24 000          | 14.77      |
| 6 000           | 12.31      | 25 000          | 14.68      |
| 7 000           | 12.11      | 26 000          | 15.25      |
| 8 000           | 12.36      | 26 500          | 15.09      |


### Notes:

Offset(dB) = RF cable loss(dB) + Attenuator(dB)

## 7. Test results

### 7.1. Maximum conducted output power

#### Test setup



#### Limit

According to §15.407(a),

| Band    | EUT category |                                   | Conducted output power limit            |
|---------|--------------|-----------------------------------|-----------------------------------------|
| UNII-1  |              | Outdoor access point              | 1 W (30 dBm)                            |
|         |              | Indoor access point               |                                         |
|         |              | Fixed point-to-point access point |                                         |
|         | √            | Client device                     | 250 mW (23.98 dBm)                      |
| UNII-2A | √            |                                   | 250 mW or 11 dBm + 10logB <sup>1)</sup> |
| UNII-2C | √            |                                   | 250 mW or 11 dBm + 10logB <sup>1)</sup> |
| UNII-3  | √            |                                   | 1 W (30 dBm)                            |

#### Note:

1) Limit B is the 26 dB emission bandwidth.

#### Test procedure

ANSI C63.10-2013-Section 12.3.2.4 or 12.3.3.1  
 KDB 789033 D02 v02r01 - Section E.2.d)

### **Test settings**

**Used test method is Section E.2.d)**

◆ **KDB 789033 D02 v02r01**

### **Section E.2.d)**

#### **Method SA-2 (trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction):**

- (i) Measure the duty cycle,  $x$ , of the transmitter output signal as described in II.B..
- (ii) Set span to encompass the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (iii) Set RBW = 1 MHz
- (iv) Set RBW  $\geq$  3 MHz
- (v) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This ensures that bin-to-bin spacing is  $\leq \text{RBW} / 2$ , so that narrowband signals are not lost between frequency bins.)
- (vi) Sweep time = auto.
- (vii) Detector = power averaging (rms), if available. Otherwise use sample detector mode.
- (viii) Do not use sweep triggering. Allow the sweep to “free run.”
- (ix) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.
- (x) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (xi) Add  $10 \log (1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add  $10 \log (1/0,25) = 6 \text{ dB}$  if the duty cycle is 25%.

## Test results

### Conducted Output Power


| Test mode       | Band    | Frequency (MHz) | Measured output power |          |              | Limit (dBm) |
|-----------------|---------|-----------------|-----------------------|----------|--------------|-------------|
|                 |         |                 | Reading (dBm)         | DCF (dB) | Result (dBm) |             |
| 802.11a         | UNII 1  | 5 180           | 13.70                 | 0.31     | 14.01        | 23.98       |
|                 |         | 5 200           | 13.24                 |          | 13.55        |             |
|                 |         | 5 240           | 13.41                 |          | 13.72        |             |
|                 | UNII 2A | 5 260           | 13.56                 |          | 13.87        | 23.98       |
|                 |         | 5 280           | 13.82                 |          | 14.13        |             |
|                 |         | 5 320           | 14.28                 |          | 14.59        |             |
|                 | UNII 2C | 5 500           | 13.76                 |          | 14.07        | 23.98       |
|                 |         | 5 600           | 13.23                 |          | 13.54        |             |
|                 |         | 5 700           | 13.55                 |          | 13.86        |             |
|                 | UNII 3  | 5 745           | 13.75                 |          | 14.06        | 30.00       |
|                 |         | 5 785           | 13.44                 |          | 13.75        |             |
|                 |         | 5 825           | 13.10                 |          | 13.41        |             |
| 802.11n<br>HT20 | UNII 1  | 5 180           | 13.47                 | 0.34     | 13.81        | 23.98       |
|                 |         | 5 200           | 13.10                 |          | 13.44        |             |
|                 |         | 5 240           | 13.40                 |          | 13.74        |             |
|                 | UNII 2A | 5 260           | 13.49                 |          | 13.83        | 23.98       |
|                 |         | 5 280           | 13.74                 |          | 14.08        |             |
|                 |         | 5 320           | 14.00                 |          | 14.34        |             |
|                 | UNII 2C | 5 500           | 13.53                 |          | 13.87        | 23.98       |
|                 |         | 5 600           | 13.16                 |          | 13.50        |             |
|                 |         | 5 700           | 13.75                 |          | 14.09        |             |
|                 | UNII 3  | 5 745           | 13.67                 |          | 14.01        | 30.00       |
|                 |         | 5 785           | 13.37                 |          | 13.71        |             |
|                 |         | 5 825           | 13.05                 |          | 13.39        |             |

#### Note:


1. Result (dBm) = Reading (dBm) + D.C.F (dB)

In order to simplify the report, attached plots were the worst case per bandwidth


**UNII 1 / 802.11a / Low ch.**




**UNII 2A / 802.11a / High ch.**



**UNII 2C / 802.11n HT20 / High ch.**




**UNII 3 / 802.11a / Low ch.**



## 7.2. Maximum Power Spectral Density

### Test setup



### Limit

According to §15.407(a),

| Band    | EUT category |                                   | Limit           |
|---------|--------------|-----------------------------------|-----------------|
| UNII-1  |              | Outdoor access point              | 17 dBm/MHz      |
|         |              | Indoor access point               |                 |
|         |              | Fixed point-to-point access point |                 |
|         | √            | Client device                     | 11 dBm /MHz     |
| UNII-2A |              | √                                 | 11 dBm /MHz     |
| UNII-2C |              | √                                 | 11 dBm /MHz     |
| UNII-3  |              | √                                 | 30 dBm /500 kHz |

### Notes:

If transmitting antennas of directional gain greater than 6 dBi are used, both the peak transmit power And the peak power spectral density shall be reduced by the amount in dB that the directional gain if the antenna exceed 6 dBi

### Test procedure

ANSI C63.10-2013 Section 12.3.2.2  
 KDB 789033 D02 v02r01 - Section F

### Test settings

#### Section F

The rules requires “maximum power spectral density” measurements where the intent is to measure the maximum value of the time average of the power spectral density measured during a period of continuous transmission. Refer to III.A for additional guidance for devices that use channel aggregation.

- Create an average power spectrum for the EUT operating mode being tested by following the instructions in II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, “Compute power...” (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- Search function on the instrument to find the peak of the spectrum and record its value.
- Adjustments to the peak value of the spectrum, if applicable:
  - If Method SA-2 or SA-2 Alternative was used, add  $10 \log (1/x)$ , where  $x$  is the duty cycle, to the peak of the spectrum.
  - If Method SA-3 Alternative was used and the linear mode was used in II.E.2.g) (viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- The result is the Maximum PSD over 1MHz reference bandwidth
- For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the preceding procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in Section 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules

specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth(i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:

- a) Set  $RBW \geq 1/T$ , where T is defined in II.B.I.a).
- b) Set  $VBW \geq 3 \text{ RBW}$ .
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add  $10 \log (500 \text{ kHz} / \text{RBW})$  to the measured result, whereas RBW (<500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add  $10 \log (1 \text{ MHz} / \text{RBW})$  to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

**Note:**

1. As a practical matter, it is recommended to use reduced RBW of 100 kHz for the II.F.5.c) and II.F.5.d), since RBW=100 kHz is available on nearly all spectrum analyzers.
2. Method SA-2 is used.

## Test results

### Power spectral density

| Test mode    | Band    | Frequency (MHz) | Measured PSD (dBm/MHz) | DCF (dB) | Maximum PSD (dB m/MHz) | Limit (dBm/MHz) |
|--------------|---------|-----------------|------------------------|----------|------------------------|-----------------|
| 802.11a      | UNII 1  | 5 180           | 3.29                   | 0.31     | 3.60                   | 11.00           |
|              |         | 5 200           | 2.68                   |          | 2.99                   |                 |
|              |         | 5 240           | 3.49                   |          | 3.80                   |                 |
|              | UNII 2A | 5 260           | 3.48                   |          | 3.79                   | 11.00           |
|              |         | 5 280           | 3.85                   |          | 4.16                   |                 |
|              |         | 5 320           | 3.81                   |          | 4.12                   |                 |
|              | UNII 2C | 5 500           | 3.27                   |          | 3.58                   | 11.00           |
|              |         | 5 600           | 3.18                   |          | 3.49                   |                 |
|              |         | 5 700           | 3.50                   |          | 3.81                   |                 |
| 802.11n HT20 | UNII 1  | 5 180           | 2.92                   | 0.34     | 3.26                   | 11.00           |
|              |         | 5 200           | 2.53                   |          | 2.87                   |                 |
|              |         | 5 240           | 2.67                   |          | 3.01                   |                 |
|              | UNII 2A | 5 260           | 2.62                   |          | 2.96                   | 11.00           |
|              |         | 5 280           | 2.82                   |          | 3.16                   |                 |
|              |         | 5 320           | 3.67                   |          | 4.01                   |                 |
|              | UNII 2C | 5 500           | 3.00                   |          | 3.34                   | 11.00           |
|              |         | 5 600           | 2.26                   |          | 2.60                   |                 |
|              |         | 5 700           | 2.69                   |          | 3.03                   |                 |


| Test mode    | Band   | Frequency (MHz) | Measured PSD (dBm /500 kHz) | DCF (dB) | Maximum PSD (dB m /500 kHz) | Limit (dBm /500 kHz) |
|--------------|--------|-----------------|-----------------------------|----------|-----------------------------|----------------------|
| 802.11a      | UNII 1 | 5 745           | 0.71                        | 0.31     | 1.02                        | 30.00                |
|              |        | 5 785           | 0.34                        |          | 0.65                        |                      |
|              |        | 5 825           | 0.52                        |          | 0.83                        |                      |
| 802.11n HT20 | UNII 1 | 5 745           | -0.40                       | 0.34     | -0.06                       | 30.00                |
|              |        | 5 785           | -0.18                       |          | 0.16                        |                      |
|              |        | 5 825           | -0.74                       |          | -0.40                       |                      |

#### Notes:


- Maximum PSD(dB m/500 kHz) = Reading (dB m/500 kHz) + D.C.F(dB)

In order to simplify the report, attached plots were the worst case per bandwidth


**UNII 1 / 802.11a / High ch.**




**UNII 2A / 802.11a / Mid ch.**



**UNII 2C / 802.11a / High ch.**




**UNII 3 / 802.11a / Low ch.**



### 7.3. 26 dB Bandwidth

#### Test setup



#### Limit

N/A

#### Test procedure

ANSI C63.10-2013 Section 12.4

KDB 789033 D02 v02r01 - Section C.1 (26dB bandwidth)

#### Test settings

##### 1. 26 dB Bandwidth


- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

### Test results


| Test mode       | Band    | Frequency(MHz) | 26 dB bandwidth (MHz) |
|-----------------|---------|----------------|-----------------------|
| 802.11a         | UNII 1  | 5 180          | 22.18                 |
|                 |         | 5 200          | 22.18                 |
|                 |         | 5 240          | 22.28                 |
|                 | UNII 2A | 5 260          | 22.18                 |
|                 |         | 5 280          | 22.23                 |
|                 |         | 5 320          | 22.23                 |
|                 | UNII 2C | 5 500          | 22.13                 |
|                 |         | 5 600          | 22.18                 |
|                 |         | 5 700          | 22.18                 |
| 802.11n<br>HT20 | UNII 1  | 5 180          | 22.43                 |
|                 |         | 5 200          | 22.48                 |
|                 |         | 5 240          | 22.48                 |
|                 | UNII 2A | 5 260          | 22.33                 |
|                 |         | 5 280          | 22.43                 |
|                 |         | 5 320          | 22.63                 |
|                 | UNII 2C | 5 500          | 22.43                 |
|                 |         | 5 600          | 22.48                 |
|                 |         | 5 700          | 22.58                 |

In order to simplify the report, only n mode test plots are attached


**UNII 1 / 802.11n HT20 / Low ch.**




**UNII 2A / 802.11n HT20 / Low ch.**




**UNII 1 / 802.11n HT20 / Mid ch.**




**UNII 2A / 802.11n HT20 / Mid ch.**




**UNII 1 / 802.11n HT20 / High ch.**




**UNII 2A / 802.11n HT20 / High ch.**




**UNII 2C / 802.11n HT20 / Low ch.**



**UNII 2C / 802.11n HT20 / Mid ch.**



**UNII 2C / 802.11n HT20 / High ch.**



Blank