

TEST REPORT

FCC LTE B4 Test for SM-S731B/DS
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2507-FC059

DATE OF ISSUE
July 15, 2025

Tested by
Jae Ryang Do



Technical Manager
Jong Seok Lee



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2507-FC059

DATE OF ISSUE

July 15, 2025

Additional Model

SM-S731B

Applicant

SAMSUNG Electronics Co., Ltd.

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

Mobile Phone

Model Name

SM-S731B/DS

Date of Test

June 05, 2025 ~ July 11, 2025

FCC ID

A3LSMS731B

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

Test Standard Used

FCC Rule Part: § 27

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 15, 2025	Initial Release

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER	6
2. INTRODUCTION	8
2.1. DESCRIPTION OF EUT	8
2.2. MEASURING INSTRUMENT CALIBRATION	8
2.3. TEST FACILITY	8
3. DESCRIPTION OF TESTS	9
3.1 TEST PROCEDURE	9
3.2 RADIATED POWER	10
3.3 RADIATED SPURIOUS EMISSIONS	11
3.4 PEAK- TO- AVERAGE RATIO	12
3.5 OCCUPIED BANDWIDTH	14
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	15
3.7 BAND EDGE	16
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	18
3.9 WORST CASE(RADIATED TEST)	19
3.10 WORST CASE(CONDUCTED TEST)	20
4. LIST OF TEST EQUIPMENT	21
5. MEASUREMENT UNCERTAINTY	22
6. SUMMARY OF TEST RESULTS	23
7. SAMPLE CALCULATION	24
8. TEST DATA(Main 1 ANT)	26
8.1 EQUIVALENT ISOTROPIC RADIATED POWER	26
8.2 RADIATED SPURIOUS EMISSIONS	29
8.3 PEAK-TO-AVERAGE RATIO	30
8.4 OCCUPIED BANDWIDTH	31
8.5 CONDUCTED SPURIOUS EMISSIONS	32
8.6 BAND EDGE	32
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	33
9. TEST DATA(Sub 2 ANT)	51
9.1 EQUIVALENT ISOTROPIC RADIATED POWER	51
9.2 RADIATED SPURIOUS EMISSIONS	54
9.3 PEAK-TO-AVERAGE RATIO	55
9.4 OCCUPIED BANDWIDTH	56
9.5 CONDUCTED SPURIOUS EMISSIONS	57
9.6 BAND EDGE	57
9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	58
10. TEST PLOTS(Main 1 ANT)	76
11. TEST PLOTS(Sub 2 ANT)	197
12. ANNEX A_ TEST SETUP PHOTO	318

MEASUREMENT REPORT

1. GENERAL INFORMATION

Model(s):	SM-S731B/DS
Additional Model(s)	SM-S731B
Tx Frequency:	1710.7 MHz – 1754.3 MHz (LTE – Band 4 (1.4 MHz)) 1711.5 MHz – 1753.5 MHz (LTE – Band 4 (3 MHz)) 1712.5 MHz – 1752.5 MHz (LTE – Band 4 (5 MHz)) 1715.0 MHz – 1750.0 MHz (LTE – Band 4 (10 MHz)) 1717.5 MHz – 1747.5 MHz (LTE – Band 4 (15 MHz)) 1720.0 MHz – 1745.0 MHz (LTE – Band 4 (20 MHz))
Serial number:	Radiated : R3CY40QLLEZ Conducted : R3CY40QLBND
Antenna Information	Please refer to the Antenna Specification document.

1.1. MAXIMUM OUTPUT POWER

Main 1 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band4 (1.4)	1710.7 – 1754.3	1M10G7D	QPSK	0.251	24.00
		1M10W7D	16QAM	0.218	23.38
		1M10W7D	64QAM	0.167	22.22
		1M09W7D	256QAM	0.081	19.10
LTE – Band4 (3)	1711.5 – 1753.5	2M72G7D	QPSK	0.252	24.02
		2M71W7D	16QAM	0.219	23.41
		2M71W7D	64QAM	0.169	22.27
		2M72W7D	256QAM	0.081	19.11
LTE – Band4 (5)	1712.5 – 1752.5	4M53G7D	QPSK	0.252	24.01
		4M52W7D	16QAM	0.216	23.35
		4M53W7D	64QAM	0.167	22.22
		4M56W7D	256QAM	0.082	19.13
LTE – Band4 (10)	1715.0 – 1750.0	9M01G7D	QPSK	0.252	24.01
		9M01W7D	16QAM	0.211	23.25
		9M01W7D	64QAM	0.163	22.11
		9M02W7D	256QAM	0.081	19.07
LTE – Band4 (15)	1717.5 – 1747.5	13M5G7D	QPSK	0.252	24.02
		13M5W7D	16QAM	0.211	23.24
		13M5W7D	64QAM	0.163	22.13
		13M5W7D	256QAM	0.081	19.10
LTE – Band4 (20)	1720.0 – 1745.0	18M0G7D	QPSK	0.253	24.03
		18M0W7D	16QAM	0.211	23.25
		17M9W7D	64QAM	0.163	22.11
		17M9W7D	256QAM	0.080	19.05

Sub 2 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band4 (1.4)	1710.7 – 1754.3	1M10G7D	QPSK	0.103	20.14
		1M10W7D	16QAM	0.087	19.41
		1M10W7D	64QAM	0.070	18.42
		1M10W7D	256QAM	0.035	15.49
LTE – Band4 (3)	1711.5 – 1753.5	2M72G7D	QPSK	0.103	20.14
		2M71W7D	16QAM	0.088	19.44
		2M71W7D	64QAM	0.070	18.44
		2M72W7D	256QAM	0.036	15.54
LTE – Band4 (5)	1712.5 – 1752.5	4M53G7D	QPSK	0.107	20.28
		4M51W7D	16QAM	0.091	19.57
		4M54W7D	64QAM	0.072	18.56
		4M55W7D	256QAM	0.035	15.49
LTE – Band4 (10)	1715.0 – 1750.0	9M03G7D	QPSK	0.109	20.36
		9M02W7D	16QAM	0.087	19.42
		9M01W7D	64QAM	0.069	18.39
		9M02W7D	256QAM	0.037	15.71
LTE – Band4 (15)	1717.5 – 1747.5	13M5G7D	QPSK	0.110	20.43
		13M5W7D	16QAM	0.090	19.56
		13M5W7D	64QAM	0.070	18.44
		13M5W7D	256QAM	0.035	15.46
LTE – Band4 (20)	1720.0 – 1745.0	18M0G7D	QPSK	0.107	20.30
		18M0W7D	16QAM	0.086	19.32
		17M9W7D	64QAM	0.069	18.40
		18M0W7D	256QAM	0.036	15.54

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [2G3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea.

Detailed description of test facility was submitted to the Commission and accepted dated March 11, 2024 (Registration Number: KR0032).

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq$ 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points > 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser
if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit)
and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets,
and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is
driven by a signal generator and the previously recorded signal was duplicated.
The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_g_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.


The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5 \%$ of the expected OBW
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep $\geq 2 \times \text{Span} / \text{RBW}$

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep Time > (Number of Points) $\times$ (Symbol Period)
9. The trace was allowed to stabilize

Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels (low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where $\text{Margin} < 1$ dB the emission level is either corrected by $10 \log(1 \text{ MHz} / \text{RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter.
Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
Worst case : Stand alone
- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.
Therefore, only the worst case(stand-alone) results were reported.
- In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported. (Worst case : 20 MHz(Main 1 ANT), 15 MHz(Sub 2 ANT))
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- SM-S731B/DS & additional models were tested and the worst case results are reported.
(Worst case : SM-S731B/DS)

[Main 1 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		Z
Radiated Spurious and Harmonic Emissions	QPSK	See Section 8.2		Z

[Sub 2 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 9.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 9.2		Z

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.
 - SM-S731B/DS & additional models were tested and the worst case results are reported.
- (Worst case : SM-S731B/DS)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Band Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		1.4, 3, 5, 10, 15, 20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	1.4, 3, 5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	Switch box(1.2 G HPF+LNA)	HCT CO., LTD.	F1L1	11/11/2025	Annual
RF Switching System	Switch box(3.3 G HPF+LNA)	HCT CO., LTD.	F1L2	11/11/2025	Annual
RF Switching System	Switch box(LNA)	HCT CO., LTD.	F1L4	11/11/2025	Annual
RF Switching System	Switch box(6 G HPF+LNA)	HCT CO., LTD.	F1L7	11/11/2025	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/19/2026	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/10/2026	Annual
DC Power Supply	E3632A	Agilent	MY40010147	08/06/2025	Annual
Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Dipole Antenna	UHAP	Schwarzbeck	01288	08/07/2026	Biennial
Chamber	SU-642	ESPEC	93008124	02/11/2026	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	147	08/17/2025	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1298	09/11/2025	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/23/2027	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/14/2026	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/10/2026	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	REOHDE & SCHWARZ	100931	08/06/2025	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/05/2025	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/07/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	08/28/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	08/19/2026	Biennial
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262094331	11/13/2025	Annual
Radio Communication Test Station	MT8000A	Anritsu Corp.	6272613402	08/28/2025	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/26/2025	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/14/2026	Annual
Signal Analyzer(2 Hz ~ 50.0 GHz)	N9040B	KEYSIGHT	US55230216	12/09/2025	Annual
Automation Software	FCC 2G/3G/4G Conducted	HCT CO., LTD	-	-	-
Automation Software	FCC NR Conducted	HCT CO., LTD	-	-	-
Automation Software	FCC LTE Radiated	HCT CO., LTD	-	-	-
Automation Software	FCC NR Radiated	HCT CO., LTD	-	-	-

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
Occupied Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)

Parameter	Expanded Uncertainty ($\pm$ dB)
Block Edge	0.70 (Confidence level about 95 %, $k=2$)
Conducted Spurious Emissions	1.18 (Confidence level about 95 %, $k=2$)
Peak- to- Average Ratio	0.68 (Confidence level about 95 %, $k=2$)
Radiated Power	4.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.68 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.75 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.82 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

-. The decision rule applies 'simple acceptance'

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(h)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	<u>Note1</u>
Peak- to- Average Ratio	§ 27.50(d)(5)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. Refer to the SAR report.

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 27.50(d)(4)	< 1 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(h)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA(Main 1 ANT)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1710.7	LTE B4 1.4 MHz	QPSK	-17.60	15.77	10.04	2.06	V	< 1.00	0.237	23.75	1	0
		16-QAM	-18.28	15.09	10.04	2.06	V		0.203	23.07		
		64-QAM	-19.42	13.95	10.04	2.06	V		0.156	21.93		
		256-QAM	-22.53	10.84	10.04	2.06	V		0.076	18.82		
1732.5		QPSK	-17.80	15.65	10.14	2.08	V		0.235	23.71	1	0
		16-QAM	-18.49	14.96	10.14	2.08	V		0.200	23.02		
		64-QAM	-19.62	13.83	10.14	2.08	V		0.155	21.89		
		256-QAM	-22.77	10.68	10.14	2.08	V		0.075	18.74		
1754.3		QPSK	-17.66	15.87	10.21	2.08	V		0.251	24.00	1	5
		16-QAM	-18.28	15.25	10.21	2.08	V		0.218	23.38		
		64-QAM	-19.44	14.09	10.21	2.08	V		0.167	22.22		
		256-QAM	-22.56	10.97	10.21	2.08	V		0.081	19.10		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1711.5	LTE B4 3 MHz	QPSK	-17.44	15.93	10.04	2.06	V	< 1.00	0.246	23.91	1	0
		16-QAM	-18.26	15.11	10.04	2.06	V		0.204	23.09		
		64-QAM	-19.40	13.97	10.04	2.06	V		0.157	21.95		
		256-QAM	-22.47	10.90	10.04	2.06	V		0.077	18.88		
1732.5		QPSK	-17.77	15.68	10.14	2.08	V		0.237	23.74	1	0
		16-QAM	-18.47	14.98	10.14	2.08	V		0.201	23.04		
		64-QAM	-19.58	13.87	10.14	2.08	V		0.156	21.93		
		256-QAM	-22.70	10.75	10.14	2.08	V		0.076	18.81		
1752.5		QPSK	-17.64	15.89	10.21	2.08	V		0.252	24.02	1	14
		16-QAM	-18.25	15.28	10.21	2.08	V		0.219	23.41		
		64-QAM	-19.39	14.14	10.21	2.08	V		0.169	22.27		
		256-QAM	-22.55	10.98	10.21	2.08	V		0.081	19.11		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1712.5	LTE B4 5 MHz	QPSK	-17.44	15.95	10.06	2.06	V	< 1.00	0.248	23.95	1	0
		16-QAM	-18.26	15.13	10.06	2.06	V		0.206	23.13		
		64-QAM	-19.40	13.99	10.06	2.06	V		0.158	21.99		
		256-QAM	-22.49	10.90	10.06	2.06	V		0.078	18.90		
1732.5		QPSK	-17.75	15.70	10.14	2.08	V		0.238	23.76	1	0
		16-QAM	-18.45	15.00	10.14	2.08	V		0.202	23.06		
		64-QAM	-19.59	13.86	10.14	2.08	V		0.156	21.92		
		256-QAM	-22.67	10.78	10.14	2.08	V		0.077	18.84		
1752.5		QPSK	-17.65	15.88	10.21	2.08	V		0.252	24.01	1	24
		16-QAM	-18.31	15.22	10.21	2.08	V		0.216	23.35		
		64-QAM	-19.44	14.09	10.21	2.08	V		0.167	22.22		
		256-QAM	-22.53	11.00	10.21	2.08	V		0.082	19.13		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1715.0	LTE B4 10 MHz	QPSK	-17.52	15.87	10.06	2.06	V	< 1.00	0.244	23.87	1	0
		16-QAM	-18.36	15.03	10.06	2.06	V		0.201	23.03		
		64-QAM	-19.49	13.90	10.06	2.06	V		0.155	21.90		
		256-QAM	-22.44	10.95	10.06	2.06	V		0.079	18.95		
1732.5		QPSK	-17.72	15.73	10.14	2.08	V		0.239	23.79	1	0
		16-QAM	-18.54	14.91	10.14	2.08	V		0.198	22.97		
		64-QAM	-19.67	13.78	10.14	2.08	V		0.153	21.84		
		256-QAM	-22.66	10.79	10.14	2.08	V		0.077	18.85		
1750.0		QPSK	-17.60	15.88	10.20	2.07	V		0.252	24.01	1	49
		16-QAM	-18.36	15.12	10.20	2.07	V		0.211	23.25		
		64-QAM	-19.50	13.98	10.20	2.07	V		0.163	22.11		
		256-QAM	-22.54	10.94	10.20	2.07	V		0.081	19.07		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1717.5	LTE B4 15 MHz	QPSK	-17.48	15.94	10.08	2.06	V	< 1.00	0.249	23.96	1	0
		16-QAM	-18.26	15.16	10.08	2.06	V		0.208	23.18		
		64-QAM	-19.39	14.03	10.08	2.06	V		0.160	22.05		
		256-QAM	-22.44	10.98	10.08	2.06	V		0.079	19.00		
1732.5		QPSK	-17.65	15.80	10.14	2.08	V		0.243	23.86	1	0
		16-QAM	-18.47	14.98	10.14	2.08	V		0.201	23.04		
		64-QAM	-19.59	13.86	10.14	2.08	V		0.156	21.92		
		256-QAM	-22.68	10.77	10.14	2.08	V		0.076	18.83		
1747.5		QPSK	-17.59	15.89	10.20	2.07	V		0.252	24.02	1	74
		16-QAM	-18.37	15.11	10.20	2.07	V		0.211	23.24		
		64-QAM	-19.48	14.00	10.20	2.07	V		0.163	22.13		
		256-QAM	-22.51	10.97	10.20	2.07	V		0.081	19.10		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1720.0	LTE B4 20 MHz	QPSK	-17.43	15.99	10.08	2.06	V	< 1.00	0.252	24.01	1	0
		16-QAM	-18.29	15.13	10.08	2.06	V		0.207	23.15		
		64-QAM	-19.40	14.02	10.08	2.06	V		0.160	22.04		
		256-QAM	-22.39	11.03	10.08	2.06	V		0.080	19.05		
1732.5		QPSK	-17.63	15.82	10.14	2.08	V		0.244	23.88	1	0
		16-QAM	-18.46	14.99	10.14	2.08	V		0.202	23.05		
		64-QAM	-19.56	13.89	10.14	2.08	V		0.157	21.95		
		256-QAM	-22.59	10.86	10.14	2.08	V		0.078	18.92		
1745.0		QPSK	-17.54	15.92	10.18	2.07	V		0.253	24.03	1	99
		16-QAM	-18.32	15.14	10.18	2.07	V		0.211	23.25		
		64-QAM	-19.46	14.00	10.18	2.07	V		0.163	22.11		
		256-QAM	-22.52	10.94	10.18	2.07	V		0.080	19.05		

8.2 RADIATED SPURIOUS EMISSIONS

■ MODE: LTE B4
 ■ MODULATION SIGNAL: 20 MHz QPSK
 ■ DISTANCE: 3 meters
 ■ LIMIT: -13 dBm

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
20050 (1720.0)	3 440.00	-43.08	12.40	-61.78	3.04	V	-52.42	1	0
	5 160.00	-42.63	12.44	-55.27	3.76	H	-46.59		
	6 880.00	-44.27	11.82	-51.28	4.44	V	-43.90		
20175 (1732.5)	3 465.00	-42.94	12.34	-61.39	3.02	V	-52.07	1	0
	5 197.50	-43.26	12.63	-56.10	3.78	V	-47.25		
	6 930.00	-42.73	11.65	-49.55	4.40	H	-42.30		
20300 (1745.0)	3 490.00	-43.15	12.34	-61.40	3.04	V	-52.10	1	99
	5 235.00	-44.07	12.84	-56.65	3.78	V	-47.59		
	6 980.00	-44.21	11.40	-50.53	4.48	H	-43.61		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)	Limit (dB)
4	1.4 MHz	1732.5	QPSK	6	0	5.19	13.00
			16-QAM			5.90	
			64-QAM			6.14	
			256-QAM			5.99	
	3 MHz		QPSK	15		5.27	
			16-QAM			5.93	
			64-QAM			6.17	
			256-QAM			6.11	
	5 MHz		QPSK	25		5.29	
			16-QAM			6.02	
			64-QAM			6.20	
			256-QAM			6.14	
	10 MHz		QPSK	50		5.40	
			16-QAM			6.05	
			64-QAM			6.30	
			256-QAM			6.19	
	15 MHz		QPSK	75		5.39	
			16-QAM			6.10	
			64-QAM			6.33	
			256-QAM			6.15	
	20 MHz		QPSK	100		5.35	
			16-QAM			6.07	
			64-QAM			6.32	
			256-QAM			6.16	

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 77 ~ 100.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
4	1.4 MHz	1732.5	QPSK	6	0	1.0988
			16-QAM			1.0955
			64-QAM			1.0945
			256-QAM			1.0916
	3 MHz		QPSK	15		2.7176
			16-QAM			2.7094
			64-QAM			2.7076
			256-QAM			2.7169
	5 MHz		QPSK	25		4.5328
			16-QAM			4.5149
			64-QAM			4.5273
			256-QAM			4.5607
	10 MHz		QPSK	50		9.0096
			16-QAM			9.0098
			64-QAM			9.0125
			256-QAM			9.0228
	15 MHz		QPSK	75		13.467
			16-QAM			13.496
			64-QAM			13.519
			256-QAM			13.484
	20 MHz		QPSK	100		17.991
			16-QAM			17.951
			64-QAM			17.929
			256-QAM			17.928

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 101 ~ 124.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
4	1.4	1710.7	2.5524	27.976	-66.389	-38.413	-13.00
		1732.5	3.6890	27.976	-66.151	-38.175	
		1754.3	6.5304	28.591	-66.446	-37.855	
	3	1711.5	3.6591	27.976	-65.140	-37.164	
		1732.5	3.7089	27.976	-66.049	-38.073	
		1753.5	3.5095	27.976	-65.676	-37.700	
	5	1712.5	3.6591	27.976	-66.347	-38.371	
		1732.5	3.6990	27.976	-66.189	-38.213	
		1752.5	3.5095	27.976	-65.553	-37.577	
	10	1715.0	3.3400	27.976	-66.391	-38.415	
		1732.5	2.6621	27.976	-66.550	-38.574	
		1750.0	6.2613	28.591	-65.634	-37.043	
	15	1717.5	3.2703	27.976	-65.880	-37.904	
		1732.5	3.6990	27.976	-65.942	-37.966	
		1747.5	3.3999	27.976	-66.071	-38.095	
	20	1720.0	2.7219	27.976	-66.093	-38.117	
		1732.5	3.4497	27.976	-65.178	-37.202	
		1745.0	3.5095	27.976	-66.326	-38.350	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 125 ~ 160.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 161 ~ 196.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE 4</u>
OPERATING FREQUENCY:	<u>1710,700,000 Hz</u>
CHANNEL:	<u>19957 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1710 700 010	0.0	0.000 000	0.000
100 %		-30	1710 700 016	6.0	0.000 000	0.004
100 %		-20	1710 700 019	8.4	0.000 000	0.005
100 %		-10	1710 700 016	5.8	0.000 000	0.003
100 %		0	1710 700 018	8.0	0.000 000	0.005
100 %		+10	1710 700 018	7.9	0.000 000	0.005
100 %		+30	1710 700 015	5.1	0.000 000	0.003
100 %		+40	1710 700 015	4.4	0.000 000	0.003
100 %		+50	1710 700 015	4.6	0.000 000	0.003
Batt. Endpoint	3.300	+20	1710 700 017	7.0	0.000 000	0.004




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1711,500,000 Hz
 ■ CHANNEL: 19965 (3 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1711 500 009	0.0	0.000 000	0.000
100 %		-30	1711 500 019	9.9	0.000 001	0.006
100 %		-20	1711 500 003	-5.8	0.000 000	-0.003
100 %		-10	1711 500 017	8.1	0.000 000	0.005
100 %		0	1711 500 018	8.3	0.000 000	0.005
100 %		+10	1711 500 017	8.2	0.000 000	0.005
100 %		+30	1711 500 016	6.9	0.000 000	0.004
100 %		+40	1711 500 016	7.0	0.000 000	0.004
100 %		+50	1711 500 016	6.7	0.000 000	0.004
Batt. Endpoint	3.300	+20	1711 500 018	8.4	0.000 000	0.005




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1712,500,000 Hz
- ▣ CHANNEL: 19975 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1712 500 006	0.0	0.000 000	0.000
100 %		-30	1712 500 013	6.8	0.000 000	0.004
100 %		-20	1712 500 012	5.1	0.000 000	0.003
100 %		-10	1712 500 012	5.3	0.000 000	0.003
100 %		0	1712 500 012	5.4	0.000 000	0.003
100 %		+10	1712 500 012	5.9	0.000 000	0.003
100 %		+30	1712 500 015	9.0	0.000 001	0.005
100 %		+40	1712 500 013	7.0	0.000 000	0.004
100 %		+50	1712 500 013	7.0	0.000 000	0.004
Batt. Endpoint	3.300	+20	1712 500 014	7.4	0.000 000	0.004




MODE:	<u>LTE 4</u>
OPERATING FREQUENCY:	<u>1715,000,000 Hz</u>
CHANNEL:	<u>20000 (10 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1715 000 008	0.0	0.000 000	0.000
100 %		-30	1715 000 016	7.6	0.000 000	0.004
100 %		-20	1715 000 017	8.9	0.000 001	0.005
100 %		-10	1715 000 013	5.0	0.000 000	0.003
100 %		0	1715 000 016	7.3	0.000 000	0.004
100 %		+10	1715 000 017	8.2	0.000 000	0.005
100 %		+30	1715 000 014	5.5	0.000 000	0.003
100 %		+40	1715 000 016	8.0	0.000 000	0.005
100 %		+50	1715 000 014	6.1	0.000 000	0.004
Batt. Endpoint	3.300	+20	1715 000 016	8.0	0.000 000	0.005




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1717,500,000 Hz
- ▣ CHANNEL: 20025 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1717 500 005	0.0	0.000 000	0.000
100 %		-30	1717 500 011	6.1	0.000 000	0.004
100 %		-20	1717 500 013	8.2	0.000 000	0.005
100 %		-10	1717 500 011	5.6	0.000 000	0.003
100 %		0	1717 500 012	6.8	0.000 000	0.004
100 %		+10	1717 500 012	6.7	0.000 000	0.004
100 %		+30	1717 500 011	5.6	0.000 000	0.003
100 %		+40	1717 500 012	7.1	0.000 000	0.004
100 %		+50	1717 500 010	4.8	0.000 000	0.003
Batt. Endpoint	3.300	+20	1717 500 011	6.1	0.000 000	0.004




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1720,000,000 Hz
 ■ CHANNEL: 20050 (20 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1720 000 007	0.0	0.000 000	0.000
100 %		-30	1720 000 015	7.8	0.000 000	0.005
100 %		-20	1720 000 015	7.8	0.000 000	0.005
100 %		-10	1720 000 016	8.4	0.000 000	0.005
100 %		0	1720 000 014	6.8	0.000 000	0.004
100 %		+10	1720 000 014	6.4	0.000 000	0.004
100 %		+30	1720 000 015	7.1	0.000 000	0.004
100 %		+40	1720 000 014	6.6	0.000 000	0.004
100 %		+50	1720 000 015	7.2	0.000 000	0.004
Batt. Endpoint	3.300	+20	1720 000 014	6.6	0.000 000	0.004




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (1.4 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 499 987	0.0	0.000 000	0.000
100 %		-30	1732 499 994	6.6	0.000 000	0.004
100 %		-20	1732 499 994	6.5	0.000 000	0.004
100 %		-10	1732 499 992	4.8	0.000 000	0.003
100 %		0	1732 499 993	5.7	0.000 000	0.003
100 %		+10	1732 499 994	6.9	0.000 000	0.004
100 %		+30	1732 499 993	5.9	0.000 000	0.003
100 %		+40	1732 499 993	5.6	0.000 000	0.003
100 %		+50	1732 499 981	-5.7	0.000 000	-0.003
Batt. Endpoint	3.300	+20	1732 499 980	-7.4	0.000 000	-0.004




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (3 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 500 006	0.0	0.000 000	0.000
100 %		-30	1732 500 014	7.4	0.000 000	0.004
100 %		-20	1732 500 014	7.3	0.000 000	0.004
100 %		-10	1732 500 014	8.1	0.000 000	0.005
100 %		0	1732 500 027	20.8	0.000 001	0.012
100 %		+10	1732 500 014	7.3	0.000 000	0.004
100 %		+30	1732 500 013	7.0	0.000 000	0.004
100 %		+40	1732 500 012	6.2	0.000 000	0.004
100 %		+50	1732 500 015	8.8	0.000 001	0.005
Batt. Endpoint	3.300	+20	1732 500 013	7.2	0.000 000	0.004




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (5 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 500 005	0.0	0.000 000	0.000
100 %		-30	1732 500 001	-4.4	0.000 000	-0.003
100 %		-20	1732 500 011	5.4	0.000 000	0.003
100 %		-10	1732 500 000	-5.5	0.000 000	-0.003
100 %		0	1732 500 011	5.6	0.000 000	0.003
100 %		+10	1732 500 012	6.7	0.000 000	0.004
100 %		+30	1732 500 011	5.4	0.000 000	0.003
100 %		+40	1732 500 001	-4.6	0.000 000	-0.003
100 %		+50	1732 500 012	6.7	0.000 000	0.004
Batt. Endpoint	3.300	+20	1732 500 012	7.1	0.000 000	0.004




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 500 007	0.0	0.000 000	0.000
100 %		-30	1732 500 013	6.3	0.000 000	0.004
100 %		-20	1732 500 014	7.2	0.000 000	0.004
100 %		-10	1732 500 015	7.8	0.000 000	0.005
100 %		0	1732 500 015	8.3	0.000 000	0.005
100 %		+10	1732 500 014	6.6	0.000 000	0.004
100 %		+30	1732 500 014	7.0	0.000 000	0.004
100 %		+40	1732 500 020	12.7	0.000 001	0.007
100 %		+50	1732 500 014	7.5	0.000 000	0.004
Batt. Endpoint	3.300	+20	1732 500 014	6.9	0.000 000	0.004




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1732,500,000 Hz
- ▣ CHANNEL: 20175 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 499 995	0.0	0.000 000	0.000
100 %		-30	1732 499 999	4.0	0.000 000	0.002
100 %		-20	1732 500 001	5.6	0.000 000	0.003
100 %		-10	1732 500 000	5.2	0.000 000	0.003
100 %		0	1732 500 000	4.7	0.000 000	0.003
100 %		+10	1732 500 001	5.8	0.000 000	0.003
100 %		+30	1732 500 001	5.7	0.000 000	0.003
100 %		+40	1732 500 001	5.8	0.000 000	0.003
100 %		+50	1732 500 001	6.0	0.000 000	0.003
Batt. Endpoint	3.300	+20	1732 500 000	4.6	0.000 000	0.003




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (20 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 500 005	0.0	0.000 000	0.000
100 %		-30	1732 500 010	5.4	0.000 000	0.003
100 %		-20	1732 500 012	7.1	0.000 000	0.004
100 %		-10	1732 500 012	7.0	0.000 000	0.004
100 %		0	1732 500 011	5.6	0.000 000	0.003
100 %		+10	1732 500 011	5.7	0.000 000	0.003
100 %		+30	1732 500 012	7.0	0.000 000	0.004
100 %		+40	1732 500 012	7.3	0.000 000	0.004
100 %		+50	1732 500 011	6.3	0.000 000	0.004
Batt. Endpoint	3.300	+20	1732 500 010	5.2	0.000 000	0.003




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1754,300,000 Hz
 ■ CHANNEL: 20393 (1.4 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1754 300 005	0.0	0.000 000	0.000
100 %		-30	1754 300 011	6.0	0.000 000	0.003
100 %		-20	1754 300 012	6.6	0.000 000	0.004
100 %		-10	1754 299 999	-5.8	0.000 000	-0.003
100 %		0	1754 300 012	7.0	0.000 000	0.004
100 %		+10	1754 300 011	5.6	0.000 000	0.003
100 %		+30	1754 300 010	4.8	0.000 000	0.003
100 %		+40	1754 300 013	7.6	0.000 000	0.004
100 %		+50	1754 300 011	6.0	0.000 000	0.003
Batt. Endpoint	3.300	+20	1754 300 011	6.1	0.000 000	0.003




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1753,500,000 Hz
 ■ CHANNEL: 20385 (3 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1753 500 012	0.0	0.000 000	0.000
100 %		-30	1753 500 022	10.2	0.000 001	0.006
100 %		-20	1753 500 023	11.0	0.000 001	0.006
100 %		-10	1753 500 020	7.6	0.000 000	0.004
100 %		0	1753 499 996	-16.3	-0.000 001	-0.009
100 %		+10	1753 500 022	10.2	0.000 001	0.006
100 %		+30	1753 500 022	10.4	0.000 001	0.006
100 %		+40	1753 500 023	11.3	0.000 001	0.006
100 %		+50	1753 500 019	7.0	0.000 000	0.004
Batt. Endpoint	3.300	+20	1753 500 031	18.5	0.000 001	0.011




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1752,500,000 Hz
 ■ CHANNEL: 20375 (5 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1752 500 009	0.0	0.000 000	0.000
100 %		-30	1752 500 018	9.0	0.000 001	0.005
100 %		-20	1752 500 015	6.5	0.000 000	0.004
100 %		-10	1752 500 017	8.2	0.000 000	0.005
100 %		0	1752 500 015	6.7	0.000 000	0.004
100 %		+10	1752 500 015	6.1	0.000 000	0.003
100 %		+30	1752 500 017	8.6	0.000 000	0.005
100 %		+40	1752 500 017	8.3	0.000 000	0.005
100 %		+50	1752 500 017	8.4	0.000 000	0.005
Batt. Endpoint	3.300	+20	1752 500 017	8.9	0.000 001	0.005




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1750,000,000 Hz
- ▣ CHANNEL: 20350 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1750 000 005	0.0	0.000 000	0.000
100 %		-30	1750 000 011	5.8	0.000 000	0.003
100 %		-20	1750 000 012	6.8	0.000 000	0.004
100 %		-10	1749 999 993	-11.6	-0.000 001	-0.007
100 %		0	1750 000 011	6.2	0.000 000	0.004
100 %		+10	1750 000 010	5.4	0.000 000	0.003
100 %		+30	1750 000 010	5.4	0.000 000	0.003
100 %		+40	1750 000 009	3.8	0.000 000	0.002
100 %		+50	1750 000 001	-4.2	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1750 000 011	5.8	0.000 000	0.003




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1747,500,000 Hz
- ▣ CHANNEL: 20325 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1747 500 007	0.0	0.000 000	0.000
100 %		-30	1747 500 015	7.8	0.000 000	0.004
100 %		-20	1747 500 013	6.1	0.000 000	0.003
100 %		-10	1747 500 015	8.1	0.000 000	0.005
100 %		0	1747 500 014	6.6	0.000 000	0.004
100 %		+10	1747 500 013	6.0	0.000 000	0.003
100 %		+30	1747 500 013	5.3	0.000 000	0.003
100 %		+40	1747 500 015	7.4	0.000 000	0.004
100 %		+50	1747 500 014	6.4	0.000 000	0.004
Batt. Endpoint	3.300	+20	1747 500 014	6.6	0.000 000	0.004



- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1745,000,000 Hz
- ▣ CHANNEL: 20300 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1745 000 006	0.0	0.000 000	0.000
100 %		-30	1745 000 000	-5.5	0.000 000	-0.003
100 %		-20	1745 000 012	6.9	0.000 000	0.004
100 %		-10	1745 000 013	7.0	0.000 000	0.004
100 %		0	1745 000 012	6.0	0.000 000	0.003
100 %		+10	1745 000 012	6.6	0.000 000	0.004
100 %		+30	1745 000 014	8.7	0.000 000	0.005
100 %		+40	1745 000 011	5.7	0.000 000	0.003
100 %		+50	1745 000 013	7.2	0.000 000	0.004
Batt. Endpoint	3.300	+20	1745 000 012	6.6	0.000 000	0.004



9. TEST DATA(Sub 2 ANT)

9.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1710.7	LTE B4 1.4 MHz	QPSK	-21.30	12.07	10.04	2.06	H	< 1.00	0.101	20.05	1	0
		16-QAM	-22.18	11.19	10.04	2.06	H		0.083	19.17		
		64-QAM	-22.93	10.44	10.04	2.06	H		0.070	18.42		
		256-QAM	-26.22	7.15	10.04	2.06	H		0.033	15.13		
1732.5		QPSK	-21.37	12.08	10.14	2.08	H		0.103	20.14	1	0
		16-QAM	-22.10	11.35	10.14	2.08	H		0.087	19.41		
		64-QAM	-23.19	10.26	10.14	2.08	H		0.068	18.32		
		256-QAM	-26.02	7.43	10.14	2.08	H		0.035	15.49		
1754.3		QPSK	-21.61	11.92	10.21	2.08	H		0.101	20.05	1	0
		16-QAM	-22.45	11.08	10.21	2.08	H		0.083	19.21		
		64-QAM	-23.52	10.01	10.21	2.08	H		0.065	18.14		
		256-QAM	-26.44	7.09	10.21	2.08	H		0.033	15.22		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1711.5	LTE B4 3 MHz	QPSK	-21.26	12.11	10.04	2.06	H	< 1.00	0.102	20.09	1	0
		16-QAM	-22.16	11.21	10.04	2.06	H		0.083	19.19		
		64-QAM	-22.91	10.46	10.04	2.06	H		0.070	18.44		
		256-QAM	-26.16	7.21	10.04	2.06	H		0.033	15.19		
1732.5		QPSK	-21.37	12.08	10.14	2.08	H		0.103	20.14	1	0
		16-QAM	-22.07	11.38	10.14	2.08	H		0.088	19.44		
		64-QAM	-23.15	10.30	10.14	2.08	H		0.069	18.36		
		256-QAM	-25.97	7.48	10.14	2.08	H		0.036	15.54		
1752.5		QPSK	-21.75	11.78	10.21	2.08	H		0.098	19.91	1	0
		16-QAM	-22.48	11.05	10.21	2.08	H		0.083	19.18		
		64-QAM	-23.57	9.96	10.21	2.08	H		0.064	18.09		
		256-QAM	-26.48	7.05	10.21	2.08	H		0.033	15.18		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1712.5	LTE B4 5 MHz	QPSK	-21.11	12.28	10.06	2.06	H	< 1.00	0.107	20.28	1	0
		16-QAM	-22.15	11.24	10.06	2.06	H		0.084	19.24		
		64-QAM	-22.90	10.49	10.06	2.06	H		0.071	18.49		
		256-QAM	-26.16	7.23	10.06	2.06	H		0.033	15.23		
1732.5		QPSK	-21.30	12.15	10.14	2.08	H		0.105	20.21	1	0
		16-QAM	-21.94	11.51	10.14	2.08	H		0.091	19.57		
		64-QAM	-22.95	10.50	10.14	2.08	H		0.072	18.56		
		256-QAM	-26.02	7.43	10.14	2.08	H		0.035	15.49		
1752.5		QPSK	-21.57	11.96	10.21	2.08	H		0.102	20.09	1	0
		16-QAM	-22.41	11.12	10.21	2.08	H		0.084	19.25		
		64-QAM	-23.49	10.04	10.21	2.08	H		0.066	18.17		
		256-QAM	-26.47	7.06	10.21	2.08	H		0.033	15.19		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1715.0	LTE B4 10 MHz	QPSK	-21.16	12.23	10.06	2.06	H	< 1.00	0.105	20.23	1	0
		16-QAM	-22.22	11.17	10.06	2.06	H		0.083	19.17		
		64-QAM	-23.00	10.39	10.06	2.06	H		0.069	18.39		
		256-QAM	-26.05	7.34	10.06	2.06	H		0.034	15.34		
1732.5		QPSK	-21.15	12.30	10.14	2.08	H		0.109	20.36	1	0
		16-QAM	-22.09	11.36	10.14	2.08	H		0.087	19.42		
		64-QAM	-23.19	10.26	10.14	2.08	H		0.068	18.32		
		256-QAM	-25.80	7.65	10.14	2.08	H		0.037	15.71		
1750.0		QPSK	-21.58	11.90	10.20	2.07	H		0.101	20.03	1	0
		16-QAM	-22.50	10.98	10.20	2.07	H		0.081	19.11		
		64-QAM	-23.60	9.88	10.20	2.07	H		0.063	18.01		
		256-QAM	-26.40	7.08	10.20	2.07	H		0.033	15.21		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1717.5	LTE B4 15 MHz	QPSK	-21.13	12.29	10.08	2.06	H	< 1.00	0.107	20.31	1	0
		16-QAM	-22.11	11.31	10.08	2.06	H		0.086	19.33		
		64-QAM	-23.00	10.42	10.08	2.06	H		0.070	18.44		
		256-QAM	-25.99	7.43	10.08	2.06	H		0.035	15.45		
1732.5		QPSK	-21.08	12.37	10.14	2.08	H		0.110	20.43	1	0
		16-QAM	-21.95	11.50	10.14	2.08	H		0.090	19.56		
		64-QAM	-23.12	10.33	10.14	2.08	H		0.069	18.39		
		256-QAM	-26.05	7.40	10.14	2.08	H		0.035	15.46		
1747.5		QPSK	-21.39	12.09	10.20	2.07	H		0.105	20.22	1	0
		16-QAM	-22.26	11.22	10.20	2.07	H		0.086	19.35		
		64-QAM	-23.44	10.04	10.20	2.07	H		0.066	18.17		
		256-QAM	-26.29	7.19	10.20	2.07	H		0.034	15.32		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1720.0	LTE B4 20 MHz	QPSK	-21.14	12.28	10.08	2.06	H	< 1.00	0.107	20.30	1	0
		16-QAM	-22.14	11.28	10.08	2.06	H		0.085	19.30		
		64-QAM	-23.40	10.02	10.08	2.06	H		0.064	18.04		
		256-QAM	-25.96	7.46	10.08	2.06	H		0.035	15.48		
1732.5		QPSK	-21.38	12.07	10.14	2.08	H		0.103	20.13	1	0
		16-QAM	-22.25	11.20	10.14	2.08	H		0.084	19.26		
		64-QAM	-23.11	10.34	10.14	2.08	H		0.069	18.40		
		256-QAM	-26.02	7.43	10.14	2.08	H		0.035	15.49		
1745.0		QPSK	-21.34	12.12	10.18	2.07	H		0.105	20.23	1	0
		16-QAM	-22.25	11.21	10.18	2.07	H		0.086	19.32		
		64-QAM	-23.32	10.14	10.18	2.07	H		0.067	18.25		
		256-QAM	-26.03	7.43	10.18	2.07	H		0.036	15.54		

9.2 RADIATED SPURIOUS EMISSIONS

MODE: LTE B4
 MODULATION SIGNAL: 15 MHz QPSK
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
20025 (1717.5)	3 435.00	-39.85	12.41	-58.61	3.03	H	-49.23	1	0
	5 152.50	-43.48	12.41	-56.14	3.76	V	-47.49		
	6 870.00	-44.81	11.85	-51.62	4.43	V	-44.20		
20175 (1732.5)	3 465.00	-41.90	12.34	-60.35	3.02	H	-51.03	1	0
	5 197.50	-43.37	12.63	-56.21	3.78	H	-47.36		
	6 930.00	-43.11	11.65	-49.93	4.40	V	-42.68		
20325 (1747.5)	3 495.00	-42.44	12.34	-60.56	3.04	H	-51.26	1	0
	5 242.50	-43.93	12.90	-56.21	3.80	H	-47.11		
	6 990.00	-44.19	11.36	-49.89	4.48	V	-43.01		

9.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)	Limit (dB)
4	1.4 MHz	1732.5	QPSK	6	0	5.45	13.00
			16-QAM			6.17	
			64-QAM			6.12	
			256-QAM			6.29	
	3 MHz		QPSK	15		5.59	
			16-QAM			6.23	
			64-QAM			6.15	
			256-QAM			6.43	
	5 MHz		QPSK	25		5.58	
			16-QAM			6.25	
			64-QAM			6.21	
			256-QAM			6.46	
	10 MHz		QPSK	50		5.74	
			16-QAM			6.34	
			64-QAM			6.27	
			256-QAM			6.49	
	15 MHz		QPSK	75		5.63	
			16-QAM			6.30	
			64-QAM			6.49	
			256-QAM			6.46	
	20 MHz		QPSK	100		5.56	
			16-QAM			6.27	
			64-QAM			6.50	
			256-QAM			6.49	

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 198 ~ 221.

9.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
4	1.4 MHz	1732.5	QPSK	6	0	1.0971
			16-QAM			1.0963
			64-QAM			1.0976
			256-QAM			1.0966
	3 MHz		QPSK	15		2.7154
			16-QAM			2.7072
			64-QAM			2.7110
			256-QAM			2.7156
	5 MHz		QPSK	25		4.5306
			16-QAM			4.5116
			64-QAM			4.5424
			256-QAM			4.5476
	10 MHz		QPSK	50		9.0246
			16-QAM			9.0224
			64-QAM			9.0074
			256-QAM			9.0227
	15 MHz		QPSK	75		13.476
			16-QAM			13.503
			64-QAM			13.501
			256-QAM			13.493
	20 MHz		QPSK	100		17.955
			16-QAM			17.952
			64-QAM			17.925
			256-QAM			17.970

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 222 ~ 245.

9.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
4	1.4	1710.7	3.1506	27.976	-65.982	-38.006	-13.00
		1732.5	3.6890	27.976	-66.170	-38.194	
		1754.3	3.6790	27.976	-65.517	-37.541	
	3	1711.5	6.9492	28.591	-64.883	-36.292	
		1732.5	6.6002	28.591	-65.783	-37.192	
		1753.5	6.7598	28.591	-66.143	-37.552	
	5	1712.5	3.4198	27.976	-64.568	-36.592	
		1732.5	3.0509	27.976	-65.417	-37.441	
		1752.5	3.6691	27.976	-65.094	-37.118	
	10	1715.0	5.6531	28.591	-66.624	-38.033	
		1732.5	3.1406	27.976	-66.129	-38.153	
		1750.0	3.6691	27.976	-66.188	-38.212	
	15	1717.5	6.2513	28.591	-65.936	-37.345	
		1732.5	3.4497	27.976	-64.913	-36.937	
		1747.5	3.5095	27.976	-66.203	-38.227	
	20	1720.0	6.5803	28.591	-65.905	-37.314	
		1732.5	3.4497	27.976	-64.431	-36.455	
		1745.0	2.5724	27.976	-66.371	-38.395	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 246 ~ 281.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


9.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 282 ~ 317.

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE 4</u>
OPERATING FREQUENCY:	<u>1710,700,000 Hz</u>
CHANNEL:	<u>19957 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1710 700 009	0.0	0.000 000	0.000
100 %		-30	1710 700 007	-1.7	0.000 000	-0.001
100 %		-20	1710 700 016	7.6	0.000 000	0.004
100 %		-10	1710 700 005	-3.4	0.000 000	-0.002
100 %		0	1710 700 000	-8.6	-0.000 001	-0.005
100 %		+10	1710 700 011	2.3	0.000 000	0.001
100 %		+30	1710 700 011	2.6	0.000 000	0.002
100 %		+40	1710 700 006	-2.9	0.000 000	-0.002
100 %		+50	1710 700 010	1.7	0.000 000	0.001
Batt. Endpoint	3.300	+20	1710 700 012	2.9	0.000 000	0.002




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1711,500,000 Hz
 ■ CHANNEL: 19965 (3 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1711 499 993	0.0	0.000 000	0.000
100 %		-30	1711 499 991	-1.9	0.000 000	-0.001
100 %		-20	1711 499 982	-11.3	-0.000 001	-0.007
100 %		-10	1711 499 997	4.1	0.000 000	0.002
100 %		0	1711 499 996	2.6	0.000 000	0.002
100 %		+10	1711 499 996	3.0	0.000 000	0.002
100 %		+30	1711 499 996	2.5	0.000 000	0.001
100 %		+40	1711 499 997	3.3	0.000 000	0.002
100 %		+50	1711 499 991	-2.5	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1711 499 995	2.0	0.000 000	0.001




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1712,500,000 Hz
 ■ CHANNEL: 19975 (5 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1712 500 003	0.0	0.000 000	0.000
100 %		-30	1712 500 006	2.1	0.000 000	0.001
100 %		-20	1712 500 007	3.3	0.000 000	0.002
100 %		-10	1712 500 007	3.3	0.000 000	0.002
100 %		0	1712 500 006	2.8	0.000 000	0.002
100 %		+10	1712 500 006	2.8	0.000 000	0.002
100 %		+30	1712 500 008	4.7	0.000 000	0.003
100 %		+40	1712 500 006	2.7	0.000 000	0.002
100 %		+50	1712 500 007	3.2	0.000 000	0.002
Batt. Endpoint	3.300	+20	1712 500 006	2.9	0.000 000	0.002




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1715,000,000 Hz
 ■ CHANNEL: 20000 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1714 999 998	0.0	0.000 000	0.000
100 %		-30	1715 000 002	4.8	0.000 000	0.003
100 %		-20	1715 000 001	3.4	0.000 000	0.002
100 %		-10	1715 000 002	4.7	0.000 000	0.003
100 %		0	1715 000 003	5.2	0.000 000	0.003
100 %		+10	1715 000 003	5.5	0.000 000	0.003
100 %		+30	1715 000 002	4.7	0.000 000	0.003
100 %		+40	1714 999 996	-1.6	0.000 000	-0.001
100 %		+50	1714 999 995	-2.9	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1715 000 000	2.6	0.000 000	0.002




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1717,500,000 Hz
 ■ CHANNEL: 20025 (15 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1717 499 998	0.0	0.000 000	0.000
100 %		-30	1717 499 996	-2.5	0.000 000	-0.001
100 %		-20	1717 500 001	2.7	0.000 000	0.002
100 %		-10	1717 500 003	4.6	0.000 000	0.003
100 %		0	1717 500 002	4.0	0.000 000	0.002
100 %		+10	1717 500 002	3.3	0.000 000	0.002
100 %		+30	1717 500 002	3.6	0.000 000	0.002
100 %		+40	1717 500 002	3.3	0.000 000	0.002
100 %		+50	1717 500 001	2.4	0.000 000	0.001
Batt. Endpoint	3.300	+20	1717 499 995	-2.8	0.000 000	-0.002




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1720,000,000 Hz
- ▣ CHANNEL: 20050 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1719 999 998	0.0	0.000 000	0.000
100 %		-30	1720 000 002	4.1	0.000 000	0.002
100 %		-20	1719 999 996	-2.4	0.000 000	-0.001
100 %		-10	1720 000 002	4.0	0.000 000	0.002
100 %		0	1719 999 996	-2.0	0.000 000	-0.001
100 %		+10	1720 000 000	1.5	0.000 000	0.001
100 %		+30	1719 999 996	-2.1	0.000 000	-0.001
100 %		+40	1720 000 001	2.4	0.000 000	0.001
100 %		+50	1720 000 004	6.0	0.000 000	0.003
Batt. Endpoint	3.300	+20	1719 999 997	-1.6	0.000 000	-0.001




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (1.4 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 499 998	0.0	0.000 000	0.000
100 %		-30	1732 499 991	-7.3	0.000 000	-0.004
100 %		-20	1732 500 000	2.2	0.000 000	0.001
100 %		-10	1732 499 996	-2.3	0.000 000	-0.001
100 %		0	1732 500 000	2.2	0.000 000	0.001
100 %		+10	1732 499 996	-2.0	0.000 000	-0.001
100 %		+30	1732 499 996	-2.3	0.000 000	-0.001
100 %		+40	1732 499 996	-2.3	0.000 000	-0.001
100 %		+50	1732 500 001	3.2	0.000 000	0.002
Batt. Endpoint	3.300	+20	1732 500 000	1.7	0.000 000	0.001




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1732,500,000 Hz
- ▣ CHANNEL: 20175 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 500 002	0.0	0.000 000	0.000
100 %		-30	1732 500 006	3.2	0.000 000	0.002
100 %		-20	1732 500 005	3.0	0.000 000	0.002
100 %		-10	1732 500 006	3.2	0.000 000	0.002
100 %		0	1732 500 005	2.8	0.000 000	0.002
100 %		+10	1732 500 007	4.5	0.000 000	0.003
100 %		+30	1732 500 000	-2.8	0.000 000	-0.002
100 %		+40	1732 500 000	-2.9	0.000 000	-0.002
100 %		+50	1732 500 001	-1.9	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1732 499 986	-16.3	-0.000 001	-0.009




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (5 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 500 003	0.0	0.000 000	0.000
100 %		-30	1732 500 005	2.6	0.000 000	0.002
100 %		-20	1732 500 001	-1.9	0.000 000	-0.001
100 %		-10	1732 500 001	-2.0	0.000 000	-0.001
100 %		0	1732 500 005	2.0	0.000 000	0.001
100 %		+10	1732 500 005	2.6	0.000 000	0.002
100 %		+30	1732 500 005	1.8	0.000 000	0.001
100 %		+40	1732 500 006	3.2	0.000 000	0.002
100 %		+50	1732 500 006	2.8	0.000 000	0.002
Batt. Endpoint	3.300	+20	1732 500 006	2.9	0.000 000	0.002




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 499 983	0.0	0.000 000	0.000
100 %		-30	1732 499 981	-1.9	0.000 000	-0.001
100 %		-20	1732 499 982	-1.5	0.000 000	-0.001
100 %		-10	1732 499 987	3.5	0.000 000	0.002
100 %		0	1732 499 985	2.0	0.000 000	0.001
100 %		+10	1732 499 987	3.8	0.000 000	0.002
100 %		+30	1732 499 985	1.4	0.000 000	0.001
100 %		+40	1732 499 985	1.4	0.000 000	0.001
100 %		+50	1732 499 981	-2.5	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1732 499 982	-1.7	0.000 000	-0.001




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (15 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 500 001	0.0	0.000 000	0.000
100 %		-30	1732 500 000	-1.0	0.000 000	-0.001
100 %		-20	1732 500 004	3.3	0.000 000	0.002
100 %		-10	1732 500 002	1.3	0.000 000	0.001
100 %		0	1732 500 003	1.7	0.000 000	0.001
100 %		+10	1732 500 002	1.4	0.000 000	0.001
100 %		+30	1732 499 999	-2.0	0.000 000	-0.001
100 %		+40	1732 500 004	2.8	0.000 000	0.002
100 %		+50	1732 500 000	-1.2	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1732 500 003	2.1	0.000 000	0.001




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1732,500,000 Hz
 ■ CHANNEL: 20175 (20 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1732 500 003	0.0	0.000 000	0.000
100 %		-30	1732 500 005	2.7	0.000 000	0.002
100 %		-20	1732 500 005	2.8	0.000 000	0.002
100 %		-10	1732 500 005	2.4	0.000 000	0.001
100 %		0	1732 500 005	2.4	0.000 000	0.001
100 %		+10	1732 500 004	1.6	0.000 000	0.001
100 %		+30	1732 500 006	3.7	0.000 000	0.002
100 %		+40	1732 500 005	2.2	0.000 000	0.001
100 %		+50	1732 500 005	2.5	0.000 000	0.001
Batt. Endpoint	3.300	+20	1732 500 004	1.5	0.000 000	0.001




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1754,300,000 Hz
 ■ CHANNEL: 20393 (1.4 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1754 300 002	0.0	0.000 000	0.000
100 %		-30	1754 300 005	3.5	0.000 000	0.002
100 %		-20	1754 300 005	3.1	0.000 000	0.002
100 %		-10	1754 300 005	3.0	0.000 000	0.002
100 %		0	1754 300 005	3.1	0.000 000	0.002
100 %		+10	1754 300 004	1.9	0.000 000	0.001
100 %		+30	1754 300 004	1.6	0.000 000	0.001
100 %		+40	1754 300 000	-1.9	0.000 000	-0.001
100 %		+50	1754 300 005	2.9	0.000 000	0.002
Batt. Endpoint	3.300	+20	1754 300 004	2.0	0.000 000	0.001




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1753,500,000 Hz
- ▣ CHANNEL: 20385 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1753 500 007	0.0	0.000 000	0.000
100 %		-30	1753 500 013	6.0	0.000 000	0.003
100 %		-20	1753 500 013	5.7	0.000 000	0.003
100 %		-10	1753 500 013	5.4	0.000 000	0.003
100 %		0	1753 500 015	7.4	0.000 000	0.004
100 %		+10	1753 500 010	3.0	0.000 000	0.002
100 %		+30	1753 500 019	11.6	0.000 001	0.007
100 %		+40	1753 500 014	6.4	0.000 000	0.004
100 %		+50	1753 500 003	-4.6	0.000 000	-0.003
Batt. Endpoint	3.300	+20	1753 500 014	6.6	0.000 000	0.004




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1752,500,000 Hz
 ■ CHANNEL: 20375 (5 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1752 499 997	0.0	0.000 000	0.000
100 %		-30	1752 499 999	1.6	0.000 000	0.001
100 %		-20	1752 500 001	3.9	0.000 000	0.002
100 %		-10	1752 500 001	3.8	0.000 000	0.002
100 %		0	1752 500 000	3.0	0.000 000	0.002
100 %		+10	1752 500 000	3.0	0.000 000	0.002
100 %		+30	1752 500 001	4.3	0.000 000	0.002
100 %		+40	1752 500 001	4.3	0.000 000	0.002
100 %		+50	1752 499 999	2.4	0.000 000	0.001
Batt. Endpoint	3.300	+20	1752 500 000	3.3	0.000 000	0.002




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1750,000,000 Hz
- ▣ CHANNEL: 20350 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1750 000 003	0.0	0.000 000	0.000
100 %		-30	1750 000 006	3.6	0.000 000	0.002
100 %		-20	1750 000 004	1.5	0.000 000	0.001
100 %		-10	1750 000 000	-2.7	0.000 000	-0.002
100 %		0	1750 000 004	1.7	0.000 000	0.001
100 %		+10	1750 000 005	2.1	0.000 000	0.001
100 %		+30	1750 000 004	1.3	0.000 000	0.001
100 %		+40	1750 000 005	1.9	0.000 000	0.001
100 %		+50	1750 000 005	2.0	0.000 000	0.001
Batt. Endpoint	3.300	+20	1750 000 005	2.5	0.000 000	0.001




- ▣ MODE: LTE 4
- ▣ OPERATING FREQUENCY: 1747,500,000 Hz
- ▣ CHANNEL: 20325 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1747 500 003	0.0	0.000 000	0.000
100 %		-30	1747 500 005	2.6	0.000 000	0.001
100 %		-20	1747 500 000	-2.7	0.000 000	-0.002
100 %		-10	1747 500 006	3.2	0.000 000	0.002
100 %		0	1747 500 006	2.8	0.000 000	0.002
100 %		+10	1747 500 005	2.1	0.000 000	0.001
100 %		+30	1747 500 006	3.1	0.000 000	0.002
100 %		+40	1747 500 005	2.4	0.000 000	0.001
100 %		+50	1747 500 005	2.4	0.000 000	0.001
Batt. Endpoint	3.300	+20	1747 500 005	2.0	0.000 000	0.001




■ MODE: LTE 4
 ■ OPERATING FREQUENCY: 1745,000,000 Hz
 ■ CHANNEL: 20300 (20 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1745 000 002	0.0	0.000 000	0.000
100 %		-30	1745 000 003	1.3	0.000 000	0.001
100 %		-20	1745 000 003	1.2	0.000 000	0.001
100 %		-10	1745 000 005	2.6	0.000 000	0.001
100 %		0	1745 000 004	2.1	0.000 000	0.001
100 %		+10	1745 000 001	-1.3	0.000 000	-0.001
100 %		+30	1745 000 004	2.0	0.000 000	0.001
100 %		+40	1745 000 005	2.5	0.000 000	0.001
100 %		+50	1745 000 005	3.0	0.000 000	0.002
Batt. Endpoint	3.300	+20	1745 000 004	1.9	0.000 000	0.001




10. TEST PLOTS(Main 1 ANT)


LTE B4_1.4M_PAR_Mid_QPSK_FullRB




LTE B4_1.4M_PAR_Mid_16QAM_FullRB




LTE B4_1.4M_PAR_Mid_64QAM_FullRB




LTE B4_1.4M_PAR_Mid_256QAM_FullRB




LTE B4_3 M_PAR_Mid_QPSK_FullRB




LTE B4_3 M_PAR_Mid_16QAM_FullRB




LTE B4_3 M_PAR_Mid_64QAM_FullRB




LTE B4_3 M_PAR_Mid_256QAM_FullRB




LTE B4_5 M_PAR_Mid_QPSK_FullRB




LTE B4_5 M_PAR_Mid_16QAM_FullRB




LTE B4_5 M_PAR_Mid_64QAM_FullRB




LTE B4_5 M_PAR_Mid_256QAM_FullRB




LTE B4_10 M_PAR_Mid_QPSK_FullRB




LTE B4_10 M_PAR_Mid_16QAM_FullRB




LTE B4_10 M_PAR_Mid_64QAM_FullRB




LTE B4_10 M_PAR_Mid_256QAM_FullRB




LTE B4_15 M_PAR_Mid_QPSK_FullRB




LTE B4_15 M_PAR_Mid_16QAM_FullRB




LTE B4_15 M_PAR_Mid_64QAM_FullRB




LTE B4_15 M_PAR_Mid_256QAM_FullRB




LTE B4_20 M_PAR_Mid_QPSK_FullRB




LTE B4_20 M_PAR_Mid_16QAM_FullRB




LTE B4_20 M_PAR_Mid_64QAM_FullRB




LTE B4_20 M_PAR_Mid_256QAM_FullRB




LTE B4_1.4M_OBW_Mid_QPSK_FullRB




LTE B4_1.4M_OBW_Mid_16QAM_FullRB




LTE B4_1.4M_OBW_Mid_64QAM_FullRB




LTE B4_1.4M_OBW_Mid_256QAM_FullRB




LTE B4_3 M_OBW_Mid_QPSK_FullRB




LTE B4_3 M_OBW_Mid_16QAM_FullRB




LTE B4_3 M_OBW_Mid_64QAM_FullRB




LTE B4_3 M_OBW_Mid_256QAM_FullRB




LTE B4_5 M_OBW_Mid_QPSK_FullRB




LTE B4_5 M_OBW_Mid_16QAM_FullRB




LTE B4_5 M_OBW_Mid_64QAM_FullRB




LTE B4_5 M_OBW_Mid_256QAM_FullRB



LTE B4_10 M_OBW_Mid_QPSK_FullRB



LTE B4_10 M_OBW_Mid_16QAM_FullRB



Agilent Spectrum Analyzer - Occupied BW

RL 50 Ω AC SENSE:INT ALIGN AUTO 01:39:43 PM Jun 23, 2025

Center Freq 1.732500000 GHz Radio Std: None
#FGain:Low #Atten: 12 dB Avg|Hold: 700/700 Radio Device: BTS

PASS

Ref Offset 27.17 dB
Ref 40.00 dBm

10 dB/div
Log

Center 1.733 GHz
#Res BW 200 kHz #VBW 820 kHz Span 20 MHz Sweep 1 ms

Occupied Bandwidth	Total Power	30.2 dBm
9.0125 MHz		
Transmit Freq Error	24.343 kHz	OBW Power 99.00 %
x dB Bandwidth	10.42 MHz	x dB -26.00 dB

MSG STATUS

Frequency


Center Freq
1.732500000 GHz

CF Step
2.000000 MHz
Man


Auto

Freq Offset
0 Hz


LTE B4_10 M_OBW_Mid_256QAM_FullRB




LTE B4_15 M_OBW_Mid_QPSK_FullRB




LTE B4_15 M_OBW_Mid_16QAM_FullRB




LTE B4_15 M_OBW_Mid_64QAM_FullRB




LTE B4_15 M_OBW_Mid_256QAM_FullRB




LTE B4_20 M_OBW_Mid_QPSK_FullRB




LTE B4_20 M_OBW_Mid_16QAM_FullRB




LTE B4_20 M_OBW_Mid_64QAM_FullRB




LTE B4_20 M_OBW_Mid_256QAM_FullRB




LTE B4_1.4M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B4_1.4M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B4_1.4M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B4_3 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B4_3 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B4_3 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



LTE B4_5 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



LTE B4_5 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



LTE B4_5 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB

