

TEST REPORT

FCC Sub6 Test for SM-S731U
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2507-FC043

DATE OF ISSUE
July 14, 2025

Tested by
Jung Ki Lim

Technical Manager
Jong Seok Lee

HCT CO., LTD.
Bongjae Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2507-FC043

DATE OF ISSUE

July 14, 2025

Additional Model

SM-S731U1

Applicant**SAMSUNG Electronics Co., Ltd.**

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

Mobile Phone

Model Name

SM-S731U

Date of Test

May 13, 2025 ~ July 10, 2025

FCC ID

A3LSMS731U

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

Test Standard Used

FCC Rule Part: § 27, § 2

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 14, 2025	Initial Release

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER	6
2. INTRODUCTION	7
2.1. DESCRIPTION OF EUT	7
2.2. MEASURING INSTRUMENT CALIBRATION	7
2.3. TEST FACILITY	7
3. DESCRIPTION OF TESTS	8
3.1 TEST PROCEDURE	8
3.2 RADIATED POWER.....	9
3.3 RADIATED SPURIOUS EMISSIONS.....	10
3.4 PEAK- TO- AVERAGE RATIO	11
3.5 OCCUPIED BANDWIDTH.....	13
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	14
3.7 BAND EDGE	15
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	17
3.9 WORST CASE(RADIATED TEST)	18
3.10 WORST CASE(CONDUCTED TEST).....	19
4. LIST OF TEST EQUIPMENT.....	20
5. MEASUREMENT UNCERTAINTY.....	21
6. SUMMARY OF TEST RESULTS	22
7. SAMPLE CALCULATION	23
8. TEST DATA(Main 1 ANT).....	25
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	25
8.2 RADIATED SPURIOUS EMISSIONS.....	26
8.3 PEAK-TO-AVERAGE RATIO	28
8.4 OCCUPIED BANDWIDTH.....	29
8.5 CONDUCTED SPURIOUS EMISSIONS	30
8.6 BAND EDGE	31
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	35
9. TEST DATA(Sub 2 ANT)	37
9.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	37
9.2 RADIATED SPURIOUS EMISSIONS.....	38
9.3 PEAK-TO-AVERAGE RATIO	40
9.4 OCCUPIED BANDWIDTH.....	41
9.5 CONDUCTED SPURIOUS EMISSIONS	42
9.6 BAND EDGE	43
9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	47
10. TEST PLOTS(Main 1 ANT).....	49
11. TEST PLOTS(Sub 2 ANT)	190
12. ANNEX A_ TEST SETUP PHOTO	331

MEASUREMENT REPORT**1. GENERAL INFORMATION**

Model(s):	SM-S731U
Additional Model(s)	SM-S731U1
SCS(kHz):	15
Waveform:	CP-OFDM, DFT-S-OFDM
Modulation:	DFT-S-OFDM: PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM CP-OFDM: QPSK, 16QAM, 64QAM, 256QAM
Tx Frequency:	2307.5 MHz – 2312.5 MHz (Sub6 n30 (5 MHz)) 2310.0 MHz (Sub6 n30 (10 MHz))
Serial number:	Radiated : R3CY40DEG0B Conducted : R3CY40XC6MR
Antenna Information	Please refer to the Antenna Specification document.

1.1. MAXIMUM OUTPUT POWER

Main 1 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
Sub6 n30 (5)	2307.5 – 2312.5	4M52G7D	PI/2 BPSK	0.157	21.96
		4M53G7D	QPSK	0.156	21.92
		4M50W7D	16QAM	0.122	20.86
		4M50W7D	64QAM	0.085	19.30
		4M52W7D	256QAM	0.055	17.38
Sub6 n30 (10)	2310.0	9M00G7D	PI/2 BPSK	0.154	21.88
		9M01G7D	QPSK	0.153	21.86
		8M98W7D	16QAM	0.124	20.93
		8M97W7D	64QAM	0.086	19.35
		8M96W7D	256QAM	0.054	17.35

Sub 2 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
Sub6 n30 (5)	2307.5 – 2312.5	4M53G7D	PI/2 BPSK	0.143	21.55
		4M51G7D	QPSK	0.142	21.53
		4M51W7D	16QAM	0.116	20.64
		4M49W7D	64QAM	0.082	19.12
		4M52W7D	256QAM	0.052	17.14
Sub6 n30 (10)	2310.0	8M99G7D	PI/2 BPSK	0.142	21.53
		8M99G7D	QPSK	0.139	21.43
		8M97W7D	16QAM	0.112	20.50
		8M98W7D	64QAM	0.079	18.98
		8M96W7D	256QAM	0.051	17.04

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [2G3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq$ 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $>$ 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin $>$ 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated. The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_g_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6$ dB if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.


The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW $\geq$ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time > Number of points in sweep $\times$ Transmitter period
6. Number of points in sweep $\geq$ 2 x Span / RBW

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep Time > (Number of Points) (Symbol Period)
9. The trace was allowed to stabilize

Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz/ RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter.
Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.
(Worst case: DFT-S-OFDM)
- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode: SA Only
Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
Worst case : Stand alone
- We were performed the RSE test in condition of co-location.
Mode : Stand alone, Simultaneous transmission scenarios
Worst case : Stand alone
- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.
Please refer to the table below.
- SM-S731U & additional models were tested and the worst case results are reported.
(Worst case : SM-S731U)

[Main 1 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Equivalent Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 8.2		X

[Sub 2 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Equivalent Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 9.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 9.2		Z

3.10 WORST CASE(CONDUCTED TEST)

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.
(Worst case: DFT-S-OFDM)
- Modulation : All Modulation of operation were investigated and the worst case configuration results are reported.
(Worst case: PI/2 BPSK)
- All modes of operation were investigated and the worst case configuration results are reported.
Mode: SA Only
- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.
Please refer to the table below.
- SM-S731U & additional models were tested and the worst case results are reported.
(Worst case : SM-S731U)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	5, 10	Mid	Full RB	0
Peak-To-Average Ratio	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	5, 10	Mid	Full RB	0
Band Edge	PI/2 BPSK	5	Low, Mid, High	1	0, 24
		10	Mid	1	0, 49
		5	Low, Mid, High	Full RB	0
		10	Mid	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	PI/2 BPSK	5	Low, Mid, High	1	0
		10	Mid	1	0

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
Precision Dipole Antenna	UHAP	Schwarzbeck	01273	03/10/2026	Biennial
Precision Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Horn Antenna(1~18 GHz)	BBHA 9120D	Schwarzbeck	02289	02/14/2026	Biennial
Horn Antenna(1~18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1299	04/17/2026	Biennial
Horn Antenna(15~40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15~40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/23/2027	Biennial
Loop Antenna(9 kHz~30 MHz)	FMZB1513	Rohde & Schwarz	1513-175	01/06/2027	Biennial
Bilog Antenna	VULB9160	Schwarzbeck	3150	03/05/2027	Biennial
Hybrid Antenna	VULB9160	Schwarzbeck	760	02/17/2027	Biennial
RF Switching System	FBSR-06B (1G HPF + LNA)	T&M SYSTEM	F3L1	05/08/2026	Annual
RF Switching System	FBSR-06B (3G HPF + LNA)	T&M SYSTEM	F3L2	05/08/2026	Annual
RF Switching System	FBSR-06B (6G HPF + LNA)	T&M SYSTEM	F3L3	05/08/2026	Annual
RF Switching System	FBSR-06B (LNA)	T&M SYSTEM	F3L4	05/08/2026	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/19/2026	Annual
DC Power Supply	E3632A	Hewlett Packard	MY40004427	08/22/2025	Annual
Power Splitter(DC~26.5 GHz)	11667B	Hewlett Packard	11275	02/04/2026	Annual
Chamber	SU-642	ESPEC	93008124	02/11/2026	Annual
Signal Analyzer(10 Hz~26.5 GHz)	N9020A	Agilent	MY51110063	03/21/2026	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/10/2026	Annual
Spectrum Analyzer (10 Hz~40 GHz)	FSV40	REOHDE & SCHWARZ	101436	02/04/2026	Annual
Signal & Spectrum Analyzer (2 Hz~67 GHz)	FSW67	REOHDE & SCHWARZ	101736	05/27/2026	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/05/2025	Annual
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262287701	05/14/2026	Annual
Wideband Radio Communication Tester	MT8000A	Anritsu Corp.	6262302511	05/08/2026	Annual
Signal Analyzer(5 Hz~40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/14/2026	Annual
4-Way Divider	ZC4PD-K1844+	Mini-Circuits	942907	09/10/2025	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/26/2025	Annual
Automation Software	FCC 2G/3G/4G Conducted	HCT CO., LTD	-	-	-
Automation Software	FCC NR Conducted	HCT CO., LTD	-	-	-
Automation Software	FCC LTE Radiated	HCT CO., LTD	-	-	-
Automation Software	FCC NR Radiated	HCT CO., LTD	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
Occupied Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)

Parameter	Expanded Uncertainty ($\pm$ dB)
Block Edge	0.70 (Confidence level about 95 %, $k=2$)
Conducted Spurious Emissions	1.18 (Confidence level about 95 %, $k=2$)
Peak- to- Average Ratio	0.68 (Confidence level about 95 %, $k=2$)
Radiated Power	4.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.68 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.75 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.82 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

-. The decision rule applies 'simple acceptance'

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(a)	Section 3.7	PASS
Conducted Output Power	§ 2.1046	N/A	<u>Note1</u>
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. Refer to the SAR report.
2. Conducted tests were tested using 5G Wireless Tester.

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 27.50(a)(3)	< 0.25 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(a)	< 70 + 10log10 (P[Watts])	PASS

Note:

1. Radiated tests were tested using 5G Wireless Tester

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4 M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4 M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4 M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA(Main 1 ANT)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2307.5	Sub6 n30/ 5 MHz	PI/2 BPSK	-23.34	13.40	10.66	2.34	H	< 0.25	0.149	21.72	1	12
		QPSK	-23.39	13.35	10.66	2.34	H		0.147	21.67		
		16-QAM	-24.42	12.32	10.66	2.34	H		0.116	20.64		
		64-QAM	-25.92	10.82	10.66	2.34	H		0.082	19.14		
		256-QAM	-27.90	8.84	10.66	2.34	H		0.052	17.16		
2310.0		PI/2 BPSK	-23.24	13.50	10.66	2.34	H		0.152	21.82	1	12
		QPSK	-23.29	13.45	10.66	2.34	H		0.150	21.77		
		16-QAM	-24.34	12.40	10.66	2.34	H		0.118	20.72		
		64-QAM	-25.84	10.90	10.66	2.34	H		0.084	19.22		
		256-QAM	-27.83	8.91	10.66	2.34	H		0.053	17.23		
2312.5		PI/2 BPSK	-23.14	13.59	10.70	2.33	H		0.157	21.96	1	12
		QPSK	-23.18	13.55	10.70	2.33	H		0.156	21.92		
		16-QAM	-24.24	12.49	10.70	2.33	H		0.122	20.86		
		64-QAM	-25.80	10.93	10.70	2.33	H		0.085	19.30		
		256-QAM	-27.72	9.01	10.70	2.33	H		0.055	17.38		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
2310.0	Sub6 n30/ 10 MHz	PI/2 BPSK	-23.18	13.56	10.66	2.34	H	< 0.25	0.154	21.88	1	50
		QPSK	-23.20	13.54	10.66	2.34	H		0.153	21.86		
		16-QAM	-24.13	12.61	10.66	2.34	H		0.124	20.93		
		64-QAM	-25.71	11.03	10.66	2.34	H		0.086	19.35		
		256-QAM	-27.71	9.03	10.66	2.34	H		0.054	17.35		

8.2 RADIATED SPURIOUS EMISSIONS

NR Band:	<u>N30</u>
Bandwidth:	<u>5 MHz</u>
Modulation:	<u>PI/2 BPSK</u>
Distance:	<u>1 meters</u>
SCS:	<u>15 kHz</u>

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
461500 (2307.5)	4 615.00	-57.04	12.17	-60.50	3.52	H	-51.85	-40.00	1	12
	6 922.50	-63.13	11.16	-57.76	4.40	V	-51.00	-40.00		
	9 230.00	-57.54	11.07	-49.81	5.16	V	-43.90	-40.00		
462000 (2310.0)	4 620.00	-58.30	12.18	-61.50	3.51	V	-52.83	-40.00	1	12
	6 930.00	-63.35	11.16	-57.94	4.40	V	-51.18	-40.00		
	9 240.00	-57.50	11.08	-49.57	5.16	V	-43.65	-40.00		
462500 (2312.5)	4 625.00	-56.42	12.18	-59.44	3.50	V	-50.76	-40.00	1	12
	6 937.50	-64.57	11.16	-58.98	4.41	V	-52.23	-40.00		
	9 250.00	-59.11	11.09	-50.93	5.17	H	-45.01	-40.00		

- ▣ NR Band: N30
- ▣ Bandwidth: 10 MHz
- ▣ Modulation: PI/2 BPSK
- ▣ Distance: 1 meters
- ▣ SCS: 15 kHz

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
462000 (2310.0)	4 620.00	-56.30	12.18	-59.50	3.51	H	-50.83	-40.00	1	50
	6 930.00	-64.52	11.16	-59.11	4.40	V	-52.35	-40.00		
	9 240.00	-59.38	11.08	-51.45	5.16	V	-45.53	-40.00		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequenc y (MHz)	Modulatio n	Resource Block Size	Resource Block Offset	Data (dB)	Limit (dB)
30	5 MHz	2310.0	BPSK	25	0	4.34	13.00
			QPSK			5.49	
			16-QAM			6.04	
			64-QAM			6.54	
			256-QAM			6.57	
	10 MHz		BPSK	50		5.47	
			QPSK			5.66	
			16-QAM			6.19	
			64-QAM			6.50	
			256-QAM			6.67	

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 50 ~ 59.
2. P.A.P.R is not required. These values are reported for information only.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
30	5 MHz	2310.0	BPSK	25	0	4.5176
			QPSK			4.5275
			16-QAM			4.5015
			64-QAM			4.4995
			256-QAM			4.5205
	10 MHz		BPSK	50		9.0043
			QPSK			9.0055
			16-QAM			8.9788
			64-QAM			8.9660
			256-QAM			8.9627

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 60 ~ 69.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
30	5	2307.5	9.2218	30.315	-80.193	-49.878	-40.00
		2310.0	8.2752	30.315	-81.955	-51.640	
		2312.5	8.2991	30.315	-81.869	-51.554	
	10	2310.0	9.2223	30.315	-80.359	-50.044	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 70 ~ 77.
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	27.012
1 – 5	29.722
5 – 10	30.315
10 – 15	30.840
15 – 20	31.213
Above 20	31.855

8.6 BAND EDGE

Band Width (MHz)	Frequency (MHz)	Modulation	RB (Size/ Offset)	Frequency Range (MHz)	Maximum Data (dBm)	Limit (dBm)
5	2307.5	BPSK	25/0	Below 2288	-61.063	-40
				2288 - 2292	-52.163	-37
				2292 - 2296	-42.704	-31
				2296 - 2300	-37.371	-25
				2300 - 2304	-25.472	-13
				2304 - 2305	-25.848	-13
				2315 - 2320	-37.334	-13
				2320 - 2324	-43.619	-25
				2324 - 2328	-52.203	-31
				2328 - 2337	-61.483	-37
				2337 - 2341	-61.723	-31
				2341 - 2345	-61.716	-25
				2345 - 2365	-61.477	-13
				Above 2365	-61.706	-40
	2310.0	BPSK	25/0	Below 2288	-61.578	-40
				2288 - 2292	-57.355	-37
				2292 - 2296	-47.983	-31
				2296 - 2300	-40.834	-25
				2300 - 2305	-30.225	-13
				2315 - 2320	-27.862	-13
				2320 - 2324	-42.286	-25
				2324 - 2328	-48.745	-31
				2328 - 2337	-61.104	-37
				2337 - 2341	-61.816	-31
				2341 - 2345	-60.861	-25
				2345 - 2365	-60.553	-13
				Above 2365	-61.895	-40
	2312.5	BPSK	25/0	Below 2288	-61.921	-40
				2288 - 2292	-59.601	-37
				2292 - 2296	-52.179	-31
				2296 - 2300	-44.165	-25
				2300 - 2305	-35.578	-13

				2315 - 2316	-26.666	-13
				2316 - 2320	-26.950	-13
				2320 - 2324	-38.934	-25
				2324 - 2328	-44.195	-31
				2328 - 2337	-58.644	-37
				2337 - 2341	-61.786	-31
				2341 - 2345	-60.748	-25
				2345 - 2365	-60.159	-13
				Above 2365	-61.858	-40
10	2310.0	BPSK	50/0	Below 2288	-50.120	-40
				2288 - 2292	-42.353	-37
				2292 - 2296	-36.424	-31
				2296 - 2300	-29.644	-25
				2300 - 2304	-24.829	-13
				2304 - 2305	-27.048	-13
				2315 - 2316	-33.584	-13
				2316 - 2320	-24.501	-13
				2320 - 2324	-31.406	-25
				2324 - 2328	-41.576	-31
				2328 - 2337	-51.425	-37
				2337 - 2341	-61.337	-31
				2341 - 2345	-61.262	-25
				2345 - 2365	-61.267	-13
				Above 2365	-61.355	-40

Band Width (MHz)	Frequency (MHz)	Modulation	RB (Size/ Offset)	Frequency Range (MHz)	Maximum Data (dBm)	Limit (dBm)
5	2307.5	BPSK	1/0	Below 2288	-61.334	-40
				2288 - 2292	-50.924	-37
				2292 - 2296	-45.544	-31
				2296 - 2300	-42.441	-25
				2300 - 2304	-26.492	-13
				2304 - 2305	-23.970	-13
			1/24	2315 - 2320	-42.114	-13
				2320 - 2324	-47.526	-25
				2324 - 2328	-54.253	-31
				2328 - 2337	-61.548	-37
				2337 - 2341	-61.878	-31
				2341 - 2345	-61.813	-25
				2345 - 2365	-61.486	-13
				Above 2365	-61.829	-40
	2310.0	BPSK	1/0	Below 2288	-61.731	-40
				2288 - 2292	-58.014	-37
				2292 - 2296	-48.275	-31
				2296 - 2300	-43.711	-25
				2300 - 2305	-36.817	-13
			1/24	2315 - 2320	-38.901	-13
				2320 - 2324	-42.578	-25
				2324 - 2328	-49.962	-31
				2328 - 2337	-61.187	-37
				2337 - 2341	-61.834	-31
				2341 - 2345	-60.999	-25
				2345 - 2365	-60.185	-13
				Above 2365	-61.877	-40
	2312.5	BPSK	1/0	Below 2288	-61.973	-40
				2288 - 2292	-60.049	-37
				2292 - 2296	-53.453	-31
				2296 - 2300	-46.070	-25
				2300 - 2305	-42.369	-13
			1/24	2315 - 2316	-28.123	-13

				2316 - 2320	-29.065	-13
				2320 - 2324	-41.552	-25
				2324 - 2328	-46.509	-31
				2328 - 2337	-59.296	-37
				2337 - 2341	-61.746	-31
				2341 - 2345	-60.822	-25
				2345 - 2365	-60.214	-13
				Above 2365	-61.818	-40
10	2310.0	BPSK	1/0	Below 2288	-60.891	-40
				2288 - 2292	-56.136	-37
				2292 - 2296	-47.319	-31
				2296 - 2300	-38.277	-25
				2300 - 2304	-25.336	-13
				2304 - 2305	-27.906	-13
			1/49	2315 - 2316	-30.853	-13
				2316 - 2320	-27.293	-13
				2320 - 2324	-40.651	-25
				2324 - 2328	-48.239	-31
				2328 - 2337	-59.760	-37
				2337 - 2341	-61.413	-31
				2341 - 2345	-61.342	-25
				2345 - 2365	-61.180	-13
				Above 2365	-61.474	-40

Note:

- Plots of the EUT's Band Edge are shown Page 71 ~ 189.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

BandWidth:	<u>5 MHz</u>
Voltage(100 %):	<u>3.880 VDC</u>
Batt. Endpoint:	<u>3.300 VDC</u>
LIMIT:	<u>Emission must remain in band</u>
BandWidth:	<u>5 MHz</u>

Test. Frequency	Voltage	Temp.	Frequency	Frequency Error	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	(Hz)	(%)	
2307.5	100 %	+20(Ref)	2307 499 980	0.0	0.000 000	0.000
	100 %	-30	2307 499 961	-19.5	-0.000 001	-0.008
	100 %	-20	2307 499 963	-17.8	-0.000 001	-0.008
	100 %	-10	2307 499 964	-16.5	-0.000 001	-0.007
	100 %	0	2307 499 966	-14.5	-0.000 001	-0.006
	100 %	+10	2307 499 967	-13.3	-0.000 001	-0.006
	100 %	+30	2307 499 965	-15.0	-0.000 001	-0.007
	100 %	+40	2307 499 970	-10.7	0.000 000	-0.005
	100 %	+50	2307 499 970	-10.5	0.000 000	-0.005
	Batt. Endpoint	+20	2307 499 969	-11.6	-0.000 001	-0.005
2312.5	100 %	+20(Ref)	2312 500 000	0.0	0.000 000	0.000
	100 %	-30	2312 500 000	-0.3	0.000 000	0.000
	100 %	-20	2312 499 999	-1.5	0.000 000	-0.001
	100 %	-10	2312 500 002	1.8	0.000 000	0.001
	100 %	0	2312 499 999	-1.3	0.000 000	-0.001
	100 %	+10	2312 500 000	-0.2	0.000 000	0.000
	100 %	+30	2312 500 001	0.1	0.000 000	0.000
	100 %	+40	2312 500 003	2.5	0.000 000	0.001
	100 %	+50	2312 500 002	1.8	0.000 000	0.001
	Batt. Endpoint	+20	2312 499 999	-1.1	0.000 000	0.000

- ▣ BandWidth: 10 MHz
- ▣ Voltage(100 %): 3.880 VDC
- ▣ Batt. Endpoint: 3.300 VDC
- ▣ LIMIT: Emission must remain in band
- ▣ BandWidth: 10 MHz

Test. Frequency	Voltage	Temp.	Frequency	Frequency Error	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	(Hz)	(%)	
2310.0	100 %	+20(Ref)	2309 999 985	0.0	0.000 000	0.000
	100 %	-30	2309 999 972	-13.0	-0.000 001	-0.006
	100 %	-20	2309 999 973	-12.2	-0.000 001	-0.005
	100 %	-10	2309 999 975	-10.5	0.000 000	-0.005
	100 %	0	2309 999 977	-8.2	0.000 000	-0.004
	100 %	+10	2309 999 977	-7.6	0.000 000	-0.003
	100 %	+30	2309 999 978	-7.1	0.000 000	-0.003
	100 %	+40	2309 999 978	-7.2	0.000 000	-0.003
	100 %	+50	2309 999 979	-6.4	0.000 000	-0.003
	Batt. Endpoint	+20	2309 999 978	-6.6	0.000 000	-0.003

9. TEST DATA(Sub 2 ANT)

9.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2307.5	Sub6 n30/ 5 MHz	PI/2 BPSK	-23.58	13.16	10.66	2.34	H	< 0.25	0.141	21.48	1	12
		QPSK	-23.82	12.92	10.66	2.34	H		0.133	21.24		
		16-QAM	-24.62	12.12	10.66	2.34	H		0.111	20.44		
		64-QAM	-26.12	10.62	10.66	2.34	H		0.078	18.94		
		256-QAM	-28.07	8.67	10.66	2.34	H		0.050	16.99		
2310.0		PI/2 BPSK	-23.52	13.22	10.66	2.34	H		0.143	21.54	1	12
		QPSK	-23.65	13.09	10.66	2.34	H		0.138	21.41		
		16-QAM	-24.58	12.16	10.66	2.34	H		0.112	20.48		
		64-QAM	-26.08	10.66	10.66	2.34	H		0.079	18.98		
		256-QAM	-28.05	8.69	10.66	2.34	H		0.050	17.01		
2312.5		PI/2 BPSK	-23.55	13.18	10.70	2.33	H		0.143	21.55	1	12
		QPSK	-23.57	13.16	10.70	2.33	H		0.142	21.53		
		16-QAM	-24.46	12.27	10.70	2.33	H		0.116	20.64		
		64-QAM	-25.98	10.75	10.70	2.33	H		0.082	19.12		
		256-QAM	-27.96	8.77	10.70	2.33	H		0.052	17.14		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
2310.0	Sub6 n30/ 10 MHz	PI/2 BPSK	-23.53	13.21	10.66	2.34	H	< 0.25	0.142	21.53	1	26
		QPSK	-23.63	13.11	10.66	2.34	H		0.139	21.43		
		16-QAM	-24.56	12.18	10.66	2.34	H		0.112	20.50		
		64-QAM	-26.08	10.66	10.66	2.34	H		0.079	18.98		
		256-QAM	-28.02	8.72	10.66	2.34	H		0.051	17.04		

9.2 RADIATED SPURIOUS EMISSIONS

NR Band:	<u>N30</u>
Bandwidth:	<u>5 MHz</u>
Modulation:	<u>PI/2 BPSK</u>
Distance:	<u>1 meters</u>
SCS:	<u>15 kHz</u>

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
461500 (2307.5)	4 615.00	-61.26	12.17	-64.72	3.52	V	-56.07	-40.00	1	12
	6 922.50	-57.87	11.16	-52.50	4.40	H	-45.74	-40.00		
	9 230.00	-57.78	11.07	-50.05	5.16	V	-44.14	-40.00		
462000 (2310.0)	4 620.00	-61.58	12.18	-64.78	3.51	V	-56.11	-40.00	1	12
	6 930.00	-55.81	11.16	-50.40	4.40	H	-43.64	-40.00		
	9 240.00	-58.02	11.08	-50.09	5.16	V	-44.17	-40.00		
462500 (2312.5)	4 625.00	-60.34	12.18	-63.36	3.50	H	-54.68	-40.00	1	12
	6 937.50	-58.68	11.16	-53.09	4.41	H	-46.34	-40.00		
	9 250.00	-57.75	11.09	-49.57	5.17	V	-43.65	-40.00		

- ▣ NR Band: N30
- ▣ Bandwidth: 10 MHz
- ▣ Modulation: PI/2 BPSK
- ▣ Distance: 1 meters
- ▣ SCS: 15 kHz

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
462000 (2310.0)	4 620.00	-60.15	12.18	-63.35	3.51	V	-54.68	-40.00	1	26
	6 930.00	-60.92	11.16	-55.51	4.40	H	-48.75	-40.00		
	9 240.00	-59.16	11.08	-51.23	5.16	V	-45.31	-40.00		

9.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequenc y (MHz)	Modulatio n	Resource Block Size	Resource Block Offset	Data (dB)	Limit (dB)
30	5 MHz	2310.0	BPSK	25	0	4.23	13.00
			QPSK			5.18	
			16-QAM			5.75	
			64-QAM			6.13	
			256-QAM			6.31	
	10 MHz		BPSK	50		5.25	
			QPSK			5.36	
			16-QAM			5.83	
			64-QAM			6.17	
			256-QAM			6.47	

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 191 ~ 200.
2. P.A.P.R is not required. These values are reported for information only.

9.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
30	5 MHz	2310.0	BPSK	25	0	4.5258
			QPSK			4.5090
			16-QAM			4.5056
			64-QAM			4.4944
			256-QAM			4.5232
	10 MHz		BPSK	50		8.9875
			QPSK			8.9928
			16-QAM			8.9721
			64-QAM			8.9763
			256-QAM			8.9570

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 201 ~ 210.

9.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
30	5	2307.5	9.7039	30.315	-81.723	-51.408	-40.00
		2310.0	8.2707	30.315	-81.430	-51.115	
		2312.5	8.2767	30.315	-81.449	-51.134	
	10	2310.0	8.2782	30.315	-81.653	-51.338	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 211 ~ 218.
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	27.012
1 – 5	29.722
5 – 10	30.315
10 – 15	30.840
15 – 20	31.213
Above 20	31.855

9.6 BAND EDGE

Band Width (MHz)	Frequency (MHz)	Modulation	RB (Size/ Offset)	Frequency Range (MHz)	Maximum Data (dBm)	Limit (dBm)
5	2307.5	BPSK	25/0	Below 2288	-62.958	-40
				2288 - 2292	-55.293	-37
				2292 - 2296	-44.300	-31
				2296 - 2300	-34.854	-25
				2300 - 2304	-22.227	-13
				2304 - 2305	-26.365	-13
				2315 - 2320	-37.203	-13
				2320 - 2324	-45.137	-25
				2324 - 2328	-56.749	-31
				2328 - 2337	-62.597	-37
				2337 - 2341	-62.608	-31
				2341 - 2345	-62.534	-25
				2345 - 2365	-62.487	-13
				Above 2365	-62.547	-40
	2310.0	BPSK	25/0	Below 2288	-61.689	-40
				2288 - 2292	-56.971	-37
				2292 - 2296	-48.183	-31
				2296 - 2300	-39.997	-25
				2300 - 2305	-28.149	-13
				2315 - 2320	-31.954	-13
				2320 - 2324	-40.912	-25
				2324 - 2328	-49.283	-31
				2328 - 2337	-61.440	-37
				2337 - 2341	-61.771	-31
				2341 - 2345	-61.800	-25
				2345 - 2365	-61.586	-13
				Above 2365	-61.838	-40
	2312.5	BPSK	25/0	Below 2288	-61.881	-40
				2288 - 2292	-59.497	-37
				2292 - 2296	-52.785	-31
				2296 - 2300	-43.505	-25
				2300 - 2305	-34.876	-13

				2315 - 2316	-26.885	-13
				2316 - 2320	-26.851	-13
				2320 - 2324	-36.412	-25
				2324 - 2328	-44.638	-31
				2328 - 2337	-59.675	-37
				2337 - 2341	-61.790	-31
				2341 - 2345	-61.743	-25
				2345 - 2365	-61.709	-13
				Above 2365	-61.717	-40
10	2310.0	BPSK	50/0	Below 2288	-51.297	-40
				2288 - 2292	-42.043	-37
				2292 - 2296	-35.149	-31
				2296 - 2300	-27.043	-25
				2300 - 2304	-23.214	-13
				2304 - 2305	-27.196	-13
				2315 - 2316	-34.505	-13
				2316 - 2320	-26.461	-13
				2320 - 2324	-32.599	-25
				2324 - 2328	-40.339	-31
				2328 - 2337	-50.998	-37
				2337 - 2341	-61.830	-31
				2341 - 2345	-61.660	-25
				2345 - 2365	-61.564	-13
				Above 2365	-61.801	-40

Band Width (MHz)	Frequency (MHz)	Modulation	RB (Size/ Offset)	Frequency Range (MHz)	Maximum Data (dBm)	Limit (dBm)
5	2307.5	BPSK	1/0	Below 2288	-62.963	-40
				2288 - 2292	-55.973	-37
				2292 - 2296	-46.069	-31
				2296 - 2300	-40.946	-25
				2300 - 2304	-26.227	-13
				2304 - 2305	-24.786	-13
			1/24	2315 - 2320	-41.867	-13
				2320 - 2324	-47.100	-25
				2324 - 2328	-57.686	-31
				2328 - 2337	-62.591	-37
				2337 - 2341	-62.633	-31
				2341 - 2345	-62.637	-25
				2345 - 2365	-62.566	-13
				Above 2365	-62.597	-40
	2310.0	BPSK	1/0	Below 2288	-61.732	-40
				2288 - 2292	-57.885	-37
				2292 - 2296	-49.007	-31
				2296 - 2300	-42.728	-25
				2300 - 2305	-35.893	-13
			1/24	2315 - 2320	-37.816	-13
				2320 - 2324	-42.314	-25
				2324 - 2328	-51.456	-31
				2328 - 2337	-61.682	-37
				2337 - 2341	-61.773	-31
				2341 - 2345	-61.803	-25
				2345 - 2365	-61.526	-13
				Above 2365	-61.841	-40
	2312.5	BPSK	1/0	Below 2288	-61.934	-40
				2288 - 2292	-59.712	-37
				2292 - 2296	-54.037	-31
				2296 - 2300	-45.889	-25
				2300 - 2305	-40.322	-13
			1/24	2315 - 2316	-28.267	-13

				2316 - 2320	-27.525	-13
				2320 - 2324	-42.085	-25
				2324 - 2328	-47.886	-31
				2328 - 2337	-60.282	-37
				2337 - 2341	-61.774	-31
				2341 - 2345	-61.832	-25
				2345 - 2365	-61.666	-13
				Above 2365	-61.782	-40
10	2310.0	BPSK	1/0	Below 2288	-61.615	-40
				2288 - 2292	-57.574	-37
				2292 - 2296	-49.698	-31
				2296 - 2300	-38.355	-25
				2300 - 2304	-25.554	-13
				2304 - 2305	-30.338	-13
			1/49	2315 - 2316	-31.398	-13
				2316 - 2320	-24.761	-13
				2320 - 2324	-38.614	-25
				2324 - 2328	-50.606	-31
				2328 - 2337	-61.240	-37
				2337 - 2341	-61.758	-31
				2341 - 2345	-61.745	-25
				2345 - 2365	-61.557	-13
				Above 2365	-61.801	-40

Note:

- Plots of the EUT's Band Edge are shown Page 219 ~ 330.

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

BandWidth:	<u>5 MHz</u>
Voltage(100 %):	<u>3.880 VDC</u>
Batt. Endpoint:	<u>3.300 VDC</u>
LIMIT:	<u>Emission must remain in band</u>
BandWidth:	<u>5 MHz</u>


Test. Frequency	Voltage	Temp.	Frequency	Frequency Error	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	(Hz)	(%)	
2307.5	100 %	+20(Ref)	2307 500 000	0.0	0.000 000	0.000
	100 %	-30	2307 499 997	-2.6	0.000 000	-0.001
	100 %	-20	2307 500 000	0.3	0.000 000	0.000
	100 %	-10	2307 499 999	-0.8	0.000 000	0.000
	100 %	0	2307 499 998	-2.0	0.000 000	-0.001
	100 %	+10	2307 499 999	-0.4	0.000 000	0.000
	100 %	+30	2307 499 999	-0.4	0.000 000	0.000
	100 %	+40	2307 500 001	1.0	0.000 000	0.000
	100 %	+50	2307 500 000	0.7	0.000 000	0.000
	Batt. Endpoint	+20	2307 499 999	-0.9	0.000 000	0.000
2312.5	100 %	+20(Ref)	2312 500 000	0.0	0.000 000	0.000
	100 %	-30	2312 500 000	-0.7	0.000 000	0.000
	100 %	-20	2312 500 000	0.0	0.000 000	0.000
	100 %	-10	2312 500 001	0.5	0.000 000	0.000
	100 %	0	2312 500 000	0.0	0.000 000	0.000
	100 %	+10	2312 499 998	-2.2	0.000 000	-0.001
	100 %	+30	2312 500 001	0.2	0.000 000	0.000
	100 %	+40	2312 500 000	-0.3	0.000 000	0.000
	100 %	+50	2312 500 001	0.4	0.000 000	0.000
	Batt. Endpoint	+20	2312 500 001	0.5	0.000 000	0.000

- ▣ BandWidth: 10 MHz
- ▣ Voltage(100 %): 3.880 VDC
- ▣ Batt. Endpoint: 3.300 VDC
- ▣ LIMIT: Emission must remain in band
- ▣ BandWidth: 10 MHz


Test. Frequency	Voltage	Temp.	Frequency	Frequency Error	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	(Hz)	(%)	
2310.0	100 %	+20(Ref)	2310 000 000	0.0	0.000 000	0.000
	100 %	-30	2310 000 000	-0.2	0.000 000	0.000
	100 %	-20	2310 000 001	0.2	0.000 000	0.000
	100 %	-10	2310 000 002	2.1	0.000 000	0.001
	100 %	0	2310 000 001	0.3	0.000 000	0.000
	100 %	+10	2309 999 999	-1.5	0.000 000	-0.001
	100 %	+30	2310 000 000	0.0	0.000 000	0.000
	100 %	+40	2310 000 001	0.4	0.000 000	0.000
	100 %	+50	2310 000 001	0.8	0.000 000	0.000
	Batt. Endpoint	+20	2309 999 999	-1.1	0.000 000	0.000

10. TEST PLOTS(Main 1 ANT)


NR30_5 M_PAR_Mid_BPSK_FullIRB



NR30_5 M_PAR_Mid_QPSK_FullIRB



NR30_5 M_PAR_Mid_16QAM_FullRB



NR30_5 M_PAR_Mid_64QAM_FullRB




NR30_5 M_PAR_Mid_256QAM_FullRB



NR30_10 M_PAR_Mid_BPSK_FullRB




NR30_10 M_PAR_Mid_QPSK_FullRB



NR30_10 M_PAR_Mid_16QAM_FullRB




NR30_10 M_PAR_Mid_64QAM_FullRB




NR30_10 M_PAR_Mid_256QAM_FullRB




NR30_5 M_OBW_Mid_BPSK_FullRB




NR30_5 M_OBW_Mid_QPSK_FullRB




NR30_5 M_OBW_Mid_16QAM_FullRB



NR30_5 M_OBW_Mid_64QAM_FullRB




NR30_5 M_OBW_Mid_256QAM_FullRB




NR30_10 M_OBW_Mid_BPSK_FullRB




NR30_10 M_OBW_Mid_QPSK_FullRB




NR30_10 M_OBW_Mid_16QAM_FullRB



NR30_10 M_OBW_Mid_64QAM_FullRB



NR30_10 M_OBW_Mid_256QAM_FullRB



NR30_5 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB



NR30_5 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB



NR30_5 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB



NR30_10 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB



NR30_5 M_Conducted Spurious(Above10 G)_Low_BPSK_1RB



NR30_5 M_Conducted Spurious(Above10 G)_Mid_BPSK_1RB



NR30_5 M_Conducted Spurious(Above10 G)_High_BPSK_1RB



NR30_10 M_Conducted Spurious(Above10 G)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2280MHz-2288MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2288MHz-2292MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2292MHz-2296MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2296MHz-2300MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2300MHz-2304MHz)_Low_BPSK_1RB



Note : We used a narrower RBW in order to increase accuracy.

Calculation = Reading Value + 10 x log(1 MHz/100 kHz) dB = -36.492 dBm + 10 dB = -26.492 dBm

NR30_5 M_Band Edge(2304MHz-2305MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2315MHz-2320MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2320MHz-2324MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2324MHz-2328MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2328MHz-2337MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2337MHz-2341MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2341MHz-2345MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2345MHz-2365MHz)_Low_BPSK_1RB




NR30_5 M_Band Edge(2365MHz-2400MHz)_Low_BPSK_1RB



NR30_5 M_Band Edge(2280MHz-2288MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2288MHz-2292MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2292MHz-2296MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2296MHz-2300MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2300MHz-2304MHz)_Low_BPSK_FullRB



Note : We used a narrower RBW in order to increase accuracy.

Calculation = Reading Value + 10 x log(1 MHz/100 kHz) dB = -35.472 dBm + 10 dB = -25.472 dBm

NR30_5 M_Band Edge(2304MHz-2305MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2315MHz-2320MHz)_Low_BPSK_FullIRB



NR30_5 M_Band Edge(2320MHz-2324MHz)_Low_BPSK_FullIRB



NR30_5 M_Band Edge(2324MHz-2328MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2328MHz-2337MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2337MHz-2341MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2341MHz-2345MHz)_Low_BPSK_FullRB



NR30_5 M_Band Edge(2345MHz-2365MHz)_Low_BPSK_FullIRB



NR30_5 M_Band Edge(2365MHz-2400MHz)_Low_BPSK_FullIRB



NR30_5 M_Band Edge(2280MHz-2288MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2288MHz-2292MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2292MHz-2296MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2296MHz-2300MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2300MHz-2305MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2315MHz-2320MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2320MHz-2324MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2324MHz-2328MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2328MHz-2337MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2337MHz-2341MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2341MHz-2345MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2345MHz-2365MHz)_Mid_BPSK_1RB




NR30_5 M_Band Edge(2365MHz-2400MHz)_Mid_BPSK_1RB



NR30_5 M_Band Edge(2280MHz-2288MHz)_Mid_BPSK_FullIRB



NR30_5 M_Band Edge(2288MHz-2292MHz)_Mid_BPSK_FullIRB



NR30_5 M_Band Edge(2292MHz-2296MHz)_Mid_BPSK_FullIRB



NR30_5 M_Band Edge(2296MHz-2300MHz)_Mid_BPSK_FullIRB

