






Plot 7-155. Ant 2 Lower Band Edge (50MHz-1CC – QPSK 1 RB)




Plot 7-156. Ant 2 Lower Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 144 of 198




Plot 7-157. Ant 2 Upper Band Edge (50MHz-1CC – QPSK Full RB)




Plot 7-158. Ant 2 Upper Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 145 of 198




Plot 7-159. Ant 2 Lower Band Edge (100MHz-1CC – QPSK 1 RB)




Plot 7-160. Ant 2 Lower Band Edge (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 146 of 198




Plot 7-161. Ant 2 Upper Band Edge (100MHz-1CC – QPSK Full RB)




Plot 7-162. Ant 2 Upper Band Edge (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 147 of 198

Band n258-R2 – Worst-Case




Plot 7-163. Ant 1 Lower Band Edge (50MHz-1CC – QPSK Full RB)




Plot 7-164. Ant 1 Lower Band Edge – TRP (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 148 of 198




Plot 7-165. Ant 1 Upper Band Edge (50MHz-1CC – QPSK Full RB)




Plot 7-166. Ant 1 Upper Band Edge – TRP (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 149 of 198




Plot 7-167. Ant 1 Lower Band Edge (100MHz-1CC – QPSK 1 RB)




Plot 7-168. Ant 1 Lower Band Edge – TRP (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 150 of 198




Plot 7-169. Ant 1 Upper Band Edge (100MHz-1CC – QPSK 1 RB)




Plot 7-170. Ant 1 Upper Band Edge – TRP (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 151 of 198




Plot 7-171. Ant 2 Lower Band Edge (50MHz-1CC – QPSK Full RB)




Plot 7-172. Ant 2 Lower Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 152 of 198




Plot 7-173. Ant 2 Upper Band Edge – TRP (50MHz-1CC – QPSK Full RB)




Plot 7-174. Ant 2 Upper Band Edge – TRP (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 153 of 198




Plot 7-175. Ant 2 Lower Band Edge (100MHz-1CC – QPSK 1 RB)




Plot 7-176. Ant 2 Lower Band Edge (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 154 of 198




Plot 7-177. Ant 2 Upper Band Edge (100MHz-1CC – QPSK Full RB)




Plot 7-178. Ant 2 Upper Band Edge – TRP (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 155 of 198

Band n261 – Worst-Case




Plot 7-179. Ant 1 Lower Band Edge – TRP (50MHz-1CC – QPSK 1 RB)




Plot 7-180. Ant 1 Lower Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 156 of 198




Plot 7-181. Ant 1 Upper Band Edge – TRP (50MHz-1CC – QPSK Full RB)




Plot 7-182. Ant 1 Upper Band Edge – TRP (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 157 of 198




Plot 7-183. Ant 1 Lower Band Edge – TRP (100MHz-1CC – QPSK 1 RB)




Plot 7-184. Ant 1 Lower Band Edge – TRP (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 158 of 198




Plot 7-185. Ant 1 Upper Band Edge (100MHz-1CC – QPSK Full RB)




Plot 7-186. Ant 1 Upper Band Edge – TRP (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 159 of 198




Plot 7-187. Ant 2 Lower Band Edge – TRP (50MHz-1CC – QPSK 1 RB)




Plot 7-188. Ant 2 Lower Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 160 of 198




Plot 7-189. Ant 2 Upper Band Edge (50MHz-1CC – QPSK Full RB)




Plot 7-190. Ant 2 Upper Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 161 of 198




Plot 7-191. Ant 2 Lower Band Edge (100MHz-1CC – QPSK 1 RB)




Plot 7-192. Ant 2 Lower Band Edge (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 162 of 198




Plot 7-193. Ant 2 Upper Band Edge (100MHz-1CC – QPSK Full RB)




Plot 7-194. Ant 2 Upper Band Edge – TRP (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 163 of 198

Band n260 – Worst Case




Plot 7-195. Ant 1 Lower Band Edge (50MHz-1CC QPSK 1 RB)




Plot 7-196. Ant 1 Lower Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 164 of 198




Plot 7-197. Ant 1 Upper Band Edge (50MHz-1CC – QPSK 1 RB)




Plot 7-198. Ant 1 Upper Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 165 of 198




Plot 7-199. Ant 1 Lower Band Edge (100MHz-1CC – QPSK 1 RB)




Plot 7-200. Ant 1 Lower Band Edge (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 166 of 198




Plot 7-201. Ant 1 Upper Band Edge (100MHz-1CC – QPSK 1 RB)




Plot 7-202. Ant 1 Upper Band Edge (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 167 of 198




Plot 7-203. Ant 2 Lower Band Edge (50MHz-1CC – QPSK 1 RB)




Plot 7-204. Ant 2 Lower Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 168 of 198




Plot 7-205. Ant 2 Upper Band Edge (50MHz-1CC – QPSK Full RB)




Plot 7-206. Ant 2 Upper Band Edge (50MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 169 of 198




Plot 7-207. Ant 2 Lower Band Edge (100MHz-1CC – QPSK 1 RB)




Plot 7-208. Ant 2 Lower Band Edge – TRP (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 170 of 198



Plot 7-209. Ant 2 Upper Band Edge (100MHz-1CC – QPSK Full RB)



Plot 7-210. Ant 2 Upper Band Edge (100MHz-2CC – QPSK 1 RB)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 171 of 198

7.6 Frequency Stability / Temperature Variation

§2.1055

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Test Procedure Used

ANSI C63.5-2015 Section 5.6

KDB 842590 D01 v01r02 Section 4.5

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was measured using horn antenna connected to a spectrum analyzer. The EUT was placed inside an environmental chamber that uses a foam plug to maintain the temperature condition inside the chamber. The horn antenna measured the frequency of the fundamental signal.

Test Notes

The Frequency Deviation column in the table below is the amount of deviation measured from the center frequency of the Reference measurement (first row).

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 172 of 198

© 2022 PCTEST

V1.0

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Frequency Stability Measurements (Band n258-R1)

§2.1055

OPERATING FREQUENCY: 24,349,920,000 Hz
CHANNEL: 2018331
REFERENCE VOLTAGE: 4.43 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.43	+ 20 (Ref)	24,350,587,037	0	0.0000000
100 %		- 30	24,350,687,533	-100,496	-0.0004127
100 %		- 20	24,350,737,438	-150,402	-0.0006177
100 %		- 10	24,350,737,690	-150,654	-0.0006187
100 %		0	24,350,671,385	-84,348	-0.0003464
100 %		+ 10	24,350,666,693	-79,656	-0.0003271
100 %		+ 20	24,350,587,037	0	0.0000000
100 %		+ 30	24,350,532,301	54,735	0.0002248
100 %		+ 40	24,350,509,264	77,773	0.0003194
100 %		+ 50	24,350,522,677	64,360	0.0002643
BATT. ENDPOINT	3.36	+ 20	24,350,692,625	-105,588	-0.0004336

Table 7-105. Frequency Stability Data (n258-R1)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 173 of 198

Frequency Stability Measurements (Band n258-R1)

§2.1055




Figure 7-1. Frequency Stability Graph (n258-R1)

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 174 of 198

Frequency Stability Measurements (Band n258-R2)

§2.1055

OPERATING FREQUENCY: 24,999,960,000 Hz
CHANNEL: 2029165
REFERENCE VOLTAGE: 4.43 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.43	+ 20 (Ref)	25,000,609,831	0	0.0000000
100 %		- 30	25,000,718,587	-108,757	-0.0004350
100 %		- 20	25,000,790,129	-180,298	-0.0007212
100 %		- 10	25,000,791,800	-181,969	-0.0007279
100 %		0	25,000,742,329	-132,498	-0.0005300
100 %		+ 10	25,000,698,237	-88,406	-0.0003536
100 %		+ 20	25,000,609,831	0	0.0000000
100 %		+ 30	25,000,545,084	64,747	0.0002590
100 %		+ 40	25,000,421,940	187,891	0.0007516
100 %		+ 50	25,000,559,948	49,883	0.0001995
BATT. ENDPOINT	3.36	+ 20	25,000,714,279	-104,449	-0.0004178

Table 7-106. Frequency Stability Data (n258-R2)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 175 of 198

Frequency Stability Measurements (Band n258-R2)

§2.1055




Figure 7-2. Frequency Stability Graph (n258-R2)

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 176 of 198

© 2022 PCTEST

V1.0

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Frequency Stability Measurements (Band n261)

§2.1055

OPERATING FREQUENCY: 27,924,960,000 Hz
CHANNEL: 2077915
REFERENCE VOLTAGE: 4.43 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.43	+ 20 (Ref)	27,925,612,998	0	0.0000000
100 %		- 30	27,925,729,898	-116,900	-0.0004186
100 %		- 20	27,925,805,258	-192,260	-0.0006885
100 %		- 10	27,925,800,454	-187,457	-0.0006713
100 %		0	27,925,756,753	-143,755	-0.0005148
100 %		+ 10	27,925,684,541	-71,543	-0.0002562
100 %		+ 20	27,925,612,998	0	0.0000000
100 %		+ 30	27,925,543,497	69,501	0.0002489
100 %		+ 40	27,925,551,075	61,923	0.0002217
100 %		+ 50	27,925,557,121	55,877	0.0002001
BATT. ENDPOINT	3.36	+ 20	27,925,667,200	-54,202	-0.0001941

Table 7-107. Frequency Stability Data (n261)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset	Page 177 of 198	

Frequency Stability Measurements (Band n261)

§2.1055




Figure 7-3. Frequency Stability Graph (n261)

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset	Page 178 of 198	

Frequency Stability Measurements (Band n260)

S2.1055

OPERATING FREQUENCY: 38,499,960,000 Hz
CHANNEL: 2254165
REFERENCE VOLTAGE: 4.43 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.43	+ 20 (Ref)	38,500,665,363	0	0.0000000
100 %		- 30	38,500,841,491	-176,128	-0.0004575
100 %		- 20	38,500,853,480	-188,117	-0.0004886
100 %		- 10	38,500,841,679	-176,316	-0.0004580
100 %		0	38,500,813,724	-148,362	-0.0003854
100 %		+ 10	38,500,827,974	-162,611	-0.0004224
100 %		+ 20	38,500,665,363	0	0.0000000
100 %		+ 30	38,500,531,853	133,510	0.0003468
100 %		+ 40	38,499,961,036	704,327	0.0018294
100 %		+ 50	38,499,905,049	760,314	0.0019748
BATT. ENDPOINT	3.36	+ 20	38,500,683,774	-18,411	-0.0000478

Table 7-108. Frequency Stability Data (n260)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMS906U	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset	Page 179 of 198

Frequency Stability Measurements (Band n260)

§2.1055




Figure 7-4. Frequency Stability Graph (n260)

FCC ID: A3LSMS906U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 180 of 198

© 2022 PCTEST

V1.0

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMS906U** complies with all the requirements of Part 30.

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 181 of 198

9.0 APPENDIX A

9.1 VDI Mixer Verification Certificate



Virginia Diodes, Inc
979 2nd St. SE
Suite 309
Charlottesville, VA 22902
Phone: 434-297-3257
Fax: 434-297-3258

Certificate of Conformance

To: PCTEST Engineering Laboratory
7185 Oakland Mills Road
Columbia, MD 21046
United States


From: Virginia Diodes, Inc
979 2nd St. SE
Suite 309
Charlottesville, VA 22902

Packing List No: 202943
Shipping Date: 08/28/20

Today's Date: 08/28/20
PO Number: 200414.DP2

Quantity	Shipped	Unit	Description	Order-Job Number
1	EA	VDIWR19.0SAX-M-M4 WR19SAX-M-M4 / SN: SAX 679	20177A-01	

The VDI product(s) in this shipment meet(s) the guidelines for performance specifications established in accordance with the corresponding Purchase Order. Data presented in the User Guide, where applicable, has been obtained in accordance with VDI's Quality Management System. All instruments, used to obtain data, which require calibration have been calibrated with equipment traceable to the National Institute of Standards and Technology (NIST) and through NIST to the International System of Units (SI).


Authorized Signature
Virginia Diodes, Inc

Page 1 of 1

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 182 of 198



Virginia Diodes, Inc
979 2nd St. SE
Suite 309
Charlottesville, VA 22902
Phone: 434-297-3257
Fax: 434-297-3258

Certificate of Conformance

To: PCTEST Engineering Laboratory
7185 Oakland Mills Road
Columbia, MD 21046
United States

From: Virginia Diodes, Inc
979 2nd St. SE
Suite 309
Charlottesville, VA 22902

Packing List No: 202695
Shipping Date: 08/12/20

Today's Date: 08/14/20
PO Number: 200414.DP2

Quantity	Shipped	Unit	Description	Order-Job Number
1		EA	VDIWR12.0SAX-M-M6 S/N: SAX 680	20177B-01

The VDI product(s) in this shipment meet(s) the guidelines for performance specifications established in accordance with the corresponding Purchase Order. Data presented in the User Guide, where applicable, has been obtained in accordance with VDI's Quality Management System. All instruments, used to obtain data, which require calibration have been calibrated with equipment traceable to the National Institute of Standards and Technology (NIST) and through NIST to the International System of Units (SI).

Authorized Signature
Virginia Diodes, Inc



Page 1 of 1

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021-01/05/2022	EUT Type: Portable Handset		Page 183 of 198



Virginia Diodes, Inc
979 2nd St. SE
Suite 309
Charlottesville, VA 22902
Phone: 434-297-3257
Fax: 434-297-3258

Certificate of Conformance

To: PCTEST Engineering Laboratory
7185 Oakland Mills Road
Columbia, MD 21046
United States


From: Virginia Diodes, Inc
979 2nd St. SE
Suite 309
Charlottesville, VA 22902

Packing List No: 203623
Shipping Date: 10/22/20

Today's Date: 10/22/20
PO Number: 200414.DP2

Quantity	Shipped	Unit	Description	Order-Job Number
1		EA	VDIWR8.0SAX-M-M9 S/N: SAX 681	20177C-01

The VDI product(s) in this shipment meet(s) the guidelines for performance specifications established in accordance with the corresponding Purchase Order. Data presented in the User Guide, where applicable, has been obtained in accordance with VDI's Quality Management System. All instruments, used to obtain data, which require calibration have been calibrated with equipment traceable to the National Institute of Standards and Technology (NIST) and through NIST to the International System of Units (SI).


Authorized Signature
Virginia Diodes, Inc

Page 1 of 1

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 184 of 198



Virginia Diodes, Inc
979 2nd St. SE
Suite 309
Charlottesville, VA 22902
Phone: 434-297-3257
Fax: 434-297-3258

Certificate of Conformance

To: PCTEST Engineering Laboratory
7185 Oakland Mills Road
Columbia, MD 21046
United States

From: Virginia Diodes, Inc
979 2nd St. SE
Suite 309
Charlottesville, VA 22902

Packing List No: 203281
Shipping Date: 09/24/20

Today's Date: 09/24/20
PO Number: 200414.DP2

Quantity	Shipped	Unit	Description	Order-Job Number
1	EA	VDIWR5.1SAX-M-M18	WR5.1SAX-M-M18 - Mini Spectrum Analyzer Extension Module; SN: SAX 682.	20177D-01

The VDI product(s) in this shipment meet(s) the guidelines for performance specifications established in accordance with the corresponding Purchase Order. Data presented in the User Guide, where applicable, has been obtained in accordance with VDI's Quality Management System. All instruments, used to obtain data, which require calibration have been calibrated with equipment traceable to the National Institute of Standards and Technology (NIST) and through NIST to the International System of Units (SI).


Authorized Signature
Virginia Diodes, Inc

Page 1 of 1

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021-01/05/2022	EUT Type: Portable Handset		Page 185 of 198

9.2 Test Scope Accreditation



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

PCTEST ENGINEERING LABORATORY, LLC
7185 Oakland Mills Road
Columbia, MD 21046
Randy Ortanez Phone: 410 290 6652

ELECTRICAL¹

Valid To: May 31, 2022

Certificate Number: 2041.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory at the location listed above, *as well as the two satellite laboratory locations listed below*, to perform the following Electromagnetic Compatibility, SAR, HAC, Telecommunications, OTA, Battery, RF, and Conformance and Protocol testing of wireless devices:

Test Technology:

Test Method(s)²:

Emissions
Radiated and Conducted

CFR 47, FCC Parts 15B/C/D/E/F/G/H (using ANSI C63.4:2014, ANSI C63.10:2013, ANSI C63.17:2013, and FCC KDB 905462 D02 (v02)), 18 (using MP-5:1986);
ANSI C63.10:2020; KDB 987594;
ETSI TS 134 124 Universal Mobile Telecommunications System (UMTS); (3GPP TS 34.124); (3GPP TS38.124 NR;
Electromagnetic Compatibility (EMC) Requirements for Mobile Terminals and Ancillary Equipment);
ETSI TS 136 124 LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); (3GPP TS 36.124);
ETSI TS 151 010-1 Digital Cellular Telecommunications System (Phase 2+) (GSM);
3GPP TS 51.010-1, Section 12 (Conducted and Radiated Spurious Emissions); EN55011; EN 55032; CNS 13438 (up to 6 GHz);
AS/NZS CISPR 11; IEC/CISPR 11; CISPR 32; FCC OET/MP-5;
ICES-003; KN 11; KN 32; VCCI V-3(2016.11);
VCCI V-3 (2015.04); VCCI 32-1: VCCI-CISPR 32

Accessibility

CFR 47, FCC Part 14

Transmitter/Receiver

RSS 111; RSS 112; RSS 117; RSS 119; RSS 123; RSS 125;
RSS 127; RSS 130; RSS 131; RSS 132; RSS 133; RSS 134;
RSS 135; RSS 137; RSS 139; RSS 140; RSS 141; RSS 142;
RSS 170; RSS 181; RSS 182; RSS 191; RSS 192; RSS 194;
RSS 195; RSS 196; RSS 197; RSS 199; RSS 210; RSS 211;
RSS 213; RSS 215; RSS 216; RSS 220; RSS 222; RSS 236;
RSS 238; RSS 243; RSS 244; RSS 246; RSS 247; RSS 251;
RSS 252; RSS 287; RSS 288; RSS 310; RSS Gen

(A2LA Cert. No. 2041.01) Revised 04/06/2021



Page 1 of 13

5202 Presidents Court, Suite 220 | Frederick, MD 21703-8515 | Phone: 301 644 3248 | Fax: 240 454 9449 | www.A2LA.org

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 186 of 198

Test Technology:

SAR/RF Exposure

Test Method(s) ²:

IEEE 1528-2013; RSS 102 Issue 5 (2015);
EN 50360-2017; EN 62209-1:2016; EN 62209-2:2010;
IEC 62209-1 2nd Edition 2016; IEC 62209-2 2010;
IEC PAS 63083-2017; EN 50566-2017; IEC 62209-2 AMD 1;
Australian Communications Authority Radio Communications
(Electromagnetic Radiation – Human Exposure) Standard 2014;
FCC KDB 248227 D01; FCC KDB 447498 D01, D02, and D03;
FCC KDB 615223 D01; FCC KDB 616217 D04;
FCC KDB 643646 D01; FCC KDB 648474 D03 and D04;
FCC KDB 680106 D01; FCC KDB 865664 D01 and D02;
FCC KDB 941225 D01, D05, D05A, D06, and D07;
EN 50401:2017; EN 50385:2017; IEC 62311:2008;
IEC 62479:2010; EN 62479:2010; EN 50663:2017;
EN 62311:2007; EN 62232:2017; IEC 62232:2017;
IEEE C95.1-2005; IEEE C95.1-1992; IEEE C95.3-2002;
RSS-102 (SAR, RF Exposure, NS), SPR-002; SPR-001;
IEC TR 62630:2010; IEEE C95.3.1:2010; IEC TR 63170:2018;
AS/NZS 2772.2:2016; IEC 62209-3: 2019; IEC 62209-3:2019;
C95.1: 2019; ICNIRP (100KHz – 300 GHz): 2020;
IEC 62311:2019; EN 62311:2020; IEC/IEEE 62209-1528:2020;
RRA Public Notification 2018-18, December 7, 2018

Hearing Aid Compatibility

ANSI C63.19:2007; ANSI C63.19:2011; ANSI C63.19:2019;
CTIA Test Plan for Hearing Aid Compatibility v.3.1.1 (2017);
FCC KDB 285076, D01 & D02; RSS-HAC

United States Radio

47 CFR FCC Parts 20, 22, 24, 25, 27, 30, 73, 74, 80, 87, 90, 95,
96, 97, 101 (using ANSI/TIA-603-E, TIA-102.CAAA-E,
ANSI C63.26:2015); ANSI/TIA-603-D; TIA-102.CAAA-D;
FCC KDB 935210 D03 (v04); FCC KDB 935210 D04 (v02);
FCC KDB 935210 D05 (v01)

European Radio

ETSI EN 302 065-1 Version 2.1.1 (2016-11);
ETSI EN 302 065-2 Version 2.1.1 (2016-11);
ETSI EN 302 065-3 Version 2.1.1 (2016-11);
ETSI EN 302 065-4 Version 1.1.1 (2016-11);
ETSI EN 302 291-1 Version 1.1.1 (2005-07);
ETSI EN 302 291-2 Version 1.1.1 (2005-07);
ETSI EN 302 502 Version 2.1.3 (2017-07);
ETSI EN 302 510-1 Version 1.1.1;
ETSI EN 302 510-2 Version 1.1.1;
ETSI EN 302 537 Version 2.1.1 (2016-10);
ETSI EN 301 511 Version 12.5.1 (2017-03);
ETSI EN 301 839 Version 2.1.1 (2016-04);
ETSI EN 301 893 Version 2.1.1 (2017-05);
ETSI EN 301 893 Version 1.8.1 (2015-03);
ETSI EN 301 908-1 Version 13.1.1 (2019-11);
ETSI EN 301 908-13 Version 13.1.1 (2019-11);
ETSI EN 300 220-1 Version 3.1.1 (2017-02);

(A2LA Cert. No. 2041.01) Revised 04/06/2021



Page 2 of 13

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 187 of 198

Test Technology:

European Radio (cont'd)

Korean Radio

Australia/New Zealand Radio

Licensed Wireless Devices

Wired and Wireless Conformance

5G NR

Test Method(s) ²:

ETSI EN 300 220-2 Version 3.2.1 (2018-06);
ETSI EN 300 328 Version 2.1.1 (2016-11);
ETSI EN 300 328 Version 2.2.2 (2019-07);
ETSI EN 300 330 Version 2.1.1 (2017-02);
ETSI EN 300 440 Version 2. (22.1 (2018-07);
ETSI EN 300 440-2 Version 1.4.1 (2010-08);
KS X 3123, KS X 3142, KS X 3270, KS X 3271;
LP0002; DGT LP0002;

Regulations on Radio Equipment
(MSIT Ordinance MSIT No. 63, Dec. 24, 2020);
Unlicensed Radio Equipment Established Without Notice
(MSIT Public Notification 2020-59, Oct. 16, 2020);
Technical Requirements for the Human Protection against
Electromagnetic Waves
(MSIT Public Notification 2019-4, January 16, 2019);
Equipment to be Subject of the Test Procedure for Electromagnetic
Field Strength and Specific Absorption Rate
(RRA Public Notification 2019-1, January 17, 2019);
Technical Requirements for Radio Equipment for
Telecommunication Services
(RRA Public Notification 2019-9, June 3, 2019);
Technical Requirements for Measurement and Test Procedure of
Specific Absorption Rate
(RRA Public Notification 2018-18, Dec 7, 2018);
Technical Requirements for Measurement of Electromagnetic Field
Strength (RRA Public Notification 2019-3, March 4, 2019)

AS/NZS 4268:2017

ANSI C63.26:2015

3GPP TS 38.508-1; 3GPP TS 38.508-2; 3GPP TS 38.521-1;
3GPP TS 38.521-2; 3GPP TS 38.521-3; 3GPP TS 38.521-4;
3GPP TS 38.522; 3GPP TS 38.523-1; 3GPP TS 38.523-2;
3GPP TS 38.523-3; 3GPP TS 38.533; VZW 5G NR FR2 RFOTA;
VZW 5G Protocol Pre-Conformance (TS 38.523-1);
VZW 5G NR FR1 Supp RF;
VZW 5G NR RF Pre Conformance (TS 38.521-3);
VZW 5G NR Radio Resource Management (RRM)
Pre-Conformance (TS 38.533)

(A2LA Cert. No. 2041.01) Revised 04/06/2021



Page 3 of 13

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 188 of 198

© 2022 PCTEST

V1.0

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Test Technology:
Test Method(s) ²:

LTE

3GPP TS 36.521-1; 3GPP TS 36.521-3; 3GPP TS 36.523-1;
3GPP 37.571-1; 3GPP 37.571-2; 3GPP TS 34.229;
3GPP Carrier Aggregation;
PTCRB NAPRD.03; PTCRB PPMD;
PTCRB Cat-M (per RFT132 eMTC);
PVG.09 LTE Data Throughput & TR 37.901 Data Throughput Performance;
PVG.04 PTCRB Radiated Spurious Emissions;
Global Certification Forum (GCF-CC) Certification / LTE Field Test (TS.11) ³;
3GPP Cat-NB & Cat-M;
MetroPCS Lab Conformance; AT&T LTE Conformance;
AT&T IoT Accelerator Conformance, 19263;
VZW Lab Conformance; VZW Supl RF;
VZW FR2 Supplementary RF, VZW FR1 Supplementary RF;
VZW Supl Signaling Conformance;
VZW Supl RRM;
VZW LTE LBS Performance;
VZW Safe for Network (SFN), VZW Phase 1, VZW Open Development and Field Interoperability Testing (FIT) ³;
VZW Network Extender; VZW PCO; VZW Data Retry;
VZW Data Throughput; VZW SMS; VZW AT Commands;
VZW CMAS; VZW eMBMS; VZW APN; VZW Cat-M VoLTE;
Live Network Extender and Android Test Plan;
Sprint LTE Test Plan; Sprint LTE Safe for Network (SFN);
Sprint LTE Conformance; Sprint LTE IoT;
Sprint Lab Conformance; USCC Lab Conformance;
KDDI LTE Device Testing; SoftBank LTE Testing

WCDMA (UTRA)

3GPP TS 34.121-1; 3GPP TS 34.123-1;
SoftBank Mobile WCDMA Testing

SVLTE / Multimode

CDMA-LTE Inter-RAT (iRAT); CDMA-LTE Inter-RAT SVD;
SVLTE: 1x RF with LTE Data Cal;
SVLTE: LTE RF with 1x Voice Call;
SVD and SVLTE: LTE Data Throughput with 1x Voice Call;
eHRPD; GMSS; SVD GMSS; E911 Data Call Processing;
Stress Testing; RSSI for MM Devices; SVD Interband;
LTE LBS Performance; VZW Multimode Supl Signaling;
VZW Multimode SMS; VZW Multimode Data Retry

VoLTE

IMS VoIP; Rich Communication Services (RCS);
VoLTE to 1xRTT Fallback for SVLTE (1xRTT Fallback);
IMS Registration and Retry; ePDG Live Network;
E911 for VoLTE; VZW hVoLTE;
VZW VoIP and VT Performance;
VZW Interband RRM and Protocol

(A2LA Cert. No. 2041.01) Revised 04/06/2021



Page 4 of 13

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 189 of 198

© 2022 PCTEST

V1.0

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Test Technology:

Carrier Aggregation

UICC

SunSpec Alliance

CBRS (OnGo) / WinnForum

Test Method(s) ²:

VZW Carrier Aggregation Supplementary RF;
VZW Carrier Aggregation Data Throughout

USIM/USAT/CSIM/ISIM Interaction Test Plan
(LTE/WCDMA/GSM/CDMA/MM);
3GPP TS 31.121; 3GPP TS 31.124;
ETSI TS 102 230;
SIM Application Interaction Test Plan;
UICC USIM ISIM Electrical;
UICC USIM ISIM Protocol
(LTE/WCDMA/GSM/CDMA);
SWP/HCI ETSI TS 102 694-1; ETSI TS 102 695-1

SunSpec – CSIP (Common Smart Inverter Profile) Conformance
Test Procedures;
SunSpec – Advanced Function Inverter Test Lab Specification;
SunSpec – UL1741 Supplement SA/Rule 21 Implementation
Guide;
IEEE 2030.5-2018 Smart Energy Profile Application Protocol

CBRS Alliance Certification Test Plan;
WinnForum Conformance and Performance Test Technical
Standards

¹ This accreditation covers testing performed at the main laboratory listed above, and the two satellite laboratories listed below:

(A2LA Cert. No. 2041.01) Revised 04/06/2021



Page 5 of 13

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 190 of 198

© 2022 PCTEST

V1.0

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

PCTEST ENGINEERING LABORATORY, LLC.
7195 Oakland Mills Rd, Suite A
Columbia, MD 21016

Test Technology:

Test Method(s) ²:

Wireless

3GPP2 C.S0011-C 20-Feb-2006 (TIA-98D/E/F)
(excluding Sections 3.2.1.3, 3.2.3.2, 3.3.3, 3.3.4, 3.3.5, 3.3.6, 3.4.6, 3.4.8, 3.4.10, 3.4.11, 3.4.12, 3.4.13, 3.7.2, 4.4.8, 4.4.9.2.1, 4.4.10, 4.4.11);
3GPP2 C.S0043-0 24-Sep-2004 (TIA-1035);
3GPP2 C.S0036-0 11-Mar-2002 (TIA-916);
3GPP2 C.S0036-A 23-May-2011 (TIA-916-A);
3GPP2 C.S0037-0 19-Apr-2002 (TIA-918);
3GPP2 C.S0056-0 22-Jul-2005 (TIA-1042);
3GPP2 C.S0059-0 20-Aug-2008 (TIA-1038);
3GPP2 C.S0060-0 06-Dec-2005 (TIA-1044);
3GPP2 C.S0061-0 22-Jun-2005 (TIA-1045);
3GPP2 C.S0062-0 14-May-2007 (TIA-1046);
3GPP2 C.S0073-0 26-Sep-2005 (TIA-1084);
3GPP2 C.S0073-B 21-Aug-2009 (TIA n/a);
3GPP2 C.S0094-0 30-Oct-2008 (TIA-1157);
CTIA Conformance Test Plan for CDMA Wireless Devices;
GCF Certification Criteria 2 (CAG2) Test Plan;
VZW Wireless Priority Services (WPS);
VZW Safe for Network (SFN);
VZW Open Development (OD) Device Specifications;
VZW Location Based Services (LBS);
VZW CMAS; VZW NBPCD; VZW Phase 1

EVDO

3GPP2 C.S0033-0 12-Dec-2003 (TIA-866);
3GPP2 C.S0033-A 14-Dec-2005 (TIA-866);
3GPP2 C.S0038-0 19-Apr-2002 (TIA-919);
3GPP2 C.S0038-A 26-Sep-2005 (TIA-919);
3GPP2 C.S0038-B 30-Mar-2009 (TIA n/a);
3GPP2 C.S0037-0 19-Apr-2002 (TIA-918);
CTIA Conformance Test Plan for CDMA Wireless Devices;
GCF Certification Criteria 2 (CAG2) Test Plan

(A2LA Cert. No. 2041.01) Revised 04/06/2021



Page 6 of 13

FCC ID: A3LSMS906U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2109090103-06-R1.A3L	Test Dates: 09/16/2021–01/05/2022	EUT Type: Portable Handset		Page 191 of 198

© 2022 PCTEST

V1.0

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.