

APPENDIX L: SAR TEST RESULTS FOR P_{LIMIT} CALCULATIONS

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.
Data highlighted in blue was tested and provided by the manufacturer.

Table L-1
DSI = 0 P_{Limit} Calculations – GPRS 850 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	GPRS 850	GPRS 2 Tx Slots	0	0733M	1:4.15	0.00	836.60	190	30.72	Back	0	0.548	31.1	30.6	27.0
Phablet	GPRS 850	GPRS 2 Tx Slots	0	0733M	1:4.15	0.02	836.60	190	30.72	Front	0	0.606	30.6		
Phablet	GPRS 850	GPRS 2 Tx Slots	0	0733M	1:4.15	-0.09	836.60	190	30.72	Bottom	0	0.451	31.9		
Phablet	GPRS 850	GPRS 2 Tx Slots	0	0733M	1:4.15	-0.10	836.60	190	30.72	Right	0	0.401	32.4		
Phablet	GPRS 850	GPRS 2 Tx Slots	0	0733M	1:4.15	-0.01	836.60	190	30.72	Left	0	0.099	38.5		
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	GPRS 850	GPRS 2 Tx Slots	6	0733M	1:4.15	-0.02	836.60	190	30.62	Back	0	0.993	28.4	27.8	27.8
Phablet	GPRS 850	GPRS 2 Tx Slots	6	0733M	1:4.15	0.01	836.60	190	30.62	Front	0	1.110	27.9		
Phablet	GPRS 850	GPRS 2 Tx Slots	6	0733M	1:4.15	-0.08	836.60	190	30.62	Top	0	0.751	29.6		
Phablet	GPRS 850	GPRS 2 Tx Slots	6	0733M	1:4.15	-0.14	836.60	190	30.62	Right	0	1.140	27.8		

Table L-2
DSI = 0 P_{Limit} Calculations – GPRS 1900 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	GPRS 1900	GPRS 4 Tx Slots	0	1063M	1:2.076	-0.03	1850.20	512	21.13	Back	0	0.976	22.0	21.2	18.8
Phablet	GPRS 1900	GPRS 4 Tx Slots	0	1063M	1:2.076	0.12	1850.20	512	21.13	Front	0	0.884	22.4		
Phablet	GPRS 1900	GPRS 4 Tx Slots	0	1063M	1:2.076	-0.18	1850.20	512	21.13	Bottom	0	1.180	21.2		
Phablet	GPRS 1900	GPRS 4 Tx Slots	0	1063M	1:2.076	0.01	1850.20	512	21.13	Right	0	0.074	33.2		
Phablet	GPRS 1900	GPRS 4 Tx Slots	0	1063M	1:2.076	0.06	1850.20	512	21.13	Left	0	0.042	35.6		

Table L-3
DSI = 0 P_{Limit} Calculations – UMTS 850 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	UMTS 850	RMC	0	0733M	1:1	0.00	826.40	4132	24.26	Back	0	1.260	27.2	27.2	26.4
Phablet	UMTS 850	RMC	0	0733M	1:1	0.00	826.40	4132	24.26	Front	0	1.140	27.6		
Phablet	UMTS 850	RMC	0	0733M	1:1	-0.02	826.40	4132	24.26	Bottom	0	1.040	28.0		
Phablet	UMTS 850	RMC	0	0733M	1:1	-0.06	826.40	4132	24.26	Right	0	0.329	33.0		
Phablet	UMTS 850	RMC	0	0733M	1:1	-0.01	826.40	4132	24.26	Left	0	0.148	36.5		
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	UMTS 850	RMC	6	0733M	1:1	-0.01	826.40	4132	24.44	Back	0	1.360	27.0	25.9	25.9
Phablet	UMTS 850	RMC	6	0733M	1:1	-0.01	826.40	4132	24.44	Front	0	1.750	25.9		
Phablet	UMTS 850	RMC	6	0733M	1:1	0.01	826.40	4132	24.44	Top	0	1.120	27.9		
Phablet	UMTS 850	RMC	6	0733M	1:1	-0.02	826.40	4132	24.44	Right	0	1.740	26.0		

FCC ID: A3LSMS928B	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2308210093-21.A3L	DUT Type: Portable Handset	APPENDIX L: Page 1 of 6

REV 1.1
04/08/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.Info@Element.com.

Table L-4
DSI = 0 P_{Limit} Calculations – UMTS 1750 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	UMTS 1750	RMC	0	1063M	1:1	0.02	1752.60	1513	17.16	Back	0	0.908	21.5	19.9	17.0
Phablet	UMTS 1750	RMC	0	1063M	1:1	0.03	1752.60	1513	17.16	Front	0	0.935	21.4		
Phablet	UMTS 1750	RMC	0	1063M	1:1	0.03	1752.60	1513	17.16	Bottom	0	1.320	19.9		
Phablet	UMTS 1750	RMC	0	1063M	1:1	-0.03	1752.60	1513	17.16	Right	0	0.098	31.2		
Phablet	UMTS 1750	RMC	0	1063M	1:1	0.09	1752.60	1513	17.16	Left	0	0.082	32.0		

Table L-5
DSI = 0 P_{Limit} Calculations – UMTS 1900 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	UMTS 1900	RMC	0	0733M	1:1	0.00	1907.60	9538	17.46	Back	0	1.030	21.3	20.2	17.0
Phablet	UMTS 1900	RMC	0	0733M	1:1	0.05	1907.60	9538	17.46	Front	0	0.907	21.8		
Phablet	UMTS 1900	RMC	0	0733M	1:1	0.00	1907.60	9538	17.46	Bottom	0	1.300	20.2		
Phablet	UMTS 1900	RMC	0	0733M	1:1	-0.14	1907.60	9538	17.46	Right	0	0.081	32.3		
Phablet	UMTS 1900	RMC	0	0733M	1:1	-0.07	1907.60	9538	17.46	Left	0	0.097	31.5		

Table L-6
DSI = 0 P_{Limit} Calculations – LTE Band 12 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 12	10	QPSK	0	0745M	1:1	-0.01	707.50	23095	0.0	23.85	1	0	Back	0	0.717	29.2	27.0	27.0
Phablet	LTE Band 12	10	QPSK	0	0745M	1:1	0.03	707.50	23095	0.0	23.85	1	0	Front	0	0.660	29.6		
Phablet	LTE Band 12	10	QPSK	0	0745M	1:1	0.08	707.50	23095	0.0	23.85	1	0	Bottom	0	0.848	28.5		
Phablet	LTE Band 12	10	QPSK	0	0745M	1:1	-0.01	707.50	23095	0.0	23.85	1	0	Right	0	1.200	27.0		
Phablet	LTE Band 12	10	QPSK	0	0745M	1:1	-0.06	707.50	23095	0.0	23.85	1	0	Left	0	0.064	39.7		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 12	10	QPSK	6	0745M	1:1	-0.10	707.50	23095	0.0	23.20	1	0	Back	0	0.726	28.5	26.6	26.6
Phablet	LTE Band 12	10	QPSK	6	0745M	1:1	-0.04	707.50	23095	0.0	23.20	1	0	Front	0	1.010	27.1		
Phablet	LTE Band 12	10	QPSK	6	0745M	1:1	-0.01	707.50	23095	0.0	23.20	1	0	Top	0	1.090	26.8		
Phablet	LTE Band 12	10	QPSK	6	0745M	1:1	0.05	707.50	23095	0.0	23.20	1	0	Right	0	1.130	26.6		

Table L-7
DSI = 0 P_{Limit} Calculations – LTE Band 13 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 13	10	QPSK	0	0745M	1:1	0.05	782.00	23230	0.0	24.22	1	0	Back	0	1.090	27.8	27.7	26.3
Phablet	LTE Band 13	10	QPSK	0	0745M	1:1	-0.04	782.00	23230	0.0	24.22	1	0	Front	0	1.100	27.7		
Phablet	LTE Band 13	10	QPSK	0	0745M	1:1	-0.08	782.00	23230	0.0	24.22	1	0	Bottom	0	1.070	27.9		
Phablet	LTE Band 13	10	QPSK	0	0745M	1:1	-0.03	782.00	23230	0.0	24.22	1	0	Right	0	0.756	29.4		
Phablet	LTE Band 13	10	QPSK	0	0745M	1:1	0.03	782.00	23230	0.0	24.22	1	0	Left	0	0.153	36.3		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 13	10	QPSK	6	0745M	1:1	-0.02	782.00	23230	0.0	24.28	1	25	Back	0	1.040	28.0	26.4	26.4
Phablet	LTE Band 13	10	QPSK	6	0745M	1:1	0.00	782.00	23230	0.0	24.28	1	25	Front	0	1.520	26.4		
Phablet	LTE Band 13	10	QPSK	6	0745M	1:1	0.01	782.00	23230	0.0	24.28	1	25	Top	0	1.440	26.6		
Phablet	LTE Band 13	10	QPSK	6	0745M	1:1	0.01	782.00	23230	0.0	24.28	1	25	Right	0	1.340	26.9		

FCC ID: A3LSMS928B	PART 0 SAR CHAR REPORT										Approved by: Technical Manager								
Document S/N: 1M2308210093-21.A3L	DUT Type: Portable Handset										APPENDIX L: Page 2 of 6								

Table L-8
DSI = 0 P_{Limit} Calculations – LTE Band 26 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 26	15	QPSK	0	0733M	1:1	0.09	831.50	26865	0.0	23.92	1	0	Back	0	1.170	27.2	27.2	26.4
Phablet	LTE Band 26	15	QPSK	0	0733M	1:1	-0.12	831.50	26865	0.0	23.92	1	0	Front	0	0.889	28.4		
Phablet	LTE Band 26	15	QPSK	0	0733M	1:1	-0.04	831.50	26865	0.0	23.92	1	0	Top	0	0.044	41.4		
Phablet	LTE Band 26	15	QPSK	0	0733M	1:1	0.10	831.50	26865	0.0	23.92	1	0	Right	0	0.586	30.2		
Phablet	LTE Band 26	15	QPSK	0	0733M	1:1	0.02	831.50	26865	0.0	23.92	1	0	Left	0	0.121	37.0		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 26	15	QPSK	6	0738M	1:1	0.00	831.50	26865	0.0	23.95	1	0	Back	0	1.070	27.6	25.9	25.9
Phablet	LTE Band 26	15	QPSK	6	0738M	1:1	-0.07	831.50	26865	0.0	23.95	1	0	Front	0	1.590	25.9		
Phablet	LTE Band 26	15	QPSK	6	0738M	1:1	0.02	831.50	26865	0.0	23.95	1	0	Top	0	0.983	28.0		
Phablet	LTE Band 26	15	QPSK	6	0738M	1:1	-0.08	831.50	26865	0.0	23.95	1	0	Right	0	1.230	27.0		

Table L-9
DSI = 0 P_{Limit} Calculations – LTE Band 66 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 66	20	QPSK	0	0742M	1:1	0.08	1720.00	132072	0.0	17.83	1	50	Back	0	1.040	21.6	20.4	17.5
Phablet	LTE Band 66	20	QPSK	0	0742M	1:1	0.04	1720.00	132072	0.0	17.83	1	50	Front	0	0.970	21.9		
Phablet	LTE Band 66	20	QPSK	0	0742M	1:1	-0.04	1720.00	132072	0.0	17.83	1	50	Bottom	0	1.370	20.4		
Phablet	LTE Band 66	20	QPSK	0	0742M	1:1	0.02	1720.00	132072	0.0	17.83	1	50	Right	0	0.141	30.3		
Phablet	LTE Band 66	20	QPSK	0	0742M	1:1	0.02	1720.00	132072	0.0	17.83	1	50	Left	0	0.089	32.3		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 66	20	QPSK	7	0742M	1:1	-0.02	1770.00	132572	0.0	19.72	1	50	Back	0	0.994	23.7	20.7	20.0
Phablet	LTE Band 66	20	QPSK	7	0742M	1:1	-0.06	1770.00	132572	0.0	19.72	1	50	Front	0	0.835	24.4		
Phablet	LTE Band 66	20	QPSK	7	0742M	1:1	0.02	1770.00	132572	0.0	19.72	1	50	Top	0	1.950	20.7		
Phablet	LTE Band 66	20	QPSK	7	0742M	1:1	0.04	1770.00	132572	0.0	19.72	1	50	Left	0	0.243	29.8		

Table L-10
DSI = 0 P_{Limit} Calculations – LTE Band 25 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 25	20	QPSK	0	0733M	1:1	-0.02	1860.00	26140	0.0	17.45	1	99	Back	0	0.883	21.9	19.8	17.5
Phablet	LTE Band 25	20	QPSK	0	0733M	1:1	0.04	1860.00	26140	0.0	17.45	1	99	Front	0	0.835	22.2		
Phablet	LTE Band 25	20	QPSK	0	0733M	1:1	-0.02	1860.00	26140	0.0	17.45	1	99	Bottom	0	1.440	19.8		
Phablet	LTE Band 25	20	QPSK	0	0733M	1:1	0.04	1860.00	26140	0.0	17.45	1	99	Right	0	0.077	32.5		
Phablet	LTE Band 25	20	QPSK	0	0733M	1:1	-0.02	1860.00	26140	0.0	17.45	1	99	Left	0	0.092	31.7		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 25	20	QPSK	7	0733M	1:1	0.02	1860.00	26140	0.0	20.58	50	0	Back	0	1.430	23.0	20.5	20.5
Phablet	LTE Band 25	20	QPSK	7	0733M	1:1	0.00	1860.00	26140	0.0	20.58	50	0	Front	0	1.410	23.0		
Phablet	LTE Band 25	20	QPSK	7	0073M	1:1	0.02	1860.00	26140	0.0	20.58	50	0	Top	0	2.540	20.5		
Phablet	LTE Band 25	20	QPSK	7	0733M	1:1	0.00	1860.00	26140	0.0	20.58	50	0	Left	0	0.202	31.5		

FCC ID: A3LSMS928B	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2308210093-21.A3L	DUT Type: Portable Handset	APPENDIX L: Page 3 of 6

Table L-11
DSI = 0 P_{Limit} Calculations – LTE Band 41 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 41	20	QPSK	1	1069M	1:1.58	0.00	2636.50	41055	0.0	21.94	1	50	Back	0	2.600	19.7	19.3	19.0
Phablet	LTE Band 41	20	QPSK	1	1069M	1:1.58	-0.04	2636.50	41055	0.0	21.94	1	50	Front	0	1.770	21.4		
Phablet	LTE Band 41	20	QPSK	1	1069M	1:1.58	0.01	2636.50	41055	0.0	21.94	1	50	Bottom	0	2.850	19.3		
Phablet	LTE Band 41	20	QPSK	1	1069M	1:1.58	-0.06	2636.50	41055	0.0	21.94	1	50	Right	0	2.030	20.8		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 41	20	QPSK	7	1069M	1:1.58	0.00	2636.50	41055	0.0	21.98	50	25	Back	0	1.130	23.4	19.5	19.0
Phablet	LTE Band 41	20	QPSK	7	1069M	1:1.58	-0.04	2636.50	41055	0.0	21.98	50	25	Front	0	1.450	22.3		
Phablet	LTE Band 41	20	QPSK	7	1069M	1:1.58	0.00	2636.50	41055	0.0	21.98	50	25	Top	0	2.780	19.5		
Phablet	LTE Band 41	20	QPSK	7	1069M	1:1.58	0.06	2636.50	41055	0.0	21.98	50	25	Left	0	0.234	30.2		

Table L-12
DSI = 0 P_{Limit} Calculations – NR Band n5 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n5	20	QPSK	0	1092M	1:1	-0.08	836.50	167300	DFT-s-OFDM	0.0	23.35	1	1	Back	0	1.210	26.5	26.5	25.7
Phablet	NR Band n5	20	QPSK	0	1092M	1:1	0.01	836.50	167300	DFT-s-OFDM	0.0	23.35	1	1	Front	0	1.090	26.9		
Phablet	NR Band n5	20	QPSK	0	1092M	1:1	0.04	836.50	167300	DFT-s-OFDM	0.0	23.35	1	1	Bottom	0	0.955	27.5		
Phablet	NR Band n5	20	QPSK	0	1092M	1:1	-0.12	836.50	167300	DFT-s-OFDM	0.0	23.35	1	1	Right	0	0.813	28.2		
Phablet	NR Band n5	20	QPSK	0	1092M	1:1	-0.02	836.50	167300	DFT-s-OFDM	0.0	23.35	1	1	Left	0	0.165	35.1		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n5	20	QPSK	6	1092M	1:1	-0.02	836.50	167300	DFT-s-OFDM	0.0	23.18	50	28	Back	0	0.991	27.1	26.0	25.9
Phablet	NR Band n5	20	QPSK	6	1092M	1:1	-0.05	836.50	167300	DFT-s-OFDM	0.0	23.18	50	28	Front	0	1.290	26.0		
Phablet	NR Band n5	20	QPSK	6	1092M	1:1	-0.06	836.50	167300	DFT-s-OFDM	0.0	23.18	50	28	Top	0	0.890	27.6		
Phablet	NR Band n5	20	QPSK	6	1092M	1:1	-0.05	836.50	167300	DFT-s-OFDM	0.0	23.18	50	28	Right	0	1.200	26.3		

Table L-13
DSI = 0 P_{Limit} Calculations – NR Band n66 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n66	40	QPSK	0	0744M	1:1	0.04	1745.00	349000	DFT-s-OFDM	0.0	17.66	1	1	Back	0	1.660	19.4	18.8	17.0
Phablet	NR Band n66	40	QPSK	0	0744M	1:1	0.10	1745.00	349000	DFT-s-OFDM	0.0	17.66	1	1	Front	0	1.310	20.4		
Phablet	NR Band n66	40	QPSK	0	0744M	1:1	0.07	1745.00	349000	DFT-s-OFDM	0.0	17.66	1	1	Bottom	0	1.910	18.8		
Phablet	NR Band n66	40	QPSK	0	0744M	1:1	0.21	1745.00	349000	DFT-s-OFDM	0.0	17.66	1	1	Right	0	0.177	29.1		
Phablet	NR Band n66	40	QPSK	0	0744M	1:1	-0.10	1745.00	349000	DFT-s-OFDM	0.0	17.66	1	1	Left	0	0.162	29.5		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n66	40	QPSK	7	0744M	1:1	0.17	1745.00	349000	CP-OFDM	0.0	20.59	1	1	Back	0	1.060	24.3	20.4	20.0
Phablet	NR Band n66	40	QPSK	7	0744M	1:1	-0.12	1745.00	349000	CP-OFDM	0.0	20.59	1	1	Front	0	1.310	23.3		
Phablet	NR Band n66	40	QPSK	7	0744M	1:1	-0.37	1745.00	349000	CP-OFDM	0.0	20.59	1	1	Top	0	2.570	20.4		
Phablet	NR Band n66	40	QPSK	7	0744M	1:1	0.10	1745.00	349000	CP-OFDM	0.0	20.59	1	1	Left	0	0.265	30.3		

Table L-14
DSI = 0 P_{Limit} Calculations – NR Band n25 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n25	40	QPSK	0	0737M	1:1	-0.07	1882.50	376500	CP-OFDM	0.0	18.21	1	1	Back	0	0.930	22.5	20.8	17.5
Phablet	NR Band n25	40	QPSK	0	0737M	1:1	-0.02	1882.50	376500	CP-OFDM	0.0	18.21	1	1	Front	0	0.878	22.7		
Phablet	NR Band n25	40	QPSK	0	0737M	1:1	0.05	1882.50	376500	CP-OFDM	0.0	18.21	1	1	Bottom	0	1.360	20.8		
Phablet	NR Band n25	40	QPSK	0	0737M	1:1	-0.11	1882.50	376500	CP-OFDM	0.0	18.21	1	1	Right	0	0.043	35.8		
Phablet	NR Band n25	40	QPSK	0	0737M	1:1	-0.02	1882.50	376500	CP-OFDM	0.0	18.21	1	1	Left	0	0.097	32.3		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n25	40	QPSK	7	0737M	1:1	-0.01	1882.50	376500	DFT-s-OFDM	0.0	20.85	108	54	Back	0	0.856	25.5	20.8	20.5
Phablet	NR Band n25	40	QPSK	7	0737M	1:1	-0.08	1882.50	376500	DFT-s-OFDM	0.0	20.85	108	54	Front	0	1.370	23.4		
Phablet	NR Band n25	40	QPSK	7	0737M	1:1	-0.09	1882.50	376500	DFT-s-OFDM	0.0	20.85	108	54	Top	0	2.510	20.8		
Phablet	NR Band n25	40	QPSK	7	0737M	1:1	0.10	1882.50	376500	DFT-s-OFDM	0.0	20.85	108	54	Left	0	0.204	31.7		

FCC ID: A3LSMS928B	PART 0 SAR CHAR REPORT															Approved by: Technical Manager				
Document S/N: 1M2308210093-21.A3L	DUT Type: Portable Handset															APPENDIX L: Page 4 of 6				

Table L-15
DSI = 0 P_{Limit} Calculations – NR Band n41 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n41	100	QPSK	7	1062M	1:1	0.00	2592.99	518598	DFT-s-OFDM	0.0	19.71	1	137	Back	0	1.010	23.6	19.0	19.0
Phablet	NR Band n41	100	QPSK	7	1062M	1:1	-0.08	2592.99	518598	DFT-s-OFDM	0.0	19.71	1	137	Front	0	1.540	21.8		
Phablet	NR Band n41	100	QPSK	7	1062M	1:1	0.06	2592.99	518598	DFT-s-OFDM	0.0	19.71	1	137	Top	0	2.930	19.0		
Phablet	NR Band n41	100	QPSK	7	1062M	1:1	0.13	2592.99	518598	DFT-s-OFDM	0.0	19.71	1	137	Left	0	0.207	30.5		
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n41	100	1	1062M	1:1	0.07	2592.99	518598	CW/SRS	20.35	Back	0	1.640	22.1	20.2	20.0				
Phablet	NR Band n41	100	1	1062M	1:1	-0.04	2592.99	518598	CW/SRS	20.35	Front	0	1.680	22.0						
Phablet	NR Band n41	100	1	1062M	1:1	0.17	2592.99	518598	CW/SRS	20.35	Bottom	0	2.550	20.2						
Phablet	NR Band n41	100	1	1062M	1:1	0.04	2592.99	518598	CW/SRS	20.35	Right	0	1.490	22.5						
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n41	100	6	1062M	1:1	0.00	2592.99	518598	CW/SRS	20.42	Back	0	0.764	25.5	21.7	20.0				
Phablet	NR Band n41	100	6	1062M	1:1	-0.10	2592.99	518598	CW/SRS	20.42	Front	0	1.170	23.7						
Phablet	NR Band n41	100	6	1062M	1:1	0.19	2592.99	518598	CW/SRS	20.42	Top	0	0.694	25.9						
Phablet	NR Band n41	100	6	1062M	1:1	0.18	2592.99	518598	CW/SRS	20.42	Right	0	1.830	21.7						
Phablet	NR Band n41	100	6	1062M	1:1	0.23	2592.99	518598	CW/SRS	20.42	Left	0	0.025	40.4						
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n41	100	3	1062M	1:1	-0.05	2592.99	518598	CW/SRS	20.48	Back	0	1.390	23.0	23.0	20.0				
Phablet	NR Band n41	100	3	1062M	1:1	0.14	2592.99	518598	CW/SRS	20.48	Front	0	0.218	31.0						
Phablet	NR Band n41	100	3	1062M	1:1	-0.37	2592.99	518598	CW/SRS	20.48	Bottom	0	0.143	32.9						
Phablet	NR Band n41	100	3	1062M	1:1	-0.13	2592.99	518598	CW/SRS	20.48	Left	0	0.055	37.0						

Table L-16
DSI = 0 P_{Limit} Calculations – NR Band n77 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n77 DoD	100	QPSK	7	06468	1:1	0.03	3500.01	633334	DFT-s-OFDM	0.0	20.14	1	1	Back	0	0.925	24.4	23.0	20.0
Phablet	NR Band n77	100	QPSK	7	06468	1:1	0.02	3930.00	662000	DFT-s-OFDM	0.0	20.06	1	271	Back	0	1.260	23.0		
Phablet	NR Band n77	100	QPSK	7	06468	1:1	-0.04	3930.00	662000	DFT-s-OFDM	0.0	20.06	1	271	Front	0	0.655	25.8		
Phablet	NR Band n77	100	QPSK	7	06468	1:1	-0.18	3930.00	662000	DFT-s-OFDM	0.0	20.06	1	271	Top	0	0.917	24.4		
Phablet	NR Band n77	100	QPSK	7	06468	1:1	0.06	3930.00	662000	DFT-s-OFDM	0.0	20.06	1	271	Left	0	0.261	29.8		
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n77	100	2	1092M	1:1	0.10	3750.00	650000	CW/SRS	17.73	Back	0	1.190	20.9	18.2	17.0				
Phablet	NR Band n77	100	2	1092M	1:1	-0.01	3750.00	650000	CW/SRS	17.73	Front	0	0.724	23.1						
Phablet	NR Band n77	100	2	1092M	1:1	0.00	3750.00	650000	CW/SRS	17.73	Bottom	0	0.381	25.9						
Phablet	NR Band n77 DoD	100	2	1092M	1:1	-0.19	3500.01	633334	CW/SRS	17.82	Right	0	2.290	18.2						
Phablet	NR Band n77	100	2	1092M	1:1	-0.11	3750.00	650000	CW/SRS	17.73	Right	0	1.500	19.9						
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n77 DoD	100	10	1092M	1:1	-0.01	3500.01	633334	CW/SRS	17.07	Back	0	0.402	25.0	23.4	17.0				
Phablet	NR Band n77	100	10	1092M	1:1	0.04	3750.00	650000	CW/SRS	17.08	Back	0	0.492	24.1						
Phablet	NR Band n77	100	10	1092M	1:1	-0.05	3750.00	650000	CW/SRS	17.08	Front	0	0.578	23.4						
Phablet	NR Band n77	100	10	1092M	1:1	-1.58	3750.00	650000	CW/SRS	17.08	Top	0	0.006	43.2						
Phablet	NR Band n77	100	10	1092M	1:1	-0.03	3750.00	650000	CW/SRS	17.08	Left	0	0.165	28.8						
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n77 DoD	100	3	10922M	1:1	0.03	3500.01	633334	CW/SRS	19.78	Back	0	2.630	19.5	19.5	19.0				
Phablet	NR Band n77	100	3	1092M	1:1	-0.05	3750.00	650000	CW/SRS	18.62	Back	0	1.820	19.9						
Phablet	NR Band n77	100	3	1092M	1:1	-0.25	3750.00	650000	CW/SRS	18.62	Front	0	0.077	33.7						
Phablet	NR Band n77	100	3	1092M	1:1	0.00	3750.00	650000	CW/SRS	18.62	Bottom	0	0.194	29.7						
Phablet	NR Band n77	100	3	1092M	1:1	-0.15	3750.00	650000	CW/SRS	18.62	Left	0	0.027	38.2						

FCC ID: A3LSMS928B	PART 0 SAR CHAR REPORT										Approved by: Technical Manager									
Document S/N: 1M2308210093-21.A3L	DUT Type: Portable Handset										APPENDIX L: Page 5 of 6									

Table L-17
DSI = 0 P_{Limit} Calculations – 2.4 GHz WLAN Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	9	1110M	98.88	-0.01	2437.00	6	1	18.78	Back	0	0.863	23.3	20.6	19.8	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	9	1110M	98.88	-0.02	2437.00	6	1	18.78	Front	0	0.661	24.5			
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	9	1110M	98.88	-0.02	2437.00	6	1	18.78	Top	0	0.344	27.3			
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	9	1110M	98.88	-0.03	2437.00	6	1	18.78	Left	0	1.590	20.6			
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	11	1110M	98.85	-0.01	2462.00	11	1	18.69	Back	0	0.317	27.6	26.7	22.2	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	11	1110M	98.85	0.03	2462.00	11	1	18.69	Front	0	0.386	26.7			
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	11	1110M	98.85	0.29	2462.00	11	1	18.69	Top	0	0.009	43.0			
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	11	1110M	98.85	0.03	2462.00	11	1	18.69	Right	0	0.132	31.4			
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Conducted Power (2nd ant) [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	MIMO	1110M	98.87	0.02	2462.00	11	6.5	18.61	18.08	Back	10	1.160	21.3	18.6	18.5
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	MIMO	1110M	98.87	0.00	2462.00	11	6.5	18.61	18.08	Front	10	1.070	21.7		
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	MIMO	1110M	98.87	0.01	2462.00	11	6.5	18.61	18.08	Top	10	0.347	26.6		
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	MIMO	1110M	98.87	0.02	2462.00	11	6.5	18.61	18.08	Right	10	0.138	30.6		
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	MIMO	1110M	98.87	0.01	2462.00	11	6.5	18.61	18.08	Left	10	2.180	18.6		

Note: To achieve the 22 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 19 dBm.

Note: To achieve the 22 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 19 dBm.

Table L-18
DSI = 0 P_{Limit} Calculations – 2.4 GHz Bluetooth Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	2.4 GHz Bluetooth	FHSS	9	1110M	77.05	0.03	2441.00	39	1	18.81	Back	0	0.697	23.2	20.0	19.8
Phablet	2.4 GHz Bluetooth	FHSS	9	1110M	77.05	0.02	2441.00	39	1	18.81	Front	0	0.736	22.9		
Phablet	2.4 GHz Bluetooth	FHSS	9	1110M	77.05	-0.33	2441.00	39	1	18.81	Top	0	0.297	26.9		
Phablet	2.4 GHz Bluetooth	FHSS	9	1110M	77.05	-0.01	2441.00	39	1	18.81	Left	0	1.460	20.0		

FCC ID: A3LSMS928B	PART 0 SAR CHAR REPORT										Approved by: Technical Manager						
Document S/N: 1M2308210093-21.A3L	DUT Type: Portable Handset										APPENDIX L: Page 6 of 6						

REV 1.1
04/08/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.Info@Element.com.