TEST REPORT

FCC LTE B66(4) Test for SC-51F
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2412-FC009

DATE OF ISSUE
December 3, 2024

Tested by
Jae Ryang Do

Technical Manager
Jong Seok Lee

HCT CO., LTD.
BongJai Huh / CEO

The report shall not be (partly) reproduced except in full without approval of the laboratory.
HCT CO., LTD. 2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea Tel. +82 31 645 6300 Fax. +82 31 645 6401

HCT CO.,LTD.
2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.
HCT-RF-2412-FC009

DATE OF ISSUE
December 3, 2024

Additional Model
SCG31

Applicant	**SAMSUNG Electronics Co., Ltd.** 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Product Name Model Name	Mobile Phone SC-51F
Date of Test	October 10, 2024 ~ December 02, 2024
FCC ID	A3LSMS931JPN
Location of Test	■ Permanent Testing Lab ☐ On Site Testing (Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
Test Standard Used	FCC Rule Part: § 27
Test Results	PASS

The report shall not be (partly) reproduced except in full without approval of the laboratory.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	December 3, 2024	Initial Release

Notice

Content
The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)
The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated. The test results have only been applied with the test methods required by the standard(s).
The laboratory is not accredited for the test results marked *. Information provided by the applicant is marked **. Test results provided by external providers are marked ***.
When confirmation of authenticity of this test report is required, please contact www.hct.co.kr
The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

The report shall not be (partly) reproduced except in full without approval of the laboratory.

CONTENTS

1. GENERAL INFORMATION 5
1.1. MAXIMUM OUTPUT POWER 6
2. INTRODUCTION 7
2.1. DESCRIPTION OF EUT 7
2.2. MEASURING INSTRUMENT CALIBRATION 7
2.3. TEST FACILITY 7
3. DESCRIPTION OF TESTS 8
3.1 TEST PROCEDURE 8
3.2 RADIATED POWER 9
3.3 RADIATED SPURIOUS EMISSIONS 10
3.4 PEAK- TO- AVERAGE RATIO 11
3.5 OCCUPIED BANDWIDTH. 13
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL 14
3.7 BAND EDGE 15
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE 17
3.9 WORST CASE(RADIATED TEST) 18
3.10 WORST CASE(CONDUCTED TEST) 19
4. LIST OF TEST EQUIPMENT 20
5. MEASUREMENT UNCERTAINTY 21
6. SUMMARY OF TEST RESULTS 22
7. SAMPLE CALCULATION 23
8. TEST DATA(Main 1 ANT) 25
8.1 EQUIVALENT ISOTROPIC RADIATED POWER 25
8.2 RADIATED SPURIOUS EMISSIONS 28
8.3 PEAK-TO-AVERAGE RATIO 29
8.4 OCCUPIED BANDWIDTH 30
8.5 CONDUCTED SPURIOUS EMISSIONS 31
8.6 BAND EDGE 31
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE 32
9. TEST PLOTS(Main 1 ANT) 50
10. ANNEX A_ TEST SETUP PHOTO 159

The report shall not be (partly) reproduced except in full without approval of the laboratory.

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMS931JPN
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§ 27
EUT Type:	Mobile phone
Model(s):	SC-51F
Additional Model(s)	SCG31
Tx Frequency:	1710.7 MHz – 1779.3 MHz (LTE – Band 66/4 (1.4 MHz)) 1711.5 MHz – 1778.5 MHz (LTE – Band 66/4 (3 MHz)) 1712.5 MHz – 1777.5 MHz (LTE – Band 66/4 (5 MHz)) 1715.0 MHz – 1775.0 MHz (LTE – Band 66/4 (10 MHz)) 1717.5 MHz – 1772.5 MHz (LTE – Band 66/4 (15 MHz)) 1720.0 MHz – 1770.0 MHz (LTE – Band 66/4 (20 MHz))
Date(s) of Tests:	October 10, 2024 ~ December 02, 2024
Serial number:	Radiated : R3CX90KCEGH Conducted : R3CX9061K4F

The report shall not be (partly) reproduced except in full without approval of the laboratory.

1.1. MAXIMUM OUTPUT POWER

Main 1 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band66/4 (1.4)	1710.7 – 1779.3	1M10G7D	QPSK	0.222	23.46
		1M10W7D	16QAM	0.189	22.76
		1M10W7D	64QAM	0.147	21.68
LTE – Band66/4 (3)	1711.5 – 1778.5	2M73G7D	QPSK	0.224	23.50
		2M72W7D	16QAM	0.189	22.77
		2M72W7D	64QAM	0.146	21.65
LTE – Band66/4 (5)	1712.5 – 1777.5	4M52G7D	QPSK	0.223	23.49
		4M51W7D	16QAM	0.187	22.71
		4M50W7D	64QAM	0.143	21.54
LTE – Band66/4 (10)	1715.0 – 1775.0	9M02G7D	QPSK	0.232	23.65
		9M00W7D	16QAM	0.195	22.89
		9M00W7D	64QAM	0.152	21.82
LTE – Band66/4 (15)	1717.5 – 1772.5	13M5G7D	QPSK	0.239	23.78
		13M5W7D	16QAM	0.195	22.91
		13M5W7D	64QAM	0.154	21.88
LTE – Band66/4 (20)	1720.0 – 1770.0	18M0G7D	QPSK	0.246	23.91
		18M0W7D	16QAM	0.207	23.16
		18M0W7D	64QAM	0.160	22.05

The report shall not be (partly) reproduced except in full without approval of the laboratory.

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE, Sub 6
It also supports IEEE 802.11 a/b/g/n/ac/ax/be (20/40/80/160/320 MHz), Bluetooth(iPA, ePA), BT LE(iPA, ePA), NFC, WPT, WIFI 6E.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea.**

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.
The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW ≥ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.
   The power is calculated by the following formula;

$$P_{d\ (dBm)} = Pg_{(dBm)} - \text{cable loss}_{(dB)} + \text{antenna gain}_{(dB)}$$

   Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.
3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.
   These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW ≥ 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points > 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10^{th} harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.
   The spurious emissions is calculated by the following formula;

$$\text{Result}_{(dBm)} = \text{Pg}_{(dBm)} - \text{cable loss}_{(dB)} + \text{antenna gain}_{(dBi)}$$

   Where: P_g is the generator output power into the substitution antenna.

   If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(dBm)} = \text{ERP}_{(dBm)} + 2.15$$

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
   .- for continuous transmissions, set to 1 ms,
   .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as as P_{Pk}.

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg}. Determine the P.A.R. from:

$$P.A.R_{(dB)} = P_{Pk(dBm)} - P_{Avg(dBm)} \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Test Settings(Peak Power)

The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW ≥ 3 × RBW.

1. Set the RBW ≥ OBW.
2. Set VBW ≥ 3 × RBW.
3. Set span ≥ 2 × OBW.
4. Sweep time ≥ 10 × (number of points in sweep) × (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to 2 × to 3 × the OBW.
2. Set RBW ≥ OBW.
3. Set VBW ≥ 3 × RBW.
4. Set number of measurement points in sweep ≥ 2 × span / RBW.
5. Sweep time:
   Set ≥ [10 × (number of points in sweep) × (transmission period)] for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add [10 log (1/duty cycle)] to the measured maximum power level to compute the average power during continuous transmission. For example, add [10 log (1/0.25)] = 6 dB if the duty cycle is a constant 25 %.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.
The EUT makes a call to the communication simulator.
The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.
Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW ≥ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW ≥ 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep ≥ 2 x Span / RBW

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points ≥ 2 x Span/RBW
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Test Notes

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.
All measurements were done at 2 channels(low and high operational frequency range.)
The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where Margin < 1 dB the emission level is either corrected by 10 log(1 MHz/ RB) or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.
The frequency stability of the transmitter is measured by:

1. Temperature:
   The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.
2. Primary Supply Voltage:
   .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
   .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter.
   Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
  Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
  Worst case : Stand alone
- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.
  Therefore, only the worst case(stand-alone) results were reported.
- In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported. (Worst case : 20 MHz)
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- LTE Band 66 (1710 – 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz) and they have the same Tune-up power. Therefore, test data provided in this report covers Band 4 as well as Band 66.
- SC-51F & additional models were tested and the worst case results are reported.
  (Worst case : SC-51F)

[Main 1 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM,	See Section 8.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 8.2		Z

The report shall not be (partly) reproduced except in full without approval of the laboratory.

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.
- LTE Band 66 (1710 – 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz) and they have the same Tune-up power. Therefore, test data provided in this report covers Band 4 as well as Band 66.
- SC-51F & additional models were tested and the worst case results are reported.
(Worst case : SC-51F)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM,	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM,	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Band Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		1.4, 3, 5, 10, 15, 20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	1.4, 3, 5, 10, 15, 20	Low, Mid, High	1	0

The report shall not be (partly) reproduced except in full without approval of the laboratory.

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	Switch box(1.2 G HPF+LNA)	HCT CO., LTD.,	F1L1	11/11/2025	Annual
RF Switching System	Switch box(3.3 G HPF+LNA)	HCT CO., LTD.,	F1L2	11/11/2025	Annual
RF Switching System	Switch box(LNA)	HCT CO., LTD.,	F1L4	11/11/2025	Annual
RF Switching System	Switch box(6 G HPF+LNA)	HCT CO., LTD.,	F1L7	11/11/2025	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/17/2025	Annual
DC Power Supply	E3632A	Agilent	MY40010147	08/06/2025	Annual
Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Dipole Antenna	UHAP	Schwarzbeck	01288	08/07/2026	Biennial
Chamber	SU-642	ESPEC	93008124	02/19/2025	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	147	08/17/2025	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1298	09/11/2025	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/19/2025	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/17/2025	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	REOHDE & SCHWARZ	100931	08/06/2025	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/05/2025	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/07/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	08/28/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	08/19/2026	Biennial
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262094331	11/13/2025	Annual
Wideband Radio Communication Tester	MT8820C	Anritsu Corp.	6201026545	11/20/2025	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/26/2025	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/17/2025	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

The report shall not be (partly) reproduced except in full without approval of the laboratory.

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (±dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.98 (Confidence level about 95 %, k=2)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, k=2)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.70 (Confidence level about 95 %, k=2)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.52 (Confidence level about 95 %, k=2)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.66 (Confidence level about 95 %, k=2)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, k=2)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(h)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	See Note1
Peak- to- Average Ratio	§ 27.50(d)(5)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. See SAR Report

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 27.50(d)(4)	< 1 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(h)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
2) During the test, the turn table is rotated until the maximum signal is found.
3) Record the field strength meter's level.
4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
2) During the test, the turn table is rotated until the maximum signal is found.
3) Record the field strength meter's level.
4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

The report shall not be (partly) reproduced except in full without approval of the laboratory.

8. TEST DATA(Main 1 ANT)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1710.7	LTE B66/B4 1.4 MHz	QPSK	-18.15	15.22	10.04	2.06	H	< 1.00	0.209	23.20	1	5
		16-QAM	-18.69	14.68	10.04	2.06	H		0.185	22.66		
		64-QAM	-19.83	13.54	10.04	2.06	H		0.142	21.52		
1745.0		QPSK	-18.11	15.35	10.18	2.07	H		0.222	23.46	1	0
		16-QAM	-18.81	14.65	10.18	2.07	H		0.189	22.76		
		64-QAM	-19.89	13.57	10.18	2.07	H		0.147	21.68		
1779.3		QPSK	-19.51	14.31	10.26	2.09	H		0.177	22.48	1	0
		16-QAM	-20.18	13.64	10.26	2.09	H		0.152	21.81		
		64-QAM	-21.27	12.55	10.26	2.09	H		0.118	20.72		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1711.5	LTE B66/B4 3 MHz	QPSK	-18.07	15.30	10.04	2.06	H	< 1.00	0.213	23.28	1	14
		16-QAM	-18.85	14.52	10.04	2.06	H		0.178	22.50		
		64-QAM	-19.97	13.40	10.04	2.06	H		0.137	21.38		
1745.0		QPSK	-18.07	15.39	10.18	2.07	H		0.224	23.50	1	0
		16-QAM	-18.80	14.66	10.18	2.07	H		0.189	22.77		
		64-QAM	-19.92	13.54	10.18	2.07	H		0.146	21.65		
1778.5		QPSK	-19.40	14.42	10.26	2.09	H		0.182	22.59	1	0
		16-QAM	-20.11	13.71	10.26	2.09	H		0.154	21.88		
		64-QAM	-21.25	12.57	10.26	2.09	H		0.119	20.74		

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1712.5	LTE B66/B4 5 MHz	QPSK	-17.99	15.40	10.06	2.06	H	< 1.00	0.219	23.40	1	24
		16-QAM	-18.76	14.63	10.06	2.06	H		0.183	22.63		
		64-QAM	-19.92	13.47	10.06	2.06	H		0.140	21.47		
1745.0		QPSK	-18.08	15.38	10.18	2.07	H		0.223	23.49	1	0
		16-QAM	-18.86	14.60	10.18	2.07	H		0.187	22.71		
		64-QAM	-20.03	13.43	10.18	2.07	H		0.143	21.54		
1777.5		QPSK	-19.27	14.55	10.26	2.09	H		0.187	22.72	1	0
		16-QAM	-19.98	13.84	10.26	2.09	H		0.159	22.01		
		64-QAM	-21.09	12.73	10.26	2.09	H		0.123	20.90		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1715.0	LTE B66/B4 10 MHz	QPSK	-17.92	15.47	10.06	2.06	H	< 1.00	0.222	23.47	1	49
		16-QAM	-18.71	14.68	10.06	2.06	H		0.185	22.68		
		64-QAM	-19.82	13.57	10.06	2.06	H		0.144	21.57		
1745.0		QPSK	-17.92	15.54	10.18	2.07	H		0.232	23.65	1	0
		16-QAM	-18.68	14.78	10.18	2.07	H		0.195	22.89		
		64-QAM	-19.75	13.71	10.18	2.07	H		0.152	21.82		
1775.0		QPSK	-18.86	14.90	10.25	2.09	H		0.202	23.06	1	0
		16-QAM	-19.72	14.04	10.25	2.09	H		0.166	22.20		
		64-QAM	-20.81	12.95	10.25	2.09	H		0.129	21.11		

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1717.5	LTE B66/B4 15 MHz	QPSK	-17.78	15.64	10.08	2.06	H	< 1.00	0.232	23.66	1	74
		16-QAM	-18.59	14.83	10.08	2.06	H		0.193	22.85		
		64-QAM	-19.68	13.74	10.08	2.06	H		0.150	21.76		
1745.0		QPSK	-17.79	15.67	10.18	2.07	H		0.239	23.78	1	0
		16-QAM	-18.66	14.80	10.18	2.07	H		0.195	22.91		
		64-QAM	-19.69	13.77	10.18	2.07	H		0.154	21.88		
1772.5		QPSK	-18.77	14.99	10.25	2.09	H		0.207	23.15	1	0
		16-QAM	-19.54	14.22	10.25	2.09	H		0.173	22.38		
		64-QAM	-20.62	13.14	10.25	2.09	H		0.135	21.30		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1720.0	LTE B66/B4 20 MHz	QPSK	-17.53	15.89	10.08	2.06	H	< 1.00	0.246	23.91	1	99
		16-QAM	-18.28	15.14	10.08	2.06	H		0.207	23.16		
		64-QAM	-19.39	14.03	10.08	2.06	H		0.160	22.05		
1745.0		QPSK	-17.70	15.76	10.18	2.07	H		0.244	23.87	1	0
		16-QAM	-18.55	14.91	10.18	2.07	H		0.200	23.02		
		64-QAM	-19.63	13.83	10.18	2.07	H		0.156	21.94		
1770.0		QPSK	-18.75	14.95	10.24	2.09	H		0.204	23.10	1	0
		16-QAM	-19.51	14.19	10.24	2.09	H		0.171	22.34		
		64-QAM	-20.54	13.16	10.24	2.09	H		0.135	21.31		

The report shall not be (partly) reproduced except in full without approval of the laboratory.

8.2 RADIATED SPURIOUS EMISSIONS

▣ MODE: LTE B66/B4

▣ MODULATION SIGNAL: 20 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log10 (W) = -13 dBm

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
132072 (1720.0)	3 440.00	-46.57	12.40	-55.35	3.04	H	-45.99	1	99
	5 160.00	-51.13	12.44	-51.83	3.76	H	-43.15		
	6 880.00	-52.93	11.82	-46.83	4.44	V	-39.45		
132322 (1745.0)	3 490.00	-48.14	12.34	-56.71	3.04	H	-47.41	1	0
	5 235.00	-51.28	12.84	-51.22	3.78	H	-42.16		
	6 980.00	-52.83	11.40	-45.25	4.48	H	-38.33		
132572 (1770.0)	3 540.00	-47.39	12.34	-55.53	3.06	V	-46.25	1	0
	5 310.00	-52.80	13.08	-54.02	3.82	V	-44.76		
	7 080.00	-52.11	10.93	-43.01	4.49	V	-36.57		

The report shall not be (partly) reproduced except in full without approval of the laboratory.

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
66/4	1.4 MHz	1745.0	QPSK	6	0	4.85
			16-QAM			5.74
			64-QAM			6.44
	3 MHz		QPSK	15		4.76
			16-QAM			5.61
			64-QAM			6.42
	5 MHz		QPSK	25		4.81
			16-QAM			5.75
			64-QAM			6.47
	10 MHz		QPSK	50		4.68
			16-QAM			5.69
			64-QAM			6.44
	15 MHz		QPSK	75		4.72
			16-QAM			5.61
			64-QAM			6.37
	20 MHz		QPSK	100		4.74
			16-QAM			5.75
			64-QAM			6.42

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 51 ~ 68.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
66/4	1.4 MHz	1745.0	QPSK	6	0	1.1007
			16-QAM			1.1042
			64-QAM			1.0991
	3 MHz		QPSK	15		2.7274
			16-QAM			2.7171
			64-QAM			2.7168
	5 MHz		QPSK	25		4.5177
			16-QAM			4.5114
			64-QAM			4.4988
	10 MHz		QPSK	50		9.0147
			16-QAM			9.0022
			64-QAM			8.9995
	15 MHz		QPSK	75		13.491
			16-QAM			13.468
			64-QAM			13.487
	20 MHz		QPSK	100		17.989
			16-QAM			18.041
			64-QAM			17.987

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 69 ~ 86.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
66/4	1.4	1710.7	3.7164	27.976	-67.415	-39.439	-13.00
		1745.0	3.7049	27.976	-67.126	-39.150	
		1779.3	3.6910	27.976	-66.969	-38.993	
	3	1711.5	3.7084	27.976	-67.083	-39.107	
		1745.0	3.7179	27.976	-67.388	-39.412	
		1778.5	3.6910	27.976	-67.294	-39.318	
	5	1712.5	3.6900	27.976	-67.234	-39.258	
		1745.0	3.6671	27.976	-67.072	-39.096	
		1777.5	3.7000	27.976	-67.195	-39.219	
	10	1715.0	3.6900	27.976	-67.235	-39.259	
		1745.0	3.6925	27.976	-67.639	-39.663	
		1775.0	3.7134	27.976	-67.367	-39.391	
	15	1717.5	3.1546	27.976	-67.552	-39.576	
		1745.0	3.6995	27.976	-66.882	-38.906	
		1772.5	3.1895	27.976	-67.139	-39.163	
	20	1720.0	3.1810	27.976	-67.255	-39.279	
		1745.0	3.6925	27.976	-67.391	-39.415	
		1770.0	3.6990	27.976	-66.575	-38.599	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 87 ~ 122.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131

8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 123 ~ 158.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1710,700,000 Hz

▣ CHANNEL: 131979 (1.4 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1710 699 996	0.0	0.000 000	0.000
100 %		-30	1710 699 999	2.4	0.000 000	0.001
100 %		-20	1710 699 992	-4.9	0.000 000	-0.003
100 %		-10	1710 699 994	-2.3	0.000 000	-0.001
100 %		0	1710 700 001	4.5	0.000 000	0.003
100 %		+10	1710 699 993	-3.0	0.000 000	-0.002
100 %		+30	1710 700 002	5.1	0.000 000	0.003
100 %		+40	1710 700 001	4.4	0.000 000	0.003
100 %		+50	1710 700 003	6.9	0.000 000	0.004
Batt. Endpoint	3.300	+20	1710 699 999	2.1	0.000 000	0.001



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1711,500,000 Hz

▣ CHANNEL: 131987 (3 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1711 500 004	0.0	0.000 000	0.000
100 %		-30	1711 500 001	-2.1	0.000 000	-0.001
100 %		-20	1711 500 007	3.2	0.000 000	0.002
100 %		-10	1711 500 008	4.5	0.000 000	0.003
100 %		0	1711 499 999	-4.1	0.000 000	-0.002
100 %		+10	1711 500 001	-3.0	0.000 000	-0.002
100 %		+30	1711 500 008	4.3	0.000 000	0.003
100 %		+40	1711 500 009	5.5	0.000 000	0.003
100 %		+50	1711 500 007	3.5	0.000 000	0.002
Batt. Endpoint	3.300	+20	1711 500 001	-2.3	0.000 000	-0.001



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1712,500,000 Hz

▣ CHANNEL: 131997 (5 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1712 499 995	0.0	0.000 000	0.000
100 %		-30	1712 499 990	-5.3	0.000 000	-0.003
100 %		-20	1712 499 992	-3.4	0.000 000	-0.002
100 %		-10	1712 499 991	-4.0	0.000 000	-0.002
100 %		0	1712 499 990	-5.1	0.000 000	-0.003
100 %		+10	1712 499 997	2.2	0.000 000	0.001
100 %		+30	1712 499 992	-3.0	0.000 000	-0.002
100 %		+40	1712 499 992	-3.2	0.000 000	-0.002
100 %		+50	1712 499 992	-3.4	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1712 499 994	-1.4	0.000 000	-0.001



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1715,000,000 Hz

▣ CHANNEL: 132022 (10 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1714 999 997	0.0	0.000 000	0.000
100 %		-30	1715 000 001	3.5	0.000 000	0.002
100 %		-20	1714 999 995	-2.5	0.000 000	-0.001
100 %		-10	1715 000 000	2.4	0.000 000	0.001
100 %		0	1714 999 999	1.8	0.000 000	0.001
100 %		+10	1714 999 995	-2.5	0.000 000	-0.001
100 %		+30	1714 999 992	-4.7	0.000 000	-0.003
100 %		+40	1714 999 999	1.7	0.000 000	0.001
100 %		+50	1714 999 994	-3.4	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1714 999 995	-2.4	0.000 000	-0.001



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1717,500,000 Hz

▣ CHANNEL: 132047 (15 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1717 500 007	0.0	0.000 000	0.000
100 %		-30	1717 500 009	2.0	0.000 000	0.001
100 %		-20	1717 500 010	3.0	0.000 000	0.002
100 %		-10	1717 500 004	-2.6	0.000 000	-0.002
100 %		0	1717 500 008	1.5	0.000 000	0.001
100 %		+10	1717 500 001	-5.9	0.000 000	-0.003
100 %		+30	1717 500 004	-2.3	0.000 000	-0.001
100 %		+40	1717 500 004	-2.8	0.000 000	-0.002
100 %		+50	1717 500 010	3.1	0.000 000	0.002
Batt. Endpoint	3.300	+20	1717 500 003	-3.5	0.000 000	-0.002



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1720,000,000 Hz

▣ CHANNEL: 132072 (20 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1719 999 994	0.0	0.000 000	0.000
100 %		-30	1719 999 991	-3.7	0.000 000	-0.002
100 %		-20	1719 999 991	-3.9	0.000 000	-0.002
100 %		-10	1719 999 992	-2.8	0.000 000	-0.002
100 %		0	1719 999 989	-5.6	0.000 000	-0.003
100 %		+10	1719 999 991	-3.9	0.000 000	-0.002
100 %		+30	1719 999 991	-3.0	0.000 000	-0.002
100 %		+40	1719 999 990	-4.8	0.000 000	-0.003
100 %		+50	1719 999 992	-2.1	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1719 999 989	-5.8	0.000 000	-0.003



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1745,000,000 Hz

▣ CHANNEL: 132322 (1.4 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 003	0.0	0.000 000	0.000
100 %		-30	1745 000 005	2.0	0.000 000	0.001
100 %		-20	1745 000 008	5.2	0.000 000	0.003
100 %		-10	1745 000 000	-2.8	0.000 000	-0.002
100 %		0	1745 000 006	2.3	0.000 000	0.001
100 %		+10	1745 000 000	-2.9	0.000 000	-0.002
100 %		+30	1745 000 000	-3.4	0.000 000	-0.002
100 %		+40	1745 000 006	2.7	0.000 000	0.002
100 %		+50	1745 000 007	3.8	0.000 000	0.002
Batt. Endpoint	3.300	+20	1745 000 006	3.1	0.000 000	0.002



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1745,000,000 Hz

▣ CHANNEL: 132322 (3 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1744 999 996	0.0	0.000 000	0.000
100 %		-30	1745 000 001	5.1	0.000 000	0.003
100 %		-20	1744 999 999	3.1	0.000 000	0.002
100 %		-10	1745 000 000	4.3	0.000 000	0.002
100 %		0	1745 000 000	4.0	0.000 000	0.002
100 %		+10	1745 000 003	7.6	0.000 000	0.004
100 %		+30	1744 999 994	-1.3	0.000 000	-0.001
100 %		+40	1744 999 993	-2.6	0.000 000	-0.001
100 %		+50	1744 999 991	-4.2	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1744 999 993	-2.4	0.000 000	-0.001



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1745,000,000 Hz

▣ CHANNEL: 132322 (5 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 004	0.0	0.000 000	0.000
100 %		-30	1745 000 007	3.0	0.000 000	0.002
100 %		-20	1745 000 007	2.9	0.000 000	0.002
100 %		-10	1745 000 001	-3.4	0.000 000	-0.002
100 %		0	1745 000 002	-2.7	0.000 000	-0.002
100 %		+10	1745 000 007	2.2	0.000 000	0.001
100 %		+30	1745 000 002	-2.1	0.000 000	-0.001
100 %		+40	1745 000 002	-2.8	0.000 000	-0.002
100 %		+50	1745 000 008	3.3	0.000 000	0.002
Batt. Endpoint	3.300	+20	1745 000 008	3.9	0.000 000	0.002



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1745,000,000 Hz

▣ CHANNEL: 132322 (10 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1744 999 996	0.0	0.000 000	0.000
100 %		-30	1744 999 999	2.3	0.000 000	0.001
100 %		-20	1745 000 000	3.4	0.000 000	0.002
100 %		-10	1744 999 992	-4.0	0.000 000	-0.002
100 %		0	1744 999 994	-2.2	0.000 000	-0.001
100 %		+10	1745 000 000	3.7	0.000 000	0.002
100 %		+30	1744 999 992	-4.4	0.000 000	-0.003
100 %		+40	1744 999 993	-3.8	0.000 000	-0.002
100 %		+50	1744 999 999	2.1	0.000 000	0.001
Batt. Endpoint	3.300	+20	1745 000 000	3.7	0.000 000	0.002



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1745,000,000 Hz

▣ CHANNEL: 132322 (15 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 003	0.0	0.000 000	0.000
100 %		-30	1744 999 999	-3.4	0.000 000	-0.002
100 %		-20	1744 999 999	-3.8	0.000 000	-0.002
100 %		-10	1744 999 999	-3.6	0.000 000	-0.002
100 %		0	1745 000 000	-2.3	0.000 000	-0.001
100 %		+10	1745 000 004	1.5	0.000 000	0.001
100 %		+30	1744 999 998	-4.8	0.000 000	-0.003
100 %		+40	1744 999 999	-3.3	0.000 000	-0.002
100 %		+50	1744 999 999	-3.5	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1745 000 000	-2.7	0.000 000	-0.002



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1745,000,000 Hz

▣ CHANNEL: 132322 (20 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 002	0.0	0.000 000	0.000
100 %		-30	1744 999 996	-6.1	0.000 000	-0.003
100 %		-20	1744 999 999	-3.2	0.000 000	-0.002
100 %		-10	1745 000 000	-2.8	0.000 000	-0.002
100 %		0	1744 999 999	-3.8	0.000 000	-0.002
100 %		+10	1745 000 005	2.8	0.000 000	0.002
100 %		+30	1744 999 998	-4.5	0.000 000	-0.003
100 %		+40	1744 999 997	-5.0	0.000 000	-0.003
100 %		+50	1745 000 000	-2.3	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1745 000 005	2.1	0.000 000	0.001



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1779,300,000 Hz

▣ CHANNEL: 132665 (1.4 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1779 300 005	0.0	0.000 000	0.000
100 %		-30	1779 300 011	5.8	0.000 000	0.003
100 %		-20	1779 300 011	6.1	0.000 000	0.003
100 %		-10	1779 300 014	8.7	0.000 000	0.005
100 %		0	1779 300 010	4.7	0.000 000	0.003
100 %		+10	1779 300 011	6.3	0.000 000	0.004
100 %		+30	1779 300 011	5.8	0.000 000	0.003
100 %		+40	1779 300 014	8.5	0.000 000	0.005
100 %		+50	1779 300 009	3.8	0.000 000	0.002
Batt. Endpoint	3.300	+20	1779 300 011	5.5	0.000 000	0.003



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1778,500,000 Hz

▣ CHANNEL: 132657 (3 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1778 499 993	0.0	0.000 000	0.000
100 %		-30	1778 499 982	-10.5	-0.000 001	-0.006
100 %		-20	1778 499 985	-8.1	0.000 000	-0.005
100 %		-10	1778 500 001	8.5	0.000 000	0.005
100 %		0	1778 500 003	9.7	0.000 001	0.005
100 %		+10	1778 499 982	-11.2	-0.000 001	-0.006
100 %		+30	1778 500 002	8.8	0.000 000	0.005
100 %		+40	1778 499 977	-16.1	-0.000 001	-0.009
100 %		+50	1778 500 011	17.7	0.000 001	0.010
Batt. Endpoint	3.300	+20	1778 499 980	-12.4	-0.000 001	-0.007



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1777,500,000 Hz

▣ CHANNEL: 132647 (5 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1777 499 994	0.0	0.000 000	0.000
100 %		-30	1777 499 989	-4.3	0.000 000	-0.002
100 %		-20	1777 499 999	5.2	0.000 000	0.003
100 %		-10	1777 499 999	5.5	0.000 000	0.003
100 %		0	1777 500 000	6.4	0.000 000	0.004
100 %		+10	1777 499 989	-4.7	0.000 000	-0.003
100 %		+30	1777 499 997	3.1	0.000 000	0.002
100 %		+40	1777 499 999	5.5	0.000 000	0.003
100 %		+50	1777 499 998	4.5	0.000 000	0.003
Batt. Endpoint	3.300	+20	1777 499 988	-5.4	0.000 000	-0.003



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1775,000,000 Hz

▣ CHANNEL: 132622 (10 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1775 000 005	0.0	0.000 000	0.000
100 %		-30	1775 000 009	4.7	0.000 000	0.003
100 %		-20	1774 999 999	-6.0	0.000 000	-0.003
100 %		-10	1775 000 000	-5.1	0.000 000	-0.003
100 %		0	1774 999 999	-5.9	0.000 000	-0.003
100 %		+10	1775 000 000	-4.4	0.000 000	-0.002
100 %		+30	1775 000 000	-5.2	0.000 000	-0.003
100 %		+40	1774 999 999	-6.2	0.000 000	-0.003
100 %		+50	1775 000 002	-3.0	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1775 000 000	-4.5	0.000 000	-0.003



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1772,500,000 Hz

▣ CHANNEL: 132597 (15 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1772 499 990	0.0	0.000 000	0.000
100 %		-30	1772 499 981	-8.9	-0.000 001	-0.005
100 %		-20	1772 499 982	-7.5	0.000 000	-0.004
100 %		-10	1772 499 980	-9.7	-0.000 001	-0.005
100 %		0	1772 499 980	-10.1	-0.000 001	-0.006
100 %		+10	1772 499 981	-8.6	0.000 000	-0.005
100 %		+30	1772 499 984	-5.7	0.000 000	-0.003
100 %		+40	1772 499 982	-7.6	0.000 000	-0.004
100 %		+50	1772 499 983	-6.7	0.000 000	-0.004
Batt. Endpoint	3.300	+20	1772 499 981	-8.9	-0.000 001	-0.005



The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ MODE: LTE 66/4

▣ OPERATING FREQUENCY: 1770,000,000 Hz

▣ CHANNEL: 132572 (20 MHz)

▣ REFERENCE VOLTAGE: 3.880 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.880	+20(Ref)	1769 999 997	0.0	0.000 000	0.000
100 %		-30	1769 999 990	-6.7	0.000 000	-0.004
100 %		-20	1770 000 002	4.9	0.000 000	0.003
100 %		-10	1769 999 993	-3.6	0.000 000	-0.002
100 %		0	1769 999 992	-4.8	0.000 000	-0.003
100 %		+10	1770 000 000	3.4	0.000 000	0.002
100 %		+30	1769 999 990	-7.0	0.000 000	-0.004
100 %		+40	1770 000 003	6.7	0.000 000	0.004
100 %		+50	1770 000 000	3.0	0.000 000	0.002
Batt. Endpoint	3.300	+20	1769 999 990	-6.5	0.000 000	-0.004



The report shall not be (partly) reproduced except in full without approval of the laboratory.

9. TEST PLOTS(Main 1 ANT)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_PAR_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_PAR_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_PAR_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_PAR_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_PAR_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_PAR_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_PAR_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_PAR_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_PAR_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_PAR_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_PAR_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_PAR_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_PAR_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_PAR_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_PAR_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_20 M_PAR_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_20 M_PAR_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_20 M_PAR_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_OBW_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_OBW_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_OBW_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_OBW_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_OBW_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_OBW_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_OBW_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_OBW_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_OBW_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_OBW_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_OBW_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_OBW_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_OBW_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_OBW_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_OBW_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_20 M_OBW_Mid_QPSK_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_20 M_OBW_Mid_16QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_20 M_OBW_Mid_64QAM_FullRB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_1.4M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_3 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_5 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_10 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_15 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_20 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.

LTE B66_20 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



The report shall not be (partly) reproduced except in full without approval of the laboratory.