

APPENDIX A: SAR TEST RESULTS FOR P_{Limit} CALCULATIONS

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation. See RF Exposure SAR Evaluation Report (Part 1) section 12 for 5/6 GHz WLAN SAR data.

Table A-1
DSI = 0 P_{Limit} Calculations – GPRS 850 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	GPRS 850	GPRS 3 Tx Slots	A	1267M	1:2.76	-0.10	848.80	251	29.38	Back	0	0.607	31.0	30.2	30.2
Phablet	GPRS 850	GPRS 3 Tx Slots	A	1267M	1:2.76	0.07	848.80	251	29.38	Front	0	0.517	31.7		
Phablet	GPRS 850	GPRS 3 Tx Slots	A	1267M	1:2.76	-0.01	848.80	251	29.38	Bottom	0	0.503	31.9		
Phablet	GPRS 850	GPRS 3 Tx Slots	A	1267M	1:2.76	0.06	848.80	251	29.38	Right	0	0.143	37.3		
Phablet	GPRS 850	GPRS 3 Tx Slots	A	1267M	1:2.76	0.05	848.80	251	29.38	Left	0	0.736	30.2		
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	GPRS 850	GPRS 3 Tx Slots	E	1267M	1:2.76	-0.06	848.80	251	28.92	Back	0	0.663	30.2	28.7	28.4
Phablet	GPRS 850	GPRS 3 Tx Slots	E	1267M	1:2.76	0.09	848.80	251	28.92	Front	0	0.525	31.2		
Phablet	GPRS 850	GPRS 3 Tx Slots	E	1267M	1:2.76	0.07	848.80	251	28.92	Top	0	0.940	28.7		
Phablet	GPRS 850	GPRS 3 Tx Slots	E	1267M	1:2.76	-0.03	848.80	251	28.92	Right	0	0.426	32.1		

Table A-2
DSI = 0 P_{Limit} Calculations – GPRS 1900 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	GPRS 1900	GPRS 4 Tx Slots	A	1298M	1:2.076	0.06	1880.00	661	20.79	Back	0	0.739	22.9	22.5	17.8
Phablet	GPRS 1900	GPRS 4 Tx Slots	A	1298M	1:2.076	0.02	1880.00	661	20.79	Front	0	0.793	22.5		
Phablet	GPRS 1900	GPRS 4 Tx Slots	A	1298M	1:2.076	-0.08	1880.00	661	20.79	Bottom	0	0.458	24.9		
Phablet	GPRS 1900	GPRS 4 Tx Slots	A	1298M	1:2.076	0.02	1880.00	661	20.79	Right	0	0.086	32.2		
Phablet	GPRS 1900	GPRS 4 Tx Slots	A	1298M	1:2.076	0.09	1880.00	661	20.79	Left	0	0.124	30.6		

Table A-3
DSI = 0 P_{Limit} Calculations – UMTS 850 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	UMTS 850	RMC	A	1267M	1:1	-0.01	846.60	4233	24.94	Back	0	1.220	28.0	28.0	28.0
Phablet	UMTS 850	RMC	A	1267M	1:1	-0.02	846.60	4233	24.94	Front	0	0.960	29.0		
Phablet	UMTS 850	RMC	A	1267M	1:1	0.05	846.60	4233	24.94	Bottom	0	0.913	29.3		
Phablet	UMTS 850	RMC	A	1267M	1:1	-0.02	846.60	4233	24.94	Right	0	0.186	36.2		
Phablet	UMTS 850	RMC	A	1267M	1:1	0.03	846.60	4233	24.94	Left	0	1.130	28.3		
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	UMTS 850	RMC	E	1267M	1:1	0.07	846.60	4233	24.23	Back	0	0.950	28.4	26.8	26.8
Phablet	UMTS 850	RMC	E	1267M	1:1	0.01	846.60	4233	24.23	Front	0	1.380	26.8		
Phablet	UMTS 850	RMC	E	1267M	1:1	0.19	846.60	4233	24.23	Top	0	0.975	28.3		
Phablet	UMTS 850	RMC	E	1267M	1:1	-0.04	846.60	4233	24.23	Right	0	1.070	27.9		

Table A-4
DSI = 0 P_{Limit} Calculations – UMTS 1900 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	UMTS 1750	RMC	A	1298M	1:1	0.03	1712.40	1312	18.85	Back	0	1.090	22.4	22.4	18.0
Phablet	UMTS 1750	RMC	A	1298M	1:1	0.00	1712.40	1312	18.85	Front	0	1.090	22.4		
Phablet	UMTS 1750	RMC	A	1298M	1:1	0.02	1712.40	1312	18.85	Bottom	0	0.695	24.4		
Phablet	UMTS 1750	RMC	A	1298M	1:1	0.02	1712.40	1312	18.85	Right	0	0.222	29.3		
Phablet	UMTS 1750	RMC	A	1298M	1:1	0.02	1712.40	1312	18.85	Left	0	0.140	31.3		

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report										Approved by: Technical Manager				
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset										APPENDIX A: Page 1 of 9				

REV 1.1
04/08/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.Info@Element.com.

Table A-5
DSI = 0 P_{Limit} Calculations – UMTS 1900 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	UMTS 1900	RMC	A	1298M	1:1	-0.03	1907.60	9538	18.20	Back	0	0.819	23.0	23.0	17.5
Phablet	UMTS 1900	RMC	A	1298M	1:1	0.02	1907.60	9538	18.20	Front	0	0.800	23.1		
Phablet	UMTS 1900	RMC	A	1298M	1:1	0.01	1907.60	9538	18.20	Bottom	0	0.601	24.3		
Phablet	UMTS 1900	RMC	A	1298M	1:1	0.01	1907.60	9538	18.20	Right	0	0.120	31.3		
Phablet	UMTS 1900	RMC	A	1298M	1:1	0.03	1907.60	9538	18.20	Left	0	0.169	29.9		

Table A-6
DSI = 0 P_{Limit} Calculations – LTE B71 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	LTE Band 71	20	QPSK	A	1247M	1:1	0.05	680.50	133297	0.0	24.46	1	50	Front	0	0.680	30.1	30.1	28.7
Phablet	LTE Band 71	20	QPSK	A	1247M	1:1	0.10	680.50	133297	0.0	24.46	1	50	Bottom	0	0.398	32.4		
Phablet	LTE Band 71	20	QPSK	A	1247M	1:1	0.03	680.50	133297	0.0	24.46	1	50	Right	0	0.106	38.1		
Phablet	LTE Band 71	20	QPSK	A	1247M	1:1	-0.01	680.50	133297	0.0	24.46	1	50	Left	0	0.247	34.5		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	LTE Band 71	20	QPSK	E	1247M	1:1	0.01	680.50	133297	0.0	21.92	1	50	Back	0	0.729	29.2	28.7	28.4
Phablet	LTE Band 71	20	QPSK	E	1247M	1:1	-0.01	680.50	133297	0.0	21.92	1	50	Front	0	0.611	30.0		
Phablet	LTE Band 71	20	QPSK	E	1247M	1:1	0.03	680.50	133297	0.0	23.92	1	50	Top	0	0.814	28.7		
Phablet	LTE Band 71	20	QPSK	E	1247M	1:1	0.09	680.50	133297	0.0	23.92	1	50	Right	0	0.466	31.2		

Table A-7
DSI = 0 P_{Limit} Calculations – LTE B12 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	LTE Band 12	10	QPSK	A	1247M	1:1	0.07	707.50	23095	0.0	24.83	1	0	Front	0	0.815	29.6	29.6	29.6
Phablet	LTE Band 12	10	QPSK	A	1247M	1:1	0.03	707.50	23095	0.0	24.83	1	0	Bottom	0	0.529	31.5		
Phablet	LTE Band 12	10	QPSK	A	1247M	1:1	0.02	707.50	23095	0.0	24.83	1	0	Right	0	0.122	37.9		
Phablet	LTE Band 12	10	QPSK	A	1247M	1:1	0.05	707.50	23095	0.0	24.83	1	0	Left	0	0.338	33.5		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	LTE Band 12	10	QPSK	E	1247M	1:1	0.00	707.50	23095	0.0	24.39	1	0	Back	0	0.940	28.6	28.1	27.9
Phablet	LTE Band 12	10	QPSK	E	1247M	1:1	0.00	707.50	23095	0.0	24.39	1	0	Front	0	0.859	29.0		
Phablet	LTE Band 12	10	QPSK	E	1247M	1:1	-0.06	707.50	23095	0.0	24.39	1	0	Top	0	1.040	28.1		
Phablet	LTE Band 12	10	QPSK	E	1247M	1:1	-0.02	707.50	23095	0.0	24.39	1	0	Right	0	0.690	29.9		

Table A-8
DSI = 0 P_{Limit} Calculations – LTE B13 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	LTE Band 13	10	QPSK	A	1247M	1:1	0.04	782.00	23230	0.0	24.09	1	49	Front	0	0.724	29.4	29.4	28.5
Phablet	LTE Band 13	10	QPSK	A	1247M	1:1	0.06	782.00	23230	0.0	24.09	1	49	Bottom	0	0.477	31.2		
Phablet	LTE Band 13	10	QPSK	A	1247M	1:1	-0.07	782.00	23230	0.0	24.09	1	49	Right	0	0.131	36.8		
Phablet	LTE Band 13	10	QPSK	A	1247M	1:1	0.02	782.00	23230	0.0	24.09	1	49	Left	0	0.524	30.8		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	LTE Band 13	10	QPSK	E	1247M	1:1	0.01	782.00	23230	1.0	22.53	25	12	Back	0	0.946	26.7	26.4	26.2
Phablet	LTE Band 13	10	QPSK	E	1247M	1:1	0.00	782.00	23230	1.0	22.53	25	12	Front	0	0.880	27.0		
Phablet	LTE Band 13	10	QPSK	E	1247M	1:1	0.01	782.00	23230	1.0	22.53	25	12	Top	0	1.010	26.4		
Phablet	LTE Band 13	10	QPSK	E	1247M	1:1	-0.03	782.00	23230	1.0	22.53	25	12	Right	0	0.695	28.0		

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report										Approved by: Technical Manager			
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset										APPENDIX A: Page 2 of 9			

Table A-9
DSI = 0 P_{Limit} Calculations – LTE B14 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 14	10	QPSK	A	1247M	1:1	-0.01	793.00	23330	0.0	24.85	1	49	Front	0	0.785	29.8	29.8	28.8
Phablet	LTE Band 14	10	QPSK	A	1247M	1:1	0.09	793.00	23330	0.0	24.85	1	49	Bottom	0	0.495	31.8		
Phablet	LTE Band 14	10	QPSK	A	1247M	1:1	0.00	793.00	23330	0.0	24.85	1	49	Right	0	0.147	37.1		
Phablet	LTE Band 14	10	QPSK	A	1247M	1:1	0.06	793.00	23330	0.0	24.85	1	49	Left	0	0.587	31.1		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 14	10	QPSK	E	1247M	1:1	-0.01	793.00	23330	0.0	24.16	1	25	Back	0	1.350	26.8	26.6	26.4
Phablet	LTE Band 14	10	QPSK	E	1247M	1:1	0.06	793.00	23330	0.0	24.16	1	25	Front	0	1.170	27.4		
Phablet	LTE Band 14	10	QPSK	E	1247M	1:1	-0.01	793.00	23330	0.0	24.16	1	25	Top	0	1.400	26.6		
Phablet	LTE Band 14	10	QPSK	E	1247M	1:1	-0.01	793.00	23330	0.0	24.16	1	25	Right	0	1.070	27.8		

Table A-10
DSI = 0 P_{Limit} Calculations – LTE B26 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 26	15	QPSK	A	1247M	1:1	-0.02	831.50	26865	0.0	24.46	1	36	Front	0	0.850	29.1	28.8	28.8
Phablet	LTE Band 26	15	QPSK	A	1247M	1:1	-0.04	831.50	26865	0.0	24.46	1	36	Bottom	0	0.743	29.7		
Phablet	LTE Band 26	15	QPSK	A	1247M	1:1	-0.04	831.50	26865	0.0	24.46	1	36	Right	0	0.096	38.6		
Phablet	LTE Band 26	15	QPSK	A	1247M	1:1	-0.04	831.50	26865	0.0	24.46	1	36	Left	0	0.920	28.8		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 26	15	QPSK	E	1247M	1:1	0.01	831.50	26865	0.0	23.67	1	36	Back	0	1.190	26.8	26.7	26.2
Phablet	LTE Band 26	15	QPSK	E	1247M	1:1	-0.02	831.50	26865	0.0	23.67	1	36	Front	0	0.892	28.1		
Phablet	LTE Band 26	15	QPSK	E	1247M	1:1	0.07	831.50	26865	0.0	23.67	1	36	Top	0	1.240	26.7		
Phablet	LTE Band 26	15	QPSK	E	1247M	1:1	0.00	831.50	26865	0.0	23.67	1	36	Right	0	0.734	28.9		

Table A-11
DSI = 0 P_{Limit} Calculations – LTE B66 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 66	20	QPSK	A	1263M	1:1	0.09	1720.00	132072	0.0	18.49	1	0	Back	0	1.210	21.6	21.6	18.5
Phablet	LTE Band 66	20	QPSK	A	1263M	1:1	0.02	1720.00	132072	0.0	18.49	1	0	Front	0	1.050	22.2		
Phablet	LTE Band 66	20	QPSK	A	1263M	1:1	-0.05	1720.00	132072	0.0	18.49	1	0	Bottom	0	1.110	22.0		
Phablet	LTE Band 66	20	QPSK	A	1263M	1:1	-0.07	1720.00	132072	0.0	18.49	1	0	Right	0	0.035	37.0		
Phablet	LTE Band 66	20	QPSK	A	1263M	1:1	-0.13	1720.00	132072	0.0	18.49	1	0	Left	0	0.195	29.5		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	0.05	1720.00	132072	0.0	20.23	50	0	Back	0	1.090	23.8	20.3	20.0
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	0.00	1720.00	132072	0.0	20.23	50	0	Front	0	1.440	22.6		
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	-0.02	1720.00	132072	0.0	20.20	1	50	Top	0	2.110	20.9		
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	0.02	1745.00	132322	0.0	19.82	1	50	Top	0	2.210	20.3		
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	-0.06	1720.00	132322	0.0	20.02	1	0	Top	0	2.140	20.6		
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	0.00	1720.00	132072	0.0	20.23	50	0	Top	0	2.060	21.0		
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	0.01	1745.00	132322	0.0	19.96	50	0	Top	0	2.200	20.5		
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	0.00	1770.00	132572	0.0	19.87	50	0	Top	0	2.180	20.4		
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	0.00	1720.00	132072	0.0	20.09	100	0	Top	0	2.120	20.8		
Phablet	LTE Band 66	20	QPSK	F	1252M	1:1	-0.17	1720.00	132072	0.0	20.23	50	0	Left	0	0.510	27.1		

Table A-12
DSI = 0 P_{Limit} Calculations – LTE B25 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 25	20	QPSK	A	1263M	1:1	0.03	1860.00	26140	0.0	18.44	1	0	Back	0	0.839	23.1	22.8	18.0
Phablet	LTE Band 25	20	QPSK	A	1263M	1:1	0.01	1860.00	26140	0.0	18.44	1	0	Front	0	0.915	22.8		
Phablet	LTE Band 25	20	QPSK	A	1263M	1:1	0.05	1860.00	26140	0.0	18.44	1	0	Bottom	0	0.854	23.1		
Phablet	LTE Band 25	20	QPSK	A	1263M	1:1	0.07	1860.00	26140	0.0	18.44	1	0	Right	0	0.117	31.7		
Phablet	LTE Band 25	20	QPSK	A	1263M	1:1	0.04	1860.00	26140	0.0	18.44	1	0	Left	0	0.132	31.2		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	0.04	1882.50	26365	0.0	20.23	1	0	Back	0	1.210	23.3	20.7	20.0
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	0.09	1882.50	26365	0.0	20.23	1	0	Front	0	1.390	22.7		
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	-0.01	1860.00	26140	0.0	20.30	1	50	Top	0	2.140	20.8		
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	-0.04	1882.50	26365	0.0	20.23	1	0	Top	0	2.010	21.1		
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	-0.01	1905.00	26590	0.0	19.96	1	0	Top	0	1.990	20.9		
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	-0.03	1860.00	26140	0.0	20.16	50	25	Top	0	2.180	20.7		
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	0.00	1882.50	26365	0.0	20.17	50	25	Top	0	2.060	21.0		
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	-0.01	1905.00	26590	0.0	20.03	50	25	Top	0	1.970	21.0		
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	-0.01	1860.00	26140	0.0	20.15	100	0	Top	0	2.150	20.8		
Phablet	LTE Band 25	20	QPSK	F	1252M	1:1	-0.09	1882.50	26365	0.0	20.23	1	0	Left	0	0.522	27.0		

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report														Approved by: Technical Manager				
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset														APPENDIX A: Page 3 of 9				

Table A-13
DSI = 0 P_{Limit} Calculations – LTE B30 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 30	10	QPSK	A	1285M	1:1	-0.13	2310.00	27710	0.0	19.52	1	25	Back	0	1.000	23.4	23.2	19.0
Phablet	LTE Band 30	10	QPSK	A	1285M	1:1	0.00	2310.00	27710	0.0	19.52	1	25	Front	0	0.565	25.9		
Phablet	LTE Band 30	10	QPSK	A	1285M	1:1	-0.03	2310.00	27710	0.0	19.52	1	25	Bottom	0	1.060	23.2		
Phablet	LTE Band 30	10	QPSK	A	1285M	1:1	0.08	2310.00	27710	0.0	19.52	1	25	Right	0	0.190	30.7		
Phablet	LTE Band 30	10	QPSK	A	1285M	1:1	-0.07	2310.00	27710	0.0	19.52	1	25	Left	0	0.294	28.8		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 30	10	QPSK	F	1285M	1:1	-0.02	2310.00	27710	0.0	18.19	1	25	Back	0	0.625	23.0	19.6	18.0
Phablet	LTE Band 30	10	QPSK	F	1285M	1:1	0.00	2310.00	27710	0.0	18.19	1	25	Front	0	1.000	22.1		
Phablet	LTE Band 30	10	QPSK	F	1285M	1:1	-0.09	2310.00	27710	0.0	18.19	1	25	Top	0	1.720	19.6		
Phablet	LTE Band 30	10	QPSK	F	1285M	1:1	0.06	2310.00	27710	0.0	18.19	1	25	Left	0	0.105	31.9		

Table A-14
DSI = 0 P_{Limit} Calculations – LTE B7 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 7	20	QPSK	B	1285M	1:1	0.01	2510.00	20850	0.0	19.73	50	0	Back	0	1.730	21.3	21.3	19.0
Phablet	LTE Band 7	20	QPSK	B	1285M	1:1	-0.12	2510.00	20850	0.0	19.73	50	0	Front	0	0.862	24.3		
Phablet	LTE Band 7	20	QPSK	B	1285M	1:1	0.01	2510.00	20850	0.0	19.73	50	0	Bottom	0	1.210	22.8		
Phablet	LTE Band 7	20	QPSK	B	1302M	1:1	0.19	2510.00	20850	0.0	19.73	50	0	Left	0	1.100	23.2		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 7	20	QPSK	F	1285M	1:1	0.03	2535.00	21100	0.0	16.95	50	0	Back	0	0.972	21.0	18.4	17.0
Phablet	LTE Band 7	20	QPSK	F	1285M	1:1	-0.01	2535.00	21100	0.0	16.95	50	0	Front	0	1.070	20.6		
Phablet	LTE Band 7	20	QPSK	F	1285M	1:1	-0.02	2535.00	21100	0.0	16.95	50	0	Top	0	1.770	18.4		
Phablet	LTE Band 7	20	QPSK	F	1285M	1:1	0.01	2535.00	21100	0.0	16.95	50	0	Left	0	0.126	29.9		

Table A-15
DSI = 0 P_{Limit} Calculations – LTE B41 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 41	20	QPSK	B	1249M	1:1.58	-0.01	2636.50	41055	0.0	21.84	1	0	Back	0	1.130	23.3	22.4	19.0
Phablet	LTE Band 41	20	QPSK	B	1249M	1:1.58	0.01	2636.50	41055	0.0	21.84	1	0	Front	0	0.994	23.8		
Phablet	LTE Band 41	20	QPSK	B	1249M	1:1.58	0.02	2636.50	41055	0.0	21.84	1	0	Bottom	0	0.932	24.1		
Phablet	LTE Band 41	20	QPSK	B	1249M	1:1.58	-0.05	2636.50	41055	0.0	21.84	1	0	Left	0	1.360	22.4		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 41	20	QPSK	F	1294M	1:1.58	-0.01	2506.00	39750	0.0	18.32	50	50	Back	0	0.721	21.7	19.6	16.0
Phablet	LTE Band 41	20	QPSK	F	1294M	1:1.58	0.00	2506.00	39750	0.0	18.32	50	50	Front	0	0.755	21.5		
Phablet	LTE Band 41	20	QPSK	F	1294M	1:1.58	0.04	2506.00	39750	0.0	18.32	50	50	Top	0	1.160	19.6		
Phablet	LTE Band 41	20	QPSK	F	1294M	1:1.58	-0.15	2506.00	39750	0.0	18.32	50	50	Left	0	0.098	30.4		

Table A-16
DSI = 0 P_{Limit} Calculations – LTE B48 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	LTE Band 48	20	QPSK	F	1263M	1:1.58	-0.05	3646.70	56207	0.0	21.64	1	99	Back	0	0.941	23.8	21.4	19.0
Phablet	LTE Band 48	20	QPSK	F	1263M	1:1.58	0.04	3646.70	56207	0.0	21.64	1	99	Front	0	0.814	24.5		
Phablet	LTE Band 48	20	QPSK	F	1263M	1:1.58	-0.02	3646.70	56207	0.0	21.64	1	99	Top	0	1.650	21.4		
Phablet	LTE Band 48	20	QPSK	F	1263M	1:1.58	0.00	3646.70	56207	0.0	21.64	1	99	Left	0	0.159	31.6		

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report										Approved by: Technical Manager								
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset										APPENDIX A: Page 4 of 9								

REV 1.1
04/08/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.Info@Element.com.

Table A-17
DSI = 0 P_{Limit} Calculations – NR n71 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	NR Band n71	35	QPSK	A	1266M	1:1	0.02	680.50	136100	DFT-s-OFDM	0.0	24.40	1	94	Back	0	0.987	28.4	28.4	28.4
Phablet	NR Band n71	35	QPSK	A	1266M	1:1	0.04	680.50	136100	DFT-s-OFDM	0.0	24.40	1	94	Front	0	0.761	29.5		
Phablet	NR Band n71	35	QPSK	A	1266M	1:1	0.03	680.50	136100	DFT-s-OFDM	0.0	24.40	1	94	Bottom	0	0.533	31.1		
Phablet	NR Band n71	35	QPSK	A	1266M	1:1	-0.12	680.50	136100	DFT-s-OFDM	0.0	24.40	1	94	Right	0	0.137	37.0		
Phablet	NR Band n71	35	QPSK	A	1266M	1:1	-0.07	680.50	136100	DFT-s-OFDM	0.0	24.40	1	94	Left	0	0.190	35.5		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	NR Band n71	20	QPSK	E	1255M	1:1	-0.11	680.50	136100	DFT-s-OFDM	0.0	23.82	1	104	Back	0	0.767	28.9	28.9	28.9
Phablet	NR Band n71	20	QPSK	E	1252M	1:1	-0.02	680.50	136100	DFT-s-OFDM	0.0	23.82	1	104	Front	0	0.596	30.0		
Phablet	NR Band n71	20	QPSK	E	1252M	1:1	-0.04	680.50	136100	DFT-s-OFDM	0.0	23.82	1	104	Top	0	0.767	28.9		
Phablet	NR Band n71	20	QPSK	E	1252M	1:1	0.13	680.50	136100	DFT-s-OFDM	0.0	23.82	1	104	Right	0	0.311	32.8		

Table A-18
DSI = 0 P_{Limit} Calculations – NR n12 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	NR Band n12	15	QPSK	A	1266M	1:1	-0.06	707.50	141500	DFT-s-OFDM	0.0	24.71	1	1	Back	0	0.862	29.3	29.3	28.6
Phablet	NR Band n12	15	QPSK	A	1266M	1:1	-0.07	707.50	141500	DFT-s-OFDM	0.0	24.71	1	1	Front	0	0.691	30.2		
Phablet	NR Band n12	15	QPSK	A	1266M	1:1	-0.03	707.50	141500	DFT-s-OFDM	0.0	24.71	1	1	Bottom	0	0.476	31.9		
Phablet	NR Band n12	15	QPSK	A	1266M	1:1	-0.20	707.50	141500	DFT-s-OFDM	0.0	24.71	1	1	Right	0	0.113	38.1		
Phablet	NR Band n12	15	QPSK	A	1266M	1:1	0.01	707.50	141500	DFT-s-OFDM	0.0	24.71	1	1	Left	0	0.289	34.0		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	NR Band n12	15	QPSK	E	1255M	1:1	0.07	707.50	141500	DFT-s-OFDM	0.0	24.37	1	40	Back	0	0.902	28.7	28.2	28.2
Phablet	NR Band n12	15	QPSK	E	1252M	1:1	-0.08	707.50	141500	DFT-s-OFDM	0.0	24.37	1	40	Front	0	0.911	28.7		
Phablet	NR Band n12	15	QPSK	E	1252M	1:1	-0.01	707.50	141500	DFT-s-OFDM	0.0	24.37	1	40	Top	0	1.080	28.2		
Phablet	NR Band n12	15	QPSK	E	1252M	1:1	0.05	707.50	141500	DFT-s-OFDM	0.0	24.37	1	40	Right	0	0.429	32.0		

Table A-19
DSI = 0 P_{Limit} Calculations – NR n14 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	NR Band n14	10	QPSK	A	1266M	1:1	-0.09	793.00	158600	DFT-s-OFDM	0.0	24.32	1	26	Back	0	0.907	28.7	28.7	28.7
Phablet	NR Band n14	10	QPSK	A	1266M	1:1	-0.01	793.00	158600	DFT-s-OFDM	0.0	24.32	1	26	Front	0	0.707	29.8		
Phablet	NR Band n14	10	QPSK	A	1266M	1:1	0.04	793.00	158600	DFT-s-OFDM	0.0	24.32	1	26	Bottom	0	0.474	31.5		
Phablet	NR Band n14	10	QPSK	A	1266M	1:1	-0.03	793.00	158600	DFT-s-OFDM	0.0	24.32	1	26	Right	0	0.146	36.6		
Phablet	NR Band n14	10	QPSK	A	1266M	1:1	-0.08	793.00	158600	DFT-s-OFDM	0.0	24.32	1	26	Left	0	0.456	31.7		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	NR Band n14	10	QPSK	E	1255M	1:1	-0.02	793.00	158600	DFT-s-OFDM	0.0	23.82	25	14	Back	0	1.140	27.2	26.9	26.8
Phablet	NR Band n14	10	QPSK	E	1252M	1:1	-0.01	793.00	158600	DFT-s-OFDM	0.0	23.82	25	14	Front	0	1.070	27.5		
Phablet	NR Band n14	10	QPSK	E	1252M	1:1	0.00	793.00	158600	DFT-s-OFDM	0.0	23.82	25	14	Top	0	1.210	26.9		
Phablet	NR Band n14	10	QPSK	E	1252M	1:1	-0.02	793.00	158600	DFT-s-OFDM	0.0	23.82	25	14	Right	0	0.539	30.4		

Table A-20
DSI = 0 P_{Limit} Calculations – NR n26 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	NR Band n26	20	QPSK	A	1266M	1:1	0.00	831.50	166300	DFT-s-OFDM	0.0	24.00	1	104	Back	0	1.070	27.6	27.6	27.6
Phablet	NR Band n26	20	QPSK	A	1266M	1:1	-0.02	831.50	166300	DFT-s-OFDM	0.0	24.00	1	104	Front	0	0.764	29.1		
Phablet	NR Band n26	20	QPSK	A	1266M	1:1	0.00	831.50	166300	DFT-s-OFDM	0.0	24.00	1	104	Bottom	0	0.529	30.7		
Phablet	NR Band n26	20	QPSK	A	1266M	1:1	0.13	831.50	166300	DFT-s-OFDM	0.0	24.00	1	104	Right	0	0.148	36.2		
Phablet	NR Band n26	20	QPSK	A	1266M	1:1	-0.03	831.50	166300	DFT-s-OFDM	0.0	24.00	1	104	Left	0	0.654	29.8		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	DFS Plimit [dBm]
Phablet	NR Band n26	20	QPSK	E	1255M	1:1	-0.07	831.50	166300	DFT-s-OFDM	0.0	23.56	1	104	Back	0	1.120	27.0	27.0	25.8
Phablet	NR Band n26	20	QPSK	E	1252M	1:1	0.06	831.50	166300	DFT-s-OFDM	0.0	23.56	1	104	Front	0	0.730	28.9		
Phablet	NR Band n26	20	QPSK	E	1252M	1:1	-0.02	831.50	166300	DFT-s-OFDM	0.0	23.56	1	104	Top	0	0.945	27.7		
Phablet	NR Band n26	20	QPSK	E	1252M	1:1	-0.14	831.50	166300	DFT-s-OFDM	0.0	23.56	1	104	Right	0	0.129	36.4		

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report	Approved by: Technical Manager
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset	APPENDIX A: Page 5 of 9

Table A-21
DSI = 0 P_{Limit} Calculations – NR n70 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n70	15	QPSK	A	1263M	1:1	-0.02	1702.50	340500	CP-OFDM	0.0	19.35	1	1	Back	0	0.761	24.5	23.5	19.0
Phablet	NR Band n70	15	QPSK	A	1263M	1:1	-0.06	1702.50	340500	CP-OFDM	0.0	19.35	1	1	Front	0	0.782	24.3		
Phablet	NR Band n70	15	QPSK	A	1263M	1:1	-0.08	1702.50	340500	CP-OFDM	0.0	19.35	1	1	Bottom	0	0.959	23.5		
Phablet	NR Band n70	15	QPSK	A	1263M	1:1	-0.02	1702.50	340500	CP-OFDM	0.0	19.35	1	1	Right	0	0.038	37.5		
Phablet	NR Band n70	15	QPSK	A	1263M	1:1	-0.02	1702.50	340500	CP-OFDM	0.0	19.35	1	1	Left	0	0.168	31.0		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n70	15	QPSK	F	1243M	1:1	0.08	1702.50	340500	CP-OFDM	0.0	19.44	1	1	Back	0	0.944	23.6	20.1	19.0
Phablet	NR Band n70	15	QPSK	F	1243M	1:1	0.02	1702.50	340500	CP-OFDM	0.0	19.44	1	1	Front	0	0.882	23.9		
Phablet	NR Band n70	15	QPSK	F	1243M	1:1	-0.02	1702.50	340500	CP-OFDM	0.0	19.44	1	1	Top	0	2.110	20.1		
Phablet	NR Band n70	15	QPSK	F	1243M	1:1	0.02	1702.50	340500	CP-OFDM	0.0	19.44	1	1	Left	0	0.426	27.1		

Table A-22
DSI = 0 P_{Limit} Calculations – NR n66 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n66	40	QPSK	A	1190M	1:1	0.09	1745.00	349000	CP-OFDM	0.0	18.74	1	1	Back	0	1.370	21.3	20.7	18.5
Phablet	NR Band n66	40	QPSK	A	1190M	1:1	0.00	1745.00	349000	CP-OFDM	0.0	18.74	1	1	Front	0	1.340	21.4		
Phablet	NR Band n66	40	QPSK	A	1190M	1:1	-0.01	1745.00	349000	CP-OFDM	0.0	18.74	1	1	Bottom	0	1.590	20.7		
Phablet	NR Band n66	40	QPSK	A	1190M	1:1	-0.08	1745.00	349000	CP-OFDM	0.0	18.74	1	1	Right	0	0.150	30.6		
Phablet	NR Band n66	40	QPSK	A	1190M	1:1	-0.10	1745.00	349000	CP-OFDM	0.0	18.74	1	1	Left	0	0.761	28.5		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n66	40	QPSK	F	1243M	1:1	0.03	1745.00	349000	CP-OFDM	0.0	20.25	1	1	Back	0	0.956	24.4	20.7	20.0
Phablet	NR Band n66	40	QPSK	F	1243M	1:1	-0.02	1745.00	349000	CP-OFDM	0.0	20.25	1	1	Front	0	0.927	24.5		
Phablet	NR Band n66	40	QPSK	F	1243M	1:1	0.02	1745.00	349000	CP-OFDM	0.0	20.25	1	1	Top	0	2.220	20.7		
Phablet	NR Band n66	40	QPSK	F	1243M	1:1	0.02	1745.00	349000	CP-OFDM	0.0	20.25	1	1	Left	0	0.417	28.0		

Table A-23
DSI = 0 P_{Limit} Calculations – NR n25 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n25	40	QPSK	A	1190M	1:1	0.04	1882.50	376500	CP-OFDM	0.0	18.24	1	1	Back	0	0.876	22.7	21.9	18.0
Phablet	NR Band n25	40	QPSK	A	1190M	1:1	0.00	1882.50	376500	CP-OFDM	0.0	18.24	1	1	Front	0	1.050	22.0		
Phablet	NR Band n25	40	QPSK	A	1190M	1:1	0.07	1882.50	376500	CP-OFDM	0.0	18.24	1	1	Bottom	0	1.070	21.9		
Phablet	NR Band n25	40	QPSK	A	1190M	1:1	-0.15	1882.50	376500	CP-OFDM	0.0	18.24	1	1	Right	0	0.125	31.2		
Phablet	NR Band n25	40	QPSK	A	1190M	1:1	0.04	1882.50	376500	CP-OFDM	0.0	18.24	1	1	Left	0	0.179	29.6		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n25	40	QPSK	F	1243M	1:1	0.08	1882.50	376500	CP-OFDM	0.0	20.39	1	1	Back	0	1.010	24.3	21.1	20.0
Phablet	NR Band n25	40	QPSK	F	1243M	1:1	0.03	1882.50	376500	CP-OFDM	0.0	20.39	1	1	Front	0	0.879	24.9		
Phablet	NR Band n25	40	QPSK	F	1243M	1:1	0.02	1882.50	376500	CP-OFDM	0.0	20.39	1	1	Top	0	2.090	21.1		
Phablet	NR Band n25	40	QPSK	F	1243M	1:1	0.03	1882.50	376500	CP-OFDM	0.0	20.39	1	1	Left	0	0.421	28.1		

Table A-24
DSI = 0 P_{Limit} Calculations – NR n30 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n30	10	QPSK	A	1285M	1:1	-0.05	2310.00	462000	CP-OFDM	0.0	19.29	1	1	Back	0	0.913	23.5	22.9	19.0
Phablet	NR Band n30	10	QPSK	A	1285M	1:1	-0.04	2310.00	462000	CP-OFDM	0.0	19.29	1	1	Front	0	0.491	26.3		
Phablet	NR Band n30	10	QPSK	A	1285M	1:1	-0.14	2310.00	462000	DFT-s-OFDM	0.0	19.26	1	1	Bottom	0	1.060	22.9		
Phablet	NR Band n30	10	QPSK	A	1285M	1:1	0.03	2310.00	462000	CP-OFDM	0.0	19.29	1	1	Right	0	0.171	30.9		
Phablet	NR Band n30	10	QPSK	A	1285M	1:1	-0.10	2310.00	462000	CP-OFDM	0.0	19.29	1	1	Left	0	0.233	29.5		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n30	10	QPSK	F	1285M	1:1	-0.03	2310.00	462000	DFT-s-OFDM	0.0	18.09	1	50	Back	0	0.923	22.4	20.6	18.0
Phablet	NR Band n30	10	QPSK	F	1285M	1:1	0.02	2310.00	462000	DFT-s-OFDM	0.0	18.09	1	50	Front	0	0.962	22.2		
Phablet	NR Band n30	10	QPSK	F	1285M	1:1	-0.06	2310.00	462000	DFT-s-OFDM	0.0	18.09	1	50	Top	0	1.390	20.6		
Phablet	NR Band n30	10	QPSK	F	1285M	1:1	-0.02	2310.00	462000	DFT-s-OFDM	0.0	18.09	1	50	Left	0	0.110	31.6		

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report															Approved by: Technical Manager				
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset															APPENDIX A: Page 6 of 9				

Table A-25
DSI = 0 P_{Limit} Calculations – NR n7 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n7	50	QPSK	B	1285M	1:1	-0.14	2535.00	507000	CP-OFDM	0.0	19.34	1	1	Back	0	1.640	21.1	21.1	19.0
Phablet	NR Band n7	50	QPSK	B	1285M	1:1	-0.02	2535.00	507000	CP-OFDM	0.0	19.34	1	1	Front	0	0.907	23.7		
Phablet	NR Band n7	50	QPSK	B	1285M	1:1	0.00	2535.00	507000	CP-OFDM	0.0	19.34	1	1	Bottom	0	1.220	22.4		
Phablet	NR Band n7	50	QPSK	B	1285M	1:1	-0.07	2535.00	507000	CP-OFDM	0.0	19.34	1	1	Left	0	1.090	22.9		
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n7	50	QPSK	F	1285M	1:1	0.11	2535.00	507000	CP-OFDM	0.0	18.20	1	1	Back	0	0.994	22.2	20.4	18.0
Phablet	NR Band n7	50	QPSK	F	1285M	1:1	0.00	2535.00	507000	CP-OFDM	0.0	18.20	1	1	Front	0	0.944	22.4		
Phablet	NR Band n7	50	QPSK	F	1285M	1:1	-0.02	2535.00	507000	CP-OFDM	0.0	18.20	1	1	Top	0	1.480	20.4		
Phablet	NR Band n7	50	QPSK	F	1285M	1:1	0.03	2535.00	507000	CP-OFDM	0.0	18.20	1	1	Left	0	0.153	30.3		

Table A-26
DSI = 0 P_{Limit} Calculations – NR n41 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n41	100	QPSK	B	1298M	1:1	0.00	2592.99	518598	CP-OFDM	0.0	20.77	1	1	Back	0	2.140	21.4	21.4	20.0
Phablet	NR Band n41	100	QPSK	B	1298M	1:1	0.09	2592.99	518598	CP-OFDM	0.0	20.77	1	1	Front	0	1.190	23.9		
Phablet	NR Band n41	100	QPSK	B	1298M	1:1	0.03	2592.99	518598	CP-OFDM	0.0	20.77	1	1	Bottom	0	1.480	23.2		
Phablet	NR Band n41	100	QPSK	B	1298M	1:1	-0.04	2592.99	518598	CP-OFDM	0.0	20.77	1	1	Left	0	1.530	22.9		
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n41	100	E	1294M	1:1	0.09	2592.99	518598	CW/SRS	18.24	Back	0	0.589	24.5	22.3	17.5				
Phablet	NR Band n41	100	E	1294M	1:1	-0.06	2592.99	518598	CW/SRS	18.24	Front	0	0.662	24.0						
Phablet	NR Band n41	100	E	1294M	1:1	0.04	2592.99	518598	CW/SRS	18.24	Top	0	0.409	26.1						
Phablet	NR Band n41	100	E	1294M	1:1	-0.01	2592.99	518598	CW/SRS	18.24	Right	0	0.969	22.3						
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n41	100	D	1294M	1:1	0.06	2592.99	518598	CW/SRS	16.01	Back	0	0.622	22.0	22.0	15.5				
Phablet	NR Band n41	100	D	1294M	1:1	-0.09	2592.99	518598	CW/SRS	16.01	Front	0	0.063	31.9						
Phablet	NR Band n41	100	D	1294M	1:1	0.02	2592.99	518598	CW/SRS	16.01	Bottom	0	0.062	32.0						
Phablet	NR Band n41	100	D	1294M	1:1	-0.17	2592.99	518598	CW/SRS	16.01	Right	0	0.004	43.9						
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n41	100	QPSK	F	1294M	1:1	0.06	2592.99	518598	CP-OFDM	0.0	17.24	1	1	Back	0	0.429	24.8	20.8	16.5
Phablet	NR Band n41	100	QPSK	F	1294M	1:1	0.06	2592.99	518598	CP-OFDM	0.0	17.24	1	1	Front	0	0.636	23.1		
Phablet	NR Band n41	100	QPSK	F	1294M	1:1	0.09	2592.99	518598	CP-OFDM	0.0	17.24	1	1	Top	0	1.080	20.8		
Phablet	NR Band n41	100	QPSK	F	1294M	1:1	-0.20	2592.99	518598	CP-OFDM	0.0	17.24	1	1	Left	0	0.093	31.5		

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report	Approved by: Technical Manager
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset	APPENDIX A: Page 7 of 9

REV 1.1
04/08/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.Info@Element.com.

Table A-27
DSI = 0 P_{Limit} Calculations – NR n48 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]					
Phablet	NR Band n48	40	C	1298M	1:1	0.08	3624.99	641666	CW/SRS	13.27	Back	0	0.355	21.7	21.3	13.0					
Phablet	NR Band n48	40	C	1298M	1:1	0.05	3624.99	641666	CW/SRS	13.27	Front	0	0.243	23.3							
Phablet	NR Band n48	40	C	1298M	1:1	0.03	3624.99	641666	CW/SRS	13.27	Bottom	0	0.078	28.3							
Phablet	NR Band n48	40	C	1298M	1:1	-0.02	3624.99	641666	CW/SRS	13.27	Left	0	0.393	21.3							
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]					
Phablet	NR Band n48	40	D	1298M	1:1	-0.01	3624.99	641666	CW/SRS	12.05	Back	0	0.570	18.4	18.4	11.5					
Phablet	NR Band n48	40	D	1298M	1:1	-0.07	3624.99	641666	CW/SRS	12.05	Front	0	0.051	28.9							
Phablet	NR Band n48	40	D	1298M	1:1	0.03	3624.99	641666	CW/SRS	12.05	Bottom	0	0.046	29.4							
Phablet	NR Band n48	40	D	1298M	1:1	0.13	3624.99	641666	CW/SRS	12.05	Right	0	0.016	33.9							
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Max Allowed Power [dBm]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n48	40	QPSK	F	1298M	1:1	0.01	3624.99	641666	DFT-s-OFDM	0.0	19.0	18.28	50	28	Back	0	0.897	22.7	20.3	18.0
Phablet	NR Band n48	40	QPSK	F	1298M	1:1	-0.02	3624.99	641666	DFT-s-OFDM	0.0	19.0	18.28	50	28	Front	0	0.696	23.8		
Phablet	NR Band n48	40	QPSK	F	1298M	1:1	-0.02	3624.99	641666	DFT-s-OFDM	0.0	19.0	18.28	50	28	Top	0	1.560	20.3		
Phablet	NR Band n48	40	QPSK	F	1298M	1:1	-0.05	3624.99	641666	DFT-s-OFDM	0.0	19.0	18.28	50	28	Left	0	0.136	30.9		
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]					
Phablet	NR Band n48	40	I	1298M	1:1	0.05	3624.99	641666	CW/SRS	16.26	Back	0	0.606	22.4	20.7	16.0					
Phablet	NR Band n48	40	I	1298M	1:1	0.01	3624.99	641666	CW/SRS	16.26	Front	0	0.890	20.7							
Phablet	NR Band n48	40	I	1298M	1:1	0.09	3624.99	641666	CW/SRS	16.26	Top	0	0.036	34.6							
Phablet	NR Band n48	40	I	1298M	1:1	0.02	3624.99	641666	CW/SRS	16.26	Left	0	0.271	25.9							

Table A-28
DSI = 0 P_{Limit} Calculations – NR n77 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n77 DoD	100	C	1313M	1:1	-0.05	3500.01	633334	CW/SRS	11.61	Back	0	0.291	20.9	20.9	11.0				
Phablet	NR Band n77	100	C	1313M	1:1	-0.01	3750.00	650000	CW/SRS	11.81	Back	0	0.193	22.9						
Phablet	NR Band n77	100	C	1313M	1:1	0.02	3750.00	650000	CW/SRS	11.81	Front	0	0.073	27.1						
Phablet	NR Band n77	100	C	1313M	1:1	-0.05	3750.00	650000	CW/SRS	11.81	Bottom	0	0.078	26.8						
Phablet	NR Band n77	100	C	1313M	1:1	-0.02	3750.00	650000	CW/SRS	11.81	Left	0	0.267	21.5						
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n77 DoD	100	D	1313M	1:1	-0.04	3500.01	633334	CW/SRS	10.48	Back	0	0.255	20.3	20.3	10.0				
Phablet	NR Band n77	100	D	1313M	1:1	-0.09	3750.00	650000	CW/SRS	10.81	Back	0	0.226	21.2						
Phablet	NR Band n77	100	D	1313M	1:1	0.21	3750.00	650000	CW/SRS	10.81	Front	0	0.023	31.1						
Phablet	NR Band n77	100	D	1313M	1:1	0.10	3750.00	650000	CW/SRS	10.81	Bottom	0	0.036	29.2						
Phablet	NR Band n77	100	D	1313M	1:1	-0.14	3750.00	650000	CW/SRS	10.81	Right	0	0.013	33.6						
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	NR Band n77	100	QPSK	F	1313M	1:1	-0.02	3750.00	650000	DFT-s-OFDM	0.0	17.66	1	1	Back	0	0.697	23.2	21.3	17.0
Phablet	NR Band n77	100	QPSK	F	1313M	1:1	0.06	3750.00	650000	DFT-s-OFDM	0.0	17.66	1	1	Front	0	0.388	25.7		
Phablet	NR Band n77	100	QPSK	F	1313M	1:1	-0.07	3750.00	650000	DFT-s-OFDM	0.0	17.66	1	1	Top	0	1.080	21.3		
Phablet	NR Band n77	100	QPSK	F	1313M	1:1	0.07	3750.00	650000	DFT-s-OFDM	0.0	17.66	1	1	Left	0	0.133	30.4		
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]				
Phablet	NR Band n77 DoD	100	I	1313M	1:1	0.00	3500.01	633334	CW/SRS	15.40	Back	0	0.449	22.8	22.8	15.0				
Phablet	NR Band n77	100	I	1313M	1:1	0.08	3750.00	650000	CW/SRS	15.47	Back	0	0.435	23.0						
Phablet	NR Band n77	100	I	1313M	1:1	-0.07	3750.00	650000	CW/SRS	15.47	Front	0	0.279	24.9						
Phablet	NR Band n77	100	I	1313M	1:1	-0.04	3750.00	650000	CW/SRS	15.47	Top	0	0.020	36.4						
Phablet	NR Band n77	100	I	1313M	1:1	0.03	3750.00	650000	CW/SRS	15.47	Left	0	0.182	26.8						

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report										Approved by: Technical Manager					
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset										APPENDIX A: Page 8 of 9					

Table A-29
DSI = 0 P_{Limit} Calculations – 2.4 GHz WLAN Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	H	1262M	98.90	-0.02	2437.00	6	1	19.47	Back	0	1.610	21.3	20.1	20.1	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	H	1262M	98.90	0.00	2437.00	6	1	19.47	Front	0	1.230	22.5			
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	H	1262M	98.90	0.00	2437.00	6	1	19.47	Top	0	0.590	25.6			
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	H	1262M	98.90	-0.01	2437.00	6	1	19.47	Left	0	2.130	20.1			
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	J	1262M	98.99	0.01	2437.00	6	1	19.48	Back	0	0.476	26.6	25.1	25.1	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	J	1262M	98.99	0.02	2437.00	6	1	19.48	Front	0	0.666	25.1			
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	J	1262M	98.99	0.05	2437.00	6	1	19.48	Top	0	0.017	41.1			
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	J	1262M	98.99	-0.10	2437.00	6	1	19.48	Right	0	0.249	29.4			
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Conducted Power (2nd ant) [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	MIMO	1262M	98.82	-0.01	2437.00	6	6.5	19.20	19.95	Back	0	1.040	22.9	19.6	19.6
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	MIMO	1262M	98.82	-0.01	2437.00	6	6.5	19.20	19.95	Front	0	1.180	22.4		
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	MIMO	1262M	98.82	0.00	2437.00	6	6.5	19.20	19.95	Top	0	0.532	25.8		
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	MIMO	1262M	98.82	0.03	2437.00	6	6.5	19.20	19.95	Right	0	0.223	29.6		
Phablet	2.4 GHz WiFi/ IEEE 802.11b	22	DSSS	MIMO	1262M	98.82	-0.03	2437.00	6	6.5	19.20	19.95	Left	0	2.220	19.6		

Table A-30
DSI = 0 P_{Limit} Calculations – 2.4 GHz Bluetooth Standalone SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]	
Phablet	2.4 GHz Bluetooth LE	DSSS	H	1262M	85.28	-0.04	2402.00	0	1	18.39	Back	0	0.717	23.1	20.2	20.2	
Phablet	2.4 GHz Bluetooth LE	DSSS	H	1262M	85.28	0.01	2402.00	0	1	18.39	Front	0	0.904	22.1			
Phablet	2.4 GHz Bluetooth LE	DSSS	H	1262M	85.28	0.00	2402.00	0	1	18.39	Top	0	0.333	26.4			
Phablet	2.4 GHz Bluetooth LE	DSSS	H	1262M	85.28	0.01	2402.00	0	1	18.39	Left	0	1.380	20.2			
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]	
Phablet	2.4 GHz Bluetooth LE	DSSS	J	1262M	85.33	0.07	2440.00	19	1	18.02	Back	0	0.185	28.6	26.9	26.9	
Phablet	2.4 GHz Bluetooth LE	DSSS	J	1262M	85.33	0.06	2440.00	19	1	18.02	Front	0	0.274	26.9			
Phablet	2.4 GHz Bluetooth LE	DSSS	J	1262M	85.33	0.08	2440.00	19	1	18.02	Top	0	0.008	42.2			
Phablet	2.4 GHz Bluetooth LE	DSSS	J	1262M	85.33	-0.04	2440.00	19	1	18.02	Right	0	0.105	31.0			
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Conducted Power (2nd ant) [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]	EFS Plimit [dBm]
Phablet	2.4 GHz Bluetooth LE	DSSS	MIMO	1262M	85.33	0.02	2402.00	0	1	12.35	11.92	Back	0	0.176	22.7	19.3	19.3
Phablet	2.4 GHz Bluetooth LE	DSSS	MIMO	1262M	85.33	0.00	2402.00	0	1	12.35	11.92	Front	0	0.219	21.8		
Phablet	2.4 GHz Bluetooth LE	DSSS	MIMO	1262M	85.33	0.00	2402.00	0	1	12.35	11.92	Top	0	0.069	26.8		
Phablet	2.4 GHz Bluetooth LE	DSSS	MIMO	1262M	85.33	0.09	2402.00	0	1	12.35	11.92	Right	0	0.036	29.6		
Phablet	2.4 GHz Bluetooth LE	DSSS	MIMO	1262M	85.33	-0.19	2402.00	0	1	12.35	11.92	Left	0	0.387	19.3		

FCC ID: A3LSMS936U	RF Exposure Part 0 Test Report	Approved by: Technical Manager
Document S/N: 1M2408260064-31.A3L	DUT Type: Portable Handset	APPENDIX A: Page 9 of 9

REV 1.1
04/08/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.Info@Element.com.